



OpenShift Container Platform 4.3

Metering

Configuring and using Metering in OpenShift Container Platform

OpenShift Container Platform 4.3 Metering

Configuring and using Metering in OpenShift Container Platform

Legal Notice

Copyright © 2020 Red Hat, Inc.

The text of and illustrations in this document are licensed by Red Hat under a Creative Commons Attribution–Share Alike 3.0 Unported license ("CC-BY-SA"). An explanation of CC-BY-SA is available at

<http://creativecommons.org/licenses/by-sa/3.0/>

. In accordance with CC-BY-SA, if you distribute this document or an adaptation of it, you must provide the URL for the original version.

Red Hat, as the licensor of this document, waives the right to enforce, and agrees not to assert, Section 4d of CC-BY-SA to the fullest extent permitted by applicable law.

Red Hat, Red Hat Enterprise Linux, the Shadowman logo, the Red Hat logo, JBoss, OpenShift, Fedora, the Infinity logo, and RHCE are trademarks of Red Hat, Inc., registered in the United States and other countries.

Linux[®] is the registered trademark of Linus Torvalds in the United States and other countries.

Java[®] is a registered trademark of Oracle and/or its affiliates.

XFS[®] is a trademark of Silicon Graphics International Corp. or its subsidiaries in the United States and/or other countries.

MySQL[®] is a registered trademark of MySQL AB in the United States, the European Union and other countries.

Node.js[®] is an official trademark of Joyent. Red Hat is not formally related to or endorsed by the official Joyent Node.js open source or commercial project.

The OpenStack[®] Word Mark and OpenStack logo are either registered trademarks/service marks or trademarks/service marks of the OpenStack Foundation, in the United States and other countries and are used with the OpenStack Foundation's permission. We are not affiliated with, endorsed or sponsored by the OpenStack Foundation, or the OpenStack community.

All other trademarks are the property of their respective owners.

Abstract

This document provides instructions for configuring and using metering in OpenShift Container Platform.

Table of Contents

CHAPTER 1. ABOUT METERING	4
1.1. METERING OVERVIEW	4
1.1.1. Metering resources	4
CHAPTER 2. INSTALLING METERING	5
2.1. PREREQUISITES	5
2.2. INSTALLING THE METERING OPERATOR	5
2.2.1. Installing metering using the web console	5
2.2.2. Installing metering using the CLI	6
2.3. INSTALLING THE METERING STACK	7
2.4. PREREQUISITES	8
2.5. VERIFYING THE METERING INSTALLATION	8
2.6. ADDITIONAL RESOURCES	10
CHAPTER 3. CONFIGURING METERING	11
3.1. ABOUT CONFIGURING METERING	11
3.2. COMMON CONFIGURATION OPTIONS	11
3.2.1. Resource requests and limits	11
3.2.2. Node selectors	12
3.3. CONFIGURING PERSISTENT STORAGE	14
3.3.1. Storing data in Amazon S3	14
3.3.2. Storing data in S3-compatible storage	17
3.3.3. Storing data in Microsoft Azure	17
3.3.4. Storing data in Google Cloud Storage	18
3.3.5. Storing data in shared volumes	19
3.4. CONFIGURING THE HIVE METASTORE	19
3.4.1. Configuring PersistentVolumes	20
3.4.1.1. Configuring the storage class for Hive metastore	20
3.4.1.2. Configuring the volume sizes for the Hive Metastore	20
3.4.2. Use MySQL or PostgreSQL for the Hive metastore	21
3.5. CONFIGURING THE REPORTING-OPERATOR	22
3.5.1. Prometheus connection	22
3.5.2. Exposing the reporting API	23
3.5.2.1. Using OpenShift Authentication	23
3.5.2.1.1. Authenticate using a service account token	23
3.5.2.1.2. Authenticate using a username and password	23
3.5.2.2. Manually Configuring Authentication	24
3.5.2.2.1. Token authentication	24
3.5.2.2.2. Basic authentication (username/password)	26
3.6. CONFIGURE AWS BILLING CORRELATION	26
CHAPTER 4. REPORTS	29
4.1. ABOUT REPORTS	29
4.1.1. Reports	29
4.1.1.1. Example Report with a Schedule	29
4.1.1.2. Example Report without a Schedule (Run-Once)	29
4.1.1.3. query	30
4.1.1.4. schedule	32
4.1.1.4.1. period	32
4.1.1.5. reportingStart	33
4.1.1.6. reportingEnd	33
4.1.1.7. runImmediately	34

4.1.1.8. inputs	34
4.1.1.9. Roll-up Reports	34
4.1.1.9.1. Report Status	35
4.2. STORAGE LOCATIONS	35
4.2.1. StorageLocation examples	35
4.2.2. Default StorageLocation	37
CHAPTER 5. USING METERING	38
5.1. PREREQUISITES	38
5.2. WRITING REPORTS	38
5.3. VIEWING REPORT RESULTS	39
CHAPTER 6. EXAMPLES OF USING METERING	42
6.1. PREREQUISITES	42
6.2. MEASURE CLUSTER CAPACITY HOURLY AND DAILY	42
6.3. MEASURE CLUSTER USAGE WITH A ONE-TIME REPORT	43
6.4. MEASURE CLUSTER UTILIZATION USING CRON EXPRESSIONS	43
CHAPTER 7. TROUBLESHOOTING AND DEBUGGING METERING	45
7.1. TROUBLESHOOTING METERING	45
7.1.1. Not enough compute resources	45
7.1.2. StorageClass not configured	45
7.1.3. Secret not configured correctly	45
7.2. DEBUGGING METERING	45
7.2.1. Get reporting operator logs	45
7.2.2. Query Presto using presto-cli	46
7.2.3. Query Hive using beeline	47
7.2.4. Port-forward to the Hive web UI	48
7.2.5. Port-forward to hdfs	48
7.2.6. Metering Ansible Operator	48
7.2.6.1. Accessing ansible logs	48
7.2.6.2. Checking the MeteringConfig Status	48
CHAPTER 8. UNINSTALLING METERING	50
8.1. REMOVING THE METERING OPERATOR FROM YOUR CLUSTER	50
8.2. UNINSTALLING A METERING NAMESPACE	50
8.3. UNINSTALLING METERING CUSTOMRESOURCEDEFINITIONS	50

CHAPTER 1. ABOUT METERING

1.1. METERING OVERVIEW

Metering is a general purpose data analysis tool that enables you to write reports to process data from different data sources. As a cluster administrator, you can use metering to analyze what is happening in your cluster. You can either write your own, or use predefined SQL queries to define how you want to process data from the different data sources you have available.

Metering focuses primarily on in-cluster metric data using Prometheus as a default data source, enabling users of metering to do reporting on pods, namespaces, and most other Kubernetes resources.

You can install metering on OpenShift Container Platform 4.x clusters and above.

1.1.1. Metering resources

Metering has many resources which can be used to manage the deployment and installation of metering, as well as the reporting functionality metering provides.

Metering is managed using the following CustomResourceDefinitions (CRDs):

MeteringC onfig	Configures the metering stack for deployment. Contains customizations and configuration options to control each component that makes up the metering stack.
Reports	Controls what query to use, when, and how often the query should be run, and where to store the results.
ReportQu eries	Contains the SQL queries used to perform analysis on the data contained within ReportDataSources.
ReportDat aSources	Controls the data available to ReportQueries and Reports. Allows configuring access to different databases for use within metering.

CHAPTER 2. INSTALLING METERING

Review the following sections before installing metering into your cluster.

To get started installing metering, first install the Metering Operator from OperatorHub. Next, configure your instance of metering by creating a **CustomResource**, referred to here as your MeteringConfig. Installing the Metering Operator creates a default MeteringConfig that you can modify using the examples in the documentation. After creating your MeteringConfig, install the metering stack. Last, verify your installation.

2.1. PREREQUISITES

Metering requires the following components:

- A StorageClass for dynamic volume provisioning. Metering supports a number of different storage solutions.
- 4GB memory and 4 CPU cores available cluster capacity and at least one node with 2 CPU cores and 2GB memory capacity available.
- The minimum resources needed for the largest single Pod installed by metering are 2GB of memory and 2 CPU cores.
 - Memory and CPU consumption may often be lower, but will spike when running reports, or collecting data for larger clusters.

2.2. INSTALLING THE METERING OPERATOR

You can install metering by deploying the Metering Operator. The Metering Operator creates and manages the components of the metering stack.



NOTE

You cannot create a Project starting with **openshift-** using the web console or by using the **oc new-project** command in the CLI.

2.2.1. Installing metering using the web console


You can use the OpenShift Container Platform web console to install the Metering Operator.

Procedure

1. Create a namespace object YAML file for the Metering Operator with the **oc create -f <file-name>.yaml** command. You must use the CLI to create the namespace. For example, **metering-namespace.yaml**:

```
apiVersion: v1
kind: Namespace
metadata:
  name: openshift-metering 1
  annotations:
    openshift.io/node-selector: "" 2
  labels:
    openshift.io/cluster-monitoring: "true"
```

- - 1 It is strongly recommended to deploy metering in the **openshift-metering** namespace.
 - 2 Include this annotation before configuring specific node selectors for the operand Pods.
2. In the OpenShift Container Platform web console, click **Operators** → **OperatorHub**. Filter for **metering** to find the Metering Operator.
 3. Click the Metering card, review the package description, and then click **Install**.
 4. Select an **Update Channel**, **Installation Mode**, and **Approval Strategy**.
 5. Click **Subscribe**.
 6. Verify that the Metering Operator is installed by switching to the **Operators** → **Installed Operators** page. The Metering Operator has a **Status** of **Succeeded** when the installation is complete.

**NOTE**

It might take several minutes for the Metering Operator to appear.

7. Click **Metering** on the **Installed Operators** page for Operator **Details**. From the **Details** page you can create different resources related to metering.

To complete the metering installation, create a MeteringConfig resource to configure metering and install the components of the metering stack.

2.2.2. Installing metering using the CLI

You can use the OpenShift Container Platform CLI to install the Metering Operator.

Procedure

1. Create a namespace object YAML file for the Metering Operator. You must use the CLI to create the namespace. For example, **metering-namespace.yaml**:

```
apiVersion: v1
kind: Namespace
metadata:
  name: openshift-metering 1
  annotations:
    openshift.io/node-selector: "" 2
  labels:
    openshift.io/cluster-monitoring: "true"
```

- 1 It is strongly recommended to deploy metering in the **openshift-metering** namespace.
 - 2 Include this annotation before configuring specific node selectors for the operand Pods.
2. Create the namespace object:

```
$ oc create -f <file-name>.yaml
```

For example:

```
$ oc create -f openshift-metering.yaml
```

3. Create the OperatorGroup object YAML file. For example, **metering-og**:

```
apiVersion: operators.coreos.com/v1
kind: OperatorGroup
metadata:
  name: openshift-metering 1
  namespace: openshift-metering 2
spec:
  targetNamespaces:
  - openshift-metering
```

- 1 The name is arbitrary.
- 2 Specify the **openshift-metering** namespace.

4. Create a Subscription object YAML file to subscribe a namespace to the Metering Operator. This object targets the most recently released version in the **redhat-operators** CatalogSource. For example, **metering-sub.yaml**:

```
apiVersion: operators.coreos.com/v1alpha1
kind: Subscription
metadata:
  name: metering-ocp 1
  namespace: openshift-metering 2
spec:
  channel: "4.3" 3
  source: "redhat-operators" 4
  sourceNamespace: "openshift-marketplace"
  name: "metering-ocp"
  installPlanApproval: "Automatic" 5
```


- 1 The name is arbitrary.
- 2 You must specify the **openshift-metering** namespace.
- 3 Specify 4.3 as the channel.
- 4 Specify the **redhat-operators** CatalogSource, which contains the **metering-ocp** package manifests. If your OpenShift Container Platform is installed on a restricted network, also known as a disconnected cluster, specify the name of the CatalogSource object you created when you configured the Operator LifeCycle Manager (OLM).
- 5 Specify "Automatic" install plan approval.

2.3. INSTALLING THE METERING STACK

After adding the Metering Operator to your cluster you can install the components of metering by installing the metering stack.

2.4. PREREQUISITES

- Review the [configuration options](#)
- Create a MeteringConfig resource. You can begin the following process to generate a default MeteringConfig, then use the examples in the documentation to modify this default file for your specific installation. Review the following topics to create your MeteringConfig resource:
 - For configuration options, review [About configuring metering](#).
 - At a minimum, you need to [configure persistent storage](#) and [configure the Hive metastore](#).



IMPORTANT

There can only be one MeteringConfig resource in the **openshift-metering** namespace. Any other configuration is not supported.

Procedure

1. From the web console, ensure you are on the **Operator Details** page for the Metering Operator in the **openshift-metering** project. You can navigate to this page by clicking **Operators** → **Installed Operators**, then selecting the Metering Operator.
2. Under **Provided APIs**, click **Create Instance** on the Metering Configuration card. This opens a YAML editor with the default MeteringConfig file where you can define your configuration.



NOTE

For example configuration files and all supported configuration options, review the [configuring metering documentation](#).

3. Enter your MeteringConfig into the YAML editor and click **Create**.

The MeteringConfig resource begins to create the necessary resources for your metering stack. You can now move on to verifying your installation.

2.5. VERIFYING THE METERING INSTALLATION

You can verify the metering installation by performing any of the following checks:

- Check the Metering Operator ClusterServiceVersion (CSV) for the metering version. This can be done through either the web console or CLI.

Procedure (UI)

1. Navigate to **Operators** → **Installed Operators** in the **openshift-metering** namespace.
2. Click **Metering Operator**.
3. Click **Subscription** for **Subscription Details**.
4. Check the **Installed Version**.

Procedure (CLI)

- Check the Metering Operator CSV in the **openshift-metering** namespace:

```
$ oc --namespace openshift-metering get csv
```

In the following example, the 4.3 Metering Operator installation is successful:

NAME	DISPLAY	VERSION	REPLACES
elasticsearch-operator.4.3.0-202006231303.p0	Elasticsearch Operator	4.3.0-	
202006231303.p0	Succeeded		
metering-operator.v4.3.0	Metering	4.3.0	
Succeeded			

- Check that all required Pods in the **openshift-metering** namespace are created. This can be done through either the web console or CLI.



NOTE

Many Pods rely on other components to function before they themselves can be considered ready. Some Pods may restart if other Pods take too long to start. This is to be expected during the Metering Operator installation.

Procedure (UI)

- Navigate to **Workloads** → **Pods** in the metering namespace and verify that Pods are being created. This can take several minutes after installing the metering stack.

Procedure (CLI)

- Check that all required Pods in the **openshift-metering** namespace are created:

```
$ oc -n openshift-metering get pods
```

The output shows that all Pods are created in the **Ready** column:

NAME	READY	STATUS	RESTARTS	AGE
hive-metastore-0	2/2	Running	0	3m28s
hive-server-0	3/3	Running	0	3m28s
metering-operator-68dd64cfb6-2k7d9	2/2	Running	0	5m17s
presto-coordinator-0	2/2	Running	0	3m9s
reporting-operator-5588964bf8-x2tkn	2/2	Running	0	2m40s

- Verify that the **ReportDataSources** are beginning to import data, indicated by a valid timestamp in the **EARLIEST METRIC** column. This might take several minutes. Filter out the "raw" **ReportDataSources**, which do not import data:

```
$ oc get reportdatasources -n openshift-metering | grep -v raw
```

```
$ oc get reportdatasources -n openshift-metering | grep -v raw
```

NAME	EARLIEST METRIC	NEWEST METRIC	IMPORT
START	IMPORT END	LAST IMPORT TIME	AGE
node-allocatable-cpu-cores	2019-08-05T16:52:00Z	2019-08-05T18:52:00Z	
2019-08-05T16:52:00Z	2019-08-05T18:52:00Z	2019-08-05T18:54:45Z	9m50s

```

node-allocatable-memory-bytes      2019-08-05T16:51:00Z 2019-08-05T18:51:00Z
2019-08-05T16:51:00Z 2019-08-05T18:51:00Z 2019-08-05T18:54:45Z 9m50s
node-capacity-cpu-cores             2019-08-05T16:51:00Z 2019-08-05T18:29:00Z
2019-08-05T16:51:00Z 2019-08-05T18:29:00Z 2019-08-05T18:54:39Z 9m50s
node-capacity-memory-bytes          2019-08-05T16:52:00Z 2019-08-05T18:41:00Z
2019-08-05T16:52:00Z 2019-08-05T18:41:00Z 2019-08-05T18:54:44Z 9m50s
persistentvolumeclaim-capacity-bytes 2019-08-05T16:51:00Z 2019-08-05T18:29:00Z
2019-08-05T16:51:00Z 2019-08-05T18:29:00Z 2019-08-05T18:54:43Z 9m50s
persistentvolumeclaim-phase         2019-08-05T16:51:00Z 2019-08-05T18:29:00Z
2019-08-05T16:51:00Z 2019-08-05T18:29:00Z 2019-08-05T18:54:28Z 9m50s
persistentvolumeclaim-request-bytes  2019-08-05T16:52:00Z 2019-08-05T18:30:00Z
2019-08-05T16:52:00Z 2019-08-05T18:30:00Z 2019-08-05T18:54:34Z 9m50s
persistentvolumeclaim-usage-bytes    2019-08-05T16:52:00Z 2019-08-05T18:30:00Z
2019-08-05T16:52:00Z 2019-08-05T18:30:00Z 2019-08-05T18:54:36Z 9m49s
pod-limit-cpu-cores                 2019-08-05T16:52:00Z 2019-08-05T18:30:00Z 2019-
08-05T16:52:00Z 2019-08-05T18:30:00Z 2019-08-05T18:54:26Z 9m49s
pod-limit-memory-bytes               2019-08-05T16:51:00Z 2019-08-05T18:40:00Z 2019-
08-05T16:51:00Z 2019-08-05T18:40:00Z 2019-08-05T18:54:30Z 9m49s
pod-persistentvolumeclaim-request-info 2019-08-05T16:51:00Z 2019-08-05T18:40:00Z
2019-08-05T16:51:00Z 2019-08-05T18:40:00Z 2019-08-05T18:54:37Z 9m49s
pod-request-cpu-cores                2019-08-05T16:51:00Z 2019-08-05T18:18:00Z 2019-
08-05T16:51:00Z 2019-08-05T18:18:00Z 2019-08-05T18:54:24Z 9m49s
pod-request-memory-bytes             2019-08-05T16:52:00Z 2019-08-05T18:08:00Z
2019-08-05T16:52:00Z 2019-08-05T18:08:00Z 2019-08-05T18:54:32Z 9m49s
pod-usage-cpu-cores                  2019-08-05T16:52:00Z 2019-08-05T17:57:00Z 2019-
08-05T16:52:00Z 2019-08-05T17:57:00Z 2019-08-05T18:54:10Z 9m49s
pod-usage-memory-bytes               2019-08-05T16:52:00Z 2019-08-05T18:08:00Z
2019-08-05T16:52:00Z 2019-08-05T18:08:00Z 2019-08-05T18:54:20Z 9m49s

```

After all Pods are ready and you have verified that data is being imported, you can begin using metering to collect data and report on your cluster.

2.6. ADDITIONAL RESOURCES

- For more information on configuration steps and available storage platforms, see [Configuring persistent storage](#).
- For the steps to configure Hive, see [Configuring the Hive metastore](#).

CHAPTER 3. CONFIGURING METERING

3.1. ABOUT CONFIGURING METERING

A **CustomResource** called your **MeteringConfig** specifies all the configuration details for your metering installation. When you first install the metering stack, a default **MeteringConfig** is generated. Use the examples in the documentation to modify this default file. Keep in mind the following key points:

- At a minimum, you need to [configure persistent storage](#) and [configure the Hive metastore](#).
- Most default configuration settings work, but larger deployments or highly customized deployments should review all configuration options carefully.
- Some configuration options can not be modified after installation.

For configuration options that can be modified after installation, make the changes in your **MeteringConfig** and reapply the file.

3.2. COMMON CONFIGURATION OPTIONS

3.2.1. Resource requests and limits

You can adjust the CPU, memory, or storage resource requests and/or limits for pods and volumes. The **default-resource-limits.yaml** below provides an example of setting resource request and limits for each component.

```
apiVersion: metering.openshift.io/v1
kind: MeteringConfig
metadata:
  name: "operator-metering"
spec:
  reporting-operator:
    spec:
      resources:
        limits:
          cpu: 1
          memory: 500Mi
        requests:
          cpu: 500m
          memory: 100Mi
  presto:
    spec:
      coordinator:
        resources:
          limits:
            cpu: 4
            memory: 4Gi
          requests:
            cpu: 2
            memory: 2Gi
  worker:
    replicas: 0
    resources:
```

```

limits:
  cpu: 8
  memory: 8Gi
requests:
  cpu: 4
  memory: 2Gi

hive:
spec:
  metastore:
  resources:
    limits:
      cpu: 4
      memory: 2Gi
    requests:
      cpu: 500m
      memory: 650Mi
  storage:
    class: null
    create: true
    size: 5Gi
  server:
  resources:
    limits:
      cpu: 1
      memory: 1Gi
    requests:
      cpu: 500m
      memory: 500Mi

```

3.2.2. Node selectors

You can run the metering components on specific sets of nodes. Set the **nodeSelector** on a metering component to control where the component is scheduled. The **node-selectors.yaml** file below provides an example of setting node selectors for each component.



NOTE

Add the **openshift.io/node-selector: ""** namespace annotation to the metering namespace YAML file before configuring specific node selectors for the operand Pods. Specify **""** as the annotation value.

```

apiVersion: metering.openshift.io/v1
kind: MeteringConfig
metadata:
  name: "operator-metering"
spec:
  reporting-operator:
  spec:
    nodeSelector:
      "node-role.kubernetes.io/infra": "" 1
presto:
spec:

```



```

coordinator:
  nodeSelector:
    "node-role.kubernetes.io/infra": "" ❷
worker:
  nodeSelector:
    "node-role.kubernetes.io/infra": "" ❸
hive:
  spec:
    metastore:
      nodeSelector:
        "node-role.kubernetes.io/infra": "" ❹
    server:
      nodeSelector:
        "node-role.kubernetes.io/infra": "" ❺

```

- ❶ ❷ ❸ ❹ ❺ Add a **nodeSelector** parameter with the appropriate value to the component you want to move. You can use a **nodeSelector** in the format shown or use key-value pairs, based on the value specified for the node.



NOTE

Add the **openshift.io/node-selector: ""** namespace annotation to the metering namespace YAML file before configuring specific node selectors for the operand Pods. When the **openshift.io/node-selector** annotation is set on the project, the value is used in preference to the value of the **spec.defaultNodeSelector** field in the cluster-wide Scheduler object.

Verification

You can verify the metering node selectors by performing any of the following checks:

- Verify that all Pods for metering are correctly scheduled on the IP of the node that is configured in the MeteringConfig custom resource:

Procedure

1. Check all pods in the **openshift-metering** namespace:

```
$ oc --namespace openshift-metering get pods -o wide
```

The output shows the **NODE** and corresponding **IP** for each Pod running in the **openshift-metering** namespace:

```

NAME                                READY  STATUS   RESTARTS  AGE   IP              NODE
NOMINATED NODE  READINESS GATES
hive-metastore-0                    1/2    Running  0         4m33s  10.129.2.26     ip-10-0-210-167.us-east-2.compute.internal <none> <none>
hive-server-0                      2/3    Running  0         4m21s  10.128.2.26     ip-10-0-150-175.us-east-2.compute.internal <none> <none>
metering-operator-964b4fb55-4p699  2/2    Running  0         7h30m  10.131.0.33     ip-10-0-189-6.us-east-2.compute.internal <none> <none>
nfs-server                          1/1    Running  0         7h30m  10.129.2.24     ip-10-0-210-167.us-east-2.compute.internal <none> <none>

```

```

presto-coordinator-0          2/2  Running  0      4m8s  10.131.0.35  ip-10-0-
189-6.us-east-2.compute.internal  <none>  <none>
reporting-operator-869b854c78-8g2x5  1/2  Running  0      7h27m  10.128.2.25  ip-
10-0-150-175.us-east-2.compute.internal  <none>  <none>

```

2. Compare the nodes in the **openshift-metering** namespace to each node **NAME** in your cluster:

```
$ oc get nodes
```

```

NAME                                STATUS  ROLES  AGE  VERSION
ip-10-0-147-106.us-east-2.compute.internal  Ready  master  14h  v1.18.3+6025c28
ip-10-0-150-175.us-east-2.compute.internal  Ready  worker  14h  v1.18.3+6025c28
ip-10-0-175-23.us-east-2.compute.internal  Ready  master  14h  v1.18.3+6025c28
ip-10-0-189-6.us-east-2.compute.internal  Ready  worker  14h  v1.18.3+6025c28
ip-10-0-205-158.us-east-2.compute.internal  Ready  master  14h  v1.18.3+6025c28
ip-10-0-210-167.us-east-2.compute.internal  Ready  worker  14h  v1.18.3+6025c28

```

- Verify that the node selector configuration in the MeteringConfig custom resource does not interfere with the cluster-wide node selector configuration such that no metering operand Pods are scheduled.

Procedure

- Check the cluster-wide Scheduler object for the **spec.defaultNodeSelector** field, which shows where Pods are scheduled by default:

```
$ oc get schedulers.config.openshift.io cluster -o yaml
```

3.3. CONFIGURING PERSISTENT STORAGE

Metering requires persistent storage to persist data collected by the **metering-operator** and to store the results of reports. A number of different storage providers and storage formats are supported. Select your storage provider and modify the example configuration files to configure persistent storage for your metering installation.

3.3.1. Storing data in Amazon S3

Metering can use an existing Amazon S3 bucket or create a bucket for storage.



NOTE

Metering does not manage or delete any S3 bucket data. When uninstalling metering, any S3 buckets used to store metering data must be manually cleaned up.

To use Amazon S3 for storage, edit the **spec.storage** section in the example **s3-storage.yaml** file below.

```

apiVersion: metering.openshift.io/v1
kind: MeteringConfig
metadata:
  name: "operator-metering"

```

```
spec:
  storage:
    type: "hive"
  hive:
    type: "s3"
  s3:
    bucket: "bucketname/path/" ❶
    region: "us-west-1" ❷
    secretName: "my-aws-secret" ❸
    # Set to false if you want to provide an existing bucket, instead of
    # having metering create the bucket on your behalf.
    createBucket: true ❹
```

- ❶ Specify the name of the bucket where you would like to store your data. You may optionally specify the path within the bucket.
- ❷ Specify the region of your bucket.
- ❸ The name of a secret in the metering namespace containing the AWS credentials in the **data.aws-access-key-id** and **data.aws-secret-access-key** fields. See the examples that follow for more details.
- ❹ Set this field to **false** if you want to provide an existing S3 bucket, or if you do not want to provide IAM credentials that have **CreateBucket** permissions.

Use the example secret below as a template.



NOTE

The values of the **aws-access-key-id** and **aws-secret-access-key** must be base64 encoded.

```
apiVersion: v1
kind: Secret
metadata:
  name: your-aws-secret
data:
  aws-access-key-id: "dGVzdAo="
  aws-secret-access-key: "c2VjcmV0Cg=="
```

You can use the following command to create the secret.



NOTE

This command automatically base64 encodes your **aws-access-key-id** and **aws-secret-access-key** values.

```
oc create secret -n openshift-metering generic your-aws-secret --from-literal=aws-access-key-id=your-access-key --from-literal=aws-secret-access-key=your-secret-key
```

The **aws-access-key-id** and **aws-secret-access-key** credentials must have read and write access to the bucket. For an example of an IAM policy granting the required permissions, see the **aws/read-write.json** file below.

```
{
  "Version": "2012-10-17",
  "Statement": [
    {
      "Sid": "1",
      "Effect": "Allow",
      "Action": [
        "s3:AbortMultipartUpload",
        "s3:DeleteObject",
        "s3:GetObject",
        "s3:HeadBucket",
        "s3:ListBucket",
        "s3:ListMultipartUploadParts",
        "s3:PutObject"
      ],
      "Resource": [
        "arn:aws:s3:::operator-metering-data/*",
        "arn:aws:s3:::operator-metering-data"
      ]
    }
  ]
}
```

If you left **spec.storage.hive.s3.createBucket** set to **true**, or unset, then you should use the **aws/read-write-create.json** file below, which contains permissions for creating and deleting buckets.

```
{
  "Version": "2012-10-17",
  "Statement": [
    {
      "Sid": "1",
      "Effect": "Allow",
      "Action": [
        "s3:AbortMultipartUpload",
        "s3:DeleteObject",
        "s3:GetObject",
        "s3:HeadBucket",
        "s3:ListBucket",
        "s3:CreateBucket",
        "s3:DeleteBucket",
        "s3:ListMultipartUploadParts",
        "s3:PutObject"
      ],
      "Resource": [
        "arn:aws:s3:::operator-metering-data/*",
        "arn:aws:s3:::operator-metering-data"
      ]
    }
  ]
}
```

3.3.2. Storing data in S3-compatible storage

To use S3-compatible storage such as Noobaa, edit the **spec.storage** section in the example **s3-compatible-storage.yaml** file below.

```
apiVersion: metering.openshift.io/v1
kind: MeteringConfig
metadata:
  name: "operator-metering"
spec:
  storage:
    type: "hive"
    hive:
      type: "s3Compatible"
      s3Compatible:
        bucket: "bucketname" ❶
        endpoint: "http://example:port-number" ❷
        secretName: "my-aws-secret" ❸
```

- ❶ Specify the name of your S3-compatible bucket.
- ❷ Specify the endpoint for your storage.
- ❸ The name of a secret in the metering namespace containing the AWS credentials in the **data.aws-access-key-id** and **data.aws-secret-access-key** fields. See the example that follows for more details.

Use the example secret below as a template.

```
apiVersion: v1
kind: Secret
metadata:
  name: your-aws-secret
data:
  aws-access-key-id: "dGVzdAo="
  aws-secret-access-key: "c2VjcmV0Cg=="
```

3.3.3. Storing data in Microsoft Azure

To store data in Azure blob storage you must use an existing container. Edit the **spec.storage** section in the example **azure-blob-storage.yaml** file below.

```
apiVersion: metering.openshift.io/v1
kind: MeteringConfig
metadata:
  name: "operator-metering"
spec:
  storage:
    type: "hive"
    hive:
      type: "azure"
      azure:
```

```

container: "bucket1" 1
secretName: "my-azure-secret" 2
rootDirectory: "/testDir" 3

```

- 1** Specify the container name.
- 2** Specify a secret in the metering namespace. See the examples that follow for more details.
- 3** You can optionally specify the directory where you would like to store your data.

Use the example secret below as a template.

```

apiVersion: v1
kind: Secret
metadata:
  name: your-azure-secret
data:
  azure-storage-account-name: "dGVzdAo="
  azure-secret-access-key: "c2VjcmV0Cg=="

```

You can use the following command to create the secret.

```

oc create secret -n openshift-metering generic your-azure-secret --from-literal=azure-storage-account-name=your-storage-account-name --from-literal=azure-secret-access-key=your-secret-key

```

3.3.4. Storing data in Google Cloud Storage

To store your data in Google Cloud Storage you must use an existing bucket. Edit the **spec.storage** section in the example **gcs-storage.yaml** file below.

```

apiVersion: metering.openshift.io/v1
kind: MeteringConfig
metadata:
  name: "operator-metering"
spec:
  storage:
    type: "hive"
    hive:
      type: "gcs"
      gcs:
        bucket: "metering-gcs/test1" 1
        secretName: "my-gcs-secret" 2

```

- 1** Specify the name of the bucket. You can optionally specify the directory within the bucket where you would like to store your data.
- 2** Specify a secret in the metering namespace. Use the example that follows for more details.

Use the example secret below as a template:

```

apiVersion: v1
kind: Secret

```

```

metadata:
  name: your-gcs-secret
data:
  gcs-service-account.json: "c2VjcmV0Cg=="

```

You can use the following command to create the secret.

```

oc create secret -n openshift-metering generic your-gcs-secret --from-file gcs-service-account.json=/path/to/your/service-account-key.json

```

3.3.5. Storing data in shared volumes



NOTE

NFS is not recommended to use with metering.

Metering has no storage by default, but it can use any ReadWriteMany PersistentVolume or any StorageClass that provisions a ReadWriteMany PersistentVolume.

Procedure

- To use a ReadWriteMany PersistentVolume for storage, modify the **shared-storage.yaml** file below.

```

apiVersion: metering.openshift.io/v1
kind: MeteringConfig
metadata:
  name: "operator-metering"
spec:
  storage:
    type: "hive"
  hive:
    type: "sharedPVC"
  sharedPVC:
    claimName: "metering-nfs" 1
    # uncomment the lines below to provision a new PVC using the specified 2
    # storageClass.
    # createPVC: true
    # storageClass: "my-nfs-storage-class"
    # size: 5Gi

```

Select one of the configuration options below:

- 1** Set **storage.hive.sharedPVC.claimName** to the name of an existing ReadWriteMany PersistentVolumeClaim (PVC). This is necessary if you do not have dynamic volume provisioning or want to have more control over how the PersistentVolume is created.
- 2** Set **storage.hive.sharedPVC.createPVC** to **true** and set the **storage.hive.sharedPVC.storageClass** to the name of a StorageClass with ReadWriteMany access mode. This will use dynamic volume provisioning to have a volume created automatically.

3.4. CONFIGURING THE HIVE METASTORE

Hive metastore is responsible for storing all the metadata about the database tables created in Presto and Hive. By default, the metastore stores this information in a local embedded Derby database in a **PersistentVolume** attached to the pod.

Generally, the default configuration of the Hive metastore works for small clusters, but users may wish to improve performance or move storage requirements out of cluster by using a dedicated SQL database for storing the Hive metastore data.

3.4.1. Configuring PersistentVolumes

By default, Hive requires one PersistentVolume to operate.

hive-metastore-db-data is the main PersistentVolumeClaim (PVC) required by default. This PVC is used by the Hive metastore to store metadata about tables, such as table name, columns, and location. Hive metastore is used by Presto and the Hive server to look up table metadata when processing queries. You remove this requirement by using MySQL or PostgreSQL for the Hive metastore database.

To install, Hive metastore requires that dynamic volume provisioning be enabled via a StorageClass, a persistent volume of the correct size must be manually pre-created, or that you use a pre-existing MySQL or PostgreSQL database.

3.4.1.1. Configuring the storage class for Hive metastore

To configure and specify a StorageClass for the **hive-metastore-db-data** PVC, specify the StorageClass in your MeteringConfig. An example StorageClass section is included in **metastore-storage.yaml** file below.

```
apiVersion: metering.openshift.io/v1
kind: MeteringConfig
metadata:
  name: "operator-metering"
spec:
  hive:
    spec:
      metastore:
        storage:
          # Default is null, which means using the default storage class if it exists.
          # If you wish to use a different storage class, specify it here
          # class: "null" 1
          size: "5Gi"
```

1 Uncomment this line and replace **null** with the name of the StorageClass to use. Leaving the value **null** will cause metering to use the default StorageClass for the cluster.

3.4.1.2. Configuring the volume sizes for the Hive Metastore

Use the **metastore-storage.yaml** file below as a template.

```
apiVersion: metering.openshift.io/v1
kind: MeteringConfig
metadata:
  name: "operator-metering"
spec:
  hive:
```



```

spec:
  metastore:
    storage:
      # Default is null, which means using the default storage class if it exists.
      # If you wish to use a different storage class, specify it here
      # class: "null"
      size: "5Gi" 1

```

- 1** Replace the value for **size** with your desired capacity. The example file shows "5Gi".

3.4.2. Use MySQL or PostgreSQL for the Hive metastore

The default installation of metering configures Hive to use an embedded Java database called Derby. This is unsuited for larger environments and can be replaced with either a MySQL or PostgreSQL database. Use the following example configuration files if your deployment requires a MySQL or PostgreSQL database for Hive.

There are 4 configuration options you can use to control the database used by Hive metastore: url, driver, username, and password.

Use the example configuration file below to use a MySQL database for Hive:

```

spec:
  hive:
    spec:
      metastore:
        storage:
          create: false
    config:
      db:
        url: "jdbc:mysql://mysql.example.com:3306/hive_metastore"
        driver: "com.mysql.jdbc.Driver"
        username: "REPLACEME"
        password: "REPLACEME"

```

You can pass additional JDBC parameters using the **spec.hive.config.url**. For more details see the [MySQL Connector/J documentation](#).

Use the example configuration file below to use a PostgreSQL database for Hive:

```

spec:
  hive:
    spec:
      metastore:
        storage:
          create: false
    config:
      db:
        url: "jdbc:postgresql://postgresql.example.com:5432/hive_metastore"
        driver: "org.postgresql.Driver"
        username: "REPLACEME"
        password: "REPLACEME"

```

You can pass additional JDBC parameters using the URL. For more details see the [PostgreSQL JDBC driver documentation](#).

3.5. CONFIGURING THE REPORTING-OPERATOR

The **reporting-operator** is responsible for collecting data from Prometheus, storing the metrics in Presto, running report queries against Presto, and exposing their results via an HTTP API. Configuring the Operator is primarily done through your **MeteringConfig** file.

3.5.1. Prometheus connection

When you install metering on OpenShift Container Platform, Prometheus is available at <https://prometheus-k8s.openshift-monitoring.svc:9091/>.

To secure the connection to Prometheus, the default metering installation uses the OpenShift Container Platform certificate authority. If your Prometheus instance uses a different CA, the CA can be injected through a ConfigMap. See the following example.

```
spec:
  reporting-operator:
    spec:
      config:
        prometheus:
          certificateAuthority:
            useServiceAccountCA: false
          configMap:
            enabled: true
            create: true
            name: reporting-operator-certificate-authority-config
            filename: "internal-ca.crt"
            value: |
              -----BEGIN CERTIFICATE-----
              (snip)
              -----END CERTIFICATE-----
```

Alternatively, to use the system certificate authorities for publicly valid certificates, set both **useServiceAccountCA** and **configMap.enabled** to **false**.

The **reporting-operator** can also be configured to use a specified bearer token to auth with Prometheus. See the following example.

```
spec:
  reporting-operator:
    spec:
      config:
        prometheus:
          metricsImporter:
            auth:
              useServiceAccountToken: false
              tokenSecret:
                enabled: true
                create: true
                value: "abc-123"
```

3.5.2. Exposing the reporting API

On OpenShift Container Platform the default metering installation automatically exposes a Route, making the reporting API available. This provides the following features:

- Automatic DNS
- Automatic TLS based on the cluster CA

Also, the default installation makes it possible to use the OpenShift service for serving certificates to protect the reporting API with TLS. The OpenShift OAuth proxy is deployed as a side-car container for **reporting-operator**, which protects the reporting API with authentication.

3.5.2.1. Using OpenShift Authentication

By default, the reporting API is secured with TLS and authentication. This is done by configuring the **reporting-operator** to deploy a pod containing both the **reporting-operator's** container, and a sidecar container running OpenShift auth-proxy.

In order to access the reporting API, the metering operator exposes a route. Once that route has been installed, you can run the following command to get the route's hostname.

```
METERING_ROUTE_HOSTNAME=$(oc -n openshift-metering get routes metering -o json | jq -r '.status.ingress[].host')
```

Next, set up authentication using either a service account token or basic authentication with a username/password.

3.5.2.1.1. Authenticate using a service account token

With this method, you use the token in the reporting Operator's service account, and pass that bearer token to the Authorization header in the following command:

```
TOKEN=$(oc -n openshift-metering serviceaccounts get-token reporting-operator)
curl -H "Authorization: Bearer $TOKEN" -k
"https://$METERING_ROUTE_HOSTNAME/api/v1/reports/get?name=[Report
Name]&namespace=openshift-metering&format=[Format]"
```

Be sure to replace the **name=[Report Name]** and **format=[Format]** parameters in the URL above. The **format** parameter can be json, csv, or tabular.

3.5.2.1.2. Authenticate using a username and password

We are able to do basic authentication using a username and password combination, which is specified in the contents of a htpasswd file. By default, we create a secret containing an empty htpasswd data. You can, however, configure the **reporting-operator.spec.authProxy.htpasswd.data** and **reporting-operator.spec.authProxy.htpasswd.createSecret** keys to use this method.

Once you have specified the above in your MeteringConfig, you can run the following command:

```
curl -u testuser:password123 -k "https://$METERING_ROUTE_HOSTNAME/api/v1/reports/get?
name=[Report Name]&namespace=openshift-metering&format=[Format]"
```

Be sure to replace **testuser:password123** with a valid username and password combination.

3.5.2.2. Manually Configuring Authentication

In order to manually configure, or disable OAuth in the **reporting-operator**, you must set **spec.tls.enabled: false** in your MeteringConfig.



WARNING

This also disables all TLS/authentication between the **reporting-operator**, presto, and hive. You would need to manually configure these resources yourself.

Authentication can be enabled by configuring the following options. Enabling authentication configures the **reporting-operator** pod to run the OpenShift auth-proxy as a sidecar container in the pod. This adjusts the ports so that the **reporting-operator** API isn't exposed directly, but instead is proxied to via the auth-proxy sidecar container.

- `reporting-operator.spec.authProxy.enabled`
- `reporting-operator.spec.authProxy.cookie.createSecret`
- `reporting-operator.spec.authProxy.cookie.seed`

You need to set **reporting-operator.spec.authProxy.enabled** and **reporting-operator.spec.authProxy.cookie.createSecret** to **true** and **reporting-operator.spec.authProxy.cookie.seed** to a 32-character random string.

You can generate a 32-character random string using the following command.

```
$ openssl rand -base64 32 | head -c32; echo.
```

3.5.2.2.1. Token authentication

When the following options are set to **true**, authentication using a bearer token is enabled for the reporting REST API. Bearer tokens can come from serviceAccounts or users.

- `reporting-operator.spec.authProxy.subjectAccessReview.enabled`
- `reporting-operator.spec.authProxy.delegateURLs.enabled`

When authentication is enabled, the Bearer token used to query the reporting API of the user or **serviceAccount** must be granted access using one of the following roles:

- `report-exporter`
- `reporting-admin`
- `reporting-viewer`
- `metering-admin`
- `metering-viewer`

The **metering-operator** is capable of creating RoleBindings for you, granting these permissions by specifying a list of subjects in the **spec.permissions** section. For an example, see the following **advanced-auth.yaml** example configuration.

```

apiVersion: metering.openshift.io/v1
kind: MeteringConfig
metadata:
  name: "operator-metering"
spec:
  permissions:
    # anyone in the "metering-admins" group can create, update, delete, etc any
    # metering.openshift.io resources in the namespace.
    # This also grants permissions to get query report results from the reporting REST API.
  meteringAdmins:
    - kind: Group
      name: metering-admins
    # Same as above except read only access and for the metering-viewers group.
  meteringViewers:
    - kind: Group
      name: metering-viewers
    # the default serviceaccount in the namespace "my-custom-ns" can:
    # create, update, delete, etc reports.
    # This also gives permissions query the results from the reporting REST API.
  reportingAdmins:
    - kind: ServiceAccount
      name: default
      namespace: my-custom-ns
    # anyone in the group reporting-readers can get, list, watch reports, and
    # query report results from the reporting REST API.
  reportingViewers:
    - kind: Group
      name: reporting-readers
    # anyone in the group cluster-admins can query report results
    # from the reporting REST API. So can the user bob-from-accounting.
  reportExporters:
    - kind: Group
      name: cluster-admins
    - kind: User
      name: bob-from-accounting

reporting-operator:
spec:
  authProxy:
    # httpasswd.data can contain httpasswd file contents for allowing auth
    # using a static list of usernames and their password hashes.
    #
    # username is 'testuser' password is 'password123'
    # generated httpasswdData using: `httpasswd -nb -s testuser password123`
    # httpasswd:
    # data: |
    #   testuser:{SHA}y/2sYAj5yrQIN4TL0YdPdmGNKpc=
    #
    # change REPLACEME to the output of your httpasswd command
  httpasswd:
    data: |
      REPLACEME

```

Alternatively, you can use any role which has rules granting **get** permissions to **reports/export**. This means **get** access to the **export** sub-resource of the Report resources in the namespace of the **reporting-operator**. For example: **admin** and **cluster-admin**.

By default, the **reporting-operator** and **metering-operator serviceAccounts** both have these permissions, and their tokens can be used for authentication.

3.5.2.2.2. Basic authentication (username/password)

For basic authentication you can supply a username and password in **reporting-operator.spec.authProxy.htpasswd.data**. The username and password must be the same format as those found in an htpasswd file. When set, you can use HTTP basic authentication to provide your username and password that has a corresponding entry in the **htpasswdData** contents.

3.6. CONFIGURE AWS BILLING CORRELATION

Metering can correlate cluster usage information with [AWS detailed billing information](#), attaching a dollar amount to resource usage. For clusters running in EC2, you can enable this by modifying the example **aws-billing.yaml** file below.

```
apiVersion: metering.openshift.io/v1
kind: MeteringConfig
metadata:
  name: "operator-metering"
spec:
  openshift-reporting:
    spec:
      awsBillingReportDataSource:
        enabled: true
        # Replace these with where your AWS billing reports are
        # stored in S3.
        bucket: "<your-aws-cost-report-bucket>" 1
        prefix: "<path/to/report>"
        region: "<your-buckets-region>"

  reporting-operator:
    spec:
      config:
        aws:
          secretName: "<your-aws-secret>" 2

  presto:
    spec:
      config:
        aws:
          secretName: "<your-aws-secret>" 3

  hive:
    spec:
      config:
        aws:
          secretName: "<your-aws-secret>" 4
```

To enable AWS billing correlation, first ensure the AWS Cost and Usage Reports are enabled. For more information, see [Turning on the AWS Cost and Usage Report](#) in the AWS documentation.

- 1 Update the bucket, prefix, and region to the location of your AWS Detailed billing report.
- 2 3 4 All **secretName** fields should be set to the name of a secret in the metering namespace containing AWS credentials in the **data.aws-access-key-id** and **data.aws-secret-access-key** fields. See the example secret file below for more details.

```
apiVersion: v1
kind: Secret
metadata:
  name: <your-aws-secret>
data:
  aws-access-key-id: "dGVzdAo="
  aws-secret-access-key: "c2VjcmV0Cg=="
```

To store data in S3, the **aws-access-key-id** and **aws-secret-access-key** credentials must have read and write access to the bucket. For an example of an IAM policy granting the required permissions, see the **aws/read-write.json** file below.

```
{
  "Version": "2012-10-17",
  "Statement": [
    {
      "Sid": "1",
      "Effect": "Allow",
      "Action": [
        "s3:AbortMultipartUpload",
        "s3:DeleteObject",
        "s3:GetObject",
        "s3:HeadBucket",
        "s3:ListBucket",
        "s3:ListMultipartUploadParts",
        "s3:PutObject"
      ],
      "Resource": [
        "arn:aws:s3:::operator-metering-data/*", 1
        "arn:aws:s3:::operator-metering-data" 2
      ]
    }
  ]
}

{
  "Version": "2012-10-17",
  "Statement": [
    {
      "Sid": "1",
      "Effect": "Allow",
      "Action": [
        "s3:AbortMultipartUpload",
        "s3:DeleteObject",
        "s3:GetObject",
        "s3:HeadBucket",
        "s3:ListBucket",
```

```
    "s3:ListMultipartUploadParts",
    "s3:PutObject"
  ],
  "Resource": [
    "arn:aws:s3::operator-metering-data/*", 3
    "arn:aws:s3::operator-metering-data" 4
  ]
}
]
```

1 2 3 4 Replace **operator-metering-data** with the name of your bucket.

This can be done either pre-installation or post-installation. Disabling it post-installation can cause errors in the **reporting-operator**.

CHAPTER 4. REPORTS

4.1. ABOUT REPORTS

A Report is an API object that provides a method to manage periodic ETL (Extract Transform and Load) jobs using SQL queries. They are composed using other Metering resources such as **ReportQueries**, which provide the actual SQL query to run, and **ReportDataSources**, which are what define the data available to the ReportQueries and Reports.

Many use cases are addressed out-of-the-box with the predefined **ReportQueries** and **ReportDataSources** that come installed with metering, so you do not need to define your own unless you have a use-case not covered by what is predefined.

4.1.1. Reports

The Report custom resource is used to manage the execution and status of reports. Metering produces reports derived from usage data sources, which can be used in further analysis and filtering.

A single Report resource represents a job that manages a database table and updates it with new information according to a schedule. The Report exposes the data in that table via the reporting-operator HTTP API. Reports with a **spec.schedule** field set are always running and track what time periods it has collected data for. This ensures that if metering is shutdown or unavailable for an extended period of time, it will backfill the data starting where it left off. If the schedule is unset, then the Report will run once for the time specified by the **reportingStart** and **reportingEnd**. By default, reports wait for ReportDataSources to have fully imported any data covered in the reporting period. If the Report has a schedule, it will wait to run until the data in the period currently being processed has finished importing.

4.1.1.1. Example Report with a Schedule

The following example Report will contain information on every Pod's CPU requests, and will run every hour, adding the last hours worth of data each time it runs.

```
apiVersion: metering.openshift.io/v1
kind: Report
metadata:
  name: pod-cpu-request-hourly
spec:
  query: "pod-cpu-request"
  reportingStart: "2019-07-01T00:00:00Z"
  schedule:
    period: "hourly"
  hourly:
    minute: 0
    second: 0
```

4.1.1.2. Example Report without a Schedule (Run-Once)

The following example Report will contain information on every Pod's CPU requests for all of July. After completion, it does not run again.

```
apiVersion: metering.openshift.io/v1
kind: Report
```

```

metadata:
  name: pod-cpu-request-hourly
spec:
  query: "pod-cpu-request"
  reportingStart: "2019-07-01T00:00:00Z"
  reportingEnd: "2019-07-31T00:00:00Z"

```

4.1.1.3. query

Names the ReportQuery used to generate the report. The report query controls the schema of the report as well as how the results are processed.

query is a required field.

Use the **oc** CLI to obtain a list of available ReportQuery objects:

```

$ oc -n openshift-metering get reportqueries
NAME                                AGE
cluster-cpu-capacity                23m
cluster-cpu-capacity-raw            23m
cluster-cpu-usage                   23m
cluster-cpu-usage-raw               23m
cluster-cpu-utilization              23m
cluster-memory-capacity              23m
cluster-memory-capacity-raw          23m
cluster-memory-usage                 23m
cluster-memory-usage-raw             23m
cluster-memory-utilization           23m
cluster-persistentvolumeclaim-request 23m
namespace-cpu-request                23m
namespace-cpu-usage                  23m
namespace-cpu-utilization             23m
namespace-memory-request              23m
namespace-memory-usage                23m
namespace-memory-utilization          23m
namespace-persistentvolumeclaim-request 23m
namespace-persistentvolumeclaim-usage 23m
node-cpu-allocatable                 23m
node-cpu-allocatable-raw             23m
node-cpu-capacity                    23m
node-cpu-capacity-raw                 23m
node-cpu-utilization                  23m
node-memory-allocatable               23m
node-memory-allocatable-raw           23m
node-memory-capacity                  23m
node-memory-capacity-raw              23m
node-memory-utilization                23m
persistentvolumeclaim-capacity        23m
persistentvolumeclaim-capacity-raw    23m
persistentvolumeclaim-phase-raw       23m
persistentvolumeclaim-request         23m
persistentvolumeclaim-request-raw     23m
persistentvolumeclaim-usage           23m
persistentvolumeclaim-usage-raw       23m
persistentvolumeclaim-usage-with-phase-raw 23m

```

pod-cpu-request	23m
pod-cpu-request-raw	23m
pod-cpu-usage	23m
pod-cpu-usage-raw	23m
pod-memory-request	23m
pod-memory-request-raw	23m
pod-memory-usage	23m
pod-memory-usage-raw	23m

ReportQueries with the **-raw** suffix are used by other ReportQueries to build more complex queries, and should not be used directly for reports.

namespace- prefixed queries aggregate Pod CPU/memory requests by namespace, providing a list of namespaces and their overall usage based on resource requests.

pod- prefixed queries are similar to **namespace-** prefixed queries but aggregate information by Pod rather than namespace. These queries include the Pod's namespace and node.

node- prefixed queries return information about each node's total available resources.

aws- prefixed queries are specific to AWS. Queries suffixed with **-aws** return the same data as queries of the same name without the suffix, and correlate usage with the EC2 billing data.

The **aws-ec2-billing-data** report is used by other queries, and should not be used as a standalone report. The **aws-ec2-cluster-cost** report provides a total cost based on the nodes included in the cluster, and the sum of their costs for the time period being reported on.

For a complete list of fields, use the **oc** CLI to get the ReportQuery as YAML, and check the **spec.columns** field:

For example, run:

```
$ oc -n openshift-metering get reportqueries namespace-memory-request -o yaml
```

You should see output like:

```
apiVersion: metering.openshift.io/v1
kind: ReportQuery
metadata:
  name: namespace-memory-request
  labels:
    operator-metering: "true"
spec:
  columns:
  - name: period_start
    type: timestamp
    unit: date
  - name: period_end
    type: timestamp
    unit: date
  - name: namespace
    type: varchar
    unit: kubernetes_namespace
  - name: pod_request_memory_byte_seconds
    type: double
    unit: byte_seconds
```

4.1.1.4. schedule

The **spec.schedule** configuration block defines when the report runs. The main fields in the **schedule** section are **period**, and then depending on the value of **period**, the fields **hourly**, **daily**, **weekly**, and **monthly** allow you to fine-tune when the report runs.

For example, if **period** is set to **weekly**, you can add a **weekly** field to the **spec.schedule** block. The following example will run once a week on Wednesday, at 1 PM (hour 13 in the day).

```
...
schedule:
  period: "weekly"
  weekly:
    dayOfWeek: "wednesday"
    hour: 13
...
```

4.1.1.4.1. period

Valid values of **schedule.period** are listed below, and the options available to set for a given period are also listed.

- **hourly**
 - **minute**
 - **second**
- **daily**
 - **hour**
 - **minute**
 - **second**
- **weekly**
 - **dayOfWeek**
 - **hour**
 - **minute**
 - **second**
- **monthly**
 - **dayOfMonth**
 - **hour**
 - **minute**
 - **second**
- **cron**

- **expression**

Generally, the **hour**, **minute**, **second** fields control when in the day the report runs, and **dayOfWeek/dayOfMonth** control what day of the week, or day of month the report runs on, if it is a weekly or monthly report period.

For each of these fields, there is a range of valid values:

- **hour** is an integer value between 0–23.
- **minute** is an integer value between 0–59.
- **second** is an integer value between 0–59.
- **dayOfWeek** is a string value that expects the day of the week (spelled out).
- **dayOfMonth** is an integer value between 1–31.

For cron periods, normal cron expressions are valid:

- **expression:** `"*/5 * * * *"`

4.1.1.5. reportingStart

To support running a Report against existing data, you can set the **spec.reportingStart** field to a [RFC3339 timestamp](#) to tell the Report to run according to its **schedule** starting from **reportingStart** rather than the current time. One important thing to understand is that this will result in the reporting-operator running many queries in succession for each interval in the schedule that is between the **reportingStart** time and the current time. This could be thousands of queries if the period is less than daily and the **reportingStart** is more than a few months back. If **reportingStart** is left unset, the Report will run at the next full reportingPeriod after the time the report is created.

As an example of how to use this field, if you had data already collected dating back to January 1st, 2019, which you wanted to be included in your Report, you could create a report with the following values:

```
apiVersion: metering.openshift.io/v1
kind: Report
metadata:
  name: pod-cpu-request-hourly
spec:
  query: "pod-cpu-request"
  schedule:
    period: "hourly"
    reportingStart: "2019-01-01T00:00:00Z"
```

4.1.1.6. reportingEnd

To configure a Report to only run until a specified time, you can set the **spec.reportingEnd** field to an [RFC3339 timestamp](#). The value of this field will cause the Report to stop running on its schedule after it has finished generating reporting data for the period covered from its start time until **reportingEnd**. Because a schedule will most likely not align with reportingEnd, the last period in the schedule will be shortened to end at the specified reportingEnd time. If left unset, then the Report will run forever, or until a **reportingEnd** is set on the Report.

For example, if you wanted to create a report that runs once a week for the month of July:

```

apiVersion: metering.openshift.io/v1
kind: Report
metadata:
  name: pod-cpu-request-hourly
spec:
  query: "pod-cpu-request"
  schedule:
    period: "weekly"
  reportingStart: "2019-07-01T00:00:00Z"
  reportingEnd: "2019-07-31T00:00:00Z"

```

4.1.1.7. runImmediately

When **runImmediately** is set to **true**, the report will be run immediately. This behavior ensures that the report is immediately processed and queued without requiring additional scheduling parameters.



NOTE

When **runImmediately** is set to **true** you must set a **reportingEnd** and **reportingStart** value.

4.1.1.8. inputs

The **spec.inputs** field of a Report can be used to override or set values defined in a ReportQuery's **spec.inputs** field.

It is a list of name-value pairs:

```

spec:
  inputs:
    - name: "NamespaceCPUUsageReportName"
      value: "namespace-cpu-usage-hourly"

```

The **name** of an input must exist in the ReportQuery's **inputs** list. The **value** of the input must be the correct type for the input's **type**.

4.1.1.9. Roll-up Reports

Report data is stored in the database much like metrics themselves, and therefore, can be used in aggregated or roll-up reports. A simple use case for a roll-up report is to spread the time required to produce a report over a longer period of time; instead of: requiring a monthly report to query and add all data over an entire month, the task can be split into daily reports that each run over a thirtieth of the data.

A custom roll-up report requires a custom report query. The ReportQuery template processor provides a function: **reportTableName** that can get the necessary table name from a Report's **metadata.name**.

Below is a snippet taken from a built-in query:

```

# Taken from pod-cpu.yaml
spec:
  ...
  inputs:
    - name: ReportingStart

```

```

    type: time
  - name: ReportingEnd
    type: time
  - name: NamespaceCPUUsageReportName
    type: Report
  - name: PodCpuUsageRawDataSourceName
    type: ReportDataSource
    default: pod-cpu-usage-raw
  ...

  query: |
  ...
  {{- if .Report.Inputs.NamespaceCPUUsageReportName }}
    namespace,
    sum(pod_usage_cpu_core_seconds) as pod_usage_cpu_core_seconds
  FROM {{ .Report.Inputs.NamespaceCPUUsageReportName | reportTableName }}
  ...

# aggregated-report.yaml
spec:
  query: "namespace-cpu-usage"
  inputs:
  - name: "NamespaceCPUUsageReportName"
    value: "namespace-cpu-usage-hourly"

```

4.1.1.9.1. Report Status

The execution of a scheduled report can be tracked using its status field. Any errors occurring during the preparation of a report will be recorded here.

The **status** field of a Report currently has two fields:

- **conditions**: Conditions is a list of conditions, each of which have a **type**, **status**, **reason**, and **message** field. Possible values of a condition's **type** field are **Running** and **Failure**, indicating the current state of the scheduled report. The **reason** indicates why its **condition** is in its current state with the **status** being either **true**, **false** or, **unknown**. The **message** provides a human readable indicating why the condition is in the current state. For detailed information on the **reason** values see [pkg/apis/metering/v1/util/report_util.go](#).
- **lastReportTime**: Indicates the time Metering has collected data up to.

4.2. STORAGE LOCATIONS

A StorageLocation is a custom resource that configures where data will be stored by the reporting-operator. This includes the data collected from Prometheus, and the results produced by generating a Report custom resource.

You only need to configure a StorageLocation if you want to store data in multiple locations, like multiple S3 buckets or both S3 and HDFS, or if you wish to access a database in Hive/Presto that was not created by metering. For most users this is not a requirement, and the [documentation on configuring metering](#) is sufficient to configure all necessary storage components.

4.2.1. StorageLocation examples

This first example is what the built-in local storage option looks like. It is configured to use Hive, and by default data is stored wherever Hive is configured to use storage (HDFS, S3, or a ReadWriteMany PVC).

Local storage example

```
apiVersion: metering.openshift.io/v1
kind: StorageLocation
metadata:
  name: hive
  labels:
    operator-metering: "true"
spec:
  hive: ❶
    databaseName: metering ❷
    unmanagedDatabase: false ❸
```

- ❶ If the **hive** section is present, then the StorageLocation will be configured to store data in Presto by creating the table using Hive server. Only `databaseName` and `unmanagedDatabase` are required fields.
- ❷ The name of the database within hive.
- ❸ If **true**, then this StorageLocation will not be actively managed, and the `databaseName` is expected to already exist in Hive. If **false**, this will cause the reporting-operator to create the database in Hive.

The next example uses an AWS S3 bucket for storage. The prefix is appended to the bucket name when constructing the path to use.

Remote storage example

```
apiVersion: metering.openshift.io/v1
kind: StorageLocation
metadata:
  name: example-s3-storage
  labels:
    operator-metering: "true"
spec:
  hive:
    databaseName: example_s3_storage
    unmanagedDatabase: false
    location: "s3a://bucket-name/path/within/bucket" ❶
```

- ❶ (optional) The filesystem URL for Presto and Hive to use for the database. This can be an **hdfs://** or **s3a://** filesystem URL.

There are some additional optional fields that can be specified in the **hive** section:

- (optional) `defaultTableProperties`: Contains configuration options for creating tables using Hive.
- (optional) `fileFormat`: The file format used for storing files in the filesystem. See the [Hive Documentation on File Storage Format](#) for a list of options and more details.

- (optional) `rowFormat`: Controls the [Hive row format](#). This controls how Hive serializes and deserializes rows. See the [Hive Documentation on Row Formats and SerDe](#) for more details.

4.2.2. Default StorageLocation

If an annotation `storagelocation.metering.openshift.io/is-default` exists and is set to `true` on a `StorageLocation` resource, then that resource becomes the default storage resource. Any components with a storage configuration option where `StorageLocation` is not specified will use the default storage resource. There can be only one default storage resource. If more than one resource with the annotation exists, an error is logged because the Operator cannot determine the default.

Default storage example

```
apiVersion: metering.openshift.io/v1
kind: StorageLocation
metadata:
  name: example-s3-storage
  labels:
    operator-metering: "true"
  annotations:
    storagelocation.metering.openshift.io/is-default: "true"
spec:
  hive:
    databaseName: example_s3_storage
    unmanagedDatabase: false
    location: "s3a://bucket-name/path/within/bucket"
```

CHAPTER 5. USING METERING

5.1. PREREQUISITES

- [Install Metering](#)
- Review the details about the available options that can be configured for a [Report](#) and how they function.

5.2. WRITING REPORTS

Writing a Report is the way to process and analyze data using Metering.

To write a Report, you must define a Report resource in a YAML file, specify the required parameters, and create it in the **openshift-metering** namespace by using **oc**.

Prerequisites

- Metering is installed.

Procedure

1. Change to the **openshift-metering** project:

```
$ oc project openshift-metering
```

2. Create a Report resource as a YAML file:
 - a. Create a YAML file with the following content:

```
apiVersion: metering.openshift.io/v1
kind: Report
metadata:
  name: namespace-cpu-request-2019 1
  namespace: openshift-metering
spec:
  reportingStart: '2019-01-01T00:00:00Z'
  reportingEnd: '2019-12-30T23:59:59Z'
  query: namespace-cpu-request 2
  runImmediately: true 3
```

- 2** The **query** specifies ReportQuery used to generate the Report. Change this based on what you want to report on. For a list of options, run **oc get reportqueries | grep -v raw**.
- 1** Use a descriptive name about what the Report does for **metadata.name**. A good name is the query, and the schedule or period you used.
- 3** Set **runImmediately** to **true** for it to run with whatever data is available, or set it to **false** if you want it to wait for **reportingEnd** to pass.

- b. Run the following command to create the Report:

■

```
$ oc create -f <file-name>.yaml
report.metering.openshift.io/namespace-cpu-request-2019 created
```

- You can list Reports and their **Running** status with the following command:

```
$ oc get reports

NAME                QUERY                SCHEDULE  RUNNING  FAILED  LAST
REPORT TIME        AGE
namespace-cpu-request-2019 namespace-cpu-request  Finished  2019-12-
30T23:59:59Z  26s
```

5.3. VIEWING REPORT RESULTS

Viewing a Report's results involves querying the reporting-api **Route** and authenticating to the API using your OpenShift Container Platform credentials. Reports can be retrieved as **JSON**, **CSV**, or **Tabular** formats.

Prerequisites

- Metering is installed.
- To access Report results, you must either be a cluster administrator, or you need to be granted access using the **report-exporter** role in the **openshift-metering** namespace.

Procedure

- Change to the **openshift-metering** project:

```
$ oc project openshift-metering
```

- Query the reporting API for results:

- Get the route to the **reporting-api**:

```
$ meteringRoute="$(oc get routes metering -o jsonpath='{.spec.host}')"
$ echo "$meteringRoute"
```

- Get the token of your current user to be used in the request:

```
$ token="$(oc whoami -t)"
```

- To get the results, use **curl** to make a request to the reporting API for your report:

```
$ reportName=namespace-cpu-request-2019 1
$ reportFormat=csv 2
$ curl --insecure -H "Authorization: Bearer ${token}"
"https://{meteringRoute}/api/v1/reports/get?
name=${reportName}&namespace=openshift-metering&format=${reportFormat}"
```

- Set **reportName** to the name of the **Report** you created.

- 2 Set **reportFormat** to one of **csv**, **json**, or **tabular** to specify the output format of the API response.

The response should look similar to the following (example output is with **reportName=namespace-cpu-request-2019** and **reportFormat=csv**):

```

period_start,period_end,namespace,pod_request_cpu_core_seconds
2019-01-01 00:00:00 +0000 UTC,2019-12-30 23:59:59 +0000 UTC,openshift-
apiserver,11745.000000
2019-01-01 00:00:00 +0000 UTC,2019-12-30 23:59:59 +0000 UTC,openshift-apiserver-
operator,261.000000
2019-01-01 00:00:00 +0000 UTC,2019-12-30 23:59:59 +0000 UTC,openshift-
authentication,522.000000
2019-01-01 00:00:00 +0000 UTC,2019-12-30 23:59:59 +0000 UTC,openshift-
authentication-operator,261.000000
2019-01-01 00:00:00 +0000 UTC,2019-12-30 23:59:59 +0000 UTC,openshift-cloud-
credential-operator,261.000000
2019-01-01 00:00:00 +0000 UTC,2019-12-30 23:59:59 +0000 UTC,openshift-cluster-
machine-approver,261.000000
2019-01-01 00:00:00 +0000 UTC,2019-12-30 23:59:59 +0000 UTC,openshift-cluster-
node-tuning-operator,3385.800000
2019-01-01 00:00:00 +0000 UTC,2019-12-30 23:59:59 +0000 UTC,openshift-cluster-
samples-operator,261.000000
2019-01-01 00:00:00 +0000 UTC,2019-12-30 23:59:59 +0000 UTC,openshift-cluster-
version,522.000000
2019-01-01 00:00:00 +0000 UTC,2019-12-30 23:59:59 +0000 UTC,openshift-
console,522.000000
2019-01-01 00:00:00 +0000 UTC,2019-12-30 23:59:59 +0000 UTC,openshift-console-
operator,261.000000
2019-01-01 00:00:00 +0000 UTC,2019-12-30 23:59:59 +0000 UTC,openshift-controller-
manager,7830.000000
2019-01-01 00:00:00 +0000 UTC,2019-12-30 23:59:59 +0000 UTC,openshift-controller-
manager-operator,261.000000
2019-01-01 00:00:00 +0000 UTC,2019-12-30 23:59:59 +0000 UTC,openshift-
dns,34372.800000
2019-01-01 00:00:00 +0000 UTC,2019-12-30 23:59:59 +0000 UTC,openshift-dns-
operator,261.000000
2019-01-01 00:00:00 +0000 UTC,2019-12-30 23:59:59 +0000 UTC,openshift-
etcd,23490.000000
2019-01-01 00:00:00 +0000 UTC,2019-12-30 23:59:59 +0000 UTC,openshift-image-
registry,5993.400000
2019-01-01 00:00:00 +0000 UTC,2019-12-30 23:59:59 +0000 UTC,openshift-
ingress,5220.000000
2019-01-01 00:00:00 +0000 UTC,2019-12-30 23:59:59 +0000 UTC,openshift-ingress-
operator,261.000000
2019-01-01 00:00:00 +0000 UTC,2019-12-30 23:59:59 +0000 UTC,openshift-kube-
apiserver,12528.000000
2019-01-01 00:00:00 +0000 UTC,2019-12-30 23:59:59 +0000 UTC,openshift-kube-
apiserver-operator,261.000000
2019-01-01 00:00:00 +0000 UTC,2019-12-30 23:59:59 +0000 UTC,openshift-kube-
controller-manager,8613.000000
2019-01-01 00:00:00 +0000 UTC,2019-12-30 23:59:59 +0000 UTC,openshift-kube-
controller-manager-operator,261.000000
2019-01-01 00:00:00 +0000 UTC,2019-12-30 23:59:59 +0000 UTC,openshift-machine-
api,1305.000000

```

2019-01-01 00:00:00 +0000 UTC,2019-12-30 23:59:59 +0000 UTC,openshift-machine-config-operator,9637.800000
2019-01-01 00:00:00 +0000 UTC,2019-12-30 23:59:59 +0000 UTC,openshift-metering,19575.000000
2019-01-01 00:00:00 +0000 UTC,2019-12-30 23:59:59 +0000 UTC,openshift-monitoring,6256.800000
2019-01-01 00:00:00 +0000 UTC,2019-12-30 23:59:59 +0000 UTC,openshift-network-operator,261.000000
2019-01-01 00:00:00 +0000 UTC,2019-12-30 23:59:59 +0000 UTC,openshift-sdn,94503.000000
2019-01-01 00:00:00 +0000 UTC,2019-12-30 23:59:59 +0000 UTC,openshift-service-ca,783.000000
2019-01-01 00:00:00 +0000 UTC,2019-12-30 23:59:59 +0000 UTC,openshift-service-ca-operator,261.000000

CHAPTER 6. EXAMPLES OF USING METERING

Use the following example Reports to get started measuring capacity, usage, and utilization in your cluster. These examples showcase the various types of reports metering offers, along with a selection of the predefined queries.

6.1. PREREQUISITES

- [Install Metering](#)
- Review the details about [writing and viewing reports](#).

6.2. MEASURE CLUSTER CAPACITY HOURLY AND DAILY

The following Report demonstrates how to measure cluster capacity both hourly and daily. The daily Report works by aggregating the hourly Report's results.

The following report measures cluster CPU capacity every hour.

Hourly CPU capacity by cluster example

```
apiVersion: metering.openshift.io/v1
kind: Report
metadata:
  name: cluster-cpu-capacity-hourly
spec:
  query: "cluster-cpu-capacity"
  schedule:
    period: "hourly" 1
```

- 1** You could change this period to **daily** to get a daily report, but with larger data sets it is more efficient to use an hourly report, then aggregate your hourly data into a daily report.

The following report aggregates the hourly data into a daily report.

Daily CPU capacity by cluster example

```
apiVersion: metering.openshift.io/v1
kind: Report
metadata:
  name: cluster-cpu-capacity-daily 1
spec:
  query: "cluster-cpu-capacity" 2
  inputs: 3
  - name: ClusterCpuCapacityReportName
    value: cluster-cpu-capacity-hourly
  schedule:
    period: "daily"
```

- 1** To stay organized, remember to change the name of your Report if you change any of the other values.

- 2 You can also measure **cluster-memory-capacity**. Remember to update the query in the associated hourly report as well.
- 3 The **inputs** section configures this report to aggregate the hourly report. Specifically, **value: cluster-cpu-capacity-hourly** is the name of the hourly report that gets aggregated.

6.3. MEASURE CLUSTER USAGE WITH A ONE-TIME REPORT

The following Reports to measure cluster usage from a specific starting date forward. The Report only runs once, after you save it and apply it.

CPU usage by cluster example

```
apiVersion: metering.openshift.io/v1
kind: Report
metadata:
  name: cluster-cpu-usage-2019 1
spec:
  reportingStart: '2019-01-01T00:00:00Z' 2
  reportingEnd: '2019-12-30T23:59:59Z'
  query: cluster-cpu-usage 3
  runImmediately: true 4
```

- 1 To stay organized, remember to change the name of your Report if you change any of the other values.
- 2 Configures the Reports to start using data from the **reportingStart** timestamp until the **reportingEnd** timestamp.
- 3 Adjust your query here. You can also measure cluster usage with the **cluster-memory-usage** query.
- 4 This tells the Report to run immediately after saving it and applying it.

6.4. MEASURE CLUSTER UTILIZATION USING CRON EXPRESSIONS

You can also use cron expressions when configuring the period of your reports. The following report measures cluster utilization by looking at CPU utilization from 9am-5pm every weekday.

Weekday CPU utilization by cluster example

```
apiVersion: metering.openshift.io/v1
kind: Report
metadata:
  name: cluster-cpu-utilization-weekdays 1
spec:
  query: "cluster-cpu-utilization" 2
  schedule:
    period: "cron"
    expression: 0 0 * * 1-5 3
```

- 1 To stay organized, remember to change the name of your Report if you change any of the other values.
- 2 Adjust your query here. You can also measure cluster utilization with the **cluster-memory-utilization** query.
- 3 For cron periods, normal cron expressions are valid.

CHAPTER 7. TROUBLESHOOTING AND DEBUGGING METERING

Use the following sections to help troubleshoot and debug specific issues with metering.

In addition to the information in this section, be sure to review the following topics:

- [Prerequisites for installing metering.](#)
- [About configuring metering](#)

7.1. TROUBLESHOOTING METERING

A common issue with metering is Pods failing to start. Pods might fail to start due to lack of resources or if they have a dependency on a resource that does not exist, such as a StorageClass or Secret.

7.1.1. Not enough compute resources

A common issue when installing or running metering is lack of compute resources. Ensure that metering is allocated the minimum resource requirements described in the installation prerequisites.

To determine if the issue is with resources or scheduling, follow the troubleshooting instructions included in the Kubernetes document [Managing Compute Resources for Containers](#).

7.1.2. StorageClass not configured

Metering requires that a default StorageClass be configured for dynamic provisioning.

See the documentation on configuring metering for information on how to check if there are any StorageClasses configured for the cluster, how to set the default, and how to configure metering to use a StorageClass other than the default.

7.1.3. Secret not configured correctly

A common issue with metering is providing the incorrect secret when configuring your persistent storage. Be sure to review the example configuration files and create your secret according to the guidelines for your storage provider.

7.2. DEBUGGING METERING

Debugging metering is much easier when you interact directly with the various components. The sections below detail how you can connect and query Presto and Hive as well as view the dashboards of the Presto and HDFS components.



NOTE

All of the commands in this section assume you have installed metering through OperatorHub in the **openshift-metering** namespace.

7.2.1. Get reporting operator logs

The command below will follow the logs of the **reporting-operator**.

■

```
$ oc -n openshift-metering logs -f "$(oc -n openshift-metering get pods -l app=reporting-operator -o name | cut -c 5-)" -c reporting-operator
```

7.2.2. Query Presto using presto-cli

The following command opens an interactive presto-cli session where you can query Presto. This session runs in the same container as Presto and launches an additional Java instance, which can create memory limits for the Pod. If this occurs, you should increase the memory request and limits of the Presto Pod.

By default, Presto is configured to communicate using TLS. You must to run the following command to run Presto queries:

```
$ oc -n openshift-metering exec -it "$(oc -n openshift-metering get pods -l app=presto,presto=coordinator -o name | cut -d/ -f2)" -- /usr/local/bin/presto-cli --server https://presto:8080 --catalog hive --schema default --user root --keystore-path /opt/presto/tls/keystore.pem
```

Once you run this command, a prompt appears where you can run queries. Use the **show tables from metering**; query to view the list of tables:

```
$ presto:default> show tables from metering;
```

Table

```
datasource_your_namespace_cluster_cpu_capacity_raw
datasource_your_namespace_cluster_cpu_usage_raw
datasource_your_namespace_cluster_memory_capacity_raw
datasource_your_namespace_cluster_memory_usage_raw
datasource_your_namespace_node_allocatable_cpu_cores
datasource_your_namespace_node_allocatable_memory_bytes
datasource_your_namespace_node_capacity_cpu_cores
datasource_your_namespace_node_capacity_memory_bytes
datasource_your_namespace_node_cpu_allocatable_raw
datasource_your_namespace_node_cpu_capacity_raw
datasource_your_namespace_node_memory_allocatable_raw
datasource_your_namespace_node_memory_capacity_raw
datasource_your_namespace_persistentvolumeclaim_capacity_bytes
datasource_your_namespace_persistentvolumeclaim_capacity_raw
datasource_your_namespace_persistentvolumeclaim_phase
datasource_your_namespace_persistentvolumeclaim_phase_raw
datasource_your_namespace_persistentvolumeclaim_request_bytes
datasource_your_namespace_persistentvolumeclaim_request_raw
datasource_your_namespace_persistentvolumeclaim_usage_bytes
datasource_your_namespace_persistentvolumeclaim_usage_raw
datasource_your_namespace_persistentvolumeclaim_usage_with_phase_raw
datasource_your_namespace_pod_cpu_request_raw
datasource_your_namespace_pod_cpu_usage_raw
datasource_your_namespace_pod_limit_cpu_cores
datasource_your_namespace_pod_limit_memory_bytes
datasource_your_namespace_pod_memory_request_raw
datasource_your_namespace_pod_memory_usage_raw
datasource_your_namespace_pod_persistentvolumeclaim_request_info
datasource_your_namespace_pod_request_cpu_cores
datasource_your_namespace_pod_request_memory_bytes
datasource_your_namespace_pod_usage_cpu_cores
```

```
datasource_your_namespace_pod_usage_memory_bytes
(32 rows)
```

```
Query 20190503_175727_00107_3venm, FINISHED, 1 node
Splits: 19 total, 19 done (100.00%)
0:02 [32 rows, 2.23KB] [19 rows/s, 1.37KB/s]
```

```
presto:default>
```

7.2.3. Query Hive using beeline

The following opens an interactive beeline session where you can query Hive. This session runs in the same container as Hive and launches an additional Java instance, which can create memory limits for the Pod. If this occurs, you should increase the memory request and limits of the Hive Pod.

```
$ oc -n openshift-metering exec -it $(oc -n openshift-metering get pods -l app=hive,hive=server -o
name | cut -d/ -f2) -c hiveserver2 -- beeline -u 'jdbc:hive2://127.0.0.1:10000/default;auth=noSasl'
```

Once you run this command, a prompt appears where you can run queries. Use the **show tables;** query to view the list of tables:

```
$ 0: jdbc:hive2://127.0.0.1:10000/default> show tables from metering;
+-----+
|          tab_name          |
+-----+
| datasource_your_namespace_cluster_cpu_capacity_raw |
| datasource_your_namespace_cluster_cpu_usage_raw |
| datasource_your_namespace_cluster_memory_capacity_raw |
| datasource_your_namespace_cluster_memory_usage_raw |
| datasource_your_namespace_node_allocatable_cpu_cores |
| datasource_your_namespace_node_allocatable_memory_bytes |
| datasource_your_namespace_node_capacity_cpu_cores |
| datasource_your_namespace_node_capacity_memory_bytes |
| datasource_your_namespace_node_cpu_allocatable_raw |
| datasource_your_namespace_node_cpu_capacity_raw |
| datasource_your_namespace_node_memory_allocatable_raw |
| datasource_your_namespace_node_memory_capacity_raw |
| datasource_your_namespace_persistentvolumeclaim_capacity_bytes |
| datasource_your_namespace_persistentvolumeclaim_capacity_raw |
| datasource_your_namespace_persistentvolumeclaim_phase |
| datasource_your_namespace_persistentvolumeclaim_phase_raw |
| datasource_your_namespace_persistentvolumeclaim_request_bytes |
| datasource_your_namespace_persistentvolumeclaim_request_raw |
| datasource_your_namespace_persistentvolumeclaim_usage_bytes |
| datasource_your_namespace_persistentvolumeclaim_usage_raw |
| datasource_your_namespace_persistentvolumeclaim_usage_with_phase_raw |
| datasource_your_namespace_pod_cpu_request_raw |
| datasource_your_namespace_pod_cpu_usage_raw |
| datasource_your_namespace_pod_limit_cpu_cores |
| datasource_your_namespace_pod_limit_memory_bytes |
| datasource_your_namespace_pod_memory_request_raw |
| datasource_your_namespace_pod_memory_usage_raw |
| datasource_your_namespace_pod_persistentvolumeclaim_request_info |
| datasource_your_namespace_pod_request_cpu_cores |
| datasource_your_namespace_pod_request_memory_bytes |
```

```
| datasource_your_namespace_pod_usage_cpu_cores |
| datasource_your_namespace_pod_usage_memory_bytes |
+-----+
32 rows selected (13.101 seconds)
0: jdbc:hive2://127.0.0.1:10000/default>
```

7.2.4. Port-forward to the Hive web UI

Run the following command:

```
$ oc -n openshift-metering port-forward hive-server-0 10002
```

You can now open <http://127.0.0.1:10002> in your browser window to view the Hive web interface.

7.2.5. Port-forward to hdfs

To the namenode:

```
$ oc -n openshift-metering port-forward hdfs-namenode-0 9870
```

You can now open <http://127.0.0.1:9870> in your browser window to view the HDFS web interface.

To the first datanode:

```
$ oc -n openshift-metering port-forward hdfs-datanode-0 9864
```

To check other datanodes, run the above command, replacing **hdfs-datanode-0** with the Pod you want to view information on.

7.2.6. Metering Ansible Operator

Metering uses the Ansible Operator to watch and reconcile resources in a cluster environment. When debugging a failed metering installation, it can be helpful to view the Ansible logs or status of your MeteringConfig custom resource.

7.2.6.1. Accessing ansible logs

In the default installation, the metering Operator is deployed as a Pod. In this case, we can check the logs of the ansible container within this Pod:

```
$ oc -n openshift-metering logs $(oc -n openshift-metering get pods -l app=metering-operator -o
name | cut -d/ -f2) -c ansible
```

Alternatively, you can view the logs of the Operator container (replace **-c ansible** with **-c operator**) for condensed output.


7.2.6.2. Checking the MeteringConfig Status

It can be helpful to view the **.status** field of your MeteringConfig custom resource to debug any recent failures. The following command shows status messages with type **Invalid**:

```
$ oc -n openshift-metering get meteringconfig operator-metering -o=jsonpath='{.status.conditions[?(@.type=="Invalid")].message}'
```

CHAPTER 8. UNINSTALLING METERING

You can remove metering from your OpenShift Container Platform cluster.



NOTE

Metering does not manage or delete Amazon S3 bucket data. After uninstalling metering, you must manually clean up S3 buckets that were used to store metering data.

8.1. REMOVING THE METERING OPERATOR FROM YOUR CLUSTER

Remove the Metering Operator from your cluster by following the documentation on [deleting Operators from a cluster](#).



NOTE

Removing the Metering Operator from your cluster does not remove its CustomResourceDefinitions or managed resources. See the following sections on [Uninstalling a metering namespace](#) and [Uninstalling metering CustomResourceDefinitions](#) for steps to remove any remaining metering components.

8.2. UNINSTALLING A METERING NAMESPACE

Uninstall your metering namespace, for example the **openshift-metering** namespace, by removing the MeteringConfig resource and deleting the **openshift-metering** namespace.

Prerequisites

- The Metering Operator is removed from your cluster.

Procedure

1. Remove all resources created by the Metering Operator:

```
$ oc --namespace openshift-metering delete meteringconfig --all
```

2. After the previous step is complete, verify that all Pods in the **openshift-metering** namespace are deleted or are reporting a terminating state:


```
$ oc --namespace openshift-metering get pods
```

3. Delete the **openshift-metering** namespace:

```
$ oc delete namespace openshift-metering
```

8.3. UNINSTALLING METERING CUSTOMRESOURCEDEFINITIONS

The metering CustomResourceDefinitions (CRDs) remain in the cluster after the Metering Operator is uninstalled and the **openshift-metering** namespace is deleted.



IMPORTANT

Deleting the metering CRDs disrupts any additional metering installations in other namespaces in your cluster. Ensure that there are no other metering installations before proceeding.

Prerequisites

- The MeteringConfig custom resource in the **openshift-metering** namespace is deleted.
- The **openshift-metering** namespace is deleted.

Procedure

- Delete the remaining metering CRDs:

```
$ oc get crd -o name | grep "metering.openshift.io" | xargs oc delete
```