



# .NET 7.0

## Getting started with .NET on RHEL 9

Installing and running .NET 7.0 on RHEL 9



# .NET 7.0 Getting started with .NET on RHEL 9

---

Installing and running .NET 7.0 on RHEL 9

## Legal Notice

Copyright © 2022 Red Hat, Inc.

The text of and illustrations in this document are licensed by Red Hat under a Creative Commons Attribution–Share Alike 3.0 Unported license ("CC-BY-SA"). An explanation of CC-BY-SA is available at

<http://creativecommons.org/licenses/by-sa/3.0/>

. In accordance with CC-BY-SA, if you distribute this document or an adaptation of it, you must provide the URL for the original version.

Red Hat, as the licensor of this document, waives the right to enforce, and agrees not to assert, Section 4d of CC-BY-SA to the fullest extent permitted by applicable law.

Red Hat, Red Hat Enterprise Linux, the Shadowman logo, the Red Hat logo, JBoss, OpenShift, Fedora, the Infinity logo, and RHCE are trademarks of Red Hat, Inc., registered in the United States and other countries.

Linux<sup>®</sup> is the registered trademark of Linus Torvalds in the United States and other countries.

Java<sup>®</sup> is a registered trademark of Oracle and/or its affiliates.

XFS<sup>®</sup> is a trademark of Silicon Graphics International Corp. or its subsidiaries in the United States and/or other countries.

MySQL<sup>®</sup> is a registered trademark of MySQL AB in the United States, the European Union and other countries.

Node.js<sup>®</sup> is an official trademark of Joyent. Red Hat is not formally related to or endorsed by the official Joyent Node.js open source or commercial project.

The OpenStack<sup>®</sup> Word Mark and OpenStack logo are either registered trademarks/service marks or trademarks/service marks of the OpenStack Foundation, in the United States and other countries and are used with the OpenStack Foundation's permission. We are not affiliated with, endorsed or sponsored by the OpenStack Foundation, or the OpenStack community.

All other trademarks are the property of their respective owners.

## Abstract

This guide describes how to install and run .NET 7.0 on RHEL 9.

---

## Table of Contents

|   |           |
|---|-----------|
| <b>MAKING OPEN SOURCE MORE INCLUSIVE</b> .....                        | <b>3</b>  |
| <b>PROVIDING FEEDBACK ON RED HAT DOCUMENTATION</b> .....              | <b>4</b>  |
| <b>CHAPTER 1. INTRODUCING .NET 7.0</b> .....                          | <b>5</b>  |
| <b>CHAPTER 2. INSTALLING .NET 7.0</b> .....                           | <b>6</b>  |
| <b>CHAPTER 3. CREATING AN APPLICATION USING .NET 7.0</b> .....        | <b>7</b>  |
| <b>CHAPTER 4. PUBLISHING APPLICATIONS WITH .NET 7.0</b> .....         | <b>8</b>  |
| 4.1. PUBLISHING .NET APPLICATIONS                                     | 8         |
| <b>CHAPTER 5. RUNNING .NET 7.0 APPLICATIONS IN CONTAINERS</b> .....   | <b>10</b> |
| <b>CHAPTER 6. USING .NET 7.0 ON OPENSIFT CONTAINER PLATFORM</b> ..... | <b>11</b> |
| 6.1. OVERVIEW   | 11        |
| 6.2. INSTALLING .NET IMAGE STREAMS                                    | 11        |
| 6.2.1. Installing image streams using OpenShift Client                | 11        |
| 6.2.2. Installing image streams on Linux and macOS                    | 12        |
| 6.2.3. Installing image streams on Windows                            | 13        |
| 6.3. DEPLOYING APPLICATIONS FROM SOURCE USING OC                      | 13        |
| 6.4. DEPLOYING APPLICATIONS FROM BINARY ARTIFACTS USING OC            | 14        |
| 6.5. ENVIRONMENT VARIABLES FOR .NET 7.0                               | 14        |
| 6.6. CREATING THE MVC SAMPLE APPLICATION                              | 17        |
| 6.7. CREATING THE CRUD SAMPLE APPLICATION                             | 17        |



## MAKING OPEN SOURCE MORE INCLUSIVE

Red Hat is committed to replacing problematic language in our code, documentation, and web properties. We are beginning with these four terms: master, slave, blacklist, and whitelist. Because of the enormity of this endeavor, these changes will be implemented gradually over several upcoming releases. For more details, see [our CTO Chris Wright's message](#).

# PROVIDING FEEDBACK ON RED HAT DOCUMENTATION

We appreciate your feedback on our documentation. Let us know how we can improve it.

## Submitting comments on specific passages

1. View the documentation in the **Multi-page HTML** format and ensure that you see the **Feedback** button in the upper right corner after the page fully loads.
2. Use your cursor to highlight the part of the text that you want to comment on.
3. Click the **Add Feedback** button that appears near the highlighted text.
4. Add your feedback and click **Submit**.

## Submitting feedback through Bugzilla (account required)

1. Log in to the [Bugzilla](#) website.
2. Select the correct version from the **Version** menu.
3. Enter a descriptive title in the **Summary** field.
4. Enter your suggestion for improvement in the **Description** field. Include links to the relevant parts of the documentation.
5. Click **Submit Bug**.



## CHAPTER 1. INTRODUCING .NET 7.0

.NET is a general-purpose development platform featuring automatic memory management and modern programming languages. Using .NET, you can build high-quality applications efficiently. .NET is available on Red Hat Enterprise Linux (RHEL) and OpenShift Container Platform through certified containers.

.NET offers the following features:

- The ability to follow a microservices-based approach, where some components are built with .NET and others with Java, but all can run on a common, supported platform on RHEL and OpenShift Container Platform.
- The capacity to more easily develop new .NET workloads on Microsoft Windows. You can deploy and run your applications on either RHEL or Windows Server.
- A heterogeneous data center, where the underlying infrastructure is capable of running .NET applications without having to rely solely on Windows Server.

.NET 7.0 is supported on RHEL 8.7 and later, RHEL 9.1 and later, and supported OpenShift Container Platform versions.

For more information about the .NET support policy, see the [Life Cycle and Support Policies for the .NET Program](#). For more information about the Red Hat OpenShift Container Platform support policy, see the [Red Hat OpenShift Container Platform Life Cycle Policy](#) .

## CHAPTER 2. INSTALLING .NET 7.0

.NET 7.0 is included in the AppStream repositories for RHEL 9. The AppStream repositories are enabled by default on RHEL 9 systems.

You can install the .NET 7.0 runtime with the latest 7.0 Software Development Kit (SDK). When a newer SDK becomes available for .NET 7.0, you can install it by running **sudo yum install**.

### Prerequisites

- Installed and registered RHEL 9 with attached subscriptions.  
For more information, see [Performing a standard RHEL 9 installation](#).

### Procedure

- Install .NET 7.0 and all of its dependencies:

```
┆ $ sudo yum install dotnet-sdk-7.0 -y
```

### Verification steps

- Verify the installation:

```
┆ $ dotnet --info
```

The output returns the relevant information about the .NET installation and the environment.

## CHAPTER 3. CREATING AN APPLICATION USING .NET 7.0

Learn how to create a C# **hello-world** application.

### Procedure

1. Create a new Console application in a directory called **my-app**:

```
$ dotnet new console --output my-app
```

The output returns:

```
The template "Console Application" was created successfully.
```

```
Processing post-creation actions...
```

```
Running 'dotnet restore' on my-app/my-app.csproj...
```

```
  Determining projects to restore...
```

```
    Restored /home/username/my-app/my-app.csproj (in 67 ms).
```

```
Restore succeeded.
```

A simple **Hello World** console application is created from a template. The application is stored in the specified **my-app** directory.

### Verification steps

- Run the project:

```
$ dotnet run --project my-app
```

The output returns:

```
Hello World!
```

## CHAPTER 4. PUBLISHING APPLICATIONS WITH .NET 7.0

.NET 7.0 applications can be published to use a shared system-wide version of .NET or to include .NET.

The following methods exist for publishing .NET 7.0 applications:

- Single-file application - The application is self-contained and can be deployed as a single executable with all dependent files contained in a single binary.
- Framework-dependent deployment (FDD) - The application uses a shared system-wide version of .NET.



### NOTE

When publishing an application for RHEL, Red Hat recommends using FDD, because it ensures that the application is using an up-to-date version of .NET, built by Red Hat, that uses a set of native dependencies.

- Self-contained deployment (SCD) - The application includes .NET. This method uses a runtime built by Microsoft.



### NOTE

SCD is not available on IBM Z, IBM LinuxONE, and IBM Power.

### Prerequisites

- Existing .NET application.  
For more information on how to create a .NET application, see [Creating an application using .NET](#).

## 4.1. PUBLISHING .NET APPLICATIONS

The following procedure outlines how to publish a framework-dependent application.

### Procedure

1. Publish the framework-dependent application:

```
$ dotnet publish my-app -f net7.0 -c Release
```

Replace *my-app* with the name of the application you want to publish.

2. **Optional:** If the application is for RHEL only, trim out the dependencies needed for other platforms:

```
$ dotnet publish my-app -f net7.0 -c Release -r rhel.9-architecture --self-contained false
```

- Replace *architecture* based on the platform you are using:
  - For Intel: **x64**
  - For IBM Z and LinuxONE: **s390x**

- For 64-bit Arm: **arm64**
- For IBM Power: **ppc64le**

## CHAPTER 5. RUNNING .NET 7.0 APPLICATIONS IN CONTAINERS

Use the **ubi9-beta/dotnet-70-runtime** image to run a precompiled application inside a Linux container.

### Prerequisites

- Preconfigured containers.  
The following example uses podman.

### Procedure

1. **Optional:** If you are in another project's directory and do not wish to create a nested project, return to the parent directory of the project:

```
# cd ..
```

2. Create a new MVC project in a directory called **mvc\_runtime\_example**:

```
$ dotnet new mvc --output mvc_runtime_example
```

3. Publish the project:

```
$ dotnet publish mvc_runtime_example -f net7.0 -c Release
```

4. Create the **Dockerfile**:

```
$ cat > Dockerfile <<EOF  
FROM registry.access.redhat.com/ubi9-beta/dotnet-70-runtime  
  
ADD bin/Release/net7.0/publish/ .  
  
CMD ["dotnet", "mvc_runtime_example.dll"]  
EOF
```

5. Build your image:

```
$ podman build -t dotnet-70-runtime-example .
```

6. Run your image:

```
$ podman run -d -p8080:8080 dotnet-70-runtime-example
```

### Verification steps

- View the application running in the container:

```
$ xdg-open http://127.0.0.1:8080
```

# CHAPTER 6. USING .NET 7.0 ON OPENSIFT CONTAINER PLATFORM

## 6.1. OVERVIEW

NET images are added to OpenShift by importing imagestream definitions from [s2i-dotnetcore](#).

The imagestream definitions include the **dotnet** imagestream which contains sdk images for different supported versions of .NET. [Life Cycle and Support Policies for the .NET Program](#) provides an up-to-date overview of supported versions.

| Version       | Tag             | Alias      |
|---------------|-----------------|------------|
| .NET Core 3.1 | dotnet:3.1-el7  | dotnet:3.1 |
|               | dotnet:3.1-ubi8 |            |
| .NET 6        | dotnet:6.0-ubi8 | dotnet:6.0 |
| .NET 7        | dotnet:7.0-ubi8 | dotnet:7.0 |

The sdk images have corresponding runtime images which are defined under the **dotnet-runtime** imagestream.

The container images work across different versions of Red Hat Enterprise Linux and OpenShift.

The RHEL7-based (suffix `-el7`) are hosted on the [registry.redhat.io](#) image repository. Authentication is required to pull these images. These credentials are configured by adding a pull secret to the OpenShift namespace.

The UBI-8 based images (suffix `-ubi8`) are hosted on the [registry.access.redhat.com](#) and do not require authentication.

## 6.2. INSTALLING .NET IMAGE STREAMS

To install .NET image streams, use image stream definitions from [s2i-dotnetcore](#) with the OpenShift Client (**oc**) binary. Image streams can be installed from Linux, Mac, and Windows. A script enables you to install, update or remove the image streams.

You can define .NET image streams in the global **openshift** namespace or locally in a project namespace. Sufficient permissions are required to update the **openshift** namespace definitions.

### 6.2.1. Installing image streams using OpenShift Client

You can use OpenShift Client (**oc**) to install .NET image streams.

#### Prerequisites

- An existing pull secret must be present in the namespace. If no pull secret is present in the namespace. Add one by following the instructions in the [Red Hat Container Registry Authentication](#) guide.

### Procedure

1. List the available .NET image streams:

```
$ oc describe is dotnet
```

The output shows installed images. If no images are installed, the **Error from server (NotFound)** message is displayed.

- If the **Error from server (NotFound)** message is displayed:
  - Install the .NET image streams:

```
$ oc create -f https://raw.githubusercontent.com/redhat-developer/s2i-dotnetcore/master/dotnet_imagestreams.json
```

- If the **Error from server (NotFound)** message is **not** displayed:
  - Include newer versions of existing .NET image streams:

```
$ oc replace -f https://raw.githubusercontent.com/redhat-developer/s2i-dotnetcore/master/dotnet_imagestreams.json
```

## 6.2.2. Installing image streams on Linux and macOS

You can use [this script](#) to install, upgrade, or remove the image streams on Linux and macOS.

### Procedure

1. Download the script.

- a. On Linux use:

```
$ wget https://raw.githubusercontent.com/redhat-developer/s2i-dotnetcore/master/install-imagestreams.sh
```

- b. On Mac use:

```
$ curl https://raw.githubusercontent.com/redhat-developer/s2i-dotnetcore/master/install-imagestreams.sh -o install-imagestreams.sh
```

2. Make the script executable:

```
$ chmod +x install-imagestreams.sh
```

3. Log in to the OpenShift cluster:

```
$ oc login
```



4. Install image streams and add a pull secret for authentication against the **registry.redhat.io**: Replace *subscription\_username* with the name of the user, and replace *subscription\_password* with the user's password. The credentials may be omitted if you do not plan to use the RHEL7-based images.

If the pull secret is already present, the **--user** and **--password** arguments are ignored.

#### Additional information

- `./install-imagestreams.sh --help`

### 6.2.3. Installing image streams on Windows

You can use [this script](#) to install, upgrade, or remove the image streams on Windows.

#### Procedure

1. Download the script.

```
Invoke-WebRequest https://raw.githubusercontent.com/redhat-developer/s2i-dotnetcore/master/install-imagestreams.ps1 -UseBasicParsing -OutFile install-imagestreams.ps1
```

2. Log in to the OpenShift cluster:

```
$ oc login
```

3. Install image streams and add a pull secret for authentication against the **registry.redhat.io**: Replace *subscription\_username* with the name of the user, and replace *subscription\_password* with the user's password. The credentials may be omitted if you do not plan to use the RHEL7-based images.

If the pull secret is already present, the **-User** and **-Password** arguments are ignored.



#### NOTE

The PowerShell **ExecutionPolicy** may prohibit executing this script. To relax the policy, run **Set-ExecutionPolicy -Scope Process -ExecutionPolicy Bypass -Force**.

#### Additional information

- `Get-Help .\install-imagestreams.ps1`

## 6.3. DEPLOYING APPLICATIONS FROM SOURCE USING `oc`

The following example demonstrates how to deploy the *example-app* application using `oc`, which is in the **app** folder on the **dotnet-7.0** branch of the **redhat-developer/s2i-dotnetcore-ex** GitHub repository:

#### Procedure

1. Create a new OpenShift project:

```
$ oc new-project sample-project
```

2. Add the ASP.NET Core application:

```
$ oc new-app --name=example-app 'dotnet:7.0-ubi8~https://github.com/redhat-developer/s2i-dotnetcore-ex#dotnet-7.0' --build-env DOTNET_STARTUP_PROJECT=app
```

3. Track the progress of the build:

```
$ oc logs -f bc/example-app
```

4. View the deployed application once the build is finished:

```
$ oc logs -f dc/example-app
```

The application is now accessible within the project.

5. **Optional:** Make the project accessible externally:

```
$ oc expose svc/example-app
```

6. Obtain the shareable URL:

```
$ oc get routes
```

## 6.4. DEPLOYING APPLICATIONS FROM BINARY ARTIFACTS USING `oc`

You can use .NET Source-to-Image (S2I) builder image to build applications using binary artifacts that you provide.

### Prerequisites

1. A published application.  
For more information, see [Publishing applications with .NET 7.0](#).

### Procedure

1. Create a new binary build:

```
$ oc new-build --name=my-web-app dotnet:7.0-ubi8 --binary=true
```

2. Start the build and specify the path to the binary artifacts on your local machine:

```
$ oc start-build my-web-app --from-dir=bin/Release/net7.0/publish
```

3. Create a new application:

```
$ oc new-app my-web-app
```

## 6.5. ENVIRONMENT VARIABLES FOR .NET 7.0

The .NET images support several environment variables to control the build behavior of your .NET application. You can set these variables as part of the build configuration, or add them to the **.s2i/environment** file in the application source code repository.

| Variable Name                    | Description  | Default                            |
|----------------------------------|--|------------------------------------|
| <b>DOTNET_STARTUP_PROJECT</b>    | Selects the project to run. This must be a project file (for example, <b>csproj</b> or <b>fsproj</b> ) or a folder containing a single project file.   | .                                  |
| <b>DOTNET_ASSEMBLY_NAME</b>      | Selects the assembly to run. This must not include the <b>.dll</b> extension. Set this to the output assembly name specified in <b>csproj</b> (PropertyGroup/AssemblyName).  | The name of the <b>csproj</b> file |
| <b>DOTNET_PUBLISH_READYTORUN</b> | When set to <b>true</b> , the application will be compiled ahead of time. This reduces startup time by reducing the amount of work the JIT needs to perform when the application is loading.   | <b>false</b>                       |
| <b>DOTNET_RESTORE_SOURCES</b>    | Specifies the space-separated list of NuGet package sources used during the restore operation. This overrides all of the sources specified in the <b>NuGet.config</b> file. This variable cannot be combined with <b>DOTNET_RESTORE_CONFIGFILE</b> . |                                    |
| <b>DOTNET_RESTORE_CONFIGFILE</b> | Specifies a <b>NuGet.Config</b> file to be used for restore operations. This variable cannot be combined with <b>DOTNET_RESTORE_SOURCES</b> .  |                                    |
| <b>DOTNET_TOOLS</b>              | Specifies a list of .NET tools to install before building the app. It is possible to install a specific version by post pending the package name with <b>@&lt;version&gt;</b> .  |                                    |
| <b>DOTNET_NPM_TOOLS</b>          | Specifies a list of NPM packages to install before building the application.   |                                    |

| Variable Name                  | Description  | Default                                   |
|--------------------------------|--|---|
| <b>DOTNET_TEST_PROJECTS</b>    | Specifies the list of test projects to test. This must be project files or folders containing a single project file. <b>dotnet test</b> is invoked for each item.  |   |
| <b>DOTNET_CONFIGURATION</b>    | Runs the application in Debug or Release mode. This value should be either <b>Release</b> or <b>Debug</b> .  | <b>Release</b>                            |
| <b>DOTNET_VERBOSITY</b>        | Specifies the verbosity of the <b>dotnet build</b> commands. When set, the environment variables are printed at the start of the build. This variable can be set to one of the msbuild verbosity values ( <b>q[uiet]</b> , <b>m[inimal]</b> , <b>n[ormal]</b> , <b>d[etailed]</b> , and <b>diag[nostic]</b> ).   |   |
| <b>HTTP_PROXY, HTTPS_PROXY</b> | Configures the HTTP or HTTPS proxy used when building and running the application, respectively.   |   |
| <b>DOTNET_RM_SRC</b>           | When set to <b>true</b> , the source code will not be included in the image.   |   |
| <b>DOTNET_SSL_DIRS</b>         | Specifies a list of folders or files with additional SSL certificates to trust. The certificates are trusted by each process that runs during the build and all processes that run in the image after the build (including the application that was built). The items can be absolute paths (starting with /) or paths in the source repository (for example, certificates). |   |
| <b>NPM_MIRROR</b>              | Uses a custom NPM registry mirror to download packages during the build process.   |   |
| <b>ASPNETCORE_URLS</b>         | This variable is set to <a href="http://*:8080">http://*:8080</a> to configure ASP.NET Core to use the port exposed by the image. Changing this is not recommended.  | <a href="http://*:8080">http://*:8080</a> |

| Variable Name                          | Description  | Default      |
|--|--|--------------|
| <b>DOTNET_RESTORE_DISABLE_PARALLEL</b> | When set to <b>true</b> , disables restoring multiple projects in parallel. This reduces restore timeout errors when the build container is running with low CPU limits. | <b>false</b> |
| <b>DOTNET_INCREMENTAL</b>              | When set to <b>true</b> , the NuGet packages will be kept so they can be re-used for an incremental build.   | <b>false</b> |
| <b>DOTNET_PACK</b>                     | When set to <b>true</b> , creates a <b>tar.gz</b> file at <b>/opt/app-root/app.tar.gz</b> that contains the published application.                                       |              |

## 6.6. CREATING THE MVC SAMPLE APPLICATION

**s2i-dotnetcore-ex** is the default Model, View, Controller (MVC) template application for .NET.

This application is used as the example application by the .NET S2I image and can be created directly from the OpenShift UI using the *Try Example* link.

The application can also be created with the OpenShift client binary (**oc**).

### Procedure

To create the sample application using **oc**:

1. Add the .NET application:

```
$ oc new-app dotnet:7.0-ubi8~https://github.com/redhat-developer/s2i-dotnetcore-ex#dotnet-7.0 --context-dir=app
```

2. Make the application accessible externally:

```
$ oc expose service s2i-dotnetcore-ex
```

3. Obtain the sharable URL:

```
$ oc get route s2i-dotnetcore-ex
```

### Additional resources

- [s2i-dotnetcore-ex application repository on GitHub](#)

## 6.7. CREATING THE CRUD SAMPLE APPLICATION

**s2i-dotnetcore-persistent-ex** is a simple Create, Read, Update, Delete (CRUD) .NET web application that stores data in a PostgreSQL database.

## Procedure

To create the sample application using **oc**:

1. Add the database:

```
$ oc new-app postgresql-ephemeral
```

2. Add the .NET application:

```
$ oc new-app dotnet:7.0-ubi8~https://github.com/redhat-developer/s2i-dotnetcore-persistent-ex#dotnet-7.0 --context-dir app
```

3. Add environment variables from the **postgresql** secret and database service name environment variable:

```
$ oc set env dc/s2i-dotnetcore-persistent-ex --from=secret/postgresql -e database-service=postgresql
```

4. Make the application accessible externally:

```
$ oc expose service s2i-dotnetcore-persistent-ex
```

5. Obtain the sharable URL:

```
$ oc get route s2i-dotnetcore-persistent-ex
```

## Additional resources

- [s2i-dotnetcore-ex application repository on GitHub](#)