



OpenShift Container Platform 3.3

REST API Reference

OpenShift Container Platform 3.3 REST API for Developers

OpenShift Container Platform 3.3 REST API Reference

OpenShift Container Platform 3.3 REST API for Developers

Legal Notice

Copyright © 2019 Red Hat, Inc.

The text of and illustrations in this document are licensed by Red Hat under a Creative Commons Attribution–Share Alike 3.0 Unported license ("CC-BY-SA"). An explanation of CC-BY-SA is available at

<http://creativecommons.org/licenses/by-sa/3.0/>

. In accordance with CC-BY-SA, if you distribute this document or an adaptation of it, you must provide the URL for the original version.

Red Hat, as the licensor of this document, waives the right to enforce, and agrees not to assert, Section 4d of CC-BY-SA to the fullest extent permitted by applicable law.

Red Hat, Red Hat Enterprise Linux, the Shadowman logo, JBoss, OpenShift, Fedora, the Infinity logo, and RHCE are trademarks of Red Hat, Inc., registered in the United States and other countries.

Linux ® is the registered trademark of Linus Torvalds in the United States and other countries.

Java ® is a registered trademark of Oracle and/or its affiliates.

XFS ® is a trademark of Silicon Graphics International Corp. or its subsidiaries in the United States and/or other countries.

MySQL ® is a registered trademark of MySQL AB in the United States, the European Union and other countries.

Node.js ® is an official trademark of Joyent. Red Hat Software Collections is not formally related to or endorsed by the official Joyent Node.js open source or commercial project.

The OpenStack ® Word Mark and OpenStack logo are either registered trademarks/service marks or trademarks/service marks of the OpenStack Foundation, in the United States and other countries and are used with the OpenStack Foundation's permission. We are not affiliated with, endorsed or sponsored by the OpenStack Foundation, or the OpenStack community.

All other trademarks are the property of their respective owners.

Abstract

The OpenShift Container Platform 3.3 distribution of Kubernetes includes the Kubernetes v1 REST API and the OpenShift v1 REST API. These are RESTful APIs accessible via HTTP(s) on the OpenShift Container Platform master servers. These REST APIs can be used to manage end-user applications, the cluster, and the users of the cluster.

Table of Contents

CHAPTER 1. OVERVIEW	81
1.1. AUTHENTICATION	81
1.1.1. Session Tokens	81
1.1.2. Service Account Tokens	81
1.2. EXAMPLES	82
1.2.1. cURL	82
1.2.2. Python	83
1.2.3. Docker Login	84
1.3. WEBSOCKETS AND WATCHING FOR CHANGES	84
CHAPTER 2. OPENSIFT CONTAINER PLATFORM V1 REST API	85
2.1. OVERVIEW	85
2.1.1. Version information	85
2.1.2. URI scheme	85
2.2. PATHS	85
2.2.1. get available resources	85
2.2.1.1. Responses	85
2.2.1.2. Consumes	85
2.2.1.3. Produces	85
2.2.1.4. Tags	85
2.2.2. list objects of kind AppliedClusterResourceQuota	86
2.2.2.1. Parameters	86
2.2.2.2. Responses	87
2.2.2.3. Consumes	87
2.2.2.4. Produces	87
2.2.2.5. Tags	87
2.2.3. create a BuildConfig	87
2.2.3.1. Parameters	87
2.2.3.2. Responses	87
2.2.3.3. Consumes	88
2.2.3.4. Produces	88
2.2.3.5. Tags	88
2.2.4. list or watch objects of kind BuildConfig	88
2.2.4.1. Parameters	88
2.2.4.2. Responses	89
2.2.4.3. Consumes	89
2.2.4.4. Produces	89
2.2.4.5. Tags	90
2.2.5. create a Build	90
2.2.5.1. Parameters	90
2.2.5.2. Responses	90
2.2.5.3. Consumes	90
2.2.5.4. Produces	90
2.2.5.5. Tags	90
2.2.6. list or watch objects of kind Build	90
2.2.6.1. Parameters	90
2.2.6.2. Responses	91
2.2.6.3. Consumes	92
2.2.6.4. Produces	92
2.2.6.5. Tags	92
2.2.7. delete collection of ClusterNetwork	92

2.2.7.1. Parameters	92
2.2.7.2. Responses	93
2.2.7.3. Consumes	93
2.2.7.4. Produces	93
2.2.7.5. Tags	94
2.2.8. create a ClusterNetwork	94
2.2.8.1. Parameters	94
2.2.8.2. Responses	94
2.2.8.3. Consumes	94
2.2.8.4. Produces	94
2.2.8.5. Tags	94
2.2.9. list or watch objects of kind ClusterNetwork	94
2.2.9.1. Parameters	94
2.2.9.2. Responses	95
2.2.9.3. Consumes	96
2.2.9.4. Produces	96
2.2.9.5. Tags	96
2.2.10. delete a ClusterNetwork	96
2.2.10.1. Parameters	96
2.2.10.2. Responses	96
2.2.10.3. Consumes	97
2.2.10.4. Produces	97
2.2.10.5. Tags	97
2.2.11. partially update the specified ClusterNetwork	97
2.2.11.1. Parameters	97
2.2.11.2. Responses	97
2.2.11.3. Consumes	97
2.2.11.4. Produces	98
2.2.11.5. Tags	98
2.2.12. replace the specified ClusterNetwork	98
2.2.12.1. Parameters	98
2.2.12.2. Responses	98
2.2.12.3. Consumes	98
2.2.12.4. Produces	98
2.2.12.5. Tags	99
2.2.13. read the specified ClusterNetwork	99
2.2.13.1. Parameters	99
2.2.13.2. Responses	99
2.2.13.3. Consumes	99
2.2.13.4. Produces	99
2.2.13.5. Tags	100
2.2.14. delete collection of ClusterPolicy	100
2.2.14.1. Parameters	100
2.2.14.2. Responses	101
2.2.14.3. Consumes	101
2.2.14.4. Produces	101
2.2.14.5. Tags	101
2.2.15. create a ClusterPolicy	101
2.2.15.1. Parameters	101
2.2.15.2. Responses	102
2.2.15.3. Consumes	102
2.2.15.4. Produces	102
2.2.15.5. Tags	102

2.2.16. list or watch objects of kind ClusterPolicy	102
2.2.16.1. Parameters	102
2.2.16.2. Responses	103
2.2.16.3. Consumes	104
2.2.16.4. Produces	104
2.2.16.5. Tags	104
2.2.17. delete a ClusterPolicy	104
2.2.17.1. Parameters	104
2.2.17.2. Responses	104
2.2.17.3. Consumes	105
2.2.17.4. Produces	105
2.2.17.5. Tags	105
2.2.18. partially update the specified ClusterPolicy	105
2.2.18.1. Parameters	105
2.2.18.2. Responses	105
2.2.18.3. Consumes	105
2.2.18.4. Produces	106
2.2.18.5. Tags	106
2.2.19. replace the specified ClusterPolicy	106
2.2.19.1. Parameters	106
2.2.19.2. Responses	106
2.2.19.3. Consumes	106
2.2.19.4. Produces	106
2.2.19.5. Tags	107
2.2.20. read the specified ClusterPolicy	107
2.2.20.1. Parameters	107
2.2.20.2. Responses	107
2.2.20.3. Consumes	107
2.2.20.4. Produces	107
2.2.20.5. Tags	108
2.2.21. delete collection of ClusterPolicyBinding	108
2.2.21.1. Parameters	108
2.2.21.2. Responses	109
2.2.21.3. Consumes	109
2.2.21.4. Produces	109
2.2.21.5. Tags	109
2.2.22. create a ClusterPolicyBinding	109
2.2.22.1. Parameters	109
2.2.22.2. Responses	110
2.2.22.3. Consumes	110
2.2.22.4. Produces	110
2.2.22.5. Tags	110
2.2.23. list or watch objects of kind ClusterPolicyBinding	110
2.2.23.1. Parameters	110
2.2.23.2. Responses	111
2.2.23.3. Consumes	112
2.2.23.4. Produces	112
2.2.23.5. Tags	112
2.2.24. delete a ClusterPolicyBinding	112
2.2.24.1. Parameters	112
2.2.24.2. Responses	112
2.2.24.3. Consumes	113
2.2.24.4. Produces	113

2.2.24.5. Tags	113
2.2.25. partially update the specified ClusterPolicyBinding	113
2.2.25.1. Parameters	113
2.2.25.2. Responses	113
2.2.25.3. Consumes	113
2.2.25.4. Produces	114
2.2.25.5. Tags	114
2.2.26. replace the specified ClusterPolicyBinding	114
2.2.26.1. Parameters	114
2.2.26.2. Responses	114
2.2.26.3. Consumes	114
2.2.26.4. Produces	114
2.2.26.5. Tags	115
2.2.27. read the specified ClusterPolicyBinding	115
2.2.27.1. Parameters	115
2.2.27.2. Responses	115
2.2.27.3. Consumes	115
2.2.27.4. Produces	115
2.2.27.5. Tags	116
2.2.28. delete collection of ClusterResourceQuota	116
2.2.28.1. Parameters	116
2.2.28.2. Responses	117
2.2.28.3. Consumes	117
2.2.28.4. Produces	117
2.2.28.5. Tags	117
2.2.29. create a ClusterResourceQuota	117
2.2.29.1. Parameters	117
2.2.29.2. Responses	118
2.2.29.3. Consumes	118
2.2.29.4. Produces	118
2.2.29.5. Tags	118
2.2.30. list or watch objects of kind ClusterResourceQuota	118
2.2.30.1. Parameters	118
2.2.30.2. Responses	119
2.2.30.3. Consumes	120
2.2.30.4. Produces	120
2.2.30.5. Tags	120
2.2.31. delete a ClusterResourceQuota	120
2.2.31.1. Parameters	120
2.2.31.2. Responses	120
2.2.31.3. Consumes	121
2.2.31.4. Produces	121
2.2.31.5. Tags	121
2.2.32. partially update the specified ClusterResourceQuota	121
2.2.32.1. Parameters	121
2.2.32.2. Responses	121
2.2.32.3. Consumes	122
2.2.32.4. Produces	122
2.2.32.5. Tags	122
2.2.33. replace the specified ClusterResourceQuota	122
2.2.33.1. Parameters	122
2.2.33.2. Responses	122
2.2.33.3. Consumes	122

2.2.33.4. Produces	123
2.2.33.5. Tags	123
2.2.34. read the specified ClusterResourceQuota	123
2.2.34.1. Parameters	123
2.2.34.2. Responses	123
2.2.34.3. Consumes	124
2.2.34.4. Produces	124
2.2.34.5. Tags	124
2.2.35. partially update status of the specified ClusterResourceQuota	124
2.2.35.1. Parameters	124
2.2.35.2. Responses	124
2.2.35.3. Consumes	125
2.2.35.4. Produces	125
2.2.35.5. Tags	125
2.2.36. replace status of the specified ClusterResourceQuota	125
2.2.36.1. Parameters	125
2.2.36.2. Responses	125
2.2.36.3. Consumes	125
2.2.36.4. Produces	126
2.2.36.5. Tags	126
2.2.37. read status of the specified ClusterResourceQuota	126
2.2.37.1. Parameters	126
2.2.37.2. Responses	126
2.2.37.3. Consumes	126
2.2.37.4. Produces	126
2.2.37.5. Tags	126
2.2.38. create a ClusterRoleBinding	127
2.2.38.1. Parameters	127
2.2.38.2. Responses	127
2.2.38.3. Consumes	127
2.2.38.4. Produces	127
2.2.38.5. Tags	127
2.2.39. list objects of kind ClusterRoleBinding	127
2.2.39.1. Parameters	127
2.2.39.2. Responses	128
2.2.39.3. Consumes	129
2.2.39.4. Produces	129
2.2.39.5. Tags	129
2.2.40. delete a ClusterRoleBinding	129
2.2.40.1. Parameters	129
2.2.40.2. Responses	129
2.2.40.3. Consumes	130
2.2.40.4. Produces	130
2.2.40.5. Tags	130
2.2.41. partially update the specified ClusterRoleBinding	130
2.2.41.1. Parameters	130
2.2.41.2. Responses	130
2.2.41.3. Consumes	130
2.2.41.4. Produces	131
2.2.41.5. Tags	131
2.2.42. replace the specified ClusterRoleBinding	131
2.2.42.1. Parameters	131
2.2.42.2. Responses	131

2.2.42.3. Consumes	131
2.2.42.4. Produces	131
2.2.42.5. Tags	132
2.2.43. read the specified ClusterRoleBinding	132
2.2.43.1. Parameters	132
2.2.43.2. Responses	132
2.2.43.3. Consumes	132
2.2.43.4. Produces	132
2.2.43.5. Tags	132
2.2.44. create a ClusterRole	132
2.2.44.1. Parameters	132
2.2.44.2. Responses	133
2.2.44.3. Consumes	133
2.2.44.4. Produces	133
2.2.44.5. Tags	133
2.2.45. list objects of kind ClusterRole	133
2.2.45.1. Parameters	133
2.2.45.2. Responses	134
2.2.45.3. Consumes	135
2.2.45.4. Produces	135
2.2.45.5. Tags	135
2.2.46. delete a ClusterRole	135
2.2.46.1. Parameters	135
2.2.46.2. Responses	135
2.2.46.3. Consumes	135
2.2.46.4. Produces	135
2.2.46.5. Tags	136
2.2.47. partially update the specified ClusterRole	136
2.2.47.1. Parameters	136
2.2.47.2. Responses	136
2.2.47.3. Consumes	136
2.2.47.4. Produces	136
2.2.47.5. Tags	137
2.2.48. replace the specified ClusterRole	137
2.2.48.1. Parameters	137
2.2.48.2. Responses	137
2.2.48.3. Consumes	137
2.2.48.4. Produces	137
2.2.48.5. Tags	137
2.2.49. read the specified ClusterRole	137
2.2.49.1. Parameters	138
2.2.49.2. Responses	138
2.2.49.3. Consumes	138
2.2.49.4. Produces	138
2.2.49.5. Tags	138
2.2.50. create a DeploymentConfigRollback	138
2.2.50.1. Parameters	138
2.2.50.2. Responses	139
2.2.50.3. Consumes	139
2.2.50.4. Produces	139
2.2.50.5. Tags	139
2.2.51. create a DeploymentConfig	139
2.2.51.1. Parameters	139

2.2.51.2. Responses	139
2.2.51.3. Consumes	140
2.2.51.4. Produces	140
2.2.51.5. Tags	140
2.2.52. list or watch objects of kind DeploymentConfig	140
2.2.52.1. Parameters	140
2.2.52.2. Responses	141
2.2.52.3. Consumes	141
2.2.52.4. Produces	141
2.2.52.5. Tags	142
2.2.53. create a EgressNetworkPolicy	142
2.2.53.1. Parameters	142
2.2.53.2. Responses	142
2.2.53.3. Consumes	142
2.2.53.4. Produces	142
2.2.53.5. Tags	142
2.2.54. list or watch objects of kind EgressNetworkPolicy	142
2.2.54.1. Parameters	142
2.2.54.2. Responses	143
2.2.54.3. Consumes	144
2.2.54.4. Produces	144
2.2.54.5. Tags	144
2.2.55. delete collection of Group	144
2.2.55.1. Parameters	144
2.2.55.2. Responses	145
2.2.55.3. Consumes	145
2.2.55.4. Produces	145
2.2.55.5. Tags	146
2.2.56. create a Group	146
2.2.56.1. Parameters	146
2.2.56.2. Responses	146
2.2.56.3. Consumes	146
2.2.56.4. Produces	146
2.2.56.5. Tags	146
2.2.57. list or watch objects of kind Group	146
2.2.57.1. Parameters	146
2.2.57.2. Responses	147
2.2.57.3. Consumes	148
2.2.57.4. Produces	148
2.2.57.5. Tags	148
2.2.58. delete a Group	148
2.2.58.1. Parameters	148
2.2.58.2. Responses	148
2.2.58.3. Consumes	148
2.2.58.4. Produces	149
2.2.58.5. Tags	149
2.2.59. partially update the specified Group	149
2.2.59.1. Parameters	149
2.2.59.2. Responses	149
2.2.59.3. Consumes	149
2.2.59.4. Produces	149
2.2.59.5. Tags	150
2.2.60. replace the specified Group	150

2.2.60.1. Parameters	150
2.2.60.2. Responses	150
2.2.60.3. Consumes	150
2.2.60.4. Produces	150
2.2.60.5. Tags	150
2.2.61. read the specified Group	151
2.2.61.1. Parameters	151
2.2.61.2. Responses	151
2.2.61.3. Consumes	151
2.2.61.4. Produces	151
2.2.61.5. Tags	152
2.2.62. delete collection of HostSubnet	152
2.2.62.1. Parameters	152
2.2.62.2. Responses	153
2.2.62.3. Consumes	153
2.2.62.4. Produces	153
2.2.62.5. Tags	153
2.2.63. create a HostSubnet	153
2.2.63.1. Parameters	153
2.2.63.2. Responses	154
2.2.63.3. Consumes	154
2.2.63.4. Produces	154
2.2.63.5. Tags	154
2.2.64. list or watch objects of kind HostSubnet	154
2.2.64.1. Parameters	154
2.2.64.2. Responses	155
2.2.64.3. Consumes	156
2.2.64.4. Produces	156
2.2.64.5. Tags	156
2.2.65. delete a HostSubnet	156
2.2.65.1. Parameters	156
2.2.65.2. Responses	156
2.2.65.3. Consumes	157
2.2.65.4. Produces	157
2.2.65.5. Tags	157
2.2.66. partially update the specified HostSubnet	157
2.2.66.1. Parameters	157
2.2.66.2. Responses	157
2.2.66.3. Consumes	157
2.2.66.4. Produces	158
2.2.66.5. Tags	158
2.2.67. replace the specified HostSubnet	158
2.2.67.1. Parameters	158
2.2.67.2. Responses	158
2.2.67.3. Consumes	158
2.2.67.4. Produces	158
2.2.67.5. Tags	159
2.2.68. read the specified HostSubnet	159
2.2.68.1. Parameters	159
2.2.68.2. Responses	159
2.2.68.3. Consumes	159
2.2.68.4. Produces	159
2.2.68.5. Tags	160

2.2.69. delete collection of Identity	160
2.2.69.1. Parameters	160
2.2.69.2. Responses	161
2.2.69.3. Consumes	161
2.2.69.4. Produces	161
2.2.69.5. Tags	161
2.2.70. create a Identity	161
2.2.70.1. Parameters	161
2.2.70.2. Responses	162
2.2.70.3. Consumes	162
2.2.70.4. Produces	162
2.2.70.5. Tags	162
2.2.71. list or watch objects of kind Identity	162
2.2.71.1. Parameters	162
2.2.71.2. Responses	163
2.2.71.3. Consumes	164
2.2.71.4. Produces	164
2.2.71.5. Tags	164
2.2.72. delete a Identity	164
2.2.72.1. Parameters	164
2.2.72.2. Responses	164
2.2.72.3. Consumes	164
2.2.72.4. Produces	164
2.2.72.5. Tags	165
2.2.73. partially update the specified Identity	165
2.2.73.1. Parameters	165
2.2.73.2. Responses	165
2.2.73.3. Consumes	165
2.2.73.4. Produces	165
2.2.73.5. Tags	166
2.2.74. replace the specified Identity	166
2.2.74.1. Parameters	166
2.2.74.2. Responses	166
2.2.74.3. Consumes	166
2.2.74.4. Produces	166
2.2.74.5. Tags	166
2.2.75. read the specified Identity	166
2.2.75.1. Parameters	167
2.2.75.2. Responses	167
2.2.75.3. Consumes	167
2.2.75.4. Produces	167
2.2.75.5. Tags	167
2.2.76. delete collection of Image	168
2.2.76.1. Parameters	168
2.2.76.2. Responses	169
2.2.76.3. Consumes	169
2.2.76.4. Produces	169
2.2.76.5. Tags	169
2.2.77. create a Image	169
2.2.77.1. Parameters	169
2.2.77.2. Responses	169
2.2.77.3. Consumes	170
2.2.77.4. Produces	170

2.2.77.5. Tags	170
2.2.78. list or watch objects of kind Image	170
2.2.78.1. Parameters	170
2.2.78.2. Responses	171
2.2.78.3. Consumes	171
2.2.78.4. Produces	171
2.2.78.5. Tags	171
2.2.79. delete a Image	172
2.2.79.1. Parameters	172
2.2.79.2. Responses	172
2.2.79.3. Consumes	172
2.2.79.4. Produces	172
2.2.79.5. Tags	172
2.2.80. partially update the specified Image	172
2.2.80.1. Parameters	173
2.2.80.2. Responses	173
2.2.80.3. Consumes	173
2.2.80.4. Produces	173
2.2.80.5. Tags	173
2.2.81. replace the specified Image	173
2.2.81.1. Parameters	173
2.2.81.2. Responses	174
2.2.81.3. Consumes	174
2.2.81.4. Produces	174
2.2.81.5. Tags	174
2.2.82. read the specified Image	174
2.2.82.1. Parameters	174
2.2.82.2. Responses	175
2.2.82.3. Consumes	175
2.2.82.4. Produces	175
2.2.82.5. Tags	175
2.2.83. create a ImageSignature	175
2.2.83.1. Parameters	176
2.2.83.2. Responses	176
2.2.83.3. Consumes	176
2.2.83.4. Produces	176
2.2.83.5. Tags	176
2.2.84. delete a ImageSignature	176
2.2.84.1. Parameters	176
2.2.84.2. Responses	177
2.2.84.3. Consumes	177
2.2.84.4. Produces	177
2.2.84.5. Tags	177
2.2.85. create a ImageStreamImport	177
2.2.85.1. Parameters	177
2.2.85.2. Responses	178
2.2.85.3. Consumes	178
2.2.85.4. Produces	178
2.2.85.5. Tags	178
2.2.86. create a ImageStreamMapping	178
2.2.86.1. Parameters	178
2.2.86.2. Responses	178
2.2.86.3. Consumes	178

2.2.86.4. Produces	179
2.2.86.5. Tags	179
2.2.87. create a ImageStream	179
2.2.87.1. Parameters	179
2.2.87.2. Responses	179
2.2.87.3. Consumes	179
2.2.87.4. Produces	179
2.2.87.5. Tags	180
2.2.88. list or watch objects of kind ImageStream	180
2.2.88.1. Parameters	180
2.2.88.2. Responses	181
2.2.88.3. Consumes	181
2.2.88.4. Produces	181
2.2.88.5. Tags	181
2.2.89. create a ImageStreamTag	181
2.2.89.1. Parameters	181
2.2.89.2. Responses	182
2.2.89.3. Consumes	182
2.2.89.4. Produces	182
2.2.89.5. Tags	182
2.2.90. list objects of kind ImageStreamTag	182
2.2.90.1. Parameters	182
2.2.90.2. Responses	183
2.2.90.3. Consumes	184
2.2.90.4. Produces	184
2.2.90.5. Tags	184
2.2.91. create a LocalResourceAccessReview	184
2.2.91.1. Parameters	184
2.2.91.2. Responses	184
2.2.91.3. Consumes	184
2.2.91.4. Produces	185
2.2.91.5. Tags	185
2.2.92. create a LocalSubjectAccessReview	185
2.2.92.1. Parameters	185
2.2.92.2. Responses	185
2.2.92.3. Consumes	185
2.2.92.4. Produces	185
2.2.92.5. Tags	186
2.2.93. list objects of kind AppliedClusterResourceQuota	186
2.2.93.1. Parameters	186
2.2.93.2. Responses	187
2.2.93.3. Consumes	187
2.2.93.4. Produces	187
2.2.93.5. Tags	187
2.2.94. read the specified AppliedClusterResourceQuota	188
2.2.94.1. Parameters	188
2.2.94.2. Responses	188
2.2.94.3. Consumes	188
2.2.94.4. Produces	188
2.2.94.5. Tags	188
2.2.95. delete collection of BuildConfig	188
2.2.95.1. Parameters	189
2.2.95.2. Responses	190

2.2.95.3. Consumes	190
2.2.95.4. Produces	190
2.2.95.5. Tags	190
2.2.96. create a BuildConfig	190
2.2.96.1. Parameters	190
2.2.96.2. Responses	191
2.2.96.3. Consumes	191
2.2.96.4. Produces	191
2.2.96.5. Tags	191
2.2.97. list or watch objects of kind BuildConfig	191
2.2.97.1. Parameters	191
2.2.97.2. Responses	192
2.2.97.3. Consumes	193
2.2.97.4. Produces	193
2.2.97.5. Tags	193
2.2.98. delete a BuildConfig	193
2.2.98.1. Parameters	193
2.2.98.2. Responses	193
2.2.98.3. Consumes	194
2.2.98.4. Produces	194
2.2.98.5. Tags	194
2.2.99. partially update the specified BuildConfig	194
2.2.99.1. Parameters	194
2.2.99.2. Responses	194
2.2.99.3. Consumes	195
2.2.99.4. Produces	195
2.2.99.5. Tags	195
2.2.100. replace the specified BuildConfig	195
2.2.100.1. Parameters	195
2.2.100.2. Responses	196
2.2.100.3. Consumes	196
2.2.100.4. Produces	196
2.2.100.5. Tags	196
2.2.101. read the specified BuildConfig	196
2.2.101.1. Parameters	196
2.2.101.2. Responses	197
2.2.101.3. Consumes	197
2.2.101.4. Produces	197
2.2.101.5. Tags	197
2.2.102. create instantiate of a BuildRequest	197
2.2.102.1. Parameters	197
2.2.102.2. Responses	198
2.2.102.3. Consumes	198
2.2.102.4. Produces	198
2.2.102.5. Tags	198
2.2.103. connect POST requests to instantiatebinary of BinaryBuildRequestOptions	198
2.2.103.1. Parameters	198
2.2.103.2. Responses	200
2.2.103.3. Consumes	200
2.2.103.4. Produces	200
2.2.103.5. Tags	200
2.2.104. connect POST requests to webhooks of Status	200
2.2.104.1. Parameters	200

2.2.104.2. Responses	201
2.2.104.3. Consumes	201
2.2.104.4. Produces	201
2.2.104.5. Tags	201
2.2.105. connect POST requests to webhooks of Status	201
2.2.105.1. Parameters	201
2.2.105.2. Responses	201
2.2.105.3. Consumes	202
2.2.105.4. Produces	202
2.2.105.5. Tags	202
2.2.106. delete collection of Build	202
2.2.106.1. Parameters	202
2.2.106.2. Responses	203
2.2.106.3. Consumes	203
2.2.106.4. Produces	203
2.2.106.5. Tags	204
2.2.107. create a Build	204
2.2.107.1. Parameters	204
2.2.107.2. Responses	204
2.2.107.3. Consumes	204
2.2.107.4. Produces	204
2.2.107.5. Tags	205
2.2.108. list or watch objects of kind Build	205
2.2.108.1. Parameters	205
2.2.108.2. Responses	206
2.2.108.3. Consumes	206
2.2.108.4. Produces	206
2.2.108.5. Tags	206
2.2.109. delete a Build	206
2.2.109.1. Parameters	207
2.2.109.2. Responses	207
2.2.109.3. Consumes	207
2.2.109.4. Produces	207
2.2.109.5. Tags	207
2.2.110. partially update the specified Build	207
2.2.110.1. Parameters	208
2.2.110.2. Responses	208
2.2.110.3. Consumes	208
2.2.110.4. Produces	208
2.2.110.5. Tags	208
2.2.111. replace the specified Build	208
2.2.111.1. Parameters	209
2.2.111.2. Responses	209
2.2.111.3. Consumes	209
2.2.111.4. Produces	209
2.2.111.5. Tags	209
2.2.112. read the specified Build	209
2.2.112.1. Parameters	209
2.2.112.2. Responses	210
2.2.112.3. Consumes	210
2.2.112.4. Produces	210
2.2.112.5. Tags	211
2.2.113. create clone of a BuildRequest	211

2.2.113.1. Parameters	211
2.2.113.2. Responses	211
2.2.113.3. Consumes	211
2.2.113.4. Produces	211
2.2.113.5. Tags	211
2.2.114. replace details of the specified Build	212
2.2.114.1. Parameters	212
2.2.114.2. Responses	212
2.2.114.3. Consumes	212
2.2.114.4. Produces	212
2.2.114.5. Tags	212
2.2.115. read log of the specified BuildLog	212
2.2.115.1. Parameters	213
2.2.115.2. Responses	216
2.2.115.3. Consumes	216
2.2.115.4. Produces	216
2.2.115.5. Tags	216
2.2.116. create a DeploymentConfigRollback	216
2.2.116.1. Parameters	217
2.2.116.2. Responses	217
2.2.116.3. Consumes	217
2.2.116.4. Produces	217
2.2.116.5. Tags	217
2.2.117. delete collection of DeploymentConfig	217
2.2.117.1. Parameters	218
2.2.117.2. Responses	219
2.2.117.3. Consumes	219
2.2.117.4. Produces	219
2.2.117.5. Tags	219
2.2.118. create a DeploymentConfig	219
2.2.118.1. Parameters	219
2.2.118.2. Responses	220
2.2.118.3. Consumes	220
2.2.118.4. Produces	220
2.2.118.5. Tags	220
2.2.119. list or watch objects of kind DeploymentConfig	220
2.2.119.1. Parameters	220
2.2.119.2. Responses	221
2.2.119.3. Consumes	222
2.2.119.4. Produces	222
2.2.119.5. Tags	222
2.2.120. delete a DeploymentConfig	222
2.2.120.1. Parameters	222
2.2.120.2. Responses	222
2.2.120.3. Consumes	223
2.2.120.4. Produces	223
2.2.120.5. Tags	223
2.2.121. partially update the specified DeploymentConfig	223
2.2.121.1. Parameters	223
2.2.121.2. Responses	223
2.2.121.3. Consumes	224
2.2.121.4. Produces	224
2.2.121.5. Tags	224

2.2.122. replace the specified DeploymentConfig	224
2.2.122.1. Parameters	224
2.2.122.2. Responses	225
2.2.122.3. Consumes	225
2.2.122.4. Produces	225
2.2.122.5. Tags	225
2.2.123. read the specified DeploymentConfig	225
2.2.123.1. Parameters	225
2.2.123.2. Responses	226
2.2.123.3. Consumes	226
2.2.123.4. Produces	226
2.2.123.5. Tags	226
2.2.124. read log of the specified DeploymentLog	226
2.2.124.1. Parameters	226
2.2.124.2. Responses	229
2.2.124.3. Consumes	230
2.2.124.4. Produces	230
2.2.124.5. Tags	230
2.2.125. create rollback of a DeploymentConfigRollback	230
2.2.125.1. Parameters	230
2.2.125.2. Responses	230
2.2.125.3. Consumes	231
2.2.125.4. Produces	231
2.2.125.5. Tags	231
2.2.126. partially update scale of the specified Scale	231
2.2.126.1. Parameters	231
2.2.126.2. Responses	231
2.2.126.3. Consumes	232
2.2.126.4. Produces	232
2.2.126.5. Tags	232
2.2.127. replace scale of the specified Scale	232
2.2.127.1. Parameters	232
2.2.127.2. Responses	233
2.2.127.3. Consumes	233
2.2.127.4. Produces	233
2.2.127.5. Tags	233
2.2.128. read scale of the specified Scale	233
2.2.128.1. Parameters	233
2.2.128.2. Responses	233
2.2.128.3. Consumes	234
2.2.128.4. Produces	234
2.2.128.5. Tags	234
2.2.129. replace status of the specified DeploymentConfig	234
2.2.129.1. Parameters	234
2.2.129.2. Responses	234
2.2.129.3. Consumes	235
2.2.129.4. Produces	235
2.2.129.5. Tags	235
2.2.130. delete collection of EgressNetworkPolicy	235
2.2.130.1. Parameters	235
2.2.130.2. Responses	236
2.2.130.3. Consumes	236
2.2.130.4. Produces	236

2.2.130.5. Tags	237
2.2.131. create a EgressNetworkPolicy	237
2.2.131.1. Parameters	237
2.2.131.2. Responses	237
2.2.131.3. Consumes	237
2.2.131.4. Produces	237
2.2.131.5. Tags	238
2.2.132. list or watch objects of kind EgressNetworkPolicy	238
2.2.132.1. Parameters	238
2.2.132.2. Responses	239
2.2.132.3. Consumes	239
2.2.132.4. Produces	239
2.2.132.5. Tags	239
2.2.133. delete a EgressNetworkPolicy	239
2.2.133.1. Parameters	240
2.2.133.2. Responses	240
2.2.133.3. Consumes	240
2.2.133.4. Produces	240
2.2.133.5. Tags	240
2.2.134. partially update the specified EgressNetworkPolicy	240
2.2.134.1. Parameters	241
2.2.134.2. Responses	241
2.2.134.3. Consumes	241
2.2.134.4. Produces	241
2.2.134.5. Tags	241
2.2.135. replace the specified EgressNetworkPolicy	242
2.2.135.1. Parameters	242
2.2.135.2. Responses	242
2.2.135.3. Consumes	242
2.2.135.4. Produces	242
2.2.135.5. Tags	242
2.2.136. read the specified EgressNetworkPolicy	243
2.2.136.1. Parameters	243
2.2.136.2. Responses	243
2.2.136.3. Consumes	243
2.2.136.4. Produces	244
2.2.136.5. Tags	244
2.2.137. read the specified DeploymentConfig	244
2.2.137.1. Parameters	244
2.2.137.2. Responses	244
2.2.137.3. Consumes	244
2.2.137.4. Produces	244
2.2.137.5. Tags	245
2.2.138. read the specified ImageStreamImage	245
2.2.138.1. Parameters	245
2.2.138.2. Responses	245
2.2.138.3. Consumes	245
2.2.138.4. Produces	245
2.2.138.5. Tags	245
2.2.139. create a ImageStreamImport	246
2.2.139.1. Parameters	246
2.2.139.2. Responses	246
2.2.139.3. Consumes	246

2.2.139.4. Produces	246
2.2.139.5. Tags	246
2.2.140. create a ImageStreamMapping	246
2.2.140.1. Parameters	247
2.2.140.2. Responses	247
2.2.140.3. Consumes	247
2.2.140.4. Produces	247
2.2.140.5. Tags	247
2.2.141. delete collection of ImageStream	247
2.2.141.1. Parameters	248
2.2.141.2. Responses	249
2.2.141.3. Consumes	249
2.2.141.4. Produces	249
2.2.141.5. Tags	249
2.2.142. create a ImageStream	249
2.2.142.1. Parameters	249
2.2.142.2. Responses	250
2.2.142.3. Consumes	250
2.2.142.4. Produces	250
2.2.142.5. Tags	250
2.2.143. list or watch objects of kind ImageStream	250
2.2.143.1. Parameters	250
2.2.143.2. Responses	252
2.2.143.3. Consumes	252
2.2.143.4. Produces	252
2.2.143.5. Tags	252
2.2.144. delete a ImageStream	252
2.2.144.1. Parameters	252
2.2.144.2. Responses	252
2.2.144.3. Consumes	253
2.2.144.4. Produces	253
2.2.144.5. Tags	253
2.2.145. partially update the specified ImageStream	253
2.2.145.1. Parameters	253
2.2.145.2. Responses	253
2.2.145.3. Consumes	254
2.2.145.4. Produces	254
2.2.145.5. Tags	254
2.2.146. replace the specified ImageStream	254
2.2.146.1. Parameters	254
2.2.146.2. Responses	255
2.2.146.3. Consumes	255
2.2.146.4. Produces	255
2.2.146.5. Tags	255
2.2.147. read the specified ImageStream	255
2.2.147.1. Parameters	255
2.2.147.2. Responses	256
2.2.147.3. Consumes	256
2.2.147.4. Produces	256
2.2.147.5. Tags	256
2.2.148. read secrets of the specified SecretList	256
2.2.148.1. Parameters	256
2.2.148.2. Responses	258

2.2.148.3. Consumes	258
2.2.148.4. Produces	258
2.2.148.5. Tags	258
2.2.149. replace status of the specified ImageStream	258
2.2.149.1. Parameters	258
2.2.149.2. Responses	259
2.2.149.3. Consumes	259
2.2.149.4. Produces	259
2.2.149.5. Tags	259
2.2.150. create a ImageStreamTag	259
2.2.150.1. Parameters	259
2.2.150.2. Responses	260
2.2.150.3. Consumes	260
2.2.150.4. Produces	260
2.2.150.5. Tags	260
2.2.151. list objects of kind ImageStreamTag	260
2.2.151.1. Parameters	260
2.2.151.2. Responses	262
2.2.151.3. Consumes	262
2.2.151.4. Produces	262
2.2.151.5. Tags	262
2.2.152. delete a ImageStreamTag	262
2.2.152.1. Parameters	262
2.2.152.2. Responses	263
2.2.152.3. Consumes	263
2.2.152.4. Produces	263
2.2.152.5. Tags	263
2.2.153. partially update the specified ImageStreamTag	263
2.2.153.1. Parameters	263
2.2.153.2. Responses	264
2.2.153.3. Consumes	264
2.2.153.4. Produces	264
2.2.153.5. Tags	264
2.2.154. replace the specified ImageStreamTag	264
2.2.154.1. Parameters	264
2.2.154.2. Responses	265
2.2.154.3. Consumes	265
2.2.154.4. Produces	265
2.2.154.5. Tags	265
2.2.155. read the specified ImageStreamTag	265
2.2.155.1. Parameters	266
2.2.155.2. Responses	266
2.2.155.3. Consumes	266
2.2.155.4. Produces	266
2.2.155.5. Tags	266
2.2.156. create a LocalResourceAccessReview	266
2.2.156.1. Parameters	266
2.2.156.2. Responses	267
2.2.156.3. Consumes	267
2.2.156.4. Produces	267
2.2.156.5. Tags	267
2.2.157. create a LocalSubjectAccessReview	267
2.2.157.1. Parameters	267

2.2.157.2. Responses	268
2.2.157.3. Consumes	268
2.2.157.4. Produces	268
2.2.157.5. Tags	268
2.2.158. delete collection of Policy	268
2.2.158.1. Parameters	268
2.2.158.2. Responses	270
2.2.158.3. Consumes	270
2.2.158.4. Produces	270
2.2.158.5. Tags	270
2.2.159. create a Policy	270
2.2.159.1. Parameters	270
2.2.159.2. Responses	271
2.2.159.3. Consumes	271
2.2.159.4. Produces	271
2.2.159.5. Tags	271
2.2.160. list or watch objects of kind Policy	271
2.2.160.1. Parameters	271
2.2.160.2. Responses	272
2.2.160.3. Consumes	273
2.2.160.4. Produces	273
2.2.160.5. Tags	273
2.2.161. delete a Policy	273
2.2.161.1. Parameters	273
2.2.161.2. Responses	273
2.2.161.3. Consumes	274
2.2.161.4. Produces	274
2.2.161.5. Tags	274
2.2.162. partially update the specified Policy	274
2.2.162.1. Parameters	274
2.2.162.2. Responses	274
2.2.162.3. Consumes	275
2.2.162.4. Produces	275
2.2.162.5. Tags	275
2.2.163. replace the specified Policy	275
2.2.163.1. Parameters	275
2.2.163.2. Responses	275
2.2.163.3. Consumes	276
2.2.163.4. Produces	276
2.2.163.5. Tags	276
2.2.164. read the specified Policy	276
2.2.164.1. Parameters	276
2.2.164.2. Responses	277
2.2.164.3. Consumes	277
2.2.164.4. Produces	277
2.2.164.5. Tags	277
2.2.165. delete collection of PolicyBinding	277
2.2.165.1. Parameters	277
2.2.165.2. Responses	279
2.2.165.3. Consumes	279
2.2.165.4. Produces	279
2.2.165.5. Tags	279
2.2.166. create a PolicyBinding	279

2.2.166.1. Parameters	279
2.2.166.2. Responses	279
2.2.166.3. Consumes	280
2.2.166.4. Produces	280
2.2.166.5. Tags	280
2.2.167. list or watch objects of kind PolicyBinding	280
2.2.167.1. Parameters	280
2.2.167.2. Responses	281
2.2.167.3. Consumes	281
2.2.167.4. Produces	281
2.2.167.5. Tags	282
2.2.168. delete a PolicyBinding	282
2.2.168.1. Parameters	282
2.2.168.2. Responses	282
2.2.168.3. Consumes	282
2.2.168.4. Produces	282
2.2.168.5. Tags	283
2.2.169. partially update the specified PolicyBinding	283
2.2.169.1. Parameters	283
2.2.169.2. Responses	283
2.2.169.3. Consumes	283
2.2.169.4. Produces	283
2.2.169.5. Tags	284
2.2.170. replace the specified PolicyBinding	284
2.2.170.1. Parameters	284
2.2.170.2. Responses	284
2.2.170.3. Consumes	284
2.2.170.4. Produces	284
2.2.170.5. Tags	285
2.2.171. read the specified PolicyBinding	285
2.2.171.1. Parameters	285
2.2.171.2. Responses	285
2.2.171.3. Consumes	286
2.2.171.4. Produces	286
2.2.171.5. Tags	286
2.2.172. create a Template	286
2.2.172.1. Parameters	286
2.2.172.2. Responses	286
2.2.172.3. Consumes	287
2.2.172.4. Produces	287
2.2.172.5. Tags	287
2.2.173. create a ResourceAccessReview	287
2.2.173.1. Parameters	287
2.2.173.2. Responses	287
2.2.173.3. Consumes	287
2.2.173.4. Produces	288
2.2.173.5. Tags	288
2.2.174. create a RoleBinding	288
2.2.174.1. Parameters	288
2.2.174.2. Responses	288
2.2.174.3. Consumes	288
2.2.174.4. Produces	288
2.2.174.5. Tags	289

2.2.175. list objects of kind RoleBinding	289
2.2.175.1. Parameters	289
2.2.175.2. Responses	290
2.2.175.3. Consumes	290
2.2.175.4. Produces	290
2.2.175.5. Tags	290
2.2.176. delete a RoleBinding	290
2.2.176.1. Parameters	291
2.2.176.2. Responses	291
2.2.176.3. Consumes	291
2.2.176.4. Produces	291
2.2.176.5. Tags	291
2.2.177. partially update the specified RoleBinding	291
2.2.177.1. Parameters	292
2.2.177.2. Responses	292
2.2.177.3. Consumes	292
2.2.177.4. Produces	292
2.2.177.5. Tags	292
2.2.178. replace the specified RoleBinding	292
2.2.178.1. Parameters	293
2.2.178.2. Responses	293
2.2.178.3. Consumes	293
2.2.178.4. Produces	293
2.2.178.5. Tags	293
2.2.179. read the specified RoleBinding	293
2.2.179.1. Parameters	293
2.2.179.2. Responses	294
2.2.179.3. Consumes	294
2.2.179.4. Produces	294
2.2.179.5. Tags	294
2.2.180. create a Role	294
2.2.180.1. Parameters	294
2.2.180.2. Responses	295
2.2.180.3. Consumes	295
2.2.180.4. Produces	295
2.2.180.5. Tags	295
2.2.181. list objects of kind Role	295
2.2.181.1. Parameters	295
2.2.181.2. Responses	297
2.2.181.3. Consumes	297
2.2.181.4. Produces	297
2.2.181.5. Tags	297
2.2.182. delete a Role	297
2.2.182.1. Parameters	297
2.2.182.2. Responses	297
2.2.182.3. Consumes	298
2.2.182.4. Produces	298
2.2.182.5. Tags	298
2.2.183. partially update the specified Role	298
2.2.183.1. Parameters	298
2.2.183.2. Responses	298
2.2.183.3. Consumes	299
2.2.183.4. Produces	299

2.2.183.5. Tags	299
2.2.184. replace the specified Role	299
2.2.184.1. Parameters	299
2.2.184.2. Responses	299
2.2.184.3. Consumes	300
2.2.184.4. Produces	300
2.2.184.5. Tags	300
2.2.185. read the specified Role	300
2.2.185.1. Parameters	300
2.2.185.2. Responses	300
2.2.185.3. Consumes	301
2.2.185.4. Produces	301
2.2.185.5. Tags	301
2.2.186. delete collection of Route	301
2.2.186.1. Parameters	301
2.2.186.2. Responses	302
2.2.186.3. Consumes	302
2.2.186.4. Produces	302
2.2.186.5. Tags	303
2.2.187. create a Route	303
2.2.187.1. Parameters	303
2.2.187.2. Responses	303
2.2.187.3. Consumes	303
2.2.187.4. Produces	303
2.2.187.5. Tags	303
2.2.188. list or watch objects of kind Route	304
2.2.188.1. Parameters	304
2.2.188.2. Responses	305
2.2.188.3. Consumes	305
2.2.188.4. Produces	305
2.2.188.5. Tags	305
2.2.189. delete a Route	305
2.2.189.1. Parameters	306
2.2.189.2. Responses	306
2.2.189.3. Consumes	306
2.2.189.4. Produces	306
2.2.189.5. Tags	306
2.2.190. partially update the specified Route	306
2.2.190.1. Parameters	306
2.2.190.2. Responses	307
2.2.190.3. Consumes	307
2.2.190.4. Produces	307
2.2.190.5. Tags	307
2.2.191. replace the specified Route	307
2.2.191.1. Parameters	308
2.2.191.2. Responses	308
2.2.191.3. Consumes	308
2.2.191.4. Produces	308
2.2.191.5. Tags	308
2.2.192. read the specified Route	308
2.2.192.1. Parameters	308
2.2.192.2. Responses	309
2.2.192.3. Consumes	309

2.2.192.4. Produces	309
2.2.192.5. Tags	310
2.2.193. replace status of the specified Route	310
2.2.193.1. Parameters	310
2.2.193.2. Responses	310
2.2.193.3. Consumes	310
2.2.193.4. Produces	310
2.2.193.5. Tags	310
2.2.194. create a SelfSubjectRulesReview	311
2.2.194.1. Parameters	311
2.2.194.2. Responses	311
2.2.194.3. Consumes	311
2.2.194.4. Produces	311
2.2.194.5. Tags	311
2.2.195. create a SubjectAccessReview	311
2.2.195.1. Parameters	312
2.2.195.2. Responses	312
2.2.195.3. Consumes	312
2.2.195.4. Produces	312
2.2.195.5. Tags	312
2.2.196. delete collection of Template	312
2.2.196.1. Parameters	312
2.2.196.2. Responses	314
2.2.196.3. Consumes	314
2.2.196.4. Produces	314
2.2.196.5. Tags	314
2.2.197. create a Template	314
2.2.197.1. Parameters	314
2.2.197.2. Responses	315
2.2.197.3. Consumes	315
2.2.197.4. Produces	315
2.2.197.5. Tags	315
2.2.198. list or watch objects of kind Template	315
2.2.198.1. Parameters	315
2.2.198.2. Responses	316
2.2.198.3. Consumes	317
2.2.198.4. Produces	317
2.2.198.5. Tags	317
2.2.199. delete a Template	317
2.2.199.1. Parameters	317
2.2.199.2. Responses	317
2.2.199.3. Consumes	317
2.2.199.4. Produces	318
2.2.199.5. Tags	318
2.2.200. partially update the specified Template	318
2.2.200.1. Parameters	318
2.2.200.2. Responses	318
2.2.200.3. Consumes	318
2.2.200.4. Produces	319
2.2.200.5. Tags	319
2.2.201. replace the specified Template	319
2.2.201.1. Parameters	319
2.2.201.2. Responses	319

2.2.201.3. Consumes	319
2.2.201.4. Produces	320
2.2.201.5. Tags	320
2.2.202. read the specified Template	320
2.2.202.1. Parameters	320
2.2.202.2. Responses	321
2.2.202.3. Consumes	321
2.2.202.4. Produces	321
2.2.202.5. Tags	321
2.2.203. delete collection of NetNamespace	321
2.2.203.1. Parameters	321
2.2.203.2. Responses	322
2.2.203.3. Consumes	322
2.2.203.4. Produces	322
2.2.203.5. Tags	322
2.2.204. create a NetNamespace	323
2.2.204.1. Parameters	323
2.2.204.2. Responses	323
2.2.204.3. Consumes	323
2.2.204.4. Produces	323
2.2.204.5. Tags	323
2.2.205. list or watch objects of kind NetNamespace	323
2.2.205.1. Parameters	323
2.2.205.2. Responses	324
2.2.205.3. Consumes	325
2.2.205.4. Produces	325
2.2.205.5. Tags	325
2.2.206. delete a NetNamespace	325
2.2.206.1. Parameters	325
2.2.206.2. Responses	325
2.2.206.3. Consumes	326
2.2.206.4. Produces	326
2.2.206.5. Tags	326
2.2.207. partially update the specified NetNamespace	326
2.2.207.1. Parameters	326
2.2.207.2. Responses	326
2.2.207.3. Consumes	326
2.2.207.4. Produces	327
2.2.207.5. Tags	327
2.2.208. replace the specified NetNamespace	327
2.2.208.1. Parameters	327
2.2.208.2. Responses	327
2.2.208.3. Consumes	327
2.2.208.4. Produces	327
2.2.208.5. Tags	328
2.2.209. read the specified NetNamespace	328
2.2.209.1. Parameters	328
2.2.209.2. Responses	328
2.2.209.3. Consumes	328
2.2.209.4. Produces	329
2.2.209.5. Tags	329
2.2.210. delete collection of OAuthAccessToken	329
2.2.210.1. Parameters	329

2.2.210.2. Responses	330
2.2.210.3. Consumes	330
2.2.210.4. Produces	330
2.2.210.5. Tags	330
2.2.211. create a OAuthAccessToken	330
2.2.211.1. Parameters	330
2.2.211.2. Responses	331
2.2.211.3. Consumes	331
2.2.211.4. Produces	331
2.2.211.5. Tags	331
2.2.212. list or watch objects of kind OAuthAccessToken	331
2.2.212.1. Parameters	331
2.2.212.2. Responses	332
2.2.212.3. Consumes	333
2.2.212.4. Produces	333
2.2.212.5. Tags	333
2.2.213. delete a OAuthAccessToken	333
2.2.213.1. Parameters	333
2.2.213.2. Responses	333
2.2.213.3. Consumes	334
2.2.213.4. Produces	334
2.2.213.5. Tags	334
2.2.214. partially update the specified OAuthAccessToken	334
2.2.214.1. Parameters	334
2.2.214.2. Responses	334
2.2.214.3. Consumes	334
2.2.214.4. Produces	335
2.2.214.5. Tags	335
2.2.215. replace the specified OAuthAccessToken	335
2.2.215.1. Parameters	335
2.2.215.2. Responses	335
2.2.215.3. Consumes	335
2.2.215.4. Produces	335
2.2.215.5. Tags	336
2.2.216. read the specified OAuthAccessToken	336
2.2.216.1. Parameters	336
2.2.216.2. Responses	336
2.2.216.3. Consumes	336
2.2.216.4. Produces	337
2.2.216.5. Tags	337
2.2.217. delete collection of OAuthAuthorizeToken	337
2.2.217.1. Parameters	337
2.2.217.2. Responses	338
2.2.217.3. Consumes	338
2.2.217.4. Produces	338
2.2.217.5. Tags	338
2.2.218. create a OAuthAuthorizeToken	338
2.2.218.1. Parameters	338
2.2.218.2. Responses	339
2.2.218.3. Consumes	339
2.2.218.4. Produces	339
2.2.218.5. Tags	339
2.2.219. list or watch objects of kind OAuthAuthorizeToken	339

2.2.219.1. Parameters	339
2.2.219.2. Responses	340
2.2.219.3. Consumes	341
2.2.219.4. Produces	341
2.2.219.5. Tags	341
2.2.220. delete a OAuthAuthorizeToken	341
2.2.220.1. Parameters	341
2.2.220.2. Responses	341
2.2.220.3. Consumes	342
2.2.220.4. Produces	342
2.2.220.5. Tags	342
2.2.221. partially update the specified OAuthAuthorizeToken	342
2.2.221.1. Parameters	342
2.2.221.2. Responses	342
2.2.221.3. Consumes	342
2.2.221.4. Produces	343
2.2.221.5. Tags	343
2.2.222. replace the specified OAuthAuthorizeToken	343
2.2.222.1. Parameters	343
2.2.222.2. Responses	343
2.2.222.3. Consumes	343
2.2.222.4. Produces	343
2.2.222.5. Tags	344
2.2.223. read the specified OAuthAuthorizeToken	344
2.2.223.1. Parameters	344
2.2.223.2. Responses	344
2.2.223.3. Consumes	344
2.2.223.4. Produces	345
2.2.223.5. Tags	345
2.2.224. delete collection of OAuthClientAuthorization	345
2.2.224.1. Parameters	345
2.2.224.2. Responses	346
2.2.224.3. Consumes	346
2.2.224.4. Produces	346
2.2.224.5. Tags	346
2.2.225. create a OAuthClientAuthorization	346
2.2.225.1. Parameters	346
2.2.225.2. Responses	347
2.2.225.3. Consumes	347
2.2.225.4. Produces	347
2.2.225.5. Tags	347
2.2.226. list or watch objects of kind OAuthClientAuthorization	347
2.2.226.1. Parameters	347
2.2.226.2. Responses	348
2.2.226.3. Consumes	349
2.2.226.4. Produces	349
2.2.226.5. Tags	349
2.2.227. delete a OAuthClientAuthorization	349
2.2.227.1. Parameters	349
2.2.227.2. Responses	349
2.2.227.3. Consumes	350
2.2.227.4. Produces	350
2.2.227.5. Tags	350

2.2.228. partially update the specified OAuthClientAuthorization	350
2.2.228.1. Parameters	350
2.2.228.2. Responses	350
2.2.228.3. Consumes	351
2.2.228.4. Produces	351
2.2.228.5. Tags	351
2.2.229. replace the specified OAuthClientAuthorization	351
2.2.229.1. Parameters	351
2.2.229.2. Responses	351
2.2.229.3. Consumes	351
2.2.229.4. Produces	352
2.2.229.5. Tags	352
2.2.230. read the specified OAuthClientAuthorization	352
2.2.230.1. Parameters	352
2.2.230.2. Responses	352
2.2.230.3. Consumes	353
2.2.230.4. Produces	353
2.2.230.5. Tags	353
2.2.231. delete collection of OAuthClient	353
2.2.231.1. Parameters	353
2.2.231.2. Responses	354
2.2.231.3. Consumes	354
2.2.231.4. Produces	354
2.2.231.5. Tags	355
2.2.232. create a OAuthClient	355
2.2.232.1. Parameters	355
2.2.232.2. Responses	355
2.2.232.3. Consumes	355
2.2.232.4. Produces	355
2.2.232.5. Tags	355
2.2.233. list or watch objects of kind OAuthClient	355
2.2.233.1. Parameters	355
2.2.233.2. Responses	356
2.2.233.3. Consumes	357
2.2.233.4. Produces	357
2.2.233.5. Tags	357
2.2.234. delete a OAuthClient	357
2.2.234.1. Parameters	357
2.2.234.2. Responses	357
2.2.234.3. Consumes	358
2.2.234.4. Produces	358
2.2.234.5. Tags	358
2.2.235. partially update the specified OAuthClient	358
2.2.235.1. Parameters	358
2.2.235.2. Responses	358
2.2.235.3. Consumes	358
2.2.235.4. Produces	359
2.2.235.5. Tags	359
2.2.236. replace the specified OAuthClient	359
2.2.236.1. Parameters	359
2.2.236.2. Responses	359
2.2.236.3. Consumes	359
2.2.236.4. Produces	359

2.2.236.5. Tags	360
2.2.237. read the specified OAuthClient	360
2.2.237.1. Parameters	360
2.2.237.2. Responses	360
2.2.237.3. Consumes	360
2.2.237.4. Produces	360
2.2.237.5. Tags	361
2.2.238. create a Policy	361
2.2.238.1. Parameters	361
2.2.238.2. Responses	361
2.2.238.3. Consumes	361
2.2.238.4. Produces	361
2.2.238.5. Tags	361
2.2.239. list or watch objects of kind Policy	361
2.2.239.1. Parameters	362
2.2.239.2. Responses	362
2.2.239.3. Consumes	363
2.2.239.4. Produces	363
2.2.239.5. Tags	363
2.2.240. create a PolicyBinding	363
2.2.240.1. Parameters	363
2.2.240.2. Responses	363
2.2.240.3. Consumes	363
2.2.240.4. Produces	364
2.2.240.5. Tags	364
2.2.241. list or watch objects of kind PolicyBinding	364
2.2.241.1. Parameters	364
2.2.241.2. Responses	365
2.2.241.3. Consumes	365
2.2.241.4. Produces	365
2.2.241.5. Tags	365
2.2.242. create a Template	365
2.2.242.1. Parameters	365
2.2.242.2. Responses	366
2.2.242.3. Consumes	366
2.2.242.4. Produces	366
2.2.242.5. Tags	366
2.2.243. create a ProjectRequest	366
2.2.243.1. Parameters	366
2.2.243.2. Responses	367
2.2.243.3. Consumes	367
2.2.243.4. Produces	367
2.2.243.5. Tags	367
2.2.244. list objects of kind ProjectRequest	367
2.2.244.1. Parameters	367
2.2.244.2. Responses	368
2.2.244.3. Consumes	368
2.2.244.4. Produces	369
2.2.244.5. Tags	369
2.2.245. create a Project	369
2.2.245.1. Parameters	369
2.2.245.2. Responses	369
2.2.245.3. Consumes	369

2.2.245.4. Produces	369
2.2.245.5. Tags	369
2.2.246. list or watch objects of kind Project	370
2.2.246.1. Parameters	370
2.2.246.2. Responses	371
2.2.246.3. Consumes	371
2.2.246.4. Produces	371
2.2.246.5. Tags	371
2.2.247. delete a Project	371
2.2.247.1. Parameters	371
2.2.247.2. Responses	371
2.2.247.3. Consumes	372
2.2.247.4. Produces	372
2.2.247.5. Tags	372
2.2.248. partially update the specified Project	372
2.2.248.1. Parameters	372
2.2.248.2. Responses	372
2.2.248.3. Consumes	372
2.2.248.4. Produces	373
2.2.248.5. Tags	373
2.2.249. replace the specified Project	373
2.2.249.1. Parameters	373
2.2.249.2. Responses	373
2.2.249.3. Consumes	373
2.2.249.4. Produces	373
2.2.249.5. Tags	374
2.2.250. read the specified Project	374
2.2.250.1. Parameters	374
2.2.250.2. Responses	374
2.2.250.3. Consumes	374
2.2.250.4. Produces	374
2.2.250.5. Tags	374
2.2.251. create a ResourceAccessReview	374
2.2.251.1. Parameters	375
2.2.251.2. Responses	375
2.2.251.3. Consumes	375
2.2.251.4. Produces	375
2.2.251.5. Tags	375
2.2.252. create a RoleBinding	375
2.2.252.1. Parameters	375
2.2.252.2. Responses	376
2.2.252.3. Consumes	376
2.2.252.4. Produces	376
2.2.252.5. Tags	376
2.2.253. list objects of kind RoleBinding	376
2.2.253.1. Parameters	376
2.2.253.2. Responses	377
2.2.253.3. Consumes	378
2.2.253.4. Produces	378
2.2.253.5. Tags	378
2.2.254. create a Role	378
2.2.254.1. Parameters	378
2.2.254.2. Responses	378

2.2.254.3. Consumes	378
2.2.254.4. Produces	378
2.2.254.5. Tags	379
2.2.255. list objects of kind Role	379
2.2.255.1. Parameters	379
2.2.255.2. Responses	380
2.2.255.3. Consumes	380
2.2.255.4. Produces	380
2.2.255.5. Tags	380
2.2.256. create a Route	380
2.2.256.1. Parameters	380
2.2.256.2. Responses	381
2.2.256.3. Consumes	381
2.2.256.4. Produces	381
2.2.256.5. Tags	381
2.2.257. list or watch objects of kind Route	381
2.2.257.1. Parameters	381
2.2.257.2. Responses	382
2.2.257.3. Consumes	383
2.2.257.4. Produces	383
2.2.257.5. Tags	383
2.2.258. create a SelfSubjectRulesReview	383
2.2.258.1. Parameters	383
2.2.258.2. Responses	383
2.2.258.3. Consumes	383
2.2.258.4. Produces	383
2.2.258.5. Tags	384
2.2.259. create a SubjectAccessReview	384
2.2.259.1. Parameters	384
2.2.259.2. Responses	384
2.2.259.3. Consumes	384
2.2.259.4. Produces	384
2.2.259.5. Tags	384
2.2.260. create a Template	384
2.2.260.1. Parameters	385
2.2.260.2. Responses	385
2.2.260.3. Consumes	385
2.2.260.4. Produces	385
2.2.260.5. Tags	385
2.2.261. list or watch objects of kind Template	385
2.2.261.1. Parameters	385
2.2.261.2. Responses	386
2.2.261.3. Consumes	387
2.2.261.4. Produces	387
2.2.261.5. Tags	387
2.2.262. create a UserIdentityMapping	387
2.2.262.1. Parameters	387
2.2.262.2. Responses	387
2.2.262.3. Consumes	387
2.2.262.4. Produces	387
2.2.262.5. Tags	388
2.2.263. delete a UserIdentityMapping	388
2.2.263.1. Parameters	388

2.2.263.2. Responses	388
2.2.263.3. Consumes	388
2.2.263.4. Produces	388
2.2.263.5. Tags	388
2.2.264. partially update the specified UserIdentityMapping	388
2.2.264.1. Parameters	389
2.2.264.2. Responses	389
2.2.264.3. Consumes	389
2.2.264.4. Produces	389
2.2.264.5. Tags	389
2.2.265. replace the specified UserIdentityMapping	389
2.2.265.1. Parameters	389
2.2.265.2. Responses	390
2.2.265.3. Consumes	390
2.2.265.4. Produces	390
2.2.265.5. Tags	390
2.2.266. read the specified UserIdentityMapping	390
2.2.266.1. Parameters	390
2.2.266.2. Responses	391
2.2.266.3. Consumes	391
2.2.266.4. Produces	391
2.2.266.5. Tags	391
2.2.267. delete collection of User	391
2.2.267.1. Parameters	391
2.2.267.2. Responses	392
2.2.267.3. Consumes	393
2.2.267.4. Produces	393
2.2.267.5. Tags	393
2.2.268. create a User	393
2.2.268.1. Parameters	393
2.2.268.2. Responses	393
2.2.268.3. Consumes	393
2.2.268.4. Produces	394
2.2.268.5. Tags	394
2.2.269. list or watch objects of kind User	394
2.2.269.1. Parameters	394
2.2.269.2. Responses	395
2.2.269.3. Consumes	395
2.2.269.4. Produces	395
2.2.269.5. Tags	395
2.2.270. delete a User	395
2.2.270.1. Parameters	395
2.2.270.2. Responses	396
2.2.270.3. Consumes	396
2.2.270.4. Produces	396
2.2.270.5. Tags	396
2.2.271. partially update the specified User	396
2.2.271.1. Parameters	396
2.2.271.2. Responses	397
2.2.271.3. Consumes	397
2.2.271.4. Produces	397
2.2.271.5. Tags	397
2.2.272. replace the specified User	397

2.2.272.1. Parameters	397
2.2.272.2. Responses	398
2.2.272.3. Consumes	398
2.2.272.4. Produces	398
2.2.272.5. Tags	398
2.2.273. read the specified User	398
2.2.273.1. Parameters	398
2.2.273.2. Responses	399
2.2.273.3. Consumes	399
2.2.273.4. Produces	399
2.2.273.5. Tags	399
2.2.274. watch individual changes to a list of BuildConfig	399
2.2.274.1. Parameters	399
2.2.274.2. Responses	400
2.2.274.3. Consumes	401
2.2.274.4. Produces	401
2.2.274.5. Tags	401
2.2.275. watch individual changes to a list of Build	401
2.2.275.1. Parameters	401
2.2.275.2. Responses	402
2.2.275.3. Consumes	402
2.2.275.4. Produces	402
2.2.275.5. Tags	403
2.2.276. watch individual changes to a list of ClusterNetwork	403
2.2.276.1. Parameters	403
2.2.276.2. Responses	404
2.2.276.3. Consumes	404
2.2.276.4. Produces	404
2.2.276.5. Tags	404
2.2.277. watch changes to an object of kind ClusterNetwork	404
2.2.277.1. Parameters	404
2.2.277.2. Responses	406
2.2.277.3. Consumes	406
2.2.277.4. Produces	406
2.2.277.5. Tags	406
2.2.278. watch individual changes to a list of ClusterPolicy	406
2.2.278.1. Parameters	406
2.2.278.2. Responses	407
2.2.278.3. Consumes	407
2.2.278.4. Produces	407
2.2.278.5. Tags	408
2.2.279. watch changes to an object of kind ClusterPolicy	408
2.2.279.1. Parameters	408
2.2.279.2. Responses	409
2.2.279.3. Consumes	409
2.2.279.4. Produces	409
2.2.279.5. Tags	409
2.2.280. watch individual changes to a list of ClusterPolicyBinding	409
2.2.280.1. Parameters	410
2.2.280.2. Responses	410
2.2.280.3. Consumes	411
2.2.280.4. Produces	411
2.2.280.5. Tags	411

2.2.281. watch changes to an object of kind ClusterPolicyBinding	411
2.2.281.1. Parameters	411
2.2.281.2. Responses	412
2.2.281.3. Consumes	412
2.2.281.4. Produces	412
2.2.281.5. Tags	413
2.2.282. watch individual changes to a list of ClusterResourceQuota	413
2.2.282.1. Parameters	413
2.2.282.2. Responses	414
2.2.282.3. Consumes	414
2.2.282.4. Produces	414
2.2.282.5. Tags	414
2.2.283. watch changes to an object of kind ClusterResourceQuota	414
2.2.283.1. Parameters	414
2.2.283.2. Responses	416
2.2.283.3. Consumes	416
2.2.283.4. Produces	416
2.2.283.5. Tags	416
2.2.284. watch individual changes to a list of DeploymentConfig	416
2.2.284.1. Parameters	416
2.2.284.2. Responses	417
2.2.284.3. Consumes	417
2.2.284.4. Produces	417
2.2.284.5. Tags	418
2.2.285. watch individual changes to a list of EgressNetworkPolicy	418
2.2.285.1. Parameters	418
2.2.285.2. Responses	419
2.2.285.3. Consumes	419
2.2.285.4. Produces	419
2.2.285.5. Tags	419
2.2.286. watch individual changes to a list of Group	419
2.2.286.1. Parameters	419
2.2.286.2. Responses	420
2.2.286.3. Consumes	421
2.2.286.4. Produces	421
2.2.286.5. Tags	421
2.2.287. watch changes to an object of kind Group	421
2.2.287.1. Parameters	421
2.2.287.2. Responses	422
2.2.287.3. Consumes	422
2.2.287.4. Produces	422
2.2.287.5. Tags	423
2.2.288. watch individual changes to a list of HostSubnet	423
2.2.288.1. Parameters	423
2.2.288.2. Responses	424
2.2.288.3. Consumes	424
2.2.288.4. Produces	424
2.2.288.5. Tags	424
2.2.289. watch changes to an object of kind HostSubnet	424
2.2.289.1. Parameters	424
2.2.289.2. Responses	426
2.2.289.3. Consumes	426
2.2.289.4. Produces	426

2.2.289.5. Tags	426
2.2.290. watch individual changes to a list of Identity	426
2.2.290.1. Parameters	426
2.2.290.2. Responses	427
2.2.290.3. Consumes	427
2.2.290.4. Produces	427
2.2.290.5. Tags	428
2.2.291. watch changes to an object of kind Identity	428
2.2.291.1. Parameters	428
2.2.291.2. Responses	429
2.2.291.3. Consumes	429
2.2.291.4. Produces	429
2.2.291.5. Tags	429
2.2.292. watch individual changes to a list of Image	429
2.2.292.1. Parameters	430
2.2.292.2. Responses	430
2.2.292.3. Consumes	431
2.2.292.4. Produces	431
2.2.292.5. Tags	431
2.2.293. watch changes to an object of kind Image	431
2.2.293.1. Parameters	431
2.2.293.2. Responses	432
2.2.293.3. Consumes	432
2.2.293.4. Produces	432
2.2.293.5. Tags	433
2.2.294. watch individual changes to a list of ImageStream	433
2.2.294.1. Parameters	433
2.2.294.2. Responses	434
2.2.294.3. Consumes	434
2.2.294.4. Produces	434
2.2.294.5. Tags	434
2.2.295. watch individual changes to a list of BuildConfig	434
2.2.295.1. Parameters	434
2.2.295.2. Responses	436
2.2.295.3. Consumes	436
2.2.295.4. Produces	436
2.2.295.5. Tags	436
2.2.296. watch changes to an object of kind BuildConfig	436
2.2.296.1. Parameters	436
2.2.296.2. Responses	438
2.2.296.3. Consumes	438
2.2.296.4. Produces	438
2.2.296.5. Tags	438
2.2.297. watch individual changes to a list of Build	438
2.2.297.1. Parameters	438
2.2.297.2. Responses	439
2.2.297.3. Consumes	440
2.2.297.4. Produces	440
2.2.297.5. Tags	440
2.2.298. watch changes to an object of kind Build	440
2.2.298.1. Parameters	440
2.2.298.2. Responses	441
2.2.298.3. Consumes	441

2.2.298.4. Produces	442
2.2.298.5. Tags	442
2.2.299. watch individual changes to a list of DeploymentConfig	442
2.2.299.1. Parameters	442
2.2.299.2. Responses	443
2.2.299.3. Consumes	443
2.2.299.4. Produces	443
2.2.299.5. Tags	443
2.2.300. watch changes to an object of kind DeploymentConfig	443
2.2.300.1. Parameters	444
2.2.300.2. Responses	445
2.2.300.3. Consumes	445
2.2.300.4. Produces	445
2.2.300.5. Tags	445
2.2.301. watch individual changes to a list of EgressNetworkPolicy	445
2.2.301.1. Parameters	445
2.2.301.2. Responses	447
2.2.301.3. Consumes	447
2.2.301.4. Produces	447
2.2.301.5. Tags	447
2.2.302. watch changes to an object of kind EgressNetworkPolicy	447
2.2.302.1. Parameters	447
2.2.302.2. Responses	448
2.2.302.3. Consumes	448
2.2.302.4. Produces	449
2.2.302.5. Tags	449
2.2.303. watch individual changes to a list of ImageStream	449
2.2.303.1. Parameters	449
2.2.303.2. Responses	450
2.2.303.3. Consumes	450
2.2.303.4. Produces	450
2.2.303.5. Tags	451
2.2.304. watch changes to an object of kind ImageStream	451
2.2.304.1. Parameters	451
2.2.304.2. Responses	452
2.2.304.3. Consumes	452
2.2.304.4. Produces	452
2.2.304.5. Tags	452
2.2.305. watch individual changes to a list of Policy	453
2.2.305.1. Parameters	453
2.2.305.2. Responses	454
2.2.305.3. Consumes	454
2.2.305.4. Produces	454
2.2.305.5. Tags	454
2.2.306. watch changes to an object of kind Policy	454
2.2.306.1. Parameters	454
2.2.306.2. Responses	456
2.2.306.3. Consumes	456
2.2.306.4. Produces	456
2.2.306.5. Tags	456
2.2.307. watch individual changes to a list of PolicyBinding	456
2.2.307.1. Parameters	456
2.2.307.2. Responses	457

2.2.307.3. Consumes	458
2.2.307.4. Produces	458
2.2.307.5. Tags	458
2.2.308. watch changes to an object of kind PolicyBinding	458
2.2.308.1. Parameters	458
2.2.308.2. Responses	459
2.2.308.3. Consumes	459
2.2.308.4. Produces	460
2.2.308.5. Tags	460
2.2.309. watch individual changes to a list of Route	460
2.2.309.1. Parameters	460
2.2.309.2. Responses	461
2.2.309.3. Consumes	461
2.2.309.4. Produces	461
2.2.309.5. Tags	461
2.2.310. watch changes to an object of kind Route	461
2.2.310.1. Parameters	462
2.2.310.2. Responses	463
2.2.310.3. Consumes	463
2.2.310.4. Produces	463
2.2.310.5. Tags	463
2.2.311. watch individual changes to a list of Template	463
2.2.311.1. Parameters	463
2.2.311.2. Responses	464
2.2.311.3. Consumes	465
2.2.311.4. Produces	465
2.2.311.5. Tags	465
2.2.312. watch changes to an object of kind Template	465
2.2.312.1. Parameters	465
2.2.312.2. Responses	466
2.2.312.3. Consumes	466
2.2.312.4. Produces	467
2.2.312.5. Tags	467
2.2.313. watch individual changes to a list of NetNamespace	467
2.2.313.1. Parameters	467
2.2.313.2. Responses	468
2.2.313.3. Consumes	468
2.2.313.4. Produces	468
2.2.313.5. Tags	468
2.2.314. watch changes to an object of kind NetNamespace	468
2.2.314.1. Parameters	468
2.2.314.2. Responses	470
2.2.314.3. Consumes	470
2.2.314.4. Produces	470
2.2.314.5. Tags	470
2.2.315. watch individual changes to a list of OAuthAccessToken	470
2.2.315.1. Parameters	470
2.2.315.2. Responses	471
2.2.315.3. Consumes	471
2.2.315.4. Produces	471
2.2.315.5. Tags	472
2.2.316. watch changes to an object of kind OAuthAccessToken	472
2.2.316.1. Parameters	472

2.2.316.2. Responses	473
2.2.316.3. Consumes	473
2.2.316.4. Produces	473
2.2.316.5. Tags	473
2.2.317. watch individual changes to a list of OAuthAuthorizeToken	473
2.2.317.1. Parameters	474
2.2.317.2. Responses	474
2.2.317.3. Consumes	475
2.2.317.4. Produces	475
2.2.317.5. Tags	475
2.2.318. watch changes to an object of kind OAuthAuthorizeToken	475
2.2.318.1. Parameters	475
2.2.318.2. Responses	476
2.2.318.3. Consumes	476
2.2.318.4. Produces	476
2.2.318.5. Tags	477
2.2.319. watch individual changes to a list of OAuthClientAuthorization	477
2.2.319.1. Parameters	477
2.2.319.2. Responses	478
2.2.319.3. Consumes	478
2.2.319.4. Produces	478
2.2.319.5. Tags	478
2.2.320. watch changes to an object of kind OAuthClientAuthorization	478
2.2.320.1. Parameters	478
2.2.320.2. Responses	480
2.2.320.3. Consumes	480
2.2.320.4. Produces	480
2.2.320.5. Tags	480
2.2.321. watch individual changes to a list of OAuthClient	480
2.2.321.1. Parameters	480
2.2.321.2. Responses	481
2.2.321.3. Consumes	481
2.2.321.4. Produces	481
2.2.321.5. Tags	482
2.2.322. watch changes to an object of kind OAuthClient	482
2.2.322.1. Parameters	482
2.2.322.2. Responses	483
2.2.322.3. Consumes	483
2.2.322.4. Produces	483
2.2.322.5. Tags	483
2.2.323. watch individual changes to a list of Policy	483
2.2.323.1. Parameters	484
2.2.323.2. Responses	484
2.2.323.3. Consumes	485
2.2.323.4. Produces	485
2.2.323.5. Tags	485
2.2.324. watch individual changes to a list of PolicyBinding	485
2.2.324.1. Parameters	485
2.2.324.2. Responses	486
2.2.324.3. Consumes	486
2.2.324.4. Produces	486
2.2.324.5. Tags	487
2.2.325. watch individual changes to a list of Project	487

2.2.325.1. Parameters	487
2.2.325.2. Responses	488
2.2.325.3. Consumes	488
2.2.325.4. Produces	488
2.2.325.5. Tags	488
2.2.326. watch changes to an object of kind Project	488
2.2.326.1. Parameters	488
2.2.326.2. Responses	490
2.2.326.3. Consumes	490
2.2.326.4. Produces	490
2.2.326.5. Tags	490
2.2.327. watch individual changes to a list of Route	490
2.2.327.1. Parameters	490
2.2.327.2. Responses	491
2.2.327.3. Consumes	491
2.2.327.4. Produces	491
2.2.327.5. Tags	492
2.2.328. watch individual changes to a list of Template	492
2.2.328.1. Parameters	492
2.2.328.2. Responses	493
2.2.328.3. Consumes	493
2.2.328.4. Produces	493
2.2.328.5. Tags	493
2.2.329. watch individual changes to a list of User	493
2.2.329.1. Parameters	493
2.2.329.2. Responses	494
2.2.329.3. Consumes	495
2.2.329.4. Produces	495
2.2.329.5. Tags	495
2.2.330. watch changes to an object of kind User	495
2.2.330.1. Parameters	495
2.2.330.2. Responses	496
2.2.330.3. Consumes	496
2.2.330.4. Produces	496
2.2.330.5. Tags	497
2.3. DEFINITIONS	497
2.3.1. versioned.Event	497
2.3.2. patch.Object	497
2.3.3. runtime.RawExtension	497
2.3.4. types.UID	497
2.3.5. unversioned.APIResource	497
2.3.6. unversioned.APIResourceList	497
2.3.7. unversioned.LabelSelector	499
2.3.8. unversioned.LabelSelectorRequirement	499
2.3.9. unversioned.ListMeta	500
2.3.10. unversioned.Patch	501
2.3.11. unversioned.Status	501
2.3.12. unversioned.StatusCause	503
2.3.13. unversioned.StatusDetails	504
2.3.14. v1.AWSElasticBlockStoreVolumeSource	505
2.3.15. v1.AppliedClusterResourceQuota	507
2.3.16. v1.AppliedClusterResourceQuotaList	508
2.3.17. v1.AzureFileVolumeSource	509

2.3.18. v1.BinaryBuildSource	510
2.3.19. v1.Build	511
2.3.20. v1.BuildConfig	512
2.3.21. v1.BuildConfigList	513
2.3.22. v1.BuildConfigSpec	514
2.3.23. v1.BuildConfigStatus	516
2.3.24. v1.BuildList	516
2.3.25. v1.BuildLog	517
2.3.26. v1.BuildOutput	518
2.3.27. v1.BuildPostCommitSpec	519
2.3.28. v1.BuildRequest	522
2.3.29. v1.BuildSource	524
2.3.30. v1.BuildSpec	527
2.3.31. v1.BuildStatus	529
2.3.32. v1.BuildStrategy	531
2.3.33. v1.BuildTriggerCause	531
2.3.34. v1.BuildTriggerPolicy	532
2.3.35. v1.Capabilities	533
2.3.36. v1.Capability	533
2.3.37. v1.CephFSVolumeSource	533
2.3.38. v1.CinderVolumeSource	535
2.3.39. v1.ClusterNetwork	535
2.3.40. v1.ClusterNetworkList	537
2.3.41. v1.ClusterPolicy	538
2.3.42. v1.ClusterPolicyBinding	540
2.3.43. v1.ClusterPolicyBindingList	541
2.3.44. v1.ClusterPolicyList	542
2.3.45. v1.ClusterResourceQuota	543
2.3.46. v1.ClusterResourceQuotaList	545
2.3.47. v1.ClusterResourceQuotaSelector	545
2.3.48. v1.ClusterResourceQuotaSpec	546
2.3.49. v1.ClusterResourceQuotaStatus	546
2.3.50. v1.ClusterRole	547
2.3.51. v1.ClusterRoleBinding	548
2.3.52. v1.ClusterRoleBindingList	550
2.3.53. v1.ClusterRoleList	551
2.3.54. v1.ClusterRoleScopeRestriction	552
2.3.55. v1.ConfigMapKeySelector	553
2.3.56. v1.ConfigMapVolumeSource	553
2.3.57. v1.Container	554
2.3.58. v1.ContainerPort	562
2.3.59. v1.CustomBuildStrategy	563
2.3.60. v1.CustomDeploymentStrategyParams	564
2.3.61. v1.DeleteOptions	565
2.3.62. v1.DeploymentCause	566
2.3.63. v1.DeploymentCauseImageTrigger	567
2.3.64. v1.DeploymentConfig	567
2.3.65. v1.DeploymentConfigList	569
2.3.66. v1.DeploymentConfigRollback	569
2.3.67. v1.DeploymentConfigRollbackSpec	571
2.3.68. v1.DeploymentConfigSpec	571
2.3.69. v1.DeploymentConfigStatus	574
2.3.70. v1.DeploymentDetails	575

2.3.71. v1.DeploymentLog	575
2.3.72. v1.DeploymentStrategy	576
2.3.73. v1.DeploymentTriggerImageChangeParams	577
2.3.74. v1.DeploymentTriggerPolicy	578
2.3.75. v1.DeprecatedDownwardAPIVolumeFile	579
2.3.76. v1.DeprecatedDownwardAPIVolumeSource	579
2.3.77. v1.DockerBuildStrategy	580
2.3.78. v1.DownwardAPIVolumeFile	581
2.3.79. v1.DownwardAPIVolumeSource	582
2.3.80. v1.EgressNetworkPolicy	582
2.3.81. v1.EgressNetworkPolicyList	583
2.3.82. v1.EgressNetworkPolicyPeer	584
2.3.83. v1.EgressNetworkPolicyRule	585
2.3.84. v1.EgressNetworkPolicySpec	585
2.3.85. v1.EmptyDirVolumeSource	585
2.3.86. v1.EnvVar	586
2.3.87. v1.EnvVarSource	587
2.3.88. v1.ExecAction	588
2.3.89. v1.ExecNewPodHook	589
2.3.90. v1.FCVolumeSource	589
2.3.91. v1.FinalizerName	590
2.3.92. v1.FlexVolumeSource	590
2.3.93. v1.FlockerVolumeSource	591
2.3.94. v1.GCEPersistentDiskVolumeSource	591
2.3.95. v1.GenericWebHookCause	593
2.3.96. v1.GitBuildSource	594
2.3.97. v1.GitHubWebHookCause	594
2.3.98. v1.GitRepoVolumeSource	595
2.3.99. v1.GitSourceRevision	595
2.3.100. v1.GlusterfsVolumeSource	596
2.3.101. v1.Group	597
2.3.102. v1.GroupList	598
2.3.103. v1.HTTPGetAction	599
2.3.104. v1.HTTPHeader	600
2.3.105. v1.Handler	600
2.3.106. v1.HostPathVolumeSource	601
2.3.107. v1.HostSubnet	601
2.3.108. v1.HostSubnetList	602
2.3.109. v1.ISCSIVolumeSource	603
2.3.110. v1.Identity	604
2.3.111. v1.IdentityList	606
2.3.112. v1.Image	607
2.3.113. v1.Image.dockerImageSignatures	610
2.3.114. v1.ImageChangeCause	610
2.3.115. v1.ImageChangeTrigger	610
2.3.116. v1.ImageImportSpec	611
2.3.117. v1.ImageImportStatus	611
2.3.118. v1.ImageLayer	612
2.3.119. v1.ImageList	612
2.3.120. v1.ImageSignature	613
2.3.121. v1.ImageSource	615
2.3.122. v1.ImageSourcePath	616
2.3.123. v1.ImageStream	617

2.3.124. v1.ImageStreamImage	618
2.3.125. v1.ImageStreamImport	619
2.3.126. v1.ImageStreamImportSpec	621
2.3.127. v1.ImageStreamImportStatus	621
2.3.128. v1.ImageStreamList	622
2.3.129. v1.ImageStreamMapping	623
2.3.130. v1.ImageStreamSpec	625
2.3.131. v1.ImageStreamStatus	625
2.3.132. v1.ImageStreamTag	625
2.3.133. v1.ImageStreamTagList	627
2.3.134. v1.JenkinsPipelineBuildStrategy	628
2.3.135. v1.KeyToPath	629
2.3.136. v1.Lifecycle	629
2.3.137. v1.LifecycleHook	631
2.3.138. v1.LocalObjectReference	632
2.3.139. v1.LocalResourceAccessReview	632
2.3.140. v1.LocalSubjectAccessReview	634
2.3.141. v1.NFSVolumeSource	637
2.3.142. v1.NamedClusterRole	638
2.3.143. v1.NamedClusterRoleBinding	638
2.3.144. v1.NamedRole	638
2.3.145. v1.NamedRoleBinding	639
2.3.146. v1.NamedTagEventList	639
2.3.147. v1.NetNamespace	639
2.3.148. v1.NetNamespaceList	641
2.3.149. v1.OAuthAccessToken	642
2.3.150. v1.OAuthAccessTokenList	644
2.3.151. v1.OAuthAuthorizeToken	645
2.3.152. v1.OAuthAuthorizeTokenList	647
2.3.153. v1.OAuthClient	648
2.3.154. v1.OAuthClientAuthorization	651
2.3.155. v1.OAuthClientAuthorizationList	652
2.3.156. v1.OAuthClientList	653
2.3.157. v1.ObjectFieldSelector	654
2.3.158. v1.ObjectMeta	655
2.3.159. v1.ObjectReference	663
2.3.160. v1.OwnerReference	665
2.3.161. v1.Parameter	666
2.3.162. v1.PersistentVolumeClaimVolumeSource	668
2.3.163. v1.PodSecurityContext	669
2.3.164. v1.PodSpec	671
2.3.165. v1.PodTemplateSpec	676
2.3.166. v1.Policy	677
2.3.167. v1.PolicyBinding	678
2.3.168. v1.PolicyBindingList	680
2.3.169. v1.PolicyList	681
2.3.170. v1.PolicyRule	682
2.3.171. v1.Preconditions	684
2.3.172. v1.Probe	684
2.3.173. v1.Project	686
2.3.174. v1.ProjectList	688
2.3.175. v1.ProjectRequest	688
2.3.176. v1.ProjectSpec	690

2.3.177. v1.ProjectStatus	690
2.3.178. v1.RBDVolumeSource	690
2.3.179. v1.RecreateDeploymentStrategyParams	692
2.3.180. v1.RepositoryImportSpec	693
2.3.181. v1.RepositoryImportStatus	694
2.3.182. v1.ResourceAccessReview	694
2.3.183. v1.ResourceFieldSelector	696
2.3.184. v1.ResourceQuotaScope	697
2.3.185. v1.ResourceQuotaSpec	697
2.3.186. v1.ResourceQuotaStatus	697
2.3.187. v1.ResourceQuotaStatusByNamespace	698
2.3.188. v1.ResourceRequirements	698
2.3.189. v1.Role	699
2.3.190. v1.RoleBinding	700
2.3.191. v1.RoleBindingList	702
2.3.192. v1.RoleList	703
2.3.193. v1.RollingDeploymentStrategyParams	704
2.3.194. v1.Route	708
2.3.195. v1.RouteIngress	710
2.3.196. v1.RouteIngressCondition	710
2.3.197. v1.RouteList	711
2.3.198. v1.RoutePort	712
2.3.199. v1.RouteSpec	712
2.3.200. v1.RouteStatus	713
2.3.201. v1.RouteTargetReference	714
2.3.202. v1.SELinuxOptions	714
2.3.203. v1.ScopeRestriction	715
2.3.204. v1.Secret	715
2.3.205. v1.SecretBuildSource	717
2.3.206. v1.SecretKeySelector	718
2.3.207. v1.SecretList	719
2.3.208. v1.SecretSpec	720
2.3.209. v1.SecretVolumeSource	720
2.3.210. v1.SecurityContext	721
2.3.211. v1.SelfSubjectRulesReview	724
2.3.212. v1.SelfSubjectRulesReviewSpec	725
2.3.213. v1.SignatureCondition	725
2.3.214. v1.SignatureIssuer	726
2.3.215. v1.SignatureSubject	726
2.3.216. v1.SourceBuildStrategy	727
2.3.217. v1.SourceControlUser	729
2.3.218. v1.SourceRevision	729
2.3.219. v1.SubjectAccessReview	730
2.3.220. v1.SubjectRulesReviewStatus	732
2.3.221. v1.TCPSocketAction	733
2.3.222. v1.TLSConfig	733
2.3.223. v1.TagEvent	734
2.3.224. v1.TagEventCondition	735
2.3.225. v1.TagImageHook	736
2.3.226. v1.TagImportPolicy	736
2.3.227. v1.TagReference	737
2.3.228. v1.Template	738
2.3.229. v1.TemplateList	740

2.3.230. v1.User	741
2.3.231. v1.UserIdentityMapping	743
2.3.232. v1.UserList	744
2.3.233. v1.Volume	745
2.3.234. v1.VolumeMount	750
2.3.235. v1.VsphereVirtualDiskVolumeSource	751
2.3.236. v1.WebHookTrigger	751
2.3.237. v1beta1.Scale	752
2.3.238. v1beta1.ScaleSpec	753
2.3.239. v1beta1.ScaleStatus	754
2.3.240. any	755
CHAPTER 3. KUBERNETES V1 REST API	756
3.1. OVERVIEW	756
3.1.1. Version information	756
3.1.2. URI scheme	756
3.2. PATHS	756
3.2.1. get available resources	756
3.2.1.1. Responses	756
3.2.1.2. Consumes	756
3.2.1.3. Produces	756
3.2.1.4. Tags	756
3.2.2. create a Binding	757
3.2.2.1. Parameters	757
3.2.2.2. Responses	757
3.2.2.3. Consumes	757
3.2.2.4. Produces	757
3.2.2.5. Tags	757
3.2.3. list objects of kind ComponentStatus	757
3.2.3.1. Parameters	757
3.2.3.2. Responses	758
3.2.3.3. Consumes	759
3.2.3.4. Produces	759
3.2.3.5. Tags	759
3.2.4. read the specified ComponentStatus	759
3.2.4.1. Parameters	759
3.2.4.2. Responses	759
3.2.4.3. Consumes	759
3.2.4.4. Produces	760
3.2.4.5. Tags	760
3.2.5. create a ConfigMap	760
3.2.5.1. Parameters	760
3.2.5.2. Responses	760
3.2.5.3. Consumes	760
3.2.5.4. Produces	760
3.2.5.5. Tags	760
3.2.6. list or watch objects of kind ConfigMap	761
3.2.6.1. Parameters	761
3.2.6.2. Responses	762
3.2.6.3. Consumes	762
3.2.6.4. Produces	762
3.2.6.5. Tags	762
3.2.7. create a Endpoints	762

3.2.7.1. Parameters	762
3.2.7.2. Responses	762
3.2.7.3. Consumes	763
3.2.7.4. Produces	763
3.2.7.5. Tags	763
3.2.8. list or watch objects of kind Endpoints	763
3.2.8.1. Parameters	763
3.2.8.2. Responses	764
3.2.8.3. Consumes	764
3.2.8.4. Produces	764
3.2.8.5. Tags	764
3.2.9. create a Event	765
3.2.9.1. Parameters	765
3.2.9.2. Responses	765
3.2.9.3. Consumes	765
3.2.9.4. Produces	765
3.2.9.5. Tags	765
3.2.10. list or watch objects of kind Event	765
3.2.10.1. Parameters	765
3.2.10.2. Responses	766
3.2.10.3. Consumes	767
3.2.10.4. Produces	767
3.2.10.5. Tags	767
3.2.11. create a LimitRange	767
3.2.11.1. Parameters	767
3.2.11.2. Responses	767
3.2.11.3. Consumes	767
3.2.11.4. Produces	767
3.2.11.5. Tags	768
3.2.12. list or watch objects of kind LimitRange	768
3.2.12.1. Parameters	768
3.2.12.2. Responses	769
3.2.12.3. Consumes	769
3.2.12.4. Produces	769
3.2.12.5. Tags	769
3.2.13. delete collection of Namespace	769
3.2.13.1. Parameters	769
3.2.13.2. Responses	770
3.2.13.3. Consumes	771
3.2.13.4. Produces	771
3.2.13.5. Tags	771
3.2.14. create a Namespace	771
3.2.14.1. Parameters	771
3.2.14.2. Responses	771
3.2.14.3. Consumes	771
3.2.14.4. Produces	772
3.2.14.5. Tags	772
3.2.15. list or watch objects of kind Namespace	772
3.2.15.1. Parameters	772
3.2.15.2. Responses	773
3.2.15.3. Consumes	773
3.2.15.4. Produces	773
3.2.15.5. Tags	773

3.2.16. create a Binding	773
3.2.16.1. Parameters	773
3.2.16.2. Responses	774
3.2.16.3. Consumes	774
3.2.16.4. Produces	774
3.2.16.5. Tags	774
3.2.17. delete collection of ConfigMap	774
3.2.17.1. Parameters	774
3.2.17.2. Responses	776
3.2.17.3. Consumes	776
3.2.17.4. Produces	776
3.2.17.5. Tags	776
3.2.18. create a ConfigMap	776
3.2.18.1. Parameters	776
3.2.18.2. Responses	777
3.2.18.3. Consumes	777
3.2.18.4. Produces	777
3.2.18.5. Tags	777
3.2.19. list or watch objects of kind ConfigMap	777
3.2.19.1. Parameters	777
3.2.19.2. Responses	778
3.2.19.3. Consumes	779
3.2.19.4. Produces	779
3.2.19.5. Tags	779
3.2.20. delete a ConfigMap	779
3.2.20.1. Parameters	779
3.2.20.2. Responses	779
3.2.20.3. Consumes	779
3.2.20.4. Produces	780
3.2.20.5. Tags	780
3.2.21. partially update the specified ConfigMap	780
3.2.21.1. Parameters	780
3.2.21.2. Responses	780
3.2.21.3. Consumes	780
3.2.21.4. Produces	781
3.2.21.5. Tags	781
3.2.22. replace the specified ConfigMap	781
3.2.22.1. Parameters	781
3.2.22.2. Responses	781
3.2.22.3. Consumes	781
3.2.22.4. Produces	782
3.2.22.5. Tags	782
3.2.23. read the specified ConfigMap	782
3.2.23.1. Parameters	782
3.2.23.2. Responses	783
3.2.23.3. Consumes	783
3.2.23.4. Produces	783
3.2.23.5. Tags	783
3.2.24. delete collection of Endpoints	783
3.2.24.1. Parameters	783
3.2.24.2. Responses	784
3.2.24.3. Consumes	784
3.2.24.4. Produces	784

3.2.24.5. Tags	785
3.2.25. create a Endpoints	785
3.2.25.1. Parameters	785
3.2.25.2. Responses	785
3.2.25.3. Consumes	785
3.2.25.4. Produces	785
3.2.25.5. Tags	785
3.2.26. list or watch objects of kind Endpoints	786
3.2.26.1. Parameters	786
3.2.26.2. Responses	787
3.2.26.3. Consumes	787
3.2.26.4. Produces	787
3.2.26.5. Tags	787
3.2.27. delete a Endpoints	787
3.2.27.1. Parameters	788
3.2.27.2. Responses	788
3.2.27.3. Consumes	788
3.2.27.4. Produces	788
3.2.27.5. Tags	788
3.2.28. partially update the specified Endpoints	788
3.2.28.1. Parameters	788
3.2.28.2. Responses	789
3.2.28.3. Consumes	789
3.2.28.4. Produces	789
3.2.28.5. Tags	789
3.2.29. replace the specified Endpoints	789
3.2.29.1. Parameters	790
3.2.29.2. Responses	790
3.2.29.3. Consumes	790
3.2.29.4. Produces	790
3.2.29.5. Tags	790
3.2.30. read the specified Endpoints	790
3.2.30.1. Parameters	790
3.2.30.2. Responses	791
3.2.30.3. Consumes	791
3.2.30.4. Produces	791
3.2.30.5. Tags	792
3.2.31. delete collection of Event	792
3.2.31.1. Parameters	792
3.2.31.2. Responses	793
3.2.31.3. Consumes	793
3.2.31.4. Produces	793
3.2.31.5. Tags	793
3.2.32. create a Event	793
3.2.32.1. Parameters	794
3.2.32.2. Responses	794
3.2.32.3. Consumes	794
3.2.32.4. Produces	794
3.2.32.5. Tags	794
3.2.33. list or watch objects of kind Event	794
3.2.33.1. Parameters	794
3.2.33.2. Responses	796
3.2.33.3. Consumes	796

3.2.33.4. Produces	796
3.2.33.5. Tags	796
3.2.34. delete a Event	796
3.2.34.1. Parameters	796
3.2.34.2. Responses	797
3.2.34.3. Consumes	797
3.2.34.4. Produces	797
3.2.34.5. Tags	797
3.2.35. partially update the specified Event	797
3.2.35.1. Parameters	797
3.2.35.2. Responses	798
3.2.35.3. Consumes	798
3.2.35.4. Produces	798
3.2.35.5. Tags	798
3.2.36. replace the specified Event	798
3.2.36.1. Parameters	798
3.2.36.2. Responses	799
3.2.36.3. Consumes	799
3.2.36.4. Produces	799
3.2.36.5. Tags	799
3.2.37. read the specified Event	799
3.2.37.1. Parameters	799
3.2.37.2. Responses	800
3.2.37.3. Consumes	800
3.2.37.4. Produces	800
3.2.37.5. Tags	801
3.2.38. delete collection of LimitRange	801
3.2.38.1. Parameters	801
3.2.38.2. Responses	802
3.2.38.3. Consumes	802
3.2.38.4. Produces	802
3.2.38.5. Tags	802
3.2.39. create a LimitRange	802
3.2.39.1. Parameters	803
3.2.39.2. Responses	803
3.2.39.3. Consumes	803
3.2.39.4. Produces	803
3.2.39.5. Tags	803
3.2.40. list or watch objects of kind LimitRange	803
3.2.40.1. Parameters	803
3.2.40.2. Responses	805
3.2.40.3. Consumes	805
3.2.40.4. Produces	805
3.2.40.5. Tags	805
3.2.41. delete a LimitRange	805
3.2.41.1. Parameters	805
3.2.41.2. Responses	806
3.2.41.3. Consumes	806
3.2.41.4. Produces	806
3.2.41.5. Tags	806
3.2.42. partially update the specified LimitRange	806
3.2.42.1. Parameters	806
3.2.42.2. Responses	807

3.2.42.3. Consumes	807
3.2.42.4. Produces	807
3.2.42.5. Tags	807
3.2.43. replace the specified LimitRange	807
3.2.43.1. Parameters	807
3.2.43.2. Responses	808
3.2.43.3. Consumes	808
3.2.43.4. Produces	808
3.2.43.5. Tags	808
3.2.44. read the specified LimitRange	808
3.2.44.1. Parameters	808
3.2.44.2. Responses	809
3.2.44.3. Consumes	809
3.2.44.4. Produces	809
3.2.44.5. Tags	810
3.2.45. delete collection of PersistentVolumeClaim	810
3.2.45.1. Parameters	810
3.2.45.2. Responses	811
3.2.45.3. Consumes	811
3.2.45.4. Produces	811
3.2.45.5. Tags	811
3.2.46. create a PersistentVolumeClaim	811
3.2.46.1. Parameters	812
3.2.46.2. Responses	812
3.2.46.3. Consumes	812
3.2.46.4. Produces	812
3.2.46.5. Tags	812
3.2.47. list or watch objects of kind PersistentVolumeClaim	812
3.2.47.1. Description	812
3.2.47.2. Parameters	813
3.2.47.3. Responses	814
3.2.47.4. Consumes	814
3.2.47.5. Produces	814
3.2.47.6. Tags	814
3.2.48. delete a PersistentVolumeClaim	814
3.2.48.1. Parameters	815
3.2.48.2. Responses	815
3.2.48.3. Consumes	815
3.2.48.4. Produces	815
3.2.48.5. Tags	815
3.2.49. partially update the specified PersistentVolumeClaim	815
3.2.49.1. Parameters	816
3.2.49.2. Responses	816
3.2.49.3. Consumes	816
3.2.49.4. Produces	816
3.2.49.5. Tags	816
3.2.50. replace the specified PersistentVolumeClaim	817
3.2.50.1. Parameters	817
3.2.50.2. Responses	817
3.2.50.3. Consumes	817
3.2.50.4. Produces	817
3.2.50.5. Tags	817
3.2.51. read the specified PersistentVolumeClaim	818

3.2.51.1. Parameters	818
3.2.51.2. Responses	818
3.2.51.3. Consumes	818
3.2.51.4. Produces	819
3.2.51.5. Tags	819
3.2.52. partially update status of the specified PersistentVolumeClaim	819
3.2.52.1. Parameters	819
3.2.52.2. Responses	819
3.2.52.3. Consumes	819
3.2.52.4. Produces	820
3.2.52.5. Tags	820
3.2.53. replace status of the specified PersistentVolumeClaim	820
3.2.53.1. Parameters	820
3.2.53.2. Responses	820
3.2.53.3. Consumes	820
3.2.53.4. Produces	821
3.2.53.5. Tags	821
3.2.54. read status of the specified PersistentVolumeClaim	821
3.2.54.1. Parameters	821
3.2.54.2. Responses	821
3.2.54.3. Consumes	821
3.2.54.4. Produces	821
3.2.54.5. Tags	822
3.2.55. delete collection of Pod	822
3.2.55.1. Parameters	822
3.2.55.2. Responses	823
3.2.55.3. Consumes	823
3.2.55.4. Produces	823
3.2.55.5. Tags	823
3.2.56. create a Pod	823
3.2.56.1. Parameters	824
3.2.56.2. Responses	824
3.2.56.3. Consumes	824
3.2.56.4. Produces	824
3.2.56.5. Tags	824
3.2.57. list or watch objects of kind Pod	824
3.2.57.1. Parameters	824
3.2.57.2. Responses	826
3.2.57.3. Consumes	826
3.2.57.4. Produces	826
3.2.57.5. Tags	826
3.2.58. delete a Pod	826
3.2.58.1. Parameters	826
3.2.58.2. Responses	827
3.2.58.3. Consumes	827
3.2.58.4. Produces	827
3.2.58.5. Tags	827
3.2.59. partially update the specified Pod	827
3.2.59.1. Parameters	827
3.2.59.2. Responses	828
3.2.59.3. Consumes	828
3.2.59.4. Produces	828
3.2.59.5. Tags	828

3.2.60. replace the specified Pod	828
3.2.60.1. Parameters	828
3.2.60.2. Responses	829
3.2.60.3. Consumes	829
3.2.60.4. Produces	829
3.2.60.5. Tags	829
3.2.61. read the specified Pod	829
3.2.61.1. Parameters	829
3.2.61.2. Responses	830
3.2.61.3. Consumes	830
3.2.61.4. Produces	830
3.2.61.5. Tags	831
3.2.62. connect POST requests to attach of Pod	831
3.2.62.1. Parameters	831
3.2.62.2. Responses	832
3.2.62.3. Consumes	832
3.2.62.4. Produces	832
3.2.62.5. Tags	832
3.2.63. connect GET requests to attach of Pod	832
3.2.63.1. Parameters	832
3.2.63.2. Responses	834
3.2.63.3. Consumes	834
3.2.63.4. Produces	834
3.2.63.5. Tags	834
3.2.64. create binding of a Binding	834
3.2.64.1. Parameters	834
3.2.64.2. Responses	835
3.2.64.3. Consumes	835
3.2.64.4. Produces	835
3.2.64.5. Tags	835
3.2.65. connect POST requests to exec of Pod	835
3.2.65.1. Parameters	835
3.2.65.2. Responses	837
3.2.65.3. Consumes	837
3.2.65.4. Produces	837
3.2.65.5. Tags	837
3.2.66. connect GET requests to exec of Pod	837
3.2.66.1. Parameters	837
3.2.66.2. Responses	839
3.2.66.3. Consumes	839
3.2.66.4. Produces	839
3.2.66.5. Tags	839
3.2.67. read log of the specified Pod	839
3.2.67.1. Parameters	839
3.2.67.2. Responses	841
3.2.67.3. Consumes	842
3.2.67.4. Produces	842
3.2.67.5. Tags	842
3.2.68. connect POST requests to portforward of Pod	842
3.2.68.1. Parameters	842
3.2.68.2. Responses	842
3.2.68.3. Consumes	842
3.2.68.4. Produces	843

3.2.68.5. Tags	843
3.2.69. connect GET requests to portforward of Pod	843
3.2.69.1. Parameters	843
3.2.69.2. Responses	843
3.2.69.3. Consumes	843
3.2.69.4. Produces	843
3.2.69.5. Tags	843
3.2.70. connect DELETE requests to proxy of Pod	843
3.2.70.1. Parameters	843
3.2.70.2. Responses	844
3.2.70.3. Consumes	844
3.2.70.4. Produces	844
3.2.70.5. Tags	844
3.2.71. connect OPTIONS requests to proxy of Pod	844
3.2.71.1. Parameters	844
3.2.71.2. Responses	845
3.2.71.3. Consumes	845
3.2.71.4. Produces	845
3.2.71.5. Tags	845
3.2.72. connect POST requests to proxy of Pod	845
3.2.72.1. Parameters	845
3.2.72.2. Responses	846
3.2.72.3. Consumes	846
3.2.72.4. Produces	846
3.2.72.5. Tags	846
3.2.73. connect PUT requests to proxy of Pod	846
3.2.73.1. Parameters	846
3.2.73.2. Responses	847
3.2.73.3. Consumes	847
3.2.73.4. Produces	847
3.2.73.5. Tags	847
3.2.74. connect GET requests to proxy of Pod	847
3.2.74.1. Parameters	847
3.2.74.2. Responses	848
3.2.74.3. Consumes	848
3.2.74.4. Produces	848
3.2.74.5. Tags	848
3.2.75. connect HEAD requests to proxy of Pod	848
3.2.75.1. Parameters	848
3.2.75.2. Responses	848
3.2.75.3. Consumes	849
3.2.75.4. Produces	849
3.2.75.5. Tags	849
3.2.76. connect DELETE requests to proxy of Pod	849
3.2.76.1. Parameters	849
3.2.76.2. Responses	849
3.2.76.3. Consumes	849
3.2.76.4. Produces	849
3.2.76.5. Tags	850
3.2.77. connect OPTIONS requests to proxy of Pod	850
3.2.77.1. Parameters	850
3.2.77.2. Responses	850
3.2.77.3. Consumes	850

3.2.77.4. Produces	850
3.2.77.5. Tags	850
3.2.78. connect POST requests to proxy of Pod	851
3.2.78.1. Parameters	851
3.2.78.2. Responses	851
3.2.78.3. Consumes	851
3.2.78.4. Produces	851
3.2.78.5. Tags	851
3.2.79. connect PUT requests to proxy of Pod	851
3.2.79.1. Parameters	852
3.2.79.2. Responses	852
3.2.79.3. Consumes	852
3.2.79.4. Produces	852
3.2.79.5. Tags	852
3.2.80. connect GET requests to proxy of Pod	852
3.2.80.1. Parameters	852
3.2.80.2. Responses	853
3.2.80.3. Consumes	853
3.2.80.4. Produces	853
3.2.80.5. Tags	853
3.2.81. connect HEAD requests to proxy of Pod	853
3.2.81.1. Parameters	853
3.2.81.2. Responses	854
3.2.81.3. Consumes	854
3.2.81.4. Produces	854
3.2.81.5. Tags	854
3.2.82. partially update status of the specified Pod	854
3.2.82.1. Parameters	854
3.2.82.2. Responses	855
3.2.82.3. Consumes	855
3.2.82.4. Produces	855
3.2.82.5. Tags	855
3.2.83. replace status of the specified Pod	855
3.2.83.1. Parameters	856
3.2.83.2. Responses	856
3.2.83.3. Consumes	856
3.2.83.4. Produces	856
3.2.83.5. Tags	856
3.2.84. read status of the specified Pod	856
3.2.84.1. Parameters	856
3.2.84.2. Responses	857
3.2.84.3. Consumes	857
3.2.84.4. Produces	857
3.2.84.5. Tags	857
3.2.85. delete collection of PodTemplate	857
3.2.85.1. Parameters	857
3.2.85.2. Responses	859
3.2.85.3. Consumes	859
3.2.85.4. Produces	859
3.2.85.5. Tags	859
3.2.86. create a PodTemplate	859
3.2.86.1. Parameters	859
3.2.86.2. Responses	859

3.2.86.3. Consumes	860
3.2.86.4. Produces	860
3.2.86.5. Tags	860
3.2.87. list or watch objects of kind PodTemplate	860
3.2.87.1. Parameters	860
3.2.87.2. Responses	861
3.2.87.3. Consumes	861
3.2.87.4. Produces	861
3.2.87.5. Tags	862
3.2.88. delete a PodTemplate	862
3.2.88.1. Parameters	862
3.2.88.2. Responses	862
3.2.88.3. Consumes	862
3.2.88.4. Produces	862
3.2.88.5. Tags	863
3.2.89. partially update the specified PodTemplate	863
3.2.89.1. Parameters	863
3.2.89.2. Responses	863
3.2.89.3. Consumes	863
3.2.89.4. Produces	863
3.2.89.5. Tags	864
3.2.90. replace the specified PodTemplate	864
3.2.90.1. Parameters	864
3.2.90.2. Responses	864
3.2.90.3. Consumes	864
3.2.90.4. Produces	864
3.2.90.5. Tags	865
3.2.91. read the specified PodTemplate	865
3.2.91.1. Parameters	865
3.2.91.2. Responses	865
3.2.91.3. Consumes	866
3.2.91.4. Produces	866
3.2.91.5. Tags	866
3.2.92. delete collection of ReplicationController	866
3.2.92.1. Parameters	866
3.2.92.2. Responses	867
3.2.92.3. Consumes	867
3.2.92.4. Produces	867
3.2.92.5. Tags	868
3.2.93. create a ReplicationController	868
3.2.93.1. Parameters	868
3.2.93.2. Responses	868
3.2.93.3. Consumes	868
3.2.93.4. Produces	868
3.2.93.5. Tags	869
3.2.94. list or watch objects of kind ReplicationController	869
3.2.94.1. Parameters	869
3.2.94.2. Responses	870
3.2.94.3. Consumes	870
3.2.94.4. Produces	870
3.2.94.5. Tags	870
3.2.95. delete a ReplicationController	870
3.2.95.1. Parameters	871

3.2.95.2. Responses	871
3.2.95.3. Consumes	871
3.2.95.4. Produces	871
3.2.95.5. Tags	871
3.2.96. partially update the specified ReplicationController	871
3.2.96.1. Parameters	872
3.2.96.2. Responses	872
3.2.96.3. Consumes	872
3.2.96.4. Produces	872
3.2.96.5. Tags	872
3.2.97. replace the specified ReplicationController	872
3.2.97.1. Parameters	873
3.2.97.2. Responses	873
3.2.97.3. Consumes	873
3.2.97.4. Produces	873
3.2.97.5. Tags	873
3.2.98. read the specified ReplicationController	873
3.2.98.1. Parameters	874
3.2.98.2. Responses	874
3.2.98.3. Consumes	874
3.2.98.4. Produces	874
3.2.98.5. Tags	875
3.2.99. partially update scale of the specified Scale	875
3.2.99.1. Parameters	875
3.2.99.2. Responses	875
3.2.99.3. Consumes	875
3.2.99.4. Produces	876
3.2.99.5. Tags	876
3.2.100. replace scale of the specified Scale	876
3.2.100.1. Parameters	876
3.2.100.2. Responses	876
3.2.100.3. Consumes	876
3.2.100.4. Produces	876
3.2.100.5. Tags	877
3.2.101. read scale of the specified Scale	877
3.2.101.1. Parameters	877
3.2.101.2. Responses	877
3.2.101.3. Consumes	877
3.2.101.4. Produces	877
3.2.101.5. Tags	877
3.2.102. partially update status of the specified ReplicationController	878
3.2.102.1. Parameters	878
3.2.102.2. Responses	878
3.2.102.3. Consumes	878
3.2.102.4. Produces	878
3.2.102.5. Tags	879
3.2.103. replace status of the specified ReplicationController	879
3.2.103.1. Parameters	879
3.2.103.2. Responses	879
3.2.103.3. Consumes	879
3.2.103.4. Produces	879
3.2.103.5. Tags	880
3.2.104. read status of the specified ReplicationController	880

3.2.104.1. Parameters	880
3.2.104.2. Responses	880
3.2.104.3. Consumes	880
3.2.104.4. Produces	880
3.2.104.5. Tags	880
3.2.105. delete collection of ResourceQuota	881
3.2.105.1. Parameters	881
3.2.105.2. Responses	882
3.2.105.3. Consumes	882
3.2.105.4. Produces	882
3.2.105.5. Tags	882
3.2.106. create a ResourceQuota	882
3.2.106.1. Parameters	882
3.2.106.2. Responses	883
3.2.106.3. Consumes	883
3.2.106.4. Produces	883
3.2.106.5. Tags	883
3.2.107. list or watch objects of kind ResourceQuota	883
3.2.107.1. Parameters	883
3.2.107.2. Responses	885
3.2.107.3. Consumes	885
3.2.107.4. Produces	885
3.2.107.5. Tags	885
3.2.108. delete a ResourceQuota	885
3.2.108.1. Parameters	885
3.2.108.2. Responses	886
3.2.108.3. Consumes	886
3.2.108.4. Produces	886
3.2.108.5. Tags	886
3.2.109. partially update the specified ResourceQuota	886
3.2.109.1. Parameters	886
3.2.109.2. Responses	887
3.2.109.3. Consumes	887
3.2.109.4. Produces	887
3.2.109.5. Tags	887
3.2.110. replace the specified ResourceQuota	887
3.2.110.1. Parameters	887
3.2.110.2. Responses	888
3.2.110.3. Consumes	888
3.2.110.4. Produces	888
3.2.110.5. Tags	888
3.2.111. read the specified ResourceQuota	888
3.2.111.1. Parameters	888
3.2.111.2. Responses	889
3.2.111.3. Consumes	889
3.2.111.4. Produces	889
3.2.111.5. Tags	889
3.2.112. partially update status of the specified ResourceQuota	890
3.2.112.1. Parameters	890
3.2.112.2. Responses	890
3.2.112.3. Consumes	890
3.2.112.4. Produces	890
3.2.112.5. Tags	890

3.2.113. replace status of the specified ResourceQuota	891
3.2.113.1. Parameters	891
3.2.113.2. Responses	891
3.2.113.3. Consumes	891
3.2.113.4. Produces	891
3.2.113.5. Tags	891
3.2.114. read status of the specified ResourceQuota	892
3.2.114.1. Parameters	892
3.2.114.2. Responses	892
3.2.114.3. Consumes	892
3.2.114.4. Produces	892
3.2.114.5. Tags	892
3.2.115. delete collection of Secret	892
3.2.115.1. Parameters	893
3.2.115.2. Responses	894
3.2.115.3. Consumes	894
3.2.115.4. Produces	894
3.2.115.5. Tags	894
3.2.116. create a Secret	894
3.2.116.1. Parameters	894
3.2.116.2. Responses	895
3.2.116.3. Consumes	895
3.2.116.4. Produces	895
3.2.116.5. Tags	895
3.2.117. list or watch objects of kind Secret	895
3.2.117.1. Parameters	895
3.2.117.2. Responses	896
3.2.117.3. Consumes	897
3.2.117.4. Produces	897
3.2.117.5. Tags	897
3.2.118. delete a Secret	897
3.2.118.1. Parameters	897
3.2.118.2. Responses	897
3.2.118.3. Consumes	898
3.2.118.4. Produces	898
3.2.118.5. Tags	898
3.2.119. partially update the specified Secret	898
3.2.119.1. Parameters	898
3.2.119.2. Responses	898
3.2.119.3. Consumes	899
3.2.119.4. Produces	899
3.2.119.5. Tags	899
3.2.120. replace the specified Secret	899
3.2.120.1. Parameters	899
3.2.120.2. Responses	899
3.2.120.3. Consumes	900
3.2.120.4. Produces	900
3.2.120.5. Tags	900
3.2.121. read the specified Secret	900
3.2.121.1. Parameters	900
3.2.121.2. Responses	901
3.2.121.3. Consumes	901
3.2.121.4. Produces	901

3.2.121.5. Tags	901
3.2.122. delete collection of ServiceAccount	901
3.2.122.1. Parameters	901
3.2.122.2. Responses	903
3.2.122.3. Consumes	903
3.2.122.4. Produces	903
3.2.122.5. Tags	903
3.2.123. create a ServiceAccount	903
3.2.123.1. Parameters	903
3.2.123.2. Responses	903
3.2.123.3. Consumes	904
3.2.123.4. Produces	904
3.2.123.5. Tags	904
3.2.124. list or watch objects of kind ServiceAccount	904
3.2.124.1. Parameters	904
3.2.124.2. Responses	905
3.2.124.3. Consumes	905
3.2.124.4. Produces	905
3.2.124.5. Tags	906
3.2.125. delete a ServiceAccount	906
3.2.125.1. Parameters	906
3.2.125.2. Responses	906
3.2.125.3. Consumes	906
3.2.125.4. Produces	906
3.2.125.5. Tags	907
3.2.126. partially update the specified ServiceAccount	907
3.2.126.1. Parameters	907
3.2.126.2. Responses	907
3.2.126.3. Consumes	907
3.2.126.4. Produces	908
3.2.126.5. Tags	908
3.2.127. replace the specified ServiceAccount	908
3.2.127.1. Parameters	908
3.2.127.2. Responses	908
3.2.127.3. Consumes	908
3.2.127.4. Produces	909
3.2.127.5. Tags	909
3.2.128. read the specified ServiceAccount	909
3.2.128.1. Parameters	909
3.2.128.2. Responses	910
3.2.128.3. Consumes	910
3.2.128.4. Produces	910
3.2.128.5. Tags	910
3.2.129. create a Service	910
3.2.129.1. Parameters	910
3.2.129.2. Responses	910
3.2.129.3. Consumes	911
3.2.129.4. Produces	911
3.2.129.5. Tags	911
3.2.130. list or watch objects of kind Service	911
3.2.130.1. Parameters	911
3.2.130.2. Responses	912
3.2.130.3. Consumes	912

3.2.130.4. Produces	912
3.2.130.5. Tags	913
3.2.131. delete a Service	913
3.2.131.1. Parameters	913
3.2.131.2. Responses	913
3.2.131.3. Consumes	913
3.2.131.4. Produces	913
3.2.131.5. Tags	913
3.2.132. partially update the specified Service	914
3.2.132.1. Parameters	914
3.2.132.2. Responses	914
3.2.132.3. Consumes	914
3.2.132.4. Produces	914
3.2.132.5. Tags	915
3.2.133. replace the specified Service	915
3.2.133.1. Parameters	915
3.2.133.2. Responses	915
3.2.133.3. Consumes	915
3.2.133.4. Produces	915
3.2.133.5. Tags	915
3.2.134. read the specified Service	916
3.2.134.1. Parameters	916
3.2.134.2. Responses	916
3.2.134.3. Consumes	916
3.2.134.4. Produces	916
3.2.134.5. Tags	917
3.2.135. connect DELETE requests to proxy of Service	917
3.2.135.1. Parameters	917
3.2.135.2. Responses	918
3.2.135.3. Consumes	918
3.2.135.4. Produces	918
3.2.135.5. Tags	918
3.2.136. connect OPTIONS requests to proxy of Service	918
3.2.136.1. Parameters	918
3.2.136.2. Responses	919
3.2.136.3. Consumes	919
3.2.136.4. Produces	919
3.2.136.5. Tags	919
3.2.137. connect POST requests to proxy of Service	919
3.2.137.1. Parameters	919
3.2.137.2. Responses	920
3.2.137.3. Consumes	920
3.2.137.4. Produces	920
3.2.137.5. Tags	921
3.2.138. connect PUT requests to proxy of Service	921
3.2.138.1. Parameters	921
3.2.138.2. Responses	921
3.2.138.3. Consumes	922
3.2.138.4. Produces	922
3.2.138.5. Tags	922
3.2.139. connect GET requests to proxy of Service	922
3.2.139.1. Parameters	922
3.2.139.2. Responses	923

3.2.139.3. Consumes	923
3.2.139.4. Produces	923
3.2.139.5. Tags	923
3.2.140. connect HEAD requests to proxy of Service	923
3.2.140.1. Parameters	923
3.2.140.2. Responses	924
3.2.140.3. Consumes	924
3.2.140.4. Produces	924
3.2.140.5. Tags	925
3.2.141. connect DELETE requests to proxy of Service	925
3.2.141.1. Parameters	925
3.2.141.2. Responses	925
3.2.141.3. Consumes	926
3.2.141.4. Produces	926
3.2.141.5. Tags	926
3.2.142. connect OPTIONS requests to proxy of Service	926
3.2.142.1. Parameters	926
3.2.142.2. Responses	927
3.2.142.3. Consumes	927
3.2.142.4. Produces	927
3.2.142.5. Tags	927
3.2.143. connect POST requests to proxy of Service	927
3.2.143.1. Parameters	927
3.2.143.2. Responses	928
3.2.143.3. Consumes	928
3.2.143.4. Produces	929
3.2.143.5. Tags	929
3.2.144. connect PUT requests to proxy of Service	929
3.2.144.1. Parameters	929
3.2.144.2. Responses	930
3.2.144.3. Consumes	930
3.2.144.4. Produces	930
3.2.144.5. Tags	930
3.2.145. connect GET requests to proxy of Service	930
3.2.145.1. Parameters	930
3.2.145.2. Responses	931
3.2.145.3. Consumes	931
3.2.145.4. Produces	932
3.2.145.5. Tags	932
3.2.146. connect HEAD requests to proxy of Service	932
3.2.146.1. Parameters	932
3.2.146.2. Responses	933
3.2.146.3. Consumes	933
3.2.146.4. Produces	933
3.2.146.5. Tags	933
3.2.147. partially update status of the specified Service	933
3.2.147.1. Parameters	933
3.2.147.2. Responses	934
3.2.147.3. Consumes	934
3.2.147.4. Produces	934
3.2.147.5. Tags	934
3.2.148. replace status of the specified Service	934
3.2.148.1. Parameters	934

3.2.148.2. Responses	935
3.2.148.3. Consumes	935
3.2.148.4. Produces	935
3.2.148.5. Tags	935
3.2.149. read status of the specified Service	935
3.2.149.1. Parameters	935
3.2.149.2. Responses	935
3.2.149.3. Consumes	936
3.2.149.4. Produces	936
3.2.149.5. Tags	936
3.2.150. delete a Namespace	936
3.2.150.1. Parameters	936
3.2.150.2. Responses	936
3.2.150.3. Consumes	936
3.2.150.4. Produces	936
3.2.150.5. Tags	937
3.2.151. partially update the specified Namespace	937
3.2.151.1. Parameters	937
3.2.151.2. Responses	937
3.2.151.3. Consumes	937
3.2.151.4. Produces	937
3.2.151.5. Tags	938
3.2.152. replace the specified Namespace	938
3.2.152.1. Parameters	938
3.2.152.2. Responses	938
3.2.152.3. Consumes	938
3.2.152.4. Produces	938
3.2.152.5. Tags	938
3.2.153. read the specified Namespace	938
3.2.153.1. Parameters	939
3.2.153.2. Responses	939
3.2.153.3. Consumes	939
3.2.153.4. Produces	939
3.2.153.5. Tags	939
3.2.154. replace finalize of the specified Namespace	940
3.2.154.1. Parameters	940
3.2.154.2. Responses	940
3.2.154.3. Consumes	940
3.2.154.4. Produces	940
3.2.154.5. Tags	940
3.2.155. partially update status of the specified Namespace	940
3.2.155.1. Parameters	940
3.2.155.2. Responses	941
3.2.155.3. Consumes	941
3.2.155.4. Produces	941
3.2.155.5. Tags	941
3.2.156. replace status of the specified Namespace	941
3.2.156.1. Parameters	941
3.2.156.2. Responses	942
3.2.156.3. Consumes	942
3.2.156.4. Produces	942
3.2.156.5. Tags	942
3.2.157. read status of the specified Namespace	942

3.2.157.1. Parameters	942
3.2.157.2. Responses	943
3.2.157.3. Consumes	943
3.2.157.4. Produces	943
3.2.157.5. Tags	943
3.2.158. delete collection of Node	943
3.2.158.1. Parameters	943
3.2.158.2. Responses	944
3.2.158.3. Consumes	944
3.2.158.4. Produces	945
3.2.158.5. Tags	945
3.2.159. create a Node	945
3.2.159.1. Parameters	945
3.2.159.2. Responses	945
3.2.159.3. Consumes	945
3.2.159.4. Produces	945
3.2.159.5. Tags	945
3.2.160. list or watch objects of kind Node	946
3.2.160.1. Parameters	946
3.2.160.2. Responses	947
3.2.160.3. Consumes	947
3.2.160.4. Produces	947
3.2.160.5. Tags	947
3.2.161. delete a Node	947
3.2.161.1. Parameters	947
3.2.161.2. Responses	947
3.2.161.3. Consumes	948
3.2.161.4. Produces	948
3.2.161.5. Tags	948
3.2.162. partially update the specified Node	948
3.2.162.1. Parameters	948
3.2.162.2. Responses	948
3.2.162.3. Consumes	948
3.2.162.4. Produces	949
3.2.162.5. Tags	949
3.2.163. replace the specified Node	949
3.2.163.1. Parameters	949
3.2.163.2. Responses	949
3.2.163.3. Consumes	949
3.2.163.4. Produces	949
3.2.163.5. Tags	950
3.2.164. read the specified Node	950
3.2.164.1. Parameters	950
3.2.164.2. Responses	950
3.2.164.3. Consumes	950
3.2.164.4. Produces	951
3.2.164.5. Tags	951
3.2.165. connect DELETE requests to proxy of Node	951
3.2.165.1. Parameters	951
3.2.165.2. Responses	951
3.2.165.3. Consumes	951
3.2.165.4. Produces	951
3.2.165.5. Tags	951

3.2.166. connect OPTIONS requests to proxy of Node	951
3.2.166.1. Parameters	952
3.2.166.2. Responses	952
3.2.166.3. Consumes	952
3.2.166.4. Produces	952
3.2.166.5. Tags	952
3.2.167. connect POST requests to proxy of Node	952
3.2.167.1. Parameters	952
3.2.167.2. Responses	953
3.2.167.3. Consumes	953
3.2.167.4. Produces	953
3.2.167.5. Tags	953
3.2.168. connect PUT requests to proxy of Node	953
3.2.168.1. Parameters	953
3.2.168.2. Responses	954
3.2.168.3. Consumes	954
3.2.168.4. Produces	954
3.2.168.5. Tags	954
3.2.169. connect GET requests to proxy of Node	954
3.2.169.1. Parameters	954
3.2.169.2. Responses	954
3.2.169.3. Consumes	954
3.2.169.4. Produces	954
3.2.169.5. Tags	955
3.2.170. connect HEAD requests to proxy of Node	955
3.2.170.1. Parameters	955
3.2.170.2. Responses	955
3.2.170.3. Consumes	955
3.2.170.4. Produces	955
3.2.170.5. Tags	955
3.2.171. connect DELETE requests to proxy of Node	955
3.2.171.1. Parameters	955
3.2.171.2. Responses	956
3.2.171.3. Consumes	956
3.2.171.4. Produces	956
3.2.171.5. Tags	956
3.2.172. connect OPTIONS requests to proxy of Node	956
3.2.172.1. Parameters	956
3.2.172.2. Responses	957
3.2.172.3. Consumes	957
3.2.172.4. Produces	957
3.2.172.5. Tags	957
3.2.173. connect POST requests to proxy of Node	957
3.2.173.1. Parameters	957
3.2.173.2. Responses	958
3.2.173.3. Consumes	958
3.2.173.4. Produces	958
3.2.173.5. Tags	958
3.2.174. connect PUT requests to proxy of Node	958
3.2.174.1. Parameters	958
3.2.174.2. Responses	958
3.2.174.3. Consumes	958
3.2.174.4. Produces	959

3.2.174.5. Tags	959
3.2.175. connect GET requests to proxy of Node	959
3.2.175.1. Parameters	959
3.2.175.2. Responses	959
3.2.175.3. Consumes	959
3.2.175.4. Produces	959
3.2.175.5. Tags	959
3.2.176. connect HEAD requests to proxy of Node	960
3.2.176.1. Parameters	960
3.2.176.2. Responses	960
3.2.176.3. Consumes	960
3.2.176.4. Produces	960
3.2.176.5. Tags	960
3.2.177. partially update status of the specified Node	960
3.2.177.1. Parameters	960
3.2.177.2. Responses	961
3.2.177.3. Consumes	961
3.2.177.4. Produces	961
3.2.177.5. Tags	961
3.2.178. replace status of the specified Node	961
3.2.178.1. Parameters	961
3.2.178.2. Responses	962
3.2.178.3. Consumes	962
3.2.178.4. Produces	962
3.2.178.5. Tags	962
3.2.179. read status of the specified Node	962
3.2.179.1. Parameters	962
3.2.179.2. Responses	963
3.2.179.3. Consumes	963
3.2.179.4. Produces	963
3.2.179.5. Tags	963
3.2.180. create a PersistentVolumeClaim	963
3.2.180.1. Parameters	963
3.2.180.2. Responses	963
3.2.180.3. Consumes	964
3.2.180.4. Produces	964
3.2.180.5. Tags	964
3.2.181. list or watch objects of kind PersistentVolumeClaim	964
3.2.181.1. Description	964
3.2.181.2. Parameters	964
3.2.181.3. Responses	965
3.2.181.4. Consumes	965
3.2.181.5. Produces	965
3.2.181.6. Tags	966
3.2.182. delete collection of PersistentVolume	966
3.2.182.1. Parameters	966
3.2.182.2. Responses	967
3.2.182.3. Consumes	967
3.2.182.4. Produces	967
3.2.182.5. Tags	967
3.2.183. create a PersistentVolume	967
3.2.183.1. Parameters	967
3.2.183.2. Responses	968

3.2.183.3. Consumes	968
3.2.183.4. Produces	968
3.2.183.5. Tags	968
3.2.184. list or watch objects of kind PersistentVolume	968
3.2.184.1. Parameters	968
3.2.184.2. Responses	969
3.2.184.3. Consumes	970
3.2.184.4. Produces	970
3.2.184.5. Tags	970
3.2.185. delete a PersistentVolume	970
3.2.185.1. Parameters	970
3.2.185.2. Responses	970
3.2.185.3. Consumes	971
3.2.185.4. Produces	971
3.2.185.5. Tags	971
3.2.186. partially update the specified PersistentVolume	971
3.2.186.1. Parameters	971
3.2.186.2. Responses	971
3.2.186.3. Consumes	972
3.2.186.4. Produces	972
3.2.186.5. Tags	972
3.2.187. replace the specified PersistentVolume	972
3.2.187.1. Parameters	972
3.2.187.2. Responses	972
3.2.187.3. Consumes	972
3.2.187.4. Produces	973
3.2.187.5. Tags	973
3.2.188. read the specified PersistentVolume	973
3.2.188.1. Parameters	973
3.2.188.2. Responses	973
3.2.188.3. Consumes	974
3.2.188.4. Produces	974
3.2.188.5. Tags	974
3.2.189. partially update status of the specified PersistentVolume	974
3.2.189.1. Parameters	974
3.2.189.2. Responses	974
3.2.189.3. Consumes	975
3.2.189.4. Produces	975
3.2.189.5. Tags	975
3.2.190. replace status of the specified PersistentVolume	975
3.2.190.1. Parameters	975
3.2.190.2. Responses	975
3.2.190.3. Consumes	975
3.2.190.4. Produces	976
3.2.190.5. Tags	976
3.2.191. read status of the specified PersistentVolume	976
3.2.191.1. Parameters	976
3.2.191.2. Responses	976
3.2.191.3. Consumes	976
3.2.191.4. Produces	976
3.2.191.5. Tags	976
3.2.192. create a Pod	977
3.2.192.1. Parameters	977

3.2.192.2. Responses	977
3.2.192.3. Consumes	977
3.2.192.4. Produces	977
3.2.192.5. Tags	977
3.2.193. list or watch objects of kind Pod	977
3.2.193.1. Parameters	977
3.2.193.2. Responses	978
3.2.193.3. Consumes	979
3.2.193.4. Produces	979
3.2.193.5. Tags	979
3.2.194. create a PodTemplate	979
3.2.194.1. Parameters	979
3.2.194.2. Responses	979
3.2.194.3. Consumes	979
3.2.194.4. Produces	980
3.2.194.5. Tags	980
3.2.195. list or watch objects of kind PodTemplate	980
3.2.195.1. Parameters	980
3.2.195.2. Responses	981
3.2.195.3. Consumes	981
3.2.195.4. Produces	981
3.2.195.5. Tags	981
3.2.196. proxy DELETE requests to Pod	981
3.2.196.1. Parameters	981
3.2.196.2. Responses	982
3.2.196.3. Consumes	982
3.2.196.4. Produces	982
3.2.196.5. Tags	982
3.2.197. proxy OPTIONS requests to Pod	982
3.2.197.1. Parameters	982
3.2.197.2. Responses	983
3.2.197.3. Consumes	983
3.2.197.4. Produces	983
3.2.197.5. Tags	983
3.2.198. proxy POST requests to Pod	983
3.2.198.1. Parameters	983
3.2.198.2. Responses	983
3.2.198.3. Consumes	983
3.2.198.4. Produces	983
3.2.198.5. Tags	984
3.2.199. proxy PUT requests to Pod	984
3.2.199.1. Parameters	984
3.2.199.2. Responses	984
3.2.199.3. Consumes	984
3.2.199.4. Produces	984
3.2.199.5. Tags	984
3.2.200. proxy GET requests to Pod	984
3.2.200.1. Parameters	984
3.2.200.2. Responses	985
3.2.200.3. Consumes	985
3.2.200.4. Produces	985
3.2.200.5. Tags	985
3.2.201. proxy HEAD requests to Pod	985

3.2.201.1. Parameters	985
3.2.201.2. Responses	986
3.2.201.3. Consumes	986
3.2.201.4. Produces	986
3.2.201.5. Tags	986
3.2.202. proxy DELETE requests to Pod	986
3.2.202.1. Parameters	986
3.2.202.2. Responses	986
3.2.202.3. Consumes	986
3.2.202.4. Produces	987
3.2.202.5. Tags	987
3.2.203. proxy OPTIONS requests to Pod	987
3.2.203.1. Parameters	987
3.2.203.2. Responses	987
3.2.203.3. Consumes	987
3.2.203.4. Produces	987
3.2.203.5. Tags	987
3.2.204. proxy POST requests to Pod	987
3.2.204.1. Parameters	988
3.2.204.2. Responses	988
3.2.204.3. Consumes	988
3.2.204.4. Produces	988
3.2.204.5. Tags	988
3.2.205. proxy PUT requests to Pod	988
3.2.205.1. Parameters	988
3.2.205.2. Responses	989
3.2.205.3. Consumes	989
3.2.205.4. Produces	989
3.2.205.5. Tags	989
3.2.206. proxy GET requests to Pod	989
3.2.206.1. Parameters	989
3.2.206.2. Responses	990
3.2.206.3. Consumes	990
3.2.206.4. Produces	990
3.2.206.5. Tags	990
3.2.207. proxy HEAD requests to Pod	990
3.2.207.1. Parameters	990
3.2.207.2. Responses	990
3.2.207.3. Consumes	991
3.2.207.4. Produces	991
3.2.207.5. Tags	991
3.2.208. proxy DELETE requests to Service	991
3.2.208.1. Parameters	991
3.2.208.2. Responses	991
3.2.208.3. Consumes	991
3.2.208.4. Produces	991
3.2.208.5. Tags	992
3.2.209. proxy OPTIONS requests to Service	992
3.2.209.1. Parameters	992
3.2.209.2. Responses	992
3.2.209.3. Consumes	992
3.2.209.4. Produces	992
3.2.209.5. Tags	992

3.2.210. proxy POST requests to Service	992
3.2.210.1. Parameters	992
3.2.210.2. Responses	993
3.2.210.3. Consumes	993
3.2.210.4. Produces	993
3.2.210.5. Tags	993
3.2.211. proxy PUT requests to Service	993
3.2.211.1. Parameters	993
3.2.211.2. Responses	994
3.2.211.3. Consumes	994
3.2.211.4. Produces	994
3.2.211.5. Tags	994
3.2.212. proxy GET requests to Service	994
3.2.212.1. Parameters	994
3.2.212.2. Responses	994
3.2.212.3. Consumes	994
3.2.212.4. Produces	994
3.2.212.5. Tags	995
3.2.213. proxy HEAD requests to Service	995
3.2.213.1. Parameters	995
3.2.213.2. Responses	995
3.2.213.3. Consumes	995
3.2.213.4. Produces	995
3.2.213.5. Tags	995
3.2.214. proxy DELETE requests to Service	995
3.2.214.1. Parameters	995
3.2.214.2. Responses	996
3.2.214.3. Consumes	996
3.2.214.4. Produces	996
3.2.214.5. Tags	996
3.2.215. proxy OPTIONS requests to Service	996
3.2.215.1. Parameters	996
3.2.215.2. Responses	997
3.2.215.3. Consumes	997
3.2.215.4. Produces	997
3.2.215.5. Tags	997
3.2.216. proxy POST requests to Service	997
3.2.216.1. Parameters	997
3.2.216.2. Responses	998
3.2.216.3. Consumes	998
3.2.216.4. Produces	998
3.2.216.5. Tags	998
3.2.217. proxy PUT requests to Service	998
3.2.217.1. Parameters	998
3.2.217.2. Responses	998
3.2.217.3. Consumes	998
3.2.217.4. Produces	999
3.2.217.5. Tags	999
3.2.218. proxy GET requests to Service	999
3.2.218.1. Parameters	999
3.2.218.2. Responses	999
3.2.218.3. Consumes	999
3.2.218.4. Produces	999

3.2.218.5. Tags	999
3.2.219. proxy HEAD requests to Service	999
3.2.219.1. Parameters	1000
3.2.219.2. Responses	1000
3.2.219.3. Consumes	1000
3.2.219.4. Produces	1000
3.2.219.5. Tags	1000
3.2.220. proxy DELETE requests to Node	1000
3.2.220.1. Parameters	1000
3.2.220.2. Responses	1000
3.2.220.3. Consumes	1001
3.2.220.4. Produces	1001
3.2.220.5. Tags	1001
3.2.221. proxy OPTIONS requests to Node	1001
3.2.221.1. Parameters	1001
3.2.221.2. Responses	1001
3.2.221.3. Consumes	1001
3.2.221.4. Produces	1001
3.2.221.5. Tags	1001
3.2.222. proxy POST requests to Node	1001
3.2.222.1. Parameters	1002
3.2.222.2. Responses	1002
3.2.222.3. Consumes	1002
3.2.222.4. Produces	1002
3.2.222.5. Tags	1002
3.2.223. proxy PUT requests to Node	1002
3.2.223.1. Parameters	1002
3.2.223.2. Responses	1002
3.2.223.3. Consumes	1002
3.2.223.4. Produces	1003
3.2.223.5. Tags	1003
3.2.224. proxy GET requests to Node	1003
3.2.224.1. Parameters	1003
3.2.224.2. Responses	1003
3.2.224.3. Consumes	1003
3.2.224.4. Produces	1003
3.2.224.5. Tags	1003
3.2.225. proxy HEAD requests to Node	1003
3.2.225.1. Parameters	1003
3.2.225.2. Responses	1004
3.2.225.3. Consumes	1004
3.2.225.4. Produces	1004
3.2.225.5. Tags	1004
3.2.226. proxy DELETE requests to Node	1004
3.2.226.1. Parameters	1004
3.2.226.2. Responses	1004
3.2.226.3. Consumes	1004
3.2.226.4. Produces	1005
3.2.226.5. Tags	1005
3.2.227. proxy OPTIONS requests to Node	1005
3.2.227.1. Parameters	1005
3.2.227.2. Responses	1005
3.2.227.3. Consumes	1005

3.2.227.4. Produces	1005
3.2.227.5. Tags	1005
3.2.228. proxy POST requests to Node	1005
3.2.228.1. Parameters	1005
3.2.228.2. Responses	1006
3.2.228.3. Consumes	1006
3.2.228.4. Produces	1006
3.2.228.5. Tags	1006
3.2.229. proxy PUT requests to Node	1006
3.2.229.1. Parameters	1006
3.2.229.2. Responses	1006
3.2.229.3. Consumes	1007
3.2.229.4. Produces	1007
3.2.229.5. Tags	1007
3.2.230. proxy GET requests to Node	1007
3.2.230.1. Parameters	1007
3.2.230.2. Responses	1007
3.2.230.3. Consumes	1007
3.2.230.4. Produces	1007
3.2.230.5. Tags	1007
3.2.231. proxy HEAD requests to Node	1007
3.2.231.1. Parameters	1008
3.2.231.2. Responses	1008
3.2.231.3. Consumes	1008
3.2.231.4. Produces	1008
3.2.231.5. Tags	1008
3.2.232. create a ReplicationController	1008
3.2.232.1. Parameters	1008
3.2.232.2. Responses	1008
3.2.232.3. Consumes	1009
3.2.232.4. Produces	1009
3.2.232.5. Tags	1009
3.2.233. list or watch objects of kind ReplicationController	1009
3.2.233.1. Parameters	1009
3.2.233.2. Responses	1010
3.2.233.3. Consumes	1010
3.2.233.4. Produces	1010
3.2.233.5. Tags	1011
3.2.234. create a ResourceQuota	1011
3.2.234.1. Parameters	1011
3.2.234.2. Responses	1011
3.2.234.3. Consumes	1011
3.2.234.4. Produces	1011
3.2.234.5. Tags	1011
3.2.235. list or watch objects of kind ResourceQuota	1011
3.2.235.1. Parameters	1012
3.2.235.2. Responses	1012
3.2.235.3. Consumes	1013
3.2.235.4. Produces	1013
3.2.235.5. Tags	1013
3.2.236. create a Secret	1013
3.2.236.1. Parameters	1013
3.2.236.2. Responses	1013

3.2.236.3. Consumes	1013
3.2.236.4. Produces	1013
3.2.236.5. Tags	1014
3.2.237. list or watch objects of kind Secret	1014
3.2.237.1. Parameters	1014
3.2.237.2. Responses	1015
3.2.237.3. Consumes	1015
3.2.237.4. Produces	1015
3.2.237.5. Tags	1015
3.2.238. delete collection of SecurityContextConstraints	1015
3.2.238.1. Parameters	1015
3.2.238.2. Responses	1016
3.2.238.3. Consumes	1017
3.2.238.4. Produces	1017
3.2.238.5. Tags	1017
3.2.239. create a SecurityContextConstraints	1017
3.2.239.1. Parameters	1017
3.2.239.2. Responses	1017
3.2.239.3. Consumes	1017
3.2.239.4. Produces	1018
3.2.239.5. Tags	1018
3.2.240. list or watch objects of kind SecurityContextConstraints	1018
3.2.240.1. Parameters	1018
3.2.240.2. Responses	1019
3.2.240.3. Consumes	1019
3.2.240.4. Produces	1019
3.2.240.5. Tags	1019
3.2.241. delete a SecurityContextConstraints	1019
3.2.241.1. Parameters	1019
3.2.241.2. Responses	1020
3.2.241.3. Consumes	1020
3.2.241.4. Produces	1020
3.2.241.5. Tags	1020
3.2.242. partially update the specified SecurityContextConstraints	1020
3.2.242.1. Parameters	1020
3.2.242.2. Responses	1021
3.2.242.3. Consumes	1021
3.2.242.4. Produces	1021
3.2.242.5. Tags	1021
3.2.243. replace the specified SecurityContextConstraints	1021
3.2.243.1. Parameters	1021
3.2.243.2. Responses	1022
3.2.243.3. Consumes	1022
3.2.243.4. Produces	1022
3.2.243.5. Tags	1022
3.2.244. read the specified SecurityContextConstraints	1022
3.2.244.1. Parameters	1022
3.2.244.2. Responses	1023
3.2.244.3. Consumes	1023
3.2.244.4. Produces	1023
3.2.244.5. Tags	1023
3.2.245. create a ServiceAccount	1023
3.2.245.1. Parameters	1024

3.2.245.2. Responses	1024
3.2.245.3. Consumes	1024
3.2.245.4. Produces	1024
3.2.245.5. Tags	1024
3.2.246. list or watch objects of kind ServiceAccount	1024
3.2.246.1. Parameters	1024
3.2.246.2. Responses	1025
3.2.246.3. Consumes	1026
3.2.246.4. Produces	1026
3.2.246.5. Tags	1026
3.2.247. create a Service	1026
3.2.247.1. Parameters	1026
3.2.247.2. Responses	1026
3.2.247.3. Consumes	1026
3.2.247.4. Produces	1026
3.2.247.5. Tags	1027
3.2.248. list or watch objects of kind Service	1027
3.2.248.1. Parameters	1027
3.2.248.2. Responses	1028
3.2.248.3. Consumes	1028
3.2.248.4. Produces	1028
3.2.248.5. Tags	1028
3.2.249. watch individual changes to a list of ConfigMap	1028
3.2.249.1. Parameters	1028
3.2.249.2. Responses	1029
3.2.249.3. Consumes	1030
3.2.249.4. Produces	1030
3.2.249.5. Tags	1030
3.2.250. watch individual changes to a list of Endpoints	1030
3.2.250.1. Parameters	1030
3.2.250.2. Responses	1031
3.2.250.3. Consumes	1031
3.2.250.4. Produces	1031
3.2.250.5. Tags	1032
3.2.251. watch individual changes to a list of Event	1032
3.2.251.1. Parameters	1032
3.2.251.2. Responses	1033
3.2.251.3. Consumes	1033
3.2.251.4. Produces	1033
3.2.251.5. Tags	1033
3.2.252. watch individual changes to a list of LimitRange	1033
3.2.252.1. Parameters	1033
3.2.252.2. Responses	1034
3.2.252.3. Consumes	1035
3.2.252.4. Produces	1035
3.2.252.5. Tags	1035
3.2.253. watch individual changes to a list of Namespace	1035
3.2.253.1. Parameters	1035
3.2.253.2. Responses	1036
3.2.253.3. Consumes	1036
3.2.253.4. Produces	1036
3.2.253.5. Tags	1037
3.2.254. watch individual changes to a list of ConfigMap	1037

3.2.254.1. Parameters	1037
3.2.254.2. Responses	1038
3.2.254.3. Consumes	1038
3.2.254.4. Produces	1038
3.2.254.5. Tags	1038
3.2.255. watch changes to an object of kind ConfigMap	1039
3.2.255.1. Parameters	1039
3.2.255.2. Responses	1040
3.2.255.3. Consumes	1040
3.2.255.4. Produces	1040
3.2.255.5. Tags	1040
3.2.256. watch individual changes to a list of Endpoints	1040
3.2.256.1. Parameters	1040
3.2.256.2. Responses	1042
3.2.256.3. Consumes	1042
3.2.256.4. Produces	1042
3.2.256.5. Tags	1042
3.2.257. watch changes to an object of kind Endpoints	1042
3.2.257.1. Parameters	1042
3.2.257.2. Responses	1044
3.2.257.3. Consumes	1044
3.2.257.4. Produces	1044
3.2.257.5. Tags	1044
3.2.258. watch individual changes to a list of Event	1044
3.2.258.1. Parameters	1044
3.2.258.2. Responses	1045
3.2.258.3. Consumes	1046
3.2.258.4. Produces	1046
3.2.258.5. Tags	1046
3.2.259. watch changes to an object of kind Event	1046
3.2.259.1. Parameters	1046
3.2.259.2. Responses	1047
3.2.259.3. Consumes	1047
3.2.259.4. Produces	1048
3.2.259.5. Tags	1048
3.2.260. watch individual changes to a list of LimitRange	1048
3.2.260.1. Parameters	1048
3.2.260.2. Responses	1049
3.2.260.3. Consumes	1049
3.2.260.4. Produces	1049
3.2.260.5. Tags	1049
3.2.261. watch changes to an object of kind LimitRange	1049
3.2.261.1. Parameters	1050
3.2.261.2. Responses	1051
3.2.261.3. Consumes	1051
3.2.261.4. Produces	1051
3.2.261.5. Tags	1051
3.2.262. watch individual changes to a list of PersistentVolumeClaim	1051
3.2.262.1. Parameters	1051
3.2.262.2. Responses	1052
3.2.262.3. Consumes	1053
3.2.262.4. Produces	1053
3.2.262.5. Tags	1053

3.2.263. watch changes to an object of kind PersistentVolumeClaim	1053
3.2.263.1. Parameters	1053
3.2.263.2. Responses	1054
3.2.263.3. Consumes	1054
3.2.263.4. Produces	1055
3.2.263.5. Tags	1055
3.2.264. watch individual changes to a list of Pod	1055
3.2.264.1. Parameters	1055
3.2.264.2. Responses	1056
3.2.264.3. Consumes	1056
3.2.264.4. Produces	1056
3.2.264.5. Tags	1056
3.2.265. watch changes to an object of kind Pod	1056
3.2.265.1. Parameters	1057
3.2.265.2. Responses	1058
3.2.265.3. Consumes	1058
3.2.265.4. Produces	1058
3.2.265.5. Tags	1058
3.2.266. watch individual changes to a list of PodTemplate	1058
3.2.266.1. Parameters	1058
3.2.266.2. Responses	1059
3.2.266.3. Consumes	1060
3.2.266.4. Produces	1060
3.2.266.5. Tags	1060
3.2.267. watch changes to an object of kind PodTemplate	1060
3.2.267.1. Parameters	1060
3.2.267.2. Responses	1061
3.2.267.3. Consumes	1061
3.2.267.4. Produces	1062
3.2.267.5. Tags	1062
3.2.268. watch individual changes to a list of ReplicationController	1062
3.2.268.1. Parameters	1062
3.2.268.2. Responses	1063
3.2.268.3. Consumes	1063
3.2.268.4. Produces	1063
3.2.268.5. Tags	1063
3.2.269. watch changes to an object of kind ReplicationController	1063
3.2.269.1. Parameters	1064
3.2.269.2. Responses	1065
3.2.269.3. Consumes	1065
3.2.269.4. Produces	1065
3.2.269.5. Tags	1065
3.2.270. watch individual changes to a list of ResourceQuota	1065
3.2.270.1. Parameters	1065
3.2.270.2. Responses	1067
3.2.270.3. Consumes	1067
3.2.270.4. Produces	1067
3.2.270.5. Tags	1067
3.2.271. watch changes to an object of kind ResourceQuota	1067
3.2.271.1. Parameters	1067
3.2.271.2. Responses	1068
3.2.271.3. Consumes	1068
3.2.271.4. Produces	1069

3.2.271.5. Tags	1069
3.2.272. watch individual changes to a list of Secret	1069
3.2.272.1. Parameters	1069
3.2.272.2. Responses	1070
3.2.272.3. Consumes	1070
3.2.272.4. Produces	1070
3.2.272.5. Tags	1071
3.2.273. watch changes to an object of kind Secret	1071
3.2.273.1. Parameters	1071
3.2.273.2. Responses	1072
3.2.273.3. Consumes	1072
3.2.273.4. Produces	1072
3.2.273.5. Tags	1072
3.2.274. watch individual changes to a list of ServiceAccount	1073
3.2.274.1. Parameters	1073
3.2.274.2. Responses	1074
3.2.274.3. Consumes	1074
3.2.274.4. Produces	1074
3.2.274.5. Tags	1074
3.2.275. watch changes to an object of kind ServiceAccount	1074
3.2.275.1. Parameters	1074
3.2.275.2. Responses	1076
3.2.275.3. Consumes	1076
3.2.275.4. Produces	1076
3.2.275.5. Tags	1076
3.2.276. watch individual changes to a list of Service	1076
3.2.276.1. Parameters	1076
3.2.276.2. Responses	1077
3.2.276.3. Consumes	1078
3.2.276.4. Produces	1078
3.2.276.5. Tags	1078
3.2.277. watch changes to an object of kind Service	1078
3.2.277.1. Parameters	1078
3.2.277.2. Responses	1079
3.2.277.3. Consumes	1079
3.2.277.4. Produces	1080
3.2.277.5. Tags	1080
3.2.278. watch changes to an object of kind Namespace	1080
3.2.278.1. Parameters	1080
3.2.278.2. Responses	1081
3.2.278.3. Consumes	1081
3.2.278.4. Produces	1081
3.2.278.5. Tags	1081
3.2.279. watch individual changes to a list of Node	1081
3.2.279.1. Parameters	1082
3.2.279.2. Responses	1082
3.2.279.3. Consumes	1083
3.2.279.4. Produces	1083
3.2.279.5. Tags	1083
3.2.280. watch changes to an object of kind Node	1083
3.2.280.1. Parameters	1083
3.2.280.2. Responses	1084
3.2.280.3. Consumes	1084

3.2.280.4. Produces	1084
3.2.280.5. Tags	1085
3.2.281. watch individual changes to a list of PersistentVolumeClaim	1085
3.2.281.1. Parameters	1085
3.2.281.2. Responses	1086
3.2.281.3. Consumes	1086
3.2.281.4. Produces	1086
3.2.281.5. Tags	1086
3.2.282. watch individual changes to a list of PersistentVolume	1086
3.2.282.1. Parameters	1086
3.2.282.2. Responses	1087
3.2.282.3. Consumes	1088
3.2.282.4. Produces	1088
3.2.282.5. Tags	1088
3.2.283. watch changes to an object of kind PersistentVolume	1088
3.2.283.1. Parameters	1088
3.2.283.2. Responses	1089
3.2.283.3. Consumes	1089
3.2.283.4. Produces	1089
3.2.283.5. Tags	1090
3.2.284. watch individual changes to a list of Pod	1090
3.2.284.1. Parameters	1090
3.2.284.2. Responses	1091
3.2.284.3. Consumes	1091
3.2.284.4. Produces	1091
3.2.284.5. Tags	1091
3.2.285. watch individual changes to a list of PodTemplate	1091
3.2.285.1. Parameters	1091
3.2.285.2. Responses	1092
3.2.285.3. Consumes	1093
3.2.285.4. Produces	1093
3.2.285.5. Tags	1093
3.2.286. watch individual changes to a list of ReplicationController	1093
3.2.286.1. Parameters	1093
3.2.286.2. Responses	1094
3.2.286.3. Consumes	1094
3.2.286.4. Produces	1094
3.2.286.5. Tags	1095
3.2.287. watch individual changes to a list of ResourceQuota	1095
3.2.287.1. Parameters	1095
3.2.287.2. Responses	1096
3.2.287.3. Consumes	1096
3.2.287.4. Produces	1096
3.2.287.5. Tags	1096
3.2.288. watch individual changes to a list of Secret	1096
3.2.288.1. Parameters	1096
3.2.288.2. Responses	1097
3.2.288.3. Consumes	1098
3.2.288.4. Produces	1098
3.2.288.5. Tags	1098
3.2.289. watch individual changes to a list of SecurityContextConstraints	1098
3.2.289.1. Parameters	1098
3.2.289.2. Responses	1099

3.2.289.3. Consumes	1099
3.2.289.4. Produces	1099
3.2.289.5. Tags	1100
3.2.290. watch changes to an object of kind SecurityContextConstraints	1100
3.2.290.1. Parameters	1100
3.2.290.2. Responses	1101
3.2.290.3. Consumes	1101
3.2.290.4. Produces	1101
3.2.290.5. Tags	1101
3.2.291. watch individual changes to a list of ServiceAccount	1101
3.2.291.1. Parameters	1102
3.2.291.2. Responses	1103
3.2.291.3. Consumes	1103
3.2.291.4. Produces	1103
3.2.291.5. Tags	1103
3.2.292. watch individual changes to a list of Service	1103
3.2.292.1. Parameters	1103
3.2.292.2. Responses	1104
3.2.292.3. Consumes	1104
3.2.292.4. Produces	1104
3.2.292.5. Tags	1105
3.3. DEFINITIONS	1105
3.3.1. versioned.Event	1105
3.3.2. types.UID	1105
3.3.3. unversioned.APIResource	1105
3.3.4. unversioned.APIResourceList	1105
3.3.5. unversioned.LabelSelector	1106
3.3.6. unversioned.LabelSelectorRequirement	1107
3.3.7. unversioned.ListMeta	1108
3.3.8. unversioned.Patch	1109
3.3.9. unversioned.Status	1109
3.3.10. unversioned.StatusCause	1111
3.3.11. unversioned.StatusDetails	1112
3.3.12. v1.AWSElasticBlockStoreVolumeSource	1113
3.3.13. v1.AttachedVolume	1115
3.3.14. v1.AzureFileVolumeSource	1115
3.3.15. v1.Binding	1116
3.3.16. v1.Capabilities	1117
3.3.17. v1.Capability	1118
3.3.18. v1.CephFSVolumeSource	1118
3.3.19. v1.CinderVolumeSource	1119
3.3.20. v1.ComponentCondition	1120
3.3.21. v1.ComponentStatus	1121
3.3.22. v1.ComponentStatusList	1122
3.3.23. v1.ConfigMap	1124
3.3.24. v1.ConfigMapKeySelector	1125
3.3.25. v1.ConfigMapList	1125
3.3.26. v1.ConfigMapVolumeSource	1127
3.3.27. v1.Container	1127
3.3.28. v1.ContainerImage	1135
3.3.29. v1.ContainerPort	1135
3.3.30. v1.ContainerState	1136
3.3.31. v1.ContainerStateRunning	1137

3.3.32. v1.ContainerStateTerminated	1137
3.3.33. v1.ContainerStateWaiting	1137
3.3.34. v1.ContainerStatus	1138
3.3.35. v1.DaemonEndpoint	1139
3.3.36. v1.DeleteOptions	1140
3.3.37. v1.DeprecatedDownwardAPIVolumeFile	1141
3.3.38. v1.DeprecatedDownwardAPIVolumeSource	1142
3.3.39. v1.DownwardAPIVolumeFile	1142
3.3.40. v1.DownwardAPIVolumeSource	1143
3.3.41. v1.EmptyDirVolumeSource	1143
3.3.42. v1.EndpointAddress	1144
3.3.43. v1.EndpointPort	1145
3.3.44. v1.EndpointSubset	1145
3.3.45. v1.Endpoints	1146
3.3.46. v1.EndpointsList	1148
3.3.47. v1.EnvVar	1150
3.3.48. v1.EnvVarSource	1150
3.3.49. v1.Event	1151
3.3.50. v1.EventList	1153
3.3.51. v1.EventSource	1155
3.3.52. v1.ExecAction	1155
3.3.53. v1.FCVolumeSource	1155
3.3.54. v1.FSGroupStrategyOptions	1156
3.3.55. v1.FSType	1157
3.3.56. v1.FinalizerName	1157
3.3.57. v1.FlexVolumeSource	1157
3.3.58. v1.FlockerVolumeSource	1158
3.3.59. v1.GCEPersistentDiskVolumeSource	1158
3.3.60. v1.GitRepoVolumeSource	1160
3.3.61. v1.GlusterfsVolumeSource	1160
3.3.62. v1.HTTPGetAction	1161
3.3.63. v1.HTTPHeader	1162
3.3.64. v1.Handler	1162
3.3.65. v1.HostPathVolumeSource	1163
3.3.66. v1.IDRange	1163
3.3.67. v1.ISCSIVolumeSource	1164
3.3.68. v1.KeyToPath	1165
3.3.69. v1.Lifecycle	1165
3.3.70. v1.LimitRange	1166
3.3.71. v1.LimitRangeItem	1168
3.3.72. v1.LimitRangeList	1169
3.3.73. v1.LimitRangeSpec	1170
3.3.74. v1.LoadBalancerIngress	1170
3.3.75. v1.LoadBalancerStatus	1171
3.3.76. v1.LocalObjectReference	1171
3.3.77. v1.NFSVolumeSource	1172
3.3.78. v1.Namespace	1172
3.3.79. v1.NamespaceList	1174
3.3.80. v1.NamespaceSpec	1175
3.3.81. v1.NamespaceStatus	1176
3.3.82. v1.Node	1176
3.3.83. v1.NodeAddress	1178
3.3.84. v1.NodeCondition	1178

3.3.85. v1.NodeDaemonEndpoints	1179
3.3.86. v1.NodeList	1179
3.3.87. v1.NodeSpec	1181
3.3.88. v1.NodeStatus	1181
3.3.89. v1.NodeSystemInfo	1183
3.3.90. v1.ObjectFieldSelector	1184
3.3.91. v1.ObjectMeta	1185
3.3.92. v1.ObjectReference	1193
3.3.93. v1.OwnerReference	1195
3.3.94. v1.PersistentVolume	1196
3.3.95. v1.PersistentVolumeAccessMode	1198
3.3.96. v1.PersistentVolumeClaim	1198
3.3.97. v1.PersistentVolumeClaimList	1200
3.3.98. v1.PersistentVolumeClaimSpec	1202
3.3.99. v1.PersistentVolumeClaimStatus	1203
3.3.100. v1.PersistentVolumeClaimVolumeSource	1203
3.3.101. v1.PersistentVolumeList	1204
3.3.102. v1.PersistentVolumeSpec	1205
3.3.103. v1.PersistentVolumeStatus	1210
3.3.104. v1.Pod	1211
3.3.105. v1.PodCondition	1213
3.3.106. v1.PodList	1214
3.3.107. v1.PodSecurityContext	1215
3.3.108. v1.PodSpec	1218
3.3.109. v1.PodStatus	1224
3.3.110. v1.PodTemplate	1225
3.3.111. v1.PodTemplateList	1227
3.3.112. v1.PodTemplateSpec	1228
3.3.113. v1.Preconditions	1229
3.3.114. v1.Probe	1229
3.3.115. v1.RBDVolumeSource	1231
3.3.116. v1.ReplicationController	1233
3.3.117. v1.ReplicationControllerList	1235
3.3.118. v1.ReplicationControllerSpec	1236
3.3.119. v1.ReplicationControllerStatus	1238
3.3.120. v1.ResourceFieldSelector	1239
3.3.121. v1.ResourceQuota	1239
3.3.122. v1.ResourceQuotaList	1241
3.3.123. v1.ResourceQuotaScope	1242
3.3.124. v1.ResourceQuotaSpec	1242
3.3.125. v1.ResourceQuotaStatus	1243
3.3.126. v1.ResourceRequirements	1244
3.3.127. v1.RunAsUserStrategyOptions	1244
3.3.128. v1.SELinuxContextStrategyOptions	1245
3.3.129. v1.SELinuxOptions	1245
3.3.130. v1.Scale	1246
3.3.131. v1.ScaleSpec	1247
3.3.132. v1.ScaleStatus	1248
3.3.133. v1.Secret	1248
3.3.134. v1.SecretKeySelector	1250
3.3.135. v1.SecretList	1251
3.3.136. v1.SecretVolumeSource	1252
3.3.137. v1.SecurityContext	1253

3.3.138. v1.SecurityContextConstraints	1255
3.3.139. v1.SecurityContextConstraintsList	1261
3.3.140. v1.Service	1262
3.3.141. v1.ServiceAccount	1264
3.3.142. v1.ServiceAccountList	1266
3.3.143. v1.ServiceList	1268
3.3.144. v1.ServicePort	1269
3.3.145. v1.ServiceSpec	1272
3.3.146. v1.ServiceStatus	1277
3.3.147. v1.SupplementalGroupsStrategyOptions	1277
3.3.148. v1.TCPSocketAction	1278
3.3.149. v1.UniqueVolumeName	1278
3.3.150. v1.Volume	1278
3.3.151. v1.VolumeMount	1283
3.3.152. v1.VsphereVirtualDiskVolumeSource	1284
3.3.153. any	1284
CHAPTER 4. REVISION HISTORY: REST API REFERENCE	1285
4.1. TUE OCT 04 2016	1285
4.2. TUE SEP 27 2016	1285

CHAPTER 1. OVERVIEW

The OpenShift Container Platform distribution of Kubernetes includes the [Kubernetes v1 REST API](#) and the [OpenShift v1 REST API](#). These are RESTful APIs accessible via HTTP(s) on the OpenShift Container Platform master servers.

These REST APIs can be used to manage end-user applications, the cluster, and the users of the cluster.

1.1. AUTHENTICATION

API calls must be authenticated with an access token or X.509 certificate. See [Authentication](#) in the Architecture documentation for an overview.

This section highlights the token authentication method. With token authentication, a bearer token must be passed in as an [HTTP Authorization header](#). There are two types of access tokens: session and service account.

1.1.1. Session Tokens

A *session token* is short-lived, expiring within 24 hours by default. It represents a [user](#). After logging in, the session token may be obtained with the `oc whoami` command:

```
$ oc login -u test_user
Using project "test".
$ oc whoami --token
dIAo76N-W-GXK3S_w_KsC6DmH3MzP79zq7jbmQvCOUo
```

1.1.2. Service Account Tokens

Service account tokens are long-lived tokens. They are [JSON Web Token \(JWT\)](#) formatted tokens and are much longer strings than session tokens. See [Using a Service Account's Credentials Externally](#) for steps on using these tokens to authenticate using the CLI.

A service account token may be obtained with these commands:

1. Create a service account in the current project (**test**) named **robot**:

```
$ oc create serviceaccount robot
serviceaccount "robot" created
```

2. Grant a role to the service account. In this example, assign the **robot** service account in the **test** project the **admin** role:

```
$ oc policy add-role-to-user admin system:serviceaccount:test:robot
```

3. Describe the service account to discover the secret token name:

```
$ oc describe serviceaccount robot
Name: robot
Namespace: test
Labels: <none>
```

```

Image pull secrets: robot-dockercfg-rdrpg

Mountable secrets:  robot-token-2dsne
                   robot-dockercfg-rdrpg

Tokens:            robot-token-2dsne
                   robot-token-9efwm

```

- Describe the secret token to get the token value:

```

$ oc describe secret robot-token-2dsne
Name:      robot-token-2dsne
Namespace: test
Labels:    <none>
Annotations: kubernetes.io/service-
account.name=robot,kubernetes.io/service-account.uid=ea70e4c7-0663-
11e6-b279-fa163e610e01

Type: kubernetes.io/service-account-token

Data
====
token:  fyJhbGciOiJSUzI1NiIyInR5cCI2IkpXVCJ9...
ca.crt: 1070 bytes
namespace: 8 bytes

```

The token value may be used in an authorization header to [authenticate API calls](#), the [CLI](#) or in the [docker login command](#). Service accounts may be created and deleted as needed with the appropriate role(s) assigned. See [Authorization](#) in the Architecture documentation for a deeper discussion on roles.

1.2. EXAMPLES

These examples are provided as a reference to provide quick success making REST API calls. They use insecure methods. In these examples a simple **GET** call is made to [list available resources](#).

1.2.1. cURL

Example 1.1. Request (Insecure)

```

$ curl -X GET -H "Authorization: Bearer <token>"
https://openshift.redhat.com:8443/oapi/v1 --insecure

```

Example 1.2. Result (Truncated)

```

{
  "kind": "APIResourceList",
  "groupVersion": "v1",
  "resources": [
    {
      "name": "buildconfigs",
      "namespaced": true,

```

```

    "kind": "BuildConfig"
  },
  {
    "name": "buildconfigs/instantiate",
    "namespaced": true,
    "kind": "BuildRequest"
  },
  {
    "name": "buildconfigs/instantiatebinary",
    "namespaced": true,
    "kind": "BinaryBuildRequestOptions"
  },
  {
    "name": "buildconfigs/webhooks",
    "namespaced": true,
    "kind": "Status"
  },
  {
    "name": "builds",
    "namespaced": true,
    "kind": "Build"
  },
  ...
  {
    "name": "subjectaccessreviews",
    "namespaced": true,
    "kind": "SubjectAccessReview"
  },
  {
    "name": "templates",
    "namespaced": true,
    "kind": "Template"
  },
  {
    "name": "useridentitymappings",
    "namespaced": false,
    "kind": "UserIdentityMapping"
  },
  {
    "name": "users",
    "namespaced": false,
    "kind": "User"
  }
]
}

```

1.2.2. Python

Example 1.3. Interactive Python API Call Using "requests" Module (Insecure)

```

>>> import requests
>>> url = 'https://openshift.redhat.com:8443/oapi/v1'
>>> headers = {'Authorization': 'Bearer dIAo76N-W-
GXX3S_w_KsC6DmH3MzP79zq7jbMQvCOUo'}

```

```
>>> requests.get(url, headers=headers, verify=False)
/usr/lib/python2.7/site-
packages/requests/packages/urllib3/connectionpool.py:791:
InsecureRequestWarning: Unverified HTTPS request is being made. Adding
certificate verification is strongly advised. See:
https://urllib3.readthedocs.org/en/latest/security.html
    InsecureRequestWarning)
<Response [200]>
```

1.2.3. Docker Login

The OpenShift Container Platform integrated Docker registry must be authenticated using either a [user session](#) or [service account](#) token. The value of the token must be used as the value for the **--password** argument. The user and email argument values are ignored:

```
$ docker login -p <token_value> -u unused -e unused <registry>[:<port>]
```

1.3. WEBSOCKETS AND WATCHING FOR CHANGES

The API is designed to work via the [websocket protocol](#). API requests may take the form of "one-shot" calls to list resources or by passing in query parameter **watch=true**. When watching an endpoint, changes to the system may be observed through an open endpoint. Using callbacks, dynamic systems may be developed that integrate with the API.

For more information and examples, see the Mozilla Developer Network page on [Writing WebSocket client applications](#).

CHAPTER 2. OPENSIFT CONTAINER PLATFORM V1 REST API

2.1. OVERVIEW

The OpenShift Container Platform API exposes operations for managing an enterprise Kubernetes cluster, including security and user management, application deployments, image and source builds, HTTP(s) routing, and project management.

2.1.1. Version information

Version: v1

2.1.2. URI scheme

Host: 127.0.0.1:8443 BasePath: / Schemes: HTTPS

2.2. PATHS

2.2.1. get available resources

GET /oapi/v1

2.2.1.1. Responses

HTTP Code	Description	Schema
default	success	Section 2.3.6 , "unversioned.APIResourceList"

2.2.1.2. Consumes

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.1.3. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.1.4. Tags

- oapiv1

2.2.2. list objects of kind `AppliedClusterResourceQuota`

GET `/oapi/v1/appliedclusterresourcequotas`

2.2.2.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamet er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParamet er	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	
QueryParamet er	resourceVersio n	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParamet er	timeoutSecond s	Timeout for the list/watch call.	false	integer	

2.2.2.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.16, “v1.AppliedClusterResourceQuota List”

2.2.2.3. Consumes

- /

2.2.2.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.2.5. Tags

- oapiv1

2.2.3. create a BuildConfig

POST /oapi/v1/buildconfigs

2.2.3.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 2.3.20, “v1.BuildConfi g”	

2.2.3.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.20, "v1.BuildConfig"

2.2.3.3. Consumes

- /

2.2.3.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.3.5. Tags

- oapiv1

2.2.4. list or watch objects of kind BuildConfig

GET /oapi/v1/buildconfigs

2.2.4.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamet er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParamet er	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersio n.	false	boolean	
QueryParamet er	resourceVersio n	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	
QueryParamet er	timeoutSecond s	Timeout for the list/watch call.	false	integer	

2.2.4.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.21, "v1.BuildConfigList"

2.2.4.3. Consumes

- /

2.2.4.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.4.5. Tags

- oapiv1

2.2.5. create a Build

POST /oapi/v1/builds

2.2.5.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 2.3.19, "v1.Build"	

2.2.5.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.19, "v1.Build"

2.2.5.3. Consumes

- /

2.2.5.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.5.5. Tags

- oapiv1

2.2.6. list or watch objects of kind Build

GET /oapi/v1/builds

2.2.6.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamet er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParamet er	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	
QueryParamet er	resourceVersio n	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	
QueryParamet er	timeoutSecond s	Timeout for the list/watch call.	false	integer	

2.2.6.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.24, "v1.BuildList"

2.2.6.3. Consumes

- /

2.2.6.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.6.5. Tags

- oapiv1

2.2.7. delete collection of ClusterNetwork

DELETE /oapi/v1/clusternetworks

2.2.7.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamet er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParamet er	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersio n.	false	boolean	
QueryParamet er	resourceVersio n	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	
QueryParamet er	timeoutSecond s	Timeout for the list/watch call.	false	integer	

2.2.7.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.11 , “unversioned.Status”

2.2.7.3. Consumes

- /

2.2.7.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.7.5. Tags

- oapiv1

2.2.8. create a ClusterNetwork

POST /oapi/v1/clusternetworks

2.2.8.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 2.3.39, "v1.ClusterNetwork"	

2.2.8.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.39, "v1.ClusterNetwork"

2.2.8.3. Consumes

- /

2.2.8.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.8.5. Tags

- oapiv1

2.2.9. list or watch objects of kind ClusterNetwork

GET /oapi/v1/clusternetworks

2.2.9.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamet er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParamet er	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersio n.	false	boolean	
QueryParamet er	resourceVersio n	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	
QueryParamet er	timeoutSecond s	Timeout for the list/watch call.	false	integer	

2.2.9.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.40 , "v1.ClusterNetworkList"

2.2.9.3. Consumes

- /

2.2.9.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.9.5. Tags

- oapiv1

2.2.10. delete a ClusterNetwork

```
DELETE /oapi/v1/clusternetworks/{name}
```

2.2.10.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 2.3.61 , "v1.DeleteOpti ons"	
PathParameter	name	name of the ClusterNetwork	true	string	

2.2.10.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.11 , "unversioned.Status"

2.2.10.3. Consumes

- /

2.2.10.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.10.5. Tags

- oapiv1

2.2.11. partially update the specified ClusterNetwork

PATCH /oapi/v1/clusternetworks/{name}

2.2.11.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 2.3.10, "unversioned.Patch"	
PathParameter	name	name of the ClusterNetwork	true	string	

2.2.11.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.39, "v1.ClusterNetwork"

2.2.11.3. Consumes

- application/json-patch+json
- application/merge-patch+json
- application/strategic-merge-patch+json

2.2.11.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.11.5. Tags

- oapiv1

2.2.12. replace the specified ClusterNetwork

```
PUT /oapi/v1/clusternetworks/{name}
```

2.2.12.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParameter	body		true	Section 2.3.39, "v1.ClusterNetwork"	
PathParameter	name	name of the ClusterNetwork	true	string	

2.2.12.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.39, "v1.ClusterNetwork"

2.2.12.3. Consumes

- /

2.2.12.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.12.5. Tags

- oapiv1

2.2.13. read the specified ClusterNetwork

```
GET /oapi/v1/clusternetworks/{name}
```

2.2.13.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	export	Should this value be exported. Export strips fields that a user can not specify.	false	boolean	
QueryParamet er	exact	Should the export be exact. Exact export maintains cluster-specific fields like 'Namespace'	false	boolean	
PathParamet er	name	name of the ClusterNetwork	true	string	

2.2.13.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.39, "v1.ClusterNetwork"

2.2.13.3. Consumes

- /

2.2.13.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.13.5. Tags

- oapiv1

2.2.14. delete collection of ClusterPolicy

```
DELETE /oapi/v1/clusterpolicies
```

2.2.14.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamet er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParamet er	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParam er	resourceVersio n	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	
QueryParam er	timeoutSecond s	Timeout for the list/watch call.	false	integer	

2.2.14.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.11 , “unversioned.Status”

2.2.14.3. Consumes

- /

2.2.14.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.14.5. Tags

- oapiv1

2.2.15. create a ClusterPolicy

```
POST /oapi/v1/clusterpolicies
```

2.2.15.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 2.3.41, "v1.ClusterPolicy"	

2.2.15.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.41, "v1.ClusterPolicy"

2.2.15.3. Consumes

- /

2.2.15.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.15.5. Tags

- oapiv1

2.2.16. list or watch objects of kind ClusterPolicy

GET /oapi/v1/clusterpolicies

2.2.16.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParamet er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamet er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParamet er	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	
QueryParamet er	resourceVersio n	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	
QueryParamet er	timeoutSecond s	Timeout for the list/watch call.	false	integer	

2.2.16.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.44 , "v1.ClusterPolicyList"

2.2.16.3. Consumes

- /

2.2.16.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.16.5. Tags

- oapiv1

2.2.17. delete a ClusterPolicy

```
DELETE /oapi/v1/clusterpolicies/{name}
```

2.2.17.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 2.3.61 , "v1.DeleteOpti ons"	
PathParameter	name	name of the ClusterPolicy	true	string	

2.2.17.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.11 , "unversioned.Status"

2.2.17.3. Consumes

- /

2.2.17.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.17.5. Tags

- oapiv1

2.2.18. partially update the specified ClusterPolicy

PATCH /oapi/v1/clusterpolicies/{name}

2.2.18.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 2.3.10, "unversioned.Patch"	
PathParameter	name	name of the ClusterPolicy	true	string	

2.2.18.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.41, "v1.ClusterPolicy"

2.2.18.3. Consumes

- application/json-patch+json
- application/merge-patch+json
- application/strategic-merge-patch+json

2.2.18.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.18.5. Tags

- oapiv1

2.2.19. replace the specified ClusterPolicy

```
PUT /oapi/v1/clusterpolicies/{name}
```

2.2.19.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParameter	body		true	Section 2.3.41, "v1.ClusterPolicy"	
PathParameter	name	name of the ClusterPolicy	true	string	

2.2.19.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.41, "v1.ClusterPolicy"

2.2.19.3. Consumes

- /

2.2.19.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.19.5. Tags

- oapiv1

2.2.20. read the specified ClusterPolicy

```
GET /oapi/v1/clusterpolicies/{name}
```

2.2.20.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	export	Should this value be exported. Export strips fields that a user can not specify.	false	boolean	
QueryParamet er	exact	Should the export be exact. Exact export maintains cluster-specific fields like 'Namespace'	false	boolean	
PathParamet er	name	name of the ClusterPolicy	true	string	

2.2.20.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.41, "v1.ClusterPolicy"

2.2.20.3. Consumes

- /

2.2.20.4. Produces

- application/json

- application/yaml
- application/vnd.kubernetes.protobuf

2.2.20.5. Tags

- oapiv1

2.2.21. delete collection of ClusterPolicyBinding

DELETE /oapi/v1/clusterpolicybindings

2.2.21.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamet er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParamet er	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParam er	resourceVersio n	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	
QueryParam er	timeoutSecond s	Timeout for the list/watch call.	false	integer	

2.2.21.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.11 , “unversioned.Status”

2.2.21.3. Consumes

- /

2.2.21.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.21.5. Tags

- oapiv1

2.2.22. create a ClusterPolicyBinding

```
POST /oapi/v1/clusterpolicybindings
```

2.2.22.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 2.3.42, "v1.ClusterPolicyBinding"	

2.2.22.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.42, "v1.ClusterPolicyBinding"

2.2.22.3. Consumes

- /

2.2.22.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.22.5. Tags

- oapiv1

2.2.23. list or watch objects of kind ClusterPolicyBinding

```
GET /oapi/v1/clusterpolicybindings
```

2.2.23.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParam er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParam er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParam er	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	
QueryParam er	resourceVersion	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	
QueryParam er	timeoutSeconds	Timeout for the list/watch call.	false	integer	

2.2.23.2. Responses

HTTP Code	Description	Schema
-----------	-------------	--------

HTTP Code	Description	Schema
200	success	Section 2.3.43 , “v1.ClusterPolicyBindingList”

2.2.23.3. Consumes

- /

2.2.23.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.23.5. Tags

- oapiv1

2.2.24. delete a ClusterPolicyBinding

```
DELETE /oapi/v1/clusterpolicybindings/{name}
```

2.2.24.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 2.3.61 , “v1.DeleteOpti ons”	
PathParameter	name	name of the ClusterPolicyBi nding	true	string	

2.2.24.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.11 , “unversioned.Status”

2.2.24.3. Consumes

- /

2.2.24.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.24.5. Tags

- oapiv1

2.2.25. partially update the specified ClusterPolicyBinding

PATCH /oapi/v1/clusterpolicybindings/{name}

2.2.25.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 2.3.10, "unversioned.Patch"	
PathParameter	name	name of the ClusterPolicyBinding	true	string	

2.2.25.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.42, "v1.ClusterPolicyBinding"

2.2.25.3. Consumes

- application/json-patch+json
- application/merge-patch+json
- application/strategic-merge-patch+json

2.2.25.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.25.5. Tags

- oapiv1

2.2.26. replace the specified ClusterPolicyBinding

```
PUT /oapi/v1/clusterpolicybindings/{name}
```

2.2.26.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParameter	body		true	Section 2.3.42, "v1.ClusterPolicyBinding"	
PathParameter	name	name of the ClusterPolicyBinding	true	string	

2.2.26.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.42, "v1.ClusterPolicyBinding"

2.2.26.3. Consumes

- /

2.2.26.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.26.5. Tags

- oapiv1

2.2.27. read the specified ClusterPolicyBinding

```
GET /oapi/v1/clusterpolicybindings/{name}
```

2.2.27.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParameter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParameter	export	Should this value be exported. Export strips fields that a user can not specify.	false	boolean	
QueryParameter	exact	Should the export be exact. Exact export maintains cluster-specific fields like 'Namespace'	false	boolean	
PathParameter	name	name of the ClusterPolicyBinding	true	string	

2.2.27.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.42, "v1.ClusterPolicyBinding"

2.2.27.3. Consumes

- /

2.2.27.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.27.5. Tags

- oapiv1

2.2.28. delete collection of ClusterResourceQuota

```
DELETE /oapi/v1/clusterresourcequotas
```

2.2.28.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamet er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParamet er	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParamet er	resourceVersio n	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	
QueryParamet er	timeoutSecond s	Timeout for the list/watch call.	false	integer	

2.2.28.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.11 , “unversioned.Status”

2.2.28.3. Consumes

- /

2.2.28.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.28.5. Tags

- oapiv1

2.2.29. create a ClusterResourceQuota

POST /oapi/v1/clusterresourcequotas

2.2.29.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 2.3.45, "v1.ClusterResourceQuota"	

2.2.29.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.45, "v1.ClusterResourceQuota"

2.2.29.3. Consumes

- /

2.2.29.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.29.5. Tags

- oapiv1

2.2.30. list or watch objects of kind ClusterResourceQuota

GET /oapi/v1/clusterresourcequotas

2.2.30.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParam er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParam er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParam er	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	
QueryParam er	resourceVersion	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	
QueryParam er	timeoutSeconds	Timeout for the list/watch call.	false	integer	

2.2.30.2. Responses

HTTP Code	Description	Schema
-----------	-------------	--------

HTTP Code	Description	Schema
200	success	Section 2.3.46 , "v1.ClusterResourceQuotaList"

2.2.30.3. Consumes

- /

2.2.30.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.30.5. Tags

- oapiv1

2.2.31. delete a ClusterResourceQuota

```
DELETE /oapi/v1/clusterresourcequotas/{name}
```

2.2.31.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 2.3.61 , "v1.DeleteOpti ons"	
PathParameter	name	name of the ClusterResour ceQuota	true	string	

2.2.31.2. Responses

HTTP Code	Description	Schema
-----------	-------------	--------

HTTP Code	Description	Schema
200	success	Section 2.3.11 , “unversioned.Status”

2.2.31.3. Consumes

- /

2.2.31.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.31.5. Tags

- oapiv1

2.2.32. partially update the specified ClusterResourceQuota

```
PATCH /oapi/v1/clusterresourcequotas/{name}
```

2.2.32.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 2.3.10 , “unversioned.P atch”	
PathParameter	name	name of the ClusterResourceQuota	true	string	

2.2.32.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.45 , “v1.ClusterResourceQuota”

2.2.32.3. Consumes

- application/json-patch+json
- application/merge-patch+json
- application/strategic-merge-patch+json

2.2.32.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.32.5. Tags

- oapiv1

2.2.33. replace the specified ClusterResourceQuota

```
PUT /oapi/v1/clusterresourcequotas/{name}
```

2.2.33.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 2.3.45, "v1.ClusterResourceQuota"	
PathParameter	name	name of the ClusterResourceQuota	true	string	

2.2.33.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.45, "v1.ClusterResourceQuota"

2.2.33.3. Consumes

- /

2.2.33.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.33.5. Tags

- oapiv1

2.2.34. read the specified ClusterResourceQuota

```
GET /oapi/v1/clusterresourcequotas/{name}
```

2.2.34.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	export	Should this value be exported. Export strips fields that a user can not specify.	false	boolean	
QueryParamet er	exact	Should the export be exact. Exact export maintains cluster-specific fields like 'Namespace'	false	boolean	
PathParameter	name	name of the ClusterResourceQuota	true	string	

2.2.34.2. Responses

HTTP Code	Description	Schema
-----------	-------------	--------

HTTP Code	Description	Schema
200	success	Section 2.3.45, "v1.ClusterResourceQuota"

2.2.34.3. Consumes

- /

2.2.34.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.34.5. Tags

- oapiv1

2.2.35. partially update status of the specified ClusterResourceQuota

```
PATCH /oapi/v1/clusterresourcequotas/{name}/status
```

2.2.35.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 2.3.10, "unversioned.Patch"	
PathParameter	name	name of the ClusterResourceQuota	true	string	

2.2.35.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.45, "v1.ClusterResourceQuota"

2.2.35.3. Consumes

- application/json-patch+json
- application/merge-patch+json
- application/strategic-merge-patch+json

2.2.35.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.35.5. Tags

- oapiv1

2.2.36. replace status of the specified ClusterResourceQuota

```
PUT /oapi/v1/clusterresourcequotas/{name}/status
```

2.2.36.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 2.3.45, "v1.ClusterResourceQuota"	
PathParameter	name	name of the ClusterResourceQuota	true	string	

2.2.36.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.45, "v1.ClusterResourceQuota"

2.2.36.3. Consumes

- /

2.2.36.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.36.5. Tags

- oapiv1

2.2.37. read status of the specified ClusterResourceQuota

```
GET /oapi/v1/clusterresourcequotas/{name}/status
```

2.2.37.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamter	pretty	If 'true', then the output is pretty printed.	false	string	
PathParameter	name	name of the ClusterResourceQuota	true	string	

2.2.37.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.45, "v1.ClusterResourceQuota"

2.2.37.3. Consumes

- /

2.2.37.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.37.5. Tags

- oapiv1

2.2.38. create a ClusterRoleBinding

POST /oapi/v1/clusterrolebindings

2.2.38.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 2.3.51, "v1.ClusterRoleBinding"	

2.2.38.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.51, "v1.ClusterRoleBinding"

2.2.38.3. Consumes

- /

2.2.38.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.38.5. Tags

- oapiv1

2.2.39. list objects of kind ClusterRoleBinding

GET /oapi/v1/clusterrolebindings

2.2.39.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamet er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParamet er	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	
QueryParamet er	resourceVersio n	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	
QueryParamet er	timeoutSecond s	Timeout for the list/watch call.	false	integer	

2.2.39.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.52 , “v1.ClusterRoleBindingList”

2.2.39.3. Consumes

- /

2.2.39.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.39.5. Tags

- oapiv1

2.2.40. delete a ClusterRoleBinding

```
DELETE /oapi/v1/clusterrolebindings/{name}
```

2.2.40.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 2.3.61 , “v1.DeleteOpti ons”	
PathParameter	name	name of the ClusterRoleBin ding	true	string	

2.2.40.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.11 , “unversioned.Status”

2.2.40.3. Consumes

- /

2.2.40.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.40.5. Tags

- oapiv1

2.2.41. partially update the specified ClusterRoleBinding

PATCH /oapi/v1/clusterrolebindings/{name}

2.2.41.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 2.3.10, "unversioned.Patch"	
PathParameter	name	name of the ClusterRoleBin ding	true	string	

2.2.41.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.51, "v1.ClusterRoleBinding"

2.2.41.3. Consumes

- application/json-patch+json
- application/merge-patch+json
- application/strategic-merge-patch+json

2.2.41.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.41.5. Tags

- oapiv1

2.2.42. replace the specified ClusterRoleBinding

```
PUT /oapi/v1/clusterrolebindings/{name}
```

2.2.42.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParameter	body		true	Section 2.3.51, "v1.ClusterRoleBinding"	
PathParameter	name	name of the ClusterRoleBinding	true	string	

2.2.42.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.51, "v1.ClusterRoleBinding"

2.2.42.3. Consumes

- /

2.2.42.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.42.5. Tags

- oapiv1

2.2.43. read the specified ClusterRoleBinding

```
GET /oapi/v1/clusterrolebindings/{name}
```

2.2.43.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
PathParameter	name	name of the ClusterRoleBin ding	true	string	

2.2.43.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.51 , "v1.ClusterRoleBinding"

2.2.43.3. Consumes

- /

2.2.43.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.43.5. Tags

- oapiv1

2.2.44. create a ClusterRole

```
POST /oapi/v1/clusterroles
```

2.2.44.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 2.3.50, "v1.ClusterRole"	

2.2.44.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.50, "v1.ClusterRole"

2.2.44.3. Consumes

- /

2.2.44.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.44.5. Tags

- oapiv1

2.2.45. list objects of kind ClusterRole

```
GET /oapi/v1/clusterroles
```

2.2.45.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParamet er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamet er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParamet er	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	
QueryParamet er	resourceVersion	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	
QueryParamet er	timeoutSeconds	Timeout for the list/watch call.	false	integer	

2.2.45.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.53, "v1.ClusterRoleList"

2.2.45.3. Consumes

- /

2.2.45.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.45.5. Tags

- oapiv1

2.2.46. delete a ClusterRole

```
DELETE /oapi/v1/clusterroles/{name}
```

2.2.46.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 2.3.61, "v1.DeleteOptions"	
PathParameter	name	name of the ClusterRole	true	string	

2.2.46.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.11, "unversioned.Status"

2.2.46.3. Consumes

- /

2.2.46.4. Produces

- application/json

- application/yaml
- application/vnd.kubernetes.protobuf

2.2.46.5. Tags

- oapiv1

2.2.47. partially update the specified ClusterRole

```
PATCH /oapi/v1/clusterroles/{name}
```

2.2.47.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 2.3.10, "unversioned.Patch"	
PathParameter	name	name of the ClusterRole	true	string	

2.2.47.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.50, "v1.ClusterRole"

2.2.47.3. Consumes

- application/json-patch+json
- application/merge-patch+json
- application/strategic-merge-patch+json

2.2.47.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.47.5. Tags

- oapiv1

2.2.48. replace the specified ClusterRole

```
PUT /oapi/v1/clusterroles/{name}
```

2.2.48.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 2.3.50, "v1.ClusterRole"	
PathParameter	name	name of the ClusterRole	true	string	

2.2.48.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.50, "v1.ClusterRole"

2.2.48.3. Consumes

- /

2.2.48.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.48.5. Tags

- oapiv1

2.2.49. read the specified ClusterRole

```
GET /oapi/v1/clusterroles/{name}
```

2.2.49.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
PathParameter	name	name of the ClusterRole	true	string	

2.2.49.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.50, "v1.ClusterRole"

2.2.49.3. Consumes

- /

2.2.49.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.49.5. Tags

- oapiv1

2.2.50. create a DeploymentConfigRollback

POST /oapi/v1/deploymentconfigrollbacks

2.2.50.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	

Type	Name	Description	Required	Schema	Default
BodyParameter	body		true	Section 2.3.66, "v1.DeploymentConfigRollback"	

2.2.50.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.66, "v1.DeploymentConfigRollback"

2.2.50.3. Consumes

- /

2.2.50.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.50.5. Tags

- oapiv1

2.2.51. create a DeploymentConfig

POST /oapi/v1/deploymentconfigs

2.2.51.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParameter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParameter	body		true	Section 2.3.64, "v1.DeploymentConfig"	

2.2.51.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.64, "v1.DeploymentConfig"

2.2.51.3. Consumes

- /

2.2.51.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.51.5. Tags

- oapiv1

2.2.52. list or watch objects of kind DeploymentConfig

```
GET /oapi/v1/deploymentconfigs
```

2.2.52.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamet er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParamet er	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersio n.	false	boolean	
QueryParamet er	resourceVersio n	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	
QueryParamet er	timeoutSecond s	Timeout for the list/watch call.	false	integer	

2.2.52.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.65, "v1.DeploymentConfigList"

2.2.52.3. Consumes

- /

2.2.52.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.52.5. Tags

- oapiv1

2.2.53. create a EgressNetworkPolicy

POST /oapi/v1/egressnetworkpolicies

2.2.53.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 2.3.80, "v1.EgressNetworkPolicy"	

2.2.53.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.80, "v1.EgressNetworkPolicy"

2.2.53.3. Consumes

- /

2.2.53.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.53.5. Tags

- oapiv1

2.2.54. list or watch objects of kind EgressNetworkPolicy

GET /oapi/v1/egressnetworkpolicies

2.2.54.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamet er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParamet er	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersio n.	false	boolean	
QueryParamet er	resourceVersio n	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	
QueryParamet er	timeoutSecond s	Timeout for the list/watch call.	false	integer	

2.2.54.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.81 , "v1.EgressNetworkPolicyList"

2.2.54.3. Consumes

- /

2.2.54.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.54.5. Tags

- oapiv1

2.2.55. delete collection of Group

```
DELETE /oapi/v1/groups
```

2.2.55.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamet er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParamet er	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersio n.	false	boolean	
QueryParamet er	resourceVersio n	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	
QueryParamet er	timeoutSecond s	Timeout for the list/watch call.	false	integer	

2.2.55.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.11 , “unversioned.Status”

2.2.55.3. Consumes

- /

2.2.55.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.55.5. Tags

- oapiv1

2.2.56. create a Group

POST /oapi/v1/groups

2.2.56.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 2.3.101, "v1.Group"	

2.2.56.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.101, "v1.Group"

2.2.56.3. Consumes

- /

2.2.56.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.56.5. Tags

- oapiv1

2.2.57. list or watch objects of kind Group

GET /oapi/v1/groups

2.2.57.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamet er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParamet er	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	
QueryParamet er	resourceVersio n	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	
QueryParamet er	timeoutSecond s	Timeout for the list/watch call.	false	integer	

2.2.57.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.102, "v1.GroupList"

2.2.57.3. Consumes

- /

2.2.57.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.57.5. Tags

- oapiv1

2.2.58. delete a Group

```
DELETE /oapi/v1/groups/{name}
```

2.2.58.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 2.3.61, "v1.DeleteOptions"	
PathParameter	name	name of the Group	true	string	

2.2.58.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.11, "unversioned.Status"

2.2.58.3. Consumes

- /

2.2.58.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.58.5. Tags

- oapiv1

2.2.59. partially update the specified Group

```
PATCH /oapi/v1/groups/{name}
```

2.2.59.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 2.3.10, "unversioned.Patch"	
PathParameter	name	name of the Group	true	string	

2.2.59.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.101, "v1.Group"

2.2.59.3. Consumes

- application/json-patch+json
- application/merge-patch+json
- application/strategic-merge-patch+json

2.2.59.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.59.5. Tags

- oapiv1

2.2.60. replace the specified Group

```
PUT /oapi/v1/groups/{name}
```

2.2.60.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParameter	body		true	Section 2.3.101, "v1.Group"	
PathParameter	name	name of the Group	true	string	

2.2.60.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.101, "v1.Group"

2.2.60.3. Consumes

- /

2.2.60.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.60.5. Tags

- oapiv1

2.2.61. read the specified Group

```
GET /oapi/v1/groups/{name}
```

2.2.61.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	export	Should this value be exported. Export strips fields that a user can not specify.	false	boolean	
QueryParamet er	exact	Should the export be exact. Exact export maintains cluster-specific fields like 'Namespace'	false	boolean	
PathParameter	name	name of the Group	true	string	

2.2.61.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.101, "v1.Group"

2.2.61.3. Consumes

- /

2.2.61.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.61.5. Tags

- oapiv1

2.2.62. delete collection of HostSubnet

```
DELETE /oapi/v1/hostsubnets
```

2.2.62.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamet er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParamet er	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParamet er	resourceVersio n	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	
QueryParamet er	timeoutSecond s	Timeout for the list/watch call.	false	integer	

2.2.62.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.11, “unversioned.Status”

2.2.62.3. Consumes

- /

2.2.62.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.62.5. Tags

- oapiv1

2.2.63. create a HostSubnet

POST /oapi/v1/hostsubnets

2.2.63.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 2.3.107 , "v1.HostSubne t"	

2.2.63.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.107 , "v1.HostSubnet"

2.2.63.3. Consumes

- /

2.2.63.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.63.5. Tags

- oapiv1

2.2.64. list or watch objects of kind HostSubnet

```
GET /oapi/v1/hostsubnets
```

2.2.64.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParamet er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamet er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParamet er	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersio n.	false	boolean	
QueryParamet er	resourceVersio n	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	
QueryParamet er	timeoutSecond s	Timeout for the list/watch call.	false	integer	

2.2.64.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.108 , "v1.HostSubnetList"

2.2.64.3. Consumes

- /

2.2.64.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.64.5. Tags

- oapiv1

2.2.65. delete a HostSubnet

```
DELETE /oapi/v1/hostsubnets/{name}
```

2.2.65.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 2.3.61 , "v1.DeleteOpti ons"	
PathParameter	name	name of the HostSubnet	true	string	

2.2.65.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.11 , "unversioned.Status"

2.2.65.3. Consumes

- /

2.2.65.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.65.5. Tags

- oapiv1

2.2.66. partially update the specified HostSubnet

PATCH /oapi/v1/hostsubnets/{name}

2.2.66.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 2.3.10, "unversioned.Patch"	
PathParameter	name	name of the HostSubnet	true	string	

2.2.66.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.107, "v1.HostSubnet"

2.2.66.3. Consumes

- application/json-patch+json
- application/merge-patch+json
- application/strategic-merge-patch+json

2.2.66.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.66.5. Tags

- oapiv1

2.2.67. replace the specified HostSubnet

```
PUT /oapi/v1/hostsubnets/{name}
```

2.2.67.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParameter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParameter	body		true	Section 2.3.107 , "v1.HostSubnet"	
PathParameter	name	name of the HostSubnet	true	string	

2.2.67.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.107 , "v1.HostSubnet"

2.2.67.3. Consumes

- /

2.2.67.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.67.5. Tags

- oapiv1

2.2.68. read the specified HostSubnet

```
GET /oapi/v1/hostsubnets/{name}
```

2.2.68.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	export	Should this value be exported. Export strips fields that a user can not specify.	false	boolean	
QueryParamet er	exact	Should the export be exact. Exact export maintains cluster-specific fields like 'Namespace'	false	boolean	
PathParamet er	name	name of the HostSubnet	true	string	

2.2.68.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.107, "v1.HostSubnet"

2.2.68.3. Consumes

- /

2.2.68.4. Produces

- application/json

- application/yaml
- application/vnd.kubernetes.protobuf

2.2.68.5. Tags

- oapiv1

2.2.69. delete collection of Identity

DELETE /oapi/v1/identities

2.2.69.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamet er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParamet er	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParam er	resourceVersio n	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	
QueryParam er	timeoutSecond s	Timeout for the list/watch call.	false	integer	

2.2.69.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.11 , “unversioned.Status”

2.2.69.3. Consumes

- /

2.2.69.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.69.5. Tags

- oapiv1

2.2.70. create a Identity

POST /oapi/v1/identities

2.2.70.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 2.3.110, "v1.Identity"	

2.2.70.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.110, "v1.Identity"

2.2.70.3. Consumes

- /

2.2.70.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.70.5. Tags

- oapiv1

2.2.71. list or watch objects of kind Identity

GET /oapi/v1/identities

2.2.71.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParamet er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamet er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParamet er	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	
QueryParamet er	resourceVersio n	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	
QueryParamet er	timeoutSecond s	Timeout for the list/watch call.	false	integer	

2.2.71.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.111, "v1.IdentityList"

2.2.71.3. Consumes

- /

2.2.71.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.71.5. Tags

- oapiv1

2.2.72. delete a Identity

```
DELETE /oapi/v1/identities/{name}
```

2.2.72.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 2.3.61, "v1.DeleteOptions"	
PathParameter	name	name of the Identity	true	string	

2.2.72.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.11, "unversioned.Status"

2.2.72.3. Consumes

- /

2.2.72.4. Produces

- application/json

- application/yaml
- application/vnd.kubernetes.protobuf

2.2.72.5. Tags

- oapiv1

2.2.73. partially update the specified Identity

```
PATCH /oapi/v1/identities/{name}
```

2.2.73.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 2.3.10, "unversioned.Patch"	
PathParameter	name	name of the Identity	true	string	

2.2.73.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.110, "v1.Identity"

2.2.73.3. Consumes

- application/json-patch+json
- application/merge-patch+json
- application/strategic-merge-patch+json

2.2.73.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.73.5. Tags

- oapiv1

2.2.74. replace the specified Identity

```
PUT /oapi/v1/identities/{name}
```

2.2.74.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 2.3.110, "v1.Identity"	
PathParameter	name	name of the Identity	true	string	

2.2.74.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.110, "v1.Identity"

2.2.74.3. Consumes

- /

2.2.74.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.74.5. Tags

- oapiv1

2.2.75. read the specified Identity

```
GET /oapi/v1/identities/{name}
```

2.2.75.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	export	Should this value be exported. Export strips fields that a user can not specify.	false	boolean	
QueryParamet er	exact	Should the export be exact. Exact export maintains cluster-specific fields like 'Namespace'	false	boolean	
PathParameter	name	name of the Identity	true	string	

2.2.75.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.110, "v1.Identity"

2.2.75.3. Consumes

- /

2.2.75.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.75.5. Tags

- oapiv1

2.2.76. delete collection of Image

DELETE /oapi/v1/images

2.2.76.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamet er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParamet er	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	
QueryParamet er	resourceVersio n	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParamet er	timeoutSecond s	Timeout for the list/watch call.	false	integer	

2.2.76.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.11 , “unversioned.Status”

2.2.76.3. Consumes

- /

2.2.76.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.76.5. Tags

- oapiv1

2.2.77. create a Image

POST /oapi/v1/images

2.2.77.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 2.3.11 2, “v1.Image”	

2.2.77.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.112, "v1.Image"

2.2.77.3. Consumes

- /

2.2.77.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.77.5. Tags

- oapiv1

2.2.78. list or watch objects of kind Image

GET /oapi/v1/images

2.2.78.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamet er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParamet er	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	
QueryParamet er	resourceVersio n	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	
QueryParamet er	timeoutSecond s	Timeout for the list/watch call.	false	integer	

2.2.78.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.119, "v1.ImageList"

2.2.78.3. Consumes

- /

2.2.78.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.78.5. Tags

- oapiv1

2.2.79. delete a Image

```
DELETE /oapi/v1/images/{name}
```

2.2.79.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 2.3.61, "v1.DeleteOptions"	
PathParameter	name	name of the Image	true	string	

2.2.79.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.11, "unversioned.Status"

2.2.79.3. Consumes

- /

2.2.79.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.79.5. Tags

- oapiv1

2.2.80. partially update the specified Image

```
PATCH /oapi/v1/images/{name}
```


2.2.80.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 2.3.10, “unversioned.Patch”	
PathParameter	name	name of the Image	true	string	

2.2.80.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.112, “v1.Image”

2.2.80.3. Consumes

- application/json-patch+json
- application/merge-patch+json
- application/strategic-merge-patch+json

2.2.80.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.80.5. Tags

- oapiv1

2.2.81. replace the specified Image

```
PUT /oapi/v1/images/{name}
```

2.2.81.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 2.3.112, "v1.Image"	
PathParameter	name	name of the Image	true	string	

2.2.81.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.112, "v1.Image"

2.2.81.3. Consumes

- /

2.2.81.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.81.5. Tags

- oapiv1

2.2.82. read the specified Image

```
GET /oapi/v1/images/{name}
```

2.2.82.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParamet er	export	Should this value be exported. Export strips fields that a user can not specify.	false	boolean	
QueryParamet er	exact	Should the export be exact. Exact export maintains cluster-specific fields like 'Namespace'	false	boolean	
PathParameter	name	name of the Image	true	string	

2.2.82.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.112, "v1.Image"

2.2.82.3. Consumes

- /

2.2.82.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.82.5. Tags

- oapiv1

2.2.83. create a ImageSignature

POST /oapi/v1/imagesignatures

2.2.83.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 2.3.120 , "v1.ImageSign ature"	

2.2.83.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.120 , "v1.ImageSignature"

2.2.83.3. Consumes

- /

2.2.83.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.83.5. Tags

- oapiv1

2.2.84. delete a ImageSignature

```
DELETE /oapi/v1/imagesignatures/{name}
```

2.2.84.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	

Type	Name	Description	Required	Schema	Default
PathParameter	name	name of the ImageSignature	true	string	

2.2.84.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.11 , “unversioned.Status”

2.2.84.3. Consumes

- /

2.2.84.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.84.5. Tags

- oapiv1

2.2.85. create a ImageStreamImport

POST /oapi/v1/imagestreamimports

2.2.85.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 2.3.125 , “v1.ImageStreamImport”	

2.2.85.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.125 , “v1.ImageStreamImport”

2.2.85.3. Consumes

- /

2.2.85.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.85.5. Tags

- oapiv1

2.2.86. create a ImageStreamMapping

POST /oapi/v1/imagestreammappings

2.2.86.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 2.3.129 , “v1.ImageStre amMapping”	

2.2.86.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.129 , “v1.ImageStreamMapping”

2.2.86.3. Consumes

- /

2.2.86.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.86.5. Tags

- oapiv1

2.2.87. create a ImageStream

POST /oapi/v1/imagestreams

2.2.87.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 2.3.123 , "v1.ImageStre am"	

2.2.87.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.123 , "v1.ImageStream"

2.2.87.3. Consumes

- /

2.2.87.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.87.5. Tags

- oapiv1

2.2.88. list or watch objects of kind ImageStream

GET /oapi/v1/imagestreams

2.2.88.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamet er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParamet er	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParam er	resourceVersio n	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	
QueryParam er	timeoutSecond s	Timeout for the list/watch call.	false	integer	

2.2.88.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.128, "v1.ImageStreamList"

2.2.88.3. Consumes

- /

2.2.88.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.88.5. Tags

- oapiv1

2.2.89. create a ImageStreamTag

POST /oapi/v1/imagestreamtags

2.2.89.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 2.3.132 , "v1.ImageStre amTag"	

2.2.89.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.132 , "v1.ImageStreamTag"

2.2.89.3. Consumes

- /

2.2.89.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.89.5. Tags

- oapiv1

2.2.90. list objects of kind ImageStreamTag

```
GET /oapi/v1/imagestreamtags
```

2.2.90.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParam er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParam er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParam er	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	
QueryParam er	resourceVersion	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	
QueryParam er	timeoutSeconds	Timeout for the list/watch call.	false	integer	

2.2.90.2. Responses

HTTP Code	Description	Schema
-----------	-------------	--------

HTTP Code	Description	Schema
200	success	Section 2.3.133 , "v1.ImageStreamTagList"

2.2.90.3. Consumes

- /

2.2.90.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.90.5. Tags

- oapiv1

2.2.91. create a LocalResourceAccessReview

POST /oapi/v1/localresourceaccessreviews

2.2.91.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 2.3.139 , "v1.LocalResourceAccessReview"	

2.2.91.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.139 , "v1.LocalResourceAccessReview"

2.2.91.3. Consumes

- /

2.2.91.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.91.5. Tags

- oapiv1

2.2.92. create a LocalSubjectAccessReview

POST /oapi/v1/localsubjectaccessreviews

2.2.92.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 2.3.140 , "v1.LocalSubje ctAccessRevie w"	

2.2.92.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.140 , "v1.LocalSubjectAccessReview"

2.2.92.3. Consumes

- /

2.2.92.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.92.5. Tags

- oapiv1

2.2.93. list objects of kind AppliedClusterResourceQuota

GET /oapi/v1/namespaces/{namespace}/appliedclusterresourcequotas

2.2.93.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamet er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParamet er	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParamet er	resourceVersio n	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	
QueryParamet er	timeoutSecond s	Timeout for the list/watch call.	false	integer	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	

2.2.93.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.16, "v1.AppliedClusterResourceQuota List"

2.2.93.3. Consumes

- /

2.2.93.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.93.5. Tags

- oapiv1

2.2.94. read the specified AppliedClusterResourceQuota

```
GET /oapi/v1/namespaces/{namespace}/appliedclusterresourcequotas/{name}
```

2.2.94.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParameter	name	name of the AppliedCluster ResourceQuota	true	string	

2.2.94.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.15, "v1.AppliedClusterResourceQuota"

2.2.94.3. Consumes

- /

2.2.94.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.94.5. Tags

- oapiv1

2.2.95. delete collection of BuildConfig


```
DELETE /oapi/v1/namespaces/{namespace}/buildconfigs
```

2.2.95.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamet er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParamet er	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	
QueryParamet er	resourceVersio n	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	
QueryParamet er	timeoutSecond s	Timeout for the list/watch call.	false	integer	

Type	Name	Description	Required	Schema	Default
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	

2.2.95.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.11, "unversioned.Status"

2.2.95.3. Consumes

- /

2.2.95.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.95.5. Tags

- oapiv1

2.2.96. create a BuildConfig

POST /oapi/v1/namespaces/{namespace}/buildconfigs

2.2.96.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 2.3.20, "v1.BuildConf ig"	

Type	Name	Description	Required	Schema	Default
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	

2.2.96.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.20, "v1.BuildConfig"

2.2.96.3. Consumes

- /

2.2.96.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.96.5. Tags

- oapiv1

2.2.97. list or watch objects of kind BuildConfig

```
GET /oapi/v1/namespaces/{namespace}/buildconfigs
```

2.2.97.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParamet er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamet er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParamet er	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersio n.	false	boolean	
QueryParamet er	resourceVersio n	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	
QueryParamet er	timeoutSecond s	Timeout for the list/watch call.	false	integer	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	

2.2.97.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.21 , “v1.BuildConfigList”

2.2.97.3. Consumes

- /

2.2.97.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.97.5. Tags

- oapiv1

2.2.98. delete a BuildConfig

```
DELETE /oapi/v1/namespaces/{namespace}/buildconfigs/{name}
```

2.2.98.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 2.3.61 , “v1.DeleteOpti ons”	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParameter	name	name of the BuildConfig	true	string	

2.2.98.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.11 , “unversioned.Status”

2.2.98.3. Consumes

- /

2.2.98.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.98.5. Tags

- oapiv1

2.2.99. partially update the specified BuildConfig

```
PATCH /oapi/v1/namespaces/{namespace}/buildconfigs/{name}
```

2.2.99.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 2.3.10 , “unversioned.P atch”	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParameter	name	name of the BuildConfig	true	string	

2.2.99.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.20, “v1.BuildConfig”

2.2.99.3. Consumes

- application/json-patch+json
- application/merge-patch+json
- application/strategic-merge-patch+json

2.2.99.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.99.5. Tags

- oapiv1

2.2.100. replace the specified BuildConfig

```
PUT /oapi/v1/namespaces/{namespace}/buildconfigs/{name}
```

2.2.100.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 2.3.20, “v1.BuildConfig”	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParameter	name	name of the BuildConfig	true	string	

2.2.100.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.20, "v1.BuildConfig"

2.2.100.3. Consumes

- /

2.2.100.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.100.5. Tags

- oapiv1

2.2.101. read the specified BuildConfig

```
GET /oapi/v1/namespaces/{namespace}/buildconfigs/{name}
```

2.2.101.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	export	Should this value be exported. Export strips fields that a user can not specify.	false	boolean	
QueryParamet er	exact	Should the export be exact. Exact export maintains cluster-specific fields like 'Namespace'	false	boolean	

Type	Name	Description	Required	Schema	Default
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParameter	name	name of the BuildConfig	true	string	

2.2.101.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.20, "v1.BuildConfig"

2.2.101.3. Consumes

- /

2.2.101.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.101.5. Tags

- oapiv1

2.2.102. create instantiate of a BuildRequest

POST /oapi/v1/namespaces/{namespace}/buildconfigs/{name}/instantiate

2.2.102.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 2.3.28, "v1.BuildRequest"	

Type	Name	Description	Required	Schema	Default
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParameter	name	name of the BuildRequest	true	string	

2.2.102.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.28, "v1.BuildRequest"

2.2.102.3. Consumes

- /

2.2.102.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.102.5. Tags

- oapiv1

2.2.103. connect POST requests to instantiatebinary of BinaryBuildRequestOptions

```
POST /oapi/v1/namespaces/{namespace}/buildconfigs/{name}/instantiatebinary
```

2.2.103.1. Parameters

Type	Name	Description	Required	Schema	Default
------	------	-------------	----------	--------	---------

Type	Name	Description	Required	Schema	Default
QueryParamet er	asFile	asFile determines if the binary should be created as a file within the source rather than extracted as an archive	false	string	
QueryParamet er	revision.commi t	revision.commi t is the value identifying a specific commit	false	string	
QueryParamet er	revision.messa ge	revision.messa ge is the description of a specific commit	false	string	
QueryParamet er	revision.author Name	revision.author Name of the source control user	false	string	
QueryParamet er	revision.author Email	revision.author Email of the source control user	false	string	
QueryParamet er	revision.commi tterName	revision.commi tterName of the source control user	false	string	
QueryParamet er	revision.commi tterEmail	revision.commi tterEmail of the source control user	false	string	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	

Type	Name	Description	Required	Schema	Default
PathParameter	name	name of the BinaryBuildRequestOptions	true	string	

2.2.103.2. Responses

HTTP Code	Description	Schema
default	success	string

2.2.103.3. Consumes

- /

2.2.103.4. Produces

- /

2.2.103.5. Tags

- oapiv1

2.2.104. connect POST requests to webhooks of Status

POST /oapi/v1/namespaces/{namespace}/buildconfigs/{name}/webhooks

2.2.104.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	path	Path is the URL path to use for the current proxy request to pod.	false	string	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParameter	name	name of the Status	true	string	

2.2.104.2. Responses

HTTP Code	Description	Schema
default	success	string

2.2.104.3. Consumes

- /

2.2.104.4. Produces

- /

2.2.104.5. Tags

- oapiv1

2.2.105. connect POST requests to webhooks of Status

POST /oapi/v1/namespaces/{namespace}/buildconfigs/{name}/webhooks/{path}

2.2.105.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	path	Path is the URL path to use for the current proxy request to pod.	false	string	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParameter	name	name of the Status	true	string	
PathParameter	path	path to the resource	true	string	

2.2.105.2. Responses

HTTP Code	Description	Schema
default	success	string

2.2.105.3. Consumes

- /

2.2.105.4. Produces

- /

2.2.105.5. Tags

- oapiv1

2.2.106. delete collection of Build

```
DELETE /oapi/v1/namespaces/{namespace}/builds
```

2.2.106.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamet er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParamet er	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersio n.	false	boolean	
QueryParamet er	resourceVersio n	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	
QueryParamet er	timeoutSecond s	Timeout for the list/watch call.	false	integer	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	

2.2.106.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.11 , "unversioned.Status"

2.2.106.3. Consumes

- /

2.2.106.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.106.5. Tags

- oapiv1

2.2.107. create a Build

POST /oapi/v1/namespaces/{namespace}/builds

2.2.107.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParameter	body		true	Section 2.3.19, "v1.Build"	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	

2.2.107.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.19, "v1.Build"

2.2.107.3. Consumes

- /

2.2.107.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.107.5. Tags

- oapiv1

2.2.108. list or watch objects of kind Build

GET /oapi/v1/namespaces/{namespace}/builds

2.2.108.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamet er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParamet er	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParameter	resourceVersion	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	
QueryParameter	timeoutSeconds	Timeout for the list/watch call.	false	integer	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	

2.2.108.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.24, "v1.BuildList"

2.2.108.3. Consumes

- /

2.2.108.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.108.5. Tags

- oapiv1

2.2.109. delete a Build

```
DELETE /oapi/v1/namespaces/{namespace}/builds/{name}
```

2.2.109.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 2.3.61, "v1.DeleteOptions"	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParameter	name	name of the Build	true	string	

2.2.109.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.11, "unversioned.Status"

2.2.109.3. Consumes

- /

2.2.109.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.109.5. Tags

- oapiv1

2.2.110. partially update the specified Build

```
PATCH /oapi/v1/namespaces/{namespace}/builds/{name}
```

2.2.110.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 2.3.10, “unversioned.Patch”	
PathParamet er	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParamet er	name	name of the Build	true	string	

2.2.110.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.19, “v1.Build”

2.2.110.3. Consumes

- application/json-patch+json
- application/merge-patch+json
- application/strategic-merge-patch+json

2.2.110.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.110.5. Tags

- oapiv1

2.2.111. replace the specified Build

```
PUT /oapi/v1/namespaces/{namespace}/builds/{name}
```

2.2.111.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 2.3.19, "v1.Build"	
PathParamet er	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParamet er	name	name of the Build	true	string	

2.2.111.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.19, "v1.Build"

2.2.111.3. Consumes

- /

2.2.111.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.111.5. Tags

- oapiv1

2.2.112. read the specified Build

```
GET /oapi/v1/namespaces/{namespace}/builds/{name}
```

2.2.112.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	export	Should this value be exported. Export strips fields that a user can not specify.	false	boolean	
QueryParamet er	exact	Should the export be exact. Exact export maintains cluster-specific fields like 'Namespace'	false	boolean	
PathParamet er	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParamet er	name	name of the Build	true	string	

2.2.112.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.19, "v1.Build"

2.2.112.3. Consumes

- /

2.2.112.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.112.5. Tags

- oapiv1

2.2.113. create clone of a BuildRequest

POST /oapi/v1/namespaces/{namespace}/builds/{name}/clone

2.2.113.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 2.3.28, "v1.BuildRequest"	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParameter	name	name of the BuildRequest	true	string	

2.2.113.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.28, "v1.BuildRequest"

2.2.113.3. Consumes

- /

2.2.113.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.113.5. Tags

- oapiv1

2.2.114. replace details of the specified Build

PUT /oapi/v1/namespaces/{namespace}/builds/{name}/details

2.2.114.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 2.3.19, "v1.Build"	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParameter	name	name of the Build	true	string	

2.2.114.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.19, "v1.Build"

2.2.114.3. Consumes

- /

2.2.114.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.114.5. Tags

- oapiv1

2.2.115. read log of the specified BuildLog

GET /oapi/v1/namespaces/{namespace}/builds/{name}/log

2.2.115.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	container	cointainer for which to stream logs. Defaults to only container if there is one container in the pod.	false	string	
QueryParamet er	follow	follow if true indicates that the build log should be streamed until the build terminates.	false	boolean	
QueryParamet er	previous	previous returns previous build logs. Defaults to false.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParamet er	sinceSeconds	sinceSeconds is a relative time in seconds before the current time from which to show logs. If this value precedes the time a pod was started, only logs since the pod start will be returned. If this value is in the future, no logs will be returned. Only one of sinceSeconds or sinceTime may be specified.	false	integer	
QueryParamet er	sinceTime	sinceTime is an RFC3339 timestamp from which to show logs. If this value precedes the time a pod was started, only logs since the pod start will be returned. If this value is in the future, no logs will be returned. Only one of sinceSeconds or sinceTime may be specified.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParamet er	timestamps	timestamps, If true, add an RFC3339 or RFC3339Nano timestamp at the beginning of every line of log output. Defaults to false.	false	boolean	
QueryParamet er	tailLines	tailLines, If set, is the number of lines from the end of the logs to show. If not specified, logs are shown from the creation of the container or sinceSeconds or sinceTime	false	integer	
QueryParamet er	limitBytes	limitBytes, If set, is the number of bytes to read from the server before terminating the log output. This may not display a complete final line of logging, and may return slightly more or slightly less than the specified limit.	false	integer	

Type	Name	Description	Required	Schema	Default
QueryParamet er	nowait	noWait if true causes the call to return immediately even if the build is not available yet. Otherwise the server will wait until the build has started.	false	boolean	
QueryParamet er	version	version of the build for which to view logs.	false	integer	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParameter	name	name of the BuildLog	true	string	

2.2.115.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.25, "v1.BuildLog"

2.2.115.3. Consumes

- /

2.2.115.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.115.5. Tags

- oapiv1

2.2.116. create a DeploymentConfigRollback

POST /oapi/v1/namespaces/{namespace}/deploymentconfigrollbacks

2.2.116.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 2.3.66, "v1.Deploymen tConfigRollbac k"	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	

2.2.116.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.66, "v1.DeploymentConfigRollback"

2.2.116.3. Consumes

- /

2.2.116.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.116.5. Tags

- oapiv1

2.2.117. delete collection of DeploymentConfig

DELETE /oapi/v1/namespaces/{namespace}/deploymentconfigs

2.2.117.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamet er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParamet er	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersio n.	false	boolean	
QueryParamet er	resourceVersio n	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	
QueryParamet er	timeoutSecond s	Timeout for the list/watch call.	false	integer	

Type	Name	Description	Required	Schema	Default
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	

2.2.117.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.11 , “unversioned.Status”

2.2.117.3. Consumes

- /

2.2.117.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.117.5. Tags

- oapiv1

2.2.118. create a DeploymentConfig

POST /oapi/v1/namespaces/{namespace}/deploymentconfigs

2.2.118.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 2.3.64 , “v1.Deploymen tConfig”	

Type	Name	Description	Required	Schema	Default
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	

2.2.118.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.64, "v1.DeploymentConfig"

2.2.118.3. Consumes

- /

2.2.118.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.118.5. Tags

- oapiv1

2.2.119. list or watch objects of kind DeploymentConfig

```
GET /oapi/v1/namespaces/{namespace}/deploymentconfigs
```

2.2.119.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParamet er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamet er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParamet er	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	
QueryParamet er	resourceVersio n	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	
QueryParamet er	timeoutSecond s	Timeout for the list/watch call.	false	integer	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	

2.2.119.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.65 , "v1.DeploymentConfigList"

2.2.119.3. Consumes

- /

2.2.119.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.119.5. Tags

- oapiv1

2.2.120. delete a DeploymentConfig

```
DELETE /oapi/v1/namespaces/{namespace}/deploymentconfigs/{name}
```

2.2.120.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 2.3.61 , "v1.DeleteOpti ons"	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParameter	name	name of the DeploymentCo nfig	true	string	

2.2.120.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.11 , “unversioned.Status”

2.2.120.3. Consumes

- /

2.2.120.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.120.5. Tags

- oapiv1

2.2.121. partially update the specified DeploymentConfig

```
PATCH /oapi/v1/namespaces/{namespace}/deploymentconfigs/{name}
```

2.2.121.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 2.3.10 , “unversioned.P atch”	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParameter	name	name of the DeploymentCo nfig	true	string	

2.2.121.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.64, "v1.DeploymentConfig"

2.2.121.3. Consumes

- application/json-patch+json
- application/merge-patch+json
- application/strategic-merge-patch+json

2.2.121.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.121.5. Tags

- oapiv1

2.2.122. replace the specified DeploymentConfig

```
PUT /oapi/v1/namespaces/{namespace}/deploymentconfigs/{name}
```

2.2.122.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 2.3.64, "v1.Deploymen tConfig"	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParameter	name	name of the DeploymentCo nfig	true	string	

2.2.122.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.64, "v1.DeploymentConfig"

2.2.122.3. Consumes

- /

2.2.122.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.122.5. Tags

- oapiv1

2.2.123. read the specified DeploymentConfig

```
GET /oapi/v1/namespaces/{namespace}/deploymentconfigs/{name}
```

2.2.123.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	export	Should this value be exported. Export strips fields that a user can not specify.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParamet er	exact	Should the export be exact. Exact export maintains cluster-specific fields like 'Namespace'	false	boolean	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParameter	name	name of the DeploymentCo nfig	true	string	

2.2.123.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.64, "v1.DeploymentConfig"

2.2.123.3. Consumes

- /

2.2.123.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.123.5. Tags

- oapiv1

2.2.124. read log of the specified DeploymentLog

```
GET /oapi/v1/namespaces/{namespace}/deploymentconfigs/{name}/log
```

2.2.124.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	container	The container for which to stream logs. Defaults to only container if there is one container in the pod.	false	string	
QueryParamet er	follow	Follow if true indicates that the build log should be streamed until the build terminates.	false	boolean	
QueryParamet er	previous	Return previous deployment logs. Defaults to false.	false	boolean	
QueryParamet er	sinceSeconds	A relative time in seconds before the current time from which to show logs. If this value precedes the time a pod was started, only logs since the pod start will be returned. If this value is in the future, no logs will be returned. Only one of sinceSeconds or sinceTime may be specified.	false	integer	

Type	Name	Description	Required	Schema	Default
QueryParam er	sinceTime	An RFC3339 timestamp from which to show logs. If this value precedes the time a pod was started, only logs since the pod start will be returned. If this value is in the future, no logs will be returned. Only one of sinceSeconds or sinceTime may be specified.	false	string	
QueryParam er	timestamps	If true, add an RFC3339 or RFC3339Nano timestamp at the beginning of every line of log output. Defaults to false.	false	boolean	
QueryParam er	tailLines	If set, the number of lines from the end of the logs to show. If not specified, logs are shown from the creation of the container or sinceSeconds or sinceTime	false	integer	

Type	Name	Description	Required	Schema	Default
QueryParamet er	limitBytes	If set, the number of bytes to read from the server before terminating the log output. This may not display a complete final line of logging, and may return slightly more or slightly less than the specified limit.	false	integer	
QueryParamet er	nowait	NoWait if true causes the call to return immediately even if the deployment is not available yet. Otherwise the server will wait until the deployment has started.	false	boolean	
QueryParamet er	version	Version of the deployment for which to view logs.	false	integer	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParameter	name	name of the DeploymentLog	true	string	

2.2.124.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.71 , "v1.DeploymentLog"

2.2.124.3. Consumes

- /

2.2.124.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.124.5. Tags

- oapiv1

2.2.125. create rollback of a DeploymentConfigRollback

POST /oapi/v1/namespaces/{namespace}/deploymentconfigs/{name}/rollback

2.2.125.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 2.3.66 , "v1.Deploymen tConfigRollbac k"	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParameter	name	name of the DeploymentCo nfigRollback	true	string	

2.2.125.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.66 , “v1.DeploymentConfigRollback”

2.2.125.3. Consumes

- /

2.2.125.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.125.5. Tags

- oapiv1

2.2.126. partially update scale of the specified Scale

```
PATCH /oapi/v1/namespaces/{namespace}/deploymentconfigs/{name}/scale
```

2.2.126.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 2.3.10 , “unversioned.P atch”	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParameter	name	name of the Scale	true	string	

2.2.126.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.237, "v1beta1.Scale"

2.2.126.3. Consumes

- application/json-patch+json
- application/merge-patch+json
- application/strategic-merge-patch+json

2.2.126.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.126.5. Tags

- oapiv1

2.2.127. replace scale of the specified Scale

```
PUT /oapi/v1/namespaces/{namespace}/deploymentconfigs/{name}/scale
```

2.2.127.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 2.3.237, "v1beta1.Scale"	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParameter	name	name of the Scale	true	string	

2.2.127.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.237, "v1beta1.Scale"

2.2.127.3. Consumes

- /

2.2.127.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.127.5. Tags

- oapiv1

2.2.128. read scale of the specified Scale

```
GET /oapi/v1/namespaces/{namespace}/deploymentconfigs/{name}/scale
```

2.2.128.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParameter	name	name of the Scale	true	string	

2.2.128.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.237, "v1beta1.Scale"

2.2.128.3. Consumes

- /

2.2.128.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.128.5. Tags

- oapiv1

2.2.129. replace status of the specified DeploymentConfig

```
PUT /oapi/v1/namespaces/{namespace}/deploymentconfigs/{name}/status
```

2.2.129.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 2.3.64, "v1.Deploymen tConfig"	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParameter	name	name of the DeploymentCo nfig	true	string	

2.2.129.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.64, "v1.DeploymentConfig"

2.2.129.3. Consumes

- /

2.2.129.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.129.5. Tags

- oapiv1

2.2.130. delete collection of EgressNetworkPolicy

```
DELETE /oapi/v1/namespaces/{namespace}/egressnetworkpolicies
```

2.2.130.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamet er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParamet er	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersio n.	false	boolean	
QueryParamet er	resourceVersio n	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	
QueryParamet er	timeoutSecond s	Timeout for the list/watch call.	false	integer	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	

2.2.130.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.11 , "unversioned.Status"

2.2.130.3. Consumes

- /

2.2.130.4. Produces

- application/json

- application/yaml
- application/vnd.kubernetes.protobuf

2.2.130.5. Tags

- oapiv1

2.2.131. create a EgressNetworkPolicy

POST /oapi/v1/namespaces/{namespace}/egressnetworkpolicies

2.2.131.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 2.3.80, "v1.EgressNetworkPolicy"	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	

2.2.131.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.80, "v1.EgressNetworkPolicy"

2.2.131.3. Consumes

- /

2.2.131.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.131.5. Tags

- oapiv1

2.2.132. list or watch objects of kind EgressNetworkPolicy

```
GET /oapi/v1/namespaces/{namespace}/egressnetworkpolicies
```

2.2.132.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamet er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParamet er	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParamet er	resourceVersio n	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	
QueryParamet er	timeoutSecond s	Timeout for the list/watch call.	false	integer	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	

2.2.132.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.81 , “v1.EgressNetworkPolicyList”

2.2.132.3. Consumes

- /

2.2.132.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.132.5. Tags

- oapiv1

2.2.133. delete a EgressNetworkPolicy

DELETE /oapi/v1/namespaces/{namespace}/egressnetworkpolicies/{name}

2.2.133.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParameter	body		true	Section 2.3.61, "v1.DeleteOptions"	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParameter	name	name of the EgressNetwork Policy	true	string	

2.2.133.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.11, "unversioned.Status"

2.2.133.3. Consumes

- /

2.2.133.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.133.5. Tags

- oapiv1

2.2.134. partially update the specified EgressNetworkPolicy

PATCH /oapi/v1/namespaces/{namespace}/egressnetworkpolicies/{name}

2.2.134.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 2.3.10, "unversioned.Patch"	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParameter	name	name of the EgressNetwork Policy	true	string	

2.2.134.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.80, "v1.EgressNetworkPolicy"

2.2.134.3. Consumes

- application/json-patch+json
- application/merge-patch+json
- application/strategic-merge-patch+json

2.2.134.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.134.5. Tags

- oapiv1

2.2.135. replace the specified EgressNetworkPolicy

```
PUT /oapi/v1/namespaces/{namespace}/egressnetworkpolicies/{name}
```

2.2.135.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 2.3.80, "v1.EgressNetworkPolicy"	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParameter	name	name of the EgressNetwork Policy	true	string	

2.2.135.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.80, "v1.EgressNetworkPolicy"

2.2.135.3. Consumes

- /

2.2.135.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.135.5. Tags

- oapiv1

2.2.136. read the specified EgressNetworkPolicy

```
GET /oapi/v1/namespaces/{namespace}/egressnetworkpolicies/{name}
```

2.2.136.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	export	Should this value be exported. Export strips fields that a user can not specify.	false	boolean	
QueryParamet er	exact	Should the export be exact. Exact export maintains cluster-specific fields like 'Namespace'	false	boolean	
PathParamet er	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParamet er	name	name of the EgressNetwork Policy	true	string	

2.2.136.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.80, "v1.EgressNetworkPolicy"

2.2.136.3. Consumes

- /

2.2.136.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.136.5. Tags

- oapiv1

2.2.137. read the specified DeploymentConfig

```
GET /oapi/v1/namespaces/{namespace}/generateddeploymentconfigs/{name}
```

2.2.137.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamter	pretty	If 'true', then the output is pretty printed.	false	string	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParameter	name	name of the DeploymentConfig	true	string	

2.2.137.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.64, "v1.DeploymentConfig"

2.2.137.3. Consumes

- /

2.2.137.4. Produces

- application/json
- application/yaml

- application/vnd.kubernetes.protobuf

2.2.137.5. Tags

- oapiv1

2.2.138. read the specified ImageStreamImage

GET /oapi/v1/namespaces/{namespace}/imagestreamimages/{name}

2.2.138.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParameter	name	name of the ImageStreamImage	true	string	

2.2.138.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.124, "v1.ImageStreamImage"

2.2.138.3. Consumes

- /

2.2.138.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.138.5. Tags

- oapiv1

2.2.139. create a ImageStreamImport

POST /oapi/v1/namespaces/{namespace}/imagestreamimports

2.2.139.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 2.3.125 , "v1.ImageStre amImport"	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	

2.2.139.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.125 , "v1.ImageStreamImport"

2.2.139.3. Consumes

- /

2.2.139.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.139.5. Tags

- oapiv1

2.2.140. create a ImageStreamMapping

POST /oapi/v1/namespaces/{namespace}/imagestreammappings

2.2.140.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 2.3.129 , "v1.ImageStre amMapping"	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	

2.2.140.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.129 , "v1.ImageStreamMapping"

2.2.140.3. Consumes

- /

2.2.140.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.140.5. Tags

- oapiv1

2.2.141. delete collection of ImageStream

DELETE /oapi/v1/namespaces/{namespace}/imagestreams

2.2.141.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamet er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParamet er	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersio n.	false	boolean	
QueryParamet er	resourceVersio n	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	
QueryParamet er	timeoutSecond s	Timeout for the list/watch call.	false	integer	

Type	Name	Description	Required	Schema	Default
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	

2.2.141.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.11 , “unversioned.Status”

2.2.141.3. Consumes

- /

2.2.141.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.141.5. Tags

- oapiv1

2.2.142. create a ImageStream

POST /oapi/v1/namespaces/{namespace}/imagestreams

2.2.142.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 2.3.12 3, “v1.ImageStre am”	

Type	Name	Description	Required	Schema	Default
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	

2.2.142.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.123, "v1.ImageStream"

2.2.142.3. Consumes

- /

2.2.142.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.142.5. Tags

- oapiv1

2.2.143. list or watch objects of kind ImageStream

```
GET /oapi/v1/namespaces/{namespace}/imagestreams
```

2.2.143.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParamet er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamet er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParamet er	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	
QueryParamet er	resourceVersio n	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	
QueryParamet er	timeoutSecond s	Timeout for the list/watch call.	false	integer	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	

2.2.143.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.128 , "v1.ImageStreamList"

2.2.143.3. Consumes

- /

2.2.143.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.143.5. Tags

- oapiv1

2.2.144. delete a ImageStream

```
DELETE /oapi/v1/namespaces/{namespace}/imagestreams/{name}
```

2.2.144.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 2.3.61 , "v1.DeleteOpti ons"	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParameter	name	name of the ImageStream	true	string	

2.2.144.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.11 , “unversioned.Status”

2.2.144.3. Consumes

- /

2.2.144.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.144.5. Tags

- oapiv1

2.2.145. partially update the specified ImageStream

```
PATCH /oapi/v1/namespaces/{namespace}/imagestreams/{name}
```

2.2.145.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 2.3.10 , “unversioned.P atch”	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParameter	name	name of the ImageStream	true	string	

2.2.145.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.123 , “v1.ImageStream”

2.2.145.3. Consumes

- application/json-patch+json
- application/merge-patch+json
- application/strategic-merge-patch+json

2.2.145.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.145.5. Tags

- oapiv1

2.2.146. replace the specified ImageStream

```
PUT /oapi/v1/namespaces/{namespace}/imagestreams/{name}
```

2.2.146.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 2.3.123 , “v1.ImageStre am”	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParameter	name	name of the ImageStream	true	string	

2.2.146.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.123 , "v1.ImageStream"

2.2.146.3. Consumes

- /

2.2.146.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.146.5. Tags

- oapiv1

2.2.147. read the specified ImageStream

```
GET /oapi/v1/namespaces/{namespace}/imagestreams/{name}
```

2.2.147.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	export	Should this value be exported. Export strips fields that a user can not specify.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParamet er	exact	Should the export be exact. Exact export maintains cluster-specific fields like 'Namespace'	false	boolean	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParameter	name	name of the ImageStream	true	string	

2.2.147.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.123, "v1.ImageStream"

2.2.147.3. Consumes

- /

2.2.147.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.147.5. Tags

- oapiv1

2.2.148. read secrets of the specified SecretList

```
GET /oapi/v1/namespaces/{namespace}/imagestreams/{name}/secrets
```

2.2.148.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamet er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParamet er	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	
QueryParamet er	resourceVersio n	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	
QueryParamet er	timeoutSecond s	Timeout for the list/watch call.	false	integer	

Type	Name	Description	Required	Schema	Default
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParameter	name	name of the SecretList	true	string	

2.2.148.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.207, "v1.SecretList"

2.2.148.3. Consumes

- /

2.2.148.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.148.5. Tags

- oapiv1

2.2.149. replace status of the specified ImageStream

```
PUT /oapi/v1/namespaces/{namespace}/imagestreams/{name}/status
```

2.2.149.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	

Type	Name	Description	Required	Schema	Default
BodyParameter	body		true	Section 2.3.123 , "v1.ImageStream"	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParameter	name	name of the ImageStream	true	string	

2.2.149.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.123 , "v1.ImageStream"

2.2.149.3. Consumes

- /

2.2.149.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.149.5. Tags

- oapiv1

2.2.150. create a ImageStreamTag

```
POST /oapi/v1/namespaces/{namespace}/imagestreamtags
```

2.2.150.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 2.3.132 , "v1.ImageStre amTag"	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	

2.2.150.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.132 , "v1.ImageStreamTag"

2.2.150.3. Consumes

- /

2.2.150.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.150.5. Tags

- oapiv1

2.2.151. list objects of kind ImageStreamTag

```
GET /oapi/v1/namespaces/{namespace}/imagestreamtags
```

2.2.151.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamet er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParamet er	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersio n.	false	boolean	
QueryParamet er	resourceVersio n	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	
QueryParamet er	timeoutSecond s	Timeout for the list/watch call.	false	integer	

Type	Name	Description	Required	Schema	Default
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	

2.2.151.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.133 , "v1.ImageStreamTagList"

2.2.151.3. Consumes

- /

2.2.151.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.151.5. Tags

- oapiv1

2.2.152. delete a ImageStreamTag

```
DELETE /oapi/v1/namespaces/{namespace}/imagestreamtags/{name}
```

2.2.152.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	

Type	Name	Description	Required	Schema	Default
PathParameter	name	name of the ImageStreamTag	true	string	

2.2.152.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.11 , “unversioned.Status”

2.2.152.3. Consumes

- /

2.2.152.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.152.5. Tags

- oapiv1

2.2.153. partially update the specified ImageStreamTag

```
PATCH /oapi/v1/namespaces/{namespace}/imagestreamtags/{name}
```

2.2.153.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 2.3.10 , “unversioned.Patch”	

Type	Name	Description	Required	Schema	Default
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParameter	name	name of the ImageStreamTag	true	string	

2.2.153.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.132, "v1.ImageStreamTag"

2.2.153.3. Consumes

- application/json-patch+json
- application/merge-patch+json
- application/strategic-merge-patch+json

2.2.153.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.153.5. Tags

- oapiv1

2.2.154. replace the specified ImageStreamTag

```
PUT /oapi/v1/namespaces/{namespace}/imagestreamtags/{name}
```

2.2.154.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 2.3.13 2 , "v1.ImageStre amTag"	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParameter	name	name of the ImageStreamTag	true	string	

2.2.154.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.132 , "v1.ImageStreamTag"

2.2.154.3. Consumes

- /

2.2.154.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.154.5. Tags

- oapiv1

2.2.155. read the specified ImageStreamTag

```
GET /oapi/v1/namespaces/{namespace}/imagestreamtags/{name}
```

2.2.155.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParameter	name	name of the ImageStreamTag	true	string	

2.2.155.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.132, "v1.ImageStreamTag"

2.2.155.3. Consumes

- /

2.2.155.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.155.5. Tags

- oapiv1

2.2.156. create a LocalResourceAccessReview

```
POST /oapi/v1/namespaces/{namespace}/localresourceaccessreviews
```

2.2.156.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 2.3.139 , “v1.LocalResourceAccessReview”	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	

2.2.156.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.139 , “v1.LocalResourceAccessReview”

2.2.156.3. Consumes

- /

2.2.156.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.156.5. Tags

- oapiv1

2.2.157. create a LocalSubjectAccessReview

```
POST /oapi/v1/namespaces/{namespace}/localsubjectaccessreviews
```

2.2.157.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 2.3.140 , “v1.LocalSubje ctAccessRevie w”	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	

2.2.157.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.140 , “v1.LocalSubjectAccessReview”

2.2.157.3. Consumes

- /

2.2.157.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.157.5. Tags

- oapiv1

2.2.158. delete collection of Policy

```
DELETE /oapi/v1/namespaces/{namespace}/policies
```

2.2.158.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamet er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParamet er	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	
QueryParamet er	resourceVersio n	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	
QueryParamet er	timeoutSecond s	Timeout for the list/watch call.	false	integer	

Type	Name	Description	Required	Schema	Default
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	

2.2.158.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.11 , “unversioned.Status”

2.2.158.3. Consumes

- /

2.2.158.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.158.5. Tags

- oapiv1

2.2.159. create a Policy

POST /oapi/v1/namespaces/{namespace}/policies

2.2.159.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 2.3.16 6, “v1.Policy”	

Type	Name	Description	Required	Schema	Default
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	

2.2.159.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.166, "v1.Policy"

2.2.159.3. Consumes

- /

2.2.159.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.159.5. Tags

- oapiv1

2.2.160. list or watch objects of kind Policy

```
GET /oapi/v1/namespaces/{namespace}/policies
```

2.2.160.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParamet er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamet er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParamet er	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	
QueryParamet er	resourceVersio n	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	
QueryParamet er	timeoutSecond s	Timeout for the list/watch call.	false	integer	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	

2.2.160.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.169, "v1.PolicyList"

2.2.160.3. Consumes

- /

2.2.160.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.160.5. Tags

- oapiv1

2.2.161. delete a Policy

```
DELETE /oapi/v1/namespaces/{namespace}/policies/{name}
```

2.2.161.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 2.3.61, "v1.DeleteOptions"	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParameter	name	name of the Policy	true	string	

2.2.161.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.11 , “unversioned.Status”

2.2.161.3. Consumes

- /

2.2.161.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.161.5. Tags

- oapiv1

2.2.162. partially update the specified Policy

```
PATCH /oapi/v1/namespaces/{namespace}/policies/{name}
```

2.2.162.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 2.3.10 , “unversioned.P atch”	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParameter	name	name of the Policy	true	string	

2.2.162.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.166, “v1.Policy”

2.2.162.3. Consumes

- application/json-patch+json
- application/merge-patch+json
- application/strategic-merge-patch+json

2.2.162.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.162.5. Tags

- oapiv1

2.2.163. replace the specified Policy

```
PUT /oapi/v1/namespaces/{namespace}/policies/{name}
```

2.2.163.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 2.3.166, “v1.Policy”	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParameter	name	name of the Policy	true	string	

2.2.163.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.166, "v1.Policy"

2.2.163.3. Consumes

- /

2.2.163.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.163.5. Tags

- oapiv1

2.2.164. read the specified Policy

```
GET /oapi/v1/namespaces/{namespace}/policies/{name}
```

2.2.164.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	export	Should this value be exported. Export strips fields that a user can not specify.	false	boolean	
QueryParamet er	exact	Should the export be exact. Exact export maintains cluster-specific fields like 'Namespace'	false	boolean	

Type	Name	Description	Required	Schema	Default
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParameter	name	name of the Policy	true	string	

2.2.164.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.166, "v1.Policy"

2.2.164.3. Consumes

- /

2.2.164.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.164.5. Tags

- oapiv1

2.2.165. delete collection of PolicyBinding

```
DELETE /oapi/v1/namespaces/{namespace}/policybindings
```

2.2.165.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParamet er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamet er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParamet er	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersio n.	false	boolean	
QueryParamet er	resourceVersio n	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	
QueryParamet er	timeoutSecond s	Timeout for the list/watch call.	false	integer	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	

2.2.165.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.11 , “unversioned.Status”

2.2.165.3. Consumes

- /

2.2.165.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.165.5. Tags

- oapiv1

2.2.166. create a PolicyBinding

POST /oapi/v1/namespaces/{namespace}/policybindings

2.2.166.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 2.3.167 , “v1.PolicyBindi ng”	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	

2.2.166.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.167, "v1.PolicyBinding"

2.2.166.3. Consumes

- /

2.2.166.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.166.5. Tags

- oapiv1

2.2.167. list or watch objects of kind PolicyBinding

```
GET /oapi/v1/namespaces/{namespace}/policybindings
```

2.2.167.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamet er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParamet er	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	
QueryParamet er	resourceVersio n	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	
QueryParamet er	timeoutSecond s	Timeout for the list/watch call.	false	integer	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	

2.2.167.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.168 , "v1.PolicyBindingList"

2.2.167.3. Consumes

- /

2.2.167.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.167.5. Tags

- oapiv1

2.2.168. delete a PolicyBinding

```
DELETE /oapi/v1/namespaces/{namespace}/policybindings/{name}
```

2.2.168.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParameter	body		true	Section 2.3.61, "v1.DeleteOptions"	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParameter	name	name of the PolicyBinding	true	string	

2.2.168.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.11, "unversioned.Status"

2.2.168.3. Consumes

- /

2.2.168.4. Produces

- application/json

- application/yaml
- application/vnd.kubernetes.protobuf

2.2.168.5. Tags

- oapiv1

2.2.169. partially update the specified PolicyBinding

PATCH /oapi/v1/namespaces/{namespace}/policybindings/{name}

2.2.169.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 2.3.10, "unversioned.Patch"	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParameter	name	name of the PolicyBinding	true	string	

2.2.169.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.167, "v1.PolicyBinding"

2.2.169.3. Consumes

- application/json-patch+json
- application/merge-patch+json
- application/strategic-merge-patch+json

2.2.169.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.169.5. Tags

- oapiv1

2.2.170. replace the specified PolicyBinding

```
PUT /oapi/v1/namespaces/{namespace}/policybindings/{name}
```

2.2.170.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParameter	body		true	Section 2.3.167 , "v1.PolicyBinding"	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParameter	name	name of the PolicyBinding	true	string	

2.2.170.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.167 , "v1.PolicyBinding"

2.2.170.3. Consumes

- /

2.2.170.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.170.5. Tags

- oapiv1

2.2.171. read the specified PolicyBinding

```
GET /oapi/v1/namespaces/{namespace}/policybindings/{name}
```

2.2.171.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	export	Should this value be exported. Export strips fields that a user can not specify.	false	boolean	
QueryParamet er	exact	Should the export be exact. Exact export maintains cluster-specific fields like 'Namespace'	false	boolean	
PathParamet er	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParamet er	name	name of the PolicyBinding	true	string	

2.2.171.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.167 , “v1.PolicyBinding”

2.2.171.3. Consumes

- /

2.2.171.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.171.5. Tags

- oapiv1

2.2.172. create a Template

POST /oapi/v1/namespaces/{namespace}/processedtemplates

2.2.172.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 2.3.228 , “v1.Template”	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	

2.2.172.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.228 , “v1.Template”

2.2.172.3. Consumes

- /

2.2.172.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.172.5. Tags

- oapiv1

2.2.173. create a ResourceAccessReview

POST /oapi/v1/namespaces/{namespace}/resourceaccessreviews

2.2.173.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 2.3.18 2 , "v1.ResourceA ccessReview"	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	

2.2.173.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.182 , "v1.ResourceAccessReview"

2.2.173.3. Consumes

- /

2.2.173.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.173.5. Tags

- oapiv1

2.2.174. create a RoleBinding

POST /oapi/v1/namespaces/{namespace}/rolebindings

2.2.174.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParameter	body		true	Section 2.3.190 , "v1.RoleBinding"	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	

2.2.174.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.190 , "v1.RoleBinding"

2.2.174.3. Consumes

- /

2.2.174.4. Produces

- application/json
- application/yaml

- application/vnd.kubernetes.protobuf

2.2.174.5. Tags

- oapiv1

2.2.175. list objects of kind RoleBinding

GET /oapi/v1/namespaces/{namespace}/rolebindings

2.2.175.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamet er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParamet er	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParamet er	resourceVersio n	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	
QueryParamet er	timeoutSecond s	Timeout for the list/watch call.	false	integer	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	

2.2.175.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.191 , "v1.RoleBindingList"

2.2.175.3. Consumes

- /

2.2.175.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.175.5. Tags

- oapiv1

2.2.176. delete a RoleBinding

```
DELETE /oapi/v1/namespaces/{namespace}/rolebindings/{name}
```

■

2.2.176.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 2.3.61, "v1.DeleteOptions"	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParameter	name	name of the RoleBinding	true	string	

2.2.176.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.11, "unversioned.Status"

2.2.176.3. Consumes

- /

2.2.176.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.176.5. Tags

- oapiv1

2.2.177. partially update the specified RoleBinding

```
PATCH /oapi/v1/namespaces/{namespace}/rolebindings/{name}
```

2.2.177.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 2.3.10, "unversioned.Patch"	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParameter	name	name of the RoleBinding	true	string	

2.2.177.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.190, "v1.RoleBinding"

2.2.177.3. Consumes

- application/json-patch+json
- application/merge-patch+json
- application/strategic-merge-patch+json

2.2.177.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.177.5. Tags

- oapiv1

2.2.178. replace the specified RoleBinding

```
PUT /oapi/v1/namespaces/{namespace}/rolebindings/{name}
```


2.2.178.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 2.3.190 , "v1.RoleBindin g"	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParameter	name	name of the RoleBinding	true	string	

2.2.178.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.190 , "v1.RoleBinding"

2.2.178.3. Consumes

- /

2.2.178.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.178.5. Tags

- oapiv1

2.2.179. read the specified RoleBinding

```
GET /oapi/v1/namespaces/{namespace}/rolebindings/{name}
```

2.2.179.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParameter	name	name of the RoleBinding	true	string	

2.2.179.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.190, "v1.RoleBinding"

2.2.179.3. Consumes

- /

2.2.179.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.179.5. Tags

- oapiv1

2.2.180. create a Role

```
POST /oapi/v1/namespaces/{namespace}/roles
```

2.2.180.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	

Type	Name	Description	Required	Schema	Default
BodyParameter	body		true	Section 2.3.189, "v1.Role"	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	

2.2.180.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.189, "v1.Role"

2.2.180.3. Consumes

- /

2.2.180.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.180.5. Tags

- oapiv1

2.2.181. list objects of kind Role

```
GET /oapi/v1/namespaces/{namespace}/roles
```

2.2.181.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParamet er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamet er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParamet er	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	
QueryParamet er	resourceVersio n	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	
QueryParamet er	timeoutSecond s	Timeout for the list/watch call.	false	integer	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	

2.2.181.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.192, "v1.RoleList"

2.2.181.3. Consumes

- /

2.2.181.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.181.5. Tags

- oapiv1

2.2.182. delete a Role

```
DELETE /oapi/v1/namespaces/{namespace}/roles/{name}
```

2.2.182.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 2.3.61, "v1.DeleteOptions"	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParameter	name	name of the Role	true	string	

2.2.182.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.11 , “unversioned.Status”

2.2.182.3. Consumes

- /

2.2.182.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.182.5. Tags

- oapiv1

2.2.183. partially update the specified Role

PATCH /oapi/v1/namespaces/{namespace}/roles/{name}

2.2.183.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParameter	body		true	Section 2.3.10 , “unversioned.Patch”	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParameter	name	name of the Role	true	string	

2.2.183.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.189, "v1.Role"

2.2.183.3. Consumes

- application/json-patch+json
- application/merge-patch+json
- application/strategic-merge-patch+json

2.2.183.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.183.5. Tags

- oapiv1

2.2.184. replace the specified Role

```
PUT /oapi/v1/namespaces/{namespace}/roles/{name}
```

2.2.184.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 2.3.189, "v1.Role"	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParameter	name	name of the Role	true	string	

2.2.184.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.189, “v1.Role”

2.2.184.3. Consumes

- /

2.2.184.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.184.5. Tags

- oapiv1

2.2.185. read the specified Role

```
GET /oapi/v1/namespaces/{namespace}/roles/{name}
```

2.2.185.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParameter	name	name of the Role	true	string	

2.2.185.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.189, “v1.Role”

2.2.185.3. Consumes

- /

2.2.185.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.185.5. Tags

- oapiv1

2.2.186. delete collection of Route

```
DELETE /oapi/v1/namespaces/{namespace}/routes
```

2.2.186.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamet er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParamet er	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	
QueryParamet er	resourceVersio n	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	
QueryParamet er	timeoutSecond s	Timeout for the list/watch call.	false	integer	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	

2.2.186.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.11 , “unversioned.Status”

2.2.186.3. Consumes

- /

2.2.186.4. Produces

- application/json

- application/yaml
- application/vnd.kubernetes.protobuf

2.2.186.5. Tags

- oapiv1

2.2.187. create a Route

POST /oapi/v1/namespaces/{namespace}/routes

2.2.187.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 2.3.194, "v1.Route"	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	

2.2.187.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.194, "v1.Route"

2.2.187.3. Consumes

- /

2.2.187.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.187.5. Tags

- oapiv1

2.2.188. list or watch objects of kind Route

```
GET /oapi/v1/namespaces/{namespace}/routes
```

2.2.188.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamet er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParamet er	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParamet er	resourceVersio n	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	
QueryParamet er	timeoutSecond s	Timeout for the list/watch call.	false	integer	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	

2.2.188.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.197, "v1.RouteList"

2.2.188.3. Consumes

- /

2.2.188.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.188.5. Tags

- oapiv1

2.2.189. delete a Route

```
DELETE /oapi/v1/namespaces/{namespace}/routes/{name}
```

2.2.189.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 2.3.61, "v1.DeleteOptions"	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParameter	name	name of the Route	true	string	

2.2.189.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.11, "unversioned.Status"

2.2.189.3. Consumes

- /

2.2.189.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.189.5. Tags

- oapiv1

2.2.190. partially update the specified Route

```
PATCH /oapi/v1/namespaces/{namespace}/routes/{name}
```

2.2.190.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 2.3.10, "unversioned.Patch"	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParameter	name	name of the Route	true	string	

2.2.190.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.194, "v1.Route"

2.2.190.3. Consumes

- application/json-patch+json
- application/merge-patch+json
- application/strategic-merge-patch+json

2.2.190.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.190.5. Tags

- oapiv1

2.2.191. replace the specified Route

```
PUT /oapi/v1/namespaces/{namespace}/routes/{name}
```

2.2.191.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 2.3.194, "v1.Route"	
PathParamet er	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParamet er	name	name of the Route	true	string	

2.2.191.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.194, "v1.Route"

2.2.191.3. Consumes

- /

2.2.191.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.191.5. Tags

- oapiv1

2.2.192. read the specified Route

```
GET /oapi/v1/namespaces/{namespace}/routes/{name}
```

2.2.192.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	export	Should this value be exported. Export strips fields that a user can not specify.	false	boolean	
QueryParamet er	exact	Should the export be exact. Exact export maintains cluster-specific fields like 'Namespace'	false	boolean	
PathParamet er	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParamet er	name	name of the Route	true	string	

2.2.192.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.194, "v1.Route"

2.2.192.3. Consumes

- /

2.2.192.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.192.5. Tags

- oapiv1

2.2.193. replace status of the specified Route

```
PUT /oapi/v1/namespaces/{namespace}/routes/{name}/status
```

2.2.193.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 2.3.194, "v1.Route"	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParameter	name	name of the Route	true	string	

2.2.193.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.194, "v1.Route"

2.2.193.3. Consumes

- /

2.2.193.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.193.5. Tags

- oapiv1

2.2.194. create a SelfSubjectRulesReview

POST /oapi/v1/namespaces/{namespace}/selfsubjectrulesreviews

2.2.194.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 2.3.211 , "v1.SelfSubject RulesReview"	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	

2.2.194.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.211 , "v1.SelfSubjectRulesReview"

2.2.194.3. Consumes

- /

2.2.194.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.194.5. Tags

- oapiv1

2.2.195. create a SubjectAccessReview

POST /oapi/v1/namespaces/{namespace}/subjectaccessreviews

2.2.195.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 2.3.219 , "v1.SubjectAccessReview"	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	

2.2.195.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.219 , "v1.SubjectAccessReview"

2.2.195.3. Consumes

- /

2.2.195.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.195.5. Tags

- oapiv1

2.2.196. delete collection of Template

```
DELETE /oapi/v1/namespaces/{namespace}/templates
```

2.2.196.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamet er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParamet er	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	
QueryParamet er	resourceVersio n	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	
QueryParamet er	timeoutSecond s	Timeout for the list/watch call.	false	integer	

Type	Name	Description	Required	Schema	Default
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	

2.2.196.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.11 , “unversioned.Status”

2.2.196.3. Consumes

- /

2.2.196.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.196.5. Tags

- oapiv1

2.2.197. create a Template

POST /oapi/v1/namespaces/{namespace}/templates

2.2.197.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 2.3.22 8, “v1.Template”	

Type	Name	Description	Required	Schema	Default
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	

2.2.197.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.228, "v1.Template"

2.2.197.3. Consumes

- /

2.2.197.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.197.5. Tags

- oapiv1

2.2.198. list or watch objects of kind Template

```
GET /oapi/v1/namespaces/{namespace}/templates
```

2.2.198.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParameter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParameter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	
QueryParameter	resourceVersion	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	
QueryParameter	timeoutSeconds	Timeout for the list/watch call.	false	integer	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	

2.2.198.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.229, "v1.TemplateList"

2.2.198.3. Consumes

- /

2.2.198.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.198.5. Tags

- oapiv1

2.2.199. delete a Template

```
DELETE /oapi/v1/namespaces/{namespace}/templates/{name}
```

2.2.199.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 2.3.61, "v1.DeleteOptions"	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParameter	name	name of the Template	true	string	

2.2.199.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.11, "unversioned.Status"

2.2.199.3. Consumes

- /

2.2.199.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.199.5. Tags

- oapiv1

2.2.200. partially update the specified Template

```
PATCH /oapi/v1/namespaces/{namespace}/templates/{name}
```

2.2.200.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 2.3.10, "unversioned.Patch"	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParameter	name	name of the Template	true	string	

2.2.200.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.228, "v1.Template"

2.2.200.3. Consumes

- application/json-patch+json

- application/merge-patch+json
- application/strategic-merge-patch+json

2.2.200.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.200.5. Tags

- oapiv1

2.2.201. replace the specified Template

```
PUT /oapi/v1/namespaces/{namespace}/templates/{name}
```

2.2.201.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 2.3.228 , "v1.Template"	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParameter	name	name of the Template	true	string	

2.2.201.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.228 , "v1.Template"

2.2.201.3. Consumes

- /

2.2.201.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.201.5. Tags

- oapiv1

2.2.202. read the specified Template

```
GET /oapi/v1/namespaces/{namespace}/templates/{name}
```

2.2.202.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	export	Should this value be exported. Export strips fields that a user can not specify.	false	boolean	
QueryParamet er	exact	Should the export be exact. Exact export maintains cluster-specific fields like 'Namespace'	false	boolean	
PathParamet er	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParamet er	name	name of the Template	true	string	

2.2.202.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.228, "v1.Template"

2.2.202.3. Consumes

- /

2.2.202.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.202.5. Tags

- oapiv1

2.2.203. delete collection of NetNamespace

```
DELETE /oapi/v1/netnamespaces
```

2.2.203.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamet er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParameter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	
QueryParameter	resourceVersion	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	
QueryParameter	timeoutSeconds	Timeout for the list/watch call.	false	integer	

2.2.203.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.11 , “unversioned.Status”

2.2.203.3. Consumes

- /

2.2.203.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.203.5. Tags

- oapiv1

2.2.204. create a NetNamespace

POST /oapi/v1/netnamespaces

2.2.204.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 2.3.147 , "v1.NetNames pace"	

2.2.204.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.147 , "v1.NetNamespace"

2.2.204.3. Consumes

- /

2.2.204.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.204.5. Tags

- oapiv1

2.2.205. list or watch objects of kind NetNamespace

GET /oapi/v1/netnamespaces

2.2.205.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamet er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParamet er	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	
QueryParamet er	resourceVersio n	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	
QueryParamet er	timeoutSecond s	Timeout for the list/watch call.	false	integer	

2.2.205.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.148 , “v1.NetNamespaceList”

2.2.205.3. Consumes

- /

2.2.205.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.205.5. Tags

- oapiv1

2.2.206. delete a NetNamespace

```
DELETE /oapi/v1/netnamespaces/{name}
```

2.2.206.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 2.3.61 , “v1.DeleteOpti ons”	
PathParameter	name	name of the NetNamespac e	true	string	

2.2.206.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.11 , “unversioned.Status”

2.2.206.3. Consumes

- /

2.2.206.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.206.5. Tags

- oapiv1

2.2.207. partially update the specified NetNamespace

PATCH /oapi/v1/netnamespaces/{name}

2.2.207.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 2.3.10, "unversioned.Patch"	
PathParameter	name	name of the NetNamespac e	true	string	

2.2.207.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.147, "v1.NetNamespace"

2.2.207.3. Consumes

- application/json-patch+json
- application/merge-patch+json
- application/strategic-merge-patch+json

2.2.207.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.207.5. Tags

- oapiv1

2.2.208. replace the specified NetNamespace

```
PUT /oapi/v1/netnamespaces/{name}
```

2.2.208.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 2.3.147 , "v1.NetNames pace"	
PathParameter	name	name of the NetNamespac e	true	string	

2.2.208.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.147 , "v1.NetNamespace"

2.2.208.3. Consumes

- /

2.2.208.4. Produces

- application/json
- application/yaml

- application/vnd.kubernetes.protobuf

2.2.208.5. Tags

- oapiv1

2.2.209. read the specified NetNamespace

GET /oapi/v1/netnamespaces/{name}

2.2.209.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	export	Should this value be exported. Export strips fields that a user can not specify.	false	boolean	
QueryParamet er	exact	Should the export be exact. Exact export maintains cluster-specific fields like 'Namespace'	false	boolean	
PathParameter	name	name of the NetNamespac e	true	string	

2.2.209.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.147, "v1.NetNamespace"

2.2.209.3. Consumes

- /

2.2.209.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.209.5. Tags

- oapiv1

2.2.210. delete collection of OAuthAccessToken

```
DELETE /oapi/v1/oauthaccesstokens
```

2.2.210.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamet er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParamet er	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParam er	resourceVersio n	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	
QueryParam er	timeoutSecond s	Timeout for the list/watch call.	false	integer	

2.2.210.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.11 , “unversioned.Status”

2.2.210.3. Consumes

- /

2.2.210.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.210.5. Tags

- oapiv1

2.2.211. create a OAuthAccessToken

POST /oapi/v1/oauthaccesstokens

2.2.211.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 2.3.149 , "v1.OAuthAcce ssToken"	

2.2.211.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.149 , "v1.OAuthAccessToken"

2.2.211.3. Consumes

- /

2.2.211.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.211.5. Tags

- oapiv1

2.2.212. list or watch objects of kind OAuthAccessToken

GET /oapi/v1/oauthaccesstokens

2.2.212.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParamet er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamet er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParamet er	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	
QueryParamet er	resourceVersio n	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	
QueryParamet er	timeoutSecond s	Timeout for the list/watch call.	false	integer	

2.2.212.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.150 , "v1.OAuthAccessTokenList"

2.2.212.3. Consumes

- /

2.2.212.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.212.5. Tags

- oapiv1

2.2.213. delete a OAuthAccessToken

```
DELETE /oapi/v1/oauthaccessstokens/{name}
```

2.2.213.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 2.3.61 , "v1.DeleteOpti ons"	
PathParameter	name	name of the OAuthAccessT oken	true	string	

2.2.213.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.11 , "unversioned.Status"

2.2.213.3. Consumes

- /

2.2.213.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.213.5. Tags

- oapiv1

2.2.214. partially update the specified OAuthAccessToken

PATCH /oapi/v1/oauthaccessstokens/{name}

2.2.214.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 2.3.10, "unversioned.Patch"	
PathParameter	name	name of the OAuthAccessT oken	true	string	

2.2.214.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.149, "v1.OAuthAccessToken"

2.2.214.3. Consumes

- application/json-patch+json
- application/merge-patch+json
- application/strategic-merge-patch+json

2.2.214.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.214.5. Tags

- oapiv1

2.2.215. replace the specified OAuthAccessToken

```
PUT /oapi/v1/oauthaccesstokens/{name}
```

2.2.215.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParameter	body		true	Section 2.3.149 , "v1.OAuthAccessToken"	
PathParameter	name	name of the OAuthAccessToken	true	string	

2.2.215.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.149 , "v1.OAuthAccessToken"

2.2.215.3. Consumes

- /

2.2.215.4. Produces

- application/json
- application/yaml

- application/vnd.kubernetes.protobuf

2.2.215.5. Tags

- oapiv1

2.2.216. read the specified OAuthAccessToken

GET /oapi/v1/oauthaccesstokens/{name}

2.2.216.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	export	Should this value be exported. Export strips fields that a user can not specify.	false	boolean	
QueryParamet er	exact	Should the export be exact. Exact export maintains cluster-specific fields like 'Namespace'	false	boolean	
PathParameter	name	name of the OAuthAccessT oken	true	string	

2.2.216.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.149, "v1.OAuthAccessToken"

2.2.216.3. Consumes

- /

2.2.216.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.216.5. Tags

- oapiv1

2.2.217. delete collection of OAuthAuthorizeToken

```
DELETE /oapi/v1/oauthauthorizetokens
```

2.2.217.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamet er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParamet er	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParamter	resourceVersion	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	
QueryParamter	timeoutSeconds	Timeout for the list/watch call.	false	integer	

2.2.217.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.11 , “unversioned.Status”

2.2.217.3. Consumes

- /

2.2.217.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.217.5. Tags

- oapiv1

2.2.218. create a OAuthAuthorizeToken

POST /oapi/v1/oauthauthorizetokens

2.2.218.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 2.3.15 1 , "v1.OAuthAuth orizeToken"	

2.2.218.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.151 , "v1.OAuthAuthorizeToken"

2.2.218.3. Consumes

- /

2.2.218.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.218.5. Tags

- oapiv1

2.2.219. list or watch objects of kind OAuthAuthorizeToken

```
GET /oapi/v1/oauthauthorizetokens
```

2.2.219.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParamet er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamet er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParamet er	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	
QueryParamet er	resourceVersio n	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	
QueryParamet er	timeoutSecond s	Timeout for the list/watch call.	false	integer	

2.2.219.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.152, "v1.OAuthAuthorizeTokenList"

2.2.219.3. Consumes

- /

2.2.219.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.219.5. Tags

- oapiv1

2.2.220. delete a OAuthAuthorizeToken

```
DELETE /oapi/v1/oauthauthorizetokens/{name}
```

2.2.220.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 2.3.61, "v1.DeleteOptions"	
PathParameter	name	name of the OAuthAuthorizeToken	true	string	

2.2.220.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.11, "unversioned.Status"

2.2.220.3. Consumes

- /

2.2.220.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.220.5. Tags

- oapiv1

2.2.221. partially update the specified OAuthAuthorizeToken

PATCH /oapi/v1/oauthauthorizetokens/{name}

2.2.221.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 2.3.10, "unversioned.Patch"	
PathParameter	name	name of the OAuthAuthorizeToken	true	string	

2.2.221.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.151, "v1.OAuthAuthorizeToken"

2.2.221.3. Consumes

- application/json-patch+json
- application/merge-patch+json
- application/strategic-merge-patch+json

2.2.221.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.221.5. Tags

- oapiv1

2.2.222. replace the specified OAuthAuthorizeToken

```
PUT /oapi/v1/oauthauthorizetokens/{name}
```

2.2.222.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParameter	body		true	Section 2.3.151 , "v1.OAuthAuthorizeToken"	
PathParameter	name	name of the OAuthAuthorizeToken	true	string	

2.2.222.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.151 , "v1.OAuthAuthorizeToken"

2.2.222.3. Consumes

- /

2.2.222.4. Produces

- application/json
- application/yaml

- application/vnd.kubernetes.protobuf

2.2.222.5. Tags

- oapiv1

2.2.223. read the specified OAuthAuthorizeToken

GET /oapi/v1/oauthauthorizetokens/{name}

2.2.223.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	export	Should this value be exported. Export strips fields that a user can not specify.	false	boolean	
QueryParamet er	exact	Should the export be exact. Exact export maintains cluster-specific fields like 'Namespace'	false	boolean	
PathParameter	name	name of the OAuthAuthorizeToken	true	string	

2.2.223.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.151 , "v1.OAuthAuthorizeToken"

2.2.223.3. Consumes

- /

2.2.223.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.223.5. Tags

- oapiv1

2.2.224. delete collection of OAuthClientAuthorization

```
DELETE /oapi/v1/oauthclientauthorizations
```

2.2.224.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamet er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParamet er	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParamet er	resourceVersio n	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	
QueryParamet er	timeoutSecond s	Timeout for the list/watch call.	false	integer	

2.2.224.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.11 , "unversioned.Status"

2.2.224.3. Consumes

- /

2.2.224.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.224.5. Tags

- oapiv1

2.2.225. create a OAuthClientAuthorization

POST /oapi/v1/oauthclientauthorizations

2.2.225.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 2.3.154 , "v1.OAuthClie ntAuthorization "	

2.2.225.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.154 , "v1.OAuthClientAuthorization"

2.2.225.3. Consumes

- /

2.2.225.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.225.5. Tags

- oapiv1

2.2.226. list or watch objects of kind OAuthClientAuthorization

```
GET /oapi/v1/oauthclientauthorizations
```

2.2.226.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParamet er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamet er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParamet er	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	
QueryParamet er	resourceVersio n	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	
QueryParamet er	timeoutSecond s	Timeout for the list/watch call.	false	integer	

2.2.226.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.155 , “v1.OAuthClientAuthorizationList”

2.2.226.3. Consumes

- /

2.2.226.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.226.5. Tags

- oapiv1

2.2.227. delete a OAuthClientAuthorization

```
DELETE /oapi/v1/oauthclientauthorizations/{name}
```

2.2.227.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 2.3.61 , “v1.DeleteOpti ons”	
PathParameter	name	name of the OAuthClientAu thorization	true	string	

2.2.227.2. Responses

HTTP Code	Description	Schema
-----------	-------------	--------

HTTP Code	Description	Schema
200	success	Section 2.3.11 , “unversioned.Status”

2.2.227.3. Consumes

- /

2.2.227.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.227.5. Tags

- oapiv1

2.2.228. partially update the specified OAuthClientAuthorization

```
PATCH /oapi/v1/oauthclientauthorizations/{name}
```

2.2.228.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 2.3.10 , “unversioned.P atch”	
PathParameter	name	name of the OAuthClientAu thorization	true	string	

2.2.228.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.154 , “v1.OAuthClientAuthorization”

2.2.228.3. Consumes

- application/json-patch+json
- application/merge-patch+json
- application/strategic-merge-patch+json

2.2.228.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.228.5. Tags

- oapiv1

2.2.229. replace the specified OAuthClientAuthorization

```
PUT /oapi/v1/oauthclientauthorizations/{name}
```

2.2.229.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 2.3.154 , "v1.OAuthClie ntAuthorization "	
PathParameter	name	name of the OAuthClientAu thorization	true	string	

2.2.229.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.154 , "v1.OAuthClientAuthorization"

2.2.229.3. Consumes

- /

2.2.229.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.229.5. Tags

- oapiv1

2.2.230. read the specified OAuthClientAuthorization

```
GET /oapi/v1/oauthclientauthorizations/{name}
```

2.2.230.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	export	Should this value be exported. Export strips fields that a user can not specify.	false	boolean	
QueryParamet er	exact	Should the export be exact. Exact export maintains cluster-specific fields like 'Namespace'	false	boolean	
PathParameter	name	name of the OAuthClientAu thorization	true	string	

2.2.230.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.154, "v1.OAuthClientAuthorization"

2.2.230.3. Consumes

- /

2.2.230.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.230.5. Tags

- oapiv1

2.2.231. delete collection of OAuthClient

```
DELETE /oapi/v1/oauthclients
```

2.2.231.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamet er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParamet er	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	
QueryParamet er	resourceVersio n	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	
QueryParamet er	timeoutSecond s	Timeout for the list/watch call.	false	integer	

2.2.231.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.11 , “unversioned.Status”

2.2.231.3. Consumes

- /

2.2.231.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.231.5. Tags

- oapiv1

2.2.232. create a OAuthClient

POST /oapi/v1/oauthclients

2.2.232.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 2.3.153 , "v1.OAuthClie nt"	

2.2.232.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.153 , "v1.OAuthClient"

2.2.232.3. Consumes

- /

2.2.232.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.232.5. Tags

- oapiv1

2.2.233. list or watch objects of kind OAuthClient

GET /oapi/v1/oauthclients

2.2.233.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamet er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParamet er	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	
QueryParamet er	resourceVersio n	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	
QueryParamet er	timeoutSecond s	Timeout for the list/watch call.	false	integer	

2.2.233.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.156 , “v1.OAuthClientList”

2.2.233.3. Consumes

- /

2.2.233.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.233.5. Tags

- oapiv1

2.2.234. delete a OAuthClient

```
DELETE /oapi/v1/oauthclients/{name}
```

2.2.234.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 2.3.61 , “v1.DeleteOpti ons”	
PathParameter	name	name of the OAuthClient	true	string	

2.2.234.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.11 , “unversioned.Status”

2.2.234.3. Consumes

- /

2.2.234.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.234.5. Tags

- oapiv1

2.2.235. partially update the specified OAuthClient

PATCH /oapi/v1/oauthclients/{name}

2.2.235.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 2.3.10, "unversioned.Patch"	
PathParameter	name	name of the OAuthClient	true	string	

2.2.235.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.153, "v1.OAuthClient"

2.2.235.3. Consumes

- application/json-patch+json
- application/merge-patch+json
- application/strategic-merge-patch+json

2.2.235.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.235.5. Tags

- oapiv1

2.2.236. replace the specified OAuthClient

```
PUT /oapi/v1/oauthclients/{name}
```

2.2.236.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParameter	body		true	Section 2.3.153 , "v1.OAuthClient"	
PathParameter	name	name of the OAuthClient	true	string	

2.2.236.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.153 , "v1.OAuthClient"

2.2.236.3. Consumes

- /

2.2.236.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.236.5. Tags

- oapiv1

2.2.237. read the specified OAuthClient

```
GET /oapi/v1/oauthclients/{name}
```

2.2.237.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	export	Should this value be exported. Export strips fields that a user can not specify.	false	boolean	
QueryParamet er	exact	Should the export be exact. Exact export maintains cluster-specific fields like 'Namespace'	false	boolean	
PathParameter	name	name of the OAuthClient	true	string	

2.2.237.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.153, "v1.OAuthClient"

2.2.237.3. Consumes

- /

2.2.237.4. Produces

- application/json

- application/yaml
- application/vnd.kubernetes.protobuf

2.2.237.5. Tags

- oapiv1

2.2.238. create a Policy

POST /oapi/v1/policies

2.2.238.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 2.3.166, "v1.Policy"	

2.2.238.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.166, "v1.Policy"

2.2.238.3. Consumes

- /

2.2.238.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.238.5. Tags

- oapiv1

2.2.239. list or watch objects of kind Policy

GET /oapi/v1/policies

2.2.239.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamet er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParamet er	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersio n.	false	boolean	
QueryParamet er	resourceVersio n	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	
QueryParamet er	timeoutSecond s	Timeout for the list/watch call.	false	integer	

2.2.239.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.169, "v1.PolicyList"

2.2.239.3. Consumes

- /

2.2.239.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.239.5. Tags

- oapiv1

2.2.240. create a PolicyBinding

POST /oapi/v1/policybindings

2.2.240.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 2.3.167, "v1.PolicyBinding"	

2.2.240.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.167, "v1.PolicyBinding"

2.2.240.3. Consumes

- /

2.2.240.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.240.5. Tags

- oapiv1

2.2.241. list or watch objects of kind PolicyBinding

GET /oapi/v1/policybindings

2.2.241.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamet er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParamet er	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParamet er	resourceVersio n	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	
QueryParamet er	timeoutSecond s	Timeout for the list/watch call.	false	integer	

2.2.241.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.168, "v1.PolicyBindingList"

2.2.241.3. Consumes

- /

2.2.241.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.241.5. Tags

- oapiv1

2.2.242. create a Template

```
POST /oapi/v1/processedtemplates
```

2.2.242.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 2.3.228 , "v1.Template"	

2.2.242.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.228 , "v1.Template"

2.2.242.3. Consumes

- /

2.2.242.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.242.5. Tags

- oapiv1

2.2.243. create a ProjectRequest

POST /oapi/v1/projectrequests

2.2.243.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	

Type	Name	Description	Required	Schema	Default
BodyParameter	body		true	Section 2.3.175 , "v1.ProjectRequest"	

2.2.243.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.175 , "v1.ProjectRequest"

2.2.243.3. Consumes

- /

2.2.243.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.243.5. Tags

- oapiv1

2.2.244. list objects of kind ProjectRequest

```
GET /oapi/v1/projectrequests
```

2.2.244.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParamet er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParamet er	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	
QueryParamet er	resourceVersio n	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	
QueryParamet er	timeoutSecond s	Timeout for the list/watch call.	false	integer	

2.2.244.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.11 , “unversioned.Status”

2.2.244.3. Consumes

- /

2.2.244.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.244.5. Tags

- oapiv1

2.2.245. create a Project

POST /oapi/v1/projects

2.2.245.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 2.3.173 , "v1.Project"	

2.2.245.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.173 , "v1.Project"

2.2.245.3. Consumes

- /

2.2.245.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.245.5. Tags

- oapiv1

2.2.246. list or watch objects of kind Project

GET /oapi/v1/projects

2.2.246.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamet er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParamet er	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	
QueryParamet er	resourceVersio n	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParamet er	timeoutSecond s	Timeout for the list/watch call.	false	integer	

2.2.246.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.174, "v1.ProjectList"

2.2.246.3. Consumes

- /

2.2.246.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.246.5. Tags

- oapiv1

2.2.247. delete a Project

```
DELETE /oapi/v1/projects/{name}
```

2.2.247.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
PathParameter	name	name of the Project	true	string	

2.2.247.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.11 , “unversioned.Status”

2.2.247.3. Consumes

- /

2.2.247.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.247.5. Tags

- oapiv1

2.2.248. partially update the specified Project

```
PATCH /oapi/v1/projects/{name}
```

2.2.248.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 2.3.10 , “unversioned.P atch”	
PathParameter	name	name of the Project	true	string	

2.2.248.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.173 , “v1.Project”

2.2.248.3. Consumes

- application/json-patch+json
- application/merge-patch+json
- application/strategic-merge-patch+json

2.2.248.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.248.5. Tags

- oapiv1

2.2.249. replace the specified Project

```
PUT /oapi/v1/projects/{name}
```

2.2.249.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 2.3.173, "v1.Project"	
PathParameter	name	name of the Project	true	string	

2.2.249.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.173, "v1.Project"

2.2.249.3. Consumes

- /

2.2.249.4. Produces

- application/json

- application/yaml
- application/vnd.kubernetes.protobuf

2.2.249.5. Tags

- oapiv1

2.2.250. read the specified Project

```
GET /oapi/v1/projects/{name}
```

2.2.250.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
PathParameter	name	name of the Project	true	string	

2.2.250.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.173, "v1.Project"

2.2.250.3. Consumes

- /

2.2.250.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.250.5. Tags

- oapiv1

2.2.251. create a ResourceAccessReview

```
POST /oapi/v1/resourceaccessreviews
```

2.2.251.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 2.3.182 , "v1.ResourceA ccessReview"	

2.2.251.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.182 , "v1.ResourceAccessReview"

2.2.251.3. Consumes

- /

2.2.251.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.251.5. Tags

- oapiv1

2.2.252. create a RoleBinding

POST /oapi/v1/rolebindings

2.2.252.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	

Type	Name	Description	Required	Schema	Default
BodyParameter	body		true	Section 2.3.190 , “v1.RoleBinding”	

2.2.252.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.190 , “v1.RoleBinding”

2.2.252.3. Consumes

- /

2.2.252.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.252.5. Tags

- oapiv1

2.2.253. list objects of kind RoleBinding

GET /oapi/v1/rolebindings

2.2.253.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamter	pretty	If 'true', then the output is pretty printed.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParamet er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamet er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParamet er	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	
QueryParamet er	resourceVersio n	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	
QueryParamet er	timeoutSecond s	Timeout for the list/watch call.	false	integer	

2.2.253.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.191, "v1.RoleBindingList"

2.2.253.3. Consumes

- /

2.2.253.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.253.5. Tags

- oapiv1

2.2.254. create a Role

POST /oapi/v1/roles

2.2.254.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 2.3.189, "v1.Role"	

2.2.254.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.189, "v1.Role"

2.2.254.3. Consumes

- /

2.2.254.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.254.5. Tags

- oapiv1

2.2.255. list objects of kind Role

GET /oapi/v1/roles

2.2.255.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamet er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParamet er	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParamet er	resourceVersio n	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	
QueryParamet er	timeoutSecond s	Timeout for the list/watch call.	false	integer	

2.2.255.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.192, "v1.RoleList"

2.2.255.3. Consumes

- /

2.2.255.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.255.5. Tags

- oapiv1

2.2.256. create a Route

POST /oapi/v1/routes

2.2.256.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 2.3.194 , “v1.Route”	

2.2.256.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.194 , “v1.Route”

2.2.256.3. Consumes

- /

2.2.256.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.256.5. Tags

- oapiv1

2.2.257. list or watch objects of kind Route

GET /oapi/v1/routes

2.2.257.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParamet er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamet er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParamet er	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersio n.	false	boolean	
QueryParamet er	resourceVersio n	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	
QueryParamet er	timeoutSecond s	Timeout for the list/watch call.	false	integer	

2.2.257.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.197, "v1.RouteList"

2.2.257.3. Consumes

- /

2.2.257.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.257.5. Tags

- oapiv1

2.2.258. create a SelfSubjectRulesReview

POST /oapi/v1/selfsubjectrulesreviews

2.2.258.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 2.3.21 1 , "v1.SelfSubject RulesReview"	

2.2.258.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.211 , "v1.SelfSubjectRulesReview"

2.2.258.3. Consumes

- /

2.2.258.4. Produces

- application/json
- application/yaml

- application/vnd.kubernetes.protobuf

2.2.258.5. Tags

- oapiv1

2.2.259. create a SubjectAccessReview

POST /oapi/v1/subjectaccessreviews

2.2.259.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 2.3.219 , "v1.SubjectAcc essReview"	

2.2.259.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.219 , "v1.SubjectAccessReview"

2.2.259.3. Consumes

- /

2.2.259.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.259.5. Tags

- oapiv1

2.2.260. create a Template

POST /oapi/v1/templates

2.2.260.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 2.3.228 , "v1.Template"	

2.2.260.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.228 , "v1.Template"

2.2.260.3. Consumes

- /

2.2.260.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.260.5. Tags

- oapiv1

2.2.261. list or watch objects of kind Template

GET /oapi/v1/templates

2.2.261.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParamet er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamet er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParamet er	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	
QueryParamet er	resourceVersio n	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	
QueryParamet er	timeoutSecond s	Timeout for the list/watch call.	false	integer	

2.2.261.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.229, “v1.TemplateList”

2.2.261.3. Consumes

- /

2.2.261.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.261.5. Tags

- oapiv1

2.2.262. create a UserIdentityMapping

POST /oapi/v1/useridentitymappings

2.2.262.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 2.3.231 , "v1.UserIdentit yMapping"	

2.2.262.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.231 , "v1.UserIdentityMapping"

2.2.262.3. Consumes

- /

2.2.262.4. Produces

- application/json
- application/yaml

- application/vnd.kubernetes.protobuf

2.2.262.5. Tags

- oapiv1

2.2.263. delete a UserIdentityMapping

```
DELETE /oapi/v1/useridentitymappings/{name}
```

2.2.263.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
PathParameter	name	name of the UserIdentityMa pping	true	string	

2.2.263.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.11 , "unversioned.Status"

2.2.263.3. Consumes

- /

2.2.263.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.263.5. Tags

- oapiv1

2.2.264. partially update the specified UserIdentityMapping

```
PATCH /oapi/v1/useridentitymappings/{name}
```


2.2.264.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 2.3.10, “unversioned.Patch”	
PathParameter	name	name of the UserIdentityMa pping	true	string	

2.2.264.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.231, “v1.UserIdentityMapping”

2.2.264.3. Consumes

- application/json-patch+json
- application/merge-patch+json
- application/strategic-merge-patch+json

2.2.264.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.264.5. Tags

- oapiv1

2.2.265. replace the specified UserIdentityMapping

```
PUT /oapi/v1/useridentitymappings/{name}
```

2.2.265.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 2.3.23 1 , "v1.UserIdentit yMapping"	
PathParameter	name	name of the UserIdentityMa pping	true	string	

2.2.265.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.231 , "v1.UserIdentityMapping"

2.2.265.3. Consumes

- /

2.2.265.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.265.5. Tags

- oapiv1

2.2.266. read the specified UserIdentityMapping

```
GET /oapi/v1/useridentitymappings/{name}
```

2.2.266.1. Parameters

Type	Name	Description	Required	Schema	Default
------	------	-------------	----------	--------	---------

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
PathParameter	name	name of the UserIdentityMa pping	true	string	

2.2.266.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.231, "v1.UserIdentityMapping"

2.2.266.3. Consumes

- /

2.2.266.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.266.5. Tags

- oapiv1

2.2.267. delete collection of User

```
DELETE /oapi/v1/users
```

2.2.267.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParamet er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamet er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParamet er	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersio n.	false	boolean	
QueryParamet er	resourceVersio n	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	
QueryParamet er	timeoutSecond s	Timeout for the list/watch call.	false	integer	

2.2.267.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.11 , “unversioned.Status”

2.2.267.3. Consumes

- /

2.2.267.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.267.5. Tags

- oapiv1

2.2.268. create a User

POST /oapi/v1/users

2.2.268.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 2.3.230 , “v1.User”	

2.2.268.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.230 , “v1.User”

2.2.268.3. Consumes

- /

2.2.268.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.268.5. Tags

- oapiv1

2.2.269. list or watch objects of kind User

GET /oapi/v1/users

2.2.269.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamet er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParamet er	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParamet er	resourceVersio n	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	
QueryParamet er	timeoutSecond s	Timeout for the list/watch call.	false	integer	

2.2.269.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.232, "v1.UserList"

2.2.269.3. Consumes

- /

2.2.269.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.269.5. Tags

- oapiv1

2.2.270. delete a User

```
DELETE /oapi/v1/users/{name}
```

2.2.270.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 2.3.61, "v1.DeleteOptions"	
PathParameter	name	name of the User	true	string	

2.2.270.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.11, "unversioned.Status"

2.2.270.3. Consumes

- /

2.2.270.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.270.5. Tags

- oapiv1

2.2.271. partially update the specified User

```
PATCH /oapi/v1/users/{name}
```

2.2.271.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 2.3.10, "unversioned.Patch"	
PathParameter	name	name of the User	true	string	

2.2.271.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.230, "v1.User"

2.2.271.3. Consumes

- application/json-patch+json
- application/merge-patch+json
- application/strategic-merge-patch+json

2.2.271.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.271.5. Tags

- oapiv1

2.2.272. replace the specified User

```
PUT /oapi/v1/users/{name}
```

2.2.272.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 2.3.230, "v1.User"	
PathParameter	name	name of the User	true	string	

2.2.272.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.230, "v1.User"

2.2.272.3. Consumes

- /

2.2.272.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.272.5. Tags

- oapiv1

2.2.273. read the specified User

```
GET /oapi/v1/users/{name}
```

2.2.273.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParamet er	export	Should this value be exported. Export strips fields that a user can not specify.	false	boolean	
QueryParamet er	exact	Should the export be exact. Exact export maintains cluster-specific fields like 'Namespace'	false	boolean	
PathParameter	name	name of the User	true	string	

2.2.273.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.230, "v1.User"

2.2.273.3. Consumes

- /

2.2.273.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.273.5. Tags

- oapiv1

2.2.274. watch individual changes to a list of BuildConfig

GET /oapi/v1/watch/buildconfigs

2.2.274.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamet er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParamet er	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	
QueryParamet er	resourceVersio n	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	
QueryParamet er	timeoutSecond s	Timeout for the list/watch call.	false	integer	

2.2.274.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.1, “versioned.Event”

2.2.274.3. Consumes

- /

2.2.274.4. Produces

- application/json
- application/json;stream=watch
- application/vnd.kubernetes.protobuf
- application/vnd.kubernetes.protobuf;stream=watch

2.2.274.5. Tags

- oapiv1

2.2.275. watch individual changes to a list of Build

GET /oapi/v1/watch/builds

2.2.275.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamet er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParamet er	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	
QueryParamet er	resourceVersio n	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	
QueryParamet er	timeoutSecond s	Timeout for the list/watch call.	false	integer	

2.2.275.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.1, “versioned.Event”

2.2.275.3. Consumes

- /

2.2.275.4. Produces

- application/json
- application/json;stream=watch
- application/vnd.kubernetes.protobuf
- application/vnd.kubernetes.protobuf;stream=watch

2.2.275.5. Tags

- oapiv1

2.2.276. watch individual changes to a list of ClusterNetwork

GET /oapi/v1/watch/clusternetworks

2.2.276.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamet er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParamet er	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParamet er	resourceVersio n	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	
QueryParamet er	timeoutSecond s	Timeout for the list/watch call.	false	integer	

2.2.276.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.1, “versioned.Event”

2.2.276.3. Consumes

- /

2.2.276.4. Produces

- application/json
- application/json;stream=watch
- application/vnd.kubernetes.protobuf
- application/vnd.kubernetes.protobuf;stream=watch

2.2.276.5. Tags

- oapiv1

2.2.277. watch changes to an object of kind ClusterNetwork

```
GET /oapi/v1/watch/clusternetworks/{name}
```

2.2.277.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamet er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParamet er	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	
QueryParamet er	resourceVersio n	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	
QueryParamet er	timeoutSecond s	Timeout for the list/watch call.	false	integer	
PathParameter	name	name of the ClusterNetwork	true	string	

2.2.277.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.1, “versioned.Event”

2.2.277.3. Consumes

- /

2.2.277.4. Produces

- application/json
- application/json;stream=watch
- application/vnd.kubernetes.protobuf
- application/vnd.kubernetes.protobuf;stream=watch

2.2.277.5. Tags

- oapiv1

2.2.278. watch individual changes to a list of ClusterPolicy

```
GET /oapi/v1/watch/clusterpolicies
```

2.2.278.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamet er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParamet er	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	
QueryParamet er	resourceVersio n	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	
QueryParamet er	timeoutSecond s	Timeout for the list/watch call.	false	integer	

2.2.278.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.1, “versioned.Event”

2.2.278.3. Consumes

- /

2.2.278.4. Produces

- application/json
- application/json;stream=watch
- application/vnd.kubernetes.protobuf

- `application/vnd.kubernetes.protobuf;stream=watch`

2.2.278.5. Tags

- `oapiv1`

2.2.279. watch changes to an object of kind ClusterPolicy

```
GET /oapi/v1/watch/clusterpolicies/{name}
```

2.2.279.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamet er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParamet er	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParamet er	resourceVersio n	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	
QueryParamet er	timeoutSecond s	Timeout for the list/watch call.	false	integer	
PathParameter	name	name of the ClusterPolicy	true	string	

2.2.279.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.1, “versioned.Event”

2.2.279.3. Consumes

- /

2.2.279.4. Produces

- application/json
- application/json;stream=watch
- application/vnd.kubernetes.protobuf
- application/vnd.kubernetes.protobuf;stream=watch

2.2.279.5. Tags

- oapiv1

2.2.280. watch individual changes to a list of ClusterPolicyBinding

GET /oapi/v1/watch/clusterpolicybindings

2.2.280.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamet er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParamet er	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersio n.	false	boolean	
QueryParamet er	resourceVersio n	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	
QueryParamet er	timeoutSecond s	Timeout for the list/watch call.	false	integer	

2.2.280.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.1, “versioned.Event”

2.2.280.3. Consumes

- /

2.2.280.4. Produces

- application/json
- application/json;stream=watch
- application/vnd.kubernetes.protobuf
- application/vnd.kubernetes.protobuf;stream=watch

2.2.280.5. Tags

- oapiv1

2.2.281. watch changes to an object of kind ClusterPolicyBinding

```
GET /oapi/v1/watch/clusterpolicybindings/{name}
```

2.2.281.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamet er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParamet er	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	
QueryParamet er	resourceVersio n	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	
QueryParamet er	timeoutSecond s	Timeout for the list/watch call.	false	integer	
PathParameter	name	name of the ClusterPolicyBinding	true	string	

2.2.281.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.1, “versioned.Event”

2.2.281.3. Consumes

- /

2.2.281.4. Produces

- application/json
- application/json;stream=watch

- application/vnd.kubernetes.protobuf
- application/vnd.kubernetes.protobuf;stream=watch

2.2.281.5. Tags

- oapiv1

2.2.282. watch individual changes to a list of ClusterResourceQuota

GET /oapi/v1/watch/clusterresourcequotas

2.2.282.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamet er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParamet er	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParamet er	resourceVersio n	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	
QueryParamet er	timeoutSecond s	Timeout for the list/watch call.	false	integer	

2.2.282.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.1, “versioned.Event”

2.2.282.3. Consumes

- /

2.2.282.4. Produces

- application/json
- application/json;stream=watch
- application/vnd.kubernetes.protobuf
- application/vnd.kubernetes.protobuf;stream=watch

2.2.282.5. Tags

- oapiv1

2.2.283. watch changes to an object of kind ClusterResourceQuota

```
GET /oapi/v1/watch/clusterresourcequotas/{name}
```

2.2.283.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamet er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParamet er	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	
QueryParamet er	resourceVersio n	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	
QueryParamet er	timeoutSecond s	Timeout for the list/watch call.	false	integer	
PathParameter	name	name of the ClusterResourceQuota	true	string	

2.2.283.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.1, “versioned.Event”

2.2.283.3. Consumes

- /

2.2.283.4. Produces

- application/json
- application/json;stream=watch
- application/vnd.kubernetes.protobuf
- application/vnd.kubernetes.protobuf;stream=watch

2.2.283.5. Tags

- oapiv1

2.2.284. watch individual changes to a list of DeploymentConfig

GET /oapi/v1/watch/deploymentconfigs

2.2.284.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamet er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParamet er	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	
QueryParamet er	resourceVersio n	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	
QueryParamet er	timeoutSecond s	Timeout for the list/watch call.	false	integer	

2.2.284.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.1, “versioned.Event”

2.2.284.3. Consumes

- /

2.2.284.4. Produces

- application/json
- application/json;stream=watch
- application/vnd.kubernetes.protobuf

- `application/vnd.kubernetes.protobuf;stream=watch`

2.2.284.5. Tags

- `oapiv1`

2.2.285. watch individual changes to a list of EgressNetworkPolicy

GET `/oapi/v1/watch/egressnetworkpolicies`

2.2.285.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	<code>pretty</code>	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	<code>labelSelector</code>	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamet er	<code>fieldSelector</code>	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParamet er	<code>watch</code>	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify <code>resourceVersion</code> .	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParamet er	resourceVersio n	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	
QueryParamet er	timeoutSecond s	Timeout for the list/watch call.	false	integer	

2.2.285.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.1, “versioned.Event”

2.2.285.3. Consumes

- /

2.2.285.4. Produces

- application/json
- application/json;stream=watch
- application/vnd.kubernetes.protobuf
- application/vnd.kubernetes.protobuf;stream=watch

2.2.285.5. Tags

- oapiv1

2.2.286. watch individual changes to a list of Group

```
GET /oapi/v1/watch/groups
```

2.2.286.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamet er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParamet er	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	
QueryParamet er	resourceVersio n	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	
QueryParamet er	timeoutSecond s	Timeout for the list/watch call.	false	integer	

2.2.286.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.1, “versioned.Event”

2.2.286.3. Consumes

- /

2.2.286.4. Produces

- application/json
- application/json;stream=watch
- application/vnd.kubernetes.protobuf
- application/vnd.kubernetes.protobuf;stream=watch

2.2.286.5. Tags

- oapiv1

2.2.287. watch changes to an object of kind Group

```
GET /oapi/v1/watch/groups/{name}
```

2.2.287.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamet er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParamet er	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersio n.	false	boolean	
QueryParamet er	resourceVersio n	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	
QueryParamet er	timeoutSecond s	Timeout for the list/watch call.	false	integer	
PathParameter	name	name of the Group	true	string	

2.2.287.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.1, “versioned.Event”

2.2.287.3. Consumes

- /

2.2.287.4. Produces

- application/json
- application/json;stream=watch
- application/vnd.kubernetes.protobuf

- application/vnd.kubernetes.protobuf;stream=watch

2.2.287.5. Tags

- oapiv1

2.2.288. watch individual changes to a list of HostSubnet

GET /oapi/v1/watch/hostsubnets

2.2.288.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamet er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParamet er	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParam er	resourceVersio n	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	
QueryParam er	timeoutSecond s	Timeout for the list/watch call.	false	integer	

2.2.288.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.1, “versioned.Event”

2.2.288.3. Consumes

- /

2.2.288.4. Produces

- application/json
- application/json;stream=watch
- application/vnd.kubernetes.protobuf
- application/vnd.kubernetes.protobuf;stream=watch

2.2.288.5. Tags

- oapiv1

2.2.289. watch changes to an object of kind HostSubnet

```
GET /oapi/v1/watch/hostsubnets/{name}
```

2.2.289.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamet er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParamet er	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	
QueryParamet er	resourceVersio n	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	
QueryParamet er	timeoutSecond s	Timeout for the list/watch call.	false	integer	
PathParameter	name	name of the HostSubnet	true	string	

2.2.289.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.1, “versioned.Event”

2.2.289.3. Consumes

- /

2.2.289.4. Produces

- application/json
- application/json;stream=watch
- application/vnd.kubernetes.protobuf
- application/vnd.kubernetes.protobuf;stream=watch

2.2.289.5. Tags

- oapiv1

2.2.290. watch individual changes to a list of Identity

GET /oapi/v1/watch/identities

2.2.290.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamet er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParamet er	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	
QueryParamet er	resourceVersio n	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	
QueryParamet er	timeoutSecond s	Timeout for the list/watch call.	false	integer	

2.2.290.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.1, “versioned.Event”

2.2.290.3. Consumes

- /

2.2.290.4. Produces

- application/json
- application/json;stream=watch
- application/vnd.kubernetes.protobuf

- `application/vnd.kubernetes.protobuf;stream=watch`

2.2.290.5. Tags

- `oapiv1`

2.2.291. watch changes to an object of kind Identity

GET `/oapi/v1/watch/identities/{name}`

2.2.291.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamet er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParamet er	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParamet er	resourceVersio n	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	
QueryParamet er	timeoutSecond s	Timeout for the list/watch call.	false	integer	
PathParameter	name	name of the Identity	true	string	

2.2.291.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.1, “versioned.Event”

2.2.291.3. Consumes

- /

2.2.291.4. Produces

- application/json
- application/json;stream=watch
- application/vnd.kubernetes.protobuf
- application/vnd.kubernetes.protobuf;stream=watch

2.2.291.5. Tags

- oapiv1

2.2.292. watch individual changes to a list of Image

GET /oapi/v1/watch/images

2.2.292.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamet er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParamet er	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersio n.	false	boolean	
QueryParamet er	resourceVersio n	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	
QueryParamet er	timeoutSecond s	Timeout for the list/watch call.	false	integer	

2.2.292.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.1, “versioned.Event”

2.2.292.3. Consumes

- /

2.2.292.4. Produces

- application/json
- application/json;stream=watch
- application/vnd.kubernetes.protobuf
- application/vnd.kubernetes.protobuf;stream=watch

2.2.292.5. Tags

- oapiv1

2.2.293. watch changes to an object of kind Image

```
GET /oapi/v1/watch/images/{name}
```

2.2.293.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamet er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParamet er	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersio n.	false	boolean	
QueryParamet er	resourceVersio n	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	
QueryParamet er	timeoutSecond s	Timeout for the list/watch call.	false	integer	
PathParameter	name	name of the Image	true	string	

2.2.293.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.1, “versioned.Event”

2.2.293.3. Consumes

- /

2.2.293.4. Produces

- application/json
- application/json;stream=watch
- application/vnd.kubernetes.protobuf

- application/vnd.kubernetes.protobuf;stream=watch

2.2.293.5. Tags

- oapiv1

2.2.294. watch individual changes to a list of ImageStream

GET /oapi/v1/watch/imagestreams

2.2.294.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamet er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParamet er	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParam er	resourceVersio n	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	
QueryParam er	timeoutSecond s	Timeout for the list/watch call.	false	integer	

2.2.294.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.1, “versioned.Event”

2.2.294.3. Consumes

- /

2.2.294.4. Produces

- application/json
- application/json;stream=watch
- application/vnd.kubernetes.protobuf
- application/vnd.kubernetes.protobuf;stream=watch

2.2.294.5. Tags

- oapiv1

2.2.295. watch individual changes to a list of BuildConfig

```
GET /oapi/v1/watch/namespaces/{namespace}/buildconfigs
```

2.2.295.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamet er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParamet er	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	
QueryParamet er	resourceVersio n	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	
QueryParamet er	timeoutSecond s	Timeout for the list/watch call.	false	integer	

Type	Name	Description	Required	Schema	Default
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	

2.2.295.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.1, “versioned.Event”

2.2.295.3. Consumes

- /

2.2.295.4. Produces

- application/json
- application/json;stream=watch
- application/vnd.kubernetes.protobuf
- application/vnd.kubernetes.protobuf;stream=watch

2.2.295.5. Tags

- oapiv1

2.2.296. watch changes to an object of kind BuildConfig

```
GET /oapi/v1/watch/namespaces/{namespace}/buildconfigs/{name}
```

2.2.296.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParamet er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamet er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParamet er	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	
QueryParamet er	resourceVersio n	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	
QueryParamet er	timeoutSecond s	Timeout for the list/watch call.	false	integer	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	

Type	Name	Description	Required	Schema	Default
PathParameter	name	name of the BuildConfig	true	string	

2.2.296.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.1, “versioned.Event”

2.2.296.3. Consumes

- /

2.2.296.4. Produces

- application/json
- application/json;stream=watch
- application/vnd.kubernetes.protobuf
- application/vnd.kubernetes.protobuf;stream=watch

2.2.296.5. Tags

- oapiv1

2.2.297. watch individual changes to a list of Build

GET /oapi/v1/watch/namespaces/{namespace}/builds

2.2.297.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParamet er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParamet er	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersio n.	false	boolean	
QueryParamet er	resourceVersio n	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	
QueryParamet er	timeoutSecond s	Timeout for the list/watch call.	false	integer	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	

2.2.297.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.1, “versioned.Event”

2.2.297.3. Consumes

- /

2.2.297.4. Produces

- application/json
- application/json;stream=watch
- application/vnd.kubernetes.protobuf
- application/vnd.kubernetes.protobuf;stream=watch

2.2.297.5. Tags

- oapiv1

2.2.298. watch changes to an object of kind Build

```
GET /oapi/v1/watch/namespaces/{namespace}/builds/{name}
```

2.2.298.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamet er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParamet er	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	
QueryParamet er	resourceVersio n	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	
QueryParamet er	timeoutSecond s	Timeout for the list/watch call.	false	integer	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParameter	name	name of the Build	true	string	

2.2.298.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.1, “versioned.Event”

2.2.298.3. Consumes

- /

2.2.298.4. Produces

- application/json
- application/json;stream=watch
- application/vnd.kubernetes.protobuf
- application/vnd.kubernetes.protobuf;stream=watch

2.2.298.5. Tags

- oapiv1

2.2.299. watch individual changes to a list of DeploymentConfig

```
GET /oapi/v1/watch/namespaces/{namespace}/deploymentconfigs
```

2.2.299.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamet er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParamet er	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParamet er	resourceVersio n	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	
QueryParamet er	timeoutSecond s	Timeout for the list/watch call.	false	integer	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	

2.2.299.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.1, “versioned.Event”

2.2.299.3. Consumes

- /

2.2.299.4. Produces

- application/json
- application/json;stream=watch
- application/vnd.kubernetes.protobuf
- application/vnd.kubernetes.protobuf;stream=watch

2.2.299.5. Tags

- oapiv1

2.2.300. watch changes to an object of kind DeploymentConfig

-

GET /oapi/v1/watch/namespaces/{namespace}/deploymentconfigs/{name}

2.2.300.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamet er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParamet er	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	
QueryParamet er	resourceVersio n	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	
QueryParamet er	timeoutSecond s	Timeout for the list/watch call.	false	integer	

Type	Name	Description	Required	Schema	Default
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParameter	name	name of the DeploymentConfig	true	string	

2.2.300.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.1, “versioned.Event”

2.2.300.3. Consumes

- /

2.2.300.4. Produces

- application/json
- application/json;stream=watch
- application/vnd.kubernetes.protobuf
- application/vnd.kubernetes.protobuf;stream=watch

2.2.300.5. Tags

- oapiv1

2.2.301. watch individual changes to a list of EgressNetworkPolicy

```
GET /oapi/v1/watch/namespaces/{namespace}/egressnetworkpolicies
```

2.2.301.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParamet er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamet er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParamet er	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersio n.	false	boolean	
QueryParamet er	resourceVersio n	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	
QueryParamet er	timeoutSecond s	Timeout for the list/watch call.	false	integer	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	

2.2.301.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.1, “versioned.Event”

2.2.301.3. Consumes

- /

2.2.301.4. Produces

- application/json
- application/json;stream=watch
- application/vnd.kubernetes.protobuf
- application/vnd.kubernetes.protobuf;stream=watch

2.2.301.5. Tags

- oapiv1

2.2.302. watch changes to an object of kind EgressNetworkPolicy

```
GET /oapi/v1/watch/namespaces/{namespace}/egressnetworkpolicies/{name}
```

2.2.302.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamet er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParamet er	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	
QueryParamet er	resourceVersio n	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	
QueryParamet er	timeoutSecond s	Timeout for the list/watch call.	false	integer	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParameter	name	name of the EgressNetwork Policy	true	string	

2.2.302.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.1, “versioned.Event”

2.2.302.3. Consumes

- /

2.2.302.4. Produces

- application/json
- application/json;stream=watch
- application/vnd.kubernetes.protobuf
- application/vnd.kubernetes.protobuf;stream=watch

2.2.302.5. Tags

- oapiv1

2.2.303. watch individual changes to a list of ImageStream

```
GET /oapi/v1/watch/namespaces/{namespace}/imagestreams
```

2.2.303.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamet er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParamet er	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersio n.	false	boolean	
QueryParamet er	resourceVersio n	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	
QueryParamet er	timeoutSecond s	Timeout for the list/watch call.	false	integer	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	

2.2.303.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.1, “versioned.Event”

2.2.303.3. Consumes

- /

2.2.303.4. Produces

- application/json

- application/json;stream=watch
- application/vnd.kubernetes.protobuf
- application/vnd.kubernetes.protobuf;stream=watch

2.2.303.5. Tags

- oapiv1

2.2.304. watch changes to an object of kind ImageStream

```
GET /oapi/v1/watch/namespaces/{namespace}/imagestreams/{name}
```

2.2.304.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamet er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParamet er	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParamter	resourceVersion	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	
QueryParamter	timeoutSeconds	Timeout for the list/watch call.	false	integer	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParameter	name	name of the ImageStream	true	string	

2.2.304.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.1, “versioned.Event”

2.2.304.3. Consumes

- /

2.2.304.4. Produces

- application/json
- application/json;stream=watch
- application/vnd.kubernetes.protobuf
- application/vnd.kubernetes.protobuf;stream=watch

2.2.304.5. Tags

- oapiv1

2.2.305. watch individual changes to a list of Policy

```
GET /oapi/v1/watch/namespaces/{namespace}/policies
```

2.2.305.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamet er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParamet er	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	
QueryParamet er	resourceVersio n	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParamet er	timeoutSecond s	Timeout for the list/watch call.	false	integer	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	

2.2.305.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.1, “versioned.Event”

2.2.305.3. Consumes

- /

2.2.305.4. Produces

- application/json
- application/json;stream=watch
- application/vnd.kubernetes.protobuf
- application/vnd.kubernetes.protobuf;stream=watch

2.2.305.5. Tags

- oapiv1

2.2.306. watch changes to an object of kind Policy

```
GET /oapi/v1/watch/namespaces/{namespace}/policies/{name}
```

2.2.306.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParamet er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamet er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParamet er	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	
QueryParamet er	resourceVersio n	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	
QueryParamet er	timeoutSecond s	Timeout for the list/watch call.	false	integer	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	

Type	Name	Description	Required	Schema	Default
PathParameter	name	name of the Policy	true	string	

2.2.306.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.1, “versioned.Event”

2.2.306.3. Consumes

- /

2.2.306.4. Produces

- application/json
- application/json;stream=watch
- application/vnd.kubernetes.protobuf
- application/vnd.kubernetes.protobuf;stream=watch

2.2.306.5. Tags

- oapiv1

2.2.307. watch individual changes to a list of PolicyBinding

GET /oapi/v1/watch/namespaces/{namespace}/policybindings

2.2.307.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParamet er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParamet er	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersio n.	false	boolean	
QueryParamet er	resourceVersio n	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	
QueryParamet er	timeoutSecond s	Timeout for the list/watch call.	false	integer	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	

2.2.307.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.1, “versioned.Event”

2.2.307.3. Consumes

- /

2.2.307.4. Produces

- application/json
- application/json;stream=watch
- application/vnd.kubernetes.protobuf
- application/vnd.kubernetes.protobuf;stream=watch

2.2.307.5. Tags

- oapiv1

2.2.308. watch changes to an object of kind PolicyBinding

```
GET /oapi/v1/watch/namespaces/{namespace}/policybindings/{name}
```

2.2.308.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamet er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParamet er	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	
QueryParamet er	resourceVersio n	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	
QueryParamet er	timeoutSecond s	Timeout for the list/watch call.	false	integer	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParameter	name	name of the PolicyBinding	true	string	

2.2.308.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.1, “versioned.Event”

2.2.308.3. Consumes

- /

2.2.308.4. Produces

- application/json
- application/json;stream=watch
- application/vnd.kubernetes.protobuf
- application/vnd.kubernetes.protobuf;stream=watch

2.2.308.5. Tags

- oapiv1

2.2.309. watch individual changes to a list of Route

```
GET /oapi/v1/watch/namespaces/{namespace}/routes
```

2.2.309.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamet er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParamet er	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParamet er	resourceVersio n	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	
QueryParamet er	timeoutSecond s	Timeout for the list/watch call.	false	integer	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	

2.2.309.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.1, “versioned.Event”

2.2.309.3. Consumes

- /

2.2.309.4. Produces

- application/json
- application/json;stream=watch
- application/vnd.kubernetes.protobuf
- application/vnd.kubernetes.protobuf;stream=watch

2.2.309.5. Tags

- oapiv1

2.2.310. watch changes to an object of kind Route

-

```
GET /oapi/v1/watch/namespaces/{namespace}/routes/{name}
```

2.2.310.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamet er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParamet er	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	
QueryParamet er	resourceVersio n	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	
QueryParamet er	timeoutSecond s	Timeout for the list/watch call.	false	integer	

Type	Name	Description	Required	Schema	Default
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParameter	name	name of the Route	true	string	

2.2.310.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.1, “versioned.Event”

2.2.310.3. Consumes

- /

2.2.310.4. Produces

- application/json
- application/json;stream=watch
- application/vnd.kubernetes.protobuf
- application/vnd.kubernetes.protobuf;stream=watch

2.2.310.5. Tags

- oapiv1

2.2.311. watch individual changes to a list of Template

```
GET /oapi/v1/watch/namespaces/{namespace}/templates
```

2.2.311.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParamet er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamet er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParamet er	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	
QueryParamet er	resourceVersio n	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	
QueryParamet er	timeoutSecond s	Timeout for the list/watch call.	false	integer	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	

2.2.311.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.1, “versioned.Event”

2.2.311.3. Consumes

- /

2.2.311.4. Produces

- application/json
- application/json;stream=watch
- application/vnd.kubernetes.protobuf
- application/vnd.kubernetes.protobuf;stream=watch

2.2.311.5. Tags

- oapiv1

2.2.312. watch changes to an object of kind Template

```
GET /oapi/v1/watch/namespaces/{namespace}/templates/{name}
```

2.2.312.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamet er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParamet er	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	
QueryParamet er	resourceVersio n	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	
QueryParamet er	timeoutSecond s	Timeout for the list/watch call.	false	integer	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParameter	name	name of the Template	true	string	

2.2.312.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.1, “versioned.Event”

2.2.312.3. Consumes

- /

2.2.312.4. Produces

- application/json
- application/json;stream=watch
- application/vnd.kubernetes.protobuf
- application/vnd.kubernetes.protobuf;stream=watch

2.2.312.5. Tags

- oapiv1

2.2.313. watch individual changes to a list of NetNamespace

GET /oapi/v1/watch/netnamespaces

2.2.313.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamet er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParamet er	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParamet er	resourceVersio n	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	
QueryParamet er	timeoutSecond s	Timeout for the list/watch call.	false	integer	

2.2.313.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.1, “versioned.Event”

2.2.313.3. Consumes

- /

2.2.313.4. Produces

- application/json
- application/json;stream=watch
- application/vnd.kubernetes.protobuf
- application/vnd.kubernetes.protobuf;stream=watch

2.2.313.5. Tags

- oapiv1

2.2.314. watch changes to an object of kind NetNamespace

```
GET /oapi/v1/watch/netnamespaces/{name}
```

2.2.314.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamet er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParamet er	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	
QueryParamet er	resourceVersio n	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	
QueryParamet er	timeoutSecond s	Timeout for the list/watch call.	false	integer	
PathParameter	name	name of the NetNamespac e	true	string	

2.2.314.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.1, “versioned.Event”

2.2.314.3. Consumes

- /

2.2.314.4. Produces

- application/json
- application/json;stream=watch
- application/vnd.kubernetes.protobuf
- application/vnd.kubernetes.protobuf;stream=watch

2.2.314.5. Tags

- oapiv1

2.2.315. watch individual changes to a list of OAuthAccessToken

GET /oapi/v1/watch/oauthaccessstokens

2.2.315.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamet er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParamet er	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	
QueryParamet er	resourceVersio n	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	
QueryParamet er	timeoutSecond s	Timeout for the list/watch call.	false	integer	

2.2.315.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.1, “versioned.Event”

2.2.315.3. Consumes

- /

2.2.315.4. Produces

- application/json
- application/json;stream=watch
- application/vnd.kubernetes.protobuf

- `application/vnd.kubernetes.protobuf;stream=watch`

2.2.315.5. Tags

- `oapiv1`

2.2.316. watch changes to an object of kind OAuthAccessToken

GET `/oapi/v1/watch/oauthaccesstokens/{name}`

2.2.316.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	<code>pretty</code>	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	<code>labelSelector</code>	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamet er	<code>fieldSelector</code>	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParamet er	<code>watch</code>	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify <code>resourceVersion</code> .	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParamter	resourceVersion	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	
QueryParamter	timeoutSeconds	Timeout for the list/watch call.	false	integer	
PathParameter	name	name of the OAuthAccessToken	true	string	

2.2.316.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.1, “versioned.Event”

2.2.316.3. Consumes

- /

2.2.316.4. Produces

- application/json
- application/json;stream=watch
- application/vnd.kubernetes.protobuf
- application/vnd.kubernetes.protobuf;stream=watch

2.2.316.5. Tags

- oapiv1

2.2.317. watch individual changes to a list of OAuthAuthorizeToken

GET /oapi/v1/watch/oauthauthorizetokens

2.2.317.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamet er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParamet er	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersio n.	false	boolean	
QueryParamet er	resourceVersio n	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	
QueryParamet er	timeoutSecond s	Timeout for the list/watch call.	false	integer	

2.2.317.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.1, “versioned.Event”

2.2.317.3. Consumes

- /

2.2.317.4. Produces

- application/json
- application/json;stream=watch
- application/vnd.kubernetes.protobuf
- application/vnd.kubernetes.protobuf;stream=watch

2.2.317.5. Tags

- oapiv1

2.2.318. watch changes to an object of kind OAuthAuthorizeToken

```
GET /oapi/v1/watch/oauthauthorizetokens/{name}
```

2.2.318.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamet er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParamet er	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	
QueryParamet er	resourceVersio n	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	
QueryParamet er	timeoutSecond s	Timeout for the list/watch call.	false	integer	
PathParameter	name	name of the OAuthAuthorizeToken	true	string	

2.2.318.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.1, “versioned.Event”

2.2.318.3. Consumes

- /

2.2.318.4. Produces

- application/json
- application/json;stream=watch

- application/vnd.kubernetes.protobuf
- application/vnd.kubernetes.protobuf;stream=watch

2.2.318.5. Tags

- oapiv1

2.2.319. watch individual changes to a list of OAuthClientAuthorization

GET /oapi/v1/watch/oauthclientauthorizations

2.2.319.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamet er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParamet er	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParam er	resourceVersio n	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	
QueryParam er	timeoutSecond s	Timeout for the list/watch call.	false	integer	

2.2.319.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.1, “versioned.Event”

2.2.319.3. Consumes

- /

2.2.319.4. Produces

- application/json
- application/json;stream=watch
- application/vnd.kubernetes.protobuf
- application/vnd.kubernetes.protobuf;stream=watch

2.2.319.5. Tags

- oapiv1

2.2.320. watch changes to an object of kind OAuthClientAuthorization

```
GET /oapi/v1/watch/oauthclientauthorizations/{name}
```

2.2.320.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamet er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParamet er	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	
QueryParamet er	resourceVersio n	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	
QueryParamet er	timeoutSecond s	Timeout for the list/watch call.	false	integer	
PathParameter	name	name of the OAuthClientAu thorization	true	string	

2.2.320.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.1, “versioned.Event”

2.2.320.3. Consumes

- /

2.2.320.4. Produces

- application/json
- application/json;stream=watch
- application/vnd.kubernetes.protobuf
- application/vnd.kubernetes.protobuf;stream=watch

2.2.320.5. Tags

- oapiv1

2.2.321. watch individual changes to a list of OAuthClient

```
GET /oapi/v1/watch/oauthclients
```

2.2.321.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamet er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParamet er	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	
QueryParamet er	resourceVersio n	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	
QueryParamet er	timeoutSecond s	Timeout for the list/watch call.	false	integer	

2.2.321.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.1, “versioned.Event”

2.2.321.3. Consumes

- /

2.2.321.4. Produces

- application/json
- application/json;stream=watch
- application/vnd.kubernetes.protobuf

- `application/vnd.kubernetes.protobuf;stream=watch`

2.2.321.5. Tags

- `oapiv1`

2.2.322. watch changes to an object of kind OAuthClient

GET `/oapi/v1/watch/oauthclients/{name}`

2.2.322.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	<code>pretty</code>	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	<code>labelSelector</code>	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamet er	<code>fieldSelector</code>	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParamet er	<code>watch</code>	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify <code>resourceVersion</code> .	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParamet er	resourceVersio n	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	
QueryParamet er	timeoutSecond s	Timeout for the list/watch call.	false	integer	
PathParameter	name	name of the OAuthClient	true	string	

2.2.322.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.1, “versioned.Event”

2.2.322.3. Consumes

- /

2.2.322.4. Produces

- application/json
- application/json;stream=watch
- application/vnd.kubernetes.protobuf
- application/vnd.kubernetes.protobuf;stream=watch

2.2.322.5. Tags

- oapiv1

2.2.323. watch individual changes to a list of Policy

GET /oapi/v1/watch/policies

2.2.323.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamet er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParamet er	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersio n.	false	boolean	
QueryParamet er	resourceVersio n	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	
QueryParamet er	timeoutSecond s	Timeout for the list/watch call.	false	integer	

2.2.323.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.1, “versioned.Event”

2.2.323.3. Consumes

- /

2.2.323.4. Produces

- application/json
- application/json;stream=watch
- application/vnd.kubernetes.protobuf
- application/vnd.kubernetes.protobuf;stream=watch

2.2.323.5. Tags

- oapiv1

2.2.324. watch individual changes to a list of PolicyBinding

GET /oapi/v1/watch/policybindings

2.2.324.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamet er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParamet er	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersio n.	false	boolean	
QueryParamet er	resourceVersio n	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	
QueryParamet er	timeoutSecond s	Timeout for the list/watch call.	false	integer	

2.2.324.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.1, “versioned.Event”

2.2.324.3. Consumes

- /

2.2.324.4. Produces

- application/json
- application/json;stream=watch
- application/vnd.kubernetes.protobuf
- application/vnd.kubernetes.protobuf;stream=watch

2.2.324.5. Tags

- oapiv1

2.2.325. watch individual changes to a list of Project

GET /oapi/v1/watch/projects

2.2.325.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamet er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParamet er	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParamet er	resourceVersio n	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	
QueryParamet er	timeoutSecond s	Timeout for the list/watch call.	false	integer	

2.2.325.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.1, “versioned.Event”

2.2.325.3. Consumes

- /

2.2.325.4. Produces

- application/json
- application/json;stream=watch
- application/vnd.kubernetes.protobuf
- application/vnd.kubernetes.protobuf;stream=watch

2.2.325.5. Tags

- oapiv1

2.2.326. watch changes to an object of kind Project

```
GET /oapi/v1/watch/projects/{name}
```

2.2.326.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamet er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParamet er	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	
QueryParamet er	resourceVersio n	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	
QueryParamet er	timeoutSecond s	Timeout for the list/watch call.	false	integer	
PathParameter	name	name of the Project	true	string	

2.2.326.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.1, “versioned.Event”

2.2.326.3. Consumes

- /

2.2.326.4. Produces

- application/json
- application/json;stream=watch
- application/vnd.kubernetes.protobuf
- application/vnd.kubernetes.protobuf;stream=watch

2.2.326.5. Tags

- oapiv1

2.2.327. watch individual changes to a list of Route

GET /oapi/v1/watch/routes

2.2.327.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamet er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParamet er	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	
QueryParamet er	resourceVersio n	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	
QueryParamet er	timeoutSecond s	Timeout for the list/watch call.	false	integer	

2.2.327.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.1, “versioned.Event”

2.2.327.3. Consumes

- /

2.2.327.4. Produces

- application/json
- application/json;stream=watch
- application/vnd.kubernetes.protobuf

- `application/vnd.kubernetes.protobuf;stream=watch`

2.2.327.5. Tags

- `oapiv1`

2.2.328. watch individual changes to a list of Template

GET `/oapi/v1/watch/templates`

2.2.328.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	<code>pretty</code>	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	<code>labelSelector</code>	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamet er	<code>fieldSelector</code>	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParamet er	<code>watch</code>	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify <code>resourceVersion</code> .	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParamet er	resourceVersio n	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	
QueryParamet er	timeoutSecond s	Timeout for the list/watch call.	false	integer	

2.2.328.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.1, “versioned.Event”

2.2.328.3. Consumes

- /

2.2.328.4. Produces

- application/json
- application/json;stream=watch
- application/vnd.kubernetes.protobuf
- application/vnd.kubernetes.protobuf;stream=watch

2.2.328.5. Tags

- oapiv1

2.2.329. watch individual changes to a list of User

```
GET /oapi/v1/watch/users
```

2.2.329.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamet er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParamet er	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	
QueryParamet er	resourceVersio n	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	
QueryParamet er	timeoutSecond s	Timeout for the list/watch call.	false	integer	

2.2.329.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.1, “versioned.Event”

2.2.329.3. Consumes

- /

2.2.329.4. Produces

- application/json
- application/json;stream=watch
- application/vnd.kubernetes.protobuf
- application/vnd.kubernetes.protobuf;stream=watch

2.2.329.5. Tags

- oapiv1

2.2.330. watch changes to an object of kind User

```
GET /oapi/v1/watch/users/{name}
```

2.2.330.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamet er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParamet er	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	
QueryParamet er	resourceVersio n	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	
QueryParamet er	timeoutSecond s	Timeout for the list/watch call.	false	integer	
PathParameter	name	name of the User	true	string	

2.2.330.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.1, “versioned.Event”

2.2.330.3. Consumes

- /

2.2.330.4. Produces

- application/json
- application/json;stream=watch
- application/vnd.kubernetes.protobuf

- application/vnd.kubernetes.protobuf;stream=watch

2.2.330.5. Tags

- oapiv1

2.3. DEFINITIONS

2.3.1. versioned.Event

2.3.2. patch.Object

represents an object patch, which may be any of: JSON patch (RFC 6902), JSON merge patch (RFC 7396), or the Kubernetes strategic merge patch

2.3.3. runtime.RawExtension

this may be any JSON object with a 'kind' and 'apiVersion' field; and is preserved unmodified by processing

2.3.4. types.UID

2.3.5. unversioned.APIResource

APIResource specifies the name of a resource and whether it is namespaced.

Name	Description	Required	Schema	Default
name	name is the name of the resource.	true	string	
namespaced	namespaced indicates if a resource is namespaced or not.	true	boolean	
kind	kind is the kind for the resource (e.g. 'Foo' is the kind for a resource 'foo')	true	string	

2.3.6. unversioned.APIResourceList

APIResourceList is a list of APIResource, it is used to expose the name of the resources supported in a specific group and version, and if the resource is namespaced.

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#types-kinds	false	string	
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#resources	false	string	
groupVersion	groupVersion is the group and version this APIResourceList is for.	true	string	
resources	resources contains the name of the resources and if they are namespaced.	true	Section 2.3.5, "unversioned.APIResource" array	

2.3.7. unversioned.LabelSelector

A label selector is a label query over a set of resources. The result of `matchLabels` and `matchExpressions` are ANDed. An empty label selector matches all objects. A null label selector matches no objects.

Name	Description	Required	Schema	Default
<code>matchLabels</code>	<code>matchLabels</code> is a map of {key,value} pairs. A single {key,value} in the <code>matchLabels</code> map is equivalent to an element of <code>matchExpressions</code> , whose key field is "key", the operator is "In", and the values array contains only "value". The requirements are ANDed.	false	object	
<code>matchExpressions</code>	<code>matchExpressions</code> is a list of label selector requirements. The requirements are ANDed.	false	Section 2.3.8, "unversioned.LabelSelectorRequirement" array	

2.3.8. unversioned.LabelSelectorRequirement

A label selector requirement is a selector that contains values, a key, and an operator that relates the key and values.

Name	Description	Required	Schema	Default
<code>key</code>	<code>key</code> is the label key that the selector applies to.	true	string	
<code>operator</code>	<code>operator</code> represents a key's relationship to a set of values. Valid operators are In, NotIn, Exists and DoesNotExist.	true	string	

Name	Description	Required	Schema	Default
values	values is an array of string values. If the operator is In or NotIn, the values array must be non-empty. If the operator is Exists or DoesNotExist, the values array must be empty. This array is replaced during a strategic merge patch.	false	string array	

2.3.9. unversioned.ListMeta

ListMeta describes metadata that synthetic resources must have, including lists and various status objects. A resource may have only one of {ObjectMeta, ListMeta}.

Name	Description	Required	Schema	Default
selfLink	SelfLink is a URL representing this object. Populated by the system. Read-only.	false	string	

Name	Description	Required	Schema	Default
resourceVersion	String that identifies the server's internal version of this object that can be used by clients to determine when objects have changed. Value must be treated as opaque by clients and passed unmodified back to the server. Populated by the system. Read-only. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#concurrency-control-and-consistency	false	string	

2.3.10. unversioned.Patch

Patch is provided to give a concrete name and type to the Kubernetes PATCH request body.

2.3.11. unversioned.Status

Status is a return value for calls that don't return other objects.

Name	Description	Required	Schema	Default
------	-------------	----------	--------	---------

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#types-kinds	false	string	
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#resources	false	string	
metadata	Standard list metadata. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#types-kinds	false	Section 2.3.9, "unversioned.ListMeta"	

Name	Description	Required	Schema	Default
status	Status of the operation. One of: "Success" or "Failure". More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#pec-and-status	false	string	
message	A human-readable description of the status of this operation.	false	string	
reason	A machine-readable description of why this operation is in the "Failure" status. If this value is empty there is no information available. A Reason clarifies an HTTP status code but does not override it.	false	string	
details	Extended data associated with the reason. Each reason may define its own extended details. This field is optional and the data returned is not guaranteed to conform to any schema except that defined by the reason type.	false	Section 2.3.13, "unversioned.StatusDetails"	
code	Suggested HTTP return code for this status, 0 if not set.	false	integer (int32)	

2.3.12. unversioned.StatusCause

StatusCause provides more information about an api.Status failure, including cases when multiple errors are encountered.

Name	Description	Required	Schema	Default
reason	A machine-readable description of the cause of the error. If this value is empty there is no information available.	false	string	
message	A human-readable description of the cause of the error. This field may be presented as-is to a reader.	false	string	
field	The field of the resource that has caused this error, as named by its JSON serialization. May include dot and postfix notation for nested attributes. Arrays are zero-indexed. Fields may appear more than once in an array of causes due to fields having multiple errors. Optional. Examples: "name" - the field "name" on the current resource "items[0].name" - the field "name" on the first array entry in "items"	false	string	

2.3.13. unversioned.StatusDetails

StatusDetails is a set of additional properties that MAY be set by the server to provide additional information about a response. The Reason field of a Status object defines what attributes will be set. Clients must ignore fields that do not match the defined type of each attribute, and should assume that any attribute may be empty, invalid, or under defined.

Name	Description	Required	Schema	Default
name	The name attribute of the resource associated with the status <code>StatusReason</code> (when there is a single name which can be described).	false	string	
group	The group attribute of the resource associated with the status <code>StatusReason</code> .	false	string	
kind	The kind attribute of the resource associated with the status <code>StatusReason</code> . On some operations may differ from the requested resource Kind. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#types-kinds	false	string	
causes	The Causes array includes more details associated with the <code>StatusReason</code> failure. Not all <code>StatusReasons</code> may provide detailed causes.	false	Section 2.3.12, “unversioned.StatusCause” array	
retryAfterSeconds	If specified, the time in seconds before the operation should be retried.	false	integer (int32)	

2.3.14. v1.AWSElasticBlockStoreVolumeSource

Represents a Persistent Disk resource in AWS.

An AWS EBS disk must exist before mounting to a container. The disk must also be in the same AWS zone as the kubelet. An AWS EBS disk can only be mounted as read/write once. AWS EBS volumes support ownership management and SELinux relabeling.

Name	Description	Required	Schema	Default
volumeID	Unique ID of the persistent disk resource in AWS (Amazon EBS volume). More info: http://releases.k8s.io/release-1.3/docs/user-guide/volumes.md#awselasticblockstore	true	string	
fsType	Filesystem type of the volume that you want to mount. Tip: Ensure that the filesystem type is supported by the host operating system. Examples: "ext4", "xfs", "ntfs". Implicitly inferred to be "ext4" if unspecified. More info: http://releases.k8s.io/release-1.3/docs/user-guide/volumes.md#awselasticblockstore	false	string	
partition	The partition in the volume that you want to mount. If omitted, the default is to mount by volume name. Examples: For volume /dev/sda1, you specify the partition as "1". Similarly, the volume partition for /dev/sda is "0" (or you can leave the property empty).	false	integer (int32)	

Name	Description	Required	Schema	Default
readOnly	Specify "true" to force and set the ReadOnly property in VolumeMounts to "true". If omitted, the default is "false". More info: http://releases.k8s.io/release-1.3/docs/user-guide/volumes.md#awselasticblockstore	false	boolean	

2.3.15. v1.AppliedClusterResourceQuota

AppliedClusterResourceQuota mirrors ClusterResourceQuota at a project scope, for projection into a project. It allows a project-admin to know which ClusterResourceQuotas are applied to his project and their associated usage.

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#types-kinds	false	string	

Name	Description	Required	Schema	Default
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#resources	false	string	
metadata	Standard object's metadata.	true	Section 2.3.158, "v1.ObjectMeta"	
spec	Spec defines the desired quota	true	Section 2.3.48, "v1.ClusterResourceQuotaSpec"	
status	Status defines the actual enforced quota and its current usage	false	Section 2.3.49, "v1.ClusterResourceQuotaStatus"	

2.3.16. v1.AppliedClusterResourceQuotaList

AppliedClusterResourceQuotaList is a collection of AppliedClusterResourceQuotas

Name	Description	Required	Schema	Default
------	-------------	----------	--------	---------

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#types-kinds	false	string	
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#resources	false	string	
metadata	Standard object's metadata.	false	Section 2.3.9, "unversioned.ListMeta"	
items	Items is a list of AppliedClusterResourceQuota	true	Section 2.3.15, "v1.AppliedClusterResourceQuota" array	

2.3.17. v1.AzureFileVolumeSource

AzureFile represents an Azure File Service mount on the host and bind mount to the pod.

Name	Description	Required	Schema	Default
secretName	the name of secret that contains Azure Storage Account Name and Key	true	string	
shareName	Share Name	true	string	
readOnly	Defaults to false (read/write). ReadOnly here will force the ReadOnly setting in VolumeMounts.	false	boolean	

2.3.18. v1.BinaryBuildSource

BinaryBuildSource describes a binary file to be used for the Docker and Source build strategies, where the file will be extracted and used as the build source.

Name	Description	Required	Schema	Default
asFile	asFile indicates that the provided binary input should be considered a single file within the build input. For example, specifying "webapp.war" would place the provided binary as /webapp.war for the builder. If left empty, the Docker and Source build strategies assume this file is a zip, tar, or tar.gz file and extract it as the source. The custom strategy receives this binary as standard input. This filename may not contain slashes or be '..' or '..'	false	string	

2.3.19. v1.Build

Build encapsulates the inputs needed to produce a new deployable image, as well as the status of the execution and a reference to the Pod which executed the build.

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#types-kinds	false	string	
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#resources	false	string	
metadata	Standard object's metadata.	false	Section 2.3.158, "v1.ObjectMeta"	
spec	spec is all the inputs used to execute the build.	false	Section 2.3.30, "v1.BuildSpec"	

Name	Description	Required	Schema	Default
status	status is the current status of the build.	false	Section 2.3.31, "v1.BuildStatus"	

2.3.20. v1.BuildConfig

Build configurations define a build process for new Docker images. There are three types of builds possible - a Docker build using a Dockerfile, a Source-to-Image build that uses a specially prepared base image that accepts source code that it can make runnable, and a custom build that can run arbitrary Docker images as a base and accept the build parameters. Builds run on the cluster and on completion are pushed to the Docker registry specified in the "output" section. A build can be triggered via a webhook, when the base image changes, or when a user manually requests a new build be created.

Each build created by a build configuration is numbered and refers back to its parent configuration. Multiple builds can be triggered at once. Builds that do not have "output" set can be used to test code or run a verification build.

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#types-kinds	false	string	

Name	Description	Required	Schema	Default
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#resources	false	string	
metadata	metadata for BuildConfig.	false	Section 2.3.158, "v1.ObjectMeta"	
spec	spec holds all the input necessary to produce a new build, and the conditions when to trigger them.	true	Section 2.3.22, "v1.BuildConfigSpec"	
status	status holds any relevant information about a build config	true	Section 2.3.23, "v1.BuildConfigStatus"	

2.3.21. v1.BuildConfigList

BuildConfigList is a collection of BuildConfigs.

Name	Description	Required	Schema	Default
------	-------------	----------	--------	---------

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#types-kinds	false	string	
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#resources	false	string	
metadata	metadata for BuildConfigList.	false	Section 2.3.9, "unversioned.ListMeta"	
items	items is a list of build configs	true	Section 2.3.20, "v1.BuildConfig" array	

2.3.22. v1.BuildConfigSpec

BuildConfigSpec describes when and how builds are created

Name	Description	Required	Schema	Default
triggers	triggers determine how new Builds can be launched from a BuildConfig. If no triggers are defined, a new build can only occur as a result of an explicit client build creation.	true	Section 2.3.34, "v1.BuildTriggerPolicy" array	
runPolicy	RunPolicy describes how the new build created from this build configuration will be scheduled for execution. This is optional, if not specified we default to "Serial".	false	string	
serviceAccount	serviceAccount is the name of the ServiceAccount to use to run the pod created by this build. The pod will be allowed to use secrets referenced by the ServiceAccount	false	string	
source	source describes the SCM in use.	false	Section 2.3.29, "v1.BuildSource"	
revision	revision is the information from the source for a specific repo snapshot. This is optional.	false	Section 2.3.218, "v1.SourceRevision"	
strategy	strategy defines how to perform a build.	true	Section 2.3.32, "v1.BuildStrategy"	

Name	Description	Required	Schema	Default
output	output describes the Docker image the Strategy should produce.	false	Section 2.3.26, "v1.BuildOutput"	
resources	resources computes resource requirements to execute the build.	false	Section 2.3.188, "v1.ResourceRequirements"	
postCommit	postCommit is a build hook executed after the build output image is committed, before it is pushed to a registry.	false	Section 2.3.27, "v1.BuildPostCommitSpec"	
completionDeadlineSeconds	completionDeadlineSeconds is an optional duration in seconds, counted from the time when a build pod gets scheduled in the system, that the build may be active on a node before the system actively tries to terminate the build; value must be positive integer	false	integer (int64)	

2.3.23. v1.BuildConfigStatus

BuildConfigStatus contains current state of the build config object.

Name	Description	Required	Schema	Default
lastVersion	lastVersion is used to inform about number of last triggered build.	true	integer (int64)	

2.3.24. v1.BuildList

BuildList is a collection of Builds.

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#types-kinds	false	string	
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#resources	false	string	
metadata	metadata for BuildList.	false	Section 2.3.9, “unversioned.ListMeta”	
items	items is a list of builds	true	Section 2.3.19, “v1.Build” array	

2.3.25. v1.BuildLog

BuildLog is the (unused) resource associated with the build log redirector

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#types-kinds	false	string	
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#resources	false	string	

2.3.26. v1.BuildOutput

BuildOutput is input to a build strategy and describes the Docker image that the strategy should produce.

Name	Description	Required	Schema	Default
------	-------------	----------	--------	---------

Name	Description	Required	Schema	Default
to	to defines an optional location to push the output of this build to. Kind must be one of 'ImageStreamTag' or 'DockerImage'. This value will be used to look up a Docker image repository to push to. In the case of an ImageStreamTag, the ImageStreamTag will be looked for in the namespace of the build unless Namespace is specified.	false	Section 2.3.159, "v1.ObjectReference"	
pushSecret	PushSecret is the name of a Secret that would be used for setting up the authentication for executing the Docker push to authentication enabled Docker Registry (or Docker Hub).	false	Section 2.3.138, "v1.LocalObjectReference"	

2.3.27. v1.BuildPostCommitSpec

A BuildPostCommitSpec holds a build post commit hook specification. The hook executes a command in a temporary container running the build output image, immediately after the last layer of the image is committed and before the image is pushed to a registry. The command is executed with the current working directory (\$PWD) set to the image's WORKDIR.

The build will be marked as failed if the hook execution fails. It will fail if the script or command return a non-zero exit code, or if there is any other error related to starting the temporary container.

There are five different ways to configure the hook. As an example, all forms below are equivalent and will execute **rake test --verbose**.

1. Shell script:

```
"postCommit": {
  "script": "rake test --verbose",
}
```

The above is a convenient form which is equivalent to:

```
"postCommit": {
  "command": ["/bin/sh", "-ic"],
  "args":    ["rake test --verbose"]
}
```

2. A command as the image entrypoint:

```
"postCommit": {
  "command": ["rake", "test", "--verbose"]
}
```

Command overrides the image entrypoint in the exec form, as documented in Docker:
<https://docs.docker.com/engine/reference/builder/#entrypoint>.

3. Pass arguments to the default entrypoint:

```
"postCommit": {
  "args": ["rake", "test", "--verbose"]
}
```

This form is only useful if the image entrypoint can handle arguments.

4. Shell script with arguments:

```
"postCommit": {
  "script": "rake test $1",
  "args":  ["--verbose"]
}
```

This form is useful if you need to pass arguments that would otherwise be hard to quote properly in the shell script. In the script, \$0 will be `/bin/sh` and \$1, \$2, etc, are the positional arguments from Args.

5. Command with arguments:

```
"postCommit": {
  "command": ["rake", "test"],
  "args":    ["--verbose"]
}
```

This form is equivalent to appending the arguments to the Command slice.

It is invalid to provide both Script and Command simultaneously. If none of the fields are specified, the hook is not executed.

Name	Description	Required	Schema	Default
command	command is the command to run. It may not be specified with Script. This might be needed if the image doesn't have /bin/sh , or if you do not want to use a shell. In all other cases, using Script might be more convenient.	false	string array	
args	args is a list of arguments that are provided to either Command, Script or the Docker image's default entrypoint. The arguments are placed immediately after the command to be run.	false	string array	

Name	Description	Required	Schema	Default
script	script is a shell script to be run with /bin/sh -i . It may not be specified with Command. Use Script when a shell script is appropriate to execute the post build hook, for example for running unit tests with rake test . If you need control over the image entrypoint, or if the image does not have /bin/sh , use Command and/or Args. The -i flag is needed to support CentOS and RHEL images that use Software Collections (SCL), in order to have the appropriate collections enabled in the shell. E.g., in the Ruby image, this is necessary to make ruby , bundle and other binaries available in the PATH.	false	string	

2.3.28. v1.BuildRequest

BuildRequest is the resource used to pass parameters to build generator

Name	Description	Required	Schema	Default
------	-------------	----------	--------	---------

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#types-kinds	false	string	
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#resources	false	string	
metadata	metadata for BuildRequest.	false	Section 2.3.158, "v1.ObjectMeta"	
revision	revision is the information from the source for a specific repo snapshot.	false	Section 2.3.218, "v1.SourceRevision"	
triggeredByImage	triggeredByImage is the Image that triggered this build.	false	Section 2.3.159, "v1.ObjectReference"	

Name	Description	Required	Schema	Default
from	from is the reference to the ImageStreamTag that triggered the build.	false	Section 2.3.159, “v1.ObjectReference”	
binary	binary indicates a request to build from a binary provided to the builder	false	Section 2.3.18, “v1.BinaryBuildSource”	
lastVersion	lastVersion (optional) is the LastVersion of the BuildConfig that was used to generate the build. If the BuildConfig in the generator doesn't match, a build will not be generated.	false	integer (int64)	
env	env contains additional environment variables you want to pass into a builder container	false	Section 2.3.86, “v1.EnvVar” array	
triggeredBy	triggeredBy describes which triggers started the most recent update to the build configuration and contains information about those triggers.	true	Section 2.3.33, “v1.BuildTriggerCause” array	

2.3.29. v1.BuildSource

BuildSource is the SCM used for the build.

Name	Description	Required	Schema	Default
type	type of build input to accept	true	string	

Name	Description	Required	Schema	Default
binary	<p>binary builds accept a binary as their input. The binary is generally assumed to be a tar, gzipped tar, or zip file depending on the strategy. For Docker builds, this is the build context and an optional Dockerfile may be specified to override any Dockerfile in the build context. For Source builds, this is assumed to be an archive as described above. For Source and Docker builds, if <code>binary.asFile</code> is set the build will receive a directory with a single file. <code>contextDir</code> may be used when an archive is provided. Custom builds will receive this binary as input on STDIN.</p>	false	Section 2.3.18, "v1.BinaryBuildSource"	

Name	Description	Required	Schema	Default
dockerfile	dockerfile is the raw contents of a Dockerfile which should be built. When this option is specified, the FROM may be modified based on your strategy base image and additional ENV stanzas from your strategy environment will be added after the FROM, but before the rest of your Dockerfile stanzas. The Dockerfile source type may be used with other options like git - in those cases the Git repo will have any innate Dockerfile replaced in the context dir.	false	string	
git	git contains optional information about git build source	false	Section 2.3.96, "v1.GitBuildSource"	
images	images describes a set of images to be used to provide source for the build	false	Section 2.3.121, "v1.ImageSource" array	
contextDir	contextDir specifies the sub-directory where the source code for the application exists. This allows to have buildable sources in directory other than root of repository.	false	string	

Name	Description	Required	Schema	Default
sourceSecret	sourceSecret is the name of a Secret that would be used for setting up the authentication for cloning private repository. The secret contains valid credentials for remote repository, where the data's key represent the authentication method to be used and value is the base64 encoded credentials. Supported auth methods are: ssh-privatekey.	false	Section 2.3.138, "v1.LocalObjectReference"	
secrets	secrets represents a list of secrets and their destinations that will be used only for the build.	false	Section 2.3.205, "v1.SecretBuildSource" array	

2.3.30. v1.BuildSpec

BuildSpec has the information to represent a build and also additional information about a build

Name	Description	Required	Schema	Default
serviceAccount	serviceAccount is the name of the ServiceAccount to use to run the pod created by this build. The pod will be allowed to use secrets referenced by the ServiceAccount	false	string	

Name	Description	Required	Schema	Default
source	source describes the SCM in use.	false	Section 2.3.29, "v1.BuildSource"	
revision	revision is the information from the source for a specific repo snapshot. This is optional.	false	Section 2.3.218, "v1.SourceRevision"	
strategy	strategy defines how to perform a build.	true	Section 2.3.32, "v1.BuildStrategy"	
output	output describes the Docker image the Strategy should produce.	false	Section 2.3.26, "v1.BuildOutput"	
resources	resources computes resource requirements to execute the build.	false	Section 2.3.188, "v1.ResourceRequirements"	
postCommit	postCommit is a build hook executed after the build output image is committed, before it is pushed to a registry.	false	Section 2.3.27, "v1.BuildPostCommitSpec"	
completionDeadlineSeconds	completionDeadlineSeconds is an optional duration in seconds, counted from the time when a build pod gets scheduled in the system, that the build may be active on a node before the system actively tries to terminate the build; value must be positive integer	false	integer (int64)	

Name	Description	Required	Schema	Default
triggeredBy	triggeredBy describes which triggers started the most recent update to the build configuration and contains information about those triggers.	true	Section 2.3.33 , “v1.BuildTriggerCause” array	

2.3.31. v1.BuildStatus

BuildStatus contains the status of a build

Name	Description	Required	Schema	Default
phase	phase is the point in the build lifecycle.	true	string	
cancelled	cancelled describes if a cancel event was triggered for the build.	false	boolean	
reason	reason is a brief CamelCase string that describes any failure and is meant for machine parsing and tidy display in the CLI.	false	string	
message	message is a human-readable message indicating details about why the build has this status.	false	string	

Name	Description	Required	Schema	Default
startTimestamp	startTimestamp is a timestamp representing the server time when this Build started running in a Pod. It is represented in RFC3339 form and is in UTC.	false	string	
completionTimestamp	completionTimestamp is a timestamp representing the server time when this Build was finished, whether that build failed or succeeded. It reflects the time at which the Pod running the Build terminated. It is represented in RFC3339 form and is in UTC.	false	string	
duration	duration contains time.Duration object describing build time.	false	time.Duration	
outputDockerImageReference	outputDockerImageReference contains a reference to the Docker image that will be built by this build. Its value is computed from Build.Spec.Output.To, and should include the registry address, so that it can be used to push and pull the image.	false	string	

Name	Description	Required	Schema	Default
config	config is an ObjectReference to the BuildConfig this Build is based on.	false	Section 2.3.159, "v1.ObjectReference"	

2.3.32. v1.BuildStrategy

BuildStrategy contains the details of how to perform a build.

Name	Description	Required	Schema	Default
type	type is the kind of build strategy.	true	string	
dockerStrategy	dockerStrategy holds the parameters to the Docker build strategy.	false	Section 2.3.77, "v1.DockerBuildStrategy"	
sourceStrategy	sourceStrategy holds the parameters to the Source build strategy.	false	Section 2.3.216, "v1.SourceBuildStrategy"	
customStrategy	customStrategy holds the parameters to the Custom build strategy	false	Section 2.3.59, "v1.CustomBuildStrategy"	
jenkinsPipelineStrategy	JenkinsPipelineStrategy holds the parameters to the Jenkins Pipeline build strategy. This strategy is in tech preview.	false	Section 2.3.134, "v1.JenkinsPipelineBuildStrategy"	

2.3.33. v1.BuildTriggerCause

BuildTriggerCause holds information about a triggered build. It is used for displaying build trigger data for each build and build configuration in oc describe. It is also used to describe which triggers led to the most recent update in the build configuration.

Name	Description	Required	Schema	Default
message	message is used to store a human readable message for why the build was triggered. E.g.: "Manually triggered by user", "Configuration change", etc.	false	string	
genericWebHook	genericWebHook holds data about a builds generic webhook trigger.	false	Section 2.3.95, "v1.GenericWebHookCause"	
githubWebHook	gitHubWebHook represents data for a GitHub webhook that fired a specific build.	false	Section 2.3.97, "v1.GitHubWebHookCause"	
imageChangeBuild	imageChangeBuild stores information about an imagechange event that triggered a new build.	false	Section 2.3.114, "v1.ImageChangeCause"	

2.3.34. v1.BuildTriggerPolicy

BuildTriggerPolicy describes a policy for a single trigger that results in a new Build.

Name	Description	Required	Schema	Default
type	type is the type of build trigger	true	string	
github	github contains the parameters for a GitHub webhook type of trigger	false	Section 2.3.236, "v1.WebHookTrigger"	
generic	generic contains the parameters for a Generic webhook type of trigger	false	Section 2.3.236, "v1.WebHookTrigger"	

Name	Description	Required	Schema	Default
imageChange	imageChange contains parameters for an ImageChange type of trigger	false	Section 2.3.115, "v1.ImageChange Trigger"	

2.3.35. v1.Capabilities

Adds and removes POSIX capabilities from running containers.

Name	Description	Required	Schema	Default
add	Added capabilities	false	Section 2.3.36, "v1.Capability" array	
drop	Removed capabilities	false	Section 2.3.36, "v1.Capability" array	

2.3.36. v1.Capability

2.3.37. v1.CephFSVolumeSource

Represents a Ceph Filesystem mount that lasts the lifetime of a pod Cephfs volumes do not support ownership management or SELinux relabeling.

Name	Description	Required	Schema	Default
monitors	Required: Monitors is a collection of Ceph monitors More info: http://releases.k8s.io/release-1.3/examples/cephfs/README.md#how-to-use-it	true	string array	
path	Optional: Used as the mounted root, rather than the full Ceph tree, default is /	false	string	

Name	Description	Required	Schema	Default
user	Optional: User is the rados user name, default is admin More info: http://releases.k8s.io/release-1.3/examples/cephfs/README.md#how-to-use-it	false	string	
secretFile	Optional: SecretFile is the path to key ring for User, default is /etc/ceph/user.secret More info: http://releases.k8s.io/release-1.3/examples/cephfs/README.md#how-to-use-it	false	string	
secretRef	Optional: SecretRef is reference to the authentication secret for User, default is empty. More info: http://releases.k8s.io/release-1.3/examples/cephfs/README.md#how-to-use-it	false	Section 2.3.138, "v1.LocalObjectReference"	
readOnly	Optional: Defaults to false (read/write). ReadOnly here will force the ReadOnly setting in VolumeMounts. More info: http://releases.k8s.io/release-1.3/examples/cephfs/README.md#how-to-use-it	false	boolean	

2.3.38. v1.CinderVolumeSource

CinderVolumeSource represents a cinder volume resource in Openstack. A Cinder volume must exist before mounting to a container. The volume must also be in the same region as the kubelet.

Name	Description	Required	Schema	Default
volumeID	volume id used to identify the volume in cinder More info: http://releases.k8s.io/release-1.3/examples/mysql-cinder-pd/README.md	true	string	
fsType	Filesystem type to mount. Must be a filesystem type supported by the host operating system. Examples: "ext4", "xfs", "ntfs". Implicitly inferred to be "ext4" if unspecified. More info: http://releases.k8s.io/release-1.3/examples/mysql-cinder-pd/README.md	false	string	
readOnly	Optional: Defaults to false (read/write). ReadOnly here will force the ReadOnly setting in VolumeMounts. More info: http://releases.k8s.io/release-1.3/examples/mysql-cinder-pd/README.md	false	boolean	

2.3.39. v1.ClusterNetwork

ClusterNetwork describes a cluster network

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#types-kinds	false	string	
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#resources	false	string	
metadata	Standard object's metadata.	false	Section 2.3.158, "v1.ObjectMeta"	
network	Network is a CIDR string to specify the global overlay network's L3 space	true	string	

Name	Description	Required	Schema	Default
hostsubnetlength	HostSubnetLength is the number of bits to allocate to each host's subnet e.g. 8 would mean a /24 network on the host	true	integer	
serviceNetwork	ServiceNetwork is the CIDR string to specify the service network	true	string	
pluginName	PluginName is the name of the network plugin	false	string	

2.3.40. v1.ClusterNetworkList

ClusterNetworkList is a collection of ClusterNetworks

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#types-kinds	false	string	

Name	Description	Required	Schema	Default
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#resources	false	string	
metadata	Standard object's metadata.	false	Section 2.3.9, "unversioned.ListMeta"	
items	Items is the list of cluster networks	true	Section 2.3.39, "v1.ClusterNetwork" array	

2.3.41. v1.ClusterPolicy

ClusterPolicy is a object that holds all the ClusterRoles for a particular namespace. There is at most one ClusterPolicy document per namespace.

Name	Description	Required	Schema	Default
------	-------------	----------	--------	---------

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#types-kinds	false	string	
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#resources	false	string	
metadata	Standard object's metadata.	false	Section 2.3.158, "v1.ObjectMeta"	
lastModified	LastModified is the last time that any part of the ClusterPolicy was created, updated, or deleted	true	string	

Name	Description	Required	Schema	Default
roles	Roles holds all the ClusterRoles held by this ClusterPolicy, mapped by ClusterRole.Name	true	Section 2.3.142, "v1.NamedClusterRole" array	

2.3.42. v1.ClusterPolicyBinding

ClusterPolicyBinding is a object that holds all the ClusterRoleBindings for a particular namespace. There is one ClusterPolicyBinding document per referenced ClusterPolicy namespace

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#types-kinds	false	string	

Name	Description	Required	Schema	Default
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#resources	false	string	
metadata	Standard object's metadata.	false	Section 2.3.158, "v1.ObjectMeta"	
lastModified	LastModified is the last time that any part of the ClusterPolicyBinding was created, updated, or deleted	true	string	
policyRef	PolicyRef is a reference to the ClusterPolicy that contains all the ClusterRoles that this ClusterPolicyBinding's RoleBindings may reference	true	Section 2.3.159, "v1.ObjectReference"	
roleBindings	RoleBindings holds all the ClusterRoleBindings held by this ClusterPolicyBinding, mapped by ClusterRoleBinding.Name	true	Section 2.3.143, "v1.NamedClusterRoleBinding" array	

2.3.43. v1.ClusterPolicyBindingList

ClusterPolicyBindingList is a collection of ClusterPolicyBindings

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#types-kinds	false	string	
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#resources	false	string	
metadata	Standard object's metadata.	false	Section 2.3.9, "unversioned.ListMeta"	
items	Items is a list of ClusterPolicyBindings	true	Section 2.3.42, "v1.ClusterPolicyBinding" array	

2.3.44. v1.ClusterPolicyList

ClusterPolicyList is a collection of ClusterPolicies

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#types-kinds	false	string	
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#resources	false	string	
metadata	Standard object's metadata.	false	Section 2.3.9, "unversioned.ListMeta"	
items	Items is a list of ClusterPolicies	true	Section 2.3.41, "v1.ClusterPolicy" array	

2.3.45. v1.ClusterResourceQuota

ClusterResourceQuota mirrors ResourceQuota at a cluster scope. This object is easily convertible to synthetic ResourceQuota object to allow quota evaluation re-use.

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#types-kinds	false	string	
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#resources	false	string	
metadata	Standard object's metadata.	true	Section 2.3.158, "v1.ObjectMeta"	
spec	Spec defines the desired quota	true	Section 2.3.48, "v1.ClusterResourceQuotaSpec"	
status	Status defines the actual enforced quota and its current usage	false	Section 2.3.49, "v1.ClusterResourceQuotaStatus"	

2.3.46. v1.ClusterResourceQuotaList

ClusterResourceQuotaList is a collection of ClusterResourceQuotas

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#types-kinds	false	string	
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#resources	false	string	
metadata	Standard object's metadata.	false	Section 2.3.9, "unversioned.ListMeta"	
items	Items is a list of ClusterResourceQuotas	true	Section 2.3.45, "v1.ClusterResourceQuota" array	

2.3.47. v1.ClusterResourceQuotaSelector

ClusterResourceQuotaSelector is used to select projects. At least one of LabelSelector or AnnotationSelector must present. If only one is present, it is the only selection criteria. If both are specified, the project must match both restrictions.

Name	Description	Required	Schema	Default
labels	LabelSelector is used to select projects by label.	true	Section 2.3.7, "unversioned.LabelSelector"	
annotations	AnnotationSelector is used to select projects by annotation.	true	object	

2.3.48. v1.ClusterResourceQuotaSpec

ClusterResourceQuotaSpec defines the desired quota restrictions

Name	Description	Required	Schema	Default
selector	Selector is the selector used to match projects. It should only select active projects on the scale of dozens (though it can select many more less active projects). These projects will contend on object creation through this resource.	true	Section 2.3.47, "v1.ClusterResourceQuotaSelector"	
quota	Quota defines the desired quota	true	Section 2.3.185, "v1.ResourceQuotaSpec"	

2.3.49. v1.ClusterResourceQuotaStatus

ClusterResourceQuotaStatus defines the actual enforced quota and its current usage

Name	Description	Required	Schema	Default
------	-------------	----------	--------	---------

Name	Description	Required	Schema	Default
total	Total defines the actual enforced quota and its current usage across all projects	true	Section 2.3.186, "v1.ResourceQuotaStatus"	
namespaces	Namespaces slices the usage by project. This division allows for quick resolution of deletion reconciliation inside of a single project without requiring a recalculation across all projects. This can be used to pull the deltas for a given project.	true	Section 2.3.187, "v1.ResourceQuotaStatusByNamespace" array	

2.3.50. v1.ClusterRole

ClusterRole is a logical grouping of PolicyRules that can be referenced as a unit by ClusterRoleBindings.

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/1.3/docs/devel/api-conventions.md#types-kinds	false	string	

Name	Description	Required	Schema	Default
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#resources	false	string	
metadata	Standard object's metadata.	false	Section 2.3.158 , "v1.ObjectMeta"	
rules	Rules holds all the PolicyRules for this ClusterRole	true	Section 2.3.170 , "v1.PolicyRule" array	

2.3.51. v1.ClusterRoleBinding

ClusterRoleBinding references a ClusterRole, but not contain it. It can reference any ClusterRole in the same namespace or in the global namespace. It adds who information via Users and Groups and namespace information by which namespace it exists in. ClusterRoleBindings in a given namespace only have effect in that namespace (excepting the master namespace which has power in all namespaces).

Name	Description	Required	Schema	Default
------	-------------	----------	--------	---------

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#types-kinds	false	string	
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#resources	false	string	
metadata	Standard object's metadata.	false	Section 2.3.158, "v1.ObjectMeta"	
userNames	UserNames holds all the usernames directly bound to the role	true	string array	
groupNames	GroupNames holds all the groups directly bound to the role	true	string array	

Name	Description	Required	Schema	Default
subjects	Subjects hold object references to authorize with this rule	true	Section 2.3.159, "v1.ObjectReference" array	
roleRef	RoleRef can only reference the current namespace and the global namespace. If the ClusterRoleRef cannot be resolved, the Authorizer must return an error. Since Policy is a singleton, this is sufficient knowledge to locate a role	true	Section 2.3.159, "v1.ObjectReference"	

2.3.52. v1.ClusterRoleBindingList

ClusterRoleBindingList is a collection of ClusterRoleBindings

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#types-kinds	false	string	

Name	Description	Required	Schema	Default
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#resources	false	string	
metadata	Standard object's metadata.	false	Section 2.3.9 , "unversioned.ListMeta"	
items	Items is a list of ClusterRoleBindings	true	Section 2.3.51 , "v1.ClusterRoleBinding" array	

2.3.53. v1.ClusterRoleList

ClusterRoleList is a collection of ClusterRoles

Name	Description	Required	Schema	Default
------	-------------	----------	--------	---------

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#types-kinds	false	string	
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#resources	false	string	
metadata	Standard object's metadata.	false	Section 2.3.9, "unversioned.ListMeta"	
items	Items is a list of ClusterRoles	true	Section 2.3.50, "v1.ClusterRole" array	

2.3.54. v1.ClusterRoleScopeRestriction

ClusterRoleScopeRestriction describes restrictions on cluster role scopes

Name	Description	Required	Schema	Default
roleNames	RoleNames is the list of cluster roles that can be referenced. * means anything	true	string array	
namespaces	Namespaces is the list of namespaces that can be referenced. * means any of them (including *)	true	string array	
allowEscalation	AllowEscalation indicates whether you can request roles and their escalating resources	true	boolean	

2.3.55. v1.ConfigMapKeySelector

Selects a key from a ConfigMap.

Name	Description	Required	Schema	Default
name	Name of the referent. More info: http://releases.k8s.io/release-1.3/docs/user-guide/identifiers.md#names	false	string	
key	The key to select.	true	string	

2.3.56. v1.ConfigMapVolumeSource

Adapts a ConfigMap into a volume.

The contents of the target ConfigMap's Data field will be presented in a volume as files using the keys in the Data field as the file names, unless the items element is populated with specific mappings of keys to paths. ConfigMap volumes support ownership management and SELinux relabeling.

Name	Description	Required	Schema	Default
name	Name of the referent. More info: http://releases.k8s.io/release-1.3/docs/user-guide/identifiers.md#names	false	string	
items	If unspecified, each key-value pair in the Data field of the referenced ConfigMap will be projected into the volume as a file whose name is the key and content is the value. If specified, the listed keys will be projected into the specified paths, and unlisted keys will not be present. If a key is specified which is not present in the ConfigMap, the volume setup will error. Paths must be relative and may not contain the '..' path or start with '..'.	false	Section 2.3.135, "v1.KeyToPath" array	

2.3.57. v1.Container

A single application container that you want to run within a pod.

Name	Description	Required	Schema	Default
------	-------------	----------	--------	---------

Name	Description	Required	Schema	Default
name	Name of the container specified as a DNS_LABEL. Each container in a pod must have a unique name (DNS_LABEL). Cannot be updated.	true	string	
image	Docker image name. More info: http://releases.k8s.io/release-1.3/docs/user-guide/images.md	false	string	

Name	Description	Required	Schema	Default
command	<p>Entrypoint array. Not executed within a shell. The docker image's ENTRYPOINT is used if this is not provided. Variable references <code>\$(VAR_NAME)</code> are expanded using the container's environment. If a variable cannot be resolved, the reference in the input string will be unchanged. The <code>\$(VAR_NAME)</code> syntax can be escaped with a double <code>,</code> ie: <code>(VAR_NAME)</code>. Escaped references will never be expanded, regardless of whether the variable exists or not. Cannot be updated. More info: http://releases.k8s.io/release-1.3/docs/user-guide/containers.md#containers-and-commands</p>	false	string array	

Name	Description	Required	Schema	Default
args	<p>Arguments to the entrypoint. The docker image's CMD is used if this is not provided. Variable references <code>\$(VAR_NAME)</code> are expanded using the container's environment. If a variable cannot be resolved, the reference in the input string will be unchanged. The <code>\$(VAR_NAME)</code> syntax can be escaped with a double <code>,</code> ie: <code>(VAR_NAME)</code>. Escaped references will never be expanded, regardless of whether the variable exists or not. Cannot be updated. More info: http://releases.k8s.io/release-1.3/docs/user-guide/containers.md#containers-and-commands</p>	false	string array	
workingDir	<p>Container's working directory. If not specified, the container runtime's default will be used, which might be configured in the container image. Cannot be updated.</p>	false	string	

Name	Description	Required	Schema	Default
ports	List of ports to expose from the container. Exposing a port here gives the system additional information about the network connections a container uses, but is primarily informational. Not specifying a port here DOES NOT prevent that port from being exposed. Any port which is listening on the default "0.0.0.0" address inside a container will be accessible from the network. Cannot be updated.	false	Section 2.3.58 , "v1.ContainerPort" array	
env	List of environment variables to set in the container. Cannot be updated.	false	Section 2.3.86 , "v1.EnvVar" array	
resources	Compute Resources required by this container. Cannot be updated. More info: http://releases.k8s.io/release-1.3/docs/user-guide/persistent-volumes.md#resources	false	Section 2.3.188 , "v1.ResourceRequirements"	
volumeMounts	Pod volumes to mount into the container's filesystem. Cannot be updated.	false	Section 2.3.234 , "v1.VolumeMount" array	

Name	Description	Required	Schema	Default
livenessProbe	Periodic probe of container liveness. Container will be restarted if the probe fails. Cannot be updated. More info: http://releases.k8s.io/release-1.3/docs/user-guide/pod-states.md#container-probes	false	Section 2.3.172, "v1.Probe"	
readinessProbe	Periodic probe of container service readiness. Container will be removed from service endpoints if the probe fails. Cannot be updated. More info: http://releases.k8s.io/release-1.3/docs/user-guide/pod-states.md#container-probes	false	Section 2.3.172, "v1.Probe"	
lifecycle	Actions that the management system should take in response to container lifecycle events. Cannot be updated.	false	Section 2.3.136, "v1.Lifecycle"	

Name	Description	Required	Schema	Default
terminationMessagePath	Optional: Path at which the file to which the container's termination message will be written is mounted into the container's filesystem. Message written is intended to be brief final status, such as an assertion failure message. Defaults to /dev/termination-log. Cannot be updated.	false	string	
imagePullPolicy	Image pull policy. One of Always, Never, IfNotPresent. Defaults to Always if :latest tag is specified, or IfNotPresent otherwise. Cannot be updated. More info: http://releases.k8s.io/release-1.3/docs/user-guide/images.md#updating-images	false	string	
securityContext	Security options the pod should run with. More info: http://releases.k8s.io/release-1.3/docs/design/security_context.md	false	Section 2.3.210, "v1.SecurityContext"	

Name	Description	Required	Schema	Default
stdin	Whether this container should allocate a buffer for stdin in the container runtime. If this is not set, reads from stdin in the container will always result in EOF. Default is false.	false	boolean	
stdinOnce	Whether the container runtime should close the stdin channel after it has been opened by a single attach. When stdin is true the stdin stream will remain open across multiple attach sessions. If stdinOnce is set to true, stdin is opened on container start, is empty until the first client attaches to stdin, and then remains open and accepts data until the client disconnects, at which time stdin is closed and remains closed until the container is restarted. If this flag is false, a container processes that reads from stdin will never receive an EOF. Default is false	false	boolean	

Name	Description	Required	Schema	Default
tty	Whether this container should allocate a TTY for itself, also requires 'stdin' to be true. Default is false.	false	boolean	

2.3.58. v1.ContainerPort

ContainerPort represents a network port in a single container.

Name	Description	Required	Schema	Default
name	If specified, this must be an IANA_SVC_NAME and unique within the pod. Each named port in a pod must have a unique name. Name for the port that can be referred to by services.	false	string	
hostPort	Number of port to expose on the host. If specified, this must be a valid port number, $0 < x < 65536$. If HostNetwork is specified, this must match ContainerPort. Most containers do not need this.	false	integer (int32)	
containerPort	Number of port to expose on the pod's IP address. This must be a valid port number, $0 < x < 65536$.	true	integer (int32)	

Name	Description	Required	Schema	Default
protocol	Protocol for port. Must be UDP or TCP. Defaults to "TCP".	false	string	
hostIP	What host IP to bind the external port to.	false	string	

2.3.59. v1.CustomBuildStrategy

CustomBuildStrategy defines input parameters specific to Custom build.

Name	Description	Required	Schema	Default
from	from is reference to an DockerImage, ImageStreamTag, or ImageStreamImage from which the docker image should be pulled	true	Section 2.3.159, "v1.ObjectReference"	
pullSecret	pullSecret is the name of a Secret that would be used for setting up the authentication for pulling the Docker images from the private Docker registries	false	Section 2.3.138, "v1.LocalObjectReference"	
env	env contains additional environment variables you want to pass into a builder container	false	Section 2.3.86, "v1.EnvVar" array	

Name	Description	Required	Schema	Default
exposeDockerSocket	exposeDockerSocket will allow running Docker commands (and build Docker images) from inside the Docker container.	false	boolean	
forcePull	forcePull describes if the controller should configure the build pod to always pull the images for the builder or only pull if it is not present locally	false	boolean	
secrets	secrets is a list of additional secrets that will be included in the build pod	false	Section 2.3.208, "v1.SecretSpec" array	
buildAPIVersion	buildAPIVersion is the requested API version for the Build object serialized and passed to the custom builder	false	string	

2.3.60. v1.CustomDeploymentStrategyParams

CustomDeploymentStrategyParams are the input to the Custom deployment strategy.

Name	Description	Required	Schema	Default
image	Image specifies a Docker image which can carry out a deployment.	false	string	
environment	Environment holds the environment which will be given to the container for Image.	false	Section 2.3.86, "v1.EnvVar" array	

Name	Description	Required	Schema	Default
command	Command is optional and overrides CMD in the container Image.	false	string array	

2.3.61. v1.DeleteOptions

DeleteOptions may be provided when deleting an API object

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#types-kinds	false	string	
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#resources	false	string	

Name	Description	Required	Schema	Default
gracePeriodSeconds	The duration in seconds before the object should be deleted. Value must be non-negative integer. The value zero indicates delete immediately. If this value is nil, the default grace period for the specified type will be used. Defaults to a per object value if not specified. zero means delete immediately.	false	integer (int64)	
preconditions	Must be fulfilled before a deletion is carried out. If not possible, a 409 Conflict status will be returned.	false	Section 2.3.171, "v1.Preconditions"	
orphanDependents	Should the dependent objects be orphaned. If true/false, the "orphan" finalizer will be added to/removed from the object's finalizers list.	false	boolean	

2.3.62. v1.DeploymentCause

DeploymentCause captures information about a particular cause of a deployment.

Name	Description	Required	Schema	Default
type	Type of the trigger that resulted in the creation of a new deployment	true	string	

Name	Description	Required	Schema	Default
imageTrigger	ImageTrigger contains the image trigger details, if this trigger was fired based on an image change	false	Section 2.3.63, "v1.DeploymentCauseImageTrigger"	

2.3.63. v1.DeploymentCauseImageTrigger

DeploymentCauseImageTrigger represents details about the cause of a deployment originating from an image change trigger

Name	Description	Required	Schema	Default
from	From is a reference to the changed object which triggered a deployment. The field may have the kinds DockerImage, ImageStreamTag, or ImageStreamImage.	true	Section 2.3.159, "v1.ObjectReference"	

2.3.64. v1.DeploymentConfig

Deployment Configs define the template for a pod and manages deploying new images or configuration changes. A single deployment configuration is usually analogous to a single micro-service. Can support many different deployment patterns, including full restart, customizable rolling updates, and fully custom behaviors, as well as pre- and post- deployment hooks. Each individual deployment is represented as a replication controller.

A deployment is "triggered" when its configuration is changed or a tag in an Image Stream is changed. Triggers can be disabled to allow manual control over a deployment. The "strategy" determines how the deployment is carried out and may be changed at any time.

Name	Description	Required	Schema	Default
------	-------------	----------	--------	---------

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#types-kinds	false	string	
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#resources	false	string	
metadata	Standard object's metadata.	false	Section 2.3.158, "v1.ObjectMeta"	
spec	Spec represents a desired deployment state and how to deploy to it.	true	Section 2.3.68, "v1.DeploymentConfigSpec"	
status	Status represents the current deployment state.	true	Section 2.3.69, "v1.DeploymentConfigStatus"	

2.3.65. v1.DeploymentConfigList

DeploymentConfigList is a collection of deployment configs.

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#types-kinds	false	string	
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#resources	false	string	
metadata	Standard object's metadata.	false	Section 2.3.9, "unversioned.ListMeta"	
items	Items is a list of deployment configs	true	Section 2.3.64, "v1.DeploymentConfig" array	

2.3.66. v1.DeploymentConfigRollback

DeploymentConfigRollback provides the input to rollback generation.

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#types-kinds	false	string	
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#resources	false	string	
name	Name of the deployment config that will be rolled back.	true	string	
updatedAnnotations	UpdatedAnnotations is a set of new annotations that will be added in the deployment config.	false	object	

Name	Description	Required	Schema	Default
spec	Spec defines the options to rollback generation.	true	Section 2.3.67, "v1.DeploymentConfigRollbackSpec"	

2.3.67. v1.DeploymentConfigRollbackSpec

DeploymentConfigRollbackSpec represents the options for rollback generation.

Name	Description	Required	Schema	Default
from	From points to a ReplicationController which is a deployment.	true	Section 2.3.159, "v1.ObjectReference"	
revision	Revision to rollback to. If set to 0, rollback to the last revision.	false	integer (int64)	
includeTriggers	IncludeTriggers specifies whether to include config Triggers.	true	boolean	
includeTemplate	IncludeTemplate specifies whether to include the PodTemplateSpec.	true	boolean	
includeReplicationMeta	IncludeReplicationMeta specifies whether to include the replica count and selector.	true	boolean	
includeStrategy	IncludeStrategy specifies whether to include the deployment Strategy.	true	boolean	

2.3.68. v1.DeploymentConfigSpec

DeploymentConfigSpec represents the desired state of the deployment.

Name	Description	Required	Schema	Default
strategy	Strategy describes how a deployment is executed.	true	Section 2.3.72, "v1.DeploymentStrategy"	
minReadySeconds	MinReadySeconds is the minimum number of seconds for which a newly created pod should be ready without any of its container crashing, for it to be considered available. Defaults to 0 (pod will be considered available as soon as it is ready)	false	integer (int32)	
triggers	Triggers determine how updates to a DeploymentConfig result in new deployments. If no triggers are defined, a new deployment can only occur as a result of an explicit client update to the DeploymentConfig with a new LatestVersion. If null, defaults to having a config change trigger.	true	Section 2.3.74, "v1.DeploymentTriggerPolicy" array	
replicas	Replicas is the number of desired replicas.	true	integer (int32)	

Name	Description	Required	Schema	Default
revisionHistoryLimit	RevisionHistoryLimit is the number of old ReplicationControllers to retain to allow for rollbacks. This field is a pointer to allow for differentiation between an explicit zero and not specified.	false	integer (int32)	
test	Test ensures that this deployment config will have zero replicas except while a deployment is running. This allows the deployment config to be used as a continuous deployment test - triggering on images, running the deployment, and then succeeding or failing. Post strategy hooks and After actions can be used to integrate successful deployment with an action.	true	boolean	
paused	Paused indicates that the deployment config is paused resulting in no new deployments on template changes or changes in the template caused by other triggers.	false	boolean	

Name	Description	Required	Schema	Default
selector	Selector is a label query over pods that should match the Replicas count.	false	object	
template	Template is the object that describes the pod that will be created if insufficient replicas are detected.	false	Section 2.3.165, "v1.PodTemplateSpec"	

2.3.69. v1.DeploymentConfigStatus

DeploymentConfigStatus represents the current deployment state.

Name	Description	Required	Schema	Default
latestVersion	LatestVersion is used to determine whether the current deployment associated with a deployment config is out of sync.	false	integer (int64)	
observedGeneration	ObservedGeneration is the most recent generation observed by the deployment config controller.	false	integer (int64)	
replicas	Replicas is the total number of pods targeted by this deployment config.	false	integer (int32)	
updatedReplicas	UpdatedReplicas is the total number of non-terminated pods targeted by this deployment config that have the desired template spec.	false	integer (int32)	

Name	Description	Required	Schema	Default
availableReplicas	AvailableReplicas is the total number of available pods targeted by this deployment config.	false	integer (int32)	
unavailableReplicas	UnavailableReplicas is the total number of unavailable pods targeted by this deployment config.	false	integer (int32)	
details	Details are the reasons for the update to this deployment config. This could be based on a change made by the user or caused by an automatic trigger	false	Section 2.3.70, "v1.DeploymentDetails"	

2.3.70. v1.DeploymentDetails

DeploymentDetails captures information about the causes of a deployment.

Name	Description	Required	Schema	Default
message	Message is the user specified change message, if this deployment was triggered manually by the user	false	string	
causes	Causes are extended data associated with all the causes for creating a new deployment	true	Section 2.3.62, "v1.DeploymentCause" array	

2.3.71. v1.DeploymentLog

A deployment log is a virtual resource used by the OpenShift client tool for retrieving the logs for a deployment.

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#types-kinds	false	string	
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#resources	false	string	

2.3.72. v1.DeploymentStrategy

DeploymentStrategy describes how to perform a deployment.

Name	Description	Required	Schema	Default
type	Type is the name of a deployment strategy.	false	string	

Name	Description	Required	Schema	Default
customParams	CustomParams are the input to the Custom deployment strategy.	false	Section 2.3.60, "v1.CustomDeploymentStrategyParams"	
recreateParams	RecreateParams are the input to the Recreate deployment strategy.	false	Section 2.3.179, "v1.RecreateDeploymentStrategyParams"	
rollingParams	RollingParams are the input to the Rolling deployment strategy.	false	Section 2.3.193, "v1.RollingDeploymentStrategyParams"	
resources	Resources contains resource requirements to execute the deployment and any hooks	false	Section 2.3.188, "v1.ResourceRequirements"	
labels	Labels is a set of key, value pairs added to custom deployer and lifecycle pre/post hook pods.	false	object	
annotations	Annotations is a set of key, value pairs added to custom deployer and lifecycle pre/post hook pods.	false	object	

2.3.73. v1.DeploymentTriggerImageChangeParams

DeploymentTriggerImageChangeParams represents the parameters to the ImageChange trigger.

Name	Description	Required	Schema	Default
------	-------------	----------	--------	---------

Name	Description	Required	Schema	Default
automatic	Automatic means that the detection of a new tag value should result in an image update inside the pod template. Deployment configs that haven't been deployed yet will always have their images updated. Deployment configs that have been deployed at least once, will have their images updated only if this is set to true.	false	boolean	
containerNames	ContainerNames is used to restrict tag updates to the specified set of container names in a pod.	false	string array	
from	From is a reference to an image stream tag to watch for changes. From.Name is the only required subfield - if From.Namespace is blank, the namespace of the current deployment trigger will be used.	true	Section 2.3.159, "v1.ObjectReference"	
lastTriggeredImage	LastTriggeredImage is the last image to be triggered.	false	string	

2.3.74. v1.DeploymentTriggerPolicy

DeploymentTriggerPolicy describes a policy for a single trigger that results in a new deployment.

Name	Description	Required	Schema	Default
type	Type of the trigger	false	string	
imageChangeParams	ImageChangeParams represents the parameters for the ImageChange trigger.	false	Section 2.3.73, "v1.DeploymentTriggerImageChangeParams"	

2.3.75. v1.DeprecatedDownwardAPIVolumeFile

DeprecatedDownwardAPIVolumeFile represents information to create the file containing the pod field. This type is deprecated and should be replaced by use of the downwardAPI volume source.

Name	Description	Required	Schema	Default
name	Required: Name is the relative path name of the file to be created. Must not be absolute or contain the '..' path. Must be utf-8 encoded. The first item of the relative path must not start with '..'	true	string	
fieldRef	Required: Selects a field of the pod: only annotations, labels, name and namespace are supported.	false	Section 2.3.157, "v1.ObjectFieldSelector"	
resourceFieldRef	Selects a resource of the container: only resources limits and requests (limits.cpu, limits.memory, requests.cpu and requests.memory) are currently supported.	false	Section 2.3.183, "v1.ResourceFieldSelector"	

2.3.76. v1.DeprecatedDownwardAPIVolumeSource

DeprecatedDownwardAPIVolumeSource represents a volume containing downward API info. This type is deprecated and should be replaced by use of the downwardAPI volume source.

Name	Description	Required	Schema	Default
items	Items is a list of downward API volume file	false	Section 2.3.75 , “v1.DeprecatedDownwardAPIVolumeFile” array	

2.3.77. v1.DockerBuildStrategy

DockerBuildStrategy defines input parameters specific to Docker build.

Name	Description	Required	Schema	Default
from	from is reference to an DockerImage, ImageStreamTag, or ImageStreamImage from which the docker image should be pulled the resulting image will be used in the FROM line of the Dockerfile for this build.	false	Section 2.3.159 , “v1.ObjectReference”	
pullSecret	pullSecret is the name of a Secret that would be used for setting up the authentication for pulling the Docker images from the private Docker registries	false	Section 2.3.138 , “v1.LocalObjectReference”	
noCache	noCache if set to true indicates that the docker build must be executed with the --no-cache=true flag	false	boolean	
env	env contains additional environment variables you want to pass into a builder container	false	Section 2.3.86 , “v1.EnvVar” array	

Name	Description	Required	Schema	Default
forcePull	forcePull describes if the builder should pull the images from registry prior to building.	false	boolean	
dockerfilePath	dockerfilePath is the path of the Dockerfile that will be used to build the Docker image, relative to the root of the context (contextDir).	false	string	

2.3.78. v1.DownwardAPIVolumeFile

DownwardAPIVolumeFile represents a single file containing information from the downward API

Name	Description	Required	Schema	Default
path	Required: Path is the relative path name of the file to be created. Must not be absolute or contain the '..' path. Must be utf-8 encoded. The first item of the relative path must not start with '..'	true	string	
fieldRef	Required: Selects a field of the pod: only annotations, labels, name and namespace are supported.	false	Section 2.3.157, "v1.ObjectFieldSelector"	

Name	Description	Required	Schema	Default
resourceFieldRef	Selects a resource of the container: only resources limits and requests (limits.cpu, limits.memory, requests.cpu and requests.memory) are currently supported.	false	Section 2.3.183, "v1.ResourceField Selector"	

2.3.79. v1.DownwardAPIVolumeSource

DownwardAPIVolumeSource represents a volume containing downward API info

Name	Description	Required	Schema	Default
items	Items is a list of downward API volume file	false	Section 2.3.78, "v1.DownwardAPI VolumeFile" array	

2.3.80. v1.EgressNetworkPolicy

EgressNetworkPolicy describes the current egress network policy for a Namespace. When using the 'redhat/openshift-ovs-multitenant' network plugin, traffic from a pod to an IP address outside the cluster will be checked against each EgressNetworkPolicyRule in the pod's namespace's EgressNetworkPolicy, in order. If no rule matches (or no EgressNetworkPolicy is present) then the traffic will be allowed by default.

Name	Description	Required	Schema	Default
------	-------------	----------	--------	---------

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#types-kinds	false	string	
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#resources	false	string	
metadata	metadata for EgressNetworkPolicy	false	Section 2.3.158, "v1.ObjectMeta"	
spec	spec is the specification of the current egress network policy	true	Section 2.3.84, "v1.EgressNetworkPolicySpec"	

2.3.81. v1.EgressNetworkPolicyList

EgressNetworkPolicyList is a collection of EgressNetworkPolicy

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#types-kinds	false	string	
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#resources	false	string	
metadata	metadata for EgressNetworkPolicyList	false	Section 2.3.9, "unversioned.ListMeta"	
items	items is the list of policies	true	Section 2.3.80, "v1.EgressNetworkPolicy" array	

2.3.82. v1.EgressNetworkPolicyPeer

EgressNetworkPolicyPeer specifies a target to apply egress network policy to

Name	Description	Required	Schema	Default
cidrSelector	cidrSelector is the CIDR range to allow/deny traffic to	true	string	

2.3.83. v1.EgressNetworkPolicyRule

EgressNetworkPolicyRule contains a single egress network policy rule

Name	Description	Required	Schema	Default
type	type marks this as an "Allow" or "Deny" rule	true	string	
to	to is the target that traffic is allowed/denied to	true	Section 2.3.82, "v1.EgressNetworkPolicyPeer"	

2.3.84. v1.EgressNetworkPolicySpec

EgressNetworkPolicySpec provides a list of policies on outgoing network traffic

Name	Description	Required	Schema	Default
egress	egress contains the list of egress policy rules	true	Section 2.3.83, "v1.EgressNetworkPolicyRule" array	

2.3.85. v1.EmptyDirVolumeSource

Represents an empty directory for a pod. Empty directory volumes support ownership management and SELinux relabeling.

Name	Description	Required	Schema	Default
------	-------------	----------	--------	---------

Name	Description	Required	Schema	Default
medium	What type of storage medium should back this directory. The default is "" which means to use the node's default medium. Must be an empty string (default) or Memory. More info: http://releases.k8s.io/release-1.3/docs/user-guide/volumes.md#emptydir	false	string	

2.3.86. v1.EnvVar

EnvVar represents an environment variable present in a Container.

Name	Description	Required	Schema	Default
name	Name of the environment variable. Must be a C_IDENTIFIER.	true	string	

Name	Description	Required	Schema	Default
value	Variable references <code>\$(VAR_NAME)</code> are expanded using the previous defined environment variables in the container and any service environment variables. If a variable cannot be resolved, the reference in the input string will be unchanged. The <code>\$(VAR_NAME)</code> syntax can be escaped with a double <code>,</code> ie: <code>(VAR_NAME)</code> . Escaped references will never be expanded, regardless of whether the variable exists or not. Defaults to <code>""</code> .	false	string	
valueFrom	Source for the environment variable's value. Cannot be used if value is not empty.	false	Section 2.3.87, "v1.EnvVarSource"	

2.3.87. v1.EnvVarSource

EnvVarSource represents a source for the value of an EnvVar.

Name	Description	Required	Schema	Default
fieldRef	Selects a field of the pod; only name and namespace are supported.	false	Section 2.3.157, "v1.ObjectFieldSelector"	

Name	Description	Required	Schema	Default
resourceFieldRef	Selects a resource of the container: only resources limits and requests (limits.cpu, limits.memory, requests.cpu and requests.memory) are currently supported.	false	Section 2.3.183, "v1.ResourceField Selector"	
configMapKeyRef	Selects a key of a ConfigMap.	false	Section 2.3.55, "v1.ConfigMapKey Selector"	
secretKeyRef	Selects a key of a secret in the pod's namespace	false	Section 2.3.206, "v1.SecretKeySelector"	

2.3.88. v1.ExecAction

ExecAction describes a "run in container" action.

Name	Description	Required	Schema	Default
command	Command is the command line to execute inside the container, the working directory for the command is root ('/') in the container's filesystem. The command is simply exec'd, it is not run inside a shell, so traditional shell instructions (' ', etc) won't work. To use a shell, you need to explicitly call out to that shell. Exit status of 0 is treated as live/healthy and non-zero is unhealthy.	false	string array	

2.3.89. v1.ExecNewPodHook

ExecNewPodHook is a hook implementation which runs a command in a new pod based on the specified container which is assumed to be part of the deployment template.

Name	Description	Required	Schema	Default
command	Command is the action command and its arguments.	true	string array	
env	Env is a set of environment variables to supply to the hook pod's container.	false	Section 2.3.86 , "v1.EnvVar" array	
containerName	ContainerName is the name of a container in the deployment pod template whose Docker image will be used for the hook pod's container.	true	string	
volumes	Volumes is a list of named volumes from the pod template which should be copied to the hook pod. Volumes names not found in pod spec are ignored. An empty list means no volumes will be copied.	false	string array	

2.3.90. v1.FCVolumeSource

Represents a Fibre Channel volume. Fibre Channel volumes can only be mounted as read/write once. Fibre Channel volumes support ownership management and SELinux relabeling.

Name	Description	Required	Schema	Default
targetWWNs	Required: FC target world wide names (WWNs)	true	string array	

Name	Description	Required	Schema	Default
lun	Required: FC target lun number	true	integer (int32)	
fsType	Filesystem type to mount. Must be a filesystem type supported by the host operating system. Ex. "ext4", "xfs", "ntfs". Implicitly inferred to be "ext4" if unspecified.	false	string	
readOnly	Optional: Defaults to false (read/write). ReadOnly here will force the ReadOnly setting in VolumeMounts.	false	boolean	

2.3.91. v1.FinalizerName

2.3.92. v1.FlexVolumeSource

FlexVolume represents a generic volume resource that is provisioned/attached using a exec based plugin. This is an alpha feature and may change in future.

Name	Description	Required	Schema	Default
driver	Driver is the name of the driver to use for this volume.	true	string	
fsType	Filesystem type to mount. Must be a filesystem type supported by the host operating system. Ex. "ext4", "xfs", "ntfs". The default filesystem depends on FlexVolume script.	false	string	

Name	Description	Required	Schema	Default
secretRef	Optional: SecretRef is reference to the secret object containing sensitive information to pass to the plugin scripts. This may be empty if no secret object is specified. If the secret object contains more than one secret, all secrets are passed to the plugin scripts.	false	Section 2.3.138, "v1.LocalObjectReference"	
readOnly	Optional: Defaults to false (read/write). ReadOnly here will force the ReadOnly setting in VolumeMounts.	false	boolean	
options	Optional: Extra command options if any.	false	object	

2.3.93. v1.FlockerVolumeSource

Represents a Flocker volume mounted by the Flocker agent. Flocker volumes do not support ownership management or SELinux relabeling.

Name	Description	Required	Schema	Default
datasetName	Required: the volume name. This is going to be store on metadata → name on the payload for Flocker	true	string	

2.3.94. v1.GCEPersistentDiskVolumeSource

Represents a Persistent Disk resource in Google Compute Engine.

A GCE PD must exist before mounting to a container. The disk must also be in the same GCE project and zone as the kubelet. A GCE PD can only be mounted as read/write once or read-only many times. GCE PDs support ownership management and SELinux relabeling.

Name	Description	Required	Schema	Default
pdName	Unique name of the PD resource in GCE. Used to identify the disk in GCE. More info: http://releases.k8s.io/release-1.3/docs/user-guide/volumes.md#gcepersistentdisk	true	string	
fsType	Filesystem type of the volume that you want to mount. Tip: Ensure that the filesystem type is supported by the host operating system. Examples: "ext4", "xfs", "ntfs". Implicitly inferred to be "ext4" if unspecified. More info: http://releases.k8s.io/release-1.3/docs/user-guide/volumes.md#gcepersistentdisk	false	string	

Name	Description	Required	Schema	Default
partition	The partition in the volume that you want to mount. If omitted, the default is to mount by volume name. Examples: For volume /dev/sda1, you specify the partition as "1". Similarly, the volume partition for /dev/sda is "0" (or you can leave the property empty). More info: http://releases.k8s.io/release-1.3/docs/user-guide/volumes.md#gcepersistentdisk	false	integer (int32)	
readOnly	ReadOnly here will force the ReadOnly setting in VolumeMounts. Defaults to false. More info: http://releases.k8s.io/release-1.3/docs/user-guide/volumes.md#gcepersistentdisk	false	boolean	

2.3.95. v1.GenericWebHookCause

GenericWebHookCause holds information about a generic WebHook that triggered a build.

Name	Description	Required	Schema	Default
revision	revision is an optional field that stores the git source revision information of the generic webhook trigger when it is available.	false	Section 2.3.218, "v1.SourceRevision"	

Name	Description	Required	Schema	Default
secret	secret is the obfuscated webhook secret that triggered a build.	false	string	

2.3.96. v1.GitBuildSource

GitBuildSource defines the parameters of a Git SCM

Name	Description	Required	Schema	Default
uri	uri points to the source that will be built. The structure of the source will depend on the type of build to run	true	string	
ref	ref is the branch/tag/ref to build.	false	string	
httpProxy	httpProxy is a proxy used to reach the git repository over http	false	string	
httpsProxy	httpsProxy is a proxy used to reach the git repository over https	false	string	

2.3.97. v1.GitHubWebHookCause

GitHubWebHookCause has information about a GitHub webhook that triggered a build.

Name	Description	Required	Schema	Default
revision	revision is the git revision information of the trigger.	false	Section 2.3.218, "v1.SourceRevision"	

Name	Description	Required	Schema	Default
secret	secret is the obfuscated webhook secret that triggered a build.	false	string	

2.3.98. v1.GitRepoVolumeSource

Represents a volume that is populated with the contents of a git repository. Git repo volumes do not support ownership management. Git repo volumes support SELinux relabeling.

Name	Description	Required	Schema	Default
repository	Repository URL	true	string	
revision	Commit hash for the specified revision.	false	string	
directory	Target directory name. Must not contain or start with '..'. If '.' is supplied, the volume directory will be the git repository. Otherwise, if specified, the volume will contain the git repository in the subdirectory with the given name.	false	string	

2.3.99. v1.GitSourceRevision

GitSourceRevision is the commit information from a git source for a build

Name	Description	Required	Schema	Default
commit	commit is the commit hash identifying a specific commit	false	string	

Name	Description	Required	Schema	Default
author	author is the author of a specific commit	false	Section 2.3.217, "v1.SourceControl User"	
committer	committer is the committer of a specific commit	false	Section 2.3.217, "v1.SourceControl User"	
message	message is the description of a specific commit	false	string	

2.3.100. v1.GlusterfsVolumeSource

Represents a Glusterfs mount that lasts the lifetime of a pod. Glusterfs volumes do not support ownership management or SELinux relabeling.

Name	Description	Required	Schema	Default
endpoints	EndpointsName is the endpoint name that details Glusterfs topology. More info: http://releases.k8s.io/release-1.3/examples/glusterfs/README.md#create-a-pod	true	string	
path	Path is the Glusterfs volume path. More info: http://releases.k8s.io/release-1.3/examples/glusterfs/README.md#create-a-pod	true	string	

Name	Description	Required	Schema	Default
readOnly	ReadOnly here will force the Glusterfs volume to be mounted with read-only permissions. Defaults to false. More info: http://releases.k8s.io/release-1.3/examples/glusterfs/README.md#create-a-pod	false	boolean	

2.3.101. v1.Group

Group represents a referenceable set of Users

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#types-kinds	false	string	

Name	Description	Required	Schema	Default
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#resources	false	string	
metadata	Standard object's metadata.	false	Section 2.3.158, "v1.ObjectMeta"	
users	Users is the list of users in this group.	true	string array	

2.3.102. v1.GroupList

GroupList is a collection of Groups

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#types-kinds	false	string	

Name	Description	Required	Schema	Default
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#resources	false	string	
metadata	Standard object's metadata.	false	Section 2.3.9, "unversioned.ListMeta"	
items	Items is the list of groups	true	Section 2.3.101, "v1.Group" array	

2.3.103. v1.HTTPGetAction

HTTPGetAction describes an action based on HTTP Get requests.

Name	Description	Required	Schema	Default
path	Path to access on the HTTP server.	false	string	
port	Name or number of the port to access on the container. Number must be in the range 1 to 65535. Name must be an IANA_SVC_NAME	true	string	

Name	Description	Required	Schema	Default
host	Host name to connect to, defaults to the pod IP. You probably want to set "Host" in httpHeaders instead.	false	string	
scheme	Scheme to use for connecting to the host. Defaults to HTTP.	false	string	
httpHeaders	Custom headers to set in the request. HTTP allows repeated headers.	false	Section 2.3.104, "v1.HTTPHeader" array	

2.3.104. v1.HTTPHeader

HTTPHeader describes a custom header to be used in HTTP probes

Name	Description	Required	Schema	Default
name	The header field name	true	string	
value	The header field value	true	string	

2.3.105. v1.Handler

Handler defines a specific action that should be taken

Name	Description	Required	Schema	Default
exec	One and only one of the following should be specified. Exec specifies the action to take.	false	Section 2.3.88, "v1.ExecAction"	
httpGet	HTTPGet specifies the http request to perform.	false	Section 2.3.103, "v1.HTTPGetAction"	

Name	Description	Required	Schema	Default
tcpSocket	TCP socket specifies an action involving a TCP port. TCP hooks not yet supported	false	Section 2.3.221, "v1.TCP socket Action"	

2.3.106. v1.HostPathVolumeSource

Represents a host path mapped into a pod. Host path volumes do not support ownership management or SELinux relabeling.

Name	Description	Required	Schema	Default
path	Path of the directory on the host. More info: http://releases.k8s.io/release-1.3/docs/user-guide/volumes.md#hostpath	true	string	

2.3.107. v1.HostSubnet

HostSubnet encapsulates the inputs needed to define the container subnet network on a node

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#types-kinds	false	string	

Name	Description	Required	Schema	Default
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#resources	false	string	
metadata	Standard object's metadata.	false	Section 2.3.158, "v1.ObjectMeta"	
host	Host is the name of the host that is registered at the master. May just be an IP address, resolvable hostname or a complete DNS. A lease will be sought after this name.	true	string	
hostIP	HostIP is the IP address to be used as vtep by other hosts in the overlay network	true	string	
subnet	Subnet is the actual subnet CIDR lease assigned to the host	true	string	

2.3.108. v1.HostSubnetList

HostSubnetList is a collection of HostSubnets

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#types-kinds	false	string	
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#resources	false	string	
metadata	Standard object's metadata.	false	Section 2.3.9, "unversioned.ListMeta"	
items	Items is the list of host subnets	true	Section 2.3.107, "v1.HostSubnet" array	

2.3.109. v1.ISCSIVolumeSource

Represents an iSCSI disk. iSCSI volumes can only be mounted as read/write once. iSCSI volumes support ownership management and SELinux relabeling.

Name	Description	Required	Schema	Default
targetPortal	iSCSI target portal. The portal is either an IP or ip_addr:port if the port is other than default (typically TCP ports 860 and 3260).	true	string	
iqn	Target iSCSI Qualified Name.	true	string	
lun	iSCSI target lun number.	true	integer (int32)	
iscsiInterface	Optional: Defaults to 'default' (tcp). iSCSI interface name that uses an iSCSI transport.	false	string	
fsType	Filesystem type of the volume that you want to mount. Tip: Ensure that the filesystem type is supported by the host operating system. Examples: "ext4", "xfs", "ntfs". Implicitly inferred to be "ext4" if unspecified. More info: http://releases.k8s.io/release-1.3/docs/user-guide/volumes.md#iscsi	false	string	
readOnly	ReadOnly here will force the ReadOnly setting in VolumeMounts. Defaults to false.	false	boolean	

2.3.110. v1.Identity

Identity records a successful authentication of a user with an identity provider

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#types-kinds	false	string	
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#resources	false	string	
metadata	Standard object's metadata.	false	Section 2.3.158, "v1.ObjectMeta"	
providerName	ProviderName is the source of identity information	true	string	

Name	Description	Required	Schema	Default
providerUserName	ProviderUserName uniquely represents this identity in the scope of the provider	true	string	
user	User is a reference to the user this identity is associated with Both Name and UID must be set	true	Section 2.3.159, "v1.ObjectReference"	
extra	Extra holds extra information about this identity	false	object	

2.3.111. v1.IdentityList

IdentityList is a collection of Identities

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#types-kinds	false	string	

Name	Description	Required	Schema	Default
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#resources	false	string	
metadata	Standard object's metadata.	false	Section 2.3.9 , "unversioned.ListMeta"	
items	Items is the list of identities	true	Section 2.3.110 , "v1.Identity" array	

2.3.112. v1.Image

Image is an immutable representation of a Docker image and metadata at a point in time.

Name	Description	Required	Schema	Default
------	-------------	----------	--------	---------

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#types-kinds	false	string	
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#resources	false	string	
metadata	Standard object's metadata.	false	Section 2.3.158, "v1.ObjectMeta"	
dockerImageReference	DockerImageReference is the string that can be used to pull this image.	false	string	
dockerImageMetadata	DockerImageMetadata contains metadata about this image	false	string	

Name	Description	Required	Schema	Default
dockerImageMetadataVersion	DockerImageMetadataVersion conveys the version of the object, which if empty defaults to "1.0"	false	string	
dockerImageManifest	DockerImageManifest is the raw JSON of the manifest	false	string	
dockerImageLayers	DockerImageLayers represents the layers in the image. May not be set if the image does not define that data.	true	Section 2.3.118 , "v1.ImageLayer" array	
signatures	Signatures holds all signatures of the image.	false	Section 2.3.120 , "v1.ImageSignature" array	
dockerImageSignatures	DockerImageSignatures provides the signatures as opaque blobs. This is a part of manifest schema v1.	false	Section 2.3.113 , "v1.Image.dockerImageSignatures" array	
dockerImageManifestMediaType	DockerImageManifestMediaType specifies the mediaType of manifest. This is a part of manifest schema v2.	false	string	
dockerImageConfig	DockerImageConfig is a JSON blob that the runtime uses to set up the container. This is a part of manifest schema v2.	false	string	

2.3.113. v1.Image.dockerImageSignatures

2.3.114. v1.ImageChangeCause

ImageChangeCause contains information about the image that triggered a build

Name	Description	Required	Schema	Default
imageID	imageID is the ID of the image that triggered a new build.	false	string	
fromRef	fromRef contains detailed information about an image that triggered a build.	false	Section 2.3.159, "v1.ObjectReference"	

2.3.115. v1.ImageChangeTrigger

ImageChangeTrigger allows builds to be triggered when an ImageStream changes

Name	Description	Required	Schema	Default
lastTriggeredImageID	lastTriggeredImageID is used internally by the ImageChangeController to save last used image ID for build	false	string	
from	from is a reference to an ImageStreamTag that will trigger a build when updated. It is optional. If no From is specified, the From image from the build strategy will be used. Only one ImageChangeTrigger with an empty From reference is allowed in a build configuration.	false	Section 2.3.159, "v1.ObjectReference"	

2.3.116. v1.ImageImportSpec

ImageImportSpec describes a request to import a specific image.

Name	Description	Required	Schema	Default
from	From is the source of an image to import; only kind DockerImage is allowed	true	Section 2.3.159, "v1.ObjectReference"	
to	To is a tag in the current image stream to assign the imported image to, if name is not specified the default tag from from.name will be used	false	Section 2.3.138, "v1.LocalObjectReference"	
importPolicy	ImportPolicy is the policy controlling how the image is imported	false	Section 2.3.226, "v1.TagImportPolicy"	
includeManifest	IncludeManifest determines if the manifest for each image is returned in the response	false	boolean	

2.3.117. v1.ImageImportStatus

ImageImportStatus describes the result of an image import.

Name	Description	Required	Schema	Default
status	Status is the status of the image import, including errors encountered while retrieving the image	true	Section 2.3.11, "unversioned.Status"	
image	Image is the metadata of that image, if the image was located	false	Section 2.3.112, "v1.Image"	

Name	Description	Required	Schema	Default
tag	Tag is the tag this image was located under, if any	false	string	

2.3.118. v1.ImageLayer

ImageLayer represents a single layer of the image. Some images may have multiple layers. Some may have none.

Name	Description	Required	Schema	Default
name	Name of the layer as defined by the underlying store.	true	string	
size	Size of the layer in bytes as defined by the underlying store.	true	integer (int64)	
mediaType	MediaType of the referenced object.	true	string	

2.3.119. v1.ImageList

ImageList is a list of Image objects.

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#types-kinds	false	string	

Name	Description	Required	Schema	Default
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#resources	false	string	
metadata	Standard object's metadata.	false	Section 2.3.9, "unversioned.ListMeta"	
items	Items is a list of images	true	Section 2.3.112, "v1.Image" array	

2.3.120. v1.ImageSignature

ImageSignature holds a signature of an image. It allows to verify image identity and possibly other claims as long as the signature is trusted. Based on this information it is possible to restrict runnable images to those matching cluster-wide policy. Mandatory fields should be parsed by clients doing image

verification. The others are parsed from signature's content by the server. They serve just an informative purpose.

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#types-kinds	false	string	
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#resources	false	string	
metadata	Standard object's metadata.	false	Section 2.3.158, "v1.ObjectMeta"	
type	Required: Describes a type of stored blob.	true	string	

Name	Description	Required	Schema	Default
content	Required: An opaque binary string which is an image's signature.	true	integer array	
conditions	Conditions represent the latest available observations of a signature's current state.	false	Section 2.3.213 , "v1.SignatureCondition" array	
imageIdentity	A human readable string representing image's identity. It could be a product name and version, or an image pull spec (e.g. "registry.access.redhat.com/rhel7/rhel:7.2").	false	string	
signedClaims	Contains claims from the signature.	false	object	
created	If specified, it is the time of signature's creation.	false	string	
issuedBy	If specified, it holds information about an issuer of signing certificate or key (a person or entity who signed the signing certificate or key).	false	Section 2.3.214 , "v1.SignatureIssuer"	
issuedTo	If specified, it holds information about a subject of signing certificate or key (a person or entity who signed the image).	false	Section 2.3.215 , "v1.SignatureSubject"	

2.3.121. v1.ImageSource

ImageSource is used to describe build source that will be extracted from an image. A reference of type ImageStreamTag, ImageStreamImage or DockerImage may be used. A pull secret can be specified to pull the image from an external registry or override the default service account secret if pulling from the internal registry. A list of paths to copy from the image and their respective destination within the build directory must be specified in the paths array.

EXPERIMENTAL. This will be changing to an array of images in the near future and no migration/compatibility will be provided. Use at your own risk.

Name	Description	Required	Schema	Default
from	from is a reference to an ImageStreamTag, ImageStreamImage, or DockerImage to copy source from.	true	Section 2.3.159, "v1.ObjectReference"	
paths	paths is a list of source and destination paths to copy from the image.	true	Section 2.3.122, "v1.ImageSourcePath" array	
pullSecret	pullSecret is a reference to a secret to be used to pull the image from a registry. If the image is pulled from the OpenShift registry, this field does not need to be set.	false	Section 2.3.138, "v1.LocalObjectReference"	

2.3.122. v1.ImageSourcePath

ImageSourcePath specifies the absolute path of a file or directory within a source image to be copied to a relative directory of the build home. If a source directory is specified, all files and directories under that directory are copied from the image.

Name	Description	Required	Schema	Default
sourcePath	sourcePath is the absolute path of the file or directory inside the image to copy to the build directory.	true	string	

Name	Description	Required	Schema	Default
destinationDir	destinationDir is the relative directory within the build directory where files copied from the image are placed.	true	string	

2.3.123. v1.ImageStream

ImageStream stores a mapping of tags to images, metadata overrides that are applied when images are tagged in a stream, and an optional reference to a Docker image repository on a registry.

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#types-kinds	false	string	

Name	Description	Required	Schema	Default
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#resources	false	string	
metadata	Standard object's metadata.	false	Section 2.3.158, "v1.ObjectMeta"	
spec	Spec describes the desired state of this stream	true	Section 2.3.130, "v1.ImageStreamSpec"	
status	Status describes the current state of this stream	false	Section 2.3.131, "v1.ImageStreamStatus"	

2.3.124. v1.ImageStreamImage

ImageStreamImage represents an Image that is retrieved by image name from an ImageStream.

Name	Description	Required	Schema	Default
------	-------------	----------	--------	---------

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#types-kinds	false	string	
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#resources	false	string	
metadata	Standard object's metadata.	false	Section 2.3.158, "v1.ObjectMeta"	
image	Image associated with the ImageStream and image name.	true	Section 2.3.112, "v1.Image"	

2.3.125. v1.ImageStreamImport

The image stream import resource provides an easy way for a user to find and import Docker images from other Docker registries into the server. Individual images or an entire image repository may be imported, and users may choose to see the results of the import prior to tagging the resulting images into

the specified image stream.

This API is intended for end-user tools that need to see the metadata of the image prior to import (for instance, to generate an application from it). Clients that know the desired image can continue to create spec.tags directly into their image streams.

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#types-kinds	false	string	
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#resources	false	string	
metadata	Standard object's metadata.	false	Section 2.3.158, "v1.ObjectMeta"	
spec	Spec is a description of the images that the user wishes to import	true	Section 2.3.126, "v1.ImageStreamImportSpec"	

Name	Description	Required	Schema	Default
status	Status is the the result of importing the image	true	Section 2.3.127, "v1.ImageStreamImportStatus"	

2.3.126. v1.ImageStreamImportSpec

ImageStreamImportSpec defines what images should be imported.

Name	Description	Required	Schema	Default
import	Import indicates whether to perform an import - if so, the specified tags are set on the spec and status of the image stream defined by the type meta.	true	boolean	
repository	Repository is an optional import of an entire Docker image repository. A maximum limit on the number of tags imported this way is imposed by the server.	false	Section 2.3.180, "v1.RepositoryImportSpec"	
images	Images are a list of individual images to import.	false	Section 2.3.116, "v1.ImageImportSpec" array	

2.3.127. v1.ImageStreamImportStatus

ImageStreamImportStatus contains information about the status of an image stream import.

Name	Description	Required	Schema	Default
import	Import is the image stream that was successfully updated or created when 'to' was set.	false	Section 2.3.123, "v1.ImageStream"	

Name	Description	Required	Schema	Default
repository	Repository is set if spec.repository was set to the outcome of the import	false	Section 2.3.181, "v1.RepositoryImportStatus"	
images	Images is set with the result of importing spec.images	false	Section 2.3.117, "v1.ImageImportStatus" array	

2.3.128. v1.ImageStreamList

ImageStreamList is a list of ImageStream objects.

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#types-kinds	false	string	

Name	Description	Required	Schema	Default
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#resources	false	string	
metadata	Standard object's metadata.	false	Section 2.3.9, "unversioned.ListMeta"	
items	Items is a list of imageStreams	true	Section 2.3.123, "v1.ImageStream" array	

2.3.129. v1.ImageStreamMapping

ImageStreamMapping represents a mapping from a single tag to a Docker image as well as the reference to the Docker image stream the image came from.

Name	Description	Required	Schema	Default
------	-------------	----------	--------	---------

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#types-kinds	false	string	
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#resources	false	string	
metadata	Standard object's metadata.	false	Section 2.3.158, "v1.ObjectMeta"	
image	Image is a Docker image.	true	Section 2.3.112, "v1.Image"	
tag	Tag is a string value this image can be located with inside the stream.	true	string	

2.3.130. v1.ImageStreamSpec

ImageStreamSpec represents options for ImageStreams.

Name	Description	Required	Schema	Default
dockerImageRepository	DockerImageRepository is optional, if specified this stream is backed by a Docker repository on this server	false	string	
tags	Tags map arbitrary string values to specific image locators	false	Section 2.3.227 , “v1.TagReference” array	

2.3.131. v1.ImageStreamStatus

ImageStreamStatus contains information about the state of this image stream.

Name	Description	Required	Schema	Default
dockerImageRepository	DockerImageRepository represents the effective location this stream may be accessed at. May be empty until the server determines where the repository is located	true	string	
tags	Tags are a historical record of images associated with each tag. The first entry in the TagEvent array is the currently tagged image.	false	Section 2.3.146 , “v1.NamedTagEventList” array	

2.3.132. v1.ImageStreamTag

ImageStreamTag represents an Image that is retrieved by tag name from an ImageStream.

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#types-kinds	false	string	
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#resources	false	string	
metadata	Standard object's metadata.	false	Section 2.3.158, "v1.ObjectMeta"	
tag	Tag is the spec tag associated with this image stream tag, and it may be null if only pushes have occurred to this image stream.	true	Section 2.3.227, "v1.TagReference"	

Name	Description	Required	Schema	Default
generation	Generation is the current generation of the tagged image - if tag is provided and this value is not equal to the tag generation, a user has requested an import that has not completed, or Conditions will be filled out indicating any error.	true	integer (int64)	
conditions	Conditions is an array of conditions that apply to the image stream tag.	false	Section 2.3.224, "v1.TagEventCondition" array	
image	Image associated with the ImageStream and tag.	true	Section 2.3.112, "v1.Image"	

2.3.133. v1.ImageStreamTagList

ImageStreamTagList is a list of ImageStreamTag objects.

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#types-kinds	false	string	

Name	Description	Required	Schema	Default
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#resources	false	string	
metadata	Standard object's metadata.	false	Section 2.3.9, "unversioned.ListMeta"	
items	Items is the list of image stream tags	true	Section 2.3.132, "v1.ImageStreamTag" array	

2.3.134. v1.JenkinsPipelineBuildStrategy

JenkinsPipelineBuildStrategy holds parameters specific to a Jenkins Pipeline build. This strategy is in tech preview.

Name	Description	Required	Schema	Default
------	-------------	----------	--------	---------

Name	Description	Required	Schema	Default
jenkinsfilePath	JenkinsfilePath is the optional path of the Jenkinsfile that will be used to configure the pipeline relative to the root of the context (contextDir). If both JenkinsfilePath & Jenkinsfile are both not specified, this defaults to Jenkinsfile in the root of the specified contextDir.	false	string	
jenkinsfile	Jenkinsfile defines the optional raw contents of a Jenkinsfile which defines a Jenkins pipeline build.	false	string	

2.3.135. v1.KeyToPath

Maps a string key to a path within a volume.

Name	Description	Required	Schema	Default
key	The key to project.	true	string	
path	The relative path of the file to map the key to. May not be an absolute path. May not contain the path element '..'. May not start with the string '..'.	true	string	

2.3.136. v1.Lifecycle

Lifecycle describes actions that the management system should take in response to container lifecycle events. For the PostStart and PreStop lifecycle handlers, management of the container blocks until the action is complete, unless the container process fails, in which case the handler is aborted.

Name	Description	Required	Schema	Default
postStart	PostStart is called immediately after a container is created. If the handler fails, the container is terminated and restarted according to its restart policy. Other management of the container blocks until the hook completes. More info: http://releases.k8s.io/release-1.3/docs/user-guide/container-environment.md#hook-details	false	Section 2.3.105, "v1.Handler"	

Name	Description	Required	Schema	Default
preStop	<p>PreStop is called immediately before a container is terminated. The container is terminated after the handler completes. The reason for termination is passed to the handler. Regardless of the outcome of the handler, the container is eventually terminated. Other management of the container blocks until the hook completes. More info: http://releases.k8s.io/release-1.3/docs/user-guide/container-environment.md#hook-details</p>	false	Section 2.3.105, "v1.Handler"	

2.3.137. v1.LifecycleHook

LifecycleHook defines a specific deployment lifecycle action. Only one type of action may be specified at any time.

Name	Description	Required	Schema	Default
failurePolicy	FailurePolicy specifies what action to take if the hook fails.	true	string	
execNewPod	ExecNewPod specifies the options for a lifecycle hook backed by a pod.	false	Section 2.3.89, "v1.ExecNewPodHook"	

Name	Description	Required	Schema	Default
tagImages	TagImages instructs the deployer to tag the current image referenced under a container onto an image stream tag.	false	Section 2.3.225, "v1.TagImageHook" array	

2.3.138. v1.LocalObjectReference

LocalObjectReference contains enough information to let you locate the referenced object inside the same namespace.

Name	Description	Required	Schema	Default
name	Name of the referent. More info: http://releases.k8s.io/release-1.3/docs/user-guide/identifiers.md#names	false	string	

2.3.139. v1.LocalResourceAccessReview

Local Resource Access Reviews are objects that allow you to determine which users and groups can perform a given action in a given namespace.

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#types-kinds	false	string	

Name	Description	Required	Schema	Default
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#resources	false	string	
namespace	Namespace is the namespace of the action being requested. Currently, there is no distinction between no namespace and all namespaces	true	string	
verb	Verb is one of: get, list, watch, create, update, delete	true	string	
resourceAPIGroup	Group is the API group of the resource Serialized as resourceAPIGroup to avoid confusion with the 'groups' field when inlined	true	string	

Name	Description	Required	Schema	Default
resourceAPIVersion	Version is the API version of the resource Serialized as resourceAPIVersion to avoid confusion with TypeMeta.apiVersion and ObjectMeta.resourceVersion when inlined	true	string	
resource	Resource is one of the existing resource types	true	string	
resourceName	ResourceName is the name of the resource being requested for a "get" or deleted for a "delete"	true	string	
content	Content is the actual content of the request for create and update	false	string	

2.3.140. v1.LocalSubjectAccessReview

Local Subject Access Reviews are objects that allow you to determine whether a given user or group can perform a particular action in a given namespace. Leaving **user** and **groups** empty allows you determine whether the identity making the request can perform the action.

Name	Description	Required	Schema	Default
------	-------------	----------	--------	---------

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#types-kinds	false	string	
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#resources	false	string	
namespace	Namespace is the namespace of the action being requested. Currently, there is no distinction between no namespace and all namespaces	true	string	
verb	Verb is one of: get, list, watch, create, update, delete	true	string	

Name	Description	Required	Schema	Default
resourceAPIGroup	Group is the API group of the resource Serialized as resourceAPIGroup to avoid confusion with the 'groups' field when inlined	true	string	
resourceAPIVersion	Version is the API version of the resource Serialized as resourceAPIVersion to avoid confusion with TypeMeta.apiVersion and ObjectMeta.resourceVersion when inlined	true	string	
resource	Resource is one of the existing resource types	true	string	
resourceName	ResourceName is the name of the resource being requested for a "get" or deleted for a "delete"	true	string	
content	Content is the actual content of the request for create and update	false	string	
user	User is optional. If both User and Groups are empty, the current authenticated user is used.	true	string	
groups	Groups is optional. Groups is the list of groups to which the User belongs.	true	string array	

Name	Description	Required	Schema	Default
scopes	Scopes to use for the evaluation. Empty means "use the unscoped (full) permissions of the user/groups". Nil for a self-SAR, means "use the scopes on this request". Nil for a regular SAR, means the same as empty.	true	string array	

2.3.141. v1.NFSVolumeSource

Represents an NFS mount that lasts the lifetime of a pod. NFS volumes do not support ownership management or SELinux relabeling.

Name	Description	Required	Schema	Default
server	Server is the hostname or IP address of the NFS server. More info: http://releases.k8s.io/release-1.3/docs/user-guide/volumes.md#nfs	true	string	
path	Path that is exported by the NFS server. More info: http://releases.k8s.io/release-1.3/docs/user-guide/volumes.md#nfs	true	string	

Name	Description	Required	Schema	Default
readOnly	ReadOnly here will force the NFS export to be mounted with read-only permissions. Defaults to false. More info: http://releases.k8s.io/release-1.3/docs/user-guide/volumes.md#nfs	false	boolean	

2.3.142. v1.NamedClusterRole

NamedClusterRole relates a name with a cluster role

Name	Description	Required	Schema	Default
name	Name is the name of the cluster role	true	string	
role	Role is the cluster role being named	true	Section 2.3.50, "v1.ClusterRole"	

2.3.143. v1.NamedClusterRoleBinding

NamedClusterRoleBinding relates a name with a cluster role binding

Name	Description	Required	Schema	Default
name	Name is the name of the cluster role binding	true	string	
roleBinding	RoleBinding is the cluster role binding being named	true	Section 2.3.51, "v1.ClusterRoleBinding"	

2.3.144. v1.NamedRole

NamedRole relates a Role with a name

Name	Description	Required	Schema	Default
name	Name is the name of the role	true	string	
role	Role is the role being named	true	Section 2.3.189, "v1.Role"	

2.3.145. v1.NamedRoleBinding

NamedRoleBinding relates a role binding with a name

Name	Description	Required	Schema	Default
name	Name is the name of the role binding	true	string	
roleBinding	RoleBinding is the role binding being named	true	Section 2.3.190, "v1.RoleBinding"	

2.3.146. v1.NamedTagEventList

NamedTagEventList relates a tag to its image history.

Name	Description	Required	Schema	Default
tag	Tag is the tag for which the history is recorded	true	string	
items	Standard object's metadata.	true	Section 2.3.223, "v1.TagEvent" array	
conditions	Conditions is an array of conditions that apply to the tag event list.	false	Section 2.3.224, "v1.TagEventCondition" array	

2.3.147. v1.NetNamespace

NetNamespace represents a segregated network namespace for an entire cluster. When a group of pods, or a project, or a group of projects get a NetNamespace assigned then the openshift-sdn's multitenant plugin ensures network layer isolation of traffic from other NetNamespaces.

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#types-kinds	false	string	
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#resources	false	string	
metadata	Standard object's metadata.	false	Section 2.3.158, "v1.ObjectMeta"	
netname	NetName is the name of the network namespace	true	string	

Name	Description	Required	Schema	Default
netid	NetID is the network identifier of the network namespace assigned to each overlay network packet	true	integer	

2.3.148. v1.NetNamespaceList

NetNamespaceList represents a list of NetNamespace objects. NetNamespace captures information about a segregated network namespace for an entire cluster. When a group of pods, or a project, or a group of projects get a NetNamespace assigned then the openshift-sdn's multitenant plugin ensures network layer isolation of traffic from other NetNamespaces.

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#types-kinds	false	string	

Name	Description	Required	Schema	Default
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#resources	false	string	
metadata	Standard object's metadata.	false	Section 2.3.9 , "unversioned.ListMeta"	
items	Items is the list of net namespaces	true	Section 2.3.147 , "v1.NetNamespace" array	

2.3.149. v1.OAuthAccessToken

OAuthAccessToken describes an OAuth access token

Name	Description	Required	Schema	Default
------	-------------	----------	--------	---------

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#types-kinds	false	string	
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#resources	false	string	
metadata	Standard object's metadata.	false	Section 2.3.158, "v1.ObjectMeta"	
clientName	ClientName references the client that created this token.	false	string	

Name	Description	Required	Schema	Default
expiresIn	ExpiresIn is the seconds from CreationTime before this token expires.	false	integer (int64)	
scopes	Scopes is an array of the requested scopes.	false	string array	
redirectURI	RedirectURI is the redirection associated with the token.	false	string	
userName	UserName is the user name associated with this token	false	string	
userID	UserUID is the unique UID associated with this token	false	string	
authorizeToken	AuthorizeToken contains the token that authorized this token	false	string	
refreshToken	RefreshToken is the value by which this token can be renewed. Can be blank.	false	string	

2.3.150. v1.OAuthAccessTokenList

OAuthAccessTokenList is a collection of OAuth access tokens

Name	Description	Required	Schema	Default
------	-------------	----------	--------	---------

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#types-kinds	false	string	
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#resources	false	string	
metadata	Standard object's metadata.	false	Section 2.3.9, "unversioned.ListMeta"	
items	Items is the list of OAuth access tokens	true	Section 2.3.149, "v1.OAuthAccessToken" array	

2.3.151. v1.OAuthAuthorizeToken

OAuthAuthorizeToken describes an OAuth authorization token

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#types-kinds	false	string	
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#resources	false	string	
metadata	Standard object's metadata.	false	Section 2.3.158, "v1.ObjectMeta"	
clientName	ClientName references the client that created this token.	false	string	
expiresIn	ExpiresIn is the seconds from CreationTime before this token expires.	false	integer (int64)	

Name	Description	Required	Schema	Default
scopes	Scopes is an array of the requested scopes.	false	string array	
redirectURI	RedirectURI is the redirection associated with the token.	false	string	
state	State data from request	false	string	
userName	UserName is the user name associated with this token	false	string	
userID	UserUID is the unique UID associated with this token. UserUID and UserName must both match for this token to be valid.	false	string	

2.3.152. v1.OAuthAuthorizeTokenList

OAuthAuthorizeTokenList is a collection of OAuth authorization tokens

Name	Description	Required	Schema	Default
------	-------------	----------	--------	---------

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#types-kinds	false	string	
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#resources	false	string	
metadata	Standard object's metadata.	false	Section 2.3.9, "unversioned.ListMeta"	
items	Items is the list of OAuth authorization tokens	true	Section 2.3.151, "v1.OAuthAuthorizeToken" array	

2.3.153. v1.OAuthClient

OAuthClient describes an OAuth client

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#types-kinds	false	string	
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#resources	false	string	
metadata	Standard object's metadata.	false	Section 2.3.158, "v1.ObjectMeta"	
secret	Secret is the unique secret associated with a client	false	string	

Name	Description	Required	Schema	Default
additionalSecrets	AdditionalSecrets holds other secrets that may be used to identify the client. This is useful for rotation and for service account token validation	false	string array	
respondWithChallenges	RespondWithChallenges indicates whether the client wants authentication needed responses made in the form of challenges instead of redirects	false	boolean	
redirectURIs	RedirectURIs is the valid redirection URIs associated with a client	false	string array	
grantMethod	GrantMethod determines how to handle grants for this client. If no method is provided, the cluster default grant handling method will be used. Valid grant handling methods are: <ul style="list-style-type: none"> - auto: always approves grant requests, useful for trusted clients - prompt: prompts the end user for approval of grant requests, useful for third-party clients - deny: always denies grant requests, useful for black-listed clients 	false	string	

Name	Description	Required	Schema	Default
scopeRestrictions	ScopeRestrictions describes which scopes this client can request. Each requested scope is checked against each restriction. If any restriction matches, then the scope is allowed. If no restriction matches, then the scope is denied.	false	Section 2.3.203, "v1.ScopeRestriction" array	

2.3.154. v1.OAuthClientAuthorization

OAuthClientAuthorization describes an authorization created by an OAuth client

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#types-kinds	false	string	

Name	Description	Required	Schema	Default
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#resources	false	string	
metadata	Standard object's metadata.	false	Section 2.3.158, "v1.ObjectMeta"	
clientName	ClientName references the client that created this authorization	false	string	
userName	UserName is the user name that authorized this client	false	string	
userID	UserUID is the unique UID associated with this authorization. UserUID and UserName must both match for this authorization to be valid.	false	string	
scopes	Scopes is an array of the granted scopes.	false	string array	

2.3.155. v1.OAuthClientAuthorizationList

OAuthClientAuthorizationList is a collection of OAuth client authorizations

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#types-kinds	false	string	
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#resources	false	string	
metadata	Standard object's metadata.	false	Section 2.3.9, "unversioned.ListMeta"	
items	Items is the list of OAuth client authorizations	true	Section 2.3.154, "v1.OAuthClientAuthorization" array	

2.3.156. v1.OAuthClientList

OAuthClientList is a collection of OAuth clients

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#types-kinds	false	string	
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#resources	false	string	
metadata	Standard object's metadata.	false	Section 2.3.9, "unversioned.ListMeta"	
items	Items is the list of OAuth clients	true	Section 2.3.153, "v1.OAuthClient" array	

2.3.157. v1.ObjectFieldSelector

ObjectFieldSelector selects an APIVersioned field of an object.

Name	Description	Required	Schema	Default
apiVersion	Version of the schema the FieldPath is written in terms of, defaults to "v1".	false	string	
fieldPath	Path of the field to select in the specified API version.	true	string	

2.3.158. v1.ObjectMeta

ObjectMeta is metadata that all persisted resources must have, which includes all objects users must create.

Name	Description	Required	Schema	Default
name	Name must be unique within a namespace. Is required when creating resources, although some resources may allow a client to request the generation of an appropriate name automatically. Name is primarily intended for creation idempotence and configuration definition. Cannot be updated. More info: http://releases.k8s.io/release-1.3/docs/user-guide/identifiers.md#names	false	string	
generateName	GenerateName is an optional prefix, used by the server, to generate a unique name ONLY IF the Name	false	string	

Name	Description	Required	Schema	Default
	<p>field has not been provided. If this field is used, the name returned to the client will be different than the name passed. This value will also be combined with a unique suffix. The provided value has the same validation rules as the Name field, and may be truncated by the length of the suffix required to make the value unique on the server.</p> <p>If this field is specified and the generated name exists, the server will NOT return a 409 - instead, it will either return 201 Created or 500 with Reason ServerTimeout indicating a unique name could not be found in the time allotted, and the client should retry (optionally after the time indicated in the Retry-After header).</p> <p>Applied only if Name is not specified. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#idempotency</p>			

Name	Description	Required	Schema	Default
namespace	<p>Namespace defines the space within each name must be unique. An empty namespace is equivalent to the "default" namespace, but "default" is the canonical representation. Not all objects are required to be scoped to a namespace - the value of this field for those objects will be empty.</p> <p>Must be a DNS_LABEL. Cannot be updated. More info: http://releases.k8s.io/release-1.3/docs/user-guide/namespaces.md</p>	false	string	
selfLink	<p>SelfLink is a URL representing this object. Populated by the system. Read-only.</p>	false	string	

Name	Description	Required	Schema	Default
uid	<p>UID is the unique in time and space value for this object. It is typically generated by the server on successful creation of a resource and is not allowed to change on PUT operations.</p> <p>Populated by the system. Read-only. More info: http://releases.k8s.io/release-1.3/docs/user-guide/identifiers.md#uids</p>	false	string	

Name	Description	Required	Schema	Default
resourceVersion	<p>An opaque value that represents the internal version of this object that can be used by clients to determine when objects have changed. May be used for optimistic concurrency, change detection, and the watch operation on a resource or set of resources. Clients must treat these values as opaque and passed unmodified back to the server. They may only be valid for a particular resource or set of resources.</p> <p>Populated by the system. Read-only. Value must be treated as opaque by clients and . More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#concurrency-control-and-consistency</p>	false	string	
generation	<p>A sequence number representing a specific generation of the desired state. Populated by the system. Read-only.</p>	false	integer (int64)	

Name	Description	Required	Schema	Default
creationTimestamp	<p>CreationTimestamp is a timestamp representing the server time when this object was created. It is not guaranteed to be set in happens-before order across separate operations. Clients may not set this value. It is represented in RFC3339 form and is in UTC.</p> <p>Populated by the system. Read-only. Null for lists. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#metadata</p>	false	string	
deletionTimestamp	<p>DeletionTimestamp is RFC 3339 date and time at which this resource will be deleted. This field is set by the server when a graceful deletion is requested by the user, and is not directly settable by a client. The resource will be deleted (no longer visible from resource lists, and not reachable by name) after the time in this field. Once set, this value may not be unset or be set further into the future, although it may be shortened</p>	false	string	

Name	Description	Required	Schema	Default
	<p>or the resource may be deleted prior to this time. For example, a user may request that a pod is deleted in 30 seconds. The Kubelet will react by sending a graceful termination signal to the containers in the pod. Once the resource is deleted in the API, the Kubelet will send a hard termination signal to the container. If not set, graceful deletion of the object has not been requested.</p> <p>Populated by the system when a graceful deletion is requested. Read-only. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#metadata</p>			
deletionGracePeriodSeconds	<p>Number of seconds allowed for this object to gracefully terminate before it will be removed from the system. Only set when deletionTimestamp is also set. May only be shortened. Read-only.</p>	false	integer (int64)	

Name	Description	Required	Schema	Default
labels	Map of string keys and values that can be used to organize and categorize (scope and select) objects. May match selectors of replication controllers and services. More info: http://releases.k8s.io/release-1.3/docs/user-guide/labels.md	false	object	
annotations	Annotations is an unstructured key value map stored with a resource that may be set by external tools to store and retrieve arbitrary metadata. They are not queryable and should be preserved when modifying objects. More info: http://releases.k8s.io/release-1.3/docs/user-guide/annotations.md	false	object	

Name	Description	Required	Schema	Default
ownerReferences	List of objects depended by this object. If ALL objects in the list have been deleted, this object will be garbage collected. If this object is managed by a controller, then an entry in this list will point to this controller, with the controller field set to true. There cannot be more than one managing controller.	false	Section 2.3.160, "v1.OwnerReference" array	
finalizers	Must be empty before the object is deleted from the registry. Each entry is an identifier for the responsible component that will remove the entry from the list. If the deletionTimestamp of the object is non-nil, entries in this list can only be removed.	false	string array	

2.3.159. v1.ObjectReference

ObjectReference contains enough information to let you inspect or modify the referred object.

Name	Description	Required	Schema	Default
kind	Kind of the referent. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#types-kinds	false	string	

Name	Description	Required	Schema	Default
namespace	Namespace of the referent. More info: http://releases.k8s.io/release-1.3/docs/user-guide/namespaces.md	false	string	
name	Name of the referent. More info: http://releases.k8s.io/release-1.3/docs/user-guide/identifiers.md#names	false	string	
uid	UID of the referent. More info: http://releases.k8s.io/release-1.3/docs/user-guide/identifiers.md#uids	false	string	
apiVersion	API version of the referent.	false	string	
resourceVersion	Specific resourceVersion to which this reference is made, if any. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#concurrency-control-and-consistency	false	string	

Name	Description	Required	Schema	Default
fieldPath	If referring to a piece of an object instead of an entire object, this string should contain a valid JSON/Go field access statement, such as <code>desiredState.manifest.containers[2]</code> . For example, if the object reference is to a container within a pod, this would take on a value like: <code>"spec.containers{name}"</code> (where "name" refers to the name of the container that triggered the event) or if no container name is specified <code>"spec.containers[2]"</code> (container with index 2 in this pod). This syntax is chosen only to have some well-defined way of referencing a part of an object.	false	string	

2.3.160. v1.OwnerReference

OwnerReference contains enough information to let you identify an owning object. Currently, an owning object must be in the same namespace, so there is no namespace field.

Name	Description	Required	Schema	Default
apiVersion	API version of the referent.	true	string	

Name	Description	Required	Schema	Default
kind	Kind of the referent. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#types-kinds	true	string	
name	Name of the referent. More info: http://releases.k8s.io/release-1.3/docs/user-guide/identifiers.md#names	true	string	
uid	UID of the referent. More info: http://releases.k8s.io/release-1.3/docs/user-guide/identifiers.md#uids	true	string	
controller	If true, this reference points to the managing controller.	false	boolean	

2.3.161. v1.Parameter

Parameter defines a name/value variable that is to be processed during the Template to Config transformation.

Name	Description	Required	Schema	Default
name	Name must be set and it can be referenced in Template Items using <code>\$(PARAMETER_NAME)</code> . Required.	true	string	

Name	Description	Required	Schema	Default
displayName	Optional: The name that will show in UI instead of parameter 'Name'	false	string	
description	Description of a parameter. Optional.	false	string	
value	Value holds the Parameter data. If specified, the generator will be ignored. The value replaces all occurrences of the Parameter <code>\${Name}</code> expression during the Template to Config transformation. Optional.	false	string	

Name	Description	Required	Schema	Default
generate	<p>generate specifies the generator to be used to generate random string from an input value specified by From field. The result string is stored into Value field. If empty, no generator is being used, leaving the result Value untouched. Optional.</p> <p>The only supported generator is "expression", which accepts a "from" value in the form of a simple regular expression containing the range expression "[a-zA-Z0-9]", and the length expression "a{length}".</p> <p>Examples:</p> <p>from</p>	value	false	string
	from	From is an input value for the generator. Optional.	false	string
	required	Optional: Indicates the parameter must have a value. Defaults to false.	false	boolean

2.3.162. v1.PersistentVolumeClaimVolumeSource

PersistentVolumeClaimVolumeSource references the user's PVC in the same namespace. This volume finds the bound PV and mounts that volume for the pod. A PersistentVolumeClaimVolumeSource is, essentially, a wrapper around another type of volume that is owned by someone else (the system).

Name	Description	Required	Schema	Default
claimName	ClaimName is the name of a PersistentVolumeClaim in the same namespace as the pod using this volume. More info: http://releases.k8s.io/release-1.3/docs/user-guide/persistent-volumes.md#persistentvolumeclaims	true	string	
readOnly	Will force the ReadOnly setting in VolumeMounts. Default false.	false	boolean	

2.3.163. v1.PodSecurityContext

PodSecurityContext holds pod-level security attributes and common container settings. Some fields are also present in container.securityContext. Field values of container.securityContext take precedence over field values of PodSecurityContext.

Name	Description	Required	Schema	Default
seLinuxOptions	The SELinux context to be applied to all containers. If unspecified, the container runtime will allocate a random SELinux context for each container. May also be set in SecurityContext. If set in both SecurityContext and PodSecurityContext, the value specified in SecurityContext takes precedence for that container.	false	Section 2.3.202, "v1.SELinuxOptions"	

Name	Description	Required	Schema	Default
runAsUser	The UID to run the entrypoint of the container process. Defaults to user specified in image metadata if unspecified. May also be set in SecurityContext. If set in both SecurityContext and PodSecurityContext, the value specified in SecurityContext takes precedence for that container.	false	integer (int64)	
runAsNonRoot	Indicates that the container must run as a non-root user. If true, the Kubelet will validate the image at runtime to ensure that it does not run as UID 0 (root) and fail to start the container if it does. If unset or false, no such validation will be performed. May also be set in SecurityContext. If set in both SecurityContext and PodSecurityContext, the value specified in SecurityContext takes precedence.	false	boolean	

Name	Description	Required	Schema	Default
supplementalGroups	A list of groups applied to the first process run in each container, in addition to the container's primary GID. If unspecified, no groups will be added to any container.	false	integer array	
fsGroup	A special supplemental group that applies to all containers in a pod. Some volume types allow the Kubelet to change the ownership of that volume to be owned by the pod: 1. The owning GID will be the FSGroup 2. The setgid bit is set (new files created in the volume will be owned by FSGroup) 3. The permission bits are OR'd with rw-rw	false	integer (int64)	

2.3.164. v1.PodSpec

PodSpec is a description of a pod.

Name	Description	Required	Schema	Default
------	-------------	----------	--------	---------

Name	Description	Required	Schema	Default
volumes	List of volumes that can be mounted by containers belonging to the pod. More info: http://releases.k8s.io/release-1.3/docs/user-guide/volumes.md	false	Section 2.3.233 , “v1.Volume” array	
containers	List of containers belonging to the pod. Containers cannot currently be added or removed. There must be at least one container in a Pod. Cannot be updated. More info: http://releases.k8s.io/release-1.3/docs/user-guide/containers.md	true	Section 2.3.57 , “v1.Container” array	
restartPolicy	Restart policy for all containers within the pod. One of Always, OnFailure, Never. Default to Always. More info: http://releases.k8s.io/release-1.3/docs/user-guide/pod-states.md#restartpolicy	false	string	

Name	Description	Required	Schema	Default
terminationGracePeriodSeconds	<p>Optional duration in seconds the pod needs to terminate gracefully. May be decreased in delete request. Value must be non-negative integer. The value zero indicates delete immediately. If this value is nil, the default grace period will be used instead. The grace period is the duration in seconds after the processes running in the pod are sent a termination signal and the time when the processes are forcibly halted with a kill signal. Set this value longer than the expected cleanup time for your process. Defaults to 30 seconds.</p>	false	integer (int64)	
activeDeadlineSeconds	<p>Optional duration in seconds the pod may be active on the node relative to StartTime before the system will actively try to mark it failed and kill associated containers. Value must be a positive integer.</p>	false	integer (int64)	

Name	Description	Required	Schema	Default
dnsPolicy	Set DNS policy for containers within the pod. One of 'ClusterFirst' or 'Default'. Defaults to "ClusterFirst".	false	string	
nodeSelector	NodeSelector is a selector which must be true for the pod to fit on a node. Selector which must match a node's labels for the pod to be scheduled on that node. More info: http://releases.k8s.io/release-1.3/docs/user-guide/node-selection/README.md	false	object	
host	A request to schedule this pod onto a specific node. Deprecated: Use nodeName instead.	false	string	
serviceAccountName	ServiceAccountName is the name of the ServiceAccount to use to run this pod. More info: http://releases.k8s.io/release-1.3/docs/design/service_accounts.md	false	string	
serviceAccount	DeprecatedServiceAccount is a deprecated alias for ServiceAccountName. Deprecated: Use serviceAccountName instead.	false	string	

Name	Description	Required	Schema	Default
nodeName	nodeName is a request to schedule this pod onto a specific node. If it is non-empty, the scheduler simply schedules this pod onto that node, assuming that it fits resource requirements.	false	string	
hostNetwork	Host networking requested for this pod. Use the host's network namespace. If this option is set, the ports that will be used must be specified. Default to false.	false	boolean	
hostPID	Use the host's pid namespace. Optional: Default to false.	false	boolean	
hostIPC	Use the host's ipc namespace. Optional: Default to false.	false	boolean	
securityContext	SecurityContext holds pod-level security attributes and common container settings. Optional: Defaults to empty. See type description for default values of each field.	false	Section 2.3.163, "v1.PodSecurityContext"	

Name	Description	Required	Schema	Default
imagePullSecrets	ImagePullSecrets is an optional list of references to secrets in the same namespace to use for pulling any of the images used by this PodSpec. If specified, these secrets will be passed to individual puller implementations for them to use. For example, in the case of docker, only DockerConfig type secrets are honored. More info: http://releases.k8s.io/release-1.3/docs/user-guide/images.md#specifying-imagepullsecrets-on-a-pod	false	Section 2.3.138, "v1.LocalObjectReference" array	
hostname	Specifies the hostname of the Pod. If not specified, the pod's hostname will be set to a system-defined value.	false	string	
subdomain	If specified, the fully qualified Pod hostname will be " <code><hostname>.<subdomain>.<pod namespace>.svc.<cluster domain></code> ". If not specified, the pod will not have a domainname at all.	false	string	

2.3.165. v1.PodTemplateSpec

PodTemplateSpec describes the data a pod should have when created from a template

Name	Description	Required	Schema	Default
metadata	Standard object's metadata. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#metadata	false	Section 2.3.158, "v1.ObjectMeta"	
spec	Specification of the desired behavior of the pod. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#spec-and-status	false	Section 2.3.164, "v1.PodSpec"	

2.3.166. v1.Policy

Policy is a object that holds all the Roles for a particular namespace. There is at most one Policy document per namespace.

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#types-kinds	false	string	

Name	Description	Required	Schema	Default
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#resources	false	string	
metadata	Standard object's metadata.	false	Section 2.3.158, "v1.ObjectMeta"	
lastModified	LastModified is the last time that any part of the Policy was created, updated, or deleted	true	string	
roles	Roles holds all the Roles held by this Policy, mapped by Role.Name	true	Section 2.3.144, "v1.NamedRole" array	

2.3.167. v1.PolicyBinding

PolicyBinding is a object that holds all the RoleBindings for a particular namespace. There is one PolicyBinding document per referenced Policy namespace

Name	Description	Required	Schema	Default
------	-------------	----------	--------	---------

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#types-kinds	false	string	
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#resources	false	string	
metadata	Standard object's metadata.	false	Section 2.3.158, "v1.ObjectMeta"	
lastModified	LastModified is the last time that any part of the PolicyBinding was created, updated, or deleted	true	string	

Name	Description	Required	Schema	Default
policyRef	PolicyRef is a reference to the Policy that contains all the Roles that this PolicyBinding's RoleBindings may reference	true	Section 2.3.159, "v1.ObjectReference"	
roleBindings	RoleBindings holds all the RoleBindings held by this PolicyBinding, mapped by RoleBinding.Name	true	Section 2.3.145, "v1.NamedRoleBinding" array	

2.3.168. v1.PolicyBindingList

PolicyBindingList is a collection of PolicyBindings

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#types-kinds	false	string	

Name	Description	Required	Schema	Default
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#resources	false	string	
metadata	Standard object's metadata.	false	Section 2.3.9, "unversioned.ListMeta"	
items	Items is a list of PolicyBindings	true	Section 2.3.167, "v1.PolicyBinding" array	

2.3.169. v1.PolicyList

PolicyList is a collection of Policies

Name	Description	Required	Schema	Default
------	-------------	----------	--------	---------

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#types-kinds	false	string	
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#resources	false	string	
metadata	Standard object's metadata.	false	Section 2.3.9, "unversioned.ListMeta"	
items	Items is a list of Policies	true	Section 2.3.166, "v1.Policy" array	

2.3.170. v1.PolicyRule

PolicyRule holds information that describes a policy rule, but does not contain information about who the rule applies to or which namespace the rule applies to.

Name	Description	Required	Schema	Default
verbs	Verbs is a list of Verbs that apply to ALL the ResourceKinds and AttributeRestrictions contained in this rule. VerbAll represents all kinds.	true	string array	
attributeRestrictions	AttributeRestrictions will vary depending on what the Authorizer/AuthorizationAttributeBuilder pair supports. If the Authorizer does not recognize how to handle the AttributeRestrictions, the Authorizer should report an error.	false	string	
apiGroups	APIGroups is the name of the APIGroup that contains the resources. If this field is empty, then both kubernetes and origin API groups are assumed. That means that if an action is requested against one of the enumerated resources in either the kubernetes or the origin API group, the request will be allowed	true	string array	

Name	Description	Required	Schema	Default
resources	Resources is a list of resources this rule applies to. ResourceAll represents all resources.	true	string array	
resourceNames	ResourceNames is an optional white list of names that the rule applies to. An empty set means that everything is allowed.	false	string array	
nonResourceURLs	NonResourceURLsSlice is a set of partial urls that a user should have access to. *s are allowed, but only as the full, final step in the path This name is intentionally different than the internal type so that the DefaultConvert works nicely and because the ordering may be different.	false	string array	

2.3.171. v1.Preconditions

Preconditions must be fulfilled before an operation (update, delete, etc.) is carried out.

Name	Description	Required	Schema	Default
uid	Specifies the target UID.	false	Section 2.3.4, "types.UID"	

2.3.172. v1.Probe

Probe describes a health check to be performed against a container to determine whether it is alive or ready to receive traffic.

Name	Description	Required	Schema	Default
exec	One and only one of the following should be specified. Exec specifies the action to take.	false	Section 2.3.88, "v1.ExecAction"	
httpGet	HTTPGet specifies the http request to perform.	false	Section 2.3.103, "v1.HTTPGetAction"	
tcpSocket	TCP socket specifies an action involving a TCP port. TCP hooks not yet supported	false	Section 2.3.221, "v1.TCPsocketAction"	
initialDelaySeconds	Number of seconds after the container has started before liveness probes are initiated. More info: http://releases.k8s.io/release-1.3/docs/user-guide/pod-states.md#container-probes	false	integer (int32)	
timeoutSeconds	Number of seconds after which the probe times out. Defaults to 1 second. Minimum value is 1. More info: http://releases.k8s.io/release-1.3/docs/user-guide/pod-states.md#container-probes	false	integer (int32)	
periodSeconds	How often (in seconds) to perform the probe. Default to 10 seconds. Minimum value is 1.	false	integer (int32)	

Name	Description	Required	Schema	Default
successThreshold	Minimum consecutive successes for the probe to be considered successful after having failed. Defaults to 1. Must be 1 for liveness. Minimum value is 1.	false	integer (int32)	
failureThreshold	Minimum consecutive failures for the probe to be considered failed after having succeeded. Defaults to 3. Minimum value is 1.	false	integer (int32)	

2.3.173. v1.Project

Projects are the unit of isolation and collaboration in OpenShift. A project has one or more members, a quota on the resources that the project may consume, and the security controls on the resources in the project. Within a project, members may have different roles - project administrators can set membership, editors can create and manage the resources, and viewers can see but not access running containers. In a normal cluster project administrators are not able to alter their quotas - that is restricted to cluster administrators.

Name	Description	Required	Schema	Default
------	-------------	----------	--------	---------

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#types-kinds	false	string	
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#resources	false	string	
metadata	Standard object's metadata.	false	Section 2.3.158, "v1.ObjectMeta"	
spec	Spec defines the behavior of the Namespace.	false	Section 2.3.176, "v1.ProjectSpec"	
status	Status describes the current status of a Namespace	false	Section 2.3.177, "v1.ProjectStatus"	

2.3.174. v1.ProjectList

ProjectList is a list of Project objects.

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#types-kinds	false	string	
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#resources	false	string	
metadata	Standard object's metadata.	false	Section 2.3.9, "unversioned.ListMeta"	
items	Items is the list of projects	true	Section 2.3.173, "v1.Project" array	

2.3.175. v1.ProjectRequest

ProjectRequest is the set of options necessary to fully qualify a project request

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#types-kinds	false	string	
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#resources	true	string	
metadata	Standard object's metadata.	subfield name	Section 2.3.158, "v1.ObjectMeta"	
displayName	DisplayName is the display name to apply to a project	false	string	
description	Description is the description to apply to a project	false	string	

2.3.176. v1.ProjectSpec

ProjectSpec describes the attributes on a Project

Name	Description	Required	Schema	Default
finalizers	Finalizers is an opaque list of values that must be empty to permanently remove object from storage	false	Section 2.3.91 , "v1.FinalizerName" array	

2.3.177. v1.ProjectStatus

ProjectStatus is information about the current status of a Project

Name	Description	Required	Schema	Default
phase	Phase is the current lifecycle phase of the project	false	string	

2.3.178. v1.RBDVolumeSource

Represents a Ceph Rados Block Device mount that lasts the lifetime of a pod. Ceph RBD volumes support ownership management and SELinux relabeling.

Name	Description	Required	Schema	Default
monitors	A collection of Ceph monitors. More info: http://releases.k8s.io/release-1.3/examples/rbd/README.md#how-to-use-it	true	string array	
image	The rados image name. More info: http://releases.k8s.io/release-1.3/examples/rbd/README.md#how-to-use-it	true	string	

Name	Description	Required	Schema	Default
fsType	Filesystem type of the volume that you want to mount. Tip: Ensure that the filesystem type is supported by the host operating system. Examples: "ext4", "xfs", "ntfs". Implicitly inferred to be "ext4" if unspecified. More info: http://releases.k8s.io/release-1.3/docs/user-guide/volumes.md#rbd	false	string	
pool	The rados pool name. Default is rbd. More info: http://releases.k8s.io/release-1.3/examples/rbd/README.md#how-to-use-it .	false	string	
user	The rados user name. Default is admin. More info: http://releases.k8s.io/release-1.3/examples/rbd/README.md#how-to-use-it	false	string	
keyring	Keyring is the path to key ring for RBDUser. Default is /etc/ceph/keyring. More info: http://releases.k8s.io/release-1.3/examples/rbd/README.md#how-to-use-it	false	string	

Name	Description	Required	Schema	Default
secretRef	SecretRef is name of the authentication secret for RBDUser. If provided overrides keyring. Default is nil. More info: http://releases.k8s.io/release-1.3/examples/rbd/README.md#how-to-use-it	false	Section 2.3.138, "v1.LocalObjectReference"	
readOnly	ReadOnly here will force the ReadOnly setting in VolumeMounts. Defaults to false. More info: http://releases.k8s.io/release-1.3/examples/rbd/README.md#how-to-use-it	false	boolean	

2.3.179. v1.RecreateDeploymentStrategyParams

RecreateDeploymentStrategyParams are the input to the Recreate deployment strategy.

Name	Description	Required	Schema	Default
timeoutSeconds	TimeoutSeconds is the time to wait for updates before giving up. If the value is nil, a default will be used.	false	integer (int64)	
pre	Pre is a lifecycle hook which is executed before the strategy manipulates the deployment. All LifecycleHookFailurePolicy values are supported.	false	Section 2.3.137, "v1.LifecycleHook"	

Name	Description	Required	Schema	Default
mid	Mid is a lifecycle hook which is executed while the deployment is scaled down to zero before the first new pod is created. All LifecycleHookFailurePolicy values are supported.	false	Section 2.3.137, "v1.LifecycleHook"	
post	Post is a lifecycle hook which is executed after the strategy has finished all deployment logic. All LifecycleHookFailurePolicy values are supported.	false	Section 2.3.137, "v1.LifecycleHook"	

2.3.180. v1.RepositoryImportSpec

RepositoryImportSpec describes a request to import images from a Docker image repository.

Name	Description	Required	Schema	Default
from	From is the source for the image repository to import; only kind DockerImage and a name of a Docker image repository is allowed	true	Section 2.3.159, "v1.ObjectReference"	
importPolicy	ImportPolicy is the policy controlling how the image is imported	false	Section 2.3.226, "v1.TagImportPolicy"	
includeManifest	IncludeManifest determines if the manifest for each image is returned in the response	false	boolean	

2.3.181. v1.RepositoryImportStatus

RepositoryImportStatus describes the result of an image repository import

Name	Description	Required	Schema	Default
status	Status reflects whether any failure occurred during import	false	Section 2.3.11, “unversioned.Status”	
images	Images is a list of images successfully retrieved by the import of the repository.	false	Section 2.3.117, “v1.ImageImportStatus” array	
additionalTags	AdditionalTags are tags that exist in the repository but were not imported because a maximum limit of automatic imports was applied.	false	string array	

2.3.182. v1.ResourceAccessReview

ResourceAccessReview is a means to request a list of which users and groups are authorized to perform the action specified by spec

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#types-kinds	false	string	

Name	Description	Required	Schema	Default
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#resources	false	string	
namespace	Namespace is the namespace of the action being requested. Currently, there is no distinction between no namespace and all namespaces	true	string	
verb	Verb is one of: get, list, watch, create, update, delete	true	string	
resourceAPIGroup	Group is the API group of the resource Serialized as resourceAPIGroup to avoid confusion with the 'groups' field when inlined	true	string	

Name	Description	Required	Schema	Default
resourceAPIVersion	Version is the API version of the resource Serialized as resourceAPIVersion to avoid confusion with TypeMeta.apiVersion and ObjectMeta.resourceVersion when inlined	true	string	
resource	Resource is one of the existing resource types	true	string	
resourceName	ResourceName is the name of the resource being requested for a "get" or deleted for a "delete"	true	string	
content	Content is the actual content of the request for create and update	false	string	

2.3.183. v1.ResourceFieldSelector

ResourceFieldSelector represents container resources (cpu, memory) and their output format

Name	Description	Required	Schema	Default
containerName	Container name: required for volumes, optional for env vars	false	string	
resource	Required: resource to select	true	string	
divisor	Specifies the output format of the exposed resources, defaults to "1"	false	string	

2.3.184. v1.ResourceQuotaScope

2.3.185. v1.ResourceQuotaSpec

ResourceQuotaSpec defines the desired hard limits to enforce for Quota.

Name	Description	Required	Schema	Default
hard	Hard is the set of desired hard limits for each named resource. More info: http://releases.k8s.io/release-1.3/docs/design/admission_control_resource_quota.md#admissioncontrol-plugin-resourcequota	false	object	
scopes	A collection of filters that must match each object tracked by a quota. If not specified, the quota matches all objects.	false	Section 2.3.184, "v1.ResourceQuotaScope" array	

2.3.186. v1.ResourceQuotaStatus

ResourceQuotaStatus defines the enforced hard limits and observed use.

Name	Description	Required	Schema	Default
hard	Hard is the set of enforced hard limits for each named resource. More info: http://releases.k8s.io/release-1.3/docs/design/admission_control_resource_quota.md#admissioncontrol-plugin-resourcequota	false	object	

Name	Description	Required	Schema	Default
used	Used is the current observed total usage of the resource in the namespace.	false	object	

2.3.187. v1.ResourceQuotaStatusByNamespace

ResourceQuotaStatusByNamespace gives status for a particular project

Name	Description	Required	Schema	Default
namespace	Namespace the project this status applies to	true	string	
status	Status indicates how many resources have been consumed by this project	true	Section 2.3.186, "v1.ResourceQuotaStatus"	

2.3.188. v1.ResourceRequirements

ResourceRequirements describes the compute resource requirements.

Name	Description	Required	Schema	Default
limits	Limits describes the maximum amount of compute resources allowed. More info: http://releases.k8s.io/release-1.3/docs/design/resources.md#resource-specifications	false	object	

Name	Description	Required	Schema	Default
requests	Requests describes the minimum amount of compute resources required. If Requests is omitted for a container, it defaults to Limits if that is explicitly specified, otherwise to an implementation-defined value. More info: http://releases.k8s.io/release-1.3/docs/design/resources.md#resource-specifications	false	object	

2.3.189. v1.Role

Role is a logical grouping of PolicyRules that can be referenced as a unit by RoleBindings.

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#types-kinds	false	string	

Name	Description	Required	Schema	Default
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#resources	false	string	
metadata	Standard object's metadata.	false	Section 2.3.158 , "v1.ObjectMeta"	
rules	Rules holds all the PolicyRules for this Role	true	Section 2.3.170 , "v1.PolicyRule" array	

2.3.190. v1.RoleBinding

RoleBinding references a Role, but not contain it. It can reference any Role in the same namespace or in the global namespace. It adds who information via Users and Groups and namespace information by which namespace it exists in. RoleBindings in a given namespace only have effect in that namespace (excepting the master namespace which has power in all namespaces).

Name	Description	Required	Schema	Default
------	-------------	----------	--------	---------

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#types-kinds	false	string	
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#resources	false	string	
metadata	Standard object's metadata.	false	Section 2.3.158, "v1.ObjectMeta"	
userNames	UserNames holds all the usernames directly bound to the role	true	string array	
groupNames	GroupNames holds all the groups directly bound to the role	true	string array	

Name	Description	Required	Schema	Default
subjects	Subjects hold object references to authorize with this rule	true	Section 2.3.159, "v1.ObjectReference" array	
roleRef	RoleRef can only reference the current namespace and the global namespace. If the RoleRef cannot be resolved, the Authorizer must return an error. Since Policy is a singleton, this is sufficient knowledge to locate a role	true	Section 2.3.159, "v1.ObjectReference"	

2.3.191. v1.RoleBindingList

RoleBindingList is a collection of RoleBindings

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#types-kinds	false	string	

Name	Description	Required	Schema	Default
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#resources	false	string	
metadata	Standard object's metadata.	false	Section 2.3.9, "unversioned.ListMeta"	
items	Items is a list of RoleBindings	true	Section 2.3.190, "v1.RoleBinding" array	

2.3.192. v1.RoleList

RoleList is a collection of Roles

Name	Description	Required	Schema	Default
------	-------------	----------	--------	---------

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#types-kinds	false	string	
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#resources	false	string	
metadata	Standard object's metadata.	false	Section 2.3.9, "unversioned.ListMeta"	
items	Items is a list of Roles	true	Section 2.3.189, "v1.Role" array	

2.3.193. v1.RollingDeploymentStrategyParams

RollingDeploymentStrategyParams are the input to the Rolling deployment strategy.

Name	Description	Required	Schema	Default
updatePeriodSeconds	UpdatePeriodSeconds is the time to wait between individual pod updates. If the value is nil, a default will be used.	false	integer (int64)	
intervalSeconds	IntervalSeconds is the time to wait between polling deployment status after update. If the value is nil, a default will be used.	false	integer (int64)	
timeoutSeconds	TimeoutSeconds is the time to wait for updates before giving up. If the value is nil, a default will be used.	false	integer (int64)	

Name	Description	Required	Schema	Default
maxUnavailable	<p>MaxUnavailable is the maximum number of pods that can be unavailable during the update. Value can be an absolute number (ex: 5) or a percentage of total pods at the start of update (ex: 10%). Absolute number is calculated from percentage by rounding up.</p> <p>This cannot be 0 if MaxSurge is 0. By default, 25% is used.</p> <p>Example: when this is set to 30%, the old RC can be scaled down by 30% immediately when the rolling update starts. Once new pods are ready, old RC can be scaled down further, followed by scaling up the new RC, ensuring that at least 70% of original number of pods are available at all times during the update.</p>	false	string	

Name	Description	Required	Schema	Default
maxSurge	<p>MaxSurge is the maximum number of pods that can be scheduled above the original number of pods. Value can be an absolute number (ex: 5) or a percentage of total pods at the start of the update (ex: 10%). Absolute number is calculated from percentage by rounding up.</p> <p>This cannot be 0 if MaxUnavailable is 0. By default, 25% is used.</p> <p>Example: when this is set to 30%, the new RC can be scaled up by 30% immediately when the rolling update starts. Once old pods have been killed, new RC can be scaled up further, ensuring that total number of pods running at any time during the update is atmost 130% of original pods.</p>	false	string	

Name	Description	Required	Schema	Default
updatePercent	UpdatePercent is the percentage of replicas to scale up or down each interval. If nil, one replica will be scaled up and down each interval. If negative, the scale order will be down/up instead of up/down. DEPRECATED: Use MaxUnavailable/MaxSurge instead.	false	integer (int32)	
pre	Pre is a lifecycle hook which is executed before the deployment process begins. All LifecycleHookFailurePolicy values are supported.	false	Section 2.3.137, "v1.LifecycleHook"	
post	Post is a lifecycle hook which is executed after the strategy has finished all deployment logic. The LifecycleHookFailurePolicyAbort policy is NOT supported.	false	Section 2.3.137, "v1.LifecycleHook"	

2.3.194. v1.Route

A route allows developers to expose services through an HTTP(S) aware load balancing and proxy layer via a public DNS entry. The route may further specify TLS options and a certificate, or specify a public CNAME that the router should also accept for HTTP and HTTPS traffic. An administrator typically configures their router to be visible outside the cluster firewall, and may also add additional security, caching, or traffic controls on the service content. Routers usually talk directly to the service endpoints.

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#types-kinds	false	string	
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#resources	false	string	
metadata	Standard object's metadata.	false	Section 2.3.158, "v1.ObjectMeta"	
spec	Spec is the desired state of the route	true	Section 2.3.199, "v1.RouteSpec"	
status	Status is the current state of the route	true	Section 2.3.200, "v1.RouteStatus"	

2.3.195. v1.RouteIngress

RouteIngress holds information about the places where a route is exposed

Name	Description	Required	Schema	Default
host	Host is the host string under which the route is exposed; this value is required	false	string	
routerName	Name is a name chosen by the router to identify itself; this value is required	false	string	
conditions	Conditions is the state of the route, may be empty.	false	Section 2.3.196, "v1.RouteIngressCondition" array	

2.3.196. v1.RouteIngressCondition

RouteIngressCondition contains details for the current condition of this pod.

Name	Description	Required	Schema	Default
type	Type is the type of the condition. Currently only Ready.	true	string	
status	Status is the status of the condition. Can be True, False, Unknown.	true	string	
reason	(brief) reason for the condition's last transition, and is usually a machine and human readable constant	false	string	
message	Human readable message indicating details about last transition.	false	string	

Name	Description	Required	Schema	Default
lastTransitionTime	RFC 3339 date and time when this condition last transitioned	false	string	

2.3.197. v1.RouteList

RouteList is a collection of Routes.

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#types-kinds	false	string	
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#resources	false	string	

Name	Description	Required	Schema	Default
metadata	Standard object's metadata.	false	Section 2.3.9, "unversioned.ListMeta"	
items	Items is a list of routes	true	Section 2.3.194, "v1.Route" array	

2.3.198. v1.RoutePort

RoutePort defines a port mapping from a router to an endpoint in the service endpoints.

Name	Description	Required	Schema	Default
targetPort	The target port on pods selected by the service this route points to. If this is a string, it will be looked up as a named port in the target endpoints port list. Required	true	string	

2.3.199. v1.RouteSpec

RouteSpec describes the route the user wishes to exist.

Name	Description	Required	Schema	Default
host	Host is an alias/DNS that points to the service. Optional Must follow DNS952 subdomain conventions.	true	string	
path	Path that the router watches for, to route traffic for to the service. Optional	false	string	

Name	Description	Required	Schema	Default
to	To is an object the route points to. Only the Service kind is allowed, and it will be defaulted to Service.	true	Section 2.3.201, "v1.RouteTargetReference"	
alternateBackends	AlternateBackends is an extension of the 'to' field. If more than one service needs to be pointed to, then use this field. Use the weight field in RouteTargetReference object to specify relative preference	false	Section 2.3.201, "v1.RouteTargetReference" array	
port	If specified, the port to be used by the router. Most routers will use all endpoints exposed by the service by default - set this value to instruct routers which port to use.	false	Section 2.3.198, "v1.RoutePort"	
tls	TLS provides the ability to configure certificates and termination for the route	false	Section 2.3.222, "v1.TLSConfig"	

2.3.200. v1.RouteStatus

RouteStatus provides relevant info about the status of a route, including which routers acknowledge it.

Name	Description	Required	Schema	Default
------	-------------	----------	--------	---------

Name	Description	Required	Schema	Default
ingress	Ingress describes the places where the route may be exposed. The list of ingress points may contain duplicate Host or RouterName values. Routes are considered live once they are Ready	true	Section 2.3.195, "v1.RouteIngress" array	

2.3.201. v1.RouteTargetReference

RouteTargetReference specifies the target that resolve into endpoints. Only the 'Service' kind is allowed. Use 'weight' field to emphasize one over others.

Name	Description	Required	Schema	Default
kind	The kind of target that the route is referring to. Currently, only 'Service' is allowed	true	string	
name	Name of the service/target that is being referred to. e.g. name of the service	true	string	
weight	Weight as an integer between 1 and 256 that specifies the target's relative weight against other target reference objects	true	integer (int32)	

2.3.202. v1.SELinuxOptions

SELinuxOptions are the labels to be applied to the container

Name	Description	Required	Schema	Default
user	User is a SELinux user label that applies to the container.	false	string	
role	Role is a SELinux role label that applies to the container.	false	string	
type	Type is a SELinux type label that applies to the container.	false	string	
level	Level is SELinux level label that applies to the container.	false	string	

2.3.203. v1.ScopeRestriction

ScopeRestriction describe one restriction on scopes. Exactly one option must be non-nil.

Name	Description	Required	Schema	Default
literals	ExactValues means the scope has to match a particular set of strings exactly	false	string array	
clusterRole	ClusterRole describes a set of restrictions for cluster role scoping.	false	Section 2.3.54, "v1.ClusterRoleScopeRestriction"	

2.3.204. v1.Secret

Secret holds secret data of a certain type. The total bytes of the values in the Data field must be less than MaxSecretSize bytes.

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#types-kinds	false	string	
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#resources	false	string	
metadata	Standard object's metadata. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#metadata	false	Section 2.3.158, "v1.ObjectMeta"	

Name	Description	Required	Schema	Default
data	Data contains the secret data. Each key must be a valid DNS_SUBDOMAIN or leading dot followed by valid DNS_SUBDOMAIN. The serialized form of the secret data is a base64 encoded string, representing the arbitrary (possibly non-string) data value here. Described in https://tools.ietf.org/html/rfc4648#section-4	false	object	
stringData	stringData allows specifying non-binary secret data in string form. It is provided as a write-only convenience method. All keys and values are merged into the data field on write, overwriting any existing values. It is never output when reading from the API.	false	object	
type	Used to facilitate programmatic handling of secret data.	false	string	

2.3.205. v1.SecretBuildSource

SecretBuildSource describes a secret and its destination directory that will be used only at the build time. The content of the secret referenced here will be copied into the destination directory instead of mounting.

Name	Description	Required	Schema	Default
secret	secret is a reference to an existing secret that you want to use in your build.	true	Section 2.3.138, "v1.LocalObjectReference"	
destinationDir	destinationDir is the directory where the files from the secret should be available for the build time. For the Source build strategy, these will be injected into a container where the assemble script runs. Later, when the script finishes, all files injected will be truncated to zero length. For the Docker build strategy, these will be copied into the build directory, where the Dockerfile is located, so users can ADD or COPY them during docker build.	false	string	

2.3.206. v1.SecretKeySelector

SecretKeySelector selects a key of a Secret.

Name	Description	Required	Schema	Default
name	Name of the referent. More info: http://releases.k8s.io/release-1.3/docs/user-guide/identifiers.md#names	false	string	

Name	Description	Required	Schema	Default
key	The key of the secret to select from. Must be a valid secret key.	true	string	

2.3.207. v1.SecretList

SecretList is a list of Secret.

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#types-kinds	false	string	
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#resources	false	string	

Name	Description	Required	Schema	Default
metadata	Standard list metadata. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#types-kinds	false	Section 2.3.9 , “unversioned.ListMeta”	
items	Items is a list of secret objects. More info: http://releases.k8s.io/release-1.3/docs/user-guide/secrets.md	true	Section 2.3.204 , “v1.Secret” array	

2.3.208. v1.SecretSpec

A SecretSpec specifies a secret and its corresponding mount point for a custom builder. The specified secret must be assigned to the service account that will run the build.

Name	Description	Required	Schema	Default
secretSource	secretSource is a reference to the secret	true	Section 2.3.138 , “v1.LocalObjectReference”	
mountPath	mountPath is the path at which to mount the secret	true	string	

2.3.209. v1.SecretVolumeSource

Adapts a Secret into a volume.

The contents of the target Secret’s Data field will be presented in a volume as files using the keys in the Data field as the file names. Secret volumes support ownership management and SELinux relabeling.

Name	Description	Required	Schema	Default
------	-------------	----------	--------	---------

Name	Description	Required	Schema	Default
secretName	Name of the secret in the pod's namespace to use. More info: http://releases.k8s.io/release-1.3/docs/user-guide/volumes.md#secrets	false	string	
items	If unspecified, each key-value pair in the Data field of the referenced Secret will be projected into the volume as a file whose name is the key and content is the value. If specified, the listed keys will be projected into the specified paths, and unlisted keys will not be present. If a key is specified which is not present in the Secret, the volume setup will error. Paths must be relative and may not contain the '..' path or start with '..'	false	Section 2.3.135, "v1.KeyToPath" array	

2.3.210. v1.SecurityContext

SecurityContext holds security configuration that will be applied to a container. Some fields are present in both SecurityContext and PodSecurityContext. When both are set, the values in SecurityContext take precedence.

Name	Description	Required	Schema	Default
------	-------------	----------	--------	---------

Name	Description	Required	Schema	Default
capabilities	The capabilities to add/drop when running containers. Defaults to the default set of capabilities granted by the container runtime.	false	Section 2.3.35, "v1.Capabilities"	
privileged	Run container in privileged mode. Processes in privileged containers are essentially equivalent to root on the host. Defaults to false.	false	boolean	
seLinuxOptions	The SELinux context to be applied to the container. If unspecified, the container runtime will allocate a random SELinux context for each container. May also be set in PodSecurityContext. If set in both SecurityContext and PodSecurityContext, the value specified in SecurityContext takes precedence.	false	Section 2.3.202, "v1.SELinuxOptions"	

Name	Description	Required	Schema	Default
runAsUser	The UID to run the entrypoint of the container process. Defaults to user specified in image metadata if unspecified. May also be set in PodSecurityContext. If set in both SecurityContext and PodSecurityContext, the value specified in SecurityContext takes precedence.	false	integer (int64)	
runAsNonRoot	Indicates that the container must run as a non-root user. If true, the Kubelet will validate the image at runtime to ensure that it does not run as UID 0 (root) and fail to start the container if it does. If unset or false, no such validation will be performed. May also be set in PodSecurityContext. If set in both SecurityContext and PodSecurityContext, the value specified in SecurityContext takes precedence.	false	boolean	
readOnlyRootFilesystem	Whether this container has a read-only root filesystem. Default is false.	false	boolean	

2.3.211. v1.SelfSubjectRulesReview

SelfSubjectRulesReview is a resource you can create to determine which actions you can perform in a namespace

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#types-kinds	false	string	
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#resources	false	string	
spec	Spec adds information about how to conduct the check	true	Section 2.3.212, "v1.SelfSubjectRulesReviewSpec"	

Name	Description	Required	Schema	Default
status	Status is completed by the server to tell which permissions you have	false	Section 2.3.220, "v1.SubjectRulesReviewStatus"	

2.3.212. v1.SelfSubjectRulesReviewSpec

SelfSubjectRulesReviewSpec adds information about how to conduct the check

Name	Description	Required	Schema	Default
scopes	Scopes to use for the evaluation. Empty means "use the unscoped (full) permissions of the user/groups". Nil means "use the scopes on this request".	true	string array	

2.3.213. v1.SignatureCondition

SignatureCondition describes an image signature condition of particular kind at particular probe time.

Name	Description	Required	Schema	Default
type	Type of signature condition, Complete or Failed.	true	string	
status	Status of the condition, one of True, False, Unknown.	true	string	
lastProbeTime	Last time the condition was checked.	false	string	
lastTransitionTime	Last time the condition transit from one status to another.	false	string	

Name	Description	Required	Schema	Default
reason	(brief) reason for the condition's last transition.	false	string	
message	Human readable message indicating details about last transition.	false	string	

2.3.214. v1.SignatureIssuer

SignatureIssuer holds information about an issuer of signing certificate or key.

Name	Description	Required	Schema	Default
organization	Organization name.	false	string	
commonName	Common name (e.g. openshift-signing-service).	false	string	

2.3.215. v1.SignatureSubject

SignatureSubject holds information about a person or entity who created the signature.

Name	Description	Required	Schema	Default
organization	Organization name.	false	string	
commonName	Common name (e.g. openshift-signing-service).	false	string	

Name	Description	Required	Schema	Default
publicKeyID	If present, it is a human readable key id of public key belonging to the subject used to verify image signature. It should contain at least 64 lowest bits of public key's fingerprint (e.g. 0x685ebe62bf278440).	true	string	

2.3.216. v1.SourceBuildStrategy

SourceBuildStrategy defines input parameters specific to an Source build.

Name	Description	Required	Schema	Default
from	from is reference to an DockerImage, ImageStreamTag, or ImageStreamImage from which the docker image should be pulled	true	Section 2.3.159, "v1.ObjectReference"	
pullSecret	pullSecret is the name of a Secret that would be used for setting up the authentication for pulling the Docker images from the private Docker registries	false	Section 2.3.138, "v1.LocalObjectReference"	
env	env contains additional environment variables you want to pass into a builder container	false	Section 2.3.86, "v1.EnvVar" array	

Name	Description	Required	Schema	Default
scripts	scripts is the location of Source scripts	false	string	
incremental	incremental flag forces the Source build to do incremental builds if true.	false	boolean	
forcePull	forcePull describes if the builder should pull the images from registry prior to building.	false	boolean	
runtimeImage	runtimeImage is an optional image that is used to run an application without unneeded dependencies installed. The building of the application is still done in the builder image but, post build, you can copy the needed artifacts in the runtime image for use. This field and the feature it enables are in tech preview.	false	Section 2.3.159, "v1.ObjectReference"	

Name	Description	Required	Schema	Default
runtimeArtifacts	runtimeArtifacts specifies a list of source/destination pairs that will be copied from the builder to the runtime image. sourcePath can be a file or directory. destinationDir must be a directory. destinationDir can also be empty or equal to ".", in this case it just refers to the root of WORKDIR. This field and the feature it enables are in tech preview.	false	Section 2.3.122 , "v1.ImageSourcePath" array	

2.3.217. v1.SourceControlUser

SourceControlUser defines the identity of a user of source control

Name	Description	Required	Schema	Default
name	name of the source control user	false	string	
email	email of the source control user	false	string	

2.3.218. v1.SourceRevision

SourceRevision is the revision or commit information from the source for the build

Name	Description	Required	Schema	Default
type	type of the build source, may be one of 'Source', 'Dockerfile', 'Binary', or 'Images'	true	string	

Name	Description	Required	Schema	Default
git	Git contains information about git-based build source	false	Section 2.3.99, "v1.GitSourceRevision"	

2.3.219. v1.SubjectAccessReview

SubjectAccessReview is an object for requesting information about whether a user or group can perform an action

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#types-kinds	false	string	
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#resources	false	string	

Name	Description	Required	Schema	Default
namespace	Namespace is the namespace of the action being requested. Currently, there is no distinction between no namespace and all namespaces	true	string	
verb	Verb is one of: get, list, watch, create, update, delete	true	string	
resourceAPIGroup	Group is the API group of the resource Serialized as resourceAPIGroup to avoid confusion with the 'groups' field when inlined	true	string	
resourceAPIVersion	Version is the API version of the resource Serialized as resourceAPIVersion to avoid confusion with TypeMeta.apiVersion and ObjectMeta.resourceVersion when inlined	true	string	
resource	Resource is one of the existing resource types	true	string	
resourceName	ResourceName is the name of the resource being requested for a "get" or deleted for a "delete"	true	string	

Name	Description	Required	Schema	Default
content	Content is the actual content of the request for create and update	false	string	
user	User is optional. If both User and Groups are empty, the current authenticated user is used.	true	string	
groups	GroupsSlice is optional. Groups is the list of groups to which the User belongs.	true	string array	
scopes	Scopes to use for the evaluation. Empty means "use the unscoped (full) permissions of the user/groups". Nil for a self-SAR, means "use the scopes on this request". Nil for a regular SAR, means the same as empty.	true	string array	

2.3.220. v1.SubjectRulesReviewStatus

SubjectRulesReviewStatus is contains the result of a rules check

Name	Description	Required	Schema	Default
rules	Rules is the list of rules (no particular sort) that are allowed for the subject	true	Section 2.3.170, "v1.PolicyRule" array	

Name	Description	Required	Schema	Default
evaluationError	EvaluationError can appear in combination with Rules. It means some error happened during evaluation that may have prevented additional rules from being populated.	false	string	

2.3.221. v1.TCPSocketAction

TCPSocketAction describes an action based on opening a socket

Name	Description	Required	Schema	Default
port	Number or name of the port to access on the container. Number must be in the range 1 to 65535. Name must be an IANA_SVC_NAME	true	string	

2.3.222. v1.TLSConfig

TLSConfig defines config used to secure a route and provide termination

Name	Description	Required	Schema	Default
termination	Termination indicates termination type.	true	string	
certificate	Certificate provides certificate contents	false	string	
key	Key provides key file contents	false	string	

Name	Description	Required	Schema	Default
caCertificate	CACertificate provides the cert authority certificate contents	false	string	
destinationCACertificate	DestinationCACertificate provides the contents of the ca certificate of the final destination. When using reencrypt termination this file should be provided in order to have routers use it for health checks on the secure connection	false	string	
insecureEdgeTerminationPolicy	InsecureEdgeTerminationPolicy indicates the desired behavior for insecure connections to an edge-terminated route: disable, allow or redirect	false	string	

2.3.223. v1.TagEvent

TagEvent is used by ImageStreamStatus to keep a historical record of images associated with a tag.

Name	Description	Required	Schema	Default
created	Created holds the time the TagEvent was created	true	string	
dockerImageReference	DockerImageReference is the string that can be used to pull this image	true	string	

Name	Description	Required	Schema	Default
image	Image is the image	true	string	
generation	Generation is the spec tag generation that resulted in this tag being updated	true	integer (int64)	

2.3.224. v1.TagEventCondition

TagEventCondition contains condition information for a tag event.

Name	Description	Required	Schema	Default
type	Type of tag event condition, currently only ImportSuccess	true	string	
status	Status of the condition, one of True, False, Unknown.	true	string	
lastTransitionTime	LastTransitionTime is the time the condition transitioned from one status to another.	false	string	
reason	Reason is a brief machine readable explanation for the condition's last transition.	false	string	
message	Message is a human readable description of the details about last transition, complementing reason.	false	string	

Name	Description	Required	Schema	Default
generation	Generation is the spec tag generation that this status corresponds to	true	integer (int64)	

2.3.225. v1.TagImageHook

TagImageHook is a request to tag the image in a particular container onto an ImageStreamTag.

Name	Description	Required	Schema	Default
containerName	ContainerName is the name of a container in the deployment config whose image value will be used as the source of the tag. If there is only a single container this value will be defaulted to the name of that container.	true	string	
to	To is the target ImageStreamTag to set the container's image onto.	true	Section 2.3.159, "v1.ObjectReference"	

2.3.226. v1.TagImportPolicy

TagImportPolicy describes the tag import policy

Name	Description	Required	Schema	Default
insecure	Insecure is true if the server may bypass certificate verification or connect directly over HTTP during image import.	false	boolean	

Name	Description	Required	Schema	Default
scheduled	Scheduled indicates to the server that this tag should be periodically checked to ensure it is up to date, and imported	false	boolean	

2.3.227. v1.TagReference

TagReference specifies optional annotations for images using this tag and an optional reference to an ImageStreamTag, ImageStreamImage, or DockerImage this tag should track.

Name	Description	Required	Schema	Default
name	Name of the tag	true	string	
annotations	Annotations associated with images using this tag	true	object	
from	From is a reference to an image stream tag or image stream this tag should track	false	Section 2.3.159, "v1.ObjectReference"	
reference	Reference states if the tag will be imported. Default value is false, which means the tag will be imported.	false	boolean	

Name	Description	Required	Schema	Default
generation	Generation is the image stream generation that updated this tag - setting it to 0 is an indication that the generation must be updated. Legacy clients will send this as nil, which means the client doesn't know or care.	true	integer (int64)	
importPolicy	Import is information that controls how images may be imported by the server.	false	Section 2.3.226, "v1.TagImportPolicy"	

2.3.228. v1.Template

Template contains the inputs needed to produce a Config.

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#types-kinds	false	string	

Name	Description	Required	Schema	Default
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#resources	false	string	
metadata	Standard object's metadata.	false	Section 2.3.158, "v1.ObjectMeta"	
message	message is an optional instructional message that will be displayed when this template is instantiated. This field should inform the user how to utilize the newly created resources. Parameter substitution will be performed on the message before being displayed so that generated credentials and other parameters can be included in the output.	false	string	
objects	objects is an array of resources to include in this template.	true	Section 2.3.3, "runtime.RawExtension" array	

Name	Description	Required	Schema	Default
parameters	parameters is an optional array of Parameters used during the Template to Config transformation.	false	Section 2.3.161 , "v1.Parameter" array	
labels	labels is a optional set of labels that are applied to every object during the Template to Config transformation.	false	object	

2.3.229. v1.TemplateList

TemplateList is a list of Template objects.

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#types-kinds	false	string	

Name	Description	Required	Schema	Default
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#resources	false	string	
metadata	Standard object's metadata.	false	Section 2.3.9 , "unversioned.ListMeta"	
items	Items is a list of templates	true	Section 2.3.228 , "v1.Template" array	

2.3.230. v1.User

Upon log in, every user of the system receives a User and Identity resource. Administrators may directly manipulate the attributes of the users for their own tracking, or set groups via the API. The user name is unique and is chosen based on the value provided by the identity provider - if a user already exists with the incoming name, the user name may have a number appended to it.

Name	Description	Required	Schema	Default
------	-------------	----------	--------	---------

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#types-kinds	false	string	
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#resources	false	string	
metadata	Standard object's metadata.	false	Section 2.3.158, "v1.ObjectMeta"	
fullName	FullName is the full name of user	false	string	
identities	Identities are the identities associated with this user	true	string array	

Name	Description	Required	Schema	Default
groups	Groups are the groups that this user is a member of	true	string array	

2.3.231. v1.UserIdentityMapping

UserIdentityMapping maps a user to an identity

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#types-kinds	false	string	
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#resources	false	string	

Name	Description	Required	Schema	Default
metadata	Standard object's metadata.	false	Section 2.3.158, "v1.ObjectMeta"	
identity	Identity is a reference to an identity	false	Section 2.3.159, "v1.ObjectReference"	
user	User is a reference to a user	false	Section 2.3.159, "v1.ObjectReference"	

2.3.232. v1.UserList

UserList is a collection of Users

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#types-kinds	false	string	

Name	Description	Required	Schema	Default
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#resources	false	string	
metadata	Standard object's metadata.	false	Section 2.3.9, "unversioned.ListMeta"	
items	Items is the list of users	true	Section 2.3.230, "v1.User" array	

2.3.233. v1.Volume

Volume represents a named volume in a pod that may be accessed by any container in the pod.

Name	Description	Required	Schema	Default
name	Volume's name. Must be a DNS_LABEL and unique within the pod. More info: http://releases.k8s.io/release-1.3/docs/user-guide/identifiers.md#names	true	string	

Name	Description	Required	Schema	Default
hostPath	HostPath represents a pre-existing file or directory on the host machine that is directly exposed to the container. This is generally used for system agents or other privileged things that are allowed to see the host machine. Most containers will NOT need this. More info: http://releases.k8s.io/release-1.3/docs/user-guide/volumes.md#hostpath	false	Section 2.3.106, "v1.HostPathVolumeSource"	
emptyDir	EmptyDir represents a temporary directory that shares a pod's lifetime. More info: http://releases.k8s.io/release-1.3/docs/user-guide/volumes.md#emptydir	false	Section 2.3.85, "v1.EmptyDirVolumeSource"	
gcePersistentDisk	GCEPersistentDisk represents a GCE Disk resource that is attached to a kubelet's host machine and then exposed to the pod. More info: http://releases.k8s.io/release-1.3/docs/user-guide/volumes.md#gcepersistentdisk	false	Section 2.3.94, "v1.GCEPersistentDiskVolumeSource"	

Name	Description	Required	Schema	Default
awsElasticBlockStore	AWSElasticBlockStore represents an AWS Disk resource that is attached to a kubelet's host machine and then exposed to the pod. More info: http://releases.k8s.io/release-1.3/docs/user-guide/volumes.md#awselasticblockstore	false	Section 2.3.14, "v1.AWSElasticBlockStoreVolumeSource"	
gitRepo	GitRepo represents a git repository at a particular revision.	false	Section 2.3.98, "v1.GitRepoVolumeSource"	
secret	Secret represents a secret that should populate this volume. More info: http://releases.k8s.io/release-1.4/docs/user-guide/volumes.md#secrets	false	Section 2.3.209, "v1.SecretVolumeSource"	
nfs	NFS represents an NFS mount on the host that shares a pod's lifetime More info: http://releases.k8s.io/release-1.4/docs/user-guide/volumes.md#nfs	false	Section 2.3.141, "v1.NFSVolumeSource"	

Name	Description	Required	Schema	Default
iscsi	ISCSI represents an ISCSI Disk resource that is attached to a kubelet's host machine and then exposed to the pod. More info: http://releases.k8s.io/release-1.4/examples/volumes/iscsi/README.md	false	Section 2.3.109, "v1.ISCSIVolumeSource"	
glusterfs	Glusterfs represents a Glusterfs mount on the host that shares a pod's lifetime. More info: http://releases.k8s.io/release-1.4/examples/volumes/glusterfs/README.md	false	Section 2.3.100, "v1.GlusterfsVolumeSource"	
persistentVolumeClaim	PersistentVolumeClaimVolumeSource represents a reference to a PersistentVolumeClaim in the same namespace. More info: http://releases.k8s.io/release-1.4/docs/user-guide/persistent-volumes.md#persistentvolumeclaims	false	Section 2.3.162, "v1.PersistentVolumeClaimVolumeSource"	
rbd	A Ceph Rados Block Device mount on the host that shares a pod's lifetime. More info: http://releases.k8s.io/release-1.4/examples/volumes/rbd/README.md	false	Section 2.3.178, "v1.RBDVolumeSource"	

Name	Description	Required	Schema	Default
flexVolume	FlexVolume represents a generic volume resource that is provisioned/attached using an exec based plugin. This is an alpha feature and may change in future.	false	Section 2.3.92, "v1.FlexVolumeSource"	
cinder	Cinder represents a cinder volume attached and mounted on kubelets host machine More info: http://releases.k8s.io/release-1.4/examples/mysql-cinder-pd/README.md	false	Section 2.3.38, "v1.CinderVolumeSource"	
cephfs	CephFS represents a Ceph FS mount on the host that shares a pod's lifetime	false	Section 2.3.37, "v1.CephFSVolumeSource"	
flocker	Flocker represents a Flocker volume attached to a kubelet's host machine. This depends on the Flocker control service being running	false	Section 2.3.93, "v1.FlockerVolumeSource"	
downwardAPI	DownwardAPI represents downward API about the pod that should populate this volume	false	Section 2.3.79, "v1.DownwardAPIVolumeSource"	

Name	Description	Required	Schema	Default
fc	FC represents a Fibre Channel resource that is attached to a kubelet's host machine and then exposed to the pod.	false	Section 2.3.90, "v1.FCVolumeSource"	
azureFile	AzureFile represents an Azure File Service mount on the host and bind mount to the pod.	false	Section 2.3.17, "v1.AzureFileVolumeSource"	
configMap	ConfigMap represents a configMap that should populate this volume	false	Section 2.3.56, "v1.ConfigMapVolumeSource"	
vsphereVolume	VsphereVolume represents a vSphere volume attached and mounted on kubelets host machine	false	Section 2.3.235, "v1.VsphereVirtualDiskVolumeSource"	
metadata	Metadata represents metadata about the pod that should populate this volume Deprecated: Use downwardAPI instead.	false	Section 2.3.76, "v1.DeprecatedDownwardAPIVolumeSource"	

2.3.234. v1.VolumeMount

VolumeMount describes a mounting of a Volume within a container.

Name	Description	Required	Schema	Default
------	-------------	----------	--------	---------

Name	Description	Required	Schema	Default
name	This must match the Name of a Volume.	true	string	
readOnly	Mounted read-only if true, read-write otherwise (false or unspecified). Defaults to false.	false	boolean	
mountPath	Path within the container at which the volume should be mounted. Must not contain '.'.	true	string	
subPath	Path within the volume from which the container's volume should be mounted. Defaults to "" (volume's root).	false	string	

2.3.235. v1.VsphereVirtualDiskVolumeSource

Represents a vSphere volume resource.

Name	Description	Required	Schema	Default
volumePath	Path that identifies vSphere volume vmdk	true	string	
fsType	Filesystem type to mount. Must be a filesystem type supported by the host operating system. Ex. "ext4", "xfs", "ntfs". Implicitly inferred to be "ext4" if unspecified.	false	string	

2.3.236. v1.WebHookTrigger

WebHookTrigger is a trigger that gets invoked using a webhook type of post

Name	Description	Required	Schema	Default
secret	secret used to validate requests.	false	string	
allowEnv	allowEnv determines whether the webhook can set environment variables; can only be set to true for GenericWebHook.	false	boolean	

2.3.237. v1beta1.Scale

Scale is a subresource representing the current "scale" of certain objects, such as ReplicationControllers and DeploymentConfigs. It may be checked to determine the current replica count of these objects, or updated to set the replica count of these objects.

In the case of ReplicationControllers, this directly reflects the scale the ReplicationController. For DeploymentConfigs, it reflects the scale of the deployment(s), or, if none are present, the scale of the DeploymentConfig's template.

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#types-kinds	false	string	

Name	Description	Required	Schema	Default
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#resources	false	string	
metadata	Standard object metadata; More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#metadata .	false	Section 2.3.158, "v1.ObjectMeta"	
spec	defines the behavior of the scale. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#spec-and-status .	false	Section 2.3.238, "v1beta1.ScaleSpec"	
status	current status of the scale. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#spec-and-status . Read-only.	false	Section 2.3.239, "v1beta1.ScaleStatus"	

2.3.238. v1beta1.ScaleSpec

describes the attributes of a scale subresource

Name	Description	Required	Schema	Default
replicas	desired number of instances for the scaled object.	false	integer (int32)	

2.3.239. v1beta1.ScaleStatus

represents the current status of a scale subresource.

Name	Description	Required	Schema	Default
replicas	actual number of observed instances of the scaled object.	true	integer (int32)	
selector	label query over pods that should match the replicas count. More info: http://releases.k8s.io/release-1.3/docs/user-guide/labels.md#label-selectors	false	object	

Name	Description	Required	Schema	Default
targetSelector	label selector for pods that should match the replicas count. This is a serialized version of both map-based and more expressive set-based selectors. This is done to avoid introspection in the clients. The string will be in the same format as the query-param syntax. If the target type only supports map-based selectors, both this field and map-based selector field are populated. More info: http://releases.k8s.io/release-1.3/docs/user-guide/labels.md#label-selectors	false	string	

2.3.240. any

Represents an untyped JSON map - see the description of the field for more info about the structure of this object.

CHAPTER 3. KUBERNETES V1 REST API

3.1. OVERVIEW

The Kubernetes API allows you to run containerized applications, bind persistent storage, link those applications through service discovery, and manage the cluster infrastructure.

3.1.1. Version information

Version: v1

3.1.2. URI scheme

Host: 127.0.0.1:8443

BasePath: /

Schemes: HTTPS

3.2. PATHS

3.2.1. get available resources

```
GET /api/v1
```

3.2.1.1. Responses

HTTP Code	Description	Schema
default	success	Section 2.3.6 , "unversioned.APIResourceList"

3.2.1.2. Consumes

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.1.3. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.1.4. Tags

- apiv1

3.2.2. create a Binding

POST /api/v1/bindings

3.2.2.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 3.3.15, "v1.Binding"	

3.2.2.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.15, "v1.Binding"

3.2.2.3. Consumes

- /

3.2.2.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.2.5. Tags

- apiv1

3.2.3. list objects of kind ComponentStatus

GET /api/v1/componentstatuses

3.2.3.1. Parameters

Type	Name	Description	Required	Schema	Default
------	------	-------------	----------	--------	---------

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamet er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParamet er	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	
QueryParamet er	resourceVersio n	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	
QueryParamet er	timeoutSecond s	Timeout for the list/watch call.	false	integer	

3.2.3.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.22 , "v1.ComponentStatusList"

3.2.3.3. Consumes

- /

3.2.3.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.3.5. Tags

- apiv1

3.2.4. read the specified ComponentStatus

```
GET /api/v1/componentstatuses/{name}
```

3.2.4.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
PathParameter	name	name of the ComponentSta tus	true	string	

3.2.4.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.21 , "v1.ComponentStatus"

3.2.4.3. Consumes

- /

3.2.4.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.4.5. Tags

- apiv1

3.2.5. create a ConfigMap

POST /api/v1/configmaps

3.2.5.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 3.3.23, "v1.ConfigMap"	

3.2.5.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.23, "v1.ConfigMap"

3.2.5.3. Consumes

- /

3.2.5.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.5.5. Tags

- apiv1

3.2.6. list or watch objects of kind ConfigMap

GET /api/v1/configmaps

3.2.6.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamet er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParamet er	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	
QueryParamet er	resourceVersio n	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParamet er	timeoutSecond s	Timeout for the list/watch call.	false	integer	

3.2.6.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.25, "v1.ConfigMapList"

3.2.6.3. Consumes

- /

3.2.6.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.6.5. Tags

- apiv1

3.2.7. create a Endpoints

POST /api/v1/endpoints

3.2.7.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 3.3.45, "v1.Endpoints"	

3.2.7.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.45, “v1.Endpoints”

3.2.7.3. Consumes

- /

3.2.7.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.7.5. Tags

- apiv1

3.2.8. list or watch objects of kind Endpoints

GET /api/v1/endpoints

3.2.8.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamet er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParamet er	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	
QueryParamet er	resourceVersio n	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	
QueryParamet er	timeoutSecond s	Timeout for the list/watch call.	false	integer	

3.2.8.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.46, "v1.EndpointsList"

3.2.8.3. Consumes

- /

3.2.8.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.8.5. Tags

- apiv1

3.2.9. create a Event

POST /api/v1/events

3.2.9.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 3.3.49, "v1.Event"	

3.2.9.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.49, "v1.Event"

3.2.9.3. Consumes

- /

3.2.9.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.9.5. Tags

- apiv1

3.2.10. list or watch objects of kind Event

GET /api/v1/events

3.2.10.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamet er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParamet er	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	
QueryParamet er	resourceVersio n	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	
QueryParamet er	timeoutSecond s	Timeout for the list/watch call.	false	integer	

3.2.10.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.50, “v1.EventList”

3.2.10.3. Consumes

- /

3.2.10.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.10.5. Tags

- apiv1

3.2.11. create a LimitRange

POST /api/v1/limitranges

3.2.11.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 3.3.70, “v1.LimitRange”	

3.2.11.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.70, “v1.LimitRange”

3.2.11.3. Consumes

- /

3.2.11.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.11.5. Tags

- apiv1

3.2.12. list or watch objects of kind LimitRange

GET /api/v1/limitranges

3.2.12.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamet er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParamet er	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParam er	resourceVersio n	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	
QueryParam er	timeoutSecond s	Timeout for the list/watch call.	false	integer	

3.2.12.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.72, "v1.LimitRangeList"

3.2.12.3. Consumes

- /

3.2.12.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.12.5. Tags

- apiv1

3.2.13. delete collection of Namespace

```
DELETE /api/v1/namespaces
```

3.2.13.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamet er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParamet er	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersio n.	false	boolean	
QueryParamet er	resourceVersio n	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	
QueryParamet er	timeoutSecond s	Timeout for the list/watch call.	false	integer	

3.2.13.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.11 , “unversioned.Status”

3.2.13.3. Consumes

- /

3.2.13.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.13.5. Tags

- apiv1

3.2.14. create a Namespace

POST /api/v1/namespaces

3.2.14.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 3.3.78 , “v1.Namespace e”	

3.2.14.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.78 , “v1.Namespace”

3.2.14.3. Consumes

- /

3.2.14.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.14.5. Tags

- apiv1

3.2.15. list or watch objects of kind Namespace

GET /api/v1/namespaces

3.2.15.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamet er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParamet er	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParamet er	resourceVersio n	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	
QueryParamet er	timeoutSecond s	Timeout for the list/watch call.	false	integer	

3.2.15.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.79, "v1.NamespaceList"

3.2.15.3. Consumes

- /

3.2.15.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.15.5. Tags

- apiv1

3.2.16. create a Binding

POST /api/v1/namespaces/{namespace}/bindings

3.2.16.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 3.3.15, "v1.Binding"	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	

3.2.16.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.15, "v1.Binding"

3.2.16.3. Consumes

- /

3.2.16.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.16.5. Tags

- apiv1

3.2.17. delete collection of ConfigMap

```
DELETE /api/v1/namespaces/{namespace}/configmaps
```

3.2.17.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamet er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParamet er	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	
QueryParamet er	resourceVersio n	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	
QueryParamet er	timeoutSecond s	Timeout for the list/watch call.	false	integer	

Type	Name	Description	Required	Schema	Default
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	

3.2.17.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.11, "unversioned.Status"

3.2.17.3. Consumes

- /

3.2.17.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.17.5. Tags

- apiv1

3.2.18. create a ConfigMap

POST /api/v1/namespaces/{namespace}/configmaps

3.2.18.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 3.3.23, "v1.ConfigMap"	

Type	Name	Description	Required	Schema	Default
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	

3.2.18.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.23, “v1.ConfigMap”

3.2.18.3. Consumes

- /

3.2.18.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.18.5. Tags

- apiv1

3.2.19. list or watch objects of kind ConfigMap

```
GET /api/v1/namespaces/{namespace}/configmaps
```

3.2.19.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParamet er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParamet er	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	
QueryParamet er	resourceVersio n	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	
QueryParamet er	timeoutSecond s	Timeout for the list/watch call.	false	integer	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	

3.2.19.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.25, "v1.ConfigMapList"

3.2.19.3. Consumes

- /

3.2.19.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.19.5. Tags

- apiv1

3.2.20. delete a ConfigMap

```
DELETE /api/v1/namespaces/{namespace}/configmaps/{name}
```

3.2.20.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 2.3.61, "v1.DeleteOptions"	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParameter	name	name of the ConfigMap	true	string	

3.2.20.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.11, "unversioned.Status"

3.2.20.3. Consumes

- /

3.2.20.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.20.5. Tags

- apiv1

3.2.21. partially update the specified ConfigMap

```
PATCH /api/v1/namespaces/{namespace}/configmaps/{name}
```

3.2.21.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 2.3.10, "unversioned.Patch"	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParameter	name	name of the ConfigMap	true	string	

3.2.21.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.23, "v1.ConfigMap"

3.2.21.3. Consumes

- application/json-patch+json

- application/merge-patch+json
- application/strategic-merge-patch+json

3.2.21.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.21.5. Tags

- apiv1

3.2.22. replace the specified ConfigMap

```
PUT /api/v1/namespaces/{namespace}/configmaps/{name}
```

3.2.22.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 3.3.23, "v1.ConfigMap"	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParameter	name	name of the ConfigMap	true	string	

3.2.22.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.23, "v1.ConfigMap"

3.2.22.3. Consumes

- /

3.2.22.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.22.5. Tags

- apiv1

3.2.23. read the specified ConfigMap

```
GET /api/v1/namespaces/{namespace}/configmaps/{name}
```

3.2.23.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	export	Should this value be exported. Export strips fields that a user can not specify.	false	boolean	
QueryParamet er	exact	Should the export be exact. Exact export maintains cluster-specific fields like 'Namespace'	false	boolean	
PathParamet er	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParamet er	name	name of the ConfigMap	true	string	

3.2.23.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.23, “v1.ConfigMap”

3.2.23.3. Consumes

- /

3.2.23.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.23.5. Tags

- apiv1

3.2.24. delete collection of Endpoints

```
DELETE /api/v1/namespaces/{namespace}/endpoints
```

3.2.24.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamet er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParamet er	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersio n.	false	boolean	
QueryParamet er	resourceVersio n	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	
QueryParamet er	timeoutSecond s	Timeout for the list/watch call.	false	integer	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	

3.2.24.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.11 , "unversioned.Status"

3.2.24.3. Consumes

- /

3.2.24.4. Produces

- application/json

- application/yaml
- application/vnd.kubernetes.protobuf

3.2.24.5. Tags

- apiv1

3.2.25. create a Endpoints

POST /api/v1/namespaces/{namespace}/endpoints

3.2.25.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 3.3.45, "v1.Endpoints"	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	

3.2.25.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.45, "v1.Endpoints"

3.2.25.3. Consumes

- /

3.2.25.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.25.5. Tags

- apiv1

3.2.26. list or watch objects of kind Endpoints

GET /api/v1/namespaces/{namespace}/endpoints

3.2.26.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamet er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParamet er	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParamet er	resourceVersio n	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	
QueryParamet er	timeoutSecond s	Timeout for the list/watch call.	false	integer	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	

3.2.26.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.46, “v1.EndpointsList”

3.2.26.3. Consumes

- /

3.2.26.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.26.5. Tags

- apiv1

3.2.27. delete a Endpoints

```
DELETE /api/v1/namespaces/{namespace}/endpoints/{name}
```

3.2.27.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 2.3.61, "v1.DeleteOptions"	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParameter	name	name of the Endpoints	true	string	

3.2.27.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.11, "unversioned.Status"

3.2.27.3. Consumes

- /

3.2.27.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.27.5. Tags

- apiv1

3.2.28. partially update the specified Endpoints

```
PATCH /api/v1/namespaces/{namespace}/endpoints/{name}
```

3.2.28.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 2.3.10, “unversioned.Patch”	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParameter	name	name of the Endpoints	true	string	

3.2.28.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.45, “v1.Endpoints”

3.2.28.3. Consumes

- application/json-patch+json
- application/merge-patch+json
- application/strategic-merge-patch+json

3.2.28.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.28.5. Tags

- apiv1

3.2.29. replace the specified Endpoints

```
PUT /api/v1/namespaces/{namespace}/endpoints/{name}
```

3.2.29.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 3.3.45, "v1.Endpoints"	
PathParamet er	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParamet er	name	name of the Endpoints	true	string	

3.2.29.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.45, "v1.Endpoints"

3.2.29.3. Consumes

- /

3.2.29.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.29.5. Tags

- apiv1

3.2.30. read the specified Endpoints

```
GET /api/v1/namespaces/{namespace}/endpoints/{name}
```

3.2.30.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	export	Should this value be exported. Export strips fields that a user can not specify.	false	boolean	
QueryParamet er	exact	Should the export be exact. Exact export maintains cluster-specific fields like 'Namespace'	false	boolean	
PathParamet er	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParamet er	name	name of the Endpoints	true	string	

3.2.30.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.45, "v1.Endpoints"

3.2.30.3. Consumes

- /

3.2.30.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.30.5. Tags

- apiv1

3.2.31. delete collection of Event

```
DELETE /api/v1/namespaces/{namespace}/events
```

3.2.31.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamet er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParamet er	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParamet er	resourceVersio n	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	
QueryParamet er	timeoutSecond s	Timeout for the list/watch call.	false	integer	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	

3.2.31.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.11 , “unversioned.Status”

3.2.31.3. Consumes

- /

3.2.31.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.31.5. Tags

- apiv1

3.2.32. create a Event

POST /api/v1/namespaces/{namespace}/events

3.2.32.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 3.3.49, "v1.Event"	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	

3.2.32.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.49, "v1.Event"

3.2.32.3. Consumes

- /

3.2.32.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.32.5. Tags

- apiv1

3.2.33. list or watch objects of kind Event

GET /api/v1/namespaces/{namespace}/events

3.2.33.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamet er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParamet er	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	
QueryParamet er	resourceVersio n	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	
QueryParamet er	timeoutSecond s	Timeout for the list/watch call.	false	integer	

Type	Name	Description	Required	Schema	Default
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	

3.2.33.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.50, "v1.EventList"

3.2.33.3. Consumes

- /

3.2.33.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.33.5. Tags

- apiv1

3.2.34. delete a Event

```
DELETE /api/v1/namespaces/{namespace}/events/{name}
```

3.2.34.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 2.3.61, "v1.DeleteOptions"	

Type	Name	Description	Required	Schema	Default
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParameter	name	name of the Event	true	string	

3.2.34.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.11 , “unversioned.Status”

3.2.34.3. Consumes

- /

3.2.34.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.34.5. Tags

- apiv1

3.2.35. partially update the specified Event

```
PATCH /api/v1/namespaces/{namespace}/events/{name}
```

3.2.35.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	

Type	Name	Description	Required	Schema	Default
BodyParameter	body		true	Section 2.3.10, “unversioned.Patch”	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParameter	name	name of the Event	true	string	

3.2.35.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.49, “v1.Event”

3.2.35.3. Consumes

- application/json-patch+json
- application/merge-patch+json
- application/strategic-merge-patch+json

3.2.35.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.35.5. Tags

- apiv1

3.2.36. replace the specified Event

```
PUT /api/v1/namespaces/{namespace}/events/{name}
```

3.2.36.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 3.3.49, "v1.Event"	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParameter	name	name of the Event	true	string	

3.2.36.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.49, "v1.Event"

3.2.36.3. Consumes

- /

3.2.36.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.36.5. Tags

- apiv1

3.2.37. read the specified Event

```
GET /api/v1/namespaces/{namespace}/events/{name}
```

3.2.37.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	export	Should this value be exported. Export strips fields that a user can not specify.	false	boolean	
QueryParamet er	exact	Should the export be exact. Exact export maintains cluster-specific fields like 'Namespace'	false	boolean	
PathParamet er	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParamet er	name	name of the Event	true	string	

3.2.37.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.49, "v1.Event"

3.2.37.3. Consumes

- /

3.2.37.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.37.5. Tags

- apiv1

3.2.38. delete collection of LimitRange

```
DELETE /api/v1/namespaces/{namespace}/limitranges
```

3.2.38.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamet er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParamet er	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParamet er	resourceVersio n	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	
QueryParamet er	timeoutSecond s	Timeout for the list/watch call.	false	integer	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	

3.2.38.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.11 , “unversioned.Status”

3.2.38.3. Consumes

- /

3.2.38.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.38.5. Tags

- apiv1

3.2.39. create a LimitRange

POST /api/v1/namespaces/{namespace}/limitranges

3.2.39.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 3.3.70, "v1.LimitRange"	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	

3.2.39.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.70, "v1.LimitRange"

3.2.39.3. Consumes

- /

3.2.39.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.39.5. Tags

- apiv1

3.2.40. list or watch objects of kind LimitRange

GET /api/v1/namespaces/{namespace}/limitranges

3.2.40.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamet er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParamet er	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	
QueryParamet er	resourceVersio n	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	
QueryParamet er	timeoutSecond s	Timeout for the list/watch call.	false	integer	

Type	Name	Description	Required	Schema	Default
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	

3.2.40.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.72, "v1.LimitRangeList"

3.2.40.3. Consumes

- /

3.2.40.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.40.5. Tags

- apiv1

3.2.41. delete a LimitRange

```
DELETE /api/v1/namespaces/{namespace}/limitranges/{name}
```

3.2.41.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 2.3.61, "v1.DeleteOptions"	

Type	Name	Description	Required	Schema	Default
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParameter	name	name of the LimitRange	true	string	

3.2.41.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.11 , "unversioned.Status"

3.2.41.3. Consumes

- /

3.2.41.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.41.5. Tags

- apiv1

3.2.42. partially update the specified LimitRange

```
PATCH /api/v1/namespaces/{namespace}/limitranges/{name}
```

3.2.42.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	

Type	Name	Description	Required	Schema	Default
BodyParameter	body		true	Section 2.3.10, “unversioned.Patch”	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParameter	name	name of the LimitRange	true	string	

3.2.42.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.70, “v1.LimitRange”

3.2.42.3. Consumes

- application/json-patch+json
- application/merge-patch+json
- application/strategic-merge-patch+json

3.2.42.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.42.5. Tags

- apiv1

3.2.43. replace the specified LimitRange

```
PUT /api/v1/namespaces/{namespace}/limitranges/{name}
```

3.2.43.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 3.3.70, "v1.LimitRange"	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParameter	name	name of the LimitRange	true	string	

3.2.43.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.70, "v1.LimitRange"

3.2.43.3. Consumes

- /

3.2.43.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.43.5. Tags

- apiv1

3.2.44. read the specified LimitRange

```
GET /api/v1/namespaces/{namespace}/limitranges/{name}
```

3.2.44.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	export	Should this value be exported. Export strips fields that a user can not specify.	false	boolean	
QueryParamet er	exact	Should the export be exact. Exact export maintains cluster-specific fields like 'Namespace'	false	boolean	
PathParamet er	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParamet er	name	name of the LimitRange	true	string	

3.2.44.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.70, "v1.LimitRange"

3.2.44.3. Consumes

- /

3.2.44.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.44.5. Tags

- apiv1

3.2.45. delete collection of PersistentVolumeClaim

```
DELETE /api/v1/namespaces/{namespace}/persistentvolumeclaims
```

3.2.45.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamet er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParamet er	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParameter	resourceVersion	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	
QueryParameter	timeoutSeconds	Timeout for the list/watch call.	false	integer	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	

3.2.45.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.11 , “unversioned.Status”

3.2.45.3. Consumes

- /

3.2.45.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.45.5. Tags

- apiv1

3.2.46. create a PersistentVolumeClaim

POST /api/v1/namespaces/{namespace}/persistentvolumeclaims

3.2.46.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 3.3.96, "v1.PersistentVolumeClaim"	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	

3.2.46.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.96, "v1.PersistentVolumeClaim"

3.2.46.3. Consumes

- /

3.2.46.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.46.5. Tags

- apiv1

3.2.47. list or watch objects of kind PersistentVolumeClaim

GET /api/v1/namespaces/{namespace}/persistentvolumeclaims

3.2.47.1. Description

Persistent Volume Claims (PVC) represent a request to use a persistent volume (PV) with a pod. When creating a pod definition (or replication controller or deployment config) a developer may specify the amount of storage they need via a persistent volume reference. If an administrator has enabled and configured persistent volumes for use, they will be allocated on demand to pods that have similar requirements. Since volumes are created lazily, some pods may be scheduled to a node before their volume is assigned. The node will detect this situation and wait to start the pod until the volume is bound. Events will be generated (visible by using the **describe** command on the pod) that indicate the pod is waiting for volumes.

3.2.47.2. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamet er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParamet er	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParamet er	resourceVersio n	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	
QueryParamet er	timeoutSecond s	Timeout for the list/watch call.	false	integer	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	

3.2.47.3. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.97 , "v1.PersistentVolumeClaimList"

3.2.47.4. Consumes

- /

3.2.47.5. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.47.6. Tags

- apiv1

3.2.48. delete a PersistentVolumeClaim

```
DELETE /api/v1/namespaces/{namespace}/persistentvolumeclaims/{name}
```

3.2.48.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParameter	body		true	Section 2.3.61, "v1.DeleteOptions"	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParameter	name	name of the PersistentVolumeClaim	true	string	

3.2.48.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.11, "unversioned.Status"

3.2.48.3. Consumes

- /

3.2.48.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.48.5. Tags

- apiv1

3.2.49. partially update the specified PersistentVolumeClaim

PATCH /api/v1/namespaces/{namespace}/persistentvolumeclaims/{name}

3.2.49.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 2.3.10, “unversioned.Patch”	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParameter	name	name of the PersistentVolumeClaim	true	string	

3.2.49.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.96, “v1.PersistentVolumeClaim”

3.2.49.3. Consumes

- application/json-patch+json
- application/merge-patch+json
- application/strategic-merge-patch+json

3.2.49.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.49.5. Tags

- apiv1

3.2.50. replace the specified PersistentVolumeClaim

```
PUT /api/v1/namespaces/{namespace}/persistentvolumeclaims/{name}
```

3.2.50.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 3.3.96, "v1.PersistentVolumeClaim"	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParameter	name	name of the PersistentVolu meClaim	true	string	

3.2.50.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.96, "v1.PersistentVolumeClaim"

3.2.50.3. Consumes

- /

3.2.50.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.50.5. Tags

- apiv1

3.2.51. read the specified PersistentVolumeClaim

```
GET /api/v1/namespaces/{namespace}/persistentvolumeclaims/{name}
```

3.2.51.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	export	Should this value be exported. Export strips fields that a user can not specify.	false	boolean	
QueryParamet er	exact	Should the export be exact. Exact export maintains cluster-specific fields like 'Namespace'	false	boolean	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParameter	name	name of the PersistentVolumeClaim	true	string	

3.2.51.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.96, "v1.PersistentVolumeClaim"

3.2.51.3. Consumes

- /

3.2.51.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.51.5. Tags

- apiv1

3.2.52. partially update status of the specified PersistentVolumeClaim

```
PATCH /api/v1/namespaces/{namespace}/persistentvolumeclaims/{name}/status
```

3.2.52.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 2.3.10, “unversioned.Patch”	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParameter	name	name of the PersistentVolumeClaim	true	string	

3.2.52.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.96, “v1.PersistentVolumeClaim”

3.2.52.3. Consumes

- application/json-patch+json
- application/merge-patch+json

- application/strategic-merge-patch+json

3.2.52.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.52.5. Tags

- apiv1

3.2.53. replace status of the specified PersistentVolumeClaim

```
PUT /api/v1/namespaces/{namespace}/persistentvolumeclaims/{name}/status
```

3.2.53.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 3.3.96, "v1.Persistent VolumeClaim"	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParameter	name	name of the PersistentVolu meClaim	true	string	

3.2.53.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.96, "v1.PersistentVolumeClaim"

3.2.53.3. Consumes

- /

3.2.53.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.53.5. Tags

- apiv1

3.2.54. read status of the specified PersistentVolumeClaim

```
GET /api/v1/namespaces/{namespace}/persistentvolumeclaims/{name}/status
```

3.2.54.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParameter	name	name of the PersistentVolumeClaim	true	string	

3.2.54.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.96, "v1.PersistentVolumeClaim"

3.2.54.3. Consumes

- /

3.2.54.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.54.5. Tags

- apiv1

3.2.55. delete collection of Pod

```
DELETE /api/v1/namespaces/{namespace}/pods
```

3.2.55.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamet er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParamet er	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParamet er	resourceVersio n	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	
QueryParamet er	timeoutSecond s	Timeout for the list/watch call.	false	integer	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	

3.2.55.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.11 , “unversioned.Status”

3.2.55.3. Consumes

- /

3.2.55.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.55.5. Tags

- apiv1

3.2.56. create a Pod

POST /api/v1/namespaces/{namespace}/pods

3.2.56.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 3.3.104, "v1.Pod"	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	

3.2.56.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.104, "v1.Pod"

3.2.56.3. Consumes

- /

3.2.56.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.56.5. Tags

- apiv1

3.2.57. list or watch objects of kind Pod

GET /api/v1/namespaces/{namespace}/pods

3.2.57.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamet er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParamet er	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	
QueryParamet er	resourceVersio n	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	
QueryParamet er	timeoutSecond s	Timeout for the list/watch call.	false	integer	

Type	Name	Description	Required	Schema	Default
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	

3.2.57.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.106, "v1.PodList"

3.2.57.3. Consumes

- /

3.2.57.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.57.5. Tags

- apiv1

3.2.58. delete a Pod

```
DELETE /api/v1/namespaces/{namespace}/pods/{name}
```

3.2.58.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 2.3.61, "v1.DeleteOptions"	

Type	Name	Description	Required	Schema	Default
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParameter	name	name of the Pod	true	string	

3.2.58.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.11 , “unversioned.Status”

3.2.58.3. Consumes

- /

3.2.58.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.58.5. Tags

- apiv1

3.2.59. partially update the specified Pod

```
PATCH /api/v1/namespaces/{namespace}/pods/{name}
```

3.2.59.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	

Type	Name	Description	Required	Schema	Default
BodyParameter	body		true	Section 2.3.10, “unversioned.Patch”	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParameter	name	name of the Pod	true	string	

3.2.59.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.104, “v1.Pod”

3.2.59.3. Consumes

- application/json-patch+json
- application/merge-patch+json
- application/strategic-merge-patch+json

3.2.59.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.59.5. Tags

- apiv1

3.2.60. replace the specified Pod

```
PUT /api/v1/namespaces/{namespace}/pods/{name}
```

3.2.60.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 3.3.10 4, "v1.Pod"	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParameter	name	name of the Pod	true	string	

3.2.60.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.104, "v1.Pod"

3.2.60.3. Consumes

- /

3.2.60.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.60.5. Tags

- apiv1

3.2.61. read the specified Pod

```
GET /api/v1/namespaces/{namespace}/pods/{name}
```

3.2.61.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	export	Should this value be exported. Export strips fields that a user can not specify.	false	boolean	
QueryParamet er	exact	Should the export be exact. Exact export maintains cluster-specific fields like 'Namespace'	false	boolean	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParameter	name	name of the Pod	true	string	

3.2.61.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.104, "v1.Pod"

3.2.61.3. Consumes

- /

3.2.61.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.61.5. Tags

- apiv1

3.2.62. connect POST requests to attach of Pod

POST /api/v1/namespaces/{namespace}/pods/{name}/attach

3.2.62.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	stdin	Stdin if true, redirects the standard input stream of the pod for this call. Defaults to false.	false	boolean	
QueryParamet er	stdout	Stdout if true indicates that stdout is to be redirected for the attach call. Defaults to true.	false	boolean	
QueryParamet er	stderr	Stderr if true indicates that stderr is to be redirected for the attach call. Defaults to true.	false	boolean	
QueryParamet er	tty	TTY if true indicates that a tty will be allocated for the attach call. This is passed through the container runtime so the tty is allocated on the worker node by the container runtime. Defaults to false.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParamter	container	The container in which to execute the command. Defaults to only container if there is only one container in the pod.	false	string	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParameter	name	name of the Pod	true	string	

3.2.62.2. Responses

HTTP Code	Description	Schema
default	success	string

3.2.62.3. Consumes

- /

3.2.62.4. Produces

- /

3.2.62.5. Tags

- apiv1

3.2.63. connect GET requests to attach of Pod

```
GET /api/v1/namespaces/{namespace}/pods/{name}/attach
```

3.2.63.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam er	stdin	Stdin if true, redirects the standard input stream of the pod for this call. Defaults to false.	false	boolean	
QueryParam er	stdout	Stdout if true indicates that stdout is to be redirected for the attach call. Defaults to true.	false	boolean	
QueryParam er	stderr	Stderr if true indicates that stderr is to be redirected for the attach call. Defaults to true.	false	boolean	
QueryParam er	tty	TTY if true indicates that a tty will be allocated for the attach call. This is passed through the container runtime so the tty is allocated on the worker node by the container runtime. Defaults to false.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParamter	container	The container in which to execute the command. Defaults to only container if there is only one container in the pod.	false	string	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParameter	name	name of the Pod	true	string	

3.2.63.2. Responses

HTTP Code	Description	Schema
default	success	string

3.2.63.3. Consumes

- /

3.2.63.4. Produces

- /

3.2.63.5. Tags

- apiv1

3.2.64. create binding of a Binding

```
POST /api/v1/namespaces/{namespace}/pods/{name}/binding
```

3.2.64.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 3.3.15, "v1.Binding"	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParameter	name	name of the Binding	true	string	

3.2.64.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.15, "v1.Binding"

3.2.64.3. Consumes

- /

3.2.64.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.64.5. Tags

- apiv1

3.2.65. connect POST requests to exec of Pod

POST /api/v1/namespaces/{namespace}/pods/{name}/exec

3.2.65.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	stdin	Redirect the standard input stream of the pod for this call. Defaults to false.	false	boolean	
QueryParamet er	stdout	Redirect the standard output stream of the pod for this call. Defaults to true.	false	boolean	
QueryParamet er	stderr	Redirect the standard error stream of the pod for this call. Defaults to true.	false	boolean	
QueryParamet er	tty	TTY if true indicates that a tty will be allocated for the exec call. Defaults to false.	false	boolean	
QueryParamet er	container	Container in which to execute the command. Defaults to only container if there is only one container in the pod.	false	string	
QueryParamet er	command	Command is the remote command to execute. argv array. Not executed within a shell.	false	string	

Type	Name	Description	Required	Schema	Default
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParameter	name	name of the Pod	true	string	

3.2.65.2. Responses

HTTP Code	Description	Schema
default	success	string

3.2.65.3. Consumes

- /

3.2.65.4. Produces

- /

3.2.65.5. Tags

- apiv1

3.2.66. connect GET requests to exec of Pod

```
GET /api/v1/namespaces/{namespace}/pods/{name}/exec
```

3.2.66.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	stdin	Redirect the standard input stream of the pod for this call. Defaults to false.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParamet er	stdout	Redirect the standard output stream of the pod for this call. Defaults to true.	false	boolean	
QueryParamet er	stderr	Redirect the standard error stream of the pod for this call. Defaults to true.	false	boolean	
QueryParamet er	tty	TTY if true indicates that a tty will be allocated for the exec call. Defaults to false.	false	boolean	
QueryParamet er	container	Container in which to execute the command. Defaults to only container if there is only one container in the pod.	false	string	
QueryParamet er	command	Command is the remote command to execute. argv array. Not executed within a shell.	false	string	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	

Type	Name	Description	Required	Schema	Default
PathParameter	name	name of the Pod	true	string	

3.2.66.2. Responses

HTTP Code	Description	Schema
default	success	string

3.2.66.3. Consumes

- /

3.2.66.4. Produces

- /

3.2.66.5. Tags

- apiv1

3.2.67. read log of the specified Pod

GET /api/v1/namespaces/{namespace}/pods/{name}/log

3.2.67.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	container	The container for which to stream logs. Defaults to only container if there is one container in the pod.	false	string	
QueryParamet er	follow	Follow the log stream of the pod. Defaults to false.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParam er	previous	Return previous terminated container logs. Defaults to false.	false	boolean	
QueryParam er	sinceSeconds	A relative time in seconds before the current time from which to show logs. If this value precedes the time a pod was started, only logs since the pod start will be returned. If this value is in the future, no logs will be returned. Only one of sinceSeconds or sinceTime may be specified.	false	integer	
QueryParam er	sinceTime	An RFC3339 timestamp from which to show logs. If this value precedes the time a pod was started, only logs since the pod start will be returned. If this value is in the future, no logs will be returned. Only one of sinceSeconds or sinceTime may be specified.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParamet er	timestamps	If true, add an RFC3339 or RFC3339Nano timestamp at the beginning of every line of log output. Defaults to false.	false	boolean	
QueryParamet er	tailLines	If set, the number of lines from the end of the logs to show. If not specified, logs are shown from the creation of the container or sinceSeconds or sinceTime	false	integer	
QueryParamet er	limitBytes	If set, the number of bytes to read from the server before terminating the log output. This may not display a complete final line of logging, and may return slightly more or slightly less than the specified limit.	false	integer	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParameter	name	name of the Pod	true	string	

3.2.67.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.104, "v1.Pod"

3.2.67.3. Consumes

- /

3.2.67.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.67.5. Tags

- apiv1

3.2.68. connect POST requests to portforward of Pod

POST /api/v1/namespaces/{namespace}/pods/{name}/portforward

3.2.68.1. Parameters

Type	Name	Description	Required	Schema	Default
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParameter	name	name of the Pod	true	string	

3.2.68.2. Responses

HTTP Code	Description	Schema
default	success	string

3.2.68.3. Consumes

- /

3.2.68.4. Produces

- /

3.2.68.5. Tags

- apiv1

3.2.69. connect GET requests to portforward of Pod

GET /api/v1/namespaces/{namespace}/pods/{name}/portforward

3.2.69.1. Parameters

Type	Name	Description	Required	Schema	Default
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParameter	name	name of the Pod	true	string	

3.2.69.2. Responses

HTTP Code	Description	Schema
default	success	string

3.2.69.3. Consumes

- /

3.2.69.4. Produces

- /

3.2.69.5. Tags

- apiv1

3.2.70. connect DELETE requests to proxy of Pod

DELETE /api/v1/namespaces/{namespace}/pods/{name}/proxy

3.2.70.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	path	Path is the URL path to use for the current proxy request to pod.	false	string	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParameter	name	name of the Pod	true	string	

3.2.70.2. Responses

HTTP Code	Description	Schema
default	success	string

3.2.70.3. Consumes

- /

3.2.70.4. Produces

- /

3.2.70.5. Tags

- apiv1

3.2.71. connect OPTIONS requests to proxy of Pod

```
OPTIONS /api/v1/namespaces/{namespace}/pods/{name}/proxy
```

3.2.71.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	path	Path is the URL path to use for the current proxy request to pod.	false	string	

Type	Name	Description	Required	Schema	Default
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParameter	name	name of the Pod	true	string	

3.2.71.2. Responses

HTTP Code	Description	Schema
default	success	string

3.2.71.3. Consumes

- /

3.2.71.4. Produces

- /

3.2.71.5. Tags

- apiv1

3.2.72. connect POST requests to proxy of Pod

POST /api/v1/namespaces/{namespace}/pods/{name}/proxy

3.2.72.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	path	Path is the URL path to use for the current proxy request to pod.	false	string	

Type	Name	Description	Required	Schema	Default
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParameter	name	name of the Pod	true	string	

3.2.72.2. Responses

HTTP Code	Description	Schema
default	success	string

3.2.72.3. Consumes

- /

3.2.72.4. Produces

- /

3.2.72.5. Tags

- apiv1

3.2.73. connect PUT requests to proxy of Pod

PUT /api/v1/namespaces/{namespace}/pods/{name}/proxy

3.2.73.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	path	Path is the URL path to use for the current proxy request to pod.	false	string	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	

Type	Name	Description	Required	Schema	Default
PathParameter	name	name of the Pod	true	string	

3.2.73.2. Responses

HTTP Code	Description	Schema
default	success	string

3.2.73.3. Consumes

- /

3.2.73.4. Produces

- /

3.2.73.5. Tags

- apiv1

3.2.74. connect GET requests to proxy of Pod

GET /api/v1/namespaces/{namespace}/pods/{name}/proxy

3.2.74.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	path	Path is the URL path to use for the current proxy request to pod.	false	string	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParameter	name	name of the Pod	true	string	

3.2.74.2. Responses

HTTP Code	Description	Schema
default	success	string

3.2.74.3. Consumes

- /

3.2.74.4. Produces

- /

3.2.74.5. Tags

- apiv1

3.2.75. connect HEAD requests to proxy of Pod

HEAD /api/v1/namespaces/{namespace}/pods/{name}/proxy

3.2.75.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	path	Path is the URL path to use for the current proxy request to pod.	false	string	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParameter	name	name of the Pod	true	string	

3.2.75.2. Responses

HTTP Code	Description	Schema
default	success	string

3.2.75.3. Consumes

- /

3.2.75.4. Produces

- /

3.2.75.5. Tags

- apiv1

3.2.76. connect DELETE requests to proxy of Pod

```
DELETE /api/v1/namespaces/{namespace}/pods/{name}/proxy/{path}
```

3.2.76.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	path	Path is the URL path to use for the current proxy request to pod.	false	string	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParameter	name	name of the Pod	true	string	
PathParameter	path	path to the resource	true	string	

3.2.76.2. Responses

HTTP Code	Description	Schema
default	success	string

3.2.76.3. Consumes

- /

3.2.76.4. Produces

- /

3.2.76.5. Tags

- apiv1

3.2.77. connect OPTIONS requests to proxy of Pod

`OPTIONS /api/v1/namespaces/{namespace}/pods/{name}/proxy/{path}`

3.2.77.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	path	Path is the URL path to use for the current proxy request to pod.	false	string	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParameter	name	name of the Pod	true	string	
PathParameter	path	path to the resource	true	string	

3.2.77.2. Responses

HTTP Code	Description	Schema
default	success	string

3.2.77.3. Consumes

- /

3.2.77.4. Produces

- /

3.2.77.5. Tags

- apiv1

3.2.78. connect POST requests to proxy of Pod

POST /api/v1/namespaces/{namespace}/pods/{name}/proxy/{path}

3.2.78.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	path	Path is the URL path to use for the current proxy request to pod.	false	string	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParameter	name	name of the Pod	true	string	
PathParameter	path	path to the resource	true	string	

3.2.78.2. Responses

HTTP Code	Description	Schema
default	success	string

3.2.78.3. Consumes

- /

3.2.78.4. Produces

- /

3.2.78.5. Tags

- apiv1

3.2.79. connect PUT requests to proxy of Pod

PUT /api/v1/namespaces/{namespace}/pods/{name}/proxy/{path}

3.2.79.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	path	Path is the URL path to use for the current proxy request to pod.	false	string	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParameter	name	name of the Pod	true	string	
PathParameter	path	path to the resource	true	string	

3.2.79.2. Responses

HTTP Code	Description	Schema
default	success	string

3.2.79.3. Consumes

- /

3.2.79.4. Produces

- /

3.2.79.5. Tags

- apiv1

3.2.80. connect GET requests to proxy of Pod

```
GET /api/v1/namespaces/{namespace}/pods/{name}/proxy/{path}
```

3.2.80.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamter	path	Path is the URL path to use for the current proxy request to pod.	false	string	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParameter	name	name of the Pod	true	string	
PathParameter	path	path to the resource	true	string	

3.2.80.2. Responses

HTTP Code	Description	Schema
default	success	string

3.2.80.3. Consumes

- /

3.2.80.4. Produces

- /

3.2.80.5. Tags

- apiv1

3.2.81. connect HEAD requests to proxy of Pod

```
HEAD /api/v1/namespaces/{namespace}/pods/{name}/proxy/{path}
```

3.2.81.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamter	path	Path is the URL path to use for the current proxy request to pod.	false	string	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParameter	name	name of the Pod	true	string	
PathParameter	path	path to the resource	true	string	

3.2.81.2. Responses

HTTP Code	Description	Schema
default	success	string

3.2.81.3. Consumes

- /

3.2.81.4. Produces

- /

3.2.81.5. Tags

- apiv1

3.2.82. partially update status of the specified Pod

```
PATCH /api/v1/namespaces/{namespace}/pods/{name}/status
```

3.2.82.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 2.3.10, “unversioned.Patch”	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParameter	name	name of the Pod	true	string	

3.2.82.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.104, “v1.Pod”

3.2.82.3. Consumes

- application/json-patch+json
- application/merge-patch+json
- application/strategic-merge-patch+json

3.2.82.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.82.5. Tags

- apiv1

3.2.83. replace status of the specified Pod

```
PUT /api/v1/namespaces/{namespace}/pods/{name}/status
```

3.2.83.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 3.3.104, "v1.Pod"	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParameter	name	name of the Pod	true	string	

3.2.83.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.104, "v1.Pod"

3.2.83.3. Consumes

- /

3.2.83.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.83.5. Tags

- apiv1

3.2.84. read status of the specified Pod

```
GET /api/v1/namespaces/{namespace}/pods/{name}/status
```

3.2.84.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParameter	name	name of the Pod	true	string	

3.2.84.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.104, "v1.Pod"

3.2.84.3. Consumes

- /

3.2.84.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.84.5. Tags

- apiv1

3.2.85. delete collection of PodTemplate

```
DELETE /api/v1/namespaces/{namespace}/podtemplates
```

3.2.85.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParamet er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamet er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParamet er	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	
QueryParamet er	resourceVersio n	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	
QueryParamet er	timeoutSecond s	Timeout for the list/watch call.	false	integer	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	

3.2.85.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.11 , “unversioned.Status”

3.2.85.3. Consumes

- /

3.2.85.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.85.5. Tags

- apiv1

3.2.86. create a PodTemplate

POST /api/v1/namespaces/{namespace}/podtemplates

3.2.86.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 3.3.110 , “v1.PodTempl ate”	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	

3.2.86.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.110, "v1.PodTemplate"

3.2.86.3. Consumes

- /

3.2.86.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.86.5. Tags

- apiv1

3.2.87. list or watch objects of kind PodTemplate

```
GET /api/v1/namespaces/{namespace}/podtemplates
```

3.2.87.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamet er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParameter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	
QueryParameter	resourceVersion	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	
QueryParameter	timeoutSeconds	Timeout for the list/watch call.	false	integer	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	

3.2.87.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.111 , "v1.PodTemplateList"

3.2.87.3. Consumes

- /

3.2.87.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.87.5. Tags

- apiv1

3.2.88. delete a PodTemplate

```
DELETE /api/v1/namespaces/{namespace}/podtemplates/{name}
```

3.2.88.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParameter	body		true	Section 2.3.61, "v1.DeleteOptions"	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParameter	name	name of the PodTemplate	true	string	

3.2.88.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.11, "unversioned.Status"

3.2.88.3. Consumes

- /

3.2.88.4. Produces

- application/json

- application/yaml
- application/vnd.kubernetes.protobuf

3.2.88.5. Tags

- apiv1

3.2.89. partially update the specified PodTemplate

PATCH /api/v1/namespaces/{namespace}/podtemplates/{name}

3.2.89.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 2.3.10, “unversioned.Patch”	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParameter	name	name of the PodTemplate	true	string	

3.2.89.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.110, “v1.PodTemplate”

3.2.89.3. Consumes

- application/json-patch+json
- application/merge-patch+json
- application/strategic-merge-patch+json

3.2.89.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.89.5. Tags

- apiv1

3.2.90. replace the specified PodTemplate

```
PUT /api/v1/namespaces/{namespace}/podtemplates/{name}
```

3.2.90.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParameter	body		true	Section 3.3.110 , "v1.PodTemplate"	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParameter	name	name of the PodTemplate	true	string	

3.2.90.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.110 , "v1.PodTemplate"

3.2.90.3. Consumes

- /

3.2.90.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.90.5. Tags

- apiv1

3.2.91. read the specified PodTemplate

```
GET /api/v1/namespaces/{namespace}/podtemplates/{name}
```

3.2.91.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	export	Should this value be exported. Export strips fields that a user can not specify.	false	boolean	
QueryParamet er	exact	Should the export be exact. Exact export maintains cluster-specific fields like 'Namespace'	false	boolean	
PathParamet er	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParamet er	name	name of the PodTemplate	true	string	

3.2.91.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.110, "v1.PodTemplate"

3.2.91.3. Consumes

- /

3.2.91.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.91.5. Tags

- apiv1

3.2.92. delete collection of ReplicationController

```
DELETE /api/v1/namespaces/{namespace}/replicationcontrollers
```

3.2.92.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamet er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParameter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	
QueryParameter	resourceVersion	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	
QueryParameter	timeoutSeconds	Timeout for the list/watch call.	false	integer	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	

3.2.92.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.11 , “unversioned.Status”

3.2.92.3. Consumes

- /

3.2.92.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.92.5. Tags

- apiv1

3.2.93. create a ReplicationController

POST /api/v1/namespaces/{namespace}/replicationcontrollers

3.2.93.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParameter	body		true	Section 3.3.116 , "v1.ReplicationController"	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	

3.2.93.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.116 , "v1.ReplicationController"

3.2.93.3. Consumes

- /

3.2.93.4. Produces

- application/json
- application/yaml

- application/vnd.kubernetes.protobuf

3.2.93.5. Tags

- apiv1

3.2.94. list or watch objects of kind ReplicationController

GET /api/v1/namespaces/{namespace}/replicationcontrollers

3.2.94.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamet er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParamet er	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParamter	resourceVersion	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	
QueryParamter	timeoutSeconds	Timeout for the list/watch call.	false	integer	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	

3.2.94.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.117 , “v1.ReplicationControllerList”

3.2.94.3. Consumes

- /

3.2.94.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.94.5. Tags

- apiv1

3.2.95. delete a ReplicationController

```
DELETE /api/v1/namespaces/{namespace}/replicationcontrollers/{name}
```

3.2.95.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 2.3.61, "v1.DeleteOptions"	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParameter	name	name of the ReplicationController	true	string	

3.2.95.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.11, "unversioned.Status"

3.2.95.3. Consumes

- /

3.2.95.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.95.5. Tags

- apiv1

3.2.96. partially update the specified ReplicationController

```
PATCH /api/v1/namespaces/{namespace}/replicationcontrollers/{name}
```

3.2.96.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 2.3.10, “unversioned.Patch”	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParameter	name	name of the ReplicationCon troller	true	string	

3.2.96.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.116, “v1.ReplicationController”

3.2.96.3. Consumes

- application/json-patch+json
- application/merge-patch+json
- application/strategic-merge-patch+json

3.2.96.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.96.5. Tags

- apiv1

3.2.97. replace the specified ReplicationController

```
PUT /api/v1/namespaces/{namespace}/replicationcontrollers/{name}
```

3.2.97.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 3.3.116 , "v1.Replication Controller"	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParameter	name	name of the ReplicationCon troller	true	string	

3.2.97.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.116 , "v1.ReplicationController"

3.2.97.3. Consumes

- /

3.2.97.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.97.5. Tags

- apiv1

3.2.98. read the specified ReplicationController

GET /api/v1/namespaces/{namespace}/replicationcontrollers/{name}

3.2.98.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	export	Should this value be exported. Export strips fields that a user can not specify.	false	boolean	
QueryParamet er	exact	Should the export be exact. Exact export maintains cluster-specific fields like 'Namespace'	false	boolean	
PathParamet er	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParamet er	name	name of the ReplicationCon troller	true	string	

3.2.98.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.116, "v1.ReplicationController"

3.2.98.3. Consumes

- /

3.2.98.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.98.5. Tags

- apiv1

3.2.99. partially update scale of the specified Scale

PATCH /api/v1/namespaces/{namespace}/replicationcontrollers/{name}/scale

3.2.99.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 2.3.10, “unversioned.Patch”	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParameter	name	name of the Scale	true	string	

3.2.99.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.130, “v1.Scale”

3.2.99.3. Consumes

- application/json-patch+json
- application/merge-patch+json
- application/strategic-merge-patch+json

3.2.99.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.99.5. Tags

- apiv1

3.2.100. replace scale of the specified Scale

```
PUT /api/v1/namespaces/{namespace}/replicationcontrollers/{name}/scale
```

3.2.100.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 3.3.130, "v1.Scale"	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParameter	name	name of the Scale	true	string	

3.2.100.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.130, "v1.Scale"

3.2.100.3. Consumes

- /

3.2.100.4. Produces

- application/json

- application/yaml
- application/vnd.kubernetes.protobuf

3.2.100.5. Tags

- apiv1

3.2.101. read scale of the specified Scale

```
GET /api/v1/namespaces/{namespace}/replicationcontrollers/{name}/scale
```

3.2.101.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParameter	name	name of the Scale	true	string	

3.2.101.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.130, "v1.Scale"

3.2.101.3. Consumes

- /

3.2.101.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.101.5. Tags

- apiv1

3.2.102. partially update status of the specified ReplicationController

PATCH /api/v1/namespaces/{namespace}/replicationcontrollers/{name}/status

3.2.102.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 2.3.10, "unversioned.Patch"	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParameter	name	name of the ReplicationController	true	string	

3.2.102.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.116, "v1.ReplicationController"

3.2.102.3. Consumes

- application/json-patch+json
- application/merge-patch+json
- application/strategic-merge-patch+json

3.2.102.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.102.5. Tags

- apiv1

3.2.103. replace status of the specified ReplicationController

```
PUT /api/v1/namespaces/{namespace}/replicationcontrollers/{name}/status
```

3.2.103.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 3.3.116 , "v1.Replication Controller"	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParameter	name	name of the ReplicationCon troller	true	string	

3.2.103.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.116 , "v1.ReplicationController"

3.2.103.3. Consumes

- /

3.2.103.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.103.5. Tags

- apiv1

3.2.104. read status of the specified ReplicationController

```
GET /api/v1/namespaces/{namespace}/replicationcontrollers/{name}/status
```

3.2.104.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParameter	name	name of the ReplicationCon troller	true	string	

3.2.104.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.116 , "v1.ReplicationController"

3.2.104.3. Consumes

- /

3.2.104.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.104.5. Tags

- apiv1

3.2.105. delete collection of ResourceQuota

```
DELETE /api/v1/namespaces/{namespace}/resourcequotas
```

3.2.105.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamet er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParamet er	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	
QueryParamet er	resourceVersio n	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParamet er	timeoutSecond s	Timeout for the list/watch call.	false	integer	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	

3.2.105.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.11 , “unversioned.Status”

3.2.105.3. Consumes

- /

3.2.105.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.105.5. Tags

- apiv1

3.2.106. create a ResourceQuota

POST /api/v1/namespaces/{namespace}/resourcequotas

3.2.106.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	

Type	Name	Description	Required	Schema	Default
BodyParameter	body		true	Section 3.3.121 , "v1.ResourceQuota"	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	

3.2.106.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.121 , "v1.ResourceQuota"

3.2.106.3. Consumes

- /

3.2.106.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.106.5. Tags

- apiv1

3.2.107. list or watch objects of kind ResourceQuota

```
GET /api/v1/namespaces/{namespace}/resourcequotas
```

3.2.107.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamter	pretty	If 'true', then the output is pretty printed.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParamet er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamet er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParamet er	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersio n.	false	boolean	
QueryParamet er	resourceVersio n	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	
QueryParamet er	timeoutSecond s	Timeout for the list/watch call.	false	integer	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	

3.2.107.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.122 , “v1.ResourceQuotaList”

3.2.107.3. Consumes

- /

3.2.107.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.107.5. Tags

- apiv1

3.2.108. delete a ResourceQuota

```
DELETE /api/v1/namespaces/{namespace}/resourcequotas/{name}
```

3.2.108.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 2.3.61 , “v1.DeleteOpti ons”	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParameter	name	name of the ResourceQuota	true	string	

3.2.108.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.11 , “unversioned.Status”

3.2.108.3. Consumes

- /

3.2.108.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.108.5. Tags

- apiv1

3.2.109. partially update the specified ResourceQuota

PATCH /api/v1/namespaces/{namespace}/resourcequotas/{name}

3.2.109.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 2.3.10 , “unversioned.P atch”	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParameter	name	name of the ResourceQuota	true	string	

3.2.109.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.121 , “v1.ResourceQuota”

3.2.109.3. Consumes

- application/json-patch+json
- application/merge-patch+json
- application/strategic-merge-patch+json

3.2.109.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.109.5. Tags

- apiv1

3.2.110. replace the specified ResourceQuota

```
PUT /api/v1/namespaces/{namespace}/resourcequotas/{name}
```

3.2.110.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 3.3.121 , “v1.ResourceQ uota”	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	

Type	Name	Description	Required	Schema	Default
PathParameter	name	name of the ResourceQuota	true	string	

3.2.110.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.121, "v1.ResourceQuota"

3.2.110.3. Consumes

- /

3.2.110.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.110.5. Tags

- apiv1

3.2.111. read the specified ResourceQuota

```
GET /api/v1/namespaces/{namespace}/resourcequotas/{name}
```

3.2.111.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParameter	export	Should this value be exported. Export strips fields that a user can not specify.	false	boolean	
QueryParameter	exact	Should the export be exact. Exact export maintains cluster-specific fields like 'Namespace'	false	boolean	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParameter	name	name of the ResourceQuota	true	string	

3.2.111.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.121, "v1.ResourceQuota"

3.2.111.3. Consumes

- /

3.2.111.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.111.5. Tags

- apiv1

3.2.112. partially update status of the specified ResourceQuota

```
PATCH /api/v1/namespaces/{namespace}/resourcequotas/{name}/status
```

3.2.112.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 2.3.10, "unversioned.Patch"	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParameter	name	name of the ResourceQuota	true	string	

3.2.112.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.121, "v1.ResourceQuota"

3.2.112.3. Consumes

- application/json-patch+json
- application/merge-patch+json
- application/strategic-merge-patch+json

3.2.112.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.112.5. Tags

- apiv1

3.2.113. replace status of the specified ResourceQuota

```
PUT /api/v1/namespaces/{namespace}/resourcequotas/{name}/status
```

3.2.113.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 3.3.121 , "v1.ResourceQ uota"	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParameter	name	name of the ResourceQuota	true	string	

3.2.113.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.121 , "v1.ResourceQuota"

3.2.113.3. Consumes

- /

3.2.113.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.113.5. Tags

- apiv1

3.2.114. read status of the specified ResourceQuota

GET /api/v1/namespaces/{namespace}/resourcequotas/{name}/status

3.2.114.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParameter	name	name of the ResourceQuota	true	string	

3.2.114.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.121, "v1.ResourceQuota"

3.2.114.3. Consumes

- /

3.2.114.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.114.5. Tags

- apiv1

3.2.115. delete collection of Secret


```
DELETE /api/v1/namespaces/{namespace}/secrets
```

3.2.115.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamet er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParamet er	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	
QueryParamet er	resourceVersio n	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	
QueryParamet er	timeoutSecond s	Timeout for the list/watch call.	false	integer	

Type	Name	Description	Required	Schema	Default
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	

3.2.115.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.11 , “unversioned.Status”

3.2.115.3. Consumes

- /

3.2.115.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.115.5. Tags

- apiv1

3.2.116. create a Secret

POST /api/v1/namespaces/{namespace}/secrets

3.2.116.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 2.3.204 , “v1.Secret”	

Type	Name	Description	Required	Schema	Default
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	

3.2.116.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.204, "v1.Secret"

3.2.116.3. Consumes

- /

3.2.116.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.116.5. Tags

- apiv1

3.2.117. list or watch objects of kind Secret

```
GET /api/v1/namespaces/{namespace}/secrets
```

3.2.117.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParamet er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamet er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParamet er	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersio n.	false	boolean	
QueryParamet er	resourceVersio n	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	
QueryParamet er	timeoutSecond s	Timeout for the list/watch call.	false	integer	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	

3.2.117.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.207, "v1.SecretList"

3.2.117.3. Consumes

- /

3.2.117.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.117.5. Tags

- apiv1

3.2.118. delete a Secret

```
DELETE /api/v1/namespaces/{namespace}/secrets/{name}
```

3.2.118.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 2.3.61, "v1.DeleteOptions"	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParameter	name	name of the Secret	true	string	

3.2.118.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.11 , “unversioned.Status”

3.2.118.3. Consumes

- /

3.2.118.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.118.5. Tags

- apiv1

3.2.119. partially update the specified Secret

```
PATCH /api/v1/namespaces/{namespace}/secrets/{name}
```

3.2.119.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 2.3.10 , “unversioned.P atch”	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParameter	name	name of the Secret	true	string	

3.2.119.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.204, "v1.Secret"

3.2.119.3. Consumes

- application/json-patch+json
- application/merge-patch+json
- application/strategic-merge-patch+json

3.2.119.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.119.5. Tags

- apiv1

3.2.120. replace the specified Secret

```
PUT /api/v1/namespaces/{namespace}/secrets/{name}
```

3.2.120.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 2.3.204, "v1.Secret"	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParameter	name	name of the Secret	true	string	

3.2.120.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.204, "v1.Secret"

3.2.120.3. Consumes

- /

3.2.120.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.120.5. Tags

- apiv1

3.2.121. read the specified Secret

```
GET /api/v1/namespaces/{namespace}/secrets/{name}
```

3.2.121.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	export	Should this value be exported. Export strips fields that a user can not specify.	false	boolean	
QueryParamet er	exact	Should the export be exact. Exact export maintains cluster-specific fields like 'Namespace'	false	boolean	

Type	Name	Description	Required	Schema	Default
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParameter	name	name of the Secret	true	string	

3.2.121.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.204, "v1.Secret"

3.2.121.3. Consumes

- /

3.2.121.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.121.5. Tags

- apiv1

3.2.122. delete collection of ServiceAccount

```
DELETE /api/v1/namespaces/{namespace}/serviceaccounts
```

3.2.122.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParamet er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamet er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParamet er	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	
QueryParamet er	resourceVersio n	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	
QueryParamet er	timeoutSecond s	Timeout for the list/watch call.	false	integer	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	

3.2.122.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.11 , “unversioned.Status”

3.2.122.3. Consumes

- /

3.2.122.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.122.5. Tags

- apiv1

3.2.123. create a ServiceAccount

POST /api/v1/namespaces/{namespace}/serviceaccounts

3.2.123.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 3.3.14 1, “v1.ServiceAcc ount”	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	

3.2.123.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.141 , "v1.ServiceAccount"

3.2.123.3. Consumes

- /

3.2.123.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.123.5. Tags

- apiv1

3.2.124. list or watch objects of kind ServiceAccount

```
GET /api/v1/namespaces/{namespace}/serviceaccounts
```

3.2.124.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamet er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParamet er	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersio n.	false	boolean	
QueryParamet er	resourceVersio n	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	
QueryParamet er	timeoutSecond s	Timeout for the list/watch call.	false	integer	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	

3.2.124.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.142 , “v1.ServiceAccountList”

3.2.124.3. Consumes

- /

3.2.124.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.124.5. Tags

- apiv1

3.2.125. delete a ServiceAccount

```
DELETE /api/v1/namespaces/{namespace}/serviceaccounts/{name}
```

3.2.125.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParameter	body		true	Section 2.3.61 , "v1.DeleteOptions"	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParameter	name	name of the ServiceAccount	true	string	

3.2.125.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.11 , "unversioned.Status"

3.2.125.3. Consumes

- /

3.2.125.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.125.5. Tags

- apiv1

3.2.126. partially update the specified ServiceAccount

PATCH /api/v1/namespaces/{namespace}/serviceaccounts/{name}

3.2.126.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParameter	body		true	Section 2.3.10, "unversioned.Patch"	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParameter	name	name of the ServiceAccount	true	string	

3.2.126.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.141, "v1.ServiceAccount"

3.2.126.3. Consumes

- application/json-patch+json
- application/merge-patch+json
- application/strategic-merge-patch+json

3.2.126.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.126.5. Tags

- apiv1

3.2.127. replace the specified ServiceAccount

```
PUT /api/v1/namespaces/{namespace}/serviceaccounts/{name}
```

3.2.127.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 3.3.141 , "v1.ServiceAccount"	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParameter	name	name of the ServiceAccount	true	string	

3.2.127.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.141 , "v1.ServiceAccount"

3.2.127.3. Consumes

- /

3.2.127.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.127.5. Tags

- apiv1

3.2.128. read the specified ServiceAccount

```
GET /api/v1/namespaces/{namespace}/serviceaccounts/{name}
```

3.2.128.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	export	Should this value be exported. Export strips fields that a user can not specify.	false	boolean	
QueryParamet er	exact	Should the export be exact. Exact export maintains cluster-specific fields like 'Namespace'	false	boolean	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParameter	name	name of the ServiceAccount	true	string	

3.2.128.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.141 , "v1.ServiceAccount"

3.2.128.3. Consumes

- /

3.2.128.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.128.5. Tags

- apiv1

3.2.129. create a Service

POST /api/v1/namespaces/{namespace}/services

3.2.129.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 3.3.140 , "v1.Service"	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	

3.2.129.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.140, "v1.Service"

3.2.129.3. Consumes

- /

3.2.129.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.129.5. Tags

- apiv1

3.2.130. list or watch objects of kind Service

GET /api/v1/namespaces/{namespace}/services

3.2.130.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamet er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParamet er	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersio n.	false	boolean	
QueryParamet er	resourceVersio n	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	
QueryParamet er	timeoutSecond s	Timeout for the list/watch call.	false	integer	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	

3.2.130.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.143, "v1.ServiceList"

3.2.130.3. Consumes

- /

3.2.130.4. Produces

- application/json

- application/yaml
- application/vnd.kubernetes.protobuf

3.2.130.5. Tags

- apiv1

3.2.131. delete a Service

```
DELETE /api/v1/namespaces/{namespace}/services/{name}
```

3.2.131.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParameter	name	name of the Service	true	string	

3.2.131.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.11, "unversioned.Status"

3.2.131.3. Consumes

- /

3.2.131.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.131.5. Tags

- apiv1

3.2.132. partially update the specified Service

PATCH /api/v1/namespaces/{namespace}/services/{name}

3.2.132.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 2.3.10, "unversioned.Patch"	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParameter	name	name of the Service	true	string	

3.2.132.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.140, "v1.Service"

3.2.132.3. Consumes

- application/json-patch+json
- application/merge-patch+json
- application/strategic-merge-patch+json

3.2.132.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.132.5. Tags

- apiv1

3.2.133. replace the specified Service

```
PUT /api/v1/namespaces/{namespace}/services/{name}
```

3.2.133.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 3.3.140, "v1.Service"	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParameter	name	name of the Service	true	string	

3.2.133.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.140, "v1.Service"

3.2.133.3. Consumes

- /

3.2.133.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.133.5. Tags

- apiv1

3.2.134. read the specified Service

```
GET /api/v1/namespaces/{namespace}/services/{name}
```

3.2.134.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	export	Should this value be exported. Export strips fields that a user can not specify.	false	boolean	
QueryParamet er	exact	Should the export be exact. Exact export maintains cluster-specific fields like 'Namespace'	false	boolean	
PathParamet er	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParamet er	name	name of the Service	true	string	

3.2.134.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.140, "v1.Service"

3.2.134.3. Consumes

- /

3.2.134.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.134.5. Tags

- apiv1

3.2.135. connect DELETE requests to proxy of Service

```
DELETE /api/v1/namespaces/{namespace}/services/{name}/proxy
```

3.2.135.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	path	Path is the part of URLs that include service endpoints, suffixes, and parameters to use for the current proxy request to service. For example, the whole request URL is http://localhost/api/v1/namespaces/kube-system/services/elasticsearch-logging/_search?q=user:kimchy . Path is <code>_search?q=user:kimchy</code> .	false	string	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParameter	name	name of the Service	true	string	

3.2.135.2. Responses

HTTP Code	Description	Schema
default	success	string

3.2.135.3. Consumes

- /

3.2.135.4. Produces

- /

3.2.135.5. Tags

- apiv1

3.2.136. connect OPTIONS requests to proxy of Service

OPTIONS /api/v1/namespaces/{namespace}/services/{name}/proxy

3.2.136.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	path	Path is the part of URLs that include service endpoints, suffixes, and parameters to use for the current proxy request to service. For example, the whole request URL is http://localhost/api/v1/namespaces/kube-system/services/elasticsearch-logging/_search?q=user:kimchy . Path is <code>_search?q=user:kimchy</code> .	false	string	

Type	Name	Description	Required	Schema	Default
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParameter	name	name of the Service	true	string	

3.2.136.2. Responses

HTTP Code	Description	Schema
default	success	string

3.2.136.3. Consumes

- /

3.2.136.4. Produces

- /

3.2.136.5. Tags

- apiv1

3.2.137. connect POST requests to proxy of Service

```
POST /api/v1/namespaces/{namespace}/services/{name}/proxy
```

3.2.137.1. Parameters

Type	Name	Description	Required	Schema	Default
------	------	-------------	----------	--------	---------

Type	Name	Description	Required	Schema	Default
QueryParam er	path	Path is the part of URLs that include service endpoints, suffixes, and parameters to use for the current proxy request to service. For example, the whole request URL is http://localhost/api/v1/namespaces/kube-system/services/elasticsearch-logging/_search?q=user:kimchy . Path is <code>_search?q=user:kimchy</code> .	false	string	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParameter	name	name of the Service	true	string	

3.2.137.2. Responses

HTTP Code	Description	Schema
default	success	string

3.2.137.3. Consumes

- /

3.2.137.4. Produces

- /

3.2.137.5. Tags

- apiv1

3.2.138. connect PUT requests to proxy of Service

```
PUT /api/v1/namespaces/{namespace}/services/{name}/proxy
```

3.2.138.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	path	Path is the part of URLs that include service endpoints, suffixes, and parameters to use for the current proxy request to service. For example, the whole request URL is http://localhost/api/v1/namespaces/kube-system/services/elasticsearch-logging/_search?q=user:kimchy . Path is <code>_search?q=user:kimchy</code> .	false	string	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParameter	name	name of the Service	true	string	

3.2.138.2. Responses

HTTP Code	Description	Schema
default	success	string

3.2.138.3. Consumes

- /

3.2.138.4. Produces

- /

3.2.138.5. Tags

- apiv1

3.2.139. connect GET requests to proxy of Service

GET /api/v1/namespaces/{namespace}/services/{name}/proxy

3.2.139.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	path	Path is the part of URLs that include service endpoints, suffixes, and parameters to use for the current proxy request to service. For example, the whole request URL is http://localhost/api/v1/namespaces/kube-system/services/elasticsearch-logging/_search?q=user:kimchy . Path is <code>_search?q=user:kimchy</code> .	false	string	

Type	Name	Description	Required	Schema	Default
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParameter	name	name of the Service	true	string	

3.2.139.2. Responses

HTTP Code	Description	Schema
default	success	string

3.2.139.3. Consumes

- /

3.2.139.4. Produces

- /

3.2.139.5. Tags

- apiv1

3.2.140. connect HEAD requests to proxy of Service

```
HEAD /api/v1/namespaces/{namespace}/services/{name}/proxy
```

3.2.140.1. Parameters

Type	Name	Description	Required	Schema	Default
------	------	-------------	----------	--------	---------

Type	Name	Description	Required	Schema	Default
QueryParamet er	path	Path is the part of URLs that include service endpoints, suffixes, and parameters to use for the current proxy request to service. For example, the whole request URL is http://localhost/api/v1/namespaces/kube-system/services/elasticsearch-logging/_search?q=user:kimchy . Path is <code>_search?q=user:kimchy</code> .	false	string	
PathParamet er	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParamet er	name	name of the Service	true	string	

3.2.140.2. Responses

HTTP Code	Description	Schema
default	success	string

3.2.140.3. Consumes

- /

3.2.140.4. Produces

- /

3.2.140.5. Tags

- apiv1

3.2.141. connect DELETE requests to proxy of Service

```
DELETE /api/v1/namespaces/{namespace}/services/{name}/proxy/{path}
```

3.2.141.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	path	Path is the part of URLs that include service endpoints, suffixes, and parameters to use for the current proxy request to service. For example, the whole request URL is http://localhost/api/v1/namespaces/kube-system/services/elasticsearch-logging/_search?q=user:kimchy . Path is <code>_search?q=user:kimchy</code> .	false	string	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParameter	name	name of the Service	true	string	
PathParameter	path	path to the resource	true	string	

3.2.141.2. Responses

HTTP Code	Description	Schema
default	success	string

3.2.141.3. Consumes

- /

3.2.141.4. Produces

- /

3.2.141.5. Tags

- apiv1

3.2.142. connect OPTIONS requests to proxy of Service

`OPTIONS /api/v1/namespaces/{namespace}/services/{name}/proxy/{path}`

3.2.142.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	path	Path is the part of URLs that include service endpoints, suffixes, and parameters to use for the current proxy request to service. For example, the whole request URL is http://localhost/api/v1/namespaces/kube-system/services/elasticsearch-logging/_search?q=user:kimchy . Path is <code>_search?q=user:kimchy</code> .	false	string	

Type	Name	Description	Required	Schema	Default
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParameter	name	name of the Service	true	string	
PathParameter	path	path to the resource	true	string	

3.2.142.2. Responses

HTTP Code	Description	Schema
default	success	string

3.2.142.3. Consumes

- /

3.2.142.4. Produces

- /

3.2.142.5. Tags

- apiv1

3.2.143. connect POST requests to proxy of Service

```
POST /api/v1/namespaces/{namespace}/services/{name}/proxy/{path}
```

3.2.143.1. Parameters

Type	Name	Description	Required	Schema	Default
------	------	-------------	----------	--------	---------

Type	Name	Description	Required	Schema	Default
QueryParamet er	path	Path is the part of URLs that include service endpoints, suffixes, and parameters to use for the current proxy request to service. For example, the whole request URL is http://localhost/api/v1/namespaces/kube-system/services/elasticsearch-logging/_search?q=user:kimchy . Path is <code>_search?q=user:kimchy</code> .	false	string	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParameter	name	name of the Service	true	string	
PathParameter	path	path to the resource	true	string	

3.2.143.2. Responses

HTTP Code	Description	Schema
default	success	string

3.2.143.3. Consumes

- /

3.2.143.4. Produces

- /

3.2.143.5. Tags

- apiv1

3.2.144. connect PUT requests to proxy of Service

```
PUT /api/v1/namespaces/{namespace}/services/{name}/proxy/{path}
```

3.2.144.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	path	Path is the part of URLs that include service endpoints, suffixes, and parameters to use for the current proxy request to service. For example, the whole request URL is http://localhost/api/v1/namespaces/kube-system/services/elasticsearch-logging/_search?q=user:kimchy . Path is <code>_search?q=user:kimchy</code> .	false	string	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParameter	name	name of the Service	true	string	

Type	Name	Description	Required	Schema	Default
PathParameter	path	path to the resource	true	string	

3.2.144.2. Responses

HTTP Code	Description	Schema
default	success	string

3.2.144.3. Consumes

- /

3.2.144.4. Produces

- /

3.2.144.5. Tags

- apiv1

3.2.145. connect GET requests to proxy of Service

```
GET /api/v1/namespaces/{namespace}/services/{name}/proxy/{path}
```

3.2.145.1. Parameters

Type	Name	Description	Required	Schema	Default
------	------	-------------	----------	--------	---------

Type	Name	Description	Required	Schema	Default
QueryParam er	path	Path is the part of URLs that include service endpoints, suffixes, and parameters to use for the current proxy request to service. For example, the whole request URL is http://localhost/api/v1/namespaces/kube-system/services/elasticsearch-logging/_search?q=user:kimchy . Path is <code>_search?q=user:kimchy</code> .	false	string	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParameter	name	name of the Service	true	string	
PathParameter	path	path to the resource	true	string	

3.2.145.2. Responses

HTTP Code	Description	Schema
default	success	string

3.2.145.3. Consumes

- /

3.2.145.4. Produces

- /

3.2.145.5. Tags

- apiv1

3.2.146. connect HEAD requests to proxy of Service

```
HEAD /api/v1/namespaces/{namespace}/services/{name}/proxy/{path}
```

3.2.146.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	path	Path is the part of URLs that include service endpoints, suffixes, and parameters to use for the current proxy request to service. For example, the whole request URL is http://localhost/api/v1/namespaces/kube-system/services/elasticsearch-logging/_search?q=user:kimchy . Path is <code>_search?q=user:kimchy</code> .	false	string	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParameter	name	name of the Service	true	string	

Type	Name	Description	Required	Schema	Default
PathParameter	path	path to the resource	true	string	

3.2.146.2. Responses

HTTP Code	Description	Schema
default	success	string

3.2.146.3. Consumes

- /

3.2.146.4. Produces

- /

3.2.146.5. Tags

- apiv1

3.2.147. partially update status of the specified Service

PATCH /api/v1/namespaces/{namespace}/services/{name}/status

3.2.147.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 2.3.10, "unversioned.Patch"	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParameter	name	name of the Service	true	string	

3.2.147.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.140, "v1.Service"

3.2.147.3. Consumes

- application/json-patch+json
- application/merge-patch+json
- application/strategic-merge-patch+json

3.2.147.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.147.5. Tags

- apiv1

3.2.148. replace status of the specified Service

```
PUT /api/v1/namespaces/{namespace}/services/{name}/status
```

3.2.148.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 3.3.140, "v1.Service"	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParameter	name	name of the Service	true	string	

3.2.148.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.140, "v1.Service"

3.2.148.3. Consumes

- /

3.2.148.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.148.5. Tags

- apiv1

3.2.149. read status of the specified Service

```
GET /api/v1/namespaces/{namespace}/services/{name}/status
```

3.2.149.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParameter	name	name of the Service	true	string	

3.2.149.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.140, "v1.Service"

3.2.149.3. Consumes

- /

3.2.149.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.149.5. Tags

- apiv1

3.2.150. delete a Namespace

```
DELETE /api/v1/namespaces/{name}
```

3.2.150.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 2.3.61, "v1.DeleteOptions"	
PathParameter	name	name of the Namespace	true	string	

3.2.150.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.11, "unversioned.Status"

3.2.150.3. Consumes

- /

3.2.150.4. Produces

- application/json

- application/yaml
- application/vnd.kubernetes.protobuf

3.2.150.5. Tags

- apiv1

3.2.151. partially update the specified Namespace

PATCH /api/v1/namespaces/{name}

3.2.151.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 2.3.10, “unversioned.Patch”	
PathParameter	name	name of the Namespace	true	string	

3.2.151.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.78, “v1.Namespace”

3.2.151.3. Consumes

- application/json-patch+json
- application/merge-patch+json
- application/strategic-merge-patch+json

3.2.151.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.151.5. Tags

- apiv1

3.2.152. replace the specified Namespace

```
PUT /api/v1/namespaces/{name}
```

3.2.152.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 3.3.78, "v1.Namespace"	
PathParameter	name	name of the Namespace	true	string	

3.2.152.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.78, "v1.Namespace"

3.2.152.3. Consumes

- /

3.2.152.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.152.5. Tags

- apiv1

3.2.153. read the specified Namespace

```
GET /api/v1/namespaces/{name}
```

3.2.153.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	export	Should this value be exported. Export strips fields that a user can not specify.	false	boolean	
QueryParamet er	exact	Should the export be exact. Exact export maintains cluster-specific fields like 'Namespace'	false	boolean	
PathParameter	name	name of the Namespace	true	string	

3.2.153.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.78, "v1.Namespace"

3.2.153.3. Consumes

- /

3.2.153.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.153.5. Tags

- apiv1

3.2.154. replace finalize of the specified Namespace

```
PUT /api/v1/namespaces/{name}/finalize
```

3.2.154.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 3.3.78, "v1.Namespace"	
PathParameter	name	name of the Namespace	true	string	

3.2.154.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.78, "v1.Namespace"

3.2.154.3. Consumes

- /

3.2.154.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.154.5. Tags

- apiv1

3.2.155. partially update status of the specified Namespace

```
PATCH /api/v1/namespaces/{name}/status
```

3.2.155.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 2.3.10, “unversioned.Patch”	
PathParameter	name	name of the Namespace	true	string	

3.2.155.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.78, “v1.Namespace”

3.2.155.3. Consumes

- application/json-patch+json
- application/merge-patch+json
- application/strategic-merge-patch+json

3.2.155.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.155.5. Tags

- apiv1

3.2.156. replace status of the specified Namespace

```
PUT /api/v1/namespaces/{name}/status
```

3.2.156.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParameter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParameter	body		true	Section 3.3.78, "v1.Namespace"	
PathParameter	name	name of the Namespace	true	string	

3.2.156.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.78, "v1.Namespace"

3.2.156.3. Consumes

- /

3.2.156.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.156.5. Tags

- apiv1

3.2.157. read status of the specified Namespace

```
GET /api/v1/namespaces/{name}/status
```

3.2.157.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParameter	pretty	If 'true', then the output is pretty printed.	false	string	

Type	Name	Description	Required	Schema	Default
PathParameter	name	name of the Namespace	true	string	

3.2.157.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.78, “v1.Namespace”

3.2.157.3. Consumes

- /

3.2.157.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.157.5. Tags

- apiv1

3.2.158. delete collection of Node

DELETE /api/v1/nodes

3.2.158.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParamet er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParamet er	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	
QueryParamet er	resourceVersio n	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	
QueryParamet er	timeoutSecond s	Timeout for the list/watch call.	false	integer	

3.2.158.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.11 , “unversioned.Status”

3.2.158.3. Consumes

- /

3.2.158.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.158.5. Tags

- apiv1

3.2.159. create a Node

POST /api/v1/nodes

3.2.159.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 3.3.82, "v1.Node"	

3.2.159.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.82, "v1.Node"

3.2.159.3. Consumes

- /

3.2.159.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.159.5. Tags

- apiv1

3.2.160. list or watch objects of kind Node

GET /api/v1/nodes

3.2.160.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamet er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParamet er	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	
QueryParamet er	resourceVersio n	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParamet er	timeoutSecond s	Timeout for the list/watch call.	false	integer	

3.2.160.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.86, “v1.NodeList”

3.2.160.3. Consumes

- /

3.2.160.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.160.5. Tags

- apiv1

3.2.161. delete a Node

```
DELETE /api/v1/nodes/{name}
```

3.2.161.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 2.3.61, “v1.DeleteOpti ons”	
PathParameter	name	name of the Node	true	string	

3.2.161.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.11 , “unversioned.Status”

3.2.161.3. Consumes

- /

3.2.161.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.161.5. Tags

- apiv1

3.2.162. partially update the specified Node

PATCH /api/v1/nodes/{name}

3.2.162.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 2.3.10 , “unversioned.Patch”	
PathParameter	name	name of the Node	true	string	

3.2.162.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.82 , “v1.Node”

3.2.162.3. Consumes

- application/json-patch+json
- application/merge-patch+json
- application/strategic-merge-patch+json

3.2.162.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.162.5. Tags

- apiv1

3.2.163. replace the specified Node

```
PUT /api/v1/nodes/{name}
```

3.2.163.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 3.3.82, "v1.Node"	
PathParameter	name	name of the Node	true	string	

3.2.163.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.82, "v1.Node"

3.2.163.3. Consumes

- /

3.2.163.4. Produces

- application/json

- application/yaml
- application/vnd.kubernetes.protobuf

3.2.163.5. Tags

- apiv1

3.2.164. read the specified Node

```
GET /api/v1/nodes/{name}
```

3.2.164.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	export	Should this value be exported. Export strips fields that a user can not specify.	false	boolean	
QueryParamet er	exact	Should the export be exact. Exact export maintains cluster-specific fields like 'Namespace'	false	boolean	
PathParamet er	name	name of the Node	true	string	

3.2.164.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.82, "v1.Node"

3.2.164.3. Consumes

- /

3.2.164.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.164.5. Tags

- apiv1

3.2.165. connect DELETE requests to proxy of Node

```
DELETE /api/v1/nodes/{name}/proxy
```

3.2.165.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	path	Path is the URL path to use for the current proxy request to node.	false	string	
PathParameter	name	name of the Node	true	string	

3.2.165.2. Responses

HTTP Code	Description	Schema
default	success	string

3.2.165.3. Consumes

- /

3.2.165.4. Produces

- /

3.2.165.5. Tags

- apiv1

3.2.166. connect OPTIONS requests to proxy of Node

OPTIONS /api/v1/nodes/{name}/proxy

3.2.166.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	path	Path is the URL path to use for the current proxy request to node.	false	string	
PathParameter	name	name of the Node	true	string	

3.2.166.2. Responses

HTTP Code	Description	Schema
default	success	string

3.2.166.3. Consumes

- /

3.2.166.4. Produces

- /

3.2.166.5. Tags

- apiv1

3.2.167. connect POST requests to proxy of Node

POST /api/v1/nodes/{name}/proxy

3.2.167.1. Parameters

Type	Name	Description	Required	Schema	Default
------	------	-------------	----------	--------	---------

Type	Name	Description	Required	Schema	Default
QueryParameter	path	Path is the URL path to use for the current proxy request to node.	false	string	
PathParameter	name	name of the Node	true	string	

3.2.167.2. Responses

HTTP Code	Description	Schema
default	success	string

3.2.167.3. Consumes

- /

3.2.167.4. Produces

- /

3.2.167.5. Tags

- apiv1

3.2.168. connect PUT requests to proxy of Node

```
PUT /api/v1/nodes/{name}/proxy
```

3.2.168.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParameter	path	Path is the URL path to use for the current proxy request to node.	false	string	
PathParameter	name	name of the Node	true	string	

3.2.168.2. Responses

HTTP Code	Description	Schema
default	success	string

3.2.168.3. Consumes

- /

3.2.168.4. Produces

- /

3.2.168.5. Tags

- apiv1

3.2.169. connect GET requests to proxy of Node

GET /api/v1/nodes/{name}/proxy

3.2.169.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	path	Path is the URL path to use for the current proxy request to node.	false	string	
PathParameter	name	name of the Node	true	string	

3.2.169.2. Responses

HTTP Code	Description	Schema
default	success	string

3.2.169.3. Consumes

- /

3.2.169.4. Produces

- /

3.2.169.5. Tags

- apiv1

3.2.170. connect HEAD requests to proxy of Node

HEAD /api/v1/nodes/{name}/proxy

3.2.170.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	path	Path is the URL path to use for the current proxy request to node.	false	string	
PathParameter	name	name of the Node	true	string	

3.2.170.2. Responses

HTTP Code	Description	Schema
default	success	string

3.2.170.3. Consumes

- /

3.2.170.4. Produces

- /

3.2.170.5. Tags

- apiv1

3.2.171. connect DELETE requests to proxy of Node

DELETE /api/v1/nodes/{name}/proxy/{path}

3.2.171.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	path	Path is the URL path to use for the current proxy request to node.	false	string	
PathParameter	name	name of the Node	true	string	
PathParameter	path	path to the resource	true	string	

3.2.171.2. Responses

HTTP Code	Description	Schema
default	success	string

3.2.171.3. Consumes

- /

3.2.171.4. Produces

- /

3.2.171.5. Tags

- apiv1

3.2.172. connect OPTIONS requests to proxy of Node

```
OPTIONS /api/v1/nodes/{name}/proxy/{path}
```

3.2.172.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	path	Path is the URL path to use for the current proxy request to node.	false	string	

Type	Name	Description	Required	Schema	Default
PathParameter	name	name of the Node	true	string	
PathParameter	path	path to the resource	true	string	

3.2.172.2. Responses

HTTP Code	Description	Schema
default	success	string

3.2.172.3. Consumes

- /

3.2.172.4. Produces

- /

3.2.172.5. Tags

- apiv1

3.2.173. connect POST requests to proxy of Node

```
POST /api/v1/nodes/{name}/proxy/{path}
```

3.2.173.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	path	Path is the URL path to use for the current proxy request to node.	false	string	
PathParameter	name	name of the Node	true	string	
PathParameter	path	path to the resource	true	string	

3.2.173.2. Responses

HTTP Code	Description	Schema
default	success	string

3.2.173.3. Consumes

- /

3.2.173.4. Produces

- /

3.2.173.5. Tags

- apiv1

3.2.174. connect PUT requests to proxy of Node

```
PUT /api/v1/nodes/{name}/proxy/{path}
```

3.2.174.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	path	Path is the URL path to use for the current proxy request to node.	false	string	
PathParameter	name	name of the Node	true	string	
PathParameter	path	path to the resource	true	string	

3.2.174.2. Responses

HTTP Code	Description	Schema
default	success	string

3.2.174.3. Consumes

- /

3.2.174.4. Produces

- /

3.2.174.5. Tags

- apiv1

3.2.175. connect GET requests to proxy of Node

```
GET /api/v1/nodes/{name}/proxy/{path}
```

3.2.175.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	path	Path is the URL path to use for the current proxy request to node.	false	string	
PathParameter	name	name of the Node	true	string	
PathParameter	path	path to the resource	true	string	

3.2.175.2. Responses

HTTP Code	Description	Schema
default	success	string

3.2.175.3. Consumes

- /

3.2.175.4. Produces

- /

3.2.175.5. Tags

- apiv1

3.2.176. connect HEAD requests to proxy of Node

HEAD /api/v1/nodes/{name}/proxy/{path}

3.2.176.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	path	Path is the URL path to use for the current proxy request to node.	false	string	
PathParameter	name	name of the Node	true	string	
PathParameter	path	path to the resource	true	string	

3.2.176.2. Responses

HTTP Code	Description	Schema
default	success	string

3.2.176.3. Consumes

- /

3.2.176.4. Produces

- /

3.2.176.5. Tags

- apiv1

3.2.177. partially update status of the specified Node

PATCH /api/v1/nodes/{name}/status

3.2.177.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 2.3.10, “unversioned.Patch”	
PathParameter	name	name of the Node	true	string	

3.2.177.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.82, “v1.Node”

3.2.177.3. Consumes

- application/json-patch+json
- application/merge-patch+json
- application/strategic-merge-patch+json

3.2.177.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.177.5. Tags

- apiv1

3.2.178. replace status of the specified Node

```
PUT /api/v1/nodes/{name}/status
```

3.2.178.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 3.3.82, "v1.Node"	
PathParameter	name	name of the Node	true	string	

3.2.178.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.82, "v1.Node"

3.2.178.3. Consumes

- /

3.2.178.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.178.5. Tags

- apiv1

3.2.179. read status of the specified Node

```
GET /api/v1/nodes/{name}/status
```

3.2.179.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	

Type	Name	Description	Required	Schema	Default
PathParameter	name	name of the Node	true	string	

3.2.179.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.82, "v1.Node"

3.2.179.3. Consumes

- /

3.2.179.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.179.5. Tags

- apiv1

3.2.180. create a PersistentVolumeClaim

POST /api/v1/persistentvolumeclaims

3.2.180.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 3.3.96, "v1.Persistent VolumeClaim"	

3.2.180.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.96, "v1.PersistentVolumeClaim"

3.2.180.3. Consumes

- /

3.2.180.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.180.5. Tags

- apiv1

3.2.181. list or watch objects of kind PersistentVolumeClaim

```
GET /api/v1/persistentvolumeclaims
```

3.2.181.1. Description

Persistent Volume Claims (PVC) represent a request to use a persistent volume (PV) with a pod. When creating a pod definition (or replication controller or deployment config) a developer may specify the amount of storage they need via a persistent volume reference. If an administrator has enabled and configured persistent volumes for use, they will be allocated on demand to pods that have similar requirements. Since volumes are created lazily, some pods may be scheduled to a node before their volume is assigned. The node will detect this situation and wait to start the pod until the volume is bound. Events will be generated (visible by using the **describe** command on the pod) that indicate the pod is waiting for volumes.

3.2.181.2. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParamet er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParamet er	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	
QueryParamet er	resourceVersio n	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	
QueryParamet er	timeoutSecond s	Timeout for the list/watch call.	false	integer	

3.2.181.3. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.97 , “v1.PersistentVolumeClaimList”

3.2.181.4. Consumes

- /

3.2.181.5. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.181.6. Tags

- apiv1

3.2.182. delete collection of PersistentVolume

```
DELETE /api/v1/persistentvolumes
```

3.2.182.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamet er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParamet er	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParam er	resourceVersio n	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	
QueryParam er	timeoutSecond s	Timeout for the list/watch call.	false	integer	

3.2.182.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.11 , “unversioned.Status”

3.2.182.3. Consumes

- /

3.2.182.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.182.5. Tags

- apiv1

3.2.183. create a PersistentVolume

POST /api/v1/persistentvolumes

3.2.183.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 3.3.94, "v1.Persistent Volume"	

3.2.183.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.94, "v1.PersistentVolume"

3.2.183.3. Consumes

- /

3.2.183.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.183.5. Tags

- apiv1

3.2.184. list or watch objects of kind PersistentVolume

GET /api/v1/persistentvolumes

3.2.184.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParam er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParam er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParam er	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	
QueryParam er	resourceVersion	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	
QueryParam er	timeoutSeconds	Timeout for the list/watch call.	false	integer	

3.2.184.2. Responses

HTTP Code	Description	Schema
-----------	-------------	--------

HTTP Code	Description	Schema
200	success	Section 3.3.101 , "v1.PersistentVolumeList"

3.2.184.3. Consumes

- /

3.2.184.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.184.5. Tags

- apiv1

3.2.185. delete a PersistentVolume

```
DELETE /api/v1/persistentvolumes/{name}
```

3.2.185.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParameter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParameter	body		true	Section 2.3.61 , "v1.DeleteOptions"	
PathParameter	name	name of the PersistentVolume	true	string	

3.2.185.2. Responses

HTTP Code	Description	Schema
-----------	-------------	--------

HTTP Code	Description	Schema
200	success	Section 2.3.11 , “unversioned.Status”

3.2.185.3. Consumes

- /

3.2.185.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.185.5. Tags

- apiv1

3.2.186. partially update the specified PersistentVolume

```
PATCH /api/v1/persistentvolumes/{name}
```

3.2.186.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 2.3.10 , “unversioned.P atch”	
PathParameter	name	name of the PersistentVolume	true	string	

3.2.186.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.94 , “v1.PersistentVolume”

3.2.186.3. Consumes

- application/json-patch+json
- application/merge-patch+json
- application/strategic-merge-patch+json

3.2.186.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.186.5. Tags

- apiv1

3.2.187. replace the specified PersistentVolume

```
PUT /api/v1/persistentvolumes/{name}
```

3.2.187.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParameter	body		true	Section 3.3.94, "v1.PersistentVolume"	
PathParameter	name	name of the PersistentVolume	true	string	

3.2.187.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.94, "v1.PersistentVolume"

3.2.187.3. Consumes

- /

3.2.187.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.187.5. Tags

- apiv1

3.2.188. read the specified PersistentVolume

```
GET /api/v1/persistentvolumes/{name}
```

3.2.188.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	export	Should this value be exported. Export strips fields that a user can not specify.	false	boolean	
QueryParamet er	exact	Should the export be exact. Exact export maintains cluster-specific fields like 'Namespace'	false	boolean	
PathParameter	name	name of the PersistentVolume	true	string	

3.2.188.2. Responses

HTTP Code	Description	Schema
-----------	-------------	--------

HTTP Code	Description	Schema
200	success	Section 3.3.94, "v1.PersistentVolume"

3.2.188.3. Consumes

- /

3.2.188.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.188.5. Tags

- apiv1

3.2.189. partially update status of the specified PersistentVolume

PATCH /api/v1/persistentvolumes/{name}/status

3.2.189.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 2.3.10, "unversioned.Patch"	
PathParameter	name	name of the PersistentVolume	true	string	

3.2.189.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.94, "v1.PersistentVolume"

3.2.189.3. Consumes

- application/json-patch+json
- application/merge-patch+json
- application/strategic-merge-patch+json

3.2.189.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.189.5. Tags

- apiv1

3.2.190. replace status of the specified PersistentVolume

```
PUT /api/v1/persistentvolumes/{name}/status
```

3.2.190.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 3.3.94, "v1.Persistent Volume"	
PathParameter	name	name of the PersistentVolume	true	string	

3.2.190.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.94, "v1.PersistentVolume"

3.2.190.3. Consumes

- /

3.2.190.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.190.5. Tags

- apiv1

3.2.191. read status of the specified PersistentVolume

```
GET /api/v1/persistentvolumes/{name}/status
```

3.2.191.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamter	pretty	If 'true', then the output is pretty printed.	false	string	
PathParameter	name	name of the PersistentVolume	true	string	

3.2.191.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.94, "v1.PersistentVolume"

3.2.191.3. Consumes

- /

3.2.191.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.191.5. Tags

- apiv1

3.2.192. create a Pod

POST /api/v1/pods

3.2.192.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 3.3.104, "v1.Pod"	

3.2.192.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.104, "v1.Pod"

3.2.192.3. Consumes

- /

3.2.192.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.192.5. Tags

- apiv1

3.2.193. list or watch objects of kind Pod

GET /api/v1/pods

3.2.193.1. Parameters

Type	Name	Description	Required	Schema	Default
------	------	-------------	----------	--------	---------

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamet er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParamet er	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	
QueryParamet er	resourceVersio n	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	
QueryParamet er	timeoutSecond s	Timeout for the list/watch call.	false	integer	

3.2.193.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.106, “v1.PodList”

3.2.193.3. Consumes

- /

3.2.193.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.193.5. Tags

- apiv1

3.2.194. create a PodTemplate

POST /api/v1/podtemplates

3.2.194.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 3.3.110, “v1.PodTempl ate”	

3.2.194.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.110, “v1.PodTemplate”

3.2.194.3. Consumes

- /

3.2.194.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.194.5. Tags

- apiv1

3.2.195. list or watch objects of kind PodTemplate

GET /api/v1/podtemplates

3.2.195.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamet er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParamet er	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParamet er	resourceVersio n	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	
QueryParamet er	timeoutSecond s	Timeout for the list/watch call.	false	integer	

3.2.195.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.111 , "v1.PodTemplateList"

3.2.195.3. Consumes

- /

3.2.195.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.195.5. Tags

- apiv1

3.2.196. proxy DELETE requests to Pod

```
DELETE /api/v1/proxy/namespaces/{namespace}/pods/{name}
```

3.2.196.1. Parameters

Type	Name	Description	Required	Schema	Default
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParameter	name	name of the Pod	true	string	

3.2.196.2. Responses

HTTP Code	Description	Schema
default	success	string

3.2.196.3. Consumes

- /

3.2.196.4. Produces

- /

3.2.196.5. Tags

- apiv1

3.2.197. proxy OPTIONS requests to Pod

```
OPTIONS /api/v1/proxy/namespaces/{namespace}/pods/{name}
```

3.2.197.1. Parameters

Type	Name	Description	Required	Schema	Default
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParameter	name	name of the Pod	true	string	

3.2.197.2. Responses

HTTP Code	Description	Schema
default	success	string

3.2.197.3. Consumes

- /

3.2.197.4. Produces

- /

3.2.197.5. Tags

- apiv1

3.2.198. proxy POST requests to Pod

POST /api/v1/proxy/namespaces/{namespace}/pods/{name}

3.2.198.1. Parameters

Type	Name	Description	Required	Schema	Default
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParameter	name	name of the Pod	true	string	

3.2.198.2. Responses

HTTP Code	Description	Schema
default	success	string

3.2.198.3. Consumes

- /

3.2.198.4. Produces

- /

3.2.198.5. Tags

- apiv1

3.2.199. proxy PUT requests to Pod

PUT /api/v1/proxy/namespaces/{namespace}/pods/{name}

3.2.199.1. Parameters

Type	Name	Description	Required	Schema	Default
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParameter	name	name of the Pod	true	string	

3.2.199.2. Responses

HTTP Code	Description	Schema
default	success	string

3.2.199.3. Consumes

- /

3.2.199.4. Produces

- /

3.2.199.5. Tags

- apiv1

3.2.200. proxy GET requests to Pod

GET /api/v1/proxy/namespaces/{namespace}/pods/{name}

3.2.200.1. Parameters

Type	Name	Description	Required	Schema	Default
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParameter	name	name of the Pod	true	string	

3.2.200.2. Responses

HTTP Code	Description	Schema
default	success	string

3.2.200.3. Consumes

- /

3.2.200.4. Produces

- /

3.2.200.5. Tags

- apiv1

3.2.201. proxy HEAD requests to Pod

```
HEAD /api/v1/proxy/namespaces/{namespace}/pods/{name}
```

3.2.201.1. Parameters

Type	Name	Description	Required	Schema	Default
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParameter	name	name of the Pod	true	string	

3.2.201.2. Responses

HTTP Code	Description	Schema
default	success	string

3.2.201.3. Consumes

- /

3.2.201.4. Produces

- /

3.2.201.5. Tags

- apiv1

3.2.202. proxy DELETE requests to Pod

DELETE /api/v1/proxy/namespaces/{namespace}/pods/{name}/{path}

3.2.202.1. Parameters

Type	Name	Description	Required	Schema	Default
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParameter	name	name of the Pod	true	string	
PathParameter	path	path to the resource	true	string	

3.2.202.2. Responses

HTTP Code	Description	Schema
default	success	string

3.2.202.3. Consumes

- /

3.2.202.4. Produces

- /

3.2.202.5. Tags

- apiv1

3.2.203. proxy OPTIONS requests to Pod

OPTIONS /api/v1/proxy/namespaces/{namespace}/pods/{name}/{path}

3.2.203.1. Parameters

Type	Name	Description	Required	Schema	Default
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParameter	name	name of the Pod	true	string	
PathParameter	path	path to the resource	true	string	

3.2.203.2. Responses

HTTP Code	Description	Schema
default	success	string

3.2.203.3. Consumes

- /

3.2.203.4. Produces

- /

3.2.203.5. Tags

- apiv1

3.2.204. proxy POST requests to Pod

POST /api/v1/proxy/namespaces/{namespace}/pods/{name}/{path}

■

3.2.204.1. Parameters

Type	Name	Description	Required	Schema	Default
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParameter	name	name of the Pod	true	string	
PathParameter	path	path to the resource	true	string	

3.2.204.2. Responses

HTTP Code	Description	Schema
default	success	string

3.2.204.3. Consumes

- /

3.2.204.4. Produces

- /

3.2.204.5. Tags

- apiv1

3.2.205. proxy PUT requests to Pod

```
PUT /api/v1/proxy/namespaces/{namespace}/pods/{name}/{path}
```

3.2.205.1. Parameters

Type	Name	Description	Required	Schema	Default
------	------	-------------	----------	--------	---------

Type	Name	Description	Required	Schema	Default
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParameter	name	name of the Pod	true	string	
PathParameter	path	path to the resource	true	string	

3.2.205.2. Responses

HTTP Code	Description	Schema
default	success	string

3.2.205.3. Consumes

- /

3.2.205.4. Produces

- /

3.2.205.5. Tags

- apiv1

3.2.206. proxy GET requests to Pod

```
GET /api/v1/proxy/namespaces/{namespace}/pods/{name}/{path}
```

3.2.206.1. Parameters

Type	Name	Description	Required	Schema	Default
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	

Type	Name	Description	Required	Schema	Default
PathParameter	name	name of the Pod	true	string	
PathParameter	path	path to the resource	true	string	

3.2.206.2. Responses

HTTP Code	Description	Schema
default	success	string

3.2.206.3. Consumes

- /

3.2.206.4. Produces

- /

3.2.206.5. Tags

- apiv1

3.2.207. proxy HEAD requests to Pod

```
HEAD /api/v1/proxy/namespaces/{namespace}/pods/{name}/{path}
```

3.2.207.1. Parameters

Type	Name	Description	Required	Schema	Default
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParameter	name	name of the Pod	true	string	
PathParameter	path	path to the resource	true	string	

3.2.207.2. Responses

HTTP Code	Description	Schema
default	success	string

3.2.207.3. Consumes

- /

3.2.207.4. Produces

- /

3.2.207.5. Tags

- apiv1

3.2.208. proxy DELETE requests to Service

DELETE /api/v1/proxy/namespaces/{namespace}/services/{name}

3.2.208.1. Parameters

Type	Name	Description	Required	Schema	Default
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParameter	name	name of the Service	true	string	

3.2.208.2. Responses

HTTP Code	Description	Schema
default	success	string

3.2.208.3. Consumes

- /

3.2.208.4. Produces

- /

3.2.208.5. Tags

- apiv1

3.2.209. proxy OPTIONS requests to Service

```
OPTIONS /api/v1/proxy/namespaces/{namespace}/services/{name}
```

3.2.209.1. Parameters

Type	Name	Description	Required	Schema	Default
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParameter	name	name of the Service	true	string	

3.2.209.2. Responses

HTTP Code	Description	Schema
default	success	string

3.2.209.3. Consumes

- /

3.2.209.4. Produces

- /

3.2.209.5. Tags

- apiv1

3.2.210. proxy POST requests to Service

```
POST /api/v1/proxy/namespaces/{namespace}/services/{name}
```

3.2.210.1. Parameters

Type	Name	Description	Required	Schema	Default
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParameter	name	name of the Service	true	string	

3.2.210.2. Responses

HTTP Code	Description	Schema
default	success	string

3.2.210.3. Consumes

- /

3.2.210.4. Produces

- /

3.2.210.5. Tags

- apiv1

3.2.211. proxy PUT requests to Service

```
PUT /api/v1/proxy/namespaces/{namespace}/services/{name}
```

3.2.211.1. Parameters

Type	Name	Description	Required	Schema	Default
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParameter	name	name of the Service	true	string	

3.2.211.2. Responses

HTTP Code	Description	Schema
default	success	string

3.2.211.3. Consumes

- /

3.2.211.4. Produces

- /

3.2.211.5. Tags

- apiv1

3.2.212. proxy GET requests to Service

GET /api/v1/proxy/namespaces/{namespace}/services/{name}

3.2.212.1. Parameters

Type	Name	Description	Required	Schema	Default
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParameter	name	name of the Service	true	string	

3.2.212.2. Responses

HTTP Code	Description	Schema
default	success	string

3.2.212.3. Consumes

- /

3.2.212.4. Produces

- /

3.2.212.5. Tags

- apiv1

3.2.213. proxy HEAD requests to Service

```
HEAD /api/v1/proxy/namespaces/{namespace}/services/{name}
```

3.2.213.1. Parameters

Type	Name	Description	Required	Schema	Default
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParameter	name	name of the Service	true	string	

3.2.213.2. Responses

HTTP Code	Description	Schema
default	success	string

3.2.213.3. Consumes

- /

3.2.213.4. Produces

- /

3.2.213.5. Tags

- apiv1

3.2.214. proxy DELETE requests to Service

```
DELETE /api/v1/proxy/namespaces/{namespace}/services/{name}/{path}
```

3.2.214.1. Parameters

Type	Name	Description	Required	Schema	Default
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParameter	name	name of the Service	true	string	
PathParameter	path	path to the resource	true	string	

3.2.214.2. Responses

HTTP Code	Description	Schema
default	success	string

3.2.214.3. Consumes

- /

3.2.214.4. Produces

- /

3.2.214.5. Tags

- apiv1

3.2.215. proxy OPTIONS requests to Service

```
OPTIONS /api/v1/proxy/namespaces/{namespace}/services/{name}/{path}
```

3.2.215.1. Parameters

Type	Name	Description	Required	Schema	Default
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	

Type	Name	Description	Required	Schema	Default
PathParameter	name	name of the Service	true	string	
PathParameter	path	path to the resource	true	string	

3.2.215.2. Responses

HTTP Code	Description	Schema
default	success	string

3.2.215.3. Consumes

- /

3.2.215.4. Produces

- /

3.2.215.5. Tags

- apiv1

3.2.216. proxy POST requests to Service

```
POST /api/v1/proxy/namespaces/{namespace}/services/{name}/{path}
```

3.2.216.1. Parameters

Type	Name	Description	Required	Schema	Default
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParameter	name	name of the Service	true	string	
PathParameter	path	path to the resource	true	string	

3.2.216.2. Responses

HTTP Code	Description	Schema
default	success	string

3.2.216.3. Consumes

- /

3.2.216.4. Produces

- /

3.2.216.5. Tags

- apiv1

3.2.217. proxy PUT requests to Service

PUT /api/v1/proxy/namespaces/{namespace}/services/{name}/{path}

3.2.217.1. Parameters

Type	Name	Description	Required	Schema	Default
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParameter	name	name of the Service	true	string	
PathParameter	path	path to the resource	true	string	

3.2.217.2. Responses

HTTP Code	Description	Schema
default	success	string

3.2.217.3. Consumes

- /

3.2.217.4. Produces

- /

3.2.217.5. Tags

- apiv1

3.2.218. proxy GET requests to Service

```
GET /api/v1/proxy/namespaces/{namespace}/services/{name}/{path}
```

3.2.218.1. Parameters

Type	Name	Description	Required	Schema	Default
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParameter	name	name of the Service	true	string	
PathParameter	path	path to the resource	true	string	

3.2.218.2. Responses

HTTP Code	Description	Schema
default	success	string

3.2.218.3. Consumes

- /

3.2.218.4. Produces

- /

3.2.218.5. Tags

- apiv1

3.2.219. proxy HEAD requests to Service

```
HEAD /api/v1/proxy/namespaces/{namespace}/services/{name}/{path}
```

■

3.2.219.1. Parameters

Type	Name	Description	Required	Schema	Default
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParameter	name	name of the Service	true	string	
PathParameter	path	path to the resource	true	string	

3.2.219.2. Responses

HTTP Code	Description	Schema
default	success	string

3.2.219.3. Consumes

- /

3.2.219.4. Produces

- /

3.2.219.5. Tags

- apiv1

3.2.220. proxy DELETE requests to Node

```
DELETE /api/v1/proxy/nodes/{name}
```

3.2.220.1. Parameters

Type	Name	Description	Required	Schema	Default
PathParameter	name	name of the Node	true	string	

3.2.220.2. Responses

HTTP Code	Description	Schema
default	success	string

3.2.220.3. Consumes

- /

3.2.220.4. Produces

- /

3.2.220.5. Tags

- apiv1

3.2.221. proxy OPTIONS requests to Node

`OPTIONS /api/v1/proxy/nodes/{name}`

3.2.221.1. Parameters

Type	Name	Description	Required	Schema	Default
PathParameter	name	name of the Node	true	string	

3.2.221.2. Responses

HTTP Code	Description	Schema
default	success	string

3.2.221.3. Consumes

- /

3.2.221.4. Produces

- /

3.2.221.5. Tags

- apiv1

3.2.222. proxy POST requests to Node

POST /api/v1/proxy/nodes/{name}

3.2.222.1. Parameters

Type	Name	Description	Required	Schema	Default
PathParameter	name	name of the Node	true	string	

3.2.222.2. Responses

HTTP Code	Description	Schema
default	success	string

3.2.222.3. Consumes

- /

3.2.222.4. Produces

- /

3.2.222.5. Tags

- apiv1

3.2.223. proxy PUT requests to Node

PUT /api/v1/proxy/nodes/{name}

3.2.223.1. Parameters

Type	Name	Description	Required	Schema	Default
PathParameter	name	name of the Node	true	string	

3.2.223.2. Responses

HTTP Code	Description	Schema
default	success	string

3.2.223.3. Consumes

- /

3.2.223.4. Produces

- /

3.2.223.5. Tags

- apiv1

3.2.224. proxy GET requests to Node

GET /api/v1/proxy/nodes/{name}

3.2.224.1. Parameters

Type	Name	Description	Required	Schema	Default
PathParameter	name	name of the Node	true	string	

3.2.224.2. Responses

HTTP Code	Description	Schema
default	success	string

3.2.224.3. Consumes

- /

3.2.224.4. Produces

- /

3.2.224.5. Tags

- apiv1

3.2.225. proxy HEAD requests to Node

HEAD /api/v1/proxy/nodes/{name}

3.2.225.1. Parameters

Type	Name	Description	Required	Schema	Default
PathParameter	name	name of the Node	true	string	

3.2.225.2. Responses

HTTP Code	Description	Schema
default	success	string

3.2.225.3. Consumes

- /

3.2.225.4. Produces

- /

3.2.225.5. Tags

- apiv1

3.2.226. proxy DELETE requests to Node

```
DELETE /api/v1/proxy/nodes/{name}/{path}
```

3.2.226.1. Parameters

Type	Name	Description	Required	Schema	Default
PathParameter	name	name of the Node	true	string	
PathParameter	path	path to the resource	true	string	

3.2.226.2. Responses

HTTP Code	Description	Schema
default	success	string

3.2.226.3. Consumes

- /

3.2.226.4. Produces

- /

3.2.226.5. Tags

- apiv1

3.2.227. proxy OPTIONS requests to Node

OPTIONS /api/v1/proxy/nodes/{name}/{path}

3.2.227.1. Parameters

Type	Name	Description	Required	Schema	Default
PathParameter	name	name of the Node	true	string	
PathParameter	path	path to the resource	true	string	

3.2.227.2. Responses

HTTP Code	Description	Schema
default	success	string

3.2.227.3. Consumes

- /

3.2.227.4. Produces

- /

3.2.227.5. Tags

- apiv1

3.2.228. proxy POST requests to Node

POST /api/v1/proxy/nodes/{name}/{path}

3.2.228.1. Parameters

Type	Name	Description	Required	Schema	Default
PathParameter	name	name of the Node	true	string	
PathParameter	path	path to the resource	true	string	

3.2.228.2. Responses

HTTP Code	Description	Schema
default	success	string

3.2.228.3. Consumes

- /

3.2.228.4. Produces

- /

3.2.228.5. Tags

- apiv1

3.2.229. proxy PUT requests to Node

```
PUT /api/v1/proxy/nodes/{name}/{path}
```

3.2.229.1. Parameters

Type	Name	Description	Required	Schema	Default
PathParameter	name	name of the Node	true	string	
PathParameter	path	path to the resource	true	string	

3.2.229.2. Responses

HTTP Code	Description	Schema
default	success	string

3.2.229.3. Consumes

- /

3.2.229.4. Produces

- /

3.2.229.5. Tags

- apiv1

3.2.230. proxy GET requests to Node

```
GET /api/v1/proxy/nodes/{name}/{path}
```

3.2.230.1. Parameters

Type	Name	Description	Required	Schema	Default
PathParameter	name	name of the Node	true	string	
PathParameter	path	path to the resource	true	string	

3.2.230.2. Responses

HTTP Code	Description	Schema
default	success	string

3.2.230.3. Consumes

- /

3.2.230.4. Produces

- /

3.2.230.5. Tags

- apiv1

3.2.231. proxy HEAD requests to Node

```
HEAD /api/v1/proxy/nodes/{name}/{path}
```

3.2.231.1. Parameters

Type	Name	Description	Required	Schema	Default
PathParameter	name	name of the Node	true	string	
PathParameter	path	path to the resource	true	string	

3.2.231.2. Responses

HTTP Code	Description	Schema
default	success	string

3.2.231.3. Consumes

- /

3.2.231.4. Produces

- /

3.2.231.5. Tags

- apiv1

3.2.232. create a ReplicationController

POST /api/v1/replicationcontrollers

3.2.232.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 3.3.11 6 , "v1.Replication Controller"	

3.2.232.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.116 , "v1.ReplicationController"

3.2.232.3. Consumes

- /

3.2.232.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.232.5. Tags

- apiv1

3.2.233. list or watch objects of kind ReplicationController

```
GET /api/v1/replicationcontrollers
```

3.2.233.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamet er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParamet er	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersio n.	false	boolean	
QueryParamet er	resourceVersio n	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	
QueryParamet er	timeoutSecond s	Timeout for the list/watch call.	false	integer	

3.2.233.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.117 , "v1.ReplicationControllerList"

3.2.233.3. Consumes

- /

3.2.233.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.233.5. Tags

- apiv1

3.2.234. create a ResourceQuota

POST /api/v1/resourcequotas

3.2.234.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 3.3.121 , "v1.ResourceQ uota"	

3.2.234.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.121 , "v1.ResourceQuota"

3.2.234.3. Consumes

- /

3.2.234.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.234.5. Tags

- apiv1

3.2.235. list or watch objects of kind ResourceQuota

GET /api/v1/resourcequotas

3.2.235.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamet er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParamet er	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersio n.	false	boolean	
QueryParamet er	resourceVersio n	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	
QueryParamet er	timeoutSecond s	Timeout for the list/watch call.	false	integer	

3.2.235.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.122 , “v1.ResourceQuotaList”

3.2.235.3. Consumes

- /

3.2.235.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.235.5. Tags

- apiv1

3.2.236. create a Secret

POST /api/v1/secrets

3.2.236.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 2.3.204 , “v1.Secret”	

3.2.236.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.204 , “v1.Secret”

3.2.236.3. Consumes

- /

3.2.236.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.236.5. Tags

- apiv1

3.2.237. list or watch objects of kind Secret

GET /api/v1/secrets

3.2.237.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamet er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParamet er	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParam er	resourceVersio n	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	
QueryParam er	timeoutSecond s	Timeout for the list/watch call.	false	integer	

3.2.237.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.207, "v1.SecretList"

3.2.237.3. Consumes

- /

3.2.237.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.237.5. Tags

- apiv1

3.2.238. delete collection of SecurityContextConstraints

```
DELETE /api/v1/securitycontextconstraints
```

3.2.238.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamet er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParamet er	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	
QueryParamet er	resourceVersio n	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	
QueryParamet er	timeoutSecond s	Timeout for the list/watch call.	false	integer	

3.2.238.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.11 , “unversioned.Status”

3.2.238.3. Consumes

- /

3.2.238.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.238.5. Tags

- apiv1

3.2.239. create a SecurityContextConstraints

POST /api/v1/securitycontextconstraints

3.2.239.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 3.3.138 , “v1.SecurityCo ntextConstraint s”	

3.2.239.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.138 , “v1.SecurityContextConstraints”

3.2.239.3. Consumes

- /

3.2.239.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.239.5. Tags

- apiv1

3.2.240. list or watch objects of kind SecurityContextConstraints

GET /api/v1/securitycontextconstraints

3.2.240.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamet er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParamet er	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParam er	resourceVersio n	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	
QueryParam er	timeoutSecond s	Timeout for the list/watch call.	false	integer	

3.2.240.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.139 , “v1.SecurityContextConstraintsList”

3.2.240.3. Consumes

- /

3.2.240.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.240.5. Tags

- apiv1

3.2.241. delete a SecurityContextConstraints

```
DELETE /api/v1/securitycontextconstraints/{name}
```

3.2.241.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 2.3.61, "v1.DeleteOptions"	
PathParameter	name	name of the SecurityContextConstraints	true	string	

3.2.241.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.11, "unversioned.Status"

3.2.241.3. Consumes

- /

3.2.241.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.241.5. Tags

- apiv1

3.2.242. partially update the specified SecurityContextConstraints

```
PATCH /api/v1/securitycontextconstraints/{name}
```

3.2.242.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	

Type	Name	Description	Required	Schema	Default
BodyParameter	body		true	Section 2.3.10, "unversioned.Patch"	
PathParameter	name	name of the SecurityContextConstraints	true	string	

3.2.242.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.138, "v1.SecurityContextConstraints"

3.2.242.3. Consumes

- application/json-patch+json
- application/merge-patch+json
- application/strategic-merge-patch+json

3.2.242.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.242.5. Tags

- apiv1

3.2.243. replace the specified SecurityContextConstraints

```
PUT /api/v1/securitycontextconstraints/{name}
```

3.2.243.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamter	pretty	If 'true', then the output is pretty printed.	false	string	

Type	Name	Description	Required	Schema	Default
BodyParameter	body		true	Section 3.3.138 , "v1.SecurityContextConstraints"	
PathParameter	name	name of the SecurityContextConstraints	true	string	

3.2.243.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.138 , "v1.SecurityContextConstraints"

3.2.243.3. Consumes

- /

3.2.243.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.243.5. Tags

- apiv1

3.2.244. read the specified SecurityContextConstraints

```
GET /api/v1/securitycontextconstraints/{name}
```

3.2.244.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParamet er	export	Should this value be exported. Export strips fields that a user can not specify.	false	boolean	
QueryParamet er	exact	Should the export be exact. Exact export maintains cluster-specific fields like 'Namespace'	false	boolean	
PathParameter	name	name of the SecurityContextConstraints	true	string	

3.2.244.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.138, "v1.SecurityContextConstraints"

3.2.244.3. Consumes

- /

3.2.244.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.244.5. Tags

- apiv1

3.2.245. create a ServiceAccount

■

POST /api/v1/serviceaccounts

3.2.245.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 3.3.141 , "v1.ServiceAccount"	

3.2.245.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.141 , "v1.ServiceAccount"

3.2.245.3. Consumes

- /

3.2.245.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.245.5. Tags

- apiv1

3.2.246. list or watch objects of kind ServiceAccount

GET /api/v1/serviceaccounts

3.2.246.1. Parameters

Type	Name	Description	Required	Schema	Default
------	------	-------------	----------	--------	---------

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamet er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParamet er	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	
QueryParamet er	resourceVersio n	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	
QueryParamet er	timeoutSecond s	Timeout for the list/watch call.	false	integer	

3.2.246.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.142 , "v1.ServiceAccountList"

3.2.246.3. Consumes

- /

3.2.246.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.246.5. Tags

- apiv1

3.2.247. create a Service

POST /api/v1/services

3.2.247.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamete r	body		true	Section 3.3.140 , "v1.Service"	

3.2.247.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.140 , "v1.Service"

3.2.247.3. Consumes

- /

3.2.247.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.247.5. Tags

- apiv1

3.2.248. list or watch objects of kind Service

GET /api/v1/services

3.2.248.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamet er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParamet er	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParam er	resourceVersio n	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	
QueryParam er	timeoutSecond s	Timeout for the list/watch call.	false	integer	

3.2.248.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.143, "v1.ServiceList"

3.2.248.3. Consumes

- /

3.2.248.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.248.5. Tags

- apiv1

3.2.249. watch individual changes to a list of ConfigMap

```
GET /api/v1/watch/configmaps
```

3.2.249.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamet er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParamet er	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	
QueryParamet er	resourceVersio n	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	
QueryParamet er	timeoutSecond s	Timeout for the list/watch call.	false	integer	

3.2.249.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.1, “versioned.Event”

3.2.249.3. Consumes

- /

3.2.249.4. Produces

- application/json
- application/json;stream=watch
- application/vnd.kubernetes.protobuf
- application/vnd.kubernetes.protobuf;stream=watch

3.2.249.5. Tags

- apiv1

3.2.250. watch individual changes to a list of Endpoints

```
GET /api/v1/watch/endpoints
```

3.2.250.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamet er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParamet er	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	
QueryParamet er	resourceVersio n	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	
QueryParamet er	timeoutSecond s	Timeout for the list/watch call.	false	integer	

3.2.250.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.1, “versioned.Event”

3.2.250.3. Consumes

- /

3.2.250.4. Produces

- application/json
- application/json;stream=watch
- application/vnd.kubernetes.protobuf
- application/vnd.kubernetes.protobuf;stream=watch

3.2.250.5. Tags

- apiv1

3.2.251. watch individual changes to a list of Event

GET /api/v1/watch/events

3.2.251.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamet er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParamet er	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParamet er	resourceVersio n	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	
QueryParamet er	timeoutSecond s	Timeout for the list/watch call.	false	integer	

3.2.251.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.1, “versioned.Event”

3.2.251.3. Consumes

- /

3.2.251.4. Produces

- application/json
- application/json;stream=watch
- application/vnd.kubernetes.protobuf
- application/vnd.kubernetes.protobuf;stream=watch

3.2.251.5. Tags

- apiv1

3.2.252. watch individual changes to a list of LimitRange

```
GET /api/v1/watch/limitranges
```

3.2.252.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamet er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParamet er	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	
QueryParamet er	resourceVersio n	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	
QueryParamet er	timeoutSecond s	Timeout for the list/watch call.	false	integer	

3.2.252.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.1, “versioned.Event”

3.2.252.3. Consumes

- /

3.2.252.4. Produces

- application/json
- application/json;stream=watch
- application/vnd.kubernetes.protobuf
- application/vnd.kubernetes.protobuf;stream=watch

3.2.252.5. Tags

- apiv1

3.2.253. watch individual changes to a list of Namespace

GET /api/v1/watch/namespaces

3.2.253.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamet er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParamet er	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	
QueryParamet er	resourceVersio n	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	
QueryParamet er	timeoutSecond s	Timeout for the list/watch call.	false	integer	

3.2.253.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.1, “versioned.Event”

3.2.253.3. Consumes

- /

3.2.253.4. Produces

- application/json
- application/json;stream=watch
- application/vnd.kubernetes.protobuf
- application/vnd.kubernetes.protobuf;stream=watch

3.2.253.5. Tags

- apiv1

3.2.254. watch individual changes to a list of ConfigMap

GET /api/v1/watch/namespaces/{namespace}/configmaps

3.2.254.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamet er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParamet er	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParamet er	resourceVersio n	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	
QueryParamet er	timeoutSecond s	Timeout for the list/watch call.	false	integer	
PathParamet er	namespace	object name and auth scope, such as for teams and projects	true	string	

3.2.254.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.1, “versioned.Event”

3.2.254.3. Consumes

- /

3.2.254.4. Produces

- application/json
- application/json;stream=watch
- application/vnd.kubernetes.protobuf
- application/vnd.kubernetes.protobuf;stream=watch

3.2.254.5. Tags

- apiv1

3.2.255. watch changes to an object of kind ConfigMap

```
GET /api/v1/watch/namespaces/{namespace}/configmaps/{name}
```

3.2.255.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamet er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParamet er	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	
QueryParamet er	resourceVersio n	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParamet er	timeoutSecond s	Timeout for the list/watch call.	false	integer	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParameter	name	name of the ConfigMap	true	string	

3.2.255.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.1, “versioned.Event”

3.2.255.3. Consumes

- /

3.2.255.4. Produces

- application/json
- application/json;stream=watch
- application/vnd.kubernetes.protobuf
- application/vnd.kubernetes.protobuf;stream=watch

3.2.255.5. Tags

- apiv1

3.2.256. watch individual changes to a list of Endpoints

```
GET /api/v1/watch/namespaces/{namespace}/endpoints
```

3.2.256.1. Parameters

Type	Name	Description	Required	Schema	Default
------	------	-------------	----------	--------	---------

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamet er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParamet er	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	
QueryParamet er	resourceVersio n	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	
QueryParamet er	timeoutSecond s	Timeout for the list/watch call.	false	integer	

Type	Name	Description	Required	Schema	Default
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	

3.2.256.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.1, “versioned.Event”

3.2.256.3. Consumes

- /

3.2.256.4. Produces

- application/json
- application/json;stream=watch
- application/vnd.kubernetes.protobuf
- application/vnd.kubernetes.protobuf;stream=watch

3.2.256.5. Tags

- apiv1

3.2.257. watch changes to an object of kind Endpoints

```
GET /api/v1/watch/namespaces/{namespace}/endpoints/{name}
```

3.2.257.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParamet er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamet er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParamet er	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	
QueryParamet er	resourceVersio n	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	
QueryParamet er	timeoutSecond s	Timeout for the list/watch call.	false	integer	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	

Type	Name	Description	Required	Schema	Default
PathParameter	name	name of the Endpoints	true	string	

3.2.257.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.1, “versioned.Event”

3.2.257.3. Consumes

- /

3.2.257.4. Produces

- application/json
- application/json;stream=watch
- application/vnd.kubernetes.protobuf
- application/vnd.kubernetes.protobuf;stream=watch

3.2.257.5. Tags

- apiv1

3.2.258. watch individual changes to a list of Event

```
GET /api/v1/watch/namespaces/{namespace}/events
```

3.2.258.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParamet er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParamet er	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersio n.	false	boolean	
QueryParamet er	resourceVersio n	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	
QueryParamet er	timeoutSecond s	Timeout for the list/watch call.	false	integer	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	

3.2.258.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.1, “versioned.Event”

3.2.258.3. Consumes

- /

3.2.258.4. Produces

- application/json
- application/json;stream=watch
- application/vnd.kubernetes.protobuf
- application/vnd.kubernetes.protobuf;stream=watch

3.2.258.5. Tags

- apiv1

3.2.259. watch changes to an object of kind Event

GET /api/v1/watch/namespaces/{namespace}/events/{name}

3.2.259.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamet er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParameter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	
QueryParameter	resourceVersion	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	
QueryParameter	timeoutSeconds	Timeout for the list/watch call.	false	integer	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParameter	name	name of the Event	true	string	

3.2.259.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.1, “versioned.Event”

3.2.259.3. Consumes

- /

3.2.259.4. Produces

- application/json
- application/json;stream=watch
- application/vnd.kubernetes.protobuf
- application/vnd.kubernetes.protobuf;stream=watch

3.2.259.5. Tags

- apiv1

3.2.260. watch individual changes to a list of LimitRange

GET /api/v1/watch/namespaces/{namespace}/limitranges

3.2.260.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamet er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParamet er	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParamet er	resourceVersio n	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	
QueryParamet er	timeoutSecond s	Timeout for the list/watch call.	false	integer	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	

3.2.260.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.1, “versioned.Event”

3.2.260.3. Consumes

- /

3.2.260.4. Produces

- application/json
- application/json;stream=watch
- application/vnd.kubernetes.protobuf
- application/vnd.kubernetes.protobuf;stream=watch

3.2.260.5. Tags

- apiv1

3.2.261. watch changes to an object of kind LimitRange

-

GET /api/v1/watch/namespaces/{namespace}/limitranges/{name}

3.2.261.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamet er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParamet er	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	
QueryParamet er	resourceVersio n	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	
QueryParamet er	timeoutSecond s	Timeout for the list/watch call.	false	integer	

Type	Name	Description	Required	Schema	Default
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParameter	name	name of the LimitRange	true	string	

3.2.261.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.1, “versioned.Event”

3.2.261.3. Consumes

- /

3.2.261.4. Produces

- application/json
- application/json;stream=watch
- application/vnd.kubernetes.protobuf
- application/vnd.kubernetes.protobuf;stream=watch

3.2.261.5. Tags

- apiv1

3.2.262. watch individual changes to a list of PersistentVolumeClaim

```
GET /api/v1/watch/namespaces/{namespace}/persistentvolumeclaims
```

3.2.262.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParamet er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamet er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParamet er	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	
QueryParamet er	resourceVersio n	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	
QueryParamet er	timeoutSecond s	Timeout for the list/watch call.	false	integer	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	

3.2.262.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.1, “versioned.Event”

3.2.262.3. Consumes

- /

3.2.262.4. Produces

- application/json
- application/json;stream=watch
- application/vnd.kubernetes.protobuf
- application/vnd.kubernetes.protobuf;stream=watch

3.2.262.5. Tags

- apiv1

3.2.263. watch changes to an object of kind PersistentVolumeClaim

```
GET /api/v1/watch/namespaces/{namespace}/persistentvolumeclaims/{name}
```

3.2.263.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamet er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParamet er	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersio n.	false	boolean	
QueryParamet er	resourceVersio n	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	
QueryParamet er	timeoutSecond s	Timeout for the list/watch call.	false	integer	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParameter	name	name of the PersistentVolu meClaim	true	string	

3.2.263.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.1, “versioned.Event”

3.2.263.3. Consumes

- /

3.2.263.4. Produces

- application/json
- application/json;stream=watch
- application/vnd.kubernetes.protobuf
- application/vnd.kubernetes.protobuf;stream=watch

3.2.263.5. Tags

- apiv1

3.2.264. watch individual changes to a list of Pod

```
GET /api/v1/watch/namespaces/{namespace}/pods
```

3.2.264.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamet er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParamet er	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParamet er	resourceVersio n	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	
QueryParamet er	timeoutSecond s	Timeout for the list/watch call.	false	integer	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	

3.2.264.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.1, “versioned.Event”

3.2.264.3. Consumes

- /

3.2.264.4. Produces

- application/json
- application/json;stream=watch
- application/vnd.kubernetes.protobuf
- application/vnd.kubernetes.protobuf;stream=watch

3.2.264.5. Tags

- apiv1

3.2.265. watch changes to an object of kind Pod

-

```
GET /api/v1/watch/namespaces/{namespace}/pods/{name}
```

3.2.265.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamet er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParamet er	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	
QueryParamet er	resourceVersio n	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	
QueryParamet er	timeoutSecond s	Timeout for the list/watch call.	false	integer	

Type	Name	Description	Required	Schema	Default
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParameter	name	name of the Pod	true	string	

3.2.265.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.1, “versioned.Event”

3.2.265.3. Consumes

- /

3.2.265.4. Produces

- application/json
- application/json;stream=watch
- application/vnd.kubernetes.protobuf
- application/vnd.kubernetes.protobuf;stream=watch

3.2.265.5. Tags

- apiv1

3.2.266. watch individual changes to a list of PodTemplate

```
GET /api/v1/watch/namespaces/{namespace}/podtemplates
```

3.2.266.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParamet er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamet er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParamet er	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersio n.	false	boolean	
QueryParamet er	resourceVersio n	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	
QueryParamet er	timeoutSecond s	Timeout for the list/watch call.	false	integer	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	

3.2.266.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.1, “versioned.Event”

3.2.266.3. Consumes

- /

3.2.266.4. Produces

- application/json
- application/json;stream=watch
- application/vnd.kubernetes.protobuf
- application/vnd.kubernetes.protobuf;stream=watch

3.2.266.5. Tags

- apiv1

3.2.267. watch changes to an object of kind PodTemplate

```
GET /api/v1/watch/namespaces/{namespace}/podtemplates/{name}
```

3.2.267.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamet er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParamet er	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	
QueryParamet er	resourceVersio n	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	
QueryParamet er	timeoutSecond s	Timeout for the list/watch call.	false	integer	
PathParamet er	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParamet er	name	name of the PodTemplate	true	string	

3.2.267.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.1, “versioned.Event”

3.2.267.3. Consumes

- /

3.2.267.4. Produces

- application/json
- application/json;stream=watch
- application/vnd.kubernetes.protobuf
- application/vnd.kubernetes.protobuf;stream=watch

3.2.267.5. Tags

- apiv1

3.2.268. watch individual changes to a list of ReplicationController

```
GET /api/v1/watch/namespaces/{namespace}/replicationcontrollers
```

3.2.268.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamet er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParamet er	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParameter	resourceVersion	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	
QueryParameter	timeoutSeconds	Timeout for the list/watch call.	false	integer	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	

3.2.268.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.1, “versioned.Event”

3.2.268.3. Consumes

- /

3.2.268.4. Produces

- application/json
- application/json;stream=watch
- application/vnd.kubernetes.protobuf
- application/vnd.kubernetes.protobuf;stream=watch

3.2.268.5. Tags

- apiv1

3.2.269. watch changes to an object of kind ReplicationController

-

```
GET /api/v1/watch/namespaces/{namespace}/replicationcontrollers/{name}
```

3.2.269.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamet er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParamet er	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	
QueryParamet er	resourceVersio n	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	
QueryParamet er	timeoutSecond s	Timeout for the list/watch call.	false	integer	

Type	Name	Description	Required	Schema	Default
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParameter	name	name of the ReplicationController	true	string	

3.2.269.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.1, “versioned.Event”

3.2.269.3. Consumes

- /

3.2.269.4. Produces

- application/json
- application/json;stream=watch
- application/vnd.kubernetes.protobuf
- application/vnd.kubernetes.protobuf;stream=watch

3.2.269.5. Tags

- apiv1

3.2.270. watch individual changes to a list of ResourceQuota

```
GET /api/v1/watch/namespaces/{namespace}/resourcequotas
```

3.2.270.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParamet er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamet er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParamet er	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersio n.	false	boolean	
QueryParamet er	resourceVersio n	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	
QueryParamet er	timeoutSecond s	Timeout for the list/watch call.	false	integer	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	

3.2.270.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.1, “versioned.Event”

3.2.270.3. Consumes

- /

3.2.270.4. Produces

- application/json
- application/json;stream=watch
- application/vnd.kubernetes.protobuf
- application/vnd.kubernetes.protobuf;stream=watch

3.2.270.5. Tags

- apiv1

3.2.271. watch changes to an object of kind ResourceQuota

```
GET /api/v1/watch/namespaces/{namespace}/resourcequotas/{name}
```

3.2.271.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamet er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParamet er	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersio n.	false	boolean	
QueryParamet er	resourceVersio n	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	
QueryParamet er	timeoutSecond s	Timeout for the list/watch call.	false	integer	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParameter	name	name of the ResourceQuot a	true	string	

3.2.271.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.1, “versioned.Event”

3.2.271.3. Consumes

- /

3.2.271.4. Produces

- application/json
- application/json;stream=watch
- application/vnd.kubernetes.protobuf
- application/vnd.kubernetes.protobuf;stream=watch

3.2.271.5. Tags

- apiv1

3.2.272. watch individual changes to a list of Secret

```
GET /api/v1/watch/namespaces/{namespace}/secrets
```

3.2.272.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamet er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParameter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	
QueryParameter	resourceVersion	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	
QueryParameter	timeoutSeconds	Timeout for the list/watch call.	false	integer	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	

3.2.272.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.1, “versioned.Event”

3.2.272.3. Consumes

- /

3.2.272.4. Produces

- application/json

- application/json;stream=watch
- application/vnd.kubernetes.protobuf
- application/vnd.kubernetes.protobuf;stream=watch

3.2.272.5. Tags

- apiv1

3.2.273. watch changes to an object of kind Secret

```
GET /api/v1/watch/namespaces/{namespace}/secrets/{name}
```

3.2.273.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParam er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParam er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParam er	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParamet er	resourceVersio n	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	
QueryParamet er	timeoutSecond s	Timeout for the list/watch call.	false	integer	
PathParamet er	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParamet er	name	name of the Secret	true	string	

3.2.273.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.1, “versioned.Event”

3.2.273.3. Consumes

- /

3.2.273.4. Produces

- application/json
- application/json;stream=watch
- application/vnd.kubernetes.protobuf
- application/vnd.kubernetes.protobuf;stream=watch

3.2.273.5. Tags

- apiv1

3.2.274. watch individual changes to a list of ServiceAccount

```
GET /api/v1/watch/namespaces/{namespace}/serviceaccounts
```

3.2.274.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamet er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParamet er	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersio n.	false	boolean	
QueryParamet er	resourceVersio n	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParamet er	timeoutSecond s	Timeout for the list/watch call.	false	integer	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	

3.2.274.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.1, “versioned.Event”

3.2.274.3. Consumes

- /

3.2.274.4. Produces

- application/json
- application/json;stream=watch
- application/vnd.kubernetes.protobuf
- application/vnd.kubernetes.protobuf;stream=watch

3.2.274.5. Tags

- apiv1

3.2.275. watch changes to an object of kind ServiceAccount

```
GET /api/v1/watch/namespaces/{namespace}/serviceaccounts/{name}
```

3.2.275.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParamet er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamet er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParamet er	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	
QueryParamet er	resourceVersio n	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	
QueryParamet er	timeoutSecond s	Timeout for the list/watch call.	false	integer	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	

Type	Name	Description	Required	Schema	Default
PathParameter	name	name of the ServiceAccount	true	string	

3.2.275.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.1, “versioned.Event”

3.2.275.3. Consumes

- /

3.2.275.4. Produces

- application/json
- application/json;stream=watch
- application/vnd.kubernetes.protobuf
- application/vnd.kubernetes.protobuf;stream=watch

3.2.275.5. Tags

- apiv1

3.2.276. watch individual changes to a list of Service

```
GET /api/v1/watch/namespaces/{namespace}/services
```

3.2.276.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParamet er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParamet er	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	
QueryParamet er	resourceVersio n	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	
QueryParamet er	timeoutSecond s	Timeout for the list/watch call.	false	integer	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	

3.2.276.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.1, “versioned.Event”

3.2.276.3. Consumes

- /

3.2.276.4. Produces

- application/json
- application/json;stream=watch
- application/vnd.kubernetes.protobuf
- application/vnd.kubernetes.protobuf;stream=watch

3.2.276.5. Tags

- apiv1

3.2.277. watch changes to an object of kind Service

```
GET /api/v1/watch/namespaces/{namespace}/services/{name}
```

3.2.277.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamet er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParameter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	
QueryParameter	resourceVersion	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	
QueryParameter	timeoutSeconds	Timeout for the list/watch call.	false	integer	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParameter	name	name of the Service	true	string	

3.2.277.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.1, “versioned.Event”

3.2.277.3. Consumes

- /

3.2.277.4. Produces

- application/json
- application/json;stream=watch
- application/vnd.kubernetes.protobuf
- application/vnd.kubernetes.protobuf;stream=watch

3.2.277.5. Tags

- apiv1

3.2.278. watch changes to an object of kind Namespace

```
GET /api/v1/watch/namespaces/{name}
```

3.2.278.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamet er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParamet er	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParamet er	resourceVersio n	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	
QueryParamet er	timeoutSecond s	Timeout for the list/watch call.	false	integer	
PathParameter	name	name of the Namespace	true	string	

3.2.278.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.1, “versioned.Event”

3.2.278.3. Consumes

- /

3.2.278.4. Produces

- application/json
- application/json;stream=watch
- application/vnd.kubernetes.protobuf
- application/vnd.kubernetes.protobuf;stream=watch

3.2.278.5. Tags

- apiv1

3.2.279. watch individual changes to a list of Node

GET /api/v1/watch/nodes

3.2.279.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamet er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParamet er	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersio n.	false	boolean	
QueryParamet er	resourceVersio n	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	
QueryParamet er	timeoutSecond s	Timeout for the list/watch call.	false	integer	

3.2.279.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.1, “versioned.Event”

3.2.279.3. Consumes

- /

3.2.279.4. Produces

- application/json
- application/json;stream=watch
- application/vnd.kubernetes.protobuf
- application/vnd.kubernetes.protobuf;stream=watch

3.2.279.5. Tags

- apiv1

3.2.280. watch changes to an object of kind Node

```
GET /api/v1/watch/nodes/{name}
```

3.2.280.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamet er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParamet er	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersio n.	false	boolean	
QueryParamet er	resourceVersio n	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	
QueryParamet er	timeoutSecond s	Timeout for the list/watch call.	false	integer	
PathParameter	name	name of the Node	true	string	

3.2.280.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.1, “versioned.Event”

3.2.280.3. Consumes

- /

3.2.280.4. Produces

- application/json
- application/json;stream=watch
- application/vnd.kubernetes.protobuf

- application/vnd.kubernetes.protobuf;stream=watch

3.2.280.5. Tags

- apiv1

3.2.281. watch individual changes to a list of PersistentVolumeClaim

GET /api/v1/watch/persistentvolumeclaims

3.2.281.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamet er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParamet er	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParam er	resourceVersio n	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	
QueryParam er	timeoutSecond s	Timeout for the list/watch call.	false	integer	

3.2.281.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.1, “versioned.Event”

3.2.281.3. Consumes

- /

3.2.281.4. Produces

- application/json
- application/json;stream=watch
- application/vnd.kubernetes.protobuf
- application/vnd.kubernetes.protobuf;stream=watch

3.2.281.5. Tags

- apiv1

3.2.282. watch individual changes to a list of PersistentVolume

```
GET /api/v1/watch/persistentvolumes
```

3.2.282.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamet er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParamet er	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	
QueryParamet er	resourceVersio n	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	
QueryParamet er	timeoutSecond s	Timeout for the list/watch call.	false	integer	

3.2.282.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.1, “versioned.Event”

3.2.282.3. Consumes

- /

3.2.282.4. Produces

- application/json
- application/json;stream=watch
- application/vnd.kubernetes.protobuf
- application/vnd.kubernetes.protobuf;stream=watch

3.2.282.5. Tags

- apiv1

3.2.283. watch changes to an object of kind PersistentVolume

```
GET /api/v1/watch/persistentvolumes/{name}
```

3.2.283.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamet er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParamet er	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersio n.	false	boolean	
QueryParamet er	resourceVersio n	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	
QueryParamet er	timeoutSecond s	Timeout for the list/watch call.	false	integer	
PathParameter	name	name of the PersistentVolu me	true	string	

3.2.283.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.1, “versioned.Event”

3.2.283.3. Consumes

- /

3.2.283.4. Produces

- application/json
- application/json;stream=watch

- application/vnd.kubernetes.protobuf
- application/vnd.kubernetes.protobuf;stream=watch

3.2.283.5. Tags

- apiv1

3.2.284. watch individual changes to a list of Pod

GET /api/v1/watch/pods

3.2.284.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamet er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParamet er	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParamet er	resourceVersio n	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	
QueryParamet er	timeoutSecond s	Timeout for the list/watch call.	false	integer	

3.2.284.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.1, “versioned.Event”

3.2.284.3. Consumes

- /

3.2.284.4. Produces

- application/json
- application/json;stream=watch
- application/vnd.kubernetes.protobuf
- application/vnd.kubernetes.protobuf;stream=watch

3.2.284.5. Tags

- apiv1

3.2.285. watch individual changes to a list of PodTemplate

```
GET /api/v1/watch/podtemplates
```

3.2.285.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamet er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParamet er	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	
QueryParamet er	resourceVersio n	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	
QueryParamet er	timeoutSecond s	Timeout for the list/watch call.	false	integer	

3.2.285.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.1, “versioned.Event”

3.2.285.3. Consumes

- /

3.2.285.4. Produces

- application/json
- application/json;stream=watch
- application/vnd.kubernetes.protobuf
- application/vnd.kubernetes.protobuf;stream=watch

3.2.285.5. Tags

- apiv1

3.2.286. watch individual changes to a list of ReplicationController

GET /api/v1/watch/replicationcontrollers

3.2.286.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamet er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParamet er	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersio n.	false	boolean	
QueryParamet er	resourceVersio n	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	
QueryParamet er	timeoutSecond s	Timeout for the list/watch call.	false	integer	

3.2.286.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.1, “versioned.Event”

3.2.286.3. Consumes

- /

3.2.286.4. Produces

- application/json
- application/json;stream=watch
- application/vnd.kubernetes.protobuf
- application/vnd.kubernetes.protobuf;stream=watch

3.2.286.5. Tags

- apiv1

3.2.287. watch individual changes to a list of ResourceQuota

GET /api/v1/watch/resourcequotas

3.2.287.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamet er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParamet er	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParam er	resourceVersio n	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	
QueryParam er	timeoutSecond s	Timeout for the list/watch call.	false	integer	

3.2.287.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.1, “versioned.Event”

3.2.287.3. Consumes

- /

3.2.287.4. Produces

- application/json
- application/json;stream=watch
- application/vnd.kubernetes.protobuf
- application/vnd.kubernetes.protobuf;stream=watch

3.2.287.5. Tags

- apiv1

3.2.288. watch individual changes to a list of Secret

```
GET /api/v1/watch/secrets
```

3.2.288.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamet er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParamet er	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	
QueryParamet er	resourceVersio n	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	
QueryParamet er	timeoutSecond s	Timeout for the list/watch call.	false	integer	

3.2.288.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.1, “versioned.Event”

3.2.288.3. Consumes

- /

3.2.288.4. Produces

- application/json
- application/json;stream=watch
- application/vnd.kubernetes.protobuf
- application/vnd.kubernetes.protobuf;stream=watch

3.2.288.5. Tags

- apiv1

3.2.289. watch individual changes to a list of SecurityContextConstraints

GET /api/v1/watch/securitycontextconstraints

3.2.289.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamet er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParamet er	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	
QueryParamet er	resourceVersio n	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	
QueryParamet er	timeoutSecond s	Timeout for the list/watch call.	false	integer	

3.2.289.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.1, “versioned.Event”

3.2.289.3. Consumes

- /

3.2.289.4. Produces

- application/json
- application/json;stream=watch
- application/vnd.kubernetes.protobuf
- application/vnd.kubernetes.protobuf;stream=watch

3.2.289.5. Tags

- apiv1

3.2.290. watch changes to an object of kind SecurityContextConstraints

```
GET /api/v1/watch/securitycontextconstraints/{name}
```

3.2.290.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamet er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParamet er	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParamet er	resourceVersio n	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	
QueryParamet er	timeoutSecond s	Timeout for the list/watch call.	false	integer	
PathParameter	name	name of the SecurityContextConstraints	true	string	

3.2.290.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.1, “versioned.Event”

3.2.290.3. Consumes

- /

3.2.290.4. Produces

- application/json
- application/json;stream=watch
- application/vnd.kubernetes.protobuf
- application/vnd.kubernetes.protobuf;stream=watch

3.2.290.5. Tags

- apiv1

3.2.291. watch individual changes to a list of ServiceAccount

GET /api/v1/watch/serviceaccounts

3.2.291.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamet er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParamet er	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	
QueryParamet er	resourceVersio n	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	
QueryParamet er	timeoutSecond s	Timeout for the list/watch call.	false	integer	

3.2.291.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.1, “versioned.Event”

3.2.291.3. Consumes

- /

3.2.291.4. Produces

- application/json
- application/json;stream=watch
- application/vnd.kubernetes.protobuf
- application/vnd.kubernetes.protobuf;stream=watch

3.2.291.5. Tags

- apiv1

3.2.292. watch individual changes to a list of Service

GET /api/v1/watch/services

3.2.292.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamet er	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamet er	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParamet er	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	
QueryParamet er	resourceVersio n	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history.	false	string	
QueryParamet er	timeoutSecond s	Timeout for the list/watch call.	false	integer	

3.2.292.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.1, “versioned.Event”

3.2.292.3. Consumes

- /

3.2.292.4. Produces

- application/json
- application/json;stream=watch
- application/vnd.kubernetes.protobuf

- application/vnd.kubernetes.protobuf;stream=watch

3.2.292.5. Tags

- apiv1

3.3. DEFINITIONS

3.3.1. versioned.Event

3.3.2. types.UID

3.3.3. unversioned.APIResource

APIResource specifies the name of a resource and whether it is namespaced.

Name	Description	Required	Schema	Default
name	name is the name of the resource.	true	string	
namespaced	namespaced indicates if a resource is namespaced or not.	true	boolean	
kind	kind is the kind for the resource (e.g. 'Foo' is the kind for a resource 'foo')	true	string	

3.3.4. unversioned.APIResourceList

APIResourceList is a list of APIResource, it is used to expose the name of the resources supported in a specific group and version, and if the resource is namespaced.

Name	Description	Required	Schema	Default
------	-------------	----------	--------	---------

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#types-kinds	false	string	
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#resources	false	string	
groupVersion	groupVersion is the group and version this APIResourceList is for.	true	string	
resources	resources contains the name of the resources and if they are namespaced.	true	Section 2.3.5, "unversioned.APIResource" array	

3.3.5. unversioned.LabelSelector

A label selector is a label query over a set of resources. The result of `matchLabels` and `matchExpressions` are ANDed. An empty label selector matches all objects. A null label selector matches no objects.

Name	Description	Required	Schema	Default
<code>matchLabels</code>	<code>matchLabels</code> is a map of {key,value} pairs. A single {key,value} in the <code>matchLabels</code> map is equivalent to an element of <code>matchExpressions</code> , whose key field is "key", the operator is "In", and the values array contains only "value". The requirements are ANDed.	false	object	
<code>matchExpressions</code>	<code>matchExpressions</code> is a list of label selector requirements. The requirements are ANDed.	false	Section 2.3.8, "unversioned.LabelSelectorRequirement" array	

3.3.6. unversioned.LabelSelectorRequirement

A label selector requirement is a selector that contains values, a key, and an operator that relates the key and values.

Name	Description	Required	Schema	Default
<code>key</code>	<code>key</code> is the label key that the selector applies to.	true	string	
<code>operator</code>	<code>operator</code> represents a key's relationship to a set of values. Valid operators are In, NotIn, Exists and DoesNotExist.	true	string	

Name	Description	Required	Schema	Default
values	values is an array of string values. If the operator is In or NotIn, the values array must be non-empty. If the operator is Exists or DoesNotExist, the values array must be empty. This array is replaced during a strategic merge patch.	false	string array	

3.3.7. unversioned.ListMeta

ListMeta describes metadata that synthetic resources must have, including lists and various status objects. A resource may have only one of {ObjectMeta, ListMeta}.

Name	Description	Required	Schema	Default
selfLink	SelfLink is a URL representing this object. Populated by the system. Read-only.	false	string	

Name	Description	Required	Schema	Default
resourceVersion	String that identifies the server's internal version of this object that can be used by clients to determine when objects have changed. Value must be treated as opaque by clients and passed unmodified back to the server. Populated by the system. Read-only. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#concurrency-control-and-consistency	false	string	

3.3.8. unversioned.Patch

Patch is provided to give a concrete name and type to the Kubernetes PATCH request body.

3.3.9. unversioned.Status

Status is a return value for calls that don't return other objects.

Name	Description	Required	Schema	Default
------	-------------	----------	--------	---------

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#types-kinds	false	string	
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#resources	false	string	
metadata	Standard list metadata. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#types-kinds	false	Section 2.3.9, "unversioned.ListMeta"	

Name	Description	Required	Schema	Default
status	Status of the operation. One of: "Success" or "Failure". More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#pec-and-status	false	string	
message	A human-readable description of the status of this operation.	false	string	
reason	A machine-readable description of why this operation is in the "Failure" status. If this value is empty there is no information available. A Reason clarifies an HTTP status code but does not override it.	false	string	
details	Extended data associated with the reason. Each reason may define its own extended details. This field is optional and the data returned is not guaranteed to conform to any schema except that defined by the reason type.	false	Section 2.3.13, "unversioned.StatusDetails"	
code	Suggested HTTP return code for this status, 0 if not set.	false	integer (int32)	

3.3.10. unversioned.StatusCause

StatusCause provides more information about an api.Status failure, including cases when multiple errors are encountered.

Name	Description	Required	Schema	Default
reason	A machine-readable description of the cause of the error. If this value is empty there is no information available.	false	string	
message	A human-readable description of the cause of the error. This field may be presented as-is to a reader.	false	string	
field	The field of the resource that has caused this error, as named by its JSON serialization. May include dot and postfix notation for nested attributes. Arrays are zero-indexed. Fields may appear more than once in an array of causes due to fields having multiple errors. Optional. Examples: "name" - the field "name" on the current resource "items[0].name" - the field "name" on the first array entry in "items"	false	string	

3.3.11. unversioned.StatusDetails

StatusDetails is a set of additional properties that MAY be set by the server to provide additional information about a response. The Reason field of a Status object defines what attributes will be set. Clients must ignore fields that do not match the defined type of each attribute, and should assume that any attribute may be empty, invalid, or under defined.

Name	Description	Required	Schema	Default
name	The name attribute of the resource associated with the status <code>StatusReason</code> (when there is a single name which can be described).	false	string	
group	The group attribute of the resource associated with the status <code>StatusReason</code> .	false	string	
kind	The kind attribute of the resource associated with the status <code>StatusReason</code> . On some operations may differ from the requested resource Kind. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#types-kinds	false	string	
causes	The Causes array includes more details associated with the <code>StatusReason</code> failure. Not all <code>StatusReasons</code> may provide detailed causes.	false	Section 2.3.12, “unversioned.StatusCause” array	
retryAfterSeconds	If specified, the time in seconds before the operation should be retried.	false	integer (int32)	

3.3.12. v1.AWSElasticBlockStoreVolumeSource

Represents a Persistent Disk resource in AWS.

An AWS EBS disk must exist before mounting to a container. The disk must also be in the same AWS zone as the kubelet. An AWS EBS disk can only be mounted as read/write once. AWS EBS volumes support ownership management and SELinux relabeling.

Name	Description	Required	Schema	Default
volumeID	Unique ID of the persistent disk resource in AWS (Amazon EBS volume). More info: http://releases.k8s.io/release-1.3/docs/user-guide/volumes.md#awselasticblockstore	true	string	
fsType	Filesystem type of the volume that you want to mount. Tip: Ensure that the filesystem type is supported by the host operating system. Examples: "ext4", "xfs", "ntfs". Implicitly inferred to be "ext4" if unspecified. More info: http://releases.k8s.io/release-1.3/docs/user-guide/volumes.md#awselasticblockstore	false	string	
partition	The partition in the volume that you want to mount. If omitted, the default is to mount by volume name. Examples: For volume /dev/sda1, you specify the partition as "1". Similarly, the volume partition for /dev/sda is "0" (or you can leave the property empty).	false	integer (int32)	

Name	Description	Required	Schema	Default
readOnly	Specify "true" to force and set the ReadOnly property in VolumeMounts to "true". If omitted, the default is "false". More info: http://releases.k8s.io/release-1.3/docs/user-guide/volumes.md#awselasticblockstore	false	boolean	

3.3.13. v1.AttachedVolume

AttachedVolume describes a volume attached to a node

Name	Description	Required	Schema	Default
name	Name of the attached volume	true	string	
devicePath	DevicePath represents the device path where the volume should be available	true	string	

3.3.14. v1.AzureFileVolumeSource

AzureFile represents an Azure File Service mount on the host and bind mount to the pod.

Name	Description	Required	Schema	Default
secretName	the name of secret that contains Azure Storage Account Name and Key	true	string	
shareName	Share Name	true	string	

Name	Description	Required	Schema	Default
readOnly	Defaults to false (read/write). ReadOnly here will force the ReadOnly setting in VolumeMounts.	false	boolean	

3.3.15. v1.Binding

Binding ties one object to another. For example, a pod is bound to a node by a scheduler.

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#types-kinds	false	string	

Name	Description	Required	Schema	Default
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#resources	false	string	
metadata	Standard object's metadata. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#metadata	false	Section 2.3.158, "v1.ObjectMeta"	
target	The target object that you want to bind to the standard object.	true	Section 2.3.159, "v1.ObjectReference"	

3.3.16. v1.Capabilities

Adds and removes POSIX capabilities from running containers.

Name	Description	Required	Schema	Default
add	Added capabilities	false	Section 2.3.36, "v1.Capability" array	
drop	Removed capabilities	false	Section 2.3.36, "v1.Capability" array	

3.3.17. v1.Capability

3.3.18. v1.CephFSVolumeSource

Represents a Ceph Filesystem mount that lasts the lifetime of a pod Cephfs volumes do not support ownership management or SELinux relabeling.

Name	Description	Required	Schema	Default
monitors	Required: Monitors is a collection of Ceph monitors More info: http://releases.k8s.io/release-1.3/examples/cephfs/README.md#how-to-use-it	true	string array	
path	Optional: Used as the mounted root, rather than the full Ceph tree, default is /	false	string	
user	Optional: User is the rados user name, default is admin More info: http://releases.k8s.io/release-1.3/examples/cephfs/README.md#how-to-use-it	false	string	
secretFile	Optional: SecretFile is the path to key ring for User, default is /etc/ceph/user.secret More info: http://releases.k8s.io/release-1.3/examples/cephfs/README.md#how-to-use-it	false	string	

Name	Description	Required	Schema	Default
secretRef	Optional: SecretRef is reference to the authentication secret for User, default is empty. More info: http://releases.k8s.io/release-1.3/examples/cephfs/README.md#how-to-use-it	false	Section 2.3.138, "v1.LocalObjectReference"	
readOnly	Optional: Defaults to false (read/write). ReadOnly here will force the ReadOnly setting in VolumeMounts. More info: http://releases.k8s.io/release-1.3/examples/cephfs/README.md#how-to-use-it	false	boolean	

3.3.19. v1.CinderVolumeSource

CinderVolumeSource represents a cinder volume resource in Openstack. A Cinder volume must exist before mounting to a container. The volume must also be in the same region as the kubelet.

Name	Description	Required	Schema	Default
volumeID	volume id used to identify the volume in cinder More info: http://releases.k8s.io/release-1.3/examples/mysql-cinder-pd/README.md	true	string	

Name	Description	Required	Schema	Default
fsType	Filesystem type to mount. Must be a filesystem type supported by the host operating system. Examples: "ext4", "xfs", "ntfs". Implicitly inferred to be "ext4" if unspecified. More info: http://releases.k8s.io/release-1.3/examples/mysql-cinder-pd/README.md	false	string	
readOnly	Optional: Defaults to false (read/write). ReadOnly here will force the ReadOnly setting in VolumeMounts. More info: http://releases.k8s.io/release-1.3/examples/mysql-cinder-pd/README.md	false	boolean	

3.3.20. v1.ComponentCondition

Information about the condition of a component.

Name	Description	Required	Schema	Default
type	Type of condition for a component. Valid value: "Healthy"	true	string	
status	Status of the condition for a component. Valid values for "Healthy": "True", "False", or "Unknown".	true	string	

Name	Description	Required	Schema	Default
message	Message about the condition for a component. For example, information about a health check.	false	string	
error	Condition error code for a component. For example, a health check error code.	false	string	

3.3.21. v1.ComponentStatus

ComponentStatus (and ComponentStatusList) holds the cluster validation info.

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#types-kinds	false	string	

Name	Description	Required	Schema	Default
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#resources	false	string	
metadata	Standard object's metadata. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#metadata	false	Section 2.3.158 , "v1.ObjectMeta"	
conditions	List of component conditions observed	false	Section 3.3.20 , "v1.ComponentCondition" array	

3.3.22. v1.ComponentStatusList

Status of all the conditions for the component as a list of ComponentStatus objects.

Name	Description	Required	Schema	Default
------	-------------	----------	--------	---------

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#types-kinds	false	string	
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#resources	false	string	
metadata	Standard list metadata. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#types-kinds	false	Section 2.3.9, “unversioned.ListMeta”	
items	List of ComponentStatus objects.	true	Section 3.3.21, “v1.ComponentStatus” array	

3.3.23. v1.ConfigMap

ConfigMap holds configuration data for pods to consume.

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#types-kinds	false	string	
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#resources	false	string	
metadata	Standard object's metadata. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#metadata	false	Section 2.3.158, "v1.ObjectMeta"	

Name	Description	Required	Schema	Default
data	Data contains the configuration data. Each key must be a valid DNS_SUBDOMAIN with an optional leading dot.	false	object	

3.3.24. v1.ConfigMapKeySelector

Selects a key from a ConfigMap.

Name	Description	Required	Schema	Default
name	Name of the referent. More info: http://releases.k8s.io/release-1.3/docs/user-guide/identifiers.md#names	false	string	
key	The key to select.	true	string	

3.3.25. v1.ConfigMapList

ConfigMapList is a resource containing a list of ConfigMap objects.

Name	Description	Required	Schema	Default
------	-------------	----------	--------	---------

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#types-kinds	false	string	
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#resources	false	string	
metadata	More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#metadata	false	Section 2.3.9, “unversioned.ListMeta”	
items	Items is the list of ConfigMaps.	true	Section 3.3.23, “v1.ConfigMap” array	

3.3.26. v1.ConfigMapVolumeSource

Adapts a ConfigMap into a volume.

The contents of the target ConfigMap's Data field will be presented in a volume as files using the keys in the Data field as the file names, unless the items element is populated with specific mappings of keys to paths. ConfigMap volumes support ownership management and SELinux relabeling.

Name	Description	Required	Schema	Default
name	Name of the referent. More info: http://releases.k8s.io/release-1.3/docs/user-guide/identifiers.md#names	false	string	
items	If unspecified, each key-value pair in the Data field of the referenced ConfigMap will be projected into the volume as a file whose name is the key and content is the value. If specified, the listed keys will be projected into the specified paths, and unlisted keys will not be present. If a key is specified which is not present in the ConfigMap, the volume setup will error. Paths must be relative and may not contain the '..' path or start with '..'.	false	Section 2.3.135, "v1.KeyToPath" array	

3.3.27. v1.Container

A single application container that you want to run within a pod.

Name	Description	Required	Schema	Default
name	Name of the container specified as a DNS_LABEL. Each container in a pod must have a unique name (DNS_LABEL). Cannot be updated.	true	string	
image	Docker image name. More info: http://releases.k8s.io/release-1.3/docs/user-guide/images.md	false	string	

Name	Description	Required	Schema	Default
command	<p>Entrypoint array. Not executed within a shell. The docker image's ENTRYPOINT is used if this is not provided. Variable references <code>\$(VAR_NAME)</code> are expanded using the container's environment. If a variable cannot be resolved, the reference in the input string will be unchanged. The <code>\$(VAR_NAME)</code> syntax can be escaped with a double <code>,</code> ie: <code>(VAR_NAME)</code>. Escaped references will never be expanded, regardless of whether the variable exists or not. Cannot be updated. More info: http://releases.k8s.io/release-1.3/docs/user-guide/containers.md#containers-and-commands</p>	false	string array	

Name	Description	Required	Schema	Default
args	<p>Arguments to the endpoint. The docker image's CMD is used if this is not provided. Variable references \$(VAR_NAME) are expanded using the container's environment. If a variable cannot be resolved, the reference in the input string will be unchanged. The \$(VAR_NAME) syntax can be escaped with a double , ie: (VAR_NAME). Escaped references will never be expanded, regardless of whether the variable exists or not. Cannot be updated. More info: http://releases.k8s.io/release-1.3/docs/user-guide/containers.md#containers-and-commands</p>	false	string array	
workingDir	<p>Container's working directory. If not specified, the container runtime's default will be used, which might be configured in the container image. Cannot be updated.</p>	false	string	

Name	Description	Required	Schema	Default
ports	List of ports to expose from the container. Exposing a port here gives the system additional information about the network connections a container uses, but is primarily informational. Not specifying a port here DOES NOT prevent that port from being exposed. Any port which is listening on the default "0.0.0.0" address inside a container will be accessible from the network. Cannot be updated.	false	Section 2.3.58 , "v1.ContainerPort" array	
env	List of environment variables to set in the container. Cannot be updated.	false	Section 2.3.86 , "v1.EnvVar" array	
resources	Compute Resources required by this container. Cannot be updated. More info: http://releases.k8s.io/release-1.3/docs/user-guide/persistent-volumes.md#resources	false	Section 2.3.188 , "v1.ResourceRequirements"	
volumeMounts	Pod volumes to mount into the container's filesystem. Cannot be updated.	false	Section 2.3.234 , "v1.VolumeMount" array	

Name	Description	Required	Schema	Default
livenessProbe	Periodic probe of container liveness. Container will be restarted if the probe fails. Cannot be updated. More info: http://releases.k8s.io/release-1.3/docs/user-guide/pod-states.md#container-probes	false	Section 2.3.172, "v1.Probe"	
readinessProbe	Periodic probe of container service readiness. Container will be removed from service endpoints if the probe fails. Cannot be updated. More info: http://releases.k8s.io/release-1.3/docs/user-guide/pod-states.md#container-probes	false	Section 2.3.172, "v1.Probe"	
lifecycle	Actions that the management system should take in response to container lifecycle events. Cannot be updated.	false	Section 2.3.136, "v1.Lifecycle"	

Name	Description	Required	Schema	Default
terminationMessagePath	Optional: Path at which the file to which the container's termination message will be written is mounted into the container's filesystem. Message written is intended to be brief final status, such as an assertion failure message. Defaults to /dev/termination-log. Cannot be updated.	false	string	
imagePullPolicy	Image pull policy. One of Always, Never, IfNotPresent. Defaults to Always if :latest tag is specified, or IfNotPresent otherwise. Cannot be updated. More info: http://releases.k8s.io/release-1.3/docs/user-guide/images.md#updating-images	false	string	
securityContext	Security options the pod should run with. More info: http://releases.k8s.io/release-1.3/docs/design/security_context.md	false	Section 2.3.210, "v1.SecurityContext"	

Name	Description	Required	Schema	Default
stdin	Whether this container should allocate a buffer for stdin in the container runtime. If this is not set, reads from stdin in the container will always result in EOF. Default is false.	false	boolean	
stdinOnce	Whether the container runtime should close the stdin channel after it has been opened by a single attach. When stdin is true the stdin stream will remain open across multiple attach sessions. If stdinOnce is set to true, stdin is opened on container start, is empty until the first client attaches to stdin, and then remains open and accepts data until the client disconnects, at which time stdin is closed and remains closed until the container is restarted. If this flag is false, a container processes that reads from stdin will never receive an EOF. Default is false	false	boolean	

Name	Description	Required	Schema	Default
tty	Whether this container should allocate a TTY for itself, also requires 'stdin' to be true. Default is false.	false	boolean	

3.3.28. v1.ContainerImage

Describe a container image

Name	Description	Required	Schema	Default
names	Names by which this image is known. e.g. ["gcr.io/google_containers/hyperkube:v1.0.7", "dockerhub.io/google_containers/hyperkube:v1.0.7"]	true	string array	
sizeBytes	The size of the image in bytes.	false	integer (int64)	

3.3.29. v1.ContainerPort

ContainerPort represents a network port in a single container.

Name	Description	Required	Schema	Default
name	If specified, this must be an IANA_SVC_NAME and unique within the pod. Each named port in a pod must have a unique name. Name for the port that can be referred to by services.	false	string	

Name	Description	Required	Schema	Default
hostPort	Number of port to expose on the host. If specified, this must be a valid port number, $0 < x < 65536$. If HostNetwork is specified, this must match ContainerPort. Most containers do not need this.	false	integer (int32)	
containerPort	Number of port to expose on the pod's IP address. This must be a valid port number, $0 < x < 65536$.	true	integer (int32)	
protocol	Protocol for port. Must be UDP or TCP. Defaults to "TCP".	false	string	
hostIP	What host IP to bind the external port to.	false	string	

3.3.30. v1.ContainerState

ContainerState holds a possible state of container. Only one of its members may be specified. If none of them is specified, the default one is ContainerStateWaiting.

Name	Description	Required	Schema	Default
waiting	Details about a waiting container	false	Section 3.3.33, "v1.ContainerState Waiting"	
running	Details about a running container	false	Section 3.3.31, "v1.ContainerState Running"	
terminated	Details about a terminated container	false	Section 3.3.32, "v1.ContainerState Terminated"	

3.3.31. v1.ContainerStateRunning

ContainerStateRunning is a running state of a container.

Name	Description	Required	Schema	Default
startedAt	Time at which the container was last (re-)started	false	string	

3.3.32. v1.ContainerStateTerminated

ContainerStateTerminated is a terminated state of a container.

Name	Description	Required	Schema	Default
exitCode	Exit status from the last termination of the container	true	integer (int32)	
signal	Signal from the last termination of the container	false	integer (int32)	
reason	(brief) reason from the last termination of the container	false	string	
message	Message regarding the last termination of the container	false	string	
startedAt	Time at which previous execution of the container started	false	string	
finishedAt	Time at which the container last terminated	false	string	
containerID	Container's ID in the format 'docker://<container_id>'	false	string	

3.3.33. v1.ContainerStateWaiting

ContainerStateWaiting is a waiting state of a container.

Name	Description	Required	Schema	Default
reason	(brief) reason the container is not yet running.	false	string	
message	Message regarding why the container is not yet running.	false	string	

3.3.34. v1.ContainerStatus

ContainerStatus contains details for the current status of this container.

Name	Description	Required	Schema	Default
name	This must be a DNS_LABEL. Each container in a pod must have a unique name. Cannot be updated.	true	string	
state	Details about the container's current condition.	false	Section 3.3.30, "v1.ContainerState"	
lastState	Details about the container's last termination condition.	false	Section 3.3.30, "v1.ContainerState"	
ready	Specifies whether the container has passed its readiness probe.	true	boolean	

Name	Description	Required	Schema	Default
restartCount	The number of times the container has been restarted, currently based on the number of dead containers that have not yet been removed. Note that this is calculated from dead containers. But those containers are subject to garbage collection. This value will get capped at 5 by GC.	true	integer (int32)	
image	The image the container is running. More info: http://releases.k8s.io/release-1.3/docs/user-guide/images.md	true	string	
imageID	ImageID of the container's image.	true	string	
containerID	Container's ID in the format 'docker://<container_id>'. More info: http://releases.k8s.io/release-1.3/docs/user-guide/container-environment.md#container-information	false	string	

3.3.35. v1.DaemonEndpoint

DaemonEndpoint contains information about a single Daemon endpoint.

Name	Description	Required	Schema	Default
------	-------------	----------	--------	---------

Name	Description	Required	Schema	Default
Port	Port number of the given endpoint.	true	integer (int32)	

3.3.36. v1.DeleteOptions

DeleteOptions may be provided when deleting an API object

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#types-kinds	false	string	
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#resources	false	string	

Name	Description	Required	Schema	Default
gracePeriodSeconds	The duration in seconds before the object should be deleted. Value must be non-negative integer. The value zero indicates delete immediately. If this value is nil, the default grace period for the specified type will be used. Defaults to a per object value if not specified. zero means delete immediately.	false	integer (int64)	
preconditions	Must be fulfilled before a deletion is carried out. If not possible, a 409 Conflict status will be returned.	false	Section 2.3.171, "v1.Preconditions"	
orphanDependents	Should the dependent objects be orphaned. If true/false, the "orphan" finalizer will be added to/removed from the object's finalizers list.	false	boolean	

3.3.37. v1.DeprecatedDownwardAPIVolumeFile

DeprecatedDownwardAPIVolumeFile represents information to create the file containing the pod field. This type is deprecated and should be replaced by use of the downwardAPI volume source.

Name	Description	Required	Schema	Default
------	-------------	----------	--------	---------

Name	Description	Required	Schema	Default
name	Required: Name is the relative path name of the file to be created. Must not be absolute or contain the '..' path. Must be utf-8 encoded. The first item of the relative path must not start with '..'	true	string	
fieldRef	Required: Selects a field of the pod: only annotations, labels, name and namespace are supported.	false	Section 2.3.157, "v1.ObjectFieldSelector"	
resourceFieldRef	Selects a resource of the container: only resources limits and requests (limits.cpu, limits.memory, requests.cpu and requests.memory) are currently supported.	false	Section 2.3.183, "v1.ResourceFieldSelector"	

3.3.38. v1.DeprecatedDownwardAPIVolumeSource

DeprecatedDownwardAPIVolumeSource represents a volume containing downward API info. This type is deprecated and should be replaced by use of the downwardAPI volume source.

Name	Description	Required	Schema	Default
items	Items is a list of downward API volume file	false	Section 2.3.75, "v1.DeprecatedDownwardAPIVolumeFile" array	

3.3.39. v1.DownwardAPIVolumeFile

DownwardAPIVolumeFile represents a single file containing information from the downward API

Name	Description	Required	Schema	Default
path	Required: Path is the relative path name of the file to be created. Must not be absolute or contain the '..' path. Must be utf-8 encoded. The first item of the relative path must not start with '..'	true	string	
fieldRef	Required: Selects a field of the pod: only annotations, labels, name and namespace are supported.	false	Section 2.3.157, "v1.ObjectFieldSelector"	
resourceFieldRef	Selects a resource of the container: only resources limits and requests (limits.cpu, limits.memory, requests.cpu and requests.memory) are currently supported.	false	Section 2.3.183, "v1.ResourceFieldSelector"	

3.3.40. v1.DownwardAPIVolumeSource

DownwardAPIVolumeSource represents a volume containing downward API info

Name	Description	Required	Schema	Default
items	Items is a list of downward API volume file	false	Section 2.3.78, "v1.DownwardAPIVolumeFile" array	

3.3.41. v1.EmptyDirVolumeSource

Represents an empty directory for a pod. Empty directory volumes support ownership management and SELinux relabeling.

Name	Description	Required	Schema	Default
------	-------------	----------	--------	---------

Name	Description	Required	Schema	Default
medium	What type of storage medium should back this directory. The default is "" which means to use the node's default medium. Must be an empty string (default) or Memory. More info: http://releases.k8s.io/release-1.3/docs/user-guide/volumes.md#emptydir	false	string	

3.3.42. v1.EndpointAddress

EndpointAddress is a tuple that describes single IP address.

Name	Description	Required	Schema	Default
ip	The IP of this endpoint. May not be loopback (127.0.0.0/8), link-local (169.254.0.0/16), or link-local multicast ((224.0.0.0/24). IPv6 is also accepted but not fully supported on all platforms. Also, certain kubernetes components, like kube-proxy, are not IPv6 ready.	true	string	
hostname	The Hostname of this endpoint	false	string	
targetRef	Reference to object providing the endpoint.	false	Section 2.3.159, "v1.ObjectReference"	

3.3.43. v1.EndpointPort

EndpointPort is a tuple that describes a single port.

Name	Description	Required	Schema	Default
name	The name of this port (corresponds to ServicePort.Name) . Must be a DNS_LABEL. Optional only if one port is defined.	false	string	
port	The port number of the endpoint.	true	integer (int32)	
protocol	The IP protocol for this port. Must be UDP or TCP. Default is TCP.	false	string	

3.3.44. v1.EndpointSubset

EndpointSubset is a group of addresses with a common set of ports. The expanded set of endpoints is the Cartesian product of Addresses x Ports. For example, given:

```
{
  Addresses: [{"ip": "10.10.1.1"}, {"ip": "10.10.2.2"}],
  Ports: [{"name": "a", "port": 8675}, {"name": "b", "port": 309}]
}
```

The resulting set of endpoints can be viewed as:

```
a: [ 10.10.1.1:8675, 10.10.2.2:8675 ],
b: [ 10.10.1.1:309, 10.10.2.2:309 ]
```

Name	Description	Required	Schema	Default
addresses	IP addresses which offer the related ports that are marked as ready. These endpoints should be considered safe for load balancers and clients to utilize.	false	Section 3.3.42, "v1.EndpointAddresses" array	

Name	Description	Required	Schema	Default
notReadyAddresses	IP addresses which offer the related ports but are not currently marked as ready because they have not yet finished starting, have recently failed a readiness check, or have recently failed a liveness check.	false	Section 3.3.42 , “v1.EndpointAddresses” array	
ports	Port numbers available on the related IP addresses.	false	Section 3.3.43 , “v1.EndpointPort” array	

3.3.45. v1.Endpoints

Endpoints is a collection of endpoints that implement the actual service. Example:

Name: "mysvc",

Subsets: [

```
{
  Addresses: [{"ip": "10.10.1.1"}, {"ip": "10.10.2.2"}],
  Ports: [{"name": "a", "port": 8675}, {"name": "b", "port": 309}]
},
{
  Addresses: [{"ip": "10.10.3.3"}],
  Ports: [{"name": "a", "port": 93}, {"name": "b", "port": 76}]
},
]
```

Name	Description	Required	Schema	Default
------	-------------	----------	--------	---------

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#types-kinds	false	string	
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#resources	false	string	
metadata	Standard object's metadata. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#metadata	false	Section 2.3.158, "v1.ObjectMeta"	

Name	Description	Required	Schema	Default
subsets	<p>The set of all endpoints is the union of all subsets.</p> <p>Addresses are placed into subsets according to the IPs they share. A single address with multiple ports, some of which are ready and some of which are not (because they come from different containers) will result in the address being displayed in different subsets for the different ports. No address will appear in both Addresses and NotReadyAddresses in the same subset. Sets of addresses and ports that comprise a service.</p>	true	Section 3.3.44 , “v1.EndpointSubset” array	

3.3.46. v1.EndpointsList

EndpointsList is a list of endpoints.

Name	Description	Required	Schema	Default
------	-------------	----------	--------	---------

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#types-kinds	false	string	
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#resources	false	string	
metadata	Standard list metadata. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#types-kinds	false	Section 2.3.9, "unversioned.ListMeta"	
items	List of endpoints.	true	Section 3.3.45, "v1.Endpoints" array	

3.3.47. v1.EnvVar

EnvVar represents an environment variable present in a Container.

Name	Description	Required	Schema	Default
name	Name of the environment variable. Must be a C_IDENTIFIER.	true	string	
value	Variable references \$(VAR_NAME) are expanded using the previous defined environment variables in the container and any service environment variables. If a variable cannot be resolved, the reference in the input string will be unchanged. The \$(VAR_NAME) syntax can be escaped with a double , ie: (VAR_NAME). Escaped references will never be expanded, regardless of whether the variable exists or not. Defaults to "".	false	string	
valueFrom	Source for the environment variable's value. Cannot be used if value is not empty.	false	Section 2.3.87, "v1.EnvVarSource"	

3.3.48. v1.EnvVarSource

EnvVarSource represents a source for the value of an EnvVar.

Name	Description	Required	Schema	Default
fieldRef	Selects a field of the pod; only name and namespace are supported.	false	Section 2.3.157, "v1.ObjectFieldSelector"	
resourceFieldRef	Selects a resource of the container: only resources limits and requests (limits.cpu, limits.memory, requests.cpu and requests.memory) are currently supported.	false	Section 2.3.183, "v1.ResourceFieldSelector"	
configMapKeyRef	Selects a key of a ConfigMap.	false	Section 2.3.55, "v1.ConfigMapKeySelector"	
secretKeyRef	Selects a key of a secret in the pod's namespace	false	Section 2.3.206, "v1.SecretKeySelector"	

3.3.49. v1.Event

Event is a report of an event somewhere in the cluster.

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#types-kinds	false	string	

Name	Description	Required	Schema	Default
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#resources	false	string	
metadata	Standard object's metadata. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#metadata	true	Section 2.3.158, "v1.ObjectMeta"	
involvedObject	The object that this event is about.	true	Section 2.3.159, "v1.ObjectReference"	
reason	This should be a short, machine understandable string that gives the reason for the transition into the object's current status.	false	string	
message	A human-readable description of the status of this operation.	false	string	

Name	Description	Required	Schema	Default
source	The component reporting this event. Should be a short machine understandable string.	false	Section 3.3.51, "v1.EventSource"	
firstTimestamp	The time at which the event was first recorded. (Time of server receipt is in TypeMeta.)	false	string	
lastTimestamp	The time at which the most recent occurrence of this event was recorded.	false	string	
count	The number of times this event has occurred.	false	integer (int32)	
type	Type of this event (Normal, Warning), new types could be added in the future	false	string	

3.3.50. v1.EventList

EventList is a list of events.

Name	Description	Required	Schema	Default
------	-------------	----------	--------	---------

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#types-kinds	false	string	
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#resources	false	string	
metadata	Standard list metadata. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#types-kinds	false	Section 2.3.9, "unversioned.ListMeta"	
items	List of events	true	Section 3.3.49, "v1.Event" array	

3.3.51. v1.EventSource

EventSource contains information for an event.

Name	Description	Required	Schema	Default
component	Component from which the event is generated.	false	string	
host	Host name on which the event is generated.	false	string	

3.3.52. v1.ExecAction

ExecAction describes a "run in container" action.

Name	Description	Required	Schema	Default
command	Command is the command line to execute inside the container, the working directory for the command is root ('/') in the container's filesystem. The command is simply exec'd, it is not run inside a shell, so traditional shell instructions (' ', etc) won't work. To use a shell, you need to explicitly call out to that shell. Exit status of 0 is treated as live/healthy and non-zero is unhealthy.	false	string array	

3.3.53. v1.FCVolumeSource

Represents a Fibre Channel volume. Fibre Channel volumes can only be mounted as read/write once. Fibre Channel volumes support ownership management and SELinux relabeling.

Name	Description	Required	Schema	Default
targetWWNs	Required: FC target world wide names (WWNs)	true	string array	
lun	Required: FC target lun number	true	integer (int32)	
fsType	Filesystem type to mount. Must be a filesystem type supported by the host operating system. Ex. "ext4", "xfs", "ntfs". Implicitly inferred to be "ext4" if unspecified.	false	string	
readOnly	Optional: Defaults to false (read/write). ReadOnly here will force the ReadOnly setting in VolumeMounts.	false	boolean	

3.3.54. v1.FSGroupStrategyOptions

FSGroupStrategyOptions is the strategy that will dictate what fs group is used by the SecurityContext.

Name	Description	Required	Schema	Default
type	Type is the strategy that will dictate what FSGroup is used in the SecurityContext.	false	string	
ranges	Ranges are the allowed ranges of fs groups. If you would like to force a single fs group then supply a single range with the same start and end.	false	Section 3.3.66, "v1.IDRange" array	

3.3.55. v1.FSType

3.3.56. v1.FinalizerName

3.3.57. v1.FlexVolumeSource

FlexVolume represents a generic volume resource that is provisioned/attached using a exec based plugin. This is an alpha feature and may change in future.

Name	Description	Required	Schema	Default
driver	Driver is the name of the driver to use for this volume.	true	string	
fsType	Filesystem type to mount. Must be a filesystem type supported by the host operating system. Ex. "ext4", "xfs", "ntfs". The default filesystem depends on FlexVolume script.	false	string	
secretRef	Optional: SecretRef is reference to the secret object containing sensitive information to pass to the plugin scripts. This may be empty if no secret object is specified. If the secret object contains more than one secret, all secrets are passed to the plugin scripts.	false	Section 2.3.138, "v1.LocalObjectReference"	
readOnly	Optional: Defaults to false (read/write). ReadOnly here will force the ReadOnly setting in VolumeMounts.	false	boolean	

Name	Description	Required	Schema	Default
options	Optional: Extra command options if any.	false	object	

3.3.58. v1.FlockerVolumeSource

Represents a Flocker volume mounted by the Flocker agent. Flocker volumes do not support ownership management or SELinux relabeling.

Name	Description	Required	Schema	Default
datasetName	Required: the volume name. This is going to be store on metadata → name on the payload for Flocker	true	string	

3.3.59. v1.GCEPersistentDiskVolumeSource

Represents a Persistent Disk resource in Google Compute Engine.

A GCE PD must exist before mounting to a container. The disk must also be in the same GCE project and zone as the kubelet. A GCE PD can only be mounted as read/write once or read-only many times. GCE PDs support ownership management and SELinux relabeling.

Name	Description	Required	Schema	Default
pdName	Unique name of the PD resource in GCE. Used to identify the disk in GCE. More info: http://releases.k8s.io/release-1.3/docs/user-guide/volumes.md#gcepersistentdisk	true	string	

Name	Description	Required	Schema	Default
fsType	<p>Filesystem type of the volume that you want to mount. Tip: Ensure that the filesystem type is supported by the host operating system. Examples: "ext4", "xfs", "ntfs". Implicitly inferred to be "ext4" if unspecified. More info: http://releases.k8s.io/release-1.3/docs/user-guide/volumes.md#gcepersistentdisk</p>	false	string	
partition	<p>The partition in the volume that you want to mount. If omitted, the default is to mount by volume name. Examples: For volume /dev/sda1, you specify the partition as "1". Similarly, the volume partition for /dev/sda is "0" (or you can leave the property empty). More info: http://releases.k8s.io/release-1.3/docs/user-guide/volumes.md#gcepersistentdisk</p>	false	integer (int32)	

Name	Description	Required	Schema	Default
readOnly	ReadOnly here will force the ReadOnly setting in VolumeMounts. Defaults to false. More info: http://releases.k8s.io/release-1.3/docs/user-guide/volumes.md#gcepersistentdisk	false	boolean	

3.3.60. v1.GitRepoVolumeSource

Represents a volume that is populated with the contents of a git repository. Git repo volumes do not support ownership management. Git repo volumes support SELinux relabeling.

Name	Description	Required	Schema	Default
repository	Repository URL	true	string	
revision	Commit hash for the specified revision.	false	string	
directory	Target directory name. Must not contain or start with '..'. If '.' is supplied, the volume directory will be the git repository. Otherwise, if specified, the volume will contain the git repository in the subdirectory with the given name.	false	string	

3.3.61. v1.GlusterfsVolumeSource

Represents a Glusterfs mount that lasts the lifetime of a pod. Glusterfs volumes do not support ownership management or SELinux relabeling.

Name	Description	Required	Schema	Default
endpoints	EndpointsName is the endpoint name that details Glusterfs topology. More info: http://releases.k8s.io/release-1.3/examples/glusterfs/README.md#create-a-pod	true	string	
path	Path is the Glusterfs volume path. More info: http://releases.k8s.io/release-1.3/examples/glusterfs/README.md#create-a-pod	true	string	
readOnly	ReadOnly here will force the Glusterfs volume to be mounted with read-only permissions. Defaults to false. More info: http://releases.k8s.io/release-1.3/examples/glusterfs/README.md#create-a-pod	false	boolean	

3.3.62. v1.HTTPGetAction

HTTPGetAction describes an action based on HTTP Get requests.

Name	Description	Required	Schema	Default
path	Path to access on the HTTP server.	false	string	

Name	Description	Required	Schema	Default
port	Name or number of the port to access on the container. Number must be in the range 1 to 65535. Name must be an IANA_SVC_NAME.	true	string	
host	Host name to connect to, defaults to the pod IP. You probably want to set "Host" in httpHeaders instead.	false	string	
scheme	Scheme to use for connecting to the host. Defaults to HTTP.	false	string	
httpHeaders	Custom headers to set in the request. HTTP allows repeated headers.	false	Section 2.3.104, "v1.HTTPHeader" array	

3.3.63. v1.HTTPHeader

HTTPHeader describes a custom header to be used in HTTP probes

Name	Description	Required	Schema	Default
name	The header field name	true	string	
value	The header field value	true	string	

3.3.64. v1.Handler

Handler defines a specific action that should be taken

Name	Description	Required	Schema	Default
exec	One and only one of the following should be specified. Exec specifies the action to take.	false	Section 2.3.88, "v1.ExecAction"	
httpGet	HTTPGet specifies the http request to perform.	false	Section 2.3.103, "v1.HTTPGetAction"	
tcpSocket	TCPsocket specifies an action involving a TCP port. TCP hooks not yet supported	false	Section 2.3.221, "v1.TCPsocketAction"	

3.3.65. v1.HostPathVolumeSource

Represents a host path mapped into a pod. Host path volumes do not support ownership management or SELinux relabeling.

Name	Description	Required	Schema	Default
path	Path of the directory on the host. More info: http://releases.k8s.io/release-1.3/docs/user-guide/volumes.md#hostpath	true	string	

3.3.66. v1.IDRange

IDRange provides a min/max of an allowed range of IDs.

Name	Description	Required	Schema	Default
min	Min is the start of the range, inclusive.	false	integer (int64)	
max	Max is the end of the range, inclusive.	false	integer (int64)	

3.3.67. v1.ISCSIVolumeSource

Represents an iSCSI disk. iSCSI volumes can only be mounted as read/write once. iSCSI volumes support ownership management and SELinux relabeling.

Name	Description	Required	Schema	Default
targetPortal	iSCSI target portal. The portal is either an IP or ip_addr:port if the port is other than default (typically TCP ports 860 and 3260).	true	string	
iqn	Target iSCSI Qualified Name.	true	string	
lun	iSCSI target lun number.	true	integer (int32)	
iscsiInterface	Optional: Defaults to 'default' (tcp). iSCSI interface name that uses an iSCSI transport.	false	string	
fsType	Filesystem type of the volume that you want to mount. Tip: Ensure that the filesystem type is supported by the host operating system. Examples: "ext4", "xfs", "ntfs". Implicitly inferred to be "ext4" if unspecified. More info: http://releases.k8s.io/release-1.3/docs/user-guide/volumes.md#iscsi	false	string	
readOnly	ReadOnly here will force the ReadOnly setting in VolumeMounts. Defaults to false.	false	boolean	

3.3.68. v1.KeyToPath

Maps a string key to a path within a volume.

Name	Description	Required	Schema	Default
key	The key to project.	true	string	
path	The relative path of the file to map the key to. May not be an absolute path. May not contain the path element '..'. May not start with the string '..'.	true	string	

3.3.69. v1.Lifecycle

Lifecycle describes actions that the management system should take in response to container lifecycle events. For the PostStart and PreStop lifecycle handlers, management of the container blocks until the action is complete, unless the container process fails, in which case the handler is aborted.

Name	Description	Required	Schema	Default
postStart	PostStart is called immediately after a container is created. If the handler fails, the container is terminated and restarted according to its restart policy. Other management of the container blocks until the hook completes. More info: http://releases.k8s.io/release-1.3/docs/user-guide/container-environment.md#hook-details	false	Section 2.3.105, "v1.Handler"	

Name	Description	Required	Schema	Default
preStop	<p>PreStop is called immediately before a container is terminated. The container is terminated after the handler completes. The reason for termination is passed to the handler. Regardless of the outcome of the handler, the container is eventually terminated. Other management of the container blocks until the hook completes. More info: http://releases.k8s.io/release-1.3/docs/user-guide/container-environment.md#hook-details</p>	false	Section 2.3.105, "v1.Handler"	

3.3.70. v1.LimitRange

LimitRange sets resource usage limits for each kind of resource in a Namespace.

Name	Description	Required	Schema	Default
------	-------------	----------	--------	---------

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#types-kinds	false	string	
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#resources	false	string	
metadata	Standard object's metadata. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#metadata	false	Section 2.3.158, "v1.ObjectMeta"	

Name	Description	Required	Schema	Default
spec	Spec defines the limits enforced. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#spec-and-status	false	Section 3.3.73, "v1.LimitRangeSpec"	

3.3.71. v1.LimitRangeItem

LimitRangeItem defines a min/max usage limit for any resource that matches on kind.

Name	Description	Required	Schema	Default
type	Type of resource that this limit applies to.	false	string	
max	Max usage constraints on this kind by resource name.	false	object	
min	Min usage constraints on this kind by resource name.	false	object	
default	Default resource requirement limit value by resource name if resource limit is omitted.	false	object	
defaultRequest	DefaultRequest is the default resource requirement request value by resource name if resource request is omitted.	false	object	

Name	Description	Required	Schema	Default
maxLimitRequestRatio	MaxLimitRequestRatio if specified, the named resource must have a request and limit that are both non-zero where limit divided by request is less than or equal to the enumerated value; this represents the max burst for the named resource.	false	object	

3.3.72. v1.LimitRangeList

LimitRangeList is a list of LimitRange items.

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#types-kinds	false	string	

Name	Description	Required	Schema	Default
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#resources	false	string	
metadata	Standard list metadata. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#types-kinds	false	Section 2.3.9 , “unversioned.ListMeta”	
items	Items is a list of LimitRange objects. More info: http://releases.k8s.io/release-1.3/docs/design/admission_control_limit_range.md	true	Section 3.3.70 , “v1.LimitRange” array	

3.3.73. v1.LimitRangeSpec

LimitRangeSpec defines a min/max usage limit for resources that match on kind.

Name	Description	Required	Schema	Default
limits	Limits is the list of LimitRangeItem objects that are enforced.	true	Section 3.3.71 , “v1.LimitRangeItem” array	

3.3.74. v1.LoadBalancerIngress

LoadBalancerIngress represents the status of a load-balancer ingress point: traffic intended for the service should be sent to an ingress point.

Name	Description	Required	Schema	Default
ip	IP is set for load-balancer ingress points that are IP based (typically GCE or OpenStack load-balancers)	false	string	
hostname	Hostname is set for load-balancer ingress points that are DNS based (typically AWS load-balancers)	false	string	

3.3.75. v1.LoadBalancerStatus

LoadBalancerStatus represents the status of a load-balancer.

Name	Description	Required	Schema	Default
ingress	Ingress is a list containing ingress points for the load-balancer. Traffic intended for the service should be sent to these ingress points.	false	Section 3.3.74, "v1.LoadBalancerIngress" array	

3.3.76. v1.LocalObjectReference

LocalObjectReference contains enough information to let you locate the referenced object inside the same namespace.

Name	Description	Required	Schema	Default
name	Name of the referent. More info: http://releases.k8s.io/release-1.3/docs/user-guide/identifiers.md#names	false	string	

3.3.77. v1.NFSVolumeSource

Represents an NFS mount that lasts the lifetime of a pod. NFS volumes do not support ownership management or SELinux relabeling.

Name	Description	Required	Schema	Default
server	Server is the hostname or IP address of the NFS server. More info: http://releases.k8s.io/release-1.3/docs/user-guide/volumes.md#nfs	true	string	
path	Path that is exported by the NFS server. More info: http://releases.k8s.io/release-1.3/docs/user-guide/volumes.md#nfs	true	string	
readOnly	ReadOnly here will force the NFS export to be mounted with read-only permissions. Defaults to false. More info: http://releases.k8s.io/release-1.3/docs/user-guide/volumes.md#nfs	false	boolean	

3.3.78. v1.Namespace

Namespace provides a scope for Names. Use of multiple namespaces is optional.

Name	Description	Required	Schema	Default
------	-------------	----------	--------	---------

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#types-kinds	false	string	
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#resources	false	string	
metadata	Standard object's metadata. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#metadata	false	Section 2.3.158, "v1.ObjectMeta"	

Name	Description	Required	Schema	Default
spec	Spec defines the behavior of the Namespace. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#spec-and-status	false	Section 3.3.80 , "v1.NamespaceSpec"	
status	Status describes the current status of a Namespace. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#spec-and-status	false	Section 3.3.81 , "v1.NamespaceStatus"	

3.3.79. v1.NamespaceList

NamespaceList is a list of Namespaces.

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#types-kinds	false	string	

Name	Description	Required	Schema	Default
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#resources	false	string	
metadata	Standard list metadata. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#types-kinds	false	Section 2.3.9, “unversioned.ListMeta”	
items	Items is the list of Namespace objects in the list. More info: http://releases.k8s.io/release-1.3/docs/user-guide/namespaces.md	true	Section 3.3.78, “v1.Namespace” array	

3.3.80. v1.NamespaceSpec

NamespaceSpec describes the attributes on a Namespace.

Name	Description	Required	Schema	Default
------	-------------	----------	--------	---------

Name	Description	Required	Schema	Default
finalizers	Finalizers is an opaque list of values that must be empty to permanently remove object from storage. More info: http://releases.k8s.io/release-1.3/docs/design/namespaces.md#finalizers	false	Section 2.3.91 , "v1.FinalizerName" array	

3.3.81. v1.NamespaceStatus

NamespaceStatus is information about the current status of a Namespace.

Name	Description	Required	Schema	Default
phase	Phase is the current lifecycle phase of the namespace. More info: http://releases.k8s.io/release-1.3/docs/design/namespaces.md#phases	false	string	

3.3.82. v1.Node

Nodes represent the machines that run the pods and containers in the cluster. A node resource is typically created and modified by the software running on the node - reporting information about capacity and the current health of the node. The labels of the node can be used by pods to specify a subset of the cluster to be scheduled on. The scheduler will only assign pods to nodes that have the **schedulable** condition set and also **ready**.

Name	Description	Required	Schema	Default
------	-------------	----------	--------	---------

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#types-kinds	false	string	
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#resources	false	string	
metadata	Standard object's metadata. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#metadata	false	Section 2.3.158, "v1.ObjectMeta"	

Name	Description	Required	Schema	Default
spec	Spec defines the behavior of a node. http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#spec-and-status	false	Section 3.3.87, "v1.NodeSpec"	
status	Most recently observed status of the node. Populated by the system. Read-only. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#spec-and-status	false	Section 3.3.88, "v1.NodeStatus"	

3.3.83. v1.NodeAddress

NodeAddress contains information for the node's address.

Name	Description	Required	Schema	Default
type	Node address type, one of Hostname, ExternalIP or InternalIP.	true	string	
address	The node address.	true	string	

3.3.84. v1.NodeCondition

NodeCondition contains condition information for a node.

Name	Description	Required	Schema	Default
type	Type of node condition.	true	string	

Name	Description	Required	Schema	Default
status	Status of the condition, one of True, False, Unknown.	true	string	
lastHeartbeatTime	Last time we got an update on a given condition.	false	string	
lastTransitionTime	Last time the condition transit from one status to another.	false	string	
reason	(brief) reason for the condition's last transition.	false	string	
message	Human readable message indicating details about last transition.	false	string	

3.3.85. v1.NodeDaemonEndpoints

NodeDaemonEndpoints lists ports opened by daemons running on the Node.

Name	Description	Required	Schema	Default
kubeletEndpoint	Endpoint on which Kubelet is listening.	false	Section 3.3.35, "v1.DaemonEndpoint"	

3.3.86. v1.NodeList

NodeList is the whole list of all Nodes which have been registered with master.

Name	Description	Required	Schema	Default
------	-------------	----------	--------	---------

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#types-kinds	false	string	
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#resources	false	string	
metadata	Standard list metadata. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#types-kinds	false	Section 2.3.9, "unversioned.ListMeta"	
items	List of nodes	true	Section 3.3.82, "v1.Node" array	

3.3.87. v1.NodeSpec

NodeSpec describes the attributes that a node is created with.

Name	Description	Required	Schema	Default
podCIDR	PodCIDR represents the pod IP range assigned to the node.	false	string	
externalID	External ID of the node assigned by some machine database (e.g. a cloud provider). Deprecated.	false	string	
providerID	ID of the node assigned by the cloud provider in the format: <ProviderName>://<ProviderSpecificNodeID>	false	string	
unschedulable	Unschedulable controls node schedulability of new pods. By default, node is schedulable. More info: http://releases.k8s.io/release-1.3/docs/admin/node.md#manual-node-administration	false	boolean	

3.3.88. v1.NodeStatus

NodeStatus is information about the current status of a node.

Name	Description	Required	Schema	Default
------	-------------	----------	--------	---------

Name	Description	Required	Schema	Default
capacity	Capacity represents the total resources of a node. More info: http://releases.k8s.io/release-1.3/docs/user-guide/persistent-volumes.md#capacity for more details.	false	object	
allocatable	Allocatable represents the resources of a node that are available for scheduling. Defaults to Capacity.	false	object	
phase	NodePhase is the recently observed lifecycle phase of the node. More info: http://releases.k8s.io/release-1.3/docs/admin/node.md#node-phase	false	string	
conditions	Conditions is an array of current observed node conditions. More info: http://releases.k8s.io/release-1.3/docs/admin/node.md#node-condition	false	Section 3.3.84, "v1.NodeCondition" array	

Name	Description	Required	Schema	Default
addresses	List of addresses reachable to the node. Queried from cloud provider, if available. More info: http://releases.k8s.io/release-1.3/docs/admin/node.md#node-addresses	false	Section 3.3.83 , “v1.NodeAddress” array	
daemonEndpoints	Endpoints of daemons running on the Node.	false	Section 3.3.85 , “v1.NodeDaemonEndpoints”	
nodeInfo	Set of ids/uuids to uniquely identify the node. More info: http://releases.k8s.io/release-1.3/docs/admin/node.md#node-info	false	Section 3.3.89 , “v1.NodeSystemInfo”	
images	List of container images on this node	false	Section 3.3.28 , “v1.ContainerImage” array	
volumesInUse	List of attachable volumes in use (mounted) by the node.	false	Section 3.3.149 , “v1.UniqueVolumeName” array	
volumesAttached	List of volumes that are attached to the node.	false	Section 3.3.13 , “v1.AttachedVolume” array	

3.3.89. v1.NodeSystemInfo

NodeSystemInfo is a set of ids/uuids to uniquely identify the node.

Name	Description	Required	Schema	Default
------	-------------	----------	--------	---------

Name	Description	Required	Schema	Default
machineID	Machine ID reported by the node.	true	string	
systemUUID	System UUID reported by the node.	true	string	
bootID	Boot ID reported by the node.	true	string	
kernelVersion	Kernel Version reported by the node from 'uname -r' (e.g. 3.16.0-0.bpo.4-amd64).	true	string	
osImage	OS Image reported by the node from /etc/os-release (e.g. Debian GNU/Linux 7 (wheezy)).	true	string	
containerRuntimeVersion	ContainerRuntime Version reported by the node through runtime remote API (e.g. docker://1.5.0).	true	string	
kubeletVersion	Kubelet Version reported by the node.	true	string	
kubeProxyVersion	KubeProxy Version reported by the node.	true	string	
operatingSystem	The Operating System reported by the node	true	string	
architecture	The Architecture reported by the node	true	string	

3.3.90. v1.ObjectFieldSelector

ObjectFieldSelector selects an APIVersioned field of an object.

Name	Description	Required	Schema	Default
apiVersion	Version of the schema the FieldPath is written in terms of, defaults to "v1".	false	string	
fieldPath	Path of the field to select in the specified API version.	true	string	

3.3.91. v1.ObjectMeta

ObjectMeta is metadata that all persisted resources must have, which includes all objects users must create.

Name	Description	Required	Schema	Default
name	Name must be unique within a namespace. Is required when creating resources, although some resources may allow a client to request the generation of an appropriate name automatically. Name is primarily intended for creation idempotence and configuration definition. Cannot be updated. More info: http://releases.k8s.io/release-1.3/docs/user-guide/identifiers.md#names	false	string	
generateName	GenerateName is an optional prefix, used by the server, to generate a unique name	false	string	

Name	Description	Required	Schema	Default
	<p>ONLY IF the Name field has not been provided. If this field is used, the name returned to the client will be different than the name passed. This value will also be combined with a unique suffix. The provided value has the same validation rules as the Name field, and may be truncated by the length of the suffix required to make the value unique on the server.</p> <p>If this field is specified and the generated name exists, the server will NOT return a 409 - instead, it will either return 201 Created or 500 with Reason ServerTimeout indicating a unique name could not be found in the time allotted, and the client should retry (optionally after the time indicated in the Retry-After header).</p> <p>Applied only if Name is not specified. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#idempotency</p>			

Name	Description	Required	Schema	Default
namespace	<p>Namespace defines the space within each name must be unique. An empty namespace is equivalent to the "default" namespace, but "default" is the canonical representation. Not all objects are required to be scoped to a namespace - the value of this field for those objects will be empty.</p> <p>Must be a DNS_LABEL. Cannot be updated. More info: http://releases.k8s.io/release-1.3/docs/user-guide/namespaces.md</p>	false	string	
selfLink	<p>SelfLink is a URL representing this object. Populated by the system. Read-only.</p>	false	string	

Name	Description	Required	Schema	Default
uid	<p>UID is the unique in time and space value for this object. It is typically generated by the server on successful creation of a resource and is not allowed to change on PUT operations.</p> <p>Populated by the system. Read-only. More info: http://releases.k8s.io/release-1.3/docs/user-guide/identifiers.md#uids</p>	false	string	

Name	Description	Required	Schema	Default
resourceVersion	<p>An opaque value that represents the internal version of this object that can be used by clients to determine when objects have changed. May be used for optimistic concurrency, change detection, and the watch operation on a resource or set of resources. Clients must treat these values as opaque and passed unmodified back to the server. They may only be valid for a particular resource or set of resources.</p> <p>Populated by the system. Read-only. Value must be treated as opaque by clients and . More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#concurrency-control-and-consistency</p>	false	string	
generation	<p>A sequence number representing a specific generation of the desired state. Populated by the system. Read-only.</p>	false	integer (int64)	

Name	Description	Required	Schema	Default
creationTimestamp	<p>CreationTimestamp is a timestamp representing the server time when this object was created. It is not guaranteed to be set in happens-before order across separate operations. Clients may not set this value. It is represented in RFC3339 form and is in UTC.</p> <p>Populated by the system. Read-only. Null for lists. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#metadata</p>	false	string	
deletionTimestamp	<p>DeletionTimestamp is RFC 3339 date and time at which this resource will be deleted. This field is set by the server when a graceful deletion is requested by the user, and is not directly settable by a client. The resource will be deleted (no longer visible from resource lists, and not reachable by name) after the time in this field. Once set, this value may not be unset or be set further into the future, although it may be shortened</p>	false	string	

Name	Description	Required	Schema	Default
	<p>or the resource may be deleted prior to this time. For example, a user may request that a pod is deleted in 30 seconds. The Kubelet will react by sending a graceful termination signal to the containers in the pod. Once the resource is deleted in the API, the Kubelet will send a hard termination signal to the container. If not set, graceful deletion of the object has not been requested.</p> <p>Populated by the system when a graceful deletion is requested. Read-only. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#metadata</p>			
deletionGracePeriodSeconds	<p>Number of seconds allowed for this object to gracefully terminate before it will be removed from the system. Only set when deletionTimestamp is also set. May only be shortened. Read-only.</p>	false	integer (int64)	

Name	Description	Required	Schema	Default
labels	Map of string keys and values that can be used to organize and categorize (scope and select) objects. May match selectors of replication controllers and services. More info: http://releases.k8s.io/release-1.3/docs/user-guide/labels.md	false	object	
annotations	Annotations is an unstructured key value map stored with a resource that may be set by external tools to store and retrieve arbitrary metadata. They are not queryable and should be preserved when modifying objects. More info: http://releases.k8s.io/release-1.3/docs/user-guide/annotations.md	false	object	

Name	Description	Required	Schema	Default
ownerReferences	List of objects depended by this object. If ALL objects in the list have been deleted, this object will be garbage collected. If this object is managed by a controller, then an entry in this list will point to this controller, with the controller field set to true. There cannot be more than one managing controller.	false	Section 2.3.160 , “v1.OwnerReference” array	
finalizers	Must be empty before the object is deleted from the registry. Each entry is an identifier for the responsible component that will remove the entry from the list. If the deletionTimestamp of the object is non-nil, entries in this list can only be removed.	false	string array	

3.3.92. v1.ObjectReference

ObjectReference contains enough information to let you inspect or modify the referred object.

Name	Description	Required	Schema	Default
kind	Kind of the referent. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#types-kinds	false	string	

Name	Description	Required	Schema	Default
namespace	Namespace of the referent. More info: http://releases.k8s.io/release-1.3/docs/user-guide/namespaces.md	false	string	
name	Name of the referent. More info: http://releases.k8s.io/release-1.3/docs/user-guide/identifiers.md#names	false	string	
uid	UID of the referent. More info: http://releases.k8s.io/release-1.3/docs/user-guide/identifiers.md#uids	false	string	
apiVersion	API version of the referent.	false	string	
resourceVersion	Specific resourceVersion to which this reference is made, if any. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#concurrency-control-and-consistency	false	string	

Name	Description	Required	Schema	Default
fieldPath	If referring to a piece of an object instead of an entire object, this string should contain a valid JSON/Go field access statement, such as <code>desiredState.manifest.containers[2]</code> . For example, if the object reference is to a container within a pod, this would take on a value like: <code>"spec.containers{name}"</code> (where "name" refers to the name of the container that triggered the event) or if no container name is specified <code>"spec.containers[2]"</code> (container with index 2 in this pod). This syntax is chosen only to have some well-defined way of referencing a part of an object.	false	string	

3.3.93. v1.OwnerReference

OwnerReference contains enough information to let you identify an owning object. Currently, an owning object must be in the same namespace, so there is no namespace field.

Name	Description	Required	Schema	Default
apiVersion	API version of the referent.	true	string	

Name	Description	Required	Schema	Default
kind	Kind of the referent. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#types-kinds	true	string	
name	Name of the referent. More info: http://releases.k8s.io/release-1.3/docs/user-guide/identifiers.md#names	true	string	
uid	UID of the referent. More info: http://releases.k8s.io/release-1.3/docs/user-guide/identifiers.md#uids	true	string	
controller	If true, this reference points to the managing controller.	false	boolean	

3.3.94. v1.PersistentVolume

A Persistent Volume (PV) is a storage device that is made available for use by applications by an administrator. When a user requests persistent storage be allocated for a pod, they create a persistent volume claim with the size and type of storage they need. The system will look for persistent volumes that match that claim and, if one is available, it will assign that persistent volume to the claim. Information about the volume (type, location, secrets necessary to use it) will be available to the claim and the claim may then be used from a pod as a volume source.

Deleting a persistent volume removes the cluster's record of the volume, and may result in automated processes destroying the underlying network store.

Name	Description	Required	Schema	Default
------	-------------	----------	--------	---------

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#types-kinds	false	string	
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#resources	false	string	
metadata	Standard object's metadata. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#metadata	false	Section 2.3.158, "v1.ObjectMeta"	

Name	Description	Required	Schema	Default
spec	Spec defines a specification of a persistent volume owned by the cluster. Provisioned by an administrator. More info: http://releases.k8s.io/release-1.3/docs/user-guide/persistent-volumes.md#persistent-volumes	false	Section 3.3.102, "v1.PersistentVolumeSpec"	
status	Status represents the current information/status for the persistent volume. Populated by the system. Read-only. More info: http://releases.k8s.io/release-1.3/docs/user-guide/persistent-volumes.md#persistent-volumes	false	Section 3.3.103, "v1.PersistentVolumeStatus"	

3.3.95. v1.PersistentVolumeAccessMode

3.3.96. v1.PersistentVolumeClaim

Persistent Volume Claims (PVC) represent a request to use a persistent volume (PV) with a pod. When creating a pod definition (or replication controller or deployment config) a developer may specify the amount of storage they need via a persistent volume reference. If an administrator has enabled and configured persistent volumes for use, they will be allocated on demand to pods that have similar requirements. Since volumes are created lazily, some pods may be scheduled to a node before their volume is assigned. The node will detect this situation and wait to start the pod until the volume is bound. Events will be generated (visible by using the **describe** command on the pod) that indicate the pod is waiting for volumes.

Name	Description	Required	Schema	Default
------	-------------	----------	--------	---------

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#types-kinds	false	string	
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#resources	false	string	
metadata	Standard object's metadata. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#metadata	false	Section 2.3.158, "v1.ObjectMeta"	

Name	Description	Required	Schema	Default
spec	Spec defines the desired characteristics of a volume requested by a pod author. More info: http://releases.k8s.io/release-1.3/docs/user-guide/persistent-volumes.md#persistentvolumeclaims	false	Section 3.3.98, "v1.PersistentVolumeClaimSpec"	
status	Status represents the current information/status of a persistent volume claim. Read-only. More info: http://releases.k8s.io/release-1.3/docs/user-guide/persistent-volumes.md#persistentvolumeclaims	false	Section 3.3.99, "v1.PersistentVolumeClaimStatus"	

3.3.97. v1.PersistentVolumeClaimList

PersistentVolumeClaimList is a list of PersistentVolumeClaim items.

Name	Description	Required	Schema	Default
------	-------------	----------	--------	---------

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#types-kinds	false	string	
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#resources	false	string	
metadata	Standard list metadata. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#types-kinds	false	Section 2.3.9, "unversioned.ListMeta"	

Name	Description	Required	Schema	Default
items	A list of persistent volume claims. More info: http://releases.k8s.io/release-1.3/docs/user-guide/persistent-volumes.md#persistentvolumeclaims	true	Section 3.3.96 , “v1.PersistentVolumeClaim” array	

3.3.98. v1.PersistentVolumeClaimSpec

PersistentVolumeClaimSpec describes the common attributes of storage devices and allows a Source for provider-specific attributes

Name	Description	Required	Schema	Default
accessModes	AccessModes contains the desired access modes the volume should have. More info: http://releases.k8s.io/release-1.3/docs/user-guide/persistent-volumes.md#access-modes-1	false	Section 3.3.95 , “v1.PersistentVolumeAccessMode” array	
selector	A label query over volumes to consider for binding.	false	Section 2.3.7 , “unversioned.LabelSelector”	
resources	Resources represents the minimum resources the volume should have. More info: http://releases.k8s.io/release-1.3/docs/user-guide/persistent-volumes.md#resources	false	Section 2.3.188 , “v1.ResourceRequirements”	

Name	Description	Required	Schema	Default
volumeName	VolumeName is the binding reference to the PersistentVolume backing this claim.	false	string	

3.3.99. v1.PersistentVolumeClaimStatus

PersistentVolumeClaimStatus is the current status of a persistent volume claim.

Name	Description	Required	Schema	Default
phase	Phase represents the current phase of PersistentVolumeClaim.	false	string	
accessModes	AccessModes contains the actual access modes the volume backing the PVC has. More info: http://releases.k8s.io/release-1.3/docs/user-guide/persistent-volumes.md#access-modes-1	false	Section 3.3.95, "v1.PersistentVolumeAccessMode" array	
capacity	Represents the actual resources of the underlying volume.	false	object	

3.3.100. v1.PersistentVolumeClaimVolumeSource

PersistentVolumeClaimVolumeSource references the user's PVC in the same namespace. This volume finds the bound PV and mounts that volume for the pod. A PersistentVolumeClaimVolumeSource is, essentially, a wrapper around another type of volume that is owned by someone else (the system).

Name	Description	Required	Schema	Default
------	-------------	----------	--------	---------

Name	Description	Required	Schema	Default
claimName	ClaimName is the name of a PersistentVolumeClaim in the same namespace as the pod using this volume. More info: http://releases.k8s.io/release-1.3/docs/user-guide/persistent-volumes.md#persistentvolumeclaims	true	string	
readOnly	Will force the ReadOnly setting in VolumeMounts. Default false.	false	boolean	

3.3.101. v1.PersistentVolumeList

PersistentVolumeList is a list of PersistentVolume items.

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#types-kinds	false	string	

Name	Description	Required	Schema	Default
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#resources	false	string	
metadata	Standard list metadata. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#types-kinds	false	Section 2.3.9, “unversioned.ListMeta”	
items	List of persistent volumes. More info: http://releases.k8s.io/release-1.3/docs/user-guide/persistent-volumes.md	true	Section 3.3.94, “v1.PersistentVolume” array	

3.3.102. v1.PersistentVolumeSpec

PersistentVolumeSpec is the specification of a persistent volume.

Name	Description	Required	Schema	Default
------	-------------	----------	--------	---------

Name	Description	Required	Schema	Default
capacity	A description of the persistent volume's resources and capacity. More info: http://releases.k8s.io/release-1.4/docs/user-guide/persistent-volumes.md#capacity	false	object	
gcePersistentDisk	GCEPersistentDisk represents a GCE Disk resource that is attached to a kubelet's host machine and then exposed to the pod. Provisioned by an admin. More info: http://releases.k8s.io/release-1.4/docs/user-guide/volumes.md#gcepersistentdisk	false	Section 2.3.94, "v1.GCEPersistentDiskVolumeSource"	
awsElasticBlockStore	AWSElasticBlockStore represents an AWS Disk resource that is attached to a kubelet's host machine and then exposed to the pod. More info: http://releases.k8s.io/release-1.4/docs/user-guide/volumes.md#awselasticblockstore	false	Section 2.3.14, "v1.AWSElasticBlockStoreVolumeSource"	

Name	Description	Required	Schema	Default
hostPath	HostPath represents a directory on the host. Provisioned by a developer or tester. This is useful for single-node development and testing only! On-host storage is not supported in any way and WILL NOT WORK in a multi-node cluster. More info: http://releases.k8s.io/release-1.4/docs/user-guide/volumes.md#hostpath	false	Section 2.3.106, "v1.HostPathVolumeSource"	
glusterfs	Glusterfs represents a Glusterfs volume that is attached to a host and exposed to the pod. Provisioned by an admin. More info: http://releases.k8s.io/release-1.4/examples/volumes/glusterfs/README.md	false	Section 2.3.100, "v1.GlusterfsVolumeSource"	
nfs	NFS represents an NFS mount on the host. Provisioned by an admin. More info: http://releases.k8s.io/release-1.4/docs/user-guide/volumes.md#nfs	false	Section 2.3.141, "v1.NFSVolumeSource"	

Name	Description	Required	Schema	Default
rbd	A Ceph Rados Block Device mount on the host that shares a pod's lifetime. More info: http://releases.k8s.io/release-1.4/examples/volumes/rbd/README.md	false	Section 2.3.178, "v1.RBDVolumeSource"	
iscsi	ISCSI represents an ISCSI Disk resource that is attached to a kubelet's host machine and then exposed to the pod. Provisioned by an admin.	false	Section 2.3.109, "v1.ISCSIVolumeSource"	
cinder	Cinder represents a cinder volume attached and mounted on kubelets host machine More info: http://releases.k8s.io/release-1.3/examples/mysql-cinder-pd/README.md	false	Section 2.3.38, "v1.CinderVolumeSource"	
cephfs	CephFS represents a Ceph FS mount on the host that shares a pod's lifetime	false	Section 2.3.37, "v1.CephFSVolumeSource"	
fc	FC represents a Fibre Channel resource that is attached to a kubelet's host machine and then exposed to the pod.	false	Section 2.3.90, "v1.FCVolumeSource"	

Name	Description	Required	Schema	Default
flocker	Flocker represents a Flocker volume attached to a kubelet's host machine and exposed to the pod for its usage. This depends on the Flocker control service being running	false	Section 2.3.93, "v1.FlockerVolume Source"	
flexVolume	FlexVolume represents a generic volume resource that is provisioned/attached using a exec based plugin. This is an alpha feature and may change in future.	false	Section 2.3.92, "v1.FlexVolumeSource"	
azureFile	AzureFile represents an Azure File Service mount on the host and bind mount to the pod.	false	Section 2.3.17, "v1.AzureFileVolumeSource"	
vsphereVolume	VsphereVolume represents a vSphere volume attached and mounted on kubelets host machine	false	Section 2.3.235, "v1.VsphereVirtualDiskVolumeSource"	
accessModes	AccessModes contains all ways the volume can be mounted. More info: http://releases.k8s.io/release-1.3/docs/user-guide/persistent-volumes.md#access-modes	false	Section 3.3.95, "v1.PersistentVolumeAccessMode" array	

Name	Description	Required	Schema	Default
claimRef	ClaimRef is part of a bi-directional binding between PersistentVolume and PersistentVolumeClaim. Expected to be non-nil when bound. claim.VolumeName is the authoritative bind between PV and PVC. More info: http://releases.k8s.io/release-1.3/docs/user-guide/persistent-volumes.md#binding	false	Section 2.3.159, "v1.ObjectReference"	
persistentVolumeReclaimPolicy	What happens to a persistent volume when released from its claim. Valid options are Retain (default) and Recycle. Recycling must be supported by the volume plugin underlying this persistent volume. More info: http://releases.k8s.io/release-1.3/docs/user-guide/persistent-volumes.md#recycling-policy	false	string	

3.3.103. v1.PersistentVolumeStatus

PersistentVolumeStatus is the current status of a persistent volume.

Name	Description	Required	Schema	Default
------	-------------	----------	--------	---------

Name	Description	Required	Schema	Default
phase	Phase indicates if a volume is available, bound to a claim, or released by a claim. More info: http://releases.k8s.io/release-1.3/docs/user-guide/persistent-volumes.md#phase	false	string	
message	A human-readable message indicating details about why the volume is in this state.	false	string	
reason	Reason is a brief CamelCase string that describes any failure and is meant for machine parsing and tidy display in the CLI.	false	string	

3.3.104. v1.Pod

A pod corresponds to a group of containers running together on the same machine. All containers in a pod share an IP address, and may have access to shared volumes and local filesystem. Like individual application containers, pods are considered to be relatively ephemeral rather than durable entities. Pods are scheduled to nodes and remain there until termination (according to restart policy) or deletion. When a node dies, the pods scheduled to that node are deleted. Specific pods are never rescheduled to new nodes; instead, they must be replaced by a component like the replication controller.

See [the Kubernetes pod documentation](#) for more information.

Name	Description	Required	Schema	Default
------	-------------	----------	--------	---------

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#types-kinds	false	string	
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#resources	false	string	
metadata	Standard object's metadata. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#metadata	false	Section 2.3.158, "v1.ObjectMeta"	

Name	Description	Required	Schema	Default
spec	Specification of the desired behavior of the pod. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#spec-and-status	false	Section 2.3.164, "v1.PodSpec"	
status	Most recently observed status of the pod. This data may not be up to date. Populated by the system. Read-only. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#spec-and-status	false	Section 3.3.109, "v1.PodStatus"	

3.3.105. v1.PodCondition

PodCondition contains details for the current condition of this pod.

Name	Description	Required	Schema	Default
type	Type is the type of the condition. Currently only Ready. More info: http://releases.k8s.io/release-1.3/docs/user-guide/pod-states.md#pod-conditions	true	string	
status	Status is the status of the condition. Can be True, False, Unknown. More info: http://releases.k8s.io/release-1.3/docs/user-guide/pod-states.md#pod-conditions	true	string	

Name	Description	Required	Schema	Default
lastProbeTime	Last time we probed the condition.	false	string	
lastTransitionTime	Last time the condition transitioned from one status to another.	false	string	
reason	Unique, one-word, CamelCase reason for the condition's last transition.	false	string	
message	Human-readable message indicating details about last transition.	false	string	

3.3.106. v1.PodList

PodList is a list of Pods.

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#types-kinds	false	string	

Name	Description	Required	Schema	Default
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#resources	false	string	
metadata	Standard list metadata. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#types-kinds	false	Section 2.3.9 , “unversioned.ListMeta”	
items	List of pods. More info: http://releases.k8s.io/release-1.3/docs/user-guide/pods.md	true	Section 3.3.104 , “v1.Pod” array	

3.3.107. v1.PodSecurityContext

PodSecurityContext holds pod-level security attributes and common container settings. Some fields are also present in container.securityContext. Field values of container.securityContext take precedence over field values of PodSecurityContext.

Name	Description	Required	Schema	Default
------	-------------	----------	--------	---------

Name	Description	Required	Schema	Default
seLinuxOptions	The SELinux context to be applied to all containers. If unspecified, the container runtime will allocate a random SELinux context for each container. May also be set in SecurityContext. If set in both SecurityContext and PodSecurityContext, the value specified in SecurityContext takes precedence for that container.	false	Section 2.3.202, "v1.SELinuxOptions"	
runAsUser	The UID to run the entrypoint of the container process. Defaults to user specified in image metadata if unspecified. May also be set in SecurityContext. If set in both SecurityContext and PodSecurityContext, the value specified in SecurityContext takes precedence for that container.	false	integer (int64)	

Name	Description	Required	Schema	Default
runAsNonRoot	Indicates that the container must run as a non-root user. If true, the Kubelet will validate the image at runtime to ensure that it does not run as UID 0 (root) and fail to start the container if it does. If unset or false, no such validation will be performed. May also be set in SecurityContext. If set in both SecurityContext and PodSecurityContext, the value specified in SecurityContext takes precedence.	false	boolean	
supplementalGroups	A list of groups applied to the first process run in each container, in addition to the container's primary GID. If unspecified, no groups will be added to any container.	false	integer array	

Name	Description	Required	Schema	Default
fsGroup	<p>A special supplemental group that applies to all containers in a pod. Some volume types allow the Kubelet to change the ownership of that volume to be owned by the pod:</p> <ol style="list-style-type: none"> 1. The owning GID will be the FSGroup 2. The setgid bit is set (new files created in the volume will be owned by FSGroup) 3. The permission bits are OR'd with rw-rw 	false	integer (int64)	

3.3.108. v1.PodSpec

PodSpec is a description of a pod.

Name	Description	Required	Schema	Default
volumes	<p>List of volumes that can be mounted by containers belonging to the pod. More info: http://releases.k8s.io/release-1.3/docs/user-guide/volumes.md</p>	false	Section 2.3.233, "v1.Volume" array	

Name	Description	Required	Schema	Default
containers	List of containers belonging to the pod. Containers cannot currently be added or removed. There must be at least one container in a Pod. Cannot be updated. More info: http://releases.k8s.io/release-1.3/docs/user-guide/containers.md	true	Section 2.3.57 , "v1.Container" array	
restartPolicy	Restart policy for all containers within the pod. One of Always, OnFailure, Never. Default to Always. More info: http://releases.k8s.io/release-1.3/docs/user-guide/pod-states.md#restartpolicy	false	string	

Name	Description	Required	Schema	Default
terminationGracePeriodSeconds	Optional duration in seconds the pod needs to terminate gracefully. May be decreased in delete request. Value must be non-negative integer. The value zero indicates delete immediately. If this value is nil, the default grace period will be used instead. The grace period is the duration in seconds after the processes running in the pod are sent a termination signal and the time when the processes are forcibly halted with a kill signal. Set this value longer than the expected cleanup time for your process. Defaults to 30 seconds.	false	integer (int64)	
activeDeadlineSeconds	Optional duration in seconds the pod may be active on the node relative to StartTime before the system will actively try to mark it failed and kill associated containers. Value must be a positive integer.	false	integer (int64)	

Name	Description	Required	Schema	Default
dnsPolicy	Set DNS policy for containers within the pod. One of 'ClusterFirst' or 'Default'. Defaults to "ClusterFirst".	false	string	
nodeSelector	NodeSelector is a selector which must be true for the pod to fit on a node. Selector which must match a node's labels for the pod to be scheduled on that node. More info: http://releases.k8s.io/release-1.3/docs/user-guide/node-selection/README.md	false	object	
host	A request to schedule this pod onto a specific node. Deprecated: Use nodeName instead.	false	string	
serviceAccountName	ServiceAccountName is the name of the ServiceAccount to use to run this pod. More info: http://releases.k8s.io/release-1.3/docs/design/service_accounts.md	false	string	
serviceAccount	DeprecatedServiceAccount is a deprecated alias for ServiceAccountName. Deprecated: Use serviceAccountName instead.	false	string	

Name	Description	Required	Schema	Default
nodeName	nodeName is a request to schedule this pod onto a specific node. If it is non-empty, the scheduler simply schedules this pod onto that node, assuming that it fits resource requirements.	false	string	
hostNetwork	Host networking requested for this pod. Use the host's network namespace. If this option is set, the ports that will be used must be specified. Default to false.	false	boolean	
hostPID	Use the host's pid namespace. Optional: Default to false.	false	boolean	
hostIPC	Use the host's ipc namespace. Optional: Default to false.	false	boolean	
securityContext	SecurityContext holds pod-level security attributes and common container settings. Optional: Defaults to empty. See type description for default values of each field.	false	Section 2.3.163, "v1.PodSecurityContext"	

Name	Description	Required	Schema	Default
imagePullSecrets	ImagePullSecrets is an optional list of references to secrets in the same namespace to use for pulling any of the images used by this PodSpec. If specified, these secrets will be passed to individual puller implementations for them to use. For example, in the case of docker, only DockerConfig type secrets are honored. More info: http://releases.k8s.io/release-1.3/docs/user-guide/images.md#specifying-imagepullsecrets-on-a-pod	false	Section 2.3.138, "v1.LocalObjectReference" array	
hostname	Specifies the hostname of the Pod. If not specified, the pod's hostname will be set to a system-defined value.	false	string	
subdomain	If specified, the fully qualified Pod hostname will be " <code><hostname>.<subdomain>.<pod namespace>.svc.<cluster domain></code> ". If not specified, the pod will not have a domainname at all.	false	string	

3.3.109. v1.PodStatus

PodStatus represents information about the status of a pod. Status may trail the actual state of a system.

Name	Description	Required	Schema	Default
phase	Current condition of the pod. More info: http://releases.k8s.io/release-1.3/docs/user-guide/pod-states.md#pod-phase	false	string	
conditions	Current service state of pod. More info: http://releases.k8s.io/release-1.3/docs/user-guide/pod-states.md#pod-conditions	false	Section 3.3.105, "v1.PodCondition" array	
message	A human readable message indicating details about why the pod is in this condition.	false	string	
reason	A brief CamelCase message indicating details about why the pod is in this state. e.g. 'OutOfDisk'	false	string	
hostIP	IP address of the host to which the pod is assigned. Empty if not yet scheduled.	false	string	
podIP	IP address allocated to the pod. Routable at least within the cluster. Empty if not yet allocated.	false	string	

Name	Description	Required	Schema	Default
startTime	RFC 3339 date and time at which the object was acknowledged by the Kubelet. This is before the Kubelet pulled the container image(s) for the pod.	false	string	
containerStatuses	The list has one entry per container in the manifest. Each entry is currently the output of docker inspect . More info: http://releases.k8s.io/release-1.3/docs/user-guide/pod-states.md#container-statuses	false	Section 3.3.34 , “v1.ContainerStatus” array	

3.3.110. v1.PodTemplate

PodTemplate describes a template for creating copies of a predefined pod.

Name	Description	Required	Schema	Default
------	-------------	----------	--------	---------

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#types-kinds	false	string	
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#resources	false	string	
metadata	Standard object's metadata. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#metadata	false	Section 2.3.158, "v1.ObjectMeta"	

Name	Description	Required	Schema	Default
template	Template defines the pods that will be created from this pod template. http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#spec-and-status	false	Section 2.3.165, "v1.PodTemplateSpec"	

3.3.111. v1.PodTemplateList

PodTemplateList is a list of PodTemplates.

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#types-kinds	false	string	

Name	Description	Required	Schema	Default
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#resources	false	string	
metadata	Standard list metadata. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#types-kinds	false	Section 2.3.9 , “unversioned.ListMeta”	
items	List of pod templates	true	Section 3.3.110 , “v1.PodTemplate” array	

3.3.112. v1.PodTemplateSpec

PodTemplateSpec describes the data a pod should have when created from a template

Name	Description	Required	Schema	Default
metadata	Standard object’s metadata. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#metadata	false	Section 2.3.158 , “v1.ObjectMeta”	

Name	Description	Required	Schema	Default
spec	Specification of the desired behavior of the pod. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#spec-and-status	false	Section 2.3.164, "v1.PodSpec"	

3.3.113. v1.Preconditions

Preconditions must be fulfilled before an operation (update, delete, etc.) is carried out.

Name	Description	Required	Schema	Default
uid	Specifies the target UID.	false	Section 2.3.4, "types.UID"	

3.3.114. v1.Probe

Probe describes a health check to be performed against a container to determine whether it is alive or ready to receive traffic.

Name	Description	Required	Schema	Default
exec	One and only one of the following should be specified. Exec specifies the action to take.	false	Section 2.3.88, "v1.ExecAction"	
httpGet	HTTPGet specifies the http request to perform.	false	Section 2.3.103, "v1.HTTPGetAction"	
tcpSocket	TCP socket specifies an action involving a TCP port. TCP hooks not yet supported	false	Section 2.3.221, "v1.TCPsocketAction"	

Name	Description	Required	Schema	Default
initialDelaySeconds	Number of seconds after the container has started before liveness probes are initiated. More info: http://releases.k8s.io/release-1.3/docs/user-guide/pod-states.md#container-probes	false	integer (int32)	
timeoutSeconds	Number of seconds after which the probe times out. Defaults to 1 second. Minimum value is 1. More info: http://releases.k8s.io/release-1.3/docs/user-guide/pod-states.md#container-probes	false	integer (int32)	
periodSeconds	How often (in seconds) to perform the probe. Default to 10 seconds. Minimum value is 1.	false	integer (int32)	
successThreshold	Minimum consecutive successes for the probe to be considered successful after having failed. Defaults to 1. Must be 1 for liveness. Minimum value is 1.	false	integer (int32)	

Name	Description	Required	Schema	Default
failureThreshold	Minimum consecutive failures for the probe to be considered failed after having succeeded. Defaults to 3. Minimum value is 1.	false	integer (int32)	

3.3.115. v1.RBDVolumeSource

Represents a Ceph Rados Block Device mount that lasts the lifetime of a pod. Ceph RBD volumes support ownership management and SELinux relabeling.

Name	Description	Required	Schema	Default
monitors	A collection of Ceph monitors. More info: http://releases.k8s.io/release-1.3/examples/rbd/README.md#how-to-use-it	true	string array	
image	The rados image name. More info: http://releases.k8s.io/release-1.3/examples/rbd/README.md#how-to-use-it	true	string	

Name	Description	Required	Schema	Default
fsType	Filesystem type of the volume that you want to mount. Tip: Ensure that the filesystem type is supported by the host operating system. Examples: "ext4", "xfs", "ntfs". Implicitly inferred to be "ext4" if unspecified. More info: http://releases.k8s.io/release-1.3/docs/user-guide/volumes.md#rbd	false	string	
pool	The rados pool name. Default is rbd. More info: http://releases.k8s.io/release-1.3/examples/rbd/README.md#how-to-use-it .	false	string	
user	The rados user name. Default is admin. More info: http://releases.k8s.io/release-1.3/examples/rbd/README.md#how-to-use-it	false	string	
keyring	Keyring is the path to key ring for RBDUser. Default is /etc/ceph/keyring. More info: http://releases.k8s.io/release-1.3/examples/rbd/README.md#how-to-use-it	false	string	

Name	Description	Required	Schema	Default
secretRef	SecretRef is name of the authentication secret for RBDUser. If provided overrides keyring. Default is nil. More info: http://releases.k8s.io/release-1.3/examples/rbd/README.md#how-to-use-it	false	Section 2.3.138, "v1.LocalObjectReference"	
readOnly	ReadOnly here will force the ReadOnly setting in VolumeMounts. Defaults to false. More info: http://releases.k8s.io/release-1.3/examples/rbd/README.md#how-to-use-it	false	boolean	

3.3.116. v1.ReplicationController

ReplicationController represents the configuration of a replication controller.

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#types-kinds	false	string	

Name	Description	Required	Schema	Default
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#resources	false	string	
metadata	If the Labels of a ReplicationController are empty, they are defaulted to be the same as the Pod(s) that the replication controller manages. Standard object's metadata. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#metadata	false	Section 2.3.158, "v1.ObjectMeta"	
spec	Spec defines the specification of the desired behavior of the replication controller. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#spec-and-status	false	Section 3.3.118, "v1.ReplicationControllerSpec"	

Name	Description	Required	Schema	Default
status	Status is the most recently observed status of the replication controller. This data may be out of date by some window of time. Populated by the system. Read-only. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#spec-and-status	false	Section 3.3.119, "v1.ReplicationControllerStatus"	

3.3.117. v1.ReplicationControllerList

ReplicationControllerList is a collection of replication controllers.

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#types-kinds	false	string	

Name	Description	Required	Schema	Default
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#resources	false	string	
metadata	Standard list metadata. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#types-kinds	false	Section 2.3.9 , “unversioned.ListMeta”	
items	List of replication controllers. More info: http://releases.k8s.io/release-1.3/docs/user-guide/replication-controller.md	true	Section 3.3.116 , “v1.ReplicationController” array	

3.3.118. v1.ReplicationControllerSpec

ReplicationControllerSpec is the specification of a replication controller.

Name	Description	Required	Schema	Default
------	-------------	----------	--------	---------

Name	Description	Required	Schema	Default
replicas	Replicas is the number of desired replicas. This is a pointer to distinguish between explicit zero and unspecified. Defaults to 1. More info: http://releases.k8s.io/release-1.3/docs/user-guide/replication-controller.md#what-is-a-replication-controller	false	integer (int32)	
selector	Selector is a label query over pods that should match the Replicas count. If Selector is empty, it is defaulted to the labels present on the Pod template. Label keys and values that must match in order to be controlled by this replication controller, if empty defaulted to labels on Pod template. More info: http://releases.k8s.io/release-1.3/docs/user-guide/labels.md#label-selectors	false	object	

Name	Description	Required	Schema	Default
template	Template is the object that describes the pod that will be created if insufficient replicas are detected. This takes precedence over a TemplateRef. More info: http://releases.k8s.io/release-1.3/docs/user-guide/replication-controller.md#pod-template	false	Section 2.3.165, "v1.PodTemplateSpec"	

3.3.119. v1.ReplicationControllerStatus

ReplicationControllerStatus represents the current status of a replication controller.

Name	Description	Required	Schema	Default
replicas	Replicas is the most recently observed number of replicas. More info: http://releases.k8s.io/release-1.3/docs/user-guide/replication-controller.md#what-is-a-replication-controller	true	integer (int32)	
fullyLabeledReplicas	The number of pods that have labels matching the labels of the pod template of the replication controller.	false	integer (int32)	

Name	Description	Required	Schema	Default
observedGeneration	ObservedGeneration reflects the generation of the most recently observed replication controller.	false	integer (int64)	

3.3.120. v1.ResourceFieldSelector

ResourceFieldSelector represents container resources (cpu, memory) and their output format

Name	Description	Required	Schema	Default
containerName	Container name: required for volumes, optional for env vars	false	string	
resource	Required: resource to select	true	string	
divisor	Specifies the output format of the exposed resources, defaults to "1"	false	string	

3.3.121. v1.ResourceQuota

ResourceQuota sets aggregate quota restrictions enforced per namespace

Name	Description	Required	Schema	Default
------	-------------	----------	--------	---------

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#types-kinds	false	string	
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#resources	false	string	
metadata	Standard object's metadata. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#metadata	false	Section 2.3.158, "v1.ObjectMeta"	

Name	Description	Required	Schema	Default
spec	Spec defines the desired quota. http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#spec-and-status	false	Section 2.3.185, "v1.ResourceQuotaSpec"	
status	Status defines the actual enforced quota and its current usage. http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#spec-and-status	false	Section 2.3.186, "v1.ResourceQuotaStatus"	

3.3.122. v1.ResourceQuotaList

ResourceQuotaList is a list of ResourceQuota items.

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#types-kinds	false	string	

Name	Description	Required	Schema	Default
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#resources	false	string	
metadata	Standard list metadata. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#types-kinds	false	Section 2.3.9 , “unversioned.ListMeta”	
items	Items is a list of ResourceQuota objects. More info: http://releases.k8s.io/release-1.3/docs/design/admission_control_resource_quota.md#admissioncontrol-plugin-resourcequota	true	Section 3.3.121 , “v1.ResourceQuota” array	

3.3.123. v1.ResourceQuotaScope

3.3.124. v1.ResourceQuotaSpec

ResourceQuotaSpec defines the desired hard limits to enforce for Quota.

Name	Description	Required	Schema	Default
------	-------------	----------	--------	---------

Name	Description	Required	Schema	Default
hard	Hard is the set of desired hard limits for each named resource. More info: http://releases.k8s.io/release-1.3/docs/design/admission_control_resource_quota.md#admissioncontrol-plugin-resourcequota	false	object	
scopes	A collection of filters that must match each object tracked by a quota. If not specified, the quota matches all objects.	false	Section 2.3.184, "v1.ResourceQuota.aScope" array	

3.3.125. v1.ResourceQuotaStatus

ResourceQuotaStatus defines the enforced hard limits and observed use.

Name	Description	Required	Schema	Default
hard	Hard is the set of enforced hard limits for each named resource. More info: http://releases.k8s.io/release-1.3/docs/design/admission_control_resource_quota.md#admissioncontrol-plugin-resourcequota	false	object	
used	Used is the current observed total usage of the resource in the namespace.	false	object	

3.3.126. v1.ResourceRequirements

ResourceRequirements describes the compute resource requirements.

Name	Description	Required	Schema	Default
limits	Limits describes the maximum amount of compute resources allowed. More info: http://releases.k8s.io/release-1.3/docs/design/resources.md#resource-specifications	false	object	
requests	Requests describes the minimum amount of compute resources required. If Requests is omitted for a container, it defaults to Limits if that is explicitly specified, otherwise to an implementation-defined value. More info: http://releases.k8s.io/release-1.3/docs/design/resources.md#resource-specifications	false	object	

3.3.127. v1.RunAsUserStrategyOptions

RunAsUserStrategyOptions defines the strategy type and any options used to create the strategy.

Name	Description	Required	Schema	Default
type	Type is the strategy that will dictate what RunAsUser is used in the SecurityContext.	false	string	

Name	Description	Required	Schema	Default
uid	UID is the user id that containers must run as. Required for the MustRunAs strategy if not using namespace/service account allocated uids.	false	integer (int64)	
uidRangeMin	UIDRangeMin defines the min value for a strategy that allocates by range.	false	integer (int64)	
uidRangeMax	UIDRangeMax defines the max value for a strategy that allocates by range.	false	integer (int64)	

3.3.128. v1.SELinuxContextStrategyOptions

SELinuxContextStrategyOptions defines the strategy type and any options used to create the strategy.

Name	Description	Required	Schema	Default
type	Type is the strategy that will dictate what SELinux context is used in the SecurityContext.	false	string	
seLinuxOptions	seLinuxOptions required to run as; required for MustRunAs	false	Section 2.3.202, "v1.SELinuxOptions"	

3.3.129. v1.SELinuxOptions

SELinuxOptions are the labels to be applied to the container

Name	Description	Required	Schema	Default
user	User is a SELinux user label that applies to the container.	false	string	
role	Role is a SELinux role label that applies to the container.	false	string	
type	Type is a SELinux type label that applies to the container.	false	string	
level	Level is SELinux level label that applies to the container.	false	string	

3.3.130. v1.Scale

Scale represents a scaling request for a resource.

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#types-kinds	false	string	

Name	Description	Required	Schema	Default
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#resources	false	string	
metadata	Standard object metadata; More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#metadata .	false	Section 2.3.158 , “v1.ObjectMeta”	
spec	defines the behavior of the scale. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#spec-and-status .	false	Section 3.3.131 , “v1.ScaleSpec”	
status	current status of the scale. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#spec-and-status . Read-only.	false	Section 3.3.132 , “v1.ScaleStatus”	

3.3.131. v1.ScaleSpec

ScaleSpec describes the attributes of a scale subresource.

Name	Description	Required	Schema	Default
replicas	desired number of instances for the scaled object.	false	integer (int32)	

3.3.132. v1.ScaleStatus

ScaleStatus represents the current status of a scale subresource.

Name	Description	Required	Schema	Default
replicas	actual number of observed instances of the scaled object.	true	integer (int32)	
selector	label query over pods that should match the replicas count. This is same as the label selector but in the string format to avoid introspection by clients. The string will be in the same format as the query-param syntax. More info about label selectors: http://releases.k8s.io/release-1.3/docs/user-guide/labels.md#label-selectors	false	string	

3.3.133. v1.Secret

Secret holds secret data of a certain type. The total bytes of the values in the Data field must be less than MaxSecretSize bytes.

Name	Description	Required	Schema	Default
------	-------------	----------	--------	---------

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#types-kinds	false	string	
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#resources	false	string	
metadata	Standard object's metadata. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#metadata	false	Section 2.3.158, "v1.ObjectMeta"	

Name	Description	Required	Schema	Default
data	Data contains the secret data. Each key must be a valid DNS_SUBDOMAIN or leading dot followed by valid DNS_SUBDOMAIN. The serialized form of the secret data is a base64 encoded string, representing the arbitrary (possibly non-string) data value here. Described in https://tools.ietf.org/html/rfc4648#section-4	false	object	
stringData	stringData allows specifying non-binary secret data in string form. It is provided as a write-only convenience method. All keys and values are merged into the data field on write, overwriting any existing values. It is never output when reading from the API.	false	object	
type	Used to facilitate programmatic handling of secret data.	false	string	

3.3.134. v1.SecretKeySelector

SecretKeySelector selects a key of a Secret.

Name	Description	Required	Schema	Default
------	-------------	----------	--------	---------

Name	Description	Required	Schema	Default
name	Name of the referent. More info: http://releases.k8s.io/release-1.3/docs/user-guide/identifiers.md#names	false	string	
key	The key of the secret to select from. Must be a valid secret key.	true	string	

3.3.135. v1.SecretList

SecretList is a list of Secret.

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#types-kinds	false	string	

Name	Description	Required	Schema	Default
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#resources	false	string	
metadata	Standard list metadata. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#types-kinds	false	Section 2.3.9 , “unversioned.ListMeta”	
items	Items is a list of secret objects. More info: http://releases.k8s.io/release-1.3/docs/user-guide/secrets.md	true	Section 2.3.204 , “v1.Secret” array	

3.3.136. v1.SecretVolumeSource

Adapts a Secret into a volume.

The contents of the target Secret’s Data field will be presented in a volume as files using the keys in the Data field as the file names. Secret volumes support ownership management and SELinux relabeling.

Name	Description	Required	Schema	Default
------	-------------	----------	--------	---------

Name	Description	Required	Schema	Default
secretName	Name of the secret in the pod's namespace to use. More info: http://releases.k8s.io/release-1.3/docs/user-guide/volumes.md#secrets	false	string	
items	If unspecified, each key-value pair in the Data field of the referenced Secret will be projected into the volume as a file whose name is the key and content is the value. If specified, the listed keys will be projected into the specified paths, and unlisted keys will not be present. If a key is specified which is not present in the Secret, the volume setup will error. Paths must be relative and may not contain the '..' path or start with '..'	false	Section 2.3.135, "v1.KeyToPath" array	

3.3.137. v1.SecurityContext

SecurityContext holds security configuration that will be applied to a container. Some fields are present in both SecurityContext and PodSecurityContext. When both are set, the values in SecurityContext take precedence.

Name	Description	Required	Schema	Default
------	-------------	----------	--------	---------

Name	Description	Required	Schema	Default
capabilities	The capabilities to add/drop when running containers. Defaults to the default set of capabilities granted by the container runtime.	false	Section 2.3.35, "v1.Capabilities"	
privileged	Run container in privileged mode. Processes in privileged containers are essentially equivalent to root on the host. Defaults to false.	false	boolean	
seLinuxOptions	The SELinux context to be applied to the container. If unspecified, the container runtime will allocate a random SELinux context for each container. May also be set in PodSecurityContext. If set in both SecurityContext and PodSecurityContext, the value specified in SecurityContext takes precedence.	false	Section 2.3.202, "v1.SELinuxOptions"	

Name	Description	Required	Schema	Default
runAsUser	The UID to run the entrypoint of the container process. Defaults to user specified in image metadata if unspecified. May also be set in PodSecurityContext. If set in both SecurityContext and PodSecurityContext, the value specified in SecurityContext takes precedence.	false	integer (int64)	
runAsNonRoot	Indicates that the container must run as a non-root user. If true, the Kubelet will validate the image at runtime to ensure that it does not run as UID 0 (root) and fail to start the container if it does. If unset or false, no such validation will be performed. May also be set in PodSecurityContext. If set in both SecurityContext and PodSecurityContext, the value specified in SecurityContext takes precedence.	false	boolean	
readOnlyRootFilesystem	Whether this container has a read-only root filesystem. Default is false.	false	boolean	

3.3.138. v1.SecurityContextConstraints

SecurityContextConstraints governs the ability to make requests that affect the SecurityContext that will be applied to a container.

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#types-kinds	false	string	
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#resources	false	string	
metadata		false	Section 2.3.158, "v1.ObjectMeta"	

Name	Description	Required	Schema	Default
priority	Priority influences the sort order of SCCs when evaluating which SCCs to try first for a given pod request based on access in the Users and Groups fields. The higher the int, the higher priority. If scores for multiple SCCs are equal they will be sorted by name.	true	integer (int32)	
allowPrivilegedContainer	AllowPrivilegedContainer determines if a container can request to be run as privileged.	true	boolean	
defaultAddCapabilities	DefaultAddCapabilities is the default set of capabilities that will be added to the container unless the pod spec specifically drops the capability. You may not list a capability in both DefaultAddCapabilities and RequiredDropCapabilities.	true	Section 2.3.36, "v1.Capability" array	
requiredDropCapabilities	RequiredDropCapabilities are the capabilities that will be dropped from the container. These are required to be dropped and cannot be added.	true	Section 2.3.36, "v1.Capability" array	

Name	Description	Required	Schema	Default
allowedCapabilities	AllowedCapabilities is a list of capabilities that can be requested to add to the container. Capabilities in this field maybe added at the pod author's discretion. You must not list a capability in both AllowedCapabilities and RequiredDropCapabilities.	true	Section 2.3.36 , "v1.Capability" array	
allowHostDirVolumePlugin	AllowHostDirVolumePlugin determines if the policy allow containers to use the HostDir volume plugin	true	boolean	
volumes	Volumes is a white list of allowed volume plugins. FSType corresponds directly with the field names of a VolumeSource (azureFile, configMap, emptyDir). To allow all volumes you may use "*".	true	Section 3.3.55 , "v1.FSType" array	
allowHostNetwork	AllowHostNetwork determines if the policy allows the use of HostNetwork in the pod spec.	true	boolean	
allowHostPorts	AllowHostPorts determines if the policy allows host ports in the containers.	true	boolean	

Name	Description	Required	Schema	Default
allowHostPID	AllowHostPID determines if the policy allows host pid in the containers.	true	boolean	
allowHostIPC	AllowHostIPC determines if the policy allows host ipc in the containers.	true	boolean	
seLinuxContext	SELinuxContext is the strategy that will dictate what labels will be set in the SecurityContext.	false	Section 3.3.128, "v1.SELinuxContextStrategyOptions"	
runAsUser	RunAsUser is the strategy that will dictate what RunAsUser is used in the SecurityContext.	false	Section 3.3.127, "v1.RunAsUserStrategyOptions"	
supplementalGroups	SupplementalGroups is the strategy that will dictate what supplemental groups are used by the SecurityContext.	false	Section 3.3.147, "v1.SupplementalGroupsStrategyOptions"	
fsGroup	FSGroup is the strategy that will dictate what fs group is used by the SecurityContext.	false	Section 3.3.54, "v1.FSGroupStrategyOptions"	

Name	Description	Required	Schema	Default
readOnlyRootFilesystem	ReadOnlyRootFilesystem when set to true will force containers to run with a read only root file system. If the container specifically requests to run with a non-read only root file system the SCC should deny the pod. If set to false the container may run with a read only root file system if it wishes but it will not be forced to.	true	boolean	
users	The users who have permissions to use this security context constraints	false	string array	
groups	The groups that have permission to use this security context constraints	false	string array	

Name	Description	Required	Schema	Default
seccompProfiles	SeccompProfiles lists the allowed profiles that may be set for the pod or container's seccomp annotations. An unset (nil) or empty value means that no profiles may be specified by the pod or container. The wildcard '*' may be used to allow all profiles. When used to generate a value for a pod the first non-wildcard profile will be used as the default.	false	string array	

3.3.139. v1.SecurityContextConstraintsList

SecurityContextConstraintsList is a list of SecurityContextConstraints objects

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#types-kinds	false	string	

Name	Description	Required	Schema	Default
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#resources	false	string	
metadata		false	Section 2.3.9, "unversioned.ListMeta"	
items		true	Section 3.3.138, "v1.SecurityContextConstraints" array	

3.3.140. v1.Service

A Service is an abstraction which defines a logical set of Pods and a policy by which to access them - sometimes called a micro-service. The set of Pods targeted by a Service is (usually) determined by a Label selector. Services broadly fall into two types - those that load balance a set of Pods and hide which Pod a client talks to (clusterIP set to an IP address), and those where clients want to talk to the individual member pods directly (clusterIP set to 'None', also known as 'headless' services). The cluster IP of a service is exposed as an environment variable in each pod in the same namespace.

Services may be exposed only inside the cluster (type ClusterIP), inside the cluster and on a high port on each node (type NodePort), or exposed to a load balancer via the hosting cloud infrastructure (type LoadBalancer). Services with a ClusterIP may choose to map the ports available on the ClusterIP to different ports on the pods. Each service has a DNS entry of the form **<name>**.

<namespace>.svc.cluster.local that will be valid from other pods in the cluster.

If the selector for pods is not specified, the service endpoints may be managed by the client directly. Update the endpoint resource to program the service - this can be used to inject external network services into a namespace.

See [the Kubernetes service documentation](#) for more information.

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#types-kinds	false	string	
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#resources	false	string	
metadata	Standard object's metadata. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#metadata	false	Section 2.3.158, "v1.ObjectMeta"	

Name	Description	Required	Schema	Default
spec	Spec defines the behavior of a service. http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#spec-and-status	false	Section 3.3.145, "v1.ServiceSpec"	
status	Most recently observed status of the service. Populated by the system. Read-only. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#spec-and-status	false	Section 3.3.146, "v1.ServiceStatus"	

3.3.141. v1.ServiceAccount

ServiceAccount binds together: * a name, understood by users, and perhaps by peripheral systems, for an identity * a principal that can be authenticated and authorized * a set of secrets

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#types-kinds	false	string	

Name	Description	Required	Schema	Default
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#resources	false	string	
metadata	Standard object's metadata. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#metadata	false	Section 2.3.158, "v1.ObjectMeta"	
secrets	Secrets is the list of secrets allowed to be used by pods running using this ServiceAccount. More info: http://releases.k8s.io/release-1.3/docs/user-guide/secrets.md	false	Section 2.3.159, "v1.ObjectReference" array	

Name	Description	Required	Schema	Default
imagePullSecrets	ImagePullSecrets is a list of references to secrets in the same namespace to use for pulling any images in pods that reference this ServiceAccount. ImagePullSecrets are distinct from Secrets because Secrets can be mounted in the pod, but ImagePullSecrets are only accessed by the kubelet. More info: http://releases.k8s.io/release-1.3/docs/user-guide/secrets.md#manually-specifying-an-imagepullsecret	false	Section 2.3.138, "v1.LocalObjectReference" array	

3.3.142. v1.ServiceAccountList

ServiceAccountList is a list of ServiceAccount objects

Name	Description	Required	Schema	Default
------	-------------	----------	--------	---------

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#types-kinds	false	string	
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#resources	false	string	
metadata	Standard list metadata. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#types-kinds	false	Section 2.3.9, "unversioned.ListMeta"	

Name	Description	Required	Schema	Default
items	List of ServiceAccounts. More info: http://releases.k8s.io/release-1.3/docs/design/service_accounts.md#service-accounts	true	Section 3.3.141 , "v1.ServiceAccount" array	

3.3.143. v1.ServiceList

ServiceList holds a list of services.

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#types-kinds	false	string	

Name	Description	Required	Schema	Default
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#resources	false	string	
metadata	Standard list metadata. More info: http://releases.k8s.io/release-1.3/docs/devel/api-conventions.md#types-kinds	false	Section 2.3.9, “unversioned.ListMeta”	
items	List of services	true	Section 3.3.140, “v1.Service” array	

3.3.144. v1.ServicePort

ServicePort contains information on service’s port.

Name	Description	Required	Schema	Default
------	-------------	----------	--------	---------

Name	Description	Required	Schema	Default
name	The name of this port within the service. This must be a DNS_LABEL. All ports within a ServiceSpec must have unique names. This maps to the 'Name' field in EndpointPort objects. Optional if only one ServicePort is defined on this service.	false	string	
protocol	The IP protocol for this port. Supports "TCP" and "UDP". Default is TCP.	false	string	
port	The port that will be exposed by this service.	true	integer (int32)	

Name	Description	Required	Schema	Default
targetPort	<p>Number or name of the port to access on the pods targeted by the service. Number must be in the range 1 to 65535. Name must be an IANA_SVC_NAME . If this is a string, it will be looked up as a named port in the target Pod's container ports. If this is not specified, the value of the 'port' field is used (an identity map). This field is ignored for services with clusterIP=None, and should be omitted or set equal to the 'port' field. More info: http://releases.k8s.io/release-1.3/docs/user-guide/services.md#defining-a-service</p>	false	string	

Name	Description	Required	Schema	Default
nodePort	The port on each node on which this service is exposed when type=NodePort or LoadBalancer. Usually assigned by the system. If specified, it will be allocated to the service if unused or else creation of the service will fail. Default is to auto-allocate a port if the ServiceType of this Service requires one. More info: http://releases.k8s.io/release-1.3/docs/user-guide/services.md#type—nodeport	false	integer (int32)	

3.3.145. v1.ServiceSpec

ServiceSpec describes the attributes that a user creates on a service.

Name	Description	Required	Schema	Default
ports	The list of ports that are exposed by this service. More info: http://releases.k8s.io/release-1.3/docs/user-guide/services.md#virtual-ips-and-service-proxies	true	Section 3.3.144, "v1.ServicePort" array	

Name	Description	Required	Schema	Default
selector	This service will route traffic to pods having labels matching this selector. Label keys and values that must match in order to receive traffic for this service. If empty, all pods are selected, if not specified, endpoints must be manually specified. More info: http://releases.k8s.io/release-1.3/docs/user-guide/services.md#overview	false	object	
portallIP	The IP Address of the service. Deprecated: Use clusterIP instead.	false	string	

Name	Description	Required	Schema	Default
clusterIP	<p>ClusterIP is usually assigned by the master and is the IP address of the service. If specified, it will be allocated to the service if it is unused or else creation of the service will fail. Valid values are None, empty string (""), or a valid IP address. 'None' can be specified for a headless service when proxying is not required. Cannot be updated. More info:</p> <p>http://releases.k8s.io/release-1.3/docs/user-guide/services.md#virtual-ips-and-service-proxies</p>	false	string	
type	<p>Type of exposed service. Must be ClusterIP, NodePort, or LoadBalancer. Defaults to ClusterIP. More info:</p> <p>http://releases.k8s.io/release-1.3/docs/user-guide/services.md#external-services</p>	false	string	

Name	Description	Required	Schema	Default
externalIPs	<p>externalIPs is a list of IP addresses for which nodes in the cluster will also accept traffic for this service. These IPs are not managed by Kubernetes. The user is responsible for ensuring that traffic arrives at a node with this IP. A common example is external load-balancers that are not part of the Kubernetes system. A previous form of this functionality exists as the deprecatedPublicIPs field. When using this field, callers should also clear the deprecatedPublicIPs field.</p>	false	string array	
deprecatedPublicIPs	<p>deprecatedPublicIPs is deprecated and replaced by the externalIPs field with almost the exact same semantics. This field is retained in the v1 API for compatibility until at least 8/20/2016. It will be removed from any new API revisions. If both deprecatedPublicIPs and externalIPs are set, deprecatedPublicIPs is used.</p>	false	string array	

Name	Description	Required	Schema	Default
sessionAffinity	Supports "ClientIP" and "None". Used to maintain session affinity. Enable client IP based session affinity. Must be ClientIP or None. Defaults to None. More info: http://releases.k8s.io/release-1.3/docs/user-guide/services.md#virtual-ips-and-service-proxies	false	string	
loadBalancerIP	Only applies to Service Type: LoadBalancer LoadBalancer will get created with the IP specified in this field. This feature depends on whether the underlying cloud-provider supports specifying the loadBalancerIP when a load balancer is created. This field will be ignored if the cloud-provider does not support the feature.	false	string	

Name	Description	Required	Schema	Default
loadBalancerSourceRanges	If specified and supported by the platform, this will restrict traffic through the cloud-provider load-balancer will be restricted to the specified client IPs. This field will be ignored if the cloud-provider does not support the feature." More info: http://releases.k8s.io/release-1.3/docs/user-guide/services-firewalls.md	false	string array	

3.3.146. v1.ServiceStatus

ServiceStatus represents the current status of a service.

Name	Description	Required	Schema	Default
loadBalancer	LoadBalancer contains the current status of the load-balancer, if one is present.	false	Section 3.3.75, "v1.LoadBalancer Status"	

3.3.147. v1.SupplementalGroupsStrategyOptions

SupplementalGroupsStrategyOptions is the strategy that will dictate what supplemental groups are used by the SecurityContext.

Name	Description	Required	Schema	Default
type	Type is the strategy that will dictate what supplemental groups is used in the SecurityContext.	false	string	

Name	Description	Required	Schema	Default
ranges	Ranges are the allowed ranges of supplemental groups. If you would like to force a single supplemental group then supply a single range with the same start and end.	false	Section 3.3.66 , "v1.IDRange" array	

3.3.148. v1.TCPSocketAction

TCPSocketAction describes an action based on opening a socket

Name	Description	Required	Schema	Default
port	Number or name of the port to access on the container. Number must be in the range 1 to 65535. Name must be an IANA_SVC_NAME	true	string	

3.3.149. v1.UniqueVolumeName

3.3.150. v1.Volume

Volume represents a named volume in a pod that may be accessed by any container in the pod.

Name	Description	Required	Schema	Default
name	Volume's name. Must be a DNS_LABEL and unique within the pod. More info: http://releases.k8s.io/release-1.3/docs/user-guide/identifiers.md#names	true	string	

Name	Description	Required	Schema	Default
hostPath	HostPath represents a pre-existing file or directory on the host machine that is directly exposed to the container. This is generally used for system agents or other privileged things that are allowed to see the host machine. Most containers will NOT need this. More info: http://releases.k8s.io/release-1.3/docs/user-guide/volumes.md#hostpath	false	Section 2.3.106, "v1.HostPathVolumeSource"	
emptyDir	EmptyDir represents a temporary directory that shares a pod's lifetime. More info: http://releases.k8s.io/release-1.3/docs/user-guide/volumes.md#emptydir	false	Section 2.3.85, "v1.EmptyDirVolumeSource"	
gcePersistentDisk	GCEPersistentDisk represents a GCE Disk resource that is attached to a kubelet's host machine and then exposed to the pod. More info: http://releases.k8s.io/release-1.3/docs/user-guide/volumes.md#gcepersistentdisk	false	Section 2.3.94, "v1.GCEPersistentDiskVolumeSource"	

Name	Description	Required	Schema	Default
awsElasticBlockStore	AWSElasticBlockStore represents an AWS Disk resource that is attached to a kubelet's host machine and then exposed to the pod. More info: http://releases.k8s.io/release-1.3/docs/user-guide/volumes.md#awselasticblockstore	false	Section 2.3.14, "v1.AWSElasticBlockStoreVolumeSource"	
gitRepo	GitRepo represents a git repository at a particular revision.	false	Section 2.3.98, "v1.GitRepoVolumeSource"	
secret	Secret represents a secret that should populate this volume. More info: http://releases.k8s.io/release-1.4/docs/user-guide/volumes.md#secrets	false	Section 2.3.209, "v1.SecretVolumeSource"	
nfs	NFS represents an NFS mount on the host that shares a pod's lifetime More info: http://releases.k8s.io/release-1.4/docs/user-guide/volumes.md#nfs	false	Section 2.3.141, "v1.NFSVolumeSource"	

Name	Description	Required	Schema	Default
iscsi	ISCSI represents an ISCSI Disk resource that is attached to a kubelet's host machine and then exposed to the pod. More info: http://releases.k8s.io/release-1.4/examples/volumes/iscsi/README.md	false	Section 2.3.109, "v1.ISCSIVolumeSource"	
glusterfs	Glusterfs represents a Glusterfs mount on the host that shares a pod's lifetime. More info: http://releases.k8s.io/release-1.4/examples/volumes/glusterfs/README.md	false	Section 2.3.100, "v1.GlusterfsVolumeSource"	
persistentVolumeClaim	PersistentVolumeClaimVolumeSource represents a reference to a PersistentVolumeClaim in the same namespace. More info: http://releases.k8s.io/release-1.4/docs/user-guide/persistent-volumes.md#persistentvolumeclaims	false	Section 2.3.162, "v1.PersistentVolumeClaimVolumeSource"	
rbd	A Ceph Rados Block Device mount on the host that shares a pod's lifetime. More info: http://releases.k8s.io/release-1.4/examples/volumes/rbd/README.md	false	Section 2.3.178, "v1.RBDVolumeSource"	

Name	Description	Required	Schema	Default
flexVolume	FlexVolume represents a generic volume resource that is provisioned/attached using an exec based plugin. This is an alpha feature and may change in future.	false	Section 2.3.92, "v1.FlexVolumeSource"	
cinder	Cinder represents a cinder volume attached and mounted on kubelets host machine More info: http://releases.k8s.io/release-1.4/examples/mysql-cinder-pd/README.md	false	Section 2.3.38, "v1.CinderVolumeSource"	
cephfs	CephFS represents a Ceph FS mount on the host that shares a pod's lifetime	false	Section 2.3.37, "v1.CephFSVolumeSource"	
flocker	Flocker represents a Flocker volume attached to a kubelet's host machine. This depends on the Flocker control service being running	false	Section 2.3.93, "v1.FlockerVolumeSource"	
downwardAPI	DownwardAPI represents downward API about the pod that should populate this volume	false	Section 2.3.79, "v1.DownwardAPIVolumeSource"	

Name	Description	Required	Schema	Default
fc	FC represents a Fibre Channel resource that is attached to a kubelet's host machine and then exposed to the pod.	false	Section 2.3.90, "v1.FCVolumeSource"	
azureFile	AzureFile represents an Azure File Service mount on the host and bind mount to the pod.	false	Section 2.3.17, "v1.AzureFileVolumeSource"	
configMap	ConfigMap represents a configMap that should populate this volume	false	Section 2.3.56, "v1.ConfigMapVolumeSource"	
vsphereVolume	VsphereVolume represents a vSphere volume attached and mounted on kubelets host machine	false	Section 2.3.235, "v1.VsphereVirtualDiskVolumeSource"	
metadata	Metadata represents metadata about the pod that should populate this volume Deprecated: Use downwardAPI instead.	false	Section 2.3.76, "v1.DeprecatedDownwardAPIVolumeSource"	

3.3.151. v1.VolumeMount

VolumeMount describes a mounting of a Volume within a container.

Name	Description	Required	Schema	Default
name	This must match the Name of a Volume.	true	string	

Name	Description	Required	Schema	Default
readOnly	Mounted read-only if true, read-write otherwise (false or unspecified). Defaults to false.	false	boolean	
mountPath	Path within the container at which the volume should be mounted. Must not contain '.'.	true	string	
subPath	Path within the volume from which the container's volume should be mounted. Defaults to "" (volume's root).	false	string	

3.3.152. v1.VsphereVirtualDiskVolumeSource

Represents a vSphere volume resource.

Name	Description	Required	Schema	Default
volumePath	Path that identifies vSphere volume vmdk	true	string	
fsType	Filesystem type to mount. Must be a filesystem type supported by the host operating system. Ex. "ext4", "xfs", "ntfs". Implicitly inferred to be "ext4" if unspecified.	false	string	

3.3.153. any

Represents an untyped JSON map - see the description of the field for more info about the structure of this object.

CHAPTER 4. REVISION HISTORY: REST API REFERENCE

4.1. TUE OCT 04 2016

Affected Topic	Description of Change
Overview	Updated the <code>oc whoami --token</code> command to show the shorter flag of <code>oc whoami --t</code> .

4.2. TUE SEP 27 2016

OpenShift Container Platform 3.3 initial release.