



Red Hat Ansible Automation Platform 2.1

Installing and Configuring Central Authentication for the Ansible Automation Platform

Enable central authentication functions for your Ansible Automation Platform

Red Hat Ansible Automation Platform 2.1 Installing and Configuring Central Authentication for the Ansible Automation Platform

Enable central authentication functions for your Ansible Automation Platform

Legal Notice

Copyright © 2022 Red Hat, Inc.

The text of and illustrations in this document are licensed by Red Hat under a Creative Commons Attribution–Share Alike 3.0 Unported license ("CC-BY-SA"). An explanation of CC-BY-SA is available at

<http://creativecommons.org/licenses/by-sa/3.0/>

. In accordance with CC-BY-SA, if you distribute this document or an adaptation of it, you must provide the URL for the original version.

Red Hat, as the licensor of this document, waives the right to enforce, and agrees not to assert, Section 4d of CC-BY-SA to the fullest extent permitted by applicable law.

Red Hat, Red Hat Enterprise Linux, the Shadowman logo, the Red Hat logo, JBoss, OpenShift, Fedora, the Infinity logo, and RHCE are trademarks of Red Hat, Inc., registered in the United States and other countries.

Linux[®] is the registered trademark of Linus Torvalds in the United States and other countries.

Java[®] is a registered trademark of Oracle and/or its affiliates.

XFS[®] is a trademark of Silicon Graphics International Corp. or its subsidiaries in the United States and/or other countries.

MySQL[®] is a registered trademark of MySQL AB in the United States, the European Union and other countries.

Node.js[®] is an official trademark of Joyent. Red Hat is not formally related to or endorsed by the official Joyent Node.js open source or commercial project.

The OpenStack[®] Word Mark and OpenStack logo are either registered trademarks/service marks or trademarks/service marks of the OpenStack Foundation, in the United States and other countries and are used with the OpenStack Foundation's permission. We are not affiliated with, endorsed or sponsored by the OpenStack Foundation, or the OpenStack community.

All other trademarks are the property of their respective owners.

Abstract

Providing Feedback: If you have a suggestion to improve this documentation, or find an error, please contact technical support at to create an issue on the Ansible Automation Platform Jira project using the Docs component.

Table of Contents

PREFACE	3
CHAPTER 1. ANSIBLE AUTOMATION PLATFORM CENTRAL AUTHENTICATION FOR AUTOMATION HUB	4
1.1. SYSTEM REQUIREMENTS	4
1.2. INSTALLING ANSIBLE AUTOMATION PLATFORM CENTRAL AUTHENTICATION FOR USE WITH AUTOMATION HUB	4
1.2.1. Choosing and obtaining a Red Hat Ansible Automation Platform installer	5
1.2.2. Configuring the Red Hat Ansible Automation Platform installer	5
1.2.3. Running the Red Hat Ansible Automation Platform installer	6
1.2.4. Log in as a central authentication admin user	6
CHAPTER 2. ADDING A USER STORAGE PROVIDER (LDAP/KERBEROS) TO ANSIBLE AUTOMATION PLATFORM CENTRAL AUTHENTICATION	7
CHAPTER 3. ASSIGNING AUTOMATION HUB ADMINISTRATOR PERMISSIONS	8
CHAPTER 4. ADDING AN IDENTITY BROKER TO ANSIBLE AUTOMATION PLATFORM CENTRAL AUTHENTICATION	9
CHAPTER 5. MANAGING GROUP PERMISSIONS WITH ANSIBLE AUTOMATION PLATFORM CENTRAL AUTHENTICATION	11
5.1. ASSIGNING PERMISSIONS TO GROUPS	11
5.2. AUTOMATION HUB PERMISSIONS	11

PREFACE

Ansible Automation Platform Central Authentication is a third-party identity provider (idP) solution, allowing for a simplified single sign-on solution that can be used across the Ansible Automation Platform. Platform administrators can utilize central authentication to test connectivity and authentication, as well as onboard new users and manage user permissions by configuring and assigning them to groups. Along with OpenID Connect-based and LDAP support, central authentication also provides a supported REST API which can be used to bootstrap customer usage.

CHAPTER 1. ANSIBLE AUTOMATION PLATFORM CENTRAL AUTHENTICATION FOR AUTOMATION HUB

To enable Ansible Automation Platform Central Authentication for your automation hub, start by downloading the Red Hat Ansible Automation Platform installer then proceed with the necessary set up procedures as detailed in this guide.



IMPORTANT

The installer in this guide will install central authentication for a basic standalone deployment. Standalone mode only runs one central authentication server instance, and thus will not be usable for clustered deployments. Standalone mode can be useful to test drive and play with the features of { CentralAuth}, but it is not recommended that you use standalone mode in production as you will only have a single point of failure.

To install central authentication in a different deployment mode, please see [this guide](#) for more deployment options.

1.1. SYSTEM REQUIREMENTS

There are several minimum requirements to install and run Ansible Automation Platform Central Authentication:

- Any operating system that runs Java
- Java 8 JDK
- zip or gzip and tar
- At least 512mb of RAM
- At least 1gb of disk space
- A shared external database like PostgreSQL, MySQL, Oracle, etc. if you want to run central authentication in a cluster. Please see the [database configuration section of this guide](#) for more information.
- Network multicast support on your machine if you want to run in a cluster. central authentication can be clustered without multicast, but this requires some configuration changes. Please see [the clustering section of this guide](#) for more information.
- On Linux, it is recommended to use `/dev/urandom` as a source of random data to prevent central authentication hanging due to lack of available entropy, unless `/dev/random` usage is mandated by your security policy. To achieve that on Oracle JDK 8 and OpenJDK 8, set the `java.security.egd` system property on startup to `file:/dev/urandom`.

1.2. INSTALLING ANSIBLE AUTOMATION PLATFORM CENTRAL AUTHENTICATION FOR USE WITH AUTOMATION HUB

The Ansible Automation Platform Central Authentication installation will be included with your Red Hat Ansible Automation Platform installer. Install the Ansible Automation Platform using the following procedures, then configure the necessary parameters in your inventory file to successfully install both the Ansible Automation Platform and central authentication.

1.2.1. Choosing and obtaining a Red Hat Ansible Automation Platform installer

Choose the Red Hat Ansible Automation Platform installer you need based on your Red Hat Enterprise Linux environment internet connectivity. Review the scenarios below and determine which Red Hat Ansible Automation Platform installer meets your needs.



NOTE

A valid Red Hat customer account is required to access Red Hat Ansible Automation Platform installer downloads on the Red Hat Customer Portal.

Installing with internet access

Choose the Red Hat Ansible Automation Platform installer if your Red Hat Enterprise Linux environment is connected to the internet. Installing with internet access will retrieve the latest required repositories, packages, and dependencies.

1. Navigate to <https://access.redhat.com/downloads/content/480>
2. Click **Download Now** for the **Ansible Automation Platform <latest-version> Setup**.
3. Extract the files:

```
$ tar xvfz ansible-automation-platform-setup-<latest-version>.tar.gz
```

Installing without internet access

Use the Red Hat Ansible Automation Platform **Bundle** installer if you are unable to access the internet, or would prefer not to install separate components and dependencies from online repositories. Access to Red Hat Enterprise Linux repositories is still needed. All other dependencies are included in the tar archive.

1. Navigate to <https://access.redhat.com/downloads/content/480>
2. Click **Download Now** for the **Ansible Automation Platform <latest-version> Setup Bundle**
3. Extract the files:

```
$ tar xvfz ansible-automation-platform-setup-bundle-<latest-version>.tar.gz
```

1.2.2. Configuring the Red Hat Ansible Automation Platform installer

Before running the installer, edit the inventory file found in the installer package to configure the installation of automation hub and Ansible Automation Platform Central Authentication.



NOTE

Provide a reachable IP address for the [automationhub] host to ensure users can sync content from Private Automation Hub from a different node and push new images to the container registry.

1. Navigate to the installer directory:
 - a. Online installer:

```
$ cd ansible-automation-platform-setup-<latest-version>
```

- b. Bundled installer:

```
$ cd ansible-automation-platform-setup-bundle-<latest-version>
```

2. Open the **inventory** file using a text editor.
3. Edit the inventory file parameters under **[automationhub]** to specify an installation of automation hub host:
 - a. Add group host information under **[automationhub]** using an IP address or FQDN for the automation hub location.
 - b. Enter passwords for **automationhub_admin_password**, **automation_pg_password**, and any additional parameters based on your installation specifications.
4. Enter a password in the **sso_keystore_password** field.
5. Edit the inventory file parameters under **[SSO]** to specify a host on which to install central authentication:
 - a. Enter a password in the **sso_console_admin_password** field, and any additional parameters based on your installation specifications.

1.2.3. Running the Red Hat Ansible Automation Platform installer

With the inventory file updated, run the installer using the **setup.sh** playbook found in the installer package.

1. Run the **setup.sh** playbook:

```
$ ./setup.sh
```

1.2.4. Log in as a central authentication admin user

With Red Hat Ansible Automation Platform installed, log in as an admin user to the central authentication server using the admin credentials that you specified in your inventory file.

1. Navigate to your Ansible Automation Platform Central Authentication instance.
2. Login using the admin credentials you specified in your inventory file, in the **sso_console_admin_username** and **sso_console_admin_password** fields.

With Ansible Automation Platform Central Authentication successfully installed, and the admin user logged in, you can proceed by adding a user storage provider (such as LDAP) using the following procedures.

CHAPTER 2. ADDING A USER STORAGE PROVIDER (LDAP/KERBEROS) TO ANSIBLE AUTOMATION PLATFORM CENTRAL AUTHENTICATION

Ansible Automation Platform Central Authentication comes with a built-in LDAP/AD provider. You can add your LDAP provider to central authentication to be able to import user attributes from your LDAP database.

Prerequisites

- You are logged in as an SSO admin user.

Procedure

- Log in to Ansible Automation Platform Central Authentication as an SSO admin user.
- Under the Configure section on the side navigation bar, click **User Federation**.
- Using the dropdown menu labeled *Add provider*, select your LDAP provider to proceed to the LDAP configuration page.

The following table lists the available options for your LDAP configuration:

Configuration Option	Description
Storage mode	Set to On if you want to import users into the central authentication user database. See this section for more information.
Edit mode	Determines the types of modifications that admins can make on user metadata. See this section for more information.
Console Display Name	Name used when this provider is referenced in the admin console
Priority	The priority of this provider when looking up users or adding a user
Sync Registrations	Enable if you want new users created by Ansible Automation Platform Central Authentication in the admin console or the registration page to be added to LDAP
Allow Kerberos authentication	Enable Kerberos/SPNEGO authentication in the realm with users data provisioned from LDAP. See this section for more information.

CHAPTER 3. ASSIGNING AUTOMATION HUB ADMINISTRATOR PERMISSIONS

Hub administrative users will need to be assigned the role of *hubadmin* in order to manage user permissions and groups. You can assign the role of *hubadmin* to a user through the Ansible Automation Platform Central Authentication client.

Prerequisites

- A user storage provider (e.g., LDAP) has been added to your central authentication

Procedure

1. Navigate to the **ansible-automation-platform** realm on your SSO client.
2. Under the *Manage* section on the side navigation bar, click **Users**.
3. Select a user from the list by clicking their ID.
4. Click the **Role Mappings** tab.
5. Using the dropdown menu under *Client Roles*, select **automation-hub**.
6. Click **hubadmin** from the *Available Roles* field, then click **Add selected** >.

The user is now a *hubadmin*. Repeat steps 3-6 to assign any additional users the *hubadmin* role.

CHAPTER 4. ADDING AN IDENTITY BROKER TO ANSIBLE AUTOMATION PLATFORM CENTRAL AUTHENTICATION

Ansible Automation Platform Central Authentication supports both social and protocol-based providers. You can add an identity broker to central authentication to enable social authentication for your realm, allowing users to log in using an existing social network account, such as Google, Facebook, GitHub etc.



NOTE

For a list of supported social networks and for more information to enable them, please see this [section](#).

Protocol-based providers are those that rely on a specific protocol in order to authenticate and authorize users. They allow you to connect to any identity provider compliant with a specific protocol. Ansible Automation Platform Central Authentication provides support for SAML v2.0 and OpenID Connect v1.0 protocols.

Procedure

1. Log in to Ansible Automation Platform Central Authentication as an admin user.
2. Under the *Configure* section on the side navigation bar, click **Identity Providers**.
3. Using the dropdown menu labeled *Add provider*, select your identity provider to proceed to the identity provider configuration page.

The following table lists the available options for your identity provider configuration:

Table 4.1. Identity Broker Configuration Options

Configuration Option	Description
Alias	The alias is a unique identifier for an identity provider. It is used to reference an identity provider internally. Some protocols such as OpenID Connect require a redirect URI or callback url in order to communicate with an identity provider. In this case, the alias is used to build the redirect URL.
Enabled	Turns the provider on/off.
Hide on Login Page	If enabled, this provider will not be shown as a login option on the login page. Clients can still request to use this provider by using the kc_idp_hint parameter in the URL they use to request a login.
Account Linking Only	If enabled, this provider cannot be used to login users and will not be shown as an option on the login page. Existing accounts can still be linked with this provider.

Store Tokens	Whether or not to store the token received from the identity provider.
Stored Tokens Readable	Whether or not users are allowed to retrieve the stored identity provider token. This also applies to the broker client-level role read token.
Trust Email	Whether an email address provided by the identity provider will be trusted. If the realm requires email validation, users that log in from this IDP will not have to go through the email verification process.
GUI Order	The order number that sorts how the available IDPs are listed on the login page.
First Login Flow	Select an authentication flow that will be triggered for users that log in to central authentication through this IDP for the first time.
Post Login Flow	Select an authentication flow that is triggered after the user finishes logging in with the external identity provider.

CHAPTER 5. MANAGING GROUP PERMISSIONS WITH ANSIBLE AUTOMATION PLATFORM CENTRAL AUTHENTICATION

You can manage user access on the Ansible Automation Platform by assigning specific permissions to user groups. As users log in to the Ansible Automation Platform for the first time, their groups will appear in the user access page in automation hub, allowing you to assign user access and permissions to each group.

5.1. ASSIGNING PERMISSIONS TO GROUPS

You can assign permissions to groups in automation hub that enable users to access specific features in the system.

Prerequisites

You are signed in as a **hubadmin** user.

Procedure

1. Log in to your local automation hub.
2. Navigate to **Groups**.
3. Click on a group name.
4. Click **Edit**.
5. Click in the field for the permission type and select permissions that appear in the list.
6. Click **Save** when finished assigning permissions.

The group can now access features in automation hub associated with their assigned permissions.

5.2. AUTOMATION HUB PERMISSIONS

Permissions provide a defined set of actions each group performs on a given object. Determine the required level of access for your groups based on the following permissions:

Table 5.1. Permissions Reference Table

Object	Permission	Description
namespace	Add namespace	Groups with these permissions can create, upload collections, or delete a namespace.
	Upload to namespace	
	Change namespace	
	Delete namespace	

Object	Permission	Description
collections	<ul style="list-style-type: none"> Modify Ansible repo content Delete collections 	Groups with this permission can move content between repositories using the Approval feature, certify or reject features to move content from the staging to published or rejected repositories, and delete collections.
users	<ul style="list-style-type: none"> View user Delete user Add user Change user 	Groups with these permissions can manage user configuration and access in automation hub.
groups	<ul style="list-style-type: none"> View group Delete group Add group Change group 	Groups with these permissions can manage group configuration and access in automation hub.
collection remotes	<ul style="list-style-type: none"> Change collection remote View collection remote 	Groups with these permissions can configure remote repository under Collections > Repo Management .
containers	<ul style="list-style-type: none"> Change container namespace permissions Change containers Change image tags Create new containers Push to existing containers Delete container repository 	Groups with these permissions can manage container repositories in automation hub.
remote registries	<ul style="list-style-type: none"> Add remote registry Change remote registry Delete remote registry 	Groups with these permissions can add, change, or delete remote registries added to automation hub.
task management	<ul style="list-style-type: none"> Change task Delete task View all tasks 	Groups with these permissions can manage tasks added to Task Management in automation hub.

