



Red Hat CloudForms

4.1

Assigning a Custom Analysis Profile to a Virtual Machine

How to assign a custom CloudForms analysis profile to a virtual machine

Red Hat CloudForms Documentation
Team

Red Hat CloudForms 4.1 Assigning a Custom Analysis Profile to a Virtual Machine

How to assign a custom CloudForms analysis profile to a virtual machine

Red Hat CloudForms Documentation Team
cloudforms-docs@redhat.com

Legal Notice

Copyright © 2017 Red Hat, Inc.

The text of and illustrations in this document are licensed by Red Hat under a Creative Commons Attribution–Share Alike 3.0 Unported license ("CC-BY-SA"). An explanation of CC-BY-SA is available at

<http://creativecommons.org/licenses/by-sa/3.0/>

. In accordance with CC-BY-SA, if you distribute this document or an adaptation of it, you must provide the URL for the original version.

Red Hat, as the licensor of this document, waives the right to enforce, and agrees not to assert, Section 4d of CC-BY-SA to the fullest extent permitted by applicable law.

Red Hat, Red Hat Enterprise Linux, the Shadowman logo, JBoss, OpenShift, Fedora, the Infinity logo, and RHCE are trademarks of Red Hat, Inc., registered in the United States and other countries.

Linux ® is the registered trademark of Linus Torvalds in the United States and other countries.

Java ® is a registered trademark of Oracle and/or its affiliates.

XFS ® is a trademark of Silicon Graphics International Corp. or its subsidiaries in the United States and/or other countries.

MySQL ® is a registered trademark of MySQL AB in the United States, the European Union and other countries.

Node.js ® is an official trademark of Joyent. Red Hat Software Collections is not formally related to or endorsed by the official Joyent Node.js open source or commercial project.

The OpenStack ® Word Mark and OpenStack logo are either registered trademarks/service marks or trademarks/service marks of the OpenStack Foundation, in the United States and other countries and are used with the OpenStack Foundation's permission. We are not affiliated with, endorsed or sponsored by the OpenStack Foundation, or the OpenStack community.

All other trademarks are the property of their respective owners.

Abstract

This guide provides instructions for assigning a custom CloudForms analysis profile to a virtual machine. If you have a suggestion for improving this guide or have found an error, please submit a Bugzilla report at <http://bugzilla.redhat.com> against Red Hat CloudForms Management Engine for the Documentation component. Please provide specific details, such as the section number, guide name, and CloudForms version so we can easily locate the content.



Table of Contents

1. CREATING A VIRTUAL MACHINE ANALYSIS PROFILE	2
2. CREATING AN ACTION TO ASSIGN THE VIRTUAL MACHINE ANALYSIS PROFILE TO THE ANALYSIS TASK	2
3. CREATING A VIRTUAL MACHINE CONTROL POLICY	3
4. CREATING A POLICY PROFILE AND ASSIGNING THE VIRTUAL MACHINE CONTROL POLICY	5
5. ASSIGNING THE POLICY PROFILE TO A VIRTUAL MACHINE	5

You can create and assign different analysis profiles for specific virtual machine configurations using the Red Hat CloudForms user interface. This document describes the steps required to create a custom virtual machine analysis profile, and assigning it to a virtual machine for use with SmartState analysis, via a control policy.

1. Creating a Virtual Machine Analysis Profile
2. Creating an Action to Assign the Virtual Machine Analysis Profile to Analysis Task
3. Creating a Virtual Machine Control Policy
4. Creating a Policy Profile and Assigning the Virtual Machine Control Policy
5. Assigning the Policy Profile to a Virtual Machine

1. CREATING A VIRTUAL MACHINE ANALYSIS PROFILE

1. Log into the appliance as the **admin** user.
2. Navigate to **Settings** → **Configuration**.
3. Expand the **Settings** accordion, then click **Analysis Profiles**.
4. Click  (**Configuration**), then  (**Add VM Analysis Profile**).
5. In **Basic Information**, enter **Name** and **Description** for the analysis profile.
6. In the **Category** tab, select the categories you want to collect information for under **Category Selection**. The **Category** tab is available for virtual machine profiles only.
7. In the **File** tab, click **<New Entry>** and specify the file to be scanned and collect contents for. Repeat the step for adding multiple file name entries.
8. In the **Registry** tab, enter the **Registry Key** and **Registry Value**. To determine whether a registry key exists without providing a value, enter * in **Registry Value**. The **Registry** tab is available for virtual machine profiles only.
9. In the **Event Log** tab, specify the event log entries to collect. Enter a **Filter Message** to look for specific text in a message. Enter a **Level** (*info*, *warn* or *error* for example) to specify the event level. Enter the **Source** for the event log entry and # (**Number**) of **Days** to specify how far back to check.
10. Click **Add**.

2. CREATING AN ACTION TO ASSIGN THE VIRTUAL MACHINE ANALYSIS PROFILE TO THE ANALYSIS TASK

Actions are performed after the condition is evaluated. You can associate actions with specific events when you create a policy. Red Hat CloudForms provides a set of default actions, but you can also create custom actions using the CloudForms user interface.

Use this procedure to create a custom action by adding the **Assign Profile to Analysis Task** action type to the virtual machine analysis profile (created in [Section 1, "Creating a Virtual Machine Analysis Profile"](#)).



Adding a new Action

Basic Information

Description	Assign VM Analysis Profile When Initiating a SmartState Analysis
Action Type	Assign Profile to Analysis Task ▾

Analysis Profiles

Analysis Profiles	VM Analysis Profile ▾
-------------------	-----------------------

1. Navigate to **Control** → **Explorer**.
2. Expand the **Actions** accordion and click  (**Configuration**), then  (**Add a new Action**).
3. Enter a **Description** for the new action. This will be the name given to your new action.
4. Select **Assign Profile to Analysis Task** from the **Action Type** list.
5. Select the newly-created virtual machine analysis profile from the **Analysis Profiles** list.
6. Click **Add**.





Note





You can only associate this action with an analysis start event.

The action is created and added to the **Available Actions** list. Associate this action with the **VM Analysis Start** event when you create a virtual machine control policy in the next procedure.

3. CREATING A VIRTUAL MACHINE CONTROL POLICY

You can create a control policy by combining an event, a condition, and an action. The procedure below describes how to create a virtual machine control policy to assign the newly-created action to the **VM Analysis Start** event. Optionally, you can use a scope expression that is tested immediately when the policy is triggered by an event. If the item is out of scope, then the policy will not continue on to the conditions, and the assigned action will not run.

1. Navigate to **Control** → **Explorer**.
2. Expand the **Policies** accordion, and click **Control Policies**.
3. Select **Vm Control Policies**.
4. Click  (**Configuration**), then  (**Add a New Vm Control Policy**).
5. Enter **Description**. This will be the name given to your VM control policy.
6. Uncheck **Active** if you do not want this policy processed even when assigned to a resource.
7. Optionally, enter **Scope** (you can also create a scope as part of a condition, or not use one at all). If the virtual machine is not included in the scope, the assigned action will not run.
8. Enter **Notes** if required.

9. Click **Add**. The policy is added and listed under **Vm Control Policies** in the **Policies** accordion.
10. Select the newly-added VM control policy. You can now associate events, conditions, and actions with the policy.
11. Click  (**Configuration**), then  (**Edit this Policy's Event assignments**).
12. Under **VM Operation**, select **VM Analysis Start**.
13. Click **Save**.
14. Click the **VM Analysis Start** event to configure actions.
15. Click  (**Configuration**), then  (**Edit Actions for this Policy Event**).
16. In **Order of Actions if ALL Conditions are True**, select the action created in [Section 2, "Creating an Action to Assign the Virtual Machine Analysis Profile to the Analysis Task"](#) from the **Available Actions** list. This action will take place if the resources meet the conditions of the policy.

Editing Event "VM Analysis Start"

Basic Information

Event Group	VM Operation
Attached to Policy	VM Control Policy

Order of Actions if ALL Conditions are True

<p>Available Actions:</p> <div style="border: 1px solid #ccc; padding: 5px;"> <ul style="list-style-type: none"> Cancel vCenter Task Check Host or VM Compliance Collect Running Processes on VM Guest OS Connect All CD-ROM Drives for Virtual Machine Connect All Floppy Drives for Virtual Machine Connect All Floppy and CD-ROM Drives for Virtual Machine Convert to Template Delete Most Recent Snapshot </div>	<p>▶</p> <p>◀◀</p> <p>◀</p>	<p>Selected Actions:</p> <div style="border: 1px solid #ccc; padding: 5px;"> <ul style="list-style-type: none"> (S) Assign VM Analysis Profile When Initiating a SmartState Analysis </div>	<p>▲</p> <p>▼</p> <p>S</p> <p>A</p>
---	-----------------------------	--	-------------------------------------


Order of Actions if ANY Conditions are False

<p>Available Actions:</p> <div style="border: 1px solid #ccc; padding: 5px;"> <ul style="list-style-type: none"> Assign VM Analysis Profile When Initiating a SmartState Analysis Cancel vCenter Task Check Host or VM Compliance Collect Running Processes on VM Guest OS Connect All CD-ROM Drives for Virtual Machine Connect All Floppy Drives for Virtual Machine Connect All Floppy and CD-ROM Drives for Virtual Machine Convert to Template </div>	<p>▶</p> <p>◀◀</p> <p>◀</p>	<p>Selected Actions:</p> <div style="border: 1px solid #ccc; padding: 5px; height: 80px;"> </div>	<p>▲</p> <p>▼</p> <p>S</p> <p>A</p>
--	-----------------------------	---	-------------------------------------






Note

Each selected action can be executed synchronously or asynchronously; a synchronous action will not start until the previous synchronous action is completed, while an asynchronous action allows the next action to start whether or not the first action has completed. Also, at least one Red Hat CloudForms server in the Red Hat CloudForms zone must have the notifier server role enabled for the trap to be sent.

17. Click () which will move the action to **Selected Actions**. The selected action is set to (S) Synchronous by default. From **Selected Actions**, select the action, then:
 - ✦ Click **A** (Set selected Actions to Asynchronous) to make it asynchronous.
 - ✦ Click **S** (Set selected Actions to Synchronous) to make it synchronous. If creating a synchronous action, use the up and down arrows to identify in what order you want the actions to run.
18. Click **Save**.





4. CREATING A POLICY PROFILE AND ASSIGNING THE VIRTUAL MACHINE CONTROL POLICY

Add a new policy profile and assign the virtual machine control policy (created in [Section 3, "Creating a Virtual Machine Control Policy"](#)) to it.

1. Navigate to **Control** → **Explorer**.
2. Expand the **Policy Profiles** accordion, click  (**Configuration**), then  (**Add a New Policy Profile**).
3. In the **Basic Information** area, enter a **Description** for the policy profile.
4. Under **Policy Selection**, select the virtual machine control policy created in [Section 3, "Creating a Virtual Machine Control Policy"](#) from the **Available Policies** list.
5. Click () to move the selected virtual machine control policy into this profile.
6. Click **Add**.

5. ASSIGNING THE POLICY PROFILE TO A VIRTUAL MACHINE

Assign the policy profile to a virtual machine and initiate SmartState analysis. Note that policy profiles can be specified at multiple levels. That is, if you assign this to a provider (Amazon EC2 or OpenStack for example), the policy profile will apply to all hosts or virtual machines for that provider.

1. Navigate to **Compute** → **Clouds** → **Instances** or **Compute** → **Infrastructure** → **Virtual Machines**, and select an available virtual machine.
2. Click  (**Policy**), then  (**Manage Policies**).
3. Under **Select Policy Profiles**, select the policy profile. It will turn blue to show the selection. Click the triangle next to the policy profile to see its member policies.
4. Click **Save**.
5. Select the virtual machine from the available virtual machines list; click  (**Configuration**), then  (**Perform SmartState Analysis**). A pop-up window appears to confirm the action.
6. Click **OK**. SmartState analysis is initiated for the selected virtual machine or instance from the Red Hat CloudForms database.

SmartState analysis will now report back findings specified by the custom virtual machine analysis profile.