



Red Hat Container Development Kit 3.6

Release Notes and Known Issues

Highlighted features and identified problems in Red Hat Container Development Kit
3.6

Red Hat Container Development Kit 3.6 Release Notes and Known Issues

Highlighted features and identified problems in Red Hat Container Development Kit 3.6

Robin Owen
kowen@redhat.com

Legal Notice

Copyright © 2018 Red Hat, Inc.

The text of and illustrations in this document are licensed by Red Hat under a Creative Commons Attribution–Share Alike 3.0 Unported license ("CC-BY-SA"). An explanation of CC-BY-SA is available at

<http://creativecommons.org/licenses/by-sa/3.0/>

. In accordance with CC-BY-SA, if you distribute this document or an adaptation of it, you must provide the URL for the original version.

Red Hat, as the licensor of this document, waives the right to enforce, and agrees not to assert, Section 4d of CC-BY-SA to the fullest extent permitted by applicable law.

Red Hat, Red Hat Enterprise Linux, the Shadowman logo, JBoss, OpenShift, Fedora, the Infinity logo, and RHCE are trademarks of Red Hat, Inc., registered in the United States and other countries.

Linux ® is the registered trademark of Linus Torvalds in the United States and other countries.

Java ® is a registered trademark of Oracle and/or its affiliates.

XFS ® is a trademark of Silicon Graphics International Corp. or its subsidiaries in the United States and/or other countries.

MySQL ® is a registered trademark of MySQL AB in the United States, the European Union and other countries.

Node.js ® is an official trademark of Joyent. Red Hat Software Collections is not formally related to or endorsed by the official Joyent Node.js open source or commercial project.

The OpenStack ® Word Mark and OpenStack logo are either registered trademarks/service marks or trademarks/service marks of the OpenStack Foundation, in the United States and other countries and are used with the OpenStack Foundation's permission. We are not affiliated with, endorsed or sponsored by the OpenStack Foundation, or the OpenStack community.

All other trademarks are the property of their respective owners.

Abstract

This document lists and briefly describes new and improved features of Red Hat Container Development Kit 3.6. It also contains information about potential problems you may encounter while using the software. Where possible, workarounds are described for identified issues.

Table of Contents

CHAPTER 1. INTRODUCING RED HAT CONTAINER DEVELOPMENT KIT	3
1.1. UNDERSTANDING CONTAINER DEVELOPMENT KIT DOCUMENTATION	3
CHAPTER 2. RELEASE NOTES	4
2.1. COMPONENT VERSIONS	4
2.2. VIRTUALBOX COMPATIBILITY	4
2.3. NEW FEATURES	4
2.3.1. Minishift	4
2.3.2. Technology Previews	5
2.3.3. Usability Improvements	5
CHAPTER 3. KNOWN ISSUES	6
3.1. ISSUES ON MACOS	6
3.1.1. OpenShift web console does not work with older versions of Safari	6
3.2. ISSUES ON MICROSOFT WINDOWS	6
3.2.1. Default Switch does not work as expected with static IP	6
3.2.2. Windows Command Prompt and PowerShell improperly parse JSON patches for the minishift openshift config set command	6
3.2.3. minishift openshift config set --patch may fail on some Windows 7 and 10 hosts	7
CHAPTER 4. ADDITIONAL RESOURCES	8

CHAPTER 1. INTRODUCING RED HAT CONTAINER DEVELOPMENT KIT

Red Hat Container Development Kit provides a platform for developing containerized applications. It is a set of tools that enables developers to quickly and easily set up an environment for developing and testing containerized applications on the Red Hat Enterprise Linux platform.

- Container Development Kit provides a personal Container Development Environment you can install on your own laptop, desktop, or server system. The Container Development Environment is provided in the form of a Red Hat Enterprise Linux virtual machine.
- Container Development Kit is available for the Microsoft Windows, macOS, and Linux operating systems, thus allowing developers to use their preferred platform while producing applications ready to be deployed in the Red Hat Enterprise Linux ecosystem.

Container Development Kit is a part of the [Red Hat Developers](#) program, which provides tools, resources, and support for developers who wish to utilize Red Hat solutions and products to create applications, both locally and in the cloud. For additional information and to register to become a part of the program, visit developers.redhat.com.

1.1. UNDERSTANDING CONTAINER DEVELOPMENT KIT DOCUMENTATION

- The [Red Hat Container Development Kit 3.6 Release Notes and Known Issues](#) contains information about the current release of the product as well as a list of known problems that users may encounter when using it.
- The [Container Development Kit Getting Started Guide](#) contains instructions on how to install and start using the Container Development Environment to develop Red Hat Enterprise Linux-based containers using tools and services such as **OpenShift Container Platform**, **Docker**, **Eclipse**, and various command line tools.
- Report issues with Red Hat Container Development Kit or request new features using the **CDK** project at <https://issues.jboss.org/projects/CDK>.
- Report issues with the Red Hat Container Development Kit 3.6 Release Notes and Known Issues and Container Development Kit Getting Started Guide using the **RHDEVDOCS** project at <https://issues.jboss.org/projects/RHDEVDOCS>.

CHAPTER 2. RELEASE NOTES

This section documents the most important features and bug fixes in the Red Hat Container Development Kit 3.6 product.

2.1. COMPONENT VERSIONS

Red Hat Container Development Kit 3.6 is shipped with the following versions of the main components:

Table 2.1. Container Development Kit, Component Versions

Component	Version
Docker	1.13.1
Docker API	1.26
Kubernetes	1.10.0
OpenShift Container Platform	3.10.45

2.2. VIRTUALBOX COMPATIBILITY

Red Hat Container Development Kit 3.6 has been tested with **VirtualBox 5.2.12** and higher, but is known to not work correctly with **VirtualBox 5.1.11** or older. Ensure that you have **VirtualBox 5.1.12** or higher if you intend to use **VirtualBox** as your virtualization provider. **VirtualBox 5.2.12** is recommended.

2.3. NEW FEATURES

This section highlights some of the new features offered by Red Hat Container Development Kit 3.6. The new version also contains a number of bug fixes.

Red Hat Container Development Kit 3.6 contains the Minishift tool, a Red Hat Enterprise Linux 7 ISO, and the **oc** (OpenShift client) binary for interacting with OpenShift Container Platform.

2.3.1. Minishift

Red Hat Container Development Kit 3.6 is based on Minishift, a command line tool to provision OpenShift locally for application developers. It supports all native hypervisors and some additional ones:

macOS

- [xhyve](#) (default)
- [VirtualBox](#)

Linux

- [KVM](#) (default)
- [VirtualBox](#)

Windows

- [Hyper-V](#) (default)
- [VirtualBox](#)

2.3.2. Technology Previews

Support for these features falls under the [Technology Preview Features Support Scope](#).

- Container Development Kit now includes the ability to run a local proxy server. The local proxy server assists with the use of CDK in a proxy environment. For more information, see [Local Proxy Server](#).

2.3.3. Usability Improvements

- Container Development Kit now saves non-default flags given to the **minishift start** command to the persistent configuration. You are not required to explicitly save these settings. To disable this feature, run the following command:

```
$ minishift config set save-start-flags false
```

- Container Development Kit now allows you to start CDK with the latest OpenShift Container Platform version using the following command:

```
$ minishift start --ocp-tag latest
```

- The **generic** driver for Container Development Kit has been improved. CDK now performs all of the required steps to allow OpenShift to start on the remote RHEL 7 machine.
- Container Development Kit now includes a way to express dependencies between add-ons. For more information, see [Defining Add-on Dependencies](#).

CHAPTER 3. KNOWN ISSUES

This section describes issues that users of Red Hat Container Development Kit 3.6 may encounter, as well as possible workarounds for these issues.

3.1. ISSUES ON MACOS

This section describes CDK issues that affect users on a macOS host.

3.1.1. OpenShift web console does not work with older versions of Safari

minishift console does not work on older versions of the Safari web browser such as version 10.1.2 (12603.3.8). Attempting to access the web console results in the following error:

```
Error unable to load details about the server
```

Retry after updating Safari to the latest version or use the Firefox or Chrome web browsers for this. Safari version 11.0.3 (13604.5.6) has been tested and works with the OpenShift web console. You can use **minishift console --url** to get the web console URL.

3.2. ISSUES ON MICROSOFT WINDOWS

This section describes CDK issues that affect users on a Microsoft Windows host.

3.2.1. Default Switch does not work as expected with static IP

The experimental [static IP](#) feature is not possible with the Default Switch provided by Windows. The **minishift** virtual machine will receive an IP address, but network traffic will not be able to pass through it.

See [Assign IP Address to Hyper-V](#) for more information about how to assign a static IP address to the **minishift** VM on Windows.

3.2.2. Windows Command Prompt and PowerShell improperly parse JSON patches for the **minishift openshift config set** command

Windows Command Prompt and PowerShell have problems with parsing JSON into the **minishift openshift config set** command. Special attention is required when using this command on Windows.

The workaround for Windows Command Prompt environments is to escape the quotes so that the JSON content is correctly parsed:

```
C:\Users\CDK> minishift.exe openshift config set --patch "{\n\"routingConfig\": {\n\"subdomain\": \"192.168.99.101.nip.io\"}}\""
```

The workaround for Windows PowerShell environments is to use a variable to store the JSON content:

```
PS C:\Users\CDK> $json='{\"routingConfig\": {\n\"subdomain\": \"192.168.99.101.nip.io\"}}'\nPS C:\Users\CDK> echo $json\n{\"routingConfig\": {\n\"subdomain\": \"192.168.99.101.nip.io\"}}
```

```
PS C:\Users\CDK> minishift.exe openshift config set --patch $json
Patching OpenShift configuration
/var/lib/origin/openshift.local.config/master/master-config.yaml with
{"routingConfig": {"subdomain": "192.168.99.101.nip.io"}}
```

3.2.3. minishift openshift config set --patch may fail on some Windows 7 and 10 hosts

The reason for this failure is currently unknown.

Workaround: Configure the OpenShift cluster from inside of the provisioned VM using **minishift ssh**:

```
C:\Users\CDK> minishift.exe ssh
[docker@minishift ~]$ docker exec -t origin /usr/bin/openshift ex config
patch /var/lib/origin/openshift.local.config/master/master-config.yaml --
patch='<json-to-be-applied-to-the-cluster>'
```

CHAPTER 4. ADDITIONAL RESOURCES

- See the [Container Development Kit Getting Started Guide](#) for an overview of Container Development Kit features and an introduction to the use of the **Docker** service and **OpenShift Container Platform**.
- Report issues with Red Hat Container Development Kit or request new features using the **CDK** project at <https://issues.jboss.org/projects/CDK>.