



Red Hat Developer Toolset 8.0 Beta

8.0 Release Notes

Release Notes for Red Hat Developer Toolset 8.0 Beta

Red Hat Developer Toolset 8.0 Beta 8.0 Release Notes

Release Notes for Red Hat Developer Toolset 8.0 Beta

Lenka Špačková
Red Hat Customer Content Services
lspackova@redhat.com

Jaromír Hradílek
Red Hat Customer Content Services
jhradilek@redhat.com

Eliška Šlobodová
Red Hat Customer Content Services

Legal Notice

Copyright © 2018 Red Hat, Inc.

This document is licensed by Red Hat under the [Creative Commons Attribution-ShareAlike 3.0 Unported License](#). If you distribute this document, or a modified version of it, you must provide attribution to Red Hat, Inc. and provide a link to the original. If the document is modified, all Red Hat trademarks must be removed.

Red Hat, as the licensor of this document, waives the right to enforce, and agrees not to assert, Section 4d of CC-BY-SA to the fullest extent permitted by applicable law.

Red Hat, Red Hat Enterprise Linux, the Shadowman logo, JBoss, OpenShift, Fedora, the Infinity logo, and RHCE are trademarks of Red Hat, Inc., registered in the United States and other countries.

Linux ® is the registered trademark of Linus Torvalds in the United States and other countries.

Java ® is a registered trademark of Oracle and/or its affiliates.

XFS ® is a trademark of Silicon Graphics International Corp. or its subsidiaries in the United States and/or other countries.

MySQL ® is a registered trademark of MySQL AB in the United States, the European Union and other countries.

Node.js ® is an official trademark of Joyent. Red Hat Software Collections is not formally related to or endorsed by the official Joyent Node.js open source or commercial project.

The OpenStack ® Word Mark and OpenStack logo are either registered trademarks/service marks or trademarks/service marks of the OpenStack Foundation, in the United States and other countries and are used with the OpenStack Foundation's permission. We are not affiliated with, endorsed or sponsored by the OpenStack Foundation, or the OpenStack community.

All other trademarks are the property of their respective owners.

Abstract

Red Hat Developer Toolset is a Software Collection from the Red Hat Software Collections offering. It is designed for developers working on the Red Hat Enterprise Linux platform. Using a framework called Software Collections, an additional set of tools is installed into the `/opt/` directory, as recommended by the UNIX Filesystem Hierarchy Standard. These tools are enabled by the user on demand using the supplied `scl` utility. Red Hat Developer Toolset 8.0 Beta provides current versions of the GNU Compiler Collection, GNU Debugger, and other development, debugging, and performance monitoring tools. These do not replace the Red Hat Enterprise Linux system versions of these tools, nor will they be used in preference to those system versions unless explicitly invoked using the `scl` utility. These Release Notes contain important information available at the time of release of Red Hat Developer Toolset 8.0 Beta. Known problems, resources, and other issues are discussed here. Read this document before beginning to use Red Hat Developer Toolset 8.0 Beta. For information on other components of Red Hat Software Collections, see the Red Hat Software Collections Release Notes. For details about length of support for individual components, refer to the

Red Hat Software Collections Product Life Cycle document. This version of the document is provided only as a preview. It is under development and is subject to substantial change. Consider the included information incomplete and use it with caution.

Table of Contents

CHAPTER 1. SYSTEM REQUIREMENTS	3
1.1. INSTALLATION PREREQUISITES	3
1.2. INSTALLATION AND UPGRADING	4
CHAPTER 2. RED HAT DEVELOPER TOOLSET 8.0 BETA RELEASE	5
2.1. CHANGES IN RED HAT DEVELOPER TOOLSET 8.0 BETA	5
2.1.1. Upgraded Components	5
2.1.2. Container Images	5
2.2. FEATURES	6
2.2.1. List of Components	6
2.2.2. Main Features	7
2.2.3. Compiler Toolsets in Red Hat Developer Tools	7
2.3. KNOWN ISSUES	7
Other Notes	9
CHAPTER 3. ADDITIONAL RESOURCES	13
3.1. RED HAT PRODUCT DOCUMENTATION	13
3.2. RED HAT DEVELOPERS	13
APPENDIX A. REVISION HISTORY	15

CHAPTER 1. SYSTEM REQUIREMENTS

This chapter specifies hardware requirements and contains information related to the installation of Red Hat Developer Toolset 8.0 Beta.

1.1. INSTALLATION PREREQUISITES

Red Hat Developer Toolset 8.0 Beta contains packages for both Red Hat Enterprise Linux 6 and Red Hat Enterprise Linux 7 running on AMD64 and Intel 64 architectures. Generation and manipulation of 32-bit binaries is also supported.

Red Hat Developer Toolset 8.0 Beta supports the following architectures on Red Hat Enterprise Linux 7:

- The 64-bit ARM architecture (AArch64)
- IBM POWER, big endian
- IBM POWER, little endian
- IBM Z

The correct packages must be installed according to the host operating system in use. Red Hat Enterprise Linux 6 RPM packages can be used only on supported versions of Red Hat Enterprise Linux 6, and Red Hat Enterprise Linux 7 RPM packages can be used only on supported versions of Red Hat Enterprise Linux 7.

Before installing Red Hat Developer Toolset 8.0 Beta, it is recommended to apply all available Red Hat Enterprise Linux errata updates. This will enable all Red Hat Developer Toolset features and apply fixes that can otherwise impact the tools or built code.

Red Hat Developer Toolset 8.0 Beta requires systems to be subscribed to the **Optional** channel in order to access all the necessary dependent packages required by the Red Hat Developer Toolset toolchain. Packages from the **Optional** channel are listed in the [Red Hat Software Collections 3.2 Release Notes](#).

If you use Red Hat Subscription Manager:

- On Red Hat Enterprise Linux 6, select **System** → **Administration** → **Add/Remove Software** from the panel and navigate to **System** → **Software Sources**.
- On Red Hat Enterprise Linux 7, you can add these repositories by navigating to **Applications** → **System Tools** → **Red Hat Subscription Manager**.

Then enable the **Optional** channel for your system. For detailed information, see <https://access.redhat.com/solutions/392003>.

Users of Red Hat Satellite can enable the **Optional** channel by following the instructions at <https://access.redhat.com/solutions/70019>.

Since Red Hat Developer Toolset 4.1, the content is available also in the ISO format at <https://access.redhat.com/downloads>, specifically for [Server](#) and [Workstation](#).



NOTE

Packages that require the **Optional** channel cannot be installed from the ISO image. A list of packages that require enabling of the **Optional** channel is provided in the [Red Hat Software Collections Release Notes](#).

Beta content is unavailable in the ISO format.

1.2. INSTALLATION AND UPGRADING

Use of Red Hat Developer Toolset 8.0 Beta requires the removal of any earlier pre-release versions. If you have installed any previous version of Red Hat Developer Toolset, uninstall it from your system as described in the [Uninstalling Red Hat Developer Toolset](#) section of the *Red Hat Developer Toolset User Guide*.

Note that installing Red Hat Developer Toolset 8.x in parallel with Red Hat Developer Toolset 7.x is supported.

For detailed information on installation of Red Hat Developer Toolset 8.0 Beta see the [Installing Red Hat Developer Toolset](#) chapter of the *Red Hat Developer Toolset User Guide*.

The in-place upgrade from Red Hat Enterprise Linux 6 to Red Hat Enterprise Linux 7 is not supported by Red Hat Developer Toolset. As a consequence, the installed components might not work correctly after the upgrade. If you want to upgrade from Red Hat Enterprise Linux 6 to Red Hat Enterprise Linux 7, it is strongly recommended to remove all Red Hat Developer Toolset packages, perform the in-place upgrade, update the Red Hat Developer Toolset repository, and install the Red Hat Developer Toolset packages again. It is advisable to back up all data before upgrading.

CHAPTER 2. RED HAT DEVELOPER TOOLSET 8.0 BETA RELEASE

This chapter serves as an overview of Red Hat Developer Toolset 8.0 Beta. It sums up its main features and changes, and provides a list of known issues.

2.1. CHANGES IN RED HAT DEVELOPER TOOLSET 8.0 BETA

2.1.1. Upgraded Components

All components in Red Hat Developer Toolset 8.0 Beta are distributed as new packages with the **devtoolset-8-** prefix.

The following components have been upgraded in Red Hat Developer Toolset 8.0 Beta compared to the previous release of Red Hat Developer Toolset:

- **GCC** to version 8.2.1
- **GDB** to version 8.2
- **Valgrind** to version 3.14.0
- **elfutils** to version 0.174
- **binutils** to version 2.30
- **strace** to version 4.24
- **OProfile** to version 1.3.0
- **SystemTap** to version 3.3

In addition, bug fix updates are available for the following components:

- **dwz**
- **ltrace**
- **Dyninst**

For detailed information on changes in Red Hat Developer Toolset 8.0 Beta, see [Red Hat Developer Toolset User Guide](#).

2.1.2. Container Images

Red Hat Developer Toolset 8 includes two pre-built container images:

- The updated **rhsc1-beta/devtoolset-8-toolchain-rhel7** image, which contains the following Red Hat Developer Toolset components:
 - **devtoolset-8-gcc**
 - **devtoolset-8-gcc-c++**
 - **devtoolset-8-gcc-fortran**

- devtoolset-8-gdb

Additionally, the **devtoolset-8-binutils** component is pulled by **devtoolset-8-gcc** in the **rhsc1/devtoolset-8-toolchain-rhel7** image.

- The **rhsc1-beta/devtoolset-8-perftools-rhel7** image, which contains the following components:
 - devtoolset-8-dwz
 - devtoolset-8-dyninst
 - devtoolset-8-elfutils
 - devtoolset-8-ltrace
 - devtoolset-8-make
 - devtoolset-8-memstomp
 - devtoolset-8-oprofile
 - devtoolset-8-strace
 - devtoolset-8-systemtap
 - devtoolset-8-valgrind

The container images are available from the Red Hat Container Registry. For details on how to obtain the images and how to run Red Hat Developer Toolset components using these images, see [Using Red Hat Software Collections Container Images](#).

2.2. FEATURES

2.2.1. List of Components

Red Hat Developer Toolset 8.0 Beta provides the following components:

Development Tools

- GNU Compiler Collection (GCC)
- binutils
- elfutils
- dwz
- make

Debugging Tools

- GNU Debugger (GDB)
- strace

- ltrace
- memstomp

Performance Monitoring Tools

- SystemTap
- Valgrind
- OProfile
- Dyninst

For details, see the [Red Hat Developer Toolset Components](#) table in the *Red Hat Developer Toolset User Guide*.

2.2.2. Main Features

Red Hat Developer Toolset 8.0 Beta introduces the following changes:

- The Red Hat Developer Toolset version of the **GNU Compiler Collection (GCC)** has been upgraded to version 8.2.1 with numerous new features and bug fixes.
- The Red Hat Developer Toolset version of the **GNU Debugger (GDB)** has been upgraded to version 8.2, which provides a number of bug fixes and enhancements.

For a full list of changes and features introduced in this release, see [Red Hat Developer Toolset User Guide](#).

2.2.3. Compiler Toolsets in Red Hat Developer Tools

The following compiler toolsets are available with Red Hat Developer Tools, including the corresponding container images:

- Clang and LLVM Toolset
- Rust Toolset
- Go Toolset

In addition, **Eclipse** is available as a part of the Red Hat Developer Tools offering.

See [Red Hat Developer Tools documentation](#) for details regarding usage.

2.3. KNOWN ISSUES

gcc component, BZ#[1570853](#)

In Red Hat Developer Toolset, libraries are linked via linker scripts which might specify some symbols through static archives. This is required to ensure compatibility with multiple versions of Red Hat Enterprise Linux. However, the linker scripts use names of the respective shared object files. As a consequence, the linker uses different symbol handling rules than expected, and does not recognize symbols required by object files when the option adding the library is specified before options specifying the object files, such as:

```
gcc -lsomelib objfile.o
```

Such use of a library from Red Hat Developer Toolset results in linker error messages **undefined reference to symbol**. To enable successful symbol resolution and linking, follow the standard linking practice and specify the option adding the library after the options specifying the object files:

```
gcc objfile.o -lsomelib
```

Note that this recommendation applies when using the version of **GCC** available as a part of Red Hat Enterprise Linux, too.

gdb component, BZ#1347993

On the 64-bit ARM architecture, the **GDB** debugger provides only limited support for unaligned hardware watchpoints used by the **watch**, **rwatch**, and **awatch** **GDB** commands. As a consequence, **GDB** running on such systems fails to register some watchpoint hits and subsequently does not stop the debugged program.

To work around this problem, set the watchpoint start address to a manually corrected memory address aligned down to a multiple of 8 bytes. An unaligned ending address does not have this negative effect. Note that with this workaround, **GDB** registers further hits for the watchpoint in the additional part of memory, which is not interesting for the user.

dyninst component, BZ#1498389

When the user installs only the **devtoolset-8-dyninst** or **devtoolset-8-systemtap** packages, the **devtoolset-8-dyninst-devel** package is not pulled. As a consequence, **Dyninst** fails to work correctly. The same problem applies also to **SystemTap** with the **Dyninst** back end when the **stap --dyninst** command is used. To work around this problem, manually install the **devtoolset-8-dyninst-devel** package, enable the **devtoolset-8 Software Collection**, and then run the **ldconfig** command.

gcc component, BZ#1433946

GCC in Red Hat Developer Toolset 3.x contained the **libasan** package, which might have conflicted with the system version of **libasan**. As a consequence, depending on which **libasan** was present in the system, the **-fsanitize=address** tool worked only either with the system **GCC** or with the Red Hat Developer Toolset version of **GCC**, but not with both at the same time. To prevent the described conflict, in Red Hat Developer Toolset 4.x and later versions, the package was renamed to **libasanN**, where **N** is a number. However, if the Red Hat Software Collections repository is enabled, the problem can occur after the system update because the system version of **libasan** is available in an earlier version than the Red Hat Developer Toolset 3.x version, which is still available in the repository. To work around this problem, exclude this package while updating:

```
~]$ yum update --exclude=libasan
```

oprofile component

OProfile 1.3.0 and **OProfile 1.2.0** shipped in Red Hat Developer Toolset works on all supported architectures, with the exception of IBM Z, where only the **ocount** tool works on the following models: z196, zEC12, and z13. **operf** and the other tools, such as **oparchive** or **opannotate**, do not work on IBM Z. For profiling purposes, users are recommended to use the Red Hat Enterprise Linux 7 system **OProfile 0.9.9** version, which supports **opcontrol** with **TIMER** software interrupts.

Note that for correct reporting of data collected by **OProfile 0.9.9**, the corresponding **opreport** utility is necessary. Thus **opcontrol**-based profiling should be performed with Red Hat Developer Toolset

disabled because the reporting tools from Red Hat Developer Toolset cannot process data collected within **opcontrol** legacy mode correctly.

valgrind component, BZ#869184

The default **Valgrind gdbserver** support (`--vgdb=yes`) can cause certain register and flags values to be not always up-to-date due to optimizations done by the **Valgrind** core. The **GDB** utility is therefore unable to show certain parameters or variables of programs running under **Valgrind**. To work around this problem, use the `--vgdb=full` parameter. Note that programs might run slower under **Valgrind** when this parameter is used.

multiple components

The `devtoolset-version-package_name-debuginfo` packages can conflict with the corresponding packages from the base Red Hat Enterprise Linux system or from other versions of Red Hat Developer Toolset. This namely applies to `devtoolset-version-gcc-debuginfo`, `devtoolset-version-ltrace-debuginfo`, `devtoolset-version-valgrind-debuginfo`, and might apply to other debuginfo packages, too. A similar conflict can also occur in a multilib environment, where 64-bit debuginfo packages conflict with 32-bit debuginfo packages.

For example, on Red Hat Enterprise Linux 7, `devtoolset-7-gcc-debuginfo` conflicts with three packages: `gcc-base-debuginfo`, `gcc-debuginfo`, and `gcc-libraries-debuginfo`. On Red Hat Enterprise Linux 6, `devtoolset-7-gcc-debuginfo` conflicts with one package: `gcc-libraries-debuginfo`. As a consequence, if conflicting debuginfo packages are installed, attempts to install Red Hat Developer Toolset can fail with a transaction check error message similar to the following examples:

```
file /usr/lib/debug/usr/lib64/libitm.so.1.0.0.debug from install of gcc-
base-debuginfo-4.8.5-16.el7.x86_64 conflicts with file from package
devtoolset-7-gcc-debuginfo-7.2.1-1.el7.x86_64
```

```
file /usr/lib/debug/usr/lib64/libtsan.so.0.0.0.debug from install of
gcc-debuginfo-4.8.5-16.el7.x86_64 conflicts with file from package
devtoolset-7-gcc-debuginfo-7.2.1-1.el7.x86_64
```

```
file /usr/lib/debug/usr/lib64/libitm.so.1.0.0.debug from install of
devtoolset-7-gcc-debuginfo-7.2.1-1.el6.x86_64 conflicts with file from
package gcc-libraries-debuginfo-7.1.1-2.3.1.el6_9.x86_64
```

To work around the problem, manually uninstall the conflicting debuginfo packages prior to installing Red Hat Developer Toolset 8.0 Beta. It is advisable to install only the relevant debuginfo packages when necessary and expect such problems to happen.

Other Notes

- Red Hat Developer Toolset primarily aims to provide a compiler for development of user applications for deployment on multiple versions of Red Hat Enterprise Linux. Operating system components, kernel modules and device drivers generally correspond to a specific version of Red Hat Enterprise Linux, for which the supplied base OS compiler is recommended.
- Red Hat Developer Toolset 8.0 Beta supports only C, C++ and Fortran development. For other languages, invoke the system version of **GCC** available on Red Hat Enterprise Linux.
- Building an application with Red Hat Developer Toolset 8.0 Beta on Red Hat Enterprise Linux (for example, Red Hat Enterprise Linux 7) and then executing that application on an earlier minor version (such as Red Hat Enterprise Linux 6.7.z) may result in runtime errors due to differences

in non-toolchain components between Red Hat Enterprise Linux releases. Users are advised to check compatibility carefully. Red Hat supports only execution of an application built with Red Hat Developer Toolset on the same, or a later, supported release of Red Hat Enterprise Linux than the version used to build that application.

- **Valgrind** must be rebuilt without Red Hat Developer Toolset's **GCC** installed, or it will be used in preference to Red Hat Enterprise Linux system **GCC**. The binary files shipped by Red Hat are build using the system **GCC**. For any testing, Red Hat Developer Toolset's **GDB** should be used.
- All code in the non-shared library **libstdc++_nonshared.a** in Red Hat Developer Toolset 8.0 Beta is licensed under the GNU General Public License v3 with additional permissions granted under Section 7, described in the GCC Runtime Library Exception version 3.1, as published by the Free Software Foundation.
- The compiler included in Red Hat Developer Toolset emits newer DWARF debugging records than previous compilers available on Red Hat Enterprise Linux. These new debugging records improve the debugging experience in a variety of ways, particularly for C++ and optimized code. However, certain tools are not yet capable of handling the newer DWARF debug records. To generate the older style debugging records, use the options **-gdwarf-2 -gstrict-dwarf** or **-gdwarf-3 -gstrict-dwarf**.
- Some newer library features are statically linked into applications built with Red Hat Developer Toolset to support execution on multiple versions of Red Hat Enterprise Linux. This adds a small additional security risk because regular Red Hat Enterprise Linux errata would not change this code. If the need for developers to rebuild their applications due to such an issue arises, Red Hat will signal this in a security erratum. Developers are strongly advised not to statically link their entire application for the same reasons.
- Note that error messages related to a missing **libitm** library when using the **-fgnu-tm** option require the **libitm** package to be installed. You can install the package with the following command:

```
yum install libitm
```

- To use the **ccache** utility with **GCC** included in Red Hat Developer Toolset, set your environment correctly. For example:

```
~]$ scl enable devtoolset-8 '/usr/lib64/ccache/gcc -c foo.c'
```

Alternatively, you can create a shell with the Red Hat Developer Toolset version of **GCC** as the default compiler:

```
~]$ scl enable devtoolset-8 'bash'
```

After you have created the shell, run the following two commands:

```
~]$ export PATH=/usr/lib64/ccache${PATH:+:${PATH}}
```

```
~]$ gcc -c foo.c
```

- Because the **elfutils** libraries contained in Red Hat Developer Toolset 8.0 Beta are linked to a client application statically, caution is advised when passing handles to **libelf**, **libdw**, and **libasm** data structures to external code and when passing handles received from external code to **libelf**, **libdw**, and **libasm**.

Be especially careful when an external library, which is linked dynamically against the system version of **elfutils**, is passed a pointer to a structure that comes from the Red Hat Developer Toolset 8.0 Beta version of **elfutils** (or vice versa).

Generally, data structures used in the Red Hat Developer Toolset 8.0 Beta version of **elfutils** are not compatible with the Red Hat Enterprise Linux system versions, and structures coming from one should never be touched by the other.

In applications that use the Red Hat Developer Toolset 8.0 Beta libraries, all code that was linked against the system version of the libraries should be recompiled against the libraries included in Red Hat Developer Toolset 8.0 Beta.

- The **elfutils EBL** library, which is used internally by **libdw**, was amended not to open back ends dynamically. Instead, a selection of back ends is compiled in the library itself: the 32-bit AMD and Intel architecture, AMD64 and Intel 64 systems, Intel Itanium, IBM Z, 32-bit IBM Power Systems, 64-bit IBM Power Systems, IBM POWER, big endian, and the 64-bit ARM architecture. Some functionality may not be available if the client wishes to work with ELF files from architectures other than those mentioned above.
- Some packages managed by the **scl** utility include privileged services that require **sudo**. The system **sudo** clears environment variables and so Red Hat Developer Toolset includes its own **sudo** shell script, wrapping **scl enable**. This script does not currently parse or pass normal **sudo** options, only **sudo COMMAND ARGS . . .**. In order to use the system version of **sudo** from within a Red Hat Developer Toolset-enabled shell, use the **/usr/bin/sudo** binary.
- Intel have issued erratum [HSW136](#) concerning TSX (Transactional Synchronization Extensions) instructions. Under certain circumstances, software using the Intel TSX instructions may result in unpredictable behavior. TSX instructions may be executed by applications built with Red Hat Developer Toolset **GCC** under certain conditions. These include use of **GCC**'s experimental Transactional Memory support (using the **-fgnu-tm** option) when executed on hardware with TSX instructions enabled. The users of Red Hat Developer Toolset are advised to exercise further caution when experimenting with Transaction Memory at this time, or to disable TSX instructions by applying an appropriate hardware or firmware update.
- To use the Memory Protection Extensions (MPX) feature in **GCC**, the Red Hat Developer Toolset version of the **libmpx** library is required, otherwise the application might not link properly.
- The two **binutils** linkers, **gold** and **ld**, have different ways of handling hidden symbols, which leads to incompatibilities in their behavior. Previously, the **gold** and **ld** linkers had inconsistent and incorrect behavior with regard to shared libraries and hidden symbols. There were two scenarios:
 - If a shared library referenced a symbol that existed elsewhere in both hidden and non-hidden versions, the **gold** linker produced a bogus warning message about the hidden version.
 - If a shared library referenced a symbol that existed elsewhere only as a hidden symbol, the **gold** linker created an executable, even though it could not work.

The **gold** linker has been updated so that it no longer issues bogus warning messages about hidden symbols that also exist in a non-hidden version. The second scenario cannot be solved in the linker. It is up to the programmer to ensure that a non-hidden version of the symbol is available when the application is run.

As a result, the two linkers' behavior is closer, but they still differ in case of a reference to a hidden symbol that cannot be found elsewhere in a non-hidden version. Unfortunately, there is not a single correct behavior for this situation, so the linkers are allowed to differ.

- The `valgrind-openmpi` subpackage is no longer provided with **Valgrind** in Red Hat Developer Toolset. The `devtoolset-<version>-valgrind-openmpi` subpackages previously caused incompatibility issues with various Red Hat Enterprise Linux minor releases and problems with rebuilding. Users are recommended to use the latest Red Hat Enterprise Linux system version of the `valgrind` and `valgrind-openmpi` packages if they need to run **Valgrind** against their programs that are built against the `openmpi-devel` libraries.

CHAPTER 3. ADDITIONAL RESOURCES

For more information about Red Hat Developer Toolset 8.0 Beta and Red Hat Enterprise Linux, see the resources listed below.

3.1. RED HAT PRODUCT DOCUMENTATION

The **Red Hat Documentation** portal located at <https://access.redhat.com/documentation/> serves as a central source of all product documentation. It is translated in 22 languages and for each product, it provides different kinds of books from release and technical notes to installation, user, and reference guides in HTML, PDF, and EPUB formats.

The following is a brief list of documents that are directly or indirectly relevant to this book:

- [Red Hat Developer Toolset 8.0 Beta User Guide](#) — The *User Guide* for Red Hat Developer Toolset contains more information about installing and using this content set.
- [Red Hat Software Collections 3.2 Beta Packaging Guide](#) — The *Packaging Guide* for Red Hat Software Collections explains the concept of Software Collections, documents the **sc1** utility, and provides a detailed explanation of how to create a custom Software Collection or extend an existing one.
- [Red Hat Software Collections 3.2 Beta Release Notes](#) — The *Release Notes* for Red Hat Software Collections document known problems, possible issues, and other important information available at the time of release of the content set. They also contain useful information on installing, rebuilding, migrating etc.
- [Using Red Hat Software Collections Container Images](#) — This book provides information on how to use container images based on Red Hat Software Collections. The available container images include applications, daemons, databases, as well as the Red Hat Developer Toolset container images. The images can be run on Red Hat Enterprise Linux 7 Server and Red Hat Enterprise Linux Atomic Host.
- [Red Hat Enterprise Linux 6 Developer Guide](#) — The *Developer Guide* for Red Hat Enterprise Linux 6 provides detailed information on compiling and building, debugging, and profiling.
- [Red Hat Enterprise Linux 7 Developer Guide](#) — The *Developer Guide* for Red Hat Enterprise Linux 7 provides an introduction to application development tools in Red Hat Enterprise Linux 7.

3.2. RED HAT DEVELOPERS

- [Red Hat Developer Program](#) — The *Red Hat Developers* community portal.
- [Overview of Red Hat Developer Toolset on Red Hat Developers](#) — The *Red Hat Developers* portal provides a number of tutorials to get you started with developing code using different development technologies. This includes the Node.js, Perl, PHP, Python, and Ruby Software Collections.
- [Red Hat Enterprise Linux Developer Program](#) — The *Red Hat Enterprise Linux Developer Program* delivers industry-leading developer tools, instructional resources, and an ecosystem of experts to help programmers maximize productivity in building Linux applications.
- [Red Hat Developer Blog](#) — The *Red Hat Developer Blog* contains up-to-date information, best

practices, opinion, product and program announcements as well as pointers to sample code and other resources for those who are designing and developing applications based on Red Hat technologies.

APPENDIX A. REVISION HISTORY

Revision 8.0-0

Tue Oct 23 2018

Lenka Špačková

Release of Red Hat Developer Toolset 8.0 Beta Release Notes.