



# Red Hat Hybrid Cloud Console 2021

## Configuring sources for Red Hat services

How to link your Red Hat account to a public cloud



# Red Hat Hybrid Cloud Console 2021 Configuring sources for Red Hat services

---

How to link your Red Hat account to a public cloud

Red Hat Subscription Management Documentation Team  
rhsm-docs@redhat.com

## Legal Notice

Copyright © 2021 Red Hat, Inc.

The text of and illustrations in this document are licensed by Red Hat under a Creative Commons Attribution–Share Alike 3.0 Unported license ("CC-BY-SA"). An explanation of CC-BY-SA is available at

<http://creativecommons.org/licenses/by-sa/3.0/>

. In accordance with CC-BY-SA, if you distribute this document or an adaptation of it, you must provide the URL for the original version.

Red Hat, as the licensor of this document, waives the right to enforce, and agrees not to assert, Section 4d of CC-BY-SA to the fullest extent permitted by applicable law.

Red Hat, Red Hat Enterprise Linux, the Shadowman logo, the Red Hat logo, JBoss, OpenShift, Fedora, the Infinity logo, and RHCE are trademarks of Red Hat, Inc., registered in the United States and other countries.

Linux<sup>®</sup> is the registered trademark of Linus Torvalds in the United States and other countries.

Java<sup>®</sup> is a registered trademark of Oracle and/or its affiliates.

XFS<sup>®</sup> is a trademark of Silicon Graphics International Corp. or its subsidiaries in the United States and/or other countries.

MySQL<sup>®</sup> is a registered trademark of MySQL AB in the United States, the European Union and other countries.

Node.js<sup>®</sup> is an official trademark of Joyent. Red Hat is not formally related to or endorsed by the official Joyent Node.js open source or commercial project.

The OpenStack<sup>®</sup> Word Mark and OpenStack logo are either registered trademarks/service marks or trademarks/service marks of the OpenStack Foundation, in the United States and other countries and are used with the OpenStack Foundation's permission. We are not affiliated with, endorsed or sponsored by the OpenStack Foundation, or the OpenStack community.

All other trademarks are the property of their respective owners.

## Abstract

Sources provide a way for applications to collect data outside of the Red Hat Hybrid Cloud Console through either a direct connection to the source or indirectly.

---

## Table of Contents

<b>MAKING OPEN SOURCE MORE INCLUSIVE</b> .....	<b>3</b>
<b>PROVIDING FEEDBACK ON RED HAT HYBRID CLOUD CONSOLE DOCUMENTATION</b> .....	<b>4</b>
<b>CHAPTER 1. CONFIGURING SOURCES FOR RED HAT SERVICES</b> .....	<b>5</b>
1.1. ABOUT SOURCES	5
1.2. ADDING CLOUD SOURCES	5
1.3. ADDING RED HAT SOURCES	8
1.4. SOURCES REFERENCE MATERIAL	8



## MAKING OPEN SOURCE MORE INCLUSIVE

Red Hat is committed to replacing problematic language in our code, documentation, and web properties. We are beginning with these four terms: master, slave, blacklist, and whitelist. Because of the enormity of this endeavor, these changes will be implemented gradually over several upcoming releases. For more details, see [our CTO Chris Wright's message](#).

## PROVIDING FEEDBACK ON RED HAT HYBRID CLOUD CONSOLE DOCUMENTATION

We appreciate your input on our documentation. Please let us know how we could make it better. To do so, create a Bugzilla ticket:

1. Go to the [Bugzilla](#) website.
2. As the Component, use **Documentation**.
3. Fill in the **Description** field with your suggestion for improvement. Include a link to the relevant part(s) of documentation.
4. Click **Submit Bug**.



# CHAPTER 1. CONFIGURING SOURCES FOR RED HAT SERVICES

A data source is a service, application, or provider that supplies data to a [Red Hat Hybrid Cloud Console](#) application or service. Sources comprise cloud sources and Red Hat sources.

## 1.1. ABOUT SOURCES

Sources are how the services and applications on the [Red Hat Hybrid Cloud Console](#) connect with public cloud providers and other services or tools to collect information for the service or application. You add and manage sources in the **Sources** application located within the **Settings** bundle. You can access **Settings** by clicking the gear icon in the masthead on the [Red Hat Hybrid Cloud Console](#).

The **Sources** menu uses a wizard to help you add cloud sources and Red Hat sources. For cloud sources, you can associate the provider with Red Hat applications, such as Cost Management and the RHEL management bundle. For Red Hat sources, you can add Red Hat OpenShift Container Platform. Adding applications is optional for cloud sources but is required for Red Hat sources.

## 1.2. ADDING CLOUD SOURCES

The **Add a cloud source** wizard steps you through creating a source. You can add Amazon Web Services (AWS), Google Cloud, and Microsoft Azure. The wizard provides detailed information for each public cloud provider.

### Amazon Web Services

The workflow for adding AWS as a cloud source includes the following high-level steps:

1. Selecting the source type
2. Naming the source
3. Selecting the configuration
4. Selecting applications
5. Configuring cost and usage reporting (for cost management)
6. Identifying tags, aliases, and organizational units (for cost management)
7. Enabling account access
8. Reviewing details
9. Adding the source

You have two choices for the configuration mode: \* **Account authorization** (recommended) \* **Manual configuration**

If you select **Account authorization**, you provide your AWS account credentials (Access key ID and Secret key ID) and Red Hat configures and manages your source for you. This option automatically selects the **Cost Management** and the **RHEL management** bundle applications. You can deselect these applications.

If you select **Manual configuration**, you choose **Cost Management**, **RHEL management** bundle, or **No application**.

The **Cost Management** application allows you to perform financially related tasks, such as:

- Visualizing, understanding, and analyzing the use of resources and costs
- Forecasting your future consumption and comparing them with budgets
- Optimizing resources and consumption
- Identifying patterns of usage for further analysis
- Integrating with third-party tools that can benefit from cost and resourcing data

The **RHEL management** bundle includes the following items:

- Red Hat gold images
- High precision subscription watch data
- Autoregistration

The **Cost Management** and the **RHEL management** bundle applications require you to enable account access. You accomplish this by creating an IAM policy, an IAM role, and entering your Amazon Resource Name (ARN). An ARN is a generic name for an Amazon resource and has a common format depending on the service involved. In this case, it is the identity and access management (IAM) service and Role resource-type.

If you select **No application**, you choose which credentials to supply:

- AWS Secret key
- Cost Management ARN
- Subscription Watch ARN

## Google Cloud

The workflow for adding Google Cloud as a cloud source includes the following high-level steps:

1. Selecting the source type
2. Naming the source
3. Selecting applications
4. Adding a project
5. Enabling account access
6. Creating a dataset
7. Setting up billing export information
8. Reviewing details
9. Adding the source

**Cost Management** is the only application choice. You must create an IAM role and assign access.

The **Cost Management** application allows you to perform financially related tasks, such as:

- Visualizing, understanding, and analyzing the use of resources and costs
- Forecasting your future consumption and comparing them with budgets
- Optimizing resources and consumption
- Identifying patterns of usage for further analysis
- Integrating with third-party tools that can benefit from cost and resourcing data

If you select **No application**, you provide the Project ID and the Service Account JSON as credentials.

## Microsoft Azure

The workflow for adding Microsoft Azure as a cloud source includes the following high-level steps:

1. Selecting the source type
2. Naming the source
3. Selecting applications
4. Creating a resource group and a storage account (for cost management)
5. Entering a Subscription ID (for cost management)
6. Creating roles (for cost management)
7. Setting up daily exports (for cost management)
8. Providing credentials
9. Reviewing details
10. Adding the source

Application choices include **Cost Management**, **RHEL management** bundle, or **No application**.

The **Cost Management** application allows you to perform financially related tasks, such as:

- Visualizing, understanding, and analyzing the use of resources and costs
- Forecasting your future consumption and comparing them with budgets
- Optimizing resources and consumption
- Identifying patterns of usage for further analysis
- Integrating with third-party tools that can benefit from cost and resourcing data

The **RHEL management** bundle includes the following items:

- Red Hat gold images

- Autoregistration

You create a dedicated resource group and a storage account in the Azure Portal so you can collect cost data and metrics for cost management. You then use your subscription ID to create a Cost Management Storage Account Contributor role in the Cloud Shell. Using the subscription ID to run a second command in the Cloud Shell gives you the tenant (directory) ID, client (application) ID, and client secret necessary to complete setting up that role.



#### NOTE

Configure dedicated credentials to grant cost management read-only access to Azure cost data.

## 1.3. ADDING RED HAT SOURCES

The workflow for adding Red Hat OpenShift Container Platform as a cloud source includes the following high-level steps:

1. Selecting the source type and application
2. Naming the source
3. Installing and configuring the operator
4. Reviewing the details
5. Adding the source

Cost Management is the only application choice. The **Cost Management** application allows you to perform financially related tasks, such as:

- Visualizing, understanding, and analyzing the use of resources and costs
- Forecasting your future consumption and comparing them with budgets
- Optimizing resources and consumption
- Identifying patterns of usage for further analysis
- Integrating with third-party tools that can benefit from cost and resourcing data



#### NOTE

For Red Hat OpenShift Container Platform 4.6 and later, install the **costmanagement-metrics-operator** from the OpenShift Container Platform web console. For more information, see [Adding an OpenShift Container Platform source to cost management](#) .

## 1.4. SOURCES REFERENCE MATERIAL

[Getting started with cost management](#)

[Getting Started with Subscription Watch](#)

[Adding sources for public cloud metering](#)

[Getting started with Automation Services Catalog](#)

[Bucket restrictions and limitations](#)

[Bucket naming rules](#)