



Red Hat Insights 1-latest

Deploying and managing RHEL systems in hybrid clouds

Deploying and managing your customized RHEL system images in hybrid clouds

Red Hat Insights 1-latest Deploying and managing RHEL systems in hybrid clouds

Deploying and managing your customized RHEL system images in hybrid clouds

Legal Notice

Copyright © 2024 Red Hat, Inc.

The text of and illustrations in this document are licensed by Red Hat under a Creative Commons Attribution–Share Alike 3.0 Unported license ("CC-BY-SA"). An explanation of CC-BY-SA is available at

<http://creativecommons.org/licenses/by-sa/3.0/>

. In accordance with CC-BY-SA, if you distribute this document or an adaptation of it, you must provide the URL for the original version.

Red Hat, as the licensor of this document, waives the right to enforce, and agrees not to assert, Section 4d of CC-BY-SA to the fullest extent permitted by applicable law.

Red Hat, Red Hat Enterprise Linux, the Shadowman logo, the Red Hat logo, JBoss, OpenShift, Fedora, the Infinity logo, and RHCE are trademarks of Red Hat, Inc., registered in the United States and other countries.

Linux[®] is the registered trademark of Linus Torvalds in the United States and other countries.

Java[®] is a registered trademark of Oracle and/or its affiliates.

XFS[®] is a trademark of Silicon Graphics International Corp. or its subsidiaries in the United States and/or other countries.

MySQL[®] is a registered trademark of MySQL AB in the United States, the European Union and other countries.

Node.js[®] is an official trademark of Joyent. Red Hat is not formally related to or endorsed by the official Joyent Node.js open source or commercial project.

The OpenStack[®] Word Mark and OpenStack logo are either registered trademarks/service marks or trademarks/service marks of the OpenStack Foundation, in the United States and other countries and are used with the OpenStack Foundation's permission. We are not affiliated with, endorsed or sponsored by the OpenStack Foundation, or the OpenStack community.

All other trademarks are the property of their respective owners.

Abstract

Red Hat Insights enables you to perform and manage multiple services as part of one larger, connected workflow. You can define your third-party content source, create customized images, use your preferred system by setting customizations in the image, and launch the image to the target public or private cloud environments, such as Amazon Web Services and Microsoft Azure. You can monitor the system infrastructure you have created, and create and apply patches when needed. You can also report and audit any issues you find in your system infrastructure to improve security and stability.

Table of Contents

MAKING OPEN SOURCE MORE INCLUSIVE	3
CHAPTER 1. WORKFLOW FOR DEPLOYING AND MANAGING RHEL SYSTEMS IN OPEN HYBRID CLOUD ENVIRONMENTS	4
CHAPTER 2. MANAGING REPOSITORIES TO BUILD YOUR CUSTOMIZED OPERATING SYSTEMS	5
2.1. ADDING A CUSTOM REPOSITORY	5
2.2. MODIFYING A CUSTOM REPOSITORY	6
2.3. REMOVING A CUSTOM REPOSITORY	6
2.4. ADDING EXISTING REPOSITORIES FROM POPULAR REPOSITORIES TO CUSTOM REPOSITORIES	6
2.5. UPDATING CUSTOM REPOSITORY AFTER CHANGES	7
2.6. REPOSITORY STATUS IN THE RED HAT HYBRID CLOUD CONSOLE	7
CHAPTER 3. CONFIGURING INTEGRATIONS TO LAUNCH RHEL IMAGES	9
3.1. CONNECTING AN AWS ACCOUNT TO THE RED HAT HYBRID CLOUD CONSOLE	9
3.2. CONNECTING MICROSOFT AZURE ACCOUNT TO THE RED HAT HYBRID CLOUD CONSOLE	10
3.3. CONNECTING GCP PROJECT TO THE RED HAT HYBRID CLOUD CONSOLE	11
CHAPTER 4. BUILDING CUSTOMIZED RHEL IMAGES	12
4.1. ABOUT BUILDING CUSTOMIZED IMAGES	12
4.2. CREATING CUSTOMIZED RHEL IMAGES FOR THE AWS ENVIRONMENT	12
4.3. COPYING YOUR CUSTOMIZED RHEL SYSTEM IMAGE FOR AWS TO A DIFFERENT REGION ON YOUR AWS EC2	16
4.4. AUTHORIZING IMAGE BUILDER TO PUSH IMAGES TO MICROSOFT AZURE CLOUD	16
4.5. CREATING CUSTOMIZED RHEL IMAGES FOR THE MICROSOFT AZURE ENVIRONMENT	18
4.6. CREATING CUSTOMIZED IMAGES FOR THE GCP ENVIRONMENT	22
4.7. COPYING THE GCE IMAGE TO YOUR PROJECT GROUP	25
4.8. CREATING CUSTOMIZED RHEL VMDK SYSTEM IMAGES	27
4.9. CREATING CUSTOMIZED RHEL GUEST SYSTEM IMAGES	29
4.10. CREATING CUSTOMIZED RHEL ISO SYSTEM IMAGES	32
4.11. CREATING CUSTOMIZED IMAGES FOR THE OCI ENVIRONMENT	34
4.12. CREATING A NEW IMAGE FROM AN EXISTING BUILD	37
4.13. SHARING AWS IMAGES TO OTHER REGIONS	38
4.14. DOWNLOADING THE JSON COMPOSE REQUEST	39
CHAPTER 5. LAUNCHING CUSTOMIZED RHEL IMAGES TO THE CLOUD PLATFORMS WITH INSIGHTS IMAGE BUILDER	40
5.1. LAUNCHING A CUSTOMIZED RHEL IMAGE ON AWS	40
5.2. LAUNCHING A CUSTOMIZED RHEL IMAGE ON MICROSOFT AZURE	41
5.3. LAUNCHING A CUSTOMIZED RHEL IMAGE ON THE GOOGLE CLOUD PLATFORM	42
5.4. CONFIGURING LAUNCH NOTIFICATIONS	43
CHAPTER 6. DEPLOYING YOUR CUSTOMIZED IMAGES	45
6.1. UPLOADING VMDK IMAGES AND CREATING A RHEL VIRTUAL MACHINE IN VSPHERE	45
6.2. DEPLOYING OVA VMDK IMAGES TO THE VSPHERE GUI	46
6.3. CREATING A VIRTUAL MACHINE FROM THE CUSTOMIZED RHEL GUEST SYSTEM IMAGE	47
6.4. INSTALLING A CUSTOMIZED RHEL ISO SYSTEM IMAGE TO A BARE METAL SYSTEM	49
6.5. IMPORTING AND RUNNING QCOW2 IMAGES ON OCI	49
PROVIDING FEEDBACK ON RED HAT DOCUMENTATION	51
OPENING A SUPPORT CASE AT RED HAT SUPPORT	52

MAKING OPEN SOURCE MORE INCLUSIVE

Red Hat is committed to replacing problematic language in our code, documentation, and web properties. We are beginning with these four terms: master, slave, blacklist, and whitelist. Because of the enormity of this endeavor, these changes will be implemented gradually over several upcoming releases. For more details, see [our CTO Chris Wright's message](#).

CHAPTER 1. WORKFLOW FOR DEPLOYING AND MANAGING RHEL SYSTEMS IN OPEN HYBRID CLOUD ENVIRONMENTS

Use Red Hat Insights to launch and manage your customized RHEL systems images in the open hybrid cloud environments. Currently, you can use Red Hat Insights to deploy and manage the RHEL systems in the following cloud:

- Amazon Web Services
- Microsoft Azure
- Google Cloud Platform

You can access the Red Hat Insights with your Red Hat account, a RHEL subscription, and an activation key. No additional SKUs are required. See [Creating an activation key](#).

As part of the deployment, by using Red Hat Insights, you can follow an end-to-end workflow to:

1. [Define or use existing repositories](#).
2. [Configure integrations to launch your images](#).
3. [Build customized images](#).
4. [Launch the images in your preferred cloud](#).

In addition, you can manage your systems by granting users access, monitoring the inventory of your system infrastructure, and applying patches to improve security and stability.

CHAPTER 2. MANAGING REPOSITORIES TO BUILD YOUR CUSTOMIZED OPERATING SYSTEMS

You can define your customized repositories with third-party content without having to manage their lifecycle. You can use your third-party content to build an image, and when you launch that image to the public cloud environment, you can use those repositories with the **dnf** tool.

2.1. ADDING A CUSTOM REPOSITORY

Define your repository to be able to add packages from this repository to your customized images.

Prerequisites

- You have a RHEL subscription.
- You have administrator access to the Red Hat Hybrid Cloud Console web user interface or **repository administrator** role.
- You have the URL link to your repository content.

Procedure

1. Access [Hybrid Cloud Console](#).
2. Click **Services > Observe > RHEL > Repositories**
3. Click **Add repositories**. The **Add custom repositories** wizard opens.
4. Enter the following information:
 - a. **NAME** - mandatory.
 - b. **URL** - mandatory.
 - c. In the **Restrict architecture** drop-down menu, select an architecture. You can allow all the architectures or restrict one to your system architecture to prevent incorrect repositories availability.
 - d. In the **Restrict OS version** drop-down menu select an operating system (OS). You can allow all the RHEL versions or select one for your system version to prevent incorrect repositories being available.
 - e. **GPG key** - upload the **.txt** file with a GPG key or paste the URL or value of an existing GPG key. The GPG key verifies the signed packages of a repository. If you do not provide the GPG key for a repository, your system cannot perform the verification.
5. If you want to add another repository, click the **+ Add another repository** button and repeat step 3.
6. Click **Save**. The Red Hat Hybrid Cloud Console validates the project status. If your repository is marked as **Invalid**, check the repository URL that you added. For details about the repository status, see [Repository status](#) section.

Verification

- Open the list of custom repositories and verify that the repository you added is listed.

2.2. MODIFYING A CUSTOM REPOSITORY

You can modify a custom repository when you need to update information for that repository.

Prerequisites

- You have a RHEL subscription.
- You have administrator access to the Red Hat Hybrid Cloud Console web user interface or **repository administrator** role.

Procedure

1. Access [Hybrid Cloud Console](#).
2. Click **Services > Observe > RHEL > Repositories**
3. Find a repository you want to modify and click **Edit** in the **Options** menu.
4. In the **Edit custom repository** wizard, modify the information you need. Click **Save changes**.

2.3. REMOVING A CUSTOM REPOSITORY

When you no longer need a custom repository you can delete it.

Prerequisites

- You have a RHEL subscription.
- You have administrator access to the Red Hat Hybrid Cloud Console web user interface or **repository administrator** role.

Procedure

1. Access [Hybrid Cloud Console](#).
2. Click **Services > Observe > RHEL > Repositories**
3. Find a repository to delete and click **Delete** in the **Options** menu.

Verification

- Open the list of custom repositories, and verify that the repository no longer exists.

2.4. ADDING EXISTING REPOSITORIES FROM POPULAR REPOSITORIES TO CUSTOM REPOSITORIES

The Red Hat Hybrid Cloud Console has pre-configured repositories that you can use to build your customized RHEL image.

Prerequisites

- You have a RHEL subscription.
- You have administrator access to the Red Hat Hybrid Cloud Console web user interface or **repository administrator** role.

Procedure

1. Access [Hybrid Cloud Console](#).
2. Click **Services > Observe > RHEL > Repositories**
3. On the **Custom repositories** page click the **Popular repositories** tab.
4. Search for the repository you want to add and click **Add**.

Verification

- Select the **Your repositories** tab and verify that the new repository is displayed in the list of custom repositories.

2.5. UPDATING CUSTOM REPOSITORY AFTER CHANGES

When you make changes to your repository you can trigger a refresh of that repository in the Red Hat Hybrid Cloud Console.

Prerequisites

- You have a RHEL subscription.
- You have administrator access to the Red Hat Hybrid Cloud Console web user interface or **repository administrator** role.
- You updated your custom repository.

Procedure

1. Access [Hybrid Cloud Console](#).
2. Click **Services > Observe > RHEL > Repositories**
3. Find a repository you want to modify and click **Introspect Now** in the **Options** menu.
4. The status of that repository changes to **In progress** that indicates the Hybrid Cloud Console is connecting to the repository and checking for changes.
The Red Hat Hybrid Cloud Console checks the status of the repositories every 24 hours and again every 8 hours if the status check fails.

2.6. REPOSITORY STATUS IN THE RED HAT HYBRID CLOUD CONSOLE

The repository status shows if the repository is available. The Red Hat Hybrid Cloud Console checks the repository status periodically and can change it. The following table describes the repository status in the Red Hat Hybrid Cloud Console.

Table 2.1. Repository status

Status	Description
Valid	The Red Hat Hybrid Cloud Console has validated the repository and you can use it.
Invalid	The Red Hat Hybrid Cloud Console never validated this repository. You cannot use it.
Unavailable	The repository was valid at least once. The Red Hat Hybrid Console cannot reach this repository at the moment. You cannot use it.
In progress	The repository validation is in progress.

CHAPTER 3. CONFIGURING INTEGRATIONS TO LAUNCH RHEL IMAGES

You can launch your customized RHEL images in a public cloud environment. To do so you must connect your public cloud account with the Hybrid Cloud Console by adding your account to Integrations. While adding your public cloud account, you may need to log in to that account and perform some actions depending on your cloud provider.

3.1. CONNECTING AN AWS ACCOUNT TO THE RED HAT HYBRID CLOUD CONSOLE

You can add your Amazon Web Services (AWS) account to the Red Hat Hybrid Cloud and configure it to launch your RHEL images in the AWS environment.

Prerequisites

- You have a RHEL subscription.
- You are an Organization Administrator or you have a non-admin user with the "Launch administrator" and the "Sources administrator" roles assigned. See [how to assign a role to a user](#).
- You installed the **awscli** and the **jq** packages.

Procedure

1. Access [Hybrid Cloud Console](#).
2. Click the **Settings** icon, then click **Settings > Integrations**.
3. Click **Add integration**. The **Add integrations** wizard opens.
4. Select **Amazon Web Service** in the **Select integration type** page and click **Next**.
5. On the **Integration name** page, name the integration for your AWS account in the **Name** field and click **Next**.
6. On the **Select configuration** page, choose between the following two options:
 - a. If you select **Account authorization**, provide your **Access key ID** and **Secret access key** for your ID from your AWS account. Click **Next** and complete the following steps:
 - i. On the **Select application** page, select the **Launch images** option. Click **Next**.
 - ii. On the **Review details** page, verify the details about your AWS account and click **Add**. The console connects to your AWS account with the credentials you provided and creates an Identity and Access Management (IAM) role with necessary permissions in your AWS account.
 - b. If you select **Manual configuration**, click **Next** and complete the following steps:
 - i. On the **Select application** page, select the **Launch images** option. Click **Next**.
 - ii. On the **Create IAM policy** page in **Enable account access**, copy the command with the **Copy to clipboard** and run it in your terminal. Click **Next**.

- iii. On the **Create IAM role** page in **Enable account access**, follow the instructions on the wizard window. Click **Next**.
 - iv. On the **Enter ARN** page in **Enable account access**, fill the ARN into the text field. Click **Next**.
7. On the **Review details** page, verify the details about your AWS account and click **Add** to finish adding it to the **Integrations**.

3.2. CONNECTING MICROSOFT AZURE ACCOUNT TO THE RED HAT HYBRID CLOUD CONSOLE

You can add your Microsoft Azure account to the Red Hat Hybrid Cloud Console and configure it to launch your RHEL images in the Azure environment.

Prerequisites

- You have a RHEL subscription.
- You are an Organization Administrator or you have a non-admin user with the "Launch administrator" and the "Sources administrator" roles assigned. See [how to assign a role to a user](#).
- You have a Microsoft Azure account.
- You have registered the following resource providers in your Microsoft Azure subscription:
 - **Microsoft.Compute**;
 - **Microsoft.Storage**;
 - **Microsoft.Network**.

Procedure

1. Access [Hybrid Cloud Console](#).
2. Click the **Settings** icon, then click **Settings > Integrations**.
3. Click **Add Integration**. The **Add integration** wizard opens.
4. Select **Microsoft Azure** in the **Select integration type** page and click **Next**.
5. On the **Name integration** page, name the integration for your Microsoft Azure account in the **Integration name** field and click **Next**.
6. On the **Select application** page, select the **Launch images** option and click **Next**.
7. On the **Configure Azure Lighthouse** page, click **Take me to Lighthouse** and complete configuration steps in Azure Lighthouse according to the Microsoft instructions. Return to the **Add integration** wizard and click **Next**.
8. On the **Set subscription ID** page, fill in the **Subscription ID** field and click **Next**.
9. On the **Review details** page, verify the details about your Microsoft Azure account and click **Add** to finish adding it to the **Integrations**.

3.3. CONNECTING GCP PROJECT TO THE RED HAT HYBRID CLOUD CONSOLE

You can add your Google Cloud Platform (GCP) project to the Red Hat Hybrid Cloud and configure it to launch your RHEL images in the AWS environment.

Prerequisites

- You have a RHEL subscription.
- You are an Organization Administrator or you have a non-admin user with the "Launch administrator" and the "Sources administrator" roles assigned. See [how to assign a role to a user](#) .
- You have a GCP project with a **default** network.

Procedure

1. Access [Hybrid Cloud Console](#).
2. Click the **Settings** icon, then click **Settings > Integrations**.
3. Click **Add integration**. The **Add integration** wizard opens.
4. Select **Google Cloud** in the **Select integration type** page and click **Next**.
5. On the **Integration name** page, name the integration for your GCP project in the **Name** field and click **Next**.
6. On the **Select application** page, select the **Launch images** option and click **Next**.
7. On the **Enable account access** page:
 - a. On the **Enter Project ID** page, fill in your GCP project name that you want to add in the **Project** field. Click **Next**.
 - b. On the **Create custom role** page, follow the instructions on the page. Click **Next**.
8. On the **Review details** page, verify the details about your GCP project and click **Add** to finish adding it to the **Integrations**.

Verification

- The console validates the data for your GCP project and shows a message **Configuration successful**.

CHAPTER 4. BUILDING CUSTOMIZED RHEL IMAGES

You can build customized RHEL images for a variety of deployment types by using Insights Images. You can build Conventional (RPM-DNF) images or Immutable (OSTree) images.

4.1. ABOUT BUILDING CUSTOMIZED IMAGES

You can build either Conventional (RPM-DNF) images or Immutable (OSTree) images.

- The **Conventional (RPM-DNF)** enables you to manage or modify the system software by using the DNF package manager and updated RPM packages.
- The **Immutable (OSTree)** images contain a complete operating system ready to be remotely installed and allows you to manage the system software by referencing a central image repository. For more details, see [Create RHEL for Edge images and configure automated management](#).

When building the images, you can perform any of the following customizations:

- Select the cloud target environment to launch the instances.
- Choose to automatically register and enable advanced capabilities to the system images, such as:
 - Red Hat Insights, to identify and address operational and vulnerability risks.
 - Remote host configuration (rhc), to enable remote remediations and system management with automation.
 - Optionally, you can manually register your systems later, with **rhc**. See [Remote Host Configuration and Management](#).
- Define the system images with a specific file system customization.
- Select packages from Red Hat and third-parties.

The image artifacts are saved for 14 days and expire after that. To avoid losing the image, transfer the image to your account before the expiration date. If an image has already expired, you can and it is expired, you can also re-create the exact image based on an existing build to reuse the previous configuration.

You can share an existing AWS image to a new region to run on your AWS account so that all regions can launch with the same configuration.

You can also download the compose request of your image and use the [image builder API](#) to automate your image building tasks.

4.2. CREATING CUSTOMIZED RHEL IMAGES FOR THE AWS ENVIRONMENT

To push a RHEL image to the Amazon Web Services (AWS) target environment, first complete the following steps to create a customized system image by using Insights Images.



NOTE



Currently, Insights Images cannot upload images to AWS GovCloud Regions.


Prerequisites

- You have a RHEL subscription.
- You have Organization Administrator permissions.
- For AWS target environments, you have created an [AWS account](#).

Procedure


1. Access [Hybrid Cloud Console](#).
2. Click **Red Hat Insights > RHEL > Inventory > Images**
The Insights Images dashboard appears.
3. Click **Create image**.
The **Create image** wizard opens.
4. On the **Image output** page, select the following:
 - a. From the **Release** list, select the release that you want to use.
 - b. From the **Architecture** list, select the architecture that you want to use.
 - c. From the **Select target environments** option, select **Amazon Web Services**.
 - d. Click **Next**.
5. On the **Target Environment - Amazon Web Service** page, perform the following actions:
 - a. Select one of the share methods to share your Red Hat image with your AWS account:
 - **Use an account configured from Source**
 - **Manually enter an account ID**
 - b. For the **Use an account configured from Source** sharing method:
 - i. From the **Source Name** dropdown menu, select the source you want.
 - ii. The **Default region fields** and **Associated Account ID** are filled automatically after you select the source. If the source is unavailable, you can enter the AWS account ID manually or try again later.
 - c. Click **Next**.
 - d. For the **Manually enter an account ID** sharing method:
 - i. Enter the **AWS account ID**. The Default region is **us-east-1** and you can copy the image to different regions later. See [Sharing AWS images to other regions](#).
 - ii. Click **Next**.
6. On the **Register** page, select one of the registration methods: **Automatically register and enable advanced capabilities** or **Register later**.

If you choose the **Automatically register and enable advanced capabilities** option, customize it further.

- a. Click the **Show additional connection options** button.
The **Monitor & manage subscriptions and access to Red Hat content** radio button enables the following option:
 - Enable predictive analytics and management capabilities - to provide actionable intelligence about your Red Hat Enterprise Linux environments, helping to identify and address operational and vulnerability risks before an issue results in downtime.
 - Enable remote remediations and system management with automation - Red Hat connector (rhc) enables Red Hat Enterprise Linux hosts to connect to Red Hat Insights to use Red Hat Insights Remediations service.
 - b. Check or uncheck the checkboxes according to your preferences.
 - c. From the dropdown menu, choose an activation key to use for the image. See [Creating an activation key](#).
 - i. **No activation keys found** - If you do not have an activation key, you can choose the default activation key by completing the following step:
 - A. Click the **Create activation key** button. The Select activation key dropdown menu enables the **activation-key-default**. It is a preset key with the basic configuration. You can manage the activation key by accessing [Activation keys](#).
 - d. Click **Next**.
7. On the **File system configuration** page, select the recommended **Use automatic partitioning** or **Manually configure partitions** for your image file system.
- a. To configure your partitions manually, click the **Manually configure partitioning** radio button.
The **Configure partitions** section opens, showing the configuration based on Red Hat standards and security guides.
 - b. From the drop-down menu, provide details to configure the partitions:
 - c. For the **Mount point** field, select one mount point type option
You can also add an additional path to the **Mount point**, such as **/tmp**. For example: **/var** as a prefix and **/tmp** as an additional path results in **/var/tmp**.
- 

NOTE

Depending on the **Mount point** type you choose, the file system type changes to **xfs**, and so on.
- d. For the **Minimum size** partition field of the file system, enter the desired minimum partition size. In the **Minimum size** drop-down menu, you can use common size units such as **GiB**, **MiB**, or **KiB**. The default unit is **GiB**.
 - e. To add more partitions, click **Add partition** and repeat the steps for each added partition. Click **Next**.
8. Optional: On the **Content** page, complete the following steps to add additional packages to your image:

- a. On the **Additional Red Hat packages** step:
 - i. On the **Available packages** search field, enter the package name and click the → button.
 - ii. Click the >> button to add all packages shown in the package search results to the **Chosen packages** dual list box. Optionally, you can click the > button to add only one selected package at a time.
 - b. On the **Custom repositories** page, click **Repositories**.
The **Custom Repositories** page opens in a new browser tab. Go to the new page.
 - i. Click **Add repositories**. Enter the following information:
 - A. **Name**
 - B. **URL**
 - C. **Restrict architecture**: from the drop-down menu, select an architecture. Either mark all the architectures or select one to restrict to your system architecture to prevent incorrect repositories availability.
 - D. **Restrict OS version**: from the drop-down menu, select an operating system (OS). Either allow all RHEL versions or select a version for your system, to prevent incorrect repositories availability.
 - E. **GPG key**: Either upload a file with a GPG key or paste the URL of an existing GPG key.
- 

NOTE

If you do not provide the GPG key for a repository, your system cannot perform the GPG key verification for signed packages in a repository.
- F. Click **Save** to validate the repository status.
- c. Return to the **Create image** dashboard and click **Next**.
9. Optional: On the **Name image** page, enter a name for the image. Each image has a unique Universally Unique Identifier (UUID). Click **Next**.
 10. On the **Review** page, verify the image details about the image creation and click **Create image**. The system verifies the build manifest of the image. After it reaches 100%, the image is added to the build queue.

Insights Images starts to compose a RHEL image for the architecture that you selected. After the image is ready, you can see it in the **Images** dashboard.

Additional resources

- [Connecting an AWS account to the Red Hat Hybrid Cloud Console](#)
- [Possible statuses for your custom repository](#)
- [Sharing AWS images to other regions](#)

- [Launching a customized RHEL image to AWS](#)

4.3. COPYING YOUR CUSTOMIZED RHEL SYSTEM IMAGE FOR AWS TO A DIFFERENT REGION ON YOUR AWS EC2

You can copy the image you successfully shared with the **Amazon Web Services EC2** to your own account. Doing so, you grant that the image you shared and copied is available until you delete it, instead of expiring after some time. To copy your image to your own account, follow the steps:

Prerequisites

- You have access to your customized image on AWS.

Procedure

1. From the list of **Public images**, select the image you want to copy.
2. On the top of the panel, click **Actions**.
3. From the dropdown menu, choose **Copy AMI**. A popup window appears.
4. Choose the **Destination region** and click **Copy AMI**.
After the copying process is complete, you are provided with the new **AMI ID**. You can launch a new instance in the new region.



NOTE

When you copy an image to a different region, it results in a separate and new **AMI** in the destination region, with a unique **AMI ID**.

4.4. AUTHORIZING IMAGE BUILDER TO PUSH IMAGES TO MICROSOFT AZURE CLOUD

To push a RHEL image to the Microsoft Azure target environment, you must authorize Image Builder to push images to the Microsoft Azure cloud. The authorization consists of the following steps:

- Configure Insights Images as an authorized application for your **tenant GUID**
- Give it the role of **Contributor** to at least one resource group.
To authorize Image Builder as an authorized application, follow the steps:

Prerequisites

- You have an existing **Resource Group** in Microsoft Azure portal.
- You have the **User Access Administrator** role rights.
- Your Microsoft Azure subscription has **Microsoft.Storage** and **Microsoft.Compute** as a resource provider.

Procedure

1. Access [Hybrid Cloud Console](#).

2. Click **Red Hat Insights > RHEL > Inventory > Images**

The Insights Images dashboard appears.

3. Click **Create image**.

The **Create image** dialog wizard opens.

On the **Image output** page, complete the following steps:

- a. From the **Release** list, select the release that you want to use.
- b. From the **Select target environments** option, select **Microsoft Azure**.
Click **Next**.
 1. On the **Target Environment - Microsoft Azure** window, to add Image Builder as an authorized application, complete the following steps:
- c. Insert your **Tenant GUID**.
Images checks if your **Tenant GUID** is correctly formatted and the **Authorize image builder** button becomes available.
- d. Click **Authorize image builder** to authorize Insights Images to push images to the Microsoft Azure cloud.
This redirects you to the Microsoft Azure portal.
 - i. Login with your credentials.
 - ii. Click **Accept** the **Permission requested**.
- e. Confirm that Image Builder is authorized for your tenant.
 - i. Search for **Azure Active Directory** and choose **Enterprise applications**, from the left menu.
 - ii. Search for Image Builder and confirm it is authorized.
- f. Add the **Enterprise application** as a contributor to your **Resource Group**.
 - i. In the search bar, type **Resource Groups** and select the first entry under **Services**. This redirects you to the **Resource Groups** dashboard.
 - ii. Select your **Resource Group**.
 - iii. On the left menu, click **Access control (IAM)** to add a permission so the **Image Builder** application can access your resource group.
 - iv. From the menu, click the tab **Role assignments**.
 - v. Click **+Add**.
 - vi. From the dropdown menu, choose **Add role assignment**. A menu appears on the left side.
 - vii. Enter the following details:
 - A. Role: Assign the **Contributor** role
 - B. Assign access to: User, group, service principal. Add members: Click **+Select members** and type **Red Hat** in the search bar. Click enter.

C. Select: **Image Builder** application

The Image Builder application is now authorized to push images to Microsoft Azure cloud.



NOTE

Even though any user can add an application to the resources group, the application is not able to locate any resource unless the account administrator adds the shared application as a contributor under the **IAM** section of the resource group.

Verification

- From the menu, click the tab **Role assignments**.
You can see Insights image builder set as a **Contributor** of the **Resource Group** you selected.

Additional resources

- [Manage Microsoft Azure Resource Manager resources group by using the Microsoft Azure portal](#)

4.5. CREATING CUSTOMIZED RHEL IMAGES FOR THE MICROSOFT AZURE ENVIRONMENT

To push a RHEL image to the Microsoft Azure target environment, first complete the following steps to create a customized system image by using Insights Images.



NOTE

Currently, Insights Images cannot upload images to **21Vianet** Microsoft Azure China.

Prerequisites

- You have a RHEL subscription.
- You have Organization Administrator permissions.
- For Azure target environments:
 - You have an **Azure Tenant ID**.
 - You have an existing **Resource Group** in [Microsoft Azure portal](#).
 - You have an Azure **Subscription ID**.

Procedure

1. Access [Hybrid Cloud Console](#).
2. Click **Red Hat Insights > RHEL > Inventory > Images**
The Insights Images dashboard appears.
3. Click **Create image**.
The **Images** wizard opens.

On the **Image output** page, complete the following steps:

- a. From the **Release** list, select the release that you want to use.
- b. From the **Select target environments** option, select the target environment you want.
- c. Click **Next**.
- d. From the **Target Environment - Microsoft Azure** page, complete the following steps:
 - e. Select one of the share methods to share your Red Hat image with your Azure account:
 - Use an account configured from Source** to import the account directly from the cloud provider.
 - Manually enter an account ID** to enter the account manually.
 - f. For the **Use an account configured from Source** sharing method:
 - i. From the **Source Name** drop-down menu, select the source you want. The **Azure Tenant GUID** and your **Subscription ID** are filled automatically. Insights Images checks if your **Azure Tenant GUID** is correct and the **Authorize Image Builder** button becomes available.
 - ii. Click **Authorize Image Builder** to authorize Insights Images to push images to the [Microsoft Azure portal](#). See [Authorizing image builder to push images to Microsoft Azure Cloud](#) to learn how to authorize Image Builder as a tenant.
 - iii. From the dropdown menu, select your **Resource group**.
 - iv. Click **Next**.
 - g. For the **Manually enter an account ID** sharing method:
 - i. Enter your **Azure Tenant GUID**. You can find your Tenant ID in the Azure Active Directory application in Microsoft Azure Portal. Insights Images checks if your **Azure Tenant GUID** is correct and the **Authorize Image Builder** button becomes available.
 - ii. Click **Authorize Image Builder** to authorize Insights Images to push images to the [Microsoft Azure portal](#). See [Authorizing image builder to push images to Microsoft Azure Cloud](#) to learn how to authorize Image Builder as a tenant.
 - iii. Enter your **Subscription ID**: you can find your **Subscription ID** account by accessing the Microsoft Azure console.
 - iv. Enter your **Resource group**: it is the name of your **Resource Group** in Microsoft Azure Portal.





NOTE

By default, Images creates Microsoft Azure images with support for generation 1 VMs. See [Support for generation 2 VMs on Azure](#).

- h. Click **Next**.
 1. On the **Register** page, select one of the registration methods: **Automatically register and enable advanced capabilities** or **Register later**.

If you choose the **Automatically register and enable advanced capabilities** option, customize it further.

- i. Click the **Show additional connection options** button.
The **Monitor & manage subscriptions and access to Red Hat content** radio button enables the following option:
 - Enable predictive analytics and management capabilities - to provide actionable intelligence about your Red Hat Enterprise Linux environments, helping to identify and address operational and vulnerability risks before an issue results in downtime.
 - Enable remote remediations and system management with automation - Red Hat connector (rhc) enables Red Hat Enterprise Linux hosts to connect to Red Hat Insights to use Red Hat Insights Remediations service.
 - j. Check or uncheck the checkboxes according to your preferences.
 - k. From the dropdown menu, choose an activation key to use for the image. See [Creating an activation key](#).
 - i. **No activation keys found** - If you do not have an activation key, you can choose the default activation key by completing the following step:
 - A. Click the **Create activation key** button. The Select activation key dropdown menu enables the **activation-key-default**. It is a preset key with the basic configuration. You can manage the activation key by accessing [Activation keys](#).
 - l. Click **Next**.
 1. On the **File system configuration** page, select the recommended **Use automatic partitioning** or **Manually configure partitions** for your image file system.
 - m. To configure your partitions manually, click the **Manually configure partitioning** radio button. The **Configure partitions** section opens, showing the configuration based on Red Hat standards and security guides.
 - n. From the drop-down menu, provide details to configure the partitions:
 - o. For the **Mount point** field, select one mount point type option
You can also add an additional path to the **Mount point**, such as **/tmp**. For example: **/var** as a prefix and **/tmp** as an additional path results in **/var/tmp**.
-  **NOTE**
- Depending on the **Mount point** type you choose, the file system type changes to **xfs**, and so on.
- p. For the **Minimum size** partition field of the file system, enter the desired minimum partition size. In the **Minimum size** drop-down menu, you can use common size units such as **GiB**, **MiB**, or **KiB**. The default unit is **GiB**.
 - q. To add more partitions, click **Add partition** and repeat the steps for each added partition. Click **Next**.
 1. Optional: On the **Content** page, complete the following steps to add additional packages to your image:

- r. On the **Additional Red Hat packages** step:
 - i. On the **Available packages** search field, enter the package name and click the → button.
 - ii. Click the >> button to add all packages shown in the package search results to the **Chosen packages** dual list box. Optionally, you can click the > button to add only one selected package at a time.
 - s. On the **Custom repositories** page, click **Repositories**.
The **Custom Repositories** page opens in a new browser tab. Go to the new page.
 - i. Click **Add repositories**. Enter the following information:
 - A. **Name**
 - B. **URL**
 - C. **Restrict architecture**: from the drop-down menu, select an architecture. Either mark all the architectures or select one to restrict to your system architecture to prevent incorrect repositories availability.
 - D. **Restrict OS version**: from the drop-down menu, select an operating system (OS). Either allow all RHEL versions or select a version for your system, to prevent incorrect repositories availability.
 - E. **GPG key**: Either upload a file with a GPG key or paste the URL of an existing GPG key.
- 

NOTE

If you do not provide the GPG key for a repository, your system cannot perform the GPG key verification for signed packages in a repository.
- F. Click **Save** to validate the repository status.
- t. Return to the **Create image** dashboard and click **Next**.
 1. Optional: On the **Name image** page, enter a name for the image. Each image has a unique Universally Unique Identifier (UUID). Click **Next**.
 2. On the **Review** page, verify the image details about the image creation and click **Create image**.
The system verifies the build manifest of the image. After it reaches 100%, the image is added to the build queue.

Insights image builder starts to compose a RHEL image for the **x86_64** architecture. After the image is ready, you can see it in the **Inventory**.

Verification

- Verify that on the dashboard, you can see details such as:
 - **Image name**
 - The **creation or update** date
 - **Image OS Release**

- The cloud **Target** environment
- The image creation **Status**
- The **Instance** details.

Additional resources

- [Connecting Microsoft Azure account to the Red Hat Hybrid Cloud Console](#)
- [Possible statuses for your custom repository](#)
- [Launching a customized RHEL image to Microsoft Azure](#)

4.6. CREATING CUSTOMIZED IMAGES FOR THE GCP ENVIRONMENT

You can create customized system images by using Insights Images and upload those images to Google Cloud Platform. Then, you can start an instance from the image you uploaded.

Prerequisites

- You have a RHEL subscription.
- You have Organization Administrator permissions.
- You have a valid Google account to share your image.
- You have a Red Hat account. Access [Portal](#).
- You have access to the [Insights Images](#).

Procedure

1. Access [Hybrid Cloud Console](#).
2. Click **Red Hat Insights > RHEL > Inventory > Images**
The Insights Images dashboard appears.
3. Click **Create image**.
The **Images** wizard opens.
4. On the **Image output** page, complete the following steps:
 - a. From the dropdown menu, select the Release: Red Hat Enterprise Linux (RHEL).
 - b. From the **Select target environments** option, select **Google Cloud Platform**.
Click **Next**.
5. On the **Target environment - Google Cloud Platform** page, select a valid account type to share your image with:
 - Google account: A Google account which interacts with Google Cloud, for example: **user@gmail.com**.
 - Service account: An application account, for example: **myapp@appspot.gserviceaccount.com**.

- Google group: A named collection of Google accounts and service accounts, for example: **admins@example.com**.
 - Google workspace domain/Cloud identity domain: A virtual group of all the Google accounts in a named organization. For example, the domain name **mycompany.com**.
6. Enter the account email address or domain name, depending on the type of target environment you chose.
Click **Next**.
 7. On the **Register** page, select one of the registration methods: **Automatically register and enable advanced capabilities** or **Register later**.
If you choose the **Automatically register and enable advanced capabilities** option, customize it further.
 - a. Click the **Show additional connection options** button.
The **Monitor & manage subscriptions and access to Red Hat content** radio button enables the following option:
 - Enable predictive analytics and management capabilities - to provide actionable intelligence about your Red Hat Enterprise Linux environments, helping to identify and address operational and vulnerability risks before an issue results in downtime.
 - Enable remote remediations and system management with automation - Red Hat connector (rhc) enables Red Hat Enterprise Linux hosts to connect to Red Hat Insights to use Red Hat Insights Remediations service.
 - b. Check or uncheck the checkboxes according to your preferences.
 - c. From the dropdown menu, choose an activation key to use for the image. See [Creating an activation key](#).
 - i. **No activation keys found** - If you do not have an activation key, you can choose the default activation key by completing the following step:
 - A. Click the **Create activation key** button. The Select activation key dropdown menu enables the **activation-key-default**. It is a preset key with the basic configuration. You can manage the activation key by accessing [Activation keys](#).
 - d. Click **Next**.
 8. On the **File system configuration** page, select the recommended **Use automatic partitioning** or **Manually configure partitions** for your image file system.
 - a. To configure your partitions manually, click the **Manually configure partitioning** radio button.
The **Configure partitions** section opens, showing the configuration based on Red Hat standards and security guides.
 - b. From the drop-down menu, provide details to configure the partitions:
 - c. For the **Mount point** field, select one mount point type option
You can also add an additional path to the **Mount point**, such as **/tmp**. For example: **/var** as a prefix and **/tmp** as an additional path results in **/var/tmp**.

**NOTE**

Depending on the **Mount point** type you choose, the file system type changes to **xfs**, and so on.

- d. For the **Minimum size** partition field of the file system, enter the desired minimum partition size. In the **Minimum size** drop-down menu, you can use common size units such as **GiB**, **MiB**, or **KiB**. The default unit is **GiB**.
 - e. To add more partitions, click **Add partition** and repeat the steps for each added partition. Click **Next**.
9. Optional: On the **Content** page, complete the following steps to add additional packages to your image:
- a. On the **Additional Red Hat packages** step:
 - i. On the **Available packages** search field, enter the package name and click the **→** button.
 - ii. Click the **>>** button to add all packages shown in the package search results to the **Chosen packages** dual list box. Optionally, you can click the **>** button to add only one selected package at a time.
 - b. On the **Custom repositories** page, click **Repositories**.
The **Custom Repositories** page opens in a new browser tab. Go to the new page.
 - i. Click **Add repositories**. Enter the following information:
 - A. **Name**
 - B. **URL**
 - C. **Restrict architecture**: from the drop-down menu, select an architecture. Either mark all the architectures or select one to restrict to your system architecture to prevent incorrect repositories availability.
 - D. **Restrict OS version**: from the drop-down menu, select an operating system (OS). Either allow all RHEL versions or select a version for your system, to prevent incorrect repositories availability.
 - E. **GPG key**: Either upload a file with a GPG key or paste the URL of an existing GPG key.

**NOTE**

If you do not provide the GPG key for a repository, your system cannot perform the GPG key verification for signed packages in a repository.

- F. Click **Save** to validate the repository status.

- c. Return to the **Create image** dashboard and click **Next**.

10. Optional: On the **Details** page, enter a name for the image. Each image has a unique Universally Unique Identifier (UUID). Click **Next**.

11. On the **Review** page, verify the image details about the image creation and click **Create image**. The system verifies the build manifest of the image. After it reaches 100%, the image is added to the build queue.

Insights Images starts to compose a RHEL image for the **x86_64** architecture. After the image is ready, you can see it in the **Inventory**.

Verification

- Verify that on the dashboard, you can see details such as:
 - **Image name**
 - The **creation or update** date
 - Image OS **Release**
 - The cloud **Target** environment
 - The image creation **Status**
 - The **Instance** details.

Additional resources

- The [Possible statuses for your custom repository](#) section.

4.7. COPYING THE GCE IMAGE TO YOUR PROJECT GROUP

After the image is built, uploaded and the cloud registration process status is marked as Ready, you can create a Virtual Machine (VM) instance using the GCE image.

Prerequisites

- The universally unique identifier (UUID) of the image you created.
- Access to the Image-builder service API endpoint.
- Access to the [Google Cloud Shell](#) from your browser.

Procedure

1. From the Images dashboard, copy the **UUID** image of the image you created.
2. Access [/composes/{composeId}](#) API endpoint.
3. Click the **Try it Out** button to activate the **composeId** string path.
4. Enter the **UUID** into the **composes/{composeId}** field in the API endpoint.
5. Click **Execute**. The API endpoint generates a response in the **Response body**, for example:

```
{
  "image_status": {
    "status": "success",
    "upload_status": {
```

```

    "options": {
      "image_name": "composer-api-03f0e19c-0050-4c8a-a69e-88790219b086",
      "project_id": "red-hat-image-builder"
    },
    "status": "success",
    "type": "gcp"
  }
}
}

```

- From the **Response body** field, copy the *image_name* and *project_id* to access the image from the Google Cloud Platform environment. From the **Response body**:

```

"image_name": "composer-api-03f0e19c-0050-4c8a-a69e-88790219b086",
"project_id": "red-hat-image-builder"

```

- From your browser, access [Google Cloud Shell](#).
- Set your Google Cloud Platform **Project ID** as the default GCP project. You can find the Product ID of your project by accessing the [Google Cloud Platform dashboard](#).

```
$ gcloud config set project PROJECT_ID
```

- In the **Authorize Cloud Shell** window prompt, click **Authorize** to allow this and future calls that require your credentials.
- Copy the image to your project by using the gcloud command:

```
$ gcloud compute images create MY_IMAGE_NAME \
  --source-image-project red-hat-image-builder \
  --source-image IMAGE_NAME
```

Where:

- MY_IMAGE_NAME* is the name you give to your instance;
- red-hat-image-builder is the *project_id* generated by **Response body**;
- IMAGE_NAME* is the *image_name* generated by **Response body**;

Verification

Confirm that the image has been successfully copied to your project:

- Using the Google Cloud Platform UI, by accessing the [Compute Engine / Images](#) section.
- Using the **gcloud** tool, by running the command in [Google Cloud Shell](#):

```
$ gcloud compute images list --no-standard-images
```

Additional resources

- [Google Cloud Shell documentation](#)

4.8. CREATING CUSTOMIZED RHEL VMDK SYSTEM IMAGES

With Insights Images, you can create customized system images in the Open virtualization format (**.ova**) or in the Virtual disk (**.vmdk**) format. You can upload these images to VMware vSphere.

You can import the Virtual disk (**.vmdk**) format only with the **govc** client. As for the Open virtualization format (**.ova**), you can import it by using both the vSphere GUI and **govc** clients.

The Open virtualization format (**.ova**) is a **.vmdk** image with additional metadata about the virtual hardware, when you import to vSphere, it creates a VM. After importing the **.ova** image into vSphere, you can configure the VM with any additional hardware, such as network, disks, and CD-ROM.



NOTE

The **.vmdk** images are available for 6 hours and expire after that. Ensure to download the image to avoid losing it.

Procedure

1. Access [Hybrid Cloud Console](#).
2. Click **Red Hat Insights > RHEL > Inventory > Images**
The Insights Images dashboard appears.
3. Click **Create image**.
The **Images** wizard opens.
4. On the **Image output** page, complete the following steps:
 - a. From the **Release** list, select the Release that you want to use: for example, choose Red Hat Enterprise Linux (RHEL).
 - b. From the **Select target environments** option, select **VMware vSphere**.
 - c. Select one of the options:
 - Open virtualization format (**.ova**)
 - Virtual disk (**.vmdk**) format
Click **Next**.
5. On the **Register** page, select one of the registration methods: **Automatically register and enable advanced capabilities** or **Register later**.
If you choose the **Automatically register and enable advanced capabilities** option, customize it further.
 - a. Click the **Show additional connection options** button.
The **Monitor & manage subscriptions and access to Red Hat content** button enables the following option:
 - Enable predictive analytics and management capabilities - to provide actionable intelligence about your Red Hat Enterprise Linux environments, helping to identify and address operational and vulnerability risks before an issue results in downtime.

- Enable remote remediations and system management with automation - Red Hat connector (rhc) enables Red Hat Enterprise Linux hosts to connect to Red Hat Insights to use Red Hat Insights Remediations service.
- b. Check or uncheck the checkboxes according to your preferences.
 - c. From the dropdown menu, choose an activation key to use for the image. See [Creating an activation key](#).
 - i. **No activation keys found**- If you do not have an activation key, you can choose the default activation key by completing the following step:
 - A. Click the **Create activation key** button. The Select activation key dropdown menu enables the **activation-key-default**. It is a preset key with the basic configuration. You can manage the activation key by accessing [Activation keys](#).
 - d. Click **Next**.
6. On the **File system configuration** page, select the recommended **Use automatic partitioning** or **Manually configure partitions** for your image file system.
 - a. To configure your partitions manually, click the **Manually configure partitioning** radio button.
The **Configure partitions** section opens, showing the configuration based on Red Hat standards and security guides.
 - b. From the drop-down menu, provide details to configure the partitions:
 - c. For the **Mount point** field, select one mount point type option
You can also add an additional path to the **Mount point**, such as **/tmp**. For example: **/var** as a prefix and **/tmp** as an additional path results in **/var/tmp**.



NOTE

Depending on the **Mount point** type you choose, the file system type changes to **xfs**, and so on.

- d. For the **Minimum size** partition field of the file system, enter the desired minimum partition size. In the **Minimum size** drop-down menu, you can use common size units such as **GiB**, **MiB**, or **KiB**. The default unit is **GiB**.
 - e. To add more partitions, click **Add partition** and repeat the steps for each added partition. Click **Next**.
7. Optional: On the **Content** page, complete the following steps to add additional packages to your image:
 - a. On the **Additional Red Hat packages** step:
 - i. On the **Available packages** search field, enter the package name and click the **→** button.
 - ii. Click the **>>** button to add all packages shown in the package search results to the **Chosen packages** dual list box. Optionally, you can click the **>** button to add only one selected package at a time.
 - b. On the **Custom repositories** page, click **Repositories**.

The **Custom Repositories** page opens in a new browser tab. Go to the new page.

i. Click **Add repositories**. Enter the following information:

A. **Name**

B. **URL**

C. **Restrict architecture**: from the drop-down menu, select an architecture. Either mark all the architectures or select one to restrict to your system architecture to prevent incorrect repositories availability.

D. **Restrict OS version**: from the drop-down menu, select an operating system (OS). Either allow all RHEL versions or select a version for your system, to prevent incorrect repositories availability.

E. **GPG key**: Either upload a file with a GPG key or paste the URL of an existing GPG key.



NOTE

If you do not provide the GPG key for a repository, your system cannot perform the GPG key verification for signed packages in a repository.

F. Click **Save** to validate the repository status.

c. Return to the **Create image** dashboard and click **Next**.

8. Optional: On the **Details** page, enter a name for the image. Each image has a unique Universally Unique Identifier (UUID). Click **Next**.

9. On the **Review** page, verify the image details about the image creation and click **Create image**. The system verifies the build manifest of the image. After it reaches 100%, the image is added to the build queue.

Insights Images starts to compose a RHEL image for the **x86_64** architecture. After the image is ready, you can see it in the **Inventory**.

Additional resource

- [Creating a new image from an existing build](#)

4.9. CREATING CUSTOMIZED RHEL GUEST SYSTEM IMAGES

Complete the following steps to create customized RHEL guest **.qcow2** images by using Insights Images.

Prerequisites

- You have a RHEL subscription.
- You have Organization Administrator permissions.

Procedure

1. Access [Hybrid Cloud Console](#).
2. Click **Red Hat Insights > RHEL > Inventory > Images**
The Insights Images dashboard appears.
3. Click **Create image**.
The **Images** wizard opens.
4. On the Image output page, complete the following steps:
 - a. From the **Releases** list, select the release of Red Hat Enterprise Linux (RHEL) that you want to use to create the image.
 - b. From the **Architecture** list, select the architecture that you want to use.
 - c. From the **Select target environments** options, select **Virtualization - Guest image (.qcow2)**.
5. Click **Next**.
6. On the **Register** page, select one of the registration methods: **Automatically register and enable advanced capabilities** or **Register later**.
If you choose the **Automatically register and enable advanced capabilities** option, customize it further.
 - a. Click the **Show additional connection options** button.
The **Monitor & manage subscriptions and access to Red Hat content** radio button enables the following option:
 - Enable predictive analytics and management capabilities - to provide actionable intelligence about your Red Hat Enterprise Linux environments, helping to identify and address operational and vulnerability risks before an issue results in downtime.
 - Enable remote remediations and system management with automation - Red Hat connector (rhc) enables Red Hat Enterprise Linux hosts to connect to Red Hat Insights to use Red Hat Insights Remediations service.
 - b. Check or uncheck the checkboxes according to your preferences.
 - c. From the dropdown menu, choose an activation key to use for the image. See [Creating an activation key](#).
 - i. **No activation keys found** - If you do not have an activation key, you can choose the default activation key by completing the following step:
 - A. Click the **Create activation key** button. The Select activation key dropdown menu enables the **activation-key-default**. It is a preset key with the basic configuration. You can manage the activation key by accessing [Activation keys](#).
 - d. Click **Next**.
7. On the **File system configuration** page, select the recommended **Use automatic partitioning** or **Manually configure partitions** for your image file system.
 - a. To configure your partitions manually, click the **Manually configure partitioning** radio button.
The **Configure partitions** section opens, showing the configuration based on Red Hat standards and security guides.

- b. From the drop-down menu, provide details to configure the partitions:
- c. For the **Mount point** field, select one mount point type option
You can also add an additional path to the **Mount point**, such as **/tmp**. For example: **/var** as a prefix and **/tmp** as an additional path results in **/var/tmp**.

**NOTE**

Depending on the **Mount point** type you choose, the file system type changes to **xfs**, and so on.

- d. For the **Minimum size** partition field of the file system, enter the desired minimum partition size. In the **Minimum size** drop-down menu, you can use common size units such as **GiB**, **MiB**, or **KiB**. The default unit is **GiB**.
 - e. To add more partitions, click **Add partition** and repeat the steps for each added partition. Click **Next**.
8. Optional: On the **Content** page, complete the following steps to add additional packages to your image:
- a. On the **Additional Red Hat packages** step:
 - i. On the **Available packages** search field, enter the package name and click the **→** button.
 - ii. Click the **>>** button to add all packages shown in the package search results to the **Chosen packages** dual list box. Optionally, you can click the **>** button to add only one selected package at a time.
 - b. On the **Custom repositories** page, click **Repositories**.
The **Custom Repositories** page opens in a new browser tab. Go to the new page.
 - i. Click **Add repositories**. Enter the following information:
 - A. **Name**
 - B. **URL**
 - C. **Restrict architecture**: from the drop-down menu, select an architecture. Either mark all the architectures or select one to restrict to your system architecture to prevent incorrect repositories availability.
 - D. **Restrict OS version**: from the drop-down menu, select an operating system (OS). Either allow all RHEL versions or select a version for your system, to prevent incorrect repositories availability.
 - E. **GPG key**: Either upload a file with a GPG key or paste the URL of an existing GPG key.

**NOTE**

If you do not provide the GPG key for a repository, your system cannot perform the GPG key verification for signed packages in a repository.

- F. Click **Save** to validate the repository status.
- c. Return to the **Create image** dashboard and click **Next**.
9. Optional: On the **Name image** page, enter a name for the image. Each image has a unique Universally Unique Identifier (UUID). Click **Next**.
10. On the **Review** page, verify the image details about the image creation and click **Create image**. The system verifies the build manifest of the image. After it reaches 100%, the image is added to the build queue.



NOTE

The **.qcow2** images are available for 6 hours and expire after that. Ensure to download the image to avoid losing it.

4.10. CREATING CUSTOMIZED RHEL ISO SYSTEM IMAGES

Complete the following steps to create customized RHEL ISO images by using the Insights Images.

Prerequisites

- You have a RHEL subscription.
- You have Organization Administrator permissions.

Procedure

1. Access [Hybrid Cloud Console](#).
2. Click **Red Hat Insights > RHEL > Inventory > Images**
The Insights Images dashboard appears.
3. Click **Create image**.
The **Create image** wizard opens.
4. On the **Image output** page, select the release. Then, click **Next**
 - a. From the **Release** list, select the release that you want to use.
 - b. From the **Architecture** list, select the architecture that you want to use.
 - c. From the **Select target environments** option, select **Bare metal - Installer (.iso)**
 - d. Click **Next**.
5. On the **Register** page, select one of the registration methods: **Automatically register and enable advanced capabilities** or **Register later**.
If you choose the **Automatically register and enable advanced capabilities** option, customize it further.
 - a. Click the **Show additional connection options** button.
The **Monitor & manage subscriptions and access to Red Hat content** radio button enables the following option:

- Enable predictive analytics and management capabilities - to provide actionable intelligence about your Red Hat Enterprise Linux environments, helping to identify and address operational and vulnerability risks before an issue results in downtime.
 - Enable remote remediations and system management with automation - Red Hat connector (rhc) enables Red Hat Enterprise Linux hosts to connect to Red Hat Insights to use Red Hat Insights Remediations service.
- b. Check or uncheck the checkboxes according to your preferences.
 - c. From the dropdown menu, choose an activation key to use for the image. See [Creating an activation key](#).
 - i. **No activation keys found** - If you do not have an activation key, you can choose the default activation key by completing the following step:
 - A. Click the **Create activation key** button. The Select activation key dropdown menu enables the **activation-key-default**. It is a preset key with the basic configuration. You can manage the activation key by accessing [Activation keys](#).
 - d. Click **Next**.
6. On the **File system configuration** page, select the recommended **Use automatic partitioning**. The Installer (**.iso**) image type does not accept customized partitions. If you try to manually configure the filesystem customization, it will not be applied to any system built by the Installer (**.iso**) image.
Click **Next**.
 7. Optional: On the **Content** page, complete the following steps to add additional packages to your image:
 - a. On the **Additional Red Hat packages** step:
 - i. On the **Available packages** search field, enter the package name and click the **→** button.
 - ii. Click the **>>** button to add all packages shown in the package search results to the **Chosen packages** dual list box. Optionally, you can click the **>** button to add only one selected package at a time.
 - b. On the **Custom repositories** page, click **Repositories**.
The **Custom Repositories** page opens in a new browser tab. Go to the new page.
 - i. Click **Add repositories**. Enter the following information:
 - A. **Name**
 - B. **URL**
 - C. **Restrict architecture**: from the drop-down menu, select an architecture. Either mark all the architectures or select one to restrict to your system architecture to prevent incorrect repositories availability.
 - D. **Restrict OS version**: from the drop-down menu, select an operating system (OS). Either allow all RHEL versions or select a version for your system, to prevent incorrect repositories availability.

- E. **GPG key:** Either upload a file with a GPG key or paste the URL of an existing GPG key.



NOTE

If you do not provide the GPG key for a repository, your system cannot perform the GPG key verification for signed packages in a repository.

- F. Click **Save** to validate the repository status.

- c. Return to the **Create image** dashboard and click **Next**.
8. Optional: On the **Details** page, enter a name for the image. Each image has a unique Universally Unique Identifier (UUID). Click **Next**.
9. On the **Review** page, verify the image details about the image creation and click **Create image**. The system verifies the build manifest of the image. After it reaches 100%, the image is added to the build queue.


Insights Images starts to compose a RHEL image for the architecture that you selected. After the image is ready, you can see it in the **Images** dashboard.

Additional resources

- The [Possible statuses for your custom repository](#) section.

4.11. CREATING CUSTOMIZED IMAGES FOR THE OCI ENVIRONMENT

You can create customized system images by using Insights Images and upload those images to Oracle Cloud Infrastructure (OCI). Then, you can run an instance from the **.qcow2** image you uploaded to your OCI bucket.



NOTE

Creating a custom image and pushing it to Oracle Cloud Infrastructure environments is available in the **Preview** mode.

Prerequisites

- You have a RHEL subscription.
- You have Organization Administrator permissions.
- You have an [Oracle Cloud](#) account.
- You must be granted security access in an **OCI policy**.
- You have a Red Hat account. Access [Portal](#).
- You have access to the [Insights Images](#).

Procedure

1. Log in to the [Hybrid Cloud Console](#) and turn on **Preview** mode by switching the Preview toggle to **On** in the menu bar.
2. Access [Hybrid Cloud Console](#) and log in.
3. Click **Red Hat Insights > RHEL > Inventory > Images**
The Insights Images dashboard appears.
4. Click **Create image**.
The **Images** wizard opens.
5. On the **Image output** page, complete the following steps:
 - a. From the dropdown menu, select the Release: Red Hat Enterprise Linux (RHEL).
 - b. From the **Select target environments** option, select **Oracle Cloud Infrastructure**.
 - c. Click **Next**.
6. On the **Target environment - Oracle Cloud Infrastructure** page, enter the following mandatory details.
 - a. User OCID: you can find it in the OCI console user details page.
 - b. Private key.
7. Click **Next**.
8. On the **Register** page, select one of the registration methods:
 - **Automatically register and enable advanced capabilities**
 - **Register later**.
If you choose the **Automatically register and enable advanced capabilities** option, customize it further.
 - a. Click **Show additional connection options**.
The **Monitor & manage subscriptions and access to Red Hat content** radio button enables the following option:
 - Enable predictive analytics and management capabilities - provides actionable intelligence about your Red Hat Enterprise Linux environments. This helps to identify and address operational and vulnerability risks before an issue results in downtime.
 - Enable remote remediations and system management with automation - Red Hat connector (rhc) enables RHEL hosts to connect to Red Hat Insights to use Red Hat Insights Remediations service.
 - b. Select the checkboxes according to your preferences.
 - c. From the dropdown menu, choose an activation key to use for the image. See [Creating an activation key](#).
 - i. **No activation keys found** - If you do not have an activation key, you can choose the default activation key by completing the following step:
 - A. Click the **Create activation key** button. The **Select activation key** dropdown

- A. Click the **Create activation key** button. The **Select activation key** dropdown menu enables the **activation-key-default**. It is a preset key with the basic configuration. You can manage the activation key by accessing [Activation keys](#).
 - d. Click **Next**.
9. On the **File system configuration** page, select the recommended **Use automatic partitioning** or **Manually configure partitions** for your image file system.
- a. To configure your partitions manually, click the **Manually configure partitioning** radio button.
The **Configure partitions** section opens and shows the configuration based on Red Hat standards and security guides.
 - b. From the drop-down menu, provide details to configure the partitions:
 - c. For the **Mount point** field, select one mount point type option.
You can also add an additional path to the **Mount point**, such as **/tmp**. For example: **/var** as a prefix and **/tmp** as an additional path results in **/var/tmp**.

**NOTE**

Depending on the **Mount point** type you choose, the file system type changes accordingly.

- d. For the **Minimum size** partition field of the file system, configure the minimum partition size.
In the **Minimum size** drop-down menu, you can use common size units such as **GiB**, **MiB**, or **KiB**. The default unit is **GiB**.
 - e. To add more partitions, click **Add partition** and repeat the steps for each added partition. Click **Next**.
10. Optional: On the **Content** page, complete the following steps to add additional packages to your image:
- a. From the **Additional Red Hat packages** step:
 - i. On the **Available packages** search field, enter the package name and click the **→** button.
 - ii. Click **>>** to add all packages shown in the package search results to the **Chosen packages** dual list box. Alternatively, you can click the **>** button to add only one selected package at a time.
 - b. On the **Custom repositories** page, click **Repositories**.
The **Custom Repositories** page opens in a new browser tab. Go to the new page.
 - i. Click **Add repositories** and enter the following information:
 - A. **Name**
 - B. **URL**
 - C. **Restrict architecture**: from the drop-down menu, select an architecture. Either mark all the architectures or select one for your system to prevent incorrect repositories availability.

- D. **Restrict OS version:** from the drop-down menu, select an operating system (OS). Either allow all RHEL versions or select a version for your system, to prevent incorrect repositories availability.
- E. **GPG key:** Either upload a file with a GPG key or paste the URL of an existing GPG key.

**NOTE**

Without a GPG key, your system cannot perform the verification for signed packages.

- F. Click **Save** to validate the repository status.

- c. Return to the **Create image** dashboard and click **Next**.

11. Optional: On the **Details** page, enter a name for the image. Each image has a unique Universally Unique Identifier (UUID).
12. Click **Next**.
13. On the **Review** page, verify the image details about the image creation.
14. Click **Create image**.

The system verifies the build manifest of the image. After it reaches 100%, the image transfers to the build queue.


Insights Images starts to compose a RHEL image for the **x86_64** architecture. After the image is ready, you can see it in the **Insights Images dashboard**.

Next step

- Import and run the image in the OCI environment. See [Importing and running QCOW2 images on OCI](#).

4.12. CREATING A NEW IMAGE FROM AN EXISTING BUILD

You can create a new image from an existing customized RHEL image by using Insights Images. The Insights Images re-creates the exact image, with a different UUID, which you can use to identify the image in the Hybrid Cloud Console. The new image also fetches package updates and refreshes the content with those updates. You can customize this new image to fit your requirements.

**NOTE**


You can re-create images from failed builds.

Prerequisites

- You created an AWS image with Insights Images.

Procedure

1. From the **Images** dashboard, select the image from which you want to create your customized image.
2. Click the **Node options** menu (☰) and select **Re-create image**. The **Create image** wizard opens.

**NOTE**

If the image status is **Expired**, click the **Re-create image** button.

- a. Optional: You can customize the new image by using the Navigation panel to open a step and making changes. Click **Next**.
- b. On the **Review** page, click **Create image**.

The Insights Images dashboard opens. The image build starts to re-create the image and lists the following information:

- **Image name**
- **UUID**
- Cloud target environment
- Image operating system release
- Status of the image creation

Verification

- From the **Status** column, check if the image is **Ready**.
- Optional: Click **Image details** to display additional information about the re-created image.

4.13. SHARING AWS IMAGES TO OTHER REGIONS


You can share an existing AWS image to a new region. Sharing the image configures it for the new regions to run on your AWS account. After configuring new regions, all these regions launch with the same configuration as the original AWS image.

Prerequisites

- You created an AWS image.

Procedure

1. From the **Images** table, select the image you want to share with other regions.
2. From the Node options menu (☰), select **Share to new region**. The **Share to new region** wizard opens.
3. From the **Select region** dropdown menu, select the region to share the image. You can choose more than one region to share your image with.
4. Click **Share**.
Your image is built, uploaded to AWS, and shared to the regions you selected.

**NOTE**

The shared image expires in 14 days.

5. To ensure that you can access the image permanently, copy the Red Hat image to your own AWS account.

4.14. DOWNLOADING THE JSON COMPOSE REQUEST

If you download the **.json** compose request of your image, you can use the image builder **API** to automate your image building tasks, such as:

- Customizing the image with extra packages
- Customizing the partition layout
- Embedding an activation key.

Prerequisites

- You created an image with Insights Images.

Procedure

1. From the **Images** table, select the image that you want to download as a **.json** compose request.
2. Click the **Node options** () menu and select **Download compose request (.json)**.
The **.json** compose request is now saved to your host server. To use the image builder API, see [Using hosted image builder via its API](#) .

CHAPTER 5. LAUNCHING CUSTOMIZED RHEL IMAGES TO THE CLOUD PLATFORMS WITH INSIGHTS IMAGE BUILDER

5.1. LAUNCHING A CUSTOMIZED RHEL IMAGE ON AWS

You can launch a customized RHEL image on the AWS cloud environment.

Prerequisites

- You have a RHEL subscription.
- You have an [AWS account created](#).
- You successfully built a customized RHEL image and [shared it with the region](#) you want to launch the new instance in.
- The customized RHEL image you built was shared with the same AWS integration account.
- You added an [AWS integration account](#) to the Hybrid Cloud Console.
- You have the "Launch on AWS User" role assigned. See [how to assign a role to a user](#) .

Procedure

1. Access [Hybrid Cloud Console](#).
2. Click **Red Hat Insights > RHEL > Inventory > Images**
3. Find an image you want to launch in the public cloud environment and click **Launch** in the **Instance** column. The **Launch** wizard opens.
4. On the **Account and customization** page, complete the following steps:
 - a. From the **Select account** drop-down menu, select the account you want to use.
 - b. From the **Select region** drop-down menu, select the region to run the instance.
 - c. Optionally: From the **Select template** drop-down menu, select the template you want to use.
If you do not specify the template, you launch the image under the default security group. Ensure that the default security group allows SSH traffic.
 - d. From the **Select instance type** drop-down menu, select the instance type configuration.
 - e. In the **Count** field, select the number of images you want to launch. Click **Next**.
The wizard notifies you if you try to launch too many images. Make sure you have enough resources in your AWS account.



NOTE

You must have the default Virtual Private Cloud (VPC) and Security Group on your AWS account. If you do not have them, contact the AWS support to re-create them.

5. On the **SSH key authentication** page, select one of the options:
 - a. **Select existing SSH public key.** From the **Select public key** drop-down menu, add an existing SSH public key.
 - b. **Add and save a new SSH public key** Enter a name for your new SSH public key and drag or upload a new SSH public key file. Click **Next**.
6. On the **Review** page, review the details about the image launch process and click **Launch**.

Verification

1. The **Launch** wizard shows the green checkmark with a message **System launched successfully**.
2. To verify the instance is running, copy the **ssh** command displayed on the screen to your terminal and connect to the instance.

To stop the running instance, see the AWS console documentation.

5.2. LAUNCHING A CUSTOMIZED RHEL IMAGE ON MICROSOFT AZURE

Prerequisites

- You have a RHEL subscription.
- You have a [Microsoft Azure account created](#).
- You successfully built a customized RHEL image.
- The customized RHEL image you built was shared with the same Microsoft Azure integration account.
- You added a [Microsoft Azure integration account](#) to the Hybrid Cloud Console.
- You have the "Launch on Azure User" role assigned. See [how to assign a role to a user](#) .

Procedure

1. Access [Hybrid Cloud Console](#).
2. Click **Red Hat Insights > RHEL > Inventory > Images**
3. Find an image you want to launch in the public cloud environment and click **Launch** in the **Instance** column. The **Launch** wizard opens.
4. On the **Account and customization** page, complete the following steps:
 - a. From the **Select account** drop-down menu, select the account you want to use.
 - b. From the **Azure resource group** drop-down menu, select the resource group in which you want to run your instance.
This creates the resources in the same region that this resource group is located. You can leave this field empty to run the instance in the same resource group as the image.
 - c. From the **Select instance size** drop-down menu, select the instance type configuration.


- d. In the **Count** field, select the number of images you want to launch. Click **Next**.
The wizard notifies you if you try to launch too many images. Make sure you have enough quotas in your Microsoft Azure subscription when you are launching a large set of images.
5. On the **SSH key authentication** page, choose to use an existing SSH key or add a new SSH key:

To select an existing SSH public key, follow the steps

- a. From the **Select public key** drop-down menu, choose an existing SSH public key.
- b. Click **Next**.

To Add and save a new SSH public key, follow the steps

- a. In the **Name** field, enter a name for your new SSH public key.
- b. In the SSH public key, drag or upload a new SSH public key file.
- c. Click **Next**.



NOTE

Microsoft Azure does not support the **ed25519** SSH keys.

6. On the **Review** page, review the details about the image launch process and click **Launch**.

The launching process takes a few minutes to start an instance on the Microsoft Azure cloud platform.

Verification

1. The **Launch** wizard shows the green checkmark with a message **System launched successfully**.
2. To verify the instance is running, copy the **ssh** command displayed on the screen to your terminal and connect to the instance.

5.3. LAUNCHING A CUSTOMIZED RHEL IMAGE ON THE GOOGLE CLOUD PLATFORM

Prerequisites

- You have a RHEL subscription.
- You have a [Google Cloud Platform \(GCP\) project created](#) .
- You successfully built a customized RHEL image.
- The customized RHEL image you built is shared with the same GCP project.
- You have the "Launch on Google User" role assigned. See [how to assign a role to a user](#) .
- You added a [GCP project](#) to the Hybrid Cloud Console.
- You have enabled the following APIs in your GCP project:

- Compute Engine API;
- Identity and Access Management API.

Procedure

1. Access [Hybrid Cloud Console](#).
2. Click **Red Hat Insights > RHEL > Inventory > Images**
3. Find the image you want to launch in the public cloud environment and click **Launch** in the **Instance** column. The **Launch** wizard opens.
4. On the **Account and customization** page, complete the following steps:
 - a. From the **Select account** drop-down menu, select the account you want to use.
 - b. Optionally: From the **Select template** drop-down menu, select the template you want to use.
If you do not specify the template, you launch the image to the default Virtual Private Cloud (VPC) with its firewall rules.
 - c. From the **Select machine type** drop-down menu, select the machine configuration.
 - d. In the **Count** field, select the number of images you want to launch and click **Next**.
5. On the **SSH key authentication** page, select one of the options:
 - a. **Select existing SSH public key.** From the **Select public key** drop-down menu, choose an existing SSH public key. Click **Next**.
 - b. **Add and save a new SSH public key** Enter a name for your new SSH public key and drag or upload a new SSH public key file. Click **Next**.
6. On the **Review** page, review the details about the image launch process and click **Launch**.

Verification

1. The **Launch** wizard shows the green checkmark with a message **System launched successfully**.
2. To verify the instance is running, copy the **ssh** command displayed on the screen to your terminal and connect to the instance.

5.4. CONFIGURING LAUNCH NOTIFICATIONS

You can configure notifications for various events of the launching process. For information on how to configure notifications in the Red Hat Hybrid Cloud Console, see [Configuring notifications on the Red Hat Hybrid Cloud Console](#).

Launch events

Launch failed

If an image launch fails, a notification is sent.

Launch completed

If an image launch is successful, a notification is sent.

Note, if you choose email notifications, these notifications contain detailed information about the event. For example, if the **Launch completed** event is triggered, the email notification contains the list of the launched instances.

CHAPTER 6. DEPLOYING YOUR CUSTOMIZED IMAGES

After creating customized images for the VMWare vSphere private cloud, you can deploy the images to VMware vSphere. For the Guest image (**.qcow2**), and Installer (**.iso**), you can then download these images and deploy them to virtual machines.

6.1. UPLOADING VMDK IMAGES AND CREATING A RHEL VIRTUAL MACHINE IN VSPHERE

After creating your image, you can deploy it to **VMware vSphere** by using the CLI. Then, you can create a VM and login into it.

Prerequisites

- You configured the **govc** VMware CLI tool client.
 - To use the **govc** VMware CLI tool client, you must set the following values in the environment:

```
GOVC_URL
GOVC_DATACENTER
GOVC_FOLDER
GOVC_DATASTORE
GOVC_RESOURCE_POOL
GOVC_NETWORK
```

Procedure

1. Access the directory where you downloaded your **.vmdk** image.
2. Create a file named **metadata.yaml**. Add the following information to this file:

```
instance-id: cloud-vm
local-hostname: vmname
```

3. Create a file named **userdata.yaml**. Add the following information to the file:

```
#cloud-config
users:
- name: admin
  sudo: "ALL=(ALL) NOPASSWD:ALL"
  ssh_authorized_keys:
  - ssh-rsa AAA...fhHQ== your.email@example.com
```

- **ssh_authorized_keys** is your SSH public key. You can find your SSH public key in **~/.ssh/id_rsa.pub**.
4. Export the **metadata.yaml** and **userdata.yaml** files to the environment, compressed with **gzip**, encoded in **base64** as follows. They will be used in further steps.

```
export METADATA=$(gzip -c9 <metadata.yaml | { base64 -w0 2>/dev/null || base64; }) \
USERDATA=$(gzip -c9 <userdata.yaml | { base64 -w0 2>/dev/null || base64; })
```

5. Launch the image on vSphere with the **metadata.yaml** and **userdata.yaml** files:

a. Import the **.vmdk** image in to vSphere:

```
$ govc import.vmdk ./composer-api.vmdk foldername
```

b. Create the VM in vSphere without powering it on:

```
govc vm.create \  
-net.adapter=vmxnet3 \  
-m=4096 -c=2 -g=rhel8_64Guest \  
-firmware=bios -disk="foldername/composer-api.vmdk" \  
-disk.controller=ide -on=false \  
vmname
```

c. Change the VM to add **ExtraConfig** variables, the **cloud-init** config:

```
govc vm.change -vm vmname \  
-e guestinfo.metadata="{METADATA}" \  
-e guestinfo.metadata.encoding="gzip+base64" \  
-e guestinfo.userdata="{USERDATA}" \  
-e guestinfo.userdata.encoding="gzip+base64"
```

d. Power-on the VM:

```
govc vm.power -on vmname
```

e. Retrieve the VM IP address:

```
HOST=$(govc vm.ip vmname)
```

f. Use SSH to log in to the VM, using the user-data specified in **cloud-init** file configuration:

```
$ ssh admin@HOST
```

Additional resources

- The [govc](#) documentation
- The [VMware - cloud init 22.2](#) documentation

6.2. DEPLOYING OVA VMDK IMAGES TO THE VSPHERE GUI

After creating your **.vmdk** image in the **open virtualization** format (**.ova**), you can deploy it to **VMware vSphere** by using the vSphere GUI client. It will create a VM which can be customized further before booting.

Prerequisite

- You logged in to the vSphere UI in a browser.
- You downloaded your (**.ova**) image.

Procedure

1. In the vSphere Client, from the **Actions** menu, select **Deploy OVF Template**.
2. On the **Deploy OVF Template** page, complete the settings for each configuration option and click **Next**.
3. Click **Finish**. The **.ova** image starts to be deployed.
After the image deployment is complete, you have a new virtual machine (VM) from the **.ova** image.
4. In the deployed image page, perform the following steps:
 - a. From the **Actions** menu, select **Edit Setting**.
 - b. On the **Virtual Hardware** tab, configure resources such as CPU, memory, add a new network adapter, between others of your choice.
 - i. On the **CD/DVD drive 1** option, attach a CD or DVD Drive that contains a **cloud-init.iso**, to provision a user on startup.
The VM is now ready to boot with the username and password from the **cloud-init.iso** file.

Additional resources

- [Deploy an OVF or OVA Template](#)
- The [govc](#) documentation
- The [VMware - cloud init 22.2](#) documentation

6.3. CREATING A VIRTUAL MACHINE FROM THE CUSTOMIZED RHEL GUEST SYSTEM IMAGE

You can create a virtual machine (VM) from the **QCOW2** image that you created by using Insights Images.

Prerequisites

- You created and downloaded a **QCOW2** image by using Insights Images.

Procedure

1. Access the directory where you downloaded your **QCOW2** image.
2. Create a file named **meta-data**. Add the following information to this file:

```
instance-id: nocloud
local-hostname: vmname
```

3. Create a file named **user-data**. Add the following information to the file:

```
#cloud-config
user: admin
password: password
```

```
chpasswd: {expire: False}
ssh_pwauth: True
ssh_authorized_keys:
  - ssh-rsa AAA...fhHQ== your.email@example.com
```

- **ssh_authorized_keys** is your SSH public key. You can find your SSH public key in `~/.ssh/id_rsa.pub`.

4. Use the **genisoimage** command to create an ISO image that includes the **user-data** and **meta-data** files.

```
# genisoimage -output cloud-init.iso -volid cidata -joliet -rock user-data meta-data

l: -input-charset not specified, using utf-8 (detected in locale settings)
Total translation table size: 0
Total rockridge attributes bytes: 331
Total directory bytes: 0
Path table size(bytes): 10
Max brk space used 0
183 extents written (0 MB)
```

5. Create a new VM from the KVM Guest Image using the **virt-install** command. Include the ISO image you created on step 4 as an attachment to the VM image.

```
# virt-install \
  --memory 4096 \
  --vcpus 4 \
  --name myvm \
  --disk composer-api.qcow2,device=disk,bus=virtio,format=qcow2 \
  --disk cloud-init.iso,device=cdrom \
  --os-variant rhel1-latest \
  --virt-type kvm \
  --graphics none \
  --import
```

Where,

- `--graphics none` - indicates that it is a headless RHEL Virtual Machine.
- `--vcpus 4` - indicates that it uses 4 virtual CPUs.
- `--memory 4096` - indicates that it uses 4096 MB RAM.

6. The VM installation starts:

```
Starting install...
Connected to domain myvm
...
[ OK ] Started Execute cloud user/final scripts.
[ OK ] Reached target Cloud-init target.

Red Hat Enterprise Linux 1-latest (Ootpa)
Kernel 4.18.0-221.el8.x86_64 on an x86_64
```

Additional resources

- [Creating virtual machines using the command-line interface](#)

6.4. INSTALLING A CUSTOMIZED RHEL ISO SYSTEM IMAGE TO A BARE METAL SYSTEM

You can create a virtual machine (VM) from the ISO image that you created using the Insights image builder.

Prerequisites

- You created and downloaded an ISO image by using Insights image builder.
- A 8 GB USB flash drive.

Procedure

1. Access the directory where you downloaded your ISO image.
2. Place the bootable ISO image file on a USB flash drive.
3. Connect the USB flash drive to the port of the computer you want to boot.
4. Boot the ISO image from the USB flash drive.
5. Perform the steps to install the customized bootable ISO image.
The boot screen shows you the following options:
 - Install Red Hat Enterprise Linux 1-latest
 - Test this media & install Red Hat Enterprise Linux 1-latest

Additional resources

- [Booting the installation](#)

6.5. IMPORTING AND RUNNING QCOW2 IMAGES ON OCI

You can import your customized **.qcow2** image to the Oracle Cloud Infrastructure (OCI). Then, you can launch the customized **.qcow2** image on a virtual machine.

Prerequisites

- You logged in to the [Oracle Cloud](#) UI in a browser.
- You downloaded your **.qcow2** image.
- You have copied the **.qcow2** image **Image Link** URL from Insights **Instance** column, in the Images dashboard.

Procedure

1. In the Oracle Cloud UI dashboard, click **Compute > Custom Images**
2. On the **Custom Images** dashboard, click **Import image**.

3. On the **Import image** window, set the following configuration:
 - a. Select the **Import from an object storage URL** option.
 - b. In the **Object Storage URL** field, paste the URL given by Insights Images into it.
 - c. Choose the **QCOW2** image type.
 - d. Under **Launch mode**, select the **Paravirtualized mode** option.
4. Click **Import Image**.

Once the system finishes importing the image, you can run the customized image in the OCI environment.

PROVIDING FEEDBACK ON RED HAT DOCUMENTATION

We appreciate and prioritize your feedback regarding our documentation. Provide as much detail as possible, so that your request can be quickly addressed.

Prerequisites

- You are logged in to the Red Hat Customer Portal.

Procedure

To provide feedback, perform the following steps:

1. Click the following link: [Create Issue](#).
2. Describe the issue or enhancement in the **Summary** text box.
3. Provide details about the issue or requested enhancement in the **Description** text box.
4. Type your name in the **Reporter** text box.
5. Click the **Create** button.

This action creates a documentation ticket and routes it to the appropriate documentation team. Thank you for taking the time to provide feedback.

OPENING A SUPPORT CASE AT RED HAT SUPPORT

Create a support case from Red Hat Insights at Red Hat Support by performing the following steps:

Prerequisites

- You are logged in to the Red Hat Customer Portal.

Procedure

1. Access the [Red Hat Hybrid Cloud Console](#) :
2. Click **Help ?** and select **Open a support case**.
You are redirected to the **Customer support** page.
3. From the **Get Support** page, select the type of issue that you want to report and click **Continue**.
4. From the **Summarize** page, perform the following steps:
 - a. On the **Summary** field, describe the issue.



NOTE

If **Red Hat Insights** is not auto-selected, you must manually select the product.

- b. From the **Product** dropdown menu, select **Red Hat Insights**.
- c. From the **Version** dropdown menu, select the component you have issues with.
- d. From the **Review** page, click **Submit**.
A support case is created.