



Red Hat Insights 1.0

Configuring Basic Authentication for Red Hat Insights

Legal Notice

Copyright © 2019 Red Hat, Inc.

The text of and illustrations in this document are licensed by Red Hat under a Creative Commons Attribution–Share Alike 3.0 Unported license ("CC-BY-SA"). An explanation of CC-BY-SA is available at

<http://creativecommons.org/licenses/by-sa/3.0/>

. In accordance with CC-BY-SA, if you distribute this document or an adaptation of it, you must provide the URL for the original version.

Red Hat, as the licensor of this document, waives the right to enforce, and agrees not to assert, Section 4d of CC-BY-SA to the fullest extent permitted by applicable law.

Red Hat, Red Hat Enterprise Linux, the Shadowman logo, the Red Hat logo, JBoss, OpenShift, Fedora, the Infinity logo, and RHCE are trademarks of Red Hat, Inc., registered in the United States and other countries.

Linux[®] is the registered trademark of Linus Torvalds in the United States and other countries.

Java[®] is a registered trademark of Oracle and/or its affiliates.

XFS[®] is a trademark of Silicon Graphics International Corp. or its subsidiaries in the United States and/or other countries.

MySQL[®] is a registered trademark of MySQL AB in the United States, the European Union and other countries.

Node.js[®] is an official trademark of Joyent. Red Hat is not formally related to or endorsed by the official Joyent Node.js open source or commercial project.

The OpenStack[®] Word Mark and OpenStack logo are either registered trademarks/service marks or trademarks/service marks of the OpenStack Foundation, in the United States and other countries and are used with the OpenStack Foundation's permission. We are not affiliated with, endorsed or sponsored by the OpenStack Foundation, or the OpenStack community.

All other trademarks are the property of their respective owners.

Abstract

Configure basic authentication in order to use Red Hat Insights on Red Hat Enterprise Linux (RHEL) systems managed by Red Hat Update Infrastructure (RHUI). Providing Feedback: If you have a suggestion for improving this documentation, or have found an error, please submit a Bugzilla report at <http://bugzilla.redhat.com> for the Cloud Software Services (cloud.redhat.com) product, and using the Documentation component.

Table of Contents

CHAPTER 1. BASIC AUTHENTICATION OVERVIEW	3
1.1. WHEN TO USE BASIC AUTHENTICATION	3
1.2. CONFIGURATION REQUIREMENTS FOR BASIC AUTHENTICATION	3
1.3. MORE INFORMATION	3
CHAPTER 2. CONFIGURING BASIC AUTHENTICATION	5

CHAPTER 1. BASIC AUTHENTICATION OVERVIEW

Red Hat Insights can use two types of authentication to validate system access to the Insights services. The default authentication method is through certificates. Certificates are generated when you register a system with Red Hat Subscription Manager (RHSM) or when your system is managed by Red Hat Satellite system management.

An alternative authentication method is through SSO credentials. A valid Red Hat SSO credential is created when you have a valid Red Hat Customer Portal user name. In order to use SSO credentials with Red Hat Insights, you must configure your system to use basic authentication.

1.1. WHEN TO USE BASIC AUTHENTICATION

Certificate-based authentication is the default for Red Hat Insights. You must use basic authentication in any of the following situations:

- Your RHEL system is not registered with Red Hat Subscription Manager (RHSM).
- Your Red Hat Enterprise Linux (RHEL) system is not managed by Red Hat Satellite services.
- Your RHEL system is provisioned through a Red Hat Certified Cloud and Service Provider and is updated by Red Hat Update Infrastructure (RHUI).
- Your RHEL system is from a cloud marketplace provider and not obtained through Red Hat Cloud Access program.



NOTE

If you have valid RHEL subscriptions for your system, you can switch between the default certificate-based authentication for Insights and the basic authentication for Insights. If you are configuring basic authentication on a new RHEL system, you must complete the basic authentication procedures before you can register the Insights client application.

1.2. CONFIGURATION REQUIREMENTS FOR BASIC AUTHENTICATION

When you configure your system to use single sign-on (SSO) credentials for basic authentication instead of the default certificate-based authentication for Red Hat Insights, you provide Red Hat SSO credentials. SSO credentials are a valid Red Hat Customer Portal user name and password.

To configure basic authentication, a plain-text username and password is stored in the configuration file. As a best practice, create a Red Hat Customer Portal account with SSO credentials that are used only for Red Hat Insights basic authentication. This action avoids exposing the SSO credentials of individual users.

1.3. MORE INFORMATION

Authentication error message indicating need to configure basic authentication

When you attempt to register a system that does not have a Red Hat generated certificate, the following error occurs. If you see this error, you must configure your system for basic authentication, which is SSO-based instead of certificate-based.

```
insights-client --register  
Running connection test...
```

```
Connection test config:
=== Begin Certificate Chain Test ===
depth=1
verify error:num=0
verify return:1
depth=0
verify error:num=0
verify return:1
=== End Certificate Chain Test: SUCCESS ===

=== Begin Upload URL Connection Test ===
HTTP Status Code: 401
HTTP Status Text: Unauthorized
HTTP Response Text:
Connection failed
=== End Upload URL Connection Test: FAILURE ===

=== Begin API URL Connection Test ===
HTTP Status Code: 200
HTTP Status Text: OK
HTTP Response Text: lub-dub
Successfully connected to: https://cert-api.access.redhat.com/r/insights/
=== End API URL Connection Test: SUCCESS ===
```

Connectivity tests completed with some errors
See `/var/log/insights-client/insights-client.log` for more details.

CHAPTER 2. CONFIGURING BASIC AUTHENTICATION

Red Hat Insights insights-client configuration is managed in **/etc/insights-client/insights-client.conf**. This file provides a configuration template for setting up basic authentication. The default configuration for certificate-based authentication is as follows:

```
auto_config=TRUE
authmethod=BASIC
username=<your customer portal username>
password=<your customer portal password>
```

Prerequisites

- You have a Red Hat SSO username and SSO password that can be stored in clear text.
- You have read/write permissions in the directory **/etc/insights-client/**.
- The **insights-client** package is installed on your system.

Procedure

1. Use a text editor to open the file **/etc/insights-client/insights-client.conf**
2. Change **auto_config=TRUE** value to **auto_config=FALSE**.
3. Replace **<your customer portal username>** with a Red Hat SSO username.
4. Replace **<your customer portal password>** with a Red Hat SSO password.
5. Save the configuration and exit the editor.
6. Register register the system.

```
# insights-client --register
```