



Red Hat Insights 2020-10

Using Cloud Connector to remediate issues across your Red Hat Satellite infrastructure

A guide to remediating RHEL system issues throughout your Satellite infrastructure from the Red Hat Insights application

Red Hat Insights 2020-10 Using Cloud Connector to remediate issues across your Red Hat Satellite infrastructure

A guide to remediating RHEL system issues throughout your Satellite infrastructure from the Red Hat Insights application

Legal Notice

Copyright © 2020 Red Hat, Inc.

The text of and illustrations in this document are licensed by Red Hat under a Creative Commons Attribution–Share Alike 3.0 Unported license ("CC-BY-SA"). An explanation of CC-BY-SA is available at

<http://creativecommons.org/licenses/by-sa/3.0/>

. In accordance with CC-BY-SA, if you distribute this document or an adaptation of it, you must provide the URL for the original version.

Red Hat, as the licensor of this document, waives the right to enforce, and agrees not to assert, Section 4d of CC-BY-SA to the fullest extent permitted by applicable law.

Red Hat, Red Hat Enterprise Linux, the Shadowman logo, the Red Hat logo, JBoss, OpenShift, Fedora, the Infinity logo, and RHCE are trademarks of Red Hat, Inc., registered in the United States and other countries.

Linux[®] is the registered trademark of Linus Torvalds in the United States and other countries.

Java[®] is a registered trademark of Oracle and/or its affiliates.

XFS[®] is a trademark of Silicon Graphics International Corp. or its subsidiaries in the United States and/or other countries.

MySQL[®] is a registered trademark of MySQL AB in the United States, the European Union and other countries.

Node.js[®] is an official trademark of Joyent. Red Hat is not formally related to or endorsed by the official Joyent Node.js open source or commercial project.

The OpenStack[®] Word Mark and OpenStack logo are either registered trademarks/service marks or trademarks/service marks of the OpenStack Foundation, in the United States and other countries and are used with the OpenStack Foundation's permission. We are not affiliated with, endorsed or sponsored by the OpenStack Foundation, or the OpenStack community.

All other trademarks are the property of their respective owners.

Abstract

This guide is for Red Hat Insights users who want to use Cloud Connector to remediate issues on RHEL systems managed by Red Hat Satellite. Providing Feedback: If you have a suggestion to improve this documentation, or find an error, submit a Bugzilla report at <http://bugzilla.redhat.com>. Select the Cloud Software Services (cloud.redhat.com) product and use the Documentation component.

Table of Contents

PREFACE	3
CHAPTER 1. CONFIGURATION OVERVIEW	4
CHAPTER 2. CONFIGURING YOUR SATELLITE INFRASTRUCTURE TO COMMUNICATE WITH INSIGHTS .	5
2.1. UPLOADING YOUR HOST INVENTORY FROM SATELLITE TO INSIGHTS	5
2.2. INSTALLING THE INSIGHTS CLIENT ON HOSTS MANAGED BY SATELLITE	5
2.3. CONFIGURING CLOUD CONNECTOR ON SATELLITE SERVER	6
2.4. CONFIGURING RED HAT INSIGHTS SYNCHRONIZATION ON SATELLITE	7
CHAPTER 3. REMEDIATING ISSUES ON RHEL SYSTEMS MANAGED BY SATELLITE	9
3.1. USING INSIGHTS TO CREATE A REMEDIATIONS PLAYBOOK	9
3.2. EXECUTING THE REMEDIATIONS PLAYBOOK	9
3.3. USING INSIGHTS TO MONITOR REMEDIATION STATUS	10

PREFACE

Red Hat Insights analyzes Red Hat Enterprise Linux systems and recommends actions to remediate issues on those systems, and helps you create Ansible Playbooks to automate remediations.

If you use Red Hat Satellite to manage your systems, you can upload your host inventory from Satellite to cloud.redhat.com so that Insights can report issues on your Satellite-managed hosts. You can then create and run remediation playbooks to fix issues on hosts across multiple Satellite Servers directly from cloud.redhat.com.

CHAPTER 1. CONFIGURATION OVERVIEW

To remediate issues across your Satellite infrastructure, complete the following steps:

Prerequisites

- Remediations Cloud Connector requires a [Red Hat Smart Management](#) subscription.
- Satellite must be version 6.7 or later.
- You must have permissions to create and execute playbooks from the Red Hat Insights Remediations service.
- Import a Subscription Manifest into Satellite. Only hosts in organizations with a valid Red Hat certificate can be connected to cloud.redhat.com. For more information, see [Importing a Subscription Manifest into Satellite Server](#) in the Red Hat Satellite *Content Management Guide*.
- Register your hosts to Satellite using an activation key to attach Red Hat subscriptions. For more information, see [Registering Hosts](#) in the Red Hat Satellite *Managing Hosts* guide.
- Enable remote execution on your hosts so that Satellite can run remediation playbooks on them. For more information, see [Distributing SSH Keys for Remote Execution](#) in the Red Hat Satellite *Managing Hosts* guide.

Procedure overview

1. [Chapter 2, Configuring your Satellite infrastructure to communicate with Insights](#) . Use the following procedures to configure Satellite and its hosts to communicate with Insights:
 - a. [Section 2.1, "Uploading your host inventory from Satellite to Insights"](#)
 - b. [Section 2.2, "Installing the Insights client on hosts managed by Satellite"](#)
 - c. [Section 2.3, "Configuring Cloud Connector on Satellite Server"](#)
 - d. [Section 2.4, "Configuring Red Hat Insights Synchronization on Satellite"](#)
2. [Chapter 3, Remediating issues on RHEL systems managed by Satellite](#) . Use the following procedures when you need to fix an issue across your Satellite infrastructure:
 - a. [Section 3.1, "Using Insights to create a remediations playbook"](#)
 - b. [Section 3.2, "Executing the remediations playbook"](#)
 - c. [Section 3.3, "Using Insights to monitor remediation status"](#)

CHAPTER 2. CONFIGURING YOUR SATELLITE INFRASTRUCTURE TO COMMUNICATE WITH INSIGHTS

Before you can remediate issues in your Satellite infrastructure, you must connect your hosts to Insights and configure Cloud Connector on Satellite Server.

2.1. UPLOADING YOUR HOST INVENTORY FROM SATELLITE TO INSIGHTS

Use this procedure to upload your host inventory from Red Hat Satellite to Red Hat Insights.

Prerequisites

- Register your hosts to Satellite using an activation key to attach Red Hat subscriptions.

Procedure

1. On Satellite Server, enable the Inventory plug-in. Note that the **--foreman-proxy-plugin-remote-execution-ssh-install-key true** option installs an SSH key for the **root** user on Satellite Server, so that Satellite can use remote execution on itself. This allows all Satellite users with the **create_job_invocation** permission to run commands over SSH as **root** on Satellite Server. If required, you can generate and install this key manually instead of using this option.

- On Satellite Server 6.8 and later, enter the following command:

```
# satellite-installer \  
--enable-foreman-plugin-rh-cloud \  
--foreman-proxy-plugin-remote-execution-ssh-install-key true
```

- On Satellite Server 6.7 and earlier, enter the following command:

```
# satellite-installer \  
--enable-foreman-plugin-inventory-upload \  
--foreman-proxy-plugin-remote-execution-ssh-install-key true \  
--upgrade
```

1. In the Satellite web UI, navigate to **Configure > Inventory Upload** and select your organization.
2. Click **Restart** to upload your host inventory to Red Hat Insights.
Repeat this step for each organization from which you want to upload a host inventory.
3. Optional: Toggle the **Auto upload** switch to the **ON** position to enable Satellite to automatically upload your host inventory once a day. Toggle the **Obfuscate host names** switch to the **ON** position to hide host names that Satellite reports to Red Hat Cloud.
Auto upload and **Obfuscate host names** are global settings. They affect hosts that belong to all organizations.

To verify that the upload was successful, log into <https://cloud.redhat.com/insights/inventory/> and search for your hosts.

2.2. INSTALLING THE INSIGHTS CLIENT ON HOSTS MANAGED BY SATELLITE

Use this procedure to install the Insights client on each of your hosts.

Prerequisites

- Register your hosts to Satellite using an activation key to attach Red Hat subscriptions.

Procedure

1. Install the Insights client:

```
# yum install insights-client
```

2. Register the host to Insights:

```
# insights-client --register
```

Repeat these steps on each host.

Alternatively, you can use the **RedHatInsights.insights-client** Ansible role to install the Insights client and register the hosts. For more information, see [Using Red Hat Insights with Hosts in Satellite](#) in the Red Hat Satellite *Managing Hosts* guide.

2.3. CONFIGURING CLOUD CONNECTOR ON SATELLITE SERVER

Before you can run remediation playbooks on your Satellite infrastructure, you must install Cloud Connector on Satellite Server. Cloud Connector manages the communication between Satellite and the Red Hat Insights service at cloud.redhat.com. Satellite provides an Ansible playbook to automate the configuration of Cloud Connector.

Use this procedure to install and configure Cloud Connector. Create a service user that Cloud Connector will use to trigger remediation jobs on Satellite, then run the Cloud Connector installation playbook. You must repeat this procedure for each Red Hat account managed by Satellite.

Procedure

1. In the Satellite web UI, navigate to **Administer** > **Users** and click **Create User**.
2. Enter a **Username** for the service user.
3. From the **Authorised by** list, select **INTERNAL**.
4. Enter and verify a password for the service user.
5. Click the **Organizations** tab and select all the organizations that are part of the same Red Hat account.
6. Ensure that the **Default on login** field is blank.
7. Click the **Roles** tab and select the **Administrator** check box.
8. Click **Submit**.
9. Navigate to **Hosts** > **All Hosts** and click the name of the Satellite Server host.
10. Click **Schedule Remote Job**.

11. From the **Job Category** list, select **Ansible Playbook**.
12. From the **Job Template** list, select **Configure Cloud Connector**.
13. In the **satellite_user** field, enter the name of the service user.
14. In the **satellite_password** field, enter the password of the service user.
15. Click **Submit**.
16. Until [BZ#1828257](#) is resolved, you must manually add the following lines to the **/etc/systemd/system/receptor@.service** file so that the service can still run after a restart:

```
[Install]
WantedBy=multi-user.target
```

To verify that the playbook was successful, log into <https://cloud.redhat.com/settings/sources/> and search for your Satellite Server.

If you add an organization for a new Red Hat account to Satellite, repeat these steps to configure a Cloud Connector instance for the new account.

If you add an organization to an existing Red Hat account on Satellite, edit that account's service user to include the new organization.

If you remove an organization, and there are no more organizations under the same Red Hat account, you can remove the Cloud Connector instance for that account by running the following commands:

```
# systemctl disable --now receptor@rh_<accountID>
# rm -rf /etc/receptor/rh_<accountID>
```

2.4. CONFIGURING RED HAT INSIGHTS SYNCHRONIZATION ON SATELLITE

You can use Red Hat Insights synchronization to provide Red Hat Insights recommendations for Satellite-managed hosts.

Use this procedure to configure Insights synchronization on Red Hat Satellite.

Procedure

1. Generate an RHSM API token at <https://access.redhat.com/management/api>.
2. Copy the token to **Red Hat Cloud token** setting in the Satellite web UI. To do so, navigate to **Administer > Settings** and click the **RH Cloud** tab. Then, in the **Red Hat Cloud token** setting value, paste the token and click save.
3. Navigate to **Configure > Insights** to synchronize Red Hat Insights recommendations manually by clicking the **Sync now** button. Optionally, toggle the **Synchronize Automatically** switch to the **ON** position to enable Red Hat Satellite to download Insights recommendations available on cloud.redhat.com automatically once a day.

You have now configured Red Hat Insights Synchronization on Satellite.

In the Satellite web UI, navigate to **Hosts** > **All Hosts** to see Red Hat Insights recommendations for each Satellite-managed host. For more information about remediating issues on RHEL systems managed by Satellite, see [Chapter 3, *Remediating issues on RHEL systems managed by Satellite*](#) .

CHAPTER 3. REMEDIATING ISSUES ON RHEL SYSTEMS MANAGED BY SATELLITE

Use Insights to create a remediations playbook, and execute that playbook on your Satellite systems from the Insights UI.

3.1. USING INSIGHTS TO CREATE A REMEDIATIONS PLAYBOOK

You can use Insights to create an Ansible Playbook for system remediation across your Satellite infrastructure.

Prerequisites

- [Section 2.1, “Uploading your host inventory from Satellite to Insights”](#)

Procedure

1. Log in to your cloud.redhat.com account and open Red Hat Insights.
2. Perform one of the following actions to see what fixes are available.
 - Click the **Advisor > Recommendations > Recommendation** tab to view a list of the recommended fixes.



NOTE

Verify that the selected remediation item has a green check mark in the **Ansible** column, which means you create an Ansible Playbook to remediate the issue.

- Click the **Vulnerability > CVEs** tab to view a list of CVEs.
3. After selecting **Advisor > Recommendations** or **Vulnerability > CVEs**, click on one of the listed remediation items.
An **Affected systems** list appears that shows you which systems might need the remediation applied.
 4. From the list, click the check box to select the systems you want to remediate. When you select the systems, the Ansible **Remediate** button becomes active.
 5. Click the Ansible **Remediate** button to create an Ansible Playbook. You can choose to create a new playbook or modify an existing playbook.

3.2. EXECUTING THE REMEDIATIONS PLAYBOOK

You can execute an Ansible Playbook that you created to apply remediations to your Satellite-managed systems.



NOTE


Only users who are assigned the **Remediations administrator** role can execute an Ansible Playbook. For information on how to manage and assign user roles, see the *User Access Configuration Guide for Red Hat Insights*.

Prerequisites

- [Chapter 2, Configuring your Satellite infrastructure to communicate with Insights](#)
- [Section 3.1, "Using Insights to create a remediations playbook"](#)

Procedure

1. Navigate to **Insights > Remediations**. A list of available playbooks appears.
2. Click the name of the playbook that you want to execute. A summary window displays information about the actions in the playbook.
3. In the summary window you can switch states of the auto reboot. If it is enabled you can turn it off and if it is disabled you can turn it on.



NOTE

The selection to **Turn off auto reboot** applies to the playbook and not individual systems. If multiple systems use the playbook, the auto reboot choice of enabled or disabled applies to all systems and cannot be individually toggled.

4. (Optional) You can select specific actions in the confirmation window and delete them.
5. Click the **Execute Playbook** button. A confirmation window appears and asks for a final confirmation to execute the playbook. You can view the readiness state for the target systems.
6. In the confirmation window, click the button **Execute Playbook on X systems** to start running the playbook. The **X** represents the number of systems.

3.3. USING INSIGHTS TO MONITOR REMEDIATION STATUS

You can view the remediation status for each playbook that you execute from the Insights Remediations service. The status information tells you the results of the latest activity and provides a summary of all activity for playbook execution. You can also view log information for playbook execution.

Prerequisites

- Create and execute a remediation playbook.

Procedure

1. In the Red Hat Insights application, click the **Remediations** tab. The tab window displays a list of remediation playbooks.
2. Click on the name of a playbook. Additional choices are displayed for the latest playbook activity and all playbook activity.
3. Click **View** in the Playbook summary area to see results of the latest activity for the playbook execution.
4. Click the **Activity** tab to see information about all activity for the playbook.
5. When you hover on any item in the **Status** column, a pop-up box appears with summary information for Run, Failed, and Pending activity.

6. Click the expand button next to a **Run on** entry to show additional activity for each connection on that run. A "Results by connection" window appears.
7. Under the **Connection** heading, click a connection name. A **Name** list appears.
8. Click on the expand button next to an entry in the **Name** list. A **Playbook log** appears.

**NOTE**

You can view the **Playbook log** while a playbook is executing to see near real time information on the execution status.

To monitor the status of a playbook in the Satellite web UI, see [Monitoring Remote Jobs](#) in the Red Hat Satellite *Managing Hosts* guide.