



Red Hat JBoss Enterprise Application Platform 7.0

Migration Guide

For Use with Red Hat JBoss Enterprise Application Platform 7.0

Red Hat JBoss Enterprise Application Platform 7.0 Migration Guide

For Use with Red Hat JBoss Enterprise Application Platform 7.0

Legal Notice

Copyright © 2018 Red Hat, Inc.

The text of and illustrations in this document are licensed by Red Hat under a Creative Commons Attribution–Share Alike 3.0 Unported license ("CC-BY-SA"). An explanation of CC-BY-SA is available at

<http://creativecommons.org/licenses/by-sa/3.0/>

. In accordance with CC-BY-SA, if you distribute this document or an adaptation of it, you must provide the URL for the original version.

Red Hat, as the licensor of this document, waives the right to enforce, and agrees not to assert, Section 4d of CC-BY-SA to the fullest extent permitted by applicable law.

Red Hat, Red Hat Enterprise Linux, the Shadowman logo, JBoss, OpenShift, Fedora, the Infinity logo, and RHCE are trademarks of Red Hat, Inc., registered in the United States and other countries.

Linux ® is the registered trademark of Linus Torvalds in the United States and other countries.

Java ® is a registered trademark of Oracle and/or its affiliates.

XFS ® is a trademark of Silicon Graphics International Corp. or its subsidiaries in the United States and/or other countries.

MySQL ® is a registered trademark of MySQL AB in the United States, the European Union and other countries.

Node.js ® is an official trademark of Joyent. Red Hat Software Collections is not formally related to or endorsed by the official Joyent Node.js open source or commercial project.

The OpenStack ® Word Mark and OpenStack logo are either registered trademarks/service marks or trademarks/service marks of the OpenStack Foundation, in the United States and other countries and are used with the OpenStack Foundation's permission. We are not affiliated with, endorsed or sponsored by the OpenStack Foundation, or the OpenStack community.

All other trademarks are the property of their respective owners.

Abstract

This guide provides information about how to migrate your application from previous versions of Red Hat JBoss Enterprise Application Platform.

Table of Contents

CHAPTER 1. INTRODUCTION	7
1.1. ABOUT RED HAT JBOSS ENTERPRISE APPLICATION PLATFORM 7	7
1.2. ABOUT THE MIGRATION GUIDE	7
1.3. ABOUT MIGRATIONS AND UPGRADES	7
1.4. ABOUT THE USE OF EAP_HOME IN THIS DOCUMENT	8
CHAPTER 2. PREPARE FOR MIGRATION	9
2.1. PREPARATION OVERVIEW	9
2.2. REVIEW THE JAVA EE 7 FEATURES	9
2.3. REVIEW WHAT'S NEW IN JBOSS EAP 7	9
2.4. REVIEW THE LIST OF DEPRECATED AND UNSUPPORTED FEATURES	10
2.5. REVIEW THE JBOSS EAP GETTING STARTED MATERIAL	11
2.6. MIGRATION ANALYSIS AND PLANNING	11
2.7. BACK UP IMPORTANT DATA AND REVIEW SERVER STATE	12
2.8. MIGRATING AN RPM INSTALLATION	13
2.9. MIGRATE JBOSS EAP RUNNING AS A SERVICE	13
CHAPTER 3. TOOLS TO ASSIST IN MIGRATION	14
3.1. USE RHAMT TO ANALYZE APPLICATIONS FOR MIGRATION	14
3.2. USE THE JBOSS SERVER MIGRATION TOOL TO MIGRATE SERVER CONFIGURATIONS	14
CHAPTER 4. SERVER CONFIGURATION CHANGES	15
4.1. SERVER CONFIGURATION MIGRATION OPTIONS	15
JBoss Server Migration Tool	15
Management CLI Migrate Operation	15
4.2. MANAGEMENT CLI MIGRATION OPERATION	15
Start the Server and the Management CLI	16
Migrate the JacORB, Messaging, and Web Subsystems	17
4.3. LOGGING MESSAGE PREFIX CHANGES	20
4.4. WEB SERVER CONFIGURATION CHANGES	21
4.4.1. Replace the Web Subsystem with Undertow	21
4.4.2. Migrate JBoss Web Rewrite Conditions	22
4.4.3. Migrate JBoss Web System Properties	24
4.4.4. Migrate JBoss Web jboss-web.xml Overlay	25
4.4.5. Migrate Global Valves	25
Migrate JBoss Web Valves	25
JDBCAccessLogValve Manual Migration Procedure	26
4.5. JGROUPS SERVER CONFIGURATION CHANGES	27
4.5.1. JGroups Defaults to a Private Network Interface	27
4.5.2. JGroups Channels Changes	27
4.6. INFINISPAN SERVER CONFIGURATION CHANGES	28
4.6.1. Infinispan Default Cache Configuration Changes	28
4.6.2. Infinispan Cache Strategy Changes	28
4.6.3. Configuring Custom Stateful Session Bean Cache for Passivation	28
4.7. EJB SERVER CONFIGURATION CHANGES	29
DuplicateServiceException	29
4.8. MESSAGING SERVER CONFIGURATION CHANGES	29
4.8.1. Messaging Subsystem Server Configuration Changes	30
Management Model	30
Messaging Subsystem Migration and Forward Compatibility	30
Change in Behavior of forward-when-no-consumers Attribute	31
Change in Default Cluster Load Balancing Policy	31

Messaging Subsystem XML Configuration	31
4.8.2. Migrate Messaging Data	31
4.8.2.1. Migrate Messaging Data Using Export and Import	32
Export Messaging Data from the Previous Release	32
Import the XML Formatted Messaging Data	33
Recovering from an Import Messaging Data Failure	34
4.8.2.2. Migrate Messaging Data Using a JMS Bridge	34
Configure the JBoss EAP 6 Server	34
Configure the JBoss EAP 7 Server	35
Migrate the Data	37
4.8.2.3. Mapping Messaging Folder Names	38
4.8.2.4. Backing Up Messaging Folder Data	38
4.8.3. Migrate JMS Destinations	38
4.8.4. Migrate Messaging Interceptors	39
4.8.5. Replace Netty Servlet Configuration	39
4.8.6. Changes in JMS Serialization Behavior Between Releases	40
4.9. JMX MANAGEMENT CHANGES	40
4.10. ORB SERVER CONFIGURATION CHANGES	42
4.11. MIGRATE THE THREADS SUBSYSTEM CONFIGURATION	44
4.12. MIGRATE THE REMOTING SUBSYSTEM CONFIGURATION	45
4.13. WEBSOCKET SERVER CONFIGURATION CHANGES	45
4.14. SINGLE SIGN-ON SERVER CHANGES	46
4.15. DATASOURCE CONFIGURATION CHANGES	46
4.15.1. JDBC Datasource Driver Name	46
Driver Containing a Single Class	46
Driver Containing Multiple Classes	46
4.16. SECURITY SERVER CONFIGURATION CHANGES	47
4.17. TRANSACTIONS SUBSYSTEM CHANGES	47
Removed Transactions Subsystem Attributes	47
Deprecated Transactions Subsystem Attributes	47
4.18. CHANGES TO MOD_CLUSTER CONFIGURATION	48
CHAPTER 5. APPLICATION MIGRATION CHANGES	49
5.1. WEB SERVICES APPLICATION CHANGES	49
5.1.1. JAX-RPC Support Changes	49
5.1.2. Apache CXF Spring Web Services Changes	49
Apache CXF Interceptors	50
Apache CXF Features	50
Apache CXF HTTP Transport	51
5.1.3. WS-Security Changes	51
5.1.4. JBoss Modules Structure Change	52
5.1.5. Bouncy Castle Requirements and Changes	52
5.1.6. Apache CXF Bus Selection Strategy	52
5.1.7. JAX-WS 2.2 Requirements for WebServiceRef	53
5.1.8. IgnoreHttpsHost CN Check Change	53
5.1.9. Server Side Configuration and Class Loading	53
5.1.10. Deprecation of Java Endorsed Standards Override Mechanism	53
5.1.11. Specification of Descriptor in EAR Archive	53
5.2. UPDATE THE REMOTE URL CONNECTOR AND PORT	53
5.3. MESSAGING APPLICATION CHANGES	54
5.3.1. Replace or Update JMS Deployment Descriptors	54
5.3.2. Update External JMS Clients	55
5.3.3. Replace the HornetQ API	55

5.4. JAX-RS AND RESTEASY APPLICATION CHANGES	55
5.4.1. RESTEasy Deprecated Classes	56
Interceptor and MessageBody Classes	56
Client API	58
StringConverter	59
5.4.2. Removed or Protected RESTEasy Classes	59
ResteasyProviderFactory Add methods	59
Additional Classes Removed From RESTEasy 3	59
5.4.3. Additional RESTEasy Changes	59
SignedInput and SignedOutput	59
Security Filters	60
Client-side Filters	60
Asynchronous HTTP Support	60
Server-side Cache	60
YAML Provider Setting Changes	60
SerializableProvider	60
5.4.4. RESTEasy SPI Changes	60
SPI Exceptions	60
InjectorFactory and Registry	61
5.4.5. Jackson Provider Changes	61
5.4.6. Spring RESTEasy Integration Changes	61
5.4.7. RESTEasy Jettison JSON Provider Changes	61
5.5. CDI 1.2 APPLICATION CHANGES	61
Bean Archives	62
Clarification of Conversation Resolution	63
Observer Resolution	63
5.6. MIGRATE EXPLICIT MODULE DEPENDENCIES	63
Review Dependencies for Availability	63
Dependencies That Require Annotation Scanning	63
5.7. HIBERNATE AND JPA MIGRATION CHANGES	64
5.7.1. Hibernate ORM 3.0	64
5.7.2. Hibernate ORM 4.0 - 4.3	64
5.7.3. Hibernate ORM 5	64
5.7.4. Migrating to Hibernate ORM 5	64
Removed and Deprecated Classes	64
Other Changes to Classes and Packages	64
Type Handling	65
Transaction Management	65
Other Hibernate ORM 5 Changes	66
5.8. HIBERNATE SEARCH CHANGES	67
Hibernate Search Mapping Changes	67
Indexing of id Fields of Embedded Relations	67
Number and Date Index Formatting Changes	67
Miscellaneous Hibernate Search Changes	67
Hibernate Search Renamed and Repackaged Classes	69
Lucene - Renamed and Repackaged Classes	69
Hibernate Search Deprecated APIs	69
Hibernate Search Deprecated Interfaces	69
Hibernate Search Deprecated Classes	69
Hibernate Search Deprecated Enums	70
Hibernate Search Deprecated Annotations	70
Hibernate Search Deprecated Methods	70
Hibernate Search Deprecated Constructors	71

Changes Impacting Advanced Integrators	71
5.9. MIGRATE ENTITY BEANS TO JPA	72
5.10. JPA PERSISTENCE PROPERTY CHANGES	74
5.11. MIGRATE EJB CLIENT CODE	74
5.11.1. Update the Default Remote Connection Port	74
5.11.2. Update the Default Connector	75
5.11.3. Migrate Remote Naming Client Code	75
5.12. MIGRATE DEPLOYMENT PLAN CONFIGURATIONS	75
5.13. MIGRATE CUSTOM APPLICATION VALVES	76
Migrate Valves Configured in Deployments	76
Migrate Custom Authenticator Valves	76
5.14. SECURITY APPLICATION CHANGES	77
5.14.1. Migrate Authenticator Valves	77
5.14.2. PicketLink Changes	77
5.14.3. Other Security Application Changes	77
5.15. JBOSS LOGGING CHANGES	77
5.16. JAVASERVER FACES (JSF) CODE CHANGES	78
Dropped Support for JSF 1.2	78
Compatibility Issue Between JSF 2.1 and JSF 2.2	78
5.17. MODULE CLASS LOADING CHANGES	78
5.18. APPLICATION CLUSTERING CHANGES	79
5.18.1. Overview of New Clustering Features	79
5.18.2. Web Session Clustering Changes	80
5.18.3. Stateful Session EJB Clustering Changes	82
5.18.4. Clustering Services Changes	83
5.18.5. Migrate Clustering HA Singleton	83
CHAPTER 6. MISCELLANEOUS CHANGES	84
6.1. CHANGES TO DELIVERY OF JBOSS EAP NATIVES AND APACHE HTTP SERVER	84
6.2. CHANGES TO DEPLOYMENTS ON AMAZON EC2	85
6.3. CHANGES TO JBOSS EAP SCRIPTS	85
6.4. REMOVAL OF OSGI SUPPORT	85
CHAPTER 7. MIGRATING FROM OLDER RELEASES OF JBOSS EAP	87
7.1. MIGRATING FROM JBOSS EAP 5 TO JBOSS EAP 7	87
7.2. SUMMARY OF CHANGES MADE TO EACH RELEASE	87
7.3. REVIEW THE CONTENT IN THE MIGRATION GUIDES	88
7.4. JBOSS EAP 5 COMPONENT UPGRADE REFERENCE	88
APPENDIX A. REFERENCE MATERIAL	95
A.1. JACORB SUBSYSTEM MIGRATION OPERATION WARNINGS	95
A.2. MESSAGING SUBSYSTEM MIGRATION OPERATION WARNINGS	96
Replace the Deprecated broadcast-group or discovery-group Attributes	99
A.3. WEB SUBSYSTEM MIGRATION OPERATION WARNINGS	100
Web Subsystem Migration Operation Attribute Warnings	104
Web SSL Connector Attributes	104
Web Static Resource Attributes	104
Web SSO Resource Attributes	105
Web Access Log Attributes	105
Web Connector Attributes	105
A.4. MIGRATE JBOSS WEB SYSTEM PROPERTIES REFERENCE	106
A.5. COMPATIBILITY AND INTEROPERABILITY BETWEEN RELEASES	115
EJB remoting over IIOP	115
EJB remoting Using JNDI	115

EJB remoting Using @WebService	115
Messaging Standalone Client	115
Messaging MDBs	116
JMS bridges	116

CHAPTER 1. INTRODUCTION

1.1. ABOUT RED HAT JBOSS ENTERPRISE APPLICATION PLATFORM 7

Red Hat JBoss Enterprise Application Platform 7 (JBoss EAP) is a middleware platform built on open standards and compliant with the Java Enterprise Edition 7 specification. It integrates WildFly Application Server 10 with messaging, high-availability clustering, and other technologies.

JBoss EAP includes a modular structure that allows service enabling only when required, improving startup speed.

The management console and management command-line interface (CLI) make editing XML configuration files unnecessary and add the ability to script and automate tasks.

JBoss EAP provides two operating modes for JBoss EAP instances: standalone server or managed domain. The standalone server operating mode represents running JBoss EAP as a single server instance. The managed domain operating mode allows for the management of multiple JBoss EAP instances from a single control point.

In addition, JBoss EAP includes APIs and development frameworks for quickly developing secure and scalable Java EE applications.

1.2. ABOUT THE MIGRATION GUIDE

The purpose of this guide is to document the changes that are required to successfully run and deploy Red Hat JBoss Enterprise Application Platform 6 applications on Red Hat JBoss Enterprise Application Platform 7. It provides information about the new features available in this release, the deprecated and unsupported features, and any application and server configuration updates that might be required to prevent changes in application behavior.

It also provides information about tools that can help with the migration, such as [Red Hat Application Migration Toolkit](#), which simplifies migration of Java applications, and the [JBoss Server Migration Tool](#), which updates the server configuration.

Once the application is successfully deployed and running, plans can be made to upgrade individual components to use the new functions and features of JBoss EAP 7.

If you plan to migrate your JBoss EAP 5 applications directly to JBoss EAP 7, see [Migrating from Older Releases of JBoss EAP](#).

1.3. ABOUT MIGRATIONS AND UPGRADES

Major Upgrades

A major upgrade or migration is required when an application is moved from one major release to another, for example, from JBoss EAP 6 to JBoss EAP 7. This is the type of migration addressed in this guide. If an application follows the Java EE specifications, does not access deprecated APIs, and does not contain proprietary code, it might be possible to run the application in JBoss EAP 7 without any application code changes. However, server configuration has changed in JBoss EAP 7 and any server configuration settings require migration.

Minor Updates

JBoss EAP periodically provides point releases, which are minor updates that include bug fixes, security fixes, and new features. The JBoss EAP [Patching and Upgrading Guide](#) describes how to upgrade from one point release to another, for example from JBoss EAP 7.0 to JBoss EAP 7.1.

Cumulative Patches

JBoss EAP also periodically provides cumulative patches that contain bug and security fixes. Cumulative patches increment the release by the last digit, for example from 7.0.0 to 7.0.1. Patch installation is covered in detail in the JBoss EAP [Patching and Upgrading Guide](#).

1.4. ABOUT THE USE OF EAP_HOME IN THIS DOCUMENT

In this document, the variable `EAP_HOME` is used to denote the path to the JBoss EAP installation. Replace this variable with the actual path to your JBoss EAP installation.

- If you installed JBoss EAP using the ZIP install method, the install directory is the `jboss-eap-7.0` directory where you extracted the ZIP archive.
- If you installed JBoss EAP using the RPM install method, the install directory is `/opt/rh/eap7/root/usr/share/wildfly/`.
- If you used the installer to install JBoss EAP, the default path for `EAP_HOME` is `${user.home}/EAP-7.0.0`:
 - For Red Hat Enterprise Linux, Solaris, and HP-UX: `/home/USER_NAME/EAP-7.0.0/`
 - For Microsoft Windows: `C:\Users\USER_NAME\EAP-7.0.0\`
- If you used the JBoss Developer Studio installer to install and configure the JBoss EAP server, the default path for `EAP_HOME` is `${user.home}/jbdevstudio/runtimes/jboss-eap`:
 - For Red Hat Enterprise Linux: `/home/USER_NAME/jbdevstudio/runtimes/jboss-eap/`
 - For Microsoft Windows: `C:\Users\USER_NAME\jbdevstudio\runtimes\jboss-eap` or `C:\Documents and Settings\USER_NAME\jbdevstudio\runtimes\jboss-eap\`



NOTE

`EAP_HOME` is not an environment variable. `JBOSS_HOME` is the environment variable used in scripts.

CHAPTER 2. PREPARE FOR MIGRATION

2.1. PREPARATION OVERVIEW

In JBoss EAP 7, an effort was made to provide backward compatibility for JBoss EAP 6 applications. However, if your application uses features that were deprecated or functionality that was removed from JBoss EAP 7, you might need to make changes to your application code.

In addition, a number of things have changed in this release that might impact deployment of JBoss EAP 7 applications. It is recommended that you do some research and planning before you attempt to migrate your application.

- Become familiar with the [features of Java EE 7](#).
- Review [what's new in JBoss EAP 7](#).
- Review the list of [deprecated and unsupported features](#).
- Review the material in the JBoss EAP 7 [Getting Started Guide](#).
- Take a look at the [tools that can help with migration tasks](#).

Once you are comfortable with the feature changes, the development materials, and the tools that can assist your migration efforts, you can begin to evaluate your applications and your server configuration to determine the changes that are needed to run in JBoss EAP 7.

2.2. REVIEW THE JAVA EE 7 FEATURES

Java EE 7 includes many improvements to make it easier to develop and run feature rich applications on private and public clouds. It incorporates new features and the latest standards such as HTML5, WebSocket, JSON, Batch, and Concurrency Utilities. Updates include JPA 2.1, JAX-RS 2.0, Servlet 3.1, Expression Language 3.0, JMS 2.0, JSF 2.2, EJB 3.2, CDI 1.2, and Bean Validation 1.1.

You can find more information about Java EE 7, including tutorials, on Oracle's web site: [Java EE at a Glance](#)

2.3. REVIEW WHAT'S NEW IN JBOSS EAP 7

JBoss EAP 7 includes some notable upgrades and improvements over the previous release.

Java EE 7

JBoss EAP 7 is a certified implementation of Java EE 7, meeting both the Web and the Full profiles. It also includes support for the latest iterations of CDI 1.2 and Web Sockets 1.1.

Undertow

Undertow is the new lightweight, flexible, and performant web server included in JBoss EAP 7, replacing JBoss Web. Written in Java, it is designed for maximum throughput and scalability. It supports the latest web technologies, such as the new HTTP/2 standard.

Apache ActiveMQ Artemis

Apache ActiveMQ Artemis is the new JBoss EAP 7 built-in messaging provider. Based on a code donation from HornetQ, this Apache subproject provides outstanding performance based on a proven non-blocking architecture.

IronJacamar 1.2

The latest IronJacamar provides a stable and feature rich support for JCA and DataSources.

JBossWS 5

The fifth generation of JBossWS is a major leap forward, bringing new features and performance improvements to JBoss EAP 7 web services.

RESTEasy 3

JBoss EAP 7 includes the latest generation of RESTEasy. It goes beyond the standard Java EE REST APIs (JAX-RS 2.0) by providing a number of useful extensions such as JSON Web Encryption, Jackson, JSON-P, and Jettison.

OpenJDK ORB

JBoss EAP 7 replaced the JacORB IIOP implementation with a downstream branch of the OpenJDK ORB, leading to better interoperability with the JVM ORB and the Java EE RI.

Feature Rich Clustering

Clustering support was heavily refactored in JBoss EAP 7 and includes several public APIs for access by applications.

Port Reduction

By utilizing HTTP upgrade, JBoss EAP 7 has moved nearly all of its protocols to be multiplexed over just two HTTP ports: a management port (9990), and an application port (8080).

Enhanced Logging

The management API now supports the ability to list and view the available log files on a server, or even define custom formatters other than the default pattern formatter. Deployment's logging setup is also greatly enhanced.

For a complete list of new features, see [New Features and Enhancements](#) in the JBoss EAP 7 *Release Notes*.

2.4. REVIEW THE LIST OF DEPRECATED AND UNSUPPORTED FEATURES

Before you migrate your application, be aware that some features that were available in previous releases of JBoss EAP might be deprecated or no longer supported.

Support for some technologies was removed due to the high maintenance cost, low community interest, and much better alternative solutions. The following is a short summary of some of the unsupported features.

EJB Entity Beans

EJB entity beans are no longer supported. If your application uses EJB entity beans, you should migrate the code to use JPA, which offers a much more performant and flexible API.

JAX-RPC

Because JAX-WS offers a much more accurate and complete solution, code written for JAX-RPC should be migrated to use JAX-WS.

JSR-88

Java EE Application Deployment API specification (JSR-88), which defined a contract to enable tools from multiple providers to configure and deploy applications on any Java EE platform product, was not widely adopted. You must use another JBoss EAP supported option for application deployment, such as the management console, the management CLI, deployment scanner, or Maven.

Generic JMS Resource Adapter

The ability to configure a generic JMS resource adapter to connect to a JMS provider is no longer supported in JBoss EAP 7.

For a comprehensive list of deprecated and unsupported features, see [Unsupported and Deprecated Functionality](#) in the JBoss EAP 7 *Release Notes*.

2.5. REVIEW THE JBOSS EAP GETTING STARTED MATERIAL

Be sure to review the JBoss EAP [Getting Started Guide](#). It contains the following important information:

- How to download and install JBoss EAP 7
- How to download and install Red Hat JBoss Developer Studio
- How to configure Maven for your development environment, manage project dependencies, and configure your projects to use the JBoss EAP Bill of Material (BOM) artifacts
- How to download and run the quickstart example applications that ship with the product

2.6. MIGRATION ANALYSIS AND PLANNING

Each application and server configuration is unique and you must thoroughly understand the components and architecture of the existing application and server platform before you attempt the migration. Your migration plan should include a detailed roadmap for testing and roll out to production that takes into account the following information.

Identify the People Responsible for the Migration

Identify the stakeholders, project managers, developers, administrators, and others who will be responsible for the migration.

Review the Application Server Platform Configuration and Hardware

Examine the existing application server and platform configuration to determine how they are impacted by feature changes in JBoss EAP 7. The review should include the following items.

- Operating systems and versions
- Database used by the applications
- Web servers
- Security architecture
- Number and type of processors
- Amount of memory
- Amount of physical disk storage
- Migration of database or messaging data
- Other components that might be impacted by the migration

Review the Current Production Environment

You should plan to recreate the production environment as closely as possible for testing and staging the migration process.

- Take into account any clustering configurations. See [Upgrading a Cluster](#) in the *JBoss EAP Patching and Upgrading Guide* for more information about how to migrate clusters.
- If you are currently running a large managed domain, consider a gradual migration approach.
- Determine whether you need to migrate any database or messaging data.

Examine and Understand the Existing Application

Thoroughly examine the existing JBoss EAP 6 application. Be totally familiar with its architecture, functions, features and components, including:

- The JVM version
- Integration with other Red Hat application server middleware components
- Integration with proprietary third-party software
- Use of deprecated features that will require replacement
- Application configuration including deployment descriptors, JNDI, persistence, JDBC configuration and pooling, JMS topics and queues, and logging

Identify any code or configuration incompatibilities that will require modification during the migration to JBoss EAP 7.

Create a Detailed Test Plan


- The plan should include regression testing and acceptance criteria requirements.
- It should also include performance testing.
- Set up a staging environment as close to the production environment as possible to test the migration before the rollout to production.
- Be sure to create a backup and backout plan!

Review the Resources Available for the Migration Process

- Assess the skills of the development team and plan for training or additional consulting help.
- Be aware that additional hardware and other resources will be required for staging and testing during the migration process until the effort is completed.
- Determine whether any formal training is needed. If so, add it to the schedule.

Execute the Plan

Gather the necessary resources and implement the migration plan.



IMPORTANT

Before making any modifications to your application, be sure to create a backup copy.

2.7. BACK UP IMPORTANT DATA AND REVIEW SERVER STATE

Before you migrate your application, you need to be aware of the following potential issues.

- The migration might remove temporary folders. Any deployments stored in the `data/content/` directory must be backed up prior to the migration and restored after it completes. Otherwise, the server will fail to start due to the missing content.
- Prior to the migration, handle any open transactions and delete the `data/tx-object-store/` transaction directory.
- The persistent timer data in `data/timer-service-data` must be checked to determine whether it is compatible. Prior to the migration, review the `deployment - *` files in that directory to determine which timers are still in use.

Be sure to also back up the current server configuration and applications before you begin.

2.8. MIGRATING AN RPM INSTALLATION



IMPORTANT

It is not supported to have more than one RPM-installed instance of JBoss EAP on a single Red Hat Enterprise Linux Server. As a result, we recommend that you migrate your JBoss EAP installation to a new machine when migrating to JBoss EAP 7.

When migrating a JBoss EAP RPM installation from JBoss EAP 6 to JBoss EAP 7, ensure that JBoss EAP 7 is installed on a machine that does not have an existing JBoss EAP RPM installation.

To install JBoss EAP 7 using RPMs, see the JBoss EAP [Installation Guide](#).

The migration advice in this guide also applies to migrating RPM installations of JBoss EAP, but you might need to alter some steps (such as how to start JBoss EAP) to suit an RPM installation compared to a ZIP or installer installation.

2.9. MIGRATE JOSS EAP RUNNING AS A SERVICE

If you run JBoss EAP 6 as a service, be sure to review [Configuring JBoss EAP to Run as a Service](#) in the JBoss EAP *Installation Guide* for updated configuration instructions for JBoss EAP 7.

CHAPTER 3. TOOLS TO ASSIST IN MIGRATION

3.1. USE RHAMT TO ANALYZE APPLICATIONS FOR MIGRATION

Red Hat Application Migration Toolkit (RHAMT) is an extensible and customizable rule-based set of tools that helps simplify migration of Java applications. It analyzes the APIs, technologies, and architectures used by the applications you plan to migrate and provides detailed migration reports for each application. These reports provide the following information.

- Detailed explanations of the migration changes needed.
- Whether the reported change is mandatory or optional.
- Whether the reported change is complex or trivial.
- Links to the code requiring the migration change.
- Hints and links to information about how to make the required changes.
- An estimate of the level of effort for each migration issue found and the total estimated effort to migrate the application.

You can use RHAMT to analyze the code and architecture of your JBoss EAP 6 applications before you migrate them to JBoss EAP 7. The RHAMT rule set for migration from JBoss EAP 6 to JBoss EAP 7 reports on XML descriptors and specific application code and parameters that need to be replaced by an alternative configuration when migrating to JBoss EAP 7.


For more information about how to use Red Hat Application Migration Toolkit to analyze your JBoss EAP 6 applications, see the Red Hat Application Migration Toolkit [Getting Started Guide](#).

3.2. USE THE JBOSS SERVER MIGRATION TOOL TO MIGRATE SERVER CONFIGURATIONS

You can use the JBoss Server Migration Tool to update your configuration to include the new features and settings in JBoss EAP 7 while keeping your existing configuration.

The JBoss Server Migration Tool reads your existing JBoss EAP 6 server configuration file and adds configurations for the new subsystems, updates existing subsystem configurations with new features, and removes obsolete subsystem configurations.

The binary distribution of JBoss Server Migration Tool 1.0.0.Final is available for download from <https://github.com/wildfly/wildfly-server-migration/releases>. This version supports the migration of standalone servers and managed domains from JBoss EAP 6.4 to JBoss EAP 7.0. For general information about how to run the tool, see the [JBoss Server Migration Tool User Guide](#).



NOTE

The JBoss Server Migration Tool is not supported in JBoss EAP 7.0.

CHAPTER 4. SERVER CONFIGURATION CHANGES

4.1. SERVER CONFIGURATION MIGRATION OPTIONS

To migrate your server configuration from JBoss EAP 6 to JBoss EAP 7, you can either use the JBoss Server Migration Tool or do a manual migration with the help of the management CLI `migrate` operation.

JBoss Server Migration Tool

You can use the JBoss Server Migration Tool to update your configuration to include the new features and settings in JBoss EAP 7 while keeping your existing configuration. See [Use the JBoss Server Migration Tool to Migrate Server Configurations](#) for more information.

Management CLI Migrate Operation

You can use the management CLI `migrate` operation to update the `jacorb`, `messaging`, and `web` subsystems in the JBoss EAP 6 server configuration file to allow them run on the new release, but be aware that the result is not a complete JBoss EAP 7 configuration. For example:

- The operation does not update the original `remote` protocol and port settings to the new `http-remoting` and new port settings now used in JBoss EAP 7.
- The configuration does not include the new JBoss EAP subsystems or features such as clustered singleton deployments, or graceful shutdown.
- The configuration does not include the new Java EE 7 features such as batch processing.
- The `migrate` operation does not migrate the `ejb3` subsystem configuration. For information about possible EJB migration issues, see [EJB Server Configuration Changes](#).

For more information about using the `migrate` operation to migration the server configuration, see [Management CLI Migration Operation](#).

4.2. MANAGEMENT CLI MIGRATION OPERATION

You can use the management CLI to update your JBoss EAP 6 server configuration files to run on JBoss EAP 7. The management CLI provides a `migrate` operation to automatically update the `jacorb`, `messaging`, and `web` subsystems from the previous release to the new configuration. You can also execute the `describe-migration` operation for the `jacorb`, `messaging`, and `web` subsystems to review the proposed migration configuration changes before you perform the migration. There are no replacements for the `cmp`, `jaxr`, or `threads` subsystems and they must be removed from the server configuration.



IMPORTANT

See [Server Configuration Migration Options](#) for limitations of the `migrate` operation. You can also use the JBoss Server Migration Tool to update your configuration to include the new features and settings in JBoss EAP 7 while keeping your existing configuration. See [Use the JBoss Server Migration Tool to Migrate Server Configurations](#) for more information.

Table 4.1. Subsystem Migration and Management CLI Operation

JBoss EAP 6 Subsystem	JBoss EAP 7 Subsystem	Management CLI Operation
cmp	no replacement	remove
jacorb	iiop-openjdk	migrate
jaxr	no replacement	remove
messaging	messaging-activemq	migrate
threads	no replacement	remove
web	undertow	migrate

Start the Server and the Management CLI

Follow the steps below to update your JBoss EAP 6 server configuration to run on JBoss EAP 7.

1. Before you begin, review [Back Up Important Data and Review Server State](#) . It contains important information about making sure the server is in a good state and the appropriate files are backed up.
2. Start the JBoss EAP 7 server with the JBoss EAP 6 configuration.
 - a. Back up the JBoss EAP 7 server configuration files.
 - b. Copy the configuration file from the previous release into the JBoss EAP 7 directory.

```
$ cp EAP6_HOME/standalone/configuration/standalone-full.xml
EAP7_HOME/standalone/configuration
```

- c. Navigate to the JBoss EAP 7 install directory and start the server with the `--admin-only` argument.

```
$ bin/standalone.sh -c standalone-full.xml --admin-only
```



NOTE

You will see the following `org.jboss.as.controller.management-operation` ERRORS in the server log when you start the server. These errors are expected and indicate that the legacy subsystem configurations must be removed or migrated to JBoss EAP 7.

- WFLYCTL0402: Subsystems [cmp] provided by legacy extension 'org.jboss.as.cmp' are not supported on servers running this version. Both the subsystem and the extension must be removed or migrated before the server will function.
- WFLYCTL0402: Subsystems [jacorb] provided by legacy extension 'org.jboss.as.jacorb' are not supported on servers running this version. Both the subsystem and the extension must be removed or migrated before the server will function.
- WFLYCTL0402: Subsystems [jaxr] provided by legacy extension 'org.jboss.as.jaxr' are not supported on servers running this version. Both the subsystem and the extension must be removed or migrated before the server will function.
- WFLYCTL0402: Subsystems [messaging] provided by legacy extension 'org.jboss.as.messaging' are not supported on servers running this version. Both the subsystem and the extension must be removed or migrated before the server will function.
- WFLYCTL0402: Subsystems [threads] provided by legacy extension 'org.jboss.as.threads' are not supported on servers running this version. Both the subsystem and the extension must be removed or migrated before the server will function.
- WFLYCTL0402: Subsystems [web] provided by legacy extension 'org.jboss.as.web' are not supported on servers running this version. Both the subsystem and the extension must be removed or migrated before the server will function.

3. Open a new terminal, navigate to the JBoss EAP 7 install directory, and start the management CLI using the `--controller=remote://localhost:9999` arguments.

```
$ bin/jboss-cli.sh --connect --controller=remote://localhost:9999
```

Migrate the JacORB, Messaging, and Web Subsystems

1. To review the configuration changes that will be made to the subsystem before you perform the migration, execute the `describe-migration` operation.

The `describe-migration` operation uses the following syntax.

```
/subsystem=SUBSYSTEM_NAME:describe-migration
```

The following example describes the configuration changes that will be made to the JBoss EAP 6.4 `standalone-full.xml` configuration file when it is migrated to JBoss EAP 7. Entries were removed from the output to improve readability and to save space.

Example: describe-migration Operation

```
[standalone@localhost:9999 /] /subsystem=messaging:describe-
migration
{
  "outcome" => "success",
  "result" => {
    "migration-warnings" => [],
    "migration-operations" => [
      {
        "operation" => "add",
        "address" => [{"extension" =>
"org.wildfly.extension.messaging-activemq"}],
        "module" => "org.wildfly.extension.messaging-
activemq"
      },
      {
        "operation" => "add",
        "address" => [{"subsystem" => "messaging-
activemq"}]
      },
      <!-- *** Entries removed for readability *** -->
      {
        "operation" => "remove",
        "address" => [{"subsystem" => "messaging"}]
      },
      {
        "operation" => "remove",
        "address" => [{"extension" =>
"org.jboss.as.messaging"}]
      }
    ]
  }
}
```

2. Execute the `migrate` operation to migrate the subsystem configuration to the subsystem that replaces it in JBoss EAP 7. The operation uses the following syntax.

```
/subsystem=SUBSYSTEM_NAME:migrate
```



NOTE

The `messaging` subsystem `describe-migration` and `migrate` operations allow you to pass an argument to configure access by legacy clients. For more information about the command syntax, see [Messaging Subsystem Migration and Forward Compatibility](#).

3. Review the outcome and result of the command. Be sure the operation completed successfully and there are no "migration-warning" entries. This means the migration configuration for the subsystem is complete.

Example: Successful migrate Operation with No Warnings

```
[standalone@localhost:9999 /] /subsystem=messaging:migrate
{
  "outcome" => "success",
```

```

    "result" => {"migration-warnings" => []}
  }

```

If you see "migration-warnings" entries in the log, this indicates the migration of the server configuration completed successfully but it was not able to migrate all of elements and attributes. You must follow the suggestions provided by the "migration-warnings" and run additional management CLI commands to modify those configurations. The following is an example of a `migrate` operation that returns "migration-warnings".

Example: migrate Operation with Warnings

```

[standalone@localhost:9999 /] /subsystem=messaging:migrate
{
  "outcome" => "success",
  "result" => {"migration-warnings" => [
    "WFLYMSG0080: Could not migrate attribute group-address from
resource [
  (\\"subsystem\\" => \\"messaging-activemq\\"),
  (\\"server\\" => \\"default\\"),
  (\\"broadcast-group\\" => \\"groupB\\")
]. Use instead the socket-binding attribute to configure this
broadcast-group.",
    "WFLYMSG0080: Could not migrate attribute group-port from
resource [
  (\\"subsystem\\" => \\"messaging-activemq\\"),
  (\\"server\\" => \\"default\\"),
  (\\"broadcast-group\\" => \\"groupB\\")
]. Use instead the socket-binding attribute to configure this
broadcast-group.",
    "WFLYMSG0080: Could not migrate attribute local-bind-address
from resource [
  (\\"subsystem\\" => \\"messaging-activemq\\"),
  (\\"server\\" => \\"default\\"),
  (\\"broadcast-group\\" => \\"groupA\\")
]. Use instead the socket-binding attribute to configure this
broadcast-group.",
    "WFLYMSG0080: Could not migrate attribute local-bind-port
from resource [
  (\\"subsystem\\" => \\"messaging-activemq\\"),
  (\\"server\\" => \\"default\\"),
  (\\"broadcast-group\\" => \\"groupA\\")
]. Use instead the socket-binding attribute to configure this
broadcast-group.",
    "WFLYMSG0080: Could not migrate attribute group-address from
resource [
  (\\"subsystem\\" => \\"messaging-activemq\\"),
  (\\"server\\" => \\"default\\"),
  (\\"broadcast-group\\" => \\"groupA\\")
]. Use instead the socket-binding attribute to configure this
broadcast-group.",
    "WFLYMSG0080: Could not migrate attribute group-port from
resource [
  (\\"subsystem\\" => \\"messaging-activemq\\"),
  (\\"server\\" => \\"default\\"),
  (\\"broadcast-group\\" => \\"groupA\\")
]. Use instead the socket-binding attribute to configure this

```

```

broadcast-group."
    ]}
}

```

**NOTE**

The list of `migrate` and `describe-migration` warnings for each subsystem is located in the [Reference Material](#) at the end of this guide.

- [Jacorb Subsystem Migration Operation Warnings](#)
- [Messaging Subsystem Migration Operation Warnings](#)
- [Web Subsystem Migration Operation Warnings](#)

4. Review the server configuration file to verify the extension, subsystem, and namespace were updated and the existing subsystem configuration was migrated to JBoss EAP 7.

**NOTE**

You must repeat this process for each of the `jacorb`, `messaging`, and `web` subsystems using the following commands.

```

/subsystem=jacorb:migrate
/subsystem=messaging:migrate
/subsystem=web:migrate


```

5. Remove the `cmp`, `jaxr`, and `threads` subsystems and extensions from the server configuration.
While still in the management CLI prompt, remove the obsolete `cmp`, `jaxr`, and `threads` subsystems by executing the following commands.

```

/subsystem=cmp:remove
/extension=org.jboss.as.cmp:remove
/subsystem=jaxr:remove
/extension=org.jboss.as.jaxr:remove
/subsystem=threads:remove
/extension=org.jboss.as.threads:remove

```

**IMPORTANT**

You must migrate the `messaging`, `jacorb`, and `web` subsystems and remove the `cmp`, `jaxr`, and `threads` extensions and subsystems before you can restart the server for normal operation. If you need to restart the server before you complete this process, be sure to include the `--admin-only` argument on the server start command line. This allows you to continue with the configuration changes.

4.3. LOGGING MESSAGE PREFIX CHANGES

Log messages are prefixed with the project code for the subsystem that reports the message. The prefixes for all log messages have changed in JBoss EAP 7.

For a complete list of the new log message project code prefixes used in JBoss EAP 7, see [Project Codes Used in JBoss EAP](#) in the JBoss EAP *Development Guide*.

4.4. WEB SERVER CONFIGURATION CHANGES

4.4.1. Replace the Web Subsystem with Undertow

Undertow replaces JBoss Web as the web server in JBoss EAP 7. This means the legacy web subsystem configuration must be migrated to the new JBoss EAP 7 `undertow` subsystem configuration.

- The `urn:jboss:domain:web:2.2` subsystem configuration namespace in the server configuration file has been replaced by the `urn:jboss:domain:undertow:3.1` namespace.
- The `org.jboss.as.web` extension module, located in `EAP_HOME/modules/system/layers/base/`, has been replaced with the `org.wildfly.extension.undertow` extension module.

You can use the management CLI `migrate` operation to migrate the `web` subsystem to `undertow` in the server configuration file. However, be aware that this operation is not able to migrate all JBoss Web subsystem configurations. If you see "migration-warning" entries, you must run additional management CLI commands to migrate those configurations to Undertow. For more information about the management CLI `migrate` operation, see [Management CLI Migration Operation](#).

The following is an example of the default `web` subsystem configuration in JBoss EAP 6.

```
<subsystem xmlns="urn:jboss:domain:web:2.2" default-virtual-
server="default-host" native="false">
  <connector name="http" protocol="HTTP/1.1" scheme="http" socket-
binding="http"/>
  <virtual-server name="default-host" enable-welcome-root="true">
    <alias name="localhost"/>
    <alias name="example.com"/>
  </virtual-server>
</subsystem>
```

The following is an example of the default `undertow` subsystem configuration in JBoss EAP 7.

```
<subsystem xmlns="urn:jboss:domain:undertow:3.1">
  <buffer-cache name="default"/>
  <server name="default-server">
    <http-listener name="default" socket-binding="http" redirect-
socket="https"/>
    <host name="default-host" alias="localhost">
      <location name="/" handler="welcome-content"/>
      <filter-ref name="server-header"/>
      <filter-ref name="x-powered-by-header"/>
    </host>
  </server>
  <servlet-container name="default">
    <jsp-config/>
    <websockets/>
  </servlet-container>
  <handlers>
```

```

        <file name="welcome-content" path="${jboss.home.dir}/welcome-
content"/>
    </handlers>
    <filters>
        <response-header name="server-header" header-name="Server" header-
value="JBoss-EAP/7"/>
        <response-header name="x-powered-by-header" header-name="X-
Powered-By" header-value="Undertow/1"/>
    </filters>
</subsystem>

```

4.4.2. Migrate JBoss Web Rewrite Conditions

The management CLI `migrate` operation is not able to automatically migrate rewrite conditions. They are reported as "migration-warnings" and you must migrate them manually. You can create the equivalent configuration in JBoss EAP 7 by using [Undertow Predicates Attributes and Handlers](#).

The following is an example of a web subsystem configuration in JBoss EAP 6 that includes `rewrite` configuration.

```

<subsystem xmlns="urn:jboss:domain:web:2.2" default-virtual-
server="default" native="false">
    <virtual-server name="default" enable-welcome-root="true">
        <alias name="localhost"/>
        <rewrite name="test" pattern="(.*)/toberewritten/(.*)"
substitution="$1/rewritten/$2" flags="NC"/>
        <rewrite name="test2" pattern="(.*)" substitution="-" flags="F">
            <condition name="get" test="%{REQUEST_METHOD}"
pattern="GET"/>
            <condition name="andCond" test="%{REQUEST_URI}"
pattern=".*index.html" flags="NC"/>
        </rewrite>
    </virtual-server>
</subsystem>

```

Follow the [Management CLI Migration Operation](#) instructions to start your server and the management CLI, then migrate the web subsystem configuration file using the following command.

```
/subsystem=web:migrate
```

The following "migration-warnings" are reported when you run the `migrate` operation on the above configuration.

```

/subsystem=web:migrate
{
    "outcome" => "success",
    "result" => {"migration-warnings" => [
        "WFLYWEB0002: Could not migrate resource {
\"pattern\" => \"(.*)\",
\"substitution\" => \"-\",
\"flags\" => \"F\",
\"operation\" => \"add\",
\"address\" => [
        (\"subsystem\" => \"web\"),

```

```

        (\"virtual-server\" => \"default-host\"),
        (\"rewrite\" => \"test2\")
    ]
} ",
    "WFLYWEB0002: Could not migrate resource {
\"test\" => \"%{REQUEST_METHOD}\" ,
\"pattern\" => \"GET\" ,
\"flags\" => undefined,
\"operation\" => \"add\" ,
\"address\" => [
    (\"subsystem\" => \"web\"),
    (\"virtual-server\" => \"default-host\"),
    (\"rewrite\" => \"test2\"),
    (\"condition\" => \"get\")
]
} ",
    "WFLYWEB0002: Could not migrate resource {
\"test\" => \"%{REQUEST_URI}\" ,
\"pattern\" => \".*index.html\" ,
\"flags\" => \"NC\" ,
\"operation\" => \"add\" ,
\"address\" => [
    (\"subsystem\" => \"web\"),
    (\"virtual-server\" => \"default-host\"),
    (\"rewrite\" => \"test2\"),
    (\"condition\" => \"andCond\")
]
} "
    ]}
}

```

Review the server configuration file and you see the following configuration for the undertow subsystem.



NOTE

The rewrite configuration is dropped.

```

<subsystem xmlns="urn:jboss:domain:undertow:3.1">
  <buffer-cache name="default"/>
  <server name="default-server">
    <http-listener name="http" socket-binding="http"/>
    <host name="default-host" alias="localhost, example.com">
      <location name="/" handler="welcome-content"/>
    </host>
  </server>
  <servlet-container name="default">
    <jsp-config/>
  </servlet-container>
  <handlers>
    <file name="welcome-content" path="${jboss.home.dir}/welcome-
content"/>
  </handlers>
</subsystem>

```

Use the management CLI to create the filter to replace the rewrite configuration in the `undertow` subsystem. You should see `"{"outcome" => "success"}"` for each command.

```
# Create the filters
/subsystem=undertow/configuration=filter/expression-
filter="test1":add(expression="path('(.*)/toberewritten/(.*)') ->
rewrite('$1/rewritten/$2')")
/subsystem=undertow/configuration=filter/expression-
filter="test2":add(expression="method('GET') and path('.*index.html') ->
response-code(403)")

# Add the filters to the default server
/subsystem=undertow/server=default-server/host=default-host/filter-
ref="test1":add
/subsystem=undertow/server=default-server/host=default-host/filter-
ref="test2":add
```

Review the updated server configuration file. The JBoss Web subsystem is now completely migrated and configured in the `undertow` subsystem.

```
<subsystem xmlns="urn:jboss:domain:undertow:3.1">
  <buffer-cache name="default"/>
  <server name="default-server">
    <http-listener name="http" socket-binding="http"/>
    <host name="default-host" alias="localhost, example.com">
      <location name="/" handler="welcome-content"/>
      <filter-ref name="test1"/>
      <filter-ref name="test2"/>
    </host>
  </server>
  <servlet-container name="default">
    <jsp-config/>
  </servlet-container>
  <handlers>
    <file name="welcome-content" path="${jboss.home.dir}/welcome-
content"/>
  </handlers>
  <filters>
    <expression-filter name="test1"
expression="path('(.*)/toberewritten/(.*)') ->
rewrite('$1/rewritten/$2')"/>
    <expression-filter name="test2" expression="method('GET') and
path('.*index.html') -> response-code(403)"/>
  </filters>
</subsystem>
```

For more information about how to configure filters and handlers using the management CLI, see [Configuring the Web Server](#) in the *JBoss EAP 7 Configuration Guide*.

4.4.3. Migrate JBoss Web System Properties

In the previous release of JBoss EAP, system properties could be used to modify the default JBoss Web behavior. For information about how to configure the same behavior in Undertow, see [JBoss Web System Properties Migration Reference](#)

4.4.4. Migrate JBoss Web `jboss-web.xml` Overlay

In JBoss EAP 6, JBoss Web supported the ability to specify additional static files for a web application using the `overlay` element in the `jboss-web.xml` file. This feature did not actually overlay existing files, but instead added static files to a deployment outside of the WAR archive.

In the following `jboss-web.xml` file example, `/tmp/mycontents/test.html` was returned by the JBoss EAP 6 server when you accessed the URL <http://localhost:8080/example/test.html>.

```
<jboss-web>
  <context-root>/example</context-root>
  <overlay>/tmp/mycontents/</overlay>
</jboss-web>
```

Undertow, which replaces JBoss Web in JBoss EAP 7, does not support the `jboss-web.xml` file overlay feature.



IMPORTANT

This overlay feature is available if you apply [Red Hat JBoss Enterprise Application Platform 7.0 Update 05](#) or a newer cumulative patch to your JBoss EAP installation.

4.4.5. Migrate Global Valves

Previous releases of JBoss EAP supported valves. Valves are custom classes inserted into the request processing pipeline for an application before servlet filters to make changes to the request or perform additional processing.

- Global valves are inserted into the request processing pipeline of all deployed applications and are configured in the server configuration file.
- Authenticator valves authenticate the credentials of the request.
- Custom application valves were created by extending the `org.apache.catalina.valves.ValveBase` class and configured in the `<valve>` element of the `jboss-web.xml` descriptor file. These valves must be migrated manually.

This section describes how to migrate global valves. Migration of custom and authenticator valves are covered in the [Migrate Custom Application Valves](#) section of this guide.

Undertow, which replaces JBoss Web in JBoss EAP 7, does not support global valves; however, you should be able to achieve similar functionality by using Undertow handlers. Undertow includes a number of built-in handlers that provide common functionality. It also provides the ability to create custom handlers, which can be used to replace custom valve functionality.

If your application uses valves, you must replace them with the appropriate Undertow handler code to achieve the same functionality when you migrate to JBoss EAP 7.

For more information about how to configure handlers, see [Configuring Handlers](#) in the *JBoss EAP 7 Configuration Guide*.

For more information about how to configure filters, see [Configuring Filters](#) in the *JBoss EAP 7 Configuration Guide*.

Migrate JBoss Web Valves

The following table lists the valves that were provided by JBoss Web in the previous release of JBoss

EAP and the corresponding Undertow built-in handler. The JBoss Web valves are located in the `org.apache.catalina.valves` package.

Table 4.2. Mapping Valves to Handlers

Valve	Handler
AccessLogValve	<code>io.undertow.server.handlers.accesslog.AccessLogHandler</code>
CrawlerSessionManagerValve	<code>io.undertow.servlet.handlers.CrawlerSessionManagerHandler</code>
ExtendedAccessLogValve	<code>io.undertow.server.handlers.accesslog.AccessLogHandler</code>
JDBCAccessLogValve	See the JDBCAccessLogValve Manual Migration Procedure below for instructions.
RemoteAddrValve	<code>io.undertow.server.handlers.IPAddressAccessControlHandler</code>
RemoteHostValve	<code>io.undertow.server.handlers.AccessControlListHandler</code>
RemoteIpValve	<code>io.undertow.server.handlers.ProxyPeerAddressHandler</code>
RequestDumperValve	<code>io.undertow.server.handlers.RequestDumpingHandler</code>
RewriteValve	See Migrate JBoss Web Rewrite Conditions for instructions to migrate these valves manually.
StuckThreadDetectionValve	<code>io.undertow.server.handlers.StuckThreadDetectionHandler</code>

You can use the management CLI `migrate` operation to automatically migrate global valves that meet the following criteria:

- They are limited to the valves listed in the previous table that do not require manual processing.
- They must be defined in the `web` subsystem of the server configuration file.

For more information about the management CLI `migrate` operation, see [Management CLI Migration Operation](#).

JDBCAccessLogValve Manual Migration Procedure

The `org.apache.catalina.valves.JDBCAccessLogValve` valve is an exception to the rule and can not be automatically migrated to `io.undertow.server.handlers.JDBCLogHandler`. Follow the steps below to migrate the following example valve.

```
<valve name="jdbc" module="org.jboss.as.web" class-
name="org.apache.catalina.valves.JDBCAccessLogValve">
  <param param-name="driverName" param-value="com.mysql.jdbc.Driver" />
  <param param-name="connectionName" param-value="root" />
  <param param-name="connectionPassword" param-value="password" />
  <param param-name="connectionURL" param-
```

```

value="jdbc:mysql://localhost:3306/wildfly?
zeroDateTimeBehavior=convertToNull" />
  <param param-name="format" param-value="combined" />
</valve>

```

1. Create a driver module for the database that will store the log entries.
2. Configure the datasource for the database and add the driver to the list of available drivers in the `datasources` subsystem.

```

<datasources>
  <datasource jndi-name="java:jboss/datasources/accessLogDS" pool-
name="accessLogDS" enabled="true" use-java-context="true">
    <connection-url>jdbc:mysql://localhost:3306/wildfly?
zeroDateTimeBehavior=convertToNull</connection-url>
    <driver>mysql</driver>
    <security>
      <user-name>root</user-name>
      <password>Password1!</password>
    </security>
  </datasource>
  ...
<drivers>
  <driver name="mysql" module="com.mysql">
    <driver-class>com.mysql.jdbc.Driver</driver-class>
  </driver>
  ...
</drivers>
</datasources>

```

3. Configure an `expression-filter` in the `undertow` subsystem with the following expression: `jdbc-access-log(datasource=DATASOURCE_JNDI_NAME)`.

```

<filters>
  <expression-filter name="jdbc-access" expression="jdbc-access-
log(datasource='java:jboss/datasources/accessLogDS')" />
  ...
</filters>

```

4.5. JGROUPS SERVER CONFIGURATION CHANGES

4.5.1. JGroups Defaults to a Private Network Interface

In the JBoss EAP 6 default configuration, JGroups used the `public` interface defined in the `<interfaces>` section of the server configuration file.

Because it is a recommended practice to use a dedicated network interface, by default, JGroups now uses the new `private` interface that is defined in the `<interfaces>` section of the server configuration file in JBoss EAP 7.

4.5.2. JGroups Channels Changes

JGroups provides group communication support for HA services in the form of JGroups channels. JBoss EAP 7 introduces `<channel>` elements to the `jgroups` subsystem in the server configuration file. You can add, remove, or change the configuration of JGroups channels using the management CLI.

For more information about how to configure JGroups, see [Cluster Communication with JGroups](#) in the JBoss EAP *Configuration Guide*.

4.6. INFINISPAN SERVER CONFIGURATION CHANGES

4.6.1. Infinispan Default Cache Configuration Changes

In JBoss EAP 6, the default clustered caches for web session replication and EJB replication were replicated `ASYNC` caches. This has changed in JBoss EAP 7. The default clustered caches are now distributed `ASYNC` caches. The replicated caches are no longer even configured by default. See [Configure the Cache Mode](#) in the JBoss EAP *Configuration Guide* for information about how to add a replicated cache and make it the default.

This only affects you when you use the new JBoss EAP 7 default configuration. If you migrate the configuration from JBoss EAP 6, the configuration of the `infinispan` subsystem will be preserved.

4.6.2. Infinispan Cache Strategy Changes

The behavior of `ASYNC` cache strategy has changed in JBoss EAP 7.

In JBoss EAP 6, `ASYNC` cache reads were lock free. Although they would never block, they were prone to dirty reads of stale data, for example on failover. This is because it would allow subsequent requests for the same user to start before the previous request completed. This permissiveness is not acceptable when using distributed mode, since cluster topology changes can affect session affinity and easily result in stale data.

In JBoss EAP 7, `ASYNC` cache reads require locks. Since they now block new requests from the same user until the previous replication finishes, dirty reads are prevented.

4.6.3. Configuring Custom Stateful Session Bean Cache for Passivation

Be aware of the following restrictions when configuring a custom stateful session bean (SFSB) cache for passivation in JBoss EAP 7.0.

- The `idle-timeout` attribute, which is configured in the `infinispan passivation-store` of the `ejb3` subsystem, is deprecated in JBoss EAP 7.0. JBoss EAP 6.4 supported eager passivation, passivating according to the `idle-timeout` value. JBoss EAP 7.0 supports lazy passivation, passivating when the `max-size` threshold is reached.
- In JBoss EAP 7.0, the cluster name used by the EJB client is determined by the actual cluster name of the channel, as configured in the `jgroups` subsystem.
- JBoss EAP 7.0 still allows you to set the `max-size` attribute to control the passivation threshold.
- You should not configure eviction or expiration in your EJB cache configuration.
 - You should configure eviction by using the `max-size` attribute of the `passivation-store` in the `ejb3` subsystem.

- o You should configure expiration by using the `@StatefulTimeout` annotation in the SFSB Java source code or by specifying a `stateful-timeout` value in the `ejb-jar.xml` file.

4.7. EJB SERVER CONFIGURATION CHANGES

There is no `migrate` operation for the `ejb3` subsystem, so if you use the management CLI `migrate` operations to upgrade your other existing JBoss EAP 6.4 configurations, be aware that the `ejb3` subsystem configuration is not migrated. Because the configuration of the `ejb3` subsystem is slightly different in JBoss EAP 7.0 than in JBoss EAP 6.4, you might see exceptions in the server log when you deploy your EJB applications.



IMPORTANT

If you use the JBoss Server Migration Tool to update your server configuration, the `ejb3` subsystem should be configured correctly and you should not see any issues when you deploy your EJB applications.

DuplicateServiceException

The following `DuplicateServiceException` is caused by caching changes in JBoss EAP 7.

DuplicateServiceException in Server Log

```
ERROR [org.jboss.msc.service.fail] (MSC service thread 1-3) MSC000001:
Failed to start service jboss.deployment.unit."mdb-1.0-
SNAPSHOT.jar".cache-dependencies-installer:
org.jboss.msc.service.StartException in service
jboss.deployment.unit."mdb-1.0-SNAPSHOT.jar".cache-dependencies-installer:
Failed to start service
...
Caused by: org.jboss.msc.service.DuplicateServiceException: Service
jboss.infinispan.ejb."mdb-1.0-SNAPSHOT.jar".config is already registered
```

You must reconfigure the cache to resolve this error.

1. Follow the instructions to [Start the Server and the Management CLI](#).
2. Issue the following commands to reconfigure caching in the `ejb3` subsystem.

```
/subsystem=ejb3/file-passivation-store=file:remove
/subsystem=ejb3/cluster-passivation-store=infinispan:remove
/subsystem=ejb3/passivation-store=infinispan:add(cache-
container=ejb, max-size=10000)

/subsystem=ejb3/cache=passivating:remove
/subsystem=ejb3/cache=clustered:remove
/subsystem=ejb3/cache=distributable:add(passivation-
store=infinispan, aliases=[passivating, clustered])
```

4.8. MESSAGING SERVER CONFIGURATION CHANGES

In JBoss EAP 7, ActiveMQ Artemis replaces HornetQ as the JMS support provider. This section describes how to migrate the configuration and related messaging data.

4.8.1. Messaging Subsystem Server Configuration Changes

The `org.jboss.as.messaging` module extension, located in `EAP_HOME/modules/system/layers/base/`, has been replaced by the `org.wildfly.extension.messaging-activemq` extension module.

The `urn:jboss:domain:messaging:3.0` subsystem configuration namespace has been replaced by the `urn:jboss:domain:messaging-activemq:1.0` namespace.

Management Model

In most cases, an effort was made to keep the element and attribute names as similar as possible to those used in previous releases. The following table lists some of the changes.

Table 4.3. Mapping Messaging Attributes

HornetQ Name	ActiveMQ Name
hornetq-server	server
hornetq-serverType	serverType
connectors	connector
discovery-group-name	discovery-group

The management operations invoked on the new `messaging-activemq` subsystem have changed from `/subsystem=messaging/hornetq-server=` to `/subsystem=messaging-activemq/server=`.

You can migrate an existing JBoss EAP 6 `messaging` subsystem configuration to the `messaging-activemq` subsystem on a JBoss EAP 7 server by invoking its `migrate` operation.

```
/subsystem=messaging:migrate
```

Before you execute the `migrate` operation, you can invoke the `describe-migration` operation to review the list of management operations that will be performed to migrate from the existing JBoss EAP 6 `messaging` subsystem configuration to the `messaging-activemq` subsystem on the JBoss EAP 7 server.

```
/subsystem=messaging:describe-migration
```

The `migrate` and `describe-migration` operations also display a list of `migration-warnings` for resources or attributes that can not be migrated automatically.

Messaging Subsystem Migration and Forward Compatibility

The `describe-migration` and `migrate` operations for the `messaging` subsystem provide an additional configuration argument. If you want to configure messaging to allow legacy JBoss EAP 6 clients to connect to the JBoss EAP 7 server, you can add the boolean `add-legacy-entries` argument to the `describe-migration` or `migrate` operation as follows.

```
/subsystem=messaging:describe-migration(add-legacy-entries=true)
/subsystem=messaging:migrate(add-legacy-entries=true)
```

-

If the boolean argument `add-legacy-entries` is set to `true`, the `messaging-activemq` subsystem creates the `legacy-connection-factory` resource and adds `legacy-entries` to the `jms-queue` and `jms-topic` resources.

If the boolean argument `add-legacy-entries` is set to `false`, no legacy resources are created in the `messaging-activemq` subsystem and legacy JMS clients will not be able to communicate with the JBoss EAP 7 servers. This is the default value.

For more information about forward and backward compatibility see the [Backward and Forward Compatibility](#) in *Configuring Messaging* for JBoss EAP.

For more information about the management CLI `migrate` and `describe-migration` operations, see [Management CLI Migration Operation](#).

Change in Behavior of `forward-when-no-consumers` Attribute

The behavior of the `forward-when-no-consumers` attribute has changed in JBoss EAP 7.

In JBoss EAP 6, when `forward-when-no-consumers` was set to `false` and there were no consumers in a cluster, messages were redistributed to all nodes in a cluster.

This behavior has changed in JBoss EAP 7. When `forward-when-no-consumers` is set to `false` and there are no consumers in a cluster, messages are not redistributed. Instead, they are kept on the original node to which they were sent.

Change in Default Cluster Load Balancing Policy

The default cluster load balancing policy has changed in JBoss EAP 7.

In JBoss EAP 6, the default cluster load balancing policy was similar to `STRICT`, which is like setting the legacy `forward-when-no-consumers` parameter to `true`. In JBoss EAP 7, the default is now `ON_DEMAND`, which is like setting the legacy `forward-when-no-consumers` parameter to `false`. For more information about these settings, see [Cluster Connection Attributes](#) in *Configuring Messaging* for JBoss EAP.

Messaging Subsystem XML Configuration

The XML configuration has changed significantly with the new `messaging-activemq` subsystem to provide an XML scheme more consistent with other JBoss EAP subsystems.

It is strongly advised that you do not attempt to modify the JBoss EAP `messaging` subsystem XML configuration to conform to the new `messaging-activemq` subsystem. Instead, invoke the legacy subsystem `migrate` operation. This operation will write the XML configuration of the new `messaging-activemq` subsystem as a part of its execution.

4.8.2. Migrate Messaging Data

Due to the change from HornetQ to ActiveMQ Artemis as the JMS support provider, both the format and the location of the messaging data has changed in JBoss EAP 7.

You can take one of the following two approaches to migrate the data:

- You can export the HornetQ messaging data from the previous release and import it using the management CLI `import-journal` operation. See [Migrate Messaging Data Using Export and Import](#) for more information.
- You can migrate the data from the previous release by configuring a JMS bridge. This process is described in [Migrate Messaging Data Using a JMS Bridge](#).

See [Mapping Messaging Folder Names](#) for details of the changes to the messaging data folder names between the releases.

4.8.2.1. Migrate Messaging Data Using Export and Import

Using this approach, you export the data from the previous release using the `HornetQ exporter` utility. You then import the XML formatted output file by using the `import -journal` operation.



WARNING

If you are using JBoss EAP 7.0, you must apply [Red Hat JBoss Enterprise Application Platform 7.0 Update 05](#) or a newer cumulative patch to your JBoss EAP installation in order to avoid a known issue when reading large messages. This issue does not affect JBoss EAP 7.1 or later.

For more information, see [JBEAP-4407 - Consumer crashes with IndexOutOfBoundsException when reading large messages from imported journal](#).

Export Messaging Data from the Previous Release



IMPORTANT

The JBoss EAP 6 server must be stopped before you export the messaging data.

The `HornetQ exporter` utility generates and exports the messaging data from JBoss EAP 6 to an XML formatted file. This command requires that you specify the paths to the required HornetQ JARs that shipped with JBoss EAP 6, pass the paths to `messagingbindings/`, `messagingjournal/`, `messagingpaging/`, and `messaginglargemessages/` folders from the previous release as arguments, and specify an output file in which to write the exported XML data.

The following is the syntax required by the `HornetQ exporter` utility.

```
java -jar -mp MODULE_PATH org.hornetq.exporter MESSAGING_BINDINGS_DIRECTORY
MESSAGING_JOURNAL_DIRECTORY MESSAGING_PAGING_DIRECTORY
MESSAGING_LARGE_MESSAGES_DIRECTORY > OUTPUT_DATA.xml
```

Create a custom module to ensure the correct versions of the HornetQ JARs, including any JARs installed with patches or upgrades, are loaded and made available to the `exporter` utility. Using your favorite editor, create a new `module.xml` file in the `EAP6_HOME/modules/org/hornetq/exporter/main/` directory and copy the following content:

```
<?xml version="1.0" encoding="UTF-8"?>
<module xmlns="urn:jboss:module:1.1" name="org.hornetq.exporter">
  <main-class
name="org.hornetq.jms.persistence.impl.journal.XmlDataExporter"/>
  <properties>
    <property name="jboss.api" value="deprecated"/>
  </properties>
  <dependencies>
```

```

    <module name="org.hornetq"/>
  </dependencies>
</module>

```



NOTE

The custom module is created in the `modules/` directory, not the `modules/system/layers/base/` directory.

Follow the steps below to export the data.

1. Stop the JBoss EAP 6 server.
2. Create the custom module as described above.
3. Run the following command to export the data.

```

$ java -jar jboss-modules.jar -mp modules/ org.hornetq.exporter
standalone/data/messagingbindings/ standalone/data/messagingjournal/
standalone/data/messagingpaging
standalone/data/messaginglargemessages/ >
OUTPUT_DIRECTORY/OldMessagingData.xml

```

4. Make sure there are no errors or warning messages in the log at the completion of the command.
5. Use tooling available for your operating system to validate the XML in the generated output file.

Import the XML Formatted Messaging Data

You then import the XML formatted output file by using the `import - journal` operation as follows.



IMPORTANT

If your target server has already performed some messaging tasks, be sure to back up your messaging folders before you begin the `import - journal` operation to prevent data loss in the event of an import failure. See [Backing Up Messaging Folder Data](#) for more information.

1. If you are migrating your JBoss EAP 6.4 server to 7.x, make sure you have completed the migration of the server configuration before you begin by using the [management CLI migrate operation](#) or by running the [JBoss Server Migration Tool](#).
2. Start the JBoss EAP 7.x server in normal mode with **NO** JMS clients connected.




IMPORTANT

It is important that you start the server with no JMS clients connected. This is because the `:import - journal` operation behaves like a JMS producer. Messages are immediately available when the operation is in progress. If this operation fails in the middle of the import and JMS clients are connected, there is no way to recover because JMS clients might have already consumed some of the messages.

```
/subsystem=messaging-activemq/server=default:import-  
journal(file=OUTPUT_DIRECTORY/OldMessagingData.xml)
```

+



IMPORTANT

Do **NOT** run this command more than one time as doing so will result in duplicate messages!

Recovering from an Import Messaging Data Failure

If the `import-journal` operation fails, you can attempt to recover by using the following steps.

1. Shut down the JBoss EAP 7.x server.
2. Delete all of the messaging journal folders. See [Backing Up Messaging Folder Data](#) for the management CLI commands to determine the correct directory location for the messaging journal folders.
3. If you backed up the target server messaging data prior to the import, copy the messaging folders from the backup location to the messaging journal directory determined in the prior step.
4. Repeat the steps to [import the XML formatted messaging data](#).

4.8.2.2. Migrate Messaging Data Using a JMS Bridge

Using this approach, you configure and deploy a JMS bridge to the JBoss EAP 7 server that moves messages from the JBoss EAP 6 HornetQ queue to the JBoss EAP 7 ActiveMQ Artemis queue.

A JMS bridge consumes messages from a source JMS queue or topic and sends them to a target JMS queue or topic, which is typically on a different server. It can be used to bridge messages between any JMS servers, as long as they are JMS 1.1 compliant. The source and destination JMS resources are looked up using JNDI and the client classes for the JNDI lookup must be bundled in a module. The module name is then declared in the JMS bridge configuration.

This section describes how to configure the servers and deploy a JMS bridge to move the messaging data from JBoss EAP 6 to JBoss EAP 7.

Configure the JBoss EAP 6 Server

1. Stop the JBoss EAP 6 server.
2. Back up the HornetQ journal and configuration files.
 - By default, the HornetQ journal is located in the `EAP6_HOME/standalone/data/` directory.
 - See [Mapping Messaging Folder Names](#) for default messaging folder locations for each release.
3. Make sure that the `InQueue` JMS queue containing the JMS messages is defined on the JBoss EAP 6 server.
4. Make sure that `messaging` subsystem configuration contains an entry for the `RemoteConnectionFactory` similar to the following.

```

<connection-factory name="RemoteConnectionFactory">
  <entries>
    <entry
name="java:jboss/exported/jms/RemoteConnectionFactory"/>
    </entries>
    ...
</connection-factory>

```

If it does not contain the entry, create one using the following management CLI command:

```

/subsystem=messaging/hornetq-server=default/connection-
factory=RemoteConnectionFactory:add(factory-type=XA_GENERIC,
connector=[netty], entries=
[java:jboss/exported/jms/RemoteConnectionFactory],ha=true,block-on-
acknowledge=true,retry-interval=1000,retry-interval-
multiplier=1.0,reconnect-attempts=-1)

```

Configure the JBoss EAP 7 Server

1. The JMS bridge configuration needs the `org.hornetq` module to connect to the HornetQ server in the previous release. This module and its direct dependencies are not present in JBoss EAP 7, so you must copy the following modules from the previous release.

- Copy the `org.hornetq` module into the JBoss EAP 7 `EAP_HOME/modules/org/` directory.
 - If you did not apply patches to this module, copy this folder from the JBoss EAP 6.4 server: `EAP6_HOME/modules/system/layers/base/org/hornetq/`
 - If you did apply patches to this module, copy this folder from the JBoss EAP 6.4 server: `EAP6_HOME/modules/system/layers/base/.overlays/layer-base-jboss-eap-6.4.x.CP/org/hornetq/`
- Remove the `<resource-root>` for the HornetQ `lib` path from the JBoss EAP 7 `EAP_HOME/modules/org/hornetq/main/module.xml` file.
 - If you did not apply patches to the JBoss EAP 6.4 `org.hornetq` module, remove the following line from the file:

```
<resource-root path="lib"/>
```

- If you did apply patches to the JBoss EAP 6.4 `org.hornetq` module, remove the following lines from the file:

```

<resource-root path="lib"/>
<resource-root path="../../../../../../../org/hornetq/main/lib"/>

```

**WARNING**

Failure to remove the HornetQ `lib` path `resource-root` will cause the bridge to fail with the following error in the log file.

```
2016-07-15 09:32:25,660 ERROR
[org.jboss.as.controller.management-operation]
(management-handler-thread - 2) WFLYCTL0013:
Operation ("add") failed - address: ([
  ("subsystem" => "messaging-activemq"),
  ("jms-bridge" => "myBridge")
]) - failure description: "WFLYMSGAMQ0086:
Unable to load module org.hornetq"
```

- Copy the `org.jboss.netty` module into the JBoss EAP 7 `EAP_HOME/modules/org/jboss/` directory.
 - If you did not apply patches to this module, copy this folder from the JBoss EAP 6.4 server: `EAP6_HOME/modules/system/layers/base/org/jboss/netty/`
 - If you did apply patches to this module, copy this folder from the JBoss EAP 6.4 server: `EAP6_HOME/modules/system/layers/base/.overlays/layer-base-jboss-eap-6.4.x.CP/org/jboss/netty`
- 2. Create the JMS queue to contain the messages received from JBoss EAP 6 server. The following is an example of a management CLI command that creates the `MigratedMessagesQueue` JMS queue to receive the message.

```
jms-queue add --queue-address=MigratedMessagesQueue --entries=
[jms/queue/MigratedMessagesQueue
java:jboss/exported/jms/queue/MigratedMessagesQueue]
```

This creates the following `jms-queue` configuration for the default server in the `messaging-activemq` subsystem of the JBoss EAP 7 server.

```
<jms-queue name="MigratedMessagesQueue"
entries="jms/queue/MigratedMessagesQueue
java:jboss/exported/jms/queue/MigratedMessagesQueue"/>
```

- 3. Make sure that `messaging-activemq` subsystem `default` server contains a configuration for the `InVmConnectionFactory` `connection-factory` similar to the following:

```
<connection-factory name="InVmConnectionFactory" factory-
type="XA_GENERIC" entries="java:/ConnectionFactory" connectors="in-
vm"/>
```

If it does not contain the entry, create one using the following management CLI command:

```
/subsystem=messaging-activemq/server=default/connection-
factory=InVmConnectionFactory:add(factory-type=XA_GENERIC,
connectors=[in-vm], entries=[java:/ConnectionFactory])
```

4. Create and deploy a JMS bridge that reads messages from the **InQueue** JMS queue configured on the JBoss EAP 6 server and transfers them to the **MigratedMessagesQueue** configured on the JBoss EAP 7 server.

```
/subsystem=messaging-activemq/jms-bridge=myBridge:add(add-messageID-
in-header=true,max-batch-time=100,max-batch-size=10,max-retries=-
1,failure-retry-interval=1000,quality-of-
service=AT_MOST_ONCE,module=org.hornetq,source-
destination=jms/queue/InQueue,source-connection-
factory=jms/RemoteConnectionFactory,source-context=
[("java.naming.factory.initial"=>"org.jboss.naming.remote.client.Ini-
tialContextFactory"),
("java.naming.provider.url"=>"remote://127.0.0.1:4447")],target-
destination=jms/queue/MigratedMessagesQueue,target-connection-
factory=java:/ConnectionFactory)
```

This creates the following **jms-bridge** configuration in the **messaging-activemq** subsystem of the JBoss EAP 7 server.

```
<jms-bridge name="myBridge" add-messageID-in-header="true" max-
batch-time="100" max-batch-size="10" max-retries="-1" failure-retry-
interval="1000" quality-of-service="AT_MOST_ONCE"
module="org.hornetq">
  <source destination="jms/queue/InQueue" connection-
factory="jms/RemoteConnectionFactory">
    <source-context>
      <property name="java.naming.factory.initial"
value="org.jboss.naming.remote.client.InitialContextFactory"/>
      <property name="java.naming.provider.url"
value="remote://127.0.0.1:4447"/>
    </source-context>
  </source>
  <target destination="jms/queue/MigratedMessagesQueue"
connection-factory="java:/ConnectionFactory"/>
</jms-bridge>
```

5. If security is configured for JBoss EAP 6, you must also configure the JMS bridge configuration **<source>** element to include a **source-context** that specifies the correct user name and password to use for the JNDI lookup when creating the connection.

Migrate the Data

1. Verify that the information you provided for the following configurations is correct.
 - Any queue and topic names
 - The `java.naming.provider.url` for JNDI lookup
2. Make sure that you have deployed the target JMS destination to the JBoss EAP 7 server.
3. Start both the JBoss EAP 6 and JBoss EAP 7 servers.

4.8.2.3. Mapping Messaging Folder Names

The following table shows the messaging directory names used in the previous release and the corresponding names used in the current release of JBoss EAP. The directories are relative to the `jboss.server.data.dir` directory, which defaults to `EAP_HOME/standalone/data/` if it is not specified.

JBoss EAP 6 Directory Name	JBoss EAP 7 Directory Name
<code>messagingbindings/</code>	<code>activemq/bindings/</code>
<code>messagingjournal/</code>	<code>activemq/journal/</code>
<code>messaginglargemessages/</code>	<code>activemq/largemessages/</code>
<code>messagingpaging/</code>	<code>activemq/paging/</code>



NOTE

The `messaginglargemessages/` and `messagingpaging/` directories might not be present if there are no large messages or if paging is disabled.

4.8.2.4. Backing Up Messaging Folder Data

If your target server has already processed messages, it is a good idea to back up the target message folders to a backup location before you begin. The default location of the messaging folders is `EAP_HOME/standalone/data/activemq/`; however it is configurable. If you are not sure of the location of your messaging data, you can use the following management CLI commands to find the location of the messaging folders.

```
/subsystem=messaging-activemq/server=default/path=journal-
directory:resolve-path
/subsystem=messaging-activemq/server=default/path=paging-
directory:resolve-path
/subsystem=messaging-activemq/server=default/path=bindings-
directory:resolve-path
/subsystem=messaging-activemq/server=default/path=large-messages-
directory:resolve-path
```

Once you know the location of the folders, copy each folder to a safe backup location.

4.8.3. Migrate JMS Destinations

In previous releases of JBoss EAP, JMS destination queues were configured in the `<jms-destinations>` element under the `<hornetq-server>` element in the `messaging` subsystem.

```
<hornetq-server>
...
<jms-destinations>
  <jms-queue name="testQueue">
    <entry name="queue/test"/>
    <entry name="java:jboss/exported/jms/queue/test"/>
```

```

        </jms-queue>
    </jms-destinations>
    ...
</hornetq-server>

```

In JBoss EAP 7, the JMS destination queue is configured in the default `<server>` element of the `messaging-activemq` subsystem.

```

<server name="default">
    ...
    <jms-queue name="testQueue" entries="queue/test
java:jboss/exported/jms/queue/test"/>
    ...
</server>

```

4.8.4. Migrate Messaging Interceptors

Messaging interceptors have changed significantly in JBoss EAP 7 with the replacement of HornetQ with ActiveMQ Artemis as the JMS messaging provider.

The HornetQ `messaging` subsystem included in the previous release of JBoss EAP required that you install the HornetQ interceptors by adding them to a JAR and then modifying the HornetQ `module.xml` file.

The `messaging-activemq` subsystem included in JBoss EAP 7 does not require modification of a `module.xml` file. User interceptor classes, which now implement the Apache ActiveMQ Artemis [Interceptor](#) interface, can now be loaded from any server module. You specify the module from which the interceptor should be loaded in the `messaging-activemq` subsystem of the server configuration file.

Example Interceptor Configuration

```

<subsystem xmlns="urn:jboss:domain:messaging-activemq:1.0">
    <server name="default">
        ...
        <incoming-interceptors>
            <class name="com.mycompany.incoming.myInterceptor"
module="com.mycompany" />
            <class name="com.othercompany.incoming.myOtherInterceptor"
module="com.othercompany" />
        </incoming-interceptors>
        <outgoing-interceptors>
            <class name="com.mycompany.outgoing.myInterceptor"
module="com.mycompany" />
            <class name="com.othercompany.outgoing.myOtherInterceptor"
module="com.othercompany" />
        </outgoing-interceptors>
    </server>
</subsystem>

```

4.8.5. Replace Netty Servlet Configuration

In JBoss EAP 6, you could configure a servlet engine to work with the Netty Servlet transport. Because ActiveMQ Artemis replaces HornetQ as the built-in messaging provider in JBoss EAP 7, this

configuration is no longer available. You must replace the servlet configuration to use the new built-in messaging http connectors and http acceptors instead.

4.8.6. Changes in JMS Serialization Behavior Between Releases

The `serialVersionUID` of `javax.jms.JMSEException` changed between JMS 1.1 and JMS 2.0.0. This means that if an instance of a `JMSEException`, or any of its subclasses, is serialized using JMS 1.1, it cannot be deserialized using JMS 2.0.0. The reverse is also true. If an instance of `JMSEException` is serialized using JMS 2.0.0, it cannot be deserialized using JMS 1.1. In both of these cases, it throws an exception similar to the following:

```
javax.jms.JMSEException: javax.jms.JMSEException; local class incompatible:
stream classdesc serialVersionUID = 8951994251593378324, local class
serialVersionUID = 2368476267211489441
```

This issue is fixed in the JMS 2.0.1 maintenance release.

The following table details the JMS implementation for each JBoss EAP release.

Table 4.4. JMS Implementation for Each JBoss EAP Release

JBoss EAP Version	JMS Implementation	JMS version
6.4	HornetQ	JMS 1.1
7.0	Apache ActiveMQ Artemis	JMS 2.0.0

Be aware that the `serialVersionUID` incompatibility can result in a migration issue in the following situation.

- If you send a message that contains a `JMSEException` using a JBoss EAP 6.4 client, migrate your messaging data to JBoss EAP 7.0, and then attempt to deserialize that message using a JBoss EAP 7.0 client, the deserialization will fail and it will throw an exception. This is because the `serialVersionUID` in JMS 1.1 is *not* compatible with the one in JMS 2.0.0.



IMPORTANT

Red Hat recommends that you consume all JMS 1.1 messages that contain `JMSEExceptions` before migrating messaging data from JBoss EAP 6.4 to JBoss EAP 7.0.

4.9. JMX MANAGEMENT CHANGES

The HornetQ component in JBoss EAP 6 provided its own JMX management; however, it was not recommended and is now deprecated and no longer supported. If you relied on this feature in JBoss EAP 6, you must migrate your management tooling to use either the JBoss EAP management CLI or the JMX management provided with JBoss EAP 7.

You must also upgrade your client libraries to use the `jboss-client.jar` that ships with JBoss EAP 7.

The following is an example of HornetQ JMX management code that was used in JBoss EAP 6.

```

JMXConnector connector = null;
try {
    HashMap environment = new HashMap();
    String[] credentials = new String[]{"admin", "Password123!"};
    environment.put(JMXConnector.CREDENTIALS, credentials);

    // HornetQ used the protocol "remoting-jmx" and port "9999"
    JMXServiceURL beanServerUrl = new JMXServiceURL("service:jmx:remoting-
jmx://127.0.0.1:9999");

    connector = JMXConnectorFactory.connect(beanServerUrl, environment);
    MBeanServerConnection mbeanServer =
connector.getMBeanServerConnection();

    // The JMX object name pointed to the HornetQ JMX management
    ObjectName objectName = new
ObjectName("org.hornetq:type=Server,module=JMS");

    // The invoked method name was "listConnectionIDs"
    String[] connections = (String[]) mbeanServer.invoke(objectName,
"listConnectionIDs", new Object[]{}, new String[]{});
    for (String connection : connections) {
        System.out.println(connection);
    }
} finally {
    if (connector != null) {
        connector.close();
    }
}

```

The following is an example of the equivalent code needed for ActiveMQ Artemis in JBoss EAP 7.

```

JMXConnector connector = null;
try {
    HashMap environment = new HashMap();
    String[] credentials = new String[]{"admin", "Password123!"};
    environment.put(JMXConnector.CREDENTIALS, credentials);

    // ActiveMQ Artemis uses the protocol "remote+http" and port "9990"
    JMXServiceURL beanServerUrl = new
JMXServiceURL("service:jmx:remote+http://127.0.0.1:9990");

    connector = JMXConnectorFactory.connect(beanServerUrl, environment);
    MBeanServerConnection mbeanServer =
connector.getMBeanServerConnection();

    // The JMX object name points to the new JMX management in the
`messaging-activemq` subsystem
    ObjectName objectName = new ObjectName("jboss.as:subsystem=messaging-
activemq,server=default");

    // The invoked method name is now "listConnectionIds"
    String[] connections = (String[]) mbeanServer.invoke(objectName,
"listConnectionIds", new Object[]{}, new String[]{});
    for (String connection : connections) {
        System.out.println(connection);
    }
}

```

```

    }
  } finally {
    if (connector != null) {
      connector.close();
    }
  }
}

```

Notice that the method names and parameters have changed in the new implementation. You can find the new method names in the JConsole by following these steps.

1. Connect to the JConsole using the following command.

```
EAP_HOME/bin/jconsole.sh
```

2. Connect to JBoss EAP local process. Note that it should start with "jboss-modules.jar".
3. In the MBeans tab, choose **jboss.as** → **messaging-activemq** → **default** → **Operations** to display the list of method names and attributes.

4.10. ORB SERVER CONFIGURATION CHANGES

The JacORB implementation has been replaced with a downstream branch of the OpenJDK ORB in JBoss EAP 7.

The `org.jboss.as.jacorb` extension module, located in `EAP_HOME/modules/system/layers/base/`, has been replaced by the `org.wildfly.iiop-openjdk` extension module.

The `urn:jboss:domain:jacorb:1.4` subsystem configuration namespace in the server configuration file has been replaced by the `urn:jboss:domain:iiop-openjdk:1.0` namespace.

The following is an example of the default `jacorb` system configuration in JBoss EAP 6.

```

<subsystem xmlns="urn:jboss:domain:jacorb:1.4">
  <orb socket-binding="jacorb" ssl-socket-binding="jacorb-ssl">
    <initializers security="identity" transactions="spec"/>
  </orb>
</subsystem>

```

The following is an example of the default `iiop-openjdk` subsystem configuration in JBoss EAP 7.

```

<subsystem xmlns="urn:jboss:domain:iiop-openjdk:1.0">
  <orb socket-binding="jacorb" ssl-socket-binding="jacorb-ssl" />
  <initializers security="identity" transactions="spec" />
</subsystem>

```

The new `iiop-openjdk` subsystem configuration accepts only a subset of the legacy elements and attributes. The following is an example of a `jacorb` subsystem configuration in the previous release of JBoss EAP that contains all valid elements and attributes:

```

<subsystem xmlns="urn:jboss:domain:jacorb:1.4">
  <orb name="JBoss" print-version="off" use-imr="off" use-bom="off"
cache-typecodes="off"
  cache-poa-names="off" giop-minor-version="2" socket-

```

```

binding="jacob" ssl-socket-binding="jacob-ssl">
  <connection retries="5" retry-interval="500" client-timeout="0"
server-timeout="0"
  max-server-connections="500" max-managed-buf-size="24" outbuf-
size="2048"
  outbuf-cache-timeout="-1"/>
  <initializers security="off" transactions="spec"/>
</orb>
<poa monitoring="off" queue-wait="on" queue-min="10" queue-max="100">
  <request-processors pool-size="10" max-threads="32"/>
</poa>
<naming root-context="JBoss/Naming/root" export-corbaloc="on"/>
<interop sun="on" comet="off" iona="off" chunk-custom-rmi-
valuetypes="on"
  lax-boolean-encoding="off" indirection-encoding-disable="off"
strict-check-on-tc-creation="off"/>
  <security support-ssl="off" add-component-via-interceptor="on" client-
supports="MutualAuth"
  client-requires="None" server-supports="MutualAuth" server-
requires="None"/>
  <properties>
    <property name="some_property" value="some_value"/>
  </properties>
</subsystem>

```

The following element attributes are no longer supported and must be removed.

Table 4.5. Attributes to Remove

Element	Unsupported Attributes
<code><orb></code>	<ul style="list-style-type: none"> • client-timeout • max-managed-buf-size • max-server-connections • outbuf-cache-timeout • outbuf-size • connection retries • retry-interval • name • server-timeout

Element	Unsupported Attributes
<poa>	<ul style="list-style-type: none"> • queue-min • queue-max • pool-size • max-threads

The following **on/off** attributes are no longer supported and will not be migrated when you run the management CLI **migrate** operation. If they are set to **on**, you will get a migration warning. Other **on/off** attributes that are not mentioned in this table, for example **<security support-ssl="on|off">**, are still supported and will be migrated successfully. The only difference is that their values will be changed from **on/off** to **true/false**.

Table 4.6. Attributes to Turn Off or Remove

Element	Attributes to Set to Off
<orb>	<ul style="list-style-type: none"> • cache-poa-names • cache-typecodes • print-version • use-bom • use-imr
<interop>	<p>(all except sun)</p> <ul style="list-style-type: none"> • comet • iona • chunk-custom-rmi-valuetypes • indirection-encoding-disable • lax-boolean-encoding • strict-check-on-tc-creation
<poa/>	<ul style="list-style-type: none"> • monitoring • queue-wait

4.11. MIGRATE THE THREADS SUBSYSTEM CONFIGURATION

The JBoss EAP 6 server configuration included a `threads` subsystem that was used to manage thread pools across the various subsystems in the server.

The `threads` subsystem is no longer available in JBoss EAP 7. Instead, each subsystem is responsible for managing its own thread pools.

For information about how to configure thread pools for the `infinispan` subsystem, see [Configure Infinispan Thread Pools](#) in the JBoss EAP *Configuration Guide*.

For information about how to configure thread pools for the `jgroups` subsystem, see [Configure JGroups Thread Pools](#) in the JBoss EAP *Configuration Guide*.

In JBoss EAP 6, you configured thread pools for connectors and listeners for the `web` subsystem by referencing an `executor` that was defined in the `threads` subsystem. In JBoss EAP 7, you now configure thread pools for the `undertow` subsystem by referencing a `worker` that is defined in the `io` subsystem. For more information, see [Configuring the IO Subsystem](#) in the JBoss EAP *Configuration Guide*.

For information about about changes to thread pool configuration in the `remoting` subsystem, see [Migrate the Remoting Subsystem Configuration](#) in this guide, and [Configuring the Endpoint](#) in the JBoss EAP *Configuration Guide*.

4.12. MIGRATE THE REMOTING SUBSYSTEM CONFIGURATION

In JBoss EAP 6, you configured the thread pool for the `remoting` subsystem by setting various `worker-*` attributes. The worker thread pool is no longer configured in the `remoting` subsystem in JBoss EAP 7 and if you attempt to modify the existing configuration, you will see the following message.

```
WFLYRMT0022: Worker configuration is no longer used, please use endpoint worker configuration
```

In JBoss EAP 7, the worker thread pool is replaced by an endpoint configuration that references a `worker` defined in the `io` subsystem.

For information about how to configure the endpoint, see [Configuring the Endpoint](#) in the JBoss EAP *Configuration Guide*.

4.13. WEBSOCKET SERVER CONFIGURATION CHANGES

To use WebSockets in JBoss EAP 6, you had to enable the non blocking Java NIO2 connector protocol for the `http` connector in the `web` subsystem of the JBoss EAP server configuration file using a command similar to the following.

```
/subsystem=web/connector=http/write-attribute(name=protocol,value=org.apache.coyote.http11.Http11NioProtocol)
```

To use WebSockets in an application, you also had to create a `<enable-websockets>` element in the application `WEB-INF/jboss-web.xml` file and set it to `true`.

In JBoss EAP 7, you no longer need to configure the server for default WebSocket support or configure the application to use it. WebSockets are a requirement of the Java EE 7 specification and the required protocols are configured by default. More complex WebSocket configuration is done in the `servlet-`

container of the `undertow` subsystem of the JBoss EAP server configuration file. You can view the available settings using the following command.

```
/subsystem=undertow/servlet-container=default/setting=websockets:read-
resource(recursive=true)
{
  "outcome" => "success",
  "result" => {
    "buffer-pool" => "default",
    "dispatch-to-worker" => true,
    "worker" => "default"
  }
}
```

WebSocket code examples can also be found in the quickstarts that ship with JBoss EAP.

4.14. SINGLE SIGN-ON SERVER CHANGES

The `infinispan` subsystem still provides distributed caching support for HA services in the form of Infinispan caches in JBoss EAP 7; however the caching and distribution of authentication information is handled differently than in previous releases.

In JBoss EAP 6, if single sign-on (SSO) was not provided an Infinispan cache, the cache was not distributed.

In JBoss EAP 7, SSO is distributed automatically when you select the HA profile. When running the HA profile, each host has its own Infinispan cache, which is based on the default cache of the web cache container. This cache stores the relevant session and SSO cookie information for the host. JBoss EAP handles propagation of individual cache information to all hosts. There is no way to specifically assign an Infinispan cache to SSO in JBoss EAP 7.

In JBoss EAP 7, SSO is configured in the `undertow` subsystem of the server configuration file.

There are no application code changes required for SSO when migrating to JBoss EAP 7.

4.15. DATASOURCE CONFIGURATION CHANGES

4.15.1. JDBC Datasource Driver Name

When you configured a datasource in the previous release of JBoss EAP, the value specified for the driver name depended on the number of classes listed in the `META-INF/services/java.sql.Driver` file contained in the JDBC driver JAR.

Driver Containing a Single Class

If the `META-INF/services/java.sql.Driver` file specified only one class, the driver name value was simply the name of the JDBC driver JAR. This has not changed in JBoss EAP 7.

Driver Containing Multiple Classes

In JBoss EAP 6, if there was more than one class listed in `META-INF/services/java.sql.Driver` file, you specified which class was the driver class by appending its name to the JAR name, along with the major and minor version, in the following format.

```
JAR_NAME + DRIVER_CLASS_NAME + "_" + MAJOR_VERSION + "_" + MINOR_VERSION
```

In JBoss EAP 7, this has changed. You now specify the driver name using the following format.

```
JAR_NAME + "_" + DRIVER_CLASS_NAME + "_" + MAJOR_VERSION + "_" +
MINOR_VERSION
```



NOTE

An underscore has been added between the JAR_NAME and the DRIVER_CLASS_NAME.

The MySQL 5.1.31 JDBC driver is an example of a driver that contains two classes. The driver class name is `com.mysql.jdbc.Driver`. The following examples demonstrate the differences between how you specify the driver name in the previous and current release of JBoss EAP.

Example JBoss EAP 6 Driver Name

```
mysql-connector-java-5.1.31-bin.jarcom.mysql.jdbc.Driver_5_1
```

Example JBoss EAP 7 Driver Name

```
mysql-connector-java-5.1.31-bin.jar_com.mysql.jdbc.Driver_5_1
```

4.16. SECURITY SERVER CONFIGURATION CHANGES

For information about Java Security Manager server configuration changes, see [Considerations Moving from Previous Versions](#) in *How To Configure Server Security* for JBoss EAP.

4.17. TRANSACTIONS SUBSYSTEM CHANGES

Some Transaction Manager configuration attributes that were available in the `transactions` subsystem in JBoss EAP 6 have changed in JBoss EAP 7.

Removed Transactions Subsystem Attributes

The following table lists the JBoss EAP 6 attributes that were removed from the `transactions` subsystem in JBoss EAP 7 and the equivalent replacement attributes.

Attribute in JBoss EAP 6	Replacement in JBoss EAP 7
<code>path</code>	<code>object-store-path</code>
<code>relative-to</code>	<code>object-store-relative-to</code>

Deprecated Transactions Subsystem Attributes

The following attributes that were available in the `transactions` subsystem in JBoss EAP 6 are deprecated in JBoss EAP 7. The deprecated attributes might be removed in a future release of the product. The following table lists the equivalent replacement attributes.

Attribute in JBoss EAP 6	Replacement in JBoss EAP 7
use-hornetq-store	use-journal-store
hornetq-store-enable-async-io-to	journal-store-enable-async-io
enable-statistics	statistics-enabled

4.18. CHANGES TO MOD_CLUSTER CONFIGURATION

The configuration for static proxy lists in `mod_cluster` has changed in JBoss EAP 7.

In JBoss EAP 6, you configured the `proxy-list` attribute, which was a comma-separated list of httpd proxy addresses specified in the format of `hostname:port`.

The `proxy-list` attribute is deprecated in JBoss EAP 7. It has been replaced by the `proxies` attribute, which is a list of outbound socket binding names.

This change impacts how you define a static proxy list, for example, when disabling advertising for `mod_cluster`. For information about how to disable advertising for `mod_cluster`, see [Disable Advertising for mod_cluster](#) in the JBoss EAP *Configuration Guide*.

For more information about `mod_cluster` attributes, see [ModCluster Subsystem Attributes](#) in the JBoss EAP *Configuration Guide*.

CHAPTER 5. APPLICATION MIGRATION CHANGES

5.1. WEB SERVICES APPLICATION CHANGES

JBossWS 5 brings new features and performance improvements to JBoss EAP 7 web services, mainly through upgrades of the [Apache CXF](#), [Apache WSS4J](#), and [Apache Santuario](#) components.

5.1.1. JAX-RPC Support Changes

The Java API for XML-based RPC (JAX-RPC) was deprecated in Java EE 6 and is optional in Java EE 7. It is no longer available or supported in JBoss EAP 7. Applications that use JAX-RPC must be migrated to use [JAX-WS](#), which is the current Java EE standard web services framework.

Use of JAX-RPC web services can be identified in any of the following ways:

- The presence of a JAX-RPC mapping file, which is an XML file with the root element `<java-wsdl-mapping>`.
- The presence of a `webservicess.xml` XML descriptor file that contains a `<webservice-description>` element, which includes a `<jaxrpc-mapping-file>` child element. The following is an example of `webservicess.xml` descriptor file that defines a JAX-RPC web service.

```
<webservicess xmlns="http://java.sun.com/xml/ns/j2ee"
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  xsi:schemaLocation="http://java.sun.com/xml/ns/j2ee
http://www.ibm.com/webservicess/xsd/j2ee_web_services_1_1.xsd"
  version="1.1">
  <webservice-description>
    <webservice-description-name>HelloService</webservice-
description-name>
    <wsdl-file>WEB-INF/wsdl/HelloService.wsdl</wsdl-file>
    <jaxrpc-mapping-file>WEB-INF/mapping.xml</jaxrpc-mapping-file>
    <port-component>
      <port-component-name>Hello</port-component-name>
      <wsdl-port>HelloPort</wsdl-port>
      <service-endpoint-
interface>org.jboss.chap12.hello.Hello</service-endpoint-interface>
      <service-impl-bean>
        <servlet-link>HelloWorldServlet</servlet-link>
      </service-impl-bean>
    </port-component>
  </webservice-description>
</webservicess>
```

- The presence of an `ejb-jar.xml` file, which contains a `<service-ref>` that references a JAX-RPC mapping file.

5.1.2. Apache CXF Spring Web Services Changes

In previous releases of JBoss EAP, you could customize the JBossWS and Apache CXF integration by including a `jbossws-cxf.xml` configuration file with the endpoint deployment archive. One use case for this was to configure interceptor chains for web service client and server endpoints on the Apache CXF bus. This integration required Spring to be deployed in the JBoss EAP server.

Spring integration is no longer supported in JBoss EAP 7. Any application that contains a `jbossws-cxf.xml` descriptor configuration file must be modified to replace the custom configuration defined in that file. While it is still possible to directly access the Apache CXF API, be aware that the application will not be portable.

The suggested approach is to replace Spring custom configurations with the new JBossWS descriptor configuration options where possible. The JBossWS descriptor-based approach provides similar functionality without requiring modification of the client endpoint code. In some cases, you can replace Spring with Context Dependency Injection (CDI).

Apache CXF Interceptors

The JBossWS descriptor provides new configuration options that allow you to declare the interceptors without modifying the client endpoint code. Instead you declare interceptors within predefined client and endpoint configurations by specifying a list of interceptor class names for the `cxf.interceptors.in` and `cxf.interceptors.out` properties.

The following is an example of a `jaxws-endpoint-config.xml` file that declares interceptors using these properties.

```
<?xml version="1.0" encoding="UTF-8"?>
<jaxws-config xmlns="urn:jboss:jbossws-jaxws-config:4.0"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:javabee="http://java.sun.com/xml/ns/javabee"
  xsi:schemaLocation="urn:jboss:jbossws-jaxws-config:4.0 schema/jbossws-
jaxws-config_4_0.xsd">
  <endpoint-config>
    <config-
name>org.jboss.test.ws.jaxws.cxf.interceptors.EndpointImpl</config-name>
    <property>
      <property-name>cxf.interceptors.in</property-name>
      <property-
value>org.jboss.test.ws.jaxws.cxf.interceptors.EndpointInterceptor,org.jbo
ss.test.ws.jaxws.cxf.interceptors.FooInterceptor</property-value>
    </property>
    <property>
      <property-name>cxf.interceptors.out</property-name>
      <property-
value>org.jboss.test.ws.jaxws.cxf.interceptors.EndpointCounterInterceptor<
/property-value>
    </property>
  </endpoint-config>
</jaxws-config>
```

Apache CXF Features

The JBossWS descriptor allows you to declare features within predefined client and endpoint configurations by specifying a list of feature class names for the `cxf.features` property.

The following is an example of a `jaxws-endpoint-config.xml` file that declares a feature using this property.

```
<?xml version="1.0" encoding="UTF-8"?>
<jaxws-config xmlns="urn:jboss:jbossws-jaxws-config:4.0"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:javabee="http://java.sun.com/xml/ns/javabee"
  xsi:schemaLocation="urn:jboss:jbossws-jaxws-config:4.0 schema/jbossws-
```

```

jaxws-config_4_0.xsd">
  <endpoint-config>
    <config-name>Custom FI Config</config-name>
    <property>
      <property-name>cxf.features</property-name>
      <property-value>org.apache.cxf.feature.FastInfosetFeature</property-
value>
    </property>
  </endpoint-config>
</jaxws-config>

```

Apache CXF HTTP Transport

In Apache CXF, HTTP transport configuration is achieved by specifying `org.apache.cxf.transport.http.HTTPConduit` options. JBossWS integration allows conduits to be modified programmatically using the Apache CXF API as follows.

```

import org.apache.cxf.frontend.ClientProxy;
import org.apache.cxf.transport.http.HTTPConduit;
import org.apache.cxf.transports.http.configuration.HTTPClientPolicy;

// Set chunking threshold before using a JAX-WS port client
...
HTTPConduit conduit =
(HTTPConduit)ClientProxy.getClient(port).getConduit();
HTTPClientPolicy client = conduit.getClient();

client.setChunkingThreshold(8192);
...

```

You can also control and override the Apache CXF `HTTPConduit` default values by setting system properties.

Property	Type	Description
<code>cxf.client.allowChunking</code>	Boolean	Specifies whether to send requests using chunking.
<code>cxf.client.chunkingThreshold</code>	Integer	Sets the threshold at which switching from non-chunking to chunking mode.
<code>cxf.client.connectionTimeout</code>	Long	Sets the number of milliseconds for the connection timeout.
<code>cxf.client.receiveTimeout</code>	Long	Sets the number of milliseconds for the receive timeout.
<code>cxf.client.connection</code>	String	Specifies whether to use the Keep-Alive or close connection type.
<code>cxf.tls-client.disableCNCheck</code>	Boolean	Specifies whether to disable the CN host name check.

5.1.3. WS-Security Changes

- If your application contains a custom callback handler that accesses the `org.apache.ws.security.WSPasswordCallback` class, be aware that this class has moved to package `org.apache.wss4j.common.ext`.
- Most of the SAML bean objects from the `org.apache.ws.security.saml.ext` package have been moved to the `org.apache.wss4j.common.saml` package.
- Use the RSA v1.5 key transport and all related algorithms are disallowed by default.
- The Security Token Service (STS) previously only validated `onBehalfOf` tokens. It now also validates `ActAs` tokens. As a consequence, a valid username and password must be specified in the `UsernameToken` that is provided for the `ActAs` token.
- SAML Bearer tokens are now required to have an internal signature. The `org.apache.wss4j.dom.validate.SamlAssertionValidator` class now has a `setRequireBearerSignature()` method to enable or disable the signature verification.

5.1.4. JBoss Modules Structure Change

The `cxf-api` and `cxf-rt-core` JARs have been merged into one `cxf-core` JAR. As a consequence, the `org.apache.cxf` module in JBoss EAP now contains the `cxf-core` JAR and exposes more classes than in the previous release.

5.1.5. Bouncy Castle Requirements and Changes

If you want to use AES encryption with Galois/Counter Mode (GCM) for symmetric encryption in XML/WS-Security, you need the BouncyCastle Security Provider.

JBoss EAP 7 ships with the `org.bouncycastle` module and JBossWS is now able to rely on its class loader to get and use the BouncyCastle Security Provider. Therefore it is no longer necessary to statically install BouncyCastle in the current JVM. For applications running outside of the container, the security provider can be made available to JBossWS by adding a BouncyCastle library to the class path.

You can disable this behavior by setting the `org.jboss.ws.cxf.noLocalBC` property value to `true` in the `jaxws-endpoint-config.xml` deployment descriptor file for the server or the `jaxws-client-config.xml` descriptor file for clients.

If you want to use a different version than the one that ships with JBoss EAP, you can still statically install BouncyCastle to the JVM. In that case, the statically installed BouncyCastle Security Provider is chosen over the provider present in the class path. To avoid any issues, you must use BouncyCastle 1.49, 1.51, or greater.

5.1.6. Apache CXF Bus Selection Strategy

The default bus selection strategy for clients running in-container has changed from `THREAD_BUS` to `TCCL_BUS`. For clients running out-of container, the default strategy is still `THREAD_BUS`. You can restore the behavior to that of the previous release by using either of the following methods.

- Boot the JBoss EAP server with the system property `org.jboss.ws.cxf.jaxws-client.bus.strategy` value set to `THREAD_BUS`.
- Explicitly set the selection strategy in the client code.

5.1.7. JAX-WS 2.2 Requirements for WebServiceRef

Containers must use JAX-WS 2.2 style constructors, which include the [WebServiceFeature](#) class as an argument in the constructor, to build clients that are injected into web service references. JBoss EAP 6.4, which ships with JBossWS 4, hides that requirement. JBoss EAP 7 ships with JBossWS 5, which no longer hides this requirement. This means that user provided service classes injected by the container must implement JAX-WS 2.2 or later by updating the existing code to use the [javax.xml.ws.Service](#) constructor that includes one or more [WebServiceFeature](#) arguments.

```
protected Service(URL wsdlDocumentLocation,
                  QName serviceName,
                  WebServiceFeature... features)
```

5.1.8. IgnoreHttpsHost CN Check Change

In previous releases, you could disable the HTTPS URL hostname check against a service's Common Name (CN) given in its certificate by setting the system property `org.jboss.security.ignoreHttpsHost` to `true`. This system property name has been replaced with `cxf.tls-client.disableCNCheck`.

5.1.9. Server Side Configuration and Class Loading

As a consequence of enabling injections into service endpoint and service client handlers, it is no longer possible to automatically load handler classes from the `org.jboss.as.webservices.server.integration` JBoss module. If your application depends on a given predefined configuration, you might need to explicitly define new module dependencies for your deployment. For more information, see [Migrate Explicit Module Dependencies](#)

5.1.10. Deprecation of Java Endorsed Standards Override Mechanism

The [Java Endorsed Standards Override Mechanism](#) was deprecated in JDK 1.8_40 with intent to remove it in JDK 9. This mechanism allowed developers to make libraries available to all deployed applications by placing JARs into an endorsed directory within the JRE.

If your application uses the JBossWS implementation of Apache CXF, JBoss EAP 7 ensures the required dependencies are added in the correct order and you should not be impacted by this change. If your application accesses Apache CXF directly, you must now provide the Apache CXF dependencies after the JBossWS dependencies as part of your application deployment.

5.1.11. Specification of Descriptor in EAR Archive

In previous releases of JBoss EAP, you could configure the `jboss-webservices.xml` deployment descriptor file for EJB web service deployments in the `META-INF/` directory of JAR archives or in the `WEB-INF/` directory for POJO web service deployments and EJB web service endpoints bundled in WAR archives.

In JBoss EAP 7, you can now configure the `jboss-webservices.xml` deployment descriptor file in the `META-INF/` directory of an EAR archive. If a `jboss-webservices.xml` file is found both in the EAR archive and the JAR or WAR archive, the configuration data in the `jboss-webservices.xml` file for the JAR or WAR overrides the corresponding data in the EAR descriptor file.

5.2. UPDATE THE REMOTE URL CONNECTOR AND PORT

In JBoss EAP 7, the default connector has changed from `remote` to `http-remoting` and the default remote connection port has changed from `4447` to `8080`. The JNDI provider URL for the default configuration has changed from `remote://localhost:4447` to `http-remoting://localhost:8080`.

If you use the JBoss EAP 7 `migrate` operation to update your configuration, you do not need to modify the remote connector, remote port, or JNDI provider URLs because the migration operation preserves the JBoss EAP 6 remoting connector and `4447` port configuration settings in the subsystem configuration. For more information about the `migrate` operation, see [Management CLI Migration Operation](#).

If you do not use the `migrate` operation and instead run with the new JBoss EAP 7 default configuration, you must change the remote connector, remote port, and JNDI provider URL to use the new settings as described above.

5.3. MESSAGING APPLICATION CHANGES

5.3.1. Replace or Update JMS Deployment Descriptors

The proprietary HornetQ JMS resource deployment descriptor files identified by the naming pattern `-jms.xml` no longer work in JBoss EAP 7. The following is an example of a JMS resource deployment descriptor file in JBoss EAP 6.

```
<?xml version="1.0" encoding="UTF-8"?>
<messaging-deployment xmlns="urn:jboss:messaging-deployment:1.0">
  <hornetq-server>
    <jms-destinations>
      <jms-queue name="testQueue">
        <entry name="queue/test"/>
        <entry name="java:jboss/exported/jms/queue/test"/>
      </jms-queue>
      <jms-topic name="testTopic">
        <entry name="topic/test"/>
        <entry name="java:jboss/exported/jms/topic/test"/>
      </jms-topic>
    </jms-destinations>
  </hornetq-server>
</messaging-deployment>
```

If you used `-jms.xml` JMS deployment descriptors in your application in the previous release, you can either convert your application to use the standard Java EE 7 deployment descriptor as specified in section EE.5.18 of the [Java EE 7 specification](#) or you can update the deployment descriptor to use the `messaging-activemq-deployment` schema instead.

If you choose to update the descriptor, you need to make the following modifications.

- Change the namespace from `"urn:jboss:messaging-deployment:1.0"` to `"urn:jboss:messaging-activemq-deployment:1.0"`.
- Change the `<hornetq-server>` element name to `<server>`.

The modified file should look like the following example.

```
<?xml version="1.0" encoding="UTF-8"?>
```

```

<messaging-deployment xmlns="urn:jboss:messaging-activemq-deployment:1.0">
  <server>
    <jms-destinations>
      <jms-queue name="testQueue">
        <entry name="queue/test"/>
        <entry name="java:jboss/exported/jms/queue/test"/>
      </jms-queue>
      <jms-topic name="testTopic">
        <entry name="topic/test"/>
        <entry name="java:jboss/exported/jms/topic/test"/>
      </jms-topic>
    </jms-destinations>
  </server>
</messaging-deployment>

```

For information about server configuration changes related to messaging, see [Messaging Server Configuration Changes](#).

5.3.2. Update External JMS Clients

JBoss EAP 7 still supports the JMS 1.1 API, so you do not need to modify your code.

The default remote connector and port has changed in JBoss EAP 7. For details about this change, see [Update the Remote URL Connector and Port](#).

If you migrate your server configuration using the `migrate` operation, the old settings are preserved and you do not need to update your `PROVIDER_URL`. However, if you run with the new JBoss EAP 7 default configuration, you must change the `PROVIDER_URL` in the client code to use the new `http-remoting://localhost:8080` setting. For more information, see [Migrate Remote Naming Client Code](#).

If you plan to migrate your code to use the JMS 2.0 API, see the `helloworld-jms` quickstart for a working example.

5.3.3. Replace the HornetQ API

JBoss EAP 6 included the `org.hornetq` module, which allowed you to use the [HornetQ API](#) in your application source code.

Apache ActiveMQ Artemis replaces HornetQ in JBoss EAP 7, so you must migrate any code that used the HornetQ API to use the [Apache ActiveMQ Artemis API](#). The libraries for this API are included in the `org.apache.activemq.artemis` module.

ActiveMQ Artemis is an evolution of HornetQ, so many of the concepts still apply.

5.4. JAX-RS AND RESTEASY APPLICATION CHANGES

The previous release of JBoss EAP bundled RESTEasy 2, which was an implementation of JAX-RS 1.x. JBoss EAP 7 includes RESTEasy 3, which is an implementation of JAX-RS 2.0 as defined by the [JSR 339: JAX-RS 2.0: The Java API for RESTful Web Services](#) specification. For more information about the Java API for RESTful Web Services, see the [JAX-RS 2.0 API Specification](#).

The version of Jackson included in JBoss EAP has changed. The previous version of JBoss EAP included Jackson 1.9.9. JBoss EAP 7 now includes Jackson 2.6.3 or greater.

This section describes how these changes might impact applications that use RESTEasy or JAX-RS.

5.4.1. RESTEasy Deprecated Classes

Interceptor and MessageBody Classes

[JSR 311: JAX-RS: The Java™ API for RESTful Web Services](#) did not include an interceptor framework, so RESTEasy 2 provided one. [JSR 339: JAX-RS 2.0: The Java API for RESTful Web Services](#) introduced an official interceptor and filter framework, so the interceptor framework included in RESTEasy 2 is now deprecated, and is replaced by the JAX-RS 2.0 compliant interceptor facility in RESTEasy 3.x. The relevant interfaces are defined in the `javax.ws.rs.ext` package of the `jaxrs-api` module.

- The following interceptor interfaces are deprecated in RESTEasy 3.x.
 - `org.jboss.resteasy.spi.interception.PreProcessInterceptor`
 - `org.jboss.resteasy.spi.interception.PostProcessInterceptor`
 - `org.jboss.resteasy.spi.interception.ClientExecutionInterceptor`
 - `org.jboss.resteasy.spi.interception.ClientExecutionContext`
 - `org.jboss.resteasy.spi.interception.AcceptedByMethod`
- The `org.jboss.resteasy.spi.interception.PreProcessInterceptor` interface is replaced by the `javax.ws.rs.container.ContainerRequestFilter` interface in RESTEasy 3.x.
- The following interfaces and classes are also deprecated in RESTEasy 3.x.
 - `org.jboss.resteasy.spi.interception.MessageBodyReaderInterceptor`
 - `org.jboss.resteasy.spi.interception.MessageBodyWriterInterceptor`
 - `org.jboss.resteasy.spi.interception.MessageBodyWriterContext`
 - `org.jboss.resteasy.spi.interception.MessageBodyReaderContext`
 - `org.jboss.resteasy.core.interception.InterceptorRegistry`
 - `org.jboss.resteasy.core.interception.InterceptorRegistryListener`
 - `org.jboss.resteasy.core.interception.ClientExecutionContextImpl`
- The `org.jboss.resteasy.spi.interception.MessageBodyWriterInterceptor` interface is replaced by the `javax.ws.rs.ext.WriterInterceptor` interface.
- In addition, some changes to the `javax.ws.rs.ext.MessageBodyWriter` interface might not be backward compatible with respect to JAX-RS 1.x. If your application used JAX-RS 1.x, review your application code to make sure you define `@Produces` or `@Consumes` for your endpoints. Failure to do so might result in an error similar to the following.

```
org.jboss.resteasy.core.NoMessageBodyWriterFoundFailure: Could not
find MessageBodyWriter for response object of type: <OBJECT> of
media type:
```

The following is an example of a REST endpoint that can cause this error.

```

@Path("dates")
public class DateService {

    @GET
    @Path("daysuntil/{targetdate}")
    public long showDaysUntil(@PathParam("targetdate") String
targetDate) {
        DateLogger.LOGGER.logDaysUntilRequest(targetDate);
        final long days;

        try {
            final LocalDate date = LocalDate.parse(targetDate,
DateTimeFormatter.ISO_DATE);
            days = ChronoUnit.DAYS.between(LocalDate.now(), date);
        } catch (DateTimeParseException ex) {
            // ** DISCLAIMER **. This example is contrived.
            throw new
WebApplicationException(Response.status(400).entity(ex.getLocalizedMessage())
.type(MediaType.TEXT_PLAIN)
                .build());
        }
        return days;
    }
}

```

To fix the issue, add the import for `javax.ws.rs.Produces` and the `@Produces` annotation as follows.

```

...
import javax.ws.rs.Produces;
...

@Path("dates")
public class DateService {

    @GET
    @Path("daysuntil/{targetdate}")
    @Produces(MediaType.TEXT_PLAIN)
    public long showDaysUntil(@PathParam("targetdate") String
targetDate) {
        DateLogger.LOGGER.logDaysUntilRequest(targetDate);
        final long days;

        try {
            final LocalDate date = LocalDate.parse(targetDate,
DateTimeFormatter.ISO_DATE);
            days = ChronoUnit.DAYS.between(LocalDate.now(), date);
        } catch (DateTimeParseException ex) {
            // ** DISCLAIMER **. This example is contrived.
            throw new
WebApplicationException(Response.status(400).entity(ex.getLocalizedMessage())
.type(MediaType.TEXT_PLAIN)
                .build());
        }
    }
}

```

```

    }
    return days;
}

```



NOTE

All interceptors from the previous release of RESTEasy can run in parallel with the new JAX-RS 2.0 filter and interceptor interfaces.

For more information about interceptors, see [RESTEasy Interceptors](#) in *Developing Web Services Applications* for JBoss EAP.

For more information about the new replacement API, see the [RESTEasy JAX-RS 3.0.13.Final API](#) or later.

Client API

The RESTEasy client framework in `resteasy-jaxrs` has been replaced by the JAX-RS 2.0 compliant `resteasy-client` module. As a result, some RESTEasy client API classes and methods are deprecated.

- The following classes are deprecated.
 - [org.jboss.resteasy.client.ClientRequest](#)
 - [org.jboss.resteasy.client.ClientRequestFactory](#)
 - [org.jboss.resteasy.client.ClientResponse](#)
 - [org.jboss.resteasy.client.ProxyBuilder](#)
 - [org.jboss.resteasy.client.ProxyConfig](#)
 - [org.jboss.resteasy.client.ProxyFactory](#)
- The [org.jboss.resteasy.client.ClientResponseFailure](#) exception and the [org.jboss.resteasy.client.ClientExecutor](#) and [org.jboss.resteasy.client.EntityTypeFactory](#) interfaces are also deprecated.
- You must replace the [org.jboss.resteasy.client.ClientRequest](#) and [org.jboss.resteasy.client.ClientResponse](#) classes with [org.jboss.resteasy.client.jaxrs.ResteasyClient](#) and [javax.ws.rs.core.Response](#) respectively.

The following is an example of how to send a link header with the RESTEasy client in RESTEasy 2.3.x.

```

ClientRequest request = new
ClientRequest(generateURL("/linkheader/str"));
request.addLink("previous chapter", "previous",
"http://example.com/TheBook/chapter2", null);
ClientResponse response = request.post();
LinkHeader header = response.getLinkHeader();

```

The following is an example of how to accomplish the same task with the RESTEasy client in RESTEasy 3.

-

```

ResteasyClient client = new ResteasyClientBuilder().build();
Response response =
client.target(generateURL("/linkheader/str")).request()
    .header("Link", "<http://example.com/TheBook/chapter2>";
rel=\"previous\"";
title=\"previous chapter\"").post(Entity.text(new String()));
javax.ws.rs.core.Link link = response.getLink("previous");

```

See the `resteasy-jaxrs-client` quickstart for an example of an external JAX-RS RESTEasy client that interacts with a JAX-RS Web service.

- The classes and interfaces in the `org.jboss.resteasy.client.cache` package are also deprecated. They are replaced by equivalent classes and interfaces in the `org.jboss.resteasy.client.jaxrs.cache` package.



NOTE

For more information about the `org.jboss.resteasy.client.jaxrs` API classes, see the [RESTEasy JAX-RS JavaDoc](#).

StringConverter

The `org.jboss.resteasy.spi.StringConverter` class is deprecated in RESTEasy 3.x. This functionality can be replaced using the JAX-RS 2.0 `javax.ws.rs.ext.ParamConverterProvider` class.

5.4.2. Removed or Protected RESTEasy Classes

ResteasyProviderFactory Add methods

Most of the `org.jboss.resteasy.spi.ResteasyProviderFactory` `add()` methods have been removed or made protected in RESTEasy 3.0. For example, the `addBuiltInMessageBodyReader()` and `addBuiltInMessageBodyWriter()` methods have been removed and the `addMessageBodyReader()` and `addMessageBodyWriter()` methods have been made protected.

You should now use the `registerProvider()` and `registerProviderInstance()` methods.

Additional Classes Removed From RESTEasy 3

The `@org.jboss.resteasy.annotations.cache.ServerCached` annotation, which specified the response to the JAX-RS method should be cached on the server, was removed from RESTEasy 3 and must be removed from the application code.

5.4.3. Additional RESTEasy Changes

SignedInput and SignedOutput

- `SignedInput` and `SignedOutput` for `resteasy-crypto` must have the `Content-Type` set to `multipart/signed` in either the `Request` or `Response` object, or by using the `@Consumes` or `@Produces` annotation.
- `SignedOutput` and `SignedInput` can be used to return the `application/pkcs7-signature` MIME type format in binary form by setting that type in the `@Produces` or `@Consumes` annotations.
- If the `@Produces` or `@Consumes` is `text/plain` MIME type, `SignedOutput` will be base64 encoded and sent as a `String`.

Security Filters

The security filters for `@RolesAllowed`, `@PermitAll`, and `@DenyAll` now return "403 Forbidden" instead of "401 Unauthorized".

Client-side Filters

The new JAX-RS 2.0 client-side filters will not be bound and run when you are using the RESTEasy client API from the previous release.

Asynchronous HTTP Support

Because the JAX-RS 2.0 specification adds asynchronous HTTP support using the `@Suspended` annotation and the `AsynResponse` interface, the RESTEasy proprietary API for asynchronous HTTP has been deprecated and might be removed as soon as RESTEasy 3.1. The asynchronous Tomcat and asynchronous JBoss Web modules have also been removed from the server installation. If you are not using the Servlet 3.0 container or higher, asynchronous HTTP server-side processing will be simulated and run synchronously in same request thread.

Server-side Cache

Server-side cache setup has changed. Please see the [RESTEasy Documentation](#) for more information.

YAML Provider Setting Changes

In previous releases of JBoss EAP, the RESTEasy YAML provider setting was enabled by default. This has changed in JBoss EAP 7. The YAML provider is now disabled by default. Its use is not supported due to a security issue in the `SnakeYAML` library used by RESTEasy for unmarshalling and it must be explicitly enabled in the application. For information about how to enable the YAML provider in your application and add the Maven dependencies, see [YAML Provider](#) in *Developing Web Services Applications* for JBoss EAP.

SerializableProvider

Deserializing Java objects from untrusted sources is not safe. For this reason, in JBoss EAP 7, the `org.jboss.resteasy.plugins.providers.SerializableProvider` class is disabled by default, and it is not recommended to use this provider.

5.4.4. RESTEasy SPI Changes

SPI Exceptions

All SPI failure exceptions have been deprecated and are no longer used internally. They have been replaced with the corresponding JAX-RS 2.0 exception.

Deprecated Exception	Replacement Exception in jaxrs-api module
<code>org.jboss.resteasy.spi.ForbiddenException</code>	<code>javax.ws.rs.ForbiddenException</code>
<code>org.jboss.resteasy.spi.MethodNotAllowedException</code>	<code>javax.ws.rs.NotAllowedException</code>
<code>org.jboss.resteasy.spi.NotAcceptableException</code>	<code>javax.ws.rs.NotAcceptableException</code>
<code>org.jboss.resteasy.spi.NotFoundException</code>	<code>javax.ws.rs.NotFoundException</code>
<code>org.jboss.resteasy.spi.UnauthorizedException</code>	<code>javax.ws.rs.NotAuthorizedException</code>
<code>org.jboss.resteasy.spi.UnsupportedMediaTypeException</code>	<code>javax.ws.rs.NotSupportedException</code>

InjectorFactory and Registry

The `InjectorFactory` and `Registry` SPIs have changed. This should not be an issue if you use `RESTEasy` as documented and supported.

5.4.5. Jackson Provider Changes

The version of Jackson included in JBoss EAP has changed. The previous version of JBoss EAP included Jackson 1.9.9. JBoss EAP 7 now includes Jackson 2.6.3 or greater. As a result, the Jackson provider has changed from `resteasy-jackson-provider` to `resteasy-jackson2-provider`.

The upgrade to the `resteasy-jackson2-provider` requires some package changes. For example, the Jackson annotation package has changed from `org.codehaus.jackson.annotate` to `com.fasterxml.jackson.annotation`.

To switch your application to use the default provider that was included in the previous release of JBoss EAP, see [Switching the Default Jackson Provider](#) in *Developing Web Services Applications* for JBoss EAP.

5.4.6. Spring RESTEasy Integration Changes

The Spring 4.0 framework introduced support for Java 8. If you plan to use the `RESTEasy 3.x` integration with Spring, be sure to specify 4.2.x as the minimum Spring version in your deployment as this is the earliest stable version supported by JBoss EAP 7.

5.4.7. RESTEasy Jettison JSON Provider Changes

The `RESTEasy Jettison JSON` provider is deprecated in JBoss EAP 7 and is no longer added to deployments by default. You are encouraged to switch to the recommended `RESTEasy Jackson` provider. If you prefer to continue to use the `Jettison` provider, you must define an explicit dependency for it in the `jboss-deployment-descriptor.xml` file as demonstrated in the following example.

```

<?xml version="1.0" encoding="UTF-8"?>
<jboss-deployment-structure>
  <deployment>
    <exclusions>
      <module name="org.jboss.resteasy.resteasy-jackson2-provider"/>
      <module name="org.jboss.resteasy.resteasy-jackson-provider"/>
    </exclusions>
    <dependencies>
      <module name="org.jboss.resteasy.resteasy-jettison-provider"
services="import"/>
    </dependencies>
  </deployment>
</jboss-deployment-structure>

```

For more information about how to define explicit dependencies, see [Add an Explicit Module Dependency to a Deployment](#) in the JBoss EAP *Development Guide*.

5.5. CDI 1.2 APPLICATION CHANGES

JBoss EAP 7 includes support for CDI 1.2. As a result, applications written using CDI 1.0 might see some changes in behavior when migrated to JBoss EAP 7. This section summarizes only a few of those changes.

You can find more information about Weld and CDI 1.2 in the following references:

- [Contexts and Dependency Injection for the Java EE platform](#)
- [CDI 1.2 Javadoc](#)
- [Weld 2.3.3.Final - CDI Reference Implementation](#)

Bean Archives

Bean classes of enabled beans must be deployed in bean archives to ensure they are scanned by CDI to find and process the bean classes.

In CDI 1.0, an archive was defined as an *explicit* bean archive if it contained a `beans.xml` file in the `META-INF/` directory for an application client, EJB, or library JAR, or if it contained a `beans.xml` file in the `WEB-INF/` directory for a WAR.

CDI 1.1 introduced *implicit* bean archives, which are archives that contain one or more bean classes with a bean defining annotation, or one or more session beans. Implicit bean archives are scanned by CDI and, during type discovery, only classes with bean defining annotations are discovered. For more information, see [Type and Bean Discovery](#) in *Contexts and Dependency Injection for the Java EE platform*

A bean archive has a bean discovery mode of `all`, `annotated` or `none`. A bean archive that contains a `beans.xml` file with no version has a default bean discovery mode of `all`. A bean archive that contains a `beans.xml` file with version `1.1` or later must specify the `bean-discovery-mode` attribute. The default value for the attribute is `annotated`.

An archive is not a bean archive in the following cases:

- It contains a `beans.xml` file with a `bean-discovery-mode` of `none`.
- It contains a CDI extension with no `beans.xml` file.

An archive is an *explicit* bean archive in the following cases:

- The archive contains a `beans.xml` file with a version number of 1.1 or later and a `bean-discovery-mode` of `all`.
- The archive contains a `beans.xml` file with no version number.
- The archive contains an empty `beans.xml` file.

An archive is an *implicit* bean archive in the following cases:

- The archive contains one or more bean classes with a bean defining annotation, or one or more session beans, even if it does not contain a `beans.xml` file.
- The archive contains a `beans.xml` file with a `bean-discovery-mode` of `annotated`.

CDI 1.2 limited [bean defining annotations](#) to the following:

- `@ApplicationScoped`, `@SessionScoped`, `@ConversationScoped`, and `@RequestScoped` annotations
- All other normal scope types
- `@Interceptor` and `@Decorator` annotations

- All stereotype annotations, which are annotations annotated with `@Stereotype`
- `@Dependent` scope annotation

For more information about bean archives, see [Bean Archives](#) in *Contexts and Dependency Injection for the Java EE platform*.

Clarification of Conversation Resolution

The conversation context lifecycle was changed to prevent conflicts with the Servlet specification as described in [CDI Specification Issue CDI-411](#). The conversation scope is active during all servlet requests and should not prevent other servlets or servlet filters from setting the request body or character encoding.

Observer Resolution

Event resolution has been partly rewritten in CDI 1.2. In CDI 1.0, an event is delivered to an observer method if the observer method has all the event qualifiers. In CDI 1.2, an event is delivered to an observer method if the observer method has no event qualifiers or has a subset of the event qualifiers.

5.6. MIGRATE EXPLICIT MODULE DEPENDENCIES

The introduction of the modular class loading system and JBoss Modules in the previous release of JBoss EAP allowed for fine-grained control of the classes available to applications. This feature allowed you to configure explicit module dependencies using the application's `MANIFEST.MF` file or the `jboss-deployment-structure.xml` deployment descriptor file.

If you defined explicit module dependencies in your application, you should be aware of the following changes in JBoss EAP 7.

Review Dependencies for Availability

The modules that are included in JBoss EAP have changed. When you migrate your application to JBoss EAP 7, review your `MANIFEST.MF` and `jboss-deployment-structure.xml` file entries to make sure they do not refer to any modules that were removed from this release of the product.

Dependencies That Require Annotation Scanning

In the previous release of JBoss EAP, if your dependency contained annotations that needed to be processed during annotation scanning, such as when declaring EJB Interceptors, you were required to generate and include a Jandex index in a new JAR file and then set a flag in the `MANIFEST.MF` or `jboss-deployment-structure.xml` deployment descriptor file.

JBoss EAP 7 now provides automatic runtime generation of annotation indexes for static modules, so you no longer need to generate them manually. However, you still need to add the `annotations` flag to the application's `MANIFEST.MF` file or the `jboss-deployment-structure.xml` deployment descriptor file as demonstrated below.

Example Annotation Flag in the MANIFEST.MF File

```
Dependencies: com.company.my-ejb annotations, com.company.other
```

Example Annotation Flag in the jboss-deployment-structure.xml File

```
<jboss-deployment-structure>
  <deployment>
    <dependencies>
      <module name="com.company.my-ejb" annotations="true"/>
    </dependencies>
  </deployment>
</jboss-deployment-structure>
```

```
<module name="com.company.other"/>
</dependencies>
</deployment>
</jboss-deployment-structure>
```

5.7. HIBERNATE AND JPA MIGRATION CHANGES

5.7.1. Hibernate ORM 3.0

The integration classes that made it easier to use Hibernate ORM 3 in the previous release were removed from JBoss EAP 7. If your application still uses Hibernate ORM 3 libraries, it is strongly recommended that you migrate your application to use Hibernate ORM 5 as Hibernate ORM 3 will no longer work in JBoss EAP without a lot of effort. If you can not migrate to Hibernate ORM 5, you must define a custom JBoss Module for the Hibernate ORM 3 JARs and exclude the Hibernate ORM 5 classes from your application.

5.7.2. Hibernate ORM 4.0 - 4.3

If your application needs second-level cache enabled, you should migrate to Hibernate ORM 5, which is integrated with Infinispan 8.x.

Applications written with Hibernate ORM 4.x can still use Hibernate ORM 4.x. You must define a custom JBoss module for the Hibernate ORM 4.x JARs and exclude the Hibernate ORM 5 classes from your application. However, it is strongly recommended that you rewrite your application code to use Hibernate ORM 5. For information about migrating to Hibernate ORM 5, see [Migrating to Hibernate ORM 5](#).

5.7.3. Hibernate ORM 5

If your application contains a `persistence.xml` file or the code uses the `@PersistenceContext` or `@PersistenceUnit` annotations, JBoss EAP 7 detects this during deployment and assumes the application uses JPA. It implicitly adds the Hibernate ORM 5 libraries plus a few other dependencies to your application class path and defaults to using these libraries.

5.7.4. Migrating to Hibernate ORM 5

This section highlights the changes you need to make when migrating from Hibernate ORM version 4.3 to version 5. For more information about the changes implemented between Hibernate ORM 4 and Hibernate ORM 5, see the [Hibernate ORM 5.0 Migration Guide](#).

Removed and Deprecated Classes

The following deprecated classes were removed from Hibernate ORM 5.

- [org.hibernate.cfg.AnnotationConfiguration](#)
- [org.hibernate.id.TableGenerator](#)
- [org.hibernate.id.TableHiLoGenerator](#)
- [org.hibernate.id.SequenceGenerator](#)

Other Changes to Classes and Packages

- The `org.hibernate.integrator.spi.Integrator` interface changed to account for bootstrap redesign.
- A new package `org.hibernate.engine.jdbc.env` package was created. It contains the `org.hibernate.engine.jdbc.env.spi.JdbcEnvironment` interface, which was extracted from `org.hibernate.engine.jdbc.spi.JdbcServices` interface.
- A new `org.hibernate.boot.model.relational.ExportableProducer` interface was introduced that will affect `org.hibernate.id.PersistentIdentifierGenerator` implementations.
- The signature of `org.hibernate.id.Configurable` was changed to accept `org.hibernate.service.ServiceRegistry` rather than just `org.hibernate.dialect.Dialect`.
- The `org.hibernate.metamodel.spi.TypeContributor` interface has migrated to `org.hibernate.boot.model.TypeContributor`.
- The `org.hibernate.metamodel.spi.TypeContributions` interface has migrated to `org.hibernate.boot.model.TypeContributions`.

Type Handling

- Built-in `org.hibernate.type.descriptor.sql.SqlTypeDescriptor` implementations no longer auto-register themselves with `org.hibernate.type.descriptor.sql.SqlTypeDescriptorRegistry`. Applications using custom `SqlTypeDescriptor` implementations that extend the built-in implementations and rely on that behavior must be updated to call `SqlTypeDescriptorRegistry.addDescriptor()` themselves.
- For IDs defined as generated UUIDs, some databases require you to explicitly set the `@Column(length=16)` in order to generate `BINARY(16)` so that comparisons work properly.
- For `EnumType` mappings defined in the `hbm.xml`, where you want `javax.persistence.EnumType.STRING` name-mapping, this configuration must be explicitly stated by using either the `useNamed(true)` setting or by specifying a `VARCHAR` value of 12.

Transaction Management

- The transaction SPI underwent a major redesign in Hibernate ORM 5. In Hibernate ORM 4.3, you used the `org.hibernate.Transaction` API to directly access different back-end transaction strategies. Hibernate ORM 5 introduced a level of indirection. On the back end, the `org.hibernate.Transaction` implementation now talks to a `org.hibernate.resource.transaction.TransactionCoordinator`, which represents the transactional context for a given session according to the back-end strategy. While this does not have a direct impact on developers, it could affect the bootstrap configuration. Previously applications would specify `hibernate.transaction.factory_class` property, which is now deprecated, and refer to a `org.hibernate.engine.transaction.spi.TransactionFactory` FQN (fully qualified name). With Hibernate ORM 5, you specify the `hibernate.transaction.coordinator_class` setting and refer to a `org.hibernate.resource.transaction.TransactionCoordinatorBuilder`. See `org.hibernate.cfg.AvailableSettings.TRANSACTION_COORDINATOR_STRATEGY` for additional details.

- The following short names are now recognized.
 - `jdbc`: Manage transactions using the JDBC `java.sql.Connection`. This is the default for non-JPA transactions.
 - `jta`: Manage transactions using JTA.



IMPORTANT

If a JPA application does not provide a setting for the `hibernate.transaction.coordinator_class` property, Hibernate will automatically build the proper transaction coordinator based on the transaction type for the persistence unit.

If a non-JPA application does not provide a setting for the `hibernate.transaction.coordinator_class` property, Hibernate will default to `jdbc` to manage the transactions. This default will cause problems if the application actually uses JTA-based transactions. A non-JPA application that uses JTA-based transactions should explicitly set the `hibernate.transaction.coordinator_class` property value to `jta` or provide a custom `org.hibernate.resource.transaction.TransactionCoordinatorBuilder` that builds a `org.hibernate.resource.transaction.TransactionCoordinator` that properly coordinates with JTA-based transactions.

Other Hibernate ORM 5 Changes

- The `cfg.xml` files are again fully parsed and integrated with events, security, and other functions.
- The properties loaded from the `cfg.xml` using the `EntityManagerFactory` did not previously prefix names with `hibernate`. This has now been made consistent.
- The configuration is no longer serializable.
- The `org.hibernate.dialect.Dialect.getQuerySequencesString()` method now retrieves catalog, schema, and increment values.
- The `AuditConfiguration` modifier was removed from `org.hibernate.envers.boot.internal.EnversService`.
- The `AuditStrategy` method parameters were changed to remove the obsolete `AuditConfiguration` and use the new `EnversService`.
- Various classes and interfaces in the `org.hibernate.hql.spi` package and subpackages have been moved to the new `org.hibernate.hql.spi.id` package. This includes the `MultiTableBulkIdStrategy` class and the `AbstractTableBasedBulkIdHandler`, `TableBasedDeleteHandlerImpl`, and `TableBasedUpdateHandlerImpl` interfaces and their subclasses.
- There was a complete redesign of property access contracts.
- Valid `hibernate.cache.default_cache_concurrency_strategy` setting values are now defined using the

`org.hibernate.cache.spi.access.AccessType.getExternalName()` method rather than the `org.hibernate.cache.spi.access.AccessType` enum constants. This is more consistent with other Hibernate settings.

5.8. HIBERNATE SEARCH CHANGES

The version of Hibernate Search that ships with JBoss EAP 7 has changed. The previous release of JBoss EAP shipped with Hibernate Search 4.6.x. JBoss EAP 7 ships with Hibernate Search 5.5.x.

Hibernate Search 5.5 is built upon Apache Lucene 5.3.1. If you use any native Lucene APIs, be sure to align with this version. The [Hibernate Search 5.5 API](#) wraps and hides the complexity of many of the Lucene API changes made between version 3 and version 5, however, some classes are now deprecated, renamed, or repackaged. This section describes how these changes might impact your application code.

Hibernate Search Mapping Changes

Indexing of id Fields of Embedded Relations

When using an `@IndexedEmbedded` annotation to include fields from a related entity, the `id` of the related entity is no longer included. You can enable the inclusion of the `id` by using the `includeEmbeddedObjectId` attribute of the `@IndexedEmbedded` annotation.

```
@IndexedEmbedded(includeEmbeddedObjectId=true)
```

Number and Date Index Formatting Changes

Numbers and dates are now indexed as numeric fields by default. Properties of type `int`, `long`, `float`, `double`, and their corresponding wrapper classes are no longer indexed as strings. Instead, they are now indexed using Lucene's appropriate numeric encoding. The `id` fields are an exception to this rule. Even when they are represented by a numeric type, they are still indexed as a string keyword by default. The use of `@NumericField` is now obsolete unless you want to specify a custom precision for the numeric encoding. You can keep the old string-based index format by explicitly specifying a string encoding field bridge. In the case of integers, this is the [org.hibernate.search.bridge.builtin.IntegerBridge](#). Check the [org.hibernate.search.bridge.builtin](#) package for other publicly available field bridges.

`Date` and `Calendar` are no longer indexed as strings. Instead, instances are encoded as long values representing the number of milliseconds since January 1, 1970, 00:00:00 GMT. You can switch the indexing format by using the new `EncodingType` enum. For example:

```
@DateBridge(encoding=EncodingType.STRING)
@CalendarBridge(encoding=EncodingType.STRING)
```

The encoding change for numbers and dates is important and can have a big impact on application behavior. If you have a query that targets a field that was previously string-encoded, but is now encoded numerically, you must update the query. Numeric fields must be searched with a `NumericRangeQuery`. You must also make sure that all fields targeted by faceting are string encoded. If you use the Search query DSL, the correct query should be created automatically for you.

Miscellaneous Hibernate Search Changes

- Sorting options have improved and field encoding specified incorrectly for sorting options now results in runtime exceptions. Lucene also offers more performant sorting if the fields used in the sort are known up front. Hibernate Search 5.5 provides the new `@SortableField` annotation and its multi-valued companion `@SortableFields`. See the [Migration Guide from Hibernate Search 5.4 to 5.5](#) for more information.

- The Lucene [SortField](#) API requires the following application code change. In the previous release of JBoss EAP, you set the type of the sort field in the query as follows.

```
fulltextQuery.setSort(new Sort(new SortField("title",
SortField.STRING)));
```

The following is an example of how you set it in JBoss EAP 7.

```
fulltextQuery.setSort(new Sort(new SortField("title",
SortField.Type.STRING)));
```

- Since **SearchFactory** should only be used by ORM integration, it was moved from the **hibernate-search-engine** module to the **hibernate-search-orm** module. Other integrators should depend exclusively on **SearchIntegrator**, which replaces the deprecated **SearchFactoryIntegrator**.
- The enum value **SpatialMode.GRID** was renamed to **SpatialMode.HASH**.
- **FullTextIndexEventListener** is now a final class. If you currently extend this class, you must find an alternate solution to achieve the same functionality.
- The **hibernate-search-analyzers** module was removed. The recommended approach is to directly use the appropriate Lucene artifact, for example **org.apache.lucene: lucene-analyzers-common**.
- The JMS controller API has changed. The JMS back-end dependency on Hibernate ORM was removed so that it could be used in other non-ORM environments. A consequence is that implementors of **org.hibernate.search.backend.impl.jms.AbstractJMSHibernateSearchController** must adjust to the new signature. This class is an internal class and it is recommended to use it as an example instead of extending it.
- The **org.hibernate.search.spi.ServiceProvider** SPI was refactored. If you were integrating with the old service contract, refer to the [Hibernate Search 5.5 Javadoc](#) of **ServiceManager**, **Service**, **Startable** and **Stoppable** for details about the new contract.
- If you have kept indexes generated by Lucene 3.x and have not rebuilt them with Hibernate Search 5.0 or later, you will get an **IndexFormatTooOldException**. It is recommended that you rebuild the indexes with the mass indexer. If you are not able to do that, try to use Lucene's **IndexUpgrader**. You must carefully update the Hibernate Search mappings in case the default behavior has changed. For more information, see the [Apache Lucene Migration Guide](#).
- Apache Lucene was upgraded from 3.6 to 5.3 in JBoss EAP 7. If your code imports Lucene code directly, see the [Apache Lucene Migration Guide](#) for details of the changes. Additional information can also be found in the [Lucene Change Log](#).
- When using **@Field(indexNullAs=)** to encode a null marker value in the index, the type of the marker must be compatible with all other values that are indexed in that same field. For example, it was previously possible to encode a null value for numeric fields using a string "null". This is no longer allowed. Instead, you must choose a number to represent the **null** value, such as **-1**.

- Significant improvements were made to the faceting engine. Most of the changes do not affect the API. The one notable exception is that you must now annotate any fields you intend to use for faceting with the `@Facet` or `@Facets` annotation.

Hibernate Search Renamed and Repackaged Classes

The following is a list of Hibernate Search classes that were repackaged or renamed.

Previous Package and Class	New Package and Class
<code>org.hibernate.search.Environment</code>	<code>org.hibernate.search.cfg.Environment</code>
<code>org.hibernate.search.FullTextFilter</code>	<code>org.hibernate.search.filter.FullTextFilter</code>
<code>org.hibernate.search.ProjectionConstants</code>	<code>org.hibernate.search.engine.ProjectionConstants</code>
<code>org.hibernate.search.SearchException</code>	<code>org.hibernate.search.exception.SearchException</code>
<code>org.hibernate.search.Version</code>	<code>org.hibernate.search.engine.Version</code>

Lucene - Renamed and Repackaged Classes

Query parsers were moved to a new module, resulting in a packaging change from `org.apache.lucene.queryParser.QueryParser` to `org.apache.lucene.queryparser.classic.QueryParser`.

Many of the Lucene analyzers were refactored, resulting in packaging changes. See the [Apache Lucene Documentation](#) to find the replacement packages.

Some Apache Solr utility classes, for example `TokenizerFactory` or `TokenFilterFactory`, were moved into Apache Lucene. If your application uses those utilities or custom analyzers, you must find the new package name in Apache Lucene.

See the [Apache Lucene Migration Guide](#) for more information.

Hibernate Search Deprecated APIs

For the complete list of Hibernate Search deprecated interfaces, classes, enums, annotation types, methods, constructors, and enum constants, see the [Hibernate Search Deprecated API](#) document.

Hibernate Search Deprecated Interfaces

Interface	Description
<code>org.hibernate.search.store.IndexShardingStrategy</code>	Deprecated as of Hibernate Search 4.4. Might be removed in Search 5. Use ShardIdentifierProvider instead.
<code>org.hibernate.search.store.Workspace</code>	This interface will be moved and should be considered non-public API. For more information, see HSEARCH-1915 .

Hibernate Search Deprecated Classes

Class	Description
<code>org.hibernate.search.filter.FilterKey</code>	Custom filter keys are deprecated and are scheduled for removal in Hibernate Search 6. As of Hibernate Search 5.1, keys for caching Lucene filters are calculated automatically based on the given filter parameters.
<code>org.hibernate.search.filter.StandardFilterKey</code>	Custom filter keys are deprecated and are scheduled for removal in Hibernate Search 6. As of Hibernate Search 5.1, keys for caching Lucene filters are calculated automatically based on the given filter parameters.

Hibernate Search Deprecated Enums

Enum	Description
<code>org.hibernate.search.annotations.FieldCacheType</code>	Remove the CacheFromIndex annotation as it is deprecated. See Hibernate Search Deprecated Annotations .

Hibernate Search Deprecated Annotations

Annotation	Description
<code>org.hibernate.search.annotations.CacheFromIndex</code>	Remove the annotation. No alternative replacement is necessary.
<code>org.hibernate.search.annotations.Key</code>	Custom filter cache keys are a deprecated feature and are scheduled to be removed in Hibernate Search 6. As of Hibernate Search 5.1, the filter cache keys are determined automatically based on the filter parameters so it is no longer required to provide a key object.

Hibernate Search Deprecated Methods

Method	Description
<code>org.hibernate.search.FullTextSharedSessionBuilder.autoClose()</code>	No replacement
<code>org.hibernate.search.FullTextSharedSessionBuilder.autoClose(boolean)</code>	No replacement
<code>org.hibernate.search.cfg.IndexedMapping.cacheFromIndex(FieldCacheType...)</code>	This will be removed with no replacement.

Method	Description
<code>org.hibernate.search.cfg.EntityDescriptor.getCacheInMemory()</code>	This will be removed with no replacement.
<code>org.hibernate.search.cfg.ContainedInMapping.numericField()</code>	Invoke <code>field().numericField()</code> instead.
<code>org.hibernate.search.cfg.EntityDescriptor.setCacheInMemory(Map<String, Object>)</code>	This will be removed with no replacement.
<code>org.hibernate.search.MassIndexer.threadsForSubsequentFetching(int)</code>	This method will be removed.
<code>org.hibernate.search.query.dsl.FuzzyContext.withThreshold(float)</code>	Use <code>FuzzyContext.withEditDistanceUpTo(int)</code> .

Hibernate Search Deprecated Constructors

Constructor	Description
<code>org.hibernate.search.cfg.NumericFieldMapping(PropertyDescriptor, EntityDescriptor, SearchMapping)</code>	Use <code>NumericFieldMapping.NumericFieldMapping(String, PropertyDescriptor, EntityDescriptor, SearchMapping)</code> instead.

Changes Impacting Advanced Integrators

This section describes changes that are not part of the public API. They should not impact the average developer as these artifacts should only be accessed by integrators who extend the Hibernate Search framework.

- The `IndexWriterSetting.MAX_THREAD_STATES` and `IndexWriterSetting.TERM_INDEX_INTERVAL` enum constants are deprecated. They affect which properties are read from the configuration, so the fact they are missing means that configuration properties such as `hibernate.search.Animals.2.indexwriter.term_index_interval = default` are now ignored. The only side effect is that the property is not applied.
- The `SearchFactoryIntegrator` interface is now deprecated. You should immediately migrate all code to use `SearchIntegrator`.
- The `SearchFactoryBuilder` class is now deprecated. Use `SearchIntegrationBuilder` instead.
- The `HSQuery.getExtendedSearchIntegrator()` method has been deprecated. It might be possible to use `SearchIntegrator`, but it is preferable to remove it altogether.

- The `DocumentBuilderIndexedEntity.getFieldCacheOption()` method has been deprecated. There is no replacement.
- The `BuildContext.getIndexingStrategy()` method is deprecated. Use `BuildContext.getIndexingMode()` instead.
- The `DirectoryHelper.getVerifiedIndexDir(String, Properties, boolean)` method is deprecated. Use `DirectoryHelper.getVerifiedIndexPath(java.lang.String, java.util.Properties, boolean)` instead.
- The following is a list of Hibernate Search classes that were repackaged or renamed.

Previous Package and Class	New Package and Class
<code>org.hibernate.search.engine.impl.SearchMappingBuilder</code>	<code>org.hibernate.search.engine.spi.SearchMappingHelper</code>
<code>org.hibernate.search.indexes.impl.DirectoryBasedIndexManager</code>	<code>org.hibernate.search.indexes.spi.DirectoryBasedIndexManager</code>
<code>org.hibernate.search.spi.MassIndexerFactory</code>	<code>org.hibernate.search.batchindexing.spi.MassIndexerFactory</code>
<code>org.hibernate.search.spi.SearchFactoryBuilder</code>	<code>org.hibernate.search.spi.SearchIntegratorBuilder</code>
<code>org.hibernate.search.spi.SearchFactoryIntegrator</code>	<code>org.hibernate.search.spi.SearchIntegrator</code>

5.9. MIGRATE ENTITY BEANS TO JPA

Support for EJB Entity Beans is optional in Java EE 7 and they are not supported in JBoss EAP 7. This means container-managed persistence (CMP) and bean-managed persistence (BMP) entity beans must be rewritten to use Java Persistence API (JPA) entities when you migrate to JBoss EAP 7.

In previous releases of JBoss EAP, entity beans were created in application source code by extending the `javax.ejb.EntityBean` class and implementing the required methods. They were then configured in the `ejb-jar.xml` file. A CMP entity bean was specified using an `<entity>` element that contained a `<persistence-type>` child element with a value of `Container`. A BMP entity bean was specified using an `<entity>` element that contained a `<persistence-type>` child element with a value of `Bean`.

In JBoss EAP 7, you must replace any CMP and BMP entity beans in your code with Java Persistence API (JPA) entities. JPA entities are created using the `javax.persistence.*` classes and are defined in the `persistence.xml` file.

The following is an example of a JPA entity class.

```
import javax.persistence.Column;
import javax.persistence.Entity;
import javax.persistence.GeneratedValue;
import javax.persistence.Id;
```

```

import javax.persistence.Table;

@Entity
// User is a keyword in some SQL dialects!
@Table(name = "MyUsers")
public class MyUser {
    @Id
    @GeneratedValue
    private Long id;

    @Column(unique = true)
    private String username;
    private String firstName;
    private String lastName;

    public Long getId() {
        return id;
    }
    public String getUsername() {
        return username;
    }
    public void setUsername(String username) {
        this.username = username;
    }
    public String getFirstName() {
        return firstName;
    }
    public void setFirstName(String firstName) {
        this.firstName = firstName;
    }
    public String getLastName() {
        return lastName;
    }
    public void setLastName(String lastName) {
        this.lastName = lastName;
    }
}

```

The following is an example of a `persistence.xml` file.

```

<persistence version="2.1"
    xmlns="http://xmlns.jcp.org/xml/ns/persistence"
    xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
    xsi:schemaLocation="
        http://xmlns.jcp.org/xml/ns/persistence
        http://xmlns.jcp.org/xml/ns/persistence/persistence_2_1.xsd">
    <persistence-unit name="my-unique-persistence-unit-name">
        <properties>
            // properties...
        </properties>
    </persistence-unit>
</persistence>

```

For working examples of JPA entities, see the `bmt`, `cmt`, and `hibernate5` quickstarts that ship with JBoss EAP 7.

5.10. JPA PERSISTENCE PROPERTY CHANGES

A new persistence property, `jboss.as.jpa.deferdetach`, was added to provide compatibility with the persistence behavior in previous releases of JBoss EAP.

The `jboss.as.jpa.deferdetach` property controls whether the transaction-scoped persistence context used in a non-JTA transaction thread detaches loaded entities after each `EntityManager` invocation or whether it waits until the persistence context is closed, for example, when the session bean invocation ends. The property value defaults to `false`, meaning entities are detached or cleared after each `EntityManager` invocation. This is the correct default behavior as defined in the [JPA specification](#). If the property value is set to `true`, the entities are not detached until the persistence context is closed.

In JBoss EAP 5, persistence behaved as if the `jboss.as.jpa.deferdetach` property was set to `true`. To get this same behavior when migrating your application from JBoss EAP 5 to JBoss EAP 7, you must set the `jboss.as.jpa.deferdetach` property value to `true` in your `persistence.xml` as shown in the following example.

```
<?xml version="1.0" encoding="UTF-8"?>
<persistence xmlns="http://java.sun.com/xml/ns/persistence" version="1.0">
  <persistence-unit name="EAP5_COMPAT_PU">
    <jta-data-source>java:jboss/datasources/ExampleDS</jta-data-source>
    <properties>
      <property name="jboss.as.jpa.deferdetach" value="true" />
    </properties>
  </persistence-unit>
</persistence>
```

In JBoss EAP 6, persistence behaved as if the `jboss.as.jpa.deferdetach` property was set to `false`. This is the same behavior as seen in JBoss EAP 7, so no changes are necessary when you migrate your application.

5.11. MIGRATE EJB CLIENT CODE

The default remote connector and port has changed in JBoss EAP 7. For details about this change, see [Update the Remote URL Connector and Port](#).

If you used the `migrate` operation to migrate your server configuration, the old settings are preserved and you do not need to make the changes detailed below. However, if you run with the new JBoss EAP 7 default configuration, you must make the following changes.

5.11.1. Update the Default Remote Connection Port

Change the remote connection port value from 4447 to 8080 in the `jboss-ejb-client.properties` file.

The following are examples of a `jboss-ejb-client.properties` file in the previous and the current release.

Example: JBoss EAP 6 `jboss-ejb-client.properties` file

```
remote.connectionprovider.create.options.org.xnio.Options.SSL_ENABLED=false
remote.connections=default
```

```
remote.connection.default.host=localhost
remote.connection.default.port=4447
remote.connection.default.connect.options.org.xnio.Options.SASL_POLICY_NOA
NONYMOUS=false
```

Example: JBoss EAP 7 `jboss-ejb-client.properties` file

```
remote.connectionprovider.create.options.org.xnio.Options.SSL_ENABLED=false
remote.connections=default
remote.connection.default.host=localhost
remote.connection.default.port=8080
remote.connection.default.connect.options.org.xnio.Options.SASL_POLICY_NOA
NONYMOUS=false
```

5.11.2. Update the Default Connector

If you are running with the new JBoss EAP 7 configuration, the default connector has changed from `remote` to `http-remoting`. This change impacts clients that use libraries from one release of JBoss EAP and to connect to server in a different release.

- If a client application uses the EJB client library from JBoss EAP 6 and wants to connect to JBoss EAP 7 server, the server must be configured to expose a `remote` connector on a port other than `8080`. The client must then connect using that newly configured connector.
- A client application that uses the EJB client library from JBoss EAP 7 and wants to connect to JBoss EAP 6 server must be aware that the server instance does not use the `http-remoting` connector and instead uses a `remote` connector. This is achieved by defining a new client-side connection property.

```
remote.connection.default.protocol=remote
```

5.11.3. Migrate Remote Naming Client Code

If you are running with the new default JBoss EAP 7 configuration, you must modify your client code to use the new default remote port and connector.

The following is an example of how remote naming properties were specified in the client code in JBoss EAP 6.

```
java.naming.factory.initial=org.jboss.naming.remote.client.InitialContextFactory
java.naming.provider.url=remote://localhost:4447
```

The following is an example of how to specify the remote naming properties in the client code in JBoss EAP 7.

```
java.naming.factory.initial=org.jboss.naming.remote.client.InitialContextFactory
java.naming.provider.url=http-remoting://localhost:8080
```

5.12. MIGRATE DEPLOYMENT PLAN CONFIGURATIONS

The Java EE Application Deployment specification (JSR-88) was intended to define a standard contract to enable tools from multiple providers to configure and deploy applications on any Java EE platform product. The contract required Java EE Product Providers to implement the **DeploymentManager** and other `javax.enterprise.deploy.spi` interfaces to be accessed by the Tool Providers. In case of JBoss EAP 6, a deployment plan is identified by an XML descriptor named `deployment-plan.xml` that is bundled in a ZIP or JAR archive.

This specification saw very little adoption because most application server products provide their own more "feature rich" deployment solutions. For this reason, JSR-88 support was dropped from Java EE 7, and in turn, dropped from JBoss EAP 7.

If you used JSR-88 to deploy your application, you must now use another method to deploy the application. The JBoss EAP management CLI `deploy` command provides a standard way to deploy archives to standalone servers or to server groups in a managed domain. For more information about the management CLI, see the [Management CLI Guide](#).

5.13. MIGRATE CUSTOM APPLICATION VALVES

You must manually migrate custom valves or any valves that are defined in the `jboss-web.xml` XML file. This includes valves created by extending the `org.apache.catalina.valves.ValveBase` class and configured in the `<valve>` element of the `jboss-web.xml` descriptor file.



IMPORTANT

Custom valves and valves that are defined in the `jboss-web.xml` file must be rewritten or replaced by the corresponding Undertow built-in handler. For information about mapping valves to Undertow handlers, see [Migrate JBoss Web Valves](#).

Authentication valves must be replaced manually using Undertow built-in authentication mechanisms.

Migrate Valves Configured in Deployments

In JBoss EAP 6, you could define custom valves at the application level by configuring them in the `jboss-web.xml` web application descriptor file. In JBoss EAP 7, it is possible to do this with Undertow handlers as well.

The following is an example of a valve configured in the `jboss-web.xml` file in JBoss EAP 6.

```
<jboss-web>
  <valve>
    <class-name>org.jboss.examples.MyValve</class-name>
    <param>
      <param-name>myParam</param-name>
      <param-value>foobar</param-value>
    </param>
  </valve>
</jboss-web>
```

For more information about how to create and configure custom handlers in JBoss EAP, see [Creating Custom Handlers](#) in the JBoss EAP *Development Guide*.

Migrate Custom Authenticator Valves

For information about how to migrate authenticator valves, see [Security Application Changes](#)

5.14. SECURITY APPLICATION CHANGES

The replacement of JBoss Web with Undertow requires changes to security configuration in JBoss EAP 7.

5.14.1. Migrate Authenticator Valves

Authentication valves must be replaced manually using Undertow built-in authentication mechanisms. See the following sections for information about how to migrate authenticator valves.

5.14.2. PicketLink Changes

For information about the changes required for SSO with SAML v2 configuration, see [Changes from Previous Versions of JBoss EAP](#) in *How to Set Up SSO with SAML v2* for JBoss EAP.

5.14.3. Other Security Application Changes

For information about the differences in SSO configuration with Kerberos, see [Differences from Configuring Previous Versions JBoss EAP](#) in *How to Set Up SSO with Kerberos* for JBoss EAP.

5.15. JBOSS LOGGING CHANGES

If your application uses JBoss Logging, be aware that the annotations in the `org.jboss.logging` package are now deprecated in JBoss EAP 7. They have been moved to the `org.jboss.logging.annotations` package, so you must update your source code to import the new package.

The annotations have also moved to a separate Maven `groupId:artifactId:version` (GAV) ID so you need to add a new project dependency for `org.jboss.logging:jboss-logging-annotations` in your project `pom.xml` file.



NOTE

Only the logging annotations have moved. The `org.jboss.logging.BasicLogger` and `org.jboss.logging.Logger` still exist in the `org.jboss.logging` package.

The following table lists the deprecated annotation classes and corresponding replacements.

Table 5.1. Deprecated Logging Annotation Replacements

Deprecated Class	Replacement Class
<code>org.jboss.logging.Cause</code>	<code>org.jboss.logging.annotations.Cause</code>
<code>org.jboss.logging.Field</code>	<code>org.jboss.logging.annotations.Field</code>
<code>org.jboss.logging.FormatWith</code>	<code>org.jboss.logging.annotations.FormatWith</code>
<code>org.jboss.logging.LoggingClass</code>	<code>org.jboss.logging.annotations.LoggingClass</code>
<code>org.jboss.logging.LogMessage</code>	<code>org.jboss.logging.annotations.LogMessage</code>

Deprecated Class	Replacement Class
org.jboss.logging.Message	org.jboss.logging.annotations.Message
org.jboss.logging.MessageBundle	org.jboss.logging.annotations.MessageBundle
org.jboss.logging.MessageLogger	org.jboss.logging.annotations.MessageLogger
org.jboss.logging.Param	org.jboss.logging.annotations.Param
org.jboss.logging.Property	org.jboss.logging.annotations.Property

5.16. JAVASERVER FACES (JSF) CODE CHANGES

Dropped Support for JSF 1.2

JBoss EAP 6 allowed you to continue to use JSF 1.2 with your application deployment by creating a `jboss-deployment-structure.xml` file.

JBoss EAP 7 includes JSF 2.2 and no longer supports the JSF 1.2 API. If your application uses JSF 1.2, you must rewrite it to use JSF 2.2.

Compatibility Issue Between JSF 2.1 and JSF 2.2

The JSF 2.1 and JSF 2.2 APIs are not fully compatible. The `FACELET_CONTEXT_KEY` constant value changed from `com.sun.faces.facelets.FACELET_CONTEXT` to `javax.faces.FACELET_CONTEXT` between the releases. This value is inlined by the compiler and code compiled against one release will not work against the other.

Applications that contain code similar to the following example, and are compiled with the JSF 2.1 API but are run in JBoss EAP 7, which uses the JSF 2.2 API, result in a `NullPointerException`. To fix the problem, you must recompile the application against the JSF 2.2 API.

```
Object obj =
FacesContext.getCurrentInstance().getAttributes().get(FaceletContext.FACELET_CONTEXT_KEY);
```

See [Prevent FaceletContext.FACELET_CONTEXT_KEY constant to be inlined by compiler](#) for more information.

5.17. MODULE CLASS LOADING CHANGES

In JBoss EAP 7, the class loading behavior has changed in cases where multiple modules contain the same classes or packages.

Assume there are two modules, `MODULE_A` and `MODULE_B`, that depend upon each other and contain some of the same packages. In JBoss EAP 6, the classes or packages that were loaded from the dependencies took precedence over those specified in the `resource-root` of the `module.xml` file. This meant `MODULE_A` saw the packages for `MODULE_B` and `MODULE_B` saw the packages for `MODULE_A`. This behavior was confusing and could cause conflicts. This behavior has changed in JBoss EAP 7. Now the classes or packages specified by the `resource-root` in the `module.xml` file take

precedence over those specified by the dependency. This means `MODULE_A` sees the packages for `MODULE_A` and `MODULE_B` sees the packages for `MODULE_B`. This prevents conflicts and provides a more appropriate behavior.

If you have defined custom modules that include `resource-root` libraries or packages that contain classes that are duplicated in their module dependencies, you might see `ClassCastException`, `LinkageError`, class loading errors, or other changes in behavior when you migrate to JBoss EAP 7. To resolve these issues, you must configure your `module.xml` file to ensure only one version of a class is used. This can be accomplished by using either of the following approaches.

- You can avoid specifying a `resource-root` that duplicates classes in the module dependency.
- You can use the `include` and `exclude` sub-elements of the `imports` and `exports` elements to control class loading in the `module.xml` file. The following is an export element that excludes classes in the specified package.

```
<exports>
  <exclude path="com/mycompany/duplicateclassespath"/>
</exports>
```

If you prefer to preserve your existing behavior, you must filter the dependency packages from the dependent `resource-root` in the `module.xml` file using the `filter` element. This allows you to retain the existing behavior without the odd looping that you would see under JBoss EAP 6. The following is an example of a `root-resource` that filters classes in a specified package.

```
<resource-root path="mycompany.jar">
  <filter>
    <exclude path="com/mycompany/duplicateclassespath"/>
  </filter>
</resource-root>
```

For more information about modules and class loading, see [Class Loading and Modules](#) in the JBoss EAP *Development Guide*.

5.18. APPLICATION CLUSTERING CHANGES

5.18.1. Overview of New Clustering Features

The following list describes some of the new clustering features to be aware of when migrating your application from JBoss EAP 6 to JBoss EAP 7.

- JBoss EAP 7 introduces a new public API for building singleton services that significantly simplifies the process. For information on singleton services, see [HA Singleton Service](#) in the JBoss EAP *Development Guide*
- A singleton deployment can be configured to deploy and start on only a single node in the cluster at a time. For more information, see [HA Singleton Deployments](#) in the JBoss EAP *Development Guide*.
- You can now define clustered singleton MDBs. For more information, see [Clustered Singleton MDBs](#) in *Developing EJB Applications* for JBoss EAP.

- JBoss EAP 7 includes the Undertow `mod_cluster` implementation. This offers a pure Java load balancing solution that does not require an `httpd` web server. For more information, see [Configuring JBoss EAP as a Front-end Load Balancer](#) in the JBoss EAP *Configuration Guide*.

The remainder of this section describes how clustering changes might impact the migration of your applications to JBoss EAP 7.

5.18.2. Web Session Clustering Changes

JBoss EAP 7 introduces a new web session clustering implementation. It replaces the previous implementation, which was tightly coupled to the legacy JBoss Web subsystem source code.

The new web session clustering implementation impacts how the application is configured in the `jboss-web.xml` JBoss proprietary web application XML descriptor file. The following are the only clustering configuration elements that remain in this file.

```
<jboss-web>
...
<max-active-sessions>...</max-active-sessions>
...
<replication-config>
  <replication-granularity>...</replication-granularity>
  <cache-name>...</cache-name>
</replication-config>
...
</jboss-web>
```

The following table describes how to achieve similar behavior for elements in the `jboss-web.xml` file that are now obsolete.

Configuration Element	Description of Change
<code><max-active-sessions/></code>	<p>Previously, the session creation would fail if it caused the number of active sessions to exceed the value specified by <code><max-active-sessions/></code>.</p> <p>In the new implementation, <code><max-active-sessions/></code> is used to enable session passivation. If session creation will cause the number of active sessions to exceed the <code><max-active-sessions/></code>, then the oldest session known to the session manager will passivate to make room for the new session.</p>
<code><passivation-config/></code>	This configuration element and its sub-elements are no longer used in JBoss EAP 7.
<code><use-session-passivation/></code>	<p>Previously, passivation was enabled using this attribute.</p> <p>In the new implementation, passivation is enabled by specifying a non-negative value for <code><max-active-sessions/></code>.</p>

Configuration Element	Description of Change
<passivation-min-idle-time/>	<p>Previously, sessions needed to be active for a minimum amount of time before becoming a candidate for passivation. This could cause session creation to fail, even when passivation was enabled.</p> <p>The new implementation does not support this logic and thus avoids this Denial of Service (DoS) vulnerability.</p>
<passivation-max-idle-time/>	<p>Previously, a session would be passivated after it was idle for a specific amount of time.</p> <p>The new implementation only supports lazy passivation. It does not support eager passivation. Sessions are only passivated when necessary to comply with <max-active-sessions/>.</p>
<replication-config/>	<p>The new implementation deprecates a number of sub-elements.</p>
<replication-trigger/>	<p>Previously, this element was used to determine when session replication was triggered. The new implementation replaces this configuration option with a single, robust strategy. For more information, see Immutable Session Attributes in the <i>JBoss EAP Development Guide</i>.</p>
<use-jk/>	<p>Previously, the instance-id of the node handling a given request was appended to the jsessionId, for use by load balancers such as <code>mod_jk</code>, <code>mod_proxy_balancer</code>, <code>mod_cluster</code>, depending on the value specified for <use-jk/>.</p> <p>In the new implementation, the instance-id, if defined, is always appended to the jsessionId.</p>
<max-unreplicated-interval/>	<p>Previously, this configuration option was intended as an optimization to prevent the replication of a session's timestamp if no session attribute was changed. While this sounds nice, in practice it does not prevent any RPCs, since session access requires cache transaction RPCs regardless of whether any session attributes changed.</p> <p>In the new implementation, the timestamp of a session is replicated on every request. This prevents stale session metadata following a failover.</p>
<snapshot-mode/>	<p>Previously, one could configure <snapshot-mode/> as INSTANT or INTERVAL. Infinispan's asynchronous replication makes this configuration option obsolete.</p>
<snapshot-interval/>	<p>This was only relevant for <snapshot-mode>INTERVAL</snapshot-mode>. Since <snapshot-mode/> is obsolete, this option is now obsolete as well.</p>

Configuration Element	Description of Change
<code><session-notification-policy/></code>	<p>Previously, the value specified by this attribute defined a policy for triggering session events.</p> <p>In the new implementation, this behavior is specification-driven and not configurable.</p>

This new implementation also supports write-through cache stores as well as passivation-only cache stores. Typically, a write-through cache store is used in conjunction with an invalidation cache. The web session clustering implementation in JBoss EAP 6 did not operate correctly when used with an invalidation cache.

5.18.3. Stateful Session EJB Clustering Changes

In JBoss EAP 6, you were required to enable the clustering behavior for stateful session beans (SFSBs) in one of the following ways.

- You could add the `org.jboss.ejb3.annotation.Clustered` annotation in the session bean.

```
@Stateful
@Clustered
public class MyBean implements MySessionInt {

    public void myMethod() {
        //
    }
}
```

- You could add the `<clustered>` element to the `jboss-ejb3.xml` file.

```
<c:clustering>
  <ejb-name>DDBasedClusteredSFSB</ejb-name>
  <c:clustered>true</c:clustered>
</c:clustering>
```

JBoss EAP 7 no longer requires you to enable the clustering behavior. By default, if the server is started using an HA profile, the state of SFSBs will be replicated automatically.

You can disable this default behavior in one of the following ways.

- You can disable the default behavior for a single stateful session bean by using `@Stateful(passivationCapable=false)`, which is new to the EJB 3.2 specification.
- You can disable this behavior globally in the configuration of the `ejb3` subsystem in the server configuration.



NOTE

If the `@Clustered` annotation is not removed from the application, it is simply ignored and does not affect the deployment of the application.

5.18.4. Clustering Services Changes

In JBoss EAP 6, the APIs for clustering services were in private modules and were not supported.

JBoss EAP 7 introduces a public clustering services API for use by applications. The new services are designed to be lightweight, easily injectable, and require no external dependencies.

- The new `org.wildfly.clustering.group.Group` interface provides access to the current cluster status and allows listening for cluster membership changes.
- The new `org.wildfly.clustering.dispatcher.CommandDispatcher` interface allows running code in the cluster, on all or a selected subset of nodes.

These services replace similar APIs that were available in previous releases, namely `HAPartition` from JBoss EAP 5 and `GroupCommunicationService`, `GroupMembershipNotifier`, and `GroupRpcDispatcher` in JBoss EAP 6.

For more information, see [Public API for Clustering Services](#) in the JBoss EAP *Development Guide*.

5.18.5. Migrate Clustering HA Singleton

In JBoss EAP 6, there was no public API available for the cluster-wide HA singleton service. If you used the private `org.jboss.as.clustering.singleton.*` classes, you must change your code to use the new public `org.wildfly.clustering.singleton.*` packages when you migrate your application to JBoss EAP 7.

For more information about how to implement an HA singleton, see [HA Singleton Service](#) in the *Development Guide* for JBoss EAP.

CHAPTER 6. MISCELLANEOUS CHANGES

6.1. CHANGES TO DELIVERY OF JBOSS EAP NATIVES AND APACHE HTTP SERVER

JBoss EAP 7 natives are delivered differently in this release than in the past. Some now ship with the new Red Hat JBoss Core Services product, which is a set of supplementary software that is common to many of the Red Hat JBoss middleware products. The new product allows for faster distribution of updates and a more consistent update experience. The JBoss Core Services product is available for download in a different location on the Red Hat Customer Portal.

- The following table lists the differences in the delivery methods between the releases.

Package	JBoss EAP 6	JBoss EAP 7
AIO Natives for Messaging	Delivered with the product in a separate "Native Utilities" download	Included within the JBoss EAP distribution. No additional download is required.
Apache HTTP Server	Delivered with the product in a separate "Apache HTTP Server" download	Delivered with the new JBoss Core Services product
mod_cluster, mod_jk, isapi, and nsapi connectors	Delivered with the product in a separate "Webserver Connector Natives" download	Delivered with the new JBoss Core Services product
JSVC	Delivered with the product in a separate "Native Utilities" download	Delivered with the new JBoss Core Services product
OpenSSL	Delivered with the product in a separate "Native Utilities" download	This was dropped in JBoss EAP 7
tcnatives	Delivered with the product in a separate "Native Components" download	This was dropped in JBoss EAP 7

- You should also be aware of the following changes:
 - Support was dropped for mod_cluster and mod_jk connectors used with Apache HTTP Server from Red Hat Enterprise Linux RPM channels. If you run Apache HTTP Server from Red Hat Enterprise Linux RPM channels and need to configure load balancing for JBoss EAP 7 servers, you can do one of the following:
 - Use the Apache HTTP Server provided by JBoss Core Services.
 - You can configure JBoss EAP 7 to act as a front-end load balancer. For more information, see [Configuring JBoss EAP as a Front-end Load Balancer](#) in the JBoss EAP Configuration Guide.
 - You can deploy Apache HTTP Server on a machine that is supported and certified and then run the load balancer on that machine. For the list of supported configurations,

see [Overview of HTTP Connectors](#) in the JBoss EAP 7 *Configuration Guide*.

- Support was dropped for `mod_cluster` and `mod_jk` connectors used with Apache HTTP Server from the HP-UX Web Server Suites. If you run Apache HTTP Server from HP-UX Web Server Suites and need to configure load balancing for JBoss EAP 7 servers, you can do one of the following:
 - You can configure JBoss EAP 7 to act as a front-end load balancer. For more information, see [Configuring JBoss EAP as a Front-end Load Balancer](#) in the JBoss EAP *Configuration Guide*.
 - You can deploy Apache HTTP Server on a machine that is supported and certified and then run the load balancer on that machine. For the list of supported configurations, see [Overview of HTTP Connectors](#) in the JBoss EAP *Configuration Guide*.
- You can find more information about [JBoss Core Services](#) in the *Apache HTTP Server Installation Guide*.

6.2. CHANGES TO DEPLOYMENTS ON AMAZON EC2

A number of changes have been made to the Amazon Machine Images (AMI) in JBoss EAP 7. This section briefly summarizes some of those changes.

- The way you launch non-clustered and clustered JBoss EAP instances and domains in Amazon EC2 has changed significantly.
- JBoss EAP 6 used the `User Data:` field for JBoss EAP configuration. The AMI scripts that parsed the configuration in the `User Data:` field and started the servers automatically on instance startup have been removed from JBoss EAP 7.
- Red Hat JBoss Operations Network agent was installed in the previous release of JBoss EAP. In JBoss EAP 7, you must install it separately.

For details on deploying JBoss EAP 7 on Amazon EC2, see [Deploying Red Hat JBoss Enterprise Application Platform on Amazon EC2](#).

6.3. CHANGES TO JBOSS EAP SCRIPTS

The `add-user` script behavior has changed in JBoss EAP 7 due to a change in password policy. JBoss EAP 6 had a strict password policy. As a result, the `add-user` script rejected weak passwords that did not satisfy the minimum requirements. In JBoss EAP 7, weak passwords are accepted and a warning is issued. For more information, see [Setting Add-User Utility Password Restrictions](#) in the JBoss EAP *Configuration Guide*.

6.4. REMOVAL OF OSGI SUPPORT

When JBoss EAP 6.0 GA was first released, JBoss OSGi, an implementation of the OSGi specification, was included as a Technology Preview feature. With the release of JBoss EAP 6.1.0, JBoss OSGi was demoted from Technology Preview to Unsupported.

In JBoss EAP 6.1.0, the `configadmin` and `osgi` extension modules and subsystem configuration for a standalone server were moved to a separate `EAP_HOME/standalone/configuration/standalone-osgi.xml` configuration file. Because you

should not migrate this unsupported configuration file, the removal of JBoss OSGi support should not impact the migration of a standalone server configuration. If you modified any of the other standalone configuration files to configure `osgi` or `configadmin`, those configurations must be removed.

For a managed domain, the `osgi` extension and subsystem configuration were removed from the `EAP_HOME/domain/configuration/domain.xml` file in the JBoss EAP 6.1.0 release. However, the `configadmin` module extension and subsystem configuration remain in the `EAP_HOME/domain/configuration/domain.xml` file. This configuration is no longer supported in JBoss EAP 7 and must be removed.

CHAPTER 7. MIGRATING FROM OLDER RELEASES OF JBOSS EAP

7.1. MIGRATING FROM JBOSS EAP 5 TO JBOSS EAP 7

This guide focuses on the changes that are required to successfully run and deploy JBoss EAP 6 applications on JBoss EAP 7. If you plan to migrate your applications directly from JBoss EAP 5 to JBoss EAP 7, there are a number of resources available to help you plan and execute your migration. We suggest you take the following approach.

1. See [Summary of Changes Made to Each Release](#) in this guide for a quick, high-level overview of the changes made to each release of JBoss EAP.
2. Read through the JBoss EAP 6 [Migration Guide](#) and this guide to become familiar with the contents of each one.
3. Use the [JBoss EAP 5 Component Upgrade Reference](#) as a quick reference to migration information about specific components and features.
4. The rule-based Red Hat Application Migration Toolkit continues to add rules to help you migrate directly from JBoss EAP 5 to JBoss EAP 7. You can use these tools to analyze your application and to generate detailed reports about the changes needed to migrate to JBoss EAP 7. For more information, see [Use Red Hat Application Migration Toolkit to Analyze Applications for Migration](#).
5. The [Customer Portal Knowledgebase](#) currently contains articles and solutions to help with migration from JBoss EAP 5 to JBoss EAP 6. There are plans in place to add additional content for migration from JBoss EAP 5 to JBoss EAP 7 over time.

7.2. SUMMARY OF CHANGES MADE TO EACH RELEASE

Before you plan your migration, you should be aware of the changes that were made to JBoss EAP 6 and JBoss EAP 7.

The [JBoss EAP 6 Migration Guide](#) covers changes that were made between JBoss EAP 5 and JBoss EAP 6. The following is a condensed list of the most significant changes made in JBoss EAP 6.

- Implemented a new architecture built on the Modular Service Container
- Was a certified implementation of the Java Enterprise Edition 6 specification
- Introduced domain management, new deployment configuration, and a new file directory structure and scripts
- Standardized on new portable JNDI namespaces

See [Review What's New and Different in JBoss EAP 6](#) in the JBoss EAP 6 *Migration Guide* for a detailed list of changes made in that release.

JBoss EAP 7 is built on the same modular structure as JBoss EAP 6 and includes the same domain management, deployment configuration, file directory structure, and scripts. It also still uses the same standardized JNDI namespaces. However, JBoss EAP 7 introduces the following changes.

- Adds support for the Java Enterprise Edition 7 specification

- Replaces the web server with Undertow
- Replaces the JacORB IIOP implementation with a downstream branch of the OpenJDK ORB
- Includes Apache ActiveMQ Artemis as the new messaging provider
- Removes the `cmp`, `jaxr`, and `threads` subsystems
- Removes support for EJB entity beans

For a more complete list of changes, see [Review What's New in JBoss EAP 7](#)

7.3. REVIEW THE CONTENT IN THE MIGRATION GUIDES

Review the entire contents of the Migration Guide for each release to become aware of the features that were added or deprecated, and to understand the server configuration and the application changes required to run existing applications for that release.

Because the underlying architecture was not changed between JBoss EAP 6 and JBoss EAP 7, many of the changes documented in the JBoss EAP 6 [Migration Guide](#) still apply. For example, changes documented under [Changes Required by Most Applications](#) are related to the underlying architectural changes made in JBoss EAP 6, which still apply to this release. The change to the new modular class loading system is significant and impacts the packaging and dependencies of almost every JBoss EAP 5 application. Many of the changes listed under [Changes Dependent on Your Application Architecture and Components](#) are also still valid. However, because JBoss EAP 7 replaced the web server, ORB, and messaging provider, removed the `cmp`, `threads`, and `jaxr` subsystems, and removed support for EJB entity beans, you must consult this guide for any changes related to those component areas. Pay particular attention to the [Server Configuration Changes](#) and [Application Migration Changes](#) detailed in this guide before you begin.

7.4. JBOSS EAP 5 COMPONENT UPGRADE REFERENCE

Use the following table to find information about how to migrate a particular feature or component from JBoss EAP 5 to JBoss EAP 7.

JBoss EAP 5 Feature or Component	Summary of Changes and Where to Find Migration Information
Application Packaging and Class Loading	<p>In JBoss EAP 6, the previous hierarchical class loading structure was replaced with a modular architecture based on JBoss Modules. Application packaging also changed due to the new modular class loading structure. This architecture is still used in JBoss EAP 7. For information about the new modular architecture, see the following chapter in the <i>JBoss EAP 7 Development Guide</i>.</p> <ul style="list-style-type: none"> • Class Loading and Modules <p>For information about how to update and repackage applications for the new modular architecture, see the following section in the <i>JBoss EAP 6 Migration Guide</i>.</p> <ul style="list-style-type: none"> • Class Loading Changes

JBoss EAP 5 Feature or Component	Summary of Changes and Where to Find Migration Information
Application Configuration Files	<p>Due to the changes in JBoss EAP 6 to use modular class loading, you might need to create or modify one or more application configuration files to add dependencies or to prevent automatic dependencies from loading. This has not changed in JBoss EAP 7. For details, see the following section in the JBoss EAP 6 <i>Migration Guide</i>.</p> <ul style="list-style-type: none"> • Configuration File Changes
Caching and Infinispan	<p>JBoss Cache was replaced by Infinispan for internal use by the server only in JBoss EAP 6. See the following sections in the JBoss EAP 6 <i>Migration Guide</i> for information about how to replace JBoss Cache in application code.</p> <ul style="list-style-type: none"> • Cache Changes <p>Infinispan caching strategy and configuration changes for JBoss EAP 7 are documented in the following section of this guide.</p> <ul style="list-style-type: none"> • Infinispan Server Configuration Changes
Data Sources and Resource Adapters	<p>JBoss EAP 6 consolidated configuration of data sources and resource adapters into mainly one file and this is still true in JBoss EAP 7. See the following section in the JBoss EAP 6 <i>Migration Guide</i> for more information.</p> <ul style="list-style-type: none"> • Datasource and Resource Adapter Configuration Changes <p>In addition, the ability to configure a generic JMS resource adapter to connect to a JMS provider is no longer supported in JBoss EAP 7. See the following section in this guide.</p> <ul style="list-style-type: none"> • Review The List of Deprecated and Unsupported Features
Directory Structure, Scripts, and Deployment Configuration	<p>In JBoss EAP 6, the directory structure, scripts, and deployment configuration changed. These changes are still valid in JBoss EAP 7. See the following section of the JBoss EAP 6 <i>Migration Guide</i> for more information.</p> <ul style="list-style-type: none"> • Review What's New and Different in JBoss EAP 6

JBoss EAP 5 Feature or Component	Summary of Changes and Where to Find Migration Information
EJB	<p>The Java EE 7 specification made EJB 2.x and earlier features optional, so it is strongly recommended that you rewrite your application code to use the EJB 3.x specification and JPA. For information about deprecated features and changes required to run EJB 2.x, see the following section in the <i>JBoss EAP 6 Migration Guide</i>.</p> <ul style="list-style-type: none"> • EJB 2.x and Earlier Changes <p>In JBoss EAP 6, stateful EJB cache and stateless session bean pool size is configured in the ejb3 subsystem of the server configuration file. The jboss-ejb3.xml deployment descriptor replaces the jboss.xml deployment descriptor file. For more information about these changes, see the following section in the <i>JBoss EAP 6 Migration Guide</i>.</p> <ul style="list-style-type: none"> • EJB Changes <p>The default remote connector and port has changed in JBoss EAP 7. For more information about this and server configuration changes, see the following sections in this guide.</p> <ul style="list-style-type: none"> • EJB Server Configuration Changes • Migrate EJB Client Code <p>EJB entity beans are not supported in JBoss EAP 7. For information about how to migrate entity beans to JPA, see the following section in this guide.</p> <ul style="list-style-type: none"> • Migrate Entity Beans to JPA
Hibernate and JPA	<p>In JBoss EAP 6, Hibernate was updated from version 3 to version 4. This version of JBoss EAP also implemented the JPA 2.0 specification and changes were made to JPA persistence properties. For information about how to modify your application for these changes, see the following section in the <i>JBoss EAP 6 Migration Guide</i>.</p> <ul style="list-style-type: none"> • Hibernate and JPA Changes <p>JBoss EAP 7 implements JPA 2.1 and includes Hibernate 5. It also updates Hibernate Search from version 4.6.x to version 5.5.x. Other changes include removal of support for EJB entity beans and additional updates to JPA persistence properties. For information about how these changes impact your applications, see the following sections in this guide.</p> <ul style="list-style-type: none"> • Hibernate and JPA Migration Changes • Hibernate Search Changes • Migrate Entity Beans to JPA • JPA Persistence Property Changes

JBoss EAP 5 Feature or Component	Summary of Changes and Where to Find Migration Information
JAX-RS and RESTEasy	<p>JBoss EAP 6 bundled RESTEasy 2, which automatically configured RESTEasy and required changes in application configuration. See the following section in the JBoss EAP 6 <i>Migration Guide</i> for information.</p> <ul style="list-style-type: none"> • JAX-RS and RESTEasy Changes <p>JBoss EAP 7 includes RESTEasy 3 and many classes have been deprecated. The version of Jackson changed from version 1.9.9 to version 2.6.3 or greater. For details about these changes, see the following section in this guide.</p> <ul style="list-style-type: none"> • JAX-RS and RESTEasy Application Changes
JBoss AOP	<p>JBoss AOP (Aspect Oriented Programming) was removed in JBoss EAP 6. For information about how to refactor applications that use JBoss AOP, see the following section in the JBoss EAP 6 <i>Migration Guide</i>.</p> <ul style="list-style-type: none"> • JBoss AOP Changes
JGroups and Clustering	<p>The way you enable clustering and specify bind addresses changed in JBoss EAP 6. See the following section in the JBoss EAP 6 <i>Migration Guide</i> for more information.</p> <ul style="list-style-type: none"> • Clustering Changes <p>In JBoss EAP 7, JGroups now defaults to using a private network interface instead of a public network interface and also introduces <code><channel></code> elements to the <code>jgroups</code> subsystem. JBoss EAP 7 also includes the Undertow <code>mod_cluster</code> implementation, introduces a new API for building singleton services, and other new clustering features. These changes are documented in the following sections of this guide.</p> <ul style="list-style-type: none"> • JGroups Server Configuration Changes • Application Clustering Changes
JNDI	<p>JBoss EAP 6 implemented a new standardized global JNDI namespace and a series of related namespaces that map to the various scopes of a Java EE application. See the following section of the JBoss EAP 6 <i>Migration Guide</i> for information about application changes needed to use the new JNDI namespace rules.</p> <ul style="list-style-type: none"> • JNDI Changes

JBoss EAP 5 Feature or Component	Summary of Changes and Where to Find Migration Information
JSF	<p>JBoss EAP 6 included JSF 2.0 and allowed you to configure your application to use an older version. This is no longer possible in JBoss EAP 7, which now includes JSF 2.2. See the following section in this guide for more information.</p> <ul style="list-style-type: none"> • JavaServer Faces (JSF) Code Changes
Logging	<p>JBoss EAP 6 introduced a new JBoss Logging framework that is still used in JBoss EAP 7. Applications that use third-party logging frameworks might be impacted by the modular class loading changes. Review the following section in the JBoss EAP 6 <i>Migration Guide</i> for information about these changes.</p> <ul style="list-style-type: none"> • Logging Changes <p>In JBoss EAP 7, annotations in the <code>org.jboss.logging</code> package are now deprecated, which impacts source code and Maven GAVs (groupid:artifactId:version). The prefixes for all log messages were also changed. For more information about these changes, see the following sections in this guide.</p> <ul style="list-style-type: none"> • JBoss Logging Changes • Logging Message Prefix Changes
Messaging and JMS	<p>In JBoss EAP 6, HornetQ replaced JBoss Messaging as the default JMS implementation. Then in JBoss EAP 7, ActiveMQ Artemis replaced HornetQ as the built-in messaging provider.</p> <p>The best approach to migrating your messaging configuration is to start with the JBoss EAP 7 default server configuration and use the following guide to apply your current messaging configuration changes.</p> <ul style="list-style-type: none"> • Configuring Messaging for JBoss EAP 7 <p>If you want to understand the changes required to move from JBoss Messaging to HornetQ, review the following section of the JBoss EAP 6 <i>Migration Guide</i>.</p> <ul style="list-style-type: none"> • HornetQ Changes <p>Then review the following information about how to migrate the HornetQ configuration and related messaging data in this guide.</p> <ul style="list-style-type: none"> • Messaging Server Configuration Changes • Messaging Application Changes

JBoss EAP 5 Feature or Component	Summary of Changes and Where to Find Migration Information
ORB	<p>In JBoss EAP 6, JacORB configuration was moved from the EAP_HOME/server/production/conf/jacorb.properties file to the server configuration file. JBoss EAP 7 then replaced the JacORB IIOp implementation with a downstream branch of the OpenJDK ORB.</p> <p>The best approach to migrating your ORB configuration is to start with the JBoss EAP 7 default server configuration and use the following section in the <i>JBoss EAP 7 Configuration Guide</i> to apply the your current ORB configuration changes.</p> <ul style="list-style-type: none"> • ORB Configuration
Remote Invocation	<p>A new EJB client API was introduced in JBoss EAP 6 for remote invocations; however, if you preferred not to rewrite your application code to use the new API, you could modify your existing code to use the <code>ejb:BEAN_REFERENCE</code> for remote access to EJBs. See the following section in the <i>JBoss EAP 6 Migration Guide</i> for more information.</p> <ul style="list-style-type: none"> • Remote Invocation Changes <p>In JBoss EAP 7, the default connector and default remote connection port changed. For more information, see the following sections in this guide.</p> <ul style="list-style-type: none"> • Update the Remote URL Connector and Port • Update External Clients • Migrate EJB Client Code
Seam 2.x	<p>While official support for Seam 2.2 applications was dropped in JBoss EAP 6, it was still possible to configure dependencies for JSF 1.2 and Hibernate 3 to allow Seam 2.2 applications to run on that release. JBoss EAP 7, which now includes JSF 2.2 and Hibernate 5, does not support Seam 2.2 or Seam 2.3 due to end of life of Red Hat JBoss Web Framework Kit. It is recommended that you rewrite your Seam components using Weld CDI beans.</p>
Security	<p>Security updates in JBoss EAP 6 included changes to security domain names and changes to how to configure security for basic authentication. The LDAP security realm configuration was moved to the server configuration file. See the following sections in the <i>JBoss EAP 6 Migration Guide</i> for more information.</p> <ul style="list-style-type: none"> • Security Changes • LDAP Security Realm Changes <p>Updates that impact security in JBoss EAP 7 include server configuration changes and application changes. Information can be found in the following sections of this guide.</p> <ul style="list-style-type: none"> • Security Server Configuration Changes • Security Application Changes

JBoss EAP 5 Feature or Component	Summary of Changes and Where to Find Migration Information
Spring Applications	<p>Spring 4.2.x is the earliest stable Spring version supported by JBoss EAP 7. For information about Apache CXF Spring web services and Spring RESTEasy integration changes, see the following sections in this guide.</p> <ul style="list-style-type: none"> • Apache CXF Spring Web Services Changes • Spring RESTEasy Integration Changes
Transactions	<p>JBoss EAP 6 consolidated transaction configuration and moved it to the server configuration file. Other updates included changes to JTA node identifier settings and how to enable JTS. For details, see the following section in the <i>JBoss EAP 6 Migration Guide</i>.</p> <ul style="list-style-type: none"> • JTS and JTA Changes <p>Some Transaction Manager configuration attributes that were available in the transactions subsystem in JBoss EAP 6 have changed in JBoss EAP 7. For more information, see the following section in this guide.</p> <ul style="list-style-type: none"> • Migrate Transactions Subsystem Changes
Valves	<p>Undertow replaced JBoss Web in JBoss EAP 7 and valves are no longer supported. See the following sections in this guide.</p> <ul style="list-style-type: none"> • Migrate Global Valves • Migrate Custom Application Valves • Migrate Authenticator Valves
Web Services	<p>JBoss EAP 6 included JBossWS 4. For information about the changes required by that version update, see the following section in the <i>JBoss EAP 6 Migration Guide</i>.</p> <ul style="list-style-type: none"> • Web Services Changes <p>JBoss EAP 7 introduced JBossWS 5. See the following section in this guide for required updates.</p> <ul style="list-style-type: none"> • Web Services Applications Changes

APPENDIX A. REFERENCE MATERIAL

A.1. JACORB SUBSYSTEM MIGRATION OPERATION WARNINGS

The `migrate` operation is not able to process all resources and attributes. The following table lists some of the warnings you might see when you run either the `migrate` or `describe-migration` operation for the `jacorb` subsystem.



NOTE

If you see "Could not migrate" or "Can not migrate" entries in the output of the `migrate` operation, this indicates the migration of the server configuration completed successfully but it was not able to automatically migrate all of the elements and attributes. You must follow the suggestions provided by the "migration-warnings" to modify those configurations.

Warning Message	What It Means / How to Fix It
The <code>iiop</code> migration can be performed when the server is in <code>admin-only</code> mode	<p>The <code>migrate</code> operation requires starting the server in <code>admin-only</code> mode, which is done by adding parameter <code>--admin-only</code> to the server start command:</p> <pre>\$ EAP_HOME/bin/standalone.sh --admin-only</pre>
Properties <code>X</code> cannot be emulated using OpenJDK ORB and are not supported	<p>Configuration of the specified property is not supported and is not included in the new <code>iiop-openjdk</code> subsystem configuration. The behavior exhibited by this property in the previous release of JBoss EAP is not migrated and the administrator must verify that the new <code>iiop-openjdk</code> subsystem in JBoss EAP 7 is able to operate correctly without that behavior.</p> <p>Unsupported properties include: <code>cache-poa-names</code>, <code>cache-typecodes</code>, <code>chunk-custom-rmi-valuetypes</code>, <code>client-timeout</code>, <code>comet</code>, <code>indirection-encoding-disable</code>, <code>iona</code>, <code>lax-boolean-encoding</code>, <code>max-managed-buf-size</code>, <code>max-server-connections</code>, <code>max-threads</code>, <code>outbuf-cache-timeout</code>, <code>outbuf-size</code>, <code>queue-max</code>, <code>queue-min</code>, <code>poa-monitoring</code>, <code>print-version</code>, <code>retries</code>, <code>retry-interval</code>, <code>queue-wait</code>, <code>server-timeout</code>, <code>strict-check-on-tc-creation</code>, <code>use-bom</code>, <code>use-imr</code>.</p>

Warning Message	What It Means / How to Fix It
<p>The properties <i>X</i> use expressions. Configuration properties that are used to resolve those expressions should be transformed manually to the new iiop-openjdk subsystem format</p>	<p>Properties that use expressions must be configured manually by the administrator.</p> <p>For example, the jacorb subsystem in JBoss EAP 6 defined a giop-minor-version property. The iiop-openjdk subsystem in JBoss EAP 7 defines a giop-version property. Suppose the jacorb subsystem minor version attribute is set to <code>\${iiop-giop-minor-version}</code> and the system property is configured in the <code>standalone.conf</code> file as <code>-Diiop-giop-minor-version=1</code>. After the migrate operation, the administrator must change the system property value to <code>1.1</code> to ensure the new subsystem is configured correctly.</p>
<p>Can not migrate: the new iiop-openjdk subsystem is already defined</p>	<p>The message contains the explanation.</p>

A.2. MESSAGING SUBSYSTEM MIGRATION OPERATION WARNINGS

The **migrate** operation is not able to process all resources and attributes. The following table lists some of the warnings you might see when you run either the **migrate** or **describe-migration** operation for the messaging subsystem.



NOTE

If you see "Could not migrate" or "Can not migrate" entries in the output of the **migrate** operation, this indicates the migration of the server configuration completed successfully but it was not able to automatically migrate all of the elements and attributes. You must follow the suggestions provided by the "migration-warnings" to modify those configurations.

Warning Message	What It Means / How to Fix It
<p>The migrate operation can not be performed: the server must be in admin-only mode</p>	<p>The migrate operation requires starting the server in admin-only mode, which is done by adding parameter <code>--admin-only</code> to the server start command:</p> <pre>\$ EAP_HOME/bin/standalone.sh --admin-only</pre>

Warning Message	What It Means / How to Fix It
Can not migrate attribute local-bind-address from resource <i>X</i> . Use instead the socket-binding attribute to configure this broadcast-group .	The message contains the explanation and how to fix it.
Can not migrate attribute local-bind-port from resource <i>X</i> . Use instead the socket-binding attribute to configure this broadcast-group .	The message contains the explanation and how to fix it.
Can not migrate attribute group-address from resource <i>X</i> . Use instead the socket-binding attribute to configure this broadcast-group .	The message contains the explanation and how to fix it.
Can not migrate attribute group-port from resource <i>X</i> . Use instead the socket-binding attribute to configure this broadcast-group .	The broadcast-group resource no longer accepts the local-bind-address , local-bind-port , group-address , or group-port attributes. It only accepts a socket-binding attribute. The warning is notification that resource <i>X</i> has an unsupported attribute. You must manually set the socket-binding attribute on the resource and ensure it corresponds to a defined socket-binding resource.
Classes providing the <i>X</i> are discarded during the migration. To use them in the new messaging-activemq subsystem, you will have to extend the Artemis-based Interceptor .	Messaging interceptors support is significantly different in JBoss EAP 7. Any interceptors configured in the previous version of the subsystem are discarded during migration. See Migrate Messaging Interceptors for more information.
Can not migrate the HA configuration of <i>X</i> . Its shared-store and backup attributes holds expressions and it is not possible to determine unambiguously how to create the corresponding ha-policy for the messaging-activemq's server.	This means the hornetq-server X's shared-store or backup attributes contained an expression, such as $\${xxx}$, and the migration operation was not able to resolve it to a concrete expression. The value is discarded and the ha-policy for the messaging-activemq must be updated manually.
Can not migrate attribute local-bind-address from resource <i>X</i> . Use instead the socket-binding attribute to configure this discovery-group .	The message contains the explanation and how to fix it.
Can not migrate attribute local-bind-port from resource <i>X</i> . Use instead the socket-binding attribute to configure this discovery-group .	The message contains the explanation and how to fix it.

Warning Message	What It Means / How to Fix It
<p>Can not migrate attribute group-address from resource X. Use instead the socket-binding attribute to configure this discovery-group.</p>	<p>The message contains the explanation and how to fix it.</p>
<p>Can not migrate attribute group-port from resource X. Use instead the socket-binding attribute to configure this discovery-group.</p>	<p>The discovery-group resources no longer accept local-bind-address, local-bind-port, group-address, or group-port attributes. It only accepts a socket-binding. The warning is notification that resource X has an unsupported attribute. You must manually set the socket-binding attribute on the resource and ensures it corresponds to a defined socket-binding resource.</p>
<p>Can not create a legacy-connection-factory based on connection-factory X. It uses a HornetQ in-vm connector that is not compatible with Artemis in-vm connector</p>	<p>The legacy HornetQ remote connection-factory resources are migrated into legacy-connection-factory resources to allow JBoss EAP 6 clients to connect to JBoss EAP 7. However, legacy-connection-factory resources are only created when the connection-factory is using remote connectors. Any connection-factory using in-vm is not migrated because in-vm clients are based on JBoss EAP 7, not JBoss EAP 6. This warning is notification that the in-vm connection-factory was not migrated.</p>
<p>Can not migrate attribute X from resource Y. The attribute uses an expression that can be resolved differently depending on system properties. After migration, this attribute must be added back with an actual value instead of the expression.</p>	<p>This warning appears when the migration can not resolve attribute X to a concrete value during the migration process. The value is discarded and the attribute must be migrated manually. This happens in the following cases:</p> <ul style="list-style-type: none"> <p>• cluster-connection forward-when-no-consumers: This boolean attribute has been replaced by the message-load-balancing-type attribute, which is an enum with a value of OFF, STRICT, or ON_DEMAND.</p> <p>• broadcast-group and discovery-group's jgroups-stack and jgroups-channel attributes They reference other resources and JBoss EAP 7 no longer accepts these expressions.</p>

Warning Message	What It Means / How to Fix It
<p>Can not migrate attribute <i>X</i> from resource <i>Y</i>. This attribute is not supported by the new messaging-activemq subsystem.</p>	<p>Some attributes are no longer supported in the new messaging-activemq subsystem and are simply discarded:</p> <ul style="list-style-type: none"> • hornetq-server's failback-delay • http-connector's use-nio attribute • http-acceptor's use-nio attribute • remote-connector's use-nio attribute • remote-acceptor's use-nio attribute
<p>Can not migrate attribute failback-delay from resource <i>X</i>. Artemis detects failback deterministically and it no longer requires to specify a delay for failback to occur.</p>	<p>The message contains the explanation.</p>

Replace the Deprecated **broadcast-group** or **discovery-group** Attributes

If you are advised to replace the deprecated **broadcast-group** or **discovery-group** attributes with the **socket-binding** attribute, you can add the new attribute using the management CLI.

This example assumes you are migrating a standalone server that contains the following **discovery-group** configuration in the **messaging** subsystem.

```
<discovery-groups>
  <discovery-group name="my-discovery-group">
    <group-address>224.0.1.105</group-address>
    <group-port>56789</group-port>
  </discovery-group>
</discovery-groups>
```

When you run the **migrate** operation for the **messaging** subsystem, you see the following output and warnings:

```
[standalone@localhost:9999 /] /subsystem=messaging:migrate
{
  "outcome" => "success",
  "result" => {"migration-warnings" => [
    "WFLYMSG0084: Can not migrate attribute group-address from
resource [
  (\\"subsystem\\" => \\"messaging-activemq\\"),
  (\\"server\\" => \\"default\\"),
  (\\"discovery-group\\" => \\"my-discovery-group\\")
]. Use instead the socket-binding attribute to configure this discovery-
group.",
    "WFLYMSG0084: Can not migrate attribute group-port from resource [
  (\\"subsystem\\" => \\"messaging-activemq\\"),
  (\\"server\\" => \\"default\\"),
```

```

    ("discovery-group\" => \"my-discovery-group\")
  ]. Use instead the socket-binding attribute to configure this discovery-
  group."
  ]}
}

```

The `migrate` operation creates a **discovery-group** named "my-discovery-group" in the new `messaging-activemq` subsystem that is now configured like the following.

```
<discovery-group name="my-discovery-group"/>
```

You must now use the following management CLI command to create a **socket-binding** element in the server configuration file named "my-discovery-group-socket-binding".

```
/socket-binding-group=standard-sockets/socket-binding=my-discovery-group-
socket-binding:add(multicast-address=224.0.1.105, multicast-port=56789)
```

Next, add the newly created **socket-binding** to the **discovery-group** named "my-discovery-group" in the `messaging-activemq` subsystem in the server configuration file using the following management CLI command.

```
/subsystem=messaging-activemq/server=default/discovery-group=my-discovery-
group:write-attribute(name=socket-binding,value=my-discovery-group-socket-
binding)
```

These commands create the following XML in the server configuration file.

```

<subsystem xmlns="urn:jboss:domain:messaging-activemq:1.0">
  <server name="default">
    ...
    <discovery-group name="my-discovery-group" socket-binding="my-
discovery-group-socket-binding"/>
    ...
  </server>
</subsystem>
...
<socket-binding-group name="standard-sockets" default-interface="public"
port-offset="${jboss.socket.binding.port-offset:0}">
  ...
  <socket-binding name="my-discovery-group-socket-binding" multicast-
address="224.0.1.105" multicast-port="56789"/>
  ...
</socket-binding-group>

```

A.3. WEB SUBSYSTEM MIGRATION OPERATION WARNINGS

The `migrate` operation is not able to process all resources and attributes. The following table lists some of the warnings you might see when you run either the `migrate` or `describe-migration` operation for the `web` subsystem.



NOTE

If you see "Could not migrate" or "Can not migrate" entries in the output of the `migrate` operation, this indicates the migration of the server configuration completed successfully but it was not able to automatically migrate all of the elements and attributes. You must follow the suggestions provided by the "migration-warnings" to modify those configurations.

Warning Message	What It Means / How to Fix It
Migrate operation only allowed in admin only mode	<p>The <code>migrate</code> operation requires starting the server in admin-only mode, which is done by adding parameter <code>--admin-only</code> to the server start command:</p> <pre data-bbox="815 689 1385 786">\$ EAP_HOME/bin/standalone.sh --admin-only</pre>
Could not migrate resource <i>X</i>	<p>The behavior exhibited by this resource in the previous release of JBoss EAP was not migrated. The administrator must verify if the new undertow subsystem in JBoss EAP 7 is able to operate correctly without that behavior or whether the behavior must be migrated manually.</p>
Could not migrate attribute <i>X</i> from resource <i>Y</i> .	<p>The behavior exhibited by this resource attribute in the previous release of JBoss EAP was not migrated. The administrator must verify if the new undertow subsystem in JBoss EAP 7 is able to operate correctly without that behavior or whether the behavior must be migrated manually.</p> <p>See Web Subsystem Migration Operation Attribute Warnings for the list of attributes that are not migrated.</p>
Could not migrate SSL connector as no SSL config is defined	<p>The message contains the explanation.</p>
Could not migrate verify-client attribute <i>X</i> to the Undertow equivalent	<p>The message contains the explanation.</p>
Could not migrate verify-client expression <i>X</i>	<p>The message contains the explanation.</p>

Warning Message	What It Means / How to Fix It
<p>Could not migrate valve <i>X</i></p>	<p>The behavior exhibited by this valve in the previous release of JBoss EAP was not migrated. The administrator must verify if the new undertow subsystem in JBoss EAP 7 is able to operate correctly without that behavior or whether the behavior must be migrated manually.</p> <p>This warning can occur for the following valves:</p> <ul style="list-style-type: none">• org.apache.catalina.valves.RemoteAddrValve It must have at least one allowed or denied value.• org.apache.catalina.valves.RemoteHostValve It must have at least one allowed or denied value.• org.apache.catalina.authenticator.BasicAuthenticator• org.apache.catalina.authenticator.DigestAuthenticator• org.apache.catalina.authenticator.FormAuthenticator• org.apache.catalina.authenticator.SSLAuthenticator• org.apache.catalina.authenticator.SpnegoAuthenticator• custom valves

Warning Message	What It Means / How to Fix It
<p>Could not migrate attribute X from valve Y</p>	<p>The behavior exhibited by this valve attribute in the previous release of JBoss EAP was not migrated. The administrator must verify if the new undertow subsystem in JBoss EAP 7 is able to operate correctly without that behavior or whether the behavior must be migrated manually. This warning can occur for the following valve attributes:</p> <ul style="list-style-type: none"> • org.apache.catalina.valves.AccessLogValve <ul style="list-style-type: none"> ◦ resolveHosts ◦ fileDateFormat ◦ renameOnRotate ◦ encoding ◦ locale ◦ requestAttributesEnabled ◦ buffered • org.apache.catalina.valves.ExtendedAccessLogValve <ul style="list-style-type: none"> ◦ resolveHosts ◦ fileDateFormat ◦ renameOnRotate ◦ encoding ◦ locale ◦ requestAttributesEnabled ◦ buffered • org.apache.catalina.valves.RemoteIpValve <ul style="list-style-type: none"> ◦ httpServerPort ◦ httpsServerPort ◦ remoteIpHeader If it is defined but not set to "x-forwarded-for" ◦ protocolHeader If it is defined but not set to "x-forwarded-proto"

Web Subsystem Migration Operation Attribute Warnings

The `migrate` operation is not able to process all JBoss Web attributes. See the following reference tables for information about how to migrate the unprocessed attributes manually.

Web SSL Connector Attributes

The following attributes were used in JBoss EAP 6 to configure the SSL connector. OpenSSL native libraries are not supported in JBoss EAP 7 so there are no equivalent settings.

Attribute	Description	Undertow Equivalent
<code>ca-revocation-url</code>	The file or URL that contains the revocation list.	No equivalent in Undertow.
<code>certificate-file</code>	When using OpenSSL encryption, the path to the file containing the server certificate.	No equivalent in Undertow.
<code>ssl-protocol</code>	The SSL protocol string.	No equivalent in Undertow.
<code>verify-depth</code>	The maximum number of intermediate certificate issuers checked before deciding that the clients do not have a valid certificate.	No equivalent in Undertow.

Web Static Resource Attributes

The following `static-resources` element attributes were used to describe how static resources were handled by the `DefaultServlet` or by the `WebdavServlet`. There are no equivalents for these attributes because WebDAV is not supported by Undertow. For more information, see <https://issues.jboss.org/browse/JBEAP-1036>.

Attribute	Description	Undertow Equivalent
<code>disabled</code>	Enable the default Servlet mapping.	No equivalent setting in Undertow.
<code>file-encoding</code>	File encoding to be used when reading static files.	No equivalent setting in Undertow.
<code>max-depth</code>	Maximum recursion for PROPFIND .	This is a WebDAV setting and WebDAV is not supported by Undertow.
<code>read-only</code>	Allow write HTTP methods (PUT, DELETE).	This is a WebDAV setting and WebDAV is not supported by Undertow.
<code>secret</code>	Secret for WebDAV locking operations.	This is a WebDAV setting and WebDAV is not supported by Undertow.
<code>sendfile</code>	Enable sendfile if possible, for files bigger than the specified byte size.	This is set to a sensible default value in Undertow and is not configurable.

Attribute	Description	Undertow Equivalent
webdav	Enable WebDAV functionality.	WebDAV is not supported by Undertow.

Web SSO Resource Attributes

SSO is handled differently than in the previous release and there are no equivalent attribute settings in JBoss EAP 7.

JBoss Web Attribute	Description	Undertow Equivalent
cache-container	Name of the cache container to use for clustered SSO.	This setting is no longer needed in Undertow. This works by default across a distributed clustered environment.
cache-name	Name of the cache to use for clustered SSO.	This setting is no longer needed in Undertow. This works by default across a distributed clustered environment.
reauthenticate	Whether each request should cause a reauthentication.	There is no equivalent setting in Undertow, which behaves similarly to the reauthenticate=true setting in JBoss EAP 6. While reauthenticate=false could possibly improve performance, it could also create security issues.

Web Access Log Attributes

JBoss Web Attribute	Description	Undertow Equivalent
resolve-hosts	Whether to enable resolving hosts for access logging.	Use the setting on the connector to accomplish the same behavior.

Web Connector Attributes

JBoss Web Attribute	Description	Undertow Equivalent
executor	The name of the executor that should be used to process the threads of this connector.	You now reference a worker that is defined in the io subsystem. See Migrate the Threads Subsystem Configuration for more information.

JBoss Web Attribute	Description	Undertow Equivalent
proxy-binding	The socket binding to define the host and port that is used when sending a redirect.	There is no direct equivalent. See https-listener Attributes in the <i>JBoss EAP Configuration Guide</i> for available configuration options.
redirect-port	The port for redirection to a secure connector.	This attribute was deprecated in JBoss EAP 6 and replaced with redirect-binding . Undertow provides the redirect-socket attribute on the http-listener element, which is a replacement for redirect-binding . See https-listener Attributes in the <i>JBoss EAP Configuration Guide</i> for more information.

A.4. MIGRATE JOSS WEB SYSTEM PROPERTIES REFERENCE

This reference describes how to map system properties previously used for JBoss Web configuration to the equivalent configuration for Undertow in JBoss EAP 7.

- [Map Servlet Container and Connectors System Properties](#)
- [Map EL System Properties](#)
- [Map JSP System Properties](#)
- [Map Security System Properties](#)

Table A.1. Map Servlet Container and Connectors System Properties

JBoss EAP 6 System Property	Description
	Equivalent in JBoss EAP 7
jvmRoute	<p>Provides a default value for the jvmRoute attribute. It does not override the automatically generated value when using the standalone-ha.xml configuration file.</p> <p>It supports reload.</p> <p>Management CLI command:</p> <pre>/subsystem=undertow:write-attribute(name=instance-id,value=VALUE)</pre>

org.apache.tomcat.util.buf.StringCache.byte.enabled	<p>If true, the String cache is enabled for ByteChunk. If the value is not specified, the default value of false is used.</p> <p>No equivalent configuration</p>
org.apache.tomcat.util.buf.StringCache.char.enabled	<p>If true, the String cache is enabled for CharChunk. If the value is not specified, the default value of false is used.</p> <p>No equivalent configuration</p>
org.apache.tomcat.util.buf.StringCache.cacheSize	<p>The size of the String cache. If the value is not specified, the default value of 5000 is used.</p> <p>No equivalent configuration</p>
org.apache.tomcat.util.buf.StringCache.maxStringSize	<p>The maximum length of String that will be cached. If the value is not specified, the default value of 128 is used.</p> <p>No equivalent configuration</p>
org.apache.tomcat.util.http.FastDateFormat.CACHE_SIZE	<p>The size of the cache to use parsed and formatted date value. If the value is not specified, the default value of 1000 is used.</p> <p>No equivalent configuration</p>
org.apache.catalina.core.StandardService.DELAY_CONNECTOR_STARTUP	<p>If true, the connector startup is not done automatically. It is useful in embedded mode.</p> <p>No equivalent configuration</p>
org.apache.catalina.connector.Request.SESSION_ID_CHECK	<p>If true, the Servlet container verifies that a session exists in a context with the specified session ID before creating a session with that ID.</p> <p>No equivalent configuration</p>
org.apache.coyote.USE_CUSTOM_STATUS_MSG_IN_HEADER	<p>If true, custom HTTP status messages are used within HTTP headers. Users must ensure that any such message is ISO-8859-1 encoded, particularly if user provided input is included in the message, to prevent a possible XSS vulnerability. If value is not specified the default value of false is used.</p> <p>Must be enabled programmatically by implementing a custom io.undertow.servlet.ServletExtension. Then use the extension to call setSendCustomReasonPhraseOnError(true) on the io.undertow.servlet.api.DeploymentInfo structure instance.</p>

<p>org.apache.tomcat.util.http.Parameters.MAX_COUNT</p>	<p>The maximum number of parameters that can be parsed in a post body. If exceeded, parsing fails using an IllegalStateException. The default value is 512 parameters.</p> <p>Management CLI command:</p> <pre> /subsystem=undertow/server=default-server/http-listener=default:write-attribute(name=max-parameters,value=VALUE) /subsystem=undertow/server=default-server/https-listener=default:write-attribute(name=max-parameters,value=VALUE) /subsystem=undertow/server=default-server/ajp-listener=default:write-attribute(name=max-parameters,value=VALUE) </pre>
<p>org.apache.tomcat.util.http.MimeHeaders.MAX_COUNT</p>	<p>The maximum number of headers that can be sent in the HTTP request. If exceeded, parsing will fail using an IllegalStateException. The default value is 128 headers.</p> <p>Management CLI command:</p> <pre> /subsystem=undertow/server=default-server/http-listener=default:write-attribute(name=max-headers,value=VALUE) /subsystem=undertow/server=default-server/https-listener=default:write-attribute(name=max-headers,value=VALUE) /subsystem=undertow/server=default-server/ajp-listener=default:write-attribute(name=max-headers,value=VALUE) </pre>
<p>org.apache.tomcat.util.net.MAX_THREADS</p>	<p>The maximum number of threads a connector is going to use to process requests. The default value is 32 x 512. (512 x Runtime.getRuntime().availableProcessors() for the JIO connector)</p> <p>Management CLI command:</p> <pre> /subsystem=io/worker=default:write-attribute(name=task-max-threads,value=VALUE) </pre>
<p>org.apache.coyote.http11.Http11Protocol.MAX_HEADER_SIZE</p>	<p>The maximum size of the HTTP headers, in bytes. If exceeded, parsing will fail using an ArrayOutOfBoundsException. The default value is 8192 bytes.</p>

	<p>Management CLI command:</p> <pre> /subsystem=undertow/server=default-server/http-listener=default:write-attribute(name=max-header-size,value=VALUE) /subsystem=undertow/server=default-server/https-listener=default:write-attribute(name=max-header-size,value=VALUE) /subsystem=undertow/server=default-server/ajp-listener=default:write-attribute(name=max-header-size,value=VALUE) </pre>
<p>org.apache.coyote.http11.Http11Protocol.COMPRESSION</p>	<p>Allows using simple compression with the HTTP connector. The default value is off, and compression can be enabled using the value on to enable it conditionally, or force to always enable it.</p> <p>Configure a filter using the management CLI:</p> <pre> # Create a filter /subsystem=undertow/configuration=filter/gzip=gzipfilter:add() /subsystem=undertow/server=default-server/host=default-host/filter-ref=gzipfilter:add() </pre>
<p>org.apache.coyote.http11.Http11Protocol.COMPRESSION_RESTRICTED_UA</p>	<p>User agents regexps that will not receive compressed content. The default value is empty.</p> <p>Configure a predicate in a filter using the management CLI:</p> <pre> # Use a predicate in a filter /subsystem=undertow/configuration=filter/gzip=gzipfilter:add() /subsystem=undertow/server=default-server/host=default-host/filter-ref=gzipfilter:add(predicate="regex[pattern='AppleWebKit',value=%{i,User-Agent}]") </pre>
<p>org.apache.coyote.http11.Http11Protocol.COMPRESSION_MIME_TYPES</p>	<p>Content type prefixes of compressible content. The default value is text/html, text/xml, text/plain.</p>

	<p>Configure a predicate in a filter using the management CLI:</p> <pre># Use a predicate in a filter /subsystem=undertow/configuration=filter/ gzip=gzipfilter:add() /subsystem=undertow/server=default- server/host=default-host/filter- ref=gzipfilter:add(predicate="regex[patte rn='text/html',value=%{o,Content-Type}]")</pre>
<p>org.apache.coyote.http11.Http11Protocol. COMPRESSION_MIN_SIZE</p>	<p>Minimum size of content that will be compressed. The default value is 2048 bytes.</p> <p>Configure a predicate in a filter using the management CLI:</p> <pre># Use a predicate in a filter /subsystem=undertow/configuration=filter/ gzip=gzipfilter:add() /subsystem=undertow/server=default- server/host=default-host/filter- ref=gzipfilter:add(predicate="max- content-size[value=MIN_SIZE]")</pre>
<p>org.apache.coyote.http11.DEFAULT_CON NECTION_TIMEOUT</p>	<p>Default socket timeout. The default value is 60000 ms.</p> <p>Management CLI command:</p> <pre>/subsystem=undertow/server=default- server/http-listener=default:write- attribute(name=no-request- timeout,value=VALUE) /subsystem=undertow/server=default- server/https-listener=default:write- attribute(name=no-request- timeout,value=VALUE) /subsystem=undertow/server=default- server/ajp-listener=default:write- attribute(name=no-request- timeout,value=VALUE)</pre>
<p>org.jboss.as.web.deployment.DELETE_W ORK_DIR_ONCONTEXTDESTROY</p>	<p>Use this property to remove .java and .class files to ensure that JSP sources are recompiled. The default value is false. Default socket timeout for keep-alive. The default value is -1 ms, which means it will use the default socket timeout.</p> <p>No equivalent configuration</p>

org.apache.tomcat.util.buf.StringCache.toStringThreshold	Specifies the number of times toString() must be invoked before activating cache. The default value is 100000 .
	No equivalent configuration

Table A.2. Map EL System Properties

JBoss EAP 6 System Property	Description
	Equivalent in JBoss EAP 7
org.apache.el.parser.COERCE_TO_ZERO	If true , when coercing expressions to numbers, empty strings ("") and null will be coerced to zero as required by the specification. If a value is not specified, the default value of true is used.
	System property is still valid and processed by the EL

Table A.3. Map JSP System Properties

JBoss EAP 6 System Property	Description
	Equivalent in JBoss EAP 7
org.apache.jasper.compiler.VariableGenerator.EXPRESSION_FACTORY	The name of the variable to use for the expression language expression factory. If value is not specified, the default value of _el_expressionfactory is used.
	System property has not changed
org.apache.jasper.compiler.VariableGenerator.INSTANCE_MANAGER	The name of the variable to use for the instance manager factory. If value is not specified, the default value of _jsp_instancemanager is used.
	System property has not changed
org.apache.jasper.compiler.Parser.STRICT_QUOTE_ESCAPING	If false , the requirements for escaping quotes in JSP attributes are relaxed so that a missing required quote does not cause an error. If value is not specified, the specification compliant default of true is used.
	System property has not changed
org.apache.jasper.Constants.DEFAULT_TAG_BUFFER_SIZE	Any tag buffer that expands beyond org.apache.jasper.Constants.DEFAULT_TAG_BUFFER_SIZE is destroyed and a new buffer is created of the default size. If value is not specified, the default value of 512 is used.

	System property has not changed
org.apache.jasper.runtime.JspFactoryImpl.USE_POOL	If true , a ThreadLocal PageContext pool is used. If value is not specified, the default value of true is used.
	System property has not changed
org.apache.jasper.runtime.JspFactoryImpl.POOL_SIZE	The size of the ThreadLocal PageContext. If value is not specified, the default value of 8 is used.
	System property has not changed
org.apache.jasper.Constants.JSP_SERVLET_BASE	The base class of the Servlets generated from the JSPs. If value is not specified, the default value of org.apache.jasper.runtime.HttpJspBase is used.
	System property has not changed
org.apache.jasper.Constants.SERVICE_METHOD_NAME	The name of the service method called by the base class. If value is not specified, the default value of _jspService is used.
	System property has not changed
org.apache.jasper.Constants.SERVLET_CLASSPATH	The name of the ServletContext attribute that provides the class path for the JSP. If value is not specified, the default value of org.apache.catalina.jsp_classpath is used.
	System property has not changed
org.apache.jasper.Constants.JSP_FILE	The name of the request attribute for <jsp-file> element of a servlet definition. If present on a request, this overrides the value returned by request.getServletPath() to select the JSP page to be executed. If value is not specified, the default value of org.apache.catalina.jsp_file is used.
	System property has not changed
org.apache.jasper.Constants.PRECOMPILE	The name of the query parameter that causes the JSP engine to just pregenerate the servlet but not invoke it. If value is not specified, the default value of org.apache.catalina.jsp_precompile is used.
	System property has not changed
org.apache.jasper.Constants.JSP_PACKAGE_NAME	The default package name for compiled JSP pages. If value not specified, the default value of org.apache.jsp is used.

	System property has not changed
org.apache.jasper.Constants.TAG_FILE_PACKAGE_NAME	The default package name for tag handlers generated from tag files. If value is not specified, the default value of org.apache.jsp.tag is used.
	System property has not changed
org.apache.jasper.Constants.TEMP_VARIABLE_NAME_PREFIX	Prefix to use for generated temporary variable names. If value is not specified, the default value of _jspx_temp is used.
	System property has not changed
org.apache.jasper.Constants.USE_INSTANCE_MANAGER_FOR_TAGS	If true , the instance manager is used to obtain tag handler instances. If value is not specified, true is used.
	System property has not changed
org.apache.jasper.Constants.INJECT_TAGS	If true , annotations specified in tags will be processed and injected. This can have a performance impact when using simple tags, or if tag pooling is disabled. If value is not specified, false is used.
	System property has not changed

Table A.4. Map Security System Properties

JBoss EAP 6 System Property	Description
	Equivalent in JBoss EAP 7
org.apache.catalina.connector.RECYCLE_FACADES	If this is true or if a security manager is in use a new facade object is created for each request. If value is not specified, the default value of false is used.
	No equivalent configuration
org.apache.catalina.connector.CoyoteAdapter.ALLOW_BACKSLASH	If this is true the \ character is permitted as a path delimiter. If value is not specified, the default value of false is used.
	No equivalent configuration
org.apache.tomcat.util.buf.UDecoder.ALL_OW_ENCODED_SLASH	If this is true , '%2F' and '%5C' is permitted as path delimiters. If value is not specified, the default value of false is used.

	<p>Management CLI command:</p> <pre> /subsystem=undertow/server=default-server/http-listener=default:write-attribute(name=allow-encoded-slash,value=VALUE) /subsystem=undertow/server=default-server/https-listener=default:write-attribute(name=allow-encoded-slash,value=VALUE) /subsystem=undertow/server=default-server/ajp-listener=default:write-attribute(name=allow-encoded-slash,value=VALUE) </pre>
<p>org.apache.catalina.STRICT_SERVLET_COMPLIANCE</p>	<p>If value is not specified, true is used. If this is true the following actions will occur: any wrapped request or response object passed to an application dispatcher is checked to ensure that it has wrapped the original request or response. (SRV.8.2 / SRV.14.2.5.1) a call to Response.getWriter() if no character encoding has been specified results in subsequent calls to Response.getCharacterEncoding() returning ISO-8859-1 and the Content-Type response header will include a charset=ISO-8859-1 component. (SRV.15.2.22.1) every request that is associated with a session causes the session's last accessed time to be updated regardless of whether or not the request explicitly accesses the session. (SRV.7.6)</p> <p>Compliant by default</p>
<p>org.apache.catalina.core.StandardWrapperValve.SERVLET_STATS</p>	<p>If true or if org.apache.catalina.STRICT_SERVLET_COMPLIANCE is true, the wrapper will collect the JSR-77 statistics for individual servlets. If value is not specified, the default value of false is used.</p> <p>No equivalent configuration</p>
<p>org.apache.catalina.session.StandardSession.ACTIVITY_CHECK</p>	<p>If this is true or if org.apache.catalina.STRICT_SERVLET_COMPLIANCE is true Tomcat tracks the number of active requests for each session. When determining if a session is valid, any session with at least one active request is always be considered valid. If value is not specified, the default value of false is used.</p> <p>No equivalent configuration</p>

A.5. COMPATIBILITY AND INTEROPERABILITY BETWEEN RELEASES

This section describes the compatibility and interoperability of client and server EJB and messaging components between the JBoss EAP 5, JBoss EAP 6, and JBoss EAP 7 releases.

EJB remoting over IIOP

You should not encounter problems with any of the following configurations.

- Connecting from a JBoss EAP 5 client to a JBoss EAP 7 server
- Connecting from a JBoss EAP 6 client to a JBoss EAP 7 server
- Connecting from a JBoss EAP 7 client to a JBoss EAP 6 server
- Connecting from a JBoss EAP 7 client to a JBoss EAP 5 server

EJB remoting Using JNDI

You should not encounter problems with any of the following configurations.

- Connecting from a JBoss EAP 6 client to a JBoss EAP 7 server
- Connecting from a JBoss EAP 7 client to a JBoss EAP 6 server

JBoss EAP 6 provided support for the EJB 3.1 specification and introduced the use of standardized global JNDI namespaces, which are still used in JBoss EAP 7. Due to the change in JNDI namespace names, the following configurations are not compatible:

- Connecting from a JBoss EAP 5 client to a JBoss EAP 7 or a JBoss EAP 6 server
- Connecting from a JBoss EAP 7 or JBoss EAP 6 client to a JBoss EAP 5 server

For more information about standardized JNDI namespace changes, see [JNDI Changes](#) in the *JBoss EAP 6 Migration Guide*.

EJB remoting Using @WebService

You should not encounter problems with any of the following configurations.

- Connecting from a JBoss EAP 5 client to a JBoss EAP 7 server
- Connecting from a JBoss EAP 6 client to a JBoss EAP 7 server
- Connecting from a JBoss EAP 7 client to a JBoss EAP 6 server
- Connecting from a JBoss EAP 7 client to a JBoss EAP 5 server

Messaging Standalone Client

You should not encounter problems with any of the following configurations.

- Connecting from a JBoss EAP 6 client to a JBoss EAP 7 server
- Connecting from a JBoss EAP 7 client to a JBoss EAP 6 server

In the following configuration, if the client is using the messaging broker-specific HornetQ API rather than the generic JMS API, the connection is possible. However, JNDI lookups must be addressed using the JBoss EAP legacy JNDI naming extension that is delivered with JBoss EAP 7.

- Connecting from a JBoss EAP 5 client to a JBoss EAP 7 server

JBoss EAP 7 built-in messaging is not able to connect to HornetQ 2.2.x that shipped with JBoss EAP 5 due to protocol compatibility issues. For this reason, the following configurations are not compatible.

- Connecting from a JBoss EAP 7 client to a JBoss EAP 5 server

Messaging MDBs

You should not encounter problems with any of the following configurations.

- Connecting from a JBoss EAP 6 client to a JBoss EAP 7 server
- Connecting from a JBoss EAP 7 client to a JBoss EAP 6 server

In the following configuration, if the client is using the messaging broker-specific HornetQ API rather than the generic JMS API, the connection is possible. However, JNDI lookups must be addressed using the JBoss EAP legacy JNDI naming extension that is delivered with JBoss EAP 7.

- Connecting from a JBoss EAP 5 client to a JBoss EAP 7 server

JBoss EAP 7 built-in messaging is not able to connect to HornetQ 2.2.x that shipped with JBoss EAP 5 due to protocol compatibility issues. For this reason, the following configurations are not compatible.

- Connecting from a JBoss EAP 7 client to a JBoss EAP 5 server

JMS bridges

You should not encounter problems with any of the following configurations.

- Connecting from a JBoss EAP 5 client to a JBoss EAP 7 server
- Connecting from a JBoss EAP 6 client to a JBoss EAP 7 server
- Connecting from a JBoss EAP 7 client to a JBoss EAP 6 server
- Connecting from a JBoss EAP 7 client to a JBoss EAP 5 server

Revised on 2018-02-08 10:18:33 EST