

Red Hat JBoss Web Server 5.6

HTTP Connectors and Load Balancing Guide 5.6

For Use with Red Hat JBoss Web Server 5.6

Last Updated: 2022-08-25

Red Hat JBoss Web Server 5.6 HTTP Connectors and Load Balancing Guide 5.6

For Use with Red Hat JBoss Web Server 5.6

Legal Notice

Copyright © 2022 Red Hat, Inc.

The text of and illustrations in this document are licensed by Red Hat under a Creative Commons Attribution–Share Alike 3.0 Unported license ("CC-BY-SA"). An explanation of CC-BY-SA is available at

http://creativecommons.org/licenses/by-sa/3.0/

. In accordance with CC-BY-SA, if you distribute this document or an adaptation of it, you must provide the URL for the original version.

Red Hat, as the licensor of this document, waives the right to enforce, and agrees not to assert, Section 4d of CC-BY-SA to the fullest extent permitted by applicable law.

Red Hat, Red Hat Enterprise Linux, the Shadowman logo, the Red Hat logo, JBoss, OpenShift, Fedora, the Infinity logo, and RHCE are trademarks of Red Hat, Inc., registered in the United States and other countries.

Linux ® is the registered trademark of Linus Torvalds in the United States and other countries.

Java [®] is a registered trademark of Oracle and/or its affiliates.

XFS [®] is a trademark of Silicon Graphics International Corp. or its subsidiaries in the United States and/or other countries.

MySQL ® is a registered trademark of MySQL AB in the United States, the European Union and other countries.

Node.js ® is an official trademark of Joyent. Red Hat is not formally related to or endorsed by the official Joyent Node.js open source or commercial project.

The OpenStack [®] Word Mark and OpenStack logo are either registered trademarks/service marks or trademarks/service marks of the OpenStack Foundation, in the United States and other countries and are used with the OpenStack Foundation's permission. We are not affiliated with, endorsed or sponsored by the OpenStack Foundation, or the OpenStack community.

All other trademarks are the property of their respective owners.

Abstract

Install and configure load-balancing solutions that use the `mod_cluster` and `mod_jk` connector modules along with other modules that the Red Hat JBoss Core Services Apache HTTP Server provides.

Table of Contents

PROVIDING FEEDBACK ON RED HAT DOCUMENTATION	. 4
MAKING OPEN SOURCE MORE INCLUSIVE	. 5
CHAPTER 1. HTTP CONNECTOR MODULES	. 6
CHAPTER 2. LOAD BALANCING WITH THE APACHE TOMCAT CONNECTOR (MOD_JK)	. 7
2.2. APACHE HTTP SERVER LOAD-BALANCING CONFIGURATION WHEN USING MOD_JK	7
2.3. CONFIGURING THE APACHE HTTP SERVER TO LOAD MOD_JK	7
2.4. CONFIGURING WORKER NODES IN MOD_JK	10
2.5. CONFIGURING TOMCAT TO WORK WITH MOD_JK	11
CHAPTER 3. LOAD BALANCING WITH THE JBOSS HTTP CONNECTOR (MOD_CLUSTER)	12
3.1. JBOSS HTTP CONNECTOR (MOD_CLUSTER)	12
3.2. MOD_CLUSTER CHARACTER LIMITS	13
3.3. MOD_CLUSTER INSTALLATION	14
3.4. APACHE HTTP SERVER LOAD-BALANCING CONFIGURATION WHEN USING MOD_CLUSTER 3.5. CONFIGURING A BASIC PROXY SERVER	14 15
3.5.1. Disabling server advertisement	16
3.5.2. Logging worker node details	17
3.6. CONFIGURING A TOMCAT WORKER NODE IN MOD_CLUSTER	18
3.7. CONFIGURING A WORKER NODE TO OPERATE WITH A STATIC LIST OF PROXY SERVERS	19
CHAPTER 4. SECURING CONNECTIONS BY USING OCSP	
4.1. ONLINE CERTIFICATE STATUS PROTOCOL	21
4.2. CONFIGURING THE APACHE HTTP SERVER FOR SSL CONNECTIONS	21
4.3. USING OCSP WITH THE APACHE HTTP SERVER	22
4.4. CONFIGURING THE APACHE HTTP SERVER TO VALIDATE OCSP CERTIFICATES 4.5. VERIFYING THE OCSP CONFIGURATION FOR THE APACHE HTTP SERVER	23 24
CHAPTER 5. CONFIGURATION EXAMPLE FOR LOAD-BALANCING WITH MOD_CLUSTER	25
5.1. SETTING UP JBOSS CORE SERVICES AS A PROXY SERVER	25
5.2. CONFIGURING A TOMCAT WORKER NODE	26
5.3. DEFINING IPTABLES FIREWALL RULES EXAMPLE	26
CHAPTER 6. CONFIGURATION EXAMPLE FOR KERBEROS AUTHENTICATION WITH MOD_AUTH_KERB	27
6.1. PREREQUISITES	27
6.2. CONFIGURING THE KERBEROS CLIENT	28
6.3. CONFIGURING MOD_AUTH_KERB	30
6.4. TESTING THE KERBEROS AUTHENTICATION	30
6.5. ADDITIONAL RESOURCES (OR NEXT STEPS)	32
APPENDIX A. APACHE HTTP SERVER PROXY MODULES	33
A.1. MOD_MANAGER MODULE AND DIRECTIVES	33
A.2. MOD_PROXY_CLUSTER MODULE AND DIRECTIVES	34
A.3. MOD_ADVERTISE MODULE AND DIRECTIVES	35
A.4. MOD_PROXY MODULE AND DIRECTIVES	36
A.S. MOD_PROXY_AJP MODULE AND DIRECTIVES	36
A.6. MOD_CLUSTER_SLOTMEM MODULE AND DIRECTIVES	36
APPENDIX B. WORKERS.PROPERTIES FILE	37
B.1. WORKERS.PROPERTIES OVERVIEW	37
B.2. WORKERS.PROPERTIES DIRECTIVES	37

Global directives for workers.properties	37
Mandatory directives for workers.properties	37
Connection directives for workers.properties	38
Load balancing directives for workers.properties	38
APPENDIX C. WORKER NODE CONFIGURATION	40
APPENDIX D. MOD_CLUSTER PROXY AND PROXY DISCOVERY CONFIGURATION ATTRIBUTES	42
APPENDIX E. LOAD CONFIGURATION FOR TOMCAT	44

PROVIDING FEEDBACK ON RED HAT DOCUMENTATION

We appreciate your feedback on our technical content and encourage you to tell us what you think. If you'd like to add comments, provide insights, correct a typo, or even ask a question, you can do so directly in the documentation.



NOTE

You must have a Red Hat account and be logged in to the customer portal.

To submit documentation feedback from the customer portal, do the following:

- 1. Select the Multi-page HTML format.
- 2. Click the **Feedback** button at the top-right of the document.
- 3. Highlight the section of text where you want to provide feedback.
- 4. Click the Add Feedback dialog next to your highlighted text.
- 5. Enter your feedback in the text box on the right of the page and then click **Submit**.

We automatically create a tracking issue each time you submit feedback. Open the link that is displayed after you click **Submit** and start watching the issue or add more comments.

Thank you for the valuable feedback.

MAKING OPEN SOURCE MORE INCLUSIVE

Red Hat is committed to replacing problematic language in our code, documentation, and web properties. We are beginning with these four terms: master, slave, blacklist, and whitelist. Because of the enormity of this endeavor, these changes will be implemented gradually over several upcoming releases. For more details, see our CTO Chris Wright's message.

CHAPTER 1. HTTP CONNECTOR MODULES

Red Hat JBoss Core Services includes two different HTTP connector modules that you can use to load-balance HTTP requests to a set of back-end servlet containers:

- The Apache Tomcat connector (mod_jk) supports the load balancing of HTTP requests to a set
 of servlet containers, while maintaining sticky sessions and communicating over the Apache
 JServ Protocol (AJP).
- The JBoss HTTP connector (mod_cluster) is a more advanced load balancer than mod_jk. The
 mod_cluster module provides all the functionality of mod_jk and additional features such as
 real-time load-balancing calculations, application life-cycle control, automatic proxy discovery,
 and multiple protocol support.

The HTTP Connectors and Load Balancing Guide describes how to install and configure the **mod_proxy** and **mod_cluster** connectors. This guide also provides information about Online Certificate Status Protocol (OCSP) and includes a set of working examples for basic load balancing and Kerberos authentication using mod_auth_kerb.



IMPORTANT

Most file and directory paths shown in this guide are for an archive installation of JBoss Core Services on Red Hat Enterprise Linux. For other platforms, use the correct paths for your respective installation, as specified in the JBoss Core Services *Installation Guide*.

Additional resources

- Load balancing with the Apache Tomcat connector (mod_jk)
- Load balancing with the JBoss HTTP connector (mod_cluster)

CHAPTER 2. LOAD BALANCING WITH THE APACHE TOMCAT CONNECTOR (MOD_JK)

The Apache Tomcat Connector, **mod_jk**, is a plug-in that allows the Apache HTTP Server to forward web requests to a back-end servlet container. The **mod_jk** module also allows the Apache HTTP Server to load-balance requests to a set of servlet containers, while maintaining sticky sessions.

2.1. MOD_JK INSTALLATION

The **mod_jk** module is included in the Apache HTTP Server part of a JBoss Core Services installation.

You can follow the procedures in the Red Hat JBoss Core Services Apache HTTP Server Installation Guide to download and install the Apache HTTP Server for your operating system.

Additional resources

• Red Hat JBoss Core Services Apache HTTP Server Installation Guide

2.2. APACHE HTTP SERVER LOAD-BALANCING CONFIGURATION WHEN USING MOD_JK

You can configure the Apache HTTP Server to use **mod_jk** to load-balance requests to a set of servlet containers. This setup includes the configuration of back-end worker nodes.

Red Hat JBoss Core Services provides example configuration files for **mod_jk** in the **JBCS_HOME**/httpd/conf.d/ directory. These example configuration files are named **mod_jk.conf.sample**, **workers.properties.sample**, and **uriworkermap.properties.sample**. To use these examples instead of creating your own configuration files, you can remove the **.sample** extension, and modify the file content as needed.



NOTE

You can also use the Load Balancer Configuration tool on the Red Hat Customer Portal to generate optimal configuration templates quickly for **mod_jk** and Tomcat worker nodes.

When you use the Load Balancer Configuration tool for JBoss Web Server 5.6, ensure that you select **2.4.x** as the Apache version, and select **Tomcat** as the back-end configuration.

2.3. CONFIGURING THE APACHE HTTP SERVER TO LOADMOD_JK

You can configure the Apache HTTP Server to load **mod_jk**, by specifying configuration settings in the **mod_jk.conf** file.

You can also perform the following optional configuration steps:

• In addition to the **JkMount** directive, you can use the **JkMountFile** directive to specify the configuration file for a mount point. The configuration file contains multiple URL mappings for Tomcat forwarding.

• You can configure the Apache HTTP Server that is functioning as the load balancer to log details of each worker node that handles a request. This can be useful if you need to troubleshoot your load balancer.

Procedure

- 1. Go to the **JBCS_HOME**/httpd/conf.d directory.
- 2. Create a new file named **mod_jk.conf** and enter the following configuration details:

```
# Load mod_jk module
# Specify the filename of the mod_jk lib
LoadModule jk_module modules/mod_jk.so
# Where to find workers.properties
JkWorkersFile conf.d/workers.properties
# Where to put jk logs
JkLogFile logs/mod jk.log
# Set the jk log level [debug/error/info]
JkLogLevel info
# Select the log format
JkLogStampFormat "[%a %b %d %H:%M:%S %Y]"
# JkOptions indicates to send SSL KEY SIZE
JkOptions +ForwardKeySize +ForwardURICompat -ForwardDirectories
# JkRequestLogFormat
JkRequestLogFormat "%w %V %T"
# Mount your applications
JkMount /application/* loadbalancer
# Add shared memory.
# This directive is present with 1.2.10 and
# later versions of mod_jk, and is needed for
# for load balancing to work properly
JkShmFile logs/jk.shm
# Add jkstatus for managing runtime data
<Location /jkstatus/>
  JkMount status
  Require ip 127.0.0.1
</Location>
```



IMPORTANT

Ensure that the **LoadModule** directive references the **mod_jk** native binary that you have installed.



The **JkMount** directive specifies the URLs that the Apache HTTP Server can forward to the **mod_jk** module. Based on the configuration for the **JkMount** directive, **mod_jk** forwards the received URL to the correct servlet containers.

To enable the Apache HTTP Server to serve static content (or PHP content) directly, and only use the load balancer for Java applications, the preceding configuration example specifies that the Apache HTTP Server sends only requests with the URL /application/* to the mod_jk load balancer.

Alternatively, you can configure the Apache HTTP Server to forward all URLs to **mod_ik** by specifying /* in the **JkMount** directive.

- 3. Optional: To use the **JkMountFile** directive to specify the configuration file for a mount point, perform the following steps:
 - a. Go to the JBCS_HOME/httpd/conf.d/ directory.
 - b. Create a file named uriworkermap.properties.
 - c. Specify the URL that you want to forward and the worker name. For example:
 - # Simple worker configuration file

Mount the Servlet context to the ajp13 worker /application=loadbalancer /application/*=loadbalancer



NOTE

The required syntax is in the format: / URL=WORKER_NAME

The preceding example configures **mod_jk** to forward requests for /application to the JBoss Web Server Tomcat back end.

- d. In the *JBCS_HOME*/httpd/conf.d/mod_jk.conf file, enter the following directive:
 - # Use external file for mount points.
 - # It will be checked for updates each 60 seconds.
 - # The format of the file is: /url=worker
 - # /examples/*=loadbalancer
 - JkMountFile conf.d/uriworkermap.properties
- 4. Optional: To enable Apache HTTP Server logging, perform either of the following steps:
 - Include %w in your JkRequestLogFormat directive, as shown in the preceding step about mod_jk.conf settings.
 - Log the name of the mod_jk worker that you want to use, by including %
 {JK WORKER NAME}n in your Apache HTTP Server LogFormat(s).

Additional resources

- The Apache Tomcat Connectors Web Server HowTo: mod_jk Directives
- Apache HTTP Server Documentation: Log Files

2.4. CONFIGURING WORKER NODES IN MOD_JK

You can configure multiple worker nodes to handle the requests that the Apache HTTP Server forwards to the servlet containers.

The example in this procedure shows how to define two **mod_jk** worker nodes in a weighted round-robin configuration that uses sticky sessions between two servlet containers.

Prerequisites

- You are familiar with the format of the workers.properties directives.
- You have configured the Apache HTTP Server to load mod_jk.

Procedure

- 1. Go to the **JBCS_HOME**/httpd/conf.d/ directory.
- 2. Create a file named workers.properties.
- 3. Enter the following configuration details:

```
# Define list of workers that will be used
# for mapping requests
worker.list=loadbalancer,status
# Define Node1
# modify the host as your host IP or DNS name.
worker.node1.port=8009
worker.node1.host=node1.mydomain.com
```

worker.node1.type=ajp13 worker.node1.ping_mode=A worker.node1.lbfactor=1

Define Node2
modify the host as your host IP or DNS name.
worker.node2.port=8009
worker.node2.host=node2.mydomain.com
worker.node2.type=ajp13
worker.node2.ping_mode=A
worker.node2.lbfactor=1

Load-balancing behavior worker.loadbalancer.type=lb worker.loadbalancer.balance_workers=node1,node2 worker.loadbalancer.sticky_session=1

Status worker for managing load balancer worker.status.type=status



In the preceding example, ensure that you replace **host**, **port**, and **secret** settings with values that are relevant for your environment.

2.5. CONFIGURING TOMCAT TO WORK WITH MOD_JK

Tomcat is configured to receive Apache JServ Protocol (AJP) traffic from **mod_jk** by default. However, before you can use a worker node with **mod_jk**, you must perform one additional configuration step.

The AJP connector is configured by default in the **JBCS_HOME**/tomcat<**VERSION>**/conf/server.xml file:

<Connector port="8009" protocol="AJP/1.3" redirectPort="8443" />

In addition to the AJP-enabled connector, you must also configure a unique value for the **jvmRoute** attribute in the Engine of each worker node:

Procedure

 To configure a unique value for the jvmRoute attribute in the Engine of each worker node, enter the following details:

<Engine name="Catalina" jvmRoute="node1" >



IMPORTANT

Ensure that the **jvmRoute** attribute value matches the worker name that is specified in the **workers.properties** file.

CHAPTER 3. LOAD BALANCING WITH THE JBOSS HTTP CONNECTOR (MOD_CLUSTER)

The **mod_cluster** connector is a reduced configuration, intelligent load-balancing solution for JBoss EAP and JBoss Web Server Tomcat. The **mod_cluster** module is based on technology originally developed by the JBoss **mod_cluster** community project.

3.1. JBOSS HTTP CONNECTOR (MOD_CLUSTER)

The **mod_cluster** module load-balances HTTP requests to JBoss EAP and JBoss Web Server Tomcat worker nodes. The **mod_cluster** module uses the Apache HTTP Server as the proxy server.

Key features of mod_cluster

The **mod_cluster** connector has several advantages over the **mod_jk** connector:

- When the mod_cluster module is enabled, the mod_cluster Management Protocol (MCMP) is an additional connection between the Tomcat servers and the Apache HTTP Server. The Tomcat servers use MCMP to transmit server-side load figures and lifecycle events back to the Apache HTTP Server, by using a custom set of HTTP methods.
- Dynamic configuration of Apache HTTP Server with mod_cluster allows Tomcat servers that
 have mod_cluster listeners to join the load-balancing arrangement without the need for
 manual configuration.
- Tomcat servers perform the load calculations rather than rely on the Apache HTTP Server. This makes load-balancing metrics more accurate than other connectors.
- The mod_cluster connector provides fine-grained application lifecycle control. Each Tomcat server forwards web application context lifecycle events to the Apache HTTP Server. These lifecycle events include informing the Apache HTTP Server to start or stop routing requests for a specific context. This prevents end users from seeing HTTP errors because of unavailable resources.
- You can use Apache JServ Protocol (AJP), Hypertext Transfer Protocol (HTTP), or Hypertext Transfer Protocol Secure (HTTPS) transports with **mod_cluster**.

Mod_cluster components

On the proxy server, **mod_cluster** consists of four Apache modules:

Component	Description
mod_cluster_slotmem.so	The Shared Memory Manager module shares real-time worker node information with multiple Apache HTTP Server processes.
mod_manager.so	The Cluster Manager module receives and acknowledges messages from worker nodes, including node registrations, node load data, and node application life-cycle events.

Component	Description
mod_proxy_cluster.so	The Proxy Balancer Module handles request routing to cluster nodes. The Proxy Balancer selects the appropriate destination node based on application location in the cluster, the current state of each of the cluster nodes, and the Session ID (if a request is part of an established session).
mod_advertise.so	The Proxy Advertisement Module broadcasts the existence of the proxy server via UDP multicast messages. The server advertisement messages contain the IP address and port number where the proxy server is listening for responses from worker nodes that want to join the loadbalancing cluster.

Additional resources

• Apache HTTP Server modules

3.2. MOD_CLUSTER CHARACTER LIMITS

The **mod_cluster** module uses shared memory to keep the nodes description. The shared memory is created at the startup of Apache HTTP Server, and the structure of each item is fixed.

When you define proxy server and worker node properties, ensure that you adhere to the following character limits:

Property	Maximum character limit	Description
Alias length	100 characters	Alias corresponds to the network name of the respective virtual host; the name is defined in the Host element.
Context length	40 characters	For example, if myapp.war is deployed in / myapp , / myapp is included in the context.
Balancer name length	40 characters	This is the balancer property in mbean .
JVMRoute string length	80 characters	JVMRoute in the < Engine > element.
Domain name length	20 characters	This is the domain property in mbean .
Hostname length for a node	64 characters	This is hostname address in the <connector></connector> element.

Property	Maximum character limit	Description
Port length for a node	7 characters	This is the port property in the <connector></connector> element. For example, 8009 is 4 characters.
Scheme length for a node	6 characters	This is the protocol of the connector. Possible values are http , https , and ajp .
Cookie name length	30 characters	This is the header cookie name for the session ID. The default value is JSESSIONID based on the org.apache.catalina.Globals.SESSION_COOKIE_NAME property.
Path name length	30 characters	This is the parameter name for the session ID. The default value is JSESSIONID based on the org.apache.catalina.Globals.SESSION_PARA METER_NAME property.
Session ID length	120 characters	A session ID is in the following type of format: BE81FAA969BF64C8EC2B6600457EAAAA.no de01

3.3. MOD_CLUSTER INSTALLATION

The **mod_cluster** module is included in the Apache HTTP Server part of a JBoss Core Services installation.

You can follow the procedures in the Red Hat JBoss Core Services Apache HTTP Server Installation Guide to download and install the Apache HTTP Server for your operating system.

Additional resources

• Red Hat JBoss Core Services Apache HTTP Server Installation Guide

3.4. APACHE HTTP SERVER LOAD-BALANCING CONFIGURATION WHEN USING MOD_CLUSTER

In JBoss Web Server 2.1 and higher, **mod_cluster** is configured correctly for Apache HTTP Server by default. For more information about setting a custom configuration, see Configuring a basic proxy server.



You can also use the Load Balancer Configuration tool on the Red Hat Customer Portal to generate optimal configuration templates quickly for **mod_cluster** and Tomcat worker nodes.

When you use the Load Balancer Configuration tool for JBoss Web Server 5.6, ensure that you select **2.4.x** as the Apache version, and select **Tomcat** as the back-end configuration.

Additional resources

- Configuring a basic proxy server
- Configuring a Tomcat worker node in **mod_cluster**

3.5. CONFIGURING A BASIC PROXY SERVER

You can configure the Apache HTTP Server to function as a proxy server that forwards requests and responses between web clients and back-end web servers. You must configure a proxy server listener to receive connection requests and responses from the back-end worker nodes. When you want to configure a load-balancing proxy server that uses **mod_cluster**, you must also configure a virtual host for the management channel.

Prerequisites

- You have installed the Apache HTTP Server and configured the mod_cluster modules for your installation. For more information, see the Red Hat JBoss Core Services Apache HTTP Server Installation Guide.
- The port that you specify for the proxy server listener must be open for incoming TCP connections.

Procedure

1. Open the **mod_cluster** configuration file.



NOTE

The **mod_cluster** configuration file is typically located in the **JBCS_HOME**/httpd/conf.d/mod_cluster.conf directory.

2. To create a **Listen** directive for the proxy server, enter the following line in the **mod_cluster.conf** file:

Listen IP_ADDRESS:PORT_NUMBER



In the preceding example, replace *IP_ADDRESS* with the address of the server network interface that the proxy server uses to communicate with the worker nodes, and replace *PORT_NUMBER* with the port that the proxy server listens on.

Ensure that the port is open for incoming TCP connections.

3. To create a virtual host, enter the following details in the **mod_cluster.conf** file:

```
<VirtualHost IP_ADDRESS:PORT_NUMBER>
  <Directory />
    Require ip IP_ADDRESS
  </Directory>
```

KeepAliveTimeout 60 MaxKeepAliveRequests 0

ManagerBalancerName mycluster AdvertiseFrequency 5 EnableMCPMReceive On

</VirtualHost>



NOTE

In the preceding example, replace *IP_ADDRESS* and *PORT_NUMBER* with the address of the server network interface and port number that you have specified for the **Listen** directive.

This address and port combination is only used for **mod_cluster** management messages. This address and port combination is not used for general traffic.

For more information about configuring **mod_jk** and starting the Apache HTTP Server service, see the Red Hat JBoss Core Services Apache HTTP Server Installation Guide .

Additional resources

Red Hat JBoss Core Services Apache HTTP Server Installation Guide

3.5.1. Disabling server advertisement

The proxy server uses UDP multicast to advertise itself. The **AdvertiseFrequency** directive instructs the server to send server advertisement messages every 10 seconds by default. Server advertisement messages contain the *IP_ADDRESS* and *PORT_NUMBER* that you specify in the **VirtualHost** definition. Worker nodes that are configured to respond to server advertisements use this information to register themselves with the proxy server. If you want to prevent worker nodes from registering with the proxy server, you can optionally disable server advertisement.



When UDP multicast is available between the proxy server and the worker nodes, server advertisement adds worker nodes without requiring further configuration on the proxy server. Server advertisement requires only minimal configuration on the worker nodes.

Prerequisites

• You have configured a basic proxy server.

Procedure

1. Open the **mod_cluster** configuration file.



NOTE

The **mod_cluster** configuration file is typically located in the **JBCS_HOME**/httpd/conf.d/mod_cluster.conf directory.

2. Add the following directive to the **VirtualHost** definition:





NOTE

If server advertisements are disabled, or UDP multicast is not available on the network between the proxy server and the worker nodes, you can configure worker nodes with a static list of proxy servers. In either case, you do not need to configure the proxy server with a list of worker nodes.

Additional resources

Configuring worker nodes with a static list of proxy servers

3.5.2. Logging worker node details

When you configure a load-balancing proxy server that uses **mod_cluster**, you can optionally configure the Apache HTTP Server to log details of each worker node that handles a request. Logging worker node details can be useful if you need to troubleshoot your load balancer.

Prerequisites

You have configured a basic proxy server.

Procedure

1. Open the **mod cluster** configuration file.



NOTE

The **mod_cluster** configuration file is typically located in the **JBCS_HOME**/httpd/conf.d/mod_cluster.conf directory.

2. Add the following details to your Apache HTTP Server **LogFormat** directive(s):

%{BALANCER NAME}e::

The name of the balancer that served the request.

%{BALANCER_WORKER_NAME}e::

The name of the worker node that served the request.

Additional resources

• Apache HTTP Server documentation about log files

3.6. CONFIGURING A TOMCAT WORKER NODE INMOD_CLUSTER

When you use **mod_cluster**, you can configure a Tomcat worker node as a JBoss Web Server Tomcat service that operates in non-clustered mode only. In this situation, only one load metric can be used at a time when calculating the load balance factor.



NOTE

JBoss Web Server Tomcat worker nodes support only a subset of **mod_cluster** functionality. Full **mod_cluster** functionality is available with JBoss EAP.

Prerequisites

- You have installed a supported instance of JBoss Web Server.
- You are familiar with the **mod_cluster** proxy and proxy discovery configuration parameters.

Procedure

 To add a listener to Tomcat, add the following Listener element below the other Listener elements in the JWS_HOME/tomcat<VERSION>/conf/server.xml file:

<Listener
className="org.jboss.modcluster.container.catalina.standalone.ModClusterListener"
advertise="true" stickySession="true" stickySessionForce="false"
stickySessionRemove="true" />

- To give the worker node a unique identity, edit the JWS_HOME/tomcat<VERSION>/conf/server.xml file, to add the jvmRoute attribute and value to the Engine element:
 - <Engine name="Catalina" defaultHost="localhost" jvmRoute="worker01">
- 3. To configure STATUS MCMP message frequency, modify the org.jboss.modcluster.container.catalina.status-frequency Java system property. For example:
 - -Dorg.jboss.modcluster.container.catalina.status-frequency=6



Tomcat worker nodes periodically send status messages that contain their current load status to the Apache HTTP Server balancer. The default frequency of these messages is 10 seconds. If you have hundreds of worker nodes, the **STATUS MCMP** messages can increase traffic congestion on your Apache HTTP Server network.

You can configure the **MCMP** message frequency by modifying the **org.jboss.modcluster.container.catalina.status-frequency** Java system property. By default, the property accepts values that are specified in seconds multiplied by 10. For example, setting the property to **1** means 10 seconds. In the preceding example, the property is set to **6**, which means 60 seconds.

- 4. Optional: To configure the firewall for proxy server advertisements, complete either of the following steps to open port **23364** for UDP connections on the worker node's firewall:
 - For Red Hat Enterprise Linux 7:

firewall-cmd --permanent --zone=public --add-port=23364/udp

• For Microsoft Windows using PowerShell

Start-Process "\$psHome\powershell.exe" -Verb Runas -ArgumentList '-command "NetSh Advfirewall firewall add rule name="UDP Port 23364" dir=in action=allow protocol=UDP localport=23364"'

Start-Process "\$psHome\powershell.exe" -Verb Runas -ArgumentList '-command "NetSh Advfirewall firewall add rule name="UDP Port 23364" dir=out action=allow protocol=UDP localport=23364"'



NOTE

When a proxy server uses **mod_cluster**, the proxy server can use UDP multicast to advertise itself. Most operating system firewalls block the server advertisement feature by default. To enable server advertisement and receive these multicast messages, you can open port **23364** for UDP connections on the worker node's firewall, as shown in the preceding examples.



IMPORTANT

Red Hat Enterprise Linux 6 is no longer supported and subsequently was removed from the documentation.

3.7. CONFIGURING A WORKER NODE TO OPERATE WITH A STATIC LIST OF PROXY SERVERS

Server advertisement allows worker nodes to discover and register themselves with proxy servers dynamically. If UDP multicast is not available or server advertisement is disabled, you must configure JBoss Web Server worker nodes with a static list of proxy server addresses and ports.

Prerequisites

- You have configured a JBoss Web Server worker node.
- You are familiar with the proxy configuration parameters for Tomcat.

Procedure

- 1. Open the JWS_HOME/tomcat<VERSION>/conf/server.xml file.
- To define a mod_cluster listener and disable dynamic proxy discovery, add or change the Listener element for ModClusterListener.
 For example:

<Listener

className="org.jboss.modcluster.container.catalina.standalone.ModClusterListener" advertise="false" stickySession="true" stickySessionForce="false" stickySessionRemove="true"/>



NOTE

Ensure that you set the **advertise** property to **false**.

3. To create a static proxy server list, update the **proxyList** property by adding a commaseparated list of proxies in the following format: **IP_ADDRESS: PORT,IP_ADDRESS: PORT**For example:

<Listener

className="org.jboss.modcluster.container.catalina.standalone.ModClusterListener" advertise="false" stickySession="true" stickySessionForce="false" stickySessionRemove="true" proxyList="10.33.144.3:6666,10.33.144.1:6666"/>

CHAPTER 4. SECURING CONNECTIONS BY USING OCSP

Online Certificate Status Protocol (OCSP) is a technology that allows web browsers and web servers to communicate over a secured connection. The encrypted data is sent from one side and decrypted by the other side before processing. The web browser and the web server both encrypt and decrypt the data.

4.1. ONLINE CERTIFICATE STATUS PROTOCOL

When a web browser and a web server communicate over a secured connection, the server presents a set of credentials in the form of a certificate. The browser then validates the certificate and sends a request for certificate status information. The server responds with a certificate status of current, expired, or unknown.

The certificate contains the following types of information:

- Syntax for communication
- Control information such as start time, end time, and address information to access an Online Certificate Status Protocol (OCSP) responder.

The web server uses an OCSP responder to check the certificate status. You can configure the web server to use the OCSP responder that is listed in the certificate or another OCSP responder. OCSP allows a grace period for expired certificates, which allows access to a server for a limited time before renewing the certificate.

OCSP overcomes limitations of the older Certificate Revocation List (CRL) method.

Additional resources

• Red Hat Certificate System Planning, Installation, and Deployment Guide.

4.2. CONFIGURING THE APACHE HTTP SERVER FOR SSL CONNECTIONS

You can configure the Apache HTTP Server to support SSL connections, by installing the **mod_ssl** package and specifying configuration settings in the **ssl.conf** file.

Prerequisites

- You have generated an SSL certificate and private key.
- You know the location of the SSL certificate and private key file.
- You have obtained the Common Name (CN) that is associated with the SSL certificate.

Procedure

- 1. To install **mod_ssl**, enter the following command:
 - # yum install jbcs-httpd24-mod_ssl
- 2. To specify SSL configuration settings:

- a. Open the JBCS_HOME/httpd/conf.d/ssl.conf file.
- b. Enter details for the **ServerName**, **SSLCertificateFile**, and **SSLCertificateKeyFile**. For example:

<VirtualHost _default_:443>
ServerName www.example.com:443
SSLCertificateFile /opt/rh/jbcs-httpd24/root/etc/pki/tls/certs/localhost.crt
SSLCertificateKeyFile /opt/rh/jbcs-httpd24/root/etc/pki/tls/private/localhost.key



NOTE

- The **ServerName** must match the Common Name (CN) that is associated with the SSL certificate. If the **ServerName** does not match the CN, client browsers display domain name mismatch errors.
- The **SSLCertificateFile** specifies the path to the SSL certificate file.
- The **SSLCertificateKeyFile** specifies the path to the private key file that is associated with the SSL certificate.
- 3. Verify that the **Listen** directive matches the hostname or IP address for the **httpd** service for your deployment.
- 4. To restart the Apache HTTP Server, enter the following command:

service jbcs-httpd24-httpd restart

4.3. USING OCSP WITH THE APACHE HTTP SERVER

You can use the Online Certificate Status Protocol (OCSP) for secure connections with the Apache HTTP Server.

Prerequisites

• You have configured Apache HTTP Server for SSL connections.

Procedure

1. Configure a certificate authority.



Ensure that your CA can issue OCSP certificates. The CA must be able to append the following attributes to the certificate:

```
[ usr_cert ]
...
authorityInfoAccess=OCSP;URI:http://<HOST>:<PORT>
...
[ v3_OCSP ]
basicConstraints = CA:FALSE
keyUsage = nonRepudiation, digitalSignature, keyEncipherment
extendedKeyUsage = OCSP Signing
```

In the preceding example, replace **HOST** and **PORT** with the details of the OCSP responder that you will configure.

2. Configure an OCSP responder.

Additional resources

- Managing certificates and certificate authorities.
- Configuring OCSP responders.

4.4. CONFIGURING THE APACHE HTTP SERVER TO VALIDATE OCSP CERTIFICATES

You can configure the Apache HTTP Server to validate OCSP certificates, by defining OCSP settings in the **ssl_conf** file.

Prerequisites

- You have configured a Certificate Authority (CA).
- You have configured an OCSP Responder.

Procedure

- 1. Open the *JBCS_HOME*/httpd/conf.d/ssl.conf file.
- 2. Specify the appropriate OCSP configuration details for your deployment. For example:

Require valid client certificates (mutual auth)
SSLVerifyClient require
SSLVerifyDepth 3
Enable OCSP
SSLOCSPEnable on
SSLOCSPDefaultResponder http://<HOST>:<PORT>
SSLOCSPOverrideResponder on



The preceding example shows how to enable OCSP validation of client certificates. In the preceding example, replace **<HOST>** and **<PORT>** with the IP address and port of the default OCSP Responder.

4.5. VERIFYING THE OCSP CONFIGURATION FOR THE APACHE HTTP SERVER

You can use the OpenSSL command-line tool to verify the OCSP configuration for the Apache HTTP Server.

Procedure

• On the command line, enter the **openssI** command in the following format:

openssl ocsp -issuer cacert.crt -cert client.cert -url http://HOST:PORT -CA ocsp_ca.cert - VAfile ocsp.cert

In the preceding command, ensure that you specify the following details:

- Use the **-issuer** option to specify the CA certificate.
- Use the **-cert** option to specify the client certificate that you want to verify.
- Use the **-url** option to specify the HTTP server validating Certificate (OCSP).
- Use the **-CA** option to specify the is the CA certificate for verifying the Apache HTTP Server server certificate.
- Use the **-VAfile** option to specify the OCSP responder certificate.

CHAPTER 5. CONFIGURATION EXAMPLE FOR LOAD-BALANCING WITH MOD_CLUSTER

You can configure JBoss Core Services to use the **mod_cluster** connector for load-balancing in a Red Hat Enterprise Linux system.

When you want to configure a load-balancing solution that uses **mod_cluster**, you must perform the following tasks:

- 1. Set up JBoss Core Services as a proxy server.
- 2. Configure a Tomcat worker node.
- 3. Define iptables firewall rules.

5.1. SETTING UP JBOSS CORE SERVICES AS A PROXY SERVER

When you configure JBoss Core Services to use **mod_cluster**, you must set up JBoss Core Services as a proxy server by specifying configuration details in the **mod_cluster.conf** file.

Procedure

- 1. Go to the **JBCS_HOME**/httpd/conf.d/ directory.
- 2. Create a file named **mod_cluster.conf**.
- 3. Enter the following configuration details:

LoadModule proxy_cluster_module modules/mod_proxy_cluster.so LoadModule cluster_slotmem_module modules/mod_cluster_slotmem.so LoadModule manager_module modules/mod_manager.so LoadModule advertise_module modules/mod_advertise.so

MemManagerFile cache/mod_cluster

```
<IfModule manager_module>
Listen 6666
<VirtualHost *:6666>
<Directory />
Require ip 127.0.0.1
</Directory>
ServerAdvertise on
EnableMCPMReceive
<Location /mod_cluster_manager>
SetHandler mod_cluster-manager
Require ip 127.0.0.1
```



NOTE

</Location> </VirtualHost> </IfModule>

The preceding example shows how to set up JBoss Core Services as a proxy server that is listening on **localhost**.

5.2. CONFIGURING A TOMCAT WORKER NODE

When you configure JBoss Core Services to use **mod_cluster**, you must configure a Tomcat worker node by adding a **Listener** element to the **server.xml** file.

Prerequisites

• You have set up JBoss Core Services as a proxy server.

Procedure

- 1. Open the JWS_HOME/tomcat<VERSION>/conf/server.xml file.
- 2. Add the following **Listener** element:

<Listener
className="org.jboss.modcluster.container.catalina.standalone.ModClusterListener"
advertise="true"/>

5.3. DEFINING IPTABLES FIREWALL RULES EXAMPLE

When you configure JBoss Core Services to use **mod_cluster**, you must define firewall rules by using **iptables**.

Prerequisites

• You have configured a Tomcat worker node.

Procedure

• Use **iptables** to define a set of firewall rules. For example:

/sbin/iptables -I INPUT 5 -p udp -d 224.0.1.0/24 -j ACCEPT -m comment --comment "mod_cluster traffic"

/sbin/iptables -I INPUT 6 -p udp -d 224.0.0.0/4 -j ACCEPT -m comment --comment "JBoss Cluster traffic"

/sbin/iptables -I INPUT 9 -p udp -s 192.168.1.0/24 -j ACCEPT -m comment --comment "cluster subnet for inter-node communication"

/sbin/iptables -I INPUT 10 -p tcp -s 192.168.1.0/24 -j ACCEPT -m comment --comment "cluster subnet for inter-node communication"

/etc/init.d/iptables save



NOTE

The preceding example shows to define firewall rules for a cluster node on the **192.168.1.0/24** subnet.

CHAPTER 6. CONFIGURATION EXAMPLE FOR KERBEROS AUTHENTICATION WITH MOD AUTH KERB

You can configure Kerberos authentication with the JBoss Core Services Apache HTTP Server and the **mod_auth_kerb** module on Red Hat Enterprise Linux.

When you want to configure Kerberos authentication, you must perform the following tasks:

- 1. Configure the Kerberos client.
- 2. Configure mod_auth_kerb.
- 3. Test the Kerberos authentication.

6.1. PREREQUISITES

- You have installed the **curl** command-line utility with Generic Security Services (GSS)-negotiated support.
- You have configured and run a Kerberos or LDAP server, such as ApacheDS, on the same host as JBoss Core Services.
- If you are using an LDAP server, you have created LDAP users called **krbtgt**, **Idap**, **HTTP**, and a test LDAP user called **hnelson**.
 - To create the **krbtgt** user, enter the following details:

dn: uid=krbtgt,ou=Users,dc=example,dc=com

objectClass: top objectClass: person

objectClass: inetOrgPerson objectClass: krb5principal objectClass: krb5kdcentry

cn: KDC Service sn: Service uid: krbtgt

userPassword: secret

krb5PrincipalName: krbtgt/EXAMPLE.COM@EXAMPLE.COM

krb5KeyVersionNumber: 0

• To create the **Idap** user, enter the following details:

dn: uid=ldap,ou=Users,dc=example,dc=com

objectClass: top objectClass: person

objectClass: inetOrgPerson objectClass: krb5principal objectClass: krb5kdcentry

cn: LDAP sn: Service uid: Idap

userPassword: randall

krb5PrincipalName: ldap/localhost@EXAMPLE.COM

krb5KeyVersionNumber: 0

• To create the **HTTP** user, enter the following details:

dn: uid=HTTP,ou=Users,dc=example,dc=com

objectClass: top objectClass: person

objectClass: inetOrgPerson objectClass: krb5principal objectClass: krb5kdcentry

cn: HTTP sn: Service uid: HTTP

userPassword: secretpwd

krb5PrincipalName: HTTP/localhost@EXAMPLE.COM

krb5KeyVersionNumber: 0

• To create the test user, **hnelson**, enter the following details:

dn: uid=hnelson,ou=Users,dc=example,dc=com

objectClass: top objectClass: person

objectClass: inetOrgPerson objectClass: krb5principal objectClass: krb5kdcentry

cn: Horatio Nelson

sn: Nelson uid: hnelson

userPassword: secret

krb5PrincipalName: hnelson@EXAMPLE.COM

krb5KeyVersionNumber: 0

6.2. CONFIGURING THE KERBEROS CLIENT

When you configure Kerberos authentication, you must configure the Kerberos client by performing the following steps:

- 1. Specify configuration settings in the **krb5.conf** file.
- 2. Create a key tab in the **JBCS_HOME**/httpd/conf file.
- 3. Assign permissions to the key tab.
- 4. Ensure that **localhost** is included in the /etc/hosts file.

Prerequisites

• You are compliant with all prerequisites for configuring Kerberos authentication.

Procedure

- 1. To specify configuration settings in the **krb5.conf** file:
 - a. Go to the /etc directory.
 - b. Create a file named krb5.conf.

c. Enter the following configuration details:

```
[logging]
 default = FILE:/var/log/krb5libs.log
 kdc = FILE:/var/log/krb5kdc.log
 admin server = FILE:/var/log/kadmind.log
[libdefaults]
 default_realm = EXAMPLE.COM
 default tgs enctypes = des-cbc-md5,des3-cbc-sha1-kd
 default_tkt_enctypes = des-cbc-md5,des3-cbc-sha1-kd
 dns_lookup_realm = false
 dns_lookup_kdc = false
 allow_weak_crypto = yes
 ticket lifetime = 24h
 renew lifetime = 7d
 forwardable = yes
[realms]
 EXAMPLE.COM = {
  kdc = localhost:60088
  admin_server = localhost:60088
[domain_realm]
 .example.com = EXAMPLE.COM
 example.com = EXAMPLE.COM
```

- 2. To create a key tab:
 - a. Open the **JBCS_HOME**/httpd/conf file.
 - b. Enter the following details:



IMPORTANT

Environment variables are not expanded within the **ktutil** prompt. You must substitute the full path for the **JBCS_HOME** variable.

3. To apply the correct group and permissions to the key tab, enter the following commands as the root user:

chgrp apache JBCS_HOME/httpd/conf/krb5.keytab # chmod 640 JBCS_HOME/httpd/conf/krb5.keytab

4. Ensure that the following host configuration is included in the /etc/hosts file:

127.0.0.1 localhost

6.3. CONFIGURING MOD_AUTH_KERB

When you configure Kerberos authentication, you must configure **mod_auth_kerb** by specifying settings in the **auth_kerb.conf** file.

Prerequisites

• You have configured the Kerberos client.

Procedure

- 1. Go to the **JBCS HOME/httpd/conf.d/** directory.
- 2. Create a file named auth kerb.conf.
- 3. Enter the following configuration details:

```
# The mod_auth_kerb module implements Kerberos authentication over HTTP, following the "Negotiate" protocol.

# 
# The LoadModule statement is done in conf.d/10-auth_kerb.conf
# LoadModule auth_kerb_module modules/mod_auth_kerb.so

<Location /kerberostest>
AuthType Kerberos
```

AuthType Kerberos
AuthName "Kerberos Login"
KrbMethodNegotiate On
KrbMethodK5Passwd Off
KrbAuthRealms EXAMPLE.COM
KrbServiceName HTTP
Krb5KeyTab \$JBCS_HOME/httpd/krb5.keytab
require valid-user
</Location>



IMPORTANT

Environment variables are not expanded within the configuration files. In the preceding example, ensure that you substitute the full path for the **JBCS_HOME** variable.

6.4. TESTING THE KERBEROS AUTHENTICATION

When you configure Kerberos authentication, you can use a test page to test the Kerberos authentication.

Prerequisites

• You have configured mod_auth_kerb.

Procedure

- 1. To create a test page, perform the following steps:
 - a. Go to the **JBCS_HOME**/httpd/www/html/kerberostest directory.
 - b. Create a test page named auth_kerb_page.html.
 - c. Enter the following details:

```
<html>
<body>
<h1>mod_auth_kerb successfully authenticated!</h1>
</body>
</html>
```

- 2. Optional: In the JBCS_HOME/httpd/conf/httpd.conf file, set the log level to debugging.
- 3. Start the Apache HTTP Server. For more information, see the Red Hat JBoss Core Services Apache HTTP Server Installation Guide.
- 4. To initiate Kerberos authentication for the test user, **hnelson**, enter the following command:
 - \$ kinit hnelson
- 5. To view the details for the test user, **hnelson**, enter the following command:
 - \$ klist

The **klist** command produces the following type of output:

```
Ticket cache: FILE:/tmp/krb5cc_18602
Default principal: hnelson@EXAMPLE.COM

Valid starting Expires Service principal
06/03/13 14:21:13 06/04/13 14:21:13 krbtgt/EXAMPLE.COM@EXAMPLE.COM
renew until 06/10/13 14:21:13
```

Verification

• To test Kerberos authentication, enter the following command:

```
$ curl --negotiate -u : http://localhost/kerberostest/auth kerb page.html
```

If Kerberos authentication is working correctly, the **curl** command produces the following output:

```
<html>
<body>
    <h1>mod_auth_kerb successfully authenticated!</h1>
</body>
</html>
```

6.5. ADDITIONAL RESOURCES (OR NEXT STEPS)

• Kerberos Module for Apache website.

APPENDIX A. APACHE HTTP SERVER PROXY MODULES

This section contains expanded definitions of the Apache HTTP Server proxy modules that **mod_cluster** includes.

A.1. MOD MANAGER MODULE AND DIRECTIVES

The cluster manager module, **mod_manager**, receives and acknowledges messages from nodes, including worker node registrations, worker node load data, and worker node application life cycle events.

LoadModule manager_module modules/mod_manager.so

Configurable directives for mod_manager

Configurable directives in the **<VirtualHost>** element are as follows:

EnableMCPMReceive

Allows the **VirtualHost** to receive the mod_cluster Protocol Message **(MCPM)** from nodes. Add one **EnableMCPMReceive** directive to the Apache HTTP Server configuration to allow **mod_cluster** to operate correctly. **EnableMCPMReceive** must be added in the **VirtualHost** configuration at the location where **advertise** is configured.

MaxMCMPMaxMessSize

Defines the maximum size of mod_cluster Management Protocol (MCMP) messages. The default value is calculated from other **Max** directives. The minimum value is **1024**.

AllowDisplay

Toggles the additional display on the **mod_cluster-manager** main page. The default value is **off**, which causes only version information to display on the **mod_cluster-manager** main page.

AllowCmd

Toggles permissions for commands using **mod_cluster-manager** URL. The default value is **on**, which allows commands.

ReduceDisplay

Toggles the reduction of information displayed on the **mod_cluster-manager** page. Reducing the information allows more nodes to display on the page. The default value is **off**, which allows all the available information to display.

MemManagerFile

Defines the location for the files in which mod_manager stores configuration details. mod_manager also uses this location for generated keys for shared memory and lock files. **This must be an absolute path name**. It is recommended that this path be on a local drive, and not an NFS share. The default value is /logs/.

Maxcontext

The maximum number of contexts mod_cluster will use. The default value is 100.

Maxnode

The maximum number of worker nodes mod_cluster will use. The default value is 20.

Maxhost

The maximum number of hosts (aliases) mod_cluster will use. This is also the maximum number of load balancers. The default value is **20**.

Maxsessionid

The maximum number of active session identifiers stored. A session is considered inactive when no information is received from that session for five minutes. This is used for demonstration and debugging purposes only. The default value is **0**, which disables this logic.

ManagerBalancerName

The name of the load balancer to use when the worker node does not provide a load balancer name. The default value is **mycluster**.

PersistSlots

When set to on, nodes, aliases, and contexts are persisted in files. The default value is off.

CheckNonce

When set to **on**, session identifiers are checked to ensure that they are unique and have not occurred before. The default is **on**.



NOTE

Setting this directive to off can leave your server vulnerable to replay attacks.

SetHandler mod_cluster-manager

Defines a handler to display information about worker nodes in the cluster. This is defined in the **Location** element:

<Location \$LOCATION>
 SetHandler mod_cluster-manager
 Require ip 127.0.0.1
</Location>

When accessing the **\$LOCATION** defined in the **Location** element in your browser, you will see something like the following. (In this case, **\$LOCATION** was also defined as **mod_cluster-handler**.)

Transferred corresponds to the POST data sent to the worker node. **Connected** corresponds to the number of requests that had been processed when this status page was requested. **Sessions** corresponds to the number of active sessions. This field is not present when **Maxsessionid** is **0**.

A.2. MOD_PROXY_CLUSTER MODULE AND DIRECTIVES

The Proxy Balancer Module, **mod_proxy_cluster**, handles the routing of requests to cluster nodes. The Proxy Balancer selects the appropriate node to forward the request to based on the application location in the cluster, the current state of each of the cluster nodes, and the Session ID (if a request is part of an established session).

LoadModule proxy_cluster_module modules/mod_proxy_cluster.so

Configurable directives for mod_proxy_cluster

You can also configure the following directives in the **<VirtualHost>** element to change the load balancing behavior.

CreateBalancers

Defines how load balancers are created in the Apache HTTP Server virtual hosts. The following values are valid in **CreateBalancers**:

• 0: Create load balancers in all virtual hosts defined in Apache HTTP Server. Remember to

configure the load balancers in the **ProxyPass** directive.

- 1: Do not create balancers. When using this value, you must also define the load balancer name in **ProxyPass** or **ProxyPassMatch**.
- 2: Create only the main server. This is the default value for **CreateBalancers**.

UseAlias

Defines whether to check that the defined **Alias** corresponds to the **ServerName**. The following values are valid for **UseAlias**:

- **0**: Ignore alias information from worker nodes. This is the default value for **UseAlias**.
- 1: Verify that the defined alias corresponds to a worker node's server name.

LBstatusRecalTime

Defines the interval in seconds between the proxy calculating the status of a worker node. The default interval is **5** seconds.

ProxyPassMatch; ProxyPass

ProxyPass maps remote servers into the local server namespace. If the local server has an address such as **http://local.com/**, the following **ProxyPass** directive converts a local request for **http://local.com/requested/file1** into a proxy request for **http://worker.local.com/file1**.

ProxyPass /requested/ http://worker.local.com/

ProxyPassMatch uses regular expressions to match local paths to which the proxied URL should apply.

For either directive, ! indicates that a specified path is local, and a request for that path should not be routed to a remote server. For example, the following directive specifies that **gif** files should be served locally.

ProxyPassMatch ^(/.*\.gif)\$!

A.3. MOD_ADVERTISE MODULE AND DIRECTIVES

The Proxy Advertisement Module, **mod_advertise**, broadcasts the existence of the proxy server via UDP multicast messages. The server advertisement messages contain the IP address and port number where the proxy is listening for responses from nodes that wish to join the load-balancing cluster.

The **mod_advertise** module must be defined along with the **mod_manager** module in the **VirtualHost** element. In the following example, the identifier for the **mod_advertise** module is **advertise_module**.

LoadModule advertise_module modules/mod_advertise.so

Configurable directives for mod_advertise

The **mod_advertise** module is configurable by using the following directives:

ServerAdvertise

Defines how the advertising mechanism is used.

The default value is Off. When set to Off, the proxy does not advertise its location.

When set to **On**, the advertising mechanism is used to tell worker nodes to send status information to this proxy. You can also specify a host name and port with the following syntax: **ServerAdvertise On http://HOSTNAME:PORT/**. This is only required when using a name-based virtual host, or when a virtual host is not defined.

AdvertiseGroup

Defines the multicast address to advertise on. The syntax is **AdvertiseGroup ADDRESS:PORT**, where **ADDRESS** must correspond to **AdvertiseGroupAddress**, and **PORT** must correspond to **AdvertisePort** in your worker nodes.

If your worker node is JBoss EAP-based, and the **-u** switch is used at startup, the default **AdvertiseGroupAddress** is the value passed via the **-u** switch.

The default value is **224.0.1.105:23364**. If a port is not specified, the port defaults to **23364**.

AdvertiseFrequency

The interval (in seconds) between multicast messages advertising the IP address and port. The default value is **10**.

AdvertiseSecurityKey

Defines a string that is used to identify **mod_cluster** in JBoss Web Server. By default this directive is not set and no information is sent.

AdvertiseManagerUrl

Defines the URL that the worker node should use to send information to the proxy server. By default this directive is not set and no information is sent.

AdvertiseBindAddress

Defines the address and port over which to send multicast messages. The syntax is **AdvertiseBindAddress ADDRESS:PORT**. This allows an address to be specified on machines with multiple IP addresses. The default value is **0.0.0.0:23364**.

A.4. MOD PROXY MODULE AND DIRECTIVES

The **mod_proxy** module is a standard Apache HTTP Server module that enables the server to act as a proxy for data that is transferred over the Apache JServ Protocol (AJP), FTP, CONNECT (for SSL), and HTTP protocols. The **mod_proxy** module does not require additional configuration. The identifier for the **mod_proxy** module is **proxy module**.

The configurable directives for **mod_proxy**, such as **ProxylOBufferSize**, are used to configure the **mod_cluster** module.

A.5. MOD_PROXY_AJP MODULE AND DIRECTIVES

The **mod_proxy_ajp** module is a standard Apache HTTP Server module that provides support for Apache JServ Protocol (AJP) proxying. The **mod_proxy** module is also required if you want to use **mod_proxy_ajp**.

A.6. MOD CLUSTER SLOTMEM MODULE AND DIRECTIVES

The **mod_cluster_slotmem** module s a shared memory provider for creating and accessing a shared memory segment in which the data sets are organized in "slots".

The **mod_cluster_slotmem** module does not require any configuration directives.

APPENDIX B. WORKERS, PROPERTIES FILE

Apache HTTP Server worker nodes are servlet containers that are mapped to the **mod_jk** load balancer. The worker nodes are defined in **JBCS_HOME**/httpd/conf/workers.properties. This file specifies where the different servlet containers are located, and how calls should be load-balanced across them.

B.1. WORKERS.PROPERTIES OVERVIEW

The workers.properties file contains a global properties section and a worker properties section.

Global Properties

This section contains directives that apply to all workers.

Worker Properties

This section contains directives that apply to each individual worker.

Each node is defined using the worker properties naming convention. The worker name can only contain lowercase letters, uppercase letters, numbers, and specific special characters (_, /).

The structure of a worker property is worker. WORKER_NAME.DIRECTIVE.

worker

The constant prefix for all worker properties.

WORKER NAME

The arbitrary name given to the worker. For example: node1, node_01, Node_1.

DIRECTIVE

The specific directive required.

B.2. WORKERS.PROPERTIES DIRECTIVES

The **workers.properties** file directives are divided into global, mandatory, connection, and load-balancing classifications.

Global directives for workers.properties

worker.list

Specifies the list of worker names that **mod_jk** uses. The workers in this list are available to map requests to.



NOTE

A single node configuration which is not managed by a load balancer must be set to **worker.list=***WORKER_NAME*.

Mandatory directives for workers.properties

type

Specifies the type of worker, which determines the directives applicable to the worker. The default value is **ajp13**, which is the preferred worker type to select for communication between the web server and Apache HTTP Server.

Other values include **lb** and **status**.

For detailed information about AJPv13, see the Apache Tomcat Connector - AJP Protocol Reference.

Connection directives for workers.properties

host

The hostname or IP address of the worker. The worker node must support the ajp13 protocol stack. The default value is **localhost**.

You can specify the **port** directive as part of the host directive by appending the port number after the host name or IP address. For example: **worker.node1.host=192.168.2.1:8009** or **worker.node1.host=node1.example.com:8009**.

port

The port number of the remote server instance listening for the defined protocol requests. The default value is **8009**, which is the default listen port for AJPv13 workers.

ping_mode

Specifies the conditions under which connections are probed for their current network health. The probe uses an empty AJPv13 packet for the **CPing**, and expects a **CPong** in return, within a specified timeout.

You specify the conditions by using a combination of the directive flags. The flags are not commaseparated. For example, a correct directive flag set is **worker.node1.ping mode=Cl**.

C (connect)

Specifies the connection is probed once after connecting to the server. You specify the timeout using the **connect_timeout** directive, otherwise the value for **ping_timeout** is used.

P (prepost)

Specifies that the connection is probed before sending each request to the server. You specify the timeout using the **prepost_timeout** directive, otherwise the value for **ping_timeout** is used.

I (interval)

Specifies that the connection is probed during regular internal maintenance cycles. You specify the idle time between each interval using the **connection_ping_interval** directive, otherwise the value for **ping_timeout** is used.

A (all)

The most common setting, which specifies that all directive flags are applied. For information about the ***_timeout** advanced directives, see the Apache Tomcat Connector - Reference Guide.

ping_timeout

Specifies the time to wait for **CPong** answers to a **CPing** connection probe (see **ping_mode**). The default value is **10000** (milliseconds).

Load balancing directives for workers.properties

Ibfactor

Specifies the load-balancing factor for an individual worker, and is only specified for a member worker of a load balancer.

This directive defines the relative amount of HTTP request load distributed to the worker compared to other workers in the cluster.

A common example where this directive applies is where you want to differentiate servers with greater processing power than others in the cluster. For example, if you require a worker to take three times the load than other workers, specify **worker**. **WORKER_NAME**.**Ibfactor=3**.

balance_workers

Specifies the worker nodes that the load balancer must manage. The directive can be used multiple times for the same load balancer, and consists of a comma-separated list of worker names as specified in the **workers.properties** file.

sticky_session

Specifies whether requests for workers with SESSION IDs are routed back to the same worker. The default is $\mathbf{0}$ (false). When set to $\mathbf{1}$ (true), load balancer persistence is enabled.

For example, if you specify **worker.loadbalancer.sticky_session=0**, each request is load balanced between each node in the cluster. In other words, different requests for the same session can go to different servers based on server load.

If you specify **worker.loadbalancer.sticky_session=1**, each session is persisted (locked) to one server until the session is terminated, providing that server is available.

Additional resources

• Apache Tomcat Connectors - Reference Guide .

APPENDIX C. WORKER NODE CONFIGURATION

Configuration values are sent to proxies under the following conditions:

- During server startup
- When a proxy is detected through the advertise mechanism
- During error recovery when a proxy's configuration is reset

Table C.1. Proxy Configuration Values for Tomcat

Value	Default	Description
stickySession	true	Specifies whether subsequent requests for a given session should be routed to the same node, if possible.
stickySessionRemove	false	Specifies whether the Apache HTTP Server proxy should remove session stickiness if the balancer is unable to route a request to the node to which it is stuck. This property is ignored if stickySession is false .
stickySessionForce	true	Specifies whether the Apache HTTP Server proxy should return an error if the balancer is unable to route a request to the node to which it is stuck. This property is ignored if stickySession is false .
workerTimeout	-1	Specifies the number of seconds to wait for a worker to become available to handle a request. When all the workers of a balancer are unusable, mod_cluster will retry after a while (workerTimeout/100) to find an usable worker. A value of -1 indicates that the Apache HTTP Server will not wait for a worker to be available and will return an error if no workers are available.
maxAttempts	1	Specifies the number of times the Apache HTTP Server proxy will attempt to send a given request to a worker before aborting. The minimum value is 1 : try once before aborting.
flushPackets	false	Specifies whether packet flushing is enabled or disabled.
flushWait	-1	Specifies the time to wait before flushing packets. A value of -1 means wait forever.
ping	10	Time to wait (in seconds) for a pong answer to a ping.

Value	Default	Description
smax		Specifies the soft maximum idle connection count. The maximum value is determined by the Apache HTTP Server thread configuration (ThreadsPerChild or 1).
ttl	60	Specifies the time (in seconds) idle connections persist, above the smax threshold.
nodeTimeout	-1	Specifies the time (in seconds) mod_cluster waits for the back-end server response before returning an error. mod_cluster always uses a cping/cpong before forwarding a request. The connectiontimeout value used by mod_cluster is the ping value.
balancer	mycluster	Specifies the name of the load-balancer.
loadBalancingGroup		Specifies the load balancing among jvmRoutes within the same load balancing group. A loadBalancingGroup is conceptually equivalent to a mod_jk domain directive.

APPENDIX D. MOD_CLUSTER PROXY AND PROXY DISCOVERY CONFIGURATION ATTRIBUTES

The following tables contain attributes and information about **mod_cluster** proxy and proxy discovery configuration attributes.

Table D.1. Proxy discovery configuration attributes formod_cluster

Attribute	Property	Default Value
proxy-list	proxyList	
proxy-url	proxyURL	
advertise	advertise	true
advertise-security-key	advertiseSecurityKey	
excluded-contexts	excludedContexts	
auto-enable-contexts	autoEnableContexts	true
stop-context-timeout	stopContextTimeout	10 seconds (in seconds)
socket-timeout	nodeTimeout	20 seconds (in milliseconds)



NOTE

When **nodeTimeout** is not defined, the **ProxyTimeout** directive, **Proxy**, is used. If **ProxyTimeout** is not defined, the server timeout (**Timeout**) is used (120 seconds by default in the JBCS httpd.conf). **nodeTimeout**, **ProxyTimeout**, and **Timeout** are set at the socket level.

Table D.2. Proxy configuration attributes formod_cluster

Attribute	Property	Default Value
sticky-session	stickySession	true
sticky-session-remove	stickySessionRemove	false
sticky-session-force	stickySessionForce	true
node-timeout	workerTimeout	-1
max-attempts	maxAttempts	1
flush-packets	flushPackets	false

Attribute Property Default Value	Attribute	Property	Default Value
----------------------------------	-----------	----------	---------------

flush-wait	flushWait	-1
ping	ping	10 (seconds)
smax	smax	-1 (uses the default value)
ttl	ttl	-1 (uses the default value)
domain	loadBalancingGroup	
load-balancing-group	IoadBalancingGroup	

APPENDIX E. LOAD CONFIGURATION FOR TOMCAT

You can configure the following additional properties for load metrics when you want to use **mod_cluster** with Apache Tomcat.

Table E.1. Load Configuration for Tomcat

Attribute	Default Value	Description
loadMetricClass	org.jboss.modcluster.load.metric.i mpl.BusyConnectorsLoadMetric	The class name of an object that is implementing org.jboss.load.metric.LoadMetric.
loadMetricCapacit y	1	The capacity of the load metric defined via the loadMetricClass property.
loadHistory	9	The number of historic load values that must be considered in the load balance factor computation.
loadDecayFactor	2	The factor by which the historic load values decrease in significance.