



# Red Hat OpenShift Data Foundation 4.9

## Deploying OpenShift Data Foundation using Microsoft Azure and Azure Red Hat OpenShift

Instructions on deploying OpenShift Data Foundation using Microsoft Azure and  
Azure Red Hat OpenShift



# Red Hat OpenShift Data Foundation 4.9 Deploying OpenShift Data Foundation using Microsoft Azure and Azure Red Hat OpenShift

---

Instructions on deploying OpenShift Data Foundation using Microsoft Azure and Azure Red Hat OpenShift

## Legal Notice

Copyright © 2022 Red Hat, Inc.

The text of and illustrations in this document are licensed by Red Hat under a Creative Commons Attribution–Share Alike 3.0 Unported license ("CC-BY-SA"). An explanation of CC-BY-SA is available at

<http://creativecommons.org/licenses/by-sa/3.0/>

. In accordance with CC-BY-SA, if you distribute this document or an adaptation of it, you must provide the URL for the original version.

Red Hat, as the licensor of this document, waives the right to enforce, and agrees not to assert, Section 4d of CC-BY-SA to the fullest extent permitted by applicable law.

Red Hat, Red Hat Enterprise Linux, the Shadowman logo, the Red Hat logo, JBoss, OpenShift, Fedora, the Infinity logo, and RHCE are trademarks of Red Hat, Inc., registered in the United States and other countries.

Linux<sup>®</sup> is the registered trademark of Linus Torvalds in the United States and other countries.

Java<sup>®</sup> is a registered trademark of Oracle and/or its affiliates.

XFS<sup>®</sup> is a trademark of Silicon Graphics International Corp. or its subsidiaries in the United States and/or other countries.

MySQL<sup>®</sup> is a registered trademark of MySQL AB in the United States, the European Union and other countries.

Node.js<sup>®</sup> is an official trademark of Joyent. Red Hat is not formally related to or endorsed by the official Joyent Node.js open source or commercial project.

The OpenStack<sup>®</sup> Word Mark and OpenStack logo are either registered trademarks/service marks or trademarks/service marks of the OpenStack Foundation, in the United States and other countries and are used with the OpenStack Foundation's permission. We are not affiliated with, endorsed or sponsored by the OpenStack Foundation, or the OpenStack community.

All other trademarks are the property of their respective owners.

## Abstract

Read this document for instructions about how to install and manage Red Hat OpenShift Data Foundation using Red Hat OpenShift Container Platform on Microsoft Azure and Azure Red Hat OpenShift.

---

## Table of Contents

<b>MAKING OPEN SOURCE MORE INCLUSIVE</b> .....	<b>3</b>
<b>PROVIDING FEEDBACK ON RED HAT DOCUMENTATION</b> .....	<b>4</b>
<b>PREFACE</b> .....	<b>5</b>
<b>CHAPTER 1. PREPARING TO DEPLOY OPENSIFT DATA FOUNDATION</b> .....	<b>6</b>
1.1. ENABLING KEY VALUE BACKEND PATH AND POLICY IN VAULT	6
<b>CHAPTER 2. DEPLOYING OPENSIFT DATA FOUNDATION ON MICROSOFT AZURE</b> .....	<b>8</b>
2.1. INSTALLING RED HAT OPENSIFT DATA FOUNDATION OPERATOR	8
2.2. CREATING AN OPENSIFT DATA FOUNDATION CLUSTER	10
<b>CHAPTER 3. DEPLOYING OPENSIFT DATA FOUNDATION ON AZURE RED HAT OPENSIFT</b> .....	<b>12</b>
3.1. GETTING A RED HAT PULL SECRET FOR NEW DEPLOYMENT OF AZURE RED HAT OPENSIFT	12
3.2. PREPARING A RED HAT PULL SECRET FOR EXISTING AZURE RED HAT OPENSIFT CLUSTERS	13
3.3. ADDING THE PULL SECRET TO THE CLUSTER	13
3.3.1. Modifying the configuration files to enable Red Hat operators	13
3.4. VALIDATING YOUR RED HAT PULL SECRET IS WORKING	13
3.5. INSTALLING RED HAT OPENSIFT DATA FOUNDATION OPERATOR	14
3.6. CREATING AN OPENSIFT DATA FOUNDATION CLUSTER	15
<b>CHAPTER 4. VERIFYING OPENSIFT DATA FOUNDATION DEPLOYMENT</b> .....	<b>18</b>
4.1. VERIFYING THE STATE OF THE PODS	18
4.2. VERIFYING THE OPENSIFT DATA FOUNDATION CLUSTER IS HEALTHY	20
4.3. VERIFYING THE MULTICLOUD OBJECT GATEWAY IS HEALTHY	20
4.4. VERIFYING THAT THE OPENSIFT DATA FOUNDATION SPECIFIC STORAGE CLASSES EXIST	20
<b>CHAPTER 5. DEPLOY STANDALONE MULTICLOUD OBJECT GATEWAY</b> .....	<b>21</b>
5.1. INSTALLING RED HAT OPENSIFT DATA FOUNDATION OPERATOR	21
5.2. CREATING STANDALONE MULTICLOUD OBJECT GATEWAY	22
<b>CHAPTER 6. UNINSTALLING OPENSIFT DATA FOUNDATION</b> .....	<b>25</b>
6.1. UNINSTALLING OPENSIFT DATA FOUNDATION IN INTERNAL MODE	25



## MAKING OPEN SOURCE MORE INCLUSIVE

Red Hat is committed to replacing problematic language in our code, documentation, and web properties. We are beginning with these four terms: master, slave, blacklist, and whitelist. Because of the enormity of this endeavor, these changes will be implemented gradually over several upcoming releases. For more details, see [our CTO Chris Wright's message](#).

## PROVIDING FEEDBACK ON RED HAT DOCUMENTATION

We appreciate your input on our documentation. Do let us know how we can make it better. To give feedback:

- For simple comments on specific passages:
  1. Make sure you are viewing the documentation in the *Multi-page HTML* format. In addition, ensure you see the **Feedback** button in the upper right corner of the document.
  2. Use your mouse cursor to highlight the part of text that you want to comment on.
  3. Click the **Add Feedback** pop-up that appears below the highlighted text.
  4. Follow the displayed instructions.
- For submitting more complex feedback, create a Bugzilla ticket:
  1. Go to the [Bugzilla](#) website.
  2. In the **Component** section, choose **documentation**.
  3. Fill in the **Description** field with your suggestion for improvement. Include a link to the relevant part(s) of documentation.
  4. Click **Submit Bug**.



---

## PREFACE

Red Hat OpenShift Data Foundation 4.8 supports deployment on existing Red Hat OpenShift Container Platform (RHOCP) Azure clusters.



### NOTE

Only internal OpenShift Data Foundation clusters are supported on Microsoft Azure. See [Planning your deployment](#) for more information about deployment requirements.

To deploy OpenShift Data Foundation, start with the requirements in [Preparing to deploy OpenShift Data Foundation](#) chapter and then follow the appropriate deployment process based on your requirement:

- [Deploy OpenShift Data Foundation on Microsoft Azure](#)
- [Deploy standalone Multicloud Object Gateway component](#)

# CHAPTER 1. PREPARING TO DEPLOY OPENSIFT DATA FOUNDATION

Deploying OpenShift Data Foundation on OpenShift Container Platform using dynamic storage devices provides you with the option to create internal cluster resources. This will result in the internal provisioning of the base services, which helps to make additional storage classes available to applications.

Before you begin the deployment of OpenShift Data Foundation, follow these steps:

1. Optional: If you want to enable cluster-wide encryption using an external Key Management System (KMS):
  - Ensure that a policy with a token exists and the key value backend path in Vault is enabled. See [enabled the key value backend path and policy in Vault](#) .
  - Ensure that you are using signed certificates on your Vault servers.
2. Minimum starting node requirements [Technology Preview]
 

An OpenShift Data Foundation cluster is deployed with minimum configuration when the standard deployment resource requirement is not met. See [Resource requirements](#) section in Planning guide.
3. Regional-DR requirements [Developer Preview]
 

Disaster Recovery features supported by Red Hat OpenShift Data Foundation require all of the following prerequisites in order to successfully implement a Disaster Recovery solution:

  - A valid Red Hat OpenShift Data Foundation Advanced subscription
  - A valid Red Hat Advanced Cluster Management for Kubernetes subscription
 

For detailed requirements, see [Regional-DR requirements](#) and [RHACM requirements](#).

## 1.1. ENABLING KEY VALUE BACKEND PATH AND POLICY IN VAULT

### Prerequisites

- Administrator access to Vault.
- Carefully, choose a unique path name as the backend **path** that follows the naming convention since it cannot be changed later.

### Procedure

1. Enable the Key/Value (KV) backend path in Vault.  
For Vault KV secret engine API, version 1:

```
$ vault secrets enable -path=odf kv
```

For Vault KV secret engine API, version 2:

```
$ vault secrets enable -path=odf kv-v2
```

2. Create a policy to restrict users to perform a write or delete operation on the secret using the following commands.

```
echo '  
path "odf/*" {  
  capabilities = ["create", "read", "update", "delete", "list"]  
}  
path "sys/mounts" {  
  capabilities = ["read"]  
}' | vault policy write odf -
```

3. Create a token matching the above policy.

```
$ vault token create -policy=odf -format json
```

## CHAPTER 2. DEPLOYING OPENSIFT DATA FOUNDATION ON MICROSOFT AZURE

You can deploy OpenShift Data Foundation on OpenShift Container Platform using dynamic storage devices provided by Microsoft Azure installer-provisioned infrastructure (IPI) (type: **managed-premium**) that enables you to create internal cluster resources. This results in internal provisioning of the base services, which helps to make additional storage classes available to applications.

Also, it is possible to deploy only the Multicloud Object Gateway (MCG) component with OpenShift Data Foundation. For more information, see [Deploy standalone Multicloud Object Gateway](#).



### NOTE

Only internal OpenShift Data Foundation clusters are supported on Microsoft Azure. See [Planning your deployment](#) for more information about deployment requirements.

Ensure that you have addressed the requirements in [Preparing to deploy OpenShift Data Foundation](#) chapter before proceeding with the below steps for deploying using dynamic storage devices:

1. [Install the Red Hat OpenShift Data Foundation Operator](#).
2. [Create the OpenShift Data Foundation Cluster](#)

### 2.1. INSTALLING RED HAT OPENSIFT DATA FOUNDATION OPERATOR

You can install Red Hat OpenShift Data Foundation Operator using the Red Hat OpenShift Container Platform Operator Hub.

#### Prerequisites

- Access to an OpenShift Container Platform cluster using an account with **cluster-admin** and Operator installation permissions.
- You must have at least three worker nodes in the Red Hat OpenShift Container Platform cluster.
- For additional resource requirements, see the [Planning your deployment](#) guide.



### IMPORTANT

- When you need to override the cluster-wide default node selector for OpenShift Data Foundation, you can use the following command in the command line interface to specify a blank node selector for the **openshift-storage** namespace (create openshift-storage namespace in this case):

```
$ oc annotate namespace openshift-storage openshift.io/node-selector=
```

- Taint a node as **infra** to ensure only Red Hat OpenShift Data Foundation resources are scheduled on that node. This helps you save on subscription costs. For more information, see [How to use dedicated worker nodes for Red Hat OpenShift Data Foundation](#) chapter in the *Managing and Allocating Storage Resources* guide.

## Procedure

1. Log in to the OpenShift Web Console.
2. Click **Operators** → **OperatorHub**.
3. Scroll or type **OpenShift Data Foundation** into the **Filter by keyword** box to find the **OpenShift Data Foundation** Operator.
4. Click **Install**.
5. Set the following options on the **Install Operator** page:
  - a. Update Channel as **stable-4.9**.
  - b. Installation Mode as **A specific namespace on the cluster**
  - c. Installed Namespace as **Operator recommended namespace openshift-storage**. If Namespace **openshift-storage** does not exist, it is created during the operator installation.
  - d. Select Approval Strategy as **Automatic** or **Manual**.  
If you select **Automatic** updates, then the Operator Lifecycle Manager (OLM) automatically upgrades the running instance of your Operator without any intervention.  
  
If you select **Manual** updates, then the OLM creates an update request. As a cluster administrator, you must then manually approve that update request to update the Operator to a newer version.
  - e. Ensure that the **Enable** option is selected for the **Console plugin**.
  - f. Click **Install**.




### NOTE

We recommend using all default settings. Changing it may result in unexpected behavior. Alter only if you are aware of its result.

## Verification steps

- Verify that the **OpenShift Data Foundation** Operator shows a green tick indicating successful installation.
- After the operator is successfully installed, a pop-up with a message, **Web console update is available** appears on the user interface. Click **Refresh web console** from this pop-up for the console changes to reflect.
  - In the Web Console, navigate to **Operators** and verify if **OpenShift Data Foundation** is available.



### IMPORTANT

In case the console plugin option was not automatically enabled after you installed the OpenShift Data Foundation Operator, you need to enable it.

For more information on how to enable the console plugin, see [Enabling the Red Hat OpenShift Data Foundation console plugin](#).

## 2.2. CREATING AN OPENSIFT DATA FOUNDATION CLUSTER

Create an OpenShift Data Foundation cluster after you install the OpenShift Data Foundation operator.

### Prerequisites

- The OpenShift Data Foundation operator must be installed from the Operator Hub. For more information, see [Installing OpenShift Data Foundation Operator using the Operator Hub](#).

### Procedure

1. In the OpenShift Web Console, click **Operators → Installed Operators** to view all the installed operators.  
Ensure that the **Project** selected is **openshift-storage**.
2. Click on the **OpenShift Data Foundation** operator, and then click **Create StorageSystem**.
3. In the **Backing storage** page, select the following:
  - a. Select the **Use an existing StorageClass** option.
  - b. Select the **Storage Class**.  
By default, it is set to **managed-premium**.
  - c. Expand **Advanced** and select **Full Deployment** for the **Deployment type** option.
  - d. Click **Next**.
4. In the **Capacity and nodes** page, provide the necessary information:
  - a. Select a value for **Requested Capacity** from the dropdown list. It is set to **2 TiB** by default.



### NOTE

Once you select the initial storage capacity, cluster expansion is performed only using the selected usable capacity (three times of raw storage).

- b. In the **Select Nodes** section, select at least three available nodes.  
For cloud platforms with multiple availability zones, ensure that the Nodes are spread across different Locations/availability zones.

If the nodes selected do not match the OpenShift Data Foundation cluster requirement of an aggregated 30 CPUs and 72 GiB of RAM, a minimal cluster is deployed. For minimum starting node requirements, see the [Resource requirements](#) section in the *Planning* guide.

- c. Click **Next**.
5. Optional: In the **Security and network** page, configure the following based on your requirements:
    - a. To enable encryption, select **Enable data encryption for block and file storage**
    - b. Choose either one or both the encryption levels:
      - **Cluster-wide encryption**  
Encrypts the entire cluster (block and file).

- **StorageClass encryption**  
Creates encrypted persistent volume (block only) using encryption enabled storage class.
- c. Select the **Connect to an external key management service** checkbox. This is optional for cluster-wide encryption.
    - i. **Key Management Service Provider** is set to **Vault** by default.
    - ii. Enter Vault **Service Name**, host **Address** of Vault server ('https://<hostname or ip>'), **Port** number and **Token**.
    - iii. Expand **Advanced Settings** to enter additional settings and certificate details based on your **Vault** configuration:
      - A. Enter the Key Value secret path in **Backend Path** that is dedicated and unique to OpenShift Data Foundation.
      - B. Optional: Enter **TLS Server Name** and **Vault Enterprise Namespace**
      - C. Upload the respective PEM encoded certificate file to provide the **CA Certificate**, **Client Certificate** and **Client Private Key** .
      - D. Click **Save**.
  - d. Click **Next**.
6. In the **Review and create** page, review the configuration details.  
To modify any configuration settings, click **Back**.
  7. Click **Create StorageSystem**.

### Verification steps


- To verify the final Status of the installed storage cluster:
  - a. In the OpenShift Web Console, navigate to **Installed Operators → OpenShift Data Foundation → Storage System → ocs-storagecluster-storagesystem → Resources**.
  - b. Verify that **Status** of **StorageCluster** is **Ready** and has a green tick mark next to it.
    1. To verify that all components for OpenShift Data Foundation are successfully installed, see [Verifying your OpenShift Data Foundation deployment](#) .

### Additional resources

To enable Overprovision Control alerts, refer to [Alerts](#) in Monitoring guide.

## CHAPTER 3. DEPLOYING OPENSIFT DATA FOUNDATION ON AZURE RED HAT OPENSIFT

The Azure Red Hat OpenShift service enables you to deploy fully managed OpenShift clusters. Red Hat OpenShift Data Foundation can be deployed on Azure Red Hat OpenShift service.



### IMPORTANT

OpenShift Data Foundation on Azure Red Hat OpenShift is not a managed service offering. Red Hat OpenShift Data Foundation subscriptions are required to have the installation supported by the Red Hat support team. Open support cases by choosing the product as **Red Hat OpenShift Data Foundation** with the [Red Hat support](#) team (and not Microsoft) if you need any assistance for Red Hat OpenShift Data Foundation on Azure Red Hat OpenShift.

To install OpenShift Data Foundation on Azure Red Hat OpenShift, follow sections:

1. [Getting a Red Hat pull secret for new deployment of Azure Red Hat OpenShift](#) .
2. [Preparing a Red Hat pull secret for existing Azure Red Hat OpenShift clusters](#) .
3. [Adding the pull secret to the cluster](#) .
4. [Validating your Red Hat pull secret is working](#) .
5. [Install the Red Hat OpenShift Data Foundation Operator](#) .
6. [Create the OpenShift Data Foundation Cluster Service](#) .

### 3.1. GETTING A RED HAT PULL SECRET FOR NEW DEPLOYMENT OF AZURE RED HAT OPENSIFT

A Red Hat pull secret enables the cluster to access Red Hat container registries along with additional content.

#### Prerequisites

- A Red Hat portal account.
- OpenShift Data Foundation subscription.

#### Procedure

To get a Red Hat pull secret for a new deployment of Azure Red Hat OpenShift, follow the steps in the section [Get a Red Hat pull secret](#) in the official Microsoft Azure documentation.

Note that while creating the [Azure Red Hat OpenShift cluster](#), you may need larger worker nodes, controlled by `--worker-vm-size` or more worker nodes, controlled by `--worker-count`. The recommended `worker-vm-size` is **Standard\_D16s\_v3**. You can also use dedicated worker nodes, for more information, see [How to use dedicated worker nodes for Red Hat OpenShift Data Foundation](#) in the *Managing and allocating storage resources* guide.



## 3.2. PREPARING A RED HAT PULL SECRET FOR EXISTING AZURE RED HAT OPENSIFT CLUSTERS

When you create an Azure Red Hat OpenShift cluster without adding a Red Hat pull secret, a pull secret is still created on the cluster automatically. However, this pull secret is not fully populated.

Use this section to update the automatically created pull secret with the additional values from the Red Hat pull secret.

### Prerequisites

- Existing Azure Red Hat OpenShift cluster without a Red Hat pull secret.

### Procedure

To prepare a Red Hat pull secret for existing an existing Azure Red Hat OpenShift clusters, follow the steps in the section [Prepare your pull secret](#) in the official Microsoft Azure documentation.

## 3.3. ADDING THE PULL SECRET TO THE CLUSTER

### Prerequisites

- A Red Hat pull secret.

### Procedure

- Run the following command to update your pull secret.



### NOTE

Running this command causes the cluster nodes to restart one by one as they are updated.

```
oc set data secret/pull-secret -n openshift-config --from-file=.dockerconfigjson=./pull-secret.json
```

After the secret is set, you can enable the Red Hat Certified Operators.

### 3.3.1. Modifying the configuration files to enable Red Hat operators

To modify the configuration files to enable Red Hat operators, follow the steps in the section [Modify the configuration files](#) in the official Microsoft Azure documentation.

## 3.4. VALIDATING YOUR RED HAT PULL SECRET IS WORKING

After you add the pull secret and modify the configuration files, the cluster can take several minutes to get updated.

To check if the cluster has been updated, run the following command to show the **Certified Operators** and **Red Hat Operators** sources available:

```
$ oc get catalogsource -A
```

NAMESPACE	NAME	DISPLAY
openshift-marketplace	redhat-operators	Red Hat Operators
TYPE	PUBLISHER	AGE
grpc	Red Hat	11s

If you do not see the Red Hat Operators, wait a few minutes and try again.

To ensure that your pull secret has been updated and is working correctly, open **Operator Hub** and check for any Red Hat verified Operator. For example, check if the OpenShift Data Foundation Operator is available, and see if you have permissions to install it.

## 3.5. INSTALLING RED HAT OPENSIFT DATA FOUNDATION OPERATOR

You can install Red Hat OpenShift Data Foundation Operator using the Red Hat OpenShift Container Platform Operator Hub.

### Prerequisites

- Access to an OpenShift Container Platform cluster using an account with **cluster-admin** and Operator installation permissions.
- You must have at least three worker nodes in the Red Hat OpenShift Container Platform cluster.
- For additional resource requirements, see the [Planning your deployment](#) guide.



### IMPORTANT

- When you need to override the cluster-wide default node selector for OpenShift Data Foundation, you can use the following command in the command line interface to specify a blank node selector for the **openshift-storage** namespace (create `openshift-storage` namespace in this case):

```
$ oc annotate namespace openshift-storage openshift.io/node-selector=
```

- Taint a node as **infra** to ensure only Red Hat OpenShift Data Foundation resources are scheduled on that node. This helps you save on subscription costs. For more information, see [How to use dedicated worker nodes for Red Hat OpenShift Data Foundation](#) chapter in the *Managing and Allocating Storage Resources* guide.

### Procedure

1. Log in to the OpenShift Web Console.
2. Click **Operators** → **OperatorHub**.
3. Scroll or type **OpenShift Data Foundation** into the **Filter by keyword** box to find the **OpenShift Data Foundation** Operator.
4. Click **Install**.

5. Set the following options on the **Install Operator** page:
  - a. Update Channel as **stable-4.9**.
  - b. Installation Mode as **A specific namespace on the cluster**
  - c. Installed Namespace as **Operator recommended namespace openshift-storage**. If Namespace **openshift-storage** does not exist, it is created during the operator installation.
  - d. Select Approval Strategy as **Automatic** or **Manual**.  
If you select **Automatic** updates, then the Operator Lifecycle Manager (OLM) automatically upgrades the running instance of your Operator without any intervention.  
  
If you select **Manual** updates, then the OLM creates an update request. As a cluster administrator, you must then manually approve that update request to update the Operator to a newer version.
  - e. Ensure that the **Enable** option is selected for the **Console plugin**.
  - f. Click **Install**.




#### NOTE

We recommend using all default settings. Changing it may result in unexpected behavior. Alter only if you are aware of its result.

#### Verification steps

- Verify that the **OpenShift Data Foundation** Operator shows a green tick indicating successful installation.
- After the operator is successfully installed, a pop-up with a message, **Web console update is available** appears on the user interface. Click **Refresh web console** from this pop-up for the console changes to reflect.
  - In the Web Console, navigate to **Operators** and verify if **OpenShift Data Foundation** is available.



#### IMPORTANT

In case the console plugin option was not automatically enabled after you installed the OpenShift Data Foundation Operator, you need to enable it.

For more information on how to enable the console plugin, see [Enabling the Red Hat OpenShift Data Foundation console plugin](#).

## 3.6. CREATING AN OPENSIFT DATA FOUNDATION CLUSTER

Create an OpenShift Data Foundation cluster after you install the OpenShift Data Foundation operator.

#### Prerequisites

- The OpenShift Data Foundation operator must be installed from the Operator Hub. For more information, see [Installing OpenShift Data Foundation Operator using the Operator Hub](#).

## Procedure

1. In the OpenShift Web Console, click **Operators → Installed Operators** to view all the installed operators.  
Ensure that the **Project** selected is **openshift-storage**.
2. Click on the **OpenShift Data Foundation** operator, and then click **Create StorageSystem**.
3. In the **Backing storage** page, select the following:
  - a. Select the **Use an existing StorageClass** option.
  - b. Select the **Storage Class**.  
By default, it is set to **managed-premium**.
  - c. Expand **Advanced** and select **Full Deployment** for the **Deployment type** option.
  - d. Click **Next**.
4. In the **Capacity and nodes** page, provide the necessary information:
  - a. Select a value for **Requested Capacity** from the dropdown list. It is set to **2 TiB** by default.



### NOTE

Once you select the initial storage capacity, cluster expansion is performed only using the selected usable capacity (three times of raw storage).

- b. In the **Select Nodes** section, select at least three available nodes.  
For cloud platforms with multiple availability zones, ensure that the Nodes are spread across different Locations/availability zones.  
  
If the nodes selected do not match the OpenShift Data Foundation cluster requirement of an aggregated 30 CPUs and 72 GiB of RAM, a minimal cluster is deployed. For minimum starting node requirements, see the [Resource requirements](#) section in the *Planning* guide.
    - c. Click **Next**.
5. Optional: In the **Security and network** page, configure the following based on your requirements:
  - a. To enable encryption, select **Enable data encryption for block and file storage**
  - b. Choose either one or both the encryption levels:
    - **Cluster-wide encryption**  
Encrypts the entire cluster (block and file).
    - **StorageClass encryption**  
Creates encrypted persistent volume (block only) using encryption enabled storage class.
  - c. Select the **Connect to an external key management service** checkbox. This is optional for cluster-wide encryption.
    - i. **Key Management Service Provider** is set to **Vault** by default.

- ii. Enter Vault **Service Name**, host **Address** of Vault server ('https://<hostname or ip>'), **Port** number and **Token**.
- iii. Expand **Advanced Settings** to enter additional settings and certificate details based on your **Vault** configuration:
  - A. Enter the Key Value secret path in **Backend Path** that is dedicated and unique to OpenShift Data Foundation.
  - B. Optional: Enter **TLS Server Name** and **Vault Enterprise Namespace**
  - C. Upload the respective PEM encoded certificate file to provide the **CA Certificate**, **Client Certificate** and **Client Private Key** .
  - D. Click **Save**.
- d. Click **Next**.
6. In the **Review and create** page, review the configuration details.  
To modify any configuration settings, click **Back**.
7. Click **Create StorageSystem**.

### Verification steps

- To verify the final Status of the installed storage cluster:
  - a. In the OpenShift Web Console, navigate to **Installed Operators** → **OpenShift Data Foundation** → **Storage System** → **ocs-storagecluster-storagesystem** → **Resources**.
  - b. Verify that **Status** of **StorageCluster** is **Ready** and has a green tick mark next to it.
    1. To verify that all components for OpenShift Data Foundation are successfully installed, see [Verifying your OpenShift Data Foundation deployment](#) .

### Additional resources

To enable Overprovision Control alerts, refer to [Alerts](#) in Monitoring guide.

## CHAPTER 4. VERIFYING OPENSIFT DATA FOUNDATION DEPLOYMENT

Use this section to verify that OpenShift Data Foundation is deployed correctly.

### 4.1. VERIFYING THE STATE OF THE PODS

#### Procedure

1. Click **Workloads** → **Pods** from the OpenShift Web Console.
2. Select **openshift-storage** from the **Project** drop-down list.



#### NOTE

If the **Show default projects** option is disabled, use the toggle button to list all the default projects.

For more information about the expected number of pods for each component and how it varies depending on the number of nodes, see [Table 4.1, “Pods corresponding to OpenShift Data Foundation cluster”](#).

3. Click the **Running** and **Completed** tabs to verify that the following pods are in **Running** and **Completed** state:

**Table 4.1. Pods corresponding to OpenShift Data Foundation cluster**

Component	Corresponding pods
OpenShift Data Foundation Operator	<ul style="list-style-type: none"> <li>● <b>ocs-operator-*</b> (1 pod on any worker node)</li> <li>● <b>ocs-metrics-exporter-*</b> (1 pod on any worker node)</li> <li>● <b>odf-operator-controller-manager-*</b> (1 pod on any worker node)</li> <li>● <b>odf-console-*</b> (1 pod on any worker node)</li> </ul>
Rook-ceph Operator	<p><b>rook-ceph-operator-*</b></p> <p>(1 pod on any worker node)</p>

Component	Corresponding pods
Multicloud Object Gateway	<ul style="list-style-type: none"> <li>● <b>noobaa-operator-*</b> (1 pod on any worker node)</li> <li>● <b>noobaa-core-*</b> (1 pod on any storage node)</li> <li>● <b>noobaa-db-pg-*</b> (1 pod on any storage node)</li> <li>● <b>noobaa-endpoint-*</b> (1 pod on any storage node)</li> </ul>
MON	<p><b>rook-ceph-mon-*</b></p> <p>(3 pods distributed across storage nodes)</p>
MGR	<p><b>rook-ceph-mgr-*</b></p> <p>(1 pod on any storage node)</p>
MDS	<p><b>rook-ceph-mds-ocs-storagecluster-cephfilesystem-*</b></p> <p>(2 pods distributed across storage nodes)</p>
CSI	<ul style="list-style-type: none"> <li>● <b>cephfs</b> <ul style="list-style-type: none"> <li>○ <b>csi-cephfsplugin-*</b> (1 pod on each worker node)</li> <li>○ <b>csi-cephfsplugin-provisioner-*</b> (2 pods distributed across worker nodes)</li> </ul> </li> <li>● <b>rbd</b> <ul style="list-style-type: none"> <li>○ <b>csi-rbdplugin-*</b> (1 pod on each worker node)</li> <li>○ <b>csi-rbdplugin-provisioner-*</b> (2 pods distributed across worker nodes)</li> </ul> </li> </ul>
rook-ceph-crashcollector	<p><b>rook-ceph-crashcollector-*</b></p> <p>(1 pod on each storage node)</p>
OSD	<ul style="list-style-type: none"> <li>● <b>rook-ceph-osd-*</b> (1 pod for each device)</li> <li>● <b>rook-ceph-osd-prepare-ocs-deviceset-*</b> (1 pod for each device)</li> </ul>

## 4.2. VERIFYING THE OPENSIFT DATA FOUNDATION CLUSTER IS HEALTHY

### Procedure

1. In the OpenShift Web Console, click **Storage → OpenShift Data Foundation**.
2. In the **Status** card of the **Overview** tab, click **Storage System** and then click the storage system link from the pop up that appears.
3. In the **Status** card of the **Block and File** tab, verify that *Storage Cluster* has a green tick.
4. In the **Details** card, verify that the cluster information is displayed.

For more information on the health of the OpenShift Data Foundation cluster using the **Block and File** dashboard, see [Monitoring OpenShift Data Foundation](#).

## 4.3. VERIFYING THE MULTICLOUD OBJECT GATEWAY IS HEALTHY

### Procedure

1. In the OpenShift Web Console, click **Storage → OpenShift Data Foundation**.
2. In the **Status** card of the **Overview** tab, click **Storage System** and then click the storage system link from the pop up that appears.
  - a. In the **Status card** of the **Object** tab, verify that both *Object Service* and *Data Resiliency* have a green tick.
  - b. In the **Details** card, verify that the MCG information is displayed.

For more information on the health of the OpenShift Data Foundation cluster using the object service dashboard, see [Monitoring OpenShift Data Foundation](#).

## 4.4. VERIFYING THAT THE OPENSIFT DATA FOUNDATION SPECIFIC STORAGE CLASSES EXIST

### Procedure

1. Click **Storage → Storage Classes** from the left pane of the OpenShift Web Console.
2. Verify that the following storage classes are created with the OpenShift Data Foundation cluster creation:
  - **ocs-storagecluster-ceph-rbd**
  - **ocs-storagecluster-cephfs**
  - **openshift-storage.noobaa.io**



## CHAPTER 5. DEPLOY STANDALONE MULTICLOUD OBJECT GATEWAY

Deploying only the Multicloud Object Gateway component with OpenShift Data Foundation provides the flexibility in deployment and helps to reduce the resource consumption. Use this section to deploy only the standalone Multicloud Object Gateway component, which involves the following steps:

- Installing Red Hat OpenShift Data Foundation Operator
- Creating standalone Multicloud Object Gateway

### 5.1. INSTALLING RED HAT OPENSIFT DATA FOUNDATION OPERATOR

You can install Red Hat OpenShift Data Foundation Operator using the Red Hat OpenShift Container Platform Operator Hub.

#### Prerequisites

- Access to an OpenShift Container Platform cluster using an account with **cluster-admin** and Operator installation permissions.
- You must have at least three worker nodes in the Red Hat OpenShift Container Platform cluster.
- For additional resource requirements, see the [Planning your deployment](#) guide.



#### IMPORTANT

- When you need to override the cluster-wide default node selector for OpenShift Data Foundation, you can use the following command in the command line interface to specify a blank node selector for the **openshift-storage** namespace (create openshift-storage namespace in this case):

```
$ oc annotate namespace openshift-storage openshift.io/node-selector=
```

- Taint a node as **infra** to ensure only Red Hat OpenShift Data Foundation resources are scheduled on that node. This helps you save on subscription costs. For more information, see [How to use dedicated worker nodes for Red Hat OpenShift Data Foundation](#) chapter in the *Managing and Allocating Storage Resources* guide.

#### Procedure

1. Log in to the OpenShift Web Console.
2. Click **Operators** → **OperatorHub**.
3. Scroll or type **OpenShift Data Foundation** into the **Filter by keyword** box to find the **OpenShift Data Foundation Operator**.
4. Click **Install**.
5. Set the following options on the **Install Operator** page:

- a. Update Channel as **stable-4.9**.
- b. Installation Mode as **A specific namespace on the cluster**
- c. Installed Namespace as **Operator recommended namespace openshift-storage**. If Namespace **openshift-storage** does not exist, it is created during the operator installation.
- d. Select Approval Strategy as **Automatic** or **Manual**.  
If you select **Automatic** updates, then the Operator Lifecycle Manager (OLM) automatically upgrades the running instance of your Operator without any intervention.  
  
If you select **Manual** updates, then the OLM creates an update request. As a cluster administrator, you must then manually approve that update request to update the Operator to a newer version.
- e. Ensure that the **Enable** option is selected for the **Console plugin**.
- f. Click **Install**.




#### NOTE

We recommend using all default settings. Changing it may result in unexpected behavior. Alter only if you are aware of its result.

#### Verification steps

- Verify that the **OpenShift Data Foundation** Operator shows a green tick indicating successful installation.
- After the operator is successfully installed, a pop-up with a message, **Web console update is available** appears on the user interface. Click **Refresh web console** from this pop-up for the console changes to reflect.
  - In the Web Console, navigate to **Operators** and verify if **OpenShift Data Foundation** is available.



#### IMPORTANT

In case the console plugin option was not automatically enabled after you installed the OpenShift Data Foundation Operator, you need to enable it.

For more information on how to enable the console plugin, see [Enabling the Red Hat OpenShift Data Foundation console plugin](#).

## 5.2. CREATING STANDALONE MULTICLOUD OBJECT GATEWAY

Use this section to create only the Multicloud Object Gateway component with OpenShift Data Foundation.

#### Prerequisites

- Ensure that OpenShift Data Foundation Operator is installed.
- (For deploying using local storage devices only) Ensure that Local Storage Operator is installed.

- Ensure that you have a storage class and is set as the default.

## Procedure

1. In the OpenShift Web Console, click **Operators** → **Installed Operators** to view all the installed operators.  
Ensure that the Project selected is **openshift-storage**.
2. Click **OpenShift Data Foundation** operator and then click **Create StorageSystem**.
3. In the **Backing storage** page, expand **Advanced**.
4. Select **Multicloud Object Gateway** for **Deployment type**.
5. Click **Next**.
6. Optional: In the **Security** page, select **Connect to an external key management service**
  - a. **Key Management Service Provider** is set to **Vault** by default.
  - b. Enter Vault **Service Name**, host Address of Vault server ('https:// <hostname or ip>'), **Port number**, and **Token**.
  - c. Expand **Advanced Settings** to enter additional settings and certificate details based on your **Vault** configuration:
    - i. Enter the Key Value secret path in the **Backend Path** that is dedicated and unique to OpenShift Data Foundation.
    - ii. Optional: Enter **TLS Server Name** and **Vault Enterprise Namespace**
    - iii. Upload the respective PEM encoded certificate file to provide the **CA Certificate**, **Client Certificate**, and **Client Private Key**.
    - iv. Click **Save**.
  - d. Click **Next**.
7. In the **Review and create** page, review the configuration details:  
To modify any configuration settings, click **Back**.
8. Click **Create StorageSystem**.

## Verification steps

### Verifying that the OpenShift Data Foundation cluster is healthy

1. In the OpenShift Web Console, click **Storage** → **OpenShift Data Foundation**.
2. In the **Status** card of the **Overview** tab, click **Storage System** and then click the storage system link from the pop up that appears.
  - a. In the **Status card** of the **Object** tab, verify that both *Object Service* and *Data Resiliency* have a green tick.
  - b. In the **Details** card, verify that the MCG information is displayed.

## Verify the state of the pods

1. Click **Workloads** → **Pods** from the OpenShift Web Console.
2. Select **openshift-storage** from the **Project** drop-down list and verify that the following pods are in **Running** state.



### NOTE

If the **Show default projects** option is disabled, use the toggle button to list all the default projects.

Component	Corresponding pods
OpenShift Data Foundation Operator	<ul style="list-style-type: none"> <li>● <b>ocs-operator-*</b> (1 pod on any worker node)</li> <li>● <b>ocs-metrics-exporter-*</b> (1 pod on any worker node)</li> <li>● <b>odf-operator-controller-manager-*</b> (1 pod on any worker node)</li> <li>● <b>odf-console-*</b> (1 pod on any worker node)</li> </ul>
Rook-ceph Operator	<p><b>rook-ceph-operator-*</b></p> <p>(1 pod on any worker node)</p>
Multicloud Object Gateway	<ul style="list-style-type: none"> <li>● <b>noobaa-operator-*</b> (1 pod on any worker node)</li> <li>● <b>noobaa-core-*</b> (1 pod on any worker node)</li> <li>● <b>noobaa-db-pg-*</b> (1 pod on any worker node)</li> <li>● <b>noobaa-endpoint-*</b> (1 pod on any worker node)</li> </ul>

## CHAPTER 6. UNINSTALLING OPENSIFT DATA FOUNDATION

### 6.1. UNINSTALLING OPENSIFT DATA FOUNDATION IN INTERNAL MODE

To uninstall OpenShift Data Foundation in Internal mode, refer to the [knowledge base article on Uninstalling OpenShift Data Foundation](#).