



Red Hat OpenStack Platform 10

Introduction to the OpenStack Dashboard

An overview of the OpenStack dashboard graphical user interface

Red Hat OpenStack Platform 10 Introduction to the OpenStack Dashboard

An overview of the OpenStack dashboard graphical user interface

OpenStack Team
rhos-docs@redhat.com

Legal Notice

Copyright © 2018 Red Hat, Inc.

The text of and illustrations in this document are licensed by Red Hat under a Creative Commons Attribution–Share Alike 3.0 Unported license ("CC-BY-SA"). An explanation of CC-BY-SA is available at

<http://creativecommons.org/licenses/by-sa/3.0/>

. In accordance with CC-BY-SA, if you distribute this document or an adaptation of it, you must provide the URL for the original version.

Red Hat, as the licensor of this document, waives the right to enforce, and agrees not to assert, Section 4d of CC-BY-SA to the fullest extent permitted by applicable law.

Red Hat, Red Hat Enterprise Linux, the Shadowman logo, JBoss, OpenShift, Fedora, the Infinity logo, and RHCE are trademarks of Red Hat, Inc., registered in the United States and other countries.

Linux ® is the registered trademark of Linus Torvalds in the United States and other countries.

Java ® is a registered trademark of Oracle and/or its affiliates.

XFS ® is a trademark of Silicon Graphics International Corp. or its subsidiaries in the United States and/or other countries.

MySQL ® is a registered trademark of MySQL AB in the United States, the European Union and other countries.

Node.js ® is an official trademark of Joyent. Red Hat Software Collections is not formally related to or endorsed by the official Joyent Node.js open source or commercial project.

The OpenStack ® Word Mark and OpenStack logo are either registered trademarks/service marks or trademarks/service marks of the OpenStack Foundation, in the United States and other countries and are used with the OpenStack Foundation's permission. We are not affiliated with, endorsed or sponsored by the OpenStack Foundation, or the OpenStack community.

All other trademarks are the property of their respective owners.

Abstract

This guide provides an outline of the options available in the OpenStack dashboard user interface.

Table of Contents

PREFACE	3
CHAPTER 1. THE OPENSTACK DASHBOARD	4
CHAPTER 2. THE ADMIN TAB	5
2.1. VIEW ALLOCATED FLOATING IP ADDRESSES	6
CHAPTER 3. THE PROJECT TAB	7
CHAPTER 4. THE IDENTITY TAB	9
CHAPTER 5. CUSTOMIZING THE DASHBOARD	10
5.1. LOGO, SITE COLORS, AND STYLESHEETS	10
5.2. HTML TITLE	11
5.3. SITE BRANDING LINK	11
5.4. HELP URL	11

PREFACE


This document provides an outline of the options available in the OpenStack dashboard graphical user interface.

CHAPTER 1. THE OPENSTACK DASHBOARD

The OpenStack dashboard is a web-based graphical user interface for managing OpenStack services.

To access the browser dashboard, the dashboard service must be installed, and you must know the dashboard host name (or IP) and login password. The dashboard URL is:

```
http://HOSTNAME/dashboard/
```



CHAPTER 2. THE ADMIN TAB

The **Admin** tab provides an interface where administrative users can view usage and manage instances, volumes, flavors, images, projects, users, services, and quotas.



NOTE

The **Admin** tab displays in the main window only if you have logged in as a user with administrative privileges.

The following options are available in the **Admin** tab:

Table 2.1. System Panel

Parameter Name	Description
Overview	View basic reports.
Resource Usage	Use the following tabs to view the following usages: <ul style="list-style-type: none"> • Usage Report - View the usage report. • Stats - View the statistics of all resources.
Hypervisors	View the hypervisor summary.
Host Aggregates	View, create, and edit host aggregates. View the list of availability zones.
Instances	View, pause, resume, suspend, migrate, soft or hard reboot, and delete running instances that belong to users of some, but not all, projects. Also, view the log for an instance or access an instance using the console.
Volumes	View, create, edit, and delete volumes, and volume types.
Flavors	View, create, edit, view extra specifications for, and delete flavors. Flavors are the virtual hardware templates in OpenStack.

Parameter Name	Description
Images	View, create, edit properties for, and delete custom images.
Networks	View, create, edit properties for, and delete networks.
Routers	View, create, edit properties for, and delete routers.
Floating IPs	View allocated floating IP addresses for all projects.
Defaults	View and edit the default quotas (maximum limits) for resources in the environment.
Metadata Definitions	Import, view, and edit metadata definition namespaces, and associate the metadata definitions with specific resource types.
System Information	Contains the following tabs: <ul style="list-style-type: none">● Services - View a list of the services.● Compute Services - View a list of all Compute services.● Network Agents - View the network agents.● Block Storage Services - View a list of all Block Storage services.● Orchestration Services - View a list of all Orchestration services.

2.1. VIEW ALLOCATED FLOATING IP ADDRESSES

You can use the **Floating IPs** panel to view a list of allocated floating IP addresses. This information can also be accessed using the command line:

```
$ nova list --all-tenants
```

CHAPTER 3. THE PROJECT TAB

The **Project** tab provides an interface for viewing and managing the resources of a project. Set a project as active in **Identity > Projects** to view and manage resources in that project.

Limit Summary

Instances Used 2 of 10

VCPUs Used 2 of 20

RAM Used 4GB of 50GB

Floating IPs Allocated 0 of 50

Security Groups Used 1 of 10

Volumes Used 0 of 10

Volume Storage Used 0Bytes of 1000GB

Usage Summary

Select a period of time to query its usage:

From: 2015-07-01 To: 2015-07-09 [Submit](#) The date should be in YYYY-mm-dd format.

Active Instances: 0 Active RAM: 0Bytes This Period's VCPU-Hours: 0.00 This Period's GB-Hours: 0.00 This Period's RAM-Hours: 0.00

Usage [Download CSV Summary](#)

Instance Name	VCPUs	Disk	RAM	Time since created
No items to display.				

Displaying 0 items

The following options are available in the **Project** tab:

Table 3.1. The Compute Tab

Parameter Name	Description
Overview	View reports for the project.
Instances	View, launch, create a snapshot from, stop, pause, or reboot instances, or connect to them through the console.
Volumes	Use the following tabs to complete these tasks: <ul style="list-style-type: none"> • Volumes - View, create, edit, and delete volumes. • Volume Snapshots - View, create, edit, and delete volume snapshots.
Images	View images, instance snapshots, and volume snapshots created by project users, and any images that are publicly available. Create, edit, and delete images, and launch instances from images and snapshots.

Parameter Name	Description
Access & Security	<p>Use the following tabs to complete these tasks:</p> <ul style="list-style-type: none"> • Security Groups - View, create, edit, and delete security groups and security group rules. • Key Pairs - View, create, edit, import, and delete key pairs. • Floating IPs - Allocate an IP address to or release it from a project. • API Access - View API endpoints, download the OpenStack RC file, download EC2 credentials, and view credentials for the logged-in project user.

Table 3.2. The Network Tab

Parameter Name	Description
Network Topology	View the interactive topology of the network.
Networks	Create and manage public and private networks and subnets.
Routers	Create and manage routers.

Table 3.3. The Object Store Tab


Parameter Name	Description
Containers	Create and manage storage containers. A container is a storage compartment for data, and provides a way for you to organize your data. It is similar to the concept of a Linux file directory, but it cannot be nested.

Table 3.4. The Orchestration Tab

Parameter Name	Description
Stacks	Orchestrate multiple composite cloud applications using templates, through both an OpenStack-native REST API and a CloudFormation-compatible Query API.

CHAPTER 4. THE IDENTITY TAB

The **Identity** tab provides an interface for viewing and managing projects and users.



The screenshot shows the OpenStack Identity tab interface. At the top, there is a navigation bar with 'RED HAT ENTERPRISE LINUX OPENSTACK PLATFORM' on the left and 'Project Admin Identity' in the center. On the right, there are links for 'Red Hat Access', 'Help', and a user profile 'admin'. Below the navigation bar, the 'Identity' section is active, with 'Projects' and 'Users' tabs. The 'Projects' tab is selected, displaying a table of projects. The table has columns for 'Name', 'Description', 'Project ID', 'Enabled', and 'Actions'. Three projects are listed: 'demo', 'services', and 'admin'. Each project has a 'Manage Members' button in the 'Actions' column. A 'Filter' input field, a '+ Create Project' button, and a 'Delete Projects' button are located above the table. At the bottom of the table, it says 'Displaying 3 items'.

<input type="checkbox"/>	Name	Description	Project ID	Enabled	Actions
<input type="checkbox"/>	demo	default tenant	4ad6d6d8629445d9beac763dbf4d3040	Yes	Manage Members
<input type="checkbox"/>	services	Tenant for the openstack services	b8f456cb2b0f41579d6a81602af45da5	Yes	Manage Members
<input type="checkbox"/>	admin	admin tenant	dad80cc4f40b4f34a6de3c5373e0200d	Yes	Manage Members

Displaying 3 items

The following options are available in the **Identity** tab:

- **Projects** - View, create, edit, and delete projects/tenants, view project usage, add or remove users as project members, modify quotas, and set an active project.
- **Users** - View, create, edit, disable, and delete users, and change user passwords. The **Users** tab displays only if you are logged in as a user with administrative privileges.

For more information on procedures to manage your cloud using the OpenStack Dashboard, see the following guides:

- [Instances and Images guide](#) (also has procedures for volumes and containers)
- [Networking guide](#)
- [Users and Identity Management guide](#)

CHAPTER 5. CUSTOMIZING THE DASHBOARD

The look and feel of the OpenStack dashboard can be customized using the settings defined in `/openstack-dashboard/openstack_dashboard/local/local_settings.py`. You can customize the following elements of the dashboard:

- HTML title
- Site branding link
- Help URL

In addition, you can create a custom theme and further customize the look and feel of the dashboard, including the following components:

- Logo
- Site colors
- Stylesheets



NOTE

The OpenStack dashboard installs a default theme. If you do not want to use this theme, remove it using the following commands:

```
# cd /usr/share/openstack-dashboard/openstack_dashboard/enabled
# cp _99_customization.py _999_remove_theme.py
# echo "DISABLED = True" >> _999_remove_theme.py
# systemctl restart httpd
```

For a director deployment, you will need to log in to each controller node as **heat-admin** to make the changes.

5.1. LOGO, SITE COLORS, AND STYLESHEETS

1. Copy the entire RCUE theme directory `/usr/share/openstack-dashboard/openstack_dashboard/themes/rcue` to a new location, for example `/usr/share/openstack-dashboard/openstack_dashboard/themes/mytheme`.
2. Create a new file `/etc/openstack-dashboard/local_settings.d/_12_mytheme_theme.py` and add the following line:

```
AVAILABLE_THEMES = [('mytheme', 'My Custom Theme',
                    'themes/mytheme')]
```

3. Change all paths inside `/usr/share/openstack-dashboard/openstack_dashboard/themes/mytheme/static/` replacing **rcue** with the new **mytheme** name.

To change a theme's colors, graphics, fonts, among others, edit the files in `/usr/share/openstack-dashboard/openstack_dashboard/themes/mytheme``.

4. If you deployed OpenStack with High Availability, restart the *httpd* service using pacemaker:

```
# pcs resource restart httpd-clone
```

Otherwise, run:

```
# systemctl restart httpd
```

To view your changes, reload your dashboard.

5.2. HTML TITLE

1. To set the HTML title that appears at the top of the browser window, add the following line to **local_settings.py**.

```
SITE_BRANDING = "Example, Inc. Cloud"
```

2. Restart the *httpd* server.

5.3. SITE BRANDING LINK

1. The logo also acts as a hyperlink, redirecting to **horizon:user_home** by default. To change this, add the following attribute with the desired URL target to **local_settings.py**.

```
SITE_BRANDING_LINK = "http://example.com"
```

2. Restart the *httpd* server.

5.4. HELP URL

1. By default the help URL points to <https://access.redhat.com/documentation/en/red-hat-openstack-platform>. You can change the help URL by editing the following attribute to the URL of your choice in **local_settings.py**:

```
'help_url': "http://openstack.example.com",
```

2. Restart the *httpd* server.