



# **Red Hat OpenStack Platform 13**

## **Keeping Red Hat OpenStack Platform Updated**

Performing minor updates of Red Hat OpenStack Platform



# Red Hat OpenStack Platform 13 Keeping Red Hat OpenStack Platform Updated

---

Performing minor updates of Red Hat OpenStack Platform

OpenStack Team  
rhos-docs@redhat.com

## Legal Notice

Copyright © 2018 Red Hat, Inc.

The text of and illustrations in this document are licensed by Red Hat under a Creative Commons Attribution–Share Alike 3.0 Unported license ("CC-BY-SA"). An explanation of CC-BY-SA is available at

<http://creativecommons.org/licenses/by-sa/3.0/>

. In accordance with CC-BY-SA, if you distribute this document or an adaptation of it, you must provide the URL for the original version.

Red Hat, as the licensor of this document, waives the right to enforce, and agrees not to assert, Section 4d of CC-BY-SA to the fullest extent permitted by applicable law.

Red Hat, Red Hat Enterprise Linux, the Shadowman logo, JBoss, OpenShift, Fedora, the Infinity logo, and RHCE are trademarks of Red Hat, Inc., registered in the United States and other countries.

Linux ® is the registered trademark of Linus Torvalds in the United States and other countries.

Java ® is a registered trademark of Oracle and/or its affiliates.

XFS ® is a trademark of Silicon Graphics International Corp. or its subsidiaries in the United States and/or other countries.

MySQL ® is a registered trademark of MySQL AB in the United States, the European Union and other countries.

Node.js ® is an official trademark of Joyent. Red Hat Software Collections is not formally related to or endorsed by the official Joyent Node.js open source or commercial project.

The OpenStack ® Word Mark and OpenStack logo are either registered trademarks/service marks or trademarks/service marks of the OpenStack Foundation, in the United States and other countries and are used with the OpenStack Foundation's permission. We are not affiliated with, endorsed or sponsored by the OpenStack Foundation, or the OpenStack community.

All other trademarks are the property of their respective owners.

## Abstract

This document provides the procedure to update your Red Hat OpenStack Platform 13 (Queens) environment. This document assumes you will update a containerized OpenStack Platform deployment installed on Red Hat Enterprise Linux 7.

---

## Table of Contents

<b>CHAPTER 1. INTRODUCTION .....</b>	<b>3</b>
1.1. HIGH LEVEL WORKFLOW .....	3
<b>CHAPTER 2. UPDATING YOUR CONTAINER IMAGE SOURCE .....</b>	<b>4</b>
2.1. REGISTRY METHODS .....	4
2.2. CONTAINER IMAGE PREPARATION COMMAND USAGE .....	4
2.3. CONTAINER IMAGES FOR ADDITIONAL SERVICES .....	6
2.4. USING THE RED HAT REGISTRY AS A REMOTE REGISTRY SOURCE .....	8
2.5. USING THE UNDERCLOUD AS A LOCAL REGISTRY .....	8
2.6. USING A SATELLITE SERVER AS A REGISTRY .....	10
2.7. NEXT STEPS .....	13
<b>CHAPTER 3. UPGRADING THE UNDERCLOUD .....</b>	<b>14</b>
3.1. PERFORMING A MINOR UPDATE OF AN UNDERCLOUD .....	14
3.2. UPDATING THE OVERCLOUD IMAGES .....	14
3.3. NEXT STEPS .....	15
<b>CHAPTER 4. UPDATING THE OVERCLOUD .....</b>	<b>16</b>
4.1. RUNNING THE OVERCLOUD UPDATE PREPARATION .....	16
4.2. UPDATING ALL CONTROLLER NODES .....	16
4.3. UPDATING ALL COMPUTE NODES .....	17
4.4. UPDATING ALL CEPH STORAGE NODES .....	17
4.5. FINALIZING THE UPDATE .....	18



# CHAPTER 1. INTRODUCTION

This document provides a workflow to help keep your Red Hat OpenStack Platform 13 environment updated with the latest packages and containers.

This guide provides an upgrade path through the following versions:

Old Overcloud Version	New Overcloud Version
Red Hat OpenStack Platform 13	Red Hat OpenStack Platform 13.z

## 1.1. HIGH LEVEL WORKFLOW

The following table provides an outline of the steps required for the upgrade process:

Step	Description
Obtaining new container images	Create a new environment file containing the latest container images for OpenStack Platform 13 services.
Updating the undercloud	Update the undercloud to the latest OpenStack Platform 13.z version.
Updating the overcloud	Update the overcloud to the latest OpenStack Platform 13.z version.
Updating the Ceph Storage nodes	Upgrade all Ceph Storage 3 services.
Finalize the upgrade	Run the convergence command to refresh your overcloud stack.

## CHAPTER 2. UPDATING YOUR CONTAINER IMAGE SOURCE

This chapter provides information on how to update your registry source with new overcloud container images for Red Hat OpenStack Platform.

### 2.1. REGISTRY METHODS

Red Hat OpenStack Platform supports the following registry types:

#### Remote Registry

The overcloud pulls container images directly from **registry.access.redhat.com**. This method is the easiest for generating the initial configuration. However, each overcloud node pulls each image directly from the Red Hat Container Catalog, which can cause network congestion and slower deployment. In addition, all overcloud nodes require internet access to the Red Hat Container Catalog.

#### Local Registry

The undercloud uses the **docker-distribution** service to act as a registry. This allows the director to synchronize the images from **registry.access.redhat.com** and push them to the **docker-distribution** registry. When creating the overcloud, the overcloud pulls the container images from the undercloud's **docker-distribution** registry. This method allows you to store a registry internally, which can speed up the deployment and decrease network congestion. However, the undercloud only acts as a basic registry and provides limited life cycle management for container images.



#### NOTE

The **docker-distribution** service acts separately from **docker**. **docker** is used to pull and push images to the **docker-distribution** registry and does not serve the images to the overcloud. The overcloud pulls the images from the **docker-distribution** registry.

#### Satellite Server

Manage the complete application life cycle of your container images and publish them through a Red Hat Satellite 6 server. The overcloud pulls the images from the Satellite server. This method provides an enterprise grade solution to store, manage, and deploy Red Hat OpenStack Platform containers.

Select a method from the list and continue configuring your registry details.



#### NOTE

When building for a multi-architecture cloud, the local registry option is not supported.

### 2.2. CONTAINER IMAGE PREPARATION COMMAND USAGE

This section provides an overview on how to use the **openstack overcloud container image prepare** command, including conceptual information on the command's various options.

#### Generating a Container Image Environment File for the Overcloud

One of the main uses of the **openstack overcloud container image prepare** command is to create an environment file that contains a list of images the overcloud uses. You include this file with your overcloud deployment commands, such as **openstack overcloud deploy**. The **openstack**



**overcloud container image prepare** command uses the following options for this function:

### **--output-env-file**

Defines the resulting environment file name.

The following snippet is an example of this file's contents:

```
parameter_defaults:
  DockerAodhApiImage: registry.access.redhat.com/rhosp13/openstack-aodh-
api:latest
  DockerAodhConfigImage: registry.access.redhat.com/rhosp13/openstack-
aodh-api:latest
  ...
```

## **Generating a Container Image List for Import Methods**

If you aim to import the OpenStack Platform container images to a different registry source, you can generate a list of images. The syntax of list is primarily used to import container images to the container registry on the undercloud, but you can modify the format of this list to suit other import methods, such as Red Hat Satellite 6.

The **openstack overcloud container image prepare** command uses the following options for this function:

### **--output-images-file**

Defines the resulting file name for the import list.

The following is an example of this file's contents:

```
container_images:
- imagename: registry.access.redhat.com/rhosp13/openstack-aodh-api:latest
- imagename: registry.access.redhat.com/rhosp13/openstack-aodh-
evaluator:latest
  ...
```

## **Setting the Namespace for Container Images**

Both the **--output-env-file** and **--output-images-file** options require a namespace to generate the resulting image locations. The **openstack overcloud container image prepare** command uses the following options to set the source location of the container images to pull:

### **--namespace**

Defines the namespace for the container images. This is usually a hostname or IP address with a directory.

### **--prefix**

Defines the prefix to add before the image names.

As a result, the director generates the image names using the following format:

- **[NAMESPACE]/[PREFIX][IMAGE NAME]**

## **Setting Container Image Tags**

The **openstack overcloud container image prepare** command uses the **latest** tag for each container image by default. However, you can select a specific tag for an image version using one of the following options:

**--tag-from-label**

Use the value of the specified container image labels to discover the versioned tag for every image.

**--tag**

Sets the specific tag for all images. All OpenStack Platform container images use the same tag to provide version synchronicity. When using in combination with **--tag-from-label**, the versioned tag is discovered starting from this tag.

## 2.3. CONTAINER IMAGES FOR ADDITIONAL SERVICES

The director only prepares container images for core OpenStack Platform Services. Some additional features use services that require additional container images. You enable these services with environment files. The **openstack overcloud container image prepare** command uses the following option to include environment files and their respective container images:

**-e**

Include environment files to enable additional container images.

The following table provides a sample list of additional services that use container images and their respective environment file locations within the **/usr/share/openstack-tripleo-heat-templates** directory.

Service	Environment File
Ceph Storage	<b>environments/ceph-ansible/ceph-ansible.yaml</b>
Collectd	<b>environments/services-docker/collectd.yaml</b>
Congress	<b>environments/services-docker/congress.yaml</b>
Fluentd	<b>environments/services-docker/fluentd-client.yaml</b>
OpenStack Bare Metal (ironic)	<b>environments/services-docker/ironic.yaml</b>
OpenStack Data Processing (sahara)	<b>environments/services-docker/sahara.yaml</b>
OpenStack EC2-API	<b>environments/services-docker/ec2-api.yaml</b>
OpenStack Key Manager (barbican)	<b>environments/services-docker/barbican.yaml</b>
OpenStack Load Balancing-as-a-Service (octavia)	<b>environments/services-docker/octavia.yaml</b>

Service	Environment File
OpenStack Shared File System Storage (manila)	<b>environments/services-docker/manila.yaml</b>
Open Virtual Network (OVN)	<b>environments/services-docker/neutron-ovn-dvr-ha.yaml</b>
Sensu	<b>environments/services-docker/sensu-client.yaml</b>

The next few sections provide examples of including additional services.

## Ceph Storage

If deploying a Red Hat Ceph Storage cluster with your overcloud, you need to include the **/usr/share/openstack-tripleo-heat-templates/environments/ceph-ansible/ceph-ansible.yaml** environment file. This file enables the composable containerized services in your overcloud and the director needs to know these services are enabled to prepare their images.

In addition to this environment file, you also need to define the Ceph Storage container location, which is different from the OpenStack Platform services. Use the **--set** option to set the following parameters specific to Ceph Storage:

### **--set ceph\_namespace**

Defines the namespace for the Ceph Storage container image. This functions similar to the **--namespace** option.

### **--set ceph\_image**

Defines the name of the Ceph Storage container image. Usually, this is **rhceph-3-rhel7**.

### **--set ceph\_tag**

Defines the tag to use for the Ceph Storage container image. This functions similar to the **--tag** option. When **--tag-from-label** is specified, the versioned tag is discovered starting from this tag.

The following snippet is an example that includes Ceph Storage in your container image files:

```
$ openstack overcloud container image prepare \
...
-e /usr/share/openstack-tripleo-heat-templates/environments/ceph-
ansible/ceph-ansible.yaml \
--set ceph_namespace=registry.access.redhat.com/rhceph \
--set ceph_image=rhceph-3-rhel7 \
--tag-from-label {version}-{release} \
...
```

## OpenStack Bare Metal (ironic)

If deploying OpenStack Bare Metal (ironic) in your overcloud, you need to include the **/usr/share/openstack-tripleo-heat-templates/environments/services-docker/ironic.yaml** environment file so the director can prepare the images. The following snippet is an example on how to include this environment file:

```
$ openstack overcloud container image prepare \
```

```
...
-e /usr/share/openstack-tripleo-heat-templates/environments/services-
docker/ironic.yaml \
...
```

## OpenStack Data Processing (sahara)

If deploying OpenStack Data Processing (sahara) in your overcloud, you need to include the `/usr/share/openstack-tripleo-heat-templates/environments/services-docker/sahara.yaml` environment file so the director can prepare the images. The following snippet is an example on how to include this environment file:

```
$ openstack overcloud container image prepare \
...
-e /usr/share/openstack-tripleo-heat-templates/environments/services-
docker/sahara.yaml \
...
```

## 2.4. USING THE RED HAT REGISTRY AS A REMOTE REGISTRY SOURCE

Red Hat hosts the overcloud container images on **registry.access.redhat.com**. Pulling the images from a remote registry is the simplest method because the registry is already setup and all you require is the URL and namespace of the image you aim to pull. However, during overcloud creation, the overcloud nodes all pull images from the remote repository, which can congest your external connection. If that is a problem, you can either:

- Setup a local registry
- Host the images on Red Hat Satellite 6

### Procedure

1. To pull the images directly from **registry.access.redhat.com** in your overcloud deployment, an environment file is required to specify the image parameters. The following command automatically creates this environment file:

```
(undercloud) $ openstack overcloud container image prepare \
--namespace=registry.access.redhat.com/rhosp13 \
--prefix=openstack- \
--tag-from-label {version}-{release} \
--output-env-file=/home/stack/templates/overcloud_images.yaml
```

- Use the `-e` option to include any environment files for optional services.
  - If using Ceph Storage, include the additional parameters to define the Ceph Storage container image location: `--set ceph_namespace`, `--set ceph_image`, `--set ceph_tag`.
2. This creates an **overcloud\_images.yaml** environment file, which contains image locations, on the undercloud. You include this file with your deployment.

## 2.5. USING THE UNDERCLOUD AS A LOCAL REGISTRY

You can configure a local registry on the undercloud to store overcloud container images. This method involves the following:

- The director pulls each image from the **registry.access.redhat.com**.
- The director pushes each images to the **docker-distribution** registry running on the undercloud.
- The director creates the overcloud.
- During the overcloud creation, the nodes pull the relevant images from the undercloud's **docker-distribution** registry.

This keeps network traffic for container images within your internal network, which does not congest your external network connection and can speed the deployment process.

## Procedure

1. Find the address of the local undercloud registry. The address will use the following pattern:

```
<REGISTRY IP ADDRESS>:8787
```

Use the IP address of your undercloud, which you previously set with the **local\_ip** parameter in your **undercloud.conf** file. For the commands below, the address is assumed to be **192.168.24.1:8787**.


2. Create a template to upload the the images to the local registry, and the environment file to refer to those images:

```
(undercloud) $ openstack overcloud container image prepare \
  --namespace=registry.access.redhat.com/rhosp13 \
  --push-destination=192.168.24.1:8787 \
  --prefix=openstack- \
  --tag-from-label {version}-{release} \
  --output-env-file=/home/stack/templates/overcloud_images.yaml \
  --output-images-file /home/stack/local_registry_images.yaml
```

- Use the **-e** option to include any environment files for optional services.
  - If using Ceph Storage, include the additional parameters to define the Ceph Storage container image location: **--set ceph\_namespace**, **--set ceph\_image**, **--set ceph\_tag**.
3. This creates two files:
    - **local\_registry\_images.yaml**, which contains container image information from the remote source. Use this file to pull the images from the Red Hat Container Registry (**registry.access.redhat.com**) to the undercloud.
    - **overcloud\_images.yaml**, which contains the eventual image locations on the undercloud. You include this file with your deployment. Check that both files exist.
  4. Pull the container images from **registry.access.redhat.com** to the undercloud.

```
(undercloud) $ sudo openstack overcloud container image upload \
  --config-file /home/stack/local_registry_images.yaml \
  --verbose
```

Pulling the required images might take some time depending on the speed of your network and your undercloud disk.



#### NOTE

The container images consume approximately 10 GB of disk space.

5. The images are now stored on the undercloud's **docker-distribution** registry. To view the list of images on the undercloud's **docker-distribution** registry using the following command:

```
(undercloud) $ curl http://192.0.2.5:8787/v2/_catalog | jq
.repositories[]
```

To view a list of tags for a specific image, use the **skopeo** command:

```
(undercloud) $ skopeo inspect --tls-verify=false
docker://192.0.2.5:8787/rhosp13/openstack-keystone | jq .RepoTags[]
```

To verify a tagged image, use the **skopeo** command:

```
(undercloud) $ skopeo inspect --tls-verify=false
docker://192.0.2.5:8787/rhosp13/openstack-keystone:13.0-44
```

The registry configuration is ready.

## 2.6. USING A SATELLITE SERVER AS A REGISTRY

Red Hat Satellite 6 offers registry synchronization capabilities. This provides a method to pull multiple images into a Satellite server and manage them as part of an application life cycle. The Satellite also acts as a registry for other container-enabled systems to use. For more details information on managing container images, see ["Managing Container Images"](#) in the *Red Hat Satellite 6 Content Management Guide*.

The examples in this procedure use the **hammer** command line tool for Red Hat Satellite 6 and an example organization called **ACME**. Substitute this organization for your own Satellite 6 organization.


### Procedure

1. Create a template to pull images to the local registry:

```
$ source ~/stackrc
(undercloud) $ openstack overcloud container image prepare \
  --namespace=rhosp13 \
  --prefix=openstack- \
  --output-images-file /home/stack/satellite_images \
```

- Use the **-e** option to include any environment files for optional services.

- If using Ceph Storage, include the additional parameters to define the Ceph Storage container image location: `--set ceph_namespace, --set ceph_image, --set ceph_tag`.



## NOTE

This version of the **openstack overcloud container image prepare** command targets the registry on the **registry.access.redhat.com** to generate an image list. It uses different values than the **openstack overcloud container image prepare** command used in a later step.

2. This creates a file called **satellite\_images** with your container image information. You will use this file to synchronize container images to your Satellite 6 server.
3. Remove the YAML-specific information from the **satellite\_images** file and convert it into a flat file containing only the list of images. The following **sed** commands accomplish this:

```
(undercloud) $ awk -F ':' '{if (NR!=1) {gsub("[[:space:]]", "");  
print $2}}' ~/satellite_images > ~/satellite_images_names
```

This provides a list of images that you pull into the Satellite server.

4. Copy the **satellite\_images\_names** file to a system that contains the Satellite 6 **hammer** tool. Alternatively, use the instructions in the [Hammer CLI Guide](#) to install the **hammer** tool to the undercloud.
5. Run the following **hammer** command to create a new product (**OSP13 Containers**) to your Satellite organization:

```
$ hammer product create \  
  --organization "ACME" \  
  --name "OSP13 Containers"
```

This custom product will contain our images.

6. Add the base container image to the product:

```
$ hammer repository create \  
  --organization "ACME" \  
  --product "OSP13 Containers" \  
  --content-type docker \  
  --url https://registry.access.redhat.com \  
  --docker-upstream-name rhosp13/openstack-base \  
  --name base
```

7. Add the overcloud container images from the **satellite\_images** file.

```
$ while read IMAGE; do \  
  IMAGENAME=$(echo $IMAGE | cut -d"/" -f2 | sed "s/openstack-//g" |  
  sed "s/:.*///g") ; \  
  hammer repository create \  
    --organization "ACME" \  
    --product "OSP13 Containers" \  
    --content-type docker \  
    --name $IMAGENAME
```

```
--url https://registry.access.redhat.com \
--docker-upstream-name $IMAGE \
--name $IMAGENAME ; done < satellite_images_names
```

8. Synchronize the container images:

```
$ hammer product synchronize \
--organization "ACME" \
--name "OSP13 Containers"
```

Wait for the Satellite server to complete synchronization.



#### NOTE

Depending on your configuration, **hammer** might ask for your Satellite server username and password. You can configure **hammer** to automatically login using a configuration file. See the ["Authentication"](#) section in the *Hammer CLI Guide*.

9. If your Satellite 6 server uses content views, create a new content view version to incorporate the images.
10. Check the tags available for the **base** image:

```
$ hammer docker tag list --repository "base" \
--organization "ACME" \
--product "OSP13 Containers"
```

This displays tags for the OpenStack Platform container images.

11. Return to the undercloud and generate an environment file for the images on your Satellite server. The following is an example command for generating the environment file:

```
(undercloud) $ openstack overcloud container image prepare \
--namespace=satellite6.example.com:5000 \
--prefix=acme-osp13_containers- \
--tag-from-label {version}-{release} \
--output-env-file=/home/stack/templates/overcloud_images.yaml
```



#### NOTE

This version of the **openstack overcloud container image prepare** command targets the Satellite server. It uses different values than the **openstack overcloud container image prepare** command used in a previous step.

When running this command, include the following data:

- **--namespace** - The URL and port of the registry on the Satellite server. The default registry port on Red Hat Satellite is 5000. For example, **--namespace=satellite6.example.com:5000**.
- **--prefix=** - The prefix is based on a Satellite 6 convention. This differs depending on whether you use content views:



- If you use content views, the structure is **[org] - [environment] - [content view] - [product] - .** For example: **acme-production-myosp13-osp13\_containers-.**
- If you do not use content views, the structure is **[org] - [product] - .** For example: **acme-osp13\_containers-.**
- **--tag-from-label {version}-{release}** - Identifies the latest tag for each image.
- **-e** - Include any environment files for optional services.
- **--set ceph\_namespace, --set ceph\_image, --set ceph\_tag** - If using Ceph Storage, include the additional parameters to define the Ceph Storage container image location. Note that **ceph\_image** now includes a Satellite-specific prefix. This prefix is the same value as the **--prefix** option. For example:

```
--set ceph_image=acme-osp13_containers-rhceph-3-rhel7
```

This ensures the overcloud uses the Ceph container image using the Satellite naming convention.

12. This creates an **overcloud\_images.yaml** environment file, which contains the image locations on the Satellite server. You include this file with your deployment.

The registry configuration is ready.

## 2.7. NEXT STEPS

You now have a new **overcloud\_images.yaml** environment file that contains a list of your container image sources. Include this file with all future upgrade and deployment operations.

You can now prepare the overcloud for the update.

## CHAPTER 3. UPGRADING THE UNDERCLOUD

This process upgrades the undercloud and its overcloud images to **Red Hat OpenStack Platform 13**.

### 3.1. PERFORMING A MINOR UPDATE OF AN UNDERCLOUD

The director provides commands to update the packages on the undercloud node. This allows you to perform a minor update within the current version of your OpenStack Platform environment.

#### Procedure

1. Log into the director as the **stack** user.
2. Update the **python-tripleoclient** package and its dependencies to ensure you have the latest scripts for the minor version update:

```
$ sudo yum update -y python-tripleoclient
```

3. The director uses the **openstack undercloud upgrade** command to update the Undercloud environment. Run the command:

```
$ openstack undercloud upgrade
```

4. Wait until the undercloud upgrade process completes.
5. Reboot the undercloud to update the operating system's kernel and other system packages:

```
$ sudo reboot
```

6. Wait until the node boots.

### 3.2. UPDATING THE OVERCLOUD IMAGES

You need to replace your current overcloud images with new versions. The new images ensure the director can introspect and provision your nodes using the latest version of OpenStack Platform software.

#### Prerequisites

- You have updated the undercloud to the latest version.

#### Procedure

1. Remove any existing images from the **images** directory on the **stack** user's home (**/home/stack/images**):

```
$ rm -rf ~/images/*
```

2. Extract the archives:

```
$ cd ~/images
$ for i in /usr/share/rhosp-director-images/overcloud-full-latest-13.0.tar /usr/share/rhosp-director-images/ironic-python-agent-
```

```
latest-13.0.tar; do tar -xvf $i; done
$ cd ~
```

3. Import the latest images into the director:


```
$ openstack overcloud image upload --update-existing --image-path
/home/stack/images/
```

4. Configure your nodes to use the new images:

```
$ openstack overcloud node configure $(openstack baremetal node list
-c UUID -f value)
```

5. Verify the existence of the new images:

```
$ openstack image list
$ ls -l /httpboot
```



### IMPORTANT

When deploying overcloud nodes, ensure the Overcloud image version corresponds to the respective Heat template version. For example, only use the OpenStack Platform 13 images with the OpenStack Platform 13 Heat templates.

## 3.3. NEXT STEPS

The undercloud upgrade is complete. You can now prepare the overcloud for the upgrade.

## CHAPTER 4. UPDATING THE OVERCLOUD

This process updates the overcloud.

### Prerequisites

- You have updated the undercloud to the latest version.

### 4.1. RUNNING THE OVERCLOUD UPDATE PREPARATION

The update requires running **openstack overcloud update prepare** command, which performs the following tasks:

- Updates the overcloud plan to OpenStack Platform 13
- Prepares the nodes for the update

### Procedure

1. Source the **stackrc** file:

```
$ source ~/stackrc
```

2. Run the update preparation command:

```
$ openstack overcloud update prepare \  
  --templates \  
  -e /home/stack/templates/overcloud_images.yaml \  
  -e <ENVIRONMENT FILE>
```

Include the following options relevant to your environment:

- Custom configuration environment files (**-e**)
  - The environment file with your new container image locations (**-e**). Note that the update command might display a warning about using the **--container-registry-file**. You can ignore this warning as this option is deprecated in favor of using **-e** for the container image environment file.
  - If applicable, your custom roles (**roles\_data**) file (**--roles-file**)
  - If applicable, your composable network (**network\_data**) file (**--networks-file**)
3. Wait until the update preparation completes.

### 4.2. UPDATING ALL CONTROLLER NODES

This process updates all the Controller nodes to the latest OpenStack Platform 13 version. The process involves running the **openstack overcloud update run** command and including the **--nodes Controller** option to restrict operations to the Controller nodes only.

### Procedure

1. Source the **stackrc** file:

```
$ source ~/stackrc
```

2. Run the update command:

```
$ openstack overcloud update run --nodes Controller
```

3. Wait until the Controller node update completes.

## 4.3. UPDATING ALL COMPUTE NODES

This process updates all Compute nodes to the latest OpenStack Platform 13 version. The process involves running the **openstack overcloud update run** command and including the **--nodes Compute** option to restrict operations to the Compute nodes only.

### Procedure

1. Source the **stackrc** file:

```
$ source ~/stackrc
```

2. Run the update command:

```
$ openstack overcloud update run --nodes Compute
```

3. Wait until the Compute node update completes.

## 4.4. UPDATING ALL CEPH STORAGE NODES

This process updates the Ceph Storage nodes. The process involves:

- Running the **openstack overcloud update run** command and including the **--nodes CephStorage** option to restrict operations to the Ceph Storage nodes only.
- Running the **openstack overcloud ceph-upgrade run** command to perform an update to a containerized Red Hat Ceph Storage 3 cluster.

### Procedure

1. Source the **stackrc** file:

```
$ source ~/stackrc
```

2. Run the update command:

```
$ openstack overcloud update run --nodes CephStorage
```

3. Wait until the node update completes.

4. Run the Ceph Storage update command. For example:

```
■
```

```
$ openstack overcloud ceph-upgrade run \
  --templates \
  -e <ENVIRONMENT FILE> \
  -e /home/stack/templates/overcloud_images.yaml
```

Include the following options relevant to your environment:

- Custom configuration environment files (**-e**)
- The environment file with your container image locations (**-e**). Note that the update command might display a warning about using the **--container-registry-file**. You can ignore this warning as this option is deprecated in favor of using **-e** for the container image environment file.
- If applicable, your custom roles (**roles\_data**) file (**--roles-file**)
- If applicable, your composable network (**network\_data**) file (**--networks-file**)

5. Wait until the Ceph Storage node update completes.

## 4.5. FINALIZING THE UPDATE

The update requires a final step to update the overcloud stack. This ensures the stack's resource structure aligns with a regular deployment of OpenStack Platform 13 and allows you to perform standard **openstack overcloud deploy** functions in the future.

### Procedure

1. Source the **stackrc** file:

```
$ source ~/stackrc
```

2. Run the update finalization command:

```
$ openstack overcloud update converge \
  --templates \
  -e <ENVIRONMENT FILE>
```

Include the following options relevant to your environment:

- Custom configuration environment files (**-e**).
- If applicable, your custom roles (**roles\_data**) file (**--roles-file**)
- If applicable, your composable network (**network\_data**) file (**--networks-file**)

3. Wait until the update finalization completes.