



## Red Hat Satellite 6.10

### Hammer Cheat Sheet

Hammer CLI Cheat Sheet for Red Hat Satellite



# Red Hat Satellite 6.10 Hammer Cheat Sheet

---

Hammer CLI Cheat Sheet for Red Hat Satellite

Red Hat Satellite Documentation Team

[satellite-doc-list@redhat.com](mailto:satellite-doc-list@redhat.com)

## Legal Notice

Copyright © 2021 Red Hat, Inc.

The text of and illustrations in this document are licensed by Red Hat under a Creative Commons Attribution–Share Alike 3.0 Unported license ("CC-BY-SA"). An explanation of CC-BY-SA is available at

<http://creativecommons.org/licenses/by-sa/3.0/>

. In accordance with CC-BY-SA, if you distribute this document or an adaptation of it, you must provide the URL for the original version.

Red Hat, as the licensor of this document, waives the right to enforce, and agrees not to assert, Section 4d of CC-BY-SA to the fullest extent permitted by applicable law.

Red Hat, Red Hat Enterprise Linux, the Shadowman logo, the Red Hat logo, JBoss, OpenShift, Fedora, the Infinity logo, and RHCE are trademarks of Red Hat, Inc., registered in the United States and other countries.

Linux<sup>®</sup> is the registered trademark of Linus Torvalds in the United States and other countries.

Java<sup>®</sup> is a registered trademark of Oracle and/or its affiliates.

XFS<sup>®</sup> is a trademark of Silicon Graphics International Corp. or its subsidiaries in the United States and/or other countries.

MySQL<sup>®</sup> is a registered trademark of MySQL AB in the United States, the European Union and other countries.

Node.js<sup>®</sup> is an official trademark of Joyent. Red Hat is not formally related to or endorsed by the official Joyent Node.js open source or commercial project.

The OpenStack<sup>®</sup> Word Mark and OpenStack logo are either registered trademarks/service marks or trademarks/service marks of the OpenStack Foundation, in the United States and other countries and are used with the OpenStack Foundation's permission. We are not affiliated with, endorsed or sponsored by the OpenStack Foundation, or the OpenStack community.

All other trademarks are the property of their respective owners.

## Abstract

This document contains Hammer CLI commands for Red Hat Satellite.

---

## Table of Contents

CHAPTER 1. INTRODUCTION .....	3
CHAPTER 2. GENERAL INFORMATION .....	4
CHAPTER 3. ORGANIZATIONS, LOCATIONS, AND REPOSITORIES .....	5
CHAPTER 4. CONTENT LIFE CYCLES .....	7
CHAPTER 5. PROVISIONING ENVIRONMENTS .....	9
CHAPTER 6. ACTIVATION KEYS .....	11
CHAPTER 7. USERS AND PERMISSIONS .....	12
CHAPTER 8. ERRATA .....	13
CHAPTER 9. HOSTS .....	14
CHAPTER 10. TASKS .....	16



## CHAPTER 1. INTRODUCTION

Hammer is a command-line tool provided with Red Hat Satellite 6. You can use Hammer to configure and manage a Red Hat Satellite Server by using either CLI commands or shell script automation. The following cheat sheet provides a condensed overview of essential Hammer commands.

For more information about Hammer, see the [Red Hat Hammer CLI Guide](#).

## CHAPTER 2. GENERAL INFORMATION

Table 2.1. General Information

Subcommand	Description and tasks
<b>--help</b>	Display hammer commands and options, append after a subcommand to get more information
<b>org</b>	<p>The setting is organization-specific, append <b>--organization <i>org_name</i></b>, or set default organization with:</p> <pre>hammer defaults add \ --param-name <i>organization_id</i> \ --param-value <i>org_ID</i></pre>
<b>loc</b>	<p>The setting is location-specific, append <b>--location <i>loc_name</i></b>, or set default location with:</p> <pre>hammer defaults add \ --param-name <i>location_id</i> \ --param-value <i>loc_ID</i></pre>

**Note:** This cheat sheet assumes saved credentials in `~/.hammer/cli_config.yml`. For more information, see [Authentication](#) in the [Red Hat Hammer CLI Guide](#).



## CHAPTER 3. ORGANIZATIONS, LOCATIONS, AND REPOSITORIES

Table 3.1. Organizations, Locations, and Repositories

Subcommand	Description and tasks
<b>organization</b>	Create an organization: <pre data-bbox="555 479 970 577">hammer organization create \ --name <i>org_name</i></pre> List organizations: <pre data-bbox="555 680 911 725">hammer organization list</pre>
<b>location</b>	See the options for organization
<b>subscription</b> org	Upload a subscription manifest: <pre data-bbox="555 943 975 1025">hammer subscription upload \ --file path</pre>
<b>repository-set</b> org	Enable a repository: <pre data-bbox="555 1160 995 1339">hammer repository-set enable \ --product <i>prod_name</i> \ --basearch <i>base_arch</i> \ --releasever <i>rel_v</i> \ --name <i>repo_name</i></pre>

Subcommand	Description and tasks
<b>repository</b> org	<p>Synchronize a repository:</p> <pre>hammer repository synchronize \ --product <i>prod_name</i> \ --name <i>repo_name</i></pre> <p>Create a custom repository:</p> <pre>hammer repository create \ --product <i>prod_name</i> \ --content-type <i>cont_type</i> \ --publish-via-http true \ --url <i>repo_url</i> \ --name <i>repo_name</i></pre> <p>Upload content to a custom repository:</p> <pre>hammer repository upload-content \ --product <i>prod_name</i> \ --id <i>repo_id</i> \ --path <i>path_to_dir</i></pre>

## CHAPTER 4. CONTENT LIFE CYCLES

Table 4.1. Content Life Cycles

Subcommand	Description and tasks
<b>lifecycle-environment</b> org	Create a life cycle environment: <pre>hammer lifecycle-environment create \ --name <i>env_name</i> --description <i>env_desc</i> --prior <i>prior_env_name</i></pre> List life cycle environments: <pre>hammer lifecycle-environment list</pre>

Subcommand	Description and tasks
<b>content-view</b> org	<p>Create a content view:</p> <pre>hammer content-view create \ --name <i>cv_n</i> \ --repository-ids <i>repo_ID1,...</i> \ --description <i>cv_description</i></pre> <p>Add repositories to a content view:</p> <pre>hammer content-view add-repository \ --name <i>cv_n</i> \ --repository-id <i>repo_ID</i></pre> <p>Add Puppet modules to a content view:</p> <pre>hammer content-view puppet-module add \ --content-view <i>cv_n</i> \ --name <i>module_name</i></pre> <p>Publishing a content view:</p> <pre>hammer content-view publish \ --id <i>cv_ID</i></pre> <p>Promoting a content view:</p> <pre>hammer content-view version promote \ --content-view <i>cv_n</i> \ --to-lifecycle-environment <i>env_name</i></pre> <p>Incremental update of a content view:</p> <pre>hammer content-view version incremental-update \ --content-view-version-id <i>cv_ID</i> \ --packages <i>pkg_n1,...</i> \ --lifecycle-environment-ids <i>env_ID1,...</i></pre>

## CHAPTER 5. PROVISIONING ENVIRONMENTS

Table 5.1. Provisioning Environments

Subcommand	Description and tasks
<b>domain</b>	Create a domain: <pre>hammer domain create \ --name <i>domain_name</i></pre>
<b>subnet</b> org loc	Add a subnet: <pre>hammer subnet create \ --name <i>subnet_name</i> \ --organization-ids <i>org_ID1</i>,... \ --location-ids <i>loc_ID1</i>,... \ --domain-ids <i>dom_ID1</i>,... \ --boot-mode <i>boot_mode</i> \ --network <i>network_address</i> \ --mask <i>netmask</i> --ipam <i>ipam</i></pre>
<b>compute-resource</b> org loc	Create a compute resource: <pre>hammer compute-resource create \ --name <i>cr_name</i> \ --organization-ids <i>org_ID1</i>,... \ --location-ids <i>loc_ID1</i>,... \ --provider <i>provider_name</i></pre>
<b>medium</b>	Add an installation medium: <pre>hammer medium create \ --name <i>med_name</i> \ --path <i>path_to_medium</i></pre>
<b>partition-table</b>	Add a partition table: <pre>hammer partition-table create \ --name <i>tab_name</i> \ --path <i>path_to_file</i> \ --os-family <i>os_family</i></pre>
<b>template</b>	Add a provisioning template: <pre>hammer template create \ --name <i>tmp_name</i> \ --file <i>path_to_template</i></pre>

Subcommand	Description and tasks
<b>os</b>	<p>Add an operating system:</p> <pre>hammer os create \ --name <i>os_name</i> \ --version <i>version_num</i></pre>

## CHAPTER 6. ACTIVATION KEYS

Table 6.1. Activation Keys

Subcommand	Description and tasks
<b>activation-key org</b>	<p>Create an activation key:</p> <pre>hammer activation-key create \ --name <i>ak_name</i> \ --content-view <i>cv_n</i> \ --lifecycle-environment <i>lc_name</i></pre> <p>Add a subscription to the activation key:</p> <pre>hammer activation-key add-subscription \ --id <i>ak_ID</i> \ --subscription-id <i>sub_ID</i></pre>

## CHAPTER 7. USERS AND PERMISSIONS

Table 7.1. Users and Permissions

Subcommand	Description and tasks
<b>user</b> <b>org</b>	<p>Create a user:</p> <pre>hammer user create \ --login <i>user_name</i> \ --mail <i>user_mail</i> \ --auth-source-id 1 \ --organization-ids <i>org_ID1,org_ID2,...</i></pre> <p>Add a role to a user:</p> <pre>hammer user add-role \ --id <i>user_id</i> \ --role <i>role_name</i></pre>
<b>user-group</b>	<p>Create a user group:</p> <pre>hammer user-group create \ --name <i>ug_name</i></pre> <p>Add a role to a user group:</p> <pre>hammer user-group add-role \ --id <i>ug_id</i> \ --role <i>role_name</i></pre>
<b>role</b>	<p>Create a role:</p> <pre>hammer role create \ --name <i>role_name</i></pre>
<b>filter</b>	<p>Create a filter and add it to a role:</p> <pre>hammer filter create \ --role <i>role_name</i> \ --permission-ids <i>perm_ID1,perm_ID2,...</i></pre>



## CHAPTER 8. ERRATA

Table 8.1. Errata

Subcommand	Description and tasks
<b>erratum</b>	<p>List errata:</p> <pre>hammer erratum list</pre> <p>Find erratum by CVE:</p> <pre>hammer erratum list --cve CVE</pre> <p>Inspect erratum:</p> <pre>hammer erratum info --id <i>err_ID</i></pre>
<b>host</b>	<p>List errata applicable to a host:</p> <pre>hammer host errata list \ --host <i>host_name</i></pre> <p>Apply errata to a host:</p> <pre>hammer host errata apply \ --host <i>host_name</i> \ --errata-ids <i>err_ID1,err_ID2,...</i></pre>

## CHAPTER 9. HOSTS

Table 9.1. Hosts

Subcommand	Description and tasks
<b>hostgroup</b> org loc	<p>Create a host group:</p> <pre>hammer hostgroup create \   --name <i>hg_name</i> \   --puppet-environment <i>env_name</i> \   --architecture <i>arch_name</i> \   --domain <i>domain_name</i> \   --subnet <i>subnet_name</i> \   --puppet-proxy <i>proxy_name</i> \   --puppet-ca-proxy <i>ca-proxy_name</i> \   --operatingsystem <i>os_name</i> \   --partition-table <i>table_name</i> \   --medium <i>medium_name</i> \   --organization-ids <i>org_ID1</i>,... \   --location-ids <i>loc_ID1</i>,...</pre> <p>Add an activation key to a host group:</p> <pre>hammer hostgroup set-parameter \   --hostgroup "hg_name" \   --name "kt_activation_keys" \   --value <i>key_name</i></pre>
<b>host</b> org loc	<p>Create a host (inheriting parameters from a host group):</p> <pre>hammer host create \   --name <i>host_name</i> \   --hostgroup <i>hg_name</i> \   --interface="primary=true, \   mac=<i>mac_addr</i>, ip=<i>ip_addr</i>, \   provision=true" \   --organization-id <i>org_ID</i> \   --location-id <i>loc_ID</i> \   --ask-root-password yes</pre>
<b>job-template</b>	<p>Add a job template for remote execution:</p> <pre>hammer job-template create \   --file <i>path</i> \   --name <i>template_name</i> \   --provider-type SSH \   --job-category <i>category_name</i></pre>

Subcommand	Description and tasks
<b>job-invocation</b>	<p data-bbox="555 219 794 250">Invoke a remote job:</p> <pre data-bbox="555 280 997 443">hammer job-invocation create \ --job-template <i>template_name</i> \ --inputs key1=<i>value</i>,... \ --search-query <i>query</i></pre> <p data-bbox="555 481 833 512">Monitor the remote job:</p> <pre data-bbox="555 542 997 629">hammer job-invocation output \ --id <i>job_id</i> --host <i>host_name</i></pre>

## CHAPTER 10. TASKS

Table 10.1. Tasks

Subcommand	Description and tasks
<b>task</b>	List all tasks:  hammer task list Monitor progress of a running task: hammer task progress \ --id <i>task_ID</i>