



# Red Hat Service Interconnect 1.4

## Installation

Installing the CLI, or the controller, or the Operator



# Red Hat Service Interconnect 1.4 Installation

---

Installing the CLI, or the controller, or the Operator

## Legal Notice

Copyright © 2023 Red Hat, Inc.

The text of and illustrations in this document are licensed by Red Hat under a Creative Commons Attribution–Share Alike 3.0 Unported license ("CC-BY-SA"). An explanation of CC-BY-SA is available at

<http://creativecommons.org/licenses/by-sa/3.0/>

. In accordance with CC-BY-SA, if you distribute this document or an adaptation of it, you must provide the URL for the original version.

Red Hat, as the licensor of this document, waives the right to enforce, and agrees not to assert, Section 4d of CC-BY-SA to the fullest extent permitted by applicable law.

Red Hat, Red Hat Enterprise Linux, the Shadowman logo, the Red Hat logo, JBoss, OpenShift, Fedora, the Infinity logo, and RHCE are trademarks of Red Hat, Inc., registered in the United States and other countries.

Linux<sup>®</sup> is the registered trademark of Linus Torvalds in the United States and other countries.

Java<sup>®</sup> is a registered trademark of Oracle and/or its affiliates.

XFS<sup>®</sup> is a trademark of Silicon Graphics International Corp. or its subsidiaries in the United States and/or other countries.

MySQL<sup>®</sup> is a registered trademark of MySQL AB in the United States, the European Union and other countries.

Node.js<sup>®</sup> is an official trademark of Joyent. Red Hat is not formally related to or endorsed by the official Joyent Node.js open source or commercial project.

The OpenStack<sup>®</sup> Word Mark and OpenStack logo are either registered trademarks/service marks or trademarks/service marks of the OpenStack Foundation, in the United States and other countries and are used with the OpenStack Foundation's permission. We are not affiliated with, endorsed or sponsored by the OpenStack Foundation, or the OpenStack community.

All other trademarks are the property of their respective owners.

## Abstract

This guide describes how to install Red Hat Service Interconnect 1.4. Red Hat Service Interconnect is a Red Hat build of the open source Skupper project.

---


## Table of Contents

<b>CHAPTER 1. INSTALLING THE SKUPPER CLI</b> .....	<b>3</b>
<b>CHAPTER 2. INSTALLING THE OPERATOR</b> .....	<b>5</b>
2.1. INSTALLING THE OPERATOR FOR ALL NAMESPACES USING THE CLI	5
2.2. INSTALLING THE OPERATOR FOR A SINGLE NAMESPACE USING THE CLI	6
2.3. INSTALLING THE OPERATOR USING THE OPENSIFT CONSOLE	7
<b>CHAPTER 3. UPGRADING THE SKUPPER CLI AND SITES</b> .....	<b>9</b>
<b>CHAPTER 4. UPGRADING THE RED HAT SERVICE INTERCONNECT OPERATOR AND SITES</b> .....	<b>10</b>
<b>CHAPTER 5. INSTALLING THE POLICY SYSTEM</b> .....	<b>11</b>
<b>CHAPTER 6. USING YOUR SUBSCRIPTION</b> .....	<b>12</b>
6.1. ACCESSING YOUR ACCOUNT	12
6.2. ACTIVATING A SUBSCRIPTION	12
6.3. REGISTERING YOUR SYSTEM FOR PACKAGES	12
<b>APPENDIX A. YAML FOR THE SKUPPER POLICY CRD</b> .....	<b>13</b>
<b>APPENDIX B. ABOUT SERVICE INTERCONNECT DOCUMENTATION</b> .....	<b>15</b>
MAKING OPEN SOURCE MORE INCLUSIVE	15



# CHAPTER 1. INSTALLING THE SKUPPER CLI

The Skupper CLI provides a method to create both Kubernetes and Podman sites.



## NOTE

Podman sites are a Technology Preview feature as described in [Release Notes](#)

## Prerequisites

- Your subscription has been activated and your system is registered. For more information about using the Customer Portal to activate your Red Hat subscription and register your system for packages, see [Chapter 6, Using your subscription](#).

## Procedure

1. Subscribe to the required repositories:

### Red Hat Enterprise Linux 8

```
$ sudo subscription-manager repos --enable=service-interconnect-1-for-rhel-8-x86_64-rpms
```

### Red Hat Enterprise Linux 9

```
$ sudo subscription-manager repos --enable=service-interconnect-1-for-rhel-9-x86_64-rpms
```

2. Use the **yum** or **dnf** command to install the **skupper** command:

```
$ sudo dnf install skupper-cli
```

3. If you want to run **skupper** to create a podman site on RHEL 8, you need to configure podman to use **netavark** if it is not already configured:

- a. Check if **netavark** is configured as the podman network backend:

```
$ podman info | grep networkBackend
```

- b. If **netavark** is not listed as the backend, install it:

```
$ sudo dnf install netavark
```

- c. Configure podman to use **netavark** by making sure the following lines exist in the **/etc/containers/containers.conf** file:

```
[network]
network_backend = "netavark"
```

- d. Verify the new configuration by repeating step a.

## Additional information

- See [Getting Started](#) for instructions about creating a site.

- Use **man containers.conf** to view more information about podman configuration.



## CHAPTER 2. INSTALLING THE OPERATOR

The Red Hat Service Interconnect Operator creates and manages sites in OpenShift.



### NOTE

The Red Hat Service Interconnect Operator is supported only on OpenShift 4. Installing an Operator requires administrator-level privileges for your cluster.

## 2.1. INSTALLING THE OPERATOR FOR ALL NAMESPACES USING THE CLI

The steps in this section show how to use the **oc** command to install and deploy the latest version of the Red Hat Service Interconnect Operator in a given OpenShift cluster. Installing the operator for all namespaces allows you create a site in any namespace. See [Getting started with the OpenShift CLI](#) for more information about the **oc** command.

### Prerequisites

- Access to an OpenShift cluster using a **cluster-admin** account. See [Release Notes](#) for supported OpenShift versions.

### Procedure

1. Log in to OpenShift as a cluster administrator. For example:

```
$ oc login -u system:admin
```

2. Complete the steps described in [Red Hat Container Registry Authentication](#) .
3. Create a file named **subscription-all.yaml** with the following:

```
apiVersion: operators.coreos.com/v1alpha1
kind: Subscription
metadata:
  name: skupper-operator
  namespace: openshift-operators
spec:
  channel: alpha
  installPlanApproval: Automatic
  name: skupper-operator
  source: redhat-operators
  sourceNamespace: openshift-marketplace
  startingCSV: skupper-operator.v1.4.2-rh-2
```



## NOTE

If you do not specify **startingCSV**, the subscription defaults to the latest operator version.

If you specify **installPlanApproval** as **Manual**, sites are not automatically upgraded to the latest version of Service Interconnect. See [Chapter 4, Upgrading the Red Hat Service Interconnect Operator and sites](#) for information on manually upgrading sites.

4. Apply the subscription YAML:

```
$ oc apply -f subscription-all.yaml
```

### Additional information

- See [Getting Started](#) for instructions about creating a site.

## 2.2. INSTALLING THE OPERATOR FOR A SINGLE NAMESPACE USING THE CLI

The steps in this section show how to use the **oc** command to install and deploy the latest version of the Red Hat Service Interconnect Operator in a given OpenShift cluster. Installing the operator for a single namespaces allows you create a site in the specified namespace. See [Getting started with the OpenShift CLI](#) for more information about the **oc** command.

### Prerequisites

- Access to an OpenShift cluster using a **cluster-admin** account. See [Release Notes](#) for supported OpenShift versions.

### Procedure

1. Log in to OpenShift as a cluster administrator. For example:

```
$ oc login -u system:admin
```

2. Complete the steps described in [Red Hat Container Registry Authentication](#) .
3. Create an Operator group in the namespace where you want to create a site:
  - a. Create a file named **operator-group.yaml** with the following:

```
kind: OperatorGroup
apiVersion: operators.coreos.com/v1
metadata:
  name: skupper-operator
  namespace: my-namespace
spec:
  targetNamespaces:
  - my-namespace
```

where **my-namespace** is the name of the namespace you want to create the site.

b. Apply the Operator group YAML:

```
$ oc apply -f operator-group.yaml
```

4. Create a file named **subscription-myns.yaml** with the following:

```
apiVersion: operators.coreos.com/v1alpha1
kind: Subscription
metadata:
  name: skupper-operator
  namespace: my-namespace
spec:
  channel: alpha
  installPlanApproval: Automatic
  name: skupper-operator
  source: redhat-operators
  sourceNamespace: openshift-marketplace
  startingCSV: skupper-operator.v1.4.2-rh-2
```

where **my-namespace** is the name of the namespace you want to create the site.



#### NOTE

If you do not specify **startingCSV**, the subscription defaults to the latest operator version.

If you specify **installPlanApproval** as **Manual**, sites are not automatically upgraded to the latest version of Service Interconnect. See [Chapter 4, Upgrading the Red Hat Service Interconnect Operator and sites](#) for information on manually upgrading sites.

5. Apply the subscription YAML:

```
$ oc apply -f subscription-myns.yaml
```

#### Additional information

- See [Getting Started](#) for instructions about creating a site.

## 2.3. INSTALLING THE OPERATOR USING THE OPENSIFT CONSOLE

The procedures in this section show how to use the OperatorHub from the OpenShift console to install and deploy the latest version of the Red Hat Service Interconnect Operator in a given OpenShift namespace.

#### Prerequisites

- Access to an OpenShift cluster using a **cluster-admin** account. See [Release Notes](#) for supported OpenShift versions.

#### Procedure

1. In the OpenShift web console, navigate to **Operators → OperatorHub**.

2. Choose **Red Hat Service Interconnect Operator** from the list of available Operators, and then click **Install**.
3. On the **Operator Installation** page, two **Installation mode** options are available:
  - **All namespaces on the cluster**
  - **A specific namespace on the cluster**  
For this example, choose **A specific namespace on the cluster**
4. Choose an **Update approval** option.  
By default, **Automatic** approval is selected, and sites will upgrade to the latest version of Service Interconnect. If you choose **Manual** approval, sites will not be automatically upgraded to the latest version of Service Interconnect. See [Chapter 4, Upgrading the Red Hat Service Interconnect Operator and sites](#) for information on manually upgrading sites.
5. Select the namespace into which you want to install the Operator, and then click **Install**.  
The **Installed Operators** page appears displaying the status of the Operator installation.
6. Verify that the Red Hat Service Interconnect Operator is displayed and wait until the **Status** changes to **Succeeded**.
7. If the installation is not successful, troubleshoot the error:
  - a. Click **Red Hat Service Interconnect Operator** on the **Installed Operators** page.
  - b. Select the **Subscription** tab and view any failures or errors.

For more information about installing Operators, see the [OpenShift Documentation](#)

#### Additional information

- See [Getting Started](#) for instructions about creating a site.

## CHAPTER 3. UPGRADING THE SKUPPER CLI AND SITES

Upgrading sites requires the latest version of the Skupper CLI.



### NOTE

Update all sites to ensure the same version of Service Interconnect is running across your service network. You can expect some minimal downtime during the update process.

### Procedure

1. Upgrade the **skupper** CLI:

```
$ dnf upgrade service-interconnect-1-for-rhel-8-x86_64-rpms
```

2. Upgrade each site:

- a. Set the context to the site you want to upgrade.
- b. Run the upgrade command:

```
$ skupper update
```

## CHAPTER 4. UPGRADING THE RED HAT SERVICE INTERCONNECT OPERATOR AND SITES

If you chose automatic updates when installing the Red Hat Service Interconnect Operator, sites are upgraded when a new version of Service Interconnect is available. If you choose manual updates, complete this procedure to upgrade your sites.

### Procedure

1. Log into the OpenShift console.
2. Navigate to the **Installed Operators** page.
3. If **Upgrade available** is displayed as the **Status** for the Red Hat Service Interconnect Operator, click that text.
4. On the **InstallPlan details** page, click **Preview InstallPlan**.
5. Click **Approve** to upgrade sites.

## CHAPTER 5. INSTALLING THE POLICY SYSTEM

Installing the Skupper policy system on a cluster allows you control how Skupper is used on the cluster.



### NOTE

Applying the policy system in a cluster without specific policy rules prohibits site linking and service exposure. If you are installing the policy system on a cluster where there are existing sites, you must create policies before installing the policy system to avoid disruption.

### Prerequisites

- Access to a Kubernetes cluster with **cluster-admin** privileges.
- The Red Hat Service Interconnect Operator is installed

### Procedure

1. Log into your cluster.
2. Deploy the policy CRD:

```
$ kubectl apply -f skupper_cluster_policy_crd.yaml
```

```
customresourcedefinition.apiextensions.k8s.io/skupperclusterpolicies.skupper.io created  
clusterrole.rbac.authorization.k8s.io/skupper-service-controller created
```

where the contents of **skupper\_cluster\_policy\_crd.yaml** is specified in the [Appendix A, YAML for the Skupper policy CRD](#) appendix.

### Additional information

See [Securing a service network using policies](#) for more information about using policies.

## CHAPTER 6. USING YOUR SUBSCRIPTION

Red Hat Service Interconnect is provided through a software subscription. To manage your subscriptions, access your account at the Red Hat Customer Portal.

### 6.1. ACCESSING YOUR ACCOUNT

#### Procedure

1. Go to [access.redhat.com](https://access.redhat.com).
2. If you do not already have an account, create one.
3. Log in to your account.

### 6.2. ACTIVATING A SUBSCRIPTION

#### Procedure

1. Go to [access.redhat.com](https://access.redhat.com).
2. Navigate to **My Subscriptions**.
3. Navigate to **Activate a subscription** and enter your 16-digit activation number.

### 6.3. REGISTERING YOUR SYSTEM FOR PACKAGES

To install RPM packages for this product on Red Hat Enterprise Linux, your system must be registered. If you are using downloaded release files, this step is not required.

#### Procedure

1. Go to [access.redhat.com](https://access.redhat.com).
2. Navigate to **Registration Assistant**.
3. Select your OS version and continue to the next page.
4. Use the listed command in your system terminal to complete the registration.

For more information about registering your system, see one of the following resources:

- [Red Hat Enterprise Linux 8 - Registering the system and managing subscriptions](#)
- [Red Hat Enterprise Linux 9 - Registering the system and managing subscriptions](#)



## APPENDIX A. YAML FOR THE SKUPPER POLICY CRD

The policy system allows a cluster administrator restrict Skupper usage on a cluster. It is not required for typical Skupper usage.

The following YAML applies the Skupper policy CRD to a cluster.

```

---
apiVersion: apiextensions.k8s.io/v1
kind: CustomResourceDefinition
metadata:
  name: skupperclusterpolicies.skupper.io
spec:
  group: skupper.io
  versions:
  - name: v1alpha1
    served: true
    storage: true
    schema:
      openAPIV3Schema:
        type: object
        properties:
          spec:
            type: object
            properties:
              namespaces:
                type: array
                items:
                  type: string
              allowIncomingLinks:
                type: boolean
              allowedOutgoingLinksHostnames:
                type: array
                items:
                  type: string
              allowedExposedResources:
                type: array
                items:
                  type: string
              allowedServices:
                type: array
                items:
                  type: string
      scope: Cluster
      names:
        plural: skupperclusterpolicies
        singular: skupperclusterpolicy
        kind: SkupperClusterPolicy
---
apiVersion: rbac.authorization.k8s.io/v1
kind: ClusterRole
metadata:
  labels:
    application: skupper-service-controller
  name: skupper-service-controller
rules:

```

- apiGroups:
  - skupper.io
- resources:
  - skupperclusterpolicies
- verbs:
  - get
  - list
  - watch
- apiGroups:
  - ""
- resources:
  - namespaces
- verbs:
  - get

## APPENDIX B. ABOUT SERVICE INTERCONNECT DOCUMENTATION

### MAKING OPEN SOURCE MORE INCLUSIVE

Red Hat is committed to replacing problematic language in our code, documentation, and web properties. We are beginning with these four terms: master, slave, blacklist, and whitelist. Because of the enormity of this endeavor, these changes will be implemented gradually over several upcoming releases. For more details, see [our CTO Chris Wright's message](#).

*Revised on 2023-11-15 15:17:45 UTC*