



# Red Hat Software Collections 3

## 3.5 Release Notes

Release Notes for Red Hat Software Collections 3.5



# Red Hat Software Collections 3 3.5 Release Notes

---

## Release Notes for Red Hat Software Collections 3.5

Lenka Špačková

Red Hat Customer Content Services

lspackova@redhat.com

Jaromír Hradílek

Red Hat Customer Content Services

jhradilek@redhat.com

Eliška Slobodová

Red Hat Customer Content Services

## Legal Notice

Copyright © 2020 Red Hat, Inc.

This document is licensed by Red Hat under the [Creative Commons Attribution-ShareAlike 3.0 Unported License](https://creativecommons.org/licenses/by-sa/3.0/). If you distribute this document, or a modified version of it, you must provide attribution to Red Hat, Inc. and provide a link to the original. If the document is modified, all Red Hat trademarks must be removed.

Red Hat, as the licensor of this document, waives the right to enforce, and agrees not to assert, Section 4d of CC-BY-SA to the fullest extent permitted by applicable law.

Red Hat, Red Hat Enterprise Linux, the Shadowman logo, the Red Hat logo, JBoss, OpenShift, Fedora, the Infinity logo, and RHCE are trademarks of Red Hat, Inc., registered in the United States and other countries.

Linux<sup>®</sup> is the registered trademark of Linus Torvalds in the United States and other countries.

Java<sup>®</sup> is a registered trademark of Oracle and/or its affiliates.

XFS<sup>®</sup> is a trademark of Silicon Graphics International Corp. or its subsidiaries in the United States and/or other countries.

MySQL<sup>®</sup> is a registered trademark of MySQL AB in the United States, the European Union and other countries.

Node.js<sup>®</sup> is an official trademark of Joyent. Red Hat is not formally related to or endorsed by the official Joyent Node.js open source or commercial project.

The OpenStack<sup>®</sup> Word Mark and OpenStack logo are either registered trademarks/service marks or trademarks/service marks of the OpenStack Foundation, in the United States and other countries and are used with the OpenStack Foundation's permission. We are not affiliated with, endorsed or sponsored by the OpenStack Foundation, or the OpenStack community.

All other trademarks are the property of their respective owners.

## Abstract

The Red Hat Software Collections 3.5 Release Notes document the major features and contain important information about known problems in Red Hat Software Collections 3.5. The Red Hat Developer Toolset collection is documented in the Red Hat Developer Toolset Release Notes and the Red Hat Developer Toolset User Guide .

## Table of Contents

<b>CHAPTER 1. RED HAT SOFTWARE COLLECTIONS 3.5</b> .....	<b>4</b>
1.1. ABOUT RED HAT SOFTWARE COLLECTIONS	4
1.1.1. Red Hat Developer Toolset	4
1.2. MAIN FEATURES	4
1.3. CHANGES IN RED HAT SOFTWARE COLLECTIONS 3.5	16
1.3.1. Overview	16
Architectures	16
New Software Collections	16
Updated Software Collections	16
Red Hat Software Collections Container Images	16
1.3.2. Changes in Red Hat Developer Toolset	17
1.3.3. Changes in Perl	17
1.3.4. Changes in Python	18
1.3.5. Changes in Ruby	19
1.3.6. Changes in Apache httpd	19
1.3.7. Changes in Varnish Cache	20
1.3.8. Changes in JDK Mission Control	20
1.3.9. Changes in HAProxy	20
1.4. COMPATIBILITY INFORMATION	20
1.5. KNOWN ISSUES	20
Other Notes	23
1.6. DEPRECATED FUNCTIONALITY	25
<b>CHAPTER 2. INSTALLATION</b> .....	<b>26</b>
2.1. GETTING ACCESS TO RED HAT SOFTWARE COLLECTIONS	26
2.1.1. Using Red Hat Subscription Management	26
2.1.2. Packages from the Optional Repository	27
2.2. INSTALLING RED HAT SOFTWARE COLLECTIONS	29
2.2.1. Installing Individual Software Collections	29
2.2.2. Installing Optional Packages	30
2.2.3. Installing Debugging Information	30
2.3. UNINSTALLING RED HAT SOFTWARE COLLECTIONS	30
2.4. REBUILDING RED HAT SOFTWARE COLLECTIONS	31
<b>CHAPTER 3. USAGE</b> .....	<b>32</b>
3.1. USING RED HAT SOFTWARE COLLECTIONS	32
3.1.1. Running an Executable from a Software Collection	32
3.1.2. Running a Shell Session with a Software Collection as Default	32
3.1.3. Running a System Service from a Software Collection	33
Running a System Service from a Software Collection in Red Hat Enterprise Linux 6	33
Running a System Service from a Software Collection in Red Hat Enterprise Linux 7	33
3.2. ACCESSING A MANUAL PAGE FROM A SOFTWARE COLLECTION	33
3.3. DEPLOYING APPLICATIONS THAT USE RED HAT SOFTWARE COLLECTIONS	34
3.4. RED HAT SOFTWARE COLLECTIONS CONTAINER IMAGES	34
<b>CHAPTER 4. SPECIFICS OF INDIVIDUAL SOFTWARE COLLECTIONS</b> .....	<b>37</b>
4.1. RED HAT DEVELOPER TOOLSET	37
4.2. MONGODB 3.6	37
4.3. MONGODB 3.4	38
MongoDB 3.4 on Red Hat Enterprise Linux 6	38
MongoDB 3.4 on Red Hat Enterprise Linux 7	38
4.4. MAVEN	39

4.5. DATABASE CONNECTORS	39
<b>CHAPTER 5. MIGRATION</b> .....	<b>42</b>
5.1. MIGRATING TO MARIADB 10.3	42
5.1.1. Notable Differences Between the rh-mariadb102 and rh-mariadb103 Software Collections	42
5.1.2. Upgrading from the rh-mariadb102 to the rh-mariadb103 Software Collection	42
5.2. MIGRATING TO MARIADB 10.2	43
5.2.1. Notable Differences Between the rh-mariadb101 and rh-mariadb102 Software Collections	44
5.2.2. Upgrading from the rh-mariadb101 to the rh-mariadb102 Software Collection	44
5.3. MIGRATING TO MYSQL 8.0	45
5.3.1. Notable Differences Between MySQL 5.7 and MySQL 8.0	46
Differences Specific to the rh-mysql80 Software Collection	46
General Changes in MySQL 8.0	46
5.3.2. Upgrading to the rh-mysql80 Software Collection	47
5.4. MIGRATING TO MONGODB 3.6	48
5.4.1. Notable Differences Between MongoDB 3.4 and MongoDB 3.6	48
General Changes	48
Compatibility Changes	48
Backwards Incompatible Features	48
5.4.2. Upgrading from the rh-mongodb34 to the rh-mongodb36 Software Collection	49
5.5. MIGRATING TO MONGODB 3.4	50
5.5.1. Notable Differences Between MongoDB 3.2 and MongoDB 3.4	50
General Changes	50
Compatibility Changes	50
5.5.2. Upgrading from the rh-mongodb32 to the rh-mongodb34 Software Collection	51
5.6. MIGRATING TO POSTGRESQL 12	52
5.6.1. Migrating from a Red Hat Enterprise Linux System Version of PostgreSQL to the PostgreSQL 12 Software Collection	53
5.6.2. Migrating from the PostgreSQL 10 Software Collection to the PostgreSQL 12 Software Collection	56
5.7. MIGRATING TO POSTGRESQL 9.6	58
5.7.1. Notable Differences Between PostgreSQL 9.5 and PostgreSQL 9.6	58
5.7.2. Migrating from a Red Hat Enterprise Linux System Version of PostgreSQL to the PostgreSQL 9.6 Software Collection	60
5.7.3. Migrating from the PostgreSQL 9.5 Software Collection to the PostgreSQL 9.6 Software Collection	62
5.8. MIGRATING TO NGINX 1.16	65
5.9. MIGRATING TO REDIS 5	65
Compatibility Notes	65
<b>CHAPTER 6. ADDITIONAL RESOURCES</b> .....	<b>66</b>
6.1. RED HAT PRODUCT DOCUMENTATION	66
6.2. RED HAT DEVELOPERS	66
<b>APPENDIX A. REVISION HISTORY</b> .....	<b>68</b>



# CHAPTER 1. RED HAT SOFTWARE COLLECTIONS 3.5

This chapter serves as an overview of the Red Hat Software Collections 3.5 content set. It provides a list of components and their descriptions, sums up changes in this version, documents relevant compatibility information, and lists known issues.

## 1.1. ABOUT RED HAT SOFTWARE COLLECTIONS

For certain applications, more recent versions of some software components are often needed in order to use their latest new features. **Red Hat Software Collections** is a Red Hat offering that provides a set of dynamic programming languages, database servers, and various related packages that are either more recent than their equivalent versions included in the base Red Hat Enterprise Linux system, or are available for this system for the first time.

Red Hat Software Collections 3.5 is available for Red Hat Enterprise Linux 7; selected previously released components also for Red Hat Enterprise Linux 6. For a complete list of components that are distributed as part of Red Hat Software Collections and a brief summary of their features, see [Section 1.2, “Main Features”](#).

Red Hat Software Collections does not replace the default system tools provided with Red Hat Enterprise Linux 6 or Red Hat Enterprise Linux 7. Instead, a parallel set of tools is installed in the `/opt/` directory and can be optionally enabled per application by the user using the supplied `scl` utility. The default versions of Perl or PostgreSQL, for example, remain those provided by the base Red Hat Enterprise Linux system.



### NOTE

In Red Hat Enterprise Linux 8, similar components are provided as [Application Streams](#).

All Red Hat Software Collections components are fully supported under Red Hat Enterprise Linux Subscription Level Agreements, are functionally complete, and are intended for production use. Important bug fix and security errata are issued to Red Hat Software Collections subscribers in a similar manner to Red Hat Enterprise Linux for at least two years from the release of each major version. In each major release stream, each version of a selected component remains backward compatible. For detailed information about length of support for individual components, refer to the [Red Hat Software Collections Product Life Cycle](#) document.

### 1.1.1. Red Hat Developer Toolset

**Red Hat Developer Toolset** is a part of Red Hat Software Collections, included as a separate Software Collection. For more information about Red Hat Developer Toolset, refer to the [Red Hat Developer Toolset Release Notes](#) and the [Red Hat Developer Toolset User Guide](#).

## 1.2. MAIN FEATURES

[Table 1.1, “Red Hat Software Collections Components”](#) lists components that are supported at the time of the Red Hat Software Collections 3.5 release.

**Table 1.1. Red Hat Software Collections Components**



Component	Software Collection	Description
Red Hat Developer Toolset 9.1	devtoolset-9	Red Hat Developer Toolset is designed for developers working on the Red Hat Enterprise Linux platform. It provides current versions of the <b>GNU Compiler Collection</b> , <b>GNU Debugger</b> , and other development, debugging, and performance monitoring tools. For a complete list of components, see the <a href="#">Red Hat Developer Toolset Components</a> table in the <i>Red Hat Developer Toolset User Guide</i> .
Perl 5.26.3 <sup>[a]</sup>	rh-perl526	A release of Perl, a high-level programming language that is commonly used for system administration utilities and web programming. The rh-perl526 Software Collection provides additional utilities, scripts, and <i>database connectors for MySQL and PostgreSQL</i> . It includes the <b>DateTime</b> Perl module and the <b>mod_perl</b> Apache httpd module, which is supported only with the httpd24 Software Collection. Additionally, it provides the <b>cpanm</b> utility for easy installation of CPAN modules. The rh-perl526 packaging is aligned with upstream; the perl526-perl package installs also core modules, while the interpreter is provided by the perl-interpreter package.
Perl 5.30.1 <sup>[a]</sup>	rh-perl530	A release of Perl, a high-level programming language that is commonly used for system administration utilities and web programming. The rh-perl530 Software Collection provides additional utilities, scripts, and database connectors for <b>MySQL</b> , <b>PostgreSQL</b> , and <b>SQLite</b> . It includes the <b>DateTime</b> Perl module and the <b>mod_perl</b> Apache httpd module, which is supported only with the httpd24 Software Collection. Additionally, it provides the <b>cpanm</b> utility for easy installation of CPAN modules, the <b>LWP::UserAgent</b> module for communicating with the HTTP servers, and the <b>LWP::Protocol::https</b> module for securing the communication. The rh-perl530 packaging is aligned with upstream; the perl530-perl package installs also core modules, while the interpreter is provided by the perl-interpreter package.
PHP 7.2.24 <sup>[a]</sup>	rh-php72	A release of PHP 7.2 with PEAR 1.10.5, APCu 5.1.12, and enhanced language features.
PHP 7.3.11 <sup>[a]</sup>	rh-php73	A release of PHP 7.3 with PEAR 1.10.9, APCu 5.1.17, and the Xdebug extension.

Component	Software Collection	Description
Python 2.7.17	python27	A release of Python 2.7 with a number of additional utilities. This Python version provides various features and enhancements, including an ordered dictionary type, faster I/O operations, and improved forward compatibility with Python 3. The python27 Software Collections contains the <i>Python 2.7.13 interpreter</i> , a set of extension libraries useful for programming web applications and <b>mod_wsgi</b> (only supported with thehttpd24 Software Collection), MySQL and PostgreSQL database connectors, and <b>numpy</b> and <b>scipy</b> .
Python 3.6.9	rh-python36	The rh-python36 Software Collection contains Python 3.6.9, which introduces a number of new features, such as <i>f-strings, syntax for variable annotations, and asynchronous generators and comprehensions</i> . In addition, a set of extension libraries useful for programming web applications is included, with <b>mod_wsgi</b> (supported only together with the httpd24 Software Collection), PostgreSQL database connector, and <b>numpy</b> and <b>scipy</b> .
Python 3.8.0 <a href="#">[a]</a>	rh-python38	The rh-python38 Software Collection contains Python 3.8, which introduces <i>new Python modules, such as <b>contextvars</b>, <b>dataclasses</b>, or <b>importlib.resources</b>, new language features, improved developer experience, and performance improvements</i> . In addition, a set of popular extension libraries is provided, including <b>mod_wsgi</b> (supported only together with thehttpd24 Software Collection), <b>numpy</b> , <b>scipy</b> , and the <b>psycopg2</b> PostgreSQL database connector.
Ruby 2.5.5 <a href="#">[a]</a>	rh-ruby25	A release of Ruby 2.5. This version provides multiple performance improvements and new features, for example, <i>simplified usage of blocks with the <b>rescue</b>, <b>else</b>, and <b>ensure</b> keywords, a new <b>yield_self</b> method, support for branch coverage and method coverage measurement, new <b>Hash#slice</b> and <b>Hash#transform_keys</b> methods</i> . Ruby 2.5.0 maintains source-level backward compatibility with Ruby 2.4.
Ruby 2.6.2 <a href="#">[a]</a>	rh-ruby26	A release of Ruby 2.6. This version provides multiple performance improvements and new features, such as <i>endless ranges, the <b>Binding#source_location</b> method, and the <b>\$SAFE</b> process global state</i> . Ruby 2.6.0 maintains source-level backward compatibility with Ruby 2.5.
Ruby 2.7.1 <a href="#">[a]</a>	rh-ruby27	A release of Ruby 2.7. This version provides multiple performance improvements and new features, such as <i>Compaction GC or command-line interface for the LALR(1) parser generator, and an enhancement to REPL</i> . Ruby 2.7 maintains source-level backward compatibility with Ruby 2.6.

Component	Software Collection	Description
MariaDB 10.2.22	rh-mariadb102	A release of MariaDB, an alternative to MySQL for users of Red Hat Enterprise Linux. For all practical purposes, MySQL is binary compatible with MariaDB and can be replaced with it without any data conversions. This version adds <i>MariaDB Backup, Flashback, support for Recursive Common Table Expressions, window functions, and JSON functions</i> .
MariaDB 10.3.13 <a href="#">[a]</a>	rh-mariadb103	A release of MariaDB, an alternative to MySQL for users of Red Hat Enterprise Linux. For all practical purposes, MySQL is binary compatible with MariaDB and can be replaced with it without any data conversions. This version introduces <i>system-versioned tables, invisible columns, a new instant <b>ADD COLUMN</b> operation for <b>InnoDB</b>, and a JDBC connector for MariaDB and MySQL</i> .
MongoDB 3.4.9	rh-mongodb34	A release of MongoDB, a cross-platform document-oriented database system classified as a NoSQL database. This release introduces support for new architectures, <i>adds message compression and support for the decimal128 type, enhances collation features and more</i> .
MongoDB 3.6.3 <a href="#">[a]</a>	rh-mongodb36	A release of MongoDB, a cross-platform document-oriented database system classified as a NoSQL database. This release introduces <i>change streams, retryable writes, and JSON Schema</i> , as well as other features.
MySQL 8.0.17 <a href="#">[a]</a>	rh-mysql80	A release of the MySQL server, which introduces a number of new <i>security and account management features</i> and enhancements.
PostgreSQL 9.6.10	rh-postgresql96	A release of PostgreSQL, which introduces parallel execution of sequential scans, joins, and aggregates, and provides enhancements to synchronous replication, full-text search, deration driver, postgres_fdw, as well as performance improvements.
PostgreSQL 10.12 <a href="#">[a]</a>	rh-postgresql10	A release of PostgreSQL, which includes a significant performance improvement and a number of new features, such as <i>logical replication using the <b>publish</b> and <b>subscribe</b> keywords, or stronger password authentication based on the <b>SCRAM-SHA-256</b> mechanism</i> .
PostgreSQL 12.1 <a href="#">[a]</a>	rh-postgresql12	A release of PostgreSQL, which provides <i>the <b>pgaudit</b> extension, various enhancements to partitioning and parallelism, support for the SQL/JSON path language, and performance improvements</i> .

Component	Software Collection	Description
Node.js 10.19.0 <a href="#">[a]</a>	rh-nodejs10	A release of Node.js, which provides multiple API enhancements and new features, including <i>V8 engine version 6.6, full N-API support</i> , and stability improvements.
Node.js 12.16.1 <a href="#">[a]</a>	rh-nodejs12	A release of Node.js, with <i>V8 engine version 7.6, support for ES6 modules</i> , and improved support for native modules.
nginx 1.14.1 <a href="#">[a]</a>	rh-nginx114	A release of nginx, a web and proxy server with a focus on high concurrency, performance, and low memory usage. This version provides a number of features, such as <i>mirror module, HTTP/2 server push, gRPC proxy module, and numerous performance improvements</i> .
nginx 1.16.1 <a href="#">[a]</a>	rh-nginx116	A release of nginx, a web and proxy server with a focus on high concurrency, performance, and low memory usage. This version introduces numerous <i>updates related to SSL, several new directives and parameters</i> , and various enhancements.
Apache httpd 2.4.34	httpd24	A release of the Apache HTTP Server (httpd), including a high performance <i>event-based processing model, enhanced SSL module and FastCGI support</i> . The <b>mod_auth_kerb</b> , <b>mod_auth_mellon</b> , and <b>ModSecurity</b> modules are also included.
Varnish Cache 5.2.1 <a href="#">[a]</a>	rh-varnish5	A release of Varnish Cache, a high-performance HTTP reverse proxy. This version includes <i>the <b>shard</b> director, experimental HTTP/2 support, and improvements to Varnish configuration</i> through separate VCL files and VCL labels.
Varnish Cache 6.0.6 <a href="#">[a]</a>	rh-varnish6	A release of Varnish Cache, a high-performance HTTP reverse proxy. This version includes <i>support for Unix Domain Sockets (both for clients and for back-end servers), new level of the VCL language (<b>vcl 4.1</b>), and improved HTTP/2 support</i> .
Maven 3.5.0 <a href="#">[a]</a>	rh-maven35	A release of Maven, a software project management and comprehension tool. This release introduces support for new architectures and a number of new features, including <i>colorized logging</i> .
Maven 3.6.1 <a href="#">[a]</a>	rh-maven36	A release of Maven, a software project management and comprehension tool. This release provides various enhancements and bug fixes.

Component	Software Collection	Description
Git 2.18.4 <sup>[a]</sup>	rh-git218	A release of Git, a distributed revision control system with a decentralized architecture. As opposed to centralized version control systems with a client-server model, Git ensures that each working copy of a Git repository is its exact copy with complete revision history. This version includes the <i>Large File Storage (LFS)</i> extension.
Redis 5.0.5 <sup>[a]</sup>	rh-redis5	A release of Redis 5.0, a <i>persistent key-value database</i> . Redis now provides <b>redis-trib</b> , a <i>cluster management tool</i> .
HAProxy 1.8.24 <sup>[a]</sup>	rh-haproxy18	A release of HAProxy 1.8, a reliable, high-performance <i>network load balancer</i> for TCP and HTTP-based applications.
JDK Mission Control 7.1.1 <sup>[a]</sup>	rh-jmc	This Software Collection includes <i>JDK Mission Control (JMC)</i> , a powerful profiler for HotSpot JVMs. JMC provides an advanced set of tools for efficient and detailed analysis of extensive data collected by the JDK Flight Recorder. JMC requires JDK version 8 or later to run. Target Java applications must run with at least OpenJDK version 11 so that JMC can access JDK Flight Recorder features. The rh-jmc Software Collection requires the rh-maven35 Software Collection.
<sup>[a]</sup> This Software Collection is available only for Red Hat Enterprise Linux 7		

Previously released Software Collections remain available in the same distribution channels. All Software Collections, including retired components, are listed in the [Table 1.2, “All Available Software Collections”](#). Software Collections that are no longer supported are marked with an asterisk ( \* ).

See the [Red Hat Software Collections Product Life Cycle](#) document for information on the length of support for individual components. For detailed information regarding previously released components, refer to the [Release Notes](#) for earlier versions of Red Hat Software Collections.

**Table 1.2. All Available Software Collections**

Component	Software Collection	Availability	Architectures supported on RHEL7
<b>Components New in Red Hat Software Collections 3.5</b>			
Perl 5.30.1	rh-perl530	RHEL7	x86_64, s390x, aarch64, ppc64le
Python 3.8.0	rh-python38	RHEL7	x86_64, s390x, aarch64, ppc64le

Component	Software Collection	Availability	Architectures supported on RHEL7
<b>Components New in Red Hat Software Collections 3.5</b>			
<b>Ruby 2.7.1</b>	rh-ruby27	RHEL7	x86_64, s390x, aarch64, ppc64le

<b>Components Updated in Red Hat Software Collections 3.5</b>			
<b>Red Hat Developer Toolset 9.1</b>	devtoolset-9	RHEL7	x86_64, s390x, aarch64, ppc64, ppc64le
<b>Apache httpd 2.4.34</b>	httpd24	RHEL6, RHEL7	x86_64, s390x, aarch64, ppc64le
<b>JDK Mission Control 7.1.1</b>	rh-jmc	RHEL7	x86_64
<b>Varnish Cache 6.0.6</b>	rh-varnish6	RHEL7	x86_64, s390x, aarch64, ppc64le
<b>HAProxy 1.8.24</b>	rh-haproxy18	RHEL7	x86_64

<b>Components Last Updated in Red Hat Software Collections 3.4</b>			
<b>Node.js 12.16.1</b>	rh-nodejs12	RHEL7	x86_64, s390x, aarch64, ppc64le
<b>PHP 7.3.11</b>	rh-php73	RHEL7	x86_64, s390x, aarch64, ppc64le
<b>nginx 1.16.1</b>	rh-nginx116	RHEL7	x86_64, s390x, aarch64, ppc64le
<b>PostgreSQL 12.1</b>	rh-postgresql12	RHEL7	x86_64, s390x, aarch64, ppc64le
<b>Maven 3.6.1</b>	rh-maven36	RHEL7	x86_64, s390x, aarch64, ppc64le

<b>Components Last Updated in Red Hat Software Collections 3.3</b>			
<b>Red Hat Developer Toolset 8.1</b>	devtoolset-8	RHEL6, RHEL7	x86_64, s390x, aarch64, ppc64, ppc64le

## Components Last Updated in Red Hat Software Collections 3.3

<b>MariaDB 10.3.13</b>	rh-mariadb103	RHEL7	x86_64, s390x, aarch64, ppc64le
<b>Redis 5.0.5</b>	rh-redis5	RHEL7	x86_64, s390x, aarch64, ppc64le
<b>Ruby 2.6.2</b>	rh-ruby26	RHEL7	x86_64, s390x, aarch64, ppc64le

## Components Last Updated in Red Hat Software Collections 3.2

<b>PHP 7.2.24</b>	rh-php72	RHEL7	x86_64, s390x, aarch64, ppc64le
<b>MySQL 8.0.17</b>	rh-mysql80	RHEL7	x86_64, s390x, aarch64, ppc64le
<b>Node.js 10.19.0</b>	rh-nodejs10	RHEL7	x86_64, s390x, aarch64, ppc64le
<b>nginx 1.14.1</b>	rh-nginx114	RHEL7	x86_64, s390x, aarch64, ppc64le
<b>Git 2.18.4</b>	rh-git218	RHEL7	x86_64, s390x, aarch64, ppc64le

## Components Last Updated in Red Hat Software Collections 3.1

<b>Red Hat Developer Toolset 7.1</b>	devtoolset-7*	RHEL6, RHEL7	x86_64, s390x, aarch64, ppc64, ppc64le
<b>Perl 5.26.3</b>	rh-perl526	RHEL7	x86_64, s390x, aarch64, ppc64le
<b>Ruby 2.5.5</b>	rh-ruby25	RHEL7	x86_64, s390x, aarch64, ppc64le
<b>MongoDB 3.6.3</b>	rh-mongodb36	RHEL7	x86_64, s390x, aarch64, ppc64le
<b>Varnish Cache 5.2.1</b>	rh-varnish5	RHEL7	x86_64, s390x, aarch64, ppc64le
<b>PostgreSQL 10.12</b>	rh-postgresql10	RHEL7	x86_64, s390x, aarch64, ppc64le

### Components Last Updated in Red Hat Software Collections 3.1

PHP 7.0.27	rh-php70*	RHEL6, RHEL7	x86_64
MySQL 5.7.24	rh-mysql57*	RHEL6, RHEL7	x86_64, s390x, aarch64, ppc64le

### Components Last Updated in Red Hat Software Collections 3.0

PHP 7.1.8	rh-php71*	RHEL7	x86_64, s390x, aarch64, ppc64le
nginx 1.12.1	rh-nginx112*	RHEL7	x86_64, s390x, aarch64, ppc64le
Python 3.6.9	rh-python36	RHEL6, RHEL7	x86_64, s390x, aarch64, ppc64le
Maven 3.5.0	rh-maven35	RHEL7	x86_64, s390x, aarch64, ppc64le
MariaDB 10.2.22	rh-mariadb102	RHEL6, RHEL7	x86_64, s390x, aarch64, ppc64le
PostgreSQL 9.6.10	rh-postgresql96	RHEL6, RHEL7	x86_64, s390x, aarch64, ppc64le
MongoDB 3.4.9	rh-mongodb34	RHEL6, RHEL7	x86_64, s390x, aarch64, ppc64le
Node.js 8.11.4	rh-nodejs8*	RHEL7	x86_64, s390x, aarch64, ppc64le

### Components Last Updated in Red Hat Software Collections 2.4

Red Hat Developer Toolset 6.1	devtoolset-6*	RHEL6, RHEL7	x86_64, s390x, aarch64, ppc64, ppc64le
Scala 2.10.6	rh-scala210*	RHEL7	x86_64
nginx 1.10.2	rh-nginx110*	RHEL6, RHEL7	x86_64
Node.js 6.11.3	rh-nodejs6*	RHEL6, RHEL7	x86_64, s390x, aarch64, ppc64le
Ruby 2.4.6	rh-ruby24*	RHEL6, RHEL7	x86_64



## Components Last Updated in Red Hat Software Collections 2.4

Ruby on Rails 5.0.1	rh-ror50*	RHEL6, RHEL7	x86_64
Eclipse 4.6.3	rh-eclipse46*	RHEL7	x86_64
Python 2.7.17	python27	RHEL6, RHEL7	x86_64, s390x, aarch64, ppc64le
Thermostat 1.6.6	rh-thermostat16*	RHEL6, RHEL7	x86_64
Maven 3.3.9	rh-maven33*	RHEL6, RHEL7	x86_64
Common Java Packages	rh-java-common*	RHEL6, RHEL7	x86_64

## Components Last Updated in Red Hat Software Collections 2.3

Git 2.9.3	rh-git29*	RHEL6, RHEL7	x86_64, s390x, aarch64, ppc64le
Redis 3.2.4	rh-redis32*	RHEL6, RHEL7	x86_64
Perl 5.24.0	rh-perl524*	RHEL6, RHEL7	x86_64
Python 3.5.1	rh-python35*	RHEL6, RHEL7	x86_64
MongoDB 3.2.10	rh-mongodb32*	RHEL6, RHEL7	x86_64
Ruby 2.3.8	rh-ruby23*	RHEL6, RHEL7	x86_64
PHP 5.6.25	rh-php56*	RHEL6, RHEL7	x86_64

## Components Last Updated in Red Hat Software Collections 2.2

Red Hat Developer Toolset 4.1	devtoolset-4*	RHEL6, RHEL7	x86_64
MariaDB 10.1.29	rh-mariadb101*	RHEL6, RHEL7	x86_64
MongoDB 3.0.11 upgrade collection	rh-mongodb30upg*	RHEL6, RHEL7	x86_64
Node.js 4.6.2	rh-nodejs4*	RHEL6, RHEL7	x86_64
PostgreSQL 9.5.14	rh-postgresql95*	RHEL6, RHEL7	x86_64

### Components Last Updated in Red Hat Software Collections 2.2

Ruby on Rails 4.2.6	rh-ror42*	RHEL6, RHEL7	x86_64
MongoDB 2.6.9	rh-mongodb26*	RHEL6, RHEL7	x86_64
Thermostat 1.4.4	thermostat1*	RHEL6, RHEL7	x86_64

### Components Last Updated in Red Hat Software Collections 2.1

Varnish Cache 4.0.3	rh-varnish4*	RHEL6, RHEL7	x86_64
nginx 1.8.1	rh-nginx18*	RHEL6, RHEL7	x86_64
Node.js 0.10	nodejs010*	RHEL6, RHEL7	x86_64
Maven 3.0.5	maven30*	RHEL6, RHEL7	x86_64
V8 3.14.5.10	v8314*	RHEL6, RHEL7	x86_64

### Components Last Updated in Red Hat Software Collections 2.0

Red Hat Developer Toolset 3.1	devtoolset-3*	RHEL6, RHEL7	x86_64
Perl 5.20.1	rh-perl520*	RHEL6, RHEL7	x86_64
Python 3.4.2	rh-python34*	RHEL6, RHEL7	x86_64
Ruby 2.2.9	rh-ruby22*	RHEL6, RHEL7	x86_64
Ruby on Rails 4.1.5	rh-ror41*	RHEL6, RHEL7	x86_64
MariaDB 10.0.33	rh-mariadb100*	RHEL6, RHEL7	x86_64
MySQL 5.6.40	rh-mysql56*	RHEL6, RHEL7	x86_64
PostgreSQL 9.4.14	rh-postgresql94*	RHEL6, RHEL7	x86_64
Passenger 4.0.50	rh-passenger40*	RHEL6, RHEL7	x86_64
PHP 5.4.40	php54*	RHEL6, RHEL7	x86_64
PHP 5.5.21	php55*	RHEL6, RHEL7	x86_64

### Components Last Updated in Red Hat Software Collections 2.0

<b>nginx 1.6.2</b>	nginx16*	RHEL6, RHEL7	x86_64
<b>DevAssistant 0.9.3</b>	devassist09*	RHEL6, RHEL7	x86_64

### Components Last Updated in Red Hat Software Collections 1

<b>Git 1.9.4</b>	git19*	RHEL6, RHEL7	x86_64
<b>Perl 5.16.3</b>	perl516*	RHEL6, RHEL7	x86_64
<b>Python 3.3.2</b>	python33*	RHEL6, RHEL7	x86_64
<b>Ruby 1.9.3</b>	ruby193*	RHEL6, RHEL7	x86_64
<b>Ruby 2.0.0</b>	ruby200*	RHEL6, RHEL7	x86_64
<b>Ruby on Rails 4.0.2</b>	ror40*	RHEL6, RHEL7	x86_64
<b>MariaDB 5.5.53</b>	mariadb55*	RHEL6, RHEL7	x86_64
<b>MongoDB 2.4.9</b>	mongodb24*	RHEL6, RHEL7	x86_64
<b>MySQL 5.5.52</b>	mysql55*	RHEL6, RHEL7	x86_64
<b>PostgreSQL 9.2.18</b>	postgresql92*	RHEL6, RHEL7	x86_64

#### Legend:

- RHEL6 – Red Hat Enterprise Linux 6
- RHEL7 – Red Hat Enterprise Linux 7
- x86\_64 – AMD64 and Intel 64 architectures
- s390x – IBM Z
- aarch64 – The 64-bit ARM architecture
- ppc64 – IBM POWER, big endian
- ppc64le – IBM POWER, little endian
- \* – Retired component; this Software Collection is no longer supported

The tables above list the latest versions available through asynchronous updates.

Note that Software Collections released in Red Hat Software Collections 2.0 and later include a **rh-** prefix in their names.

**Eclipse** is available as a part of the [Red Hat Developer Tools](#) offering.

## 1.3. CHANGES IN RED HAT SOFTWARE COLLECTIONS 3.5

### 1.3.1. Overview

#### Architectures

The Red Hat Software Collections offering contains packages for Red Hat Enterprise Linux 7 running on AMD64 and Intel 64 architectures; certain earlier Software Collections are available also for Red Hat Enterprise Linux 6.

In addition, Red Hat Software Collections 3.5 supports the following architectures on Red Hat Enterprise Linux 7:

- The 64-bit ARM architecture
- IBM Z
- IBM POWER, little endian

For a full list of components and their availability, see [Table 1.2, "All Available Software Collections"](#).

#### New Software Collections

Red Hat Software Collections 3.5 adds the following new Software Collections:

- rh-perl530 – see [Section 1.3.3, "Changes in Perl"](#)
- rh-python38 – see [Section 1.3.4, "Changes in Python"](#)
- rh-ruby27 – see [Section 1.3.5, "Changes in Ruby"](#)

All new Software Collections are available only for Red Hat Enterprise Linux 7.

#### Updated Software Collections

The following components has been updated in Red Hat Software Collections 3.5:

- devtoolset-9 – see [Section 1.3.2, "Changes in Red Hat Developer Toolset"](#)
- httpd24 – see [Section 1.3.6, "Changes in Apache httpd"](#)
- rh-varnish6 – see [Section 1.3.7, "Changes in Varnish Cache"](#)
- rh-jmc – see [Section 1.3.8, "Changes in JDK Mission Control"](#)
- rh-haproxy18 – see [Section 1.3.9, "Changes in HAProxy"](#)

#### Red Hat Software Collections Container Images

The following container images are new in Red Hat Software Collections 3.5:

- rhsc1/perl-530-rhel7
- rhsc1/python-38-rhel7

- `rhsc/ruby-27-rhel7`

The following container image has been updated in Red Hat Software Collections 3.5

- `rhsc/httpd-24-rhel7`
- `rhsc/varnish-6-rhel7`
- `rhsc/devtoolset-9-toolchain-rhel7`
- `rhsc/devtoolset-9-perftools-rhel7`

For detailed information regarding Red Hat Software Collections container images, see [Section 3.4, “Red Hat Software Collections Container Images”](#).

### 1.3.2. Changes in Red Hat Developer Toolset

The following component has been upgraded in Red Hat Developer Toolset 9.1 compared to the previous release of Red Hat Developer Toolset:

- **GCC** to version 9.3.1

In addition, bug fix updates are available for the following components:

- **binutils**
- **elfutils**
- **ltrace**
- **make**
- **strace**
- **SystemTap**

For detailed information on changes in 9.1, see the [Red Hat Developer Toolset User Guide](#).

### 1.3.3. Changes in Perl

The new `rh-perl530` Software Collection includes **Perl 5.30.1**, which provides a number of bug fixes and enhancements over the previously released `rh-perl526` Software Collection. The new version also deprecates or removes certain language features.

Notable changes with significant impact include:

- The **`Math::BigInt::CalcEmu`**, **`arybase`**, and **`B::Debug`** modules have been removed
- File descriptors are now opened with a **`close-on-exec`** flag
- Opening the same symbol as a file and as a directory handle is no longer allowed
- Subroutine attributes now must precede subroutine signatures
- The **`:locked`** and **`:uniq`** attributes have been removed
- Comma-less variable lists in formats are no longer allowed

- A bare `<<` here-document operator is no longer allowed
- Certain formerly deprecated uses of an unescaped left brace (`{}`) character in regular expression patterns are no longer permitted
- The **AUTOLOAD()** subroutine can no longer be inherited to non-method functions
- The **sort** pragma no longer allows specifying a **sort** algorithm
- The **B::OP::terse()** subroutine has been replaced by the **B::Concise::b\_terse()** subroutine
- The **File::Glob::glob()** function has been replaced by the **File::Glob::bsd\_glob()** function
- The **dump()** function now must be invoked fully qualified as **CORE::dump()**
- The yada-yada operator (`...`) is a statement now, it cannot be used as an expression
- Assigning a non-zero value to the **\$[** variable now returns a fatal error
- The **\$\*** and **\$#** variables are no longer allowed
- Declaring variables using the **my()** function in a false condition branch is no longer allowed
- Using the **sysread()** and **syswrite()** functions on the **:utf8** handles now returns a fatal error
- The **pack()** function no longer returns malformed UTF-8 format
- Unicode code points with a value greater than **IV\_MAX** are no longer allowed
- Unicode 12.1 is now supported

In addition, the rh-perl530 Software Collection now provides the Library for WWW in Perl (LWP) and other HTTP-related modules in the rh-perl530-perl-libwww-perl and rh-perl530-perl-LWP-Protocol-https RPM packages.

For detailed changes between **Perl 5.26** and **Perl 5.30.1**, see the upstream change log for versions [5.28.0](#), [5.30.0](#), and [5.30.1](#).

### 1.3.4. Changes in Python

The new rh-python38 Software Collection introduces **Python 3.8.0**. Notable enhancements compared to **Python 3.6** include:

- New Python modules, for example, **contextvars**, **dataclasses**, or **importlib.resources**
- New language features, such as assignment expressions (the so-called walrus operator, **:=**) or positional-only parameters
- Improved developer experience with the **breakpoint()** built-in function, the **=** format string specification, and compatibility between debug and non-debug builds of Python and extension modules
- Performance improvements
- Improved support for optional static type hints
- An addition of the **=** specifier to formatted string literals (f-strings) for easier debugging

- Updated versions of packages, such as pip, requests, or Cython

For detailed changes, see the [upstream documentation](#).

Note that similarly to the previously released **Python** Software Collections, the rh-python38 Software Collection does not include the same binary bindings to system tools (RPM, DNF, SELinux, and others) that are provided for the base RHEL 7 version of **Python**.

### 1.3.5. Changes in Ruby

The new rh-ruby27 Software Collection provides **Ruby 2.7.1**, which introduces a number of performance improvements, bug and security fixes, and new features.

Notable enhancements include:

- A new Compaction Garbage Collector (GC) has been introduced, which can defragment a fragmented memory space.
- A new `rubygem-racc` package has been added. Ruby yet Another Compiler-Compiler (Racc) now provides a command-line interface for the one-token Look-Ahead Left-to-Right – LALR(1) – parser generator.
- Interactive Ruby Shell (**irb**), the bundled Read–Eval–Print Loop (REPL) environment, now supports multi-line editing.
- Pattern matching, frequently used in functional programming languages, has been introduced as an experimental feature.
- Numbered parameter as the default block parameter has been introduced as an experimental feature.

The following performance improvements have been implemented:

- Fiber cache strategy has been changed to accelerate fiber creation.
- Performance of the **CGI.escapeHTML** method has been improved.
- Performance of the **Monitor** class and **MonitorMixin** module has been improved.

In addition, automatic conversion of keyword arguments and positional arguments has been deprecated. In Ruby 3.0, positional arguments and keyword arguments will be separated. For more information, see the [upstream documentation](#).

To suppress warnings against experimental features, use the **-W:no-experimental** command-line option. To disable a deprecation warning, use the **-W:no-deprecated** command-line option or add **Warning[:deprecated] = false** to your code.

For more information about changes in Ruby 2.7, see the upstream announcement for versions [2.7.0](#) and [2.7.1](#).

### 1.3.6. Changes in Apache httpd

The **mod\_md** module of the httpd24 Software Collection has been updated to version 2.0.8. This update adds a number of features, notably support for version 2 of the Automatic Certificate Management Environment (ACME) certificate issuance and management protocol, which is the Internet

Engineering Task Force (IETF) standard (RFC 8555). The original ACMEv1 protocol remains supported but is deprecated by popular service providers.

In addition, a security fix for CVE-2019-10098 in the **mod\_rewrite** module is now available.

### 1.3.7. Changes in Varnish Cache

The rh-varnish6 Software Collection has been updated to version 6.0.6. This release includes numerous bug and security fixes and various minor enhancements.

For detailed changes in **Varnish Cache 6.0.6** since the previous Red Hat Software Collections release, see the upstream change log for versions [6.0.3](#), [6.0.4](#), [6.0.5](#), and [6.0.6](#).

### 1.3.8. Changes in JDK Mission Control

JDK Mission Control, provided by the rh-jmc Software Collection, has been updated to version 7.1.1. This update includes numerous bug fixes and enhancements, including:

- Multiple rule optimizations
- A new JOverflow view based on Standard Widget Toolkit (SWT)
- A new flame graph view
- A new way of latency visualization using the High Dynamic Range (HDR) Histogram

### 1.3.9. Changes in HAProxy

The rh-haproxy18 Software Collection has been updated to version 1.8.24 to provide multiple bug and security fixes.

## 1.4. COMPATIBILITY INFORMATION

Red Hat Software Collections 3.5 is available for all supported releases of Red Hat Enterprise Linux 7 on AMD64 and Intel 64 architectures, the 64-bit ARM architecture, IBM Z, and IBM POWER, little endian.

Certain components are available also for all supported releases of Red Hat Enterprise Linux 6 on AMD64 and Intel 64 architectures.

For a full list of available components, see [Table 1.2, "All Available Software Collections"](#).

## 1.5. KNOWN ISSUES

### rh-ruby27 component, BZ#1836201

When a custom script requires the Psych YAML parser and afterwards uses the **Gem.load\_yaml** method, running the script fails with the following error message:

```
superclass mismatch for class Mark (TypeError)
```

To work around this problem, add the **gem 'psych'** line to the script somewhere above the **require 'psych'** line:

```
...
```



```
gem 'psych'
...
require 'psych'
Gem.load_yaml
```

### multiple components, BZ#1716378

Certain files provided by the Software Collections debuginfo packages might conflict with the corresponding debuginfo package files from the base Red Hat Enterprise Linux system or from other versions of Red Hat Software Collections components. For example, the `python27-python-debuginfo` package files might conflict with the corresponding files from the `python-debuginfo` package installed on the core system. Similarly, files from the `httpd24-mod_auth_mellon-debuginfo` package might conflict with similar files provided by the base system `mod_auth_mellon-debuginfo` package. To work around this problem, uninstall the base system debuginfo package prior to installing the Software Collection debuginfo package.

### rh-mysql80 component, BZ#1646363

The **mysql-connector-java** database connector does not work with the **MySQL 8.0** server. To work around this problem, use the **mariadb-java-client** database connector from the `rh-mariadb103` Software Collection.

### rh-mysql80 component, BZ#1646158

The default character set has been changed to **utf8mb4** in **MySQL 8.0** but this character set is unsupported by the **php-mysqldb** database connector. Consequently, **php-mysqldb** fails to connect in the default configuration. To work around this problem, specify a known character set as a parameter of the MySQL server configuration. For example, modify the `/etc/opt/rh/rh-mysql80/my.cnf.d/mysql-server.cnf` file to read:

```
[mysqld]
character-set-server=utf8
```

### httpd24 component, BZ#1429006

Since **httpd 2.4.27**, the **mod\_http2** module is no longer supported with the default **prefork** Multi-Processing Module (MPM). To enable HTTP/2 support, edit the configuration file at `/opt/rh/httpd24/root/etc/httpd/conf.modules.d/00-mpm.conf` and switch to the **event** or **worker** MPM.

Note that the HTTP/2 server-push feature does not work on the 64-bit ARM architecture, IBM Z, and IBM POWER, little endian.

### httpd24 component, BZ#1327548

The **mod\_ssl** module does not support the ALPN protocol on Red Hat Enterprise Linux 6, or on Red Hat Enterprise Linux 7.3 and earlier. Consequently, clients that support upgrading TLS connections to HTTP/2 only using ALPN are limited to HTTP/1.1 support.

### httpd24 component, BZ#1224763

When using the **mod\_proxy\_fcgi** module with FastCGI Process Manager (PHP-FPM), **httpd** uses port **8000** for the FastCGI protocol by default instead of the correct port **9000**. To work around this problem, specify the correct port explicitly in configuration.

### httpd24 component, BZ#1382706

When SELinux is enabled, the **LD\_LIBRARY\_PATH** environment variable is not passed through to

CGI scripts invoked by **httpd**. As a consequence, in some cases it is impossible to invoke executables from Software Collections enabled in the **/opt/rh/httpd24/service-environment** file from CGI scripts run by **httpd**. To work around this problem, set **LD\_LIBRARY\_PATH** as desired from within the CGI script.

### **httpd24 component**

Compiling external applications against the Apache Portable Runtime (APR) and APR-util libraries from the httpd24 Software Collection is not supported. The **LD\_LIBRARY\_PATH** environment variable is not set in httpd24 because it is not required by any application in this Software Collection.

### **rh-python35, rh-python36 components, BZ#1499990**

The **pytz** module, which is used by **Babel** for time zone support, is not included in the **rh-python35**, and **rh-python36** Software Collections. Consequently, when the user tries to import the **dates** module from **Babel**, a traceback is returned. To work around this problem, install **pytz** through the **pip** package manager from the **pypi** public repository by using the **pip install pytz** command.

### **rh-python36 component**

Certain complex trigonometric functions provided by **numpy** might return incorrect values on the 64-bit ARM architecture, IBM Z, and IBM POWER, little endian. The AMD64 and Intel 64 architectures are not affected by this problem.

### **python27 component, BZ#1330489**

The **python27-python-pymongo** package has been updated to version 3.2.1. Note that this version is not fully compatible with the previously shipped version 2.5.2. For details, see <https://api.mongodb.org/python/current/changelog.html>.

### **scl-utils component**

In Red Hat Enterprise Linux 7.5 and earlier, due to an architecture-specific macro bug in the **scl-utils** package, the **<collection>/root/usr/lib64/** directory does not have the correct package ownership on the 64-bit ARM architecture and on IBM POWER, little endian. As a consequence, this directory is not removed when a Software Collection is uninstalled. To work around this problem, manually delete **<collection>/root/usr/lib64/** when removing a Software Collection.

### **maven component**

When the user has installed both the Red Hat Enterprise Linux system version of **maven-local** package and the **rh-maven\*-maven-local** package, **XMvn**, a tool used for building Java RPM packages, run from the Maven Software Collection tries to read the configuration file from the base system and fails. To work around this problem, uninstall the **maven-local** package from the base Red Hat Enterprise Linux system.

### **perl component**

It is impossible to install more than one **mod\_perl.so** library. As a consequence, it is not possible to use the **mod\_perl** module from more than one **Perl** Software Collection.

### **postgresql component**

The **rh-postgresql9\*** packages for Red Hat Enterprise Linux 6 do not provide the **sepgsql** module as this feature requires installation of **libselinux** version 2.0.99, which is not available in Red Hat Enterprise Linux 6.

### **httpd, mariadb, mongodb, mysql, nodejs, perl, php, python, ruby, and ror components, BZ#1072319**

When uninstalling the `httpd24`, `rh-mariadb*`, `rh-mongodb*`, `rh-mysql*`, `rh-nodejs*`, `rh-perl*`, `rh-php*`, `python27`, `rh-python*`, `rh-ruby*`, or `rh-ror*` packages, the order of uninstalling can be relevant due to ownership of dependent packages. As a consequence, some directories and files might not be removed properly and might remain on the system.

### **mariadb, mysql components, BZ#1194611**

Since **MariaDB 10** and **MySQL 5.6**, the `rh-mariadb*-mariadb-server` and `rh-mysql*-mysql-server` packages no longer provide the **test** database by default. Although this database is not created during initialization, the grant tables are prefilled with the same values as when **test** was created by default. As a consequence, upon a later creation of the **test** or **test\_\*** databases, these databases have less restricted access rights than is default for new databases.

Additionally, when running benchmarks, the **run-all-tests** script no longer works out of the box with example parameters. You need to create a test database before running the tests and specify the database name in the **--database** parameter. If the parameter is not specified, **test** is taken by default but you need to make sure the **test** database exist.

### **mariadb, mysql, postgresql, mongodb components**

Red Hat Software Collections contains the **MySQL 5.7**, **MySQL 8.0**, **MariaDB 10.2**, **MariaDB 10.3**, **PostgreSQL 9.6**, **PostgreSQL 10**, **PostgreSQL 12**, **MongoDB 3.4**, and **MongoDB 3.6** databases. The core Red Hat Enterprise Linux 6 provides earlier versions of the **MySQL** and **PostgreSQL** databases (client library and daemon). The core Red Hat Enterprise Linux 7 provides earlier versions of the **MariaDB** and **PostgreSQL** databases (client library and daemon). Client libraries are also used in database connectors for dynamic languages, libraries, and so on.

The client library packaged in the Red Hat Software Collections database packages in the **PostgreSQL** component is not supposed to be used, as it is included only for purposes of server utilities and the daemon. Users are instead expected to use the system library and the database connectors provided with the core system.

A protocol, which is used between the client library and the daemon, is stable across database versions, so, for example, using the **PostgreSQL 9.2** client library with the **PostgreSQL 9.4** or **9.5** daemon works as expected.

The core Red Hat Enterprise Linux 6 and Red Hat Enterprise Linux 7 do not include the client library for **MongoDB**. In order to use this client library for your application, you should use the client library from Red Hat Software Collections and always use the **scl enable ...** call every time you run an application linked against this **MongoDB** client library.

### **mariadb, mysql, mongodb components**

MariaDB, MySQL, and MongoDB do not make use of the `/opt/provider/collection/root` prefix when creating log files. Note that log files are saved in the `/var/opt/provider/collection/log/` directory, not in `/opt/provider/collection/root/var/log/`.

## **Other Notes**

### **rh-ruby\*, rh-python\*, rh-php\* components**

Using Software Collections on a read-only NFS has several limitations.

- Ruby gems cannot be installed while the `rh-ruby*` Software Collection is on a read-only NFS. Consequently, for example, when the user tries to install the `ab` gem using the **gem install ab** command, an error message is displayed, for example:

```
ERROR: While executing gem ... (Errno::EROFS)
  Read-only file system @ dir_s_mkdir - /opt/rh/rh-ruby22/root/usr/local/share/gems
```

The same problem occurs when the user tries to update or install gems from an external source by running the **bundle update** or **bundle install** commands.

- When installing Python packages on a read-only NFS using the Python Package Index (PyPI), running the **pip** command fails with an error message similar to this:

```
Read-only file system: '/opt/rh/rh-python34/root/usr/lib/python3.4/site-packages/ipython-3.1.0.dist-info'
```

- Installing packages from PHP Extension and Application Repository (PEAR) on a read-only NFS using the **pear** command fails with the error message:

```
Cannot install, php_dir for channel "pear.php.net" is not writeable by the current user
```

This is an expected behavior.

### httpd component

Language modules for Apache are supported only with the Red Hat Software Collections version of **Apache httpd** and not with the Red Hat Enterprise Linux system versions of **httpd**. For example, the **mod\_wsgi** module from the `rh-python35` Collection can be used only with the `httpd24` Collection.

### all components

Since Red Hat Software Collections 2.0, configuration files, variable data, and runtime data of individual Collections are stored in different directories than in previous versions of Red Hat Software Collections.

### coreutils, util-linux, screen components

Some utilities, for example, **su**, **login**, or **screen**, do not export environment settings in all cases, which can lead to unexpected results. It is therefore recommended to use **sudo** instead of **su** and set the **env\_keep** environment variable in the `/etc/sudoers` file. Alternatively, you can run commands in a reverse order; for example:

```
su -l postgres -c "scl enable rh-postgresql94 psql"
```

instead of

```
scl enable rh-postgresql94 bash
su -l postgres -c psql
```

When using tools like **screen** or **login**, you can use the following command to preserve the environment settings:

```
source /opt/rh/<collection_name>/enable
```

### python component

When the user tries to install more than one `scld` package from the `python27` and `rh-python*` Software Collections, a transaction check error message is returned. This is an expected behavior because the user can install only one set of the macro files provided by the packages (`%scl_python`,

`%scl_prefix_python`).

### php component

When the user tries to install more than one `sc-devel` package from the `rh-php*` Software Collections, a transaction check error message is returned. This is an expected behavior because the user can install only one set of the macro files provided by the packages (`%scl_php`, `%scl_prefix_php`).

### ruby component

When the user tries to install more than one `sc-devel` package from the `rh-ruby*` Software Collections, a transaction check error message is returned. This is an expected behavior because the user can install only one set of the macro files provided by the packages (`%scl_ruby`, `%scl_prefix_ruby`).

### perl component

When the user tries to install more than one `sc-devel` package from the `rh-perl*` Software Collections, a transaction check error message is returned. This is an expected behavior because the user can install only one set of the macro files provided by the packages (`%scl_perl`, `%scl_prefix_perl`).

### nginx component

When the user tries to install more than one `sc-devel` package from the `rh-nginx*` Software Collections, a transaction check error message is returned. This is an expected behavior because the user can install only one set of the macro files provided by the packages (`%scl_nginx`, `%scl_prefix_nginx`).

## 1.6. DEPRECATED FUNCTIONALITY

### httpd24 component, [BZ#1434053](#)

Previously, in an SSL/TLS configuration requiring name-based SSL virtual host selection, the `mod_ssl` module rejected requests with a **400 Bad Request** error, if the host name provided in the **Host:** header did not match the host name provided in a Server Name Indication (SNI) header. Such requests are no longer rejected if the configured SSL/TLS security parameters are identical between the selected virtual hosts, in-line with the behavior of upstream `mod_ssl`.

## CHAPTER 2. INSTALLATION

This chapter describes in detail how to get access to the content set, install Red Hat Software Collections 3.5 on the system, and rebuild Red Hat Software Collections.

### 2.1. GETTING ACCESS TO RED HAT SOFTWARE COLLECTIONS

The Red Hat Software Collections content set is available to customers with Red Hat Enterprise Linux 6 and Red Hat Enterprise Linux 7 subscriptions listed at <https://access.redhat.com/solutions/472793>. For information on how to register your system with Red Hat Subscription Management (RHSM), see [Using and Configuring Red Hat Subscription Manager](#). For detailed instructions on how to enable Red Hat Software Collections using RHSM, see [Section 2.1.1, “Using Red Hat Subscription Management”](#).

Since Red Hat Software Collections 2.2, the Red Hat Software Collections and Red Hat Developer Toolset content is available also in the ISO format at <https://access.redhat.com/downloads>, specifically for [Server](#) and [Workstation](#). Note that packages that require the **Optional** repository, which are listed in [Section 2.1.2, “Packages from the Optional Repository”](#), cannot be installed from the ISO image.



#### NOTE

Packages that require the **Optional** repository cannot be installed from the ISO image. A list of packages that require enabling of the **Optional** repository is provided in [Section 2.1.2, “Packages from the Optional Repository”](#).

Beta content is unavailable in the ISO format.

#### 2.1.1. Using Red Hat Subscription Management

If your system is registered with Red Hat Subscription Management, complete the following steps to attach the subscription that provides access to the repository for Red Hat Software Collections and enable the repository:

1. Display a list of all subscriptions that are available for your system and determine the pool ID of a subscription that provides Red Hat Software Collections. To do so, type the following at a shell prompt as **root**:

```
subscription-manager list --available
```

For each available subscription, this command displays its name, unique identifier, expiration date, and other details related to it. The pool ID is listed on a line beginning with **Pool Id**.

2. Attach the appropriate subscription to your system by running the following command as **root**:

```
subscription-manager attach --pool=pool_id
```

Replace *pool\_id* with the pool ID you determined in the previous step. To verify the list of subscriptions your system has currently attached, type as **root**:

```
subscription-manager list --consumed
```

3. Display the list of available Yum list repositories to retrieve repository metadata and determine the exact name of the Red Hat Software Collections repositories. As **root**, type:

### subscription-manager repos --list

Or alternatively, run **yum repolist all** for a brief list.

The repository names depend on the specific version of Red Hat Enterprise Linux you are using and are in the following format:

```
rhel-variant-rhsc-6-rpms
rhel-variant-rhsc-6-debug-rpms
rhel-variant-rhsc-6-source-rpms

rhel-server-rhsc-6-eus-rpms
rhel-server-rhsc-6-eus-source-rpms
rhel-server-rhsc-6-eus-debug-rpms

rhel-variant-rhsc-7-rpms
rhel-variant-rhsc-7-debug-rpms
rhel-variant-rhsc-7-source-rpms

rhel-server-rhsc-7-eus-rpms
rhel-server-rhsc-7-eus-source-rpms
rhel-server-rhsc-7-eus-debug-rpms>
```

Replace *variant* with the Red Hat Enterprise Linux system variant, that is, **server** or **workstation**. Note that Red Hat Software Collections is supported neither on the **Client** nor on the **ComputeNode** variant.

4. Enable the appropriate repository by running the following command as **root**:

### subscription-manager repos --enable *repository*

Once the subscription is attached to the system, you can install Red Hat Software Collections as described in [Section 2.2, "Installing Red Hat Software Collections"](#). For more information on how to register your system using Red Hat Subscription Management and associate it with subscriptions, see [Using and Configuring Red Hat Subscription Manager](#).



#### NOTE

Subscription through RHN is no longer available. For information how to migrate to RHSM, see <https://access.redhat.com/products/red-hat-subscription-management/#migration>.

## 2.1.2. Packages from the Optional Repository

Some of the Red Hat Software Collections packages require the **Optional** repository to be enabled in order to complete the full installation of these packages. For detailed instructions on how to subscribe your system to this repository, see the relevant Knowledgebase article at <https://access.redhat.com/solutions/392003>.

Packages from Software Collections for Red Hat Enterprise Linux that require the **Optional** repository to be enabled are listed in the tables below. Note that packages from the **Optional** repository are unsupported. For details, see the Knowledgebase article at <https://access.redhat.com/articles/1150793>.

**Table 2.1. Packages That Require Enabling of the Optional Repository in Red Hat Enterprise Linux 7**

Package from a Software Collection	Required Package from the Optional Repository
devtoolset-8-build	scl-utils-build
devtoolset-8-dyninst-testsuite	glibc-static
devtoolset-8-gcc-plugin-devel	libmpc-devel
devtoolset-9-build	scl-utils-build
devtoolset-9-dyninst-testsuite	glibc-static
devtoolset-9-gcc-plugin-devel	libmpc-devel
devtoolset-9-gdb	source-highlight
httpd24-mod_ldap	apr-util-ldap
httpd24-mod_session	apr-util-openssl
rh-git218-git-cvs	cvspcs
rh-git218-git-svn	subversion-perl
rh-git218-perl-Git-SVN	subversion-perl
rh-maven35-xpp3-javadoc	java-11-openjdk-javadoc
rh-php72-php-aspell	aspell
rh-php73-php-devel	pcre2-devel
rh-php73-php-aspell	aspell
rh-python36-python-devel	scl-utils-build
rh-python36-python-sphinx	texlive-threeparttable,texlive-wrapfig,texlive-titlesec,texlive-framed
rh-python38-python-devel	scl-utils-build

**Table 2.2. Packages That Require Enabling of the Optional Repository in Red Hat Enterprise Linux 6**



Package from a Software Collection	Required Package from the Optional Repository
devtoolset-8-build	scl-utils-build
devtoolset-8-dyninst-testsuite	glibc-static
devtoolset-8-elfutils-devel	xz-devel
devtoolset-8-gcc-plugin-devel	gmp-devel,mpfr-devel
devtoolset-8-libatomic-devel	libatomic
devtoolset-8-libgccjit	mpfr
rh-mariadb102-mariadb-bench	perl-GD
rh-mongodb34-boost-devel	libcxx-devel
rh-python36-python-devel	scl-utils-build

## 2.2. INSTALLING RED HAT SOFTWARE COLLECTIONS

Red Hat Software Collections is distributed as a collection of RPM packages that can be installed, updated, and uninstalled by using the standard package management tools included in Red Hat Enterprise Linux. Note that a valid subscription is required to install Red Hat Software Collections on your system. For detailed instructions on how to associate your system with an appropriate subscription and get access to Red Hat Software Collections, see [Section 2.1, “Getting Access to Red Hat Software Collections”](#).

Use of Red Hat Software Collections 3.5 requires the removal of any earlier pre-release versions. If you have installed any previous version of Red Hat Software Collections 2.1 component, uninstall it from your system and install the new version as described in the [Section 2.3, “Uninstalling Red Hat Software Collections”](#) and [Section 2.2.1, “Installing Individual Software Collections”](#) sections.

The in-place upgrade from Red Hat Enterprise Linux 6 to Red Hat Enterprise Linux 7 is not supported by Red Hat Software Collections. As a consequence, the installed Software Collections might not work correctly after the upgrade. If you want to upgrade from Red Hat Enterprise Linux 6 to Red Hat Enterprise Linux 7, it is strongly recommended to remove all Red Hat Software Collections packages, perform the in-place upgrade, update the Red Hat Software Collections repository, and install the Software Collections packages again. It is advisable to back up all data before upgrading.

### 2.2.1. Installing Individual Software Collections

To install any of the Software Collections that are listed in [Table 1.1, “Red Hat Software Collections Components”](#), install the corresponding meta package by typing the following at a shell prompt as **root**:

```
yum install software_collection...
```

Replace *software\_collection* with a space-separated list of Software Collections you want to install. For example, to install php54 and rh-mariadb100, type as **root**:

```
~]# yum install rh-php72 rh-mariadb102
```

This installs the main meta package for the selected Software Collection and a set of required packages as its dependencies. For information on how to install additional packages such as additional modules, see [Section 2.2.2, “Installing Optional Packages”](#).

### 2.2.2. Installing Optional Packages

Each component of Red Hat Software Collections is distributed with a number of optional packages that are not installed by default. To list all packages that are part of a certain Software Collection but are not installed on your system, type the following at a shell prompt:

```
yum list available software_collection^*
```

To install any of these optional packages, type as **root**:

```
yum install package_name...
```

Replace *package\_name* with a space-separated list of packages that you want to install. For example, to install the rh-perl526-perl-CPAN and rh-perl526-perl-Archive-Tar, type:

```
~]# yum install rh-perl526-perl-CPAN rh-perl526-perl-Archive-Tar
```

### 2.2.3. Installing Debugging Information

To install debugging information for any of the Red Hat Software Collections packages, make sure that the yum-utils package is installed and type the following command as **root**:

```
debuginfo-install package_name
```

For example, to install debugging information for the rh-ruby25-ruby package, type:

```
~]# debuginfo-install rh-ruby25-ruby
```

Note that you need to have access to the repository with these packages. If your system is registered with Red Hat Subscription Management, enable the **rhel-variant-rhsc1-6-debug-rpms** or **rhel-variant-rhsc1-7-debug-rpms** repository as described in [Section 2.1.1, “Using Red Hat Subscription Management”](#). For more information on how to get access to debuginfo packages, see <https://access.redhat.com/solutions/9907>.

## 2.3. UNINSTALLING RED HAT SOFTWARE COLLECTIONS

To uninstall any of the Software Collections components, type the following at a shell prompt as **root**:

```
yum remove software_collection^*
```

Replace *software\_collection* with the Software Collection component you want to uninstall.

Note that uninstallation of the packages provided by Red Hat Software Collections does not affect the Red Hat Enterprise Linux system versions of these tools.

## 2.4. REBUILDING RED HAT SOFTWARE COLLECTIONS

<collection>-build packages are not provided by default. If you wish to rebuild a collection and do not want or cannot use the **rpmbuild --define 'scl foo'** command, you first need to rebuild the metapackage, which provides the <collection>-build package.

Note that existing collections should not be rebuilt with different content. To add new packages into an existing collection, you need to create a new collection containing the new packages and make it dependent on packages from the original collection. The original collection has to be used without changes.

For detailed information on building Software Collections, refer to the [Red Hat Software Collections Packaging Guide](#).

## CHAPTER 3. USAGE

This chapter describes the necessary steps for using Red Hat Software Collections 3.5, and deploying applications that use Red Hat Software Collections.

### 3.1. USING RED HAT SOFTWARE COLLECTIONS

#### 3.1.1. Running an Executable from a Software Collection

To run an executable from a particular Software Collection, type the following command at a shell prompt:

```
scl enable software_collection... 'command...'
```

Or, alternatively, use the following command:

```
scl enable software_collection... -- command...
```

Replace *software\_collection* with a space-separated list of Software Collections you want to use and *command* with the command you want to run. For example, to execute a Perl program stored in a file named **hello.pl** with the Perl interpreter from the `perl526` Software Collection, type:

```
~]$ scl enable rh-perl526 'perl hello.pl'  
Hello, World!
```

You can execute any command using the **scl** utility, causing it to be run with the executables from a selected Software Collection in preference to their possible Red Hat Enterprise Linux system equivalents. For a complete list of Software Collections that are distributed with Red Hat Software Collections, see [Table 1.1, “Red Hat Software Collections Components”](#).

#### 3.1.2. Running a Shell Session with a Software Collection as Default

To start a new shell session with executables from a selected Software Collection in preference to their Red Hat Enterprise Linux equivalents, type the following at a shell prompt:

```
scl enable software_collection... bash
```

Replace *software\_collection* with a space-separated list of Software Collections you want to use. For example, to start a new shell session with the `python27` and `rh-postgresql10` Software Collections as default, type:

```
~]$ scl enable python27 rh-postgresql10 bash
```

The list of Software Collections that are enabled in the current session is stored in the **\$X\_SCLS** environment variable, for instance:

```
~]$ echo $X_SCLS  
python27 rh-postgresql10
```

For a complete list of Software Collections that are distributed with Red Hat Software Collections, see [Table 1.1, “Red Hat Software Collections Components”](#).

### 3.1.3. Running a System Service from a Software Collection

#### Running a System Service from a Software Collection in Red Hat Enterprise Linux 6

Software Collections that include system services install corresponding init scripts in the `/etc/rc.d/init.d/` directory. To start such a service in the current session, type the following at a shell prompt as **root**:

```
service software_collection-service_name start
```

Replace *software\_collection* with the name of the Software Collection and *service\_name* with the name of the service you want to start.

To configure this service to start automatically at boot time, type the following command as **root**:

```
chkconfig software_collection-service_name on
```

For example, to start the **postgresql** service from the `rh-postgresql96` Software Collection and enable it in runlevels 2, 3, 4, and 5, type as **root**:

```
~]# service rh-postgresql96-postgresql start
Starting rh-postgresql96-postgresql service:          [ OK ]
~]# chkconfig rh-postgresql96-postgresql on
```

For more information on how to manage system services in Red Hat Enterprise Linux 6, refer to the [Red Hat Enterprise Linux 6 Deployment Guide](#). For a complete list of Software Collections that are distributed with Red Hat Software Collections, see [Table 1.1, "Red Hat Software Collections Components"](#).

#### Running a System Service from a Software Collection in Red Hat Enterprise Linux 7

In Red Hat Enterprise Linux 7, init scripts have been replaced by **systemd** service unit files, which end with the **.service** file extension and serve a similar purpose as init scripts. To start a service in the current session, execute the following command as **root**:

```
systemctl start software_collection-service_name.service
```

Replace *software\_collection* with the name of the Software Collection and *service\_name* with the name of the service you want to start.

To configure this service to start automatically at boot time, type the following command as **root**:

```
systemctl enable software_collection-service_name.service
```

For example, to start the **postgresql** service from the `rh-postgresql10` Software Collection and enable it at boot time, type as **root**:

```
~]# systemctl start rh-postgresql10-postgresql.service
~]# systemctl enable rh-postgresql10-postgresql.service
```

For more information on how to manage system services in Red Hat Enterprise Linux 7, refer to the [Red Hat Enterprise Linux 7 System Administrator's Guide](#). For a complete list of Software Collections that are distributed with Red Hat Software Collections, see [Table 1.1, "Red Hat Software Collections Components"](#).

## 3.2. ACCESSING A MANUAL PAGE FROM A SOFTWARE COLLECTION

Every Software Collection contains a general manual page that describes the content of this component. Each manual page has the same name as the component and it is located in the `/opt/rh` directory.

To read a manual page for a Software Collection, type the following command:

```
scl enable software_collection 'man software_collection'
```

Replace *software\_collection* with the particular Red Hat Software Collections component. For example, to display the manual page for `rh-mariadb102`, type:

```
~]# scl enable rh-mariadb102 "man rh-mariadb102"
```

### 3.3. DEPLOYING APPLICATIONS THAT USE RED HAT SOFTWARE COLLECTIONS

In general, you can use one of the following two approaches to deploy an application that depends on a component from Red Hat Software Collections in production:

- Install all required Software Collections and packages manually and then deploy your application, or
- Create a new Software Collection for your application and specify all required Software Collections and other packages as dependencies.

For more information on how to manually install individual Red Hat Software Collections components, see [Section 2.2, “Installing Red Hat Software Collections”](#). For further details on how to use Red Hat Software Collections, see [Section 3.1, “Using Red Hat Software Collections”](#). For a detailed explanation of how to create a custom Software Collection or extend an existing one, read the [Red Hat Software Collections Packaging Guide](#).

### 3.4. RED HAT SOFTWARE COLLECTIONS CONTAINER IMAGES

Container images based on Red Hat Software Collections include applications, daemons, and databases. The images can be run on Red Hat Enterprise Linux 7 Server and Red Hat Enterprise Linux Atomic Host. For information about their usage, see [Using Red Hat Software Collections 3 Container Images](#). For details regarding container images based on Red Hat Software Collections versions 2.4 and earlier, see [Using Red Hat Software Collections 2 Container Images](#).

The following container images are available with Red Hat Software Collections 3.5:

- `rhsc/perl-530-rhel7`
- `rhsc/python-38-rhel7`
- `rhsc/ruby-26-rhel7`
- `rhsc/httpd-24-rhel7`
- `rhsc/varnish-6-rhel7`
- `rhsc/devtoolset-9-toolchain-rhel7`
- `rhsc/devtoolset-9-perftools-rhel7`

---

The following container images are based on Red Hat Software Collections 3.4:

- `rhsc/nodejs-12-rhel7`
- `rhsc/php-73-rhel7`
- `rhsc/nginx-116-rhel7`
- `rhsc/postgresql-12-rhel7`

The following container images are based on Red Hat Software Collections 3.3:

- `rhsc/mariadb-103-rhel7`
- `rhsc/redis-5-rhel7`
- `rhsc/ruby-26-rhel7`
- `rhsc/devtoolset-8-toolchain-rhel7`
- `rhsc/devtoolset-8-perftools-rhel7`

The following container images are based on Red Hat Software Collections 3.2:

- `rhsc/mysql-80-rhel7`
- `rhsc/nginx-114-rhel7`
- `rhsc/php-72-rhel7`
- `rhsc/nodejs-10-rhel7`

The following container images are based on Red Hat Software Collections 3.1:

- `rhsc/mongodb-36-rhel7`
- `rhsc/perl-526-rhel7`
- `rhsc/postgresql-10-rhel7`
- `rhsc/ruby-25-rhel7`
- `rhsc/varnish-5-rhel7`

The following container images are based on Red Hat Software Collections 3.0:

- `rhsc/mariadb-102-rhel7`
- `rhsc/mongodb-34-rhel7`
- `rhsc/postgresql-96-rhel7`
- `rhsc/python-36-rhel7`

The following container images are based on Red Hat Software Collections 2:

- `rhsc/python-27-rhel7`

- rhsc/s2i-base-rhel7



## CHAPTER 4. SPECIFICS OF INDIVIDUAL SOFTWARE COLLECTIONS

This chapter is focused on the specifics of certain Software Collections and provides additional details concerning these components.

### 4.1. RED HAT DEVELOPER TOOLSET

Red Hat Developer Toolset is designed for developers working on the Red Hat Enterprise Linux platform. Red Hat Developer Toolset provides current versions of the **GNU Compiler Collection**, **GNU Debugger**, and other development, debugging, and performance monitoring tools. Similarly to other Software Collections, an additional set of tools is installed into the `/opt/` directory. These tools are enabled by the user on demand using the supplied `scl` utility. Similarly to other Software Collections, these do not replace the Red Hat Enterprise Linux system versions of these tools, nor will they be used in preference to those system versions unless explicitly invoked using the `scl` utility.

For an overview of features, refer to the [Features](#) section of the *Red Hat Developer Toolset Release Notes*. For detailed information regarding usage and changes in 9.1, see the [Red Hat Developer Toolset User Guide](#).

### 4.2. MONGODB 3.6

The `rh-mongodb36` Software Collection is available only for Red Hat Enterprise Linux 7. See [Section 4.3, “MongoDB 3.4”](#) for instructions on how to use **MongoDB 3.4** on Red Hat Enterprise Linux 6.

To install the `rh-mongodb36` collection, type the following command as **root**:

```
yum install rh-mongodb36
```

To run the **MongoDB** shell utility, type the following command:

```
scl enable rh-mongodb36 'mongo'
```



#### NOTE

The `rh-mongodb36-mongo-cxx-driver` package has been built with the `-std=gnu++14` option using **GCC** from Red Hat Developer Toolset 6. Binaries using the shared library for the MongoDB C++ Driver that use C++11 (or later) features have to be built also with Red Hat Developer Toolset 6 or later. See C++ compatibility details in the [Red Hat Developer Toolset 6 User Guide](#).

To start the **MongoDB** daemon, type the following command as **root**:

```
systemctl start rh-mongodb36-mongod.service
```

To start the **MongoDB** daemon on boot, type this command as **root**:

```
systemctl enable rh-mongodb36-mongod.service
```

To start the **MongoDB** sharding server, type the following command as **root**:

**systemctl start rh-mongodb36-mongos.service**

To start the MongoDB sharding server on boot, type this command as **root**:

**systemctl enable rh-mongodb36-mongos.service**

Note that the MongoDB sharding server does not work unless the user starts at least one configuration server and specifies it in the **mongos.conf** file.

## 4.3. MONGODB 3.4

To install the rh-mongodb34 collection, type the following command as **root**:

**yum install rh-mongodb34**

To run the MongoDB shell utility, type the following command:

**scl enable rh-mongodb34 'mongo'****NOTE**

The rh-mongodb34-mongo-cxx-driver package has been built with the **-std=gnu++14** option using **GCC** from Red Hat Developer Toolset 6. Binaries using the shared library for the MongoDB C++ Driver that use C++11 (or later) features have to be built also with Red Hat Developer Toolset 6. See C++ compatibility details in the [Red Hat Developer Toolset 6 User Guide](#).

### MongoDB 3.4 on Red Hat Enterprise Linux 6

If you are using Red Hat Enterprise Linux 6, the following instructions apply to your system.

To start the MongoDB daemon, type the following command as **root**:

**service rh-mongodb34-mongod start**

To start the MongoDB daemon on boot, type this command as **root**:

**chkconfig rh-mongodb34-mongod on**

To start the MongoDB sharding server, type this command as **root**:

**service rh-mongodb34-mongos start**

To start the MongoDB sharding server on boot, type the following command as **root**:

**chkconfig rh-mongodb34-mongos on**

Note that the MongoDB sharding server does not work unless the user starts at least one configuration server and specifies it in the **mongos.conf** file.

### MongoDB 3.4 on Red Hat Enterprise Linux 7

When using Red Hat Enterprise Linux 7, the following commands are applicable.

To start the **MongoDB** daemon, type the following command as **root**:

```
systemctl start rh-mongodb34-mongod.service
```

To start the **MongoDB** daemon on boot, type this command as **root**:

```
systemctl enable rh-mongodb34-mongod.service
```

To start the **MongoDB** sharding server, type the following command as **root**:

```
systemctl start rh-mongodb34-mongos.service
```

To start the **MongoDB** sharding server on boot, type this command as **root**:

```
systemctl enable rh-mongodb34-mongos.service
```

Note that the **MongoDB** sharding server does not work unless the user starts at least one configuration server and specifies it in the **mongos.conf** file.

## 4.4. MAVEN

The **rh-maven36** Software Collection, available only for Red Hat Enterprise Linux 7, provides a software project management and comprehension tool. Based on the concept of a project object model (POM), **Maven** can manage a project's build, reporting, and documentation from a central piece of information.

To install the **rh-maven36** Collection, type the following command as **root**:

```
yum install rh-maven36
```

To enable this collection, type the following command at a shell prompt:

```
scl enable rh-maven36 bash
```

Global Maven settings, such as remote repositories or mirrors, can be customized by editing the **/opt/rh/rh-maven36/root/etc/maven/settings.xml** file.

For more information about using Maven, refer to the [Maven documentation](#). Usage of plug-ins is described in [this section](#); to find documentation regarding individual plug-ins, see the [index of plug-ins](#).

## 4.5. DATABASE CONNECTORS

Database connector packages provide the database client functionality, which is necessary for local or remote connection to a database server. [Table 4.1, "Interoperability Between Languages and Databases"](#) lists Software Collections with language runtimes that include connectors for certain database servers:

- **yes** - the combination is supported
- **no** - the combination is not supported

**Table 4.1. Interoperability Between Languages and Databases**

Language (Software Collection)	Database					
	MariaDB	MongoDB	MySQL	PostgreSQL	Redis	SQLite3
rh-nodejs4	no	no	no	no	no	no
rh-nodejs6	no	no	no	no	no	no
rh-nodejs8	no	no	no	no	no	no
rh-nodejs10	no	no	no	no	no	no
rh-nodejs12	no	no	no	no	no	no
rh-perl520	yes	no	yes	yes	no	no
rh-perl524	yes	no	yes	yes	no	no
rh-perl526	yes	no	yes	yes	no	no
rh-perl530	yes	no	yes	yes	no	yes
rh-php56	yes	yes	yes	yes	no	yes
rh-php70	yes	no	yes	yes	no	yes
rh-php71	yes	no	yes	yes	no	yes
rh-php72	yes	no	yes	yes	no	yes
rh-php73	yes	no	yes	yes	no	yes
python27	yes	yes	yes	yes	no	yes
rh-python34	no	yes	no	yes	no	yes
rh-python35	yes	yes	yes	yes	no	yes
rh-python36	yes	yes	yes	yes	no	yes
rh-python38	yes	no	yes	yes	no	yes
rh-ror41	yes	yes	yes	yes	no	yes
rh-ror42	yes	yes	yes	yes	no	yes

Language (Software Collection)	Database					
	MariaDB	MongoDB	MySQL	PostgreSQL	Redis	SQLite3
rh-ror50	yes	yes	yes	yes	no	yes
rh-ruby25	yes	yes	yes	yes	no	no
rh-ruby26	yes	yes	yes	yes	no	no
rh-ruby27	yes	yes	yes	yes	no	no

## CHAPTER 5. MIGRATION

This chapter provides information on migrating to versions of components included in Red Hat Software Collections 3.5.

### 5.1. MIGRATING TO MARIADB 10.3

The rh-mariadb103 Software Collection is available for Red Hat Enterprise Linux 7, which includes **MariaDB 5.5** as the default MySQL implementation.

The rh-mariadb103 Software Collection does not conflict with the `mysql` or `mariadb` packages from the core systems. Unless the `*-syspaths` packages are installed (see below), it is possible to install the rh-mariadb103 Software Collection together with the `mysql` or `mariadb` packages. It is also possible to run both versions at the same time, however, the port number and the socket in the **my.cnf** files need to be changed to prevent these specific resources from conflicting. Additionally, it is possible to install the rh-mariadb103 Software Collection while the rh-mariadb102 Collection is still installed and even running.

The rh-mariadb103 Software Collection includes the `rh-mariadb103-syspaths` package, which installs packages that provide system-wide wrappers for binaries, scripts, manual pages, and other. After installing the `rh-mariadb103*-syspaths` packages, users are not required to use the **scl enable** command for correct functioning of the binaries and scripts provided by the `rh-mariadb103*` packages. Note that the `*-syspaths` packages conflict with the corresponding packages from the base Red Hat Enterprise Linux system and from the rh-mariadb102 and rh-mysql80 Software Collections. To find out more about syspaths, see the [Red Hat Software Collections Packaging Guide](#).

The recommended migration path from **MariaDB 5.5** to **MariaDB 10.3** is to upgrade to **MariaDB 10.0** first, and then upgrade by one version successively. For details, see instructions in earlier Red Hat Software Collections Release Notes: [Migrating to MariaDB 10.0](#), [Migrating to MariaDB 10.1](#), and [Migrating to MariaDB 10.2](#).



#### NOTE


The rh-mariadb103 Software Collection supports neither mounting over NFS nor dynamical registering using the **scl register** command.

#### 5.1.1. Notable Differences Between the rh-mariadb102 and rh-mariadb103 Software Collections

- The `mariadb-bench` subpackage has been removed.
- The default allowed level of the plug-in maturity has been changed to one level less than the server maturity. As a result, plug-ins with a lower maturity level that were previously working, will no longer load.

For more information regarding **MariaDB 10.3**, see the upstream documentation about [changes](#) and about [upgrading](#).

#### 5.1.2. Upgrading from the rh-mariadb102 to the rh-mariadb103 Software Collection



#### IMPORTANT

Prior to upgrading, back up all your data, including any MariaDB databases.

1. Stop the rh-mariadb102 database server if it is still running.

Before stopping the server, set the **innodb\_fast\_shutdown** option to **0**, so that **InnoDB** performs a slow shutdown, including a full purge and insert buffer merge. Read more about this option in the [upstream documentation](#). This operation can take a longer time than in case of a normal shutdown.

```
mysql -uroot -p -e "SET GLOBAL innodb_fast_shutdown = 0"
```

Stop the rh-mariadb102 server.

```
systemctl stop rh-mariadb102-mariadb.service
```

2. Install the rh-mariadb103 Software Collection, including the subpackage providing the **mysql\_upgrade** utility.

```
yum install rh-mariadb103-mariadb-server rh-mariadb103-mariadb-server-utils
```

Note that it is possible to install the rh-mariadb103 Software Collection while the rh-mariadb102 Software Collection is still installed because these Collections do not conflict.

3. Inspect configuration of rh-mariadb103, which is stored in the **/etc/opt/rh/rh-mariadb103/my.cnf** file and the **/etc/opt/rh/rh-mariadb103/my.cnf.d/** directory. Compare it with configuration of rh-mariadb102 stored in **/etc/opt/rh/rh-mariadb102/my.cnf** and **/etc/opt/rh/rh-mariadb102/my.cnf.d/** and adjust it if necessary.
4. All data of the rh-mariadb102 Software Collection is stored in the **/var/opt/rh/rh-mariadb102/lib/mysql/** directory unless configured differently. Copy the whole content of this directory to **/var/opt/rh/rh-mariadb103/lib/mysql/**. You can move the content but remember to back up your data before you continue to upgrade. Make sure the data are owned by the **mysql** user and SELinux context is correct.
5. Start the rh-mariadb103 database server.

```
systemctl start rh-mariadb103-mariadb.service
```

6. Perform the data migration. Note that running the **mysql\_upgrade** command is required due to upstream changes introduced in [MDEV-14637](#).

```
scl enable rh-mariadb103 mysql_upgrade
```

If the **root** user has a non-empty password defined (it should have a password defined), it is necessary to call the **mysql\_upgrade** utility with the **-p** option and specify the password.

```
scl enable rh-mariadb103 -- mysql_upgrade -p
```

Note that when the rh-mariadb103\*-sypaths packages are installed, the **scl enable** command is not required. However, the \*-sypaths packages conflict with the corresponding packages from the base Red Hat Enterprise Linux system and from the rh-mariadb102 and rh-mysql80 Software Collections.


## 5.2. MIGRATING TO MARIADB 10.2

Red Hat Enterprise Linux 6 contains **MySQL 5.1** as the default **MySQL** implementation. Red Hat Enterprise Linux 7 includes **MariaDB 5.5** as the default **MySQL** implementation. **MariaDB** is a community-developed drop-in replacement for **MySQL**. **MariaDB 10.1** has been available as a Software Collection since Red Hat Software Collections 2.2; Red Hat Software Collections 3.5 is distributed with **MariaDB 10.2**.

The `rh-mariadb102` Software Collection, available for both Red Hat Enterprise Linux 6 and Red Hat Enterprise Linux 7, does not conflict with the `mysql` or `mariadb` packages from the core systems. Unless the `*-syspaths` packages are installed (see below), it is possible to install the `rh-mariadb102` Software Collection together with the `mysql` or `mariadb` packages. It is also possible to run both versions at the same time, however, the port number and the socket in the `my.cnf` files need to be changed to prevent these specific resources from conflicting. Additionally, it is possible to install the `rh-mariadb102` Software Collection while the `rh-mariadb101` Collection is still installed and even running.

The recommended migration path from **MariaDB 5.5** to **MariaDB 10.3** is to upgrade to **MariaDB 10.0** first, and then upgrade by one version successively. For details, see instructions in earlier Red Hat Software Collections Release Notes: [Migrating to MariaDB 10.0](#) and [Migrating to MariaDB 10.1](#).

For more information about **MariaDB 10.2**, see the upstream documentation about [changes in version 10.2](#) and about [upgrading](#).



#### NOTE

The `rh-mariadb102` Software Collection supports neither mounting over NFS nor dynamical registering using the `scl register` command.

### 5.2.1. Notable Differences Between the `rh-mariadb101` and `rh-mariadb102` Software Collections


Major changes in **MariaDB 10.2** are described in the [Red Hat Software Collections 3.0 Release Notes](#).

Since **MariaDB 10.2**, behavior of the `SQL_MODE` variable has been changed; see the [upstream documentation](#) for details.

Multiple options have changed their default values or have been deprecated or removed. For details, see the Knowledgebase article [Migrating from MariaDB 10.1 to the MariaDB 10.2 Software Collection](#).

The `rh-mariadb102` Software Collection includes the `rh-mariadb102-syspaths` package, which installs packages that provide system-wide wrappers for binaries, scripts, manual pages, and other. After installing the `rh-mariadb102*-syspaths` packages, users are not required to use the `scl enable` command for correct functioning of the binaries and scripts provided by the `rh-mariadb102*` packages. Note that the `*-syspaths` packages conflict with the corresponding packages from the base Red Hat Enterprise Linux system and from the `rh-mysql80` Software Collection. To find out more about `syspaths`, see the [Red Hat Software Collections Packaging Guide](#).

### 5.2.2. Upgrading from the `rh-mariadb101` to the `rh-mariadb102` Software Collection



#### IMPORTANT

Prior to upgrading, back up all your data, including any MariaDB databases.

1. Stop the `rh-mariadb101` database server if it is still running.

Before stopping the server, set the `innodb_fast_shutdown` option to `0`, so that **InnoDB**



performs a slow shutdown, including a full purge and insert buffer merge. Read more about this option in the [upstream documentation](#). This operation can take a longer time than in case of a normal shutdown.

```
mysql -uroot -p -e "SET GLOBAL innodb_fast_shutdown = 0"
```

Stop the rh-mariadb101 server.

```
service rh-mariadb101-mariadb stop
```

2. Install the rh-mariadb102 Software Collection.

```
yum install rh-mariadb102-mariadb-server
```

Note that it is possible to install the rh-mariadb102 Software Collection while the rh-mariadb101 Software Collection is still installed because these Collections do not conflict.

3. Inspect configuration of rh-mariadb102, which is stored in the `/etc/opt/rh/rh-mariadb102/my.cnf` file and the `/etc/opt/rh/rh-mariadb102/my.cnf.d/` directory. Compare it with configuration of rh-mariadb101 stored in `/etc/opt/rh/rh-mariadb101/my.cnf` and `/etc/opt/rh/rh-mariadb101/my.cnf.d/` and adjust it if necessary.
4. All data of the rh-mariadb101 Software Collection is stored in the `/var/opt/rh/rh-mariadb101/lib/mysql/` directory unless configured differently. Copy the whole content of this directory to `/var/opt/rh/rh-mariadb102/lib/mysql/`. You can move the content but remember to back up your data before you continue to upgrade. Make sure the data are owned by the **mysql** user and SELinux context is correct.
5. Start the rh-mariadb102 database server.

```
service rh-mariadb102-mariadb start
```

6. Perform the data migration.

```
scl enable rh-mariadb102 mysql_upgrade
```

If the **root** user has a non-empty password defined (it should have a password defined), it is necessary to call the **mysql\_upgrade** utility with the **-p** option and specify the password.

```
scl enable rh-mariadb102 -- mysql_upgrade -p
```

Note that when the rh-mariadb102\*-syspaths packages are installed, the **scl enable** command is not required. However, the \*-syspaths packages conflict with the corresponding packages from the base Red Hat Enterprise Linux system and from the rh-mysql80 Software Collection.

### 5.3. MIGRATING TO MYSQL 8.0

The rh-mysql80 Software Collection is available for Red Hat Enterprise Linux 7, which includes **MariaDB 5.5** as the default **MySQL** implementation.

The rh-mysql80 Software Collection conflicts neither with the **mysql** or **mariadb** packages from the core systems nor with the rh-mysql\* or rh-mariadb\* Software Collections, unless the \*-syspaths packages are installed (see below). It is also possible to run multiple versions at the same time; however,

the port number and the socket in the **my.cnf** files need to be changed to prevent these specific resources from conflicting.

Note that it is possible to upgrade to **MySQL 8.0** only from **MySQL 5.7**. If you need to upgrade from an earlier version, upgrade to **MySQL 5.7** first. For instructions, see [Migration to MySQL 5.7](#).

### 5.3.1. Notable Differences Between MySQL 5.7 and MySQL 8.0

#### Differences Specific to the rh-mysql80 Software Collection

- The **MySQL 8.0** server provided by the rh-mysql80 Software Collection is configured to use **mysql\_native\_password** as the default authentication plug-in because client tools and libraries in Red Hat Enterprise Linux 7 are incompatible with the **caching\_sha2\_password** method, which is used by default in the upstream **MySQL 8.0** version.

To change the default authentication plug-in to **caching\_sha2\_password**, edit the **/etc/opt/rh/rh-mysql80/my.cnf.d/mysql-default-authentication-plugin.cnf** file as follows:

```
[mysqld]
default_authentication_plugin=caching_sha2_password
```

For more information about the **caching\_sha2\_password** authentication plug-in, see the [upstream documentation](#).

- The rh-mysql80 Software Collection includes the rh-mysql80-syspaths package, which installs the rh-mysql80-mysql-config-syspaths, rh-mysql80-mysql-server-syspaths, and rh-mysql80-mysql-syspaths packages. These subpackages provide system-wide wrappers for binaries, scripts, manual pages, and other. After installing the rh-mysql80\*-syspaths packages, users are not required to use the **scl enable** command for correct functioning of the binaries and scripts provided by the rh-mysql80\* packages. Note that the \*-syspaths packages conflict with the corresponding packages from the base Red Hat Enterprise Linux system and from the rh-mariadb102 and rh-mariadb103 Software Collections. To find out more about syspaths, see the [Red Hat Software Collections Packaging Guide](#).


#### General Changes in MySQL 8.0

- Binary logging is enabled by default during the server startup. The **log\_bin** system variable is now set to **ON** by default even if the **--log-bin** option has not been specified. To disable binary logging, specify the **--skip-log-bin** or **--disable-log-bin** option at startup.
- For a **CREATE FUNCTION** statement to be accepted, at least one of the **DETERMINISTIC**, **NO SQL**, or **READS SQL DATA** keywords must be specified explicitly, otherwise an error occurs.
- Certain features related to account management have been removed. Namely, using the **GRANT** statement to modify account properties other than privilege assignments, such as authentication, SSL, and resource-limit, is no longer possible. To establish the mentioned properties at account-creation time, use the **CREATE USER** statement. To modify these properties, use the **ALTER USER** statement.
- Certain SSL-related options have been removed on the client-side. Use the **--ssl-mode=REQUIRED** option instead of **--ssl=1** or **--enable-ssl**. Use the **--ssl-mode=DISABLED** option instead of **--ssl=0**, **--skip-ssl**, or **--disable-ssl**. Use the **--ssl-mode=VERIFY\_IDENTITY** option instead of **--ssl-verify-server-cert** options. Note that these option remains unchanged on the server side.
- The default character set has been changed from **latin1** to **utf8mb4**.

- The **utf8** character set is currently an alias for **utf8mb3** but in the future, it will become a reference to **utf8mb4**. To prevent ambiguity, specify **utf8mb4** explicitly for character set references instead of **utf8**.
- Setting user variables in statements other than **SET** has been deprecated.
- The **log\_syslog** variable, which previously configured error logging to the system logs, has been removed.
- Certain incompatible changes to spatial data support have been introduced.
- The deprecated **ASC** or **DESC** qualifiers for **GROUP BY** clauses have been removed. To produce a given sort order, provide an **ORDER BY** clause.

For detailed changes in **MySQL 8.0** compared to earlier versions, see the upstream documentation: [What Is New in MySQL 8.0](#) and [Changes Affecting Upgrades to MySQL 8.0](#).

### 5.3.2. Upgrading to the rh-mysql80 Software Collection



#### IMPORTANT

Prior to upgrading, back-up all your data, including any MySQL databases.

1. Install the rh-mysql80 Software Collection.

```
yum install rh-mysql80-mysql-server
```

2. Inspect the configuration of rh-mysql80, which is stored in the `/etc/opt/rh/rh-mysql80/my.cnf` file and the `/etc/opt/rh/rh-mysql80/my.cnf.d/` directory. Compare it with the configuration of rh-mysql57 stored in `/etc/opt/rh/rh-mysql57/my.cnf` and `/etc/opt/rh/rh-mysql57/my.cnf.d/` and adjust it if necessary.
3. Stop the rh-mysql57 database server, if it is still running.

```
systemctl stop rh-mysql57-mysqld.service
```

4. All data of the rh-mysql57 Software Collection is stored in the `/var/opt/rh/rh-mysql57/lib/mysql/` directory. Copy the whole content of this directory to `/var/opt/rh/rh-mysql80/lib/mysql/`. You can also move the content but remember to back up your data before you continue to upgrade.
5. Start the rh-mysql80 database server.

```
systemctl start rh-mysql80-mysqld.service
```

6. Perform the data migration.

```
scl enable rh-mysql80 mysql_upgrade
```

If the **root** user has a non-empty password defined (it should have a password defined), it is necessary to call the **mysql\_upgrade** utility with the **-p** option and specify the password.

```
scl enable rh-mysql80 -- mysql_upgrade -p
```

-

Note that when the `rh-mysql80*-syspaths` packages are installed, the **scl enable** command is not required. However, the `*-syspaths` packages conflict with the corresponding packages from the base Red Hat Enterprise Linux system and from the `rh-mariadb102` and `rh-mariadb103` Software Collections.

## 5.4. MIGRATING TO MONGODB 3.6

Red Hat Software Collections 3.5 is released with **MongoDB 3.6**, provided by the `rh-mongodb36` Software Collection and available only for Red Hat Enterprise Linux 7.

The `rh-mongodb36` Software Collection includes the `rh-mongodb36-syspaths` package, which installs packages that provide system-wide wrappers for binaries, scripts, manual pages, and other. After installing the `rh-mongodb36*-syspaths` packages, users are not required to use the **scl enable** command for correct functioning of the binaries and scripts provided by the `rh-mongodb36*` packages. To find out more about `syspaths`, see the [Red Hat Software Collections Packaging Guide](#).

### 5.4.1. Notable Differences Between MongoDB 3.4 and MongoDB 3.6

#### General Changes

The `rh-mongodb36` Software Collection introduces the following significant general change:

- On Non-Uniform Access Memory (NUMA) hardware, it is possible to configure **systemd** services to be launched using the **numactl** command; see the [upstream recommendation](#). To use **MongoDB** with the **numactl** command, you need to install the `numactl` RPM package and change the `/etc/opt/rh/rh-mongodb36/sysconfig/mongod` and `/etc/opt/rh/rh-mongodb36/sysconfig/mongos` configuration files accordingly.

#### Compatibility Changes

**MongoDB 3.6** includes various minor changes that can affect compatibility with previous versions of **MongoDB**:

- **MongoDB** binaries now bind to **localhost** by default, so listening on different IP addresses needs to be explicitly enabled. Note that this is already the default behavior for **systemd** services distributed with **MongoDB** Software Collections.
- The MONGODB-CR authentication mechanism has been deprecated. For databases with users created by **MongoDB** versions earlier than 3.0, upgrade authentication schema to [SCRAM](#).
- The HTTP interface and REST API have been removed
- Arbiters in replica sets have priority **0**
- Master-slave replication has been deprecated

For detailed compatibility changes in **MongoDB 3.6**, see the [upstream release notes](#).

#### Backwards Incompatible Features


The following **MongoDB 3.6** features are backwards incompatible and require the version to be set to 3.6 using the **featureCompatibilityVersion** command:

- UUID for collections
- **\$jsonSchema** document validation
- Change streams

- Chunk aware secondaries
- View definitions, document validators, and partial index filters that use version 3.6 query features
- Sessions and retryable writes
- Users and roles with **authenticationRestrictions**

For details regarding backward incompatible changes in **MongoDB 3.6**, see the [upstream release notes](#).

## 5.4.2. Upgrading from the rh-mongodb34 to the rh-mongodb36 Software Collection



### IMPORTANT

Before migrating from the rh-mongodb34 to the rh-mongodb36 Software Collection, back up all your data, including any **MongoDB** databases, which are by default stored in the `/var/opt/rh/rh-mongodb34/lib/mongodb/` directory. In addition, see the [Compatibility Changes](#) to ensure that your applications and deployments are compatible with **MongoDB 3.6**.

To upgrade to the rh-mongodb36 Software Collection, perform the following steps.

1. To be able to upgrade, the rh-mongodb34 instance must have **featureCompatibilityVersion** set to **3.4**. Check **featureCompatibilityVersion**:

```
~]$ scli enable rh-mongodb34 'mongo --host localhost --port 27017 admin' --eval
'db.adminCommand({getParameter: 1, featureCompatibilityVersion: 1})'
```

If the **mongod** server is configured with enabled access control, add the **--username** and **--password** options to the **mongo** command.

2. Install the **MongoDB** servers and shells from the rh-mongodb36 Software Collections:

```
~]# yum install rh-mongodb36
```

3. Stop the **MongoDB 3.4** server:

```
~]# systemctl stop rh-mongodb34-mongod.service
```

4. Copy your data to the new location:

```
~]# cp -a /var/opt/rh/rh-mongodb34/lib/mongodb/* /var/opt/rh/rh-
mongodb36/lib/mongodb/
```

5. Configure the **rh-mongodb36-mongod** daemon in the `/etc/opt/rh/rh-mongodb36/mongod.conf` file.

6. Start the **MongoDB 3.6** server:

```
~]# systemctl start rh-mongodb36-mongod.service
```

7. Enable backwards incompatible features:

```
~]$ scli enable rh-mongodb36 'mongo --host localhost --port 27017 admin' --eval
'db.adminCommand( { setFeatureCompatibilityVersion: "3.6" } )'
```

If the **mongod** server is configured with enabled access control, add the **--username** and **--password** options to the **mongo** command.



#### NOTE

After upgrading, it is recommended to run the deployment first without enabling the backwards incompatible features for a burn-in period of time, to minimize the likelihood of a downgrade.

For detailed information about upgrading, see the [upstream release notes](#).

For information about upgrading a Replica Set, see the upstream [MongoDB Manual](#).

For information about upgrading a Sharded Cluster, see the upstream [MongoDB Manual](#).

## 5.5. MIGRATING TO MONGODB 3.4

The rh-mongodb34 Software Collection, available for both Red Hat Enterprise Linux 6 and Red Hat Enterprise Linux 7, provides **MongoDB 3.4**.

### 5.5.1. Notable Differences Between MongoDB 3.2 and MongoDB 3.4

#### General Changes

The rh-mongodb34 Software Collection introduces various general changes. Major changes are listed in the Knowledgebase article [Migrating from MongoDB 3.2 to MongoDB 3.4](#). For detailed changes, see the [upstream release notes](#).

In addition, this Software Collection includes the rh-mongodb34-syspaths package, which installs packages that provide system-wide wrappers for binaries, scripts, manual pages, and other. After installing the rh-mongodb34\*-syspaths packages, users are not required to use the **scli enable** command for correct functioning of the binaries and scripts provided by the rh-mongodb34\* packages. To find out more about syspaths, see the [Red Hat Software Collections Packaging Guide](#).

#### Compatibility Changes

**MongoDB 3.4** includes various minor changes that can affect compatibility with previous versions of **MongoDB**. For details, see the Knowledgebase article [Migrating from MongoDB 3.2 to MongoDB 3.4](#) and the [upstream documentation](#).


Notably, the following **MongoDB 3.4** features are backwards incompatible and require that the version is set to **3.4** using the **featureCompatibilityVersion** command:

- Support for creating read-only views from existing collections or other views
- Index version **v: 2**, which adds support for collation, decimal data and case-insensitive indexes
- Support for the **decimal128** format with the new **decimal** data type

For details regarding backward incompatible changes in **MongoDB 3.4**, see the [upstream release notes](#).

## 5.5.2. Upgrading from the rh-mongodb32 to the rh-mongodb34 Software Collection

Note that once you have upgraded to **MongoDB 3.4** and started using new features, cannot downgrade to version 3.2.7 or earlier. You can only downgrade to version 3.2.8 or later.



### IMPORTANT

Before migrating from the rh-mongodb32 to the rh-mongodb34 Software Collection, back up all your data, including any **MongoDB** databases, which are by default stored in the `/var/opt/rh/rh-mongodb32/lib/mongodb/` directory. In addition, see the compatibility changes to ensure that your applications and deployments are compatible with **MongoDB 3.4**.

To upgrade to the rh-mongodb34 Software Collection, perform the following steps.

1. Install the **MongoDB** servers and shells from the rh-mongodb34 Software Collections:

```
~]# yum install rh-mongodb34
```

2. Stop the **MongoDB 3.2** server:

```
~]# systemctl stop rh-mongodb32-mongod.service
```

Use the **service rh-mongodb32-mongod stop** command on a Red Hat Enterprise Linux 6 system.

3. Copy your data to the new location:

```
~]# cp -a /var/opt/rh/rh-mongodb32/lib/mongodb/* /var/opt/rh/rh-mongodb34/lib/mongodb/
```

4. Configure the **rh-mongodb34-mongod** daemon in the `/etc/opt/rh/rh-mongodb34/mongod.conf` file.

5. Start the **MongoDB 3.4** server:

```
~]# systemctl start rh-mongodb34-mongod.service
```

On Red Hat Enterprise Linux 6, use the **service rh-mongodb34-mongod start** command instead.

6. Enable backwards-incompatible features:

```
~]$ scl enable rh-mongodb34 'mongo --host localhost --port 27017 admin' --eval 'db.adminCommand( { setFeatureCompatibilityVersion: "3.4" } )'
```

If the **mongod** server is configured with enabled access control, add the **--username** and **--password** options to **mongo** command.

Note that it is recommended to run the deployment after the upgrade without enabling these features first.

For detailed information about upgrading, see the [upstream release notes](#).

For information about upgrading a Replica Set, see the upstream [MongoDB Manual](#).

For information about upgrading a Sharded Cluster, see the upstream [MongoDB Manual](#).

## 5.6. MIGRATING TO POSTGRESQL 12

Red Hat Software Collections 3.5 is distributed with **PostgreSQL 12**, available only for Red Hat Enterprise Linux 7. The `rh-postgresql12` Software Collection can be safely installed on the same machine in parallel with the base Red Hat Enterprise Linux system version of **PostgreSQL** or any **PostgreSQL** Software Collection. It is also possible to run more than one version of **PostgreSQL** on a machine at the same time, but you need to use different ports or IP addresses and adjust SELinux policy. See [Section 5.7, “Migrating to PostgreSQL 9.6”](#) for instructions how to migrate to an earlier version or when using Red Hat Enterprise Linux 6.

The `rh-postgresql12` Software Collection includes the `rh-postgresql12-syspaths` package, which installs packages that provide system-wide wrappers for binaries, scripts, manual pages, and other. After installing the `rh-postgresql12*-syspaths` packages, users are not required to use the **scl enable** command for correct functioning of the binaries and scripts provided by the `rh-postgresql12*` packages. Note that the `*-syspaths` packages conflict with the corresponding packages from the base Red Hat Enterprise Linux system. To find out more about `syspaths`, see the [Red Hat Software Collections Packaging Guide](#).



### IMPORTANT

Before migrating to **PostgreSQL 12**, see the upstream compatibility notes for [PostgreSQL 11](#) and [PostgreSQL 12](#).

In case of upgrading the **PostgreSQL** database in a container, see the [container-specific instructions](#).

The following table provides an overview of different paths in a Red Hat Enterprise Linux 7 system version of **PostgreSQL** provided by the `postgresql` package, and in the `rh-postgresql10` and `rh-postgresql12` Software Collections.

**Table 5.1. Differences in the PostgreSQL paths**

Content	postgresql	rh-postgresql10	rh-postgresql12
Executables	<code>/usr/bin/</code>	<code>/opt/rh/rh-postgresql10/root/usr/bin/</code>	<code>/opt/rh/rh-postgresql12/root/usr/bin/</code>
Libraries	<code>/usr/lib64/</code>	<code>/opt/rh/rh-postgresql10/root/usr/lib64/</code>	<code>/opt/rh/rh-postgresql12/root/usr/lib64/</code>
Documentation	<code>/usr/share/doc/postgresql/html/</code>	<code>/opt/rh/rh-postgresql10/root/usr/share/doc/postgresql/html/</code>	<code>/opt/rh/rh-postgresql12/root/usr/share/doc/postgresql/html/</code>



Content	postgresql	rh-postgresql10	rh-postgresql12
PDF documentation	/usr/share/doc/postgresql-docs/	/opt/rh/rh-postgresql10/root/usr/share/doc/postgresql-docs/	/opt/rh/rh-postgresql12/root/usr/share/doc/postgresql-docs/
Contrib documentation	/usr/share/doc/postgresql-contrib/	/opt/rh/rh-postgresql10/root/usr/share/doc/postgresql-contrib/	/opt/rh/rh-postgresql12/root/usr/share/doc/postgresql-contrib/
Source	not installed	not installed	not installed
Data	/var/lib/pgsql/data/	/var/opt/rh/rh-postgresql10/lib/pgsql/data/	/var/opt/rh/rh-postgresql12/lib/pgsql/data/
Backup area	/var/lib/pgsql/backups/	/var/opt/rh/rh-postgresql10/lib/pgsql/backups/	/var/opt/rh/rh-postgresql12/lib/pgsql/backups/
Templates	/usr/share/pgsql/	/opt/rh/rh-postgresql10/root/usr/share/pgsql/	/opt/rh/rh-postgresql12/root/usr/share/pgsql/
Procedural Languages	/usr/lib64/pgsql/	/opt/rh/rh-postgresql10/root/usr/lib64/pgsql/	/opt/rh/rh-postgresql12/root/usr/lib64/pgsql/
Development Headers	/usr/include/pgsql/	/opt/rh/rh-postgresql10/root/usr/include/pgsql/	/opt/rh/rh-postgresql12/root/usr/include/pgsql/
Other shared data	/usr/share/pgsql/	/opt/rh/rh-postgresql10/root/usr/share/pgsql/	/opt/rh/rh-postgresql12/root/usr/share/pgsql/
Regression tests	/usr/lib64/pgsql/test/regress/ (in the -test package)	/opt/rh/rh-postgresql10/root/usr/lib64/pgsql/test/regress/ (in the -test package)	/opt/rh/rh-postgresql12/root/usr/lib64/pgsql/test/regress/ (in the -test package)

### 5.6.1. Migrating from a Red Hat Enterprise Linux System Version of PostgreSQL to the PostgreSQL 12 Software Collection

Red Hat Enterprise Linux 7 is distributed with **PostgreSQL 9.2**. To migrate your data from a Red Hat Enterprise Linux system version of **PostgreSQL** to the rh-postgresql12 Software Collection, you can either perform a fast upgrade using the **pg\_upgrade** tool (recommended), or dump the database data into a text file with SQL commands and import it in the new database. Note that the second method is usually significantly slower and may require manual fixes; see the [PostgreSQL documentation](#) for more information about this upgrade method.



## IMPORTANT

Before migrating your data from a Red Hat Enterprise Linux system version of PostgreSQL to PostgreSQL 12, make sure that you back up all your data, including the PostgreSQL database files, which are *by default* located in the `/var/lib/pgsql/data/` directory.

### Procedure 5.1. Fast Upgrade Using the `pg_upgrade` Tool

To perform a fast upgrade of your PostgreSQL server, complete the following steps:

1. Stop the old PostgreSQL server to ensure that the data is not in an inconsistent state. To do so, type the following at a shell prompt as **root**:

```
systemctl stop postgresql.service
```

To verify that the server is not running, type:

```
systemctl status postgresql.service
```

2. Verify that the old directory `/var/lib/pgsql/data/` exists:

```
file /var/lib/pgsql/data/
```

and back up your data.

3. Verify that the new data directory `/var/opt/rh/rh-postgresql12/lib/pgsql/data/` does not exist:

```
file /var/opt/rh/rh-postgresql12/lib/pgsql/data/
```

If you are running a fresh installation of **PostgreSQL 12**, this directory should not be present in your system. If it is, back it up by running the following command as **root**:

```
mv /var/opt/rh/rh-postgresql12/lib/pgsql/data{-,scl-backup}
```

4. Upgrade the database data for the new server by running the following command as **root**:

```
scl enable rh-postgresql12 -- postgresql-setup --upgrade
```

Alternatively, you can use the `/opt/rh/rh-postgresql12/root/usr/bin/postgresql-setup --upgrade` command.

Note that you can use the `--upgrade-from` option for upgrade from different versions of **PostgreSQL**. The list of possible upgrade scenarios is available using the `--upgrade-ids` option.

It is recommended that you read the resulting `/var/lib/pgsql/upgrade_rh-postgresql12-postgresql.log` log file to find out if any problems occurred during the upgrade.

5. Start the new server as **root**:

```
systemctl start rh-postgresql12-postgresql.service
```

It is also advised that you run the `analyze_new_cluster.sh` script as follows:

```
su - postgres -c 'scl enable rh-postgresql12 ~/analyze_new_cluster.sh'
```

- Optionally, you can configure the PostgreSQL 12 server to start automatically at boot time. To disable the old system PostgreSQL server, type the following command as **root**:

```
chkconfig postgresql off
```

To enable the PostgreSQL 12 server, type as **root**:

```
chkconfig rh-postgresql12-postgresql on
```

- If your configuration differs from the default one, make sure to update configuration files, especially the `/var/opt/rh/rh-postgresql12/lib/pgsql/data/pg_hba.conf` configuration file. Otherwise only the **postgres** user will be allowed to access the database.

### Procedure 5.2. Performing a Dump and Restore Upgrade

To perform a dump and restore upgrade of your PostgreSQL server, complete the following steps:

- Ensure that the old PostgreSQL server is running by typing the following at a shell prompt as **root**:

```
systemctl start postgresql.service
```

- Dump all data in the PostgreSQL database into a script file. As **root**, type:

```
su - postgres -c 'pg_dumpall > ~/pgdump_file.sql'
```

- Stop the old server by running the following command as **root**:

```
systemctl stop postgresql.service
```

- Initialize the data directory for the new server as **root**:

```
scl enable rh-postgresql12 -- postgresql-setup initdb
```

- Start the new server as **root**:

```
systemctl start rh-postgresql12-postgresql.service
```

- Import data from the previously created SQL file:

```
su - postgres -c 'scl enable rh-postgresql12 "psql -f ~/pgdump_file.sql postgres"'
```

- Optionally, you can configure the PostgreSQL 12 server to start automatically at boot time. To disable the old system PostgreSQL server, type the following command as **root**:

```
chkconfig postgresql off
```

To enable the PostgreSQL 12 server, type as **root**:

-

## chkconfig rh-postgresql12-postgresql on

- If your configuration differs from the default one, make sure to update configuration files, especially the `/var/opt/rh/rh-postgresql12/lib/pgsql/data/pg_hba.conf` configuration file. Otherwise only the **postgres** user will be allowed to access the database.

## 5.6.2. Migrating from the PostgreSQL 10 Software Collection to the PostgreSQL 12 Software Collection

To migrate your data from the rh-postgresql10 Software Collection to the rh-postgresql12 Collection, you can either perform a fast upgrade using the **pg\_upgrade** tool (recommended), or dump the database data into a text file with SQL commands and import it in the new database. Note that the second method is usually significantly slower and may require manual fixes; see the [PostgreSQL documentation](#) for more information about this upgrade method.



### IMPORTANT

Before migrating your data from **PostgreSQL 10** to **PostgreSQL 12**, make sure that you back up all your data, including the PostgreSQL database files, which are by default located in the `/var/opt/rh/rh-postgresql10/lib/pgsql/data/` directory.

### Procedure 5.3. Fast Upgrade Using the `pg_upgrade` Tool

To perform a fast upgrade of your PostgreSQL server, complete the following steps:

- Stop the old PostgreSQL server to ensure that the data is not in an inconsistent state. To do so, type the following at a shell prompt as **root**:

```
systemctl stop rh-postgresql10-postgresql.service
```

To verify that the server is not running, type:

```
systemctl status rh-postgresql10-postgresql.service
```

- Verify that the old directory `/var/opt/rh/rh-postgresql10/lib/pgsql/data/` exists:

```
file /var/opt/rh/rh-postgresql10/lib/pgsql/data/
```

and back up your data.

- Verify that the new data directory `/var/opt/rh/rh-postgresql12/lib/pgsql/data/` does not exist:

```
file /var/opt/rh/rh-postgresql12/lib/pgsql/data/
```

If you are running a fresh installation of **PostgreSQL 12**, this directory should not be present in your system. If it is, back it up by running the following command as **root**:

```
mv /var/opt/rh/rh-postgresql12/lib/pgsql/data{-,scl-backup}
```

- Upgrade the database data for the new server by running the following command as **root**:

```
scl enable rh-postgresql12 -- postgresql-setup --upgrade --upgrade-from=rh-  
postgresql10-postgresql
```

Alternatively, you can use the `/opt/rh/rh-postgresql12/root/usr/bin/postgresql-setup --upgrade --upgrade-from=rh-postgresql10-postgresql` command.

Note that you can use the `--upgrade-from` option for upgrading from different versions of PostgreSQL. The list of possible upgrade scenarios is available using the `--upgrade-ids` option.

It is recommended that you read the resulting `/var/lib/pgsql/upgrade_rh-postgresql12-postgresql.log` log file to find out if any problems occurred during the upgrade.

5. Start the new server as **root**:

```
systemctl start rh-postgresql12-postgresql.service
```

It is also advised that you run the `analyze_new_cluster.sh` script as follows:

```
su - postgres -c 'scl enable rh-postgresql12 ~/analyze_new_cluster.sh'
```

6. Optionally, you can configure the PostgreSQL 12 server to start automatically at boot time. To disable the old PostgreSQL 10 server, type the following command as **root**:

```
chkconfig rh-postgresql10-postgresql off
```

To enable the PostgreSQL 12 server, type as **root**:

```
chkconfig rh-postgresql12-postgresql on
```

7. If your configuration differs from the default one, make sure to update configuration files, especially the `/var/opt/rh/rh-postgresql12/lib/pgsql/data/pg_hba.conf` configuration file. Otherwise only the **postgres** user will be allowed to access the database.

#### Procedure 5.4. Performing a Dump and Restore Upgrade

To perform a dump and restore upgrade of your PostgreSQL server, complete the following steps:

1. Ensure that the old PostgreSQL server is running by typing the following at a shell prompt as **root**:

```
systemctl start rh-postgresql10-postgresql.service
```

2. Dump all data in the PostgreSQL database into a script file. As **root**, type:

```
su - postgres -c 'scl enable rh-postgresql10 "pg_dumpall > ~/pgdump_file.sql"'
```

3. Stop the old server by running the following command as **root**:

```
systemctl stop rh-postgresql10-postgresql.service
```

4. Initialize the data directory for the new server as **root**:

```
scl enable rh-postgresql12 -- postgresql-setup initdb
```

5. Start the new server as **root**:

```
systemctl start rh-postgresql12-postgresql.service
```

6. Import data from the previously created SQL file:

```
su - postgres -c 'scl enable rh-postgresql12 "psql -f ~/pgdump_file.sql postgres"'
```

7. Optionally, you can configure the PostgreSQL 12 server to start automatically at boot time. To disable the old PostgreSQL 10 server, type the following command as **root**:

```
chkconfig rh-postgresql10-postgresql off
```

To enable the PostgreSQL 12 server, type as **root**:

```
chkconfig rh-postgresql12-postgresql on
```

8. If your configuration differs from the default one, make sure to update configuration files, especially the `/var/opt/rh/rh-postgresql12/lib/pgsql/data/pg_hba.conf` configuration file. Otherwise only the **postgres** user will be allowed to access the database.

## 5.7. MIGRATING TO POSTGRESQL 9.6

**PostgreSQL 9.6** is available for both Red Hat Enterprise Linux 6 and Red Hat Enterprise Linux 7 and it can be safely installed on the same machine in parallel with **PostgreSQL 8.4** from Red Hat Enterprise Linux 6, **PostgreSQL 9.2** from Red Hat Enterprise Linux 7, or any version of **PostgreSQL** released in previous versions of Red Hat Software Collections. It is also possible to run more than one version of **PostgreSQL** on a machine at the same time, but you need to use different ports or IP addresses and adjust SELinux policy.



### IMPORTANT

In case of upgrading the **PostgreSQL** database in a container, see the [container-specific instructions](#). Note that it is currently impossible to upgrade **PostgreSQL** from 9.5 to 9.6 in a container in an OpenShift environment that is configured with Gluster file volumes.

### 5.7.1. Notable Differences Between PostgreSQL 9.5 and PostgreSQL 9.6

The most notable changes between **PostgreSQL 9.5** and **PostgreSQL 9.6** are described in the [upstream release notes](#).

The `rh-postgresql96` Software Collection includes the `rh-postgresql96-syspaths` package, which installs packages that provide system-wide wrappers for binaries, scripts, manual pages, and other. After installing the `rh-postgresql96*-syspaths` packages, users are not required to use the **scl enable** command for correct functioning of the binaries and scripts provided by the `rh-postgresql96*` packages. Note that the `*-syspaths` packages conflict with the corresponding packages from the base Red Hat Enterprise Linux system. To find out more about `syspaths`, see the [Red Hat Software Collections Packaging Guide](#).

The following table provides an overview of different paths in a Red Hat Enterprise Linux system version

of **PostgreSQL** (postgresql) and in the postgresql92, rh-postgresql95, and rh-postgresql96 Software Collections. Note that the paths of **PostgreSQL 8.4** distributed with Red Hat Enterprise Linux 6 and the system version of **PostgreSQL 9.2** shipped with Red Hat Enterprise Linux 7 are the same; the paths for the rh-postgresql94 Software Collection are analogous to rh-postgresql95.

**Table 5.2. Differences in the PostgreSQL paths**

Content	postgresql	postgresql92	rh-postgresql95	rh-postgresql96
Executables	/usr/bin/	/opt/rh/postgresql92 /root/usr/bin/	/opt/rh/rh- postgresql95/root/us r/bin/	/opt/rh/rh- postgresql96/root/us r/bin/
Libraries	/usr/lib64/	/opt/rh/postgresql92 /root/usr/lib64/	/opt/rh/rh- postgresql95/root/us r/lib64/	/opt/rh/rh- postgresql96/root/us r/lib64/
Documenta tion	/usr/share/doc /postgresql/ht ml/	/opt/rh/postgresql92 /root/usr/share/doc/ postgresql/html/	/opt/rh/rh- postgresql95/root/us r/share/doc/postgres ql/html/	/opt/rh/rh- postgresql96/root/us r/share/doc/postgres ql/html/
PDF documentat ion	/usr/share/doc /postgresql- docs/	/opt/rh/postgresql92 /root/usr/share/doc/ postgresql-docs/	/opt/rh/rh- postgresql95/root/us r/share/doc/postgres ql-docs/	/opt/rh/rh- postgresql96/root/us r/share/doc/postgres ql-docs/
Contrib documentat ion	/usr/share/doc /postgresql- contrib/	/opt/rh/postgresql92 /root/usr/share/doc/ postgresql-contrib/	/opt/rh/rh- postgresql95/root/us r/share/doc/postgres ql-contrib/	/opt/rh/rh- postgresql96/root/us r/share/doc/postgres ql-contrib/
Source	not installed	not installed	not installed	not installed
Data	/var/lib/pgsql/ data/	/opt/rh/postgresql92 /root/var/lib/pgsql/d ata/	/var/opt/rh/rh- postgresql95/lib/pgs ql/data/	/var/opt/rh/rh- postgresql96/lib/pgs ql/data/
Backup area	/var/lib/pgsql/ backups/	/opt/rh/postgresql92 /root/var/lib/pgsql/b ackups/	/var/opt/rh/rh- postgresql95/lib/pgs ql/backups/	/var/opt/rh/rh- postgresql96/lib/pgs ql/backups/
Templates	/usr/share/pgs ql/	/opt/rh/postgresql92 /root/usr/share/pgs ql/ /	/opt/rh/rh- postgresql95/root/us r/share/pgs ql/	/opt/rh/rh- postgresql96/root/us r/share/pgs ql/
Procedural Languages	/usr/lib64/pgs ql/	/opt/rh/postgresql92 /root/usr/lib64/pgs ql/ /	/opt/rh/rh- postgresql95/root/us r/lib64/pgs ql/	/opt/rh/rh- postgresql96/root/us r/lib64/pgs ql/

Content	postgresql	postgresql92	rh-postgresql95	rh-postgresql96
Development Headers	/usr/include/postgresql/	/opt/rh/postgresql92/root/usr/include/postgresql/	/opt/rh/rh-postgresql95/root/usr/include/postgresql/	/opt/rh/rh-postgresql96/root/usr/include/postgresql/
Other shared data	/usr/share/postgresql/	/opt/rh/postgresql92/root/usr/share/postgresql/	/opt/rh/rh-postgresql95/root/usr/share/postgresql/	/opt/rh/rh-postgresql96/root/usr/share/postgresql/
Regression tests	/usr/lib64/postgresql/test/regress/ (in the -test package)	/opt/rh/postgresql92/root/usr/lib64/postgresql/test/regress/ (in the -test package)	/opt/rh/rh-postgresql95/root/usr/lib64/postgresql/test/regress/ (in the -test package)	/opt/rh/rh-postgresql96/root/usr/lib64/postgresql/test/regress/ (in the -test package)

For changes between **PostgreSQL 8.4** and **PostgreSQL 9.2**, refer to the [Red Hat Software Collections 1.2 Release Notes](#). Notable changes between **PostgreSQL 9.2** and **PostgreSQL 9.4** are described in [Red Hat Software Collections 2.0 Release Notes](#). For differences between **PostgreSQL 9.4** and **PostgreSQL 9.5**, refer to [Red Hat Software Collections 2.2 Release Notes](#).

### 5.7.2. Migrating from a Red Hat Enterprise Linux System Version of PostgreSQL to the PostgreSQL 9.6 Software Collection

Red Hat Enterprise Linux 6 includes **PostgreSQL 8.4**, Red Hat Enterprise Linux 7 is distributed with **PostgreSQL 9.2**. To migrate your data from a Red Hat Enterprise Linux system version of **PostgreSQL** to the rh-postgresql96 Software Collection, you can either perform a fast upgrade using the **pg\_upgrade** tool (recommended), or dump the database data into a text file with SQL commands and import it in the new database. Note that the second method is usually significantly slower and may require manual fixes; see the [PostgreSQL documentation](#) for more information about this upgrade method. The following procedures are applicable for both Red Hat Enterprise Linux 6 and Red Hat Enterprise Linux 7 system versions of **PostgreSQL**.



#### IMPORTANT

Before migrating your data from a Red Hat Enterprise Linux system version of PostgreSQL to PostgreSQL 9.6, make sure that you back up all your data, including the PostgreSQL database files, which are *by default* located in the **/var/lib/postgresql/data/** directory.

#### Procedure 5.5. Fast Upgrade Using the **pg\_upgrade** Tool

To perform a fast upgrade of your PostgreSQL server, complete the following steps:

1. Stop the old PostgreSQL server to ensure that the data is not in an inconsistent state. To do so, type the following at a shell prompt as **root**:

```
service postgresql stop
```

To verify that the server is not running, type:



```
service postgresql status
```

2. Verify that the old directory `/var/lib/pgsql/data/` exists:

```
file /var/lib/pgsql/data/
```

and back up your data.

3. Verify that the new data directory `/var/opt/rh/rh-postgresql96/lib/pgsql/data/` does not exist:

```
file /var/opt/rh/rh-postgresql96/lib/pgsql/data/
```

If you are running a fresh installation of **PostgreSQL 9.6**, this directory should not be present in your system. If it is, back it up by running the following command as **root**:

```
mv /var/opt/rh/rh-postgresql96/lib/pgsql/data{-,scl-backup}
```

4. Upgrade the database data for the new server by running the following command as **root**:

```
scl enable rh-postgresql96 -- postgresql-setup --upgrade
```

Alternatively, you can use the `/opt/rh/rh-postgresql96/root/usr/bin/postgresql-setup --upgrade` command.

Note that you can use the `--upgrade-from` option for upgrade from different versions of **PostgreSQL**. The list of possible upgrade scenarios is available using the `--upgrade-ids` option.

It is recommended that you read the resulting `/var/lib/pgsql/upgrade_rh-postgresql96-postgresql.log` log file to find out if any problems occurred during the upgrade.

5. Start the new server as **root**:

```
service rh-postgresql96-postgresql start
```

It is also advised that you run the `analyze_new_cluster.sh` script as follows:

```
su - postgres -c 'scl enable rh-postgresql96 ~/analyze_new_cluster.sh'
```

6. Optionally, you can configure the PostgreSQL 9.6 server to start automatically at boot time. To disable the old system PostgreSQL server, type the following command as **root**:

```
chkconfig postgresql off
```

To enable the PostgreSQL 9.6 server, type as **root**:

```
chkconfig rh-postgresql96-postgresql on
```

7. If your configuration differs from the default one, make sure to update configuration files, especially the `/var/opt/rh/rh-postgresql96/lib/pgsql/data/pg_hba.conf` configuration file. Otherwise only the **postgres** user will be allowed to access the database.

## Procedure 5.6. Performing a Dump and Restore Upgrade

To perform a dump and restore upgrade of your PostgreSQL server, complete the following steps:

1. Ensure that the old PostgreSQL server is running by typing the following at a shell prompt as **root**:

```
service postgresql start
```

2. Dump all data in the PostgreSQL database into a script file. As **root**, type:

```
su - postgres -c 'pg_dumpall > ~/pgdump_file.sql'
```

3. Stop the old server by running the following command as **root**:

```
service postgresql stop
```

4. Initialize the data directory for the new server as **root**:

```
scl enable rh-postgresql96-postgresql -- postgresql-setup --initdb
```

5. Start the new server as **root**:

```
service rh-postgresql96-postgresql start
```

6. Import data from the previously created SQL file:

```
su - postgres -c 'scl enable rh-postgresql96 "psql -f ~/pgdump_file.sql postgres"'
```

7. Optionally, you can configure the PostgreSQL 9.6 server to start automatically at boot time. To disable the old system PostgreSQL server, type the following command as **root**:

```
chkconfig postgresql off
```

To enable the PostgreSQL 9.6 server, type as **root**:

```
chkconfig rh-postgresql96-postgresql on
```

8. If your configuration differs from the default one, make sure to update configuration files, especially the `/var/opt/rh/rh-postgresql96/lib/pgsql/data/pg_hba.conf` configuration file. Otherwise only the **postgres** user will be allowed to access the database.

### 5.7.3. Migrating from the PostgreSQL 9.5 Software Collection to the PostgreSQL 9.6 Software Collection

To migrate your data from the rh-postgresql95 Software Collection to the rh-postgresql96 Collection, you can either perform a fast upgrade using the **pg\_upgrade** tool (recommended), or dump the database data into a text file with SQL commands and import it in the new database. Note that the second method is usually significantly slower and may require manual fixes; see the [PostgreSQL documentation](#) for more information about this upgrade method.



## IMPORTANT

Before migrating your data from **PostgreSQL 9.5** to **PostgreSQL 9.6**, make sure that you back up all your data, including the PostgreSQL database files, which are by default located in the `/var/opt/rh/rh-postgresql95/lib/pgsql/data/` directory.

### Procedure 5.7. Fast Upgrade Using the `pg_upgrade` Tool

To perform a fast upgrade of your PostgreSQL server, complete the following steps:

1. Stop the old PostgreSQL server to ensure that the data is not in an inconsistent state. To do so, type the following at a shell prompt as **root**:

```
service rh-postgresql95-postgresql stop
```

To verify that the server is not running, type:

```
service rh-postgresql95-postgresql status
```

2. Verify that the old directory `/var/opt/rh/rh-postgresql95/lib/pgsql/data/` exists:

```
file /var/opt/rh/rh-postgresql95/lib/pgsql/data/
```

and back up your data.

3. Verify that the new data directory `/var/opt/rh/rh-postgresql96/lib/pgsql/data/` does not exist:

```
file /var/opt/rh/rh-postgresql96/lib/pgsql/data/
```

If you are running a fresh installation of **PostgreSQL 9.6**, this directory should not be present in your system. If it is, back it up by running the following command as **root**:

```
mv /var/opt/rh/rh-postgresql96/lib/pgsql/data{-,scl-backup}
```

4. Upgrade the database data for the new server by running the following command as **root**:

```
scl enable rh-postgresql96 -- postgresql-setup --upgrade --upgrade-from=rh-postgresql95-postgresql
```

Alternatively, you can use the `/opt/rh/rh-postgresql96/root/usr/bin/postgresql-setup --upgrade --upgrade-from=rh-postgresql95-postgresql` command.

Note that you can use the `--upgrade-from` option for upgrading from different versions of **PostgreSQL**. The list of possible upgrade scenarios is available using the `--upgrade-ids` option.

It is recommended that you read the resulting `/var/lib/pgsql/upgrade_rh-postgresql96-postgresql.log` log file to find out if any problems occurred during the upgrade.

5. Start the new server as **root**:

```
service rh-postgresql96-postgresql start
```

It is also advised that you run the `analyze_new_cluster.sh` script as follows:

```
su - postgres -c 'scl enable rh-postgresql96 ~/analyze_new_cluster.sh'
```

6. Optionally, you can configure the PostgreSQL 9.6 server to start automatically at boot time. To disable the old PostgreSQL 9.5 server, type the following command as **root**:

```
chkconfig rh-postgresql95-postgresql off
```

To enable the PostgreSQL 9.6 server, type as **root**:

```
chkconfig rh-postgresql96-postgresql on
```

7. If your configuration differs from the default one, make sure to update configuration files, especially the `/var/opt/rh/rh-postgresql96/lib/pgsql/data/pg_hba.conf` configuration file. Otherwise only the **postgres** user will be allowed to access the database.

### Procedure 5.8. Performing a Dump and Restore Upgrade

To perform a dump and restore upgrade of your PostgreSQL server, complete the following steps:

1. Ensure that the old PostgreSQL server is running by typing the following at a shell prompt as **root**:

```
service rh-postgresql95-postgresql start
```

2. Dump all data in the PostgreSQL database into a script file. As **root**, type:

```
su - postgres -c 'scl enable rh-postgresql95 "pg_dumpall > ~/pgdump_file.sql"'
```

3. Stop the old server by running the following command as **root**:

```
service rh-postgresql95-postgresql stop
```

4. Initialize the data directory for the new server as **root**:

```
scl enable rh-postgresql96-postgresql -- postgresql-setup --initdb
```

5. Start the new server as **root**:

```
service rh-postgresql96-postgresql start
```

6. Import data from the previously created SQL file:

```
su - postgres -c 'scl enable rh-postgresql96 "psql -f ~/pgdump_file.sql postgres"'
```

7. Optionally, you can configure the PostgreSQL 9.6 server to start automatically at boot time. To disable the old PostgreSQL 9.5 server, type the following command as **root**:

```
chkconfig rh-postgresql95-postgresql off
```

To enable the PostgreSQL 9.6 server, type as **root**:

-

## chkconfig rh-postgresql96-postgresql on

- If your configuration differs from the default one, make sure to update configuration files, especially the `/var/opt/rh/rh-postgresql96/lib/pgsql/data/pg_hba.conf` configuration file. Otherwise only the **postgres** user will be allowed to access the database.

If you need to migrate from the postgresql92 Software Collection, refer to [Red Hat Software Collections 2.0 Release Notes](#); the procedure is the same, you just need to adjust the version of the new Collection. The same applies to migration from the rh-postgresql94 Software Collection, which is described in [Red Hat Software Collections 2.2 Release Notes](#).

## 5.8. MIGRATING TO NGINX 1.16

The root directory for the rh-nginx116 Software Collection is located in `/opt/rh/rh-nginx116/root/`. The error log is stored in `/var/opt/rh/rh-nginx116/log/nginx` by default.

Configuration files are stored in the `/etc/opt/rh/rh-nginx116/nginx/` directory. Configuration files in **nginx 1.16** have the same syntax and largely the same format as previous **nginx** Software Collections.

Configuration files (with a `.conf` extension) in the `/etc/opt/rh/rh-nginx116/nginx/default.d/` directory are included in the default server block configuration for port **80**.



### IMPORTANT

Before upgrading from **nginx 1.14** to **nginx 1.16**, back up all your data, including web pages located in the `/opt/rh/nginx114/root/` tree and configuration files located in the `/etc/opt/rh/nginx114/nginx/` tree.

If you have made any specific changes, such as changing configuration files or setting up web applications, in the `/opt/rh/nginx114/root/` tree, replicate those changes in the new `/opt/rh/rh-nginx116/root/` and `/etc/opt/rh/rh-nginx116/nginx/` directories, too.

You can use this procedure to upgrade directly from **nginx 1.8**, **nginx 1.10**, **nginx 1.12**, or **nginx 1.14** to **nginx 1.16**. Use the appropriate paths in this case.

For the official **nginx** documentation, refer to <http://nginx.org/en/docs/>.

## 5.9. MIGRATING TO REDIS 5

**Redis 3.2**, provided by the rh-redis32 Software Collection, is mostly a strict subset of **Redis 4.0**, which is mostly a strict subset of **Redis 5.0**. Therefore, no major issues should occur when upgrading from version 3.2 to version 5.0.

To upgrade a **Redis** Cluster to version 5.0, a mass restart of all the instances is needed.

### Compatibility Notes

- The format of RDB files has been changed. **Redis 5** is able to read formats of all the earlier versions, but earlier versions are incapable of reading the **Redis 5** format.
- Since version 4.0, the **Redis** Cluster bus protocol is no longer compatible with **Redis 3.2**.
- For minor non-backward compatible changes, see the upstream release notes for [version 4.0](#) and [version 5.0](#).

## CHAPTER 6. ADDITIONAL RESOURCES

This chapter provides references to other relevant sources of information about Red Hat Software Collections 3.5 and Red Hat Enterprise Linux.

### 6.1. RED HAT PRODUCT DOCUMENTATION

The following documents are directly or indirectly relevant to this book:

- [Red Hat Software Collections 3.5 Packaging Guide](#) – The *Packaging Guide* for Red Hat Software Collections explains the concept of Software Collections, documents the **scl** utility, and provides a detailed explanation of how to create a custom Software Collection or extend an existing one.
- [Red Hat Developer Toolset 9.1 Release Notes](#) – The *Release Notes* for Red Hat Developer Toolset document known problems, possible issues, changes, and other important information about this Software Collection.
- [Red Hat Developer Toolset 9.1 User Guide](#) – The *User Guide* for Red Hat Developer Toolset contains more information about installing and using this Software Collection.
- [Using Red Hat Software Collections Container Images](#) – This book provides information on how to use container images based on Red Hat Software Collections. The available container images include applications, daemons, databases, as well as the Red Hat Developer Toolset container images. The images can be run on Red Hat Enterprise Linux 7 Server and Red Hat Enterprise Linux Atomic Host.
- [Getting Started with Containers](#) – This guide contains a comprehensive overview of information about building and using container images on Red Hat Enterprise Linux 7 and Red Hat Enterprise Linux Atomic Host.
- [Using and Configuring Red Hat Subscription Manager](#) – The *Using and Configuring Red Hat Subscription Manager* book provides detailed information on how to register Red Hat Enterprise Linux systems, manage subscriptions, and view notifications for the registered systems.
- [Red Hat Enterprise Linux 6 Deployment Guide](#) – The *Deployment Guide* for Red Hat Enterprise Linux 6 provides relevant information regarding the deployment, configuration, and administration of this system.
- [Red Hat Enterprise Linux 7 System Administrator's Guide](#) – The *System Administrator's Guide* for Red Hat Enterprise Linux 7 provides information on deployment, configuration, and administration of this system.

### 6.2. RED HAT DEVELOPERS

- [Red Hat Developer Program](#) – The *Red Hat Developers* community portal.
- [Overview of Red Hat Software Collections on Red Hat Developers](#) – The *Red Hat Developers* portal provides a number of tutorials to get you started with developing code using different development technologies. This includes the Node.js, Perl, PHP, Python, and Ruby Software Collections.
- [Red Hat Developer Blog](#) – The *Red Hat Developer Blog* contains up-to-date information, best practices, opinion, product and program announcements as well as pointers to sample code and

other resources for those who are designing and developing applications based on Red Hat technologies.

## APPENDIX A. REVISION HISTORY

<b>Revision 3.5-2</b> Updated <a href="#">Section 4.5, "Database Connectors"</a> .	<b>Fri Nov 12 2021</b>	<b>Lenka Špačková</b>
<b>Revision 3.5-1</b> Release of Red Hat Software Collections 3.5 Release Notes.	<b>Tue May 26 2020</b>	<b>Lenka Špačková</b>
<b>Revision 3.5-0</b> Release of Red Hat Software Collections 3.5 Beta Release Notes.	<b>Tue Apr 21 2020</b>	<b>Lenka Špačková</b>