



Red Hat OpenStack Platform 16.2

Back Up and Restore the Director Undercloud

Back up and restore the Red Hat OpenStack Platform director undercloud

Red Hat OpenStack Platform 16.2 Back Up and Restore the Director Undercloud

Back up and restore the Red Hat OpenStack Platform director undercloud

OpenStack Team
rhos-docs@redhat.com

Legal Notice

Copyright © 2021 Red Hat, Inc.

The text of and illustrations in this document are licensed by Red Hat under a Creative Commons Attribution–Share Alike 3.0 Unported license ("CC-BY-SA"). An explanation of CC-BY-SA is available at

<http://creativecommons.org/licenses/by-sa/3.0/>

. In accordance with CC-BY-SA, if you distribute this document or an adaptation of it, you must provide the URL for the original version.

Red Hat, as the licensor of this document, waives the right to enforce, and agrees not to assert, Section 4d of CC-BY-SA to the fullest extent permitted by applicable law.

Red Hat, Red Hat Enterprise Linux, the Shadowman logo, the Red Hat logo, JBoss, OpenShift, Fedora, the Infinity logo, and RHCE are trademarks of Red Hat, Inc., registered in the United States and other countries.

Linux[®] is the registered trademark of Linus Torvalds in the United States and other countries.

Java[®] is a registered trademark of Oracle and/or its affiliates.

XFS[®] is a trademark of Silicon Graphics International Corp. or its subsidiaries in the United States and/or other countries.

MySQL[®] is a registered trademark of MySQL AB in the United States, the European Union and other countries.

Node.js[®] is an official trademark of Joyent. Red Hat is not formally related to or endorsed by the official Joyent Node.js open source or commercial project.

The OpenStack[®] Word Mark and OpenStack logo are either registered trademarks/service marks or trademarks/service marks of the OpenStack Foundation, in the United States and other countries and are used with the OpenStack Foundation's permission. We are not affiliated with, endorsed or sponsored by the OpenStack Foundation, or the OpenStack community.

All other trademarks are the property of their respective owners.

Abstract

You can back up the database and critical filesystems on your undercloud node and restore them to a newly installed undercloud node.

Table of Contents

MAKING OPEN SOURCE MORE INCLUSIVE	3
PROVIDING FEEDBACK ON RED HAT DOCUMENTATION	4
CHAPTER 1. BACKING UP THE DIRECTOR UNDERCLOUD	5
1.1. BACKING UP A CONTAINERIZED UNDERCLOUD	5
CHAPTER 2. RESTORING THE DIRECTOR UNDERCLOUD	7
2.1. RESTORING A CONTAINERIZED UNDERCLOUD	7
2.2. VALIDATING THE UNDERCLOUD RESTORATION	10

MAKING OPEN SOURCE MORE INCLUSIVE

Red Hat is committed to replacing problematic language in our code, documentation, and web properties. We are beginning with these four terms: master, slave, blacklist, and whitelist. Because of the enormity of this endeavor, these changes will be implemented gradually over several upcoming releases. For more details, see [our CTO Chris Wright's message](#).

PROVIDING FEEDBACK ON RED HAT DOCUMENTATION

We appreciate your input on our documentation. Tell us how we can make it better.

Using the Direct Documentation Feedback (DDF) function

Use the **Add Feedback** DDF function for direct comments on specific sentences, paragraphs, or code blocks.

1. View the documentation in the *Multi-page HTML* format.
2. Ensure that you see the **Feedback** button in the upper right corner of the document.
3. Highlight the part of text that you want to comment on.
4. Click **Add Feedback**.
5. Complete the **Add Feedback** field with your comments.
6. Optional: Add your email address so that the documentation team can contact you for clarification on your issue.
7. Click **Submit**.

CHAPTER 1. BACKING UP THE DIRECTOR UNDERCLOUD

To minimize data loss and system downtime, you can create and recover backups of the database and critical filesystems that run on the Red Hat OpenStack Platform (RHOSP) director undercloud node. The undercloud is usually a single physical node, although high availability (HA) options exist that use a two-node pacemaker cluster that runs director in a virtual machine instance.

Red Hat does not prescribe any particular requirements for HA on the undercloud node. You can implement undercloud HA that is suitable for your environment. For example, you can run your undercloud node as a highly available virtual machine with Red Hat Enterprise Virtualization (RHEV). You can also use physical nodes with Pacemaker that provide HA for the required services.

To validate the success of the completed backup process, you can run and validate the restoration process. For more information, see [Chapter 2, Restoring the director undercloud](#).

1.1. BACKING UP A CONTAINERIZED UNDERCLOUD

A full undercloud backup includes the following databases and files:

- All MariaDB databases on the undercloud node
- MariaDB configuration file on the undercloud so that you can accurately restore databases
- The configuration data: **/etc**
- Log data: **/var/log**
- Image data: **/var/lib/glance**
- Certificate generation data if using SSL: **/var/lib/certmonger**
- Any container image data: **/var/lib/containers** and **/var/lib/image-serve**
- All swift data: **/srv/node**
- All data in the stack user home directory: **/home/stack**

Prerequisites

- You have a minimum of 3.5 GB of available space on the undercloud for the archive file.

Procedure

1. Log in to the undercloud as the **root** user.
2. Retrieve the MySQL root password:

```
[root@director ~]# PASSWORD=$(/bin/hiera -c /etc/puppet/hiera.yaml
mysql::server::root_password)
```

3. Perform the backup:

```
[root@director ~]# podman exec mysql bash -c "mysqldump -uroot -p$PASSWORD --opt --
all-databases" > /root/undercloud-all-databases.sql
```

4. Archive the database backup and the configuration files:

```
[root@director ~]# cd /backup
[root@director backup]# tar --xattrs --xattrs-include='*.*' --ignore-failed-read -cf \
  undercloud-backup-`date +%F`.tar \
  /root/undercloud-all-databases.sql \
  /etc \
  /var/log \
  /var/lib/glance \
  /var/lib/certmonger \
  /var/lib/containers \
  /var/lib/image-serve \
  /var/lib/config-data \
  /srv/node \
  /root \
  /home/stack
```

- The **--ignore-failed-read** option skips any directory that does not apply to your undercloud.
- The **--xattrs** option includes extended attributes, which are required to store metadata for Object Storage (swift).

This command creates a file named **undercloud-backup-<timestamp>.tar**, where **<timestamp>** is the system date. Copy this **tar** file to a secure location.

CHAPTER 2. RESTORING THE DIRECTOR UNDERCLOUD

You can use your Red Hat OpenStack Platform (RHOSP) undercloud backup to restore the undercloud data on to a newly installed undercloud node in your deployment.

As a result, the restored undercloud uses the latest packages.

2.1. RESTORING A CONTAINERIZED UNDERCLOUD

If the undercloud node in your deployment has failed and is in an unrecoverable state, you can restore the database and critical file systems on to a newly deployed undercloud node.

Prerequisites

- You have created an undercloud backup archive of your director undercloud databases and files. For more information, see [Section 1.1, “Backing up a containerized undercloud”](#)
- You have re-installed the Red Hat Enterprise Linux (RHEL) 8.4.
- The new undercloud node has the same hardware resources as the failed node.
- Ensure that, for the new undercloud node in your deployment, you use the same hostname and undercloud settings as the failed node.

Procedure

1. Log in to your new undercloud node as the **root** user.
2. Register your system with the Content Delivery Network and enter your Customer Portal user name and password at the prompt:

```
[root@director ~]# subscription-manager register
```

3. Attach the RHOSP entitlement:

```
[root@director ~]# subscription-manager attach --pool=<pool_number>
```

4. Disable all default repositories, and enable the required RHEL repositories:

```
[root@director ~]# subscription-manager repos --disable=*
[root@director ~]# subscription-manager repos \
--enable=rhel-8-for-x86_64-baseos-eus-\
--enable=rhel-8-for-x86_64-appstream-eus-\
--enable=rhel-8-for-x86_64-highavailability-eus-\
--enable=ansible-2.9-for-rhel-8-x86_64-\
--enable=openstack-16.2-for-rhel-8-x86_64-\
--enable=fast-datapath-for-rhel-8-x86_64-\
--enable=advanced-virt-for-rhel-8-x86_64-rpms
```

5. Set the **container-tools** repository module to version **3.0**:

```
[root@director ~]# sudo dnf module disable -y container-tools:rhel8
[root@director ~]# sudo dnf module enable -y container-tools:3.0
```

6. Set the **virt** repository module to version **av**:

```
[root@director ~]# sudo dnf module disable -y virt:rhel
[root@director ~]# sudo dnf module enable -y virt:av
```

7. Perform an update of your base operating system:

```
[root@director ~]# dnf update -y
[root@director ~]# reboot
```

8. Ensure that the time on your undercloud is synchronized:

```
[root@director ~]# dnf install -y chrony
[root@director ~]# systemctl start chronyd
[root@director ~]# systemctl enable chronyd
```

9. Copy the undercloud backup archive to the **root** directory of the newly deployed undercloud node.

10. Install the **tar** and **policycoreutils-python-utils** packages:

```
[root@director ~]# dnf install -y tar policycoreutils-python-utils
```

11. Create the **stack** user:

```
[root@director ~]# useradd stack
```

12. Set a password for the **stack** user:

```
[root@director ~]# passwd stack
```

13. Configure the **stack** user account with **sudo** privileges:

```
[root@director ~]# echo "stack ALL=(root) NOPASSWD:ALL" | tee -a /etc/sudoers.d/stack
[root@director ~]# chmod 0440 /etc/sudoers.d/stack
```

14. Extract the following databases and files, and replace **<timestamp>** with the value of your archive file name:

```
[root@director ~]# tar --xattrs -xvC / -f undercloud-backup-<timestamp>.tar root/undercloud-
all-databases.sql var/lib/glance srv/node etc/pki/undercloud-certs/undercloud.pem etc/pki/ca-
trust/source/anchors/* etc/puppet home/stack var/lib/config-data/ var/lib/image-serve
var/lib/containers --exclude=var/lib/containers/storage/overlay/*/merged/*
```

- **/root/undercloud-all-databases.sql** is the database backup
- **/var/lib/glance** stores the Image service (glance) data
- **/srv/node** stores the Object service (swift) data
- **/etc/pki/undercloud-certs/undercloud.pem** and **/etc/pki/ca-trust/source/anchors/*** stores certificates

- **/etc/puppet** stores the hieradata that has already been generated
- **/home/stack** stores the **stack** user data and configuration
- **/var/lib/config-data** stores configuration container files
- **/var/lib/image-serve** and **/var/lib/containers** stores container image database

15. Restore the the necessary file properties for the certificates:

```
[root@director ~]# restorecon -R /etc/pki
[root@director ~]# semanage fcontext -a -t etc_t "/etc/pki/undercloud-certs(/.*)?"
[root@director ~]# restorecon -R /etc/pki/undercloud-certs
[root@director ~]# update-ca-trust extract
```

16. Install the **python3-tripleoclient** and the **ceph-ansible** packages:

```
[root@director ~]# dnf -y install python3-tripleoclient ceph-ansible
```

17. Delete the containers from the previous undercloud:

```
[root@director ~]# podman ps -a --filter='status=created' --format '{{ .Names }}' | xargs -i
podman rm {}
[root@director ~]# podman ps -a --filter='status=exited' --format '{{ .Names }}' | xargs -i
podman rm {}
```

18. To restore the database, complete the following steps:

- Create and set the SELinux attributes for the database directory:

```
[root@director ~]# sudo mkdir /var/lib/mysql
[root@director ~]# sudo chown 42434:42434 /var/lib/mysql
[root@director ~]# sudo chmod 0755 /var/lib/mysql
[root@director ~]# sudo chcon -t container_file_t /var/lib/mysql
[root@director ~]# sudo chcon -r object_r /var/lib/mysql
[root@director ~]# sudo chcon -u system_u /var/lib/mysql
```

- Create a local tag for the **mariadb** image. Replace **<image_id>** and **<undercloud.ctlplane.example.com>** with the values applicable in your environment:

```
[root@director ~]# podman images | grep mariadb
<undercloud.ctlplane.example.com>:8787/rh-osbs/rhosp16-openstack-mariadb
16.1_20210322.1 <image_id> 3 weeks ago 718 MB
```

```
[root@director ~]# podman tag <image_id> mariadb
```

```
[root@director ~]# podman images | grep maria
localhost/mariadb latest <image_id> 3
weeks ago 718 MB
<undercloud.ctlplane.example.com>:8787/rh-osbs/rhosp16-openstack-mariadb
16.1_20210322.1 <image_id> 3 weeks ago 718 MB
```

- Initialize the **/var/lib/mysql** directory with the container:

■

```
[root@director ~]# podman run -v /var/lib/mysql:/var/lib/mysql localhost/mariadb
mysql_install_db --datadir=/var/lib/mysql --user=mysql
```

- d. Copy the database backup file that you want to import to the database:

```
[root@director ~]# cp /root/undercloud-all-databases.sql /var/lib/mysql
```

- e. Start the database service to import the data and replace `<container_id>` with the container ID value applicable in your environment:

```
[root@director ~]# podman run -dt -v /var/lib/mysql:/var/lib/mysql localhost/mariadb
/usr/libexec/mysqld
<container_id>
```

- f. To import the data and configure the `max_allowed_packet` parameter, you must log in to the container to configure it, stop the container, and ensure that there are no containers running:

```
[root@director ~]# podman exec -it <container_id> /bin/bash
()[mysql@5a4e429c6f40 /]$ mysql -u root -e "set global max_allowed_packet =
1073741824;"
()[mysql@5a4e429c6f40 /]$ mysql -u root < /var/lib/mysql/undercloud-all-databases.sql
()[mysql@5a4e429c6f40 /]$ mysql -u root -e 'flush privileges'
()[mysql@5a4e429c6f40 /]$ exit
exit
```

```
[root@director ~]# podman stop <container_id>
```

```
[root@director ~]# podman ps
CONTAINER ID IMAGE COMMAND CREATED STATUS PORTS NAMES
[root@director ~]#
```

19. Set the name of the server and replace `<undercloud.example.com>` with the value applicable in your environment:

```
[root@director ~]# hostnamectl set-hostname <undercloud.example.com>
```

20. Run the undercloud installation command:

```
[root@director ~]# openstack undercloud install
```

Wait until the installation procedure completes. The undercloud automatically restores the connection to the overcloud. The overcloud nodes continue to poll the OpenStack Orchestration service (heat) for pending tasks.

2.2. VALIDATING THE UNDERCLOUD RESTORATION

A robust backup strategy includes regular restoration tests of backed up data. This can help validate that the correct data is backed up and that no corruption is introduced during the back up or restoration processes. To validate that the undercloud restoration process is successful, you can query the Identity service (keystone).

Procedure

1. Log in to the new undercloud host as the **stack** user.
2. Source the **stackrc** credentials file:

```
[stack@director ~]$ source ~/stackrc
```

3. Retrieve a list of users in your environment:

```
[stack@director ~]$ openstack user list
```

The output of this command includes a list of users in your environment. This validation demonstrates that the Identity service (keystone) is running and successfully authenticating user requests.

```
+-----+
| ID                | Name                |
+-----+
| f273be1a982b419591ccc7f89c1a5c0d | admin                |
| a0e1efeb5b654d61a393bcef92c505d2 | heat_admin           |
| 59604e2d56424f9bb4f7c825d0bdc615 | heat                 |
| 35d36ebc2f7043148943d0e0707336d9 | heat-cfn             |
| 233ff3b22c884fa289f7a9a6ec2de326 | neutron              |
| db7af369a9ed4f7fa8d8179ceae3233f | glance               |
| d883b3690d7f434d9eb9cabd6b5db8f5 | nova                 |
| 3dc52d74feb6402983863c8e9effbf5c | placement            |
| e3bdcc9465254cbea86222191c88edd3 | swift                |
| 8e68fcc40215446c8c1412fb736522de | ironic               |
| 366ccd100176495cb409dba872516cb2 | ironic-inspector    |
| fe99722603fe424d99d618c368dc0257 | mistral              |
| 05ae215b6b4043b6a60208ccd203644a | zaqar                |
| 83813ec920fe4b01b198770bfa538962 | zaqar-websocket     |
| 5fc6bc52c7364131b1e36fd4321325e6 | heat_stack_domain_admin |
+-----+
```