



Red Hat Developer Tools 1

Using LLVM 15.0.7 Toolset

Installing and using LLVM 15.0.7 Toolset

Red Hat Developer Tools 1 Using LLVM 15.0.7 Toolset

Installing and using LLVM 15.0.7 Toolset

Jacob Valdez

jvaldez@redhat.com

Legal Notice

Copyright © 2023 Red Hat, Inc.

The text of and illustrations in this document are licensed by Red Hat under a Creative Commons Attribution–Share Alike 3.0 Unported license ("CC-BY-SA"). An explanation of CC-BY-SA is available at

<http://creativecommons.org/licenses/by-sa/3.0/>

. In accordance with CC-BY-SA, if you distribute this document or an adaptation of it, you must provide the URL for the original version.

Red Hat, as the licensor of this document, waives the right to enforce, and agrees not to assert, Section 4d of CC-BY-SA to the fullest extent permitted by applicable law.

Red Hat, Red Hat Enterprise Linux, the Shadowman logo, the Red Hat logo, JBoss, OpenShift, Fedora, the Infinity logo, and RHCE are trademarks of Red Hat, Inc., registered in the United States and other countries.

Linux[®] is the registered trademark of Linus Torvalds in the United States and other countries.

Java[®] is a registered trademark of Oracle and/or its affiliates.

XFS[®] is a trademark of Silicon Graphics International Corp. or its subsidiaries in the United States and/or other countries.

MySQL[®] is a registered trademark of MySQL AB in the United States, the European Union and other countries.

Node.js[®] is an official trademark of Joyent. Red Hat is not formally related to or endorsed by the official Joyent Node.js open source or commercial project.

The OpenStack[®] Word Mark and OpenStack logo are either registered trademarks/service marks or trademarks/service marks of the OpenStack Foundation, in the United States and other countries and are used with the OpenStack Foundation's permission. We are not affiliated with, endorsed or sponsored by the OpenStack Foundation, or the OpenStack community.

All other trademarks are the property of their respective owners.

Abstract

LLVM Toolset is a Red Hat offering for developers on the Red Hat Enterprise Linux (RHEL) operating system. Use this guide for an overview of LLVM Toolset, to learn how to invoke and use different versions of LLVM tools, and to find resources with more in-depth information.

Table of Contents

MAKING OPEN SOURCE MORE INCLUSIVE	3
CHAPTER 1. LLVM TOOLSET	4
1.1. LLVM TOOLSET COMPONENTS	4
1.2. LLVM TOOLSET COMPATIBILITY	4
1.3. GETTING ACCESS TO LLVM TOOLSET ON RED HAT ENTERPRISE LINUX 7	5
1.4. INSTALLING LLVM TOOLSET	6
1.5. INSTALLING THE CMAKE BUILD MANAGER	7
1.6. INSTALLING LLVM TOOLSET DOCUMENTATION	8
1.7. INSTALLING CMAKE DOCUMENTATION	8
1.8. ADDITIONAL RESOURCES	9
CHAPTER 2. THE CLANG COMPILER	10
2.1. PREREQUISITES	10
2.2. COMPILING A SOURCE FILE	10
2.3. RUNNING A PROGRAM	10
2.4. LINKING OBJECT FILES TOGETHER	11
2.5. ADDITIONAL RESOURCES	12
CHAPTER 3. THE LLDB DEBUGGER	13
3.1. PREREQUISITES	13
3.2. STARTING A DEBUGGING SESSION	13
3.3. EXECUTING YOUR PROGRAM DURING A DEBUGGING SESSION	14
3.4. USING BREAKPOINTS	14
3.5. STEPPING THROUGH CODE	15
3.6. LISTING SOURCE CODE	15
3.7. DISPLAYING CURRENT PROGRAM DATA	16
3.8. ADDITIONAL RESOURCES	16
CHAPTER 4. CONTAINER IMAGES WITH LLVM TOOLSET ON RHEL 8	17
4.1. CREATING A CONTAINER IMAGE OF LLVM TOOLSET ON RHEL 8	17
4.2. ADDITIONAL RESOURCES	17
CHAPTER 5. CHANGES IN LLVM TOOLSET	18

MAKING OPEN SOURCE MORE INCLUSIVE

Red Hat is committed to replacing problematic language in our code, documentation, and web properties. We are beginning with these four terms: master, slave, blacklist, and whitelist. Because of the enormity of this endeavor, these changes will be implemented gradually over several upcoming releases. For more details, see [our CTO Chris Wright's message](#).

CHAPTER 1. LLVM TOOLSET

LLVM Toolset is a Red Hat offering for developers on Red Hat Enterprise Linux (RHEL). It provides the LLVM compiler infrastructure framework, the Clang compiler for the C and C++ languages, the LLDB debugger, and related tools for code analysis.

LLVM Toolset is distributed as a part of Red Hat Developer Tools for Red Hat Enterprise Linux 7. For Red Hat Enterprise Linux 8, LLVM Toolset is available as a module. LLVM Toolset is available as packages for Red Hat Enterprise Linux 9.

1.1. LLVM TOOLSET COMPONENTS

The following components are available as a part of LLVM Toolset:

Name	Version	Description
clang	15.0.7	An LLVM compiler front end for C and C++.
lldb	15.0.7	A C and C++ debugger using portions of LLVM.
compiler-rt	15.0.7	Runtime libraries for LLVM and Clang.
llvm	15.0.7	A collection of modular and reusable compiler and toolchain technologies.
libomp	15.0.7	A library for using Open MP API specification for parallel programming.
lld	15.0.7	An LLVM linker.
python-lit	15.0.7	A software testing tool for LLVM- and Clang-based test suites.



NOTE

The CMake build manager is not part of LLVM Toolset. On Red Hat Enterprise Linux 7, CMake is provided as a separate package. On Red Hat Enterprise Linux 8, CMake is available in the system repository. On Red Hat Enterprise Linux 9, CMake is available in the system repository. For more information on how to install CMake, see [Installing CMake on Red Hat Enterprise Linux](#).

1.2. LLVM TOOLSET COMPATIBILITY

LLVM Toolset is available for Red Hat Enterprise Linux 7 and Red Hat Enterprise Linux 8 and Red Hat Enterprise Linux 9 on the following architectures:

- AMD and Intel 64-bit
- 64-bit ARM (RHEL 8 and RHEL 9)
- IBM Power Systems, Little Endian
- IBM Power Systems, Big Endian (Only RHEL 7)
- 64-bit IBM Z

1.3. GETTING ACCESS TO LLVM TOOLSET ON RED HAT ENTERPRISE LINUX 7

To be able to install LLVM Toolset on Red Hat Enterprise Linux 7, you must access and enable Red Hat Developer Tools and Red Hat Software Collections repositories.

If these repositories are already attached to your system, see [Installing LLVM Toolset](#).

Procedure

1. Install **Wget** by running:

```
# yum install wget
```

2. Download the latest subscription data by running:

```
# subscription-manager refresh
```

3. Register your system by running:

```
# subscription-manager register
```

To register your system using a graphical user interface (GUI), follow the [Registering and Unregistering a System](#) guide.

4. Display a list of all available subscriptions and identify the pool ID by running:

```
# subscription-manager list --available
```

5. Find the pool ID on the line beginning with **Pool ID**.

6. Attach the subscription that provides access to the **Red Hat Developer Tools** repository to your system by running:

```
# subscription-manager attach --pool=<pool ID from the subscription>
```

- Replace **<pool ID from the subscription>** with the pool ID you identified in the previous step.

7. Verify which subscriptions are attached to your system by running:

```
# sudo subscription-manager list --consumed
```

8. Enable the **rhel-7-variant-devtools-rpms** repository by running:

```
# subscription-manager repos --enable rhel-7-<variant>-devtools-rpms
```

- Replace **<variant>** with your Red Hat Enterprise Linux system variant: **server** or **workstation**.
Use **server** to access the widest range of development tools.

9. Enable the **rhel-variant-rhsc1-7-rpms** repository by running:

```
# subscription-manager repos --enable rhel-<variant>-rhsc1-7-rpms
```

- Replace **<variant>** with your Red Hat Enterprise Linux system variant: **server** or **workstation**.

10. Add the Red Hat Developer Tools GPG key to your system by running:

```
# cd /etc/pki/rpm-gpg
# wget -O RPM-GPG-KEY-redhat-devel https://www.redhat.com/security/data/a5787476.txt
# rpm --import RPM-GPG-KEY-redhat-devel
```

Additional resources

- For more information on registering your system and associating it with subscriptions, see the [Red Hat Subscription Management](#) guides collection.

1.4. INSTALLING LLVM TOOLSET

Complete the following steps to install LLVM Toolset including all development and debugging tools as well as dependent packages.

Prerequisites

- On Red Hat Enterprise Linux 7, a subscription providing access to the Red Hat Developer Tools content set is attached to your system.
To attach the subscription, see [Getting access to LLVM Toolset on Red Hat Enterprise Linux 7](#).
- All available Red Hat Enterprise Linux updates are installed.

Procedure

On Red Hat Enterprise Linux 7, install the **llvm-toolset-15.0** collection by running:

```
# yum install llvm-toolset-15.0
```



IMPORTANT

This does not install the LLDB debugger on Red Hat Enterprise Linux 7. To install the LLDB debugger, run:

```
# yum install llvm-toolset-15.0-lldb
```

On Red Hat Enterprise Linux 8, install the **llvm-toolset** module by running:

```
# yum module install llvm-toolset
```




IMPORTANT

This does not install the LLDB debugger or the **python3-lit** package on Red Hat Enterprise Linux 8. To install the LLDB debugger and the **python3-lit** package, run:

```
# yum install lldb python3-lit
```

On Red Hat Enterprise Linux 9, install the **llvm-toolset** package by running:

```
# dnf install llvm-toolset
```



IMPORTANT

This does not install the LLDB debugger or the **python3-lit** package on Red Hat Enterprise Linux 9. To install the LLDB debugger and the **python3-lit** package, run:

```
# dnf install lldb python3-lit
```

1.5. INSTALLING THE CMAKE BUILD MANAGER

The CMake build manager is a tool that manages the build process of your source code independently from your compiler. CMake can generate a native build environment to compile source code, create libraries, generate wrappers, and build executable files.

Complete the following steps to install the CMake build manager.

Prerequisites

- LLVM Toolset is installed.
For more information, see [Installing LLVM Toolset](#).

Procedure

To install CMake, run the following command:

- On Red Hat Enterprise Linux 7:

```
# yum install llvm-toolset-15.0-cmake
```

- On Red Hat Enterprise Linux 8:

```
# yum install cmake
```

- On Red Hat Enterprise Linux 9:

```
# dnf install cmake
```

Additional resources

- For more information on the CMake build manager, see the official CMake documentation overview [About CMake](#).
- For an introduction to using the CMake build manager, see:
 - The CMake Reference Documentation [Introduction](#).
 - The official CMake documentation [CMake Tutorial](#).

1.6. INSTALLING LLVM TOOLSET DOCUMENTATION

You can install documentation for LLVM Toolset on your local system.

Prerequisites

- LLVM Toolset is installed.
For more information, see [Installing LLVM Toolset](#).

Procedure

To install the **llvm-doc** package, run the following command:

- On Red Hat Enterprise Linux 7:

```
# yum install llvm-toolset-15.0-llvm-doc
```

You can find the documentation under the following path: **`/opt/rh/llvm-toolset-15.0/root/usr/share/doc/llvm-toolset-15.0-llvm-15.0.7/html/index.html`**.

- On Red Hat Enterprise Linux 8:

```
# yum install llvm-doc
```

You can find the documentation under the following path: **`/usr/share/doc/llvm/html/index.html`**.

- On Red Hat Enterprise Linux 9:

```
# dnf install llvm-doc
```

You can find the documentation under the following path: **`/usr/share/doc/llvm/html/index.html`**.

1.7. INSTALLING CMAKE DOCUMENTATION

You can install documentation for the CMake build manager on your local system.

Prerequisites

- CMake is installed.
For more information, see [Installing the CMake build manager](#).

Procedure

To install the **cmake-doc** package, run the following command:

- On Red Hat Enterprise Linux 7:

```
# yum install llvm-toolset-15.0-cmake-doc
```

You can find the documentation under the following path: **opt/rh/llvm-toolset-15.0/root/usr/share/doc/llvm-toolset-15.0-cmake-3.18.2/html/index.html**.

- On Red Hat Enterprise Linux 8:

```
# yum install cmake-doc
```

You can find the documentation under the following path: **/usr/share/doc/cmake/html/index.html**.

- On Red Hat Enterprise Linux 9:

```
# dnf install cmake-doc
```

You can find the documentation under the following path: **/usr/share/doc/cmake/html/index.html**.

1.8. ADDITIONAL RESOURCES

- For more information on LLVM Toolset, see the [official LLVM documentation](#).

CHAPTER 2. THE CLANG COMPILER

Clang is an LLVM compiler front end for the C-based languages C, C++, Objective C/C++, OpenCL, and Cuda.

LLVM Toolset is distributed with Clang 15.0.7.

2.1. PREREQUISITES

- LLVM Toolset is installed.
For more information, see [Installing LLVM Toolset](#).

2.2. COMPILING A SOURCE FILE

Use the Clang compiler to compile source files as well as assembly language source files. Clang creates an executable binary file as a result of compiling. To be able to debug your code, enable debug information by adding the **-g** flag to your Clang commands.



NOTE

To compile a C++ program, use **clang++** instead of **clang**.

Procedure

To compile your program, run the following command:

- On Red Hat Enterprise Linux 7:

```
$ scl enable llvm-toolset-15.0 'clang -o <binary_file> <source_file>'
```

- Replace **<binary_file>** with the desired name of your output file and **<source_file>** with the name of your source file.

- On Red Hat Enterprise Linux 8:

```
$ clang -o -g <binary_file> <source_file>
```

- Replace **<binary_file>** with the desired name of your output file and **<source_file>** with the name of your source file.

- On Red Hat Enterprise Linux 9:

```
$ clang -o -g <binary_file> <source_file>
```

- Replace **<binary_file>** with the desired name of your output file and **<source_file>** with the name of your source file.

2.3. RUNNING A PROGRAM

The Clang compiler creates an executable binary file as a result of compiling. Complete the following steps to execute this file and run your program.

Prerequisites

- Your program is compiled.
For more information on how to compile your program, see [Compiling a source file](#).

Procedure

To run your program, run in the directory containing the executable file:

```
$ ./<binary_file>
```

- Replace **<binary_file>** with the name of your executable file.

2.4. LINKING OBJECT FILES TOGETHER

By linking object files together, you can compile only source files that contain changes instead of your entire project.

When you are working on a project that consists of several source files, use the Clang compiler to compile an object file for each of the source files. As a next step, link those object files together. Clang automatically generates an executable file containing your linked object files. After compilation, link your object files together again.



NOTE

To compile a C++ program, use **clang++** instead of **clang**.

Procedure

1. To compile a source file to an object file, run the following command:

- On Red Hat Enterprise Linux 7:

```
$ scl enable llvm-toolset-15.0 'clang -o <object_file> -c <source_file>'
```

- Replace **<object_file>** with the desired name of your object file and **<source_file>** with the name of your source file.

- On Red Hat Enterprise Linux 8:

```
$ clang -o <object_file> -c <source_file>
```

- Replace **<object_file>** with the desired name of your object file and **<source_file>** with the name of your source file.

- On Red Hat Enterprise Linux 9:

```
$ clang -o <object_file> -c <source_file>
```

- Replace **<object_file>** with the desired name of your object file and **<source_file>** with the name of your source file.

2. To link object files together, run the following command:

- On Red Hat Enterprise Linux 7:

```
$ scl enable llvm-toolset-15.0 'clang -o <output_file> <object_file_0> <object_file_1>'
```

- Replace **<output_file>** with the desired name of your output file and **<object_file>** with the names of the object files you want to link.
- On Red Hat Enterprise Linux 8:

```
$ clang -o <output_file> <object_file_0> <object_file_1>
```

- Replace **<output_file>** with the desired name of your output file and **<object_file>** with the names of the object files you want to link.
- On Red Hat Enterprise Linux 9:

```
$ clang -o <output_file> <object_file_0> <object_file_1>
```

- Replace **<output_file>** with the desired name of your output file and **<object_file>** with the names of the object files you want to link.



IMPORTANT

At the moment, certain library features are statically linked into applications built with LLVM Toolset to support their execution on multiple versions of Red Hat Enterprise Linux. This creates a small security risk. Red Hat will issue a security erratum in case you need to rebuild your applications due to this risk.

Red Hat advises to not statically link your entire application.

2.5. ADDITIONAL RESOURCES

- For more information on the Clang compiler, see the [official Clang compiler documentation](#).
- To display the manual page included in LLVM Toolset, run:



NOTE

To compile a C++ program, use **clang++** instead of **clang**.

- On Red Hat Enterprise Linux 7:

```
$ scl enable llvm-toolset-15.0 'man clang'
```

- On Red Hat Enterprise Linux 8:

```
$ man clang
```

- On Red Hat Enterprise Linux 9:

```
$ man clang
```


CHAPTER 3. THE LLDB DEBUGGER

The LLDB debugger is a command-line tool for debugging C and C++ programs. Use LLDB to inspect memory within the code being debugged, control the execution state of the code, and detect the execution of particular sections of code.

LLVM Toolset is distributed with LLDB 15.0.7.

3.1. PREREQUISITES

- LLVM Toolset is installed.
For more information, see [Installing LLVM Toolset](#).
- Your compiler is configured to create debug information.
For instructions on configuring the Clang compiler, see [Controlling Debug Information](#) in the Clang Compiler User's Manual.
For instructions on configuring the GCC compiler, see [Preparing a Program for Debugging](#) in the Red Hat Developer Toolset User Guide.

3.2. STARTING A DEBUGGING SESSION

Use LLDB to start an interactive debugging session.

Procedure

- To run LLDB on a program you want to debug, use the following command:
 - On Red Hat Enterprise Linux 7:

```
$ scl enable llvm-toolset-15.0 'lldb <binary_file>'
```

 - Replace **<binary_file>** with the name of your compiled program.
You have started your LLDB debugging session in interactive mode. Your command-line terminal now displays the default prompt **(lldb)**.
 - On Red Hat Enterprise Linux 8:

```
$ lldb <binary_file_name>
```

 - Replace **<binary_file>** with the name of your compiled program.
You have started your LLDB debugging session in interactive mode. Your command-line terminal now displays the default prompt **(lldb)**.
 - On Red Hat Enterprise Linux 9:

```
$ lldb <binary_file>
```

 - Replace **<binary_file>** with the name of your compiled program.
You have started your LLDB debugging session in interactive mode. Your command-line terminal now displays the default prompt **(lldb)**.
- To quit the debugging session and return to the shell prompt, run the following command:

```
(lldb) quit
```

3.3. EXECUTING YOUR PROGRAM DURING A DEBUGGING SESSION

Use LLDB to execute your program during your debugging session. The execution of your program stops when the first breakpoint is reached, when an error occurs, or when the program terminates.

Prerequisites

- You have started an interactive debugging session.
For more information, see [Starting a debugging session with LLDB](#).

Procedure

- To execute the program you are debugging, run:

```
(lldb) run
```

- To execute the program you are debugging using a specific argument, run:

```
(lldb) run <argument>
```

- Replace **<argument>** with the command-line argument you want to use.

3.4. USING BREAKPOINTS

Use breakpoints to pause the execution of your program at a set point in your source code.

Prerequisites

- You have started an interactive debugging session.
For more information, see [Starting a debugging session with LLDB](#).

Procedure

- To set a new breakpoint on a specific line, run the following command:

```
(lldb) breakpoint set --file <source_file_name> --line <line_number>
```

- Replace **<source_file_name>** with the name of your source file and **<line_number>** with the line number you want to set your breakpoint at.

- To set a breakpoint on a specific function, run the following command:

```
(lldb) breakpoint set --name <function_name>
```

- Replace **<function_name>** with the name of the function you want to set your breakpoint at.

- To display a list of currently set breakpoints, run the following command:

```
(lldb) breakpoint list
```

- To delete a breakpoint, run:

```
(lldb) breakpoint clear -f <source_file_name> -l <line_number>
```

- Replace **<source_file_name>** with the name of your source file and **<line_number>** with line number of the breakpoint you want to delete.

- To resume the execution of your program after it reached a breakpoint, run:

```
(lldb) continue
```

- To skip a specific number of breakpoints, run the following command:

```
(lldb) continue -i <breakpoints_to_skip>
```

- Replace **<breakpoints_to_skip>** with the number of breakpoints you want to skip.



NOTE

To skip a loop, set the **<breakpoints_to_skip>** to match the loop iteration count.

3.5. STEPPING THROUGH CODE

You can use LLDB to step through the code of your program to execute only one line of code after the line pointer.

Prerequisites

- You have started an interactive debugging session.
For more information, see [Starting a debugging session with LLDB](#).

Procedure

- To step through one line of code:
 1. Set your line pointer to the line you want to execute.
 2. Run the following command:

```
(lldb) step
```

- To step through a specific number of lines of code:
 1. Set your line pointer to the line you want to execute.
 2. Run the following command:

```
(lldb) step -c <number>
```

- Replace **<number>** with the number of lines you want to execute.

3.6. LISTING SOURCE CODE

Before you execute the program you are debugging, the LLDB debugger automatically displays the first 10 lines of source code. Each time the execution of the program is stopped, LLDB displays the line of source code on which it stopped as well as its surrounding lines. You can use LLDB to manually trigger the display of source code during your debugging session.

Prerequisites

- You have started an interactive debugging session.
For more information, see [Starting a debugging session with LLDB](#) .

Procedure

- To list the first 10 lines of the source code of the program you are debugging, run:

```
(lldb) list
```

- To display the source code from a specific line, run:

```
(lldb) list <source_file_name>:<line_number>
```

- Replace **<source_file_name>** with the name of your source file and **<line_number>** with the number of the line you want to display.

3.7. DISPLAYING CURRENT PROGRAM DATA

The LLDB debugger provides data on variables of any complexity, any valid expressions, and function call return values. You can use LLDB to display data relevant to the program state.

Prerequisites

- You have started an interactive debugging session.
For more information, see [Starting a debugging session with LLDB](#) .

Procedure

To display the current value of a certain variable, expression, or return value, run:

```
(lldb) print <data_name>
```

- Replace **<data_name>** with data you want to display.

3.8. ADDITIONAL RESOURCES

- For more information on the LLDB debugger, see the official LLDB documentation [LLDB Tutorial](#).
- For a list of GDB commands and their LLDB equivalents, see the [GDB to LLDB Command Map](#) .

CHAPTER 4. CONTAINER IMAGES WITH LLVM TOOLSET ON RHEL 8

On RHEL 8, you can build your own LLVM Toolset container images on top of Red Hat Universal Base Images (UBI) containers using Containerfiles.

4.1. CREATING A CONTAINER IMAGE OF LLVM TOOLSET ON RHEL 8

On RHEL 8, LLVM Toolset packages are part of the Red Hat Universal Base Images (UBIs) repositories. To keep the container image size small, install only individual packages instead of the entire LLVM Toolset.

Prerequisites

- An existing Containerfile.
For information on creating Containerfiles, see the [Dockerfile reference](#) page.

Procedure

- Visit the [Red Hat Container Catalog](#).
- Select a UBI.
- Click **Get this image** and follow the instructions.
- To create a container image containing LLVM Toolset, add the following lines to your Containerfile:

```
FROM registry.access.redhat.com/ubi8/ubi:latest
```

```
RUN yum module install -y llvm-toolset
```

- To create a container image containing an individual package only, add the following lines to your Containerfile:

```
RUN yum install -y <package-name>
```

- Replace **<package-name>** with the name of the package you want to install.

4.2. ADDITIONAL RESOURCES

- For more information on Red Hat UBI images, see [Working with Container Images](#).
- For more information on Red Hat UBI repositories, see [Universal Base Images \(UBI\): Images, repositories, packages, and source code](#).

CHAPTER 5. CHANGES IN LLVM TOOLSET

LLVM Toolset has been updated from version 14.0.6 to 15.0.7 on RHEL 7, RHEL 8, and RHEL 9. Notable changes include:

- The **-Wimplicit-function-declaration** and **-Wimplicit-int** warnings are enabled by default in C99 and newer. These warnings will become errors by default in Clang 16 and beyond.