



Red Hat OpenStack Platform 13

Hyperconverged Infrastructure Guide

Understanding and configuring Hyperconverged Infrastructure on the Red Hat OpenStack Platform overcloud

Red Hat OpenStack Platform 13 Hyperconverged Infrastructure Guide

Understanding and configuring Hyperconverged Infrastructure on the Red Hat OpenStack Platform overcloud

Enter your first name here. Enter your surname here.

Enter your organisation's name here. Enter your organisational division here.

Enter your email address here.

法律上の通知

Copyright © 2022 | You need to change the HOLDER entity in the en-US/Hyperconverged_Infrastructure_Guide.ent file |.

The text of and illustrations in this document are licensed by Red Hat under a Creative Commons Attribution–Share Alike 3.0 Unported license ("CC-BY-SA"). An explanation of CC-BY-SA is available at

<http://creativecommons.org/licenses/by-sa/3.0/>

. In accordance with CC-BY-SA, if you distribute this document or an adaptation of it, you must provide the URL for the original version.

Red Hat, as the licensor of this document, waives the right to enforce, and agrees not to assert, Section 4d of CC-BY-SA to the fullest extent permitted by applicable law.

Red Hat, Red Hat Enterprise Linux, the Shadowman logo, the Red Hat logo, JBoss, OpenShift, Fedora, the Infinity logo, and RHCE are trademarks of Red Hat, Inc., registered in the United States and other countries.

Linux[®] is the registered trademark of Linus Torvalds in the United States and other countries.

Java[®] is a registered trademark of Oracle and/or its affiliates.

XFS[®] is a trademark of Silicon Graphics International Corp. or its subsidiaries in the United States and/or other countries.

MySQL[®] is a registered trademark of MySQL AB in the United States, the European Union and other countries.

Node.js[®] is an official trademark of Joyent. Red Hat is not formally related to or endorsed by the official Joyent Node.js open source or commercial project.

The OpenStack[®] Word Mark and OpenStack logo are either registered trademarks/service marks or trademarks/service marks of the OpenStack Foundation, in the United States and other countries and are used with the OpenStack Foundation's permission. We are not affiliated with, endorsed or sponsored by the OpenStack Foundation, or the OpenStack community.

All other trademarks are the property of their respective owners.

概要

This document describes the Red Hat OpenStack Platform implementation of hyperconvergence, which colocates Compute and Ceph Storage services on the same host.

目次

PREFACE	3
MAKING OPEN SOURCE MORE INCLUSIVE	4
PROVIDING FEEDBACK ON RED HAT DOCUMENTATION	5
第1章 CONFIGURING AND DEPLOYING A RED HAT OPENSTACK PLATFORM HYPERCONVERGED INFRASTRUCTURE	6
1.1. PREREQUISITES	6
1.2. PREPARING THE OVERCLOUD ROLE FOR HYPERCONVERGED NODES	7
1.2.1. Defining the root disk	9
1.3. CONFIGURING RESOURCE ISOLATION ON HYPERCONVERGED NODES	11
1.3.1. Process for autogenerating CPU and memory resources to reserve for the Compute service	12
1.3.2. Red Hat Ceph Storage backfill and recovery operations	14
1.4. PRE-DEPLOYMENT VALIDATIONS FOR CEPH STORAGE	14
1.4.1. Verifying the ceph-ansible package version	14
1.4.2. Verifying packages for pre-provisioned nodes	14
1.5. DEPLOYING THE HCI OVERCLOUD	15
1.6. OPENSTACK WORKFLOW COMPUTE CPU AND MEMORY CALCULATOR	16
1.7. ADDITIONAL RESOURCES	17
第2章 SCALING HYPERCONVERGED NODES	18
2.1. SCALING UP HYPERCONVERGED NODES IN HCI ENVIRONMENTS	18
2.2. SCALING DOWN HYPERCONVERGED NODES IN HCI ENVIRONMENTS	18

PREFACE

MAKING OPEN SOURCE MORE INCLUSIVE

Red Hat is committed to replacing problematic language in our code, documentation, and web properties. We are beginning with these four terms: master, slave, blacklist, and whitelist. Because of the enormity of this endeavor, these changes will be implemented gradually over several upcoming releases. For more details, see [our CTO Chris Wright's message](#).

PROVIDING FEEDBACK ON RED HAT DOCUMENTATION

We appreciate your input on our documentation. Tell us how we can make it better.


Using the Direct Documentation Feedback (DDF) function

Use the **Add Feedback** DDF function for direct comments on specific sentences, paragraphs, or code blocks.

1. View the documentation in the **Multi-page HTML** format.
2. Ensure that you see the **Feedback** button in the upper right corner of the document.
3. Highlight the part of text that you want to comment on.
4. Click **Add Feedback**.
5. Complete the **Add Feedback** field with your comments.
6. Optional: Add your email address so that the documentation team can contact you for clarification on your issue.
7. Click **Submit**.

第1章 CONFIGURING AND DEPLOYING A RED HAT OPENSTACK PLATFORM HYPERCONVERGED INFRASTRUCTURE

Red Hat OpenStack Platform (RHOSP) hyperconverged infrastructures (HCI) consist of hyperconverged nodes. Services are colocated on these hyperconverged nodes for optimized resource usage. In a RHOSP HCI, the Compute and storage services are colocated on hyperconverged nodes. You can deploy an overcloud with only hyperconverged nodes, or a mixture of hyperconverged nodes with normal Compute and Ceph Storage nodes.



注記

You must use Red Hat Ceph Storage as the storage provider.

ヒント

- Use ceph-ansible 3.2 and later to automatically tune Ceph memory settings.
- Use BlueStore as the back end for HCI deployments, to make use of the BlueStore memory handling features.

To create and deploy HCI on an overcloud, integrate with other features in your overcloud such as Network Function Virtualization, and ensure optimal performance of both Compute and Red Hat Ceph Storage services on hyperconverged nodes, you must complete the following:

1. Prepare the predefined custom overcloud role for hyperconverged nodes, **ComputeHCI**.
2. Configure resource isolation.
3. Verify the available Red Hat Ceph Storage packages.
4. Deploy the HCI overcloud.

1.1. PREREQUISITES

- You have deployed the undercloud. For instructions on how to deploy the undercloud, see [Director Installation and Usage](#).
- Your environment can provision nodes that meet RHOSP Compute and Red Hat Ceph Storage requirements. For more information, see [Basic Overcloud Deployment](#).
- You have registered all nodes in your environment. For more information, see [Registering Nodes](#).
- You have tagged all nodes in your environment. For more information, see [Manually Tagging the Nodes](#).
- You have cleaned the disks on nodes that you plan to use for Compute and Ceph OSD services. For more information, see [Cleaning Ceph Storage Node Disks](#).
- You have prepared your overcloud nodes for registration with the Red Hat Content Delivery Network or a Red Hat Satellite server. For more information, see [Ansible-based Overcloud Registration](#).

1.2. PREPARING THE OVERCLOUD ROLE FOR HYPERCONVERGED NODES

To designate nodes as hyperconverged, you need to define a hyperconverged role. Red Hat OpenStack Platform (RHOSP) provides the predefined role **ComputeHCI** for hyperconverged nodes. This role colocates the Compute and Ceph object storage daemon (OSD) services, allowing you to deploy them together on the same hyperconverged node.

Procedure

1. Log in to the undercloud as the **stack** user.
2. Source the **stackrc** file:

```
[stack@director ~]$ source ~/stackrc
```

3. Generate a new custom roles data file that includes the **ComputeHCI** role, along with other roles you intend to use for the overcloud. The following example generates the roles data file **roles_data_hci.yaml** that includes the roles **Controller**, **ComputeHCI**, **Compute**, and **CephStorage**:

```
(undercloud)$ openstack overcloud roles \
generate -o /home/stack/templates/roles_data_hci.yaml \
Controller ComputeHCI Compute CephStorage
```



注記

The networks listed for the **ComputeHCI** role in the generated custom roles data file include the networks required for both Compute and Storage services, for example:

```
- name: ComputeHCI
  description: |
    Compute node role hosting Ceph OSD
  tags:
    - compute
  networks:
    InternalApi:
      subnet: internal_api_subnet
    Tenant:
      subnet: tenant_subnet
    Storage:
      subnet: storage_subnet
    StorageMgmt:
      subnet: storage_mgmt_subnet
```

4. Create a local copy of the **network_data.yaml** file to add a composable network to your overcloud. The **network_data.yaml** file interacts with the default network environment files, **/usr/share/openstack-tripleo-heat-templates/environments/***, to associate the networks you defined for your **ComputeHCI** role with the hyperconverged nodes. For more information, see [Adding a composable network](#) in the **Advanced Overcloud Customization** guide.
5. To improve the performance of Red Hat Ceph Storage, update the MTU setting for both the

Storage and **StorageMgmt** networks to **9000**, for jumbo frames, in your local copy of **network_data.yaml**. For more information, see [Configuring MTU Settings in Director](#) and [Configuring jumbo frames](#).

6. Create the **computeHCI** overcloud flavor for hyperconverged nodes:

```
(undercloud)$ openstack flavor create --id auto \
--ram <ram_size_mb> --disk <disk_size_gb> \
--vcpus <no_vcpus> computeHCI
```

- Replace **<ram_size_mb>** with the RAM of the bare metal node, in MB.
- Replace **<disk_size_gb>** with the size of the disk on the bare metal node, in GB.
- Replace **<no_vcpus>** with the number of CPUs on the bare metal node.



注記

These properties are not used for scheduling instances. However, the Compute scheduler does use the disk size to determine the root partition size.

7. Retrieve a list of your nodes to identify their UUIDs:

```
(undercloud)$ openstack baremetal node list
```

8. Tag each bare metal node that you want to designate as hyperconverged with a custom HCI resource class:


```
(undercloud)$ openstack baremetal node set \
--resource-class baremetal.HCI <node>
```

Replace **<node>** with the ID of the bare metal node.

9. Associate the **computeHCI** flavor with the custom HCI resource class:

```
(undercloud)$ openstack flavor set \
--property resources:CUSTOM_BAREMETAL_HCI=1 \
computeHCI
```

To determine the name of a custom resource class that corresponds to a resource class of a Bare Metal service node, convert the resource class to uppercase, replace all punctuation with an underscore, and prefix with **CUSTOM_**.



注記

A flavor can request only one instance of a bare metal resource class.

10. Set the following flavor properties to prevent the Compute scheduler from using the bare metal flavor properties to schedule instances:

```
(undercloud)$ openstack flavor set \
--property resources:VCPU=0 \
--property resources:MEMORY_MB=0 \
```

```
--property resources:DISK_GB=0 computeHCI
```

11. Add the following parameters to the **node-info.yaml** file to specify the number of hyperconverged and Controller nodes, and the flavor to use for the hyperconverged and controller designated nodes:

```
parameter_defaults:
  OvercloudComputeHCIFlavor: computeHCI
  ComputeHCICount: 3
  OvercloudControlFlavor: baremetal
  ControllerCount: 3
```

Additional resources

- [Composable Services and Custom Roles](#)
- [Examining the roles_data file](#)
- [Assigning Nodes and Flavors to Roles](#)

1.2.1. Defining the root disk

Director must identify the root disk during provisioning in the case of nodes with multiple disks. For example, most Ceph Storage nodes use multiple disks. By default, the director writes the overcloud image to the root disk during the provisioning process.

There are several properties that you can define to help the director identify the root disk:

- **model** (String): Device identifier.
- **vendor** (String): Device vendor.
- **serial** (String): Disk serial number.
- **hctl** (String): Host:Channel:Target:Lun for SCSI.
- **size** (Integer): Size of the device in GB.
- **wwn** (String): Unique storage identifier.
- **wwn_with_extension** (String): Unique storage identifier with the vendor extension appended.
- **wwn_vendor_extension** (String): Unique vendor storage identifier.
- **rotational** (Boolean): True for a rotational device (HDD), otherwise false (SSD).
- **name** (String): The name of the device, for example: /dev/sdb1.
- **by_path** (String): The unique PCI path of the device. Use this property if you do not want to use the UUID of the device.



重要

Use the **name** property only for devices with persistent names. Do not use **name** to set the root disk for any other device because this value can change when the node boots.

Complete the following steps to specify the root device using its serial number.

Procedure

1. Check the disk information from the hardware introspection of each node. Run the following command to display the disk information of a node:

```
(undercloud) $ openstack baremetal introspection data save 1a4e30da-b6dc-499d-ba87-0bd8a3819bc0 | jq ".inventory.disks"
```

For example, the data for one node might show three disks:

```
[
  {
    "size": 299439751168,
    "rotational": true,
    "vendor": "DELL",
    "name": "/dev/sda",
    "wwn_vendor_extension": "0x1ea4dcc412a9632b",
    "wwn_with_extension": "0x61866da04f3807001ea4dcc412a9632b",
    "model": "PERC H330 Mini",
    "wwn": "0x61866da04f380700",
    "serial": "61866da04f3807001ea4dcc412a9632b"
  }
  {
    "size": 299439751168,
    "rotational": true,
    "vendor": "DELL",
    "name": "/dev/sdb",
    "wwn_vendor_extension": "0x1ea4e13c12e36ad6",
    "wwn_with_extension": "0x61866da04f380d001ea4e13c12e36ad6",
    "model": "PERC H330 Mini",
    "wwn": "0x61866da04f380d00",
    "serial": "61866da04f380d001ea4e13c12e36ad6"
  }
  {
    "size": 299439751168,
    "rotational": true,
    "vendor": "DELL",
    "name": "/dev/sdc",
    "wwn_vendor_extension": "0x1ea4e31e121cfb45",
    "wwn_with_extension": "0x61866da04f37fc001ea4e31e121cfb45",
    "model": "PERC H330 Mini",
    "wwn": "0x61866da04f37fc00",
    "serial": "61866da04f37fc001ea4e31e121cfb45"
  }
]
```

2. Change to the **root_device** parameter for the node definition. The following example shows how to set the root device to disk 2, which has **61866da04f380d001ea4e13c12e36ad6** as the serial number:

```
(undercloud) $ openstack baremetal node set --property root_device='{ "serial": "61866da04f380d001ea4e13c12e36ad6" }' 1a4e30da-b6dc-499d-ba87-0bd8a3819bc0
```



注記

Ensure that you configure the BIOS of each node to include booting from the root disk that you choose. Configure the boot order to boot from the network first, then to boot from the root disk.

The director identifies the specific disk to use as the root disk. When you run the **openstack overcloud deploy** command, the director provisions and writes the Overcloud image to the root disk.

1.3. CONFIGURING RESOURCE ISOLATION ON HYPERCONVERGED NODES

Colocating Ceph OSD and Compute services on hyperconverged nodes risks resource contention between Red Hat Ceph Storage and Compute services, as neither are aware of each other's presence on the same host. Resource contention can result in degradation of service, which offsets the benefits of hyperconvergence.

You must configure resource isolation for both Ceph and Compute services to prevent contention.

Procedure

- Optional: Override the autogenerated Compute settings by adding the following parameters to a Compute environment file:

```
parameter_defaults:
  ComputeHCIParameters:
    NovaReservedHostMemory: <ram>
    NovaCPUAllocationRatio: <ratio>
```

- Replace **<ram>** with the amount of RAM to reserve for the Ceph OSD services and instance overhead on hyperconverged nodes, in MB.
 - Replace **<ratio>** with the ratio that the Compute scheduler should use when choosing which Compute node to deploy an instance on.
For more information on the autogenerated Compute settings, see [Process for autogenerating CPU and memory resources to reserve for the Compute service](#).
- To reserve memory resources for Red Hat Ceph Storage, set the parameter **is_hci** to **true** in **/home/stack/templates/storage-container-config.yaml**:

```
parameter_defaults:
  CephAnsibleExtraConfig:
    is_hci: true
```

This allows **ceph-ansible** to reserve memory resources for Red Hat Ceph Storage, and reduce memory growth by Ceph OSDs, by automatically adjusting the **osd_memory_target** parameter setting for a HCI deployment.

**警告**

Red Hat does not recommend directly overriding the **ceph_osd_docker_memory_limit** parameter.

**注記**

As of ceph-ansible 3.2, the **ceph_osd_docker_memory_limit** is set automatically to the maximum memory of the host, as discovered by Ansible, regardless of whether the FileStore or BlueStore back end is used.

- Optional: By default, **ceph-ansible** reserves one vCPU for each Ceph OSD. If you require more than one CPU per Ceph OSD, add the following configuration to **/home/stack/templates/storage-container-config.yaml**:

```
parameter_defaults:
  CephAnsibleExtraConfig:
    ceph_osd_docker_cpu_limit: <cpu_limit>
```

Replace **<cpu_limit>** with the number of CPUs to reserve for each Ceph OSD.

For more information on how to tune CPU resources based on your hardware and workload, see [Red Hat Ceph Storage Hardware Selection Guide](#) .

- Optional: Reduce the priority of Red Hat Ceph Storage backfill and recovery operations when a Ceph OSD is removed by adding the following parameters to a Ceph environment file:

```
parameter_defaults:
  CephConfigOverrides:
    osd_recovery_op_priority: <priority_value>
    osd_recovery_max_active: <no_active_recovery_requests>
    osd_max_backfills: <max_no_backfills>
```


- Replace **<priority_value>** with the priority for recovery operations, relative to the OSD client OP priority.
- Replace **<no_active_recovery_requests>** with the number of active recovery requests per OSD, at one time.
- Replace **<max_no_backfills>** with the maximum number of backfills allowed to or from a single OSD.

For more information on default Red Hat Ceph Storage backfill and recovery options, see [Red Hat Ceph Storage backfill and recovery operations](#) .

1.3.1. Process for autogenerating CPU and memory resources to reserve for the Compute service

Director provides a default plan environment file for configuring resource constraints on hyperconverged nodes during deployment. This plan environment file instructs the OpenStack Workflow to complete the following processes:

1. Retrieve the hardware introspection data collected during inspection of the hardware nodes.
2. Calculate optimal CPU and memory allocation workload for Compute on hyperconverged nodes based on that data.
3. Autogenerate the parameters required to configure those constraints and reserve CPU and memory resources for Compute. These parameters are defined under the **hci_profile_config** section of the **plan-environment-derived-params.yaml** file.



注記

The **average_guest_memory_size_in_mb** and **average_guest_cpu_utilization_percentage** parameters in each workload profile are used to calculate values for the **reserved_host_memory** and **cpu_allocation_ratio** settings of Compute.

You can override the autogenerated Compute settings by adding the following parameters to your Compute environment file:

Autogenerated nova.conf parameter	Compute environment file override	Description
reserved_host_memory	<pre>parameter_defaults: ComputeHCIParameters: NovaReservedHostMemory: 181000</pre>	Sets how much RAM should be reserved for the Ceph OSD services and per-guest instance overhead on hyperconverged nodes.
cpu_allocation_ratio	<pre>parameter_defaults: ComputeHCIParameters: NovaCPUAllocationRatio: 8.2</pre>	Sets the ratio that the Compute scheduler should use when choosing which Compute node to deploy an instance on.

These overrides are applied to all nodes that use the ComputeHCI role, namely, all hyperconverged nodes. For more information about manually determining optimal values for **NovaReservedHostMemory** and **NovaCPUAllocationRatio**, see [OpenStack Workflow Compute CPU and memory calculator](#).

ヒント

You can use the following script to calculate suitable baseline **NovaReservedHostMemory** and **NovaCPUAllocationRatio** values for your hyperconverged nodes.

[nova_mem_cpu_calc.py](#)

Additional resources

- [Inspecting the hardware of nodes for IPv4 provisioning](#)
- [Inspecting the hardware of nodes for IPv6 provisioning](#)

1.3.2. Red Hat Ceph Storage backfill and recovery operations

When a Ceph OSD is removed, Red Hat Ceph Storage uses backfill and recovery operations to rebalance the cluster. Red Hat Ceph Storage does this to keep multiple copies of data according to the placement group policy. These operations use system resources. If a Red Hat Ceph Storage cluster is under load, its performance drops as it diverts resources to backfill and recovery.

To mitigate this performance effect during OSD removal, you can reduce the priority of backfill and recovery operations. The trade off for this is that there are less data replicas for a longer time, which puts the data at a slightly greater risk.

The parameters detailed in the following table are used to configure the priority of backfill and recovery operations.

Parameter	Description	Default value
osd_recovery_op_priority	Sets the priority for recovery operations, relative to the OSD client OP priority.	3
osd_recovery_max_active	Sets the number of active recovery requests per OSD, at one time. More requests accelerate recovery, but the requests place an increased load on the cluster. Set this to 1 if you want to reduce latency.	3
osd_max_backfills	Sets the maximum number of backfills allowed to or from a single OSD.	1

1.4. PRE-DEPLOYMENT VALIDATIONS FOR CEPH STORAGE

To help avoid overcloud deployment failures, validate that the required packages exist on your servers.

1.4.1. Verifying the ceph-ansible package version

The undercloud contains Ansible-based validations that you can run to identify potential problems before you deploy the overcloud. These validations can help you avoid overcloud deployment failures by identifying common problems before they happen.

Procedure

Verify that the correction version of the **ceph-ansible** package is installed:

```
$ ansible-playbook -i /usr/bin/tripleo-ansible-inventory /usr/share/openstack-tripleo-
validations/validations/ceph-ansible-installed.yaml
```

1.4.2. Verifying packages for pre-provisioned nodes

When you use pre-provisioned nodes in your overcloud deployment, you can verify that the servers have the packages required to be overcloud nodes that host Ceph services.

For more information about pre-provisioned nodes, see [Configuring a Basic Overcloud using Pre-Provisioned Nodes](#).

Procedure

Verify that the servers contained the required packages:

```
ansible-playbook -i /usr/bin/tripleo-ansible-inventory /usr/share/openstack-tripleo-
validations/validations/ceph-dependencies-installed.yaml
```

1.5. DEPLOYING THE HCI OVERCLOUD

You must deploy the overcloud after you complete the HCI configuration.



重要

Do not enable Instance HA when you deploy a Red Hat OpenStack Platform (RHOSP) HCI environment. Contact your Red Hat representative if you want to use Instance HA with hyperconverged RHOSP deployments with Red Hat Ceph Storage.

Prerequisites

- You are using a separate base environment file, or set of files, for all other Red Hat Ceph Storage settings, for example, **/home/stack/templates/storage-config.yaml**. For more information, see [Customizing the Storage service](#) and [Appendix A. Sample environment file: creating a Ceph Storage cluster](#).
- You have defined the number of nodes you are assigning to each role in the base environment file. For more information, see [Assigning nodes and flavors to roles](#).
- During undercloud installation, you set **generate_service_certificate=false** in the **undercloud.conf** file. Otherwise, you must inject a trust anchor when you deploy the overcloud, as described in [Enabling SSL/TLS on Overcloud Public Endpoints](#).

Procedure

- Add your new role and environment files to the stack with your other environment files and deploy your HCI overcloud:

```
(undercloud)$ openstack overcloud deploy --templates \
-e [your environment files] \
-r /home/stack/templates/roles_data_hci.yaml \
-e /usr/share/openstack-tripleo-heat-templates/environments/ceph-ansible/ceph-
ansible.yaml \
-e /usr/share/openstack-tripleo-heat-templates/environments/network-isolation.yaml \
-e /usr/share/openstack-tripleo-heat-templates/environments/network-environment.yaml \
-e /usr/share/openstack-tripleo-heat-templates/environments/net-single-nic-with-vlans.yaml \
-e /home/stack/templates/storage-config.yaml \
-e /home/stack/templates/storage-container-config.yaml \
-n /home/stack/templates/network_data.yaml \
[-e /home/stack/templates/ceph-backfill-recovery.yaml \]
--ntp-server pool.ntp.org
```

Including `/usr/share/openstack-tripleo-heat-templates/environments/ceph-ansible/ceph-ansible.yaml` in the deployment command adds the base environment file that deploys a containerized Red Hat Ceph cluster, with all default settings. For more information, see [Deploying an Overcloud with Containerized Red Hat Ceph](#).



注記

Include the following options in the deployment command if your deployment uses single root input/output virtualization (SR-IOV):

```
-e /usr/share/openstack-tripleo-heat-templates/environments/services/neutron-sriov.yaml
-e /home/stack/templates/network-environment.yaml
```

ヒント

You can also use an **answers** file to specify which environment files to include in your deployment. For more information, see [Including environment files in an overcloud deployment](#) in the **Director Installation and Usage** guide.

1.6. OPENSTACK WORKFLOW COMPUTE CPU AND MEMORY CALCULATOR

The OpenStack Workflow calculates the optimal settings for CPU and memory and uses the results to populate the parameters **NovaReservedHostMemory** and **NovaCPUAllocationRatio**.

NovaReservedHostMemory

The **NovaReservedHostMemory** parameter sets the amount of memory (in MB) to reserve for the host node. To determine an appropriate value for hyper-converged nodes, assume that each OSD consumes 3 GB of memory. Given a node with 256 GB memory and 10 OSDs, you can allocate 30 GB of memory for Ceph, leaving 226 GB for Compute. With that much memory a node can host, for example, 113 instances using 2 GB of memory each.

However, you still need to consider additional overhead per instance for the **hypervisor**. Assuming this overhead is 0.5 GB, the same node can only host 90 instances, which accounts for the 226 GB divided by 2.5 GB. The amount of memory to reserve for the host node (that is, memory the Compute service should not use) is:

$$(In * Ov) + (Os * RA)$$

Where:

- **In**: number of instances
- **Ov**: amount of overhead memory needed per instance
- **Os**: number of OSDs on the node
- **RA**: amount of RAM that each OSD should have

With 90 instances, this give us $(90 * 0.5) + (10 * 3) = 75$ GB. The Compute service expects this value in MB, namely 75000.

The following Python code provides this computation:

```

left_over_mem = mem - (GB_per_OSD * osds)
number_of_guests = int(left_over_mem /
    (average_guest_size + GB_overhead_per_guest))
nova_reserved_mem_MB = MB_per_GB * (
    (GB_per_OSD * osds) +
    (number_of_guests * GB_overhead_per_guest))

```

NovaCPUAllocationRatio

The Compute scheduler uses **NovaCPUAllocationRatio** when choosing which Compute nodes on which to deploy an instance. By default, this is **16.0** (as in, 16:1). This means if there are 56 cores on a node, the Compute scheduler will schedule enough instances to consume 896 vCPUs on a node before considering the node unable to host any more.

To determine a suitable **NovaCPUAllocationRatio** for a hyper-converged node, assume each Ceph OSD uses at least one core (unless the workload is I/O-intensive, and on a node with no SSD). On a node with 56 cores and 10 OSDs, this would leave 46 cores for Compute. If each instance uses 100 per cent of the CPU it receives, then the ratio would simply be the number of instance vCPUs divided by the number of cores; that is, $46 / 56 = 0.8$. However, since instances do not normally consume 100 per cent of their allocated CPUs, you can raise the **NovaCPUAllocationRatio** by taking the anticipated percentage into account when determining the number of required guest vCPUs.

So, if we can predict that instances will only use 10 per cent (or 0.1) of their vCPU, then the number of vCPUs for instances can be expressed as $46 / 0.1 = 460$. When this value is divided by the number of cores (56), the ratio increases to approximately 8.

The following Python code provides this computation:

```

cores_per_OSD = 1.0
average_guest_util = 0.1 # 10%
nonceph_cores = cores - (cores_per_OSD * osds)
guest_vCPUs = nonceph_cores / average_guest_util
cpu_allocation_ratio = guest_vCPUs / cores

```

1.7. ADDITIONAL RESOURCES

For more detailed information about the Red Hat OpenStack Platform (RHOSP), see the following guides:

- [Director Installation and Usage](#): This guide provides guidance on the end-to-end deployment of a RHOSP environment, both undercloud and overcloud.
- [Advanced Overcloud Customization](#): This guide describes how to configure advanced RHOSP features through the director, such as how to use custom roles.
- [Deploying an Overcloud with Containerized Red Hat Ceph](#) : This guide describes how to deploy an overcloud that uses Red Hat Ceph Storage as a storage provider.
- [Networking Guide](#): This guide provides details on RHOSP networking tasks.

第2章 SCALING HYPERCONVERGED NODES

To scale HCI nodes up or down, the same principles and methods for scaling Compute nodes or Red Hat Ceph Storage nodes apply.

2.1. SCALING UP HYPERCONVERGED NODES IN HCI ENVIRONMENTS

To scale up hyperconverged nodes in HCI environments follow the same procedure for scaling up non-hyperconverged nodes. For more information, see [Adding nodes to the overcloud](#).



注記

When you tag new nodes, remember to use the right flavor.

For information about how to scale up HCI nodes by adding OSDs to a Red Hat Ceph Storage cluster, see [Adding an OSD to a Ceph Storage node](#) in **Deploying an Overcloud with Containerized Red Hat Ceph**.

2.2. SCALING DOWN HYPERCONVERGED NODES IN HCI ENVIRONMENTS

To scale down hyperconverged nodes in HCI environments you must rebalance the Ceph OSD services on the HCI node, migrate instances from the HCI nodes, and remove the Compute nodes from the overcloud.

Procedure

1. Disable and rebalance the Ceph OSD services on the HCI node. This step is necessary because director does not automatically rebalance the Red Hat Ceph Storage cluster when you remove HCI or Red Hat Ceph Storage nodes.
2. Migrate the instances from the HCI nodes. For more information, see [Migrating virtual machines between Compute nodes](#) in the **Configuring the Compute Service for Instance Creation** guide.
3. Remove the Compute nodes from the overcloud. For more information, see [Removing Compute nodes](#).