



# Red Hat Process Automation Manager 7.1

Deploying a Red Hat Process Automation  
Manager immutable server environment on  
Red Hat OpenShift Container Platform



# Red Hat Process Automation Manager 7.1 Deploying a Red Hat Process Automation Manager immutable server environment on Red Hat OpenShift Container Platform

---

Red Hat Customer Content Services  
brms-docs@redhat.com

## Legal Notice

Copyright © 2020 Red Hat, Inc.

The text of and illustrations in this document are licensed by Red Hat under a Creative Commons Attribution–Share Alike 3.0 Unported license ("CC-BY-SA"). An explanation of CC-BY-SA is available at

<http://creativecommons.org/licenses/by-sa/3.0/>

. In accordance with CC-BY-SA, if you distribute this document or an adaptation of it, you must provide the URL for the original version.

Red Hat, as the licensor of this document, waives the right to enforce, and agrees not to assert, Section 4d of CC-BY-SA to the fullest extent permitted by applicable law.

Red Hat, Red Hat Enterprise Linux, the Shadowman logo, the Red Hat logo, JBoss, OpenShift, Fedora, the Infinity logo, and RHCE are trademarks of Red Hat, Inc., registered in the United States and other countries.

Linux<sup>®</sup> is the registered trademark of Linus Torvalds in the United States and other countries.

Java<sup>®</sup> is a registered trademark of Oracle and/or its affiliates.

XFS<sup>®</sup> is a trademark of Silicon Graphics International Corp. or its subsidiaries in the United States and/or other countries.

MySQL<sup>®</sup> is a registered trademark of MySQL AB in the United States, the European Union and other countries.

Node.js<sup>®</sup> is an official trademark of Joyent. Red Hat is not formally related to or endorsed by the official Joyent Node.js open source or commercial project.

The OpenStack<sup>®</sup> Word Mark and OpenStack logo are either registered trademarks/service marks or trademarks/service marks of the OpenStack Foundation, in the United States and other countries and are used with the OpenStack Foundation's permission. We are not affiliated with, endorsed or sponsored by the OpenStack Foundation, or the OpenStack community.

All other trademarks are the property of their respective owners.

## Abstract

This document describes how to deploy a Red Hat Process Automation Manager 7.1 immutable server environment on Red Hat OpenShift Container Platform.

# Table of Contents

|   |           |
|---|-----------|
| <b>PREFACE</b> .....  | <b>5</b>  |
| <b>CHAPTER 1. OVERVIEW OF RED HAT PROCESS AUTOMATION MANAGER ON RED HAT OPENSIFT<br/>CONTAINER PLATFORM</b> ..... | <b>6</b>  |
| <b>CHAPTER 2. PREPARING TO DEPLOY RED HAT PROCESS AUTOMATION MANAGER IN YOUR OPENSIFT<br/>ENVIRONMENT</b> .....   | <b>8</b>  |
| 2.1. ENSURING THE AVAILABILITY OF IMAGE STREAMS   | 8         |
| 2.2. CREATING THE SECRETS FOR PROCESS SERVER  | 8         |
| 2.3. CREATING THE SECRETS FOR BUSINESS CENTRAL  | 9         |
| 2.4. CHANGING GLUSTERFS CONFIGURATION   | 9         |
| <b>CHAPTER 3. ENVIRONMENT WITH IMMUTABLE SERVERS</b> .....  | <b>11</b> |
| 3.1. DEPLOYING MONITORING AND SMART ROUTER FOR AN ENVIRONMENT WITH IMMUTABLE SERVERS                              | 11        |
| 3.2. EXTRACTING THE SOURCE CODE FROM BUSINESS CENTRAL FOR USE IN AN S2I BUILD                                     | 14        |
| 3.3. DEPLOYING AN IMMUTABLE PROCESS SERVER  | 15        |
| 3.4. MODIFYING THE SERVER CONFIGURATION FOR AN IMMUTABLE SERVER ENVIRONMENT                                       | 19        |
| 3.5. BUILDING A CUSTOM PROCESS SERVER IMAGE FOR AN EXTERNAL DATABASE  | 20        |
| <b>CHAPTER 4. OPENSIFT TEMPLATE REFERENCE INFORMATION</b> .....   | <b>23</b> |
| 4.1. RHPAM71-PROD-IMMUTABLE-MONITOR   | 23        |
| 4.1.1. Parameters   | 23        |
| 4.1.2. Objects  | 34        |
| 4.1.2.1. Services   | 34        |
| 4.1.2.2. Routes   | 35        |
| 4.1.2.3. Deployment Configurations  | 35        |
| 4.1.2.3.1. Triggers   | 35        |
| 4.1.2.3.2. Replicas   | 36        |
| 4.1.2.3.3. Pod Template   | 36        |
| 4.1.2.3.3.1. Image  | 36        |
| 4.1.2.3.3.2. Readiness Probe  | 36        |
| 4.1.2.3.3.3. Liveness Probe   | 36        |
| 4.1.2.3.3.4. Exposed Ports  | 36        |
| 4.1.2.3.3.5. Image Environment Variables  | 37        |
| 4.1.2.3.3.6. Volumes  | 45        |
| 4.1.2.4. External Dependencies  | 45        |
| 4.1.2.4.1. Volume Claims  | 45        |
| 4.2. RHPAM71-PROD-IMMUTABLE-KIESERVER   | 46        |
| 4.2.1. Parameters   | 46        |
| 4.2.2. Objects  | 60        |
| 4.2.2.1. Services   | 60        |
| 4.2.2.2. Routes   | 61        |
| 4.2.2.3. Build Configurations   | 61        |
| 4.2.2.4. Deployment Configurations  | 61        |
| 4.2.2.4.1. Triggers   | 62        |
| 4.2.2.4.2. Replicas   | 62        |
| 4.2.2.4.3. Pod Template   | 62        |
| 4.2.2.4.3.1. Service Accounts   | 62        |
| 4.2.2.4.3.2. Image  | 62        |
| 4.2.2.4.3.3. Readiness Probe  | 62        |
| 4.2.2.4.3.4. Liveness Probe   | 63        |
| 4.2.2.4.3.5. Exposed Ports  | 63        |

|  |     |
|--|-----|
| 4.2.2.4.3.6. Image Environment Variables | 63  |
| 4.2.2.4.3.7. Volumes                     | 74  |
| 4.2.2.5. External Dependencies           | 74  |
| 4.2.2.5.1. Volume Claims                 | 74  |
| 4.2.2.5.2. Secrets                       | 74  |
| 4.3. RHPAM71-KIESERVER-EXTERNALDB        | 74  |
| 4.3.1. Parameters                        | 75  |
| 4.3.2. Objects                           | 89  |
| 4.3.2.1. Services                        | 89  |
| 4.3.2.2. Routes                          | 89  |
| 4.3.2.3. Deployment Configurations       | 90  |
| 4.3.2.3.1. Triggers                      | 90  |
| 4.3.2.3.2. Replicas                      | 90  |
| 4.3.2.3.3. Pod Template                  | 90  |
| 4.3.2.3.3.1. Service Accounts            | 90  |
| 4.3.2.3.3.2. Image                       | 91  |
| 4.3.2.3.3.3. Readiness Probe             | 91  |
| 4.3.2.3.3.4. Liveness Probe              | 91  |
| 4.3.2.3.3.5. Exposed Ports               | 91  |
| 4.3.2.3.3.6. Image Environment Variables | 91  |
| 4.3.2.3.3.7. Volumes                     | 102 |
| 4.3.2.4. External Dependencies           | 103 |
| 4.3.2.4.1. Secrets                       | 103 |
| 4.4. RHPAM71-KIESERVER-MYSQL             | 103 |
| 4.4.1. Parameters                        | 103 |
| 4.4.2. Objects                           | 117 |
| 4.4.2.1. Services                        | 117 |
| 4.4.2.2. Routes                          | 118 |
| 4.4.2.3. Deployment Configurations       | 118 |
| 4.4.2.3.1. Triggers                      | 118 |
| 4.4.2.3.2. Replicas                      | 118 |
| 4.4.2.3.3. Pod Template                  | 118 |
| 4.4.2.3.3.1. Service Accounts            | 118 |
| 4.4.2.3.3.2. Image                       | 119 |
| 4.4.2.3.3.3. Readiness Probe             | 119 |
| 4.4.2.3.3.4. Liveness Probe              | 119 |
| 4.4.2.3.3.5. Exposed Ports               | 119 |
| 4.4.2.3.3.6. Image Environment Variables | 120 |
| 4.4.2.3.3.7. Volumes                     | 130 |
| 4.4.2.4. External Dependencies           | 130 |
| 4.4.2.4.1. Volume Claims                 | 130 |
| 4.4.2.4.2. Secrets                       | 131 |
| 4.5. RHPAM71-KIESERVER-POSTGRESQL        | 131 |
| 4.5.1. Parameters                        | 131 |
| 4.5.2. Objects                           | 145 |
| 4.5.2.1. Services                        | 145 |
| 4.5.2.2. Routes                          | 146 |
| 4.5.2.3. Deployment Configurations       | 146 |
| 4.5.2.3.1. Triggers                      | 146 |
| 4.5.2.3.2. Replicas                      | 146 |
| 4.5.2.3.3. Pod Template                  | 146 |
| 4.5.2.3.3.1. Service Accounts            | 146 |
| 4.5.2.3.3.2. Image                       | 147 |

---

|   |            |
|---|------------|
| 4.5.2.3.3.3. Readiness Probe                    | 147        |
| 4.5.2.3.3.4. Liveness Probe                     | 147        |
| 4.5.2.3.3.5. Exposed Ports                      | 147        |
| 4.5.2.3.3.6. Image Environment Variables        | 148        |
| 4.5.2.3.3.7. Volumes                            | 158        |
| 4.5.2.4. External Dependencies                  | 158        |
| 4.5.2.4.1. Volume Claims                        | 159        |
| 4.5.2.4.2. Secrets                              | 159        |
| 4.6. OPENSIFT USAGE QUICK REFERENCE             | 159        |
| <b>APPENDIX A. VERSIONING INFORMATION</b> ..... | <b>161</b> |





---

## PREFACE

As a system engineer, you can deploy a Red Hat Process Automation Manager immutable server environment on Red Hat OpenShift Container Platform to provide an infrastructure to execute services, process applications, and other business assets. You can use standard integration tools to manage the immutable Process Server image. You can create new server images to add and update the business assets.

### Prerequisites

- At least four gigabytes of memory must be available in the OpenShift cluster/namespace.
  - If you do not deploy monitoring infrastructure but only deploy an immutable Process Server, three gigabytes can be sufficient.
- The OpenShift project for the deployment must be created.
- You must be logged in to the project using the **oc** command. For more information about the **oc** command-line tool, see the OpenShift [CLI Reference](#). If you want to use the OpenShift Web console to deploy templates, you must also be logged on using the Web console.
- Dynamic persistent volume (PV) provisioning must be enabled. Alternatively, if dynamic PV provisioning is not enabled, enough persistent volumes must be available. By default, the following sizes are required:
  - Each immutable server deployment includes a replicated set of Process Server pods, which, by default, requires one 1Gi PV for the database. You can change the database PV size in the template parameters. You can deploy multiple immutable servers; each requires a separate database PV. This requirement does not apply if you use an external database server.
  - If you deploy the immutable monitoring template, two 64Mi PVs are also required (one for Business Central Monitoring and one for Smart Router).

# CHAPTER 1. OVERVIEW OF RED HAT PROCESS AUTOMATION MANAGER ON RED HAT OPENSIFT CONTAINER PLATFORM

You can deploy Red Hat Process Automation Manager into a Red Hat OpenShift Container Platform environment.

In this solution, components of Red Hat Process Automation Manager are deployed as separate OpenShift pods. You can scale each of the pods up and down individually, providing as few or as many containers as necessary for a particular component. You can use standard OpenShift methods to manage the pods and balance the load.

The following key components of Red Hat Process Automation Manager are available on OpenShift:

- Process Server, also known as *Execution Server* or *KIE Server*, is the infrastructure element that runs decision services, process applications, and other deployable assets (collectively referred to as *services*). All logic of the services runs on execution servers.

A database server is normally required for Process Server. You can provide a database server in another OpenShift pod or configure an execution server on OpenShift to use any other database server. Alternatively, Process Server can use an H2 database; in this case, the pod cannot be scaled.


You can freely scale up a Process Server pod, providing as many copies as necessary, running on the same host or different hosts. As you scale a pod up or down, all its copies use the same database server and run the same services. OpenShift provides load balancing and a request can be handled by any of the pods.

You can deploy a separate Process Server pod to run a different group of services. That pod can also be scaled up or down. You can have as many separate replicated Process Server pods as necessary.

- Business Central is a web-based interactive environment for authoring services. It also provides a management and monitoring console. You can use Business Central to develop services and deploy them to Process Servers. You can also use Business Central to monitor the execution of processes.

Business Central is a centralized application. However, you can configure it for high availability, where multiple pods run and share the same data.

Business Central includes a Git repository that holds the source for the services that you develop on it. It also includes a built-in Maven repository. Depending on configuration, Business Central can place the compiled services (KJAR files) into the built-in Maven repository or (if configured) into an external Maven repository.



## IMPORTANT

In the current version, high-availability Business Central functionality is a technology preview.

- Business Central Monitoring is a web-based management and monitoring console. It can manage deployment of services to Process Servers and provide monitoring information, but does not include authoring capabilities. You can use this component to manage staging and production environments.
- Smart Router is an optional layer between Process Servers and other components that interact with them. It is required if you want Business Central or Business Central Monitoring to interact with several different Process Servers. Also, when your environment includes many services

running on different Process Servers, Smart Router provides a single endpoint to all client applications. A client application can make a REST API call requiring any service. Smart Router automatically determines which Process Server must be called for any particular request.

You can arrange these and other components into various environment configurations within OpenShift.

The following environment types are typical:

- *Authoring*: An environment for creating and modifying services using Business Central. It consists of pods that provide Business Central for the authoring work and a Process Server for test execution of the services. For instructions about deploying this environment, see [Deploying a Red Hat Process Automation Manager authoring environment on Red Hat OpenShift Container Platform](#).
- *Managed deployment*: An environment for running existing services for staging and production purposes. This environment includes several groups of Process Server pods; you can deploy and undeploy services on every such group and also scale the group up or down as necessary. Use Business Central Monitoring to deploy, run, and stop the services and to monitor their execution. For instructions about deploying this environment, see [Deploying a Red Hat Process Automation Manager managed server environment on Red Hat OpenShift Container Platform](#).
- *Deployment with immutable servers*: An alternate environment for running existing services for staging and production purposes. In this environment, when you deploy a Process Server pod, it builds an image that loads and starts a service or group of services. You cannot stop any service on the pod or add any new service to the pod. If you want to use another version of a service or modify the configuration in any other way, you deploy a new server image and displace the old one. In this system, the Process Server runs like any other pod on the OpenShift environment; you can use any container-based integration workflows and do not need to use any other tools to manage the pods. Optionally, you can use Business Central Monitoring to monitor the performance of the environment and to stop and restart some of the service instances, but not to deploy additional services to any Process Server or undeploy any existing ones (you can not add or remove containers). For instructions about deploying this environment, see [Deploying a Red Hat Process Automation Manager immutable server environment on Red Hat OpenShift Container Platform](#).

You can also deploy a *trial* or evaluation environment. This environment includes Business Central and a Process Server. You can set it up quickly and use it to evaluate or demonstrate developing and running assets. However, the environment does not use any persistent storage, and any work you do in the environment is not saved. For instructions about deploying this environment, see [Deploying a Red Hat Process Automation Manager trial environment on Red Hat OpenShift Container Platform](#).

To deploy a Red Hat Process Automation Manager environment on OpenShift, you can use the templates that are provided with Red Hat Process Automation Manager. You can modify the templates to ensure that the configuration suits your environment.

## CHAPTER 2. PREPARING TO DEPLOY RED HAT PROCESS AUTOMATION MANAGER IN YOUR OPENSHIFT ENVIRONMENT

Before deploying Red Hat Process Automation Manager in your OpenShift environment, you need to complete several preparatory tasks. You do not need to repeat these tasks if you want to deploy additional images, for example, for new versions of processes or for other processes.

### 2.1. ENSURING THE AVAILABILITY OF IMAGE STREAMS

You must ensure that the image streams that are required for the deployment are available in your OpenShift environment. Some versions of the OpenShift environment include the necessary image streams. You must check if they are available. If they are not available, you must install the **rhpm71-image-streams.yaml** file.

#### Procedure

1. Run the following commands:

```
$ oc get imagestreamtag -n openshift | grep rhpm71-businesscentral
$ oc get imagestreamtag -n openshift | grep rhpm71-kieserver
```

If the outputs of both commands are not empty, the required image streams are available and no further action is required.

2. If the output of one or both of the commands is empty, download the **rhpm71-image-streams.zip** product deliverable file from the [Software Downloads](#) page. Extract the **rhpm71-image-streams.yaml** file from it. Complete one of the following actions:

- Run the following command:

```
$ oc create -f rhpm71-image-streams.yaml
```

- Using the OpenShift Web UI, select **Add to Project → Import YAML / JSON**, then choose the file or paste its contents.

### 2.2. CREATING THE SECRETS FOR PROCESS SERVER

OpenShift uses objects called **Secrets** to hold sensitive information, such as passwords or keystores. See the [Secrets chapter](#) in the OpenShift documentation for more information.

You must create an SSL certificate for Process Server and provide it to your OpenShift environment as a secret.

#### Procedure

1. Generate an SSL keystore with a private and public key for SSL encryption for Process Server. In a production environment, generate a valid signed certificate that matches the expected URL of the Process Server. Save the keystore in a file named **keystore.jks**. Record the name of the certificate and the password of the keystore file.  
See [Generate a SSL Encryption Key and Certificate](#) for more information on how to create a keystore with self-signed or purchased SSL certificates.

- Use the **oc** command to generate a secret named **kieserver-app-secret** from the new keystore file:

```
$ oc create secret generic kieserver-app-secret --from-file=keystore.jks
```

## 2.3. CREATING THE SECRETS FOR BUSINESS CENTRAL

If you are planning to deploy Business Central or Business Central Monitoring in your OpenShift environment, you must create an SSL certificate for Business Central and provide it to your OpenShift environment as a secret. Do not use the same certificate and keystore for Business Central and for Process Server.

### Procedure

- Generate an SSL keystore with a private and public key for SSL encryption for Business Central. In a production environment, generate a valid signed certificate that matches the expected URL of the Business Central. Save the keystore in a file named **keystore.jks**. Record the name of the certificate and the password of the keystore file.  
See [Generate a SSL Encryption Key and Certificate](#) for more information on how to create a keystore with self-signed or purchased SSL certificates.
- Use the **oc** command to generate a secret named **businesscentral-app-secret** from the new keystore file:

```
$ oc create secret generic businesscentral-app-secret --from-file=keystore.jks
```

## 2.4. CHANGING GLUSTERFS CONFIGURATION

Check whether your OpenShift environment uses GlusterFS to provide permanent storage volumes. If it uses GlusterFS, to ensure optimal performance, tune your GlusterFS storage by changing the storage class configuration.

### Procedure

- To check whether your environment uses GlusterFS, run the following command:

```
oc get storageclass
```

In the results, check whether the **(default)** marker is on the storage class that lists **glusterfs**. For example, in the following output the default storage class is **gluster-container**, which does list **glusterfs**:

| NAME                        | PROVISIONER              | AGE |
|-----------------------------|--------------------------|-----|
| gluster-block               | gluster.org/glusterblock | 8d  |
| gluster-container (default) | kubernetes.io/glusterfs  | 8d  |

If the result has a default storage class that does not list **glusterfs** or if the result is empty, you do not need to make any changes. In this case, skip the rest of this procedure.

- To save the configuration of the default storage class into a YAML file, run the following command:

```
oc get storageclass <class-name> -o yaml >storage_config.yaml
```

Where **class-name** is the name of the default storage class. For example:

```
oc get storageclass gluster-container -o yaml >storage_config.yaml
```

3. Edit the **storage\_config.yaml** file:

a. Remove the lines with the following keys:

- **creationTimestamp**
- **resourceVersion**
- **selfLink**
- **uid**

b. On the line with the **volumeoptions** key, add the following two options: **features.cache-invalidation on, performance.nl-cache on**. For example:

```
volumeoptions: client.ssl off, server.ssl off, features.cache-invalidation on,  
performance.nl-cache on
```

4. To remove the existing default storage class, run the following command:

```
oc delete storageclass <class-name>
```

Where **class-name** is the name of the default storage class. For example:

```
oc delete storageclass gluster-container
```

5. To re-create the storage class using the new configuration, run the following command:

```
oc create -f storage_config.yaml
```

## CHAPTER 3. ENVIRONMENT WITH IMMUTABLE SERVERS

You can deploy an environment that includes one or more pods running Process Server with preloaded services. The database servers are, by default, also run in pods. Each Process Server pod can be separately scaled as necessary.

In this case, any services (KJAR files) must be loaded onto a Process Server at the time the image is created. You cannot load or unload services on a running Process Server. The advantage of this approach is that the Process Server with the services in it runs like any other containerized service and does not require specialized management. The Process Server runs like any other pod on the OpenShift environment; you can use any container-based integration workflows as necessary.

Optionally, you can also deploy a pod with Business Central Monitoring and a pod with Smart Router. You can use Business Central Monitoring to start and stop (but not deploy) services on your Process Servers and to view monitoring data.

Smart Router is a single endpoint that can receive calls from client applications to any of your services and route each call automatically to the server that actually runs the process.

When you create a Process Server image, you must build your services using S2I (Source to Image). Provide a Git repository with the source of your services and other business assets; if you develop the services or assets in Business Central, copy the source into a separate repository for the S2I build. OpenShift automatically builds the source, installs the process into the Process Server image, and starts the process. No further management of the image is required. If you want to use a new version of the process, you can build a new image.

If you are using Business Central for authoring services, you can extract the source for your process and place it into a separate Git repository (such as GitHub or an on-premise installation of GitLab) for use in the S2I build.

If you want to use Business Central Monitoring, you must install the Monitoring and Smart Router template *before* creating any Process Server images. You must also provide a Maven repository. Your integration process must ensure that all the versions of KJAR files built into any Process Server image are also available in the Maven repository.

### 3.1. DEPLOYING MONITORING AND SMART ROUTER FOR AN ENVIRONMENT WITH IMMUTABLE SERVERS

If you want to use Business Central Monitoring and Smart Router for an environment with immutable servers, you must deploy them before deploying any Process Servers. If you do not want to use these components, skip this procedure.

To deploy Business Central Monitoring and Smart Router for an environment with immutable servers, use the **rhcam71-prod-immutable-monitor.yaml** template file. You can extract this file from the **rhcam-7.1.0-openshift-templates.zip** product deliverable file. You can download the file from the [Software Downloads](#) page.

#### Procedure

1. Use one of the following methods to deploy the template:
  - In the OpenShift Web UI, select **Add to Project** → **Import YAML / JSON** and then select or paste the **rhcam71-prod-immutable-monitor.yaml** file. In the **Add Template** window, ensure **Process the template** is selected and click **Continue**.

- To use the OpenShift command line console, prepare the following command line:

```
oc new-app -f <template-path>/rhpam71-prod-immutable-monitor.yaml -p  
BUSINESS_CENTRAL_HTTPS_SECRET=businesscentral-app-secret
```

In this command line:

- Replace **<template-path>** with the path to the downloaded template file.
  - Use as many **-p PARAMETER=value** pairs as needed to set the required parameters. You can view the template file to see descriptions for all parameters.
2. Set the following parameters as necessary:
- **Business Central Server Keystore Secret Name** (**BUSINESS\_CENTRAL\_HTTPS\_SECRET**): The name of the secret for Business Central, as created in [Section 2.3, "Creating the secrets for Business Central"](#).
  - **Application Name** (**APPLICATION\_NAME**): The name of the OpenShift application. It is used in the default URLs for Business Central Monitoring and Smart Router. OpenShift also uses the application name to create a separate set of deployment configurations, services, routes, labels, and artifacts. You can deploy several applications using the same template into the same project, as long as you use different application names.
  - **Maven repository URL** (**MAVEN\_REPO\_URL**): A URL for a Maven repository. You must upload all the processes (KJAR files) that are to be deployed in your environment into this repository.
  - **Maven repository username** (**MAVEN\_REPO\_USERNAME**): The username for the Maven repository.
  - **Maven repository password** (**MAVEN\_REPO\_PASSWORD**): The password for the Maven repository.
  - **Business Central Server Certificate Name** (**BUSINESS\_CENTRAL\_HTTPS\_NAME**): The name of the certificate in the keystore that you created in [Section 2.3, "Creating the secrets for Business Central"](#).
  - **Business Central Server Keystore Password** (**BUSINESS\_CENTRAL\_HTTPS\_PASSWORD**): The password for the keystore that you created in [Section 2.3, "Creating the secrets for Business Central"](#).
  - **ImageStream Namespace** (**IMAGE\_STREAM\_NAMESPACE**): The namespace where the image streams are available. If the image streams were already available in your OpenShift environment (see [Section 2.1, "Ensuring the availability of image streams"](#)), the namespace is **openshift**. If you have installed the image streams file, the namespace is the name of the OpenShift project.  
You can also set other parameters as necessary.
3. If you want to use RH-SSO or LDAP authentication, complete the following additional configuration:
- a. In the RH-SSO or LDAP service, create all user names in the deployment parameters. If you do not set any of the parameters, create users with the default user names. The created users must also be assigned to roles:



- **KIE\_ADMIN\_USER**: default user name **adminUser**, roles: **kie-server,rest-all,admin,kiemgmt,Administrators**
  - **KIE\_SERVER\_MONITOR\_USER**: user name **monitorUser**. You **must not** change this user name. You also **must** configure the **KIE\_SERVER\_MONITOR\_PASSWORD** parameter to the same value as the password for this user in the RH-SSO service. Otherwise, the suggested parameter settings for the server deployments will be incorrect. Roles: **kie-server,rest-all,guest**
- b. If you want to configure Red Hat Single Sign On (RH-SSO) authentication, an RH-SSO realm that applies to Red Hat Process Automation Manager must exist. A client within RH-SSO must also exist for Business Central Monitoring. If the client does not yet exist, the template can create it during deployment.  
For the user roles that you can configure in RH-SSO, see [Roles and users](#).

Use one of the following procedures:

- i. If the client for Red Hat Process Automation Manager within RH-SSO already exists, set the following parameters in the template:
  - **RH-SSO URL (SSO\_URL)**: The URL for RH-SSO.
  - **RH-SSO Realm name (SSO\_REALM)**: The RH-SSO realm for Red Hat Process Automation Manager.
  - **Business Central Monitoring RH-SSO Client name (BUSINESS\_CENTRAL\_SSO\_CLIENT)**: The RH-SSO client name for Business Central Monitoring.
  - **Business Central Monitoring RH-SSO Client Secret (BUSINESS\_CENTRAL\_SSO\_SECRET)**: The secret string that is set in RH-SSO for the client for Business Central Monitoring.
  - **RH-SSO Disable SSL Certificate Validation (SSO\_DISABLE\_SSL\_CERTIFICATE\_VALIDATION)**: Set to **true** if your RH-SSO installation does not use a valid HTTPS certificate.
- ii. To create the client for Red Hat Process Automation Manager within RH-SSO, set the following parameters in the template:
  - **RH-SSO URL (SSO\_URL)**: The URL for RH-SSO.
  - **RH-SSO Realm name (SSO\_REALM)**: The RH-SSO realm for Red Hat Process Automation Manager.
  - **Business Central Monitoring RH-SSO Client name (BUSINESS\_CENTRAL\_SSO\_CLIENT)**: The name of the client to create in RH-SSO for Business Central Monitoring.
  - **Business Central Monitoring RH-SSO Client Secret (BUSINESS\_CENTRAL\_SSO\_SECRET)**: The secret string to set in RH-SSO for the client for Business Central Monitoring.
  - **Business Central Monitoring Custom http Route Hostname (BUSINESS\_CENTRAL\_HOSTNAME\_HTTP)**: The fully qualified host name to use for the HTTP endpoint for Business Central Monitoring. If you need to create a client in RH-SSO, you can not leave this parameter blank.

- **Business Central Monitoring Custom https Route Hostname** (**BUSINESS\_CENTRAL\_HOSTNAME\_HTTPS**): The fully qualified host name to use for the HTTPS endpoint for Business Central Monitoring. If you need to create a client in RH-SSO, you can not leave this parameter blank.
  - **RH-SSO Realm Admin Username** (**SSO\_USERNAME**) and **RH-SSO Realm Admin Password** (**SSO\_PASSWORD**): The user name and password for the realm administrator user for the RH-SSO realm for Red Hat Process Automation Manager.
  - **RH-SSO Disable SSL Certificate Validation** (**SSO\_DISABLE\_SSL\_CERTIFICATE\_VALIDATION**): Set to **true** if your RH-SSO installation does not use a valid HTTPS certificate.
- c. To configure LDAP, set the **AUTH\_LDAP\*** parameters of the template. These parameters correspond to the settings of the LdapExtended Login module of Red Hat JBoss EAP. For instructions about using these settings, see [LdapExtended Login Module](#). Do not configure LDAP authentication and RH-SSO authentication in the same deployment.
4. Complete the creation of the environment, depending on the method that you are using:
- In the OpenShift Web UI, click **Create**.
    - If the **This will create resources that may have security or project behavior implications** message appears, click **Create Anyway**.
  - Complete and run the command line.
5. Record the suggested command line that is displayed. This command line includes the parameters that you must set when deploying the immutable servers.

## 3.2. EXTRACTING THE SOURCE CODE FROM BUSINESS CENTRAL FOR USE IN AN S2I BUILD

If you are using Business Central for authoring services, you can extract the source code for your service and place it into a separate Git repository (such as GitHub or an on-premise installation of GitLab) for use in the S2I build.

### Procedure

1. Use the following command to extract the source code:

```
git clone ssh://adminUser@business-central-host:8001/MySpace/MyProject
```

Replace:

- **adminUser** with the administrative user for Business Central
  - **business-central-host** with the host on which Business Central is running
  - **MySpace** with the name of the Business Central space in which the project is located
  - **MyProject** with the name of the project
2. Upload the source code to another Git repository for the S2I build.

### 3.3. DEPLOYING AN IMMUTABLE PROCESS SERVER

To deploy an immutable Process Server, use the **rhpm71-prod-immutable-kieserver.yaml** template file. You can extract this file from the **rhpm-7.1.0-openshift-templates.zip** product deliverable file. You can download the file from the [Software Downloads](#) page.

If you want to modify the environment defined by the template file, see [Section 3.4, “Modifying the server configuration for an immutable server environment”](#).

When you deploy an immutable Process Server, the deployment procedure retrieves the source code for any services that must run on this server, builds the services, and includes them in the server image.

You can configure the Process Server to connect to Smart Router and to Business Central Monitoring. If you use the server with Business Central Monitoring, you must ensure that the same versions of KJAR files are uploaded to the Maven repository that the Business Central Monitoring instance uses.

#### Procedure

1. Use one of the following methods to deploy the template:

- In the OpenShift Web UI, select **Add to Project → Import YAML / JSON** and then select or paste the **rhpm71-prod-immutable-kieserver.yaml** file. In the **Add Template** window, ensure **Process the template** is selected and click **Continue**.
- To use the OpenShift command line console, prepare the following command line:

```
oc new-app -f <template-path>/rhpm71-prod-immutable-kieserver.yaml -p
KIE_SERVER_HTTPS_SECRET=kieserver-app-secret
```

In this command line:

- Replace **<template-path>** with the path to the downloaded template file.
  - Use as many **-p PARAMETER=value** pairs as needed to set the required parameters. You can view the template file to see descriptions for all parameters. Alternatively, if you have deployed the monitoring infrastructure (see [Section 3.1, “Deploying monitoring and Smart Router for an environment with immutable servers”](#)), use the command line that was displayed when you deployed the infrastructure and add the **-p KIE\_SERVER\_HTTPS\_SECRET=kieserver-app-secret** parameter.
2. Set the following parameters as necessary:
- **KIE Server Keystore Secret Name (KIE\_SERVER\_HTTPS\_SECRET)**: The name of the secret for Process Server, as created in [Section 2.2, “Creating the secrets for Process Server”](#).
  - **Application Name (APPLICATION\_NAME)**: The name of the OpenShift application. It is used in the default URL for Process Server. OpenShift uses the application name to create a separate set of deployment configurations, services, routes, labels, and artifacts. You can deploy several applications using the same template into the same project, as long as you use different application names. Also, the application name determines the name of the server configuration (server template) on the Business Central that the Process Server is to join.
  - **KIE Server Certificate Name (KIE\_SERVER\_HTTPS\_NAME)**: The name of the certificate in the keystore that you created in [Section 2.2, “Creating the secrets for Process Server”](#).

- **KIE Server Keystore Password (KIE\_SERVER\_HTTPS\_PASSWORD):** The password for the keystore that you created in [Section 2.2, “Creating the secrets for Process Server”](#).
  - **KIE Server Container Deployment(KIE\_SERVER\_CONTAINER\_DEPLOYMENT):** The identifying information of the decision service (KJAR file) that is built from your source. The format is: **<containerId>=<groupId>:<artifactId>:<version>**. You can provide two or more KJAR files using the | separator, for example: **containerId=groupId:artifactId:version|c2=g2:a2:v2**. The Maven build process must produce all these files from the source in the Git repository.
  - **Git Repository URL (SOURCE\_REPOSITORY\_URL):** The URL for the Git repository that contains the source for your decision service.
  - **Git Reference (SOURCE\_REPOSITORY\_REF):** The branch in the Git repository
  - **Context Directory (CONTEXT\_DIR):** The path to the source within the project downloaded from the Git repository
  - **Artifact Directory (ARTIFACT\_DIR):** The path within the project that contains the required binary files (KJAR files and any other necessary files) after a successful Maven build. Normally this directory is the target directory of the build. However, you can provide prebuilt binaries in this directory in the Git repository
  - **ImageStream Namespace (IMAGE\_STREAM\_NAMESPACE):** The namespace where the image streams are available. If the image streams were already available in your OpenShift environment (see [Section 2.1, “Ensuring the availability of image streams”](#)), the namespace is **openshift**. If you have installed the image streams file, the namespace is the name of the OpenShift project.
3. If your build includes dependencies that are not available on the public Maven tree and require a separate repository, set the parameters to provide this repository:
    - **Maven repository URL (MAVEN\_REPO\_URL):** The URL for the Maven repository.
    - **Maven repository username (MAVEN\_REPO\_USERNAME):** The username for the Maven repository.
    - **Maven repository password (MAVEN\_REPO\_PASSWORD):** The username for the Maven repository.
  4. If you want to use Business Central Monitoring or Smart Router, set the parameters that were displayed in the sample command line after you deployed the monitoring infrastructure (see [Section 3.1, “Deploying monitoring and Smart Router for an environment with immutable servers”](#)).
  5. If you want to use RH-SSO or LDAP authentication, complete the following additional configuration:
    - a. In the RH-SSO or LDAP service, create all user names in the deployment parameters. If you do not set any of the parameters, create users with the default user names. The created users must also be assigned to roles:
      - **KIE\_ADMIN\_USER:** default user name **adminUser**, roles: **kie-server,rest-all,admin,kiemgmt,Administrators**
      - **KIE\_SERVER\_USER:** default user name **executionUser**, roles **kie-server,rest-all,guest**

- b. If you want to configure Red Hat Single Sign On (RH-SSO) authentication, an RH-SSO realm that applies to Red Hat Process Automation Manager must exist. A client within RH-SSO must also exist for
- For the user roles that you can configure in RH-SSO, see [Roles and users](#).

Use one of the following procedures:

- i. If the client for Red Hat Process Automation Manager within RH-SSO already exists, set the following parameters in the template:
- **RH-SSO URL (SSO\_URL)**: The URL for RH-SSO.
  - **RH-SSO Realm name (SSO\_REALM)**: The RH-SSO realm for Red Hat Process Automation Manager.
  - **KIE Server RH-SSO Client name (KIE\_SERVER\_SSO\_CLIENT)**: The RH-SSO client name for Process Server.
  - **KIE Server RH-SSO Client Secret (KIE\_SERVER\_SSO\_SECRET)**: The secret string that is set in RH-SSO for the client for Process Server.
  - **RH-SSO Disable SSL Certificate Validation (SSO\_DISABLE\_SSL\_CERTIFICATE\_VALIDATION)**: Set to **true** if your RH-SSO installation does not use a valid HTTPS certificate.
- ii. To create the client for Red Hat Process Automation Manager within RH-SSO, set the following parameters in the template:
- **RH-SSO URL (SSO\_URL)**: The URL for RH-SSO.
  - **RH-SSO Realm name (SSO\_REALM)**: The RH-SSO realm for Red Hat Process Automation Manager.
  - **KIE Server RH-SSO Client name (KIE\_SERVER\_SSO\_CLIENT)**: The name of the client to create in RH-SSO for Process Server.
  - **KIE Server RH-SSO Client Secret (KIE\_SERVER\_SSO\_SECRET)**: The secret string to set in RH-SSO for the client for Process Server.
  - **KIE Server Custom http Route Hostname (KIE\_SERVER\_HOSTNAME\_HTTP)**: The fully qualified host name to use for the HTTP endpoint for Process Server. If you need to create a client in RH-SSO, you can not leave this parameter blank.
  - **KIE Server Custom https Route Hostname (KIE\_SERVER\_HOSTNAME\_HTTPS)**: The fully qualified host name to use for the HTTPS endpoint for Process Server. If you need to create a client in RH-SSO, you can not leave this parameter blank.
  - **RH-SSO Realm Admin Username (SSO\_USERNAME) and RH-SSO Realm Admin Password (SSO\_PASSWORD)**: The user name and password for the realm administrator user for the RH-SSO realm for Red Hat Process Automation Manager.
  - **RH-SSO Disable SSL Certificate Validation (SSO\_DISABLE\_SSL\_CERTIFICATE\_VALIDATION)**: Set to **true** if your RH-SSO installation does not use a valid HTTPS certificate.

- c. To configure LDAP, set the **AUTH\_LDAP\*** parameters of the template. These parameters correspond to the settings of the LdapExtended Login module of Red Hat JBoss EAP. For instructions about using these settings, see [LdapExtended Login Module](#). Do not configure LDAP authentication and RH-SSO authentication in the same deployment.
6. If you modified the template to use an external database server for the Process Server, as described in [Section 3.4, "Modifying the server configuration for an immutable server environment"](#), set the following parameters:
    - **KIE Server External Database Driver(KIE\_SERVER\_EXTERNALDB\_DRIVER)**: The driver for the server, depending on the server type:
      - mysql
      - postgresql
      - mariadb
      - mssql
      - db2
      - oracle
      - sybase
    - **KIE Server External Database User(KIE\_SERVER\_EXTERNALDB\_USER)** and **KIE Server External Database Password (KIE\_SERVER\_EXTERNALDB\_PWD)**: The user name and password for the external database server.
    - **KIE Server External Database URL(KIE\_SERVER\_EXTERNALDB\_HOST)**: The JDBC URL for the external database server.
    - **KIE Server External Database Dialect(KIE\_SERVER\_EXTERNALDB\_DIALECT)**: The Hibernate dialect for the server, depending on the server type:
      - **org.hibernate.dialect.MySQL5Dialect** (used for MySQL and MariaDB)
      - **org.hibernate.dialect.PostgreSQLDialect**
      - **org.hibernate.dialect.SQLServer2012Dialect** (used for MS SQL)
      - **org.hibernate.dialect.DB2Dialect**
      - **org.hibernate.dialect.Oracle12cDialect**
      - **org.hibernate.dialect.SybaseASE15Dialect**
    - **KIE Server External Database Host(KIE\_SERVER\_EXTERNALDB\_HOST)**: The host name of the external database server.
    - **KIE Server External Database Port(KIE\_SERVER\_EXTERNALDB\_PORT)**: The port number of the external database server.
    - **KIE Server External Database name(KIE\_SERVER\_EXTERNALDB\_DB)**: The database name to use on the external database server.

7. If you created a custom image for using an external database server other than MySQL or PostgreSQL, as described in [Section 3.5, “Building a custom Process Server image for an external database”](#), set the KIE Server Image Stream Name (**KIE\_SERVER\_IMAGE\_STREAM\_NAME**) parameter to the following value:
  - For Microsoft SQL Server, **rhcam71-kieserver-mssql-openshift**
  - For MariaDB, **rhcam71-kieserver-mariadb-openshift**
  - For IBM DB2, **rhcam71-kieserver-db2-openshift**
  - For Oracle Database, **rhcam71-kieserver-oracle-openshift**
  - For Sybase, **rhcam71-kieserver-sybase-openshift**
8. Complete the creation of the environment, depending on the method that you are using:
  - In the OpenShift Web UI, click **Create**.
    - If the **This will create resources that may have security or project behavior implications** message appears, click **Create Anyway**.
  - Complete and run the command line.

### 3.4. MODIFYING THE SERVER CONFIGURATION FOR AN IMMUTABLE SERVER ENVIRONMENT

By default, the immutable server configuration creates a separate PostgreSQL pod to provide the database server for each replicable Process Server. If you prefer to use MySQL or to use an external server (outside the OpenShift project), you need to modify the **rhcam71-prod-immutable-kieserver.yaml** template before deploying the server.

An OpenShift template defines a set of objects that can be created by OpenShift. To change an environment configuration, you need to modify, add, or delete these objects. To simplify this task, comments are provided in the Red Hat Process Automation Manager templates.

Some comments mark blocks within the template, starting with **BEGIN** and ending with **END**. For example, the following block is named **Sample block**:

```
## Sample block BEGIN
sample line 1
sample line 2
sample line 3
## Sample block END
```

For some changes, you might need to replace a block in one template file with a block from another template file provided with Red Hat Process Automation Manager. In this case, delete the block, then paste the new block in its exact location.

#### Procedure

- If you want to use MySQL instead of PostgreSQL, replace several blocks of the file, marked with comments from **BEGIN** to **END**, with blocks from the **rhcam71-kieserver-mysql.yaml** file:

1. Replace the block named **PostgreSQL database parameters** with the block named **MySQL database parameters**. (Take this block and all subsequent replacement blocks from the `rhcam71-kieserver-postgresql.yaml` file.)
  2. Replace the block named **PostgreSQL service** with the block named **MySQL service**.
  3. Replace the block named **PostgreSQL driver settings** with the block named **MySQL driver settings**.
  4. Replace the block named **PostgreSQL deployment config** with the block named **MySQL deployment config**.
  5. Replace the block named **PostgreSQL persistent volume claim** with the block named **MySQL persistent volume claim**.
- If you want to use an external database server, replace several blocks of the file, marked with comments from **BEGIN** to **END**, with blocks from the `rhcam71-kieserver-externaldb.yaml` file, and also remove some blocks:
    1. Replace the block named **PostgreSQL database parameters** with the block named **External database parameters**. (Take this block and all subsequent replacement blocks from the `rhcam71-kieserver-externaldb.yaml` file.)
    2. Replace the block named **PostgreSQL driver settings** with the block named **External database driver settings**.
    3. Remove the following blocks of the file, marked with comments from **BEGIN** to **END**:
      - **PostgreSQL service**
      - **PostgreSQL deployment config**
      - **PostgreSQL persistent volume claim**



### IMPORTANT

The standard Process Server image includes drivers for MySQL and PostgreSQL external database servers. If you want to use another database server, you must build a custom Process Server image. For instructions, see [Section 3.5, "Building a custom Process Server image for an external database"](#).

## 3.5. BUILDING A CUSTOM PROCESS SERVER IMAGE FOR AN EXTERNAL DATABASE

If you want to use an external database server for a Process Server and this server is neither MySQL nor PostgreSQL, you must build a custom Process Server image with drivers for this server before deploying your environment.

You can use this build procedure to provide drivers for the following database servers:

- Microsoft SQL Server
- MariaDB
- IBM DB2



- Oracle Database
- Sybase

For the tested versions of the database servers, see [Red Hat Process Automation Manager 7 Supported Configurations](#).

The build procedure creates a custom image that extends the existing Process Server image. It pushes this custom image into a new **ImageStream** in the **openshift** namespace with the same version tag as the original image.

### Prerequisites

- You have logged on to your project in the OpenShift environment using the **oc** command as a user with the **cluster-admin** role.
- For IBM DB2, Oracle Database, or Sybase, you have downloaded the JDBC driver from the database server vendor.

### Procedure

1. For IBM DB2, Oracle Database, or Sybase, provide the JDBC driver JAR in a local directory or on an HTTP server. Within the local directory or HTTP server, the following paths are expected:
  - For IBM DB2, **<local\_path\_or\_url>/com/ibm/db2/jcc/db2jcc4/10.5/db2jcc4-10.5.jar**
  - For Oracle Database, **<local\_path\_or\_url>/com/oracle/ojdbc7/12.1.0.1/ojdbc7-12.1.0.1.jar**
  - For Sybase, **<local\_path\_or\_url>/com/sybase/jconn4/16.0\_PL05/jconn4-16.0\_PL05.jar**  
Where **<local\_path\_or\_url>** is the path to the local directory or the URL for the HTTP server where the driver is provided.
2. To install the source code for the custom build, download the **rhpmam-7.1.0-openshift-templates.zip** product deliverable file from the [Software Downloads](#) page. Unzip the file and, using the command line, change to the **templates/contrib/jdbc** directory of the unzipped file.
3. Change to the following subdirectory:
  - For Microsoft SQL Server, **mssql-driver-image**
  - For MariaDB, **mariadb-driver-image**
  - For IBM DB2, **db2-driver-image**
  - For Oracle Database, **oracle-driver-image**
  - For Sybase, **sybase-driver-image**
4. Run the following command:
  - For Microsoft SQL Server or MariaDB:
 

```
./build.sh
```
  - For IBM DB2, Oracle Database, or Sybase:
    -

```
../build.sh --artifact-repo=<local_path_or_url>
```

Where **<local\_path\_or\_url>** is the path to the local directory or the URL for the HTTP server where the driver is provided. For example:

```
../build.sh --artifact-repo=/home/builder/drivers  
../build.sh --artifact-repo=http://nexus.example.com/nexus/content/groups/public
```

If you want to configure your OpenShift docker registry address in the process, add also the **--registry=<registry\_name.domain\_name:port>** parameter to your build command.

Examples:

```
../build.sh --registry=docker-registry.custom-domain:80  
../build.sh --artifact-repo=/home/builder/drivers --registry=docker-registry.custom-domain:80
```

## CHAPTER 4. OPENSIFT TEMPLATE REFERENCE INFORMATION

Red Hat Process Automation Manager provides the following OpenShift templates. To access the templates, download and extract the **rhpmam-7.1.0-openshift-templates.zip** product deliverable file from the [Software Downloads](#) page of the Red Hat customer portal.

- **rhpmam71-prod-immutable-monitor.yaml** provides a Business Central Monitoring instance and a Smart Router that you can use with immutable Process Servers. When you deploy this template, OpenShift displays the settings that you must then use for deploying the **rhpmam71-prod-immutable-kieserver.yaml** template. For details about this template, see [Section 4.1, “rhpmam71-prod-immutable-monitor”](#).
- **rhpmam71-prod-immutable-kieserver.yaml** provides an immutable Process Server. When you deploy this template, a source-to-image (S2I) build is triggered for one or several services that are to run on the Process Server. The Process Server can optionally be configured to connect to the Business Central Monitoring and Smart Router provided by **rhpmam71-prod-immutable-monitor.yaml**. For details about this template, see [Section 4.2, “rhpmam71-prod-immutable-kieserver”](#).
- **rhpmam71-kieserver-externaldb.yaml** provides a Process Server that uses an external database. You can configure the Process Server to connect to a Business Central. Also, you can copy sections from this template into another template to configure a Process Server in the other template to use an external database. For details about this template, see [Section 4.3, “rhpmam71-kieserver-externaldb”](#).
- **rhpmam71-kieserver-mysql.yaml** provides a Process Server and a MySQL instance that the Process Server uses. You can configure the Process Server to connect to a Business Central. Also, you can copy sections from this template into another template to configure a Process Server in the other template to use MySQL and to provide the MySQL instance. For details about this template, see [Section 4.4, “rhpmam71-kieserver-mysql”](#).
- **rhpmam71-kieserver-postgresql.yaml** provides a Process Server and a PostgreSQL instance that the Process Server uses. You can configure the Process Server to connect to a Business Central. Also, you can copy sections from this template into another template to configure a Process Server in the other template to use PostgreSQL and to provide the PostgreSQL instance. For details about this template, see [Section 4.4, “rhpmam71-kieserver-mysql”](#).

### 4.1. RHPAM71-PROD-IMMUTABLE-MONITOR

Application template for a router and monitoring console in a production environment, for Red Hat Process Automation Manager 7.1

#### 4.1.1. Parameters

Templates allow you to define parameters which take on a value. That value is then substituted wherever the parameter is referenced. References can be defined in any text field in the objects list field. Refer to the [Openshift documentation](#) for more information.

| Variable name                          | Image Environment Variable              | Description   | Example value                                | Required |
|--|---|---|--|----------|
| <b>APPLICATION_NAME</b>                | –                                       | The name for the application.   | myapp  | True     |
| <b>MAVEN_REPO_ID</b>                   | <b>EXTERNAL_MAVEN_REPO_ID</b>           | The id to use for the maven repository, if set. Default is generated randomly.  | <b>`\${MAVEN_REPO_ID}`</b>                   | False    |
| <b>MAVEN_REPO_URL</b>                  | <b>EXTERNAL_MAVEN_REPO_URL</b>          | Fully qualified URL to a Maven repository or service.   | <b>`\${MAVEN_REPO_URL}`</b>                  | False    |
| <b>MAVEN_REPO_USERNAME</b>             | <b>RHPAMCENTRAL_MAVEN_REPO_USERNAME</b> | Username to access the Maven repository, if required.   | <b>`\${BUSINESS_CENTRAL_MAVEN_USERNAME}`</b> | False    |
| <b>MAVEN_REPO_PASSWORD</b>             | <b>RHPAMCENTRAL_MAVEN_REPO_PASSWORD</b> | Password to access the Maven repository, if required.   | <b>`\${BUSINESS_CENTRAL_MAVEN_PASSWORD}`</b> | False    |
| <b>BUSINESS_CENTRAL_MAVEN_SERVICE</b>  | –                                       | The service name for the optional business central, where it can be reached, to allow service lookups (for maven repo usage), if required | –  | False    |
| <b>BUSINESS_CENTRAL_MAVEN_USERNAME</b> | –                                       | Username to access the Maven service hosted by Business Central inside EAP.   | –  | False    |
| <b>BUSINESS_CENTRAL_MAVEN_PASSWORD</b> | –                                       | Password to access the Maven service hosted by Business Central inside EAP.   | –  | False    |
| <b>KIE_ADMIN_USERNAME</b>              | <b>KIE_ADMIN_USERNAME</b>               | KIE administrator username  | adminUser                                    | False    |

| Variable name                 | Image Environment Variable | Description   | Example value             | Required |
|-------------------------------|----------------------------|---|---------------------------|----------|
| <b>KIE_ADMIN_PWD</b>          | <b>KIE_ADMIN_PWD</b>       | KIE administrator password  | <b>\${KIE_ADMIN_PWD}</b>  | False    |
| <b>KIE_SERVER_USER</b>        | <b>KIE_SERVER_USER</b>     | KIE server username (Sets the org.kie.server.user system property)  | executionUser             | False    |
| <b>KIE_SERVER_PWD</b>         | <b>KIE_SERVER_PWD</b>      | KIE server password, used to connect to KIE servers. Generated value can be a suggestion to use for the various (Sets the org.kie.server.pwd system property)   | <b>\${KIE_SERVER_PWD}</b> | False    |
| <b>IMAGE_STREAM_NAMESPACE</b> | –                          | Namespace in which the ImageStreams for Red Hat Middleware images are installed. These ImageStreams are normally installed in the openshift namespace. You should only need to modify this if you've installed the ImageStreams in a different namespace/project. | openshift                 | True     |
| <b>IMAGE_STREAM_TAG</b>       | –                          | A named pointer to an image in an image stream. Default is "1.1".   | 1.1                       | False    |

| Variable name                         | Image Environment Variable            | Description   | Example value                               | Required |
|---------------------------------------|---------------------------------------|---|---|----------|
| <b>SMART_ROUTER_HOSTNAME_HTTP</b>     | <b>HOSTNAME_HTTP</b>                  | Custom hostname for http service route. Leave blank for default hostname, e.g. <application-name>-smartrouter-<project>.<default-domain-suffix>'                                      | <b>`\${BUSINESS_CENTRAL_HOSTNAME_HTTP}`</b> | False    |
| <b>KIE_SERVER_ROUTER_ID</b>           | <b>KIE_SERVER_ROUTER_ID</b>           | Router ID used when connecting to the controller (router property org.kie.server.router.id)   | kie-server-router                           | True     |
| <b>KIE_SERVER_ROUTER_PROTOCOL</b>     | <b>KIE_SERVER_ROUTER_PROTOCOL</b>     | KIE server router protocol (Used to build the org.kie.server.router.url.external property)  | <b>`\${KIE_SERVER_ROUTER_PROTOCOL}`</b>     | False    |
| <b>KIE_SERVER_ROUTER_URL_EXTERNAL</b> | <b>KIE_SERVER_ROUTER_URL_EXTERNAL</b> | Public URL where the router can be found. Format <a href="http://&lt;host&gt;:&lt;port&gt;">http://&lt;host&gt;:&lt;port&gt;</a> (router property org.kie.server.router.url.external) | <b>`\${KIE_SERVER_ROUTER_URL_EXTERNAL}`</b> | False    |
| <b>KIE_SERVER_ROUTER_NAME</b>         | <b>KIE_SERVER_ROUTER_NAME</b>         | Router name used when connecting to the controller (router property org.kie.server.router.name)   | KIE Server Router                           | True     |
| <b>KIE_SERVER_MONITOR_USER</b>        | –                                     | KIE server monitor username (Sets the org.kie.server.controller.user.system property)   | monitorUser                                 | False    |

| Variable name                          | Image Environment Variable | Description  | Example value                                | Required |
|--|----------------------------|--|--|----------|
| <b>KIE_SERVER_MONITOR_PWD</b>          | –                          | KIE server monitor password (Sets the org.kie.server.controller.pwd system property)   | –  | False    |
| <b>KIE_SERVER_MONITOR_TOKEN</b>        | –                          | KIE server monitor token for bearer authentication (Sets the org.kie.server.controller.token system property)  | –  | False    |
| <b>BUSINESS_CENTRAL_HOSTNAME_HTTP</b>  | <b>HOSTNAME_HTTP</b>       | Custom hostname for http service route. Leave blank for default hostname, e.g.: <application-name>-rhpamcentrmon-<project>.<default-domain-suffix>         | <b>`\${BUSINESS_CENTRAL_HOSTNAME_HTTP}`</b>  | False    |
| <b>BUSINESS_CENTRAL_HOSTNAME_HTTPS</b> | <b>HOSTNAME_HTTPS</b>      | Custom hostname for https service route. Leave blank for default hostname, e.g.: secure-<application-name>-rhpamcentrmon-<project>.<default-domain-suffix> | <b>`\${BUSINESS_CENTRAL_HOSTNAME_HTTPS}`</b> | False    |
| <b>BUSINESS_CENTRAL_HTTPS_SECRET</b>   | –                          | The name of the secret containing the keystore file  | –  | True     |
| <b>BUSINESS_CENTRAL_HTTPS_KEYSTORE</b> | <b>HTTPS_KEYSTORE</b>      | The name of the keystore file within the secret  | keystore.jks                                 | False    |

| Variable name                          | Image Environment Variable | Description  | Example value                               | Required |
|--|----------------------------|--|---|----------|
| <b>BUSINESS_CENTRAL_HTTPS_NAME</b>     | <b>HTTPS_NAME</b>          | The name associated with the server certificate  | jboss                                       | False    |
| <b>BUSINESS_CENTRAL_HTTPS_PASSWORD</b> | <b>HTTPS_PASSWORD</b>      | The password for the keystore and certificate  | mykeystorepass                              | False    |
| <b>SMART_ROUTER_HOSTNAME_HTTP</b>      | <b>HOSTNAME_HTTP</b>       | Custom hostname for http service route. Leave blank for default hostname, e.g.: <application-name>-rhpamcentrmon-<project>.<default-domain-suffix> | <b>`\${BUSINESS_CENTRAL_HOSTNAME_HTTP}`</b> | False    |
| <b>BUSINESS_CENTRAL_MEMORY_LIMIT</b>   | –                          | Business Central Container memory limit  | 2Gi   | False    |
| <b>SMART_ROUTER_MEMORY_LIMIT</b>       | –                          | Smart Router Container memory limit  | 512Mi                                       | False    |
| <b>SSO_URL</b>                         | <b>SSO_URL</b>             | RH-SSO URL   | <b>`\${SSO_URL}`</b>                        | False    |
| <b>SSO_REALM</b>                       | <b>SSO_REALM</b>           | RH-SSO Realm name  | <b>`\${SSO_REALM}`</b>                      | False    |
| <b>BUSINESS_CENTRAL_SSO_CLIENT</b>     | <b>SSO_CLIENT</b>          | Business Central Monitoring RH-SSO Client name   | <b>`\${BUSINESS_CENTRAL_SSO_CLIENT}`</b>    | False    |
| <b>BUSINESS_CENTRAL_SSO_SECRET</b>     | <b>SSO_SECRET</b>          | Business Central Monitoring RH-SSO Client Secret   | <b>`\${BUSINESS_CENTRAL_SSO_SECRET}`</b>    | False    |
| <b>SSO_USERNAME</b>                    | <b>SSO_USERNAME</b>        | RH-SSO Realm Admin Username used to create the Client if it doesn't exist  | <b>`\${SSO_USERNAME}`</b>                   | False    |



| Variable name                                 | Image Environment Variable                    | Description  | Example value                             | Required |
|---|---|--|---|----------|
| <b>SSO_PASSWORD</b>                           | <b>SSO_PASSWORD</b>                           | RH-SSO Realm Admin Password used to create the Client                      | <b>\${SSO_PASSWORD}</b>                   | False    |
| <b>SSO_DISABLE_SSL_CERTIFICATE_VALIDATION</b> | <b>SSO_DISABLE_SSL_CERTIFICATE_VALIDATION</b> | RH-SSO Disable SSL Certificate Validation                                  | false                                     | False    |
| <b>SSO_PRINCIPAL_ATTRIBUTE</b>                | <b>SSO_PRINCIPAL_ATTRIBUTE</b>                | RH-SSO Principal Attribute to use as username.                             | preferred_username                        | False    |
| <b>AUTH_LDAP_URL</b>                          | <b>AUTH_LDAP_URL</b>                          | LDAP Endpoint to connect for authentication                                | <b>\${AUTH_LDAP_URL}</b>                  | False    |
| <b>AUTH_LDAP_BIND_DN</b>                      | <b>AUTH_LDAP_BIND_DN</b>                      | Bind DN used for authentication  | <b>\${AUTH_LDAP_BIND_DN}</b>              | False    |
| <b>AUTH_LDAP_BIND_CREDENTIAL</b>              | <b>AUTH_LDAP_BIND_CREDENTIAL</b>              | LDAP Credentials used for authentication                                   | <b>\${AUTH_LDAP_BIND_CREDENTIAL}</b>      | False    |
| <b>AUTH_LDAP_JAAS_SECURITY_DOMAIN</b>         | <b>AUTH_LDAP_JAAS_SECURITY_DOMAIN</b>         | The JMX ObjectName of the JaasSecurityDomain used to decrypt the password. | <b>\${AUTH_LDAP_JAAS_SECURITY_DOMAIN}</b> | False    |
| <b>AUTH_LDAP_BASE_CTX_DN</b>                  | <b>AUTH_LDAP_BASE_CTX_DN</b>                  | LDAP Base DN of the top-level context to begin the user search.            | <b>\${AUTH_LDAP_BASE_CTX_DN}</b>          | False    |

| Variable name                                 | Image Environment Variable                    | Description  | Example value                                       | Required |
|---|---|--|---|----------|
| <b>AUTH_LDAP_BASE_FILTER</b>                  | <b>AUTH_LDAP_BASE_FILTER</b>                  | LDAP search filter used to locate the context of the user to authenticate. The input username or userDN obtained from the login module callback is substituted into the filter anywhere a {0} expression is used. A common example for the search filter is (uid={0}).           | <b>`\${AUTH_LDAP_BASE_FILTER}`</b>                  | False    |
| <b>AUTH_LDAP_SEARCH_SCOPE</b>                 | <b>AUTH_LDAP_SEARCH_SCOPE</b>                 | The search scope to use.   | <b>`\${AUTH_LDAP_SEARCH_SCOPE}`</b>                 | False    |
| <b>AUTH_LDAP_SEARCH_TIME_LIMIT</b>            | <b>AUTH_LDAP_SEARCH_TIME_LIMIT</b>            | The timeout in milliseconds for user or role searches.   | <b>`\${AUTH_LDAP_SEARCH_TIME_LIMIT}`</b>            | False    |
| <b>AUTH_LDAP_DISTINGUISHED_NAME_ATTRIBUTE</b> | <b>AUTH_LDAP_DISTINGUISHED_NAME_ATTRIBUTE</b> | The name of the attribute in the user entry that contains the DN of the user. This may be necessary if the DN of the user itself contains special characters, backslash for example, that prevent correct user mapping. If the attribute does not exist, the entry's DN is used. | <b>`\${AUTH_LDAP_DISTINGUISHED_NAME_ATTRIBUTE}`</b> | False    |

| Variable name                          | Image Environment Variable             | Description   | Example value   | Required |
|--|--|---|---|----------|
| <b>AUTH_LDAP_PARSE_USERNAME</b>        | <b>AUTH_LDAP_PARSE_USERNAME</b>        | A flag indicating if the DN is to be parsed for the username. If set to true, the DN is parsed for the username. If set to false the DN is not parsed for the username. This option is used together with <code>usernameBeginString</code> and <code>usernameEndString</code> . | <b><code>\${AUTH_LDAP_PARSE_USERNAME}</code></b>        | False    |
| <b>AUTH_LDAP_USERNAME_BEGIN_STRING</b> | <b>AUTH_LDAP_USERNAME_BEGIN_STRING</b> | Defines the String which is to be removed from the start of the DN to reveal the username. This option is used together with <code>usernameEndString</code> and only taken into account if <code>parseUsername</code> is set to true.   | <b><code>\${AUTH_LDAP_USERNAME_BEGIN_STRING}</code></b> | False    |
| <b>AUTH_LDAP_USERNAME_END_STRING</b>   | <b>AUTH_LDAP_USERNAME_END_STRING</b>   | Defines the String which is to be removed from the end of the DN to reveal the username. This option is used together with <code>usernameEndString</code> and only taken into account if <code>parseUsername</code> is set to true.   | <b><code>\${AUTH_LDAP_USERNAME_END_STRING}</code></b>   | False    |
| <b>AUTH_LDAP_ROLE_ATTRIBUTE_ID</b>     | <b>AUTH_LDAP_ROLE_ATTRIBUTE_ID</b>     | Name of the attribute containing the user roles.  | <b><code>\${AUTH_LDAP_ROLE_ATTRIBUTE_ID}</code></b>     | False    |

| Variable name                 | Image Environment Variable    | Description   | Example value                       | Required |
|-------------------------------|-------------------------------|---|-------------------------------------|----------|
| <b>AUTH_LDAP_ROLES_CTX_DN</b> | <b>AUTH_LDAP_ROLES_CTX_DN</b> | The fixed DN of the context to search for user roles. This is not the DN where the actual roles are, but the DN where the objects containing the user roles are. For example, in a Microsoft Active Directory server, this is the DN where the user account is.   | <b>`\${AUTH_LDAP_ROLES_CTX_DN}`</b> | False    |
| <b>AUTH_LDAP_ROLE_FILTER</b>  | <b>AUTH_LDAP_ROLE_FILTER</b>  | A search filter used to locate the roles associated with the authenticated user. The input username or userDN obtained from the login module callback is substituted into the filter anywhere a <code>{0}</code> expression is used. The authenticated userDN is substituted into the filter anywhere a <code>{1}</code> is used. An example search filter that matches on the input username is <code>(member={0})</code> . An alternative that matches on the authenticated userDN is <code>(member={1})</code> . | <b>`\${AUTH_LDAP_ROLE_FILTER}`</b>  | False    |

| Variable name                            | Image Environment Variable               | Description  | Example value                                  | Required |
|--|--|--|--|----------|
| <b>AUTH_LDAP_ROLE_RECURSION</b>          | <b>AUTH_LDAP_ROLE_RECURSION</b>          | The number of levels of recursion the role search will go below a matching context. Disable recursion by setting this to 0.  | <b>`\${AUTH_LDAP_ROLE_RECURSION}`</b>          | False    |
| <b>AUTH_LDAP_DEFAULT_ROLE</b>            | <b>AUTH_LDAP_DEFAULT_ROLE</b>            | A role included for all authenticated users  | <b>`\${AUTH_LDAP_DEFAULT_ROLE}`</b>            | False    |
| <b>AUTH_LDAP_ROLE_NAME_ATTRIBUTE_ID</b>  | <b>AUTH_LDAP_ROLE_NAME_ATTRIBUTE_ID</b>  | Name of the attribute within the roleCtxDN context which contains the role name. If the roleAttributelsDN property is set to true, this property is used to find the role object's name attribute.   | <b>`\${AUTH_LDAP_ROLE_NAME_ATTRIBUTE_ID}`</b>  | False    |
| <b>AUTH_LDAP_PARSE_ROLE_NAME_FROM_DN</b> | <b>AUTH_LDAP_PARSE_ROLE_NAME_FROM_DN</b> | A flag indicating if the DN returned by a query contains the roleNameAttribute ID. If set to true, the DN is checked for the roleNameAttribute ID. If set to false, the DN is not checked for the roleNameAttribute ID. This flag can improve the performance of LDAP queries. | <b>`\${AUTH_LDAP_PARSE_ROLE_NAME_FROM_DN}`</b> | False    |

| Variable name  | Image Environment Variable                           | Description  | Example value  | Required |
|--|--|--|--|----------|
| <b>AUTH_LDAP_ROLE_ATTRIBUTE_IS_DN</b>                | <b>AUTH_LDAP_ROLE_ATTRIBUTE_IS_DN</b>                | Whether or not the roleAttributeID contains the fully-qualified DN of a role object. If false, the role name is taken from the value of the roleNameAttributeId attribute of the context name. Certain directory schemas, such as Microsoft Active Directory, require this attribute to be set to true.  | <b>`\${AUTH_LDAP_ROLE_ATTRIBUTE_IS_DN}`</b>                | False    |
| <b>AUTH_LDAP_REFERRAL_USER_ATTRIBUTE_ID_TO_CHECK</b> | <b>AUTH_LDAP_REFERRAL_USER_ATTRIBUTE_ID_TO_CHECK</b> | If you are not using referrals, this option can be ignored. When using referrals, this option denotes the attribute name which contains users defined for a certain role, for example member, if the role object is inside the referral. Users are checked against the content of this attribute name. If this option is not set, the check will always fail, so role objects cannot be stored in a referral tree. | <b>`\${AUTH_LDAP_REFERRAL_USER_ATTRIBUTE_ID_TO_CHECK}`</b> | False    |

## 4.1.2. Objects

The CLI supports various object types. A list of these object types as well as their abbreviations can be found in the [Openshift documentation](#).

### 4.1.2.1. Services

A service is an abstraction which defines a logical set of pods and a policy by which to access them. Refer to the [container-engine documentation](#) for more information.

| Service  | Port | Name  | Description   |
|--|------|-------|---|
| <b>\${APPLICATION_NAME}-rhpamcentrmon</b>      | 8080 | http  | All the Business Central Monitoring web server's ports. |
|  | 8443 | https |   |
| <b>\${APPLICATION_NAME}-rhpamcentrmon-ping</b> | 8888 | ping  | The JGroups ping port for clustering.                   |
| <b>\${APPLICATION_NAME}-smartrouter</b>        | 9000 | –     | The smart router server http port.                      |

#### 4.1.2.2. Routes

A route is a way to expose a service by giving it an externally-reachable hostname such as **www.example.com**. A defined route and the endpoints identified by its service can be consumed by a router to provide named connectivity from external clients to your applications. Each route consists of a route name, service selector, and (optionally) security configuration. Refer to the [OpenShift documentation](#) for more information.

| Service   | Security        | Hostname                                   |
|---|-----------------|--|
| <b>\${APPLICATION_NAME}-rhpamcentrmon-http</b>  | none            | <b>\${BUSINESS_CENTRAL_HOSTNAME_HTTP}</b>  |
| <b>\${APPLICATION_NAME}-rhpamcentrmon-https</b> | TLS passthrough | <b>\${BUSINESS_CENTRAL_HOSTNAME_HTTPS}</b> |
| <b>\${APPLICATION_NAME}-smartrouter-http</b>    | none            | <b>\${SMART_ROUTER_HOSTNAME_HTTP}</b>      |

#### 4.1.2.3. Deployment Configurations

A deployment in OpenShift is a replication controller based on a user defined template called a deployment configuration. Deployments are created manually or in response to triggered events. Refer to the [OpenShift documentation](#) for more information.

##### 4.1.2.3.1. Triggers

A trigger drives the creation of new deployments in response to events, both inside and outside OpenShift. Refer to the [OpenShift documentation](#) for more information.

| Deployment                                | Triggers    |
|---|-------------|
| <b>\${APPLICATION_NAME}-rhpamcentrmon</b> | ImageChange |

| Deployment   | Triggers    |
|--|-------------|
| <b><code>\${APPLICATION_NAME}-smartrouter</code></b> | ImageChange |

#### 4.1.2.3.2. Replicas

A replication controller ensures that a specified number of pod "replicas" are running at any one time. If there are too many, the replication controller kills some pods. If there are too few, it starts more. Refer to the [container-engine documentation](#) for more information.

| Deployment   | Replicas |
|--|----------|
| <b><code>\${APPLICATION_NAME}-rhpancentrmon</code></b> | 1        |
| <b><code>\${APPLICATION_NAME}-smartrouter</code></b>   | 2        |

#### 4.1.2.3.3. Pod Template

##### 4.1.2.3.3.1. Image

| Deployment   | Image  |
|--|--|
| <b><code>\${APPLICATION_NAME}-rhpancentrmon</code></b> | rhpan71-businesscentral-monitoring-openshift |
| <b><code>\${APPLICATION_NAME}-smartrouter</code></b>   | rhpan71-smartrouter-openshift                |

##### 4.1.2.3.3.2. Readiness Probe

###### **`${APPLICATION_NAME}-rhpancentrmon`**

```
/bin/bash -c curl --fail --silent -u '${KIE_ADMIN_USER}:${KIE_ADMIN_PWD}'
http://localhost:8080/kie-wb.jsp
```

##### 4.1.2.3.3.3. Liveness Probe

###### **`${APPLICATION_NAME}-rhpancentrmon`**

```
/bin/bash -c curl --fail --silent -u '${KIE_ADMIN_USER}:${KIE_ADMIN_PWD}'
http://localhost:8080/kie-wb.jsp
```

##### 4.1.2.3.3.4. Exposed Ports



| Deployments                               | Name    | Port | Protocol   |
|---|---------|------|------------|
| <b>\${APPLICATION_NAME}-rhpamcentrmon</b> | jolokia | 8778 | <b>TCP</b> |
|   | http    | 8080 | <b>TCP</b> |
|   | https   | 8443 | <b>TCP</b> |
|   | ping    | 8888 | <b>TCP</b> |
| <b>\${APPLICATION_NAME}-smartrouter</b>   | http    | 9000 | <b>TCP</b> |

#### 4.1.2.3.3.5. Image Environment Variables

| Deployment                                | Variable name                        | Description   | Example value                             |
|---|--------------------------------------|---|---|
| <b>\${APPLICATION_NAME}-rhpamcentrmon</b> | <b>KIE_ADMIN_PWD</b>                 | KIE administrator password  | <b>\${KIE_ADMIN_PWD}</b>                  |
|   | <b>KIE_ADMIN_USER</b>                | KIE administrator username  | <b>\${KIE_ADMIN_USER}</b>                 |
|   | <b>KIE_SERVER_PWD</b>                | KIE server password, used to connect to KIE servers. Generated value can be a suggestion to use for the s2i various (Sets the org.kie.server.pwd system property) | <b>\${KIE_SERVER_PWD}</b>                 |
|   | <b>KIE_SERVER_USER</b>               | KIE server username (Sets the org.kie.server.user system property)  | <b>\${KIE_SERVER_USER}</b>                |
|   | <b>MAVEN_REPOS</b>                   | –   | RHPAMCENTR,EXTERNAL                       |
|   | <b>RHPAMCENTR_MAVEN_REPO_SERVICE</b> | –   | <b>\${BUSINESS_CENTRAL_MAVEN_SERVICE}</b> |
|   | <b>RHPAMCENTR_MAVEN_REPO_PATH</b>    | –   | <b>/maven2/</b>                           |

| Deployment | Variable name                         | Description  | Example value                                |
|------------|---------------------------------------|--|--|
|            | <b>RHPAMCENTR_MAVEN_REPO_USERNAME</b> | Username to access the Maven repository, if required.                          | <b>`\${BUSINESS_CENTRAL_MAVEN_USERNAME}`</b> |
|            | <b>RHPAMCENTR_MAVEN_REPO_PASSWORD</b> | Password to access the Maven repository, if required.                          | <b>`\${BUSINESS_CENTRAL_MAVEN_PASSWORD}`</b> |
|            | <b>EXTERNAL_MAVEN_REPO_ID</b>         | The id to use for the maven repository, if set. Default is generated randomly. | <b>`\${MAVEN_REPO_ID}`</b>                   |
|            | <b>EXTERNAL_MAVEN_REPO_URL</b>        | Fully qualified URL to a Maven repository or service.                          | <b>`\${MAVEN_REPO_URL}`</b>                  |
|            | <b>EXTERNAL_MAVEN_REPO_USERNAME</b>   | Username to access the Maven repository, if required.                          | <b>`\${MAVEN_REPO_USERNAME}`</b>             |
|            | <b>EXTERNAL_MAVEN_REPO_PASSWORD</b>   | Password to access the Maven repository, if required.                          | <b>`\${MAVEN_REPO_PASSWORD}`</b>             |
|            | <b>KIE_SERVER_CONTROLLER_USER</b>     | –  | <b>`\${KIE_SERVER_MONITOR_USER}`</b>         |
|            | <b>KIE_SERVER_CONTROLLER_PWD</b>      | –  | <b>`\${KIE_SERVER_MONITOR_PWD}`</b>          |
|            | <b>KIE_SERVER_CONTROLLER_TOKEN</b>    | –  | <b>`\${KIE_SERVER_MONITOR_TOKEN}`</b>        |
|            | <b>HTTPS_KEYSTORE_DIR</b>             | –  | <b>/etc/businesscentral-secret-volume</b>    |
|            | <b>HTTPS_KEYSTORE</b>                 | The name of the keystore file within the secret                                | <b>`\${BUSINESS_CENTRAL_HTTPS_KEYSTORE}`</b> |
|            | <b>HTTPS_NAME</b>                     | The name associated with the server certificate                                | <b>`\${BUSINESS_CENTRAL_HTTPS_NAME}`</b>     |
|            | <b>HTTPS_PASSWORD</b>                 | The password for the keystore and certificate                                  | <b>`\${BUSINESS_CENTRAL_HTTPS_PASSWORD}`</b> |

| Deployment | Variable name                                 | Description   | Example value                                     |
|------------|---|---|---|
|            | <b>JGROUPS_PING_PROTOCOL</b>                  | –   | openshift.DNS_PING                                |
|            | <b>OPENSIFT_DNS_PING_SERVICE_NAME</b>         | –   | <b>\${APPLICATION_NAME}-rhpmcentrmon-ping</b>     |
|            | <b>OPENSIFT_DNS_PING_SERVICE_PORT</b>         | –   | 8888  |
|            | <b>SSO_URL</b>                                | RH-SSO URL  | <b>\${SSO_URL}</b>                                |
|            | <b>SSO_OPENIDCONNECT_DEPLOYMENTS</b>          | –   | ROOT.war  |
|            | <b>SSO_REALM</b>                              | RH-SSO Realm name   | <b>\${SSO_REALM}</b>                              |
|            | <b>SSO_SECRET</b>                             | Business Central Monitoring RH-SSO Client Secret                          | <b>\${BUSINESS_CENTRAL_SSO_SECRET}</b>            |
|            | <b>SSO_CLIENT</b>                             | Business Central Monitoring RH-SSO Client name                            | <b>\${BUSINESS_CENTRAL_SSO_CLIENT}</b>            |
|            | <b>SSO_USERNAME</b>                           | RH-SSO Realm Admin Username used to create the Client if it doesn't exist | <b>\${SSO_USERNAME}</b>                           |
|            | <b>SSO_PASSWORD</b>                           | RH-SSO Realm Admin Password used to create the Client                     | <b>\${SSO_PASSWORD}</b>                           |
|            | <b>SSO_DISABLE_SSL_CERTIFICATE_VALIDATION</b> | RH-SSO Disable SSL Certificate Validation                                 | <b>\${SSO_DISABLE_SSL_CERTIFICATE_VALIDATION}</b> |
|            | <b>SSO_PRINCIPAL_ATTRIBUTE</b>                | RH-SSO Principal Attribute to use as username.                            | <b>\${SSO_PRINCIPAL_ATTRIBUTE}</b>                |

| Deployment | Variable name                         | Description  | Example value                                |
|------------|---------------------------------------|--|--|
|            | <b>HOSTNAME_HTTP</b>                  | Custom hostname for http service route.<br>Leave blank for default hostname, e.g. <application-name>-smartrouter-<project>.<default-domain-suffix>   | <b>`\${BUSINESS_CENTRAL_HOSTNAME_HTTP}`</b>  |
|            | <b>HOSTNAME_HTTPS</b>                 | Custom hostname for https service route.<br>Leave blank for default hostname, e.g.: secure-<application-name>-rhpamcentrmon-<project>.<default-domain-suffix>  | <b>`\${BUSINESS_CENTRAL_HOSTNAME_HTTPS}`</b> |
|            | <b>AUTH_LDAP_URL</b>                  | LDAP Endpoint to connect for authentication  | <b>`\${AUTH_LDAP_URL}`</b>                   |
|            | <b>AUTH_LDAP_BIND_DN</b>              | Bind DN used for authentication  | <b>`\${AUTH_LDAP_BIND_DN}`</b>               |
|            | <b>AUTH_LDAP_BIND_CREDENTIAL</b>      | LDAP Credentials used for authentication   | <b>`\${AUTH_LDAP_BIND_CREDENTIAL}`</b>       |
|            | <b>AUTH_LDAP_JAAS_SECURITY_DOMAIN</b> | The JMX ObjectName of the JaasSecurityDomain used to decrypt the password.   | <b>`\${AUTH_LDAP_JAAS_SECURITY_DOMAIN}`</b>  |
|            | <b>AUTH_LDAP_BASE_CTX_DN</b>          | LDAP Base DN of the top-level context to begin the user search.  | <b>`\${AUTH_LDAP_BASE_CTX_DN}`</b>           |
|            | <b>AUTH_LDAP_BASE_FILTER</b>          | LDAP search filter used to locate the context of the user to authenticate. The input username or userDN obtained from the login module callback is substituted into the filter anywhere a {0} expression is used. A common example for the search filter is (uid={0}). | <b>`\${AUTH_LDAP_BASE_FILTER}`</b>           |

| Deployment | Variable name                                 | Description  | Example value                                       |
|------------|---|--|---|
|            | <b>AUTH_LDAP_SEARCH_SCOPE</b>                 | The search scope to use.   | <b>`\${AUTH_LDAP_SEARCH_SCOPE}`</b>                 |
|            | <b>AUTH_LDAP_SEARCH_TIME_LIMIT</b>            | The timeout in milliseconds for user or role searches.   | <b>`\${AUTH_LDAP_SEARCH_TIME_LIMIT}`</b>            |
|            | <b>AUTH_LDAP_DISTINGUISHED_NAME_ATTRIBUTE</b> | The name of the attribute in the user entry that contains the DN of the user. This may be necessary if the DN of the user itself contains special characters, backslash for example, that prevent correct user mapping. If the attribute does not exist, the entry's DN is used. | <b>`\${AUTH_LDAP_DISTINGUISHED_NAME_ATTRIBUTE}`</b> |
|            | <b>AUTH_LDAP_PARSE_USERNAME</b>               | A flag indicating if the DN is to be parsed for the username. If set to true, the DN is parsed for the username. If set to false the DN is not parsed for the username. This option is used together with <code>usernameBeginString</code> and <code>usernameEndString</code> .  | <b>`\${AUTH_LDAP_PARSE_USERNAME}`</b>               |
|            | <b>AUTH_LDAP_USERNAME_BEGIN_STRING</b>        | Defines the String which is to be removed from the start of the DN to reveal the username. This option is used together with <code>usernameEndString</code> and only taken into account if <code>parseUsername</code> is set to true.  | <b>`\${AUTH_LDAP_USERNAME_BEGIN_STRING}`</b>        |

| Deployment | Variable name                         | Description   | Example value   |
|------------|---------------------------------------|---|---|
|            | <b>AUTH_LDAP_USER_NAME_END_STRING</b> | Defines the String which is to be removed from the end of the DN to reveal the username. This option is used together with <code>usernameEndString</code> and only taken into account if <code>parseUsername</code> is set to true.   | <b><code>\${AUTH_LDAP_USERNAME_END_STRING}</code></b> |
|            | <b>AUTH_LDAP_ROLE_ATTRIBUTE_ID</b>    | Name of the attribute containing the user roles.  | <b><code>\${AUTH_LDAP_ROLE_ATTRIBUTE_ID}</code></b>   |
|            | <b>AUTH_LDAP_ROLE_S_CTX_DN</b>        | The fixed DN of the context to search for user roles. This is not the DN where the actual roles are, but the DN where the objects containing the user roles are. For example, in a Microsoft Active Directory server, this is the DN where the user account is.   | <b><code>\${AUTH_LDAP_ROLE_S_CTX_DN}</code></b>       |
|            | <b>AUTH_LDAP_ROLE_FILTER</b>          | A search filter used to locate the roles associated with the authenticated user. The input username or userDN obtained from the login module callback is substituted into the filter anywhere a <code>{0}</code> expression is used. The authenticated userDN is substituted into the filter anywhere a <code>{1}</code> is used. An example search filter that matches on the input username is <code>(member={0})</code> . An alternative that matches on the authenticated userDN is <code>(member={1})</code> . | <b><code>\${AUTH_LDAP_ROLE_FILTER}</code></b>         |

| Deployment | Variable name                            | Description   | Example value                                  |
|------------|--|---|--|
|            | <b>AUTH_LDAP_ROLE_RECURSION</b>          | The number of levels of recursion the role search will go below a matching context. Disable recursion by setting this to 0.   | <b>`\${AUTH_LDAP_ROLE_RECURSION}`</b>          |
|            | <b>AUTH_LDAP_DEFAULT_ROLE</b>            | A role included for all authenticated users   | <b>`\${AUTH_LDAP_DEFAULT_ROLE}`</b>            |
|            | <b>AUTH_LDAP_ROLE_NAME_ATTRIBUTE_ID</b>  | Name of the attribute within the roleCtxDN context which contains the role name. If the roleAttributesDN property is set to true, this property is used to find the role object's name attribute.   | <b>`\${AUTH_LDAP_ROLE_NAME_ATTRIBUTE_ID}`</b>  |
|            | <b>AUTH_LDAP_PARSE_ROLE_NAME_FROM_DN</b> | A flag indicating if the DN returned by a query contains the roleNameAttributeID. If set to true, the DN is checked for the roleNameAttributeID. If set to false, the DN is not checked for the roleNameAttributeID. This flag can improve the performance of LDAP queries.                             | <b>`\${AUTH_LDAP_PARSE_ROLE_NAME_FROM_DN}`</b> |
|            | <b>AUTH_LDAP_ROLE_ATTRIBUTE_IS_DN</b>    | Whether or not the roleAttributeID contains the fully-qualified DN of a role object. If false, the role name is taken from the value of the roleNameAttributeID attribute of the context name. Certain directory schemas, such as Microsoft Active Directory, require this attribute to be set to true. | <b>`\${AUTH_LDAP_ROLE_ATTRIBUTE_IS_DN}`</b>    |

| Deployment                              | Variable name  | Description  | Example value  |
|---|--|--|--|
|   | <b>AUTH_LDAP_REFERRAL_USER_ATTRIBUTE_ID_TO_CHECK</b> | If you are not using referrals, this option can be ignored. When using referrals, this option denotes the attribute name which contains users defined for a certain role, for example member, if the role object is inside the referral. Users are checked against the content of this attribute name. If this option is not set, the check will always fail, so role objects cannot be stored in a referral tree. | <b>\${AUTH_LDAP_REFERRAL_USER_ATTRIBUTE_ID_TO_CHECK}</b> |
| <b>\${APPLICATION_NAME}-smartrouter</b> | <b>KIE_SERVER_ROUTER_HOST</b>                        | –  | –  |
|   | <b>KIE_SERVER_ROUTER_PORT</b>                        | –  | 9000   |
|   | <b>KIE_SERVER_ROUTER_URL_EXTERNAL</b>                | Public URL where the router can be found. Format <a href="http://&lt;host&gt;:&lt;port&gt;">http://&lt;host&gt;:&lt;port&gt;</a> (router property org.kie.server.router.url.external)  | <b>\${KIE_SERVER_ROUTER_URL_EXTERNAL}</b>                |
|   | <b>KIE_SERVER_ROUTER_ID</b>                          | Router ID used when connecting to the controller (router property org.kie.server.router.id)  | <b>\${KIE_SERVER_ROUTER_ID}</b>                          |
|   | <b>KIE_SERVER_ROUTER_NAME</b>                        | Router name used when connecting to the controller (router property org.kie.server.router.name)  | <b>\${KIE_SERVER_ROUTER_NAME}</b>                        |
|   | <b>KIE_SERVER_ROUTER_PROTOCOL</b>                    | KIE server router protocol (Used to build the org.kie.server.router.url.external property)   | <b>\${KIE_SERVER_ROUTER_PROTOCOL}</b>                    |



| Deployment | Variable name                            | Description | Example value                      |
|------------|--|-------------|------------------------------------|
|            | KIE_SERVER_CONTROLLER_USER               | –           | \${KIE_SERVER_MONITOR_USER}        |
|            | KIE_SERVER_CONTROLLER_PWD                | –           | \${KIE_SERVER_MONITOR_PWD}         |
|            | KIE_SERVER_CONTROLLER_TOKEN              | –           | \${KIE_SERVER_MONITOR_TOKEN}       |
|            | KIE_SERVER_CONTROLLER_SERVICE            | –           | \${APPLICATION_NAME}-rhpamcentrmon |
|            | KIE_SERVER_CONTROLLER_PROTOCOL           | –           | ws                                 |
|            | KIE_SERVER_ROUTER_REPO                   | –           | /opt/rhpam-smartrouter/data        |
|            | KIE_SERVER_ROUTER_CONFIG_WATCHER_ENABLED | –           | true                               |

#### 4.1.2.3.3.6. Volumes

| Deployment                         | Name                             | mountPath                          | Purpose   | readOnly |
|------------------------------------|----------------------------------|------------------------------------|-----------|----------|
| \${APPLICATION_NAME}-rhpamcentrmon | businesscentral-keystore-volume  | /etc/businesscentral-secret-volume | ssl certs | True     |
| \${APPLICATION_NAME}-smartrouter   | \${APPLICATION_NAME}-smartrouter | /opt/rhpam-smartrouter/data        | –         | false    |

#### 4.1.2.4. External Dependencies

##### 4.1.2.4.1. Volume Claims

A **PersistentVolume** object is a storage resource in an OpenShift cluster. Storage is provisioned by an administrator by creating **PersistentVolume** objects from sources such as GCE Persistent Disks, AWS Elastic Block Stores (EBS), and NFS mounts. Refer to the [OpenShift documentation](#) for more information.

| Name  | Access Mode   |
|---|---------------|
| <b>\${APPLICATION_NAME}-smartrouter-claim</b> | ReadWriteMany |
| <b>\${APPLICATION_NAME}-rhpamcentr-claim</b>  | ReadWriteMany |

## 4.2. RHPAM71-PROD-IMMUTABLE-KIESERVER

Application template for an immutable KIE server in a production environment, for Red Hat Process Automation Manager 7.1

### 4.2.1. Parameters

Templates allow you to define parameters which take on a value. That value is then substituted wherever the parameter is referenced. References can be defined in any text field in the objects list field. Refer to the [Openshift documentation](#) for more information.

| Variable name              | Image Environment Variable | Description   | Example value                  | Required |
|----------------------------|----------------------------|---|--------------------------------|----------|
| <b>APPLICATION_NAME</b>    | –                          | The name for the application.   | myapp                          | True     |
| <b>KIE_ADMIN_USERNAME</b>  | <b>KIE_ADMIN_USERNAME</b>  | KIE administrator username  | adminUser                      | False    |
| <b>KIE_ADMIN_PASSWORD</b>  | <b>KIE_ADMIN_PASSWORD</b>  | KIE administrator password  | <b>\${KIE_ADMIN_PASSWORD}</b>  | False    |
| <b>KIE_SERVER_USERNAME</b> | <b>KIE_SERVER_USERNAME</b> | KIE server username (Sets the org.kie.server.user system property)  | executionUser                  | False    |
| <b>KIE_SERVER_PASSWORD</b> | <b>KIE_SERVER_PASSWORD</b> | KIE server password, used to connect to KIE servers. Generated value can be a suggestion to use for the s2i various (Sets the org.kie.server.pwd system property) | <b>\${KIE_SERVER_PASSWORD}</b> | False    |

| Variable name                       | Image Environment Variable | Description   | Example value               | Required |
|-------------------------------------|----------------------------|---|-----------------------------|----------|
| <b>IMAGE_STREAM_NAMESPACE</b>       | –                          | Namespace in which the ImageStreams for Red Hat Middleware images are installed. These ImageStreams are normally installed in the openshift namespace. You should only need to modify this if you've installed the ImageStreams in a different namespace/project. | openshift                   | True     |
| <b>KIE_SERVER_IMAGE_STREAM_NAME</b> | –                          | The name of the image stream to use for KIE server. Default is "rhpam71-kieserver-openshift".   | rhpam71-kieserver-openshift | True     |
| <b>IMAGE_STREAM_TAG</b>             | –                          | A named pointer to an image in an image stream. Default is "1.1".   | 1.1                         | True     |
| <b>KIE_SERVER_MONITOR_USER</b>      | –                          | KIE server monitor username, for optional use of the business-central-monitor (Sets the org.kie.server.controller.user system property)   | monitorUser                 | False    |
| <b>KIE_SERVER_MONITOR_PWD</b>       | –                          | KIE server monitor password, for optional use of the business-central-monitor (Sets the org.kie.server.controller.pwd system property)  | –                           | False    |

| Variable name                     | Image Environment Variable       | Description   | Example value                          | Required |
|-----------------------------------|----------------------------------|---|--|----------|
| <b>KIE_SERVER_MONITOR_TOKEN</b>   | –                                | KIE server monitor token for bearer authentication (Sets the org.kie.server.controller.token.system property)   | –                                      | False    |
| <b>KIE_SERVER_MONITOR_SERVICE</b> | –                                | The service name for the optional business central monitor, where it can be reached to allow service lookup, and registered with to allow monitoring console functionality (If set, will be used to discover host and port) | –                                      | False    |
| <b>KIE_SERVER_ROUTER_SERVICE</b>  | <b>KIE_SERVER_ROUTER_SERVICE</b> | The service name for the optional smart router, where it can be reached, to allow smart routing   | <b>`\${KIE_SERVER_ROUTER_SERVICE}`</b> | False    |
| <b>KIE_SERVER_ROUTER_HOST</b>     | <b>KIE_SERVER_ROUTER_HOST</b>    | The host name of the smart router, which could be the service name resolved by OpenShift or a globally resolvable domain name   | <b>`\${KIE_SERVER_ROUTER_HOST}`</b>    | False    |

| Variable name                            | Image Environment Variable        | Description  | Example value                                      | Required |
|--|-----------------------------------|--|--|----------|
| <b>KIE_SERVER_ROUTER_PORT</b>            | <b>KIE_SERVER_ROUTER_PORT</b>     | Port in which the smart router server listens (router property org.kie.server.router.port)   | <b><code>\${KIE_SERVER_ROUTER_PORT}</code></b>     | False    |
| <b>KIE_SERVER_ROUTER_PROTOCOL</b>        | <b>KIE_SERVER_ROUTER_PROTOCOL</b> | KIE server router protocol (Used to build the org.kie.server.router.url.external property)   | <b><code>\${KIE_SERVER_ROUTER_PROTOCOL}</code></b> | False    |
| <b>KIE_SERVER_PERSISTENCE_DS</b>         | <b>KIE_SERVER_PERSISTENCE_DS</b>  | KIE server persistence datasource (Sets the org.kie.server.persistence.ds system property)   | java:/jboss/datasources/rhpam                      | False    |
| <b>POSTGRESQL_IMAGE_STREAM_NAMESPACE</b> | –                                 | Namespace in which the ImageStream for the PostgreSQL image is installed. The ImageStream is already installed in the openshift namespace. You should only need to modify this if you've installed the ImageStream in a different namespace/project. Default is "openshift". | openshift  | False    |

| Variable name                               | Image Environment Variable                  | Description  | Example value | Required |
|---|---|--|---------------|----------|
| <b>POSTGRESQL_IMAGE_STREAM_TAG</b>          | –   | The PostgreSQL image version, which is intended to correspond to the PostgreSQL version. Default is "9.6". | 9.6           | False    |
| <b>KIE_SERVER_POSTGRESQL_USER</b>           | <b>POSTGRESQL_USER</b>                      | KIE server PostgreSQL database username  | rhpan         | False    |
| <b>KIE_SERVER_POSTGRESQL_PASSWORD</b>       | –   | KIE server PostgreSQL database password  | –             | False    |
| <b>KIE_SERVER_POSTGRESQL_DATABASE</b>       | –   | KIE server PostgreSQL database name  | rhpan7        | False    |
| <b>POSTGRESQL_MAX_PREPARED_TRANSACTIONS</b> | <b>POSTGRESQL_MAX_PREPARED_TRANSACTIONS</b> | Allows the PostgreSQL to handle XA transactions.   | 100           | True     |
| <b>DB_VOLUME_CAPACITY</b>                   | –   | Size of persistent storage for database volume.  | 1Gi           | True     |
| <b>DROOLS_SERVER_FILTER_CLASSES</b>         | <b>DROOLS_SERVER_FILTER_CLASSES</b>         | KIE server class filtering (Sets the org.drools.server.filter.classes.system property)                     | true          | False    |
| <b>KIE_MBEANS</b>                           | <b>KIE_MBEANS</b>                           | KIE server mbeans enabled/disabled (Sets the kie.mbeans and kie.scanner.mbeans system properties)          | enabled       | False    |

| Variable name                           | Image Environment Variable              | Description  | Example value                          | Required |
|---|---|--|--|----------|
| <b>KIE_SERVER_HOSTNAME_HTTP</b>         | <b>KIE_SERVER_HOST</b>                  | Custom hostname for http service route, if set will also configure the KIE_SERVER_HOST. Leave blank for default hostname, e.g.: <application-name>-kieserver-<project>.<default-domain-suffix> | <b>`\${KIE_SERVER_HOSTNAME_HTTP}`</b>  | False    |
| <b>KIE_SERVER_HOSTNAME_HTTPS</b>        | <b>KIE_SERVER_HOST</b>                  | Custom hostname for https service route. Leave blank for default hostname, e.g.: secure-<application-name>-kieserver-<project>.<default-domain-suffix>   | <b>`\${KIE_SERVER_HOSTNAME_HTTPS}`</b> | False    |
| <b>KIE_SERVER_USE_SECURE_ROUTE_NAME</b> | <b>KIE_SERVER_USE_SECURE_ROUTE_NAME</b> | Use https for the KIE_SERVER_HOST when it is not explicit configured to a custom value.  | false                                  | False    |
| <b>KIE_SERVER_HTTPS_SECRET</b>          | –                                       | The name of the secret containing the keystore file  | –                                      | True     |
| <b>KIE_SERVER_HTTPS_KEYSTORE</b>        | <b>HTTPS_KEYSTORE</b>                   | The name of the keystore file within the secret  | keystore.jks                           | False    |
| <b>KIE_SERVER_HTTPS_NAME</b>            | <b>HTTPS_NAME</b>                       | The name associated with the server certificate  | jboss                                  | False    |
| <b>KIE_SERVER_HTTPS_PASSWORD</b>        | <b>HTTPS_PASSWORD</b>                   | The password for the keystore and certificate  | mykeystorepass                         | False    |

| Variable name                          | Image Environment Variable             | Description  | Example value                              | Required |
|--|--|--|--|----------|
| <b>KIE_SERVER_BYPASS_AUTH_USER</b>     | <b>KIE_SERVER_BYPASS_AUTH_USER</b>     | KIE server bypass auth user (Sets the org.kie.server.bypass.auth.user system property)                         | false                                      | False    |
| <b>KIE_SERVER_CONTAINER_DEPLOYMENT</b> | <b>KIE_SERVER_CONTAINER_DEPLOYMENT</b> | KIE Server Container deployment configuration in format:<br>containerId=groupId:artifactId:version c2=g2:a2:v2 | <b>\${KIE_SERVER_CONTAINER_DEPLOYMENT}</b> | True     |
| <b>SOURCE_REPOSITORY_URL</b>           | –                                      | Git source URI for application   | –  | True     |
| <b>SOURCE_REPOSITORY_REF</b>           | –                                      | Git branch/tag reference   | –  | False    |
| <b>CONTEXT_DIR</b>                     | –                                      | Path within Git project to build; empty for root project directory.  | –  | False    |
| <b>GITHUB_WEBHOOK_SECRET</b>           | –                                      | GitHub trigger secret  | –  | True     |
| <b>GENERIC_WEBHOOK_SECRET</b>          | –                                      | Generic build trigger secret   | –  | True     |
| <b>MAVEN_MIRROR_URL</b>                | –                                      | Maven mirror to use for S2I builds   | –  | False    |
| <b>MAVEN_REPO_ID</b>                   | <b>EXTERNAL_MAVEN_REPO_ID</b>          | The id to use for the maven repository, if set. Default is generated randomly.                                 | <b>\${MAVEN_REPO_ID}</b>                   | False    |
| <b>MAVEN_REPO_URL</b>                  | <b>EXTERNAL_MAVEN_REPO_URL</b>         | Fully qualified URL to a Maven repository.   | <b>\${MAVEN_REPO_URL}</b>                  | False    |



| Variable name                                    | Image Environment Variable              | Description  | Example value                                     | Required |
|--|---|--|---|----------|
| <b>MAVEN_REPO_USERNAME</b>                       | <b>RHPAMCENTRAL_MAVEN_REPO_USERNAME</b> | Username to access the Maven repository, if required.  | <b>`\${BUSINESS_CENTRAL_MAVEN_REPO_USERNAME}`</b> | False    |
| <b>MAVEN_REPO_PASSWORD</b>                       | <b>RHPAMCENTRAL_MAVEN_REPO_PASSWORD</b> | Password to access the Maven repository, if required.  | <b>`\${BUSINESS_CENTRAL_MAVEN_REPO_PASSWORD}`</b> | False    |
| <b>BUSINESS_CENTRAL_MAVEN_SERVICE</b>            | –                                       | The service name for the optional business central, where it can be reached, to allow service lookups (for maven repo usage), if required  | –   | False    |
| <b>BUSINESS_CENTRAL_MAVEN_USERNAME</b>           | –                                       | Username to access the Maven service hosted by Business Central inside EAP.  | –   | False    |
| <b>BUSINESS_CENTRAL_MAVEN_PASSWORD</b>           | –                                       | Password to access the Maven service hosted by Business Central inside EAP.  | –   | False    |
| <b>ARTIFACT_DIR</b>                              | –                                       | List of directories from which archives will be copied into the deployment folder. If unspecified, all archives in /target will be copied. | –   | False    |
| <b>TIMER_SERVICE_DATA_STORE_REFRESH_INTERVAL</b> | <b>TIMER_SERVICE_DATA_STORE</b>         | Sets refresh-interval for the EJB timer service database-data-store.   | 30000   | False    |

| Variable name                      | Image Environment Variable         | Description  | Example value                    | Required |
|------------------------------------|------------------------------------|--|----------------------------------|----------|
| <b>KIE_SERVER_MEMORY_LIMIT</b>     | –                                  | KIE server Container memory limit  | 1Gi                              | False    |
| <b>KIE_SERVER_MGMT_DISABLED</b>    | <b>KIE_SERVER_MGMT_DISABLED</b>    | Disable management api and don't allow KIE containers to be deployed/undeployed or started/stopped sets the property org.kie.server.management.api.disabled to true and org.kie.server.startup.strategy to LocalContainersStartupStrategy. | true                             | True     |
| <b>KIE_SERVER_STARTUP_STRATEGY</b> | <b>KIE_SERVER_STARTUP_STRATEGY</b> | When set to LocalContainersStartupStrategy, allows KIE server to start up and function with local config, even when a controller is configured and unavailable.  | LocalContainersStartupStrategy   | True     |
| <b>SSO_URL</b>                     | <b>SSO_URL</b>                     | RH-SSO URL   | <b>\${SSO_URL}</b>               | False    |
| <b>SSO_REALM</b>                   | <b>SSO_REALM</b>                   | RH-SSO Realm name  | <b>\${SSO_REALM}</b>             | False    |
| <b>KIE_SERVER_SSO_CLIENT</b>       | <b>SSO_CLIENT</b>                  | KIE Server RH-SSO Client name  | <b>\${KIE_SERVER_SSO_CLIENT}</b> | False    |
| <b>KIE_SERVER_SSO_SECRET</b>       | <b>SSO_SECRET</b>                  | KIE Server RH-SSO Client Secret  | <b>\${KIE_SERVER_SSO_SECRET}</b> | False    |
| <b>SSO_USERNAME</b>                | <b>SSO_USERNAME</b>                | RH-SSO Realm Admin Username used to create the Client if it doesn't exist  | <b>\${SSO_USERNAME}</b>          | False    |

| Variable name                                 | Image Environment Variable                    | Description  | Example value                             | Required |
|---|---|--|---|----------|
| <b>SSO_PASSWORD</b>                           | <b>SSO_PASSWORD</b>                           | RH-SSO Realm Admin Password used to create the Client                      | <b>\${SSO_PASSWORD}</b>                   | False    |
| <b>SSO_DISABLE_SSL_CERTIFICATE_VALIDATION</b> | <b>SSO_DISABLE_SSL_CERTIFICATE_VALIDATION</b> | RH-SSO Disable SSL Certificate Validation                                  | false                                     | False    |
| <b>SSO_PRINCIPAL_ATTRIBUTE</b>                | <b>SSO_PRINCIPAL_ATTRIBUTE</b>                | RH-SSO Principal Attribute to use as username.                             | preferred_username                        | False    |
| <b>AUTH_LDAP_URL</b>                          | <b>AUTH_LDAP_URL</b>                          | LDAP Endpoint to connect for authentication                                | <b>\${AUTH_LDAP_URL}</b>                  | False    |
| <b>AUTH_LDAP_BIND_DN</b>                      | <b>AUTH_LDAP_BIND_DN</b>                      | Bind DN used for authentication  | <b>\${AUTH_LDAP_BIND_DN}</b>              | False    |
| <b>AUTH_LDAP_BIND_CREDENTIAL</b>              | <b>AUTH_LDAP_BIND_CREDENTIAL</b>              | LDAP Credentials used for authentication                                   | <b>\${AUTH_LDAP_BIND_CREDENTIAL}</b>      | False    |
| <b>AUTH_LDAP_JAAS_SECURITY_DOMAIN</b>         | <b>AUTH_LDAP_JAAS_SECURITY_DOMAIN</b>         | The JMX ObjectName of the JaasSecurityDomain used to decrypt the password. | <b>\${AUTH_LDAP_JAAS_SECURITY_DOMAIN}</b> | False    |
| <b>AUTH_LDAP_BASE_CTX_DN</b>                  | <b>AUTH_LDAP_BASE_CTX_DN</b>                  | LDAP Base DN of the top-level context to begin the user search.            | <b>\${AUTH_LDAP_BASE_CTX_DN}</b>          | False    |

| Variable name                                 | Image Environment Variable                    | Description  | Example value                                       | Required |
|---|---|--|---|----------|
| <b>AUTH_LDAP_BASE_FILTER</b>                  | <b>AUTH_LDAP_BASE_FILTER</b>                  | LDAP search filter used to locate the context of the user to authenticate. The input username or userDN obtained from the login module callback is substituted into the filter anywhere a {0} expression is used. A common example for the search filter is (uid={0}).           | <b>`\${AUTH_LDAP_BASE_FILTER}`</b>                  | False    |
| <b>AUTH_LDAP_SEARCH_SCOPE</b>                 | <b>AUTH_LDAP_SEARCH_SCOPE</b>                 | The search scope to use.   | <b>`\${AUTH_LDAP_SEARCH_SCOPE}`</b>                 | False    |
| <b>AUTH_LDAP_SEARCH_TIME_LIMIT</b>            | <b>AUTH_LDAP_SEARCH_TIME_LIMIT</b>            | The timeout in milliseconds for user or role searches.   | <b>`\${AUTH_LDAP_SEARCH_TIME_LIMIT}`</b>            | False    |
| <b>AUTH_LDAP_DISTINGUISHED_NAME_ATTRIBUTE</b> | <b>AUTH_LDAP_DISTINGUISHED_NAME_ATTRIBUTE</b> | The name of the attribute in the user entry that contains the DN of the user. This may be necessary if the DN of the user itself contains special characters, backslash for example, that prevent correct user mapping. If the attribute does not exist, the entry's DN is used. | <b>`\${AUTH_LDAP_DISTINGUISHED_NAME_ATTRIBUTE}`</b> | False    |

| Variable name                          | Image Environment Variable             | Description   | Example value   | Required |
|--|--|---|---|----------|
| <b>AUTH_LDAP_PARSE_USERNAME</b>        | <b>AUTH_LDAP_PARSE_USERNAME</b>        | A flag indicating if the DN is to be parsed for the username. If set to true, the DN is parsed for the username. If set to false the DN is not parsed for the username. This option is used together with <code>usernameBeginString</code> and <code>usernameEndString</code> . | <b><code>\${AUTH_LDAP_PARSE_USERNAME}</code></b>        | False    |
| <b>AUTH_LDAP_USERNAME_BEGIN_STRING</b> | <b>AUTH_LDAP_USERNAME_BEGIN_STRING</b> | Defines the String which is to be removed from the start of the DN to reveal the username. This option is used together with <code>usernameEndString</code> and only taken into account if <code>parseUsername</code> is set to true.   | <b><code>\${AUTH_LDAP_USERNAME_BEGIN_STRING}</code></b> | False    |
| <b>AUTH_LDAP_USERNAME_END_STRING</b>   | <b>AUTH_LDAP_USERNAME_END_STRING</b>   | Defines the String which is to be removed from the end of the DN to reveal the username. This option is used together with <code>usernameEndString</code> and only taken into account if <code>parseUsername</code> is set to true.   | <b><code>\${AUTH_LDAP_USERNAME_END_STRING}</code></b>   | False    |
| <b>AUTH_LDAP_ROLE_ATTRIBUTE_ID</b>     | <b>AUTH_LDAP_ROLE_ATTRIBUTE_ID</b>     | Name of the attribute containing the user roles.  | <b><code>\${AUTH_LDAP_ROLE_ATTRIBUTE_ID}</code></b>     | False    |

| Variable name                 | Image Environment Variable    | Description   | Example value                       | Required |
|-------------------------------|-------------------------------|---|-------------------------------------|----------|
| <b>AUTH_LDAP_ROLES_CTX_DN</b> | <b>AUTH_LDAP_ROLES_CTX_DN</b> | The fixed DN of the context to search for user roles. This is not the DN where the actual roles are, but the DN where the objects containing the user roles are. For example, in a Microsoft Active Directory server, this is the DN where the user account is.   | <b>`\${AUTH_LDAP_ROLES_CTX_DN}`</b> | False    |
| <b>AUTH_LDAP_ROLE_FILTER</b>  | <b>AUTH_LDAP_ROLE_FILTER</b>  | A search filter used to locate the roles associated with the authenticated user. The input username or userDN obtained from the login module callback is substituted into the filter anywhere a <code>{0}</code> expression is used. The authenticated userDN is substituted into the filter anywhere a <code>{1}</code> is used. An example search filter that matches on the input username is <code>(member={0})</code> . An alternative that matches on the authenticated userDN is <code>(member={1})</code> . | <b>`\${AUTH_LDAP_ROLE_FILTER}`</b>  | False    |

| Variable name                            | Image Environment Variable               | Description  | Example value                                  | Required |
|--|--|--|--|----------|
| <b>AUTH_LDAP_ROLE_RECURSION</b>          | <b>AUTH_LDAP_ROLE_RECURSION</b>          | The number of levels of recursion the role search will go below a matching context. Disable recursion by setting this to 0.  | <b>`\${AUTH_LDAP_ROLE_RECURSION}`</b>          | False    |
| <b>AUTH_LDAP_DEFAULT_ROLE</b>            | <b>AUTH_LDAP_DEFAULT_ROLE</b>            | A role included for all authenticated users  | <b>`\${AUTH_LDAP_DEFAULT_ROLE}`</b>            | False    |
| <b>AUTH_LDAP_ROLE_NAME_ATTRIBUTE_ID</b>  | <b>AUTH_LDAP_ROLE_NAME_ATTRIBUTE_ID</b>  | Name of the attribute within the roleCtxDN context which contains the role name. If the roleAttributesDN property is set to true, this property is used to find the role object's name attribute.  | <b>`\${AUTH_LDAP_ROLE_NAME_ATTRIBUTE_ID}`</b>  | False    |
| <b>AUTH_LDAP_PARSE_ROLE_NAME_FROM_DN</b> | <b>AUTH_LDAP_PARSE_ROLE_NAME_FROM_DN</b> | A flag indicating if the DN returned by a query contains the roleNameAttribute ID. If set to true, the DN is checked for the roleNameAttribute ID. If set to false, the DN is not checked for the roleNameAttribute ID. This flag can improve the performance of LDAP queries. | <b>`\${AUTH_LDAP_PARSE_ROLE_NAME_FROM_DN}`</b> | False    |

| Variable name  | Image Environment Variable                           | Description  | Example value  | Required |
|--|--|--|--|----------|
| <b>AUTH_LDAP_ROLE_ATTRIBUTE_IS_DN</b>                | <b>AUTH_LDAP_ROLE_ATTRIBUTE_IS_DN</b>                | Whether or not the roleAttributeID contains the fully-qualified DN of a role object. If false, the role name is taken from the value of the roleNameAttributeId attribute of the context name. Certain directory schemas, such as Microsoft Active Directory, require this attribute to be set to true.  | <b>`\${AUTH_LDAP_ROLE_ATTRIBUTE_IS_DN}`</b>                | False    |
| <b>AUTH_LDAP_REFERRAL_USER_ATTRIBUTE_ID_TO_CHECK</b> | <b>AUTH_LDAP_REFERRAL_USER_ATTRIBUTE_ID_TO_CHECK</b> | If you are not using referrals, this option can be ignored. When using referrals, this option denotes the attribute name which contains users defined for a certain role, for example member, if the role object is inside the referral. Users are checked against the content of this attribute name. If this option is not set, the check will always fail, so role objects cannot be stored in a referral tree. | <b>`\${AUTH_LDAP_REFERRAL_USER_ATTRIBUTE_ID_TO_CHECK}`</b> | False    |

## 4.2.2. Objects

The CLI supports various object types. A list of these object types as well as their abbreviations can be found in the [OpenShift documentation](#).

### 4.2.2.1. Services



A service is an abstraction which defines a logical set of pods and a policy by which to access them. Refer to the [container-engine documentation](#) for more information.

| Service                                    | Port | Name  | Description                            |
|--|------|-------|--|
| <b>\${APPLICATION_NAME}-kieserver</b>      | 8080 | http  | All the KIE server web server's ports. |
|  | 8443 | https |  |
| <b>\${APPLICATION_NAME}-kieserver-ping</b> | 8888 | ping  | The JGroups ping port for clustering.  |
| <b>\${APPLICATION_NAME}-postgresql</b>     | 5432 | –     | The database server's port.            |

#### 4.2.2.2. Routes

A route is a way to expose a service by giving it an externally-reachable hostname such as **www.example.com**. A defined route and the endpoints identified by its service can be consumed by a router to provide named connectivity from external clients to your applications. Each route consists of a route name, service selector, and (optionally) security configuration. Refer to the [OpenShift documentation](#) for more information.

| Service                                     | Security        | Hostname                             |
|---|-----------------|--------------------------------------|
| <b>\${APPLICATION_NAME}-kieserver-http</b>  | none            | <b>\${KIE_SERVER_HOSTNAME_HTTP}</b>  |
| <b>\${APPLICATION_NAME}-kieserver-https</b> | TLS passthrough | <b>\${KIE_SERVER_HOSTNAME_HTTPS}</b> |

#### 4.2.2.3. Build Configurations

A **buildConfig** describes a single build definition and a set of triggers for when a new build should be created. A **buildConfig** is a REST object, which can be used in a POST to the API server to create a new instance. Refer to the [OpenShift documentation](#) for more information.

| S2I image                      | link  | Build output                                 | BuildTriggers and Settings                 |
|--------------------------------|---|--|--|
| rhpm71-kieserver-openshift:1.1 | <a href="#">rhpm-7/rhpm71-kieserver-openshift</a> | <b>\${APPLICATION_NAME}-kieserver:latest</b> | GitHub, Generic, ImageChange, ConfigChange |

#### 4.2.2.4. Deployment Configurations

A deployment in OpenShift is a replication controller based on a user defined template called a deployment configuration. Deployments are created manually or in response to triggered events. Refer to the [OpenShift documentation](#) for more information.

#### 4.2.2.4.1. Triggers

A trigger drives the creation of new deployments in response to events, both inside and outside OpenShift. Refer to the [Openshift documentation](#) for more information.

| Deployment  | Triggers    |
|---|-------------|
| <b><code>\${APPLICATION_NAME}-kieserver</code></b>  | ImageChange |
| <b><code>\${APPLICATION_NAME}-postgresql</code></b> | ImageChange |

#### 4.2.2.4.2. Replicas

A replication controller ensures that a specified number of pod "replicas" are running at any one time. If there are too many, the replication controller kills some pods. If there are too few, it starts more. Refer to the [container-engine documentation](#) for more information.

| Deployment  | Replicas |
|---|----------|
| <b><code>\${APPLICATION_NAME}-kieserver</code></b>  | 2        |
| <b><code>\${APPLICATION_NAME}-postgresql</code></b> | 1        |

#### 4.2.2.4.3. Pod Template

##### 4.2.2.4.3.1. Service Accounts

Service accounts are API objects that exist within each project. They can be created or deleted like any other API object. Refer to the [Openshift documentation](#) for more information.

| Deployment   | Service Account                                    |
|--|--|
| <b><code>\${APPLICATION_NAME}-kieserver</code></b> | <b><code>\${APPLICATION_NAME}-kieserver</code></b> |

##### 4.2.2.4.3.2. Image

| Deployment  | Image  |
|---|--|
| <b><code>\${APPLICATION_NAME}-kieserver</code></b>  | <b><code>\${APPLICATION_NAME}-kieserver</code></b> |
| <b><code>\${APPLICATION_NAME}-postgresql</code></b> | postgresql   |

##### 4.2.2.4.3.3. Readiness Probe

**`${APPLICATION_NAME}-kieserver`**

```
/bin/bash -c curl --fail --silent -u '${KIE_ADMIN_USER}:${KIE_ADMIN_PWD}'
http://localhost:8080/services/rest/server/readycheck
```

#### **\${APPLICATION\_NAME}-postgresql**

```
/usr/libexec/check-container
```

#### 4.2.2.4.3.4. Liveness Probe

#### **\${APPLICATION\_NAME}-kieserver**

```
/bin/bash -c curl --fail --silent -u '${KIE_ADMIN_USER}:${KIE_ADMIN_PWD}'
http://localhost:8080/services/rest/server/readycheck
```

#### **\${APPLICATION\_NAME}-postgresql**

```
/usr/libexec/check-container
```

#### 4.2.2.4.3.5. Exposed Ports

| Deployments                            | Name    | Port | Protocol   |
|--|---------|------|------------|
| <b>\${APPLICATION_NAME}-kieserver</b>  | jolokia | 8778 | <b>TCP</b> |
|  | http    | 8080 | <b>TCP</b> |
|  | https   | 8443 | <b>TCP</b> |
|  | ping    | 8888 | <b>TCP</b> |
| <b>\${APPLICATION_NAME}-postgresql</b> | –       | 5432 | <b>TCP</b> |

#### 4.2.2.4.3.6. Image Environment Variables

| Deployment                            | Variable name                       | Description  | Example value                           |
|---------------------------------------|-------------------------------------|--|---|
| <b>\${APPLICATION_NAME}-kieserver</b> | <b>DROOLS_SERVER_FILTER_CLASSES</b> | KIE server class filtering (Sets the org.drools.server.filter.classes system property) | <b>\${DROOLS_SERVER_FILTER_CLASSES}</b> |
|                                       | <b>KIE_ADMIN_USER</b>               | KIE administrator username   | <b>\${KIE_ADMIN_USER}</b>               |
|                                       | <b>KIE_ADMIN_PWD</b>                | KIE administrator password   | <b>\${KIE_ADMIN_PWD}</b>                |

| Deployment | Variable name                           | Description   | Example value                               |
|------------|---|---|---|
|            | <b>KIE_MBEANS</b>                       | KIE server mbeans enabled/disabled (Sets the kie.mbeans and kie.scanner.mbeans system properties)   | <b>\${KIE_MBEANS}</b>                       |
|            | <b>KIE_SERVER_BYPASS_AUTH_USER</b>      | KIE server bypass auth user (Sets the org.kie.server.bypass.auth.user system property)  | <b>\${KIE_SERVER_BYPASS_AUTH_USER}</b>      |
|            | <b>KIE_SERVER_CONTROLLER_USER</b>       | –   | <b>\${KIE_SERVER_MONITOR_USER}</b>          |
|            | <b>KIE_SERVER_CONTROLLER_PWD</b>        | –   | <b>\${KIE_SERVER_MONITOR_PWD}</b>           |
|            | <b>KIE_SERVER_CONTROLLER_TOKEN</b>      | –   | <b>\${KIE_SERVER_MONITOR_TOKEN}</b>         |
|            | <b>KIE_SERVER_CONTROLLER_SERVICE</b>    | –   | <b>\${KIE_SERVER_MONITOR_SERVICE}</b>       |
|            | <b>KIE_SERVER_CONTROLLER_PROTOCOL</b>   | –   | ws  |
|            | <b>KIE_SERVER_ID</b>                    | –   | <b>\${APPLICATION_NAME}-kieserver</b>       |
|            | <b>KIE_SERVER_HOST</b>                  | Custom hostname for http service route, if set will also configure the KIE_SERVER_HOST. Leave blank for default hostname, e.g.:<br><application-name>-kieserver-<project>.<br><default-domain-suffix> | <b>\${KIE_SERVER_HOSTNAME_HTTP}</b>         |
|            | <b>KIE_SERVER_ROUTE_NAME</b>            | –   | <b>\${APPLICATION_NAME}-kieserver</b>       |
|            | <b>KIE_SERVER_USE_SECURE_ROUTE_NAME</b> | Use https for the KIE_SERVER_HOST when it is not explicit configured to a custom value.   | <b>\${KIE_SERVER_USE_SECURE_ROUTE_NAME}</b> |

| Deployment | Variable name                          | Description   | Example value                              |
|------------|--|---|--|
|            | <b>KIE_SERVER_USER</b>                 | KIE server username<br>(Sets the org.kie.server.user system property)   | <b>\${KIE_SERVER_USER}</b>                 |
|            | <b>KIE_SERVER_PWD</b>                  | KIE server password, used to connect to KIE servers. Generated value can be a suggestion to use for the various (Sets the org.kie.server.pwd system property) | <b>\${KIE_SERVER_PWD}</b>                  |
|            | <b>KIE_SERVER_CONTAINER_DEPLOYMENT</b> | KIE Server Container deployment configuration in format: containerId=groupId:artifactId:version c2=g2:a2:v2   | <b>\${KIE_SERVER_CONTAINER_DEPLOYMENT}</b> |
|            | <b>MAVEN_REPOS</b>                     | –   | RHPAMCENTR,EXTERNAL                        |
|            | <b>RHPAMCENTR_MAVEN_REPO_SERVICE</b>   | –   | <b>\${BUSINESS_CENTRAL_MAVEN_SERVICE}</b>  |
|            | <b>RHPAMCENTR_MAVEN_REPO_PATH</b>      | –   | <b>/maven2/</b>                            |
|            | <b>RHPAMCENTR_MAVEN_REPO_USERNAME</b>  | Username to access the Maven repository, if required.   | <b>\${BUSINESS_CENTRAL_MAVEN_USERNAME}</b> |
|            | <b>RHPAMCENTR_MAVEN_REPO_PASSWORD</b>  | Password to access the Maven repository, if required.   | <b>\${BUSINESS_CENTRAL_MAVEN_PASSWORD}</b> |
|            | <b>EXTERNAL_MAVEN_REPO_ID</b>          | The id to use for the maven repository, if set. Default is generated randomly.  | <b>\${MAVEN_REPO_ID}</b>                   |
|            | <b>EXTERNAL_MAVEN_REPO_URL</b>         | Fully qualified URL to a Maven repository.  | <b>\${MAVEN_REPO_URL}</b>                  |

| Deployment | Variable name                       | Description   | Example value                           |
|------------|-------------------------------------|---|---|
|            | <b>EXTERNAL_MAVEN_REPO_USERNAME</b> | Username to access the Maven repository, if required.   | <b>`\${MAVEN_REPO_USERNAME}`</b>        |
|            | <b>EXTERNAL_MAVEN_REPO_PASSWORD</b> | Password to access the Maven repository, if required.   | <b>`\${MAVEN_REPO_PASSWORD}`</b>        |
|            | <b>KIE_SERVER_ROUTER_SERVICE</b>    | The service name for the optional smart router, where it can be reached, to allow smart routing                               | <b>`\${KIE_SERVER_ROUTER_SERVICE}`</b>  |
|            | <b>KIE_SERVER_ROUTER_HOST</b>       | The host name of the smart router, which could be the service name resolved by OpenShift or a globally resolvable domain name | <b>`\${KIE_SERVER_ROUTER_HOST}`</b>     |
|            | <b>KIE_SERVER_ROUTER_PORT</b>       | Port in which the smart router server listens (router property org.kie.server.router.port)                                    | <b>`\${KIE_SERVER_ROUTER_PORT}`</b>     |
|            | <b>KIE_SERVER_ROUTER_PROTOCOL</b>   | KIE server router protocol (Used to build the org.kie.server.router.url.external property)                                    | <b>`\${KIE_SERVER_ROUTER_PROTOCOL}`</b> |
|            | <b>KIE_SERVER_PERSISTENCE_DS</b>    | KIE server persistence datasource (Sets the org.kie.server.persistence.ds system property)                                    | <b>`\${KIE_SERVER_PERSISTENCE_DS}`</b>  |
|            | <b>DATASOURCES</b>                  | –   | <b>RHPAM</b>                            |
|            | <b>RHPAM_DATABASE</b>               | –   | <b>`\${KIE_SERVER_POSTGRES_DB}`</b>     |
|            | <b>RHPAM_JNDI</b>                   | –   | <b>`\${KIE_SERVER_PERSISTENCE_DS}`</b>  |
|            | <b>RHPAM_JTA</b>                    | –   | true                                    |

| Deployment | Variable name                                    | Description  | Example value  |
|------------|--|--|--|
|            | <b>RHPAM_DRIVER</b>                              | –  | postgresql   |
|            | <b>KIE_SERVER_PERSISTENCE_DIALECT</b>            | –  | org.hibernate.dialect.PostgreSQLDialect              |
|            | <b>RHPAM_USERNAME</b>                            | –  | <b>\${KIE_SERVER_POSTGRESQL_USER}</b>                |
|            | <b>RHPAM_PASSWORD</b>                            | –  | <b>\${KIE_SERVER_POSTGRESQL_PWD}</b>                 |
|            | <b>RHPAM_SERVICE_HOST</b>                        | –  | <b>\${APPLICATION_NAME}-postgresql</b>               |
|            | <b>RHPAM_SERVICE_PORT</b>                        | –  | 5432   |
|            | <b>TIMER_SERVICE_DATA_STORE</b>                  | Sets refresh-interval for the EJB timer service database-data-store. | <b>\${APPLICATION_NAME}-postgresql</b>               |
|            | <b>TIMER_SERVICE_DATA_STORE_REFRESH_INTERVAL</b> | Sets refresh-interval for the EJB timer service database-data-store. | <b>\${TIMER_SERVICE_DATA_STORE_REFRESH_INTERVAL}</b> |
|            | <b>HTTPS_KEYSTORE_DIR</b>                        | –  | <b>/etc/kieserver-secret-volume</b>                  |
|            | <b>HTTPS_KEYSTORE</b>                            | The name of the keystore file within the secret                      | <b>\${KIE_SERVER_HTTPS_KEYSTORE}</b>                 |
|            | <b>HTTPS_NAME</b>                                | The name associated with the server certificate                      | <b>\${KIE_SERVER_HTTPS_NAME}</b>                     |
|            | <b>HTTPS_PASSWORD</b>                            | The password for the keystore and certificate                        | <b>\${KIE_SERVER_HTTPS_PASSWORD}</b>                 |

| Deployment | Variable name                         | Description  | Example value                              |
|------------|---------------------------------------|--|--|
|            | <b>KIE_SERVER_MGMT_DISABLED</b>       | Disable management api and don't allow KIE containers to be deployed/undeployed or started/stopped sets the property org.kie.server.mgmt.api.disabled to true and org.kie.server.startup.strategy to LocalContainersStartupStrategy. | <b>\${KIE_SERVER_MGMT_DISABLED}</b>        |
|            | <b>KIE_SERVER_STARTUP_STRATEGY</b>    | When set to LocalContainersStartupStrategy, allows KIE server to start up and function with local config, even when a controller is configured and unavailable.  | <b>\${KIE_SERVER_STARTUP_STRATEGY}</b>     |
|            | <b>JGROUPS_PING_PROTOCOL</b>          | –  | openshift.DNS_PING                         |
|            | <b>OPENSIFT_DNS_PING_SERVICE_NAME</b> | –  | <b>\${APPLICATION_NAME}-kieserver-ping</b> |
|            | <b>OPENSIFT_DNS_PING_SERVICE_PORT</b> | –  | 8888                                       |
|            | <b>SSO_URL</b>                        | RH-SSO URL   | <b>\${SSO_URL}</b>                         |
|            | <b>SSO_OPENIDCONNECT_DEPLOYMENTS</b>  | –  | ROOT.war                                   |
|            | <b>SSO_REALM</b>                      | RH-SSO Realm name  | <b>\${SSO_REALM}</b>                       |
|            | <b>SSO_SECRET</b>                     | KIE Server RH-SSO Client Secret  | <b>\${KIE_SERVER_SSO_SECRET}</b>           |
|            | <b>SSO_CLIENT</b>                     | KIE Server RH-SSO Client name  | <b>\${KIE_SERVER_SSO_CLIENT}</b>           |
|            | <b>SSO_USERNAME</b>                   | RH-SSO Realm Admin Username used to create the Client if it doesn't exist  | <b>\${SSO_USERNAME}</b>                    |



| Deployment | Variable name                                 | Description   | Example value                                     |
|------------|---|---|---|
|            | <b>SSO_PASSWORD</b>                           | RH-SSO Realm Admin Password used to create the Client   | <b>\${SSO_PASSWORD}</b>                           |
|            | <b>SSO_DISABLE_SSL_CERTIFICATE_VALIDATION</b> | RH-SSO Disable SSL Certificate Validation   | <b>\${SSO_DISABLE_SSL_CERTIFICATE_VALIDATION}</b> |
|            | <b>SSO_PRINCIPAL_ATTRIBUTE</b>                | RH-SSO Principal Attribute to use as username.  | <b>\${SSO_PRINCIPAL_ATTRIBUTE}</b>                |
|            | <b>HOSTNAME_HTTP</b>                          | Custom hostname for http service route, if set will also configure the KIE_SERVER_HOST. Leave blank for default hostname, e.g.: <application-name>-kieserver-<project>. <default-domain-suffix> | <b>\${KIE_SERVER_HOSTNAME_HTTP}</b>               |
|            | <b>HOSTNAME_HTTPS</b>                         | Custom hostname for https service route. Leave blank for default hostname, e.g.: secure-<application-name>-kieserver-<project>. <default-domain-suffix>   | <b>\${KIE_SERVER_HOSTNAME_HTTPS}</b>              |
|            | <b>AUTH_LDAP_URL</b>                          | LDAP Endpoint to connect for authentication   | <b>\${AUTH_LDAP_URL}</b>                          |
|            | <b>AUTH_LDAP_BIND_DN</b>                      | Bind DN used for authentication   | <b>\${AUTH_LDAP_BIND_DN}</b>                      |
|            | <b>AUTH_LDAP_BIND_CREDENTIAL</b>              | LDAP Credentials used for authentication  | <b>\${AUTH_LDAP_BIND_CREDENTIAL}</b>              |
|            | <b>AUTH_LDAP_JAAS_SECURITY_DOMAIN</b>         | The JMX ObjectName of the JaasSecurityDomain used to decrypt the password.  | <b>\${AUTH_LDAP_JAAS_SECURITY_DOMAIN}</b>         |
|            | <b>AUTH_LDAP_BASE_CTX_DN</b>                  | LDAP Base DN of the top-level context to begin the user search.   | <b>\${AUTH_LDAP_BASE_CTX_DN}</b>                  |

| Deployment | Variable name                                 | Description  | Example value                                       |
|------------|---|--|---|
|            | <b>AUTH_LDAP_BASE_FILTER</b>                  | LDAP search filter used to locate the context of the user to authenticate. The input username or userDN obtained from the login module callback is substituted into the filter anywhere a {0} expression is used. A common example for the search filter is (uid={0}).           | <b>`\${AUTH_LDAP_BASE_FILTER}`</b>                  |
|            | <b>AUTH_LDAP_SEARCH_SCOPE</b>                 | The search scope to use.   | <b>`\${AUTH_LDAP_SEARCH_SCOPE}`</b>                 |
|            | <b>AUTH_LDAP_SEARCH_TIME_LIMIT</b>            | The timeout in milliseconds for user or role searches.   | <b>`\${AUTH_LDAP_SEARCH_TIME_LIMIT}`</b>            |
|            | <b>AUTH_LDAP_DISTINGUISHED_NAME_ATTRIBUTE</b> | The name of the attribute in the user entry that contains the DN of the user. This may be necessary if the DN of the user itself contains special characters, backslash for example, that prevent correct user mapping. If the attribute does not exist, the entry's DN is used. | <b>`\${AUTH_LDAP_DISTINGUISHED_NAME_ATTRIBUTE}`</b> |
|            | <b>AUTH_LDAP_PARSE_USERNAME</b>               | A flag indicating if the DN is to be parsed for the username. If set to true, the DN is parsed for the username. If set to false the DN is not parsed for the username. This option is used together with <code>usernameBeginString</code> and <code>usernameEndString</code> .  | <b>`\${AUTH_LDAP_PARSE_USERNAME}`</b>               |

| Deployment | Variable name                           | Description   | Example value  |
|------------|---|---|--|
|            | <b>AUTH_LDAP_USER_NAME_BEGIN_STRING</b> | Defines the String which is to be removed from the start of the DN to reveal the username. This option is used together with <code>usernameEndString</code> and only taken into account if <code>parseUsername</code> is set to true.                           | <b><code>\${AUTH_LDAP_USER_NAME_BEGIN_STRING}</code></b> |
|            | <b>AUTH_LDAP_USER_NAME_END_STRING</b>   | Defines the String which is to be removed from the end of the DN to reveal the username. This option is used together with <code>usernameEndString</code> and only taken into account if <code>parseUsername</code> is set to true.                             | <b><code>\${AUTH_LDAP_USER_NAME_END_STRING}</code></b>   |
|            | <b>AUTH_LDAP_ROLE_ATTRIBUTE_ID</b>      | Name of the attribute containing the user roles.  | <b><code>\${AUTH_LDAP_ROLE_ATTRIBUTE_ID}</code></b>      |
|            | <b>AUTH_LDAP_ROLE_S_CTX_DN</b>          | The fixed DN of the context to search for user roles. This is not the DN where the actual roles are, but the DN where the objects containing the user roles are. For example, in a Microsoft Active Directory server, this is the DN where the user account is. | <b><code>\${AUTH_LDAP_ROLE_S_CTX_DN}</code></b>          |
|            |   |   |  |

| Deployment | Variable name                           | Description   | Example value                                 |
|------------|---|---|---|
|            | <b>AUTH_LDAP_ROLE_FILTER</b>            | A search filter used to locate the roles associated with the authenticated user. The input username or userDN obtained from the login module callback is substituted into the filter anywhere a {0} expression is used. The authenticated userDN is substituted into the filter anywhere a {1} is used. An example search filter that matches on the input username is (member={0}). An alternative that matches on the authenticated userDN is (member={1}). | <b>`\${AUTH_LDAP_ROLE_FILTER}`</b>            |
|            | <b>AUTH_LDAP_ROLE_RECURSION</b>         | The number of levels of recursion the role search will go below a matching context. Disable recursion by setting this to 0.   | <b>`\${AUTH_LDAP_ROLE_RECURSION}`</b>         |
|            | <b>AUTH_LDAP_DEFAULT_ROLE</b>           | A role included for all authenticated users   | <b>`\${AUTH_LDAP_DEFAULT_ROLE}`</b>           |
|            | <b>AUTH_LDAP_ROLE_NAME_ATTRIBUTE_ID</b> | Name of the attribute within the roleCtxDN context which contains the role name. If the roleAttributesDN property is set to true, this property is used to find the role object's name attribute.   | <b>`\${AUTH_LDAP_ROLE_NAME_ATTRIBUTE_ID}`</b> |

| Deployment | Variable name  | Description  | Example value  |
|------------|--|--|--|
|            | <b>AUTH_LDAP_PARSE_ROLE_NAME_FROM_DN</b>             | A flag indicating if the DN returned by a query contains the roleNameAttributeID. If set to true, the DN is checked for the roleNameAttributeID. If set to false, the DN is not checked for the roleNameAttributeID. This flag can improve the performance of LDAP queries.  | <b>\${AUTH_LDAP_PARSE_ROLE_NAME_FROM_DN}</b>             |
|            | <b>AUTH_LDAP_ROLE_ATTRIBUTE_IS_DN</b>                | Whether or not the roleAttributeID contains the fully-qualified DN of a role object. If false, the role name is taken from the value of the roleNameAttributeID attribute of the context name. Certain directory schemas, such as Microsoft Active Directory, require this attribute to be set to true.  | <b>\${AUTH_LDAP_ROLE_ATTRIBUTE_IS_DN}</b>                |
|            | <b>AUTH_LDAP_REFERRAL_USER_ATTRIBUTE_ID_TO_CHECK</b> | If you are not using referrals, this option can be ignored. When using referrals, this option denotes the attribute name which contains users defined for a certain role, for example member, if the role object is inside the referral. Users are checked against the content of this attribute name. If this option is not set, the check will always fail, so role objects cannot be stored in a referral tree. | <b>\${AUTH_LDAP_REFERRAL_USER_ATTRIBUTE_ID_TO_CHECK}</b> |

| Deployment                             | Variable name                               | Description                                      | Example value                                   |
|--|---|--|---|
| <b>\${APPLICATION_NAME}-postgresql</b> | <b>POSTGRESQL_USER</b>                      | KIE server PostgreSQL database username          | <b>\${KIE_SERVER_POSTGRESQL_USER}</b>           |
|  | <b>POSTGRESQL_PASSWORD</b>                  | –  | <b>\${KIE_SERVER_POSTGRESQL_PWD}</b>            |
|  | <b>POSTGRESQL_DATABASE</b>                  | –  | <b>\${KIE_SERVER_POSTGRESQL_DB}</b>             |
|  | <b>POSTGRESQL_MAX_PREPARED_TRANSACTIONS</b> | Allows the PostgreSQL to handle XA transactions. | <b>\${POSTGRESQL_MAX_PREPARED_TRANSACTIONS}</b> |

#### 4.2.2.4.3.7. Volumes

| Deployment                             | Name  | mountPath                           | Purpose    | readOnly |
|--|---|-------------------------------------|------------|----------|
| <b>\${APPLICATION_NAME}-kieserver</b>  | kieserver-keystore-volume                   | <b>/etc/kieserver-secret-volume</b> | ssl certs  | True     |
| <b>\${APPLICATION_NAME}-postgresql</b> | <b>\${APPLICATION_NAME}-postgresql-pvol</b> | <b>/var/lib/pgsql/data</b>          | postgresql | false    |

#### 4.2.2.5. External Dependencies

##### 4.2.2.5.1. Volume Claims

A **PersistentVolume** object is a storage resource in an OpenShift cluster. Storage is provisioned by an administrator by creating **PersistentVolume** objects from sources such as GCE Persistent Disks, AWS Elastic Block Stores (EBS), and NFS mounts. Refer to the [OpenShift documentation](#) for more information.

| Name   | Access Mode   |
|--|---------------|
| <b>\${APPLICATION_NAME}-postgresql-claim</b> | ReadWriteOnce |

##### 4.2.2.5.2. Secrets

This template requires the following secrets to be installed for the application to run.

kieserver-app-secret

## 4.3. RHPAM71-KIESERVER-EXTERNALDB

Application template for a managed KIE Server with an external database, for Red Hat Process Automation Manager 7.1

### 4.3.1. Parameters

Templates allow you to define parameters which take on a value. That value is then substituted wherever the parameter is referenced. References can be defined in any text field in the objects list field. Refer to the [Openshift documentation](#) for more information.

| Variable name                          | Image Environment Variable              | Description   | Example value                              | Required |
|--|---|---|--|----------|
| <b>APPLICATION_NAME</b>                | –                                       | The name for the application.   | myapp                                      | True     |
| <b>MAVEN_REPO_ID</b>                   | <b>EXTERNAL_MAVEN_REPO_ID</b>           | The id to use for the maven repository, if set. Default is generated randomly.  | <b>\${MAVEN_REPO_ID}</b>                   | False    |
| <b>MAVEN_REPO_URL</b>                  | <b>EXTERNAL_MAVEN_REPO_URL</b>          | Fully qualified URL to a Maven repository or service.   | <b>\${MAVEN_REPO_URL}</b>                  | True     |
| <b>MAVEN_REPO_USERNAME</b>             | <b>RHPAMCENTRAL_MAVEN_REPO_USERNAME</b> | Username to access the Maven repository, if required.   | <b>\${BUSINESS_CENTRAL_MAVEN_USERNAME}</b> | False    |
| <b>MAVEN_REPO_PASSWORD</b>             | <b>RHPAMCENTRAL_MAVEN_REPO_PASSWORD</b> | Password to access the Maven repository, if required.   | <b>\${BUSINESS_CENTRAL_MAVEN_PASSWORD}</b> | False    |
| <b>BUSINESS_CENTRAL_MAVEN_SERVICE</b>  | –                                       | The service name for the optional business central, where it can be reached, to allow service lookups (for maven repo usage), if required | –  | False    |
| <b>BUSINESS_CENTRAL_MAVEN_USERNAME</b> | –                                       | Username to access the Maven service hosted by Business Central inside EAP.   | –  | False    |

| Variable name                          | Image Environment Variable | Description   | Example value                  | Required |
|--|----------------------------|---|--------------------------------|----------|
| <b>BUSINESS_CENTRAL_MAVEN_PASSWORD</b> | –                          | Password to access the Maven service hosted by Business Central inside EAP.   | –                              | False    |
| <b>KIE_ADMIN_USER</b>                  | <b>KIE_ADMIN_USER</b>      | KIE administrator username  | adminUser                      | False    |
| <b>KIE_ADMIN_PASSWORD</b>              | <b>KIE_ADMIN_PASSWORD</b>  | KIE administrator password  | <b>\${KIE_ADMIN_PASSWORD}</b>  | False    |
| <b>KIE_SERVER_USER</b>                 | <b>KIE_SERVER_USER</b>     | KIE server username (Sets the org.kie.server.user system property)  | executionUser                  | False    |
| <b>KIE_SERVER_PASSWORD</b>             | <b>KIE_SERVER_PASSWORD</b> | KIE server password (Sets the org.kie.server.pwd system property)   | <b>\${KIE_SERVER_PASSWORD}</b> | False    |
| <b>IMAGE_STREAM_NAMESPACE</b>          | –                          | Namespace in which the ImageStreams for Red Hat Middleware images are installed. These ImageStreams are normally installed in the openshift namespace. You should only need to modify this if you've installed the ImageStreams in a different namespace/project. | openshift                      | True     |



| Variable name                       | Image Environment Variable        | Description   | Example value                           | Required |
|-------------------------------------|-----------------------------------|---|---|----------|
| <b>KIE_SERVER_IMAGE_STREAM_NAME</b> | –                                 | The name of the image stream to use for KIE server. Default is "rhpam71-kieserver-openshift".                                 | rhpam71-kieserver-openshift             | True     |
| <b>IMAGE_STREAM_TAG</b>             | –                                 | A named pointer to an image in an image stream. Default is "1.1".   | 1.1                                     | True     |
| <b>KIE_SERVER_ROUTER_SERVICE</b>    | <b>KIE_SERVER_ROUTER_SERVICE</b>  | The service name for the optional smart router, where it can be reached, to allow smart routing                               | <b>`\${KIE_SERVER_ROUTER_SERVICE}`</b>  | False    |
| <b>KIE_SERVER_ROUTER_HOST</b>       | <b>KIE_SERVER_ROUTER_HOST</b>     | The host name of the smart router, which could be the service name resolved by OpenShift or a globally resolvable domain name | <b>`\${KIE_SERVER_ROUTER_HOST}`</b>     | False    |
| <b>KIE_SERVER_ROUTER_PORT</b>       | <b>KIE_SERVER_ROUTER_PORT</b>     | Port in which the smart router server listens (router property org.kie.server.router.port)                                    | <b>`\${KIE_SERVER_ROUTER_PORT}`</b>     | False    |
| <b>KIE_SERVER_ROUTER_PROTOCOL</b>   | <b>KIE_SERVER_ROUTER_PROTOCOL</b> | KIE server router protocol (Used to build the org.kie.server.router.url.external property)                                    | <b>`\${KIE_SERVER_ROUTER_PROTOCOL}`</b> | False    |

| Variable name                        | Image Environment Variable           | Description   | Example value                            | Required |
|--------------------------------------|--------------------------------------|---|--|----------|
| <b>KIE_SERVER_CONTROLLER_USER</b>    | <b>KIE_SERVER_CONTROLLER_USER</b>    | KIE server controller username (Sets the org.kie.server.controller.user system property)  | controllerUser                           | False    |
| <b>KIE_SERVER_CONTROLLER_PWD</b>     | <b>KIE_SERVER_CONTROLLER_PWD</b>     | KIE server controller password (Sets the org.kie.server.controller.pwd system property)   | <b>\${KIE_SERVER_CONTROLLER_PWD}</b>     | False    |
| <b>KIE_SERVER_CONTROLLER_TOKEN</b>   | <b>KIE_SERVER_CONTROLLER_TOKEN</b>   | KIE server controller token for bearer authentication (Sets the org.kie.server.controller.token system property)  | <b>\${KIE_SERVER_CONTROLLER_TOKEN}</b>   | False    |
| <b>KIE_SERVER_CONTROLLER_SERVICE</b> | <b>KIE_SERVER_CONTROLLER_SERVICE</b> | The service name for the optional business central monitor, where it can be reached to allow service lookup, and registered with to allow monitoring console functionality (If set, will be used to discover host and port) | <b>\${KIE_SERVER_CONTROLLER_SERVICE}</b> | False    |
| <b>KIE_SERVER_CONTROLLER_HOST</b>    | <b>KIE_SERVER_CONTROLLER_HOST</b>    | KIE server controller host (Used to set the org.kie.server.controller system property)  | <b>\${KIE_SERVER_CONTROLLER_HOST}</b>    | False    |

| Variable name                            | Image Environment Variable        | Description   | Example value                           | Required |
|--|-----------------------------------|---|---|----------|
| <b>KIE_SERVER_CONTROLLER_PORT</b>        | <b>KIE_SERVER_CONTROLLER_PORT</b> | KIE server controller port (Used to set the org.kie.server.controller.system property)                  | <b>`\${KIE_SERVER_CONTROLLER_PORT}`</b> | False    |
| <b>KIE_SERVER_PERSISTENCE_DS</b>         | <b>KIE_SERVER_PERSISTENCE_DS</b>  | KIE server persistence datasource (Sets the org.kie.server.persistence.ds system property)              | java:/jboss/datasources/rhpam           | False    |
| <b>KIE_SERVER_EXTERNALDB_DRIVER</b>      | –                                 | KIE server external database driver   | –                                       | True     |
| <b>KIE_SERVER_EXTERNALDB_DRIVER_TYPE</b> | –                                 | KIE server external database driver type, applicable only for DB2, possible values are 4 (default) or 2 | –                                       | False    |
| <b>KIE_SERVER_EXTERNALDB_USERNAME</b>    | –                                 | KIE server external database username   | –                                       | True     |
| <b>KIE_SERVER_EXTERNALDB_PASSWORD</b>    | –                                 | KIE server external database password   | –                                       | True     |
| <b>KIE_SERVER_EXTERNALDB_URL</b>         | –                                 | KIE server external database JDBC URL   | –                                       | False    |
| <b>KIE_SERVER_EXTERNALDB_DIALECT</b>     | –                                 | KIE server external database Hibernate dialect  | –                                       | True     |

| Variable name                       | Image Environment Variable          | Description   | Example value                         | Required |
|-------------------------------------|-------------------------------------|---|---------------------------------------|----------|
| <b>KIE_SERVER_EXTERNALDB_HOST</b>   | –                                   | KIE server external database host, for <code>ejb_timer</code> <code>datasource</code> configuration   | –                                     | True     |
| <b>KIE_SERVER_EXTERNALDB_PORT</b>   | –                                   | KIE server external database port, for <code>ejb_timer</code> <code>datasource</code> configuration   | –                                     | True     |
| <b>KIE_SERVER_EXTERNALDB_DB</b>     | –                                   | KIE server external database name, for <code>ejb_timer</code> <code>datasource</code> configuration   | rhpm                                  | False    |
| <b>DROOLS_SERVER_FILTER_CLASSES</b> | <b>DROOLS_SERVER_FILTER_CLASSES</b> | KIE server class filtering (Sets the <code>org.drools.server.filter.classes</code> system property)   | true                                  | False    |
| <b>KIE_MBEANS</b>                   | <b>KIE_MBEANS</b>                   | KIE server mbeans enabled/disabled (Sets the <code>kie.mbeans</code> and <code>kie.scanner.mbeans</code> system properties)   | enabled                               | False    |
| <b>KIE_SERVER_HOSTNAME_HTTP</b>     | <b>KIE_SERVER_HOST</b>              | Custom hostname for http service route, if set will also configure the <code>KIE_SERVER_HOST</code> . Leave blank for default hostname, e.g.: <code>&lt;application-name&gt;-kieserver-&lt;project&gt;.&lt;default-domain-suffix&gt;</code> | <b>`\${KIE_SERVER_HOSTNAME_HTTP}`</b> | False    |

| Variable name                                    | Image Environment Variable                       | Description   | Example value                          | Required |
|--|--|---|--|----------|
| <b>KIE_SERVER_HOSTNAME_HTTPS</b>                 | <b>KIE_SERVER_HOST</b>                           | Custom hostname for https service route. Leave blank for default hostname, e.g.:<br>secure-<br><application-name>-kieserver-<br><project>.<default-domain-suffix> | <b>`\${KIE_SERVER_HOSTNAME_HTTPS}`</b> | False    |
| <b>KIE_SERVER_USE_SECURE_ROUTE_NAME</b>          | <b>KIE_SERVER_USE_SECURE_ROUTE_NAME</b>          | Use https for the KIE_SERVER_HOST when it is not explicit configured to a custom value.   | false                                  | False    |
| <b>KIE_SERVER_HTTPS_SECRET</b>                   | –  | The name of the secret containing the keystore file   | –                                      | True     |
| <b>KIE_SERVER_HTTPS_KEYSTORE</b>                 | <b>HTTPS_KEYSTORE</b>                            | The name of the keystore file within the secret   | keystore.jks                           | False    |
| <b>KIE_SERVER_HTTPS_NAME</b>                     | <b>HTTPS_NAME</b>                                | The name associated with the server certificate   | jboss                                  | False    |
| <b>KIE_SERVER_HTTPS_PASSWORD</b>                 | <b>HTTPS_PASSWORD</b>                            | The password for the keystore and certificate   | mykeystorepass                         | False    |
| <b>KIE_SERVER_BYPASS_AUTH_USER</b>               | <b>KIE_SERVER_BYPASS_AUTH_USER</b>               | KIE server bypass auth user (Sets the org.kie.server.bypass.auth.user system property)  | false                                  | False    |
| <b>TIMER_SERVICE_DATA_STORE_REFRESH_INTERVAL</b> | <b>TIMER_SERVICE_DATA_STORE_REFRESH_INTERVAL</b> | Sets refresh-interval for the EJB timer database data-store service.  | 30000                                  | False    |

| Variable name                          | Image Environment Variable             | Description  | Example value                                | Required |
|--|--|--|--|----------|
| <b>KIE_SERVER_MEMORY_LIMIT</b>         | –                                      | KIE server Container memory limit  | 1Gi  | False    |
| <b>KIE_SERVER_CONTAINER_DEPLOYMENT</b> | <b>KIE_SERVER_CONTAINER_DEPLOYMENT</b> | KIE Server Container deployment configuration in format:<br>containerId=groupId:artifactId:version c2=g2:a2:v2   | <b>`\${KIE_SERVER_CONTAINER_DEPLOYMENT}`</b> | False    |
| <b>KIE_SERVER_MGMT_DISABLED</b>        | <b>KIE_SERVER_MGMT_DISABLED</b>        | Disable management api and don't allow KIE containers to be deployed/undeployed or started/stopped sets the property org.kie.server.management.api.disabled to true and org.kie.server.startup.strategy to LocalContainersStartupStrategy. | <b>`\${KIE_SERVER_MGMT_DISABLED}`</b>        | False    |
| <b>KIE_SERVER_STARTUP_STRATEGY</b>     | <b>KIE_SERVER_STARTUP_STRATEGY</b>     | When set to LocalContainersStartupStrategy, allows KIE server to start up and function with local config, even when a controller is configured and unavailable.  | <b>`\${KIE_SERVER_STARTUP_STRATEGY}`</b>     | False    |
| <b>SSO_URL</b>                         | <b>SSO_URL</b>                         | RH-SSO URL   | <b>`\${SSO_URL}`</b>                         | False    |
| <b>SSO_REALM</b>                       | <b>SSO_REALM</b>                       | RH-SSO Realm name  | <b>`\${SSO_REALM}`</b>                       | False    |

| Variable name                                 | Image Environment Variable                    | Description  | Example value                             | Required |
|---|---|--|---|----------|
| <b>KIE_SERVER_SSO_CLIENT</b>                  | <b>SSO_CLIENT</b>                             | KIE Server RH-SSO Client name  | <b>\${KIE_SERVER_SSO_CLIENT}</b>          | False    |
| <b>KIE_SERVER_SSO_SECRET</b>                  | <b>SSO_SECRET</b>                             | KIE Server RH-SSO Client Secret  | <b>\${KIE_SERVER_SSO_SECRET}</b>          | False    |
| <b>SSO_USERNAME</b>                           | <b>SSO_USERNAME</b>                           | RH-SSO Realm Admin Username used to create the Client if it doesn't exist  | <b>\${SSO_USERNAME}</b>                   | False    |
| <b>SSO_PASSWORD</b>                           | <b>SSO_PASSWORD</b>                           | RH-SSO Realm Admin Password used to create the Client                      | <b>\${SSO_PASSWORD}</b>                   | False    |
| <b>SSO_DISABLE_SSL_CERTIFICATE_VALIDATION</b> | <b>SSO_DISABLE_SSL_CERTIFICATE_VALIDATION</b> | RH-SSO Disable SSL Certificate Validation                                  | false                                     | False    |
| <b>SSO_PRINCIPAL_ATTRIBUTE</b>                | <b>SSO_PRINCIPAL_ATTRIBUTE</b>                | RH-SSO Principal Attribute to use as username.                             | preferred_username                        | False    |
| <b>AUTH_LDAP_URL</b>                          | <b>AUTH_LDAP_URL</b>                          | LDAP Endpoint to connect for authentication                                | <b>\${AUTH_LDAP_URL}</b>                  | False    |
| <b>AUTH_LDAP_BIND_DN</b>                      | <b>AUTH_LDAP_BIND_DN</b>                      | Bind DN used for authentication  | <b>\${AUTH_LDAP_BIND_DN}</b>              | False    |
| <b>AUTH_LDAP_BIND_CREDENTIAL</b>              | <b>AUTH_LDAP_BIND_CREDENTIAL</b>              | LDAP Credentials used for authentication                                   | <b>\${AUTH_LDAP_BIND_CREDENTIAL}</b>      | False    |
| <b>AUTH_LDAP_JAAS_SECURITY_DOMAIN</b>         | <b>AUTH_LDAP_JAAS_SECURITY_DOMAIN</b>         | The JMX ObjectName of the JaasSecurityDomain used to decrypt the password. | <b>\${AUTH_LDAP_JAAS_SECURITY_DOMAIN}</b> | False    |

| Variable name                      | Image Environment Variable         | Description  | Example value                            | Required |
|------------------------------------|------------------------------------|--|--|----------|
| <b>AUTH_LDAP_BASE_CTX_DN</b>       | <b>AUTH_LDAP_BASE_CTX_DN</b>       | LDAP Base DN of the top-level context to begin the user search.  | <b>`\${AUTH_LDAP_BASE_CTX_DN}`</b>       | False    |
| <b>AUTH_LDAP_BASE_FILTER</b>       | <b>AUTH_LDAP_BASE_FILTER</b>       | LDAP search filter used to locate the context of the user to authenticate. The input username or userDN obtained from the login module callback is substituted into the filter anywhere a {O} expression is used. A common example for the search filter is (uid={O}). | <b>`\${AUTH_LDAP_BASE_FILTER}`</b>       | False    |
| <b>AUTH_LDAP_SEARCH_SCOPE</b>      | <b>AUTH_LDAP_SEARCH_SCOPE</b>      | The search scope to use.   | <b>`\${AUTH_LDAP_SEARCH_SCOPE}`</b>      | False    |
| <b>AUTH_LDAP_SEARCH_TIME_LIMIT</b> | <b>AUTH_LDAP_SEARCH_TIME_LIMIT</b> | The timeout in milliseconds for user or role searches.   | <b>`\${AUTH_LDAP_SEARCH_TIME_LIMIT}`</b> | False    |



| Variable name                                 | Image Environment Variable                    | Description  | Example value                                       | Required |
|---|---|--|---|----------|
| <b>AUTH_LDAP_DISTINGUISHED_NAME_ATTRIBUTE</b> | <b>AUTH_LDAP_DISTINGUISHED_NAME_ATTRIBUTE</b> | The name of the attribute in the user entry that contains the DN of the user. This may be necessary if the DN of the user itself contains special characters, backslash for example, that prevent correct user mapping. If the attribute does not exist, the entry's DN is used. | <b>`\${AUTH_LDAP_DISTINGUISHED_NAME_ATTRIBUTE}`</b> | False    |
| <b>AUTH_LDAP_PARSE_USERNAME</b>               | <b>AUTH_LDAP_PARSE_USERNAME</b>               | A flag indicating if the DN is to be parsed for the username. If set to true, the DN is parsed for the username. If set to false the DN is not parsed for the username. This option is used together with <code>usernameBeginString</code> and <code>usernameEndString</code> .  | <b>`\${AUTH_LDAP_PARSE_USERNAME}`</b>               | False    |
| <b>AUTH_LDAP_USERNAME_BEGIN_STRING</b>        | <b>AUTH_LDAP_USERNAME_BEGIN_STRING</b>        | Defines the String which is to be removed from the start of the DN to reveal the username. This option is used together with <code>usernameEndString</code> and only taken into account if <code>parseUsername</code> is set to true.  | <b>`\${AUTH_LDAP_USERNAME_BEGIN_STRING}`</b>        | False    |

| Variable name                        | Image Environment Variable           | Description   | Example value   | Required |
|--------------------------------------|--------------------------------------|---|---|----------|
| <b>AUTH_LDAP_USERNAME_END_STRING</b> | <b>AUTH_LDAP_USERNAME_END_STRING</b> | Defines the String which is to be removed from the end of the DN to reveal the username. This option is used together with <code>usernameEndString</code> and only taken into account if <code>parseUsername</code> is set to true.                             | <b><code>\${AUTH_LDAP_USERNAME_END_STRING}</code></b> | False    |
| <b>AUTH_LDAP_ROLE_ATTRIBUTE_ID</b>   | <b>AUTH_LDAP_ROLE_ATTRIBUTE_ID</b>   | Name of the attribute containing the user roles.  | <b><code>\${AUTH_LDAP_ROLE_ATTRIBUTE_ID}</code></b>   | False    |
| <b>AUTH_LDAP_ROLES_CTX_DN</b>        | <b>AUTH_LDAP_ROLES_CTX_DN</b>        | The fixed DN of the context to search for user roles. This is not the DN where the actual roles are, but the DN where the objects containing the user roles are. For example, in a Microsoft Active Directory server, this is the DN where the user account is. | <b><code>\${AUTH_LDAP_ROLES_CTX_DN}</code></b>        | False    |

| Variable name                   | Image Environment Variable      | Description   | Example value                         | Required |
|---------------------------------|---------------------------------|---|---------------------------------------|----------|
| <b>AUTH_LDAP_ROLE_FILTER</b>    | <b>AUTH_LDAP_ROLE_FILTER</b>    | A search filter used to locate the roles associated with the authenticated user. The input username or userDN obtained from the login module callback is substituted into the filter anywhere a {0} expression is used. The authenticated userDN is substituted into the filter anywhere a {1} is used. An example search filter that matches on the input username is (member={0}). An alternative that matches on the authenticated userDN is (member={1}). | <b>`\${AUTH_LDAP_ROLE_FILTER}`</b>    | False    |
| <b>AUTH_LDAP_ROLE_RECURSION</b> | <b>AUTH_LDAP_ROLE_RECURSION</b> | The number of levels of recursion the role search will go below a matching context. Disable recursion by setting this to 0.   | <b>`\${AUTH_LDAP_ROLE_RECURSION}`</b> | False    |
| <b>AUTH_LDAP_DEFAULT_ROLE</b>   | <b>AUTH_LDAP_DEFAULT_ROLE</b>   | A role included for all authenticated users   | <b>`\${AUTH_LDAP_DEFAULT_ROLE}`</b>   | False    |

| Variable name                            | Image Environment Variable               | Description  | Example value                                  | Required |
|--|--|--|--|----------|
| <b>AUTH_LDAP_ROLE_NAME_ATTRIBUTE_ID</b>  | <b>AUTH_LDAP_ROLE_NAME_ATTRIBUTE_ID</b>  | Name of the attribute within the roleCtxDN context which contains the role name. If the roleAttributesDN property is set to true, this property is used to find the role object's name attribute.  | <b>`\${AUTH_LDAP_ROLE_NAME_ATTRIBUTE_ID}`</b>  | False    |
| <b>AUTH_LDAP_PARSE_ROLE_NAME_FROM_DN</b> | <b>AUTH_LDAP_PARSE_ROLE_NAME_FROM_DN</b> | A flag indicating if the DN returned by a query contains the roleNameAttribute ID. If set to true, the DN is checked for the roleNameAttribute ID. If set to false, the DN is not checked for the roleNameAttribute ID. This flag can improve the performance of LDAP queries.                           | <b>`\${AUTH_LDAP_PARSE_ROLE_NAME_FROM_DN}`</b> | False    |
| <b>AUTH_LDAP_ROLE_ATTRIBUTE_IS_DN</b>    | <b>AUTH_LDAP_ROLE_ATTRIBUTE_IS_DN</b>    | Whether or not the roleAttributeID contains the fully-qualified DN of a role object. If false, the role name is taken from the value of the roleNameAttribute Id attribute of the context name. Certain directory schemas, such as Microsoft Active Directory, require this attribute to be set to true. | <b>`\${AUTH_LDAP_ROLE_ATTRIBUTE_IS_DN}`</b>    | False    |

| Variable name   | Image Environment Variable                            | Description  | Example value   | Required |
|---|---|--|---|----------|
| <b>AUTH_LDAP_REFERRAL_USE_R_ATTRIBUTE_ID_TO_CHECK</b> | <b>AUTH_LDAP_REFERRAL_USE_R_ATTRIBUTE_ID_TO_CHECK</b> | If you are not using referrals, this option can be ignored. When using referrals, this option denotes the attribute name which contains users defined for a certain role, for example member, if the role object is inside the referral. Users are checked against the content of this attribute name. If this option is not set, the check will always fail, so role objects cannot be stored in a referral tree. | <b><code>\${AUTH_LDAP_REFERRAL_USER_ATTRIBUTE_ID_TO_CHECK}</code></b> | False    |

### 4.3.2. Objects

The CLI supports various object types. A list of these object types as well as their abbreviations can be found in the [Openshift documentation](#).

#### 4.3.2.1. Services

A service is an abstraction which defines a logical set of pods and a policy by which to access them. Refer to the [container-engine documentation](#) for more information.

| Service   | Port | Name  | Description                            |
|---|------|-------|--|
| <b><code>\${APPLICATION_NAME}-kieserver</code></b>      | 8080 | http  | All the KIE server web server's ports. |
|   | 8443 | https |  |
| <b><code>\${APPLICATION_NAME}-kieserver-ping</code></b> | 8888 | ping  | The JGroups ping port for clustering.  |

#### 4.3.2.2. Routes

A route is a way to expose a service by giving it an externally-reachable hostname such as **`www.example.com`**. A defined route and the endpoints identified by its service can be consumed by a

router to provide named connectivity from external clients to your applications. Each route consists of a route name, service selector, and (optionally) security configuration. Refer to the [OpenShift documentation](#) for more information.

| Service                                     | Security        | Hostname                             |
|---|-----------------|--------------------------------------|
| <b>\${APPLICATION_NAME}-kieserver-http</b>  | none            | <b>\${KIE_SERVER_HOSTNAME_HTTP}</b>  |
| <b>\${APPLICATION_NAME}-kieserver-https</b> | TLS passthrough | <b>\${KIE_SERVER_HOSTNAME_HTTPS}</b> |

### 4.3.2.3. Deployment Configurations

A deployment in OpenShift is a replication controller based on a user defined template called a deployment configuration. Deployments are created manually or in response to triggered events. Refer to the [OpenShift documentation](#) for more information.

#### 4.3.2.3.1. Triggers

A trigger drives the creation of new deployments in response to events, both inside and outside OpenShift. Refer to the [OpenShift documentation](#) for more information.

| Deployment                            | Triggers    |
|---------------------------------------|-------------|
| <b>\${APPLICATION_NAME}-kieserver</b> | ImageChange |

#### 4.3.2.3.2. Replicas

A replication controller ensures that a specified number of pod "replicas" are running at any one time. If there are too many, the replication controller kills some pods. If there are too few, it starts more. Refer to the [container-engine documentation](#) for more information.

| Deployment                            | Replicas |
|---------------------------------------|----------|
| <b>\${APPLICATION_NAME}-kieserver</b> | 1        |

#### 4.3.2.3.3. Pod Template

##### 4.3.2.3.3.1. Service Accounts

Service accounts are API objects that exist within each project. They can be created or deleted like any other API object. Refer to the [OpenShift documentation](#) for more information.

| Deployment                            | Service Account                       |
|---------------------------------------|---------------------------------------|
| <b>\${APPLICATION_NAME}-kieserver</b> | <b>\${APPLICATION_NAME}-kieserver</b> |

## 4.3.2.3.3.2. Image

| Deployment                            | Image                                   |
|---------------------------------------|---|
| <b>\${APPLICATION_NAME}-kieserver</b> | <b>\${KIE_SERVER_IMAGE_STREAM_NAME}</b> |

## 4.3.2.3.3.3. Readiness Probe

**\${APPLICATION\_NAME}-kieserver**

```
/bin/bash -c curl --fail --silent -u '${KIE_ADMIN_USER}:${KIE_ADMIN_PWD}'
http://localhost:8080/services/rest/server/readycheck
```

## 4.3.2.3.3.4. Liveness Probe

**\${APPLICATION\_NAME}-kieserver**

```
/bin/bash -c curl --fail --silent -u '${KIE_ADMIN_USER}:${KIE_ADMIN_PWD}'
http://localhost:8080/services/rest/server/readycheck
```

## 4.3.2.3.3.5. Exposed Ports

| Deployments                           | Name    | Port | Protocol   |
|---------------------------------------|---------|------|------------|
| <b>\${APPLICATION_NAME}-kieserver</b> | jolokia | 8778 | <b>TCP</b> |
|                                       | http    | 8080 | <b>TCP</b> |
|                                       | https   | 8443 | <b>TCP</b> |
|                                       | ping    | 8888 | <b>TCP</b> |

## 4.3.2.3.3.6. Image Environment Variables

| Deployment                            | Variable name                       | Description   | Example value                           |
|---------------------------------------|-------------------------------------|---|---|
| <b>\${APPLICATION_NAME}-kieserver</b> | <b>DROOLS_SERVER_FILTER_CLASSES</b> | KIE server class filtering (Sets the org.drools.server.filter.cl asses system property) | <b>\${DROOLS_SERVER_FILTER_CLASSES}</b> |
|                                       | <b>KIE_ADMIN_USER</b>               | KIE administrator username  | <b>\${KIE_ADMIN_USER}</b>               |
|                                       | <b>KIE_ADMIN_PWD</b>                | KIE administrator password  | <b>\${KIE_ADMIN_PWD}</b>                |

| Deployment | Variable name                         | Description   | Example value                            |
|------------|---------------------------------------|---|--|
|            | <b>KIE_MBEANS</b>                     | KIE server mbeans enabled/disabled (Sets the kie.mbeans and kie.scanner.mbeans system properties)   | <b>\${KIE_MBEANS}</b>                    |
|            | <b>KIE_SERVER_BYPASS_AUTH_USER</b>    | KIE server bypass auth user (Sets the org.kie.server.bypass.auth.user system property)  | <b>\${KIE_SERVER_BYPASS_AUTH_USER}</b>   |
|            | <b>KIE_SERVER_CONTROLLER_USER</b>     | KIE server controller username (Sets the org.kie.server.controller.user system property)  | <b>\${KIE_SERVER_CONTROLLER_USER}</b>    |
|            | <b>KIE_SERVER_CONTROLLER_PWD</b>      | KIE server controller password (Sets the org.kie.server.controller.pwd system property)   | <b>\${KIE_SERVER_CONTROLLER_PWD}</b>     |
|            | <b>KIE_SERVER_CONTROLLER_TOKEN</b>    | KIE server controller token for bearer authentication (Sets the org.kie.server.controller.token system property)  | <b>\${KIE_SERVER_CONTROLLER_TOKEN}</b>   |
|            | <b>KIE_SERVER_CONTROLLER_SERVICE</b>  | The service name for the optional business central monitor, where it can be reached to allow service lookup, and registered with to allow monitoring console functionality (If set, will be used to discover host and port) | <b>\${KIE_SERVER_CONTROLLER_SERVICE}</b> |
|            | <b>KIE_SERVER_CONTROLLER_PROTOCOL</b> | –   | ws                                       |
|            | <b>KIE_SERVER_CONTROLLER_HOST</b>     | KIE server controller host (Used to set the org.kie.server.controller system property)  | <b>\${KIE_SERVER_CONTROLLER_HOST}</b>    |



| Deployment | Variable name                           | Description   | Example value                               |
|------------|---|---|---|
|            | <b>KIE_SERVER_CONTROLLER_PORT</b>       | KIE server controller port (Used to set the org.kie.server.controller system property)  | <b>\${KIE_SERVER_CONTROLLER_PORT}</b>       |
|            | <b>KIE_SERVER_ID</b>                    | –   | <b>\${APPLICATION_NAME}-kieserver</b>       |
|            | <b>KIE_SERVER_HOST</b>                  | Custom hostname for http service route, if set will also configure the KIE_SERVER_HOST. Leave blank for default hostname, e.g.:<br><application-name>-kieserver-<project>.<br><default-domain-suffix> | <b>\${KIE_SERVER_HOSTNAME_HTTP}</b>         |
|            | <b>KIE_SERVER_ROUTE_NAME</b>            | –   | <b>\${APPLICATION_NAME}-kieserver</b>       |
|            | <b>KIE_SERVER_USE_SECURE_ROUTE_NAME</b> | Use https for the KIE_SERVER_HOST when it is not explicit configured to a custom value.   | <b>\${KIE_SERVER_USE_SECURE_ROUTE_NAME}</b> |
|            | <b>KIE_SERVER_USER</b>                  | KIE server username (Sets the org.kie.server.user system property)  | <b>\${KIE_SERVER_USER}</b>                  |
|            | <b>KIE_SERVER_PWD</b>                   | KIE server password (Sets the org.kie.server.pwd system property)   | <b>\${KIE_SERVER_PWD}</b>                   |
|            | <b>KIE_SERVER_CONTAINER_DEPLOYMENT</b>  | KIE Server Container deployment configuration in format: containerId=groupId:artifactId:version c2=g2:a2:v2   | <b>\${KIE_SERVER_CONTAINER_DEPLOYMENT}</b>  |
|            | <b>MAVEN_REPOS</b>                      | –   | RHPAMCENTR,EXTERNAL                         |

| Deployment | Variable name                         | Description   | Example value                                |
|------------|---------------------------------------|---|--|
|            | <b>RHPAMCENTR_MAVEN_REPO_SERVICE</b>  | –   | <b>`\${BUSINESS_CENTRAL_MAVEN_SERVICE}`</b>  |
|            | <b>RHPAMCENTR_MAVEN_REPO_PATH</b>     | –   | <b><code>/maven2/</code></b>                 |
|            | <b>RHPAMCENTR_MAVEN_REPO_USERNAME</b> | Username to access the Maven repository, if required.   | <b>`\${BUSINESS_CENTRAL_MAVEN_USERNAME}`</b> |
|            | <b>RHPAMCENTR_MAVEN_REPO_PASSWORD</b> | Password to access the Maven repository, if required.   | <b>`\${BUSINESS_CENTRAL_MAVEN_PASSWORD}`</b> |
|            | <b>EXTERNAL_MAVEN_REPO_ID</b>         | The id to use for the maven repository, if set. Default is generated randomly.  | <b>`\${MAVEN_REPO_ID}`</b>                   |
|            | <b>EXTERNAL_MAVEN_REPO_URL</b>        | Fully qualified URL to a Maven repository or service.   | <b>`\${MAVEN_REPO_URL}`</b>                  |
|            | <b>EXTERNAL_MAVEN_REPO_USERNAME</b>   | Username to access the Maven repository, if required.   | <b>`\${MAVEN_REPO_USERNAME}`</b>             |
|            | <b>EXTERNAL_MAVEN_REPO_PASSWORD</b>   | Password to access the Maven repository, if required.   | <b>`\${MAVEN_REPO_PASSWORD}`</b>             |
|            | <b>KIE_SERVER_ROUTER_SERVICE</b>      | The service name for the optional smart router, where it can be reached, to allow smart routing                               | <b>`\${KIE_SERVER_ROUTER_SERVICE}`</b>       |
|            | <b>KIE_SERVER_ROUTER_HOST</b>         | The host name of the smart router, which could be the service name resolved by OpenShift or a globally resolvable domain name | <b>`\${KIE_SERVER_ROUTER_HOST}`</b>          |

| Deployment | Variable name                         | Description  | Example value                            |
|------------|---------------------------------------|--|--|
|            | <b>KIE_SERVER_ROUTER_PORT</b>         | Port in which the smart router server listens (router property org.kie.server.router.port)   | <b>\${KIE_SERVER_ROUTER_PORT}</b>        |
|            | <b>KIE_SERVER_ROUTER_PROTOCOL</b>     | KIE server router protocol (Used to build the org.kie.server.router.url. external property)  | <b>\${KIE_SERVER_ROUTER_PROTOCOL}</b>    |
|            | <b>KIE_SERVER_MGMT_DISABLED</b>       | Disable management api and don't allow KIE containers to be deployed/undeployed or started/stopped sets the property org.kie.server.mgmt.api.disabled to true and org.kie.server.startup.strategy to LocalContainersStartupStrategy. | <b>\${KIE_SERVER_MGMT_DISABLED}</b>      |
|            | <b>KIE_SERVER_STARTUP_STRATEGY</b>    | When set to LocalContainersStartupStrategy, allows KIE server to start up and function with local config, even when a controller is configured and unavailable.  | <b>\${KIE_SERVER_STARTUP_STRATEGY}</b>   |
|            | <b>KIE_SERVER_PERSISTENCE_DS</b>      | KIE server persistence datasource (Sets the org.kie.server.persistence.ds system property)   | <b>\${KIE_SERVER_PERSISTENCE_DS}</b>     |
|            | <b>DATASOURCES</b>                    | –  | <b>RHPAM</b>                             |
|            | <b>RHPAM_JNDI</b>                     | –  | <b>\${KIE_SERVER_PERSISTENCE_DS}</b>     |
|            | <b>KIE_SERVER_PERSISTENCE_DIALECT</b> | –  | <b>\${KIE_SERVER_EXTERNALDB_DIALECT}</b> |

| Deployment | Variable name                                    | Description  | Example value  |
|------------|--|--|--|
|            | <b>RHPAM_DRIVER</b>                              | –  | <b>\${KIE_SERVER_EXTERNALDB_DRIVER}</b>              |
|            | <b>RHPAM_DRIVER_TYPE</b>                         | –  | <b>\${KIE_SERVER_EXTERNALDB_DRIVER_TYPE}</b>         |
|            | <b>RHPAM_USERNAME</b>                            | –  | <b>\${KIE_SERVER_EXTERNALDB_USER}</b>                |
|            | <b>RHPAM_PASSWORD</b>                            | –  | <b>\${KIE_SERVER_EXTERNALDB_PWD}</b>                 |
|            | <b>RHPAM_XA_CONNECTION_PROPERTY_URL</b>          | –  | <b>\${KIE_SERVER_EXTERNALDB_URL}</b>                 |
|            | <b>RHPAM_SERVICE_HOST</b>                        | –  | <b>\${KIE_SERVER_EXTERNALDB_HOST}</b>                |
|            | <b>RHPAM_SERVICE_PORT</b>                        | –  | <b>\${KIE_SERVER_EXTERNALDB_PORT}</b>                |
|            | <b>RHPAM_DATABASE</b>                            | –  | <b>\${KIE_SERVER_EXTERNALDB_DB}</b>                  |
|            | <b>RHPAM_JTA</b>                                 | –  | true   |
|            | <b>TIMER_SERVICE_DATA_STORE_REFRESH_INTERVAL</b> | Sets refresh-interval for the EJB timer database data-store service. | <b>\${TIMER_SERVICE_DATA_STORE_REFRESH_INTERVAL}</b> |
|            | <b>HTTPS_KEYSTORE_DIR</b>                        | –  | <b>/etc/kieserver-secret-volume</b>                  |
|            | <b>HTTPS_KEYSTORE</b>                            | The name of the keystore file within the secret                      | <b>\${KIE_SERVER_HTTPS_KEYSTORE}</b>                 |
|            | <b>HTTPS_NAME</b>                                | The name associated with the server certificate                      | <b>\${KIE_SERVER_HTTPS_NAME}</b>                     |
|            | <b>HTTPS_PASSWORD</b>                            | The password for the keystore and certificate                        | <b>\${KIE_SERVER_HTTPS_PASSWORD}</b>                 |
|            | <b>JGROUPS_PING_PROTOCOL</b>                     | –  | openshift.DNS_PING                                   |

| Deployment | Variable name                                 | Description   | Example value                                     |
|------------|---|---|---|
|            | <b>OPENSIFT_DNS_PING_SERVICE_NAME</b>         | –   | <b>\${APPLICATION_NAME}-kieserver-ping</b>        |
|            | <b>OPENSIFT_DNS_PING_SERVICE_PORT</b>         | –   | 8888  |
|            | <b>SSO_URL</b>                                | RH-SSO URL  | <b>\${SSO_URL}</b>                                |
|            | <b>SSO_OPENIDCONNECT_DEPLOYMENTS</b>          | –   | ROOT.war  |
|            | <b>SSO_REALM</b>                              | RH-SSO Realm name   | <b>\${SSO_REALM}</b>                              |
|            | <b>SSO_SECRET</b>                             | KIE Server RH-SSO Client Secret   | <b>\${KIE_SERVER_SSO_SECRET}</b>                  |
|            | <b>SSO_CLIENT</b>                             | KIE Server RH-SSO Client name   | <b>\${KIE_SERVER_SSO_CLIENT}</b>                  |
|            | <b>SSO_USERNAME</b>                           | RH-SSO Realm Admin Username used to create the Client if it doesn't exist | <b>\${SSO_USERNAME}</b>                           |
|            | <b>SSO_PASSWORD</b>                           | RH-SSO Realm Admin Password used to create the Client                     | <b>\${SSO_PASSWORD}</b>                           |
|            | <b>SSO_DISABLE_SSL_CERTIFICATE_VALIDATION</b> | RH-SSO Disable SSL Certificate Validation                                 | <b>\${SSO_DISABLE_SSL_CERTIFICATE_VALIDATION}</b> |
|            | <b>SSO_PRINCIPAL_ATTRIBUTE</b>                | RH-SSO Principal Attribute to use as username.                            | <b>\${SSO_PRINCIPAL_ATTRIBUTE}</b>                |

| Deployment | Variable name                         | Description  | Example value                             |
|------------|---------------------------------------|--|---|
|            | <b>HOSTNAME_HTTP</b>                  | Custom hostname for http service route, if set will also configure the KIE_SERVER_HOST. Leave blank for default hostname, e.g.: <application-name>-kieserver-<project>.<default-domain-suffix> | <b>\${KIE_SERVER_HOSTNAME_HTTP}</b>       |
|            | <b>HOSTNAME_HTTPS</b>                 | Custom hostname for https service route. Leave blank for default hostname, e.g.: secure-<application-name>-kieserver-<project>.<default-domain-suffix>   | <b>\${KIE_SERVER_HOSTNAME_HTTPS}</b>      |
|            | <b>AUTH_LDAP_URL</b>                  | LDAP Endpoint to connect for authentication  | <b>\${AUTH_LDAP_URL}</b>                  |
|            | <b>AUTH_LDAP_BIND_DN</b>              | Bind DN used for authentication  | <b>\${AUTH_LDAP_BIND_DN}</b>              |
|            | <b>AUTH_LDAP_BIND_CREDENTIAL</b>      | LDAP Credentials used for authentication   | <b>\${AUTH_LDAP_BIND_CREDENTIAL}</b>      |
|            | <b>AUTH_LDAP_JAAS_SECURITY_DOMAIN</b> | The JMX ObjectName of the JaasSecurityDomain used to decrypt the password.   | <b>\${AUTH_LDAP_JAAS_SECURITY_DOMAIN}</b> |
|            | <b>AUTH_LDAP_BASE_CTX_DN</b>          | LDAP Base DN of the top-level context to begin the user search.  | <b>\${AUTH_LDAP_BASE_CTX_DN}</b>          |

| Deployment | Variable name                                 | Description  | Example value                                       |
|------------|---|--|---|
|            | <b>AUTH_LDAP_BASE_FILTER</b>                  | LDAP search filter used to locate the context of the user to authenticate. The input username or userDN obtained from the login module callback is substituted into the filter anywhere a {0} expression is used. A common example for the search filter is (uid={0}).           | <b>`\${AUTH_LDAP_BASE_FILTER}`</b>                  |
|            | <b>AUTH_LDAP_SEARCH_SCOPE</b>                 | The search scope to use.   | <b>`\${AUTH_LDAP_SEARCH_SCOPE}`</b>                 |
|            | <b>AUTH_LDAP_SEARCH_TIME_LIMIT</b>            | The timeout in milliseconds for user or role searches.   | <b>`\${AUTH_LDAP_SEARCH_TIME_LIMIT}`</b>            |
|            | <b>AUTH_LDAP_DISTINGUISHED_NAME_ATTRIBUTE</b> | The name of the attribute in the user entry that contains the DN of the user. This may be necessary if the DN of the user itself contains special characters, backslash for example, that prevent correct user mapping. If the attribute does not exist, the entry's DN is used. | <b>`\${AUTH_LDAP_DISTINGUISHED_NAME_ATTRIBUTE}`</b> |
|            | <b>AUTH_LDAP_PARSE_USERNAME</b>               | A flag indicating if the DN is to be parsed for the username. If set to true, the DN is parsed for the username. If set to false the DN is not parsed for the username. This option is used together with <code>usernameBeginString</code> and <code>usernameEndString</code> .  | <b>`\${AUTH_LDAP_PARSE_USERNAME}`</b>               |

| Deployment | Variable name                           | Description   | Example value  |
|------------|---|---|--|
|            | <b>AUTH_LDAP_USER_NAME_BEGIN_STRING</b> | Defines the String which is to be removed from the start of the DN to reveal the username. This option is used together with <code>usernameEndString</code> and only taken into account if <code>parseUsername</code> is set to true.                           | <b><code>\${AUTH_LDAP_USER_NAME_BEGIN_STRING}</code></b> |
|            | <b>AUTH_LDAP_USER_NAME_END_STRING</b>   | Defines the String which is to be removed from the end of the DN to reveal the username. This option is used together with <code>usernameEndString</code> and only taken into account if <code>parseUsername</code> is set to true.                             | <b><code>\${AUTH_LDAP_USER_NAME_END_STRING}</code></b>   |
|            | <b>AUTH_LDAP_ROLE_ATTRIBUTE_ID</b>      | Name of the attribute containing the user roles.  | <b><code>\${AUTH_LDAP_ROLE_ATTRIBUTE_ID}</code></b>      |
|            | <b>AUTH_LDAP_ROLE_S_CTX_DN</b>          | The fixed DN of the context to search for user roles. This is not the DN where the actual roles are, but the DN where the objects containing the user roles are. For example, in a Microsoft Active Directory server, this is the DN where the user account is. | <b><code>\${AUTH_LDAP_ROLE_S_CTX_DN}</code></b>          |



| Deployment | Variable name                           | Description   | Example value                                 |
|------------|---|---|---|
|            | <b>AUTH_LDAP_ROLE_FILTER</b>            | A search filter used to locate the roles associated with the authenticated user. The input username or userDN obtained from the login module callback is substituted into the filter anywhere a {0} expression is used. The authenticated userDN is substituted into the filter anywhere a {1} is used. An example search filter that matches on the input username is (member={0}). An alternative that matches on the authenticated userDN is (member={1}). | <b>`\${AUTH_LDAP_ROLE_FILTER}`</b>            |
|            | <b>AUTH_LDAP_ROLE_RECURSION</b>         | The number of levels of recursion the role search will go below a matching context. Disable recursion by setting this to 0.   | <b>`\${AUTH_LDAP_ROLE_RECURSION}`</b>         |
|            | <b>AUTH_LDAP_DEFAULT_ROLE</b>           | A role included for all authenticated users   | <b>`\${AUTH_LDAP_DEFAULT_ROLE}`</b>           |
|            | <b>AUTH_LDAP_ROLE_NAME_ATTRIBUTE_ID</b> | Name of the attribute within the roleCtxDN context which contains the role name. If the roleAttributesDN property is set to true, this property is used to find the role object's name attribute.   | <b>`\${AUTH_LDAP_ROLE_NAME_ATTRIBUTE_ID}`</b> |

| Deployment | Variable name  | Description  | Example value  |
|------------|--|--|--|
|            | <b>AUTH_LDAP_PARSE_ROLE_NAME_FROM_DN</b>             | A flag indicating if the DN returned by a query contains the roleNameAttributeID. If set to true, the DN is checked for the roleNameAttributeID. If set to false, the DN is not checked for the roleNameAttributeID. This flag can improve the performance of LDAP queries.  | <b>`\${AUTH_LDAP_PARSE_ROLE_NAME_FROM_DN}`</b>             |
|            | <b>AUTH_LDAP_ROLE_ATTRIBUTE_IS_DN</b>                | Whether or not the roleAttributeID contains the fully-qualified DN of a role object. If false, the role name is taken from the value of the roleNameAttributeID attribute of the context name. Certain directory schemas, such as Microsoft Active Directory, require this attribute to be set to true.  | <b>`\${AUTH_LDAP_ROLE_ATTRIBUTE_IS_DN}`</b>                |
|            | <b>AUTH_LDAP_REFERRAL_USER_ATTRIBUTE_ID_TO_CHECK</b> | If you are not using referrals, this option can be ignored. When using referrals, this option denotes the attribute name which contains users defined for a certain role, for example member, if the role object is inside the referral. Users are checked against the content of this attribute name. If this option is not set, the check will always fail, so role objects cannot be stored in a referral tree. | <b>`\${AUTH_LDAP_REFERRAL_USER_ATTRIBUTE_ID_TO_CHECK}`</b> |

#### 4.3.2.3.3.7. Volumes

| Deployment                            | Name                      | mountPath                           | Purpose   | readOnly |
|---------------------------------------|---------------------------|-------------------------------------|-----------|----------|
| <b>\${APPLICATION_NAME}-kieserver</b> | kieserver-keystore-volume | <b>/etc/kieserver-secret-volume</b> | ssl certs | True     |

#### 4.3.2.4. External Dependencies

##### 4.3.2.4.1. Secrets

This template requires the following secrets to be installed for the application to run.

kieserver-app-secret

## 4.4. RHPAM71-KIESERVER-MYSQL

Application template for a managed KIE Server with a MySQL database, for Red Hat Process Automation Manager 7.1

### 4.4.1. Parameters

Templates allow you to define parameters which take on a value. That value is then substituted wherever the parameter is referenced. References can be defined in any text field in the objects list field. Refer to the [Openshift documentation](#) for more information.

| Variable name              | Image Environment Variable              | Description  | Example value                              | Required |
|----------------------------|---|--|--|----------|
| <b>APPLICATION_NAME</b>    | –                                       | The name for the application.  | myapp                                      | True     |
| <b>MAVEN_REPO_ID</b>       | <b>EXTERNAL_MAVEN_REPO_ID</b>           | The id to use for the maven repository, if set. Default is generated randomly. | <b>\${MAVEN_REPO_ID}</b>                   | False    |
| <b>MAVEN_REPO_URL</b>      | <b>EXTERNAL_MAVEN_REPO_URL</b>          | Fully qualified URL to a Maven repository or service.                          | <b>\${MAVEN_REPO_URL}</b>                  | True     |
| <b>MAVEN_REPO_USERNAME</b> | <b>RHPAMCENTRAL_MAVEN_REPO_USERNAME</b> | Username to access the Maven repository, if required.                          | <b>\${BUSINESS_CENTRAL_MAVEN_USERNAME}</b> | False    |

| Variable name                          | Image Environment Variable              | Description   | Example value                                     | Required |
|--|---|---|---|----------|
| <b>MAVEN_REPO_PASSWORD</b>             | <b>RHPAMCENTRAL_MAVEN_REPO_PASSWORD</b> | Password to access the Maven repository, if required.   | <b>`\${BUSINESS_CENTRAL_MAVEN_REPO_PASSWORD}`</b> | False    |
| <b>BUSINESS_CENTRAL_MAVEN_SERVICE</b>  | –                                       | The service name for the optional business central, where it can be reached, to allow service lookups (for maven repo usage), if required | –   | False    |
| <b>BUSINESS_CENTRAL_MAVEN_USERNAME</b> | –                                       | Username to access the Maven service hosted by Business Central inside EAP.   | –   | False    |
| <b>BUSINESS_CENTRAL_MAVEN_PASSWORD</b> | –                                       | Password to access the Maven service hosted by Business Central inside EAP.   | –   | False    |
| <b>KIE_ADMIN_USERNAME</b>              | <b>KIE_ADMIN_USERNAME</b>               | KIE administrator username  | adminUser   | False    |
| <b>KIE_ADMIN_PASSWORD</b>              | <b>KIE_ADMIN_PASSWORD</b>               | KIE administrator password  | <b>`\${KIE_ADMIN_PASSWORD}`</b>                   | False    |
| <b>KIE_SERVER_USERNAME</b>             | <b>KIE_SERVER_USERNAME</b>              | KIE server username (Sets the org.kie.server.user system property)  | executionUser                                     | False    |
| <b>KIE_SERVER_PASSWORD</b>             | <b>KIE_SERVER_PASSWORD</b>              | KIE server password (Sets the org.kie.server.pwd system property)   | <b>`\${KIE_SERVER_PASSWORD}`</b>                  | False    |

| Variable name                       | Image Environment Variable       | Description   | Example value                          | Required |
|-------------------------------------|----------------------------------|---|--|----------|
| <b>IMAGE_STREAM_NAMESPACE</b>       | –                                | Namespace in which the ImageStreams for Red Hat Middleware images are installed. These ImageStreams are normally installed in the openshift namespace. You should only need to modify this if you've installed the ImageStreams in a different namespace/project. | openshift                              | True     |
| <b>KIE_SERVER_IMAGE_STREAM_NAME</b> | –                                | The name of the image stream to use for KIE server. Default is "rhpam71-kieserver-openshift".   | rhpam71-kieserver-openshift            | True     |
| <b>IMAGE_STREAM_TAG</b>             | –                                | A named pointer to an image in an image stream. Default is "1.1".   | 1.1                                    | True     |
| <b>KIE_SERVER_ROUTER_SERVICE</b>    | <b>KIE_SERVER_ROUTER_SERVICE</b> | The service name for the optional smart router, where it can be reached, to allow smart routing   | <b>`\${KIE_SERVER_ROUTER_SERVICE}`</b> | False    |
| <b>KIE_SERVER_ROUTER_HOST</b>       | <b>KIE_SERVER_ROUTER_HOST</b>    | The host name of the smart router, which could be the service name resolved by OpenShift or a globally resolvable domain name   | <b>`\${KIE_SERVER_ROUTER_HOST}`</b>    | False    |

| Variable name                         | Image Environment Variable            | Description  | Example value                               | Required |
|---------------------------------------|---------------------------------------|--|---|----------|
| <b>KIE_SERVER_ROUTER_PORT</b>         | <b>KIE_SERVER_ROUTER_PORT</b>         | Port in which the smart router server listens (router property org.kie.server.router.port)                       | <b>`\${KIE_SERVER_ROUTER_PORT}`</b>         | False    |
| <b>KIE_SERVER_ROUTER_PROTOCOL</b>     | <b>KIE_SERVER_ROUTER_PROTOCOL</b>     | KIE server router protocol (Used to build the org.kie.server.router.url.external property)                       | <b>`\${KIE_SERVER_ROUTER_PROTOCOL}`</b>     | False    |
| <b>KIE_SERVER_CONTROLLER_USER</b>     | <b>KIE_SERVER_CONTROLLER_USER</b>     | KIE server controller username (Sets the org.kie.server.controller.user system property)                         | controllerUser                              | False    |
| <b>KIE_SERVER_CONTROLLER_PASSWORD</b> | <b>KIE_SERVER_CONTROLLER_PASSWORD</b> | KIE server controller password (Sets the org.kie.server.controller.pwd system property)                          | <b>`\${KIE_SERVER_CONTROLLER_PASSWORD}`</b> | False    |
| <b>KIE_SERVER_CONTROLLER_TOKEN</b>    | <b>KIE_SERVER_CONTROLLER_TOKEN</b>    | KIE server controller token for bearer authentication (Sets the org.kie.server.controller.token system property) | <b>`\${KIE_SERVER_CONTROLLER_TOKEN}`</b>    | False    |

| Variable name                        | Image Environment Variable           | Description   | Example value                              | Required |
|--------------------------------------|--------------------------------------|---|--|----------|
| <b>KIE_SERVER_CONTROLLER_SERVICE</b> | <b>KIE_SERVER_CONTROLLER_SERVICE</b> | The service name for the optional business central monitor, where it can be reached to allow service lookup, and registered with to allow monitoring console functionality (If set, will be used to discover host and port) | <b>`\${KIE_SERVER_CONTROLLER_SERVICE}`</b> | False    |
| <b>KIE_SERVER_CONTROLLER_HOST</b>    | <b>KIE_SERVER_CONTROLLER_HOST</b>    | KIE server controller host (Used to set the org.kie.server.controller.system property)  | <b>`\${KIE_SERVER_CONTROLLER_HOST}`</b>    | False    |
| <b>KIE_SERVER_CONTROLLER_PORT</b>    | <b>KIE_SERVER_CONTROLLER_PORT</b>    | KIE server controller port (Used to set the org.kie.server.controller.system property)  | <b>`\${KIE_SERVER_CONTROLLER_PORT}`</b>    | False    |
| <b>KIE_SERVER_PERSISTENCE_DS</b>     | <b>KIE_SERVER_PERSISTENCE_DS</b>     | KIE server persistence datasource (Sets the org.kie.server.persistence.ds system property)  | java:/jboss/datasources/rhpam              | False    |

| Variable name                       | Image Environment Variable          | Description   | Example value | Required |
|-------------------------------------|-------------------------------------|---|---------------|----------|
| <b>MYSQL_IMAGE_STREAM_NAMESPACE</b> | –                                   | Namespace in which the ImageStream for the MySQL image is installed. The ImageStream is already installed in the openshift namespace. You should only need to modify this if you've installed the ImageStream in a different namespace/project. Default is "openshift". | openshift     | False    |
| <b>MYSQL_IMAGE_STREAM_TAG</b>       | –                                   | The MySQL image version, which is intended to correspond to the MySQL version. Default is "5.7".  | 5.7           | False    |
| <b>KIE_SERVER_MYSQL_USER</b>        | <b>MYSQL_USER</b>                   | KIE server MySQL database username  | rhcam         | False    |
| <b>KIE_SERVER_MYSQL_PWD</b>         | –                                   | KIE server MySQL database password  | –             | False    |
| <b>KIE_SERVER_MYSQL_DB</b>          | –                                   | KIE server MySQL database name  | rhcam7        | False    |
| <b>DB_VOLUME_CAPACITY</b>           | –                                   | Size of persistent storage for database volume.   | 1Gi           | True     |
| <b>DROOLS_SERVER_FILTER_CLASSES</b> | <b>DROOLS_SERVER_FILTER_CLASSES</b> | KIE server class filtering (Sets the org.drools.server.filter.classes system property)  | true          | False    |



| Variable name                           | Image Environment Variable              | Description  | Example value                         | Required |
|---|---|--|---------------------------------------|----------|
| <b>KIE_MBEANS</b>                       | <b>KIE_MBEANS</b>                       | KIE server mbeans enabled/disabled (Sets the kie.mbeans and kie.scanner.mbeans system properties)  | enabled                               | False    |
| <b>KIE_SERVER_HOSTNAME_HTTP</b>         | <b>KIE_SERVER_HOST</b>                  | Custom hostname for http service route, if set will also configure the KIE_SERVER_HOST. Leave blank for default hostname, e.g.: <application-name>-kieserver-<project>.<default-domain-suffix> | <b>`\${KIE_SERVER_HOSTNAME_HTTP}`</b> | False    |
| <b>KIE_SERVER_HOSTNAME_HTTPS</b>        | <b>KIE_SERVER_HOST</b>                  | Custom hostname for https service route. Leave blank for default hostname, e.g.: secure-<application-name>-kieserver-<project>.<default-domain-suffix>   | <b>`\${KIE_SERVER_HOSTNAME_HTTP}`</b> | False    |
| <b>KIE_SERVER_USE_SECURE_ROUTE_NAME</b> | <b>KIE_SERVER_USE_SECURE_ROUTE_NAME</b> | Use https for the KIE_SERVER_HOST when it is not explicit configured to a custom value.  | false                                 | False    |
| <b>KIE_SERVER_HTTPS_SECRET</b>          | –                                       | The name of the secret containing the keystore file  | –                                     | True     |
| <b>KIE_SERVER_HTTPS_KEYSTORE</b>        | <b>HTTPS_KEYSTORE</b>                   | The name of the keystore file within the secret  | keystore.jks                          | False    |

| Variable name                                    | Image Environment Variable             | Description   | Example value                              | Required |
|--|--|---|--|----------|
| <b>KIE_SERVER_HTTPS_NAME</b>                     | <b>HTTPS_NAME</b>                      | The name associated with the server certificate   | jboss                                      | False    |
| <b>KIE_SERVER_HTTPS_PASSWORD</b>                 | <b>HTTPS_PASSWORD</b>                  | The password for the keystore and certificate   | mykeystorepass                             | False    |
| <b>KIE_SERVER_BYPASS_AUTH_USER</b>               | <b>KIE_SERVER_BYPASS_AUTH_USER</b>     | KIE server bypass auth user (Sets the org.kie.server.bypass.auth.user system property)  | false                                      | False    |
| <b>TIMER_SERVICE_DATA_STORE_REFRESH_INTERVAL</b> | <b>TIMER_SERVICE_DATA_STORE</b>        | Sets refresh-interval for the EJB timer database data-store service.  | 30000                                      | False    |
| <b>KIE_SERVER_MEMORY_LIMIT</b>                   | –                                      | KIE server Container memory limit   | 1Gi  | False    |
| <b>KIE_SERVER_CONTAINER_DEPLOYMENT</b>           | <b>KIE_SERVER_CONTAINER_DEPLOYMENT</b> | KIE Server Container deployment configuration in format:<br>containerId=groupId:artifactId:version c2=g2:a2:v2  | <b>\${KIE_SERVER_CONTAINER_DEPLOYMENT}</b> | False    |
| <b>KIE_SERVER_MGMT_DISABLED</b>                  | <b>KIE_SERVER_MGMT_DISABLED</b>        | When set to LocalContainersStartupStrategy, allows KIE server to start up and function with local config, even when a controller is configured and unavailable. | <b>\${KIE_SERVER_MGMT_DISABLED}</b>        | False    |

| Variable name                                 | Image Environment Variable                    | Description   | Example value                            | Required |
|---|---|---|--|----------|
| <b>KIE_SERVER_STARTUP_STRATEGY</b>            | <b>KIE_SERVER_STARTUP_STRATEGY</b>            | When set to LocalContainersStartupStrategy, allows KIE server to start up and function with local config, even when a controller is configured and unavailable. | <b>`\${KIE_SERVER_STARTUP_STRATEGY}`</b> | False    |
| <b>SSO_URL</b>                                | <b>SSO_URL</b>                                | RH-SSO URL  | <b>`\${SSO_URL}`</b>                     | False    |
| <b>SSO_REALM</b>                              | <b>SSO_REALM</b>                              | RH-SSO Realm name   | <b>`\${SSO_REALM}`</b>                   | False    |
| <b>KIE_SERVER_SSO_CLIENT</b>                  | <b>SSO_CLIENT</b>                             | KIE Server RH-SSO Client name   | <b>`\${KIE_SERVER_SSO_CLIENT}`</b>       | False    |
| <b>KIE_SERVER_SSO_SECRET</b>                  | <b>SSO_SECRET</b>                             | KIE Server RH-SSO Client Secret   | <b>`\${KIE_SERVER_SSO_SECRET}`</b>       | False    |
| <b>SSO_USERNAME</b>                           | <b>SSO_USERNAME</b>                           | RH-SSO Realm Admin Username used to create the Client if it doesn't exist   | <b>`\${SSO_USERNAME}`</b>                | False    |
| <b>SSO_PASSWORD</b>                           | <b>SSO_PASSWORD</b>                           | RH-SSO Realm Admin Password used to create the Client   | <b>`\${SSO_PASSWORD}`</b>                | False    |
| <b>SSO_DISABLE_SSL_CERTIFICATE_VALIDATION</b> | <b>SSO_DISABLE_SSL_CERTIFICATE_VALIDATION</b> | RH-SSO Disable SSL Certificate Validation   | false                                    | False    |
| <b>SSO_PRINCIPAL_ATTRIBUTE</b>                | <b>SSO_PRINCIPAL_ATTRIBUTE</b>                | RH-SSO Principal Attribute to use as username.  | preferred_username                       | False    |
| <b>AUTH_LDAP_URL</b>                          | <b>AUTH_LDAP_URL</b>                          | LDAP Endpoint to connect for authentication   | <b>`\${AUTH_LDAP_URL}`</b>               | False    |

| Variable name                         | Image Environment Variable            | Description  | Example value                             | Required |
|---------------------------------------|---------------------------------------|--|---|----------|
| <b>AUTH_LDAP_BIND_DN</b>              | <b>AUTH_LDAP_BIND_DN</b>              | Bind DN used for authentication  | <b>\${AUTH_LDAP_BIND_DN}</b>              | False    |
| <b>AUTH_LDAP_BIND_CREDENTIAL</b>      | <b>AUTH_LDAP_BIND_CREDENTIAL</b>      | LDAP Credentials used for authentication   | <b>\${AUTH_LDAP_BIND_CREDENTIAL}</b>      | False    |
| <b>AUTH_LDAP_JAAS_SECURITY_DOMAIN</b> | <b>AUTH_LDAP_JAAS_SECURITY_DOMAIN</b> | The JMX ObjectName of the JaasSecurityDomain used to decrypt the password.   | <b>\${AUTH_LDAP_JAAS_SECURITY_DOMAIN}</b> | False    |
| <b>AUTH_LDAP_BASE_CTX_DN</b>          | <b>AUTH_LDAP_BASE_CTX_DN</b>          | LDAP Base DN of the top-level context to begin the user search.  | <b>\${AUTH_LDAP_BASE_CTX_DN}</b>          | False    |
| <b>AUTH_LDAP_BASE_FILTER</b>          | <b>AUTH_LDAP_BASE_FILTER</b>          | LDAP search filter used to locate the context of the user to authenticate. The input username or userDN obtained from the login module callback is substituted into the filter anywhere a {0} expression is used. A common example for the search filter is (uid={0}). | <b>\${AUTH_LDAP_BASE_FILTER}</b>          | False    |
| <b>AUTH_LDAP_SEARCH_SCOPE</b>         | <b>AUTH_LDAP_SEARCH_SCOPE</b>         | The search scope to use.   | <b>\${AUTH_LDAP_SEARCH_SCOPE}</b>         | False    |
| <b>AUTH_LDAP_SEARCH_TIME_LIMIT</b>    | <b>AUTH_LDAP_SEARCH_TIME_LIMIT</b>    | The timeout in milliseconds for user or role searches.   | <b>\${AUTH_LDAP_SEARCH_TIME_LIMIT}</b>    | False    |

| Variable name                                 | Image Environment Variable                    | Description  | Example value                                       | Required |
|---|---|--|---|----------|
| <b>AUTH_LDAP_DISTINGUISHED_NAME_ATTRIBUTE</b> | <b>AUTH_LDAP_DISTINGUISHED_NAME_ATTRIBUTE</b> | The name of the attribute in the user entry that contains the DN of the user. This may be necessary if the DN of the user itself contains special characters, backslash for example, that prevent correct user mapping. If the attribute does not exist, the entry's DN is used. | <b>`\${AUTH_LDAP_DISTINGUISHED_NAME_ATTRIBUTE}`</b> | False    |
| <b>AUTH_LDAP_PARSE_USERNAME</b>               | <b>AUTH_LDAP_PARSE_USERNAME</b>               | A flag indicating if the DN is to be parsed for the username. If set to true, the DN is parsed for the username. If set to false the DN is not parsed for the username. This option is used together with <code>usernameBeginString</code> and <code>usernameEndString</code> .  | <b>`\${AUTH_LDAP_PARSE_USERNAME}`</b>               | False    |
| <b>AUTH_LDAP_USERNAME_BEGIN_STRING</b>        | <b>AUTH_LDAP_USERNAME_BEGIN_STRING</b>        | Defines the String which is to be removed from the start of the DN to reveal the username. This option is used together with <code>usernameEndString</code> and only taken into account if <code>parseUsername</code> is set to true.  | <b>`\${AUTH_LDAP_USERNAME_BEGIN_STRING}`</b>        | False    |

| Variable name                        | Image Environment Variable           | Description   | Example value   | Required |
|--------------------------------------|--------------------------------------|---|---|----------|
| <b>AUTH_LDAP_USERNAME_END_STRING</b> | <b>AUTH_LDAP_USERNAME_END_STRING</b> | Defines the String which is to be removed from the end of the DN to reveal the username. This option is used together with <code>usernameEndString</code> and only taken into account if <code>parseUsername</code> is set to true.                             | <b><code>\${AUTH_LDAP_USERNAME_END_STRING}</code></b> | False    |
| <b>AUTH_LDAP_ROLE_ATTRIBUTE_ID</b>   | <b>AUTH_LDAP_ROLE_ATTRIBUTE_ID</b>   | Name of the attribute containing the user roles.  | <b><code>\${AUTH_LDAP_ROLE_ATTRIBUTE_ID}</code></b>   | False    |
| <b>AUTH_LDAP_ROLES_CTX_DN</b>        | <b>AUTH_LDAP_ROLES_CTX_DN</b>        | The fixed DN of the context to search for user roles. This is not the DN where the actual roles are, but the DN where the objects containing the user roles are. For example, in a Microsoft Active Directory server, this is the DN where the user account is. | <b><code>\${AUTH_LDAP_ROLES_CTX_DN}</code></b>        | False    |

| Variable name                   | Image Environment Variable      | Description   | Example value                         | Required |
|---------------------------------|---------------------------------|---|---------------------------------------|----------|
| <b>AUTH_LDAP_ROLE_FILTER</b>    | <b>AUTH_LDAP_ROLE_FILTER</b>    | A search filter used to locate the roles associated with the authenticated user. The input username or userDN obtained from the login module callback is substituted into the filter anywhere a {0} expression is used. The authenticated userDN is substituted into the filter anywhere a {1} is used. An example search filter that matches on the input username is (member={0}). An alternative that matches on the authenticated userDN is (member={1}). | <b>`\${AUTH_LDAP_ROLE_FILTER}`</b>    | False    |
| <b>AUTH_LDAP_ROLE_RECURSION</b> | <b>AUTH_LDAP_ROLE_RECURSION</b> | The number of levels of recursion the role search will go below a matching context. Disable recursion by setting this to 0.   | <b>`\${AUTH_LDAP_ROLE_RECURSION}`</b> | False    |
| <b>AUTH_LDAP_DEFAULT_ROLE</b>   | <b>AUTH_LDAP_DEFAULT_ROLE</b>   | A role included for all authenticated users   | <b>`\${AUTH_LDAP_DEFAULT_ROLE}`</b>   | False    |

| Variable name                            | Image Environment Variable               | Description   | Example value                                  | Required |
|--|--|---|--|----------|
| <b>AUTH_LDAP_ROLE_NAME_ATTRIBUTE_ID</b>  | <b>AUTH_LDAP_ROLE_NAME_ATTRIBUTE_ID</b>  | Name of the attribute within the roleCtxDN context which contains the role name. If the roleAttributesDN property is set to true, this property is used to find the role object's name attribute.   | <b>`\${AUTH_LDAP_ROLE_NAME_ATTRIBUTE_ID}`</b>  | False    |
| <b>AUTH_LDAP_PARSE_ROLE_NAME_FROM_DN</b> | <b>AUTH_LDAP_PARSE_ROLE_NAME_FROM_DN</b> | A flag indicating if the DN returned by a query contains the roleNameAttribute ID. If set to true, the DN is checked for the roleNameAttribute ID. If set to false, the DN is not checked for the roleNameAttribute ID. This flag can improve the performance of LDAP queries.                          | <b>`\${AUTH_LDAP_PARSE_ROLE_NAME_FROM_DN}`</b> | False    |
| <b>AUTH_LDAP_ROLE_ATTRIBUTE_IS_DN</b>    | <b>AUTH_LDAP_ROLE_ATTRIBUTE_IS_DN</b>    | Whether or not the roleAttributeID contains the fully-qualified DN of a role object. If false, the role name is taken from the value of the roleNameAttributeId attribute of the context name. Certain directory schemas, such as Microsoft Active Directory, require this attribute to be set to true. | <b>`\${AUTH_LDAP_ROLE_ATTRIBUTE_IS_DN}`</b>    | False    |



| Variable name  | Image Environment Variable                           | Description  | Example value   | Required |
|--|--|--|---|----------|
| <b>AUTH_LDAP_REFERRAL_USER_ATTRIBUTE_ID_TO_CHECK</b> | <b>AUTH_LDAP_REFERRAL_USER_ATTRIBUTE_ID_TO_CHECK</b> | If you are not using referrals, this option can be ignored. When using referrals, this option denotes the attribute name which contains users defined for a certain role, for example member, if the role object is inside the referral. Users are checked against the content of this attribute name. If this option is not set, the check will always fail, so role objects cannot be stored in a referral tree. | <b><code>\${AUTH_LDAP_REFERRAL_USER_ATTRIBUTE_ID_TO_CHECK}</code></b> | False    |

## 4.4.2. Objects

The CLI supports various object types. A list of these object types as well as their abbreviations can be found in the [Openshift documentation](#).

### 4.4.2.1. Services

A service is an abstraction which defines a logical set of pods and a policy by which to access them. Refer to the [container-engine documentation](#) for more information.

| Service   | Port | Name  | Description                            |
|---|------|-------|--|
| <b><code>\${APPLICATION_NAME}-kieserver</code></b>      | 8080 | http  | All the KIE server web server's ports. |
|   | 8443 | https |  |
| <b><code>\${APPLICATION_NAME}-kieserver-ping</code></b> | 8888 | ping  | The JGroups ping port for clustering.  |
| <b><code>\${APPLICATION_NAME}-mysql</code></b>          | 3306 | –     | The database server's port.            |

#### 4.4.2.2. Routes

A route is a way to expose a service by giving it an externally-reachable hostname such as **www.example.com**. A defined route and the endpoints identified by its service can be consumed by a router to provide named connectivity from external clients to your applications. Each route consists of a route name, service selector, and (optionally) security configuration. Refer to the [OpenShift documentation](#) for more information.

| Service                                     | Security        | Hostname                             |
|---|-----------------|--------------------------------------|
| <b>\${APPLICATION_NAME}-kieserver-http</b>  | none            | <b>\${KIE_SERVER_HOSTNAME_HTTP}</b>  |
| <b>\${APPLICATION_NAME}-kieserver-https</b> | TLS passthrough | <b>\${KIE_SERVER_HOSTNAME_HTTPS}</b> |

#### 4.4.2.3. Deployment Configurations

A deployment in OpenShift is a replication controller based on a user defined template called a deployment configuration. Deployments are created manually or in response to triggered events. Refer to the [OpenShift documentation](#) for more information.

##### 4.4.2.3.1. Triggers

A trigger drives the creation of new deployments in response to events, both inside and outside OpenShift. Refer to the [OpenShift documentation](#) for more information.

| Deployment                            | Triggers    |
|---------------------------------------|-------------|
| <b>\${APPLICATION_NAME}-kieserver</b> | ImageChange |
| <b>\${APPLICATION_NAME}-mysql</b>     | ImageChange |

##### 4.4.2.3.2. Replicas

A replication controller ensures that a specified number of pod "replicas" are running at any one time. If there are too many, the replication controller kills some pods. If there are too few, it starts more. Refer to the [container-engine documentation](#) for more information.

| Deployment                            | Replicas |
|---------------------------------------|----------|
| <b>\${APPLICATION_NAME}-kieserver</b> | 1        |
| <b>\${APPLICATION_NAME}-mysql</b>     | 1        |

##### 4.4.2.3.3. Pod Template

###### 4.4.2.3.3.1. Service Accounts

Service accounts are API objects that exist within each project. They can be created or deleted like any other API object. Refer to the [Openshift documentation](#) for more information.

| Deployment                            | Service Account                       |
|---------------------------------------|---------------------------------------|
| <b>\${APPLICATION_NAME}-kieserver</b> | <b>\${APPLICATION_NAME}-kieserver</b> |

#### 4.4.2.3.3.2. Image

| Deployment                            | Image                                   |
|---------------------------------------|---|
| <b>\${APPLICATION_NAME}-kieserver</b> | <b>\${KIE_SERVER_IMAGE_STREAM_NAME}</b> |
| <b>\${APPLICATION_NAME}-mysql</b>     | mysql                                   |

#### 4.4.2.3.3.3. Readiness Probe

##### **\${APPLICATION\_NAME}-kieserver**

```
/bin/bash -c curl --fail --silent -u '${KIE_ADMIN_USER}:${KIE_ADMIN_PWD}'
http://localhost:8080/services/rest/server/readycheck
```

##### **\${APPLICATION\_NAME}-mysql**

```
/bin/sh -i -c MYSQL_PWD="$MYSQL_PASSWORD" mysql -h 127.0.0.1 -u $MYSQL_USER -D
$MYSQL_DATABASE -e 'SELECT 1'
```

#### 4.4.2.3.3.4. Liveness Probe

##### **\${APPLICATION\_NAME}-kieserver**

```
/bin/bash -c curl --fail --silent -u '${KIE_ADMIN_USER}:${KIE_ADMIN_PWD}'
http://localhost:8080/services/rest/server/readycheck
```

#### 4.4.2.3.3.5. Exposed Ports

| Deployments                           | Name    | Port | Protocol   |
|---------------------------------------|---------|------|------------|
| <b>\${APPLICATION_NAME}-kieserver</b> | jolokia | 8778 | <b>TCP</b> |
|                                       | http    | 8080 | <b>TCP</b> |
|                                       | https   | 8443 | <b>TCP</b> |
|                                       | ping    | 8888 | <b>TCP</b> |

| Deployments                       | Name | Port | Protocol   |
|-----------------------------------|------|------|------------|
| <b>\${APPLICATION_NAME}-mysql</b> | –    | 3306 | <b>TCP</b> |

#### 4.4.2.3.3.6. Image Environment Variables

| Deployment                            | Variable name                       | Description  | Example value                           |
|---------------------------------------|-------------------------------------|--|---|
| <b>\${APPLICATION_NAME}-kieserver</b> | <b>DROOLS_SERVER_FILTER_CLASSES</b> | KIE server class filtering (Sets the org.drools.server.filter.classes system property)                           | <b>\${DROOLS_SERVER_FILTER_CLASSES}</b> |
|                                       | <b>KIE_ADMIN_USER</b>               | KIE administrator username   | <b>\${KIE_ADMIN_USER}</b>               |
|                                       | <b>KIE_ADMIN_PWD</b>                | KIE administrator password   | <b>\${KIE_ADMIN_PWD}</b>                |
|                                       | <b>KIE_MBEANS</b>                   | KIE server mbeans enabled/disabled (Sets the kie.mbeans and kie.scanner.mbeans system properties)                | <b>\${KIE_MBEANS}</b>                   |
|                                       | <b>KIE_SERVER_BYPASS_AUTH_USER</b>  | KIE server bypass auth user (Sets the org.kie.server.bypass.auth.user system property)                           | <b>\${KIE_SERVER_BYPASS_AUTH_USER}</b>  |
|                                       | <b>KIE_SERVER_CONTROLLER_USER</b>   | KIE server controller username (Sets the org.kie.server.controller.user system property)                         | <b>\${KIE_SERVER_CONTROLLER_USER}</b>   |
|                                       | <b>KIE_SERVER_CONTROLLER_PWD</b>    | KIE server controller password (Sets the org.kie.server.controller.pwd system property)                          | <b>\${KIE_SERVER_CONTROLLER_PWD}</b>    |
|                                       | <b>KIE_SERVER_CONTROLLER_TOKEN</b>  | KIE server controller token for bearer authentication (Sets the org.kie.server.controller.token system property) | <b>\${KIE_SERVER_CONTROLLER_TOKEN}</b>  |

| Deployment | Variable name                           | Description   | Example value                                 |
|------------|---|---|---|
|            | <b>KIE_SERVER_CONTROLLER_SERVICE</b>    | The service name for the optional business central monitor, where it can be reached to allow service lookup, and registered with to allow monitoring console functionality (If set, will be used to discover host and port) | <b>`\${KIE_SERVER_CONTROLLER_SERVICE}`</b>    |
|            | <b>KIE_SERVER_CONTROLLER_PROTOCOL</b>   | –   | ws  |
|            | <b>KIE_SERVER_CONTROLLER_HOST</b>       | KIE server controller host (Used to set the org.kie.server.controller system property)  | <b>`\${KIE_SERVER_CONTROLLER_HOST}`</b>       |
|            | <b>KIE_SERVER_CONTROLLER_PORT</b>       | KIE server controller port (Used to set the org.kie.server.controller system property)  | <b>`\${KIE_SERVER_CONTROLLER_PORT}`</b>       |
|            | <b>KIE_SERVER_ID</b>                    | –   | <b>`\${APPLICATION_NAME}-kieserver`</b>       |
|            | <b>KIE_SERVER_HOST</b>                  | Custom hostname for http service route, if set will also configure the KIE_SERVER_HOST. Leave blank for default hostname, e.g.:<br><application-name>-kieserver-<project>.<br><default-domain-suffix>                       | <b>`\${KIE_SERVER_HOSTNAME_HTTP}`</b>         |
|            | <b>KIE_SERVER_ROUTE_NAME</b>            | –   | <b>`\${APPLICATION_NAME}-kieserver`</b>       |
|            | <b>KIE_SERVER_USE_SECURE_ROUTE_NAME</b> | Use https for the KIE_SERVER_HOST when it is not explicit configured to a custom value.   | <b>`\${KIE_SERVER_USE_SECURE_ROUTE_NAME}`</b> |

| Deployment | Variable name                          | Description   | Example value                              |
|------------|--|---|--|
|            | <b>KIE_SERVER_USER</b>                 | KIE server username<br>(Sets the org.kie.server.user system property)                                       | <b>\${KIE_SERVER_USER}</b>                 |
|            | <b>KIE_SERVER_PWD</b>                  | KIE server password<br>(Sets the org.kie.server.pwd system property)  | <b>\${KIE_SERVER_PWD}</b>                  |
|            | <b>KIE_SERVER_CONTAINER_DEPLOYMENT</b> | KIE Server Container deployment configuration in format: containerId=groupId:artifactId:version c2=g2:a2:v2 | <b>\${KIE_SERVER_CONTAINER_DEPLOYMENT}</b> |
|            | <b>MAVEN_REPOS</b>                     | –   | RHPAMCENTR,EXTERNAL                        |
|            | <b>RHPAMCENTR_MAVEN_REPO_SERVICE</b>   | –   | <b>\${BUSINESS_CENTRAL_MAVEN_SERVICE}</b>  |
|            | <b>RHPAMCENTR_MAVEN_REPO_PATH</b>      | –   | <b>/maven2/</b>                            |
|            | <b>RHPAMCENTR_MAVEN_REPO_USERNAME</b>  | Username to access the Maven repository, if required.   | <b>\${BUSINESS_CENTRAL_MAVEN_USERNAME}</b> |
|            | <b>RHPAMCENTR_MAVEN_REPO_PASSWORD</b>  | Password to access the Maven repository, if required.   | <b>\${BUSINESS_CENTRAL_MAVEN_PASSWORD}</b> |
|            | <b>EXTERNAL_MAVEN_REPO_ID</b>          | The id to use for the maven repository, if set. Default is generated randomly.                              | <b>\${MAVEN_REPO_ID}</b>                   |
|            | <b>EXTERNAL_MAVEN_REPO_URL</b>         | Fully qualified URL to a Maven repository or service.   | <b>\${MAVEN_REPO_URL}</b>                  |
|            | <b>EXTERNAL_MAVEN_REPO_USERNAME</b>    | Username to access the Maven repository, if required.   | <b>\${MAVEN_REPO_USERNAME}</b>             |

| Deployment | Variable name                       | Description   | Example value                            |
|------------|-------------------------------------|---|--|
|            | <b>EXTERNAL_MAVEN_REPO_PASSWORD</b> | Password to access the Maven repository, if required.   | <b>`\${MAVEN_REPO_PASSWORD}`</b>         |
|            | <b>KIE_SERVER_ROUTER_SERVICE</b>    | The service name for the optional smart router, where it can be reached, to allow smart routing   | <b>`\${KIE_SERVER_ROUTER_SERVICE}`</b>   |
|            | <b>KIE_SERVER_ROUTER_HOST</b>       | The host name of the smart router, which could be the service name resolved by OpenShift or a globally resolvable domain name                                   | <b>`\${KIE_SERVER_ROUTER_HOST}`</b>      |
|            | <b>KIE_SERVER_ROUTER_PORT</b>       | Port in which the smart router server listens (router property org.kie.server.router.port)  | <b>`\${KIE_SERVER_ROUTER_PORT}`</b>      |
|            | <b>KIE_SERVER_ROUTER_PROTOCOL</b>   | KIE server router protocol (Used to build the org.kie.server.router.url.external property)  | <b>`\${KIE_SERVER_ROUTER_PROTOCOL}`</b>  |
|            | <b>KIE_SERVER_MGMT_DISABLED</b>     | When set to LocalContainersStartupStrategy, allows KIE server to start up and function with local config, even when a controller is configured and unavailable. | <b>`\${KIE_SERVER_MGMT_DISABLED}`</b>    |
|            | <b>KIE_SERVER_STARTUP_STRATEGY</b>  | When set to LocalContainersStartupStrategy, allows KIE server to start up and function with local config, even when a controller is configured and unavailable. | <b>`\${KIE_SERVER_STARTUP_STRATEGY}`</b> |
|            | <b>KIE_SERVER_PERSISTENCE_DS</b>    | KIE server persistence datasource (Sets the org.kie.server.persistence.ds system property)  | <b>`\${KIE_SERVER_PERSISTENCE_DS}`</b>   |

| Deployment | Variable name                                    | Description  | Example value  |
|------------|--|--|--|
|            | <b>DATASOURCES</b>                               | –  | <b>RHPAM</b>   |
|            | <b>RHPAM_JNDI</b>                                | –  | <b>\${KIE_SERVER_PERSISTENCE_DS}</b>                 |
|            | <b>RHPAM_DATABASE</b>                            | –  | <b>\${KIE_SERVER_MYSQL_DB}</b>                       |
|            | <b>RHPAM_DRIVER</b>                              | –  | mysql  |
|            | <b>KIE_SERVER_PERSISTENCE_DIALECT</b>            | –  | org.hibernate.dialect.MySQL5Dialect                  |
|            | <b>RHPAM_USERNAME</b>                            | –  | <b>\${KIE_SERVER_MYSQL_USER}</b>                     |
|            | <b>RHPAM_PASSWORD</b>                            | –  | <b>\${KIE_SERVER_MYSQL_PWD}</b>                      |
|            | <b>RHPAM_SERVICE_HOST</b>                        | –  | <b>\${APPLICATION_NAME}-mysql</b>                    |
|            | <b>RHPAM_SERVICE_PORT</b>                        | –  | 3306   |
|            | <b>TIMER_SERVICE_DATA_STORE</b>                  | Sets refresh-interval for the EJB timer database data-store service. | <b>\${APPLICATION_NAME}-mysql</b>                    |
|            | <b>RHPAM_JTA</b>                                 | –  | true   |
|            | <b>TIMER_SERVICE_DATA_STORE_REFRESH_INTERVAL</b> | Sets refresh-interval for the EJB timer database data-store service. | <b>\${TIMER_SERVICE_DATA_STORE_REFRESH_INTERVAL}</b> |
|            | <b>HTTPS_KEYSTORE_DIR</b>                        | –  | <b>/etc/kieserver-secret-volume</b>                  |
|            | <b>HTTPS_KEYSTORE</b>                            | The name of the keystore file within the secret                      | <b>\${KIE_SERVER_HTTPS_KEYSTORE}</b>                 |
|            | <b>HTTPS_NAME</b>                                | The name associated with the server certificate                      | <b>\${KIE_SERVER_HTTPS_NAME}</b>                     |



| Deployment | Variable name                                 | Description   | Example value                                       |
|------------|---|---|---|
|            | <b>HTTPS_PASSWORD</b>                         | The password for the keystore and certificate                             | <b>`\${KIE_SERVER_HTTPS_PASSWORD}`</b>              |
|            | <b>JGROUPS_PING_PROTOCOL</b>                  | –   | openshift.DNS_PING                                  |
|            | <b>OPENSIFT_DNS_PING_SERVICE_NAME</b>         | –   | <b>`\${APPLICATION_NAME}-kieserver-ping`</b>        |
|            | <b>OPENSIFT_DNS_PING_SERVICE_PORT</b>         | –   | 8888  |
|            | <b>SSO_URL</b>                                | RH-SSO URL  | <b>`\${SSO_URL}`</b>                                |
|            | <b>SSO_OPENIDCONNECT_DEPLOYMENTS</b>          | –   | ROOT.war  |
|            | <b>SSO_REALM</b>                              | RH-SSO Realm name   | <b>`\${SSO_REALM}`</b>                              |
|            | <b>SSO_SECRET</b>                             | KIE Server RH-SSO Client Secret   | <b>`\${KIE_SERVER_SSO_SECRET}`</b>                  |
|            | <b>SSO_CLIENT</b>                             | KIE Server RH-SSO Client name   | <b>`\${KIE_SERVER_SSO_CLIENT}`</b>                  |
|            | <b>SSO_USERNAME</b>                           | RH-SSO Realm Admin Username used to create the Client if it doesn't exist | <b>`\${SSO_USERNAME}`</b>                           |
|            | <b>SSO_PASSWORD</b>                           | RH-SSO Realm Admin Password used to create the Client                     | <b>`\${SSO_PASSWORD}`</b>                           |
|            | <b>SSO_DISABLE_SSL_CERTIFICATE_VALIDATION</b> | RH-SSO Disable SSL Certificate Validation                                 | <b>`\${SSO_DISABLE_SSL_CERTIFICATE_VALIDATION}`</b> |
|            | <b>SSO_PRINCIPAL_ATTRIBUTE</b>                | RH-SSO Principal Attribute to use as username.                            | <b>`\${SSO_PRINCIPAL_ATTRIBUTE}`</b>                |

| Deployment | Variable name                         | Description  | Example value                             |
|------------|---------------------------------------|--|---|
|            | <b>HOSTNAME_HTTP</b>                  | Custom hostname for http service route, if set will also configure the KIE_SERVER_HOST. Leave blank for default hostname, e.g.: <application-name>-kieserver-<project>. <default-domain-suffix>  | <b>\${KIE_SERVER_HOSTNAME_HTTP}</b>       |
|            | <b>HOSTNAME_HTTPS</b>                 | Custom hostname for https service route. Leave blank for default hostname, e.g.: secure-<application-name>-kieserver-<project>. <default-domain-suffix>  | <b>\${KIE_SERVER_HOSTNAME_HTTPS}</b>      |
|            | <b>AUTH_LDAP_URL</b>                  | LDAP Endpoint to connect for authentication  | <b>\${AUTH_LDAP_URL}</b>                  |
|            | <b>AUTH_LDAP_BIND_DN</b>              | Bind DN used for authentication  | <b>\${AUTH_LDAP_BIND_DN}</b>              |
|            | <b>AUTH_LDAP_BIND_CREDENTIAL</b>      | LDAP Credentials used for authentication   | <b>\${AUTH_LDAP_BIND_CREDENTIAL}</b>      |
|            | <b>AUTH_LDAP_JAAS_SECURITY_DOMAIN</b> | The JMX ObjectName of the JaasSecurityDomain used to decrypt the password.   | <b>\${AUTH_LDAP_JAAS_SECURITY_DOMAIN}</b> |
|            | <b>AUTH_LDAP_BASE_CTX_DN</b>          | LDAP Base DN of the top-level context to begin the user search.  | <b>\${AUTH_LDAP_BASE_CTX_DN}</b>          |
|            | <b>AUTH_LDAP_BASE_FILTER</b>          | LDAP search filter used to locate the context of the user to authenticate. The input username or userDN obtained from the login module callback is substituted into the filter anywhere a {0} expression is used. A common example for the search filter is (uid={0}). | <b>\${AUTH_LDAP_BASE_FILTER}</b>          |

| Deployment | Variable name                                 | Description  | Example value                                       |
|------------|---|--|---|
|            | <b>AUTH_LDAP_SEARCH_SCOPE</b>                 | The search scope to use.   | <b>`\${AUTH_LDAP_SEARCH_SCOPE}`</b>                 |
|            | <b>AUTH_LDAP_SEARCH_TIME_LIMIT</b>            | The timeout in milliseconds for user or role searches.   | <b>`\${AUTH_LDAP_SEARCH_TIME_LIMIT}`</b>            |
|            | <b>AUTH_LDAP_DISTINGUISHED_NAME_ATTRIBUTE</b> | The name of the attribute in the user entry that contains the DN of the user. This may be necessary if the DN of the user itself contains special characters, backslash for example, that prevent correct user mapping. If the attribute does not exist, the entry's DN is used. | <b>`\${AUTH_LDAP_DISTINGUISHED_NAME_ATTRIBUTE}`</b> |
|            | <b>AUTH_LDAP_PARSE_USERNAME</b>               | A flag indicating if the DN is to be parsed for the username. If set to true, the DN is parsed for the username. If set to false the DN is not parsed for the username. This option is used together with <code>usernameBeginString</code> and <code>usernameEndString</code> .  | <b>`\${AUTH_LDAP_PARSE_USERNAME}`</b>               |
|            | <b>AUTH_LDAP_USERNAME_BEGIN_STRING</b>        | Defines the String which is to be removed from the start of the DN to reveal the username. This option is used together with <code>usernameEndString</code> and only taken into account if <code>parseUsername</code> is set to true.  | <b>`\${AUTH_LDAP_USERNAME_BEGIN_STRING}`</b>        |

| Deployment | Variable name                         | Description   | Example value  |
|------------|---------------------------------------|---|--|
|            | <b>AUTH_LDAP_USER_NAME_END_STRING</b> | Defines the String which is to be removed from the end of the DN to reveal the username. This option is used together with <code>usernameEndString</code> and only taken into account if <code>parseUsername</code> is set to true.   | <b><code>\${AUTH_LDAP_USER_NAME_END_STRING}</code></b> |
|            | <b>AUTH_LDAP_ROLE_ATTRIBUTE_ID</b>    | Name of the attribute containing the user roles.  | <b><code>\${AUTH_LDAP_ROLE_ATTRIBUTE_ID}</code></b>    |
|            | <b>AUTH_LDAP_ROLE_S_CTX_DN</b>        | The fixed DN of the context to search for user roles. This is not the DN where the actual roles are, but the DN where the objects containing the user roles are. For example, in a Microsoft Active Directory server, this is the DN where the user account is.   | <b><code>\${AUTH_LDAP_ROLE_S_CTX_DN}</code></b>        |
|            | <b>AUTH_LDAP_ROLE_FILTER</b>          | A search filter used to locate the roles associated with the authenticated user. The input username or userDN obtained from the login module callback is substituted into the filter anywhere a <code>{0}</code> expression is used. The authenticated userDN is substituted into the filter anywhere a <code>{1}</code> is used. An example search filter that matches on the input username is <code>(member={0})</code> . An alternative that matches on the authenticated userDN is <code>(member={1})</code> . | <b><code>\${AUTH_LDAP_ROLE_FILTER}</code></b>          |

| Deployment | Variable name                            | Description   | Example value                                  |
|------------|--|---|--|
|            | <b>AUTH_LDAP_ROLE_RECURSION</b>          | The number of levels of recursion the role search will go below a matching context. Disable recursion by setting this to 0.   | <b>`\${AUTH_LDAP_ROLE_RECURSION}`</b>          |
|            | <b>AUTH_LDAP_DEFAULT_ROLE</b>            | A role included for all authenticated users   | <b>`\${AUTH_LDAP_DEFAULT_ROLE}`</b>            |
|            | <b>AUTH_LDAP_ROLE_NAME_ATTRIBUTE_ID</b>  | Name of the attribute within the roleCtxDN context which contains the role name. If the roleAttributesDN property is set to true, this property is used to find the role object's name attribute.   | <b>`\${AUTH_LDAP_ROLE_NAME_ATTRIBUTE_ID}`</b>  |
|            | <b>AUTH_LDAP_PARSE_ROLE_NAME_FROM_DN</b> | A flag indicating if the DN returned by a query contains the roleNameAttributeID. If set to true, the DN is checked for the roleNameAttributeID. If set to false, the DN is not checked for the roleNameAttributeID. This flag can improve the performance of LDAP queries.                             | <b>`\${AUTH_LDAP_PARSE_ROLE_NAME_FROM_DN}`</b> |
|            | <b>AUTH_LDAP_ROLE_ATTRIBUTE_IS_DN</b>    | Whether or not the roleAttributeID contains the fully-qualified DN of a role object. If false, the role name is taken from the value of the roleNameAttributeID attribute of the context name. Certain directory schemas, such as Microsoft Active Directory, require this attribute to be set to true. | <b>`\${AUTH_LDAP_ROLE_ATTRIBUTE_IS_DN}`</b>    |

| Deployment                        | Variable name  | Description  | Example value  |
|-----------------------------------|--|--|--|
|                                   | <b>AUTH_LDAP_REFERRAL_USER_ATTRIBUTE_ID_TO_CHECK</b> | If you are not using referrals, this option can be ignored. When using referrals, this option denotes the attribute name which contains users defined for a certain role, for example member, if the role object is inside the referral. Users are checked against the content of this attribute name. If this option is not set, the check will always fail, so role objects cannot be stored in a referral tree. | <b>\${AUTH_LDAP_REFERRAL_USER_ATTRIBUTE_ID_TO_CHECK}</b> |
| <b>\${APPLICATION_NAME}-mysql</b> | <b>MYSQL_USER</b>                                    | KIE server MySQL database username   | <b>\${KIE_SERVER_MYSQL_USER}</b>                         |
|                                   | <b>MYSQL_PASSWORD</b>                                | –  | <b>\${KIE_SERVER_MYSQL_PWD}</b>                          |
|                                   | <b>MYSQL_DATABASE</b>                                | –  | <b>\${KIE_SERVER_MYSQL_DB}</b>                           |

#### 4.4.2.3.3.7. Volumes

| Deployment                            | Name                                   | mountPath                           | Purpose   | readOnly |
|---------------------------------------|--|-------------------------------------|-----------|----------|
| <b>\${APPLICATION_NAME}-kieserver</b> | kieserver-keystore-volume              | <b>/etc/kieserver-secret-volume</b> | ssl certs | True     |
| <b>\${APPLICATION_NAME}-mysql</b>     | <b>\${APPLICATION_NAME}-mysql-pvol</b> | <b>/var/lib/mysql/data</b>          | mysql     | false    |

#### 4.4.2.4. External Dependencies

##### 4.4.2.4.1. Volume Claims

A **PersistentVolume** object is a storage resource in an OpenShift cluster. Storage is provisioned by an administrator by creating **PersistentVolume** objects from sources such as GCE Persistent Disks, AWS Elastic Block Stores (EBS), and NFS mounts. Refer to the [OpenShift documentation](#) for more information.

| Name  | Access Mode   |
|---|---------------|
| <code>\${APPLICATION_NAME}-mysql-claim</code> | ReadWriteOnce |

#### 4.4.2.4.2. Secrets

This template requires the following secrets to be installed for the application to run.

kieserver-app-secret

## 4.5. RHPAM71-KIESERVER-POSTGRESQL

Application template for a managed KIE Server with a PostgreSQL database, for Red Hat Process Automation Manager 7.1

### 4.5.1. Parameters

Templates allow you to define parameters which take on a value. That value is then substituted wherever the parameter is referenced. References can be defined in any text field in the objects list field. Refer to the [Openshift documentation](#) for more information.

| Variable name              | Image Environment Variable              | Description  | Example value                              | Required |
|----------------------------|---|--|--|----------|
| <b>APPLICATION_NAME</b>    | –                                       | The name for the application.  | myapp                                      | True     |
| <b>MAVEN_REPO_ID</b>       | <b>EXTERNAL_MAVEN_REPO_ID</b>           | The id to use for the maven repository, if set. Default is generated randomly. | <b>\${MAVEN_REPO_ID}</b>                   | False    |
| <b>MAVEN_REPO_URL</b>      | <b>EXTERNAL_MAVEN_REPO_URL</b>          | Fully qualified URL to a Maven repository or service.                          | <b>\${MAVEN_REPO_URL}</b>                  | True     |
| <b>MAVEN_REPO_USERNAME</b> | <b>RHPAMCENTRAL_MAVEN_REPO_USERNAME</b> | Username to access the Maven repository, if required.                          | <b>\${BUSINESS_CENTRAL_MAVEN_USERNAME}</b> | False    |
| <b>MAVEN_REPO_PASSWORD</b> | <b>RHPAMCENTRAL_MAVEN_REPO_PASSWORD</b> | Password to access the Maven repository, if required.                          | <b>\${BUSINESS_CENTRAL_MAVEN_PASSWORD}</b> | False    |

| Variable name                          | Image Environment Variable | Description   | Example value                  | Required |
|--|----------------------------|---|--------------------------------|----------|
| <b>BUSINESS_CENTRAL_MAVEN_SERVICE</b>  | –                          | The service name for the optional business central, where it can be reached, to allow service lookups (for maven repo usage), if required | –                              | False    |
| <b>BUSINESS_CENTRAL_MAVEN_USERNAME</b> | –                          | Username to access the Maven service hosted by Business Central inside EAP.   | –                              | False    |
| <b>BUSINESS_CENTRAL_MAVEN_PASSWORD</b> | –                          | Password to access the Maven service hosted by Business Central inside EAP.   | –                              | False    |
| <b>KIE_ADMIN_USER</b>                  | <b>KIE_ADMIN_USER</b>      | KIE administrator username  | adminUser                      | False    |
| <b>KIE_ADMIN_PASSWORD</b>              | <b>KIE_ADMIN_PASSWORD</b>  | KIE administrator password  | <b>\${KIE_ADMIN_PASSWORD}</b>  | False    |
| <b>KIE_SERVER_USER</b>                 | <b>KIE_SERVER_USER</b>     | KIE server username (Sets the org.kie.server.user system property)  | executionUser                  | False    |
| <b>KIE_SERVER_PASSWORD</b>             | <b>KIE_SERVER_PASSWORD</b> | KIE server password (Sets the org.kie.server.pwd system property)   | <b>\${KIE_SERVER_PASSWORD}</b> | False    |



| Variable name                       | Image Environment Variable       | Description   | Example value                          | Required |
|-------------------------------------|----------------------------------|---|--|----------|
| <b>IMAGE_STREAM_NAMESPACE</b>       | –                                | Namespace in which the ImageStreams for Red Hat Middleware images are installed. These ImageStreams are normally installed in the openshift namespace. You should only need to modify this if you've installed the ImageStreams in a different namespace/project. | openshift                              | True     |
| <b>KIE_SERVER_IMAGE_STREAM_NAME</b> | –                                | The name of the image stream to use for KIE server. Default is "rhpam71-kieserver-openshift".   | rhpam71-kieserver-openshift            | True     |
| <b>IMAGE_STREAM_TAG</b>             | –                                | A named pointer to an image in an image stream. Default is "1.1".   | 1.1                                    | True     |
| <b>KIE_SERVER_ROUTER_SERVICE</b>    | <b>KIE_SERVER_ROUTER_SERVICE</b> | The service name for the optional smart router, where it can be reached, to allow smart routing   | <b>`\${KIE_SERVER_ROUTER_SERVICE}`</b> | False    |
| <b>KIE_SERVER_ROUTER_HOST</b>       | <b>KIE_SERVER_ROUTER_HOST</b>    | The host name of the smart router, which could be the service name resolved by OpenShift or a globally resolvable domain name   | <b>`\${KIE_SERVER_ROUTER_HOST}`</b>    | False    |

| Variable name                         | Image Environment Variable            | Description  | Example value                               | Required |
|---------------------------------------|---------------------------------------|--|---|----------|
| <b>KIE_SERVER_ROUTER_PORT</b>         | <b>KIE_SERVER_ROUTER_PORT</b>         | Port in which the smart router server listens (router property org.kie.server.router.port)                       | <b>`\${KIE_SERVER_ROUTER_PORT}`</b>         | False    |
| <b>KIE_SERVER_ROUTER_PROTOCOL</b>     | <b>KIE_SERVER_ROUTER_PROTOCOL</b>     | KIE server router protocol (Used to build the org.kie.server.router.url.external property)                       | <b>`\${KIE_SERVER_ROUTER_PROTOCOL}`</b>     | False    |
| <b>KIE_SERVER_CONTROLLER_USER</b>     | <b>KIE_SERVER_CONTROLLER_USER</b>     | KIE server controller username (Sets the org.kie.server.controller.user system property)                         | controllerUser                              | False    |
| <b>KIE_SERVER_CONTROLLER_PASSWORD</b> | <b>KIE_SERVER_CONTROLLER_PASSWORD</b> | KIE server controller password (Sets the org.kie.server.controller.pwd system property)                          | <b>`\${KIE_SERVER_CONTROLLER_PASSWORD}`</b> | False    |
| <b>KIE_SERVER_CONTROLLER_TOKEN</b>    | <b>KIE_SERVER_CONTROLLER_TOKEN</b>    | KIE server controller token for bearer authentication (Sets the org.kie.server.controller.token system property) | <b>`\${KIE_SERVER_CONTROLLER_TOKEN}`</b>    | False    |

| Variable name                         | Image Environment Variable           | Description   | Example value                              | Required |
|---------------------------------------|--------------------------------------|---|--|----------|
| <b>KIE_SERVER_CONTROLLER_SERVICE</b>  | <b>KIE_SERVER_CONTROLLER_SERVICE</b> | The service name for the optional business central monitor, where it can be reached to allow service lookup, and registered with to allow monitoring console functionality (If set, will be used to discover host and port) | <b>`\${KIE_SERVER_CONTROLLER_SERVICE}`</b> | False    |
| <b>KIE_SERVER_CONTROLLER_HOST</b>     | <b>KIE_SERVER_CONTROLLER_HOST</b>    | KIE server controller host (Used to set the org.kie.server.controller.system property)  | <b>`\${KIE_SERVER_CONTROLLER_HOST}`</b>    | False    |
| <b>KIE_SERVER_CONTROLLER_PORT</b>     | <b>KIE_SERVER_CONTROLLER_PORT</b>    | KIE server controller port (Used to set the org.kie.server.controller.system property)  | <b>`\${KIE_SERVER_CONTROLLER_PORT}`</b>    | False    |
| <b>KIE_SERVER_PERSISTENCE_DS</b>      | <b>KIE_SERVER_PERSISTENCE_DS</b>     | KIE server persistence datasource (Sets the org.kie.server.persistence.ds system property)  | java:/jboss/datasources/rhpam              | False    |
| <b>KIE_SERVER_POSTGRESQL_USER</b>     | <b>POSTGRESQL_USER</b>               | KIE server PostgreSQL database username   | rhpam                                      | False    |
| <b>KIE_SERVER_POSTGRESQL_PASSWORD</b> | –                                    | KIE server PostgreSQL database password   | –  | False    |

| Variable name                               | Image Environment Variable                  | Description  | Example value | Required |
|---|---|--|---------------|----------|
| <b>KIE_SERVER_POSTGRESQL_DATABASE</b>       | –   | KIE server PostgreSQL database name  | rh pam7       | False    |
| <b>POSTGRESQL_IMAGE_STREAM_NAMESPACE</b>    | –   | Namespace in which the ImageStream for the PostgreSQL image is installed. The ImageStream is already installed in the openshift namespace. You should only need to modify this if you've installed the ImageStream in a different namespace/project. Default is "openshift". | openshift     | False    |
| <b>POSTGRESQL_IMAGE_STREAM_TAG</b>          | –   | The PostgreSQL image version, which is intended to correspond to the PostgreSQL version. Default is "9.6".   | 9.6           | False    |
| <b>POSTGRESQL_MAX_PREPARED_TRANSACTIONS</b> | <b>POSTGRESQL_MAX_PREPARED_TRANSACTIONS</b> | Allows the PostgreSQL to handle XA transactions.   | 100           | True     |
| <b>DB_VOLUME_CAPACITY</b>                   | –   | Size of persistent storage for database volume.  | 1Gi           | True     |
| <b>DROOLS_SERVER_FILTER_CLASSES</b>         | <b>DROOLS_SERVER_FILTER_CLASSES</b>         | KIE server class filtering (Sets the org.drools.server.filter.classes system property)   | true          | False    |

| Variable name                           | Image Environment Variable              | Description  | Example value                          | Required |
|---|---|--|--|----------|
| <b>KIE_MBEANS</b>                       | <b>KIE_MBEANS</b>                       | KIE server mbeans enabled/disabled (Sets the kie.mbeans and kie.scanner.mbeans system properties)  | enabled                                | False    |
| <b>KIE_SERVER_HOSTNAME_HTTP</b>         | <b>KIE_SERVER_HOST</b>                  | Custom hostname for http service route, if set will also configure the KIE_SERVER_HOST. Leave blank for default hostname, e.g.: <application-name>-kieserver-<project>.<default-domain-suffix> | <b>`\${KIE_SERVER_HOSTNAME_HTTP}`</b>  | False    |
| <b>KIE_SERVER_HOSTNAME_HTTPS</b>        | <b>KIE_SERVER_HOST</b>                  | Custom hostname for https service route. Leave blank for default hostname, e.g.: secure-<application-name>-kieserver-<project>.<default-domain-suffix>   | <b>`\${KIE_SERVER_HOSTNAME_HTTPS}`</b> | False    |
| <b>KIE_SERVER_USE_SECURE_ROUTE_NAME</b> | <b>KIE_SERVER_USE_SECURE_ROUTE_NAME</b> | Use https for the KIE_SERVER_HOST when it is not explicit configured to a custom value.  | false                                  | False    |
| <b>KIE_SERVER_HTTPS_SECRET</b>          | –                                       | The name of the secret containing the keystore file  | –                                      | True     |
| <b>KIE_SERVER_HTTPS_KEYSTORE</b>        | <b>HTTPS_KEYSTORE</b>                   | The name of the keystore file within the secret  | keystore.jks                           | False    |

| Variable name                                    | Image Environment Variable             | Description  | Example value                              | Required |
|--|--|--|--|----------|
| <b>KIE_SERVER_HTTPS_NAME</b>                     | <b>HTTPS_NAME</b>                      | The name associated with the server certificate  | jboss                                      | False    |
| <b>KIE_SERVER_HTTPS_PASSWORD</b>                 | <b>HTTPS_PASSWORD</b>                  | The password for the keystore and certificate  | mykeystorepass                             | False    |
| <b>KIE_SERVER_BYPASS_AUTH_USER</b>               | <b>KIE_SERVER_BYPASS_AUTH_USER</b>     | KIE server bypass auth user (Sets the org.kie.server.bypass.auth.user system property)   | false                                      | False    |
| <b>TIMER_SERVICE_DATA_STORE_REFRESH_INTERVAL</b> | <b>TIMER_SERVICE_DATA_STORE</b>        | Sets refresh-interval for the EJB timer database data-store service.   | 30000                                      | False    |
| <b>KIE_SERVER_MEMORY_LIMIT</b>                   | –                                      | KIE server Container memory limit  | 1Gi  | False    |
| <b>KIE_SERVER_CONTAINER_DEPLOYMENT</b>           | <b>KIE_SERVER_CONTAINER_DEPLOYMENT</b> | KIE Server Container deployment configuration in format:<br>containerId=groupId:artifactId:version c2=g2:a2:v2   | <b>\${KIE_SERVER_CONTAINER_DEPLOYMENT}</b> | False    |
| <b>KIE_SERVER_MGMT_DISABLED</b>                  | <b>KIE_SERVER_MGMT_DISABLED</b>        | When set to LocalContainersStartupStrategy, allows KIE server to start up and function with local config, even when a controller is configured and unavailable | <b>\${KIE_SERVER_MGMT_DISABLED}</b>        | False    |

| Variable name                                 | Image Environment Variable                    | Description   | Example value                            | Required |
|---|---|---|--|----------|
| <b>KIE_SERVER_STARTUP_STRATEGY</b>            | <b>KIE_SERVER_STARTUP_STRATEGY</b>            | When set to LocalContainersStartupStrategy, allows KIE server to start up and function with local config, even when a controller is configured and unavailable. | <b>`\${KIE_SERVER_STARTUP_STRATEGY}`</b> | False    |
| <b>SSO_URL</b>                                | <b>SSO_URL</b>                                | RH-SSO URL  | <b>`\${SSO_URL}`</b>                     | False    |
| <b>SSO_REALM</b>                              | <b>SSO_REALM</b>                              | RH-SSO Realm name   | <b>`\${SSO_REALM}`</b>                   | False    |
| <b>KIE_SERVER_SSO_CLIENT</b>                  | <b>SSO_CLIENT</b>                             | KIE Server RH-SSO Client name   | <b>`\${KIE_SERVER_SSO_CLIENT}`</b>       | False    |
| <b>KIE_SERVER_SSO_SECRET</b>                  | <b>SSO_SECRET</b>                             | KIE Server RH-SSO Client Secret   | <b>`\${KIE_SERVER_SSO_SECRET}`</b>       | False    |
| <b>SSO_USERNAME</b>                           | <b>SSO_USERNAME</b>                           | RH-SSO Realm Admin Username used to create the Client if it doesn't exist   | <b>`\${SSO_USERNAME}`</b>                | False    |
| <b>SSO_PASSWORD</b>                           | <b>SSO_PASSWORD</b>                           | RH-SSO Realm Admin Password used to create the Client   | <b>`\${SSO_PASSWORD}`</b>                | False    |
| <b>SSO_DISABLE_SSL_CERTIFICATE_VALIDATION</b> | <b>SSO_DISABLE_SSL_CERTIFICATE_VALIDATION</b> | RH-SSO Disable SSL Certificate Validation   | false                                    | False    |
| <b>SSO_PRINCIPAL_ATTRIBUTE</b>                | <b>SSO_PRINCIPAL_ATTRIBUTE</b>                | RH-SSO Principal Attribute to use as username.  | preferred_username                       | False    |
| <b>AUTH_LDAP_URL</b>                          | <b>AUTH_LDAP_URL</b>                          | LDAP Endpoint to connect for authentication   | <b>`\${AUTH_LDAP_URL}`</b>               | False    |

| Variable name                         | Image Environment Variable            | Description  | Example value                             | Required |
|---------------------------------------|---------------------------------------|--|---|----------|
| <b>AUTH_LDAP_BIND_DN</b>              | <b>AUTH_LDAP_BIND_DN</b>              | Bind DN used for authentication  | <b>\${AUTH_LDAP_BIND_DN}</b>              | False    |
| <b>AUTH_LDAP_BIND_CREDENTIAL</b>      | <b>AUTH_LDAP_BIND_CREDENTIAL</b>      | LDAP Credentials used for authentication   | <b>\${AUTH_LDAP_BIND_CREDENTIAL}</b>      | False    |
| <b>AUTH_LDAP_JAAS_SECURITY_DOMAIN</b> | <b>AUTH_LDAP_JAAS_SECURITY_DOMAIN</b> | The JMX ObjectName of the JaasSecurityDomain used to decrypt the password.   | <b>\${AUTH_LDAP_JAAS_SECURITY_DOMAIN}</b> | False    |
| <b>AUTH_LDAP_BASE_CTX_DN</b>          | <b>AUTH_LDAP_BASE_CTX_DN</b>          | LDAP Base DN of the top-level context to begin the user search.  | <b>\${AUTH_LDAP_BASE_CTX_DN}</b>          | False    |
| <b>AUTH_LDAP_BASE_FILTER</b>          | <b>AUTH_LDAP_BASE_FILTER</b>          | LDAP search filter used to locate the context of the user to authenticate. The input username or userDN obtained from the login module callback is substituted into the filter anywhere a {0} expression is used. A common example for the search filter is (uid={0}). | <b>\${AUTH_LDAP_BASE_FILTER}</b>          | False    |
| <b>AUTH_LDAP_SEARCH_SCOPE</b>         | <b>AUTH_LDAP_SEARCH_SCOPE</b>         | The search scope to use.   | <b>\${AUTH_LDAP_SEARCH_SCOPE}</b>         | False    |
| <b>AUTH_LDAP_SEARCH_TIME_LIMIT</b>    | <b>AUTH_LDAP_SEARCH_TIME_LIMIT</b>    | The timeout in milliseconds for user or role searches.   | <b>\${AUTH_LDAP_SEARCH_TIME_LIMIT}</b>    | False    |



| Variable name                                 | Image Environment Variable                    | Description  | Example value                                       | Required |
|---|---|--|---|----------|
| <b>AUTH_LDAP_DISTINGUISHED_NAME_ATTRIBUTE</b> | <b>AUTH_LDAP_DISTINGUISHED_NAME_ATTRIBUTE</b> | The name of the attribute in the user entry that contains the DN of the user. This may be necessary if the DN of the user itself contains special characters, backslash for example, that prevent correct user mapping. If the attribute does not exist, the entry's DN is used. | <b>`\${AUTH_LDAP_DISTINGUISHED_NAME_ATTRIBUTE}`</b> | False    |
| <b>AUTH_LDAP_PARSE_USERNAME</b>               | <b>AUTH_LDAP_PARSE_USERNAME</b>               | A flag indicating if the DN is to be parsed for the username. If set to true, the DN is parsed for the username. If set to false the DN is not parsed for the username. This option is used together with <code>usernameBeginString</code> and <code>usernameEndString</code> .  | <b>`\${AUTH_LDAP_PARSE_USERNAME}`</b>               | False    |
| <b>AUTH_LDAP_USERNAME_BEGIN_STRING</b>        | <b>AUTH_LDAP_USERNAME_BEGIN_STRING</b>        | Defines the String which is to be removed from the start of the DN to reveal the username. This option is used together with <code>usernameEndString</code> and only taken into account if <code>parseUsername</code> is set to true.  | <b>`\${AUTH_LDAP_USERNAME_BEGIN_STRING}`</b>        | False    |

| Variable name                        | Image Environment Variable           | Description   | Example value   | Required |
|--------------------------------------|--------------------------------------|---|---|----------|
| <b>AUTH_LDAP_USERNAME_END_STRING</b> | <b>AUTH_LDAP_USERNAME_END_STRING</b> | Defines the String which is to be removed from the end of the DN to reveal the username. This option is used together with <code>usernameEndString</code> and only taken into account if <code>parseUsername</code> is set to true.                             | <b><code>\${AUTH_LDAP_USERNAME_END_STRING}</code></b> | False    |
| <b>AUTH_LDAP_ROLE_ATTRIBUTE_ID</b>   | <b>AUTH_LDAP_ROLE_ATTRIBUTE_ID</b>   | Name of the attribute containing the user roles.  | <b><code>\${AUTH_LDAP_ROLE_ATTRIBUTE_ID}</code></b>   | False    |
| <b>AUTH_LDAP_ROLES_CTX_DN</b>        | <b>AUTH_LDAP_ROLES_CTX_DN</b>        | The fixed DN of the context to search for user roles. This is not the DN where the actual roles are, but the DN where the objects containing the user roles are. For example, in a Microsoft Active Directory server, this is the DN where the user account is. | <b><code>\${AUTH_LDAP_ROLES_CTX_DN}</code></b>        | False    |

| Variable name                   | Image Environment Variable      | Description   | Example value                         | Required |
|---------------------------------|---------------------------------|---|---------------------------------------|----------|
| <b>AUTH_LDAP_ROLE_FILTER</b>    | <b>AUTH_LDAP_ROLE_FILTER</b>    | A search filter used to locate the roles associated with the authenticated user. The input username or userDN obtained from the login module callback is substituted into the filter anywhere a {0} expression is used. The authenticated userDN is substituted into the filter anywhere a {1} is used. An example search filter that matches on the input username is (member={0}). An alternative that matches on the authenticated userDN is (member={1}). | <b>`\${AUTH_LDAP_ROLE_FILTER}`</b>    | False    |
| <b>AUTH_LDAP_ROLE_RECURSION</b> | <b>AUTH_LDAP_ROLE_RECURSION</b> | The number of levels of recursion the role search will go below a matching context. Disable recursion by setting this to 0.   | <b>`\${AUTH_LDAP_ROLE_RECURSION}`</b> | False    |
| <b>AUTH_LDAP_DEFAULT_ROLE</b>   | <b>AUTH_LDAP_DEFAULT_ROLE</b>   | A role included for all authenticated users   | <b>`\${AUTH_LDAP_DEFAULT_ROLE}`</b>   | False    |

| Variable name                            | Image Environment Variable               | Description   | Example value                                  | Required |
|--|--|---|--|----------|
| <b>AUTH_LDAP_ROLE_NAME_ATTRIBUTE_ID</b>  | <b>AUTH_LDAP_ROLE_NAME_ATTRIBUTE_ID</b>  | Name of the attribute within the roleCtxDN context which contains the role name. If the roleAttributesDN property is set to true, this property is used to find the role object's name attribute.   | <b>`\${AUTH_LDAP_ROLE_NAME_ATTRIBUTE_ID}`</b>  | False    |
| <b>AUTH_LDAP_PARSE_ROLE_NAME_FROM_DN</b> | <b>AUTH_LDAP_PARSE_ROLE_NAME_FROM_DN</b> | A flag indicating if the DN returned by a query contains the roleNameAttribute ID. If set to true, the DN is checked for the roleNameAttribute ID. If set to false, the DN is not checked for the roleNameAttribute ID. This flag can improve the performance of LDAP queries.                          | <b>`\${AUTH_LDAP_PARSE_ROLE_NAME_FROM_DN}`</b> | False    |
| <b>AUTH_LDAP_ROLE_ATTRIBUTE_IS_DN</b>    | <b>AUTH_LDAP_ROLE_ATTRIBUTE_IS_DN</b>    | Whether or not the roleAttributeID contains the fully-qualified DN of a role object. If false, the role name is taken from the value of the roleNameAttributeId attribute of the context name. Certain directory schemas, such as Microsoft Active Directory, require this attribute to be set to true. | <b>`\${AUTH_LDAP_ROLE_ATTRIBUTE_IS_DN}`</b>    | False    |

| Variable name  | Image Environment Variable                           | Description  | Example value   | Required |
|--|--|--|---|----------|
| <b>AUTH_LDAP_REFERRAL_USER_ATTRIBUTE_ID_TO_CHECK</b> | <b>AUTH_LDAP_REFERRAL_USER_ATTRIBUTE_ID_TO_CHECK</b> | If you are not using referrals, this option can be ignored. When using referrals, this option denotes the attribute name which contains users defined for a certain role, for example member, if the role object is inside the referral. Users are checked against the content of this attribute name. If this option is not set, the check will always fail, so role objects cannot be stored in a referral tree. | <b><code>\${AUTH_LDAP_REFERRAL_USER_ATTRIBUTE_ID_TO_CHECK}</code></b> | False    |

## 4.5.2. Objects

The CLI supports various object types. A list of these object types as well as their abbreviations can be found in the [Openshift documentation](#).

### 4.5.2.1. Services

A service is an abstraction which defines a logical set of pods and a policy by which to access them. Refer to the [container-engine documentation](#) for more information.

| Service   | Port | Name  | Description                            |
|---|------|-------|--|
| <b><code>\${APPLICATION_NAME}-kieserver</code></b>      | 8080 | http  | All the KIE server web server's ports. |
|   | 8443 | https |  |
| <b><code>\${APPLICATION_NAME}-kieserver-ping</code></b> | 8888 | ping  | The JGroups ping port for clustering.  |
| <b><code>\${APPLICATION_NAME}-postgresql</code></b>     | 5432 | –     | The database server's port.            |

### 4.5.2.2. Routes

A route is a way to expose a service by giving it an externally-reachable hostname such as **www.example.com**. A defined route and the endpoints identified by its service can be consumed by a router to provide named connectivity from external clients to your applications. Each route consists of a route name, service selector, and (optionally) security configuration. Refer to the [OpenShift documentation](#) for more information.

| Service                                     | Security        | Hostname                             |
|---|-----------------|--------------------------------------|
| <b>\${APPLICATION_NAME}-kieserver-http</b>  | none            | <b>\${KIE_SERVER_HOSTNAME_HTTP}</b>  |
| <b>\${APPLICATION_NAME}-kieserver-https</b> | TLS passthrough | <b>\${KIE_SERVER_HOSTNAME_HTTPS}</b> |

### 4.5.2.3. Deployment Configurations

A deployment in OpenShift is a replication controller based on a user defined template called a deployment configuration. Deployments are created manually or in response to triggered events. Refer to the [OpenShift documentation](#) for more information.

#### 4.5.2.3.1. Triggers

A trigger drives the creation of new deployments in response to events, both inside and outside OpenShift. Refer to the [OpenShift documentation](#) for more information.

| Deployment                             | Triggers    |
|--|-------------|
| <b>\${APPLICATION_NAME}-kieserver</b>  | ImageChange |
| <b>\${APPLICATION_NAME}-postgresql</b> | ImageChange |

#### 4.5.2.3.2. Replicas

A replication controller ensures that a specified number of pod "replicas" are running at any one time. If there are too many, the replication controller kills some pods. If there are too few, it starts more. Refer to the [container-engine documentation](#) for more information.

| Deployment                             | Replicas |
|--|----------|
| <b>\${APPLICATION_NAME}-kieserver</b>  | 1        |
| <b>\${APPLICATION_NAME}-postgresql</b> | 1        |

#### 4.5.2.3.3. Pod Template

##### 4.5.2.3.3.1. Service Accounts

Service accounts are API objects that exist within each project. They can be created or deleted like any other API object. Refer to the [Openshift documentation](#) for more information.

| Deployment                            | Service Account                       |
|---------------------------------------|---------------------------------------|
| <b>\${APPLICATION_NAME}-kieserver</b> | <b>\${APPLICATION_NAME}-kieserver</b> |

#### 4.5.2.3.3.2. Image

| Deployment                             | Image                                   |
|--|---|
| <b>\${APPLICATION_NAME}-kieserver</b>  | <b>\${KIE_SERVER_IMAGE_STREAM_NAME}</b> |
| <b>\${APPLICATION_NAME}-postgresql</b> | postgresql                              |

#### 4.5.2.3.3.3. Readiness Probe

##### **\${APPLICATION\_NAME}-kieserver**

```
/bin/bash -c curl --fail --silent -u '${KIE_ADMIN_USER}:${KIE_ADMIN_PWD}'
http://localhost:8080/services/rest/server/readycheck
```

##### **\${APPLICATION\_NAME}-postgresql**

```
/usr/libexec/check-container
```

#### 4.5.2.3.3.4. Liveness Probe

##### **\${APPLICATION\_NAME}-kieserver**

```
/bin/bash -c curl --fail --silent -u '${KIE_ADMIN_USER}:${KIE_ADMIN_PWD}'
http://localhost:8080/services/rest/server/readycheck
```

##### **\${APPLICATION\_NAME}-postgresql**

```
/usr/libexec/check-container
```

#### 4.5.2.3.3.5. Exposed Ports

| Deployments                           | Name    | Port | Protocol   |
|---------------------------------------|---------|------|------------|
| <b>\${APPLICATION_NAME}-kieserver</b> | jolokia | 8778 | <b>TCP</b> |
|                                       | http    | 8080 | <b>TCP</b> |
|                                       | https   | 8443 | <b>TCP</b> |

| Deployments                            | Name | Port | Protocol |
|--|------|------|----------|
|  | ping | 8888 | TCP      |
| <b>\${APPLICATION_NAME}-postgresql</b> | –    | 5432 | TCP      |

#### 4.5.2.3.3.6. Image Environment Variables

| Deployment                            | Variable name                       | Description  | Example value                           |
|---------------------------------------|-------------------------------------|--|---|
| <b>\${APPLICATION_NAME}-kieserver</b> | <b>DROOLS_SERVER_FILTER_CLASSES</b> | KIE server class filtering (Sets the org.drools.server.filter.classes system property)                           | <b>\${DROOLS_SERVER_FILTER_CLASSES}</b> |
|                                       | <b>KIE_ADMIN_USER</b>               | KIE administrator username   | <b>\${KIE_ADMIN_USER}</b>               |
|                                       | <b>KIE_ADMIN_PWD</b>                | KIE administrator password   | <b>\${KIE_ADMIN_PWD}</b>                |
|                                       | <b>KIE_MBEANS</b>                   | KIE server mbeans enabled/disabled (Sets the kie.mbeans and kie.scanner.mbeans system properties)                | <b>\${KIE_MBEANS}</b>                   |
|                                       | <b>KIE_SERVER_BYPASS_AUTH_USER</b>  | KIE server bypass auth user (Sets the org.kie.server.bypass.auth.user system property)                           | <b>\${KIE_SERVER_BYPASS_AUTH_USER}</b>  |
|                                       | <b>KIE_SERVER_CONTROLLER_USER</b>   | KIE server controller username (Sets the org.kie.server.controller.user system property)                         | <b>\${KIE_SERVER_CONTROLLER_USER}</b>   |
|                                       | <b>KIE_SERVER_CONTROLLER_PWD</b>    | KIE server controller password (Sets the org.kie.server.controller.pwd system property)                          | <b>\${KIE_SERVER_CONTROLLER_PWD}</b>    |
|                                       | <b>KIE_SERVER_CONTROLLER_TOKEN</b>  | KIE server controller token for bearer authentication (Sets the org.kie.server.controller.token system property) | <b>\${KIE_SERVER_CONTROLLER_TOKEN}</b>  |



| Deployment | Variable name                           | Description   | Example value                               |
|------------|---|---|---|
|            | <b>KIE_SERVER_CONTROLLER_SERVICE</b>    | The service name for the optional business central monitor, where it can be reached to allow service lookup, and registered with to allow monitoring console functionality (If set, will be used to discover host and port) | <b>\${KIE_SERVER_CONTROLLER_SERVICE}</b>    |
|            | <b>KIE_SERVER_CONTROLLER_PROTOCOL</b>   | –   | ws  |
|            | <b>KIE_SERVER_CONTROLLER_HOST</b>       | KIE server controller host (Used to set the org.kie.server.controller system property)  | <b>\${KIE_SERVER_CONTROLLER_HOST}</b>       |
|            | <b>KIE_SERVER_CONTROLLER_PORT</b>       | KIE server controller port (Used to set the org.kie.server.controller system property)  | <b>\${KIE_SERVER_CONTROLLER_PORT}</b>       |
|            | <b>KIE_SERVER_ID</b>                    | –   | <b>\${APPLICATION_NAME}-kieserver</b>       |
|            | <b>KIE_SERVER_HOST</b>                  | Custom hostname for http service route, if set will also configure the KIE_SERVER_HOST. Leave blank for default hostname, e.g.:<br><application-name>-kieserver-<project>.<br><default-domain-suffix>                       | <b>\${KIE_SERVER_HOSTNAME_HTTP}</b>         |
|            | <b>KIE_SERVER_ROUTE_NAME</b>            | –   | <b>\${APPLICATION_NAME}-kieserver</b>       |
|            | <b>KIE_SERVER_USE_SECURE_ROUTE_NAME</b> | Use https for the KIE_SERVER_HOST when it is not explicit configured to a custom value.   | <b>\${KIE_SERVER_USE_SECURE_ROUTE_NAME}</b> |
|            | <b>KIE_SERVER_USER</b>                  | KIE server username (Sets the org.kie.server.user system property)  | <b>\${KIE_SERVER_USER}</b>                  |

| Deployment | Variable name                          | Description   | Example value                              |
|------------|--|---|--|
|            | <b>KIE_SERVER_PWD</b>                  | KIE server password<br>(Sets the org.kie.server.pwd system property)  | <b>\${KIE_SERVER_PWD}</b>                  |
|            | <b>KIE_SERVER_CONTAINER_DEPLOYMENT</b> | KIE Server Container deployment configuration in format: containerId=groupId:artifactId:version c2=g2:a2:v2 | <b>\${KIE_SERVER_CONTAINER_DEPLOYMENT}</b> |
|            | <b>MAVEN_REPOS</b>                     | –   | RHPAMCENTR,EXTERNAL                        |
|            | <b>RHPAMCENTR_MAVEN_REPO_SERVICE</b>   | –   | <b>\${BUSINESS_CENTRAL_MAVEN_SERVICE}</b>  |
|            | <b>RHPAMCENTR_MAVEN_REPO_PATH</b>      | –   | /maven2/                                   |
|            | <b>RHPAMCENTR_MAVEN_REPO_USERNAME</b>  | Username to access the Maven repository, if required.   | <b>\${BUSINESS_CENTRAL_MAVEN_USERNAME}</b> |
|            | <b>RHPAMCENTR_MAVEN_REPO_PASSWORD</b>  | Password to access the Maven repository, if required.   | <b>\${BUSINESS_CENTRAL_MAVEN_PASSWORD}</b> |
|            | <b>EXTERNAL_MAVEN_REPO_ID</b>          | The id to use for the maven repository, if set. Default is generated randomly.                              | <b>\${MAVEN_REPO_ID}</b>                   |
|            | <b>EXTERNAL_MAVEN_REPO_URL</b>         | Fully qualified URL to a Maven repository or service.   | <b>\${MAVEN_REPO_URL}</b>                  |
|            | <b>EXTERNAL_MAVEN_REPO_USERNAME</b>    | Username to access the Maven repository, if required.   | <b>\${MAVEN_REPO_USERNAME}</b>             |
|            | <b>EXTERNAL_MAVEN_REPO_PASSWORD</b>    | Password to access the Maven repository, if required.   | <b>\${MAVEN_REPO_PASSWORD}</b>             |

| Deployment | Variable name                      | Description  | Example value                            |
|------------|------------------------------------|--|--|
|            | <b>KIE_SERVER_ROUTER_SERVICE</b>   | The service name for the optional smart router, where it can be reached, to allow smart routing  | <b>`\${KIE_SERVER_ROUTER_SERVICE}`</b>   |
|            | <b>KIE_SERVER_ROUTER_HOST</b>      | The host name of the smart router, which could be the service name resolved by OpenShift or a globally resolvable domain name                                    | <b>`\${KIE_SERVER_ROUTER_HOST}`</b>      |
|            | <b>KIE_SERVER_ROUTER_PORT</b>      | Port in which the smart router server listens (router property org.kie.server.router.port)   | <b>`\${KIE_SERVER_ROUTER_PORT}`</b>      |
|            | <b>KIE_SERVER_ROUTER_PROTOCOL</b>  | KIE server router protocol (Used to build the org.kie.server.router.url.external property)   | <b>`\${KIE_SERVER_ROUTER_PROTOCOL}`</b>  |
|            | <b>KIE_SERVER_MGMT_DISABLED</b>    | When set to LocalContainersStartup Strategy, allows KIE server to start up and function with local config, even when a controller is configured and unavailable  | <b>`\${KIE_SERVER_MGMT_DISABLED}`</b>    |
|            | <b>KIE_SERVER_STARTUP_STRATEGY</b> | When set to LocalContainersStartup Strategy, allows KIE server to start up and function with local config, even when a controller is configured and unavailable. | <b>`\${KIE_SERVER_STARTUP_STRATEGY}`</b> |
|            | <b>KIE_SERVER_PERSISTENCE_DS</b>   | KIE server persistence datasource (Sets the org.kie.server.persistence.ds system property)   | <b>`\${KIE_SERVER_PERSISTENCE_DS}`</b>   |
|            | <b>DATASOURCES</b>                 | –  | <b>RHPAM</b>                             |

| Deployment | Variable name                                    | Description  | Example value  |
|------------|--|--|--|
|            | <b>RHPAM_DATABASE</b>                            | –  | <b>\${KIE_SERVER_POSTGRESQL_DB}</b>                  |
|            | <b>RHPAM_DRIVER</b>                              | –  | postgresql   |
|            | <b>RHPAM_USERNAME</b>                            | –  | <b>\${KIE_SERVER_POSTGRESQL_USER}</b>                |
|            | <b>RHPAM_PASSWORD</b>                            | –  | <b>\${KIE_SERVER_POSTGRESQL_PWD}</b>                 |
|            | <b>RHPAM_SERVICE_HOST</b>                        | –  | <b>\${APPLICATION_NAME}-postgresql</b>               |
|            | <b>RHPAM_SERVICE_PORT</b>                        | –  | 5432   |
|            | <b>TIMER_SERVICE_DATA_STORE</b>                  | Sets refresh-interval for the EJB timer database data-store service. | <b>\${APPLICATION_NAME}-postgresql</b>               |
|            | <b>KIE_SERVER_PERSISTENCE_DIALECT</b>            | –  | org.hibernate.dialect.PostgreSQLDialect              |
|            | <b>RHPAM_JTA</b>                                 | –  | true   |
|            | <b>RHPAM_JNDI</b>                                | –  | <b>\${KIE_SERVER_PERSISTENCE_DS}</b>                 |
|            | <b>TIMER_SERVICE_DATA_STORE_REFRESH_INTERVAL</b> | Sets refresh-interval for the EJB timer database data-store service. | <b>\${TIMER_SERVICE_DATA_STORE_REFRESH_INTERVAL}</b> |
|            | <b>HTTPS_KEYSTORE_DIR</b>                        | –  | <b>/etc/kieserver-secret-volume</b>                  |
|            | <b>HTTPS_KEYSTORE</b>                            | The name of the keystore file within the secret                      | <b>\${KIE_SERVER_HTTPS_KEYSTORE}</b>                 |
|            | <b>HTTPS_NAME</b>                                | The name associated with the server certificate                      | <b>\${KIE_SERVER_HTTPS_NAME}</b>                     |
|            | <b>HTTPS_PASSWORD</b>                            | The password for the keystore and certificate                        | <b>\${KIE_SERVER_HTTPS_PASSWORD}</b>                 |

| Deployment | Variable name                                 | Description   | Example value                                     |
|------------|---|---|---|
|            | <b>JGROUPS_PING_PROTOCOL</b>                  | –   | opensift.DNS_PING                                 |
|            | <b>OPENSIFT_DNS_PING_SERVICE_NAME</b>         | –   | <b>\${APPLICATION_NAME}-kieserver-ping</b>        |
|            | <b>OPENSIFT_DNS_PING_SERVICE_PORT</b>         | –   | 8888  |
|            | <b>SSO_URL</b>                                | RH-SSO URL  | <b>\${SSO_URL}</b>                                |
|            | <b>SSO_OPENIDCONNECT_DEPLOYMENTS</b>          | –   | ROOT.war  |
|            | <b>SSO_REALM</b>                              | RH-SSO Realm name   | <b>\${SSO_REALM}</b>                              |
|            | <b>SSO_SECRET</b>                             | KIE Server RH-SSO Client Secret   | <b>\${KIE_SERVER_SSO_SECRET}</b>                  |
|            | <b>SSO_CLIENT</b>                             | KIE Server RH-SSO Client name   | <b>\${KIE_SERVER_SSO_CLIENT}</b>                  |
|            | <b>SSO_USERNAME</b>                           | RH-SSO Realm Admin Username used to create the Client if it doesn't exist | <b>\${SSO_USERNAME}</b>                           |
|            | <b>SSO_PASSWORD</b>                           | RH-SSO Realm Admin Password used to create the Client                     | <b>\${SSO_PASSWORD}</b>                           |
|            | <b>SSO_DISABLE_SSL_CERTIFICATE_VALIDATION</b> | RH-SSO Disable SSL Certificate Validation                                 | <b>\${SSO_DISABLE_SSL_CERTIFICATE_VALIDATION}</b> |
|            | <b>SSO_PRINCIPAL_ATTRIBUTE</b>                | RH-SSO Principal Attribute to use as username.                            | <b>\${SSO_PRINCIPAL_ATTRIBUTE}</b>                |

| Deployment | Variable name                         | Description  | Example value                             |
|------------|---------------------------------------|--|---|
|            | <b>HOSTNAME_HTTP</b>                  | Custom hostname for http service route, if set will also configure the KIE_SERVER_HOST. Leave blank for default hostname, e.g.: <application-name>-kieserver-<project>. <default-domain-suffix>  | <b>\${KIE_SERVER_HOSTNAME_HTTP}</b>       |
|            | <b>HOSTNAME_HTTPS</b>                 | Custom hostname for https service route. Leave blank for default hostname, e.g.: secure-<application-name>-kieserver-<project>. <default-domain-suffix>  | <b>\${KIE_SERVER_HOSTNAME_HTTPS}</b>      |
|            | <b>AUTH_LDAP_URL</b>                  | LDAP Endpoint to connect for authentication  | <b>\${AUTH_LDAP_URL}</b>                  |
|            | <b>AUTH_LDAP_BIND_DN</b>              | Bind DN used for authentication  | <b>\${AUTH_LDAP_BIND_DN}</b>              |
|            | <b>AUTH_LDAP_BIND_CREDENTIAL</b>      | LDAP Credentials used for authentication   | <b>\${AUTH_LDAP_BIND_CREDENTIAL}</b>      |
|            | <b>AUTH_LDAP_JAAS_SECURITY_DOMAIN</b> | The JMX ObjectName of the JaasSecurityDomain used to decrypt the password.   | <b>\${AUTH_LDAP_JAAS_SECURITY_DOMAIN}</b> |
|            | <b>AUTH_LDAP_BASE_CTX_DN</b>          | LDAP Base DN of the top-level context to begin the user search.  | <b>\${AUTH_LDAP_BASE_CTX_DN}</b>          |
|            | <b>AUTH_LDAP_BASE_FILTER</b>          | LDAP search filter used to locate the context of the user to authenticate. The input username or userDN obtained from the login module callback is substituted into the filter anywhere a {0} expression is used. A common example for the search filter is (uid={0}). | <b>\${AUTH_LDAP_BASE_FILTER}</b>          |

| Deployment | Variable name                                 | Description  | Example value                                     |
|------------|---|--|---|
|            | <b>AUTH_LDAP_SEARCH_SCOPE</b>                 | The search scope to use.   | <b>\${AUTH_LDAP_SEARCH_SCOPE}</b>                 |
|            | <b>AUTH_LDAP_SEARCH_TIME_LIMIT</b>            | The timeout in milliseconds for user or role searches.   | <b>\${AUTH_LDAP_SEARCH_TIME_LIMIT}</b>            |
|            | <b>AUTH_LDAP_DISTINGUISHED_NAME_ATTRIBUTE</b> | The name of the attribute in the user entry that contains the DN of the user. This may be necessary if the DN of the user itself contains special characters, backslash for example, that prevent correct user mapping. If the attribute does not exist, the entry's DN is used. | <b>\${AUTH_LDAP_DISTINGUISHED_NAME_ATTRIBUTE}</b> |
|            | <b>AUTH_LDAP_PARSE_USERNAME</b>               | A flag indicating if the DN is to be parsed for the username. If set to true, the DN is parsed for the username. If set to false the DN is not parsed for the username. This option is used together with <code>usernameBeginString</code> and <code>usernameEndString</code> .  | <b>\${AUTH_LDAP_PARSE_USERNAME}</b>               |
|            | <b>AUTH_LDAP_USERNAME_BEGIN_STRING</b>        | Defines the String which is to be removed from the start of the DN to reveal the username. This option is used together with <code>usernameEndString</code> and only taken into account if <code>parseUsername</code> is set to true.  | <b>\${AUTH_LDAP_USERNAME_BEGIN_STRING}</b>        |

| Deployment | Variable name                         | Description   | Example value  |
|------------|---------------------------------------|---|--|
|            | <b>AUTH_LDAP_USER_NAME_END_STRING</b> | Defines the String which is to be removed from the end of the DN to reveal the username. This option is used together with <code>usernameEndString</code> and only taken into account if <code>parseUsername</code> is set to true.   | <b><code>\${AUTH_LDAP_USER_NAME_END_STRING}</code></b> |
|            | <b>AUTH_LDAP_ROLE_ATTRIBUTE_ID</b>    | Name of the attribute containing the user roles.  | <b><code>\${AUTH_LDAP_ROLE_ATTRIBUTE_ID}</code></b>    |
|            | <b>AUTH_LDAP_ROLE_S_CTX_DN</b>        | The fixed DN of the context to search for user roles. This is not the DN where the actual roles are, but the DN where the objects containing the user roles are. For example, in a Microsoft Active Directory server, this is the DN where the user account is.   | <b><code>\${AUTH_LDAP_ROLE_S_CTX_DN}</code></b>        |
|            | <b>AUTH_LDAP_ROLE_FILTER</b>          | A search filter used to locate the roles associated with the authenticated user. The input username or userDN obtained from the login module callback is substituted into the filter anywhere a <code>{0}</code> expression is used. The authenticated userDN is substituted into the filter anywhere a <code>{1}</code> is used. An example search filter that matches on the input username is <code>(member={0})</code> . An alternative that matches on the authenticated userDN is <code>(member={1})</code> . | <b><code>\${AUTH_LDAP_ROLE_FILTER}</code></b>          |



| Deployment | Variable name                            | Description   | Example value                                  |
|------------|--|---|--|
|            | <b>AUTH_LDAP_ROLE_RECURSION</b>          | The number of levels of recursion the role search will go below a matching context. Disable recursion by setting this to 0.   | <b>`\${AUTH_LDAP_ROLE_RECURSION}`</b>          |
|            | <b>AUTH_LDAP_DEFAULT_ROLE</b>            | A role included for all authenticated users   | <b>`\${AUTH_LDAP_DEFAULT_ROLE}`</b>            |
|            | <b>AUTH_LDAP_ROLE_NAME_ATTRIBUTE_ID</b>  | Name of the attribute within the roleCtxDN context which contains the role name. If the roleAttributesDN property is set to true, this property is used to find the role object's name attribute.   | <b>`\${AUTH_LDAP_ROLE_NAME_ATTRIBUTE_ID}`</b>  |
|            | <b>AUTH_LDAP_PARSE_ROLE_NAME_FROM_DN</b> | A flag indicating if the DN returned by a query contains the roleNameAttributeID. If set to true, the DN is checked for the roleNameAttributeID. If set to false, the DN is not checked for the roleNameAttributeID. This flag can improve the performance of LDAP queries.                             | <b>`\${AUTH_LDAP_PARSE_ROLE_NAME_FROM_DN}`</b> |
|            | <b>AUTH_LDAP_ROLE_ATTRIBUTE_IS_DN</b>    | Whether or not the roleAttributeID contains the fully-qualified DN of a role object. If false, the role name is taken from the value of the roleNameAttributeID attribute of the context name. Certain directory schemas, such as Microsoft Active Directory, require this attribute to be set to true. | <b>`\${AUTH_LDAP_ROLE_ATTRIBUTE_IS_DN}`</b>    |

| Deployment                               | Variable name  | Description  | Example value  |
|--|--|--|--|
|  | <b>AUTH_LDAP_REFERRAL_USER_ATTRIBUTE_ID_TO_CHECK</b> | If you are not using referrals, this option can be ignored. When using referrals, this option denotes the attribute name which contains users defined for a certain role, for example member, if the role object is inside the referral. Users are checked against the content of this attribute name. If this option is not set, the check will always fail, so role objects cannot be stored in a referral tree. | <b>`\${AUTH_LDAP_REFERRAL_USER_ATTRIBUTE_ID_TO_CHECK}`</b> |
| <b>`\${APPLICATION_NAME}`-postgresql</b> | <b>POSTGRESQL_USER</b>                               | KIE server PostgreSQL database username  | <b>`\${KIE_SERVER_POSTGRESQL_USER}`</b>                    |
|  | <b>POSTGRESQL_PASSWORD</b>                           | –  | <b>`\${KIE_SERVER_POSTGRESQL_PWD}`</b>                     |
|  | <b>POSTGRESQL_DATABASE</b>                           | –  | <b>`\${KIE_SERVER_POSTGRESQL_DB}`</b>                      |
|  | <b>POSTGRESQL_MAX_PREPARED_TRANSACTIONS</b>          | Allows the PostgreSQL to handle XA transactions.   | <b>`\${POSTGRESQL_MAX_PREPARED_TRANSACTIONS}`</b>          |

#### 4.5.2.3.3.7. Volumes

| Deployment                               | Name  | mountPath                           | Purpose    | readOnly |
|--|---|-------------------------------------|------------|----------|
| <b>`\${APPLICATION_NAME}`-kieserver</b>  | kieserver-keystore-volume                     | <b>/etc/kieserver-secret-volume</b> | ssl certs  | True     |
| <b>`\${APPLICATION_NAME}`-postgresql</b> | <b>`\${APPLICATION_NAME}`-postgresql-pvol</b> | <b>/var/lib/pgsql/data</b>          | postgresql | false    |

#### 4.5.2.4. External Dependencies

#### 4.5.2.4.1. Volume Claims

A **PersistentVolume** object is a storage resource in an OpenShift cluster. Storage is provisioned by an administrator by creating **PersistentVolume** objects from sources such as GCE Persistent Disks, AWS Elastic Block Stores (EBS), and NFS mounts. Refer to the [OpenShift documentation](#) for more information.

| Name   | Access Mode   |
|--|---------------|
| <code>\${APPLICATION_NAME}-postgresql-claim</code> | ReadWriteOnce |

#### 4.5.2.4.2. Secrets

This template requires the following secrets to be installed for the application to run.

kieserver-app-secret

## 4.6. OPENSIFT USAGE QUICK REFERENCE

To deploy, monitor, manage, and undeploy Red Hat Process Automation Manager templates on Red Hat OpenShift Container Platform, you can use the OpenShift Web console or the **oc** command.

For instructions about using the Web console, see [Create and build an image using the Web console](#).

For detailed instructions about using the **oc** command, see [CLI Reference](#). The following commands are likely to be required:

- To create a project, use the following command:

```
$ oc new-project <project-name>
```

For more information, see [Creating a project using the CLI](#).

- To deploy a template (create an application from a template), use the following command:

```
$ oc new-app -f <template-name> -p <parameter>=<value> -p <parameter>=<value> ...
```

For more information, see [Creating an application using the CLI](#).

- To view a list of the active pods in the project, use the following command:

```
$ oc get pods
```

- To view the current status of a pod, including information whether or not the pod deployment has completed and it is now in a running state, use the following command:

```
$ oc describe pod <pod-name>
```

You can also use the **oc describe** command to view the current status of other objects. For more information, see [Application modification operations](#).

- To view the logs for a pod, use the following command:

```
$ oc logs <pod-name>
```

- To view deployment logs, look up a **DeploymentConfig** name in the template reference and run the following command:

```
$ oc logs -f dc/<deployment-config-name>
```

For more information, see [Viewing deployment logs](#).

- To view build logs, look up a **BuildConfig** name in the template reference and run the command:

```
$ oc logs -f bc/<build-config-name>
```

For more information, see [Accessing build logs](#).

- To scale a pod in the application, look up a **DeploymentConfig** name in the template reference and run the command:

```
$ oc scale dc/<deployment-config-name> --replicas=<number>
```

For more information, see [Manual scaling](#).

- To undeploy the application, you can delete the project by using the command:

```
$ oc delete project <project-name>
```

Alternatively, you can use the **oc delete** command to remove any part of the application, such as a pod or replication controller. For details, see [Application modification CLI operation](#).

## APPENDIX A. VERSIONING INFORMATION

Documentation last updated on Wednesday, March 27, 2019.