



Red Hat 3scale API Management 2.5

Liquid Reference

Find additional information related to your 3scale installation.

Red Hat 3scale API Management 2.5 Liquid Reference

Find additional information related to your 3scale installation.

Legal Notice

Copyright © 2019 Red Hat, Inc.

The text of and illustrations in this document are licensed by Red Hat under a Creative Commons Attribution–Share Alike 3.0 Unported license ("CC-BY-SA"). An explanation of CC-BY-SA is available at

<http://creativecommons.org/licenses/by-sa/3.0/>

. In accordance with CC-BY-SA, if you distribute this document or an adaptation of it, you must provide the URL for the original version.

Red Hat, as the licensor of this document, waives the right to enforce, and agrees not to assert, Section 4d of CC-BY-SA to the fullest extent permitted by applicable law.

Red Hat, Red Hat Enterprise Linux, the Shadowman logo, the Red Hat logo, JBoss, OpenShift, Fedora, the Infinity logo, and RHCE are trademarks of Red Hat, Inc., registered in the United States and other countries.

Linux[®] is the registered trademark of Linus Torvalds in the United States and other countries.

Java[®] is a registered trademark of Oracle and/or its affiliates.

XFS[®] is a trademark of Silicon Graphics International Corp. or its subsidiaries in the United States and/or other countries.

MySQL[®] is a registered trademark of MySQL AB in the United States, the European Union and other countries.

Node.js[®] is an official trademark of Joyent. Red Hat is not formally related to or endorsed by the official Joyent Node.js open source or commercial project.

The OpenStack[®] Word Mark and OpenStack logo are either registered trademarks/service marks or trademarks/service marks of the OpenStack Foundation, in the United States and other countries and are used with the OpenStack Foundation's permission. We are not affiliated with, endorsed or sponsored by the OpenStack Foundation, or the OpenStack community.

All other trademarks are the property of their respective owners.

Abstract

This guide provides the information about components that interact with your 3scale installation.

Table of Contents

CHAPTER 1. LIQUID REFERENCE	15
1.1. WHAT ARE LIQUIDS?	15
1.1.1. Pros and cons	15
1.2. HOW TO USE LIQUIDS	15
1.2.1. Liquid drops, tags, and their meanings	15
1.2.2. The context	16
1.2.3. Hierarchy	16
1.3. LIQUID TEMPLATES	17
1.4. DROPS	17
1.5. TAGS	19
1.6. FILTERS	20
1.7. DROPS (UP)	20
1.7.1. Account drop (up)	20
1.7.1.1. Methods	20
1.7.1.1.1. errors	20
1.7.1.1.2. id	20
1.7.1.1.3. name	20
1.7.1.1.4. vat_zero_text	21
1.7.1.1.5. vat_rate	21
1.7.1.1.6. unread_messages	21
1.7.1.1.7. latest_messages	21
1.7.1.1.8. bought_account_plan	21
1.7.1.1.9. bought_account_contract	21
1.7.1.1.10. credit_card_display_number	21
1.7.1.1.11. credit_card_expiration_date	21
1.7.1.1.12. credit_card_required?	21
1.7.1.1.13. credit_card_stored?	21
1.7.1.1.14. credit_card_missing?	21
1.7.1.1.15. timezone	21
1.7.1.1.16. paid?	21
1.7.1.1.17. on_trial?	21
1.7.1.1.18. telephone_number	21
1.7.1.1.19. approval_required?	22
1.7.1.1.20. created_at	22
1.7.1.1.21. full_address	22
1.7.1.1.22. applications	22
1.7.1.1.23. subscribed_services	22
1.7.1.1.24. admin	22
1.7.1.1.25. extra_fields_plain_text	22
1.7.1.1.26. fields_plain_text	22
1.7.1.1.27. extra_fields	22
1.7.1.1.28. fields	22
1.7.1.1.29. builtin_fields	23
1.7.1.1.30. multiple_applications_allowed?	23
1.7.1.1.31. billing_address	23
1.7.1.1.32. has_billing_address?	23
1.7.1.1.33. can	23
1.7.1.1.34. edit_url	23
1.7.1.1.35. edit_ogone_billing_address_url	23
1.7.1.1.36. edit_payment_express_billing_address_url	23
1.7.1.1.37. edit_braintree_blue_credit_card_details_url	23

1.7.1.1.38. domain	23
1.7.1.1.39. upgraded?	23
1.7.1.1.40. requires_credit_card?	23
1.7.1.1.41. support_email	23
1.7.1.1.42. finance_support_email	23
1.7.2. AccountPlan drop (up)	23
1.7.2.1. Methods	24
1.7.2.1.1. selected?	24
1.7.2.1.2. bought?	24
1.7.2.1.3. features	24
1.7.2.1.4. setup_fee	24
1.7.2.1.5. name	24
1.7.2.1.6. system_name	24
1.7.2.1.7. id	24
1.7.2.1.8. free?	24
1.7.2.1.9. paid?	25
1.7.2.1.10. approval_required?	25
1.7.2.1.11. flat_cost	25
1.7.3. Alert drop (up)	25
1.7.3.1. Methods	25
1.7.3.1.1. level	25
1.7.3.1.2. message	25
1.7.3.1.3. utilization	26
1.7.4. Application drop (up)	26
1.7.4.1. Methods	26
1.7.4.1.1. errors	26
1.7.4.1.2. id	26
1.7.4.1.3. can_change_plan?	26
1.7.4.1.4. trial?	26
1.7.4.1.5. live?	26
1.7.4.1.6. state	26
1.7.4.1.7. remaining_trial_period_days	26
1.7.4.1.8. plan	26
1.7.4.1.9. plan_change_permission_name	27
1.7.4.1.10. plan_change_permission_warning	27
1.7.4.1.11. contract	27
1.7.4.1.12. admin_url	27
1.7.4.1.13. name	27
1.7.4.1.14. can	27
1.7.4.1.15. oauth	27
1.7.4.1.16. pending?	27
1.7.4.1.17. buyer_alerts_enabled?	27
1.7.4.1.18. description	27
1.7.4.1.19. redirect_url	27
1.7.4.1.20. filters_limit	27
1.7.4.1.21. keys_limit	27
1.7.4.1.22. referrer_filters	27
1.7.4.1.23. rejection_reason	27
1.7.4.1.24. user_key	28
1.7.4.1.25. application_id	28
1.7.4.1.26. key	28
1.7.4.1.27. url	28
1.7.4.1.28. edit_url	28

1.7.4.1.29. update_user_key_url	28
1.7.4.1.30. log_requests_url	28
1.7.4.1.31. alerts_url	28
1.7.4.1.32. application_keys_url	28
1.7.4.1.33. service	28
1.7.4.1.34. keys	28
1.7.4.1.35. user_key_mode?	29
1.7.4.1.36. app_id_mode?	29
1.7.4.1.37. change_plan_url	29
1.7.4.1.38. log_requests?	29
1.7.4.1.39. application_keys	29
1.7.4.1.40. extra_fields	29
1.7.4.1.41. fields	29
1.7.4.1.42. builtin_fields	29
1.7.4.1.43. cinstance	29
1.7.5. ApplicationKey drop (up)	29
1.7.5.1. Methods	29
1.7.5.1.1. id	29
1.7.5.1.2. value	29
1.7.5.1.3. url	29
1.7.5.1.4. application	29
1.7.6. ApplicationPlan drop (up)	29
1.7.6.1. Methods	29
1.7.6.1.1. selected?	30
1.7.6.1.2. bought?	30
1.7.6.1.3. features	30
1.7.6.1.4. setup_fee	30
1.7.6.1.5. name	30
1.7.6.1.6. system_name	30
1.7.6.1.7. id	30
1.7.6.1.8. free?	31
1.7.6.1.9. paid?	31
1.7.6.1.10. approval_required?	31
1.7.6.1.11. flat_cost	31
1.7.6.1.12. metrics	31
1.7.6.1.13. usage_limits	31
1.7.6.1.14. service	31
1.7.7. Base drop (up)	31
1.7.7.1. Methods	31
1.7.7.1.1. login_url	32
1.7.7.1.2. user_identified?	32
1.7.8. Base drop (up)	32
1.7.8.1. Methods	32
1.7.8.1.1. errors	32
1.7.8.1.2. title	32
1.7.8.1.3. kind	32
1.7.8.1.4. url	32
1.7.8.1.5. description	32
1.7.9. BillingAddressField drop (up)	32
1.7.9.1. Methods	32
1.7.9.1.1. input_name	32
1.7.9.1.2. label	32
1.7.9.1.3. choices	32

1.7.9.1.4. errors	32
1.7.9.1.5. html_id	32
1.7.9.1.6. hidden?	32
1.7.9.1.7. visible?	32
1.7.9.1.8. read_only?	33
1.7.9.1.9. name	33
1.7.9.1.10. value	33
1.7.9.1.11. required	33
1.7.10. Can drop (up)	33
1.7.10.1. Methods	33
1.7.10.1.1. be_updated?	33
1.7.10.1.2. add_referrer_filters?	33
1.7.10.1.3. add_application_keys?	33
1.7.10.1.4. regenerate_user_key?	33
1.7.10.1.5. regenerate_oauth_secret?	33
1.7.10.1.6. manage_keys?	33
1.7.10.1.7. delete_key?	33
1.7.11. Can drop (up)	33
1.7.11.1. Methods	33
1.7.11.1.1. change_plan?	33
1.7.12. Cas drop (up)	33
1.7.12.1. Methods	33
1.7.12.1.1. login_url	33
1.7.12.1.2. user_identified?	33
1.7.13. Contract drop (up)	33
1.7.13.1. Methods	33
1.7.13.1.1. errors	34
1.7.13.1.2. id	34
1.7.13.1.3. can_change_plan?	34
1.7.13.1.4. trial?	34
1.7.13.1.5. live?	34
1.7.13.1.6. state	34
1.7.13.1.7. remaining_trial_period_days	34
1.7.13.1.8. plan	34
1.7.13.1.9. plan_change_permission_name	34
1.7.13.1.10. plan_change_permission_warning	34
1.7.13.1.11. contract	34
1.7.14. Country drop (up)	34
1.7.14.1. Methods	34
1.7.14.1.1. errors	35
1.7.14.1.2. to_str	35
1.7.14.1.3. code	35
1.7.14.1.4. label	35
1.7.15. CountryField drop (up)	35
1.7.15.1. Methods	35
1.7.15.1.1. value	35
1.7.15.1.2. name	35
1.7.15.1.3. required	35
1.7.15.1.4. hidden?	35
1.7.15.1.5. hidden	35
1.7.15.1.6. visible?	35
1.7.15.1.7. visible	35
1.7.15.1.8. read_only	35

1.7.15.1.9. errors	35
1.7.15.1.10. input_name	35
1.7.15.1.11. html_id	35
1.7.15.1.12. label	36
1.7.15.1.13. to_str	36
1.7.15.1.14. choices	36
1.7.16. CurrentUser drop (up)	36
1.7.16.1. Methods	36
1.7.16.1.1. errors	36
1.7.16.1.2. admin?	36
1.7.16.1.3. username	36
1.7.16.1.4. account	36
1.7.16.1.5. name	36
1.7.16.1.6. email	36
1.7.16.1.7. password_required?	36
1.7.16.1.8. sections	37
1.7.16.1.9. role	37
1.7.16.1.10. roles_collection	37
1.7.16.1.11. url	37
1.7.16.1.12. edit_url	37
1.7.16.1.13. can	37
1.7.16.1.14. extra_fields	38
1.7.16.1.15. fields	38
1.7.16.1.16. builtin_fields	38
1.7.17. Error drop (up)	38
1.7.17.1. Methods	38
1.7.17.1.1. attribute	38
1.7.17.1.2. message	38
1.7.17.1.3. value	39
1.7.17.1.4. to_str	39
1.7.18. Errors drop (up)	39
1.7.18.1. Methods	39
1.7.18.1.1. empty?	39
1.7.18.1.2. present?	39
1.7.19. Feature drop (up)	39
1.7.19.1. Methods	39
1.7.19.1.1. errors	39
1.7.19.1.2. name	40
1.7.19.1.3. description	40
1.7.19.1.4. has_description?	40
1.7.20. Field drop (up)	40
1.7.20.1. Methods	40
1.7.20.1.1. value	40
1.7.20.1.2. name	40
1.7.20.1.3. required	40
1.7.20.1.4. hidden?	40
1.7.20.1.5. hidden	40
1.7.20.1.6. visible?	40
1.7.20.1.7. visible	40
1.7.20.1.8. read_only	40
1.7.20.1.9. errors	41
1.7.20.1.10. input_name	41
1.7.20.1.11. html_id	41

1.7.20.1.12. label	41
1.7.20.1.13. to_str	41
1.7.20.1.14. choices	41
1.7.21. Flash drop (up)	41
1.7.21.1. Methods	41
1.7.21.1.1. messages	42
1.7.22. Forum drop (up)	42
1.7.22.1. Methods	42
1.7.22.1.1. enabled?	42
1.7.22.1.2. latest_posts	42
1.7.23. I18n drop (up)	42
1.7.23.1. Methods	42
1.7.23.1.1. short_date	42
1.7.23.1.2. long_date	42
1.7.23.1.3. default_date	42
1.7.24. Invitation drop (up)	43
1.7.24.1. Methods	43
1.7.24.1.1. errors	43
1.7.24.1.2. email	43
1.7.24.1.3. accepted?	43
1.7.24.1.4. accepted_at	43
1.7.24.1.5. sent_at	43
1.7.24.1.6. resend_url	43
1.7.24.1.7. url	44
1.7.25. Invoice drop (up)	44
1.7.25.1. Methods	44
1.7.25.1.1. errors	44
1.7.25.1.2. friendly_id	44
1.7.25.1.3. name	44
1.7.25.1.4. state	44
1.7.25.1.5. cost	44
1.7.25.1.6. currency	44
1.7.25.1.7. cost_without_vat	44
1.7.25.1.8. vat_amount	44
1.7.25.1.9. exists_pdf?	44
1.7.25.1.10. period_begin	45
1.7.25.1.11. period_end	45
1.7.25.1.12. issued_on	45
1.7.25.1.13. due_on	45
1.7.25.1.14. paid_on	45
1.7.25.1.15. vat_code	45
1.7.25.1.16. fiscal_code	45
1.7.25.1.17. account	45
1.7.25.1.18. buyer_account	45
1.7.25.1.19. line_items	45
1.7.25.1.20. payment_transactions	45
1.7.25.1.21. url	46
1.7.25.1.22. pdf_url	46
1.7.26. Janrain drop (up)	46
1.7.26.1. Methods	46
1.7.26.1.1. login_url	46
1.7.26.1.2. user_identified?	46
1.7.26.1.3. session_url	46

1.7.26.1.4. relying_party	46
1.7.27. Lineltem drop (up)	46
1.7.27.1. Methods	46
1.7.27.1.1. errors	46
1.7.27.1.2. name	46
1.7.27.1.3. description	47
1.7.27.1.4. quantity	47
1.7.27.1.5. cost	47
1.7.28. Message drop (up)	47
1.7.28.1. Methods	47
1.7.28.1.1. errors	47
1.7.28.1.2. id	47
1.7.28.1.3. subject	47
1.7.28.1.4. body	47
1.7.28.1.5. created_at	47
1.7.28.1.6. url	47
1.7.28.1.7. state	47
1.7.28.1.8. sender	47
1.7.28.1.9. to	48
1.7.28.1.10. recipients	48
1.7.29. Message drop (up)	48
1.7.29.1. Methods	48
1.7.29.1.1. type	48
1.7.29.1.2. text	48
1.7.30. Metric drop (up)	48
1.7.30.1. Methods	48
1.7.30.1.1. errors	48
1.7.30.1.2. unit	48
1.7.30.1.3. description	48
1.7.30.1.4. name	48
1.7.30.1.5. system_name	49
1.7.30.1.6. usage_limits	49
1.7.30.1.7. pricing_rules	49
1.7.30.1.8. has_parent	49
1.7.31. Page drop (up)	49
1.7.31.1. Methods	49
1.7.31.1.1. errors	49
1.7.31.1.2. title	49
1.7.31.1.3. system_name	50
1.7.32. Page drop (up)	50
1.7.32.1. Methods	50
1.7.32.1.1. errors	50
1.7.32.1.2. title	50
1.7.32.1.3. kind	50
1.7.32.1.4. url	50
1.7.32.1.5. description	50
1.7.33. Pagination drop (up)	50
1.7.33.1. Methods	50
1.7.33.1.1. page_size	50
1.7.33.1.2. current_page	51
1.7.33.1.3. current_offset	51
1.7.33.1.4. pages	51
1.7.33.1.5. items	51

1.7.33.1.6. previous	51
1.7.33.1.7. next	52
1.7.33.1.8. parts	52
1.7.34. Part drop (up)	52
1.7.34.1. Methods	52
1.7.34.1.1. url	52
1.7.34.1.2. rel	52
1.7.34.1.3. current?	52
1.7.34.1.4. is_link	52
1.7.34.1.5. title	52
1.7.34.1.6. to_s	52
1.7.35. PaymentGateway drop (up)	52
1.7.35.1. Methods	52
1.7.35.1.1. braintree_blue?	52
1.7.35.1.2. authorize_net?	52
1.7.35.1.3. type	52
1.7.36. PaymentTransaction drop (up)	52
1.7.36.1. Methods	52
1.7.36.1.1. errors	52
1.7.36.1.2. currency	53
1.7.36.1.3. amount	53
1.7.36.1.4. created_at	53
1.7.36.1.5. success?	53
1.7.36.1.6. message	53
1.7.36.1.7. reference	53
1.7.37. PlanFeature drop (up)	53
1.7.37.1. Methods	53
1.7.37.1.1. errors	53
1.7.37.1.2. name	53
1.7.37.1.3. description	54
1.7.37.1.4. has_description?	54
1.7.37.1.5. enabled?	54
1.7.38. Post drop (up)	54
1.7.38.1. Methods	54
1.7.38.1.1. errors	54
1.7.38.1.2. body	54
1.7.38.1.3. topic	54
1.7.38.1.4. created_at	54
1.7.38.1.5. url	54
1.7.39. Post drop (up)	54
1.7.39.1. Methods	54
1.7.39.1.1. errors	55
1.7.39.1.2. title	55
1.7.39.1.3. kind	55
1.7.39.1.4. url	55
1.7.39.1.5. description	55
1.7.40. PricingRule drop (up)	55
1.7.40.1. Methods	55
1.7.40.1.1. cost_per_unit	55
1.7.40.1.2. min	55
1.7.40.1.3. max	55
1.7.40.1.4. plan	55
1.7.41. Provider drop (up)	55

1.7.41.1. Methods	55
1.7.41.1.1. name	55
1.7.41.1.2. payment_gateway	56
1.7.41.1.3. domain	56
1.7.41.1.4. timezone	56
1.7.41.1.5. support_email	56
1.7.41.1.6. finance_support_email	56
1.7.41.1.7. telephone_number	56
1.7.41.1.8. multiple_applications_allowed?	56
1.7.41.1.9. logo_url	57
1.7.41.1.10. multiple_services_allowed?	57
1.7.41.1.11. finance_allowed?	57
1.7.41.1.12. multiple_users_allowed?	57
1.7.41.1.13. account_plans	57
1.7.41.1.14. services	57
1.7.41.1.15. signups_enabled?	58
1.7.41.1.16. account_management_enabled?	58
1.7.42. ReferrerFilter drop (up)	58
1.7.42.1. Methods	58
1.7.42.1.1. id	58
1.7.42.1.2. value	58
1.7.42.1.3. delete_url	58
1.7.42.1.4. application	58
1.7.43. Request drop (up)	58
1.7.43.1. Methods	58
1.7.43.1.1. request_uri	58
1.7.43.1.2. host_with_port	58
1.7.43.1.3. host	58
1.7.43.1.4. path	58
1.7.44. Role drop (up)	59
1.7.44.1. Methods	59
1.7.44.1.1. name	59
1.7.44.1.2. description	59
1.7.45. Search drop (up)	59
1.7.45.1. Methods	59
1.7.45.1.1. errors	59
1.7.45.1.2. query	59
1.7.45.1.3. total_found	59
1.7.45.1.4. results	60
1.7.46. Service drop (up)	60
1.7.46.1. Methods	60
1.7.46.1.1. errors	60
1.7.46.1.2. name	60
1.7.46.1.3. system_name	60
1.7.46.1.4. description	60
1.7.46.1.5. subscribed?	60
1.7.46.1.6. subscription	60
1.7.46.1.7. subscribable?	61
1.7.46.1.8. subscribe_url	61
1.7.46.1.9. application_plans	61
1.7.46.1.10. service_plans	61
1.7.46.1.11. plans	61
1.7.46.1.12. features	61

1.7.46.1.13. apps_identifier	62
1.7.46.1.14. backend_version	62
1.7.46.1.15. referrer_filters_required?	62
1.7.46.1.16. metrics	62
1.7.46.1.17. support_email	62
1.7.47. ServiceContract drop (up)	62
1.7.47.1. Methods	62
1.7.47.1.1. errors	62
1.7.47.1.2. id	62
1.7.47.1.3. can_change_plan?	62
1.7.47.1.4. trial?	62
1.7.47.1.5. live?	63
1.7.47.1.6. state	63
1.7.47.1.7. remaining_trial_period_days	63
1.7.47.1.8. plan	63
1.7.47.1.9. plan_change_permission_name	63
1.7.47.1.10. plan_change_permission_warning	63
1.7.47.1.11. contract	63
1.7.47.1.12. name	63
1.7.47.1.13. system_name	63
1.7.47.1.14. change_plan_url	63
1.7.47.1.15. service	63
1.7.47.1.16. applications	63
1.7.47.1.17. can	63
1.7.48. ServicePlan drop (up)	63
1.7.48.1. Methods	64
1.7.48.1.1. selected?	64
1.7.48.1.2. bought?	64
1.7.48.1.3. features	64
1.7.48.1.4. setup_fee	64
1.7.48.1.5. name	64
1.7.48.1.6. system_name	64
1.7.48.1.7. id	64
1.7.48.1.8. free?	65
1.7.48.1.9. paid?	65
1.7.48.1.10. approval_required?	65
1.7.48.1.11. flat_cost	65
1.7.48.1.12. service	65
1.7.49. TimeZone drop (up)	65
1.7.49.1. Methods	65
1.7.49.1.1. full_name	65
1.7.49.1.2. to_str	66
1.7.50. Today drop (up)	66
1.7.50.1. Methods	66
1.7.50.1.1. month	66
1.7.50.1.2. day	66
1.7.50.1.3. year	66
1.7.50.1.4. beginning_of_month	66
1.7.51. Topic drop (up)	66
1.7.51.1. Methods	66
1.7.51.1.1. errors	66
1.7.51.1.2. title	66
1.7.51.1.3. kind	66

1.7.51.1.4. url	66
1.7.51.1.5. description	66
1.7.52. Topic drop (up)	66
1.7.52.1. Methods	66
1.7.52.1.1. errors	67
1.7.52.1.2. title	67
1.7.52.1.3. url	67
1.7.53. Url drop (up)	67
1.7.53.1. Methods	67
1.7.53.1.1. to_s	67
1.7.53.1.2. to_str	67
1.7.53.1.3. title	67
1.7.53.1.4. current_or_subpath?	67
1.7.53.1.5. current?	67
1.7.53.1.6. active?	68
1.7.54. Urls drop (up)	68
1.7.54.1. Methods	68
1.7.54.1.1. provider	68
1.7.54.1.2. cas_login	68
1.7.54.1.3. new_application	68
1.7.54.1.4. signup	68
1.7.54.1.5. search	68
1.7.54.1.6. login	68
1.7.54.1.7. logout	68
1.7.54.1.8. forgot_password	68
1.7.54.1.9. service_subscription	69
1.7.54.1.10. compose_message	69
1.7.54.1.11. messages_outbox	69
1.7.54.1.12. messages_trash	69
1.7.54.1.13. empty_messages_trash	69
1.7.54.1.14. credit_card_terms	69
1.7.54.1.15. credit_card_privacy	69
1.7.54.1.16. credit_card_refunds	69
1.7.54.1.17. users	69
1.7.54.1.18. personal_details	69
1.7.54.1.19. access_details	69
1.7.54.1.20. payment_details	69
1.7.54.1.21. new_invitation	69
1.7.54.1.22. invitations	69
1.7.54.1.23. dashboard	69
1.7.54.1.24. applications	69
1.7.54.1.25. api_access_details	70
1.7.54.1.26. services	70
1.7.54.1.27. messages_inbox	70
1.7.54.1.28. stats	70
1.7.54.1.29. account_overview	70
1.7.54.1.30. account_plans	70
1.7.54.1.31. invoices	70
1.7.55. UsageLimit drop (up)	70
1.7.55.1. Methods	70
1.7.55.1.1. period	70
1.7.55.1.2. metric	70
1.7.55.1.3. value	70

1.7.56. User drop (up)	70
1.7.56.1. Methods	70
1.7.56.1.1. errors	70
1.7.56.1.2. admin?	71
1.7.56.1.3. username	71
1.7.56.1.4. account	71
1.7.56.1.5. name	71
1.7.56.1.6. email	71
1.7.56.1.7. password_required?	71
1.7.56.1.8. sections	71
1.7.56.1.9. role	71
1.7.56.1.10. roles_collection	72
1.7.56.1.11. url	72
1.7.56.1.12. edit_url	72
1.7.56.1.13. can	72
1.7.56.1.14. extra_fields	72
1.7.56.1.15. fields	72
1.7.56.1.16. builtin_fields	72
1.8. TAGS (UP)	73
1.8.1. Tag 'braintree_customer_form' (up)	73
1.8.2. Tag 'csrf' (up)	73
1.8.3. Tag 'content' (up)	73
1.8.4. Tag 'content_for' (up)	73
1.8.5. Tag 'debug' (up)	73
1.8.6. Tag 'email' (up)	73
1.8.7. Tag 'flash' (up)	74
1.8.8. Tag 'footer' (up)	74
1.8.9. Tag 'form' (up)	75
1.8.10. Tag 'latest_forum_posts' (up)	77
1.8.11. Tag 'latest_messages' (up)	77
1.8.12. Tag 'logo' (up)	77
1.8.13. Tag 'menu' (up)	77
1.8.14. Tag 'oldfooter' (up)	77
1.8.15. Tag 'plan_widget' (up)	77
1.8.16. Tag 'portlet' (up)	78
1.8.17. Tag 'submenu' (up)	78
1.8.18. Tag '3scale_essentials' (up)	78
1.8.19. Tag 'user_widget' (up)	78
1.9. FILTERS (UP)	78
1.9.1. FormHelpers filters (up)	78
1.9.1.1. error_class filter	78
1.9.1.2. inline_errors filter	78
1.9.2. ParamFilter filters (up)	78
1.9.2.1. to_param filter	79
1.9.3. Common filters (up)	79
1.9.3.1. group_by filter	79
1.9.3.2. any filter	79
1.9.3.3. stylesheet_link_tag filter	79
1.9.3.4. javascript_include_tag filter	79
1.9.3.5. image_tag filter	79
1.9.3.6. mail_to filter	79
1.9.3.7. html_safe filter	80
1.9.3.8. pluralize filter	80

1.9.3.9. delete_button filter	80
1.9.3.10. delete_button_ajax filter	80
1.9.3.11. update_button filter	80
1.9.3.12. create_button filter	80
1.9.3.13. create_button_ajax filter	80
1.9.3.14. regenerate_oauth_secret_button filter	80
1.9.3.15. link_to filter	80

CHAPTER 1. LIQUID REFERENCE

1.1. WHAT ARE LIQUIDS?

Liquid is a simple programming language used for displaying and processing most of the data from the 3scale system available for API providers. Liquid was originally developed by [Shopify](#) and is used in many other CMS engines throughout the web. In the 3scale platform, it is used to expose server-side data to your API developers, greatly extending the usefulness of the CMS while maintaining a high level of security.

1.1.1. Pros and cons

Liquids are mainly used to fetch and display server-side data on your Developer Portal pages. However there is much more power in liquids than just this. They serve very well for:

- Altering the DOM and content of a page based on server-side data
- Adding logic to pages, layouts, and partials
- Manipulating the email templates sent to developers

There are some use cases where liquids don't provide the best solution to the problem, mostly situations where you need to use dynamic data such as input from the user or the page URL.

Some general advice is to use them as the primary way to add logic to the page, but then if you find it impossible or overly complicated, switch to JavaScript (or add them to it, as liquids also work well with JS).

1.2. HOW TO USE LIQUIDS

Liquid markup is divided into two types: logic tags and output tags. The logic tags, marked as `MISSING`, are conditional liquid statements that include standard programming language elements such as the "if" clause, loops, etc.

```
{% if current_user %}      <!-- if the user is logged in -->
  <a href="/logout">Logout</a> <!-- show the logout link -->
{% else %}                 <!-- if the user is not logged in -->
  <a href="/login">Login</a>  <!-- display the login link -->
{% endif %}
```

Output tags, marked as `'{{ }}'`, are used to display the value of the tag between the curly braces.

```
{{ current_user.username }} <!-- display the logged-in user's username value -->
```

For documentation on logic tags, please refer to the [Shopify tutorial](#). The full reference of the 3scale liquid output tags can be found both on [this page](#) as well as in your Admin Portal under **Help > Liquid Reference**.

1.2.1. Liquid drops, tags, and their meanings

In the 3scale CMS, you will have access to three types of liquid markup:

- liquid drops (e.g. `{{ current_account.name }}`)

- liquid tags (e.g. `{% content %}`)
- filters (e.g. `{{ form.errors.description | error_class }}`)

You can find a [complete list of liquid tags, drops, and filters available here](#)

As you can see, they're almost the same as the logic and output tags, and they work very similarly. Liquid drops are the most basic structure, and you will be using them most of the time. They give access to certain values stored in the system such as the name of the user and the ID of the application. They're handled by the interpreter in the same way as any other output tags.

On the other hand, liquid tags are a type of logic tag that renders or accesses certain parts of the system for further customization – for example, to render content in the layout or customize email templates.

Filters, as the name suggests, enable the option of filtering results from the drops, converting values, grouping by some key, etc. There is a group of standard liquids filters, which you can find on the [Shopify website](#)) and a group of special 3scale internal filters, which are listed on the [reference page](#).

1.2.2. The context

The context describes which variables (drops) are available to use on the current page. The basic set includes the following variables:

- provider
- urls
- current_user
- current_account
- today

These variables are available on every page throughout the CMS (except for email templates). However, most of the built-in pages will have some additional variables available. For example, the edit user form will have a user variable exposed (instead of current user – on edit user page, the identity of the user is already known). To check which variables are available on the current page, there is a special tag: `{% debug:help %}`. It adds the list of all the top-level variables available to use as a comment in the source of the page.

1.2.3. Hierarchy

The direct consequence of the context is that the liquid drops are organized in a hierarchical structure. The available set of variables only gives you the list of the top level drops that are available. Using them, you can get access to elements much deeper inside the hierarchy. For example, if you would like to show the username of the logged-in user, you would write `{{ current_user.username }}`.

Displaying lower level drops is a little bit more complicated. Assume that you would like to display the name of the only application for a user. Looking at the reference guide, you can see that the method "applications" is a part of the account drop. This means that applications is an array of single-application tags. If your users are allowed to have more than one application, then you would have to iterate through them using the logic tags. Otherwise, you can refer to the first (and only) application on the account. The code to display this would look like this: `{{ current_account.applications.first.name }}`.

1.3. LIQUID TEMPLATES

The following variables are available in every Liquid template:

- [provider](#) - all your services, plans and settings under one hood
- [urls](#) - routes to built-in pages of the developers portal (login, signup etc.)
- [current_user](#) - username, address and rights of the **currently logged-in user**
- [current_account](#) - messages, applications and plans of the **currently logged-in user**
- [today](#) - current date

Builtin pages can also have other variables available (they are mentioned in the CMS editor). For example, an edit user form edit will have a **user** variable assigned or while displaying an application detail, you can expect to have a variable **application** accessible.

The type of a variable (an important thing to know to use this reference) can be determined by putting a **{% debug:help %}** tag into the page which will list all the available variables and it's types in an HTML comment for you. However, usually they can be guessed quite easily from the method or variable name.

1.4. DROPS

- [Account drop](#)
- [AccountPlan drop](#)
- [Alert drop](#)
- [Application drop](#)
- [ApplicationKey drop](#)
- [ApplicationPlan drop](#)
- [Base drop](#)
- [Base drop](#)
- [BillingAddressField drop](#)
- [Can drop](#)
- [Can drop](#)
- [Cas drop](#)
- [Contract drop](#)
- [Country drop](#)
- [CountryField drop](#)
- [CurrentUser drop](#)
- [Error drop](#)

- [Errors drop](#)
- [Feature drop](#)
- [Field drop](#)
- [Flash drop](#)
- [Forum drop](#)
- [I18n drop](#)
- [Invitation drop](#)
- [Invoice drop](#)
- [LineItem drop](#)
- [Message drop](#)
- [Message drop](#)
- [Metric drop](#)
- [Page drop](#)
- [Page drop](#)
- [Pagination drop](#)
- [Part drop](#)
- [PaymentGateway drop](#)
- [PaymentTransaction drop](#)
- [PlanFeature drop](#)
- [Post drop](#)
- [Post drop](#)
- [PricingRule drop](#)
- [Provider drop](#)
- [ReferrerFilter drop](#)
- [Request drop](#)
- [Role drop](#)
- [Search drop](#)
- [Service drop](#)
- [ServiceContract drop](#)

- [ServicePlan drop](#)
- [TimeZone drop](#)
- [Today drop](#)
- [Topic drop](#)
- [Topic drop](#)
- [URL drop](#)
- [URLs drop](#)
- [UsageLimit drop](#)
- [User drop](#)

1.5. TAGS

- [Tag 'braintree_customer_form'](#)
- [Tag 'csrf'](#)
- [Tag 'content'](#)
- [Tag 'content_for'](#)
- [Tag 'debug'](#)
- [Tag 'email'](#)
- [Tag 'flash'](#)
- [Tag 'footer'](#)
- [Tag 'form'](#)
- [Tag 'latest_forum_posts'](#)
- [Tag 'latest_messages'](#)
- [Tag 'logo'](#)
- [Tag 'menu'](#)
- [Tag 'oldfooter'](#)
- [Tag 'plan_widget'](#)
- [Tag 'portlet'](#)
- [Tag 'submenu'](#)
- [Tag '3scale_essentials'](#)
- [Tag 'user_widget'](#)

1.6. FILTERS

- [FormHelpers filters](#)
- [ParamFilter filters](#)
- [Common filters](#)

1.7. DROPS (UP)

1.7.1. Account drop (up)

A developer account. See **User** drop if you are looking for the email addresses or similar information.

```

<h2>Account organization name {{ current_account.name }}</h2>
Plan {{ current_account.bought_account_plan.name }}
Telephone {{ current_account.telephone_number }}

{{ current_account.fields_plain_text }}
{{ current_account.extra_fields_plain_text }}

{% if current_account.approval_required? %}
  <p>This account requires approval.</p>
{% endif %}

{% if current_account.credit_card_required? %}

  {% if current_account.credit_card_stored? %}
    <p>This account has credit card details stored in database.</p>
  {% else %}
    <p>Please enter your {{ 'credit card details' | link_to: urls.payment_details }}.</p>
  {% endif %}

  {% if current_account.credit_card_missing? %}
    <p>This account has no credit card details stored in database.</p>
  {% endif %}
{% endif %}

```

1.7.1.1. Methods

1.7.1.1.1. errors

If a form of this model is rendered after unsuccessful submit, this returns" errors that occurred.

```

{{ account.errors.name | inline_errors }}

```

1.7.1.1.2. id

Returns the id of the account

1.7.1.1.3. name

Returns the organization name of the developer's account

1.7.1.1.4. vat_zero_text

Return a text about a vat zero

1.7.1.1.5. vat_rate

Return the vat rate

1.7.1.1.6. unread_messages

Unread messages

1.7.1.1.7. latest_messages

Return the latest messages

1.7.1.1.8. bought_account_plan

Returns the plan the account has contracted

1.7.1.1.9. bought_account_contract

Returns the contract account

1.7.1.1.10. credit_card_display_number**1.7.1.1.11. credit_card_expiration_date****1.7.1.1.12. credit_card_required?**

Returns whether the account is required to enter credit card details

1.7.1.1.13. credit_card_stored?

Returns whether the account has credit card details stored

1.7.1.1.14. credit_card_missing?

Returns whether the account has no credit card details stored

1.7.1.1.15. timezone

Returns timezone of this account

1.7.1.1.16. paid?

Returns whether the account has at least a paid contract

1.7.1.1.17. on_trial?

Returns whether the account is on trial period, i.e. all his paid contracts has to be in trial period

1.7.1.1.18. telephone_number

Returns the telephone number of the account

1.7.1.1.19. approval_required?

Returns whether the account requires approval?

1.7.1.1.20. created_at

Returns UNIX timestamp of account creation (signup) **Example:** Converting timestamp to JavaScript Date

```
<script>
  var data = new Date({{ account.created_at }} * 1000);
</script>
```

1.7.1.1.21. full_address

Can be composed by legal address, city and state

1.7.1.1.22. applications

Returns the applications of the account

1.7.1.1.23. subscribed_services

Returns a array with ServiceContract drops

1.7.1.1.24. admin

Returns the admin user of this account

1.7.1.1.25. extra_fields_plain_text

Returns the extra fields defined for the account as plain text

1.7.1.1.26. fields_plain_text

Returns the fields defined for the account as plain text

1.7.1.1.27. extra_fields

Returns only extra fields with values of this account **Example:** Print all extra fields

```
{% for field in account.extra_fields %}
  {{ field.label }}: {{ field.value }}
{% endfor %}
```

1.7.1.1.28. fields

Returns all fields with values of this account **Example:** Print all fields

```
{% for field in account.fields %}
  {{ field.label }}: {{ field.value }}
{% endfor %}
```

1.7.1.1.29. builtin_fields

1.7.1.1.30. multiple_applications_allowed?

1.7.1.1.31. billing_address

Returns the billing address of this account

1.7.1.1.32. has_billing_address?

Returns whether this account has a billing address or not

1.7.1.1.33. can

Give access to permission methods

```
{% if account.can.be_deleted? %}
  <!-- do something -->
{% endif %}
```

1.7.1.1.34. edit_url

1.7.1.1.35. edit_ogone_billing_address_url

1.7.1.1.36. edit_payment_express_billing_address_url

1.7.1.1.37. edit_braintree_blue_credit_card_details_url

1.7.1.1.38. domain

1.7.1.1.39. upgraded?

1.7.1.1.40. requires_credit_card?

1.7.1.1.41. support_email

1.7.1.1.42. finance_support_email

1.7.2. AccountPlan drop (up)

Example: Using account plan drop in liquid

```
<p class="notice">The examples for plan drop apply here</p>
```

1.7.2.1. Methods

1.7.2.1.1. selected?

Returns whether the plan is selected

```
{% if plan.selected? %}  
  <p>You will signup to {{ plan.name }}</p>  
{% endif %}
```

1.7.2.1.2. bought?

Returns whether the plan is bought

```
{% if plan.bought? %}  
  <p>You are on this plan already!</p>  
{% endif %}
```

1.7.2.1.3. features

Returns an array of available features

1.7.2.1.4. setup_fee

Returns the setup fee

1.7.2.1.5. name

Returns the name of the plan

```
<h2>We offer you a new {{ plan.name }} plan!</h2>
```

1.7.2.1.6. system_name

Returns the system name of the plan

```
{% for plan in available_plans %}  
  {% if plan.system_name == 'my_free_plan' %}  
  
    <p>You will buy our only free plan!</p>  
  {% endif %}  
{% endfor %}
```

1.7.2.1.7. id

Returns the plan id

1.7.2.1.8. free?

The plan is free if it is not 'paid' (see the 'paid?' method)

```
{% if plan.free? %}
  <p>This plan is free of charge.</p>
{% else %}

  <p>Plan costs</p>
  Setup fee {{ plan.setup_fee }}
  Flat cost {{ plan.flat_cost }}

{% endif %}
```

1.7.2.1.9. paid?

The plan is 'paid' when it has non-zero fixed or setup fee or there are some pricing rules present

```
{% if plan.paid? %}
  <p>this plan is a paid one.</p>
{% else %}
  <p>this plan is a free one.</p>
{% endif %}
```

1.7.2.1.10. approval_required?

Returns whether the plan requires approval?

```
{% if plan.approval_required? %}
  <p>This plan requires approval.</p>
{% endif %}
```

1.7.2.1.11. flat_cost

Returns the monthly fixed fee of the plan

1.7.3. Alert drop (up)

Example: Using alert drop in liquid

```
<h2>Alert details</h2>
Level {{ alert.level }}
Message {{ alert.message }}
Utilization {{ alert.utilization }}
```

1.7.3.1. Methods

1.7.3.1.1. level

The alert level can be one of 50, 80, 90, 100, 120, 150, 200, 300.

1.7.3.1.2. message

Text message describing the alert, for example 'hits per minute: 5 of 5'

1.7.3.1.3. utilization

Decimal number marking the actual utilization that triggered the alert (1.0 is equal to 100%).

Used by `{{ alert.utilization | times: 100 }}` percent.

1.7.4. Application drop (up)

Example: Using application drop in liquid

```
<h2>Application {{ application.name }} ({{ application.application_id }})</h2>
<p>{{ application.description }}</p>
```

1.7.4.1. Methods

1.7.4.1.1. errors

If a form of this model is rendered after unsuccessful submit, this returns" errors that occurred.

```
{{ application.errors.name | inline_errors }}
```

1.7.4.1.2. id

Returns the id of the application

1.7.4.1.3. can_change_plan?

Returns 'true' if changing of the application is allowed either directly or by request.

1.7.4.1.4. trial?

Returns true if the contract is still in the trial period.

Note: If you change the trial period length of a plan, it does not affect the existing contracts.

1.7.4.1.5. live?

1.7.4.1.6. state

There are three possible states:

- pending
- live
- suspended

1.7.4.1.7. remaining_trial_period_days

Number of day still left in the trial period.

1.7.4.1.8. plan

Returns a plan drop with the plan of the application

1.7.4.1.9. plan_change_permission_name

Returns name of the allowed action

1.7.4.1.10. plan_change_permission_warning

Returns a warning messenger of the allowed action

1.7.4.1.11. contract

1.7.4.1.12. admin_url

Returns the admin_url of the application

1.7.4.1.13. name

Returns the name of the application

1.7.4.1.14. can

1.7.4.1.15. oauth

1.7.4.1.16. pending?

Returns 'true' if application state is pending

1.7.4.1.17. buyer_alerts_enabled?

1.7.4.1.18. description

Returns the description of the application

1.7.4.1.19. redirect_url

Returns the redirect url for the OAuth of the application

1.7.4.1.20. filters_limit

Returns the amount of referrer filters allowed for this application

1.7.4.1.21. keys_limit

Returns the amount of application keys allowed for this application

1.7.4.1.22. referrer_filters

Returns the referrer filters associated with this application

1.7.4.1.23. rejection_reason

Returns the reason for rejecting an application

1.7.4.1.24. user_key

Returns the user_key of application

1.7.4.1.25. application_id

Returns the application_id of an application

1.7.4.1.26. key

Returns the application id or the user key

1.7.4.1.27. url

Returns URL of the builtin detail view for this application.

1.7.4.1.28. edit_url

Returns URL of the builtin edit view for this application.

1.7.4.1.29. update_user_key_url

1.7.4.1.30. log_requests_url

1.7.4.1.31. alerts_url

1.7.4.1.32. application_keys_url

1.7.4.1.33. service

Service to which that application belongs to.

1.7.4.1.34. keys

Returns the keys of an application

```
{% case application.keys.size %}
{% when 0 %}
  Generate your application key.
{% when 1 %}
  <h4>Application key for {{ application.name }} {{ application.application_id }}</h4>
  <p>Key is: {{ application.keys.first }}</p>
{% else %}
  <h4>Application keys for {{ application.name }} {{ application.application_id }}</h4>
  <ul>
    {% for key in application.keys %}
      <li>{{ key }}</li>
    {% endfor %}
  </ul>
{% endcase %}
```


1.7.4.1.35. user_key_mode?

1.7.4.1.36. app_id_mode?

1.7.4.1.37. change_plan_url

1.7.4.1.38. log_requests?

1.7.4.1.39. application_keys

1.7.4.1.40. extra_fields

Returns non-hidden extra fields with values for this application **Example:** Print all extra fields

```
{% for field in application.extra_fields %}
  {{ field.label }}: {{ field.value }}
{% endfor %}
```

1.7.4.1.41. fields

Returns all builtin and extra fields with values for this application **Example:** Print all fields

```
{% for field in application.fields %}
  {{ field.label }}: {{ field.value }}
{% endfor %}
```

1.7.4.1.42. builtin_fields

Returns only builtin fields of the application

1.7.4.1.43. cinstance

1.7.5. ApplicationKey drop [\(up\)](#)

1.7.5.1. Methods

1.7.5.1.1. id

1.7.5.1.2. value

1.7.5.1.3. url

1.7.5.1.4. application

1.7.6. ApplicationPlan drop [\(up\)](#)

1.7.6.1. Methods

1.7.6.1.1. selected?

Returns whether the plan is selected

```
{% if plan.selected? %}  
  <p>You will signup to {{ plan.name }}</p>  
{% endif %}
```

1.7.6.1.2. bought?

Returns whether the plan is bought

```
{% if plan.bought? %}  
  <p>You are on this plan already!</p>  
{% endif %}
```

1.7.6.1.3. features

Returns the visible features of the plan

```
{% if plan == my_free_plan %}  
  <p>These plans are the same.</p>  
{% else %}  
  <p>These plans are not the same.</p>  
{% endif %}
```

1.7.6.1.4. setup_fee

Returns the setup fee of the plan

1.7.6.1.5. name

Returns the name of the plan

```
<h2>We offer you a new {{ plan.name }} plan!</h2>
```

1.7.6.1.6. system_name

Returns the system name of the plan

```
{% for plan in available_plans %}  
  {% if plan.system_name == 'my_free_plan' %}  
  
    <p>You will buy our only free plan!</p>  
  {% endif %}  
{% endfor %}
```

1.7.6.1.7. id

Returns the plan id

1.7.6.1.8. free?

The plan is free if it is not 'paid' (see the 'paid?' method)

```

{% if plan.free? %}
  <p>This plan is free of charge.</p>
{% else %}

  <p>Plan costs</p>
  Setup fee {{ plan.setup_fee }}
  Flat cost {{ plan.flat_cost }}

{% endif %}

```

1.7.6.1.9. paid?

The plan is 'paid' when it has non-zero fixed or setup fee or there are some pricing rules present

```

{% if plan.paid? %}
  <p>this plan is a paid one.</p>
{% else %}
  <p>this plan is a free one.</p>
{% endif %}

```

1.7.6.1.10. approval_required?

Returns whether the plan requires approval?

```

{% if plan.approval_required? %}
  <p>This plan requires approval.</p>
{% endif %}

```

1.7.6.1.11. flat_cost

Returns the monthly fixed fee of the plan

1.7.6.1.12. metrics

Returns the metrics of the plan

1.7.6.1.13. usage_limits

Returns the usage limits of the plan

1.7.6.1.14. service

Returns the service of the plan

1.7.7. Base drop (up)

1.7.7.1. Methods

1.7.7.1.1. login_url

1.7.7.1.2. user_identified?

1.7.8. Base drop (up)

1.7.8.1. Methods

1.7.8.1.1. errors

If a form of this model is rendered after unsuccessful submit, this returns" errors that occurred.

```
{{ base.errors.name | inline_errors }}
```

1.7.8.1.2. title

Returns the title result

1.7.8.1.3. kind

Returns the kind of result, can be 'topic' or 'page'

1.7.8.1.4. url

Returns the resource url of the result

1.7.8.1.5. description

Returns a descriptive string for the result

1.7.9. BillingAddressField drop (up)

1.7.9.1. Methods

1.7.9.1.1. input_name

1.7.9.1.2. label

1.7.9.1.3. choices

1.7.9.1.4. errors

1.7.9.1.5. html_id

1.7.9.1.6. hidden?

1.7.9.1.7. visible?

1.7.9.1.8. read_only?

1.7.9.1.9. name

1.7.9.1.10. value

1.7.9.1.11. required

1.7.10. Can drop (up)

1.7.10.1. Methods

1.7.10.1.1. be_updated?

1.7.10.1.2. add_referrer_filters?

1.7.10.1.3. add_application_keys?

1.7.10.1.4. regenerate_user_key?

1.7.10.1.5. regenerate_oauth_secret?

1.7.10.1.6. manage_keys?

1.7.10.1.7. delete_key?

1.7.11. Can drop (up)

1.7.11.1. Methods

1.7.11.1.1. change_plan?

1.7.12. Cas drop (up)

1.7.12.1. Methods

1.7.12.1.1. login_url

1.7.12.1.2. user_identified?

1.7.13. Contract drop (up)

Plan of the contract {{ contract.plan.name }}

1.7.13.1. Methods

1.7.13.1.1. errors

If a form of this model is rendered after unsuccessful submit, this returns" errors that occurred.

```
{{ contract.errors.name | inline_errors }}
```

1.7.13.1.2. id

Returns the id

1.7.13.1.3. can_change_plan?

Returns true if any form of change is possible

1.7.13.1.4. trial?

Returns true if the contract is still in the trial period.

Note: If you change the trial period length of a plan, it does not affect the existing contracts.

1.7.13.1.5. live?

1.7.13.1.6. state

There are three possible states:

- pending
- live
- suspended

1.7.13.1.7. remaining_trial_period_days

Number of day still left in the trial period.

1.7.13.1.8. plan

Returns the plan of the contract

1.7.13.1.9. plan_change_permission_name

Returns name of the allowed action

1.7.13.1.10. plan_change_permission_warning

Returns a warning messenger of the allowed action

1.7.13.1.11. contract

1.7.14. Country drop (up)

1.7.14.1. Methods

1.7.14.1.1. errors

If a form of this model is rendered after unsuccessful submit, this returns" errors that occurred.

```
{{ country.errors.name | inline_errors }}
```

1.7.14.1.2. to_str

1.7.14.1.3. code

1.7.14.1.4. label

1.7.15. CountryField drop (up)

1.7.15.1. Methods

1.7.15.1.1. value

Returns ID of the country

```
{{ account.fields.country.value }} => 42
```

compare with:

```
{{ account.fields.country }} => 'United States'
```

1.7.15.1.2. name

Returns system name of the field

1.7.15.1.3. required

1.7.15.1.4. hidden?

1.7.15.1.5. hidden

1.7.15.1.6. visible?

1.7.15.1.7. visible

1.7.15.1.8. read_only

1.7.15.1.9. errors

1.7.15.1.10. input_name

1.7.15.1.11. html_id

1.7.15.1.12. label

Returns label of the field

```
{{ account.fields.country.label }}  
<!-- => 'Country' -->
```

1.7.15.1.13. to_str

Returns name of the country

```
{{ account.fields.country }} => 'United States'
```

1.7.15.1.14. choices

1.7.16. CurrentUser drop (up)

1.7.16.1. Methods

1.7.16.1.1. errors

If a form of this model is rendered after unsuccessful submit, this returns" errors that occurred.

```
{{ current_user.errors.name | inline_errors }}
```

1.7.16.1.2. admin?

Returns whether the user is an admin.

```
{% if user.admin? %}  
<p>You are an admin of your account.</p>  
{% endif %}
```

1.7.16.1.3. username

Returns the username of the user, html escaped.

1.7.16.1.4. account

Returns the account of the user.

1.7.16.1.5. name

Returns the first and surname of the user.

1.7.16.1.6. email

Returns the email of the user.

1.7.16.1.7. password_required?

This method will return **true** for users using the builtin Developer Portal authentication mechanisms and **false** for those that are authenticated via Janrain, CAS or other single-sign-on method.

```

{{ if user.password_required? }}

{{ endif }}

```

1.7.16.1.8. sections

Returns the list of sections the user has access to.

```

{% if user.sections.size > 0 %}
  <p>You can access following sections of our portal:</p>
  <ul>
    {% for section in user.sections %}
      <li>{{ section }}</li>
    {% endfor %}
  </ul>
{% endif %}

```

1.7.16.1.9. role

Returns the role of the user

1.7.16.1.10. roles_collection

Returns a list of available roles for the user

```

{% for role in user.roles_collection %}
  <li>
    <label for="user_role_{{ role.key }}">

      {{ role.text&nbsp; }}
    </label>
  </li>
{% endfor %}

```

1.7.16.1.11. url

Return the resource url of the user

```

{{ 'Delete' | delete_button: user.url }}

```

1.7.16.1.12. edit_url

Return the url to edit the user

```

{{ 'Edit' | link_to: user.edit_url, title: 'Edit', class: 'action edit' }}

```

1.7.16.1.13. can

Exposes rights of current user which are dependent on your settings and user's role. You can call these methods on the returned object:

- `invite_user?`
- `create_application?`
- `see_log_requests?`

```
{% if current_user.can.see_log_requests? and application.log_requests? %}
  (<a href="{{ application.log_requests_url }}" class="action edit">App Request Log</a>)
{% endif %}
```

1.7.16.1.14. `extra_fields`

Returns non-hidden extra fields with values for this user **Example:** Print all extra fields

```
{% for field in user.extra_fields %}
  {{ field.label }}: {{ field.value }}
{% endfor %}
```

1.7.16.1.15. `fields`

Returns all fields with values for this user **Example:** Print all fields

```
{% for field in user.fields %}
  {{ field.label }}: {{ field.value }}
{% endfor %}
```

1.7.16.1.16. `builtin_fields`

Returns all builtin fields with values for this user

1.7.17. Error drop (up)

When a form fails to submit because of invalid data, the **errors** array will be available on the related model.

1.7.17.1. Methods

1.7.17.1.1. `attribute`

Returns attribute of the model to this error is related

```
{{ account.errors.org_name.first.attribute }}
<!-- org_name -->
```

1.7.17.1.2. `message`

Returns description of the error

```

{{ account.errors.first.message }}
<!-- can't be blank -->

```

1.7.17.1.3. value

Returns value of the attribute to which the **error** is related

```

{{ account.errors.org_name.first.value }}
<!-- => "ACME Co." -->

```

1.7.17.1.4. to_str

Returns full description of the error (includes the attribute name)

```

{{ model.errors.first }}
<!-- => "Attribute can't be blank" -->

```

1.7.18. Errors drop (up)

Example: get all errors

```

{% for error in form.errors %}
  attribute: {{ error.attribute }}
  ...
{% endfor %}

```

1.7.18.1. Methods

1.7.18.1.1. empty?

Returns true if there are no errors

```

{% if form.errors == empty %}
  Congratulations! You have no errors!
{% endif %}

```

1.7.18.1.2. present?

Returns true if there are some errors

```

{% if form.errors == present %}
  Sorry, there were some errors.
{% endif %}

```

1.7.19. Feature drop (up)

1.7.19.1. Methods

1.7.19.1.1. errors

If a form of this model is rendered after unsuccessful submit, this returns" errors that occurred.

```
{{ feature.errors.name | inline_errors }}
```

1.7.19.1.2. name

Returns the name of the feature

```
<h2>Feature {{ feature.name }}</h2>
```

1.7.19.1.3. description

Returns the description of the feature

1.7.19.1.4. has_description?

Returns whether the feature has description

```
{% if feature.has_description? %}  
  {{ feature.description }}  
{% else %}  
  This feature has no description.  
{% endif %}
```

1.7.20. Field drop [\(up\)](#)

1.7.20.1. Methods

1.7.20.1.1. value

Returns value if the field

```
Name: {{ account.fields.first_name.value }}
```

1.7.20.1.2. name

Returns system name of the field

1.7.20.1.3. required

1.7.20.1.4. hidden?

1.7.20.1.5. hidden

1.7.20.1.6. visible?

1.7.20.1.7. visible

1.7.20.1.8. read_only

1.7.20.1.9. errors

1.7.20.1.10. input_name

Returns name for the HTML input that is expected when the form is submitted.

```
<!-- the 'name' attribute will be 'account[country]' -->
```

1.7.20.1.11. html_id

Returns a unique field identifier that is commonly used as HTML ID attribute.

```
{{ account.fields.country.html_id }}
<!-- => 'account_country' -->
```

1.7.20.1.12. label

Returns label of the field

```
{{ account.fields.country.label }}
<!-- => 'Country' -->
```

1.7.20.1.13. to_str

Returns value of the field if used as variable

```
{{ account.fields.first_name }} => 'Tom'
```

1.7.20.1.14. choices

Returns array of choices available for that field, if any. For example for a field called **fruit** it may respond with **['apple', 'bannana', 'orange']**.

You can define the choices in your `/admin/fields_definitions[admin dashboard]`. Each of the array elements responds to **id** and **label** which are usually just the same unless the field is a special builtin one (like **country**) It is recommended to use those methods rather than output the **choice** 'as is' for future compatibility.

```
{% for choice in field.choices %}
  <select name="{{ field.input_name }}" id="{{ field.html_id }}_id"
    class="{{ field.errors | error_class }}">
    <option {% if field.value == choice %} selected {% endif %} value="{{ choice.id }}">
      {{ choice }}
    </option>
  {% endfor %}
```

1.7.21. Flash drop (up)

1.7.21.1. Methods

1.7.21.1.1. messages

Return an array of messages

```
{% for message in flash.messages %}
  <p id="flash-{{ message.type }}">
    {{ message.text }}
  </p>
{% endfor %}
```

1.7.22. Forum drop (up)

1.7.22.1. Methods

1.7.22.1.1. enabled?

Returns true if you have forum functionality enabled.

```
{% if forum.enabled? %}
  <a href="/forum">Check out our forum!</a>
{% endif %}
```

1.7.22.1.2. latest_posts

1.7.23. I18n drop (up)

Provide useful strings for i18n support.

```
{{ object.some_date | date: i18n.long_date }}
```

1.7.23.1. Methods

1.7.23.1.1. short_date

Alias for **%b %d**

```
Dec 11
```

1.7.23.1.2. long_date

Alias for **%B %d, %Y**

```
December 11, 2013
```

1.7.23.1.3. default_date

Alias for **%Y-%m-%d**

```
2013-12-11
```

1.7.24. Invitation drop (up)

```
Email: {{ invitation.email }}
```

```
<tr id="invitation_{{ invitation.id }}">
  <td> {{ invitation.email }} </td>
  <td> {{ invitation.sent_at | date: i18n.short_date }} </td>
  <td>
    {% if invitation.accepted? %}
      yes, on {{invitation.accepted_at | format: i18n.short_date }}
    {% else %}
      no
    {% endif %}
  </td>
</tr>
```

1.7.24.1. Methods

1.7.24.1.1. errors

If a form of this model is rendered after unsuccessful submit, this returns" errors that occurred.

```
{{ invitation.errors.name | inline_errors }}
```

1.7.24.1.2. email

Returns email address

1.7.24.1.3. accepted?

Returns true if the invitation was accepted

1.7.24.1.4. accepted_at

Returns a date if the invitations was accepted

```
{{ invitation.accepted_at | date: i18n.short_date }}
```

1.7.24.1.5. sent_at

Returns the creation date

```
{{ invitation.sent_at | date: i18n.short_date }}
```

1.7.24.1.6. resend_url

Returns the url for resend the invitation

```
{{ "Resend" | update_button: invitation.resend_url}}
```

1.7.24.1.7. url

Returns the resource url

```
{{ "Delete" | delete_button: invitation.url }}
```

1.7.25. Invoice drop (up)

1.7.25.1. Methods

1.7.25.1.1. errors

If a form of this model is rendered after unsuccessful submit, this returns" errors that occurred.

```
{{ invoice.errors.name | inline_errors }}
```

1.7.25.1.2. friendly_id

Returns a friendly id

```
<td> {{ invoice.id }} </td>  
<td> {{ invoice.name }} </td>  
<td> {{ invoice.state }} </td>  
<td> {{ invoice.cost }} {{ invoice.currency }} </td>
```

1.7.25.1.3. name

String composed by month and year

1.7.25.1.4. state

1.7.25.1.5. cost

Returns a number with two decimals

```
23.00
```

1.7.25.1.6. currency

1.7.25.1.7. cost_without_vat

Returns cost without VAT

1.7.25.1.8. vat_amount

Returns vat amount

1.7.25.1.9. exists_pdf?

Return true if the pdf was generated

1.7.25.1.10. period_begin

```

{{ invoice.period_begin | date: i18n.short_date }}

```

1.7.25.1.11. period_end

```

{{ invoice.period_end | date: i18n.long_date }}

```

1.7.25.1.12. issued_on

```

{{ invoice.issued_on | date: i18n.long_date }}

```

1.7.25.1.13. due_on

```

{{ invoice.due_on | date: i18n.long_date }}

```

1.7.25.1.14. paid_on

```

{{ invoice.paid_on | date: i18n.long_date }}

```

1.7.25.1.15. vat_code**1.7.25.1.16. fiscal_code****1.7.25.1.17. account**

Return a AccountDrop

1.7.25.1.18. buyer_account**1.7.25.1.19. line_items**

Returns a array of LineltemDrop

```

{% for line_item in invoice.line_items %}
  <tr class="line_item {% cycle 'odd', 'even' %}">
    <th>{{ line_item.name }}</th>
    <td>{{ line_item.description }}</td>
    <td>{{ line_item.quantity }}</td>
    <td>{{ line_item.cost }}</td>
  </tr>
{% endfor %}

```

1.7.25.1.20. payment_transactions

Returns a array of PaymentTransactionDrop

```

{% for payment_transaction in invoice.payment_transactions %}
  <tr>

```

```

<td> {% if payment_transaction.success? %} Success {% else %} Failure {% endif %} </td>
<td> {{ payment_transaction.created_at }} </td>
<td> {{ payment_transaction.reference }} </td>
<td> {{ payment_transaction.message }} </td>
<td> {{ payment_transaction.amount }} {{ payment_transaction.currency }} </td>
</tr>
{% endfor %}

```

1.7.25.1.21. url

Return the resource url of the invoice

```

{{ "Show" | link_to: invoice.url }}

```

1.7.25.1.22. pdf_url

Return the resource url of the invoice pdf

```

{{ "PDF" | link_to: invoice.pdf_url }}

```

1.7.26. Janrain drop [\(up\)](#)

1.7.26.1. Methods

1.7.26.1.1. login_url

1.7.26.1.2. user_identified?

1.7.26.1.3. session_url

1.7.26.1.4. relying_party

1.7.27. Lineltem drop [\(up\)](#)

1.7.27.1. Methods

1.7.27.1.1. errors

If a form of this model is rendered after unsuccessful submit, this returns" errors that occurred.

```

{{ line_item.errors.name | inline_errors }}

```

1.7.27.1.2. name

```

{% for line_item in invoice.line_items %}
<tr class="line_item {% cycle 'odd', 'even' %}">
<th>{{ line_item.name }}</th>
<td>{{ line_item.description }}</td>
<td>{{ line_item.quantity }}</td>

```

```

    <td>{{ line_item.cost }}</td>
  </tr>
{% endfor %}

```

1.7.27.1.3. description

1.7.27.1.4. quantity

1.7.27.1.5. cost

1.7.28. Message drop (up)

1.7.28.1. Methods

1.7.28.1.1. errors

If a form of this model is rendered after unsuccessful submit, this returns" errors that occurred.

```

{{ message.errors.name | inline_errors }}

```

1.7.28.1.2. id

Returns the id of the message

1.7.28.1.3. subject

If subject is not present then either a truncated body or **(no subject)** string is returned.

1.7.28.1.4. body

Body of the message

1.7.28.1.5. created_at

Returns the creation date

```

{{ message.created_at | date: i18n.short_date }}

```

1.7.28.1.6. url

URL of the message detail, points either to inbox or outbox.

1.7.28.1.7. state

Either 'read' or 'unread'

1.7.28.1.8. sender

Returns the name of the sender

1.7.28.1.9. to

Returns the name of the receiver

1.7.28.1.10. recipients

1.7.29. Message drop (up)

1.7.29.1. Methods

1.7.29.1.1. type

The possible types of the messages are:

- success (not used by now)
- info
- warning
- danger

1.7.29.1.2. text

1.7.30. Metric drop (up)

1.7.30.1. Methods

1.7.30.1.1. errors

If a form of this model is rendered after unsuccessful submit, this returns" errors that occurred.

```
{{ metric.errors.name | inline_errors }}
```

1.7.30.1.2. unit

Returns the unit of the metric

```
This metric is measured in {{ metric.unit | pluralize }}
```

1.7.30.1.3. description

Returns the description of the metric

1.7.30.1.4. name

Returns the name of the metric

```
<h4>Metric {{ metric.name }}</h4>  
<p>{{ metric.description }}</p>
```

1.7.30.1.5. system_name

Returns the system name of this metric

```

<h4>Metric {{ metric.name }}</h4>
<p>{{ metric.system_name }}</p>

```

1.7.30.1.6. usage_limits

Returns the usage limits of the metric

```

{% if metric.usage_limits.size > 0 %}
  <p>Usage limits of the metric</p>
  <ul>
    {% for usage_limit in metric.usage_limits %}
      <li>{{ usage_limit.period }} : {{ usage_limit.value }}</li>
    {% endfor %}
  </ul>
{% else %}
  <p>This metric has no usage limits</p>
{% endif %}

```

1.7.30.1.7. pricing_rules

Returns the pricing rules of the metric

```

{% if metric.pricing_rules.size > 0 %}
  <p>Pricing rules of the metric</p>
  <ul>
    {% for pricing_rule in metric.pricing_rules %}
      <li>{{ pricing_rule.cost_per_unit }}</li>
    {% endfor %}
  </ul>

  {% else %}
    <p>This metric has no pricing rules</p>
  {% endif %}

```

1.7.30.1.8. has_parent

1.7.31. Page drop (up)

1.7.31.1. Methods

1.7.31.1.1. errors

If a form of this model is rendered after unsuccessful submit, this returns" errors that occurred.

```

{{ page.errors.name | inline_errors }}

```

1.7.31.1.2. title

Returns the title of the page

```
<title>{{ page.title }}</title>
```

1.7.31.1.3. system_name

Returns system name of the page

```
{% if page.system_name == 'my_page' %}
  {% include 'custom_header' %}
{% endif %}
```

1.7.32. Page drop (up)

1.7.32.1. Methods

1.7.32.1.1. errors

If a form of this model is rendered after unsuccessful submit, this returns" errors that occurred.

```
{{ page.errors.name | inline_errors }}
```

1.7.32.1.2. title

1.7.32.1.3. kind

1.7.32.1.4. url

1.7.32.1.5. description

1.7.33. Pagination drop (up)

1.7.33.1. Methods

1.7.33.1.1. page_size

Number of items on one full page.

```
{% for part in pagination.parts %}
  {% if part.is_link %}
    {% case part.rel %}
      {% when 'previous' %}
        {% assign css_class = 'previous_page' %}
      {% when 'next' %}
        {% assign css_class = 'next_page' %}
      {% else %}
        {% assign css_class = "" %}
      {% endcase %}
  {% endfor %}
```

```

<a class="{{ css_class }}" rel="{{ part.rel }}" href="{{ part.url }}">{{ part.title }}</a>
{% else %}
  {% case part.rel %}
  {% when 'current' %}
    <em class="current">{{ part.title }}</em>
  {% when 'gap' %}
    &#x2026;
  {% else %}
    {{ part.title }}
  {% endcase %}
{% endif %}
{% endfor %}

```

<!-- Outputs:

```
=====
```

```

<a class="previous_page" rel="prev" href="?page=7">&#x2190; Previous</a>
<a rel="start" href="?page=1">1</a>
<a href="?page=2">2</a>
<a href="?page=3">3</a>
<a href="?page=4">4</a>
<a href="?page=5">5</a>
<a href="?page=6">6</a>
<a rel="prev" href="?page=7">7</a>
<em class="current">8</em>
<a rel="next" href="?page=9">9</a>
<a href="?page=10">10</a>
<a href="?page=11">11</a>
<a href="?page=12">12</a>
&#x2026;
<a href="?page=267">267</a>
<a href="?page=268">268</a>
<a class="next_page" rel="next" href="?page=9">Next &#x2192;</a>

```

```
=====
```

-->

1.7.33.1.2. current_page

Number of the currently selected page.

1.7.33.1.3. current_offset

Items skipped so far.

1.7.33.1.4. pages

Total number of pages.

1.7.33.1.5. items

Total number of items in all pages together.

1.7.33.1.6. previous

Number of the previous page or empty.

1.7.33.1.7. next

Number of the next page or empty.

1.7.33.1.8. parts

Elements that help to render a user-friendly pagination. See the `[[part-drop[part drop]]` for more information.

1.7.34. Part drop (up)

1.7.34.1. Methods

1.7.34.1.1. url

1.7.34.1.2. rel

1.7.34.1.3. current?

1.7.34.1.4. is_link

1.7.34.1.5. title

1.7.34.1.6. to_s

1.7.35. PaymentGateway drop (up)

1.7.35.1. Methods

1.7.35.1.1. braintree_blue?

Returns whether current payment gateway is authorize.Net

1.7.35.1.2. authorize_net?

Returns whether current payment gateway is authorize.Net

1.7.35.1.3. type

Returns the type of this payment gateway.

1.7.36. PaymentTransaction drop (up)

1.7.36.1. Methods

1.7.36.1.1. errors

If a form of this model is rendered after unsuccessful submit, this returns" errors that occurred.

```

{{ payment_transaction.errors.name | inline_errors }}

```

1.7.36.1.2. currency

Returns the currency

```

{% for payment_transaction in invoice.payment_transactions %}
  <tr>
    <td> {% if payment_transaction.success? %} Success {% else %} Failure {% endif %} </td>
    <td> {{ payment_transaction.created_at }} </td>
    <td> {{ payment_transaction.reference }} </td>
    <td> {{ payment_transaction.message }} </td>
    <td> {{ payment_transaction.amount }} {{ payment_transaction.currency }} </td>
  </tr>
{% endfor %}

```

1.7.36.1.3. amount

Returns the amount

1.7.36.1.4. created_at

Returns the creation date

1.7.36.1.5. success?

Returns true if was success

1.7.36.1.6. message

Returns the message of the transaction

1.7.36.1.7. reference

Returns the reference

1.7.37. PlanFeature drop (up)

1.7.37.1. Methods

1.7.37.1.1. errors

If a form of this model is rendered after unsuccessful submit, this returns" errors that occurred.

```

{{ plan_feature.errors.name | inline_errors }}

```

1.7.37.1.2. name

Returns the name of the feature

```
<h2>Feature {{ feature.name }}</h2>
```

1.7.37.1.3. description

Returns the description of the feature

1.7.37.1.4. has_description?

Returns whether the feature has description

```
{% if feature.has_description? %}  
  {{ feature.description }}  
{% else %}  
  This feature has no description.  
{% endif %}
```

1.7.37.1.5. enabled?

1.7.38. Post drop (up)

1.7.38.1. Methods

1.7.38.1.1. errors

If a form of this model is rendered after unsuccessful submit, this returns " errors that occurred.

```
{{ post.errors.name | inline_errors }}
```

1.7.38.1.2. body

Text of the post.

1.7.38.1.3. topic

Every post belongs to a [\[\[topic-drop\[topic\]](#)

1.7.38.1.4. created_at

Date when this post created

```
{{ post.created_at | date: i18n.short_date }}
```

1.7.38.1.5. url

The url of this post within its topic

1.7.39. Post drop (up)

1.7.39.1. Methods

1.7.39.1.1. errors

If a form of this model is rendered after unsuccessful submit, this returns" errors that occurred.

```
{{ post.errors.name | inline_errors }}
```

1.7.39.1.2. title

1.7.39.1.3. kind

1.7.39.1.4. url

1.7.39.1.5. description

1.7.40. PricingRule drop (up)

1.7.40.1. Methods

1.7.40.1.1. cost_per_unit

Returns the cost per unit of the pricing rule **Example:** Using pricing rule drop in liquid

```
<h2>Pricing rule</h2>
Min value {{ pricing_rule.min }}
Max value {{ pricing_rule.max }}
Cost per unit {{ pricing_rule.cost_per_unit }}
```

1.7.40.1.2. min

Returns the minimum value of the pricing rule

1.7.40.1.3. max

Returns the maximum value of the pricing rule

1.7.40.1.4. plan

Returns plan of pricing rule

1.7.41. Provider drop (up)

1.7.41.1. Methods

1.7.41.1.1. name

Returns the name of your organization.

```
Domain {{ provider.domain }}
{% if provider.multiple_applications_allowed? %}
```

```

<p>Applications</p>
<ul>
  {% for app in account.applications %}
    <li>{{ app.name }}</li>
  {% endfor %}
</ul>

```

```

{% else %}
  Application {{ account.applications.first.name }}
{% endif %}

```

For general questions contact us at {{ provider.support_email }},
 for invoice or payment related questions contact us at {{ provider.finance_support_email }}

1.7.41.1.2. payment_gateway

Returns the payment gateway associated with your organization

1.7.41.1.3. domain

Domain of your developer portal

1.7.41.1.4. timezone

Returns timezone that you use. Can be changed in your /p/admin/account/edit[administration dashboard].

1.7.41.1.5. support_email

Support email of the account

1.7.41.1.6. finance_support_email

Finance support email of the account

1.7.41.1.7. telephone_number

Returns the telephone number of the account

1.7.41.1.8. multiple_applications_allowed?

True if developers can have more separate applications with their own keys, stats, etc. **Depends on your 3scale plan.**

```

{% if provider.multiple_applications_allowed? %}
  <p>Applications</p>
  <ul>
    {% for app in account.applications %}
      <li>{{ app.name }}</li>
    {% endfor %}
  </ul>

```

```
{% else %}
  Application {{ account.applications.first.name }}
{% endif %}
```

1.7.41.1.9. logo_url

Return the logo url

1.7.41.1.10. multiple_services_allowed?

True if your 3scale plan allows you to manage multiple APIs as separate [services](#).

```
{% if provider.multiple_services_allowed? %}
  {% for service in provider.services %}
    Service {{ service.name }} is available.
  {% endfor %}
{% endif %}
```

1.7.41.1.11. finance_allowed?

1.7.41.1.12. multiple_users_allowed?

True if the developer accounts can have multiple logins associated with them (**depends on your 3scale plan**) and its visibility has been turned on for your developer portal in the `/p/admin/cms/switches[settings]`.

```
{% if provider.multiple_users_allowed? %}
  <ul id="subsubmenu">
    <li>
      {{ 'Users' | link_to: urls.users }}
    </li>
    <li>
      {{ 'Sent invitations' | link_to: urls.invitations }}
    </li>
  </ul>
{% endif %}
```

1.7.41.1.13. account_plans

Returns all published account plans.

```
<p>We offer following account plans:</p>
<ul>
  {% for plan in model.account_plans %}
    <li>{{ plan.name }} </li>
  {% endfor %}
</ul>
```

1.7.41.1.14. services

Returns all defined services.

```
<p>You can signup to any of our services!</p>
<ul>
{% for service in provider.services %}
  <li>{{ service.name }} <a href="/signup/service/{{ service.system_name }}">Signup!</a></li>
{% endfor %}
```

1.7.41.15. signups_enabled?

You can enable or disable signups in the Usage rules section of your Admin Portal.

1.7.41.16. account_management_enabled?

You can enable or disable account management in the Usage rules section.

1.7.42. ReferrerFilter drop (up)

1.7.42.1. Methods

1.7.42.1.1. id

1.7.42.1.2. value

1.7.42.1.3. delete_url

1.7.42.1.4. application

1.7.43. Request drop (up)

Example: Using request drop in liquid

```
<h2>Request details</h2>
URI {{ request.request_uri }}
Host {{ request.host }}
Host and port {{ request.host_with_port }}
```

1.7.43.1. Methods

1.7.43.1.1. request_uri

Returns the URI of the request

1.7.43.1.2. host_with_port

Returns the host with port of the request

1.7.43.1.3. host

Returns the host part of the request URL

1.7.43.1.4. path

Returns the path part of the request URL

```
{% if request.path == '/' %}
  Welcome on a landing page!
{% else %}
  This just an ordinary page.
{% endif %}
```

1.7.44. Role drop (up)

1.7.44.1. Methods

1.7.44.1.1. name

Return internal name of the role, important for the system

1.7.44.1.2. description

Return a descriptive text for the role

1.7.45. Search drop (up)

1.7.45.1. Methods

1.7.45.1.1. errors

If a form of this model is rendered after unsuccessful submit, this returns" errors that occurred.

```
{{ search.errors.name | inline_errors }}
```

1.7.45.1.2. query

Returns the searched string

```
<h3>{{ search.token }}</h3>
<p>found on {{ search.total_found }} {{ search.item | pluralize }} </p>
<dl>
  {% for result in search.results %}
    <dt>
      [ {{ result.kind | capitalize}} ]
      {{ result.title | link_to: result.url }}
    </dt>
    <dd>
      {{ result.description }}
    </dd>
  {% endfor %}
</dl>
```

1.7.45.1.3. total_found

Returns the number of matching elements

1.7.45.1.4. results

Returns an array of results for que search

1.7.46. Service drop (up)

1.7.46.1. Methods

1.7.46.1.1. errors

If a form of this model is rendered after unsuccessful submit, this returns" errors that occurred.

```
{{ service.errors.name | inline_errors }}
```

1.7.46.1.2. name

Returns the name of the service

1.7.46.1.3. system_name

Returns the system name of the service

```
{% case service.system_name %}
{% when 'api' %}
  API is our newest service!
{% when 'old' %}
  Unfortunately we dont allow more signups to our old service.
{% endcase %}
```

1.7.46.1.4. description

Returns the description of the service

1.7.46.1.5. subscribed?

Returns whether the service is subscribed

```
{% if service.subscribed? %}
  <p>You already subscribed this service.</p>
{% endif %}
```

1.7.46.1.6. subscription

Returns a subscription(**ServiceContract** drop) if the currently logged in user is subscribed to this service, Nil otherwise.

```
{% if service.subscription %}
  Your applications for service {{ service.name }} are:
  {% for app in service.subscription.applications %}
    {{ app.name }}<br/>
  {% endfor %}
{% endif %}
```



```
{% else %}
  <p>You are not subscribed to this.</p>
{% endif %}
```

1.7.46.1.7. subscribable?

1.7.46.1.8. subscribe_url

1.7.46.1.9. application_plans

Returns the **published** application plans of the service

```
{% for service in model.services %}
  <h4>{{ service.name }} application plans:</h4>
  <dl>
    {% for application_plan in service.application_plans %}
      <dt>{{ application_plan.name }}</dt>
      <dd>{{ application_plan.system_name }}</dd>
    {% endfor %}
  </dl>
{% endfor %}
```

1.7.46.1.10. service_plans

Returns the *published* service plans of the service

```
<p>We offer following service plans:</p>
<dl>
  {% for service in model.services %}
    {% for service_plan in service.service_plans %}
      <dt>{{ service_plan.name }}</dt>
      <dd>{{ service_plan.system_name }}</dd>
    {% endfor %}
  {% endfor %}
</dl>
```

1.7.46.1.11. plans

Returns the application plans of the service

1.7.46.1.12. features

Returns the visible features of the service

```
{% if service.features.size > 0 %}
  <p>{{ service.name }} has following features:</p>
  <ul>
    {% for feature in service.features %}
      <li>{{ feature.name }}</li>
    {% endfor %}
  </ul>
```

```
{% else %}  
<p>Unfortunately, {{ service.name }} currently has no features.</p>  
{% endif %}
```

1.7.46.113. apps_identifier

Depending on the authentication mode set, returns either 'ID', 'API key' or 'Client ID' for OAuth authentication.

```
{{ service.application_key_name }}
```

1.7.46.114. backend_version

1.7.46.115. referrer_filters_required?

1.7.46.116. metrics

Returns the metrics of the service

```
<p>On {{ service.name }} we measure following metrics:</p>  
<ul>  
{% for metric in service.metrics %}  
<li>{{ metric.name }}</li>  
{% endfor %}  
</ul>
```

1.7.46.117. support_email

Support email of the service

1.7.47. ServiceContract drop (up)

1.7.47.1. Methods

1.7.47.1.1. errors

If a form of this model is rendered after unsuccessful submit, this returns " errors that occurred.

```
{{ service_contract.errors.name | inline_errors }}
```

1.7.47.1.2. id

1.7.47.1.3. can_change_plan?

Returns true if any form of change is possible

1.7.47.1.4. trial?

Returns true if the contract is still in the trial period.

Note: If you change the trial period length of a plan, it does not affect the existing contracts.

1.7.47.1.5. live?

1.7.47.1.6. state

There are three possible states:

- pending
- live
- suspended

1.7.47.1.7. remaining_trial_period_days

Number of day still left in the trial period.

1.7.47.1.8. plan

Returns the plan of the contract

1.7.47.1.9. plan_change_permission_name

Returns name of the allowed action

1.7.47.1.10. plan_change_permission_warning

Returns a warning messenger of the allowed action

1.7.47.1.11. contract

1.7.47.1.12. name

1.7.47.1.13. system_name

1.7.47.1.14. change_plan_url

1.7.47.1.15. service

1.7.47.1.16. applications

1.7.47.1.17. can

Exposes specific rights of the current user for that subscription.

```
{% if subscription.can.change_plan? %}
...
{% endif %}
```

1.7.48. ServicePlan drop (up)

1.7.48.1. Methods

1.7.48.1.1. selected?

Returns whether the plan is selected

```
{% if plan.selected? %}  
  <p>You will signup to {{ plan.name }}</p>  
{% endif %}
```

1.7.48.1.2. bought?

Returns whether the plan is bought

```
{% if plan.bought? %}  
  <p>You are on this plan already!</p>  
{% endif %}
```

1.7.48.1.3. features

Returns the visible features of the plan

```
{% if plan == my_free_plan %}  
  <p>These plans are the same.</p>  
{% else %}  
  <p>These plans are not the same.</p>  
{% endif %}
```

1.7.48.1.4. setup_fee

Returns the setup fee of the plan

1.7.48.1.5. name

Returns the name of the plan

```
<h2>We offer you a new {{ plan.name }} plan!</h2>
```

1.7.48.1.6. system_name

Returns the system name of the plan

```
{% for plan in available_plans %}  
  {% if plan.system_name == 'my_free_plan' %}  
  
    <p>You will buy our only free plan!</p>  
  {% endif %}  
{% endfor %}
```

1.7.48.1.7. id

Returns the plan id

1.7.48.1.8. free?

The plan is free if it is not 'paid' (see the 'paid?' method)

```
{% if plan.free? %}
  <p>This plan is free of charge.</p>
{% else %}

  <p>Plan costs</p>
  Setup fee {{ plan.setup_fee }}
  Flat cost {{ plan.flat_cost }}

{% endif %}
```

1.7.48.1.9. paid?

The plan is 'paid' when it has non-zero fixed or setup fee or there are some pricing rules present

```
{% if plan.paid? %}
  <p>this plan is a paid one.</p>
{% else %}
  <p>this plan is a free one.</p>
{% endif %}
```

1.7.48.1.10. approval_required?

Returns whether the plan requires approval?

```
{% if plan.approval_required? %}
  <p>This plan requires approval.</p>
{% endif %}
```

1.7.48.1.11. flat_cost

Returns the monthly fixed fee of the plan

1.7.48.1.12. service

Example: Using service plan drop in liquid

```
<p class="notice">The examples for plan drop apply here</p>
Service of this plan {{ plan.service.name }}
```

1.7.49. TimeZone drop (up)

1.7.49.1. Methods

1.7.49.1.1. full_name

1.7.49.1.2. to_str

1.7.50. Today drop (up)

1.7.50.1. Methods

1.7.50.1.1. month

Returns current month (1-12)

1.7.50.1.2. day

Returns current day of the month (1-31)

1.7.50.1.3. year

Returns current year **Example:** Create dynamic copyright

```
&copy;{{ today.year }}
```

1.7.50.1.4. beginning_of_month

Returns date of beginning of current month

```
This month began on {{ today.beginning_of_month | date: '%A' }}
```

1.7.51. Topic drop (up)

1.7.51.1. Methods

1.7.51.1.1. errors

If a form of this model is rendered after unsuccessful submit, this returns" errors that occurred.

```
{{ topic.errors.name | inline_errors }}
```

1.7.51.1.2. title

1.7.51.1.3. kind

1.7.51.1.4. url

1.7.51.1.5. description

1.7.52. Topic drop (up)

1.7.52.1. Methods

1.7.52.1.1. errors

If a form of this model is rendered after unsuccessful submit, this returns" errors that occurred.

```
{{ topic.errors.name | inline_errors }}
```

1.7.52.1.2. title

Name of the topic. Submitted when first post to the thread is posted.

1.7.52.1.3. url

1.7.53. Url drop (up)

1.7.53.1. Methods

1.7.53.1.1. to_s

1.7.53.1.2. to_str

1.7.53.1.3. title

1.7.53.1.4. current_or_subpath?

True if the path of the current page is the same as this one or it's a 'direct subpath' of it (i.e. extended by ID). For example with `{{ urls.outbox }}` these will return true:

- `/admin/sent/messages/received`
- `/admin/sent/messages/received/42`

But not these:

- `/admin/sent/messages/new`
- `/admin/sent/messages/longer/subpath`

See also `'#active?'`, `'#current?'`.

1.7.53.1.5. current?

True if the URL's path is the the same as of the current. Parameters and other components are not taken into account. See also `'#active?'`.

```
{% assign url = urls.messages_inbox %}
<!-- => http://awesome.3scale.net/admin/messages/sent -->

<!-- Current page: http://awesome.3scale.net/admin/messages/sent?unread=1 -->
{{ url.current? }} => true

<!-- Current page: http://awesome.3scale.net/admin/messages -->
{{ url.current? }} => false
```

1.7.53.1.6. active?

True if the current page is in the same menu structure as this URL. See also '#current?'.

```
{% assign url = urls.messages_inbox %}
<!-- => http://awesome.3scale.net/admin/messages/sent -->

<!-- Current page: http://awesome.3scale.net/admin/messages -->
{{ url.active? }} => true

<!-- Current page: http://awesome.3scale.net/admin/messages/trash -->
{{ url.active? }} => true

<!-- Current page: http://awesome.3scale.net/admin/stats -->
{{ url.active? }} => false
```

1.7.54. Urls drop (up)

1.7.54.1. Methods

1.7.54.1.1. provider

1.7.54.1.2. cas_login

```
<a href="{{ urls.signup }}">signup here</a>
<a href="{{ urls.service_subscription }}">subscribe to a service here</a>
```

1.7.54.1.3. new_application

1.7.54.1.4. signup

URL of a signup page. Accessible for all.

```
<a href="{{ urls.signup }}?{{ service_plan | param_filter }}&{{ app_plan | param_filter }}">Signup Now!
</a>
```

1.7.54.1.5. search

URL to which all the search requests should be sent

```
<form action="{{ urls.search }}" method="get">

</form>
```

1.7.54.1.6. login

1.7.54.1.7. logout

1.7.54.1.8. forgot_password

1.7.54.1.9. service_subscription

URL to a service subscription page. Only for logged in users.

```
<a href="{{ urls.service_subscription }}?{{ service_plan | param_filter }}" >
  Subscribe to service {{ service.name }}
</a>
```

1.7.54.1.10. compose_message

URL to a page that allows the developer contact provider via the internal messaging system.

1.7.54.1.11. messages_outbox

URL to the list of messages sent by a developer.

1.7.54.1.12. messages_trash

1.7.54.1.13. empty_messages_trash

1.7.54.1.14. credit_card_terms

1.7.54.1.15. credit_card_privacy

1.7.54.1.16. credit_card_refunds

1.7.54.1.17. users

1.7.54.1.18. personal_details

URL or Nil if user account management is disabled (check your Usage rules).

1.7.54.1.19. access_details

A page with API key(s) and other authentication info. Differs depending on the authentication strategy.

1.7.54.1.20. payment_details

1.7.54.1.21. new_invitation

Page to invite new users

1.7.54.1.22. invitations

List of all the sent invitations

1.7.54.1.23. dashboard

1.7.54.1.24. applications

1.7.54.1.25. api_access_details

1.7.54.1.26. services

1.7.54.1.27. messages_inbox

URL to the list of received messages.

1.7.54.1.28. stats

1.7.54.1.29. account_overview

1.7.54.1.30. account_plans

1.7.54.1.31. invoices

1.7.55. UsageLimit drop (up)

Example: Using usage limit drop in liquid

You cannot do more than `{{ limit.value }}` `{{ limit.metric.unit }}`s per `{{ limit.period }}`

1.7.55.1. Methods

1.7.55.1.1. period

Returns the period of the usage limit

1.7.55.1.2. metric

Usually **hits** but can be any custom method.

1.7.55.1.3. value

Returns the value of the usage limit

1.7.56. User drop (up)

```
<h2>User {{ user.display_name }}</h2>
Account {{ user.account.name }}
Username {{ user.username }}
Email {{ user.email }}
Website {{ user.website }}
```

1.7.56.1. Methods

1.7.56.1.1. errors

If a form of this model is rendered after unsuccessful submit, this returns" errors that occurred.

```
{{ user.errors.name | inline_errors }}
```

1.7.56.1.2. admin?

Returns whether the user is an admin.

```
{% if user.admin? %}
  <p>You are an admin of your account.</p>
{% endif %}
```

1.7.56.1.3. username

Returns the username of the user, html escaped.

1.7.56.1.4. account

Returns the account of the user.

1.7.56.1.5. name

Returns the first and surname of the user.

1.7.56.1.6. email

Returns the email of the user.

1.7.56.1.7. password_required?

This method will return **true** for users using the builtin Developer Portal authentication mechanisms and **false** for those that are authenticated via Janrain, CAS or other single-sign-on method.

```
{% if user.password_required? %}

{% endif %}
```

1.7.56.1.8. sections

Returns the list of sections the user has access to.

```
{% if user.sections.size > 0 %}
  <p>You can access following sections of our portal:</p>
  <ul>
    {% for section in user.sections %}
      <li>{{ section }}</li>
    {% endfor %}
  </ul>
{% endif %}
```

1.7.56.1.9. role

Returns the role of the user

1.7.56.1.10. roles_collection

Returns a list of available roles for the user

```
{% for role in user.roles_collection %}
  <li>
    <label for="user_role_{{ role.key }}">

      {{ role.text&nbsp; }}
    </label>
  </li>
{% endfor %}
```

1.7.56.1.11. url

Return the resource url of the user

```
{{ 'Delete' | delete_button: user.url }}
```

1.7.56.1.12. edit_url

Return the url to edit the user

```
{{ 'Edit' | link_to: user.edit_url, title: 'Edit', class: 'action edit' }}
```

1.7.56.1.13. can

Give access to permission methods

```
{% if user.can.be_managed? %}
  <!-- do something -->
{% endif %}
```

1.7.56.1.14. extra_fields

Returns non-hidden extra fields with values for this user **Example:** Print all extra fields

```
{% for field in user.extra_fields %}
  {{ field.label }}: {{ field.value }}
{% endfor %}
```

1.7.56.1.15. fields

Returns all fields with values for this user **Example:** Print all fields

```
{% for field in user.fields %}
  {{ field.label }}: {{ field.value }}
{% endfor %}
```

1.7.56.1.16. builtin_fields

Returns all builtin fields with values for this user

1.8. TAGS (UP)

1.8.1. Tag 'braintree_customer_form' (up)

Renders a form to enter data required for Braintree Blue payment gateway

1.8.2. Tag 'csrf' (up)

Renders the cross site request forgery meta tags.

Example: Using csrf tag in liquid

```
<head>
  {% csrf %}
</head>
```

1.8.3. Tag 'content' (up)

Renders body of a page. Use this only inside a layout.

1.8.4. Tag 'content_for' (up)

1.8.5. Tag 'debug' (up)

Prints all liquid variables available in a template into an HTML comment.' We recommend **to remove this tag** from public templates.

```
`{% debug:help %}`
```

1.8.6. Tag 'email' (up)

The **email** tag allows you to customize headers of your outgoing emails and is available only inside the email templates.

There are several convenience subtags such as **cc** or **subject** (see the table below) that simplify the job but you can also use a **header** subtag to set an arbitrary SMTP header for the message.

Subtag	Description	Example
subject	dynamic subject	{% subject = 'Greetings from Example company!' %}
cc	carbon copy	{% cc = 'boss@example.com' %}
bcc	blind carbon copy	{% bcc = 'all@example.com' %}

from	the actual sender	{% from = 'system@example.com' %}
reply-to		{% reply-to = 'support@example.com' %}
header	custom SMTP header	{% header 'X-SMTP-Group' = 'Important' %}
do_not_send	discard the email	{% do_not_send %}

Example: Conditional blind carbon copy

```
{% email %}
  {% if plan.system_name == 'enterprise' %}
    {% bcc 'marketing@world-domination.org' %}
  {% endif %}
{% endemail %}
```

Example: Disabling emails at all

```
{% email %}
  {% do_not_send %}
{% endemail %}
```

Example: Signup email filter

```
{% email %}
  {% if plan.system == 'enterprise' %}
    {% subject = 'Greetings from Example company!' %}
    {% reply-to = 'support@example.com' %}
  {% else %}
    {% do_not_send %}
  {% endif %}
{% endemail %}
```

1.8.7. Tag 'flash' (up)

Renders informational or error messages of the system.

DEPRECATED: This tag is deprecated, use FlashDrop instead.

Example: Using flash tag in liquid

```
{% flash %}
```

1.8.8. Tag 'footer' (up)

Renders a footer html snippet.

DEPRECATED: This tag is deprecated, use a CMS partial instead

1.8.9. Tag 'form' (up)

Renders a form tag with an action and class attribute specified, depending on the name of the form. The supported forms are:

Form	Allowed Field Names	Spam Protection	Notes
application.create	<ul style="list-style-type: none">● application[name]● application[description]● application[<any-extra-field>]	No	
application.update	<ul style="list-style-type: none">● application[name]● application[description]● application[<any-extra-field>]	No	

signup	<ul style="list-style-type: none"> ● account[org_name] ● account[org_legaladdress] ● account[org_legaladdress_content] ● account[city] ● account[state] ● account[zip] ● account[telephone_number] ● account[country_id] ● account[<any-extra-field>] ● account[user][username] ● account[user][email] ● account[user][first_name] ● account[user][last_name] ● account[user][password] ● account[user][password_confirmation] ● account[user][title] ● account[user][<any-extra-field>] 	Yes	<p>Sign Up directly to plans of your choice by adding one or more hidden fields with a name plan_ids[]. If a parameter of such name is found in the current URL, the input field is filled automatically.</p>
--------	---	-----	--

Example: A form to create an application

```
{% form 'application.create', application %}
```

```
{{ application.errors.name | inline_errors }}
```



```
{% endform %}
```

1.8.10. Tag 'latest_forum_posts' (up)

An HTML table with latest forum posts.

DEPRECATED: Use **forum** drop instead.

Example: Using latest_forum_posts tag liquid

```
{% latest_forum_posts %}
```

1.8.11. Tag 'latest_messages' (up)

Renders a html snippet with the latest messages for the user.

Example: Using latest_messages tag liquid

```
{% latest_messages %}
```

1.8.12. Tag 'logo' (up)

Renders the logo.

DEPRECATED: This tag is deprecated, use `{{ provider.logo_url }}` instead.

Example: Using menu tag in liquid

```
{% logo %}
```

1.8.13. Tag 'menu' (up)

DEPRECATED: This tag is deprecated, use `'{% include "menu" %}'` instead.

1.8.14. Tag 'oldfooter' (up)

Renders a footer html snippet.

DEPRECATED: This tag is deprecated, use a CMS partial instead

1.8.15. Tag 'plan_widget' (up)

Includes a widget to review or change application plan

```
{% if application.can_change_plan? %}
<a href="#choose-plan-{{ application.id }}"
  id="choose-plan-{{application.id}}">
  Review/Change
```

```
</a>
{% plan_widget application %}
{% endif %}
```

1.8.16. Tag 'portlet' (up)

This tag includes portlet by system name.

1.8.17. Tag 'submenu' (up)

Renders a submenu html snippet for a logged in user.

DEPRECATED: This tag is deprecated, use a 'submenu' partial instead

Example: Using submenu tag in liquid

```
{% submenu %}
```

1.8.18. Tag '3scale_essentials' (up)

1.8.19. Tag 'user_widget' (up)

Renders a user widget html snippet.

DEPRECATED: This tag is deprecated, use a CMS partial instead

Example: Using user_widget tag in liquid

```
{% user_widget %}
<p class="notice">If you are logged in you see profile related links above.</p>
<p class="notice">If you are not login you are invited to login or signup.</p>
```

1.9. FILTERS (UP)

1.9.1. FormHelpers filters (up)

1.9.1.1. error_class filter

Outputs error class if argument is not empty **Example:** Using error_class to show output an error class

```
■
```

1.9.1.2. inline_errors filter

Outputs error fields inline in paragraph **Example:** Using inline_errors to show errors inline

```
{{ form.errors.description | inline_errors }}
```

1.9.2. ParamFilter filters (up)

1.9.2.1. to_param filter

Converts a supplied drop to URL parameter if possible. **Example:** Using to_param filter in liquid

```
<h2>Signup to a service</h2>
<a href="{{ urls.signup }}?{{ service | to_param }}">Signup to {{ service.name }}</a>
```

1.9.3. Common filters (up)

1.9.3.1. group_by filter

Group collection by some key **Example:** Group applications by service

```
{% assign grouped = applications | group_by: 'service' %}
{% for group in grouped %}
  Service: {{ group[0] }}
  {% for app in group[1] %}
    Application: {{ app.name }}
  {% endfor %}
{% endfor %}
```

1.9.3.2. any filter

True if any string in the collection equals to the parameter **Example:** Are there any pending apps of the current account?

```
{% assign has_pending_apps = current_account.applications | map: 'state' | any: 'live' %}
```

1.9.3.3. stylesheet_link_tag filter

Stylesheet link

1.9.3.4. javascript_include_tag filter

Javascript include tag

1.9.3.5. image_tag filter

Outputs an tag using the parameters as its **src** attribute.

```
{{ 'http://example.com/cool.gif' | image_tag }}
## =>
```

1.9.3.6. mail_to filter

Converts email address to a 'mailto' link.

```
{{ 'me@there.is' | mail_to }}
## => <a href="mailto:me@there.is">me@there.is</a>
```

1.9.3.7. `html_safe` filter

Marks content as HTML safe so that it is not escaped.

1.9.3.8. `pluralize` filter

Convert word to plural form

1.9.3.9. `delete_button` filter

Generates a button to delete a resource present on the URL. First parameter is a URL, second is a title. You can also add more HTML tag attributes as a third parameter.

```
{{ 'Delete Message' | delete_button: message.url, class: 'my-button' }}
```

1.9.3.10. `delete_button_ajax` filter

Generates a button to delete a resource present on the URL using AJAX. First parameter is a URL, second is a title.

```
{{ 'Delete Message' | delete_button_ajax: message.url }}
```

1.9.3.11. `update_button` filter

Generates a button to 'update' (HTTP PUT request) a resource present on the URL. First parameter is a URL, second is a title. You can also add more HTML tag attributes as a third parameter.

```
{{ 'Resend' | update_button: message.url, class: 'my-button' }}
```

1.9.3.12. `create_button` filter

Generates a button to create a resource present on the URL. First parameter is a URL, second is a title.

```
{{ 'Create Message' | create_button: message.url }}
```

1.9.3.13. `create_button_ajax` filter

1.9.3.14. `regenerate_oauth_secret_button` filter

1.9.3.15. `link_to` filter

Create link from given text

```
{{ "See your App keys" | link_to: '/my-app-keys' }}
```