



OpenShift Dedicated 3

REST API Reference

OpenShift Dedicated 3 REST API for Developers

OpenShift Dedicated 3 REST API Reference

OpenShift Dedicated 3 REST API for Developers

Legal Notice

Copyright © 2018 Red Hat, Inc.

The text of and illustrations in this document are licensed by Red Hat under a Creative Commons Attribution-Share Alike 3.0 Unported license ("CC-BY-SA"). An explanation of CC-BY-SA is available at

<http://creativecommons.org/licenses/by-sa/3.0/>

. In accordance with CC-BY-SA, if you distribute this document or an adaptation of it, you must provide the URL for the original version.

Red Hat, as the licensor of this document, waives the right to enforce, and agrees not to assert, Section 4d of CC-BY-SA to the fullest extent permitted by applicable law.

Red Hat, Red Hat Enterprise Linux, the Shadowman logo, JBoss, OpenShift, Fedora, the Infinity logo, and RHCE are trademarks of Red Hat, Inc., registered in the United States and other countries.

Linux ® is the registered trademark of Linus Torvalds in the United States and other countries.

Java ® is a registered trademark of Oracle and/or its affiliates.

XFS ® is a trademark of Silicon Graphics International Corp. or its subsidiaries in the United States and/or other countries.

MySQL ® is a registered trademark of MySQL AB in the United States, the European Union and other countries.

Node.js ® is an official trademark of Joyent. Red Hat Software Collections is not formally related to or endorsed by the official Joyent Node.js open source or commercial project.

The OpenStack ® Word Mark and OpenStack logo are either registered trademarks/service marks or trademarks/service marks of the OpenStack Foundation, in the United States and other countries and are used with the OpenStack Foundation's permission. We are not affiliated with, endorsed or sponsored by the OpenStack Foundation, or the OpenStack community.

All other trademarks are the property of their respective owners.

Abstract

The OpenShift Dedicated 3 distribution of Kubernetes includes the Kubernetes v1 REST API and the OpenShift v1 REST API. These are RESTful APIs accessible via HTTP(s) on the OpenShift Dedicated master servers. These REST APIs can be used to manage end-user applications, the cluster, and the users of the cluster.

Table of Contents

CHAPTER 1. OVERVIEW	86
1.1. AUTHENTICATION	86
1.1.1. Session Tokens	86
1.1.2. Service Account Tokens	86
1.2. EXAMPLES	87
1.2.1. cURL	87
1.2.2. Python	88
1.2.3. Docker Login	88
1.3. WEBSOCKETS AND WATCHING FOR CHANGES	89
CHAPTER 2. OPENSIFT DEDICATED V1 REST API	90
2.1. OVERVIEW	90
2.1.1. Version information	90
2.1.2. URI scheme	90
2.2. PATHS	90
2.2.1. get available resources	90
2.2.1.1. Responses	90
2.2.1.2. Consumes	90
2.2.1.3. Produces	90
2.2.1.4. Tags	90
2.2.2. list objects of kind AppliedClusterResourceQuota	91
2.2.2.1. Parameters	91
2.2.2.2. Responses	92
2.2.2.3. Consumes	93
2.2.2.4. Produces	93
2.2.2.5. Tags	93
2.2.3. list or watch objects of kind BuildConfig	93
2.2.3.1. Parameters	93
2.2.3.2. Responses	95
2.2.3.3. Consumes	96
2.2.3.4. Produces	96
2.2.3.5. Tags	96
2.2.4. create a BuildConfig	96
2.2.4.1. Parameters	96
2.2.4.2. Responses	96
2.2.4.3. Consumes	97
2.2.4.4. Produces	97
2.2.4.5. Tags	97
2.2.5. list or watch objects of kind Build	97
2.2.5.1. Parameters	97
2.2.5.2. Responses	99
2.2.5.3. Consumes	100
2.2.5.4. Produces	100
2.2.5.5. Tags	100
2.2.6. create a Build	100
2.2.6.1. Parameters	100
2.2.6.2. Responses	100
2.2.6.3. Consumes	100
2.2.6.4. Produces	100
2.2.6.5. Tags	101
2.2.7. list or watch objects of kind ClusterNetwork	101

2.2.7.1. Parameters	101
2.2.7.2. Responses	102
2.2.7.3. Consumes	103
2.2.7.4. Produces	103
2.2.7.5. Tags	103
2.2.8. create a ClusterNetwork	103
2.2.8.1. Parameters	103
2.2.8.2. Responses	103
2.2.8.3. Consumes	104
2.2.8.4. Produces	104
2.2.8.5. Tags	104
2.2.9. delete collection of ClusterNetwork	104
2.2.9.1. Parameters	104
2.2.9.2. Responses	106
2.2.9.3. Consumes	107
2.2.9.4. Produces	107
2.2.9.5. Tags	107
2.2.10. read the specified ClusterNetwork	107
2.2.10.1. Parameters	107
2.2.10.2. Responses	108
2.2.10.3. Consumes	108
2.2.10.4. Produces	108
2.2.10.5. Tags	108
2.2.11. partially update the specified ClusterNetwork	108
2.2.11.1. Parameters	108
2.2.11.2. Responses	108
2.2.11.3. Consumes	109
2.2.11.4. Produces	109
2.2.11.5. Tags	109
2.2.12. replace the specified ClusterNetwork	109
2.2.12.1. Parameters	109
2.2.12.2. Responses	109
2.2.12.3. Consumes	110
2.2.12.4. Produces	110
2.2.12.5. Tags	110
2.2.13. delete a ClusterNetwork	110
2.2.13.1. Parameters	110
2.2.13.2. Responses	113
2.2.13.3. Consumes	113
2.2.13.4. Produces	113
2.2.13.5. Tags	113
2.2.14. list or watch objects of kind ClusterPolicy	113
2.2.14.1. Parameters	113
2.2.14.2. Responses	115
2.2.14.3. Consumes	116
2.2.14.4. Produces	116
2.2.14.5. Tags	116
2.2.15. create a ClusterPolicy	116
2.2.15.1. Parameters	116
2.2.15.2. Responses	116
2.2.15.3. Consumes	116
2.2.15.4. Produces	116
2.2.15.5. Tags	117

2.2.16. delete collection of ClusterPolicy	117
2.2.16.1. Parameters	117
2.2.16.2. Responses	119
2.2.16.3. Consumes	120
2.2.16.4. Produces	120
2.2.16.5. Tags	120
2.2.17. read the specified ClusterPolicy	120
2.2.17.1. Parameters	120
2.2.17.2. Responses	120
2.2.17.3. Consumes	121
2.2.17.4. Produces	121
2.2.17.5. Tags	121
2.2.18. partially update the specified ClusterPolicy	121
2.2.18.1. Parameters	121
2.2.18.2. Responses	121
2.2.18.3. Consumes	122
2.2.18.4. Produces	122
2.2.18.5. Tags	122
2.2.19. replace the specified ClusterPolicy	122
2.2.19.1. Parameters	122
2.2.19.2. Responses	122
2.2.19.3. Consumes	122
2.2.19.4. Produces	123
2.2.19.5. Tags	123
2.2.20. delete a ClusterPolicy	123
2.2.20.1. Parameters	123
2.2.20.2. Responses	126
2.2.20.3. Consumes	126
2.2.20.4. Produces	126
2.2.20.5. Tags	126
2.2.21. list or watch objects of kind ClusterPolicyBinding	126
2.2.21.1. Parameters	126
2.2.21.2. Responses	128
2.2.21.3. Consumes	129
2.2.21.4. Produces	129
2.2.21.5. Tags	129
2.2.22. create a ClusterPolicyBinding	129
2.2.22.1. Parameters	129
2.2.22.2. Responses	129
2.2.22.3. Consumes	129
2.2.22.4. Produces	129
2.2.22.5. Tags	130
2.2.23. delete collection of ClusterPolicyBinding	130
2.2.23.1. Parameters	130
2.2.23.2. Responses	132
2.2.23.3. Consumes	133
2.2.23.4. Produces	133
2.2.23.5. Tags	133
2.2.24. read the specified ClusterPolicyBinding	133
2.2.24.1. Parameters	133
2.2.24.2. Responses	134
2.2.24.3. Consumes	134
2.2.24.4. Produces	134

2.2.24.5. Tags	134
2.2.25. partially update the specified ClusterPolicyBinding	134
2.2.25.1. Parameters	134
2.2.25.2. Responses	134
2.2.25.3. Consumes	135
2.2.25.4. Produces	135
2.2.25.5. Tags	135
2.2.26. replace the specified ClusterPolicyBinding	135
2.2.26.1. Parameters	135
2.2.26.2. Responses	135
2.2.26.3. Consumes	136
2.2.26.4. Produces	136
2.2.26.5. Tags	136
2.2.27. delete a ClusterPolicyBinding	136
2.2.27.1. Parameters	136
2.2.27.2. Responses	139
2.2.27.3. Consumes	139
2.2.27.4. Produces	139
2.2.27.5. Tags	139
2.2.28. list or watch objects of kind ClusterResourceQuota	139
2.2.28.1. Parameters	139
2.2.28.2. Responses	141
2.2.28.3. Consumes	142
2.2.28.4. Produces	142
2.2.28.5. Tags	142
2.2.29. create a ClusterResourceQuota	142
2.2.29.1. Parameters	142
2.2.29.2. Responses	142
2.2.29.3. Consumes	143
2.2.29.4. Produces	143
2.2.29.5. Tags	143
2.2.30. delete collection of ClusterResourceQuota	143
2.2.30.1. Parameters	143
2.2.30.2. Responses	145
2.2.30.3. Consumes	146
2.2.30.4. Produces	146
2.2.30.5. Tags	146
2.2.31. read the specified ClusterResourceQuota	146
2.2.31.1. Parameters	146
2.2.31.2. Responses	147
2.2.31.3. Consumes	147
2.2.31.4. Produces	147
2.2.31.5. Tags	147
2.2.32. partially update the specified ClusterResourceQuota	147
2.2.32.1. Parameters	147
2.2.32.2. Responses	147
2.2.32.3. Consumes	148
2.2.32.4. Produces	148
2.2.32.5. Tags	148
2.2.33. replace the specified ClusterResourceQuota	148
2.2.33.1. Parameters	148
2.2.33.2. Responses	148
2.2.33.3. Consumes	149

2.2.33.4. Produces	149
2.2.33.5. Tags	149
2.2.34. delete a ClusterResourceQuota	149
2.2.34.1. Parameters	149
2.2.34.2. Responses	152
2.2.34.3. Consumes	152
2.2.34.4. Produces	152
2.2.34.5. Tags	152
2.2.35. read status of the specified ClusterResourceQuota	152
2.2.35.1. Parameters	152
2.2.35.2. Responses	152
2.2.35.3. Consumes	153
2.2.35.4. Produces	153
2.2.35.5. Tags	153
2.2.36. partially update status of the specified ClusterResourceQuota	153
2.2.36.1. Parameters	153
2.2.36.2. Responses	153
2.2.36.3. Consumes	154
2.2.36.4. Produces	154
2.2.36.5. Tags	154
2.2.37. replace status of the specified ClusterResourceQuota	154
2.2.37.1. Parameters	154
2.2.37.2. Responses	154
2.2.37.3. Consumes	155
2.2.37.4. Produces	155
2.2.37.5. Tags	155
2.2.38. list objects of kind ClusterRoleBinding	155
2.2.38.1. Parameters	155
2.2.38.2. Responses	157
2.2.38.3. Consumes	158
2.2.38.4. Produces	158
2.2.38.5. Tags	158
2.2.39. create a ClusterRoleBinding	158
2.2.39.1. Parameters	158
2.2.39.2. Responses	158
2.2.39.3. Consumes	158
2.2.39.4. Produces	158
2.2.39.5. Tags	159
2.2.40. read the specified ClusterRoleBinding	159
2.2.40.1. Parameters	159
2.2.40.2. Responses	159
2.2.40.3. Consumes	159
2.2.40.4. Produces	159
2.2.40.5. Tags	159
2.2.41. partially update the specified ClusterRoleBinding	160
2.2.41.1. Parameters	160
2.2.41.2. Responses	160
2.2.41.3. Consumes	160
2.2.41.4. Produces	160
2.2.41.5. Tags	160
2.2.42. replace the specified ClusterRoleBinding	160
2.2.42.1. Parameters	161
2.2.42.2. Responses	161

2.2.42.3. Consumes	161
2.2.42.4. Produces	161
2.2.42.5. Tags	161
2.2.43. delete a ClusterRoleBinding	161
2.2.43.1. Parameters	161
2.2.43.2. Responses	164
2.2.43.3. Consumes	164
2.2.43.4. Produces	164
2.2.43.5. Tags	164
2.2.44. list objects of kind ClusterRole	164
2.2.44.1. Parameters	164
2.2.44.2. Responses	166
2.2.44.3. Consumes	167
2.2.44.4. Produces	167
2.2.44.5. Tags	167
2.2.45. create a ClusterRole	167
2.2.45.1. Parameters	167
2.2.45.2. Responses	167
2.2.45.3. Consumes	167
2.2.45.4. Produces	167
2.2.45.5. Tags	168
2.2.46. read the specified ClusterRole	168
2.2.46.1. Parameters	168
2.2.46.2. Responses	168
2.2.46.3. Consumes	168
2.2.46.4. Produces	168
2.2.46.5. Tags	168
2.2.47. partially update the specified ClusterRole	169
2.2.47.1. Parameters	169
2.2.47.2. Responses	169
2.2.47.3. Consumes	169
2.2.47.4. Produces	169
2.2.47.5. Tags	169
2.2.48. replace the specified ClusterRole	169
2.2.48.1. Parameters	170
2.2.48.2. Responses	170
2.2.48.3. Consumes	170
2.2.48.4. Produces	170
2.2.48.5. Tags	170
2.2.49. delete a ClusterRole	170
2.2.49.1. Parameters	170
2.2.49.2. Responses	173
2.2.49.3. Consumes	173
2.2.49.4. Produces	173
2.2.49.5. Tags	173
2.2.50. create a DeploymentConfigRollback	173
2.2.50.1. Parameters	173
2.2.50.2. Responses	173
2.2.50.3. Consumes	174
2.2.50.4. Produces	174
2.2.50.5. Tags	174
2.2.51. list or watch objects of kind DeploymentConfig	174
2.2.51.1. Parameters	174

2.2.51.2. Responses	176
2.2.51.3. Consumes	177
2.2.51.4. Produces	177
2.2.51.5. Tags	177
2.2.52. create a DeploymentConfig	177
2.2.52.1. Parameters	177
2.2.52.2. Responses	177
2.2.52.3. Consumes	177
2.2.52.4. Produces	177
2.2.52.5. Tags	178
2.2.53. list or watch objects of kind EgressNetworkPolicy	178
2.2.53.1. Parameters	178
2.2.53.2. Responses	180
2.2.53.3. Consumes	181
2.2.53.4. Produces	181
2.2.53.5. Tags	181
2.2.54. create an EgressNetworkPolicy	181
2.2.54.1. Parameters	181
2.2.54.2. Responses	181
2.2.54.3. Consumes	181
2.2.54.4. Produces	181
2.2.54.5. Tags	182
2.2.55. list or watch objects of kind Group	182
2.2.55.1. Parameters	182
2.2.55.2. Responses	184
2.2.55.3. Consumes	185
2.2.55.4. Produces	185
2.2.55.5. Tags	185
2.2.56. create a Group	185
2.2.56.1. Parameters	185
2.2.56.2. Responses	185
2.2.56.3. Consumes	185
2.2.56.4. Produces	185
2.2.56.5. Tags	186
2.2.57. delete collection of Group	186
2.2.57.1. Parameters	186
2.2.57.2. Responses	187
2.2.57.3. Consumes	188
2.2.57.4. Produces	188
2.2.57.5. Tags	188
2.2.58. read the specified Group	188
2.2.58.1. Parameters	188
2.2.58.2. Responses	188
2.2.58.3. Consumes	189
2.2.58.4. Produces	189
2.2.58.5. Tags	189
2.2.59. partially update the specified Group	189
2.2.59.1. Parameters	189
2.2.59.2. Responses	189
2.2.59.3. Consumes	189
2.2.59.4. Produces	190
2.2.59.5. Tags	190
2.2.60. replace the specified Group	190

2.2.60.1. Parameters	190
2.2.60.2. Responses	190
2.2.60.3. Consumes	190
2.2.60.4. Produces	190
2.2.60.5. Tags	191
2.2.61. delete a Group	191
2.2.61.1. Parameters	191
2.2.61.2. Responses	194
2.2.61.3. Consumes	194
2.2.61.4. Produces	194
2.2.61.5. Tags	194
2.2.62. list or watch objects of kind HostSubnet	194
2.2.62.1. Parameters	194
2.2.62.2. Responses	196
2.2.62.3. Consumes	197
2.2.62.4. Produces	197
2.2.62.5. Tags	197
2.2.63. create a HostSubnet	197
2.2.63.1. Parameters	197
2.2.63.2. Responses	197
2.2.63.3. Consumes	197
2.2.63.4. Produces	197
2.2.63.5. Tags	198
2.2.64. delete collection of HostSubnet	198
2.2.64.1. Parameters	198
2.2.64.2. Responses	200
2.2.64.3. Consumes	201
2.2.64.4. Produces	201
2.2.64.5. Tags	201
2.2.65. read the specified HostSubnet	201
2.2.65.1. Parameters	201
2.2.65.2. Responses	201
2.2.65.3. Consumes	202
2.2.65.4. Produces	202
2.2.65.5. Tags	202
2.2.66. partially update the specified HostSubnet	202
2.2.66.1. Parameters	202
2.2.66.2. Responses	202
2.2.66.3. Consumes	203
2.2.66.4. Produces	203
2.2.66.5. Tags	203
2.2.67. replace the specified HostSubnet	203
2.2.67.1. Parameters	203
2.2.67.2. Responses	203
2.2.67.3. Consumes	203
2.2.67.4. Produces	204
2.2.67.5. Tags	204
2.2.68. delete a HostSubnet	204
2.2.68.1. Parameters	204
2.2.68.2. Responses	207
2.2.68.3. Consumes	207
2.2.68.4. Produces	207
2.2.68.5. Tags	207

2.2.69. list or watch objects of kind Identity	207
2.2.69.1. Parameters	207
2.2.69.2. Responses	209
2.2.69.3. Consumes	210
2.2.69.4. Produces	210
2.2.69.5. Tags	210
2.2.70. create an Identity	210
2.2.70.1. Parameters	210
2.2.70.2. Responses	210
2.2.70.3. Consumes	210
2.2.70.4. Produces	210
2.2.70.5. Tags	211
2.2.71. delete collection of Identity	211
2.2.71.1. Parameters	211
2.2.71.2. Responses	212
2.2.71.3. Consumes	213
2.2.71.4. Produces	213
2.2.71.5. Tags	213
2.2.72. read the specified Identity	213
2.2.72.1. Parameters	213
2.2.72.2. Responses	213
2.2.72.3. Consumes	214
2.2.72.4. Produces	214
2.2.72.5. Tags	214
2.2.73. partially update the specified Identity	214
2.2.73.1. Parameters	214
2.2.73.2. Responses	214
2.2.73.3. Consumes	214
2.2.73.4. Produces	215
2.2.73.5. Tags	215
2.2.74. replace the specified Identity	215
2.2.74.1. Parameters	215
2.2.74.2. Responses	215
2.2.74.3. Consumes	215
2.2.74.4. Produces	215
2.2.74.5. Tags	216
2.2.75. delete an Identity	216
2.2.75.1. Parameters	216
2.2.75.2. Responses	219
2.2.75.3. Consumes	219
2.2.75.4. Produces	219
2.2.75.5. Tags	219
2.2.76. list or watch objects of kind Image	219
2.2.76.1. Parameters	219
2.2.76.2. Responses	221
2.2.76.3. Consumes	222
2.2.76.4. Produces	222
2.2.76.5. Tags	222
2.2.77. create an Image	222
2.2.77.1. Parameters	222
2.2.77.2. Responses	222
2.2.77.3. Consumes	222
2.2.77.4. Produces	222

2.2.77.5. Tags	223
2.2.78. delete collection of Image	223
2.2.78.1. Parameters	223
2.2.78.2. Responses	224
2.2.78.3. Consumes	225
2.2.78.4. Produces	225
2.2.78.5. Tags	225
2.2.79. read the specified Image	225
2.2.79.1. Parameters	225
2.2.79.2. Responses	225
2.2.79.3. Consumes	226
2.2.79.4. Produces	226
2.2.79.5. Tags	226
2.2.80. partially update the specified Image	226
2.2.80.1. Parameters	226
2.2.80.2. Responses	226
2.2.80.3. Consumes	226
2.2.80.4. Produces	227
2.2.80.5. Tags	227
2.2.81. replace the specified Image	227
2.2.81.1. Parameters	227
2.2.81.2. Responses	227
2.2.81.3. Consumes	227
2.2.81.4. Produces	227
2.2.81.5. Tags	228
2.2.82. delete an Image	228
2.2.82.1. Parameters	228
2.2.82.2. Responses	231
2.2.82.3. Consumes	231
2.2.82.4. Produces	231
2.2.82.5. Tags	231
2.2.83. create an ImageSignature	231
2.2.83.1. Parameters	231
2.2.83.2. Responses	231
2.2.83.3. Consumes	231
2.2.83.4. Produces	232
2.2.83.5. Tags	232
2.2.84. delete an ImageSignature	232
2.2.84.1. Parameters	232
2.2.84.2. Responses	232
2.2.84.3. Consumes	232
2.2.84.4. Produces	232
2.2.84.5. Tags	233
2.2.85. create an ImageStreamImport	233
2.2.85.1. Parameters	233
2.2.85.2. Responses	233
2.2.85.3. Consumes	233
2.2.85.4. Produces	233
2.2.85.5. Tags	233
2.2.86. create an ImageStreamMapping	233
2.2.86.1. Parameters	234
2.2.86.2. Responses	234
2.2.86.3. Consumes	234

2.2.86.4. Produces	234
2.2.86.5. Tags	234
2.2.87. list or watch objects of kind ImageStream	234
2.2.87.1. Parameters	234
2.2.87.2. Responses	236
2.2.87.3. Consumes	237
2.2.87.4. Produces	237
2.2.87.5. Tags	237
2.2.88. create an ImageStream	237
2.2.88.1. Parameters	237
2.2.88.2. Responses	237
2.2.88.3. Consumes	237
2.2.88.4. Produces	237
2.2.88.5. Tags	238
2.2.89. list objects of kind ImageStreamTag	238
2.2.89.1. Parameters	238
2.2.89.2. Responses	240
2.2.89.3. Consumes	241
2.2.89.4. Produces	241
2.2.89.5. Tags	241
2.2.90. create an ImageStreamTag	241
2.2.90.1. Parameters	241
2.2.90.2. Responses	241
2.2.90.3. Consumes	241
2.2.90.4. Produces	241
2.2.90.5. Tags	242
2.2.91. create a LocalResourceAccessReview	242
2.2.91.1. Parameters	242
2.2.91.2. Responses	242
2.2.91.3. Consumes	242
2.2.91.4. Produces	242
2.2.91.5. Tags	242
2.2.92. create a LocalSubjectAccessReview	243
2.2.92.1. Parameters	243
2.2.92.2. Responses	243
2.2.92.3. Consumes	243
2.2.92.4. Produces	243
2.2.92.5. Tags	243
2.2.93. list objects of kind AppliedClusterResourceQuota	243
2.2.93.1. Parameters	244
2.2.93.2. Responses	245
2.2.93.3. Consumes	246
2.2.93.4. Produces	246
2.2.93.5. Tags	246
2.2.94. read the specified AppliedClusterResourceQuota	246
2.2.94.1. Parameters	246
2.2.94.2. Responses	247
2.2.94.3. Consumes	247
2.2.94.4. Produces	247
2.2.94.5. Tags	247
2.2.95. list or watch objects of kind BuildConfig	247
2.2.95.1. Parameters	247
2.2.95.2. Responses	249

2.2.95.3. Consumes	250
2.2.95.4. Produces	250
2.2.95.5. Tags	250
2.2.96. create a BuildConfig	250
2.2.96.1. Parameters	250
2.2.96.2. Responses	250
2.2.96.3. Consumes	251
2.2.96.4. Produces	251
2.2.96.5. Tags	251
2.2.97. delete collection of BuildConfig	251
2.2.97.1. Parameters	251
2.2.97.2. Responses	253
2.2.97.3. Consumes	254
2.2.97.4. Produces	254
2.2.97.5. Tags	254
2.2.98. read the specified BuildConfig	254
2.2.98.1. Parameters	254
2.2.98.2. Responses	255
2.2.98.3. Consumes	255
2.2.98.4. Produces	255
2.2.98.5. Tags	255
2.2.99. partially update the specified BuildConfig	255
2.2.99.1. Parameters	255
2.2.99.2. Responses	256
2.2.99.3. Consumes	256
2.2.99.4. Produces	256
2.2.99.5. Tags	256
2.2.100. replace the specified BuildConfig	256
2.2.100.1. Parameters	256
2.2.100.2. Responses	257
2.2.100.3. Consumes	257
2.2.100.4. Produces	257
2.2.100.5. Tags	257
2.2.101. delete a BuildConfig	257
2.2.101.1. Parameters	257
2.2.101.2. Responses	260
2.2.101.3. Consumes	260
2.2.101.4. Produces	260
2.2.101.5. Tags	260
2.2.102. create instantiate of a BuildRequest	260
2.2.102.1. Parameters	260
2.2.102.2. Responses	261
2.2.102.3. Consumes	261
2.2.102.4. Produces	261
2.2.102.5. Tags	261
2.2.103. connect POST requests to instantiatebinary of BinaryBuildRequestOptions	261
2.2.103.1. Parameters	261
2.2.103.2. Responses	263
2.2.103.3. Consumes	263
2.2.103.4. Produces	263
2.2.103.5. Tags	263
2.2.104. connect POST requests to webhooks of Build	263
2.2.104.1. Parameters	263

2.2.104.2. Responses	264
2.2.104.3. Consumes	264
2.2.104.4. Produces	264
2.2.104.5. Tags	264
2.2.105. connect POST requests to webhooks of Build	264
2.2.105.1. Parameters	264
2.2.105.2. Responses	264
2.2.105.3. Consumes	265
2.2.105.4. Produces	265
2.2.105.5. Tags	265
2.2.106. list or watch objects of kind Build	265
2.2.106.1. Parameters	265
2.2.106.2. Responses	267
2.2.106.3. Consumes	268
2.2.106.4. Produces	268
2.2.106.5. Tags	268
2.2.107. create a Build	268
2.2.107.1. Parameters	268
2.2.107.2. Responses	268
2.2.107.3. Consumes	269
2.2.107.4. Produces	269
2.2.107.5. Tags	269
2.2.108. delete collection of Build	269
2.2.108.1. Parameters	269
2.2.108.2. Responses	271
2.2.108.3. Consumes	272
2.2.108.4. Produces	272
2.2.108.5. Tags	272
2.2.109. read the specified Build	272
2.2.109.1. Parameters	272
2.2.109.2. Responses	273
2.2.109.3. Consumes	273
2.2.109.4. Produces	273
2.2.109.5. Tags	273
2.2.110. partially update the specified Build	273
2.2.110.1. Parameters	273
2.2.110.2. Responses	274
2.2.110.3. Consumes	274
2.2.110.4. Produces	274
2.2.110.5. Tags	274
2.2.111. replace the specified Build	274
2.2.111.1. Parameters	274
2.2.111.2. Responses	275
2.2.111.3. Consumes	275
2.2.111.4. Produces	275
2.2.111.5. Tags	275
2.2.112. delete a Build	275
2.2.112.1. Parameters	275
2.2.112.2. Responses	278
2.2.112.3. Consumes	278
2.2.112.4. Produces	278
2.2.112.5. Tags	278
2.2.113. create clone of a BuildRequest	278

2.2.113.1. Parameters	278
2.2.113.2. Responses	279
2.2.113.3. Consumes	279
2.2.113.4. Produces	279
2.2.113.5. Tags	279
2.2.114. replace details of the specified Build	279
2.2.114.1. Parameters	279
2.2.114.2. Responses	280
2.2.114.3. Consumes	280
2.2.114.4. Produces	280
2.2.114.5. Tags	280
2.2.115. read log of the specified BuildLog	280
2.2.115.1. Parameters	280
2.2.115.2. Responses	284
2.2.115.3. Consumes	284
2.2.115.4. Produces	284
2.2.115.5. Tags	284
2.2.116. create a DeploymentConfigRollback	284
2.2.116.1. Parameters	284
2.2.116.2. Responses	285
2.2.116.3. Consumes	285
2.2.116.4. Produces	285
2.2.116.5. Tags	285
2.2.117. list or watch objects of kind DeploymentConfig	285
2.2.117.1. Parameters	285
2.2.117.2. Responses	287
2.2.117.3. Consumes	288
2.2.117.4. Produces	288
2.2.117.5. Tags	288
2.2.118. create a DeploymentConfig	288
2.2.118.1. Parameters	288
2.2.118.2. Responses	288
2.2.118.3. Consumes	289
2.2.118.4. Produces	289
2.2.118.5. Tags	289
2.2.119. delete collection of DeploymentConfig	289
2.2.119.1. Parameters	289
2.2.119.2. Responses	291
2.2.119.3. Consumes	292
2.2.119.4. Produces	292
2.2.119.5. Tags	292
2.2.120. read the specified DeploymentConfig	292
2.2.120.1. Parameters	292
2.2.120.2. Responses	293
2.2.120.3. Consumes	293
2.2.120.4. Produces	293
2.2.120.5. Tags	293
2.2.121. partially update the specified DeploymentConfig	293
2.2.121.1. Parameters	293
2.2.121.2. Responses	294
2.2.121.3. Consumes	294
2.2.121.4. Produces	294
2.2.121.5. Tags	294

2.2.122. replace the specified DeploymentConfig	294
2.2.122.1. Parameters	295
2.2.122.2. Responses	295
2.2.122.3. Consumes	295
2.2.122.4. Produces	295
2.2.122.5. Tags	295
2.2.123. delete a DeploymentConfig	295
2.2.123.1. Parameters	296
2.2.123.2. Responses	298
2.2.123.3. Consumes	298
2.2.123.4. Produces	298
2.2.123.5. Tags	298
2.2.124. create instantiate of a DeploymentRequest	298
2.2.124.1. Parameters	298
2.2.124.2. Responses	299
2.2.124.3. Consumes	299
2.2.124.4. Produces	299
2.2.124.5. Tags	299
2.2.125. read log of the specified DeploymentLog	299
2.2.125.1. Parameters	299
2.2.125.2. Responses	303
2.2.125.3. Consumes	303
2.2.125.4. Produces	303
2.2.125.5. Tags	303
2.2.126. create rollback of a DeploymentConfigRollback	303
2.2.126.1. Parameters	303
2.2.126.2. Responses	304
2.2.126.3. Consumes	304
2.2.126.4. Produces	304
2.2.126.5. Tags	304
2.2.127. read scale of the specified Scale	304
2.2.127.1. Parameters	304
2.2.127.2. Responses	305
2.2.127.3. Consumes	305
2.2.127.4. Produces	305
2.2.127.5. Tags	305
2.2.128. partially update scale of the specified Scale	305
2.2.128.1. Parameters	305
2.2.128.2. Responses	306
2.2.128.3. Consumes	306
2.2.128.4. Produces	306
2.2.128.5. Tags	306
2.2.129. replace scale of the specified Scale	306
2.2.129.1. Parameters	307
2.2.129.2. Responses	307
2.2.129.3. Consumes	307
2.2.129.4. Produces	307
2.2.129.5. Tags	307
2.2.130. read status of the specified DeploymentConfig	307
2.2.130.1. Parameters	308
2.2.130.2. Responses	308
2.2.130.3. Consumes	308
2.2.130.4. Produces	308

2.2.130.5. Tags	308
2.2.131. partially update status of the specified DeploymentConfig	308
2.2.131.1. Parameters	308
2.2.131.2. Responses	309
2.2.131.3. Consumes	309
2.2.131.4. Produces	309
2.2.131.5. Tags	309
2.2.132. replace status of the specified DeploymentConfig	309
2.2.132.1. Parameters	310
2.2.132.2. Responses	310
2.2.132.3. Consumes	310
2.2.132.4. Produces	310
2.2.132.5. Tags	310
2.2.133. list or watch objects of kind EgressNetworkPolicy	311
2.2.133.1. Parameters	311
2.2.133.2. Responses	312
2.2.133.3. Consumes	313
2.2.133.4. Produces	313
2.2.133.5. Tags	313
2.2.134. create an EgressNetworkPolicy	313
2.2.134.1. Parameters	313
2.2.134.2. Responses	313
2.2.134.3. Consumes	314
2.2.134.4. Produces	314
2.2.134.5. Tags	314
2.2.135. delete collection of EgressNetworkPolicy	314
2.2.135.1. Parameters	314
2.2.135.2. Responses	316
2.2.135.3. Consumes	317
2.2.135.4. Produces	317
2.2.135.5. Tags	317
2.2.136. read the specified EgressNetworkPolicy	317
2.2.136.1. Parameters	317
2.2.136.2. Responses	318
2.2.136.3. Consumes	318
2.2.136.4. Produces	318
2.2.136.5. Tags	318
2.2.137. partially update the specified EgressNetworkPolicy	318
2.2.137.1. Parameters	318
2.2.137.2. Responses	319
2.2.137.3. Consumes	319
2.2.137.4. Produces	319
2.2.137.5. Tags	319
2.2.138. replace the specified EgressNetworkPolicy	319
2.2.138.1. Parameters	320
2.2.138.2. Responses	320
2.2.138.3. Consumes	320
2.2.138.4. Produces	320
2.2.138.5. Tags	320
2.2.139. delete an EgressNetworkPolicy	320
2.2.139.1. Parameters	321
2.2.139.2. Responses	323
2.2.139.3. Consumes	323

2.2.139.4. Produces	323
2.2.139.5. Tags	323
2.2.140. read the specified ImageStreamImage	323
2.2.140.1. Parameters	323
2.2.140.2. Responses	324
2.2.140.3. Consumes	324
2.2.140.4. Produces	324
2.2.140.5. Tags	324
2.2.141. create an ImageStreamImport	324
2.2.141.1. Parameters	324
2.2.141.2. Responses	325
2.2.141.3. Consumes	325
2.2.141.4. Produces	325
2.2.141.5. Tags	325
2.2.142. create an ImageStreamMapping	325
2.2.142.1. Parameters	325
2.2.142.2. Responses	326
2.2.142.3. Consumes	326
2.2.142.4. Produces	326
2.2.142.5. Tags	326
2.2.143. list or watch objects of kind ImageStream	326
2.2.143.1. Parameters	326
2.2.143.2. Responses	328
2.2.143.3. Consumes	329
2.2.143.4. Produces	329
2.2.143.5. Tags	329
2.2.144. create an ImageStream	329
2.2.144.1. Parameters	329
2.2.144.2. Responses	329
2.2.144.3. Consumes	330
2.2.144.4. Produces	330
2.2.144.5. Tags	330
2.2.145. delete collection of ImageStream	330
2.2.145.1. Parameters	330
2.2.145.2. Responses	332
2.2.145.3. Consumes	333
2.2.145.4. Produces	333
2.2.145.5. Tags	333
2.2.146. read the specified ImageStream	333
2.2.146.1. Parameters	333
2.2.146.2. Responses	334
2.2.146.3. Consumes	334
2.2.146.4. Produces	334
2.2.146.5. Tags	334
2.2.147. partially update the specified ImageStream	334
2.2.147.1. Parameters	334
2.2.147.2. Responses	335
2.2.147.3. Consumes	335
2.2.147.4. Produces	335
2.2.147.5. Tags	335
2.2.148. replace the specified ImageStream	335
2.2.148.1. Parameters	335
2.2.148.2. Responses	336

2.2.148.3. Consumes	336
2.2.148.4. Produces	336
2.2.148.5. Tags	336
2.2.149. delete an ImageStream	336
2.2.149.1. Parameters	336
2.2.149.2. Responses	339
2.2.149.3. Consumes	339
2.2.149.4. Produces	339
2.2.149.5. Tags	339
2.2.150. read secrets of the specified SecretList	339
2.2.150.1. Parameters	339
2.2.150.2. Responses	342
2.2.150.3. Consumes	342
2.2.150.4. Produces	342
2.2.150.5. Tags	342
2.2.151. read status of the specified ImageStream	342
2.2.151.1. Parameters	342
2.2.151.2. Responses	343
2.2.151.3. Consumes	343
2.2.151.4. Produces	343
2.2.151.5. Tags	343
2.2.152. partially update status of the specified ImageStream	343
2.2.152.1. Parameters	343
2.2.152.2. Responses	344
2.2.152.3. Consumes	344
2.2.152.4. Produces	344
2.2.152.5. Tags	344
2.2.153. replace status of the specified ImageStream	344
2.2.153.1. Parameters	344
2.2.153.2. Responses	345
2.2.153.3. Consumes	345
2.2.153.4. Produces	345
2.2.153.5. Tags	345
2.2.154. list objects of kind ImageStreamTag	345
2.2.154.1. Parameters	345
2.2.154.2. Responses	347
2.2.154.3. Consumes	348
2.2.154.4. Produces	348
2.2.154.5. Tags	348
2.2.155. create an ImageStreamTag	348
2.2.155.1. Parameters	348
2.2.155.2. Responses	348
2.2.155.3. Consumes	349
2.2.155.4. Produces	349
2.2.155.5. Tags	349
2.2.156. read the specified ImageStreamTag	349
2.2.156.1. Parameters	349
2.2.156.2. Responses	349
2.2.156.3. Consumes	350
2.2.156.4. Produces	350
2.2.156.5. Tags	350
2.2.157. partially update the specified ImageStreamTag	350
2.2.157.1. Parameters	350

2.2.157.2. Responses	351
2.2.157.3. Consumes	351
2.2.157.4. Produces	351
2.2.157.5. Tags	351
2.2.158. replace the specified ImageStreamTag	351
2.2.158.1. Parameters	351
2.2.158.2. Responses	352
2.2.158.3. Consumes	352
2.2.158.4. Produces	352
2.2.158.5. Tags	352
2.2.159. delete an ImageStreamTag	352
2.2.159.1. Parameters	352
2.2.159.2. Responses	353
2.2.159.3. Consumes	353
2.2.159.4. Produces	353
2.2.159.5. Tags	353
2.2.160. create a LocalResourceAccessReview	353
2.2.160.1. Parameters	353
2.2.160.2. Responses	354
2.2.160.3. Consumes	354
2.2.160.4. Produces	354
2.2.160.5. Tags	354
2.2.161. create a LocalSubjectAccessReview	354
2.2.161.1. Parameters	354
2.2.161.2. Responses	355
2.2.161.3. Consumes	355
2.2.161.4. Produces	355
2.2.161.5. Tags	355
2.2.162. create a PodSecurityPolicyReview	355
2.2.162.1. Parameters	355
2.2.162.2. Responses	356
2.2.162.3. Consumes	356
2.2.162.4. Produces	356
2.2.162.5. Tags	356
2.2.163. create a PodSecurityPolicySelfSubjectReview	356
2.2.163.1. Parameters	356
2.2.163.2. Responses	357
2.2.163.3. Consumes	357
2.2.163.4. Produces	357
2.2.163.5. Tags	357
2.2.164. create a PodSecurityPolicySubjectReview	357
2.2.164.1. Parameters	357
2.2.164.2. Responses	358
2.2.164.3. Consumes	358
2.2.164.4. Produces	358
2.2.164.5. Tags	358
2.2.165. list or watch objects of kind Policy	358
2.2.165.1. Parameters	358
2.2.165.2. Responses	360
2.2.165.3. Consumes	361
2.2.165.4. Produces	361
2.2.165.5. Tags	361
2.2.166. create a Policy	361

2.2.166.1. Parameters	361
2.2.166.2. Responses	361
2.2.166.3. Consumes	362
2.2.166.4. Produces	362
2.2.166.5. Tags	362
2.2.167. delete collection of Policy	362
2.2.167.1. Parameters	362
2.2.167.2. Responses	364
2.2.167.3. Consumes	365
2.2.167.4. Produces	365
2.2.167.5. Tags	365
2.2.168. read the specified Policy	365
2.2.168.1. Parameters	365
2.2.168.2. Responses	366
2.2.168.3. Consumes	366
2.2.168.4. Produces	366
2.2.168.5. Tags	366
2.2.169. partially update the specified Policy	366
2.2.169.1. Parameters	366
2.2.169.2. Responses	367
2.2.169.3. Consumes	367
2.2.169.4. Produces	367
2.2.169.5. Tags	367
2.2.170. replace the specified Policy	367
2.2.170.1. Parameters	367
2.2.170.2. Responses	368
2.2.170.3. Consumes	368
2.2.170.4. Produces	368
2.2.170.5. Tags	368
2.2.171. delete a Policy	368
2.2.171.1. Parameters	368
2.2.171.2. Responses	371
2.2.171.3. Consumes	371
2.2.171.4. Produces	371
2.2.171.5. Tags	371
2.2.172. list or watch objects of kind PolicyBinding	371
2.2.172.1. Parameters	371
2.2.172.2. Responses	373
2.2.172.3. Consumes	374
2.2.172.4. Produces	374
2.2.172.5. Tags	374
2.2.173. create a PolicyBinding	374
2.2.173.1. Parameters	374
2.2.173.2. Responses	374
2.2.173.3. Consumes	375
2.2.173.4. Produces	375
2.2.173.5. Tags	375
2.2.174. delete collection of PolicyBinding	375
2.2.174.1. Parameters	375
2.2.174.2. Responses	377
2.2.174.3. Consumes	378
2.2.174.4. Produces	378
2.2.174.5. Tags	378

2.2.175. read the specified PolicyBinding	378
2.2.175.1. Parameters	378
2.2.175.2. Responses	379
2.2.175.3. Consumes	379
2.2.175.4. Produces	379
2.2.175.5. Tags	379
2.2.176. partially update the specified PolicyBinding	379
2.2.176.1. Parameters	379
2.2.176.2. Responses	380
2.2.176.3. Consumes	380
2.2.176.4. Produces	380
2.2.176.5. Tags	380
2.2.177. replace the specified PolicyBinding	380
2.2.177.1. Parameters	380
2.2.177.2. Responses	381
2.2.177.3. Consumes	381
2.2.177.4. Produces	381
2.2.177.5. Tags	381
2.2.178. delete a PolicyBinding	381
2.2.178.1. Parameters	381
2.2.178.2. Responses	384
2.2.178.3. Consumes	384
2.2.178.4. Produces	384
2.2.178.5. Tags	384
2.2.179. create a Template	384
2.2.179.1. Parameters	384
2.2.179.2. Responses	385
2.2.179.3. Consumes	385
2.2.179.4. Produces	385
2.2.179.5. Tags	385
2.2.180. create a ResourceAccessReview	385
2.2.180.1. Parameters	385
2.2.180.2. Responses	386
2.2.180.3. Consumes	386
2.2.180.4. Produces	386
2.2.180.5. Tags	386
2.2.181. list or watch objects of kind RoleBindingRestriction	386
2.2.181.1. Parameters	386
2.2.181.2. Responses	388
2.2.181.3. Consumes	389
2.2.181.4. Produces	389
2.2.181.5. Tags	389
2.2.182. create a RoleBindingRestriction	389
2.2.182.1. Parameters	389
2.2.182.2. Responses	390
2.2.182.3. Consumes	390
2.2.182.4. Produces	390
2.2.182.5. Tags	390
2.2.183. delete collection of RoleBindingRestriction	390
2.2.183.1. Parameters	390
2.2.183.2. Responses	392
2.2.183.3. Consumes	393
2.2.183.4. Produces	393

2.2.183.5. Tags	393
2.2.184. read the specified RoleBindingRestriction	393
2.2.184.1. Parameters	393
2.2.184.2. Responses	394
2.2.184.3. Consumes	394
2.2.184.4. Produces	394
2.2.184.5. Tags	394
2.2.185. partially update the specified RoleBindingRestriction	394
2.2.185.1. Parameters	394
2.2.185.2. Responses	395
2.2.185.3. Consumes	395
2.2.185.4. Produces	395
2.2.185.5. Tags	395
2.2.186. replace the specified RoleBindingRestriction	395
2.2.186.1. Parameters	396
2.2.186.2. Responses	396
2.2.186.3. Consumes	396
2.2.186.4. Produces	396
2.2.186.5. Tags	396
2.2.187. delete a RoleBindingRestriction	396
2.2.187.1. Parameters	397
2.2.187.2. Responses	399
2.2.187.3. Consumes	399
2.2.187.4. Produces	399
2.2.187.5. Tags	399
2.2.188. list objects of kind RoleBinding	399
2.2.188.1. Parameters	399
2.2.188.2. Responses	401
2.2.188.3. Consumes	402
2.2.188.4. Produces	402
2.2.188.5. Tags	402
2.2.189. create a RoleBinding	402
2.2.189.1. Parameters	402
2.2.189.2. Responses	402
2.2.189.3. Consumes	403
2.2.189.4. Produces	403
2.2.189.5. Tags	403
2.2.190. read the specified RoleBinding	403
2.2.190.1. Parameters	403
2.2.190.2. Responses	403
2.2.190.3. Consumes	404
2.2.190.4. Produces	404
2.2.190.5. Tags	404
2.2.191. partially update the specified RoleBinding	404
2.2.191.1. Parameters	404
2.2.191.2. Responses	404
2.2.191.3. Consumes	405
2.2.191.4. Produces	405
2.2.191.5. Tags	405
2.2.192. replace the specified RoleBinding	405
2.2.192.1. Parameters	405
2.2.192.2. Responses	406
2.2.192.3. Consumes	406

2.2.192.4. Produces	406
2.2.192.5. Tags	406
2.2.193. delete a RoleBinding	406
2.2.193.1. Parameters	406
2.2.193.2. Responses	409
2.2.193.3. Consumes	409
2.2.193.4. Produces	409
2.2.193.5. Tags	409
2.2.194. list objects of kind Role	409
2.2.194.1. Parameters	409
2.2.194.2. Responses	411
2.2.194.3. Consumes	412
2.2.194.4. Produces	412
2.2.194.5. Tags	412
2.2.195. create a Role	412
2.2.195.1. Parameters	412
2.2.195.2. Responses	412
2.2.195.3. Consumes	413
2.2.195.4. Produces	413
2.2.195.5. Tags	413
2.2.196. read the specified Role	413
2.2.196.1. Parameters	413
2.2.196.2. Responses	413
2.2.196.3. Consumes	414
2.2.196.4. Produces	414
2.2.196.5. Tags	414
2.2.197. partially update the specified Role	414
2.2.197.1. Parameters	414
2.2.197.2. Responses	414
2.2.197.3. Consumes	414
2.2.197.4. Produces	415
2.2.197.5. Tags	415
2.2.198. replace the specified Role	415
2.2.198.1. Parameters	415
2.2.198.2. Responses	415
2.2.198.3. Consumes	416
2.2.198.4. Produces	416
2.2.198.5. Tags	416
2.2.199. delete a Role	416
2.2.199.1. Parameters	416
2.2.199.2. Responses	419
2.2.199.3. Consumes	419
2.2.199.4. Produces	419
2.2.199.5. Tags	419
2.2.200. list or watch objects of kind Route	419
2.2.200.1. Parameters	419
2.2.200.2. Responses	421
2.2.200.3. Consumes	422
2.2.200.4. Produces	422
2.2.200.5. Tags	422
2.2.201. create a Route	422
2.2.201.1. Parameters	422
2.2.201.2. Responses	422

2.2.201.3. Consumes	423
2.2.201.4. Produces	423
2.2.201.5. Tags	423
2.2.202. delete collection of Route	423
2.2.202.1. Parameters	423
2.2.202.2. Responses	425
2.2.202.3. Consumes	426
2.2.202.4. Produces	426
2.2.202.5. Tags	426
2.2.203. read the specified Route	426
2.2.203.1. Parameters	426
2.2.203.2. Responses	427
2.2.203.3. Consumes	427
2.2.203.4. Produces	427
2.2.203.5. Tags	427
2.2.204. partially update the specified Route	427
2.2.204.1. Parameters	427
2.2.204.2. Responses	428
2.2.204.3. Consumes	428
2.2.204.4. Produces	428
2.2.204.5. Tags	428
2.2.205. replace the specified Route	428
2.2.205.1. Parameters	428
2.2.205.2. Responses	429
2.2.205.3. Consumes	429
2.2.205.4. Produces	429
2.2.205.5. Tags	429
2.2.206. delete a Route	429
2.2.206.1. Parameters	429
2.2.206.2. Responses	432
2.2.206.3. Consumes	432
2.2.206.4. Produces	432
2.2.206.5. Tags	432
2.2.207. read status of the specified Route	432
2.2.207.1. Parameters	432
2.2.207.2. Responses	433
2.2.207.3. Consumes	433
2.2.207.4. Produces	433
2.2.207.5. Tags	433
2.2.208. partially update status of the specified Route	433
2.2.208.1. Parameters	433
2.2.208.2. Responses	434
2.2.208.3. Consumes	434
2.2.208.4. Produces	434
2.2.208.5. Tags	434
2.2.209. replace status of the specified Route	434
2.2.209.1. Parameters	434
2.2.209.2. Responses	435
2.2.209.3. Consumes	435
2.2.209.4. Produces	435
2.2.209.5. Tags	435
2.2.210. create a SelfSubjectRulesReview	435
2.2.210.1. Parameters	435

2.2.210.2. Responses	436
2.2.210.3. Consumes	436
2.2.210.4. Produces	436
2.2.210.5. Tags	436
2.2.211. create a SubjectAccessReview	436
2.2.211.1. Parameters	436
2.2.211.2. Responses	437
2.2.211.3. Consumes	437
2.2.211.4. Produces	437
2.2.211.5. Tags	437
2.2.212. create a SubjectRulesReview	437
2.2.212.1. Parameters	437
2.2.212.2. Responses	438
2.2.212.3. Consumes	438
2.2.212.4. Produces	438
2.2.212.5. Tags	438
2.2.213. list or watch objects of kind Template	438
2.2.213.1. Parameters	438
2.2.213.2. Responses	440
2.2.213.3. Consumes	441
2.2.213.4. Produces	441
2.2.213.5. Tags	441
2.2.214. create a Template	441
2.2.214.1. Parameters	441
2.2.214.2. Responses	441
2.2.214.3. Consumes	442
2.2.214.4. Produces	442
2.2.214.5. Tags	442
2.2.215. delete collection of Template	442
2.2.215.1. Parameters	442
2.2.215.2. Responses	444
2.2.215.3. Consumes	445
2.2.215.4. Produces	445
2.2.215.5. Tags	445
2.2.216. read the specified Template	445
2.2.216.1. Parameters	445
2.2.216.2. Responses	446
2.2.216.3. Consumes	446
2.2.216.4. Produces	446
2.2.216.5. Tags	446
2.2.217. partially update the specified Template	446
2.2.217.1. Parameters	446
2.2.217.2. Responses	447
2.2.217.3. Consumes	447
2.2.217.4. Produces	447
2.2.217.5. Tags	447
2.2.218. replace the specified Template	447
2.2.218.1. Parameters	447
2.2.218.2. Responses	448
2.2.218.3. Consumes	448
2.2.218.4. Produces	448
2.2.218.5. Tags	448
2.2.219. delete a Template	448

2.2.219.1. Parameters	448
2.2.219.2. Responses	451
2.2.219.3. Consumes	451
2.2.219.4. Produces	451
2.2.219.5. Tags	451
2.2.220. list or watch objects of kind NetNamespace	451
2.2.220.1. Parameters	451
2.2.220.2. Responses	453
2.2.220.3. Consumes	454
2.2.220.4. Produces	454
2.2.220.5. Tags	454
2.2.221. create a NetNamespace	454
2.2.221.1. Parameters	454
2.2.221.2. Responses	454
2.2.221.3. Consumes	455
2.2.221.4. Produces	455
2.2.221.5. Tags	455
2.2.222. delete collection of NetNamespace	455
2.2.222.1. Parameters	455
2.2.222.2. Responses	457
2.2.222.3. Consumes	458
2.2.222.4. Produces	458
2.2.222.5. Tags	458
2.2.223. read the specified NetNamespace	458
2.2.223.1. Parameters	458
2.2.223.2. Responses	459
2.2.223.3. Consumes	459
2.2.223.4. Produces	459
2.2.223.5. Tags	459
2.2.224. partially update the specified NetNamespace	459
2.2.224.1. Parameters	459
2.2.224.2. Responses	459
2.2.224.3. Consumes	460
2.2.224.4. Produces	460
2.2.224.5. Tags	460
2.2.225. replace the specified NetNamespace	460
2.2.225.1. Parameters	460
2.2.225.2. Responses	460
2.2.225.3. Consumes	461
2.2.225.4. Produces	461
2.2.225.5. Tags	461
2.2.226. delete a NetNamespace	461
2.2.226.1. Parameters	461
2.2.226.2. Responses	464
2.2.226.3. Consumes	464
2.2.226.4. Produces	464
2.2.226.5. Tags	464
2.2.227. list or watch objects of kind OAuthAccessToken	464
2.2.227.1. Parameters	464
2.2.227.2. Responses	466
2.2.227.3. Consumes	467
2.2.227.4. Produces	467
2.2.227.5. Tags	467

2.2.228. create an OAuthAccessToken	467
2.2.228.1. Parameters	467
2.2.228.2. Responses	467
2.2.228.3. Consumes	467
2.2.228.4. Produces	467
2.2.228.5. Tags	468
2.2.229. delete collection of OAuthAccessToken	468
2.2.229.1. Parameters	468
2.2.229.2. Responses	470
2.2.229.3. Consumes	471
2.2.229.4. Produces	471
2.2.229.5. Tags	471
2.2.230. read the specified OAuthAccessToken	471
2.2.230.1. Parameters	471
2.2.230.2. Responses	472
2.2.230.3. Consumes	472
2.2.230.4. Produces	472
2.2.230.5. Tags	472
2.2.231. partially update the specified OAuthAccessToken	472
2.2.231.1. Parameters	472
2.2.231.2. Responses	472
2.2.231.3. Consumes	473
2.2.231.4. Produces	473
2.2.231.5. Tags	473
2.2.232. replace the specified OAuthAccessToken	473
2.2.232.1. Parameters	473
2.2.232.2. Responses	473
2.2.232.3. Consumes	474
2.2.232.4. Produces	474
2.2.232.5. Tags	474
2.2.233. delete an OAuthAccessToken	474
2.2.233.1. Parameters	474
2.2.233.2. Responses	477
2.2.233.3. Consumes	477
2.2.233.4. Produces	477
2.2.233.5. Tags	477
2.2.234. list or watch objects of kind OAuthAuthorizeToken	477
2.2.234.1. Parameters	477
2.2.234.2. Responses	479
2.2.234.3. Consumes	480
2.2.234.4. Produces	480
2.2.234.5. Tags	480
2.2.235. create an OAuthAuthorizeToken	480
2.2.235.1. Parameters	480
2.2.235.2. Responses	480
2.2.235.3. Consumes	480
2.2.235.4. Produces	481
2.2.235.5. Tags	481
2.2.236. delete collection of OAuthAuthorizeToken	481
2.2.236.1. Parameters	481
2.2.236.2. Responses	483
2.2.236.3. Consumes	484
2.2.236.4. Produces	484

2.2.236.5. Tags	484
2.2.237. read the specified OAuthAuthorizeToken	484
2.2.237.1. Parameters	484
2.2.237.2. Responses	485
2.2.237.3. Consumes	485
2.2.237.4. Produces	485
2.2.237.5. Tags	485
2.2.238. partially update the specified OAuthAuthorizeToken	485
2.2.238.1. Parameters	485
2.2.238.2. Responses	485
2.2.238.3. Consumes	486
2.2.238.4. Produces	486
2.2.238.5. Tags	486
2.2.239. replace the specified OAuthAuthorizeToken	486
2.2.239.1. Parameters	486
2.2.239.2. Responses	486
2.2.239.3. Consumes	487
2.2.239.4. Produces	487
2.2.239.5. Tags	487
2.2.240. delete an OAuthAuthorizeToken	487
2.2.240.1. Parameters	487
2.2.240.2. Responses	490
2.2.240.3. Consumes	490
2.2.240.4. Produces	490
2.2.240.5. Tags	490
2.2.241. list or watch objects of kind OAuthClientAuthorization	490
2.2.241.1. Parameters	490
2.2.241.2. Responses	492
2.2.241.3. Consumes	493
2.2.241.4. Produces	493
2.2.241.5. Tags	493
2.2.242. create an OAuthClientAuthorization	493
2.2.242.1. Parameters	493
2.2.242.2. Responses	493
2.2.242.3. Consumes	494
2.2.242.4. Produces	494
2.2.242.5. Tags	494
2.2.243. delete collection of OAuthClientAuthorization	494
2.2.243.1. Parameters	494
2.2.243.2. Responses	496
2.2.243.3. Consumes	497
2.2.243.4. Produces	497
2.2.243.5. Tags	497
2.2.244. read the specified OAuthClientAuthorization	497
2.2.244.1. Parameters	497
2.2.244.2. Responses	498
2.2.244.3. Consumes	498
2.2.244.4. Produces	498
2.2.244.5. Tags	498
2.2.245. partially update the specified OAuthClientAuthorization	498
2.2.245.1. Parameters	498
2.2.245.2. Responses	498
2.2.245.3. Consumes	499

2.2.245.4. Produces	499
2.2.245.5. Tags	499
2.2.246. replace the specified OAuthClientAuthorization	499
2.2.246.1. Parameters	499
2.2.246.2. Responses	499
2.2.246.3. Consumes	500
2.2.246.4. Produces	500
2.2.246.5. Tags	500
2.2.247. delete an OAuthClientAuthorization	500
2.2.247.1. Parameters	500
2.2.247.2. Responses	503
2.2.247.3. Consumes	503
2.2.247.4. Produces	503
2.2.247.5. Tags	503
2.2.248. list or watch objects of kind OAuthClient	503
2.2.248.1. Parameters	503
2.2.248.2. Responses	505
2.2.248.3. Consumes	506
2.2.248.4. Produces	506
2.2.248.5. Tags	506
2.2.249. create an OAuthClient	506
2.2.249.1. Parameters	506
2.2.249.2. Responses	506
2.2.249.3. Consumes	506
2.2.249.4. Produces	506
2.2.249.5. Tags	507
2.2.250. delete collection of OAuthClient	507
2.2.250.1. Parameters	507
2.2.250.2. Responses	509
2.2.250.3. Consumes	510
2.2.250.4. Produces	510
2.2.250.5. Tags	510
2.2.251. read the specified OAuthClient	510
2.2.251.1. Parameters	510
2.2.251.2. Responses	510
2.2.251.3. Consumes	511
2.2.251.4. Produces	511
2.2.251.5. Tags	511
2.2.252. partially update the specified OAuthClient	511
2.2.252.1. Parameters	511
2.2.252.2. Responses	511
2.2.252.3. Consumes	512
2.2.252.4. Produces	512
2.2.252.5. Tags	512
2.2.253. replace the specified OAuthClient	512
2.2.253.1. Parameters	512
2.2.253.2. Responses	512
2.2.253.3. Consumes	512
2.2.253.4. Produces	513
2.2.253.5. Tags	513
2.2.254. delete an OAuthClient	513
2.2.254.1. Parameters	513
2.2.254.2. Responses	516

2.2.254.3. Consumes	516
2.2.254.4. Produces	516
2.2.254.5. Tags	516
2.2.255. create a PodSecurityPolicyReview	516
2.2.255.1. Parameters	516
2.2.255.2. Responses	516
2.2.255.3. Consumes	517
2.2.255.4. Produces	517
2.2.255.5. Tags	517
2.2.256. create a PodSecurityPolicySelfSubjectReview	517
2.2.256.1. Parameters	517
2.2.256.2. Responses	517
2.2.256.3. Consumes	517
2.2.256.4. Produces	517
2.2.256.5. Tags	518
2.2.257. create a PodSecurityPolicySubjectReview	518
2.2.257.1. Parameters	518
2.2.257.2. Responses	518
2.2.257.3. Consumes	518
2.2.257.4. Produces	518
2.2.257.5. Tags	518
2.2.258. list or watch objects of kind Policy	519
2.2.258.1. Parameters	519
2.2.258.2. Responses	520
2.2.258.3. Consumes	521
2.2.258.4. Produces	521
2.2.258.5. Tags	521
2.2.259. create a Policy	521
2.2.259.1. Parameters	521
2.2.259.2. Responses	521
2.2.259.3. Consumes	521
2.2.259.4. Produces	521
2.2.259.5. Tags	522
2.2.260. list or watch objects of kind PolicyBinding	522
2.2.260.1. Parameters	522
2.2.260.2. Responses	523
2.2.260.3. Consumes	524
2.2.260.4. Produces	524
2.2.260.5. Tags	524
2.2.261. create a PolicyBinding	524
2.2.261.1. Parameters	524
2.2.261.2. Responses	524
2.2.261.3. Consumes	525
2.2.261.4. Produces	525
2.2.261.5. Tags	525
2.2.262. create a Template	525
2.2.262.1. Parameters	525
2.2.262.2. Responses	525
2.2.262.3. Consumes	525
2.2.262.4. Produces	526
2.2.262.5. Tags	526
2.2.263. list objects of kind ProjectRequest	526
2.2.263.1. Parameters	526

2.2.263.2. Responses	528
2.2.263.3. Consumes	529
2.2.263.4. Produces	529
2.2.263.5. Tags	529
2.2.264. create a ProjectRequest	529
2.2.264.1. Parameters	529
2.2.264.2. Responses	529
2.2.264.3. Consumes	529
2.2.264.4. Produces	529
2.2.264.5. Tags	530
2.2.265. list or watch objects of kind Project	530
2.2.265.1. Parameters	530
2.2.265.2. Responses	532
2.2.265.3. Consumes	533
2.2.265.4. Produces	533
2.2.265.5. Tags	533
2.2.266. create a Project	533
2.2.266.1. Parameters	533
2.2.266.2. Responses	533
2.2.266.3. Consumes	533
2.2.266.4. Produces	533
2.2.266.5. Tags	534
2.2.267. read the specified Project	534
2.2.267.1. Parameters	534
2.2.267.2. Responses	534
2.2.267.3. Consumes	534
2.2.267.4. Produces	534
2.2.267.5. Tags	534
2.2.268. partially update the specified Project	534
2.2.268.1. Parameters	535
2.2.268.2. Responses	535
2.2.268.3. Consumes	535
2.2.268.4. Produces	535
2.2.268.5. Tags	535
2.2.269. replace the specified Project	535
2.2.269.1. Parameters	535
2.2.269.2. Responses	536
2.2.269.3. Consumes	536
2.2.269.4. Produces	536
2.2.269.5. Tags	536
2.2.270. delete a Project	536
2.2.270.1. Parameters	536
2.2.270.2. Responses	537
2.2.270.3. Consumes	537
2.2.270.4. Produces	537
2.2.270.5. Tags	537
2.2.271. create a ResourceAccessReview	537
2.2.271.1. Parameters	537
2.2.271.2. Responses	538
2.2.271.3. Consumes	538
2.2.271.4. Produces	538
2.2.271.5. Tags	538
2.2.272. list or watch objects of kind RoleBindingRestriction	538

2.2.272.1. Parameters	538
2.2.272.2. Responses	540
2.2.272.3. Consumes	541
2.2.272.4. Produces	541
2.2.272.5. Tags	541
2.2.273. create a RoleBindingRestriction	541
2.2.273.1. Parameters	541
2.2.273.2. Responses	541
2.2.273.3. Consumes	542
2.2.273.4. Produces	542
2.2.273.5. Tags	542
2.2.274. list objects of kind RoleBinding	542
2.2.274.1. Parameters	542
2.2.274.2. Responses	544
2.2.274.3. Consumes	545
2.2.274.4. Produces	545
2.2.274.5. Tags	545
2.2.275. create a RoleBinding	545
2.2.275.1. Parameters	545
2.2.275.2. Responses	545
2.2.275.3. Consumes	546
2.2.275.4. Produces	546
2.2.275.5. Tags	546
2.2.276. list objects of kind Role	546
2.2.276.1. Parameters	546
2.2.276.2. Responses	548
2.2.276.3. Consumes	549
2.2.276.4. Produces	549
2.2.276.5. Tags	549
2.2.277. create a Role	549
2.2.277.1. Parameters	549
2.2.277.2. Responses	549
2.2.277.3. Consumes	549
2.2.277.4. Produces	549
2.2.277.5. Tags	550
2.2.278. list or watch objects of kind Route	550
2.2.278.1. Parameters	550
2.2.278.2. Responses	551
2.2.278.3. Consumes	552
2.2.278.4. Produces	552
2.2.278.5. Tags	552
2.2.279. create a Route	552
2.2.279.1. Parameters	552
2.2.279.2. Responses	552
2.2.279.3. Consumes	553
2.2.279.4. Produces	553
2.2.279.5. Tags	553
2.2.280. create a SelfSubjectRulesReview	553
2.2.280.1. Parameters	553
2.2.280.2. Responses	553
2.2.280.3. Consumes	553
2.2.280.4. Produces	553
2.2.280.5. Tags	554

2.2.281. create a SubjectAccessReview	554
2.2.281.1. Parameters	554
2.2.281.2. Responses	554
2.2.281.3. Consumes	554
2.2.281.4. Produces	554
2.2.281.5. Tags	554
2.2.282. create a SubjectRulesReview	555
2.2.282.1. Parameters	555
2.2.282.2. Responses	555
2.2.282.3. Consumes	555
2.2.282.4. Produces	555
2.2.282.5. Tags	555
2.2.283. list or watch objects of kind Template	555
2.2.283.1. Parameters	555
2.2.283.2. Responses	557
2.2.283.3. Consumes	558
2.2.283.4. Produces	558
2.2.283.5. Tags	558
2.2.284. create a Template	558
2.2.284.1. Parameters	558
2.2.284.2. Responses	558
2.2.284.3. Consumes	558
2.2.284.4. Produces	558
2.2.284.5. Tags	559
2.2.285. create an UserIdentityMapping	559
2.2.285.1. Parameters	559
2.2.285.2. Responses	559
2.2.285.3. Consumes	559
2.2.285.4. Produces	559
2.2.285.5. Tags	559
2.2.286. read the specified UserIdentityMapping	560
2.2.286.1. Parameters	560
2.2.286.2. Responses	560
2.2.286.3. Consumes	560
2.2.286.4. Produces	560
2.2.286.5. Tags	560
2.2.287. partially update the specified UserIdentityMapping	560
2.2.287.1. Parameters	560
2.2.287.2. Responses	561
2.2.287.3. Consumes	561
2.2.287.4. Produces	561
2.2.287.5. Tags	561
2.2.288. replace the specified UserIdentityMapping	561
2.2.288.1. Parameters	561
2.2.288.2. Responses	562
2.2.288.3. Consumes	562
2.2.288.4. Produces	562
2.2.288.5. Tags	562
2.2.289. delete an UserIdentityMapping	562
2.2.289.1. Parameters	562
2.2.289.2. Responses	563
2.2.289.3. Consumes	563
2.2.289.4. Produces	563

2.2.289.5. Tags	563
2.2.290. list or watch objects of kind User	563
2.2.290.1. Parameters	563
2.2.290.2. Responses	565
2.2.290.3. Consumes	566
2.2.290.4. Produces	566
2.2.290.5. Tags	566
2.2.291. create an User	566
2.2.291.1. Parameters	566
2.2.291.2. Responses	566
2.2.291.3. Consumes	566
2.2.291.4. Produces	566
2.2.291.5. Tags	567
2.2.292. delete collection of User	567
2.2.292.1. Parameters	567
2.2.292.2. Responses	568
2.2.292.3. Consumes	569
2.2.292.4. Produces	569
2.2.292.5. Tags	569
2.2.293. read the specified User	569
2.2.293.1. Parameters	569
2.2.293.2. Responses	569
2.2.293.3. Consumes	570
2.2.293.4. Produces	570
2.2.293.5. Tags	570
2.2.294. partially update the specified User	570
2.2.294.1. Parameters	570
2.2.294.2. Responses	570
2.2.294.3. Consumes	570
2.2.294.4. Produces	571
2.2.294.5. Tags	571
2.2.295. replace the specified User	571
2.2.295.1. Parameters	571
2.2.295.2. Responses	571
2.2.295.3. Consumes	571
2.2.295.4. Produces	571
2.2.295.5. Tags	572
2.2.296. delete an User	572
2.2.296.1. Parameters	572
2.2.296.2. Responses	575
2.2.296.3. Consumes	575
2.2.296.4. Produces	575
2.2.296.5. Tags	575
2.2.297. watch individual changes to a list of BuildConfig	575
2.2.297.1. Parameters	575
2.2.297.2. Responses	577
2.2.297.3. Consumes	578
2.2.297.4. Produces	578
2.2.297.5. Tags	578
2.2.298. watch individual changes to a list of Build	578
2.2.298.1. Parameters	578
2.2.298.2. Responses	580
2.2.298.3. Consumes	581

2.2.298.4. Produces	581
2.2.298.5. Tags	581
2.2.299. watch individual changes to a list of ClusterNetwork	581
2.2.299.1. Parameters	581
2.2.299.2. Responses	583
2.2.299.3. Consumes	584
2.2.299.4. Produces	584
2.2.299.5. Tags	584
2.2.300. watch changes to an object of kind ClusterNetwork	584
2.2.300.1. Parameters	584
2.2.300.2. Responses	586
2.2.300.3. Consumes	587
2.2.300.4. Produces	587
2.2.300.5. Tags	587
2.2.301. watch individual changes to a list of ClusterPolicy	587
2.2.301.1. Parameters	587
2.2.301.2. Responses	589
2.2.301.3. Consumes	590
2.2.301.4. Produces	590
2.2.301.5. Tags	590
2.2.302. watch changes to an object of kind ClusterPolicy	590
2.2.302.1. Parameters	590
2.2.302.2. Responses	592
2.2.302.3. Consumes	593
2.2.302.4. Produces	593
2.2.302.5. Tags	593
2.2.303. watch individual changes to a list of ClusterPolicyBinding	593
2.2.303.1. Parameters	593
2.2.303.2. Responses	595
2.2.303.3. Consumes	596
2.2.303.4. Produces	596
2.2.303.5. Tags	596
2.2.304. watch changes to an object of kind ClusterPolicyBinding	596
2.2.304.1. Parameters	596
2.2.304.2. Responses	598
2.2.304.3. Consumes	599
2.2.304.4. Produces	599
2.2.304.5. Tags	599
2.2.305. watch individual changes to a list of ClusterResourceQuota	599
2.2.305.1. Parameters	599
2.2.305.2. Responses	601
2.2.305.3. Consumes	602
2.2.305.4. Produces	602
2.2.305.5. Tags	602
2.2.306. watch changes to an object of kind ClusterResourceQuota	602
2.2.306.1. Parameters	602
2.2.306.2. Responses	604
2.2.306.3. Consumes	605
2.2.306.4. Produces	605
2.2.306.5. Tags	605
2.2.307. watch individual changes to a list of DeploymentConfig	605
2.2.307.1. Parameters	605
2.2.307.2. Responses	607

2.2.307.3. Consumes	608
2.2.307.4. Produces	608
2.2.307.5. Tags	608
2.2.308. watch individual changes to a list of EgressNetworkPolicy	608
2.2.308.1. Parameters	608
2.2.308.2. Responses	610
2.2.308.3. Consumes	611
2.2.308.4. Produces	611
2.2.308.5. Tags	611
2.2.309. watch individual changes to a list of Group	611
2.2.309.1. Parameters	611
2.2.309.2. Responses	613
2.2.309.3. Consumes	614
2.2.309.4. Produces	614
2.2.309.5. Tags	614
2.2.310. watch changes to an object of kind Group	614
2.2.310.1. Parameters	614
2.2.310.2. Responses	616
2.2.310.3. Consumes	617
2.2.310.4. Produces	617
2.2.310.5. Tags	617
2.2.311. watch individual changes to a list of HostSubnet	617
2.2.311.1. Parameters	617
2.2.311.2. Responses	619
2.2.311.3. Consumes	620
2.2.311.4. Produces	620
2.2.311.5. Tags	620
2.2.312. watch changes to an object of kind HostSubnet	620
2.2.312.1. Parameters	620
2.2.312.2. Responses	622
2.2.312.3. Consumes	623
2.2.312.4. Produces	623
2.2.312.5. Tags	623
2.2.313. watch individual changes to a list of Identity	623
2.2.313.1. Parameters	623
2.2.313.2. Responses	625
2.2.313.3. Consumes	626
2.2.313.4. Produces	626
2.2.313.5. Tags	626
2.2.314. watch changes to an object of kind Identity	626
2.2.314.1. Parameters	626
2.2.314.2. Responses	628
2.2.314.3. Consumes	629
2.2.314.4. Produces	629
2.2.314.5. Tags	629
2.2.315. watch individual changes to a list of Image	629
2.2.315.1. Parameters	629
2.2.315.2. Responses	631
2.2.315.3. Consumes	632
2.2.315.4. Produces	632
2.2.315.5. Tags	632
2.2.316. watch changes to an object of kind Image	632
2.2.316.1. Parameters	632

2.2.316.2. Responses	634
2.2.316.3. Consumes	635
2.2.316.4. Produces	635
2.2.316.5. Tags	635
2.2.317. watch individual changes to a list of ImageStream	635
2.2.317.1. Parameters	635
2.2.317.2. Responses	637
2.2.317.3. Consumes	638
2.2.317.4. Produces	638
2.2.317.5. Tags	638
2.2.318. watch individual changes to a list of BuildConfig	638
2.2.318.1. Parameters	638
2.2.318.2. Responses	641
2.2.318.3. Consumes	641
2.2.318.4. Produces	641
2.2.318.5. Tags	641
2.2.319. watch changes to an object of kind BuildConfig	641
2.2.319.1. Parameters	641
2.2.319.2. Responses	644
2.2.319.3. Consumes	644
2.2.319.4. Produces	644
2.2.319.5. Tags	644
2.2.320. watch individual changes to a list of Build	644
2.2.320.1. Parameters	644
2.2.320.2. Responses	646
2.2.320.3. Consumes	647
2.2.320.4. Produces	647
2.2.320.5. Tags	647
2.2.321. watch changes to an object of kind Build	647
2.2.321.1. Parameters	647
2.2.321.2. Responses	650
2.2.321.3. Consumes	650
2.2.321.4. Produces	650
2.2.321.5. Tags	650
2.2.322. watch individual changes to a list of DeploymentConfig	650
2.2.322.1. Parameters	650
2.2.322.2. Responses	652
2.2.322.3. Consumes	653
2.2.322.4. Produces	653
2.2.322.5. Tags	653
2.2.323. watch changes to an object of kind DeploymentConfig	653
2.2.323.1. Parameters	653
2.2.323.2. Responses	656
2.2.323.3. Consumes	656
2.2.323.4. Produces	656
2.2.323.5. Tags	656
2.2.324. watch individual changes to a list of EgressNetworkPolicy	656
2.2.324.1. Parameters	656
2.2.324.2. Responses	658
2.2.324.3. Consumes	659
2.2.324.4. Produces	659
2.2.324.5. Tags	659
2.2.325. watch changes to an object of kind EgressNetworkPolicy	659

2.2.325.1. Parameters	659
2.2.325.2. Responses	662
2.2.325.3. Consumes	662
2.2.325.4. Produces	662
2.2.325.5. Tags	662
2.2.326. watch individual changes to a list of ImageStream	662
2.2.326.1. Parameters	662
2.2.326.2. Responses	664
2.2.326.3. Consumes	665
2.2.326.4. Produces	665
2.2.326.5. Tags	665
2.2.327. watch changes to an object of kind ImageStream	665
2.2.327.1. Parameters	665
2.2.327.2. Responses	668
2.2.327.3. Consumes	668
2.2.327.4. Produces	668
2.2.327.5. Tags	668
2.2.328. watch individual changes to a list of Policy	668
2.2.328.1. Parameters	668
2.2.328.2. Responses	670
2.2.328.3. Consumes	671
2.2.328.4. Produces	671
2.2.328.5. Tags	671
2.2.329. watch changes to an object of kind Policy	671
2.2.329.1. Parameters	671
2.2.329.2. Responses	674
2.2.329.3. Consumes	674
2.2.329.4. Produces	674
2.2.329.5. Tags	674
2.2.330. watch individual changes to a list of PolicyBinding	674
2.2.330.1. Parameters	674
2.2.330.2. Responses	676
2.2.330.3. Consumes	677
2.2.330.4. Produces	677
2.2.330.5. Tags	677
2.2.331. watch changes to an object of kind PolicyBinding	677
2.2.331.1. Parameters	677
2.2.331.2. Responses	680
2.2.331.3. Consumes	680
2.2.331.4. Produces	680
2.2.331.5. Tags	680
2.2.332. watch individual changes to a list of RoleBindingRestriction	680
2.2.332.1. Parameters	680
2.2.332.2. Responses	682
2.2.332.3. Consumes	683
2.2.332.4. Produces	683
2.2.332.5. Tags	683
2.2.333. watch changes to an object of kind RoleBindingRestriction	683
2.2.333.1. Parameters	683
2.2.333.2. Responses	686
2.2.333.3. Consumes	686
2.2.333.4. Produces	686
2.2.333.5. Tags	686

2.2.334. watch individual changes to a list of Route	686
2.2.334.1. Parameters	686
2.2.334.2. Responses	688
2.2.334.3. Consumes	689
2.2.334.4. Produces	689
2.2.334.5. Tags	689
2.2.335. watch changes to an object of kind Route	689
2.2.335.1. Parameters	689
2.2.335.2. Responses	692
2.2.335.3. Consumes	692
2.2.335.4. Produces	692
2.2.335.5. Tags	692
2.2.336. watch individual changes to a list of Template	692
2.2.336.1. Parameters	692
2.2.336.2. Responses	694
2.2.336.3. Consumes	695
2.2.336.4. Produces	695
2.2.336.5. Tags	695
2.2.337. watch changes to an object of kind Template	695
2.2.337.1. Parameters	695
2.2.337.2. Responses	698
2.2.337.3. Consumes	698
2.2.337.4. Produces	698
2.2.337.5. Tags	698
2.2.338. watch individual changes to a list of NetNamespace	698
2.2.338.1. Parameters	698
2.2.338.2. Responses	700
2.2.338.3. Consumes	701
2.2.338.4. Produces	701
2.2.338.5. Tags	701
2.2.339. watch changes to an object of kind NetNamespace	701
2.2.339.1. Parameters	701
2.2.339.2. Responses	703
2.2.339.3. Consumes	704
2.2.339.4. Produces	704
2.2.339.5. Tags	704
2.2.340. watch individual changes to a list of OAuthAccessToken	704
2.2.340.1. Parameters	704
2.2.340.2. Responses	706
2.2.340.3. Consumes	707
2.2.340.4. Produces	707
2.2.340.5. Tags	707
2.2.341. watch changes to an object of kind OAuthAccessToken	707
2.2.341.1. Parameters	707
2.2.341.2. Responses	709
2.2.341.3. Consumes	710
2.2.341.4. Produces	710
2.2.341.5. Tags	710
2.2.342. watch individual changes to a list of OAuthAuthorizeToken	710
2.2.342.1. Parameters	710
2.2.342.2. Responses	712
2.2.342.3. Consumes	713
2.2.342.4. Produces	713

2.2.342.5. Tags	713
2.2.343. watch changes to an object of kind OAuthAuthorizeToken	713
2.2.343.1. Parameters	713
2.2.343.2. Responses	715
2.2.343.3. Consumes	716
2.2.343.4. Produces	716
2.2.343.5. Tags	716
2.2.344. watch individual changes to a list of OAuthClientAuthorization	716
2.2.344.1. Parameters	716
2.2.344.2. Responses	718
2.2.344.3. Consumes	719
2.2.344.4. Produces	719
2.2.344.5. Tags	719
2.2.345. watch changes to an object of kind OAuthClientAuthorization	719
2.2.345.1. Parameters	719
2.2.345.2. Responses	721
2.2.345.3. Consumes	722
2.2.345.4. Produces	722
2.2.345.5. Tags	722
2.2.346. watch individual changes to a list of OAuthClient	722
2.2.346.1. Parameters	722
2.2.346.2. Responses	724
2.2.346.3. Consumes	725
2.2.346.4. Produces	725
2.2.346.5. Tags	725
2.2.347. watch changes to an object of kind OAuthClient	725
2.2.347.1. Parameters	725
2.2.347.2. Responses	727
2.2.347.3. Consumes	728
2.2.347.4. Produces	728
2.2.347.5. Tags	728
2.2.348. watch individual changes to a list of Policy	728
2.2.348.1. Parameters	728
2.2.348.2. Responses	730
2.2.348.3. Consumes	731
2.2.348.4. Produces	731
2.2.348.5. Tags	731
2.2.349. watch individual changes to a list of PolicyBinding	731
2.2.349.1. Parameters	731
2.2.349.2. Responses	733
2.2.349.3. Consumes	734
2.2.349.4. Produces	734
2.2.349.5. Tags	734
2.2.350. watch individual changes to a list of Project	734
2.2.350.1. Parameters	734
2.2.350.2. Responses	736
2.2.350.3. Consumes	737
2.2.350.4. Produces	737
2.2.350.5. Tags	737
2.2.351. watch changes to an object of kind Project	737
2.2.351.1. Parameters	737
2.2.351.2. Responses	739
2.2.351.3. Consumes	740

2.2.351.4. Produces	740
2.2.351.5. Tags	740
2.2.352. watch individual changes to a list of RoleBindingRestriction	740
2.2.352.1. Parameters	740
2.2.352.2. Responses	742
2.2.352.3. Consumes	743
2.2.352.4. Produces	743
2.2.352.5. Tags	743
2.2.353. watch individual changes to a list of Route	743
2.2.353.1. Parameters	743
2.2.353.2. Responses	745
2.2.353.3. Consumes	746
2.2.353.4. Produces	746
2.2.353.5. Tags	746
2.2.354. watch individual changes to a list of Template	746
2.2.354.1. Parameters	746
2.2.354.2. Responses	748
2.2.354.3. Consumes	749
2.2.354.4. Produces	749
2.2.354.5. Tags	749
2.2.355. watch individual changes to a list of User	749
2.2.355.1. Parameters	749
2.2.355.2. Responses	751
2.2.355.3. Consumes	752
2.2.355.4. Produces	752
2.2.355.5. Tags	752
2.2.356. watch changes to an object of kind User	752
2.2.356.1. Parameters	752
2.2.356.2. Responses	754
2.2.356.3. Consumes	755
2.2.356.4. Produces	755
2.2.356.5. Tags	755
2.3. DEFINITIONS	755
2.3.1. patch.Object	755
2.3.2. runtime.RawExtension	755
2.3.3. types.UID	755
2.3.4. v1.APIResource	755
2.3.5. v1.APIResourceList	756
2.3.6. v1.AWSElasticBlockStoreVolumeSource	758
2.3.7. v1.Affinity	760
2.3.8. v1.AppliedClusterResourceQuota	760
2.3.9. v1.AppliedClusterResourceQuotaList	762
2.3.10. v1.AzureDataDiskCachingMode	763
2.3.11. v1.AzureDiskVolumeSource	763
2.3.12. v1.AzureFileVolumeSource	764
2.3.13. v1.BinaryBuildSource	765
2.3.14. v1.BitbucketWebHookCause	765
2.3.15. v1.Build	766
2.3.16. v1.BuildConfig	767
2.3.17. v1.BuildConfigList	769
2.3.18. v1.BuildConfigSpec	770
2.3.19. v1.BuildConfigStatus	773
2.3.20. v1.BuildList	774

2.3.21. v1.BuildLog	775
2.3.22. v1.BuildOutput	776
2.3.23. v1.BuildPostCommitSpec	778
2.3.24. v1.BuildRequest	781
2.3.25. v1.BuildSource	784
2.3.26. v1.BuildSpec	788
2.3.27. v1.BuildStatus	790
2.3.28. v1.BuildStatusOutput	792
2.3.29. v1.BuildStatusOutputTo	793
2.3.30. v1.BuildStrategy	793
2.3.31. v1.BuildTriggerCause	794
2.3.32. v1.BuildTriggerPolicy	795
2.3.33. v1.Capabilities	796
2.3.34. v1.Capability	796
2.3.35. v1.CephFSVolumeSource	797
2.3.36. v1.CinderVolumeSource	798
2.3.37. v1.ClusterNetwork	799
2.3.38. v1.ClusterNetworkList	801
2.3.39. v1.ClusterPolicy	803
2.3.40. v1.ClusterPolicyBinding	804
2.3.41. v1.ClusterPolicyBindingList	806
2.3.42. v1.ClusterPolicyList	807
2.3.43. v1.ClusterResourceQuota	809
2.3.44. v1.ClusterResourceQuotaList	810
2.3.45. v1.ClusterResourceQuotaSelector	811
2.3.46. v1.ClusterResourceQuotaSpec	811
2.3.47. v1.ClusterResourceQuotaStatus	812
2.3.48. v1.ClusterRole	813
2.3.49. v1.ClusterRoleBinding	814
2.3.50. v1.ClusterRoleBindingList	818
2.3.51. v1.ClusterRoleList	819
2.3.52. v1.ClusterRoleScopeRestriction	820
2.3.53. v1.ConfigMapEnvSource	821
2.3.54. v1.ConfigMapKeySelector	821
2.3.55. v1.ConfigMapProjection	822
2.3.56. v1.ConfigMapVolumeSource	823
2.3.57. v1.Container	825
2.3.58. v1.ContainerPort	834
2.3.59. v1.CustomBuildStrategy	835
2.3.60. v1.CustomDeploymentStrategyParams	837
2.3.61. v1.DeleteOptions	837
2.3.62. v1.DeletionPropagation	840
2.3.63. v1.DeploymentCause	840
2.3.64. v1.DeploymentCauseImageTrigger	840
2.3.65. v1.DeploymentCondition	841
2.3.66. v1.DeploymentConfig	842
2.3.67. v1.DeploymentConfigList	843
2.3.68. v1.DeploymentConfigRollback	845
2.3.69. v1.DeploymentConfigRollbackSpec	846
2.3.70. v1.DeploymentConfigSpec	847
2.3.71. v1.DeploymentConfigStatus	850
2.3.72. v1.DeploymentDetails	851
2.3.73. v1.DeploymentLog	852

2.3.74. v1.DeploymentRequest	853
2.3.75. v1.DeploymentStrategy	855
2.3.76. v1.DeploymentTriggerImageChangeParams	856
2.3.77. v1.DeploymentTriggerPolicy	858
2.3.78. v1.DeploymentTriggerType	858
2.3.79. v1.DeprecatedDownwardAPIVolumeFile	858
2.3.80. v1.DeprecatedDownwardAPIVolumeSource	860
2.3.81. v1.DockerBuildStrategy	861
2.3.82. v1.DockerStrategyOptions	864
2.3.83. v1.DownwardAPIProjection	865
2.3.84. v1.DownwardAPIVolumeFile	865
2.3.85. v1.DownwardAPIVolumeSource	866
2.3.86. v1.EgressNetworkPolicy	867
2.3.87. v1.EgressNetworkPolicyList	869
2.3.88. v1.EgressNetworkPolicyPeer	870
2.3.89. v1.EgressNetworkPolicyRule	871
2.3.90. v1.EgressNetworkPolicySpec	871
2.3.91. v1.EmptyDirVolumeSource	871
2.3.92. v1.EnvFromSource	872
2.3.93. v1.EnvVar	872
2.3.94. v1.EnvVarSource	873
2.3.95. v1.ExecAction	874
2.3.96. v1.ExecNewPodHook	875
2.3.97. v1.FCVolumeSource	876
2.3.98. v1.FinalizerName	877
2.3.99. v1.FlexVolumeSource	877
2.3.100. v1.FlockerVolumeSource	878
2.3.101. v1.GCEPersistentDiskVolumeSource	879
2.3.102. v1.GenericWebHookCause	881
2.3.103. v1.GitBuildSource	881
2.3.104. v1.GitHubWebHookCause	882
2.3.105. v1.GitLabWebHookCause	883
2.3.106. v1.GitRepoVolumeSource	883
2.3.107. v1.GitSourceRevision	884
2.3.108. v1.GlusterfsVolumeSource	884
2.3.109. v1.Group	885
2.3.110. v1.GroupList	887
2.3.111. v1.GroupRestriction	888
2.3.112. v1.HTTPGetAction	888
2.3.113. v1.HTTPHeader	889
2.3.114. v1.Handler	889
2.3.115. v1.HostPathVolumeSource	890
2.3.116. v1.HostSubnet	890
2.3.117. v1.HostSubnetList	892
2.3.118. v1.ISCSIVolumeSource	893
2.3.119. v1.Identity	895
2.3.120. v1.IdentityList	897
2.3.121. v1.Image	898
2.3.122. v1.ImageChangeCause	901
2.3.123. v1.ImageChangeTrigger	901
2.3.124. v1.ImageImportSpec	902
2.3.125. v1.ImageImportStatus	903
2.3.126. v1.ImageLabel	904

2.3.127. v1.ImageLayer	904
2.3.128. v1.ImageList	905
2.3.129. v1.ImageLookupPolicy	906
2.3.130. v1.ImageOptimizationPolicy	906
2.3.131. v1.ImageSignature	906
2.3.132. v1.ImageSource	909
2.3.133. v1.ImageSourcePath	910
2.3.134. v1.ImageStream	910
2.3.135. v1.ImageStreamImage	912
2.3.136. v1.ImageStreamImport	913
2.3.137. v1.ImageStreamImportSpec	915
2.3.138. v1.ImageStreamImportStatus	915
2.3.139. v1.ImageStreamList	916
2.3.140. v1.ImageStreamMapping	917
2.3.141. v1.ImageStreamSpec	919
2.3.142. v1.ImageStreamStatus	919
2.3.143. v1.ImageStreamTag	920
2.3.144. v1.ImageStreamTagList	922
2.3.145. v1.JenkinsPipelineBuildStrategy	924
2.3.146. v1.KeyToPath	924
2.3.147. v1.LabelSelector	925
2.3.148. v1.LabelSelectorRequirement	926
2.3.149. v1.Lifecycle	927
2.3.150. v1.LifecycleHook	928
2.3.151. v1.ListMeta	929
2.3.152. v1.LocalObjectReference	930
2.3.153. v1.LocalResourceAccessReview	930
2.3.154. v1.LocalSubjectAccessReview	933
2.3.155. v1.NFSVolumeSource	936
2.3.156. v1.NamedClusterRole	937
2.3.157. v1.NamedClusterRoleBinding	937
2.3.158. v1.NamedRole	937
2.3.159. v1.NamedRoleBinding	938
2.3.160. v1.NamedTagEventList	938
2.3.161. v1.NetNamespace	938
2.3.162. v1.NetNamespaceList	940
2.3.163. v1.NodeAffinity	941
2.3.164. v1.NodeSelector	943
2.3.165. v1.NodeSelectorRequirement	944
2.3.166. v1.NodeSelectorTerm	945
2.3.167. v1.OAuthAccessToken	945
2.3.168. v1.OAuthAccessTokenList	947
2.3.169. v1.OAuthAuthorizeToken	949
2.3.170. v1.OAuthAuthorizeTokenList	951
2.3.171. v1.OAuthClient	952
2.3.172. v1.OAuthClientAuthorization	955
2.3.173. v1.OAuthClientAuthorizationList	957
2.3.174. v1.OAuthClientList	959
2.3.175. v1.ObjectFieldSelector	960
2.3.176. v1.ObjectMeta	960
2.3.177. v1.ObjectReference	970
2.3.178. v1.OwnerReference	972
2.3.179. v1.Parameter	974

2.3.180. v1.Patch	977
2.3.181. v1.PersistentVolumeClaimVolumeSource	977
2.3.182. v1.PhotonPersistentDiskVolumeSource	977
2.3.183. v1.PodAffinity	978
2.3.184. v1.PodAffinityTerm	980
2.3.185. v1.PodAntiAffinity	982
2.3.186. v1.PodSecurityContext	985
2.3.187. v1.PodSecurityPolicyReview	988
2.3.188. v1.PodSecurityPolicyReviewSpec	990
2.3.189. v1.PodSecurityPolicyReviewStatus	991
2.3.190. v1.PodSecurityPolicySelfSubjectReview	991
2.3.191. v1.PodSecurityPolicySelfSubjectReviewSpec	993
2.3.192. v1.PodSecurityPolicySubjectReview	993
2.3.193. v1.PodSecurityPolicySubjectReviewSpec	994
2.3.194. v1.PodSecurityPolicySubjectReviewStatus	995
2.3.195. v1.PodSpec	996
2.3.196. v1.PodTemplateSpec	1005
2.3.197. v1.Policy	1006
2.3.198. v1.PolicyBinding	1007
2.3.199. v1.PolicyBindingList	1009
2.3.200. v1.PolicyList	1011
2.3.201. v1.PolicyRule	1012
2.3.202. v1.PortworxVolumeSource	1014
2.3.203. v1.Preconditions	1015
2.3.204. v1.PreferredSchedulingTerm	1015
2.3.205. v1.Probe	1015
2.3.206. v1.Project	1017
2.3.207. v1.ProjectList	1019
2.3.208. v1.ProjectRequest	1020
2.3.209. v1.ProjectSpec	1022
2.3.210. v1.ProjectStatus	1022
2.3.211. v1.ProjectedVolumeSource	1022
2.3.212. v1.QuobyteVolumeSource	1023
2.3.213. v1.RBDVolumeSource	1024
2.3.214. v1.RecreateDeploymentStrategyParams	1026
2.3.215. v1.RepositoryImportSpec	1027
2.3.216. v1.RepositoryImportStatus	1028
2.3.217. v1.ResourceAccessReview	1029
2.3.218. v1.ResourceFieldSelector	1031
2.3.219. v1.ResourceQuotaScope	1032
2.3.220. v1.ResourceQuotaSpec	1032
2.3.221. v1.ResourceQuotaStatus	1033
2.3.222. v1.ResourceQuotaStatusByNamespace	1033
2.3.223. v1.ResourceRequirements	1033
2.3.224. v1.Role	1034
2.3.225. v1.RoleBinding	1036
2.3.226. v1.RoleBindingList	1038
2.3.227. v1.RoleBindingRestriction	1040
2.3.228. v1.RoleBindingRestrictionList	1041
2.3.229. v1.RoleBindingRestrictionSpec	1043
2.3.230. v1.RoleList	1043
2.3.231. v1.RollingDeploymentStrategyParams	1044
2.3.232. v1.Route	1048

2.3.233. v1.RouteIngress	1050
2.3.234. v1.RouteIngressCondition	1051
2.3.235. v1.RouteList	1051
2.3.236. v1.RoutePort	1053
2.3.237. v1.RouteSpec	1053
2.3.238. v1.RouteStatus	1055
2.3.239. v1.RouteTargetReference	1055
2.3.240. v1.SELinuxOptions	1056
2.3.241. v1.ScaleIOVolumeSource	1057
2.3.242. v1.ScopeRestriction	1058
2.3.243. v1.Secret	1059
2.3.244. v1.SecretBuildSource	1061
2.3.245. v1.SecretEnvSource	1062
2.3.246. v1.SecretKeySelector	1063
2.3.247. v1.SecretList	1063
2.3.248. v1.SecretProjection	1065
2.3.249. v1.SecretSpec	1066
2.3.250. v1.SecretVolumeSource	1067
2.3.251. v1.SecurityContext	1069
2.3.252. v1.SelfSubjectRulesReview	1072
2.3.253. v1.SelfSubjectRulesReviewSpec	1073
2.3.254. v1.ServiceAccountPodSecurityPolicyReviewStatus	1074
2.3.255. v1.ServiceAccountReference	1075
2.3.256. v1.ServiceAccountRestriction	1075
2.3.257. v1.SignatureCondition	1076
2.3.258. v1.SignatureIssuer	1077
2.3.259. v1.SignatureSubject	1077
2.3.260. v1.SourceBuildStrategy	1077
2.3.261. v1.SourceControlUser	1080
2.3.262. v1.SourceRevision	1080
2.3.263. v1.StageInfo	1081
2.3.264. v1.Status	1082
2.3.265. v1.StatusCause	1085
2.3.266. v1.StatusDetails	1086
2.3.267. v1.StepInfo	1088
2.3.268. v1.SubjectAccessReview	1088
2.3.269. v1.SubjectRulesReview	1091
2.3.270. v1.SubjectRulesReviewSpec	1093
2.3.271. v1.SubjectRulesReviewStatus	1093
2.3.272. v1.TCPSocketAction	1094
2.3.273. v1.TLSConfig	1094
2.3.274. v1.TagEvent	1096
2.3.275. v1.TagEventCondition	1097
2.3.276. v1.TagImageHook	1098
2.3.277. v1.TagImportPolicy	1098
2.3.278. v1.TagReference	1099
2.3.279. v1.TagReferencePolicy	1100
2.3.280. v1.Template	1102
2.3.281. v1.TemplateList	1104
2.3.282. v1.Toleration	1106
2.3.283. v1.User	1107
2.3.284. v1.UserIdentityMapping	1109
2.3.285. v1.UserList	1110

2.3.286. v1.UserRestriction	1111
2.3.287. v1.Volume	1112
2.3.288. v1.VolumeMount	1119
2.3.289. v1.VolumeProjection	1119
2.3.290. v1.VsphereVirtualDiskVolumeSource	1120
2.3.291. v1.WatchEvent	1120
2.3.292. v1.WebHookTrigger	1121
2.3.293. v1.WeightedPodAffinityTerm	1121
2.3.294. v1beta1.Scale	1121
2.3.295. v1beta1.ScaleSpec	1123
2.3.296. v1beta1.ScaleStatus	1123
CHAPTER 3. KUBERNETES V1 REST API	1125
3.1. OVERVIEW	1125
3.1.1. Version information	1125
3.1.2. URI scheme	1125
3.2. PATHS	1125
3.2.1. get available resources	1125
3.2.1.1. Responses	1125
3.2.1.2. Consumes	1125
3.2.1.3. Produces	1125
3.2.1.4. Tags	1125
3.2.2. create a Binding	1126
3.2.2.1. Parameters	1126
3.2.2.2. Responses	1126
3.2.2.3. Consumes	1126
3.2.2.4. Produces	1126
3.2.2.5. Tags	1126
3.2.3. list objects of kind ComponentStatus	1126
3.2.3.1. Parameters	1126
3.2.3.2. Responses	1128
3.2.3.3. Consumes	1129
3.2.3.4. Produces	1129
3.2.3.5. Tags	1129
3.2.4. read the specified ComponentStatus	1129
3.2.4.1. Parameters	1129
3.2.4.2. Responses	1129
3.2.4.3. Consumes	1129
3.2.4.4. Produces	1129
3.2.4.5. Tags	1130
3.2.5. list or watch objects of kind ConfigMap	1130
3.2.5.1. Parameters	1130
3.2.5.2. Responses	1132
3.2.5.3. Consumes	1133
3.2.5.4. Produces	1133
3.2.5.5. Tags	1133
3.2.6. create a ConfigMap	1133
3.2.6.1. Parameters	1133
3.2.6.2. Responses	1133
3.2.6.3. Consumes	1133
3.2.6.4. Produces	1133
3.2.6.5. Tags	1134
3.2.7. list or watch objects of kind Endpoints	1134

3.2.7.1. Parameters	1134
3.2.7.2. Responses	1136
3.2.7.3. Consumes	1137
3.2.7.4. Produces	1137
3.2.7.5. Tags	1137
3.2.8. create Endpoints	1137
3.2.8.1. Parameters	1137
3.2.8.2. Responses	1137
3.2.8.3. Consumes	1137
3.2.8.4. Produces	1137
3.2.8.5. Tags	1138
3.2.9. list or watch objects of kind Event	1138
3.2.9.1. Parameters	1138
3.2.9.2. Responses	1140
3.2.9.3. Consumes	1141
3.2.9.4. Produces	1141
3.2.9.5. Tags	1141
3.2.10. create an Event	1141
3.2.10.1. Parameters	1141
3.2.10.2. Responses	1141
3.2.10.3. Consumes	1141
3.2.10.4. Produces	1141
3.2.10.5. Tags	1142
3.2.11. list or watch objects of kind LimitRange	1142
3.2.11.1. Parameters	1142
3.2.11.2. Responses	1143
3.2.11.3. Consumes	1144
3.2.11.4. Produces	1144
3.2.11.5. Tags	1144
3.2.12. create a LimitRange	1144
3.2.12.1. Parameters	1144
3.2.12.2. Responses	1144
3.2.12.3. Consumes	1145
3.2.12.4. Produces	1145
3.2.12.5. Tags	1145
3.2.13. list or watch objects of kind Namespace	1145
3.2.13.1. Parameters	1145
3.2.13.2. Responses	1147
3.2.13.3. Consumes	1148
3.2.13.4. Produces	1148
3.2.13.5. Tags	1148
3.2.14. create a Namespace	1148
3.2.14.1. Parameters	1148
3.2.14.2. Responses	1148
3.2.14.3. Consumes	1148
3.2.14.4. Produces	1148
3.2.14.5. Tags	1149
3.2.15. delete collection of Namespace	1149
3.2.15.1. Parameters	1149
3.2.15.2. Responses	1151
3.2.15.3. Consumes	1152
3.2.15.4. Produces	1152
3.2.15.5. Tags	1152

3.2.16. create a Binding	1152
3.2.16.1. Parameters	1152
3.2.16.2. Responses	1152
3.2.16.3. Consumes	1152
3.2.16.4. Produces	1153
3.2.16.5. Tags	1153
3.2.17. list or watch objects of kind ConfigMap	1153
3.2.17.1. Parameters	1153
3.2.17.2. Responses	1155
3.2.17.3. Consumes	1156
3.2.17.4. Produces	1156
3.2.17.5. Tags	1156
3.2.18. create a ConfigMap	1156
3.2.18.1. Parameters	1156
3.2.18.2. Responses	1156
3.2.18.3. Consumes	1157
3.2.18.4. Produces	1157
3.2.18.5. Tags	1157
3.2.19. delete collection of ConfigMap	1157
3.2.19.1. Parameters	1157
3.2.19.2. Responses	1159
3.2.19.3. Consumes	1160
3.2.19.4. Produces	1160
3.2.19.5. Tags	1160
3.2.20. read the specified ConfigMap	1160
3.2.20.1. Parameters	1160
3.2.20.2. Responses	1161
3.2.20.3. Consumes	1161
3.2.20.4. Produces	1161
3.2.20.5. Tags	1161
3.2.21. partially update the specified ConfigMap	1161
3.2.21.1. Parameters	1161
3.2.21.2. Responses	1162
3.2.21.3. Consumes	1162
3.2.21.4. Produces	1162
3.2.21.5. Tags	1162
3.2.22. replace the specified ConfigMap	1162
3.2.22.1. Parameters	1162
3.2.22.2. Responses	1163
3.2.22.3. Consumes	1163
3.2.22.4. Produces	1163
3.2.22.5. Tags	1163
3.2.23. delete a ConfigMap	1163
3.2.23.1. Parameters	1163
3.2.23.2. Responses	1166
3.2.23.3. Consumes	1166
3.2.23.4. Produces	1166
3.2.23.5. Tags	1166
3.2.24. list or watch objects of kind Endpoints	1166
3.2.24.1. Parameters	1166
3.2.24.2. Responses	1168
3.2.24.3. Consumes	1169
3.2.24.4. Produces	1169

3.2.24.5. Tags	1169
3.2.25. create Endpoints	1169
3.2.25.1. Parameters	1169
3.2.25.2. Responses	1169
3.2.25.3. Consumes	1170
3.2.25.4. Produces	1170
3.2.25.5. Tags	1170
3.2.26. delete collection of Endpoints	1170
3.2.26.1. Parameters	1170
3.2.26.2. Responses	1172
3.2.26.3. Consumes	1173
3.2.26.4. Produces	1173
3.2.26.5. Tags	1173
3.2.27. read the specified Endpoints	1173
3.2.27.1. Parameters	1173
3.2.27.2. Responses	1174
3.2.27.3. Consumes	1174
3.2.27.4. Produces	1174
3.2.27.5. Tags	1174
3.2.28. partially update the specified Endpoints	1174
3.2.28.1. Parameters	1174
3.2.28.2. Responses	1175
3.2.28.3. Consumes	1175
3.2.28.4. Produces	1175
3.2.28.5. Tags	1175
3.2.29. replace the specified Endpoints	1175
3.2.29.1. Parameters	1175
3.2.29.2. Responses	1176
3.2.29.3. Consumes	1176
3.2.29.4. Produces	1176
3.2.29.5. Tags	1176
3.2.30. delete Endpoints	1176
3.2.30.1. Parameters	1176
3.2.30.2. Responses	1179
3.2.30.3. Consumes	1179
3.2.30.4. Produces	1179
3.2.30.5. Tags	1179
3.2.31. list or watch objects of kind Event	1179
3.2.31.1. Parameters	1179
3.2.31.2. Responses	1181
3.2.31.3. Consumes	1182
3.2.31.4. Produces	1182
3.2.31.5. Tags	1182
3.2.32. create an Event	1182
3.2.32.1. Parameters	1182
3.2.32.2. Responses	1182
3.2.32.3. Consumes	1183
3.2.32.4. Produces	1183
3.2.32.5. Tags	1183
3.2.33. delete collection of Event	1183
3.2.33.1. Parameters	1183
3.2.33.2. Responses	1185
3.2.33.3. Consumes	1186

3.2.33.4. Produces	1186
3.2.33.5. Tags	1186
3.2.34. read the specified Event	1186
3.2.34.1. Parameters	1186
3.2.34.2. Responses	1187
3.2.34.3. Consumes	1187
3.2.34.4. Produces	1187
3.2.34.5. Tags	1187
3.2.35. partially update the specified Event	1187
3.2.35.1. Parameters	1187
3.2.35.2. Responses	1188
3.2.35.3. Consumes	1188
3.2.35.4. Produces	1188
3.2.35.5. Tags	1188
3.2.36. replace the specified Event	1188
3.2.36.1. Parameters	1188
3.2.36.2. Responses	1189
3.2.36.3. Consumes	1189
3.2.36.4. Produces	1189
3.2.36.5. Tags	1189
3.2.37. delete an Event	1189
3.2.37.1. Parameters	1189
3.2.37.2. Responses	1192
3.2.37.3. Consumes	1192
3.2.37.4. Produces	1192
3.2.37.5. Tags	1192
3.2.38. list or watch objects of kind LimitRange	1192
3.2.38.1. Parameters	1192
3.2.38.2. Responses	1194
3.2.38.3. Consumes	1195
3.2.38.4. Produces	1195
3.2.38.5. Tags	1195
3.2.39. create a LimitRange	1195
3.2.39.1. Parameters	1195
3.2.39.2. Responses	1195
3.2.39.3. Consumes	1196
3.2.39.4. Produces	1196
3.2.39.5. Tags	1196
3.2.40. delete collection of LimitRange	1196
3.2.40.1. Parameters	1196
3.2.40.2. Responses	1198
3.2.40.3. Consumes	1199
3.2.40.4. Produces	1199
3.2.40.5. Tags	1199
3.2.41. read the specified LimitRange	1199
3.2.41.1. Parameters	1199
3.2.41.2. Responses	1200
3.2.41.3. Consumes	1200
3.2.41.4. Produces	1200
3.2.41.5. Tags	1200
3.2.42. partially update the specified LimitRange	1200
3.2.42.1. Parameters	1200
3.2.42.2. Responses	1201

3.2.42.3. Consumes	1201
3.2.42.4. Produces	1201
3.2.42.5. Tags	1201
3.2.43. replace the specified LimitRange	1201
3.2.43.1. Parameters	1201
3.2.43.2. Responses	1202
3.2.43.3. Consumes	1202
3.2.43.4. Produces	1202
3.2.43.5. Tags	1202
3.2.44. delete a LimitRange	1202
3.2.44.1. Parameters	1202
3.2.44.2. Responses	1205
3.2.44.3. Consumes	1205
3.2.44.4. Produces	1205
3.2.44.5. Tags	1205
3.2.45. list or watch objects of kind PersistentVolumeClaim	1205
3.2.45.1. Parameters	1205
3.2.45.2. Responses	1207
3.2.45.3. Consumes	1208
3.2.45.4. Produces	1208
3.2.45.5. Tags	1208
3.2.46. create a PersistentVolumeClaim	1208
3.2.46.1. Parameters	1208
3.2.46.2. Responses	1209
3.2.46.3. Consumes	1209
3.2.46.4. Produces	1209
3.2.46.5. Tags	1209
3.2.47. delete collection of PersistentVolumeClaim	1209
3.2.47.1. Parameters	1209
3.2.47.2. Responses	1211
3.2.47.3. Consumes	1212
3.2.47.4. Produces	1212
3.2.47.5. Tags	1212
3.2.48. read the specified PersistentVolumeClaim	1212
3.2.48.1. Parameters	1212
3.2.48.2. Responses	1213
3.2.48.3. Consumes	1213
3.2.48.4. Produces	1213
3.2.48.5. Tags	1213
3.2.49. partially update the specified PersistentVolumeClaim	1213
3.2.49.1. Parameters	1213
3.2.49.2. Responses	1214
3.2.49.3. Consumes	1214
3.2.49.4. Produces	1214
3.2.49.5. Tags	1214
3.2.50. replace the specified PersistentVolumeClaim	1214
3.2.50.1. Parameters	1215
3.2.50.2. Responses	1215
3.2.50.3. Consumes	1215
3.2.50.4. Produces	1215
3.2.50.5. Tags	1215
3.2.51. delete a PersistentVolumeClaim	1215
3.2.51.1. Parameters	1216

3.2.51.2. Responses	1218
3.2.51.3. Consumes	1218
3.2.51.4. Produces	1218
3.2.51.5. Tags	1218
3.2.52. read status of the specified PersistentVolumeClaim	1218
3.2.52.1. Parameters	1218
3.2.52.2. Responses	1219
3.2.52.3. Consumes	1219
3.2.52.4. Produces	1219
3.2.52.5. Tags	1219
3.2.53. partially update status of the specified PersistentVolumeClaim	1219
3.2.53.1. Parameters	1219
3.2.53.2. Responses	1220
3.2.53.3. Consumes	1220
3.2.53.4. Produces	1220
3.2.53.5. Tags	1220
3.2.54. replace status of the specified PersistentVolumeClaim	1220
3.2.54.1. Parameters	1220
3.2.54.2. Responses	1221
3.2.54.3. Consumes	1221
3.2.54.4. Produces	1221
3.2.54.5. Tags	1221
3.2.55. list or watch objects of kind Pod	1221
3.2.55.1. Parameters	1222
3.2.55.2. Responses	1223
3.2.55.3. Consumes	1224
3.2.55.4. Produces	1224
3.2.55.5. Tags	1224
3.2.56. create a Pod	1224
3.2.56.1. Parameters	1224
3.2.56.2. Responses	1224
3.2.56.3. Consumes	1225
3.2.56.4. Produces	1225
3.2.56.5. Tags	1225
3.2.57. delete collection of Pod	1225
3.2.57.1. Parameters	1225
3.2.57.2. Responses	1227
3.2.57.3. Consumes	1228
3.2.57.4. Produces	1228
3.2.57.5. Tags	1228
3.2.58. read the specified Pod	1228
3.2.58.1. Parameters	1228
3.2.58.2. Responses	1229
3.2.58.3. Consumes	1229
3.2.58.4. Produces	1229
3.2.58.5. Tags	1229
3.2.59. partially update the specified Pod	1229
3.2.59.1. Parameters	1229
3.2.59.2. Responses	1230
3.2.59.3. Consumes	1230
3.2.59.4. Produces	1230
3.2.59.5. Tags	1230
3.2.60. replace the specified Pod	1230

3.2.60.1. Parameters	1230
3.2.60.2. Responses	1231
3.2.60.3. Consumes	1231
3.2.60.4. Produces	1231
3.2.60.5. Tags	1231
3.2.61. delete a Pod	1231
3.2.61.1. Parameters	1231
3.2.61.2. Responses	1234
3.2.61.3. Consumes	1234
3.2.61.4. Produces	1234
3.2.61.5. Tags	1234
3.2.62. connect GET requests to attach of Pod	1234
3.2.62.1. Parameters	1234
3.2.62.2. Responses	1236
3.2.62.3. Consumes	1236
3.2.62.4. Produces	1236
3.2.62.5. Tags	1236
3.2.63. connect POST requests to attach of Pod	1236
3.2.63.1. Parameters	1236
3.2.63.2. Responses	1238
3.2.63.3. Consumes	1238
3.2.63.4. Produces	1238
3.2.63.5. Tags	1238
3.2.64. create binding of a Binding	1238
3.2.64.1. Parameters	1238
3.2.64.2. Responses	1239
3.2.64.3. Consumes	1239
3.2.64.4. Produces	1239
3.2.64.5. Tags	1239
3.2.65. create eviction of an Eviction	1239
3.2.65.1. Parameters	1239
3.2.65.2. Responses	1240
3.2.65.3. Consumes	1240
3.2.65.4. Produces	1240
3.2.65.5. Tags	1240
3.2.66. connect GET requests to exec of Pod	1240
3.2.66.1. Parameters	1240
3.2.66.2. Responses	1242
3.2.66.3. Consumes	1242
3.2.66.4. Produces	1242
3.2.66.5. Tags	1242
3.2.67. connect POST requests to exec of Pod	1242
3.2.67.1. Parameters	1242
3.2.67.2. Responses	1244
3.2.67.3. Consumes	1244
3.2.67.4. Produces	1244
3.2.67.5. Tags	1244
3.2.68. read log of the specified Pod	1244
3.2.68.1. Parameters	1244
3.2.68.2. Responses	1247
3.2.68.3. Consumes	1247
3.2.68.4. Produces	1247
3.2.68.5. Tags	1248

3.2.69. connect GET requests to portforward of Pod	1248
3.2.69.1. Parameters	1248
3.2.69.2. Responses	1248
3.2.69.3. Consumes	1248
3.2.69.4. Produces	1248
3.2.69.5. Tags	1248
3.2.70. connect POST requests to portforward of Pod	1248
3.2.70.1. Parameters	1249
3.2.70.2. Responses	1249
3.2.70.3. Consumes	1249
3.2.70.4. Produces	1249
3.2.70.5. Tags	1249
3.2.71. connect GET requests to proxy of Pod	1249
3.2.71.1. Parameters	1249
3.2.71.2. Responses	1250
3.2.71.3. Consumes	1250
3.2.71.4. Produces	1250
3.2.71.5. Tags	1250
3.2.72. connect OPTIONS requests to proxy of Pod	1250
3.2.72.1. Parameters	1250
3.2.72.2. Responses	1251
3.2.72.3. Consumes	1251
3.2.72.4. Produces	1251
3.2.72.5. Tags	1251
3.2.73. connect POST requests to proxy of Pod	1251
3.2.73.1. Parameters	1251
3.2.73.2. Responses	1252
3.2.73.3. Consumes	1252
3.2.73.4. Produces	1252
3.2.73.5. Tags	1252
3.2.74. connect HEAD requests to proxy of Pod	1252
3.2.74.1. Parameters	1252
3.2.74.2. Responses	1253
3.2.74.3. Consumes	1253
3.2.74.4. Produces	1253
3.2.74.5. Tags	1253
3.2.75. connect PUT requests to proxy of Pod	1253
3.2.75.1. Parameters	1253
3.2.75.2. Responses	1254
3.2.75.3. Consumes	1254
3.2.75.4. Produces	1254
3.2.75.5. Tags	1254
3.2.76. connect DELETE requests to proxy of Pod	1254
3.2.76.1. Parameters	1254
3.2.76.2. Responses	1255
3.2.76.3. Consumes	1255
3.2.76.4. Produces	1255
3.2.76.5. Tags	1255
3.2.77. connect GET requests to proxy of Pod	1255
3.2.77.1. Parameters	1255
3.2.77.2. Responses	1256
3.2.77.3. Consumes	1256
3.2.77.4. Produces	1256

3.2.77.5. Tags	1256
3.2.78. connect OPTIONS requests to proxy of Pod	1256
3.2.78.1. Parameters	1256
3.2.78.2. Responses	1257
3.2.78.3. Consumes	1257
3.2.78.4. Produces	1257
3.2.78.5. Tags	1257
3.2.79. connect POST requests to proxy of Pod	1257
3.2.79.1. Parameters	1257
3.2.79.2. Responses	1258
3.2.79.3. Consumes	1258
3.2.79.4. Produces	1258
3.2.79.5. Tags	1258
3.2.80. connect HEAD requests to proxy of Pod	1258
3.2.80.1. Parameters	1258
3.2.80.2. Responses	1259
3.2.80.3. Consumes	1259
3.2.80.4. Produces	1259
3.2.80.5. Tags	1259
3.2.81. connect PUT requests to proxy of Pod	1259
3.2.81.1. Parameters	1259
3.2.81.2. Responses	1260
3.2.81.3. Consumes	1260
3.2.81.4. Produces	1260
3.2.81.5. Tags	1260
3.2.82. connect DELETE requests to proxy of Pod	1260
3.2.82.1. Parameters	1260
3.2.82.2. Responses	1261
3.2.82.3. Consumes	1261
3.2.82.4. Produces	1261
3.2.82.5. Tags	1261
3.2.83. read status of the specified Pod	1261
3.2.83.1. Parameters	1261
3.2.83.2. Responses	1262
3.2.83.3. Consumes	1262
3.2.83.4. Produces	1262
3.2.83.5. Tags	1262
3.2.84. partially update status of the specified Pod	1262
3.2.84.1. Parameters	1262
3.2.84.2. Responses	1263
3.2.84.3. Consumes	1263
3.2.84.4. Produces	1263
3.2.84.5. Tags	1263
3.2.85. replace status of the specified Pod	1263
3.2.85.1. Parameters	1264
3.2.85.2. Responses	1264
3.2.85.3. Consumes	1264
3.2.85.4. Produces	1264
3.2.85.5. Tags	1264
3.2.86. list or watch objects of kind PodTemplate	1264
3.2.86.1. Parameters	1264
3.2.86.2. Responses	1266
3.2.86.3. Consumes	1267

3.2.86.4. Produces	1267
3.2.86.5. Tags	1267
3.2.87. create a PodTemplate	1267
3.2.87.1. Parameters	1267
3.2.87.2. Responses	1267
3.2.87.3. Consumes	1268
3.2.87.4. Produces	1268
3.2.87.5. Tags	1268
3.2.88. delete collection of PodTemplate	1268
3.2.88.1. Parameters	1268
3.2.88.2. Responses	1270
3.2.88.3. Consumes	1271
3.2.88.4. Produces	1271
3.2.88.5. Tags	1271
3.2.89. read the specified PodTemplate	1271
3.2.89.1. Parameters	1271
3.2.89.2. Responses	1272
3.2.89.3. Consumes	1272
3.2.89.4. Produces	1272
3.2.89.5. Tags	1272
3.2.90. partially update the specified PodTemplate	1272
3.2.90.1. Parameters	1272
3.2.90.2. Responses	1273
3.2.90.3. Consumes	1273
3.2.90.4. Produces	1273
3.2.90.5. Tags	1273
3.2.91. replace the specified PodTemplate	1273
3.2.91.1. Parameters	1273
3.2.91.2. Responses	1274
3.2.91.3. Consumes	1274
3.2.91.4. Produces	1274
3.2.91.5. Tags	1274
3.2.92. delete a PodTemplate	1274
3.2.92.1. Parameters	1274
3.2.92.2. Responses	1277
3.2.92.3. Consumes	1277
3.2.92.4. Produces	1277
3.2.92.5. Tags	1277
3.2.93. list or watch objects of kind ReplicationController	1277
3.2.93.1. Parameters	1277
3.2.93.2. Responses	1279
3.2.93.3. Consumes	1280
3.2.93.4. Produces	1280
3.2.93.5. Tags	1280
3.2.94. create a ReplicationController	1280
3.2.94.1. Parameters	1280
3.2.94.2. Responses	1280
3.2.94.3. Consumes	1281
3.2.94.4. Produces	1281
3.2.94.5. Tags	1281
3.2.95. delete collection of ReplicationController	1281
3.2.95.1. Parameters	1281
3.2.95.2. Responses	1283

3.2.95.3. Consumes	1284
3.2.95.4. Produces	1284
3.2.95.5. Tags	1284
3.2.96. read the specified ReplicationController	1284
3.2.96.1. Parameters	1284
3.2.96.2. Responses	1285
3.2.96.3. Consumes	1285
3.2.96.4. Produces	1285
3.2.96.5. Tags	1285
3.2.97. partially update the specified ReplicationController	1285
3.2.97.1. Parameters	1285
3.2.97.2. Responses	1286
3.2.97.3. Consumes	1286
3.2.97.4. Produces	1286
3.2.97.5. Tags	1286
3.2.98. replace the specified ReplicationController	1286
3.2.98.1. Parameters	1287
3.2.98.2. Responses	1287
3.2.98.3. Consumes	1287
3.2.98.4. Produces	1287
3.2.98.5. Tags	1287
3.2.99. delete a ReplicationController	1287
3.2.99.1. Parameters	1288
3.2.99.2. Responses	1290
3.2.99.3. Consumes	1290
3.2.99.4. Produces	1290
3.2.99.5. Tags	1290
3.2.100. read scale of the specified Scale	1290
3.2.100.1. Parameters	1290
3.2.100.2. Responses	1291
3.2.100.3. Consumes	1291
3.2.100.4. Produces	1291
3.2.100.5. Tags	1291
3.2.101. partially update scale of the specified Scale	1291
3.2.101.1. Parameters	1291
3.2.101.2. Responses	1292
3.2.101.3. Consumes	1292
3.2.101.4. Produces	1292
3.2.101.5. Tags	1292
3.2.102. replace scale of the specified Scale	1292
3.2.102.1. Parameters	1292
3.2.102.2. Responses	1293
3.2.102.3. Consumes	1293
3.2.102.4. Produces	1293
3.2.102.5. Tags	1293
3.2.103. read status of the specified ReplicationController	1293
3.2.103.1. Parameters	1293
3.2.103.2. Responses	1294
3.2.103.3. Consumes	1294
3.2.103.4. Produces	1294
3.2.103.5. Tags	1294
3.2.104. partially update status of the specified ReplicationController	1294
3.2.104.1. Parameters	1294

3.2.104.2. Responses	1295
3.2.104.3. Consumes	1295
3.2.104.4. Produces	1295
3.2.104.5. Tags	1295
3.2.105. replace status of the specified ReplicationController	1295
3.2.105.1. Parameters	1296
3.2.105.2. Responses	1296
3.2.105.3. Consumes	1296
3.2.105.4. Produces	1296
3.2.105.5. Tags	1296
3.2.106. list or watch objects of kind ResourceQuota	1297
3.2.106.1. Parameters	1297
3.2.106.2. Responses	1298
3.2.106.3. Consumes	1299
3.2.106.4. Produces	1299
3.2.106.5. Tags	1299
3.2.107. create a ResourceQuota	1299
3.2.107.1. Parameters	1299
3.2.107.2. Responses	1299
3.2.107.3. Consumes	1300
3.2.107.4. Produces	1300
3.2.107.5. Tags	1300
3.2.108. delete collection of ResourceQuota	1300
3.2.108.1. Parameters	1300
3.2.108.2. Responses	1302
3.2.108.3. Consumes	1303
3.2.108.4. Produces	1303
3.2.108.5. Tags	1303
3.2.109. read the specified ResourceQuota	1303
3.2.109.1. Parameters	1303
3.2.109.2. Responses	1304
3.2.109.3. Consumes	1304
3.2.109.4. Produces	1304
3.2.109.5. Tags	1304
3.2.110. partially update the specified ResourceQuota	1304
3.2.110.1. Parameters	1304
3.2.110.2. Responses	1305
3.2.110.3. Consumes	1305
3.2.110.4. Produces	1305
3.2.110.5. Tags	1305
3.2.111. replace the specified ResourceQuota	1305
3.2.111.1. Parameters	1306
3.2.111.2. Responses	1306
3.2.111.3. Consumes	1306
3.2.111.4. Produces	1306
3.2.111.5. Tags	1306
3.2.112. delete a ResourceQuota	1306
3.2.112.1. Parameters	1307
3.2.112.2. Responses	1309
3.2.112.3. Consumes	1309
3.2.112.4. Produces	1309
3.2.112.5. Tags	1309
3.2.113. read status of the specified ResourceQuota	1309

3.2.113.1. Parameters	1309
3.2.113.2. Responses	1310
3.2.113.3. Consumes	1310
3.2.113.4. Produces	1310
3.2.113.5. Tags	1310
3.2.114. partially update status of the specified ResourceQuota	1310
3.2.114.1. Parameters	1310
3.2.114.2. Responses	1311
3.2.114.3. Consumes	1311
3.2.114.4. Produces	1311
3.2.114.5. Tags	1311
3.2.115. replace status of the specified ResourceQuota	1311
3.2.115.1. Parameters	1311
3.2.115.2. Responses	1312
3.2.115.3. Consumes	1312
3.2.115.4. Produces	1312
3.2.115.5. Tags	1312
3.2.116. list or watch objects of kind Secret	1312
3.2.116.1. Parameters	1313
3.2.116.2. Responses	1314
3.2.116.3. Consumes	1315
3.2.116.4. Produces	1315
3.2.116.5. Tags	1315
3.2.117. create a Secret	1315
3.2.117.1. Parameters	1315
3.2.117.2. Responses	1315
3.2.117.3. Consumes	1316
3.2.117.4. Produces	1316
3.2.117.5. Tags	1316
3.2.118. delete collection of Secret	1316
3.2.118.1. Parameters	1316
3.2.118.2. Responses	1318
3.2.118.3. Consumes	1319
3.2.118.4. Produces	1319
3.2.118.5. Tags	1319
3.2.119. read the specified Secret	1319
3.2.119.1. Parameters	1319
3.2.119.2. Responses	1320
3.2.119.3. Consumes	1320
3.2.119.4. Produces	1320
3.2.119.5. Tags	1320
3.2.120. partially update the specified Secret	1320
3.2.120.1. Parameters	1320
3.2.120.2. Responses	1321
3.2.120.3. Consumes	1321
3.2.120.4. Produces	1321
3.2.120.5. Tags	1321
3.2.121. replace the specified Secret	1321
3.2.121.1. Parameters	1321
3.2.121.2. Responses	1322
3.2.121.3. Consumes	1322
3.2.121.4. Produces	1322
3.2.121.5. Tags	1322

3.2.122. delete a Secret	1322
3.2.122.1. Parameters	1322
3.2.122.2. Responses	1325
3.2.122.3. Consumes	1325
3.2.122.4. Produces	1325
3.2.122.5. Tags	1325
3.2.123. list or watch objects of kind ServiceAccount	1325
3.2.123.1. Parameters	1325
3.2.123.2. Responses	1327
3.2.123.3. Consumes	1328
3.2.123.4. Produces	1328
3.2.123.5. Tags	1328
3.2.124. create a ServiceAccount	1328
3.2.124.1. Parameters	1328
3.2.124.2. Responses	1328
3.2.124.3. Consumes	1329
3.2.124.4. Produces	1329
3.2.124.5. Tags	1329
3.2.125. delete collection of ServiceAccount	1329
3.2.125.1. Parameters	1329
3.2.125.2. Responses	1331
3.2.125.3. Consumes	1332
3.2.125.4. Produces	1332
3.2.125.5. Tags	1332
3.2.126. read the specified ServiceAccount	1332
3.2.126.1. Parameters	1332
3.2.126.2. Responses	1333
3.2.126.3. Consumes	1333
3.2.126.4. Produces	1333
3.2.126.5. Tags	1333
3.2.127. partially update the specified ServiceAccount	1333
3.2.127.1. Parameters	1333
3.2.127.2. Responses	1334
3.2.127.3. Consumes	1334
3.2.127.4. Produces	1334
3.2.127.5. Tags	1334
3.2.128. replace the specified ServiceAccount	1334
3.2.128.1. Parameters	1335
3.2.128.2. Responses	1335
3.2.128.3. Consumes	1335
3.2.128.4. Produces	1335
3.2.128.5. Tags	1335
3.2.129. delete a ServiceAccount	1335
3.2.129.1. Parameters	1336
3.2.129.2. Responses	1338
3.2.129.3. Consumes	1338
3.2.129.4. Produces	1338
3.2.129.5. Tags	1338
3.2.130. list or watch objects of kind Service	1338
3.2.130.1. Parameters	1338
3.2.130.2. Responses	1340
3.2.130.3. Consumes	1341
3.2.130.4. Produces	1341

3.2.130.5. Tags	1341
3.2.131. create a Service	1341
3.2.131.1. Parameters	1341
3.2.131.2. Responses	1341
3.2.131.3. Consumes	1342
3.2.131.4. Produces	1342
3.2.131.5. Tags	1342
3.2.132. read the specified Service	1342
3.2.132.1. Parameters	1342
3.2.132.2. Responses	1343
3.2.132.3. Consumes	1343
3.2.132.4. Produces	1343
3.2.132.5. Tags	1343
3.2.133. partially update the specified Service	1343
3.2.133.1. Parameters	1343
3.2.133.2. Responses	1344
3.2.133.3. Consumes	1344
3.2.133.4. Produces	1344
3.2.133.5. Tags	1344
3.2.134. replace the specified Service	1344
3.2.134.1. Parameters	1344
3.2.134.2. Responses	1345
3.2.134.3. Consumes	1345
3.2.134.4. Produces	1345
3.2.134.5. Tags	1345
3.2.135. delete a Service	1345
3.2.135.1. Parameters	1345
3.2.135.2. Responses	1346
3.2.135.3. Consumes	1346
3.2.135.4. Produces	1346
3.2.135.5. Tags	1346
3.2.136. connect GET requests to proxy of Service	1346
3.2.136.1. Parameters	1346
3.2.136.2. Responses	1347
3.2.136.3. Consumes	1347
3.2.136.4. Produces	1348
3.2.136.5. Tags	1348
3.2.137. connect OPTIONS requests to proxy of Service	1348
3.2.137.1. Parameters	1348
3.2.137.2. Responses	1349
3.2.137.3. Consumes	1349
3.2.137.4. Produces	1349
3.2.137.5. Tags	1349
3.2.138. connect POST requests to proxy of Service	1349
3.2.138.1. Parameters	1349
3.2.138.2. Responses	1350
3.2.138.3. Consumes	1350
3.2.138.4. Produces	1351
3.2.138.5. Tags	1351
3.2.139. connect HEAD requests to proxy of Service	1351
3.2.139.1. Parameters	1351
3.2.139.2. Responses	1352
3.2.139.3. Consumes	1352

3.2.139.4. Produces	1352
3.2.139.5. Tags	1352
3.2.140. connect PUT requests to proxy of Service	1352
3.2.140.1. Parameters	1352
3.2.140.2. Responses	1353
3.2.140.3. Consumes	1353
3.2.140.4. Produces	1354
3.2.140.5. Tags	1354
3.2.141. connect DELETE requests to proxy of Service	1354
3.2.141.1. Parameters	1354
3.2.141.2. Responses	1355
3.2.141.3. Consumes	1355
3.2.141.4. Produces	1355
3.2.141.5. Tags	1355
3.2.142. connect GET requests to proxy of Service	1355
3.2.142.1. Parameters	1355
3.2.142.2. Responses	1356
3.2.142.3. Consumes	1357
3.2.142.4. Produces	1357
3.2.142.5. Tags	1357
3.2.143. connect OPTIONS requests to proxy of Service	1357
3.2.143.1. Parameters	1357
3.2.143.2. Responses	1358
3.2.143.3. Consumes	1358
3.2.143.4. Produces	1358
3.2.143.5. Tags	1358
3.2.144. connect POST requests to proxy of Service	1358
3.2.144.1. Parameters	1358
3.2.144.2. Responses	1359
3.2.144.3. Consumes	1359
3.2.144.4. Produces	1360
3.2.144.5. Tags	1360
3.2.145. connect HEAD requests to proxy of Service	1360
3.2.145.1. Parameters	1360
3.2.145.2. Responses	1361
3.2.145.3. Consumes	1361
3.2.145.4. Produces	1361
3.2.145.5. Tags	1361
3.2.146. connect PUT requests to proxy of Service	1361
3.2.146.1. Parameters	1361
3.2.146.2. Responses	1362
3.2.146.3. Consumes	1362
3.2.146.4. Produces	1363
3.2.146.5. Tags	1363
3.2.147. connect DELETE requests to proxy of Service	1363
3.2.147.1. Parameters	1363
3.2.147.2. Responses	1364
3.2.147.3. Consumes	1364
3.2.147.4. Produces	1364
3.2.147.5. Tags	1364
3.2.148. read status of the specified Service	1364
3.2.148.1. Parameters	1364
3.2.148.2. Responses	1365

3.2.148.3. Consumes	1365
3.2.148.4. Produces	1365
3.2.148.5. Tags	1365
3.2.149. partially update status of the specified Service	1365
3.2.149.1. Parameters	1365
3.2.149.2. Responses	1366
3.2.149.3. Consumes	1366
3.2.149.4. Produces	1366
3.2.149.5. Tags	1366
3.2.150. replace status of the specified Service	1366
3.2.150.1. Parameters	1366
3.2.150.2. Responses	1367
3.2.150.3. Consumes	1367
3.2.150.4. Produces	1367
3.2.150.5. Tags	1367
3.2.151. read the specified Namespace	1367
3.2.151.1. Parameters	1367
3.2.151.2. Responses	1368
3.2.151.3. Consumes	1368
3.2.151.4. Produces	1368
3.2.151.5. Tags	1368
3.2.152. partially update the specified Namespace	1369
3.2.152.1. Parameters	1369
3.2.152.2. Responses	1369
3.2.152.3. Consumes	1369
3.2.152.4. Produces	1369
3.2.152.5. Tags	1369
3.2.153. replace the specified Namespace	1369
3.2.153.1. Parameters	1370
3.2.153.2. Responses	1370
3.2.153.3. Consumes	1370
3.2.153.4. Produces	1370
3.2.153.5. Tags	1370
3.2.154. delete a Namespace	1370
3.2.154.1. Parameters	1370
3.2.154.2. Responses	1373
3.2.154.3. Consumes	1373
3.2.154.4. Produces	1373
3.2.154.5. Tags	1373
3.2.155. replace finalize of the specified Namespace	1373
3.2.155.1. Parameters	1373
3.2.155.2. Responses	1373
3.2.155.3. Consumes	1374
3.2.155.4. Produces	1374
3.2.155.5. Tags	1374
3.2.156. read status of the specified Namespace	1374
3.2.156.1. Parameters	1374
3.2.156.2. Responses	1374
3.2.156.3. Consumes	1374
3.2.156.4. Produces	1375
3.2.156.5. Tags	1375
3.2.157. partially update status of the specified Namespace	1375
3.2.157.1. Parameters	1375

3.2.157.2. Responses	1375
3.2.157.3. Consumes	1375
3.2.157.4. Produces	1375
3.2.157.5. Tags	1376
3.2.158. replace status of the specified Namespace	1376
3.2.158.1. Parameters	1376
3.2.158.2. Responses	1376
3.2.158.3. Consumes	1376
3.2.158.4. Produces	1376
3.2.158.5. Tags	1376
3.2.159. list or watch objects of kind Node	1377
3.2.159.1. Parameters	1377
3.2.159.2. Responses	1378
3.2.159.3. Consumes	1379
3.2.159.4. Produces	1379
3.2.159.5. Tags	1379
3.2.160. create a Node	1379
3.2.160.1. Parameters	1379
3.2.160.2. Responses	1379
3.2.160.3. Consumes	1379
3.2.160.4. Produces	1379
3.2.160.5. Tags	1380
3.2.161. delete collection of Node	1380
3.2.161.1. Parameters	1380
3.2.161.2. Responses	1381
3.2.161.3. Consumes	1382
3.2.161.4. Produces	1382
3.2.161.5. Tags	1382
3.2.162. read the specified Node	1382
3.2.162.1. Parameters	1382
3.2.162.2. Responses	1382
3.2.162.3. Consumes	1383
3.2.162.4. Produces	1383
3.2.162.5. Tags	1383
3.2.163. partially update the specified Node	1383
3.2.163.1. Parameters	1383
3.2.163.2. Responses	1383
3.2.163.3. Consumes	1383
3.2.163.4. Produces	1384
3.2.163.5. Tags	1384
3.2.164. replace the specified Node	1384
3.2.164.1. Parameters	1384
3.2.164.2. Responses	1384
3.2.164.3. Consumes	1384
3.2.164.4. Produces	1384
3.2.164.5. Tags	1385
3.2.165. delete a Node	1385
3.2.165.1. Parameters	1385
3.2.165.2. Responses	1388
3.2.165.3. Consumes	1388
3.2.165.4. Produces	1388
3.2.165.5. Tags	1388
3.2.166. connect GET requests to proxy of Node	1388

3.2.166.1. Parameters	1388
3.2.166.2. Responses	1388
3.2.166.3. Consumes	1388
3.2.166.4. Produces	1389
3.2.166.5. Tags	1389
3.2.167. connect OPTIONS requests to proxy of Node	1389
3.2.167.1. Parameters	1389
3.2.167.2. Responses	1389
3.2.167.3. Consumes	1389
3.2.167.4. Produces	1389
3.2.167.5. Tags	1389
3.2.168. connect POST requests to proxy of Node	1389
3.2.168.1. Parameters	1390
3.2.168.2. Responses	1390
3.2.168.3. Consumes	1390
3.2.168.4. Produces	1390
3.2.168.5. Tags	1390
3.2.169. connect HEAD requests to proxy of Node	1390
3.2.169.1. Parameters	1390
3.2.169.2. Responses	1391
3.2.169.3. Consumes	1391
3.2.169.4. Produces	1391
3.2.169.5. Tags	1391
3.2.170. connect PUT requests to proxy of Node	1391
3.2.170.1. Parameters	1391
3.2.170.2. Responses	1391
3.2.170.3. Consumes	1392
3.2.170.4. Produces	1392
3.2.170.5. Tags	1392
3.2.171. connect DELETE requests to proxy of Node	1392
3.2.171.1. Parameters	1392
3.2.171.2. Responses	1392
3.2.171.3. Consumes	1392
3.2.171.4. Produces	1392
3.2.171.5. Tags	1393
3.2.172. connect GET requests to proxy of Node	1393
3.2.172.1. Parameters	1393
3.2.172.2. Responses	1393
3.2.172.3. Consumes	1393
3.2.172.4. Produces	1393
3.2.172.5. Tags	1393
3.2.173. connect OPTIONS requests to proxy of Node	1393
3.2.173.1. Parameters	1393
3.2.173.2. Responses	1394
3.2.173.3. Consumes	1394
3.2.173.4. Produces	1394
3.2.173.5. Tags	1394
3.2.174. connect POST requests to proxy of Node	1394
3.2.174.1. Parameters	1394
3.2.174.2. Responses	1395
3.2.174.3. Consumes	1395
3.2.174.4. Produces	1395
3.2.174.5. Tags	1395

3.2.175. connect HEAD requests to proxy of Node	1395
3.2.175.1. Parameters	1395
3.2.175.2. Responses	1396
3.2.175.3. Consumes	1396
3.2.175.4. Produces	1396
3.2.175.5. Tags	1396
3.2.176. connect PUT requests to proxy of Node	1396
3.2.176.1. Parameters	1396
3.2.176.2. Responses	1396
3.2.176.3. Consumes	1396
3.2.176.4. Produces	1397
3.2.176.5. Tags	1397
3.2.177. connect DELETE requests to proxy of Node	1397
3.2.177.1. Parameters	1397
3.2.177.2. Responses	1397
3.2.177.3. Consumes	1397
3.2.177.4. Produces	1397
3.2.177.5. Tags	1397
3.2.178. read status of the specified Node	1397
3.2.178.1. Parameters	1398
3.2.178.2. Responses	1398
3.2.178.3. Consumes	1398
3.2.178.4. Produces	1398
3.2.178.5. Tags	1398
3.2.179. partially update status of the specified Node	1398
3.2.179.1. Parameters	1398
3.2.179.2. Responses	1399
3.2.179.3. Consumes	1399
3.2.179.4. Produces	1399
3.2.179.5. Tags	1399
3.2.180. replace status of the specified Node	1399
3.2.180.1. Parameters	1399
3.2.180.2. Responses	1400
3.2.180.3. Consumes	1400
3.2.180.4. Produces	1400
3.2.180.5. Tags	1400
3.2.181. list or watch objects of kind PersistentVolumeClaim	1400
3.2.181.1. Parameters	1400
3.2.181.2. Responses	1402
3.2.181.3. Consumes	1403
3.2.181.4. Produces	1403
3.2.181.5. Tags	1403
3.2.182. create a PersistentVolumeClaim	1403
3.2.182.1. Parameters	1403
3.2.182.2. Responses	1403
3.2.182.3. Consumes	1404
3.2.182.4. Produces	1404
3.2.182.5. Tags	1404
3.2.183. list or watch objects of kind PersistentVolume	1404
3.2.183.1. Parameters	1404
3.2.183.2. Responses	1406
3.2.183.3. Consumes	1407
3.2.183.4. Produces	1407

3.2.183.5. Tags	1407
3.2.184. create a PersistentVolume	1407
3.2.184.1. Parameters	1407
3.2.184.2. Responses	1407
3.2.184.3. Consumes	1408
3.2.184.4. Produces	1408
3.2.184.5. Tags	1408
3.2.185. delete collection of PersistentVolume	1408
3.2.185.1. Parameters	1408
3.2.185.2. Responses	1410
3.2.185.3. Consumes	1411
3.2.185.4. Produces	1411
3.2.185.5. Tags	1411
3.2.186. read the specified PersistentVolume	1411
3.2.186.1. Parameters	1411
3.2.186.2. Responses	1412
3.2.186.3. Consumes	1412
3.2.186.4. Produces	1412
3.2.186.5. Tags	1412
3.2.187. partially update the specified PersistentVolume	1412
3.2.187.1. Parameters	1412
3.2.187.2. Responses	1412
3.2.187.3. Consumes	1413
3.2.187.4. Produces	1413
3.2.187.5. Tags	1413
3.2.188. replace the specified PersistentVolume	1413
3.2.188.1. Parameters	1413
3.2.188.2. Responses	1413
3.2.188.3. Consumes	1414
3.2.188.4. Produces	1414
3.2.188.5. Tags	1414
3.2.189. delete a PersistentVolume	1414
3.2.189.1. Parameters	1414
3.2.189.2. Responses	1417
3.2.189.3. Consumes	1417
3.2.189.4. Produces	1417
3.2.189.5. Tags	1417
3.2.190. read status of the specified PersistentVolume	1417
3.2.190.1. Parameters	1417
3.2.190.2. Responses	1417
3.2.190.3. Consumes	1418
3.2.190.4. Produces	1418
3.2.190.5. Tags	1418
3.2.191. partially update status of the specified PersistentVolume	1418
3.2.191.1. Parameters	1418
3.2.191.2. Responses	1418
3.2.191.3. Consumes	1419
3.2.191.4. Produces	1419
3.2.191.5. Tags	1419
3.2.192. replace status of the specified PersistentVolume	1419
3.2.192.1. Parameters	1419
3.2.192.2. Responses	1419
3.2.192.3. Consumes	1419

3.2.192.4. Produces	1420
3.2.192.5. Tags	1420
3.2.193. list or watch objects of kind Pod	1420
3.2.193.1. Parameters	1420
3.2.193.2. Responses	1422
3.2.193.3. Consumes	1423
3.2.193.4. Produces	1423
3.2.193.5. Tags	1423
3.2.194. create a Pod	1423
3.2.194.1. Parameters	1423
3.2.194.2. Responses	1423
3.2.194.3. Consumes	1423
3.2.194.4. Produces	1423
3.2.194.5. Tags	1424
3.2.195. list or watch objects of kind PodTemplate	1424
3.2.195.1. Parameters	1424
3.2.195.2. Responses	1425
3.2.195.3. Consumes	1426
3.2.195.4. Produces	1426
3.2.195.5. Tags	1426
3.2.196. create a PodTemplate	1426
3.2.196.1. Parameters	1426
3.2.196.2. Responses	1426
3.2.196.3. Consumes	1427
3.2.196.4. Produces	1427
3.2.196.5. Tags	1427
3.2.197. proxy GET requests to Pod	1427
3.2.197.1. Parameters	1427
3.2.197.2. Responses	1427
3.2.197.3. Consumes	1427
3.2.197.4. Produces	1428
3.2.197.5. Tags	1428
3.2.198. proxy OPTIONS requests to Pod	1428
3.2.198.1. Parameters	1428
3.2.198.2. Responses	1428
3.2.198.3. Consumes	1428
3.2.198.4. Produces	1428
3.2.198.5. Tags	1428
3.2.199. proxy POST requests to Pod	1428
3.2.199.1. Parameters	1428
3.2.199.2. Responses	1429
3.2.199.3. Consumes	1429
3.2.199.4. Produces	1429
3.2.199.5. Tags	1429
3.2.200. proxy PATCH requests to Pod	1429
3.2.200.1. Parameters	1429
3.2.200.2. Responses	1429
3.2.200.3. Consumes	1430
3.2.200.4. Produces	1430
3.2.200.5. Tags	1430
3.2.201. proxy HEAD requests to Pod	1430
3.2.201.1. Parameters	1430
3.2.201.2. Responses	1430

3.2.201.3. Consumes	1430
3.2.201.4. Produces	1430
3.2.201.5. Tags	1431
3.2.202. proxy PUT requests to Pod	1431
3.2.202.1. Parameters	1431
3.2.202.2. Responses	1431
3.2.202.3. Consumes	1431
3.2.202.4. Produces	1431
3.2.202.5. Tags	1431
3.2.203. proxy DELETE requests to Pod	1431
3.2.203.1. Parameters	1431
3.2.203.2. Responses	1432
3.2.203.3. Consumes	1432
3.2.203.4. Produces	1432
3.2.203.5. Tags	1432
3.2.204. proxy GET requests to Pod	1432
3.2.204.1. Parameters	1432
3.2.204.2. Responses	1433
3.2.204.3. Consumes	1433
3.2.204.4. Produces	1433
3.2.204.5. Tags	1433
3.2.205. proxy OPTIONS requests to Pod	1433
3.2.205.1. Parameters	1433
3.2.205.2. Responses	1433
3.2.205.3. Consumes	1434
3.2.205.4. Produces	1434
3.2.205.5. Tags	1434
3.2.206. proxy POST requests to Pod	1434
3.2.206.1. Parameters	1434
3.2.206.2. Responses	1434
3.2.206.3. Consumes	1434
3.2.206.4. Produces	1434
3.2.206.5. Tags	1435
3.2.207. proxy PATCH requests to Pod	1435
3.2.207.1. Parameters	1435
3.2.207.2. Responses	1435
3.2.207.3. Consumes	1435
3.2.207.4. Produces	1435
3.2.207.5. Tags	1435
3.2.208. proxy HEAD requests to Pod	1435
3.2.208.1. Parameters	1436
3.2.208.2. Responses	1436
3.2.208.3. Consumes	1436
3.2.208.4. Produces	1436
3.2.208.5. Tags	1436
3.2.209. proxy PUT requests to Pod	1436
3.2.209.1. Parameters	1436
3.2.209.2. Responses	1437
3.2.209.3. Consumes	1437
3.2.209.4. Produces	1437
3.2.209.5. Tags	1437
3.2.210. proxy DELETE requests to Pod	1437
3.2.210.1. Parameters	1437

3.2.210.2. Responses	1438
3.2.210.3. Consumes	1438
3.2.210.4. Produces	1438
3.2.210.5. Tags	1438
3.2.211. proxy GET requests to Service	1438
3.2.211.1. Parameters	1438
3.2.211.2. Responses	1438
3.2.211.3. Consumes	1438
3.2.211.4. Produces	1438
3.2.211.5. Tags	1439
3.2.212. proxy OPTIONS requests to Service	1439
3.2.212.1. Parameters	1439
3.2.212.2. Responses	1439
3.2.212.3. Consumes	1439
3.2.212.4. Produces	1439
3.2.212.5. Tags	1439
3.2.213. proxy POST requests to Service	1439
3.2.213.1. Parameters	1439
3.2.213.2. Responses	1440
3.2.213.3. Consumes	1440
3.2.213.4. Produces	1440
3.2.213.5. Tags	1440
3.2.214. proxy PATCH requests to Service	1440
3.2.214.1. Parameters	1440
3.2.214.2. Responses	1441
3.2.214.3. Consumes	1441
3.2.214.4. Produces	1441
3.2.214.5. Tags	1441
3.2.215. proxy HEAD requests to Service	1441
3.2.215.1. Parameters	1441
3.2.215.2. Responses	1441
3.2.215.3. Consumes	1441
3.2.215.4. Produces	1441
3.2.215.5. Tags	1442
3.2.216. proxy PUT requests to Service	1442
3.2.216.1. Parameters	1442
3.2.216.2. Responses	1442
3.2.216.3. Consumes	1442
3.2.216.4. Produces	1442
3.2.216.5. Tags	1442
3.2.217. proxy DELETE requests to Service	1442
3.2.217.1. Parameters	1442
3.2.217.2. Responses	1443
3.2.217.3. Consumes	1443
3.2.217.4. Produces	1443
3.2.217.5. Tags	1443
3.2.218. proxy GET requests to Service	1443
3.2.218.1. Parameters	1443
3.2.218.2. Responses	1444
3.2.218.3. Consumes	1444
3.2.218.4. Produces	1444
3.2.218.5. Tags	1444
3.2.219. proxy OPTIONS requests to Service	1444

3.2.219.1. Parameters	1444
3.2.219.2. Responses	1444
3.2.219.3. Consumes	1445
3.2.219.4. Produces	1445
3.2.219.5. Tags	1445
3.2.220. proxy POST requests to Service	1445
3.2.220.1. Parameters	1445
3.2.220.2. Responses	1445
3.2.220.3. Consumes	1445
3.2.220.4. Produces	1445
3.2.220.5. Tags	1446
3.2.221. proxy PATCH requests to Service	1446
3.2.221.1. Parameters	1446
3.2.221.2. Responses	1446
3.2.221.3. Consumes	1446
3.2.221.4. Produces	1446
3.2.221.5. Tags	1446
3.2.222. proxy HEAD requests to Service	1446
3.2.222.1. Parameters	1447
3.2.222.2. Responses	1447
3.2.222.3. Consumes	1447
3.2.222.4. Produces	1447
3.2.222.5. Tags	1447
3.2.223. proxy PUT requests to Service	1447
3.2.223.1. Parameters	1447
3.2.223.2. Responses	1448
3.2.223.3. Consumes	1448
3.2.223.4. Produces	1448
3.2.223.5. Tags	1448
3.2.224. proxy DELETE requests to Service	1448
3.2.224.1. Parameters	1448
3.2.224.2. Responses	1449
3.2.224.3. Consumes	1449
3.2.224.4. Produces	1449
3.2.224.5. Tags	1449
3.2.225. proxy GET requests to Node	1449
3.2.225.1. Parameters	1449
3.2.225.2. Responses	1449
3.2.225.3. Consumes	1449
3.2.225.4. Produces	1449
3.2.225.5. Tags	1449
3.2.226. proxy OPTIONS requests to Node	1450
3.2.226.1. Parameters	1450
3.2.226.2. Responses	1450
3.2.226.3. Consumes	1450
3.2.226.4. Produces	1450
3.2.226.5. Tags	1450
3.2.227. proxy POST requests to Node	1450
3.2.227.1. Parameters	1450
3.2.227.2. Responses	1450
3.2.227.3. Consumes	1451
3.2.227.4. Produces	1451
3.2.227.5. Tags	1451

3.2.228. proxy PATCH requests to Node	1451
3.2.228.1. Parameters	1451
3.2.228.2. Responses	1451
3.2.228.3. Consumes	1451
3.2.228.4. Produces	1451
3.2.228.5. Tags	1451
3.2.229. proxy HEAD requests to Node	1451
3.2.229.1. Parameters	1451
3.2.229.2. Responses	1452
3.2.229.3. Consumes	1452
3.2.229.4. Produces	1452
3.2.229.5. Tags	1452
3.2.230. proxy PUT requests to Node	1452
3.2.230.1. Parameters	1452
3.2.230.2. Responses	1452
3.2.230.3. Consumes	1452
3.2.230.4. Produces	1452
3.2.230.5. Tags	1453
3.2.231. proxy DELETE requests to Node	1453
3.2.231.1. Parameters	1453
3.2.231.2. Responses	1453
3.2.231.3. Consumes	1453
3.2.231.4. Produces	1453
3.2.231.5. Tags	1453
3.2.232. proxy GET requests to Node	1453
3.2.232.1. Parameters	1453
3.2.232.2. Responses	1454
3.2.232.3. Consumes	1454
3.2.232.4. Produces	1454
3.2.232.5. Tags	1454
3.2.233. proxy OPTIONS requests to Node	1454
3.2.233.1. Parameters	1454
3.2.233.2. Responses	1454
3.2.233.3. Consumes	1454
3.2.233.4. Produces	1455
3.2.233.5. Tags	1455
3.2.234. proxy POST requests to Node	1455
3.2.234.1. Parameters	1455
3.2.234.2. Responses	1455
3.2.234.3. Consumes	1455
3.2.234.4. Produces	1455
3.2.234.5. Tags	1455
3.2.235. proxy PATCH requests to Node	1455
3.2.235.1. Parameters	1455
3.2.235.2. Responses	1456
3.2.235.3. Consumes	1456
3.2.235.4. Produces	1456
3.2.235.5. Tags	1456
3.2.236. proxy HEAD requests to Node	1456
3.2.236.1. Parameters	1456
3.2.236.2. Responses	1456
3.2.236.3. Consumes	1457
3.2.236.4. Produces	1457

3.2.236.5. Tags	1457
3.2.237. proxy PUT requests to Node	1457
3.2.237.1. Parameters	1457
3.2.237.2. Responses	1457
3.2.237.3. Consumes	1457
3.2.237.4. Produces	1457
3.2.237.5. Tags	1457
3.2.238. proxy DELETE requests to Node	1457
3.2.238.1. Parameters	1458
3.2.238.2. Responses	1458
3.2.238.3. Consumes	1458
3.2.238.4. Produces	1458
3.2.238.5. Tags	1458
3.2.239. list or watch objects of kind ReplicationController	1458
3.2.239.1. Parameters	1458
3.2.239.2. Responses	1460
3.2.239.3. Consumes	1461
3.2.239.4. Produces	1461
3.2.239.5. Tags	1461
3.2.240. create a ReplicationController	1461
3.2.240.1. Parameters	1461
3.2.240.2. Responses	1461
3.2.240.3. Consumes	1462
3.2.240.4. Produces	1462
3.2.240.5. Tags	1462
3.2.241. list or watch objects of kind ResourceQuota	1462
3.2.241.1. Parameters	1462
3.2.241.2. Responses	1464
3.2.241.3. Consumes	1465
3.2.241.4. Produces	1465
3.2.241.5. Tags	1465
3.2.242. create a ResourceQuota	1465
3.2.242.1. Parameters	1465
3.2.242.2. Responses	1465
3.2.242.3. Consumes	1465
3.2.242.4. Produces	1465
3.2.242.5. Tags	1466
3.2.243. list or watch objects of kind Secret	1466
3.2.243.1. Parameters	1466
3.2.243.2. Responses	1468
3.2.243.3. Consumes	1469
3.2.243.4. Produces	1469
3.2.243.5. Tags	1469
3.2.244. create a Secret	1469
3.2.244.1. Parameters	1469
3.2.244.2. Responses	1469
3.2.244.3. Consumes	1469
3.2.244.4. Produces	1469
3.2.244.5. Tags	1470
3.2.245. list or watch objects of kind SecurityContextConstraints	1470
3.2.245.1. Parameters	1470
3.2.245.2. Responses	1471
3.2.245.3. Consumes	1472

3.2.245.4. Produces	1472
3.2.245.5. Tags	1472
3.2.246. create SecurityContextConstraints	1472
3.2.246.1. Parameters	1472
3.2.246.2. Responses	1472
3.2.246.3. Consumes	1473
3.2.246.4. Produces	1473
3.2.246.5. Tags	1473
3.2.247. delete collection of SecurityContextConstraints	1473
3.2.247.1. Parameters	1473
3.2.247.2. Responses	1475
3.2.247.3. Consumes	1476
3.2.247.4. Produces	1476
3.2.247.5. Tags	1476
3.2.248. read the specified SecurityContextConstraints	1476
3.2.248.1. Parameters	1476
3.2.248.2. Responses	1477
3.2.248.3. Consumes	1477
3.2.248.4. Produces	1477
3.2.248.5. Tags	1477
3.2.249. partially update the specified SecurityContextConstraints	1477
3.2.249.1. Parameters	1477
3.2.249.2. Responses	1477
3.2.249.3. Consumes	1478
3.2.249.4. Produces	1478
3.2.249.5. Tags	1478
3.2.250. replace the specified SecurityContextConstraints	1478
3.2.250.1. Parameters	1478
3.2.250.2. Responses	1479
3.2.250.3. Consumes	1479
3.2.250.4. Produces	1479
3.2.250.5. Tags	1479
3.2.251. delete SecurityContextConstraints	1479
3.2.251.1. Parameters	1479
3.2.251.2. Responses	1482
3.2.251.3. Consumes	1482
3.2.251.4. Produces	1482
3.2.251.5. Tags	1482
3.2.252. list or watch objects of kind ServiceAccount	1482
3.2.252.1. Parameters	1482
3.2.252.2. Responses	1484
3.2.252.3. Consumes	1485
3.2.252.4. Produces	1485
3.2.252.5. Tags	1485
3.2.253. create a ServiceAccount	1485
3.2.253.1. Parameters	1485
3.2.253.2. Responses	1485
3.2.253.3. Consumes	1485
3.2.253.4. Produces	1485
3.2.253.5. Tags	1486
3.2.254. list or watch objects of kind Service	1486
3.2.254.1. Parameters	1486
3.2.254.2. Responses	1488

3.2.254.3. Consumes	1489
3.2.254.4. Produces	1489
3.2.254.5. Tags	1489
3.2.255. create a Service	1489
3.2.255.1. Parameters	1489
3.2.255.2. Responses	1489
3.2.255.3. Consumes	1489
3.2.255.4. Produces	1489
3.2.255.5. Tags	1490
3.2.256. watch individual changes to a list of ConfigMap	1490
3.2.256.1. Parameters	1490
3.2.256.2. Responses	1491
3.2.256.3. Consumes	1492
3.2.256.4. Produces	1492
3.2.256.5. Tags	1492
3.2.257. watch individual changes to a list of Endpoints	1492
3.2.257.1. Parameters	1492
3.2.257.2. Responses	1494
3.2.257.3. Consumes	1495
3.2.257.4. Produces	1495
3.2.257.5. Tags	1495
3.2.258. watch individual changes to a list of Event	1495
3.2.258.1. Parameters	1495
3.2.258.2. Responses	1497
3.2.258.3. Consumes	1498
3.2.258.4. Produces	1498
3.2.258.5. Tags	1498
3.2.259. watch individual changes to a list of LimitRange	1498
3.2.259.1. Parameters	1498
3.2.259.2. Responses	1500
3.2.259.3. Consumes	1501
3.2.259.4. Produces	1501
3.2.259.5. Tags	1501
3.2.260. watch individual changes to a list of Namespace	1501
3.2.260.1. Parameters	1501
3.2.260.2. Responses	1503
3.2.260.3. Consumes	1504
3.2.260.4. Produces	1504
3.2.260.5. Tags	1504
3.2.261. watch individual changes to a list of ConfigMap	1504
3.2.261.1. Parameters	1504
3.2.261.2. Responses	1507
3.2.261.3. Consumes	1507
3.2.261.4. Produces	1507
3.2.261.5. Tags	1507
3.2.262. watch changes to an object of kind ConfigMap	1507
3.2.262.1. Parameters	1507
3.2.262.2. Responses	1510
3.2.262.3. Consumes	1510
3.2.262.4. Produces	1510
3.2.262.5. Tags	1510
3.2.263. watch individual changes to a list of Endpoints	1510
3.2.263.1. Parameters	1510

3.2.263.2. Responses	1512
3.2.263.3. Consumes	1513
3.2.263.4. Produces	1513
3.2.263.5. Tags	1513
3.2.264. watch changes to an object of kind Endpoints	1513
3.2.264.1. Parameters	1513
3.2.264.2. Responses	1516
3.2.264.3. Consumes	1516
3.2.264.4. Produces	1516
3.2.264.5. Tags	1516
3.2.265. watch individual changes to a list of Event	1516
3.2.265.1. Parameters	1516
3.2.265.2. Responses	1518
3.2.265.3. Consumes	1519
3.2.265.4. Produces	1519
3.2.265.5. Tags	1519
3.2.266. watch changes to an object of kind Event	1519
3.2.266.1. Parameters	1519
3.2.266.2. Responses	1522
3.2.266.3. Consumes	1522
3.2.266.4. Produces	1522
3.2.266.5. Tags	1522
3.2.267. watch individual changes to a list of LimitRange	1522
3.2.267.1. Parameters	1522
3.2.267.2. Responses	1524
3.2.267.3. Consumes	1525
3.2.267.4. Produces	1525
3.2.267.5. Tags	1525
3.2.268. watch changes to an object of kind LimitRange	1525
3.2.268.1. Parameters	1525
3.2.268.2. Responses	1528
3.2.268.3. Consumes	1528
3.2.268.4. Produces	1528
3.2.268.5. Tags	1528
3.2.269. watch individual changes to a list of PersistentVolumeClaim	1528
3.2.269.1. Parameters	1528
3.2.269.2. Responses	1530
3.2.269.3. Consumes	1531
3.2.269.4. Produces	1531
3.2.269.5. Tags	1531
3.2.270. watch changes to an object of kind PersistentVolumeClaim	1531
3.2.270.1. Parameters	1531
3.2.270.2. Responses	1534
3.2.270.3. Consumes	1534
3.2.270.4. Produces	1534
3.2.270.5. Tags	1534
3.2.271. watch individual changes to a list of Pod	1534
3.2.271.1. Parameters	1534
3.2.271.2. Responses	1536
3.2.271.3. Consumes	1537
3.2.271.4. Produces	1537
3.2.271.5. Tags	1537
3.2.272. watch changes to an object of kind Pod	1537

3.2.272.1. Parameters	1537
3.2.272.2. Responses	1540
3.2.272.3. Consumes	1540
3.2.272.4. Produces	1540
3.2.272.5. Tags	1540
3.2.273. watch individual changes to a list of PodTemplate	1540
3.2.273.1. Parameters	1540
3.2.273.2. Responses	1542
3.2.273.3. Consumes	1543
3.2.273.4. Produces	1543
3.2.273.5. Tags	1543
3.2.274. watch changes to an object of kind PodTemplate	1543
3.2.274.1. Parameters	1543
3.2.274.2. Responses	1546
3.2.274.3. Consumes	1546
3.2.274.4. Produces	1546
3.2.274.5. Tags	1546
3.2.275. watch individual changes to a list of ReplicationController	1546
3.2.275.1. Parameters	1546
3.2.275.2. Responses	1548
3.2.275.3. Consumes	1549
3.2.275.4. Produces	1549
3.2.275.5. Tags	1549
3.2.276. watch changes to an object of kind ReplicationController	1549
3.2.276.1. Parameters	1549
3.2.276.2. Responses	1552
3.2.276.3. Consumes	1552
3.2.276.4. Produces	1552
3.2.276.5. Tags	1552
3.2.277. watch individual changes to a list of ResourceQuota	1552
3.2.277.1. Parameters	1552
3.2.277.2. Responses	1554
3.2.277.3. Consumes	1555
3.2.277.4. Produces	1555
3.2.277.5. Tags	1555
3.2.278. watch changes to an object of kind ResourceQuota	1555
3.2.278.1. Parameters	1555
3.2.278.2. Responses	1558
3.2.278.3. Consumes	1558
3.2.278.4. Produces	1558
3.2.278.5. Tags	1558
3.2.279. watch individual changes to a list of Secret	1558
3.2.279.1. Parameters	1558
3.2.279.2. Responses	1560
3.2.279.3. Consumes	1561
3.2.279.4. Produces	1561
3.2.279.5. Tags	1561
3.2.280. watch changes to an object of kind Secret	1561
3.2.280.1. Parameters	1561
3.2.280.2. Responses	1564
3.2.280.3. Consumes	1564
3.2.280.4. Produces	1564
3.2.280.5. Tags	1564

3.2.281. watch individual changes to a list of ServiceAccount	1564
3.2.281.1. Parameters	1564
3.2.281.2. Responses	1566
3.2.281.3. Consumes	1567
3.2.281.4. Produces	1567
3.2.281.5. Tags	1567
3.2.282. watch changes to an object of kind ServiceAccount	1567
3.2.282.1. Parameters	1567
3.2.282.2. Responses	1570
3.2.282.3. Consumes	1570
3.2.282.4. Produces	1570
3.2.282.5. Tags	1570
3.2.283. watch individual changes to a list of Service	1570
3.2.283.1. Parameters	1570
3.2.283.2. Responses	1572
3.2.283.3. Consumes	1573
3.2.283.4. Produces	1573
3.2.283.5. Tags	1573
3.2.284. watch changes to an object of kind Service	1573
3.2.284.1. Parameters	1573
3.2.284.2. Responses	1576
3.2.284.3. Consumes	1576
3.2.284.4. Produces	1576
3.2.284.5. Tags	1576
3.2.285. watch changes to an object of kind Namespace	1576
3.2.285.1. Parameters	1576
3.2.285.2. Responses	1578
3.2.285.3. Consumes	1579
3.2.285.4. Produces	1579
3.2.285.5. Tags	1579
3.2.286. watch individual changes to a list of Node	1579
3.2.286.1. Parameters	1579
3.2.286.2. Responses	1581
3.2.286.3. Consumes	1582
3.2.286.4. Produces	1582
3.2.286.5. Tags	1582
3.2.287. watch changes to an object of kind Node	1582
3.2.287.1. Parameters	1582
3.2.287.2. Responses	1584
3.2.287.3. Consumes	1585
3.2.287.4. Produces	1585
3.2.287.5. Tags	1585
3.2.288. watch individual changes to a list of PersistentVolumeClaim	1585
3.2.288.1. Parameters	1585
3.2.288.2. Responses	1587
3.2.288.3. Consumes	1588
3.2.288.4. Produces	1588
3.2.288.5. Tags	1588
3.2.289. watch individual changes to a list of PersistentVolume	1588
3.2.289.1. Parameters	1588
3.2.289.2. Responses	1590
3.2.289.3. Consumes	1591
3.2.289.4. Produces	1591

3.2.289.5. Tags	1591
3.2.290. watch changes to an object of kind PersistentVolume	1591
3.2.290.1. Parameters	1591
3.2.290.2. Responses	1593
3.2.290.3. Consumes	1594
3.2.290.4. Produces	1594
3.2.290.5. Tags	1594
3.2.291. watch individual changes to a list of Pod	1594
3.2.291.1. Parameters	1594
3.2.291.2. Responses	1596
3.2.291.3. Consumes	1597
3.2.291.4. Produces	1597
3.2.291.5. Tags	1597
3.2.292. watch individual changes to a list of PodTemplate	1597
3.2.292.1. Parameters	1597
3.2.292.2. Responses	1599
3.2.292.3. Consumes	1600
3.2.292.4. Produces	1600
3.2.292.5. Tags	1600
3.2.293. watch individual changes to a list of ReplicationController	1600
3.2.293.1. Parameters	1600
3.2.293.2. Responses	1602
3.2.293.3. Consumes	1603
3.2.293.4. Produces	1603
3.2.293.5. Tags	1603
3.2.294. watch individual changes to a list of ResourceQuota	1603
3.2.294.1. Parameters	1603
3.2.294.2. Responses	1605
3.2.294.3. Consumes	1606
3.2.294.4. Produces	1606
3.2.294.5. Tags	1606
3.2.295. watch individual changes to a list of Secret	1606
3.2.295.1. Parameters	1606
3.2.295.2. Responses	1608
3.2.295.3. Consumes	1609
3.2.295.4. Produces	1609
3.2.295.5. Tags	1609
3.2.296. watch individual changes to a list of SecurityContextConstraints	1609
3.2.296.1. Parameters	1609
3.2.296.2. Responses	1611
3.2.296.3. Consumes	1612
3.2.296.4. Produces	1612
3.2.296.5. Tags	1612
3.2.297. watch changes to an object of kind SecurityContextConstraints	1612
3.2.297.1. Parameters	1612
3.2.297.2. Responses	1614
3.2.297.3. Consumes	1615
3.2.297.4. Produces	1615
3.2.297.5. Tags	1615
3.2.298. watch individual changes to a list of ServiceAccount	1615
3.2.298.1. Parameters	1615
3.2.298.2. Responses	1617
3.2.298.3. Consumes	1618

3.2.298.4. Produces	1618
3.2.298.5. Tags	1618
3.2.299. watch individual changes to a list of Service	1618
3.2.299.1. Parameters	1618
3.2.299.2. Responses	1620
3.2.299.3. Consumes	1621
3.2.299.4. Produces	1621
3.2.299.5. Tags	1621
3.3. DEFINITIONS	1621
3.3.1. types.UID	1621
3.3.2. v1.APIResource	1621
3.3.3. v1.APIResourceList	1622
3.3.4. v1.AWSElasticBlockStoreVolumeSource	1623
3.3.5. v1.Affinity	1625
3.3.6. v1.AttachedVolume	1626
3.3.7. v1.AzureDataDiskCachingMode	1626
3.3.8. v1.AzureDiskVolumeSource	1626
3.3.9. v1.AzureFileVolumeSource	1627
3.3.10. v1.Binding	1628
3.3.11. v1.Capabilities	1629
3.3.12. v1.Capability	1630
3.3.13. v1.CephFSVolumeSource	1630
3.3.14. v1.CinderVolumeSource	1631
3.3.15. v1.ComponentCondition	1632
3.3.16. v1.ComponentStatus	1633
3.3.17. v1.ComponentStatusList	1635
3.3.18. v1.ConfigMap	1636
3.3.19. v1.ConfigMapEnvSource	1638
3.3.20. v1.ConfigMapKeySelector	1638
3.3.21. v1.ConfigMapList	1639
3.3.22. v1.ConfigMapProjection	1640
3.3.23. v1.ConfigMapVolumeSource	1641
3.3.24. v1.Container	1643
3.3.25. v1.ContainerImage	1652
3.3.26. v1.ContainerPort	1653
3.3.27. v1.ContainerState	1654
3.3.28. v1.ContainerStateRunning	1654
3.3.29. v1.ContainerStateTerminated	1655
3.3.30. v1.ContainerStateWaiting	1655
3.3.31. v1.ContainerStatus	1656
3.3.32. v1.DaemonEndpoint	1657
3.3.33. v1.DeleteOptions	1658
3.3.34. v1.DeletionPropagation	1660
3.3.35. v1.DeprecatedDownwardAPIVolumeFile	1661
3.3.36. v1.DeprecatedDownwardAPIVolumeSource	1662
3.3.37. v1.DownwardAPIProjection	1663
3.3.38. v1.DownwardAPIVolumeFile	1663
3.3.39. v1.DownwardAPIVolumeSource	1665
3.3.40. v1.EmptyDirVolumeSource	1666
3.3.41. v1.EndpointAddress	1666
3.3.42. v1.EndpointPort	1667
3.3.43. v1.EndpointSubset	1668
3.3.44. v1.Endpoints	1669

3.3.45. v1.EndpointsList	1671
3.3.46. v1.EnvFromSource	1673
3.3.47. v1.EnvVar	1673
3.3.48. v1.EnvVarSource	1674
3.3.49. v1.Event	1675
3.3.50. v1.EventList	1678
3.3.51. v1.EventSource	1679
3.3.52. v1.ExecAction	1679
3.3.53. v1.FCVolumeSource	1680
3.3.54. v1.FSGroupStrategyOptions	1681
3.3.55. v1.FSType	1681
3.3.56. v1.FinalizerName	1681
3.3.57. v1.FlexVolumeSource	1682
3.3.58. v1.FlockerVolumeSource	1683
3.3.59. v1.GCEPersistentDiskVolumeSource	1683
3.3.60. v1.GitRepoVolumeSource	1685
3.3.61. v1.GlusterfsVolumeSource	1686
3.3.62. v1.HTTPGetAction	1687
3.3.63. v1.HTTPHeader	1688
3.3.64. v1.Handler	1688
3.3.65. v1.HostPathVolumeSource	1689
3.3.66. v1.IDRange	1689
3.3.67. v1.ISCSIVolumeSource	1689
3.3.68. v1.KeyToPath	1691
3.3.69. v1.LabelSelector	1692
3.3.70. v1.LabelSelectorRequirement	1693
3.3.71. v1.Lifecycle	1694
3.3.72. v1.LimitRange	1695
3.3.73. v1.LimitRangeItem	1697
3.3.74. v1.LimitRangeList	1698
3.3.75. v1.LimitRangeSpec	1699
3.3.76. v1.ListMeta	1700
3.3.77. v1.LoadBalancerIngress	1700
3.3.78. v1.LoadBalancerStatus	1701
3.3.79. v1.LocalObjectReference	1701
3.3.80. v1.NFSVolumeSource	1702
3.3.81. v1.Namespace	1702
3.3.82. v1.NamespaceList	1704
3.3.83. v1.NamespaceSpec	1706
3.3.84. v1.NamespaceStatus	1706
3.3.85. v1.Node	1706
3.3.86. v1.NodeAddress	1708
3.3.87. v1.NodeAffinity	1708
3.3.88. v1.NodeCondition	1710
3.3.89. v1.NodeDaemonEndpoints	1711
3.3.90. v1.NodeList	1711
3.3.91. v1.NodeSelector	1713
3.3.92. v1.NodeSelectorRequirement	1713
3.3.93. v1.NodeSelectorTerm	1714
3.3.94. v1.NodeSpec	1714
3.3.95. v1.NodeStatus	1715
3.3.96. v1.NodeSystemInfo	1717
3.3.97. v1.ObjectFieldSelector	1719

3.3.98. v1.ObjectMeta	1720
3.3.99. v1.ObjectReference	1729
3.3.100. v1.OwnerReference	1731
3.3.101. v1.Patch	1733
3.3.102. v1.PersistentVolume	1733
3.3.103. v1.PersistentVolumeAccessMode	1735
3.3.104. v1.PersistentVolumeClaim	1735
3.3.105. v1.PersistentVolumeClaimList	1737
3.3.106. v1.PersistentVolumeClaimSpec	1739
3.3.107. v1.PersistentVolumeClaimStatus	1740
3.3.108. v1.PersistentVolumeClaimVolumeSource	1741
3.3.109. v1.PersistentVolumeList	1741
3.3.110. v1.PersistentVolumeSpec	1743
3.3.111. v1.PersistentVolumeStatus	1750
3.3.112. v1.PhotonPersistentDiskVolumeSource	1750
3.3.113. v1.Pod	1751
3.3.114. v1.PodAffinity	1753
3.3.115. v1.PodAffinityTerm	1755
3.3.116. v1.PodAntiAffinity	1757
3.3.117. v1.PodCondition	1760
3.3.118. v1.PodList	1761
3.3.119. v1.PodSecurityContext	1763
3.3.120. v1.PodSpec	1765
3.3.121. v1.PodStatus	1773
3.3.122. v1.PodTemplate	1776
3.3.123. v1.PodTemplateList	1777
3.3.124. v1.PodTemplateSpec	1779
3.3.125. v1.PortworxVolumeSource	1779
3.3.126. v1.Preconditions	1780
3.3.127. v1.PreferredSchedulingTerm	1780
3.3.128. v1.Probe	1781
3.3.129. v1.ProjectedVolumeSource	1782
3.3.130. v1.QuobyteVolumeSource	1783
3.3.131. v1.RBDVolumeSource	1784
3.3.132. v1.ReplicationController	1786
3.3.133. v1.ReplicationControllerCondition	1789
3.3.134. v1.ReplicationControllerList	1790
3.3.135. v1.ReplicationControllerSpec	1791
3.3.136. v1.ReplicationControllerStatus	1793
3.3.137. v1.ResourceFieldSelector	1795
3.3.138. v1.ResourceQuota	1795
3.3.139. v1.ResourceQuotaList	1797
3.3.140. v1.ResourceQuotaScope	1798
3.3.141. v1.ResourceQuotaSpec	1798
3.3.142. v1.ResourceQuotaStatus	1799
3.3.143. v1.ResourceRequirements	1800
3.3.144. v1.RunAsUserStrategyOptions	1800
3.3.145. v1.SELinuxContextStrategyOptions	1801
3.3.146. v1.SELinuxOptions	1802
3.3.147. v1.Scale	1802
3.3.148. v1.ScaleIOVolumeSource	1804
3.3.149. v1.ScaleSpec	1806
3.3.150. v1.ScaleStatus	1806

3.3.151. v1.Secret	1807
3.3.152. v1.SecretEnvSource	1809
3.3.153. v1.SecretKeySelector	1810
3.3.154. v1.SecretList	1810
3.3.155. v1.SecretProjection	1812
3.3.156. v1.SecretVolumeSource	1813
3.3.157. v1.SecurityContext	1815
3.3.158. v1.SecurityContextConstraints	1818
3.3.159. v1.SecurityContextConstraintsList	1824
3.3.160. v1.Service	1826
3.3.161. v1.ServiceAccount	1828
3.3.162. v1.ServiceAccountList	1830
3.3.163. v1.ServiceList	1832
3.3.164. v1.ServicePort	1833
3.3.165. v1.ServiceSpec	1836
3.3.166. v1.ServiceStatus	1843
3.3.167. v1.Status	1843
3.3.168. v1.StatusCause	1846
3.3.169. v1.StatusDetails	1847
3.3.170. v1.SupplementalGroupsStrategyOptions	1849
3.3.171. v1.TCPSocketAction	1849
3.3.172. v1.Taint	1850
3.3.173. v1.Toleration	1851
3.3.174. v1.UniqueVolumeName	1852
3.3.175. v1.Volume	1852
3.3.176. v1.VolumeMount	1859
3.3.177. v1.VolumeProjection	1860
3.3.178. v1.VsphereVirtualDiskVolumeSource	1860
3.3.179. v1.WatchEvent	1861
3.3.180. v1.WeightedPodAffinityTerm	1861
3.3.181. v1beta1.Eviction	1861

CHAPTER 1. OVERVIEW

The OpenShift Dedicated distribution of Kubernetes includes the [Kubernetes v1 REST API](#) and the [OpenShift v1 REST API](#). These are RESTful APIs accessible via HTTP(s) on the OpenShift Dedicated master servers.

These REST APIs can be used to manage end-user applications, the cluster, and the users of the cluster.

1.1. AUTHENTICATION

API calls must be authenticated with an access token or X.509 certificate. See [Authentication](#) in the Architecture documentation for an overview.

This section highlights the token authentication method. With token authentication, a bearer token must be passed in as an [HTTP Authorization header](#). There are two types of access tokens: session and service account.

1.1.1. Session Tokens

A *session token* is short-lived, expiring within 24 hours by default. It represents [a user](#). After logging in, the session token may be obtained with the `oc whoami` command:

```
$ oc login -u test_user
Using project "test".
$ oc whoami --token
dIAo76N-W-GXK3S_w_KsC6DmH3MzP79zq7jbMQvCOUo
```

1.1.2. Service Account Tokens

Service account tokens are long-lived tokens. They are [JSON Web Token \(JWT\)](#) formatted tokens and are much longer strings than session tokens. See [Using a Service Account's Credentials Externally](#) for steps on using these tokens to authenticate using the CLI.

A service account token may be obtained with these commands:

1. Create a service account in the current project (**test**) named **robot**:

```
$ oc create serviceaccount robot
serviceaccount "robot" created
```

2. Grant a role to the service account. In this example, assign the **robot** service account in the **test** project the **admin** role:

```
$ oc policy add-role-to-user admin system:serviceaccounts:test:robot
```

3. Get the token value:

```
$ oc serviceaccounts get-token robot
eyJhbGciOiJIUzI1NiIsInR5cCI6IkpXVCJ9.eyJpc3MiOiJrdWJlcm5ldGVzL3NlcnZpY2VhY2NvdW50Iiwia3ViZXJuZXRlcy5pby9zZXJ2aWNlYWNjb3VudC9uYW1lc3BhY2UiOiJpc3YtY2VydCI6Imt1YmVybWV0ZXMuw8vc2VydmljZWZjY291bnQvc2VjcmV0Lm5
```

```

hbWUi0iJpbWctYnVpbGQtdG9rZW4teG1rMHciLCJrdWJlcm5ldGVzLmlvL3NlcnZpY2V
hY2NvdW50L3NlcnZpY2UtYWVjb3VudC5uYWw1IjoiaWlnLWJ1aWxkIiwia3ViZXJvZXR
lcy5pby9zZXJ2aWNlYWVjb3VudC9zZXJ2aWNlLWFjY291bnQudWlkIjoiTmZmM0NWM
tNDA4Zi0xMWU3LTg1NTktMDAxYTRhZTBkZjQ1Iiwic3ViIjoic3lzdGVtOnNlcnZpY2V
hY2NvdW50Omlzdi1jZXJ0OmltZy1idWlsZCJ9.Xt5cc9k7fucc7ZAYqt6cz6WvyDhbCZ
cfHXH-0w6vStI4Gy7dS3qxIewcXfw8-
h1_wkLRUYvyVVYDCRIIbmWL68ybzY2ND8FyuQwCOWP-2_vFvm8xmpjFURZwuNv-
eGULNwz0frSCiElqM2ImCYcM3tpbnyMPeW_KoSI4LGKxXZZqBIcpa9Xb0Zr225uhpZJ2
tb_Ituqd0XPUC0GZdHbpbCI0I-Yu-
IudCRBHZZ_2SlAi3vbJcvmjpxHfaz49enR602S8ztXF4gXG4_lXa0fS5QYtB0lnIv9q8
HXzxKioG_P301yD1HqdLYXhZaMNDyg1Xm-5hAkfQ4A7UMPgK4a2zg

```

The token value may be used as an in an authorization header to [authenticate API calls](#), the [CLI](#) or in the [docker login command](#). Service accounts may be created and deleted as needed with the appropriate role(s) assigned. See [Authorization](#) in the Architecture documentation for a deeper discussion on roles.

1.2. EXAMPLES

These examples provide a quick reference for making successful REST API calls. They use insecure methods. In these examples, a simple **GET** call is made to [list available resources](#).

1.2.1. cURL

Example 1.1. Request (Insecure)

```

$ curl -X GET -H "Authorization: Bearer <token>"
https://openshift.redhat.com:8443/oapi/v1 --insecure

```

Example 1.2. Result (Truncated)

```

{
  "kind": "APIResourceList",
  "groupVersion": "v1",
  "resources": [
    {
      "name": "buildconfigs",
      "namespaced": true,
      "kind": "BuildConfig"
    },
    {
      "name": "buildconfigs/instantiate",
      "namespaced": true,
      "kind": "BuildRequest"
    },
    {
      "name": "buildconfigs/instantiatebinary",
      "namespaced": true,
      "kind": "BinaryBuildRequestOptions"
    },
    {
      "name": "buildconfigs/webhooks",
      "namespaced": true,

```

```

    "kind": "Status"
  },
  {
    "name": "builds",
    "namespaced": true,
    "kind": "Build"
  },
  ...
  {
    "name": "subjectaccessreviews",
    "namespaced": true,
    "kind": "SubjectAccessReview"
  },
  {
    "name": "templates",
    "namespaced": true,
    "kind": "Template"
  },
  {
    "name": "useridentitymappings",
    "namespaced": false,
    "kind": "UserIdentityMapping"
  },
  {
    "name": "users",
    "namespaced": false,
    "kind": "User"
  }
]
}

```

1.2.2. Python

Example 1.3. Interactive Python API Call Using "requests" Module (Insecure)

```

>>> import requests
>>> url = 'https://openshift.redhat.com:8443/oapi/v1'
>>> headers = {'Authorization': 'Bearer dIAo76N-W-
GXX3S_w_KsC6DmH3MzP79zq7jbMQvCOUo'}
>>> requests.get(url, headers=headers, verify=False)
/usr/lib/python2.7/site-
packages/requests/packages/urllib3/connectionpool.py:791:
InsecureRequestWarning: Unverified HTTPS request is being made. Adding
certificate verification is strongly advised. See:
https://urllib3.readthedocs.org/en/latest/security.html
  InsecureRequestWarning)
<Response [200]>

```

1.2.3. Docker Login

The OpenShift Dedicated integrated Docker registry must be authenticated using either a [user session](#) or [service account](#) token. The value of the token must be used as the value for the **--password** argument. The user and email argument values are ignored:

```
$ docker login -p <token_value> -u unused -e unused <registry>[:<port>]
```

1.3. WEBSOCKETS AND WATCHING FOR CHANGES

The API is designed to work via the [websocket protocol](#). API requests may take the form of "one-shot" calls to list resources or by passing in query parameter **watch=true**. When watching an endpoint, changes to the system may be observed through an open endpoint. Using callbacks, dynamic systems may be developed that integrate with the API.

For more information and examples, see the Mozilla Developer Network page on [Writing WebSocket client applications](#).

CHAPTER 2. OPENSIFT DEDICATED V1 REST API

2.1. OVERVIEW

The OpenShift API exposes operations for managing an enterprise Kubernetes cluster, including security and user management, application deployments, image and source builds, HTTP(s) routing, and project management.

2.1.1. Version information

Version: v1

2.1.2. URI scheme

Host: 127.0.0.1:8443 BasePath: / Schemes: HTTPS

2.2. PATHS

2.2.1. get available resources

GET /oapi/v1

2.2.1.1. Responses

HTTP Code	Description	Schema
default	success	Section 2.3.5, "v1.APIResourceList"

2.2.1.2. Consumes

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.1.3. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.1.4. Tags

- oapiv1

2.2.2. list objects of kind `AppliedClusterResourceQuota`

GET /oapi/v1/appliedclusterresourcequotas

2.2.2.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParameter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParameter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParameter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParameter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParamter	resourceVersion	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParamter	timeoutSeconds	Timeout for the list/watch call.	false	integer	

2.2.2.2. Responses

HTTP Code	Description	Schema
-----------	-------------	--------

HTTP Code	Description	Schema
200	success	Section 2.3.9, "v1.AppliedClusterResourceQuotaList"

2.2.2.3. Consumes

- /

2.2.2.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf
- application/json;stream=watch
- application/vnd.kubernetes.protobuf;stream=watch

2.2.2.5. Tags

- oapiv1

2.2.3. list or watch objects of kind BuildConfig

GET /oapi/v1/buildconfigs

2.2.3.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParam ter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParam ter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParam ter	resourceVersi on	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParam ter	timeoutSecon ds	Timeout for the list/watch call.	false	integer	

2.2.3.2. Responses

HTTP Code	Description	Schema
-----------	-------------	--------

HTTP Code	Description	Schema
200	success	Section 2.3.17, "v1.BuildConfigList"

2.2.3.3. Consumes

- /

2.2.3.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf
- application/json;stream=watch
- application/vnd.kubernetes.protobuf;stream=watch

2.2.3.5. Tags

- oapiv1

2.2.4. create a BuildConfig

POST /oapi/v1/buildconfigs

2.2.4.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParameter	body		true	Section 2.3.16, "v1.BuildConfig"	

2.2.4.2. Responses

HTTP Code	Description	Schema
-----------	-------------	--------

HTTP Code	Description	Schema
200	success	Section 2.3.16, "v1.BuildConfig"

2.2.4.3. Consumes

- /

2.2.4.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.4.5. Tags

- oapiv1

2.2.5. list or watch objects of kind Build

GET /oapi/v1/builds

2.2.5.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParameter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParameter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParam ter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParam ter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParamter	resourceVersion	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParamter	timeoutSeconds	Timeout for the list/watch call.	false	integer	

2.2.5.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.20, "v1.BuildList"

2.2.5.3. Consumes

- /

2.2.5.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf
- application/json;stream=watch
- application/vnd.kubernetes.protobuf;stream=watch

2.2.5.5. Tags

- oapiv1

2.2.6. create a Build

POST /oapi/v1/builds

2.2.6.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParameter	body		true	Section 2.3.15, "v1.Build"	

2.2.6.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.15, "v1.Build"

2.2.6.3. Consumes

- /

2.2.6.4. Produces

- application/json

- application/yaml
- application/vnd.kubernetes.protobuf

2.2.6.5. Tags

- oapiv1

2.2.7. list or watch objects of kind ClusterNetwork

GET /oapi/v1/clusternetworks

2.2.7.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParam eter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParam eter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParam eter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParamter	resourceVersion	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParamter	timeoutSeconds	Timeout for the list/watch call.	false	integer	

2.2.7.2. Responses

HTTP Code	Description	Schema
-----------	-------------	--------

HTTP Code	Description	Schema
200	success	Section 2.3.38 , "v1.ClusterNetworkList"

2.2.7.3. Consumes

- /

2.2.7.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf
- application/json;stream=watch
- application/vnd.kubernetes.protobuf;stream=watch

2.2.7.5. Tags

- oapiv1

2.2.8. create a ClusterNetwork

POST /oapi/v1/clusternetworks

2.2.8.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParameter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParameter	body		true	Section 2.3.37 , "v1.ClusterNetwork"	

2.2.8.2. Responses

HTTP Code	Description	Schema
-----------	-------------	--------

HTTP Code	Description	Schema
200	success	Section 2.3.37, "v1.ClusterNetwork"

2.2.8.3. Consumes

- /

2.2.8.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.8.5. Tags

- oapiv1

2.2.9. delete collection of ClusterNetwork

DELETE /oapi/v1/clusternetworks

2.2.9.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParam eter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParam ter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParam ter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParamter	resourceVersion	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParamter	timeoutSeconds	Timeout for the list/watch call.	false	integer	

2.2.9.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.264, "v1.Status"

2.2.9.3. Consumes

- /

2.2.9.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.9.5. Tags

- oapiv1

2.2.10. read the specified ClusterNetwork

```
GET /oapi/v1/clusternetworks/{name}
```

2.2.10.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParam eter	export	Should this value be exported. Export strips fields that a user can not specify.	false	boolean	
QueryParam eter	exact	Should the export be exact. Exact export maintains cluster-specific fields like 'Namespace'.	false	boolean	
PathParamet er	name	name of the ClusterNetwo rk	true	string	

2.2.10.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.37 , "v1.ClusterNetwork"

2.2.10.3. Consumes

- /

2.2.10.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.10.5. Tags

- oapiv1

2.2.11. partially update the specified ClusterNetwork

PATCH /oapi/v1/clusternetworks/{name}

2.2.11.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamet er	body		true	Section 2.3.180 , "v1.Patch"	
PathParamet er	name	name of the ClusterNetwo rk	true	string	

2.2.11.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.37, "v1.ClusterNetwork"

2.2.11.3. Consumes

- application/json-patch+json
- application/merge-patch+json
- application/strategic-merge-patch+json

2.2.11.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.11.5. Tags

- oapiv1

2.2.12. replace the specified ClusterNetwork

```
PUT /oapi/v1/clusternetworks/{name}
```

2.2.12.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParameter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParameter	body		true	Section 2.3.37, "v1.ClusterNetwork"	
PathParameter	name	name of the ClusterNetwork	true	string	

2.2.12.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.37 , "v1.ClusterNetwork"

2.2.12.3. Consumes

- /

2.2.12.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.12.5. Tags

- oapiv1

2.2.13. delete a ClusterNetwork

DELETE /oapi/v1/clusternetworks/{name}

2.2.13.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamet er	body		true	Section 2.3.61 , "v1.DeleteOptions"	

Type	Name	Description	Required	Schema	Default
QueryParam ter	gracePeriodS econds	The duration in seconds before the object should be deleted. Value must be non-negative integer. The value zero indicates delete immediately. If this value is nil, the default grace period for the specified type will be used. Defaults to a per object value if not specified. zero means delete immediately.	false	integer	

Type	Name	Description	Required	Schema	Default
QueryParam ter	orphanDepen dents	Deprecated: please use the PropagationP olicy, this field will be deprecated in 1.7. Should the dependent objects be orphaned. If true/false, the "orphan" finalizer will be added to/removed from the object's finalizers list. Either this field or PropagationP olicy may be set, but not both.	false	boolean	
QueryParam ter	propagationP olicy	Whether and how garbage collection will be performed. Either this field or OrphanDepen dents may be set, but not both. The default policy is decided by the existing finalizer set in the metadata.fin alizers and the resource- specific default policy.	false	string	

Type	Name	Description	Required	Schema	Default
PathParamet er	name	name of the ClusterNetwo rk	true	string	

2.2.13.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.264, "v1.Status"

2.2.13.3. Consumes

- /

2.2.13.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.13.5. Tags

- oapiv1

2.2.14. list or watch objects of kind ClusterPolicy

GET /oapi/v1/clusterpolicies

2.2.14.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParame ter	pretty	If 'true', then the output is pretty printed.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParam ter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParam ter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParam ter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParamter	resourceVersion	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParamter	timeoutSeconds	Timeout for the list/watch call.	false	integer	

2.2.14.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.42, "v1.ClusterPolicyList"

2.2.14.3. Consumes

- /

2.2.14.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf
- application/json;stream=watch
- application/vnd.kubernetes.protobuf;stream=watch

2.2.14.5. Tags

- oapiv1

2.2.15. create a ClusterPolicy

POST /oapi/v1/clusterpolicies

2.2.15.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParameter	body		true	Section 2.3.39 , "v1.ClusterPolicy"	

2.2.15.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.39 , "v1.ClusterPolicy"

2.2.15.3. Consumes

- /

2.2.15.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.15.5. Tags

- oapiv1

2.2.16. delete collection of ClusterPolicy

```
DELETE /oapi/v1/clusterpolicies
```

2.2.16.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParam eter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParam eter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParam ter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParam ter	resourceVersi on	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParam ter	timeoutSecon ds	Timeout for the list/watch call.	false	integer	

2.2.16.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.264, "v1.Status"

2.2.16.3. Consumes

- /

2.2.16.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.16.5. Tags

- oapiv1

2.2.17. read the specified ClusterPolicy

```
GET /oapi/v1/clusterpolicies/{name}
```

2.2.17.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParam eter	export	Should this value be exported. Export strips fields that a user can not specify.	false	boolean	
QueryParam eter	exact	Should the export be exact. Exact export maintains cluster-specific fields like 'Namespace'.	false	boolean	
PathParamet er	name	name of the ClusterPolicy	true	string	

2.2.17.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.39, "v1.ClusterPolicy"

2.2.17.3. Consumes

- /

2.2.17.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.17.5. Tags

- oapiv1

2.2.18. partially update the specified ClusterPolicy

```
PATCH /oapi/v1/clusterpolicies/{name}
```

2.2.18.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParameter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParameter	body		true	Section 2.3.180, "v1.Patch"	
PathParameter	name	name of the ClusterPolicy	true	string	

2.2.18.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.39, "v1.ClusterPolicy"

2.2.18.3. Consumes

- application/json-patch+json
- application/merge-patch+json
- application/strategic-merge-patch+json

2.2.18.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.18.5. Tags

- oapiv1

2.2.19. replace the specified ClusterPolicy

```
PUT /oapi/v1/clusterpolicies/{name}
```

2.2.19.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamet er	body		true	Section 2.3.39 , "v1.ClusterPo licy"	
PathParamet er	name	name of the ClusterPolicy	true	string	

2.2.19.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.39 , "v1.ClusterPolicy"

2.2.19.3. Consumes

- /

2.2.19.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.19.5. Tags

- oapiv1

2.2.20. delete a ClusterPolicy

```
DELETE /oapi/v1/clusterpolicies/{name}
```

2.2.20.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamet er	body		true	Section 2.3.6 1, "v1.DeleteOptions"	

Type	Name	Description	Required	Schema	Default
QueryParam ter	gracePeriodS econds	The duration in seconds before the object should be deleted. Value must be non-negative integer. The value zero indicates delete immediately. If this value is nil, the default grace period for the specified type will be used. Defaults to a per object value if not specified. zero means delete immediately.	false	integer	

Type	Name	Description	Required	Schema	Default
QueryParam eter	orphanDepen dents	Deprecated: please use the PropagationP olicy, this field will be deprecated in 1.7. Should the dependent objects be orphaned. If true/false, the "orphan" finalizer will be added to/removed from the object's finalizers list. Either this field or PropagationP olicy may be set, but not both.	false	boolean	
QueryParam eter	propagationP olicy	Whether and how garbage collection will be performed. Either this field or OrphanDepen dents may be set, but not both. The default policy is decided by the existing finalizer set in the metadata.fin alizers and the resource- specific default policy.	false	string	
PathParamet er	name	name of the ClusterPolicy	true	string	

2.2.20.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.264, "v1.Status"

2.2.20.3. Consumes

- /

2.2.20.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.20.5. Tags

- oapiv1

2.2.21. list or watch objects of kind ClusterPolicyBinding

GET /oapi/v1/clusterpolicybindings

2.2.21.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParam eter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParam ter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParam ter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParamter	resourceVersion	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParamter	timeoutSeconds	Timeout for the list/watch call.	false	integer	

2.2.21.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.41, "v1.ClusterPolicyBindingList"

2.2.21.3. Consumes

- /

2.2.21.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf
- application/json;stream=watch
- application/vnd.kubernetes.protobuf;stream=watch

2.2.21.5. Tags

- oapiv1

2.2.22. create a ClusterPolicyBinding

POST /oapi/v1/clusterpolicybindings

2.2.22.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParameter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParameter	body		true	Section 2.3.40 , "v1.ClusterPolicyBinding"	

2.2.22.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.40 , "v1.ClusterPolicyBinding"

2.2.22.3. Consumes

- /

2.2.22.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.22.5. Tags

- oapiv1

2.2.23. delete collection of ClusterPolicyBinding

```
DELETE /oapi/v1/clusterpolicybindings
```

2.2.23.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParam eter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParam eter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParam ter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParamter	resourceVersion	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParamter	timeoutSeconds	Timeout for the list/watch call.	false	integer	

2.2.23.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.264, "v1.Status"

2.2.23.3. Consumes

- /

2.2.23.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.23.5. Tags

- oapiv1

2.2.24. read the specified ClusterPolicyBinding

```
GET /oapi/v1/clusterpolicybindings/{name}
```

2.2.24.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParam eter	export	Should this value be exported. Export strips fields that a user can not specify.	false	boolean	
QueryParam eter	exact	Should the export be exact. Exact export maintains cluster-specific fields like 'Namespace'.	false	boolean	
PathParamet er	name	name of the ClusterPolicy Binding	true	string	

2.2.24.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.40, "v1.ClusterPolicyBinding"

2.2.24.3. Consumes

- /

2.2.24.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.24.5. Tags

- oapiv1

2.2.25. partially update the specified ClusterPolicyBinding

PATCH /oapi/v1/clusterpolicybindings/{name}

2.2.25.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamet er	body		true	Section 2.3.180, "v1.Patch"	
PathParamet er	name	name of the ClusterPolicy Binding	true	string	

2.2.25.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.40, "v1.ClusterPolicyBinding"

2.2.25.3. Consumes

- application/json-patch+json
- application/merge-patch+json
- application/strategic-merge-patch+json

2.2.25.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.25.5. Tags

- oapiv1

2.2.26. replace the specified ClusterPolicyBinding

```
PUT /oapi/v1/clusterpolicybindings/{name}
```

2.2.26.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamet er	body		true	Section 2.3.40, "v1.ClusterPolicyBinding"	
PathParamet er	name	name of the ClusterPolicy Binding	true	string	

2.2.26.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.40, "v1.ClusterPolicyBinding"

2.2.26.3. Consumes

- /

2.2.26.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.26.5. Tags

- oapiv1

2.2.27. delete a ClusterPolicyBinding

```
DELETE /oapi/v1/clusterpolicybindings/{name}
```

2.2.27.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamet er	body		true	Section 2.3.61, "v1.DeleteOptions"	

Type	Name	Description	Required	Schema	Default
QueryParam ter	gracePeriodS econds	The duration in seconds before the object should be deleted. Value must be non-negative integer. The value zero indicates delete immediately. If this value is nil, the default grace period for the specified type will be used. Defaults to a per object value if not specified. zero means delete immediately.	false	integer	

Type	Name	Description	Required	Schema	Default
QueryParam ter	orphanDepen dents	Deprecated: please use the PropagationP olicy, this field will be deprecated in 1.7. Should the dependent objects be orphaned. If true/false, the "orphan" finalizer will be added to/removed from the object's finalizers list. Either this field or PropagationP olicy may be set, but not both.	false	boolean	
QueryParam ter	propagationP olicy	Whether and how garbage collection will be performed. Either this field or OrphanDepen dents may be set, but not both. The default policy is decided by the existing finalizer set in the metadata.fin alizers and the resource- specific default policy.	false	string	

Type	Name	Description	Required	Schema	Default
PathParam eter	name	name of the ClusterPolicy Binding	true	string	

2.2.27.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.264, "v1.Status"

2.2.27.3. Consumes

- /

2.2.27.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.27.5. Tags

- oapiv1

2.2.28. list or watch objects of kind ClusterResourceQuota

GET /oapi/v1/clusterresourcequotas

2.2.28.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParam ter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParam ter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParam ter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParam eter	resourceVersi on	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParam eter	timeoutSecon ds	Timeout for the list/watch call.	false	integer	

2.2.28.2. Responses

HTTP Code	Description	Schema
-----------	-------------	--------

HTTP Code	Description	Schema
200	success	Section 2.3.44 , "v1.ClusterResourceQuotaList"

2.2.28.3. Consumes

- /

2.2.28.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf
- application/json;stream=watch
- application/vnd.kubernetes.protobuf;stream=watch

2.2.28.5. Tags

- oapiv1

2.2.29. create a ClusterResourceQuota

POST /oapi/v1/clusterresourcequotas

2.2.29.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamenter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParameter	body		true	Section 2.3.43 , "v1.ClusterResourceQuota"	

2.2.29.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.43, "v1.ClusterResourceQuota"

2.2.29.3. Consumes

- /

2.2.29.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.29.5. Tags

- oapiv1

2.2.30. delete collection of ClusterResourceQuota

DELETE /oapi/v1/clusterresourcequotas

2.2.30.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParam eter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParam ter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParam ter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParam ter	resourceVersi on	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParam ter	timeoutSecon ds	Timeout for the list/watch call.	false	integer	

2.2.30.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.264, "v1.Status"

2.2.30.3. Consumes

- /

2.2.30.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.30.5. Tags

- oapiv1

2.2.31. read the specified ClusterResourceQuota

```
GET /oapi/v1/clusterresourcequotas/{name}
```

2.2.31.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParam eter	export	Should this value be exported. Export strips fields that a user can not specify.	false	boolean	
QueryParam eter	exact	Should the export be exact. Exact export maintains cluster-specific fields like 'Namespace'.	false	boolean	
PathParamet er	name	name of the ClusterResourceQuota	true	string	

2.2.31.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.43, "v1.ClusterResourceQuota"

2.2.31.3. Consumes

- /

2.2.31.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.31.5. Tags

- oapiv1

2.2.32. partially update the specified ClusterResourceQuota

PATCH /oapi/v1/clusterresourcequotas/{name}

2.2.32.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamet er	body		true	Section 2.3.180, "v1.Patch"	
PathParamet er	name	name of the ClusterResourceQuota	true	string	

2.2.32.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.43, "v1.ClusterResourceQuota"

2.2.32.3. Consumes

- application/json-patch+json
- application/merge-patch+json
- application/strategic-merge-patch+json

2.2.32.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.32.5. Tags

- oapiv1

2.2.33. replace the specified ClusterResourceQuota

```
PUT /oapi/v1/clusterresourcequotas/{name}
```

2.2.33.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamenter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParameter	body		true	Section 2.3.43, "v1.ClusterResourceQuota"	
PathParamenter	name	name of the ClusterResourceQuota	true	string	

2.2.33.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.43 , “v1.ClusterResourceQuota”

2.2.33.3. Consumes

- /

2.2.33.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.33.5. Tags

- oapiv1

2.2.34. delete a ClusterResourceQuota

```
DELETE /oapi/v1/clusterresourcequotas/{name}
```

2.2.34.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamet er	body		true	Section 2.3.61 , “v1.DeleteOptions”	

Type	Name	Description	Required	Schema	Default
QueryParam ter	gracePeriodS econds	The duration in seconds before the object should be deleted. Value must be non-negative integer. The value zero indicates delete immediately. If this value is nil, the default grace period for the specified type will be used. Defaults to a per object value if not specified. zero means delete immediately.	false	integer	

Type	Name	Description	Required	Schema	Default
QueryParam eter	orphanDepen dents	Deprecated: please use the PropagationP olicy, this field will be deprecated in 1.7. Should the dependent objects be orphaned. If true/false, the "orphan" finalizer will be added to/removed from the object's finalizers list. Either this field or PropagationP olicy may be set, but not both.	false	boolean	
QueryParam eter	propagationP olicy	Whether and how garbage collection will be performed. Either this field or OrphanDepen dents may be set, but not both. The default policy is decided by the existing finalizer set in the metadata.fin alizers and the resource- specific default policy.	false	string	

Type	Name	Description	Required	Schema	Default
PathParamet er	name	name of the ClusterResourceQuota	true	string	

2.2.34.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.264, "v1.Status"

2.2.34.3. Consumes

- /

2.2.34.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.34.5. Tags

- oapiv1

2.2.35. read status of the specified ClusterResourceQuota

GET /oapi/v1/clusterresourcequotas/{name}/status

2.2.35.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
PathParamet er	name	name of the ClusterResourceQuota	true	string	

2.2.35.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.43 , "v1.ClusterResourceQuota"

2.2.35.3. Consumes

- /

2.2.35.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.35.5. Tags

- oapiv1

2.2.36. partially update status of the specified ClusterResourceQuota

PATCH /oapi/v1/clusterresourcequotas/{name}/status

2.2.36.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamet er	body		true	Section 2.3.180 , "v1.Patch"	
PathParamet er	name	name of the ClusterResou rceQuota	true	string	

2.2.36.2. Responses

HTTP Code	Description	Schema
-----------	-------------	--------

HTTP Code	Description	Schema
200	success	Section 2.3.43, "v1.ClusterResourceQuota"

2.2.36.3. Consumes

- application/json-patch+json
- application/merge-patch+json
- application/strategic-merge-patch+json

2.2.36.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.36.5. Tags

- oapiv1

2.2.37. replace status of the specified ClusterResourceQuota

```
PUT /oapi/v1/clusterresourcequotas/{name}/status
```

2.2.37.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamenter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParameter	body		true	Section 2.3.43, "v1.ClusterResourceQuota"	
PathParamenter	name	name of the ClusterResourceQuota	true	string	

2.2.37.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.43, "v1.ClusterResourceQuota"

2.2.37.3. Consumes

- /

2.2.37.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.37.5. Tags

- oapiv1

2.2.38. list objects of kind ClusterRoleBinding

GET /oapi/v1/clusterrolebindings

2.2.38.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParam eter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParam ter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParam ter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParamter	resourceVersion	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParamter	timeoutSeconds	Timeout for the list/watch call.	false	integer	

2.2.38.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.50, "v1.ClusterRoleBindingList"

2.2.38.3. Consumes

- /

2.2.38.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf
- application/json;stream=watch
- application/vnd.kubernetes.protobuf;stream=watch

2.2.38.5. Tags

- oapiv1

2.2.39. create a ClusterRoleBinding

POST /oapi/v1/clusterrolebindings

2.2.39.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParameter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParameter	body		true	Section 2.3.49 , "v1.ClusterRoleBinding"	

2.2.39.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.49 , "v1.ClusterRoleBinding"

2.2.39.3. Consumes

- /

2.2.39.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.39.5. Tags

- oapiv1

2.2.40. read the specified ClusterRoleBinding

```
GET /oapi/v1/clusterrolebindings/{name}
```

2.2.40.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
PathParam eter	name	name of the ClusterRoleBinding	true	string	

2.2.40.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.49, "v1.ClusterRoleBinding"

2.2.40.3. Consumes

- /

2.2.40.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.40.5. Tags

- oapiv1

2.2.41. partially update the specified ClusterRoleBinding

PATCH /oapi/v1/clusterrolebindings/{name}

2.2.41.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamet er	body		true	Section 2.3.180 , "v1.Patch"	
PathParamet er	name	name of the ClusterRoleBi nding	true	string	

2.2.41.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.49 , "v1.ClusterRoleBinding"

2.2.41.3. Consumes

- application/json-patch+json
- application/merge-patch+json
- application/strategic-merge-patch+json

2.2.41.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.41.5. Tags

- oapiv1

2.2.42. replace the specified ClusterRoleBinding

■

```
PUT /oapi/v1/clusterrolebindings/{name}
```

2.2.42.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParameter	body		true	Section 2.3.49 , "v1.ClusterRoleBinding"	
PathParamter	name	name of the ClusterRoleBinding	true	string	

2.2.42.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.49 , "v1.ClusterRoleBinding"

2.2.42.3. Consumes

- /

2.2.42.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.42.5. Tags

- oapiv1

2.2.43. delete a ClusterRoleBinding

```
DELETE /oapi/v1/clusterrolebindings/{name}
```

2.2.43.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParameter	body		true	Section 2.3.6 1, "v1.DeleteOptions"	
QueryParamter	gracePeriodSeconds	The duration in seconds before the object should be deleted. Value must be non-negative integer. The value zero indicates delete immediately. If this value is nil, the default grace period for the specified type will be used. Defaults to a per object value if not specified. zero means delete immediately.	false	integer	

Type	Name	Description	Required	Schema	Default
QueryParam eter	orphanDepen dents	Deprecated: please use the PropagationP olicy, this field will be deprecated in 1.7. Should the dependent objects be orphaned. If true/false, the "orphan" finalizer will be added to/removed from the object's finalizers list. Either this field or PropagationP olicy may be set, but not both.	false	boolean	
QueryParam eter	propagationP olicy	Whether and how garbage collection will be performed. Either this field or OrphanDepen dents may be set, but not both. The default policy is decided by the existing finalizer set in the metadata.fin alizers and the resource- specific default policy.	false	string	

Type	Name	Description	Required	Schema	Default
PathParamet er	name	name of the ClusterRoleBinding	true	string	

2.2.43.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.264, "v1.Status"

2.2.43.3. Consumes

- /

2.2.43.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.43.5. Tags

- oapiv1

2.2.44. list objects of kind ClusterRole

GET /oapi/v1/clusterroles

2.2.44.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParam ter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParam ter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParam ter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParamter	resourceVersion	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParamter	timeoutSeconds	Timeout for the list/watch call.	false	integer	

2.2.44.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.51, "v1.ClusterRoleList"

2.2.44.3. Consumes

- /

2.2.44.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf
- application/json;stream=watch
- application/vnd.kubernetes.protobuf;stream=watch

2.2.44.5. Tags

- oapiv1

2.2.45. create a ClusterRole

POST /oapi/v1/clusterroles

2.2.45.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParameter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParameter	body		true	Section 2.3.48 , "v1.ClusterRole"	

2.2.45.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.48 , "v1.ClusterRole"

2.2.45.3. Consumes

- /

2.2.45.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.45.5. Tags

- oapiv1

2.2.46. read the specified ClusterRole

```
GET /oapi/v1/clusterroles/{name}
```

2.2.46.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam	pretty	If 'true', then the output is pretty printed.	false	string	
PathParameter	name	name of the ClusterRole	true	string	

2.2.46.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.48, "v1.ClusterRole"

2.2.46.3. Consumes

- /

2.2.46.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.46.5. Tags

- oapiv1

2.2.47. partially update the specified ClusterRole

PATCH /oapi/v1/clusterroles/{name}

2.2.47.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParameter	body		true	Section 2.3.180 , "v1.Patch"	
PathParamter	name	name of the ClusterRole	true	string	

2.2.47.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.48 , "v1.ClusterRole"

2.2.47.3. Consumes

- application/json-patch+json
- application/merge-patch+json
- application/strategic-merge-patch+json

2.2.47.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.47.5. Tags

- oapiv1

2.2.48. replace the specified ClusterRole

PUT /oapi/v1/clusterroles/{name}

■

2.2.48.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParameter	body		true	Section 2.3.48 , "v1.ClusterRole"	
PathParamter	name	name of the ClusterRole	true	string	

2.2.48.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.48 , "v1.ClusterRole"

2.2.48.3. Consumes

- /

2.2.48.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.48.5. Tags

- oapiv1

2.2.49. delete a ClusterRole

```
DELETE /oapi/v1/clusterroles/{name}
```

2.2.49.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParameter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParameter	body		true	Section 2.3.6 1, "v1.DeleteOptions"	
QueryParameter	gracePeriodSeconds	The duration in seconds before the object should be deleted. Value must be non-negative integer. The value zero indicates delete immediately. If this value is nil, the default grace period for the specified type will be used. Defaults to a per object value if not specified. zero means delete immediately.	false	integer	

Type	Name	Description	Required	Schema	Default
QueryParam ter	orphanDepen dents	Deprecated: please use the PropagationP olicy, this field will be deprecated in 1.7. Should the dependent objects be orphaned. If true/false, the "orphan" finalizer will be added to/removed from the object's finalizers list. Either this field or PropagationP olicy may be set, but not both.	false	boolean	
QueryParam ter	propagationP olicy	Whether and how garbage collection will be performed. Either this field or OrphanDepen dents may be set, but not both. The default policy is decided by the existing finalizer set in the metadata.fin alizers and the resource- specific default policy.	false	string	
PathParamet er	name	name of the ClusterRole	true	string	

2.2.49.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.264, "v1.Status"

2.2.49.3. Consumes

- /

2.2.49.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.49.5. Tags

- oapiv1

2.2.50. create a DeploymentConfigRollback

POST /oapi/v1/deploymentconfigrollbacks

2.2.50.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParameter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParameter	body		true	Section 2.3.68, "v1.DeploymentConfigRollback"	

2.2.50.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.68, "v1.DeploymentConfigRollback"

2.2.50.3. Consumes

- /

2.2.50.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.50.5. Tags

- oapiv1

2.2.51. list or watch objects of kind DeploymentConfig

GET /oapi/v1/deploymentconfigs

2.2.51.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParam eter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParam eter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParam ter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParamter	resourceVersion	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParamter	timeoutSeconds	Timeout for the list/watch call.	false	integer	

2.2.51.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.67, "v1.DeploymentConfigList"

2.2.51.3. Consumes

- /

2.2.51.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf
- application/json;stream=watch
- application/vnd.kubernetes.protobuf;stream=watch

2.2.51.5. Tags

- oapiv1

2.2.52. create a DeploymentConfig

POST /oapi/v1/deploymentconfigs

2.2.52.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamet er	body		true	Section 2.3.66 , "v1.Deploy mentConfig"	

2.2.52.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.66 , "v1.DeploymentConfig"

2.2.52.3. Consumes

- /

2.2.52.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.52.5. Tags

- oapiv1

2.2.53. list or watch objects of kind EgressNetworkPolicy

GET /oapi/v1/egressnetworkpolicies

2.2.53.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParam eter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParam eter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParam ter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParamter	resourceVersion	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParamter	timeoutSeconds	Timeout for the list/watch call.	false	integer	

2.2.53.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.87, "v1.EgressNetworkPolicyList"

2.2.53.3. Consumes

- /

2.2.53.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf
- application/json;stream=watch
- application/vnd.kubernetes.protobuf;stream=watch

2.2.53.5. Tags

- oapiv1

2.2.54. create an EgressNetworkPolicy

POST /oapi/v1/egressnetworkpolicies

2.2.54.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamet er	body		true	Section 2.3.86 , "v1.EgressNe tworkPolicy"	

2.2.54.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.86 , "v1.EgressNetworkPolicy"

2.2.54.3. Consumes

- /

2.2.54.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.54.5. Tags

- oapiv1

2.2.55. list or watch objects of kind Group

GET /oapi/v1/groups

2.2.55.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParam eter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParam eter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParam ter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParamter	resourceVersion	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParamter	timeoutSeconds	Timeout for the list/watch call.	false	integer	

2.2.55.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.110, "v1.GroupList"

2.2.55.3. Consumes

- /

2.2.55.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf
- application/json;stream=watch
- application/vnd.kubernetes.protobuf;stream=watch

2.2.55.5. Tags

- oapiv1

2.2.56. create a Group

POST /oapi/v1/groups

2.2.56.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParameter	body		true	Section 2.3.109 , "v1.Group"	

2.2.56.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.109 , "v1.Group"

2.2.56.3. Consumes

- /

2.2.56.4. Produces

- application/json

- application/yaml
- application/vnd.kubernetes.protobuf

2.2.56.5. Tags

- oapiv1

2.2.57. delete collection of Group

DELETE /oapi/v1/groups

2.2.57.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParam eter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParam eter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParam eter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParam ter	resourceVersi on	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParam ter	timeoutSecon ds	Timeout for the list/watch call.	false	integer	

2.2.57.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.264, "v1.Status"

2.2.57.3. Consumes

- /

2.2.57.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.57.5. Tags

- oapiv1

2.2.58. read the specified Group

GET /oapi/v1/groups/{name}

2.2.58.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParam eter	export	Should this value be exported. Export strips fields that a user can not specify.	false	boolean	
QueryParam eter	exact	Should the export be exact. Exact export maintains cluster-specific fields like 'Namespace'.	false	boolean	
PathParam eter	name	name of the Group	true	string	

2.2.58.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.109, "v1.Group"

2.2.58.3. Consumes

- /

2.2.58.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.58.5. Tags

- oapiv1

2.2.59. partially update the specified Group

PATCH /oapi/v1/groups/{name}

2.2.59.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamet er	body		true	Section 2.3.180, "v1.Patch"	
PathParamet er	name	name of the Group	true	string	

2.2.59.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.109, "v1.Group"

2.2.59.3. Consumes

- application/json-patch+json
- application/merge-patch+json
- application/strategic-merge-patch+json

2.2.59.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.59.5. Tags

- oapiv1

2.2.60. replace the specified Group

```
PUT /oapi/v1/groups/{name}
```

2.2.60.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParameter	body		true	Section 2.3.109, "v1.Group"	
PathParamter	name	name of the Group	true	string	

2.2.60.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.109, "v1.Group"

2.2.60.3. Consumes

- /

2.2.60.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.60.5. Tags

- oapiv1

2.2.61. delete a Group

```
DELETE /oapi/v1/groups/{name}
```

2.2.61.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamet er	body		true	Section 2.3.6 1 , "v1.DeleteOptions"	

Type	Name	Description	Required	Schema	Default
QueryParam ter	gracePeriodS econds	The duration in seconds before the object should be deleted. Value must be non-negative integer. The value zero indicates delete immediately. If this value is nil, the default grace period for the specified type will be used. Defaults to a per object value if not specified. zero means delete immediately.	false	integer	

Type	Name	Description	Required	Schema	Default
QueryParam eter	orphanDepen dents	Deprecated: please use the PropagationP olicy, this field will be deprecated in 1.7. Should the dependent objects be orphaned. If true/false, the "orphan" finalizer will be added to/removed from the object's finalizers list. Either this field or PropagationP olicy may be set, but not both.	false	boolean	
QueryParam eter	propagationP olicy	Whether and how garbage collection will be performed. Either this field or OrphanDepen dents may be set, but not both. The default policy is decided by the existing finalizer set in the metadata.fin alizers and the resource- specific default policy.	false	string	
PathParamet er	name	name of the Group	true	string	

2.2.61.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.264, "v1.Status"

2.2.61.3. Consumes

- /

2.2.61.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.61.5. Tags

- oapiv1

2.2.62. list or watch objects of kind HostSubnet

GET /oapi/v1/hostsubnets

2.2.62.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParam eter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParam ter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParam ter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParamter	resourceVersion	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParamter	timeoutSeconds	Timeout for the list/watch call.	false	integer	

2.2.62.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.117, "v1.HostSubnetList"

2.2.62.3. Consumes

- /

2.2.62.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf
- application/json;stream=watch
- application/vnd.kubernetes.protobuf;stream=watch

2.2.62.5. Tags

- oapiv1

2.2.63. create a HostSubnet

POST /oapi/v1/hostsubnets

2.2.63.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamet er	body		true	Section 2.3.116 , "v1.HostSubn et"	

2.2.63.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.116 , "v1.HostSubnet"

2.2.63.3. Consumes

- /

2.2.63.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.63.5. Tags

- oapiv1

2.2.64. delete collection of HostSubnet

```
DELETE /oapi/v1/hostsubnets
```

2.2.64.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParam eter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParam eter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParam ter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParamter	resourceVersion	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParamter	timeoutSeconds	Timeout for the list/watch call.	false	integer	

2.2.64.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.264, "v1.Status"

2.2.64.3. Consumes

- /

2.2.64.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.64.5. Tags

- oapiv1

2.2.65. read the specified HostSubnet

```
GET /oapi/v1/hostsubnets/{name}
```

2.2.65.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParam eter	export	Should this value be exported. Export strips fields that a user can not specify.	false	boolean	
QueryParam eter	exact	Should the export be exact. Exact export maintains cluster-specific fields like 'Namespace'.	false	boolean	
PathParam eter	name	name of the HostSubnet	true	string	

2.2.65.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.116, "v1.HostSubnet"

2.2.65.3. Consumes

- /

2.2.65.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.65.5. Tags

- oapiv1

2.2.66. partially update the specified HostSubnet

```
PATCH /oapi/v1/hostsubnets/{name}
```

2.2.66.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParameter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParameter	body		true	Section 2.3.180, "v1.Patch"	
PathParameter	name	name of the HostSubnet	true	string	

2.2.66.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.116, "v1.HostSubnet"

2.2.66.3. Consumes

- application/json-patch+json
- application/merge-patch+json
- application/strategic-merge-patch+json

2.2.66.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.66.5. Tags

- oapiv1

2.2.67. replace the specified HostSubnet

```
PUT /oapi/v1/hostsubnets/{name}
```

2.2.67.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParameter	body		true	Section 2.3.116 , "v1.HostSubnet"	
PathParamter	name	name of the HostSubnet	true	string	

2.2.67.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.116 , "v1.HostSubnet"

2.2.67.3. Consumes

- /

2.2.67.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.67.5. Tags

- oapiv1

2.2.68. delete a HostSubnet

DELETE /oapi/v1/hostsubnets/{name}

2.2.68.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamenter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParameter	body		true	Section 2.3.61 , "v1.DeleteOptions"	

Type	Name	Description	Required	Schema	Default
QueryParam ter	gracePeriodS econds	The duration in seconds before the object should be deleted. Value must be non-negative integer. The value zero indicates delete immediately. If this value is nil, the default grace period for the specified type will be used. Defaults to a per object value if not specified. zero means delete immediately.	false	integer	

Type	Name	Description	Required	Schema	Default
QueryParam eter	orphanDepen dents	Deprecated: please use the PropagationP olicy, this field will be deprecated in 1.7. Should the dependent objects be orphaned. If true/false, the "orphan" finalizer will be added to/removed from the object's finalizers list. Either this field or PropagationP olicy may be set, but not both.	false	boolean	
QueryParam eter	propagationP olicy	Whether and how garbage collection will be performed. Either this field or OrphanDepen dents may be set, but not both. The default policy is decided by the existing finalizer set in the metadata.fin alizers and the resource- specific default policy.	false	string	
PathParamet er	name	name of the HostSubnet	true	string	

2.2.68.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.264, "v1.Status"

2.2.68.3. Consumes

- /

2.2.68.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.68.5. Tags

- oapiv1

2.2.69. list or watch objects of kind Identity

GET /oapi/v1/identities

2.2.69.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParam eter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParam ter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParam ter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParamter	resourceVersion	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParamter	timeoutSeconds	Timeout for the list/watch call.	false	integer	

2.2.69.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.120, "v1.IdentityList"

2.2.69.3. Consumes

- /

2.2.69.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf
- application/json;stream=watch
- application/vnd.kubernetes.protobuf;stream=watch

2.2.69.5. Tags

- oapiv1

2.2.70. create an Identity

POST /oapi/v1/identities

2.2.70.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParameter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParameter	body		true	Section 2.3.119 , "v1.Identity"	

2.2.70.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.119 , "v1.Identity"

2.2.70.3. Consumes

- /

2.2.70.4. Produces

- application/json

- application/yaml
- application/vnd.kubernetes.protobuf

2.2.70.5. Tags

- oapiv1

2.2.71. delete collection of Identity

DELETE /oapi/v1/identities

2.2.71.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParam eter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParam eter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParam eter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParamter	resourceVersion	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParamter	timeoutSeconds	Timeout for the list/watch call.	false	integer	

2.2.71.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.264, "v1.Status"

2.2.71.3. Consumes

- /

2.2.71.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.71.5. Tags

- oapiv1

2.2.72. read the specified Identity

```
GET /oapi/v1/identities/{name}
```

2.2.72.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParam eter	export	Should this value be exported. Export strips fields that a user can not specify.	false	boolean	
QueryParam eter	exact	Should the export be exact. Exact export maintains cluster-specific fields like 'Namespace'.	false	boolean	
PathParam eter	name	name of the Identity	true	string	

2.2.72.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.119, "v1.Identity"

2.2.72.3. Consumes

- /

2.2.72.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.72.5. Tags

- oapiv1

2.2.73. partially update the specified Identity

```
PATCH /oapi/v1/identities/{name}
```

2.2.73.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamet er	body		true	Section 2.3.180, "v1.Patch"	
PathParamet er	name	name of the Identity	true	string	

2.2.73.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.119, "v1.Identity"

2.2.73.3. Consumes

- application/json-patch+json
- application/merge-patch+json
- application/strategic-merge-patch+json

2.2.73.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.73.5. Tags

- oapiv1

2.2.74. replace the specified Identity

```
PUT /oapi/v1/identities/{name}
```

2.2.74.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParameter	body		true	Section 2.3.119 , "v1.Identity"	
PathParamter	name	name of the Identity	true	string	

2.2.74.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.119 , "v1.Identity"

2.2.74.3. Consumes

- /

2.2.74.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.74.5. Tags

- oapiv1

2.2.75. delete an Identity

```
DELETE /oapi/v1/identities/{name}
```

2.2.75.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamet er	body		true	Section 2.3.6 1 , "v1.DeleteOptions"	

Type	Name	Description	Required	Schema	Default
QueryParam ter	gracePeriodS econds	The duration in seconds before the object should be deleted. Value must be non-negative integer. The value zero indicates delete immediately. If this value is nil, the default grace period for the specified type will be used. Defaults to a per object value if not specified. zero means delete immediately.	false	integer	

Type	Name	Description	Required	Schema	Default
QueryParam eter	orphanDepen dents	Deprecated: please use the PropagationP olicy, this field will be deprecated in 1.7. Should the dependent objects be orphaned. If true/false, the "orphan" finalizer will be added to/removed from the object's finalizers list. Either this field or PropagationP olicy may be set, but not both.	false	boolean	
QueryParam eter	propagationP olicy	Whether and how garbage collection will be performed. Either this field or OrphanDepen dents may be set, but not both. The default policy is decided by the existing finalizer set in the metadata.fin alizers and the resource- specific default policy.	false	string	
PathParamet er	name	name of the Identity	true	string	

2.2.75.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.264, "v1.Status"

2.2.75.3. Consumes

- /

2.2.75.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.75.5. Tags

- oapiv1

2.2.76. list or watch objects of kind Image

GET /oapi/v1/images

2.2.76.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParam eter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParam ter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParam ter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParamter	resourceVersion	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParamter	timeoutSeconds	Timeout for the list/watch call.	false	integer	

2.2.76.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.128, "v1.ImageList"

2.2.76.3. Consumes

- /

2.2.76.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf
- application/json;stream=watch
- application/vnd.kubernetes.protobuf;stream=watch

2.2.76.5. Tags

- oapiv1

2.2.77. create an Image

POST /oapi/v1/images

2.2.77.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParameter	body		true	Section 2.3.121 , "v1.Image"	

2.2.77.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.121 , "v1.Image"

2.2.77.3. Consumes

- /

2.2.77.4. Produces

- application/json

- application/yaml
- application/vnd.kubernetes.protobuf

2.2.77.5. Tags

- oapiv1

2.2.78. delete collection of Image

DELETE /oapi/v1/images

2.2.78.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParam eter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParam eter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParam eter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParamter	resourceVersion	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParamter	timeoutSeconds	Timeout for the list/watch call.	false	integer	

2.2.78.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.264, "v1.Status"

2.2.78.3. Consumes

- /

2.2.78.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.78.5. Tags

- oapiv1

2.2.79. read the specified Image

```
GET /oapi/v1/images/{name}
```

2.2.79.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParam eter	export	Should this value be exported. Export strips fields that a user can not specify.	false	boolean	
QueryParam eter	exact	Should the export be exact. Exact export maintains cluster-specific fields like 'Namespace'.	false	boolean	
PathParam eter	name	name of the Image	true	string	

2.2.79.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.121, "v1.Image"

2.2.79.3. Consumes

- /

2.2.79.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.79.5. Tags

- oapiv1

2.2.80. partially update the specified Image

PATCH /oapi/v1/images/{name}

2.2.80.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamet er	body		true	Section 2.3.180, "v1.Patch"	
PathParamet er	name	name of the Image	true	string	

2.2.80.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.121, "v1.Image"

2.2.80.3. Consumes

- application/json-patch+json
- application/merge-patch+json
- application/strategic-merge-patch+json

2.2.80.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.80.5. Tags

- oapiv1

2.2.81. replace the specified Image

```
PUT /oapi/v1/images/{name}
```

2.2.81.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParameter	body		true	Section 2.3.121 , "v1.Image"	
PathParamter	name	name of the Image	true	string	

2.2.81.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.121 , "v1.Image"

2.2.81.3. Consumes

- /

2.2.81.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.81.5. Tags

- oapiv1

2.2.82. delete an Image

```
DELETE /oapi/v1/images/{name}
```

2.2.82.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamet er	body		true	Section 2.3.6 1 , "v1.DeleteOptions"	

Type	Name	Description	Required	Schema	Default
QueryParam ter	gracePeriodS econds	The duration in seconds before the object should be deleted. Value must be non-negative integer. The value zero indicates delete immediately. If this value is nil, the default grace period for the specified type will be used. Defaults to a per object value if not specified. zero means delete immediately.	false	integer	

Type	Name	Description	Required	Schema	Default
QueryParam eter	orphanDepen dents	Deprecated: please use the PropagationP olicy, this field will be deprecated in 1.7. Should the dependent objects be orphaned. If true/false, the "orphan" finalizer will be added to/removed from the object's finalizers list. Either this field or PropagationP olicy may be set, but not both.	false	boolean	
QueryParam eter	propagationP olicy	Whether and how garbage collection will be performed. Either this field or OrphanDepen dents may be set, but not both. The default policy is decided by the existing finalizer set in the metadata.fin alizers and the resource- specific default policy.	false	string	
PathParamet er	name	name of the Image	true	string	

2.2.82.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.264, "v1.Status"

2.2.82.3. Consumes

- /

2.2.82.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.82.5. Tags

- oapiv1

2.2.83. create an ImageSignature

POST /oapi/v1/imagesignatures

2.2.83.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamet er	body		true	Section 2.3.131, "v1.ImageSignature"	

2.2.83.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.131, "v1.ImageSignature"

2.2.83.3. Consumes

- /

2.2.83.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.83.5. Tags

- oapiv1

2.2.84. delete an ImageSignature

DELETE /oapi/v1/imagesignatures/{name}

2.2.84.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
PathParam eter	name	name of the ImageSignature	true	string	

2.2.84.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.264, "v1.Status"

2.2.84.3. Consumes

- /

2.2.84.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.84.5. Tags

- oapiv1

2.2.85. create an ImageStreamImport

POST /oapi/v1/imagestreamimports

2.2.85.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParameter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParameter	body		true	Section 2.3.136 , "v1.ImageStreamImport"	

2.2.85.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.136 , "v1.ImageStreamImport"

2.2.85.3. Consumes

- /

2.2.85.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.85.5. Tags

- oapiv1

2.2.86. create an ImageStreamMapping

POST /oapi/v1/imagestreammappings

2.2.86.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParameter	body		true	Section 2.3.140 , "v1.ImageStreamMapping"	

2.2.86.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.140 , "v1.ImageStreamMapping"

2.2.86.3. Consumes

- /

2.2.86.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.86.5. Tags

- oapiv1

2.2.87. list or watch objects of kind ImageStream

GET /oapi/v1/imagestreams

2.2.87.1. Parameters

Type	Name	Description	Required	Schema	Default
------	------	-------------	----------	--------	---------

Type	Name	Description	Required	Schema	Default
QueryParam ter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParam ter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParam ter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParam ter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParamter	resourceVersion	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParamter	timeoutSeconds	Timeout for the list/watch call.	false	integer	

2.2.87.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.139, "v1.ImageStreamList"

2.2.87.3. Consumes

- /

2.2.87.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf
- application/json;stream=watch
- application/vnd.kubernetes.protobuf;stream=watch

2.2.87.5. Tags

- oapiv1

2.2.88. create an ImageStream

POST /oapi/v1/imagestreams

2.2.88.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamet er	body		true	Section 2.3.134 , "v1.ImageStream"	

2.2.88.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.134 , "v1.ImageStream"

2.2.88.3. Consumes

- /

2.2.88.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.88.5. Tags

- oapiv1

2.2.89. list objects of kind ImageStreamTag

GET /oapi/v1/imagestreamtags

2.2.89.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParam eter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParam eter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParam ter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParamter	resourceVersion	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParamter	timeoutSeconds	Timeout for the list/watch call.	false	integer	

2.2.89.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.144, "v1.ImageStreamTagList"

2.2.89.3. Consumes

- /

2.2.89.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf
- application/json;stream=watch
- application/vnd.kubernetes.protobuf;stream=watch

2.2.89.5. Tags

- oapiv1

2.2.90. create an ImageStreamTag

POST /oapi/v1/imagestreamtags

2.2.90.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParameter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParameter	body		true	Section 2.3.143 , "v1.ImageStreamTag"	

2.2.90.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.143 , "v1.ImageStreamTag"

2.2.90.3. Consumes

- /

2.2.90.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.90.5. Tags

- oapiv1

2.2.91. create a LocalResourceAccessReview

POST /oapi/v1/localresourceaccessreviews

2.2.91.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamet er	body		true	Section 2.3.153 , "v1.LocalResourceAccessReview"	

2.2.91.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.153 , "v1.LocalResourceAccessReview"

2.2.91.3. Consumes

- /

2.2.91.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.91.5. Tags

- oapiv1

2.2.92. create a LocalSubjectAccessReview

POST /oapi/v1/localsubjectaccessreviews

2.2.92.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamet er	body		true	Section 2.3.154 , "v1.LocalSubj ectAccessRev iew"	

2.2.92.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.154 , "v1.LocalSubjectAccessReview "

2.2.92.3. Consumes

- /

2.2.92.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.92.5. Tags

- oapiv1

2.2.93. list objects of kind AppliedClusterResourceQuota

GET /oapi/v1/namespaces/{namespace}/appliedclusterresourcequotas

2.2.93.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParam eter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParam eter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParam eter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParam eter	resourceVersi on	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParam eter	timeoutSecon ds	Timeout for the list/watch call.	false	integer	
PathParamet er	namespace	object name and auth scope, such as for teams and projects	true	string	

2.2.93.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.9, "v1.AppliedClusterResourceQuotaList"

2.2.93.3. Consumes

- /

2.2.93.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf
- application/json;stream=watch
- application/vnd.kubernetes.protobuf;stream=watch

2.2.93.5. Tags

- oapiv1

2.2.94. read the specified AppliedClusterResourceQuota

```
GET /oapi/v1/namespaces/{namespace}/appliedclusterresourcequotas/{name}
```

2.2.94.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamter	pretty	If 'true', then the output is pretty printed.	false	string	
PathParamter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParamter	name	name of the AppliedClusterResourceQuota	true	string	

2.2.94.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.8 , "v1.AppliedClusterResourceQuota"

2.2.94.3. Consumes

- /

2.2.94.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.94.5. Tags

- oapiv1

2.2.95. list or watch objects of kind BuildConfig

GET /oapi/v1/namespaces/{namespace}/buildconfigs

2.2.95.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParam ter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParam ter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParam eter	resourceVersi on	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParam eter	timeoutSecon ds	Timeout for the list/watch call.	false	integer	
PathParamet er	namespace	object name and auth scope, such as for teams and projects	true	string	

2.2.95.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.17, "v1.BuildConfigList"

2.2.95.3. Consumes

- /

2.2.95.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf
- application/json;stream=watch
- application/vnd.kubernetes.protobuf;stream=watch

2.2.95.5. Tags

- oapiv1

2.2.96. create a BuildConfig

POST /oapi/v1/namespaces/{namespace}/buildconfigs

2.2.96.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParameter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParameter	body		true	Section 2.3.16, "v1.BuildConfig"	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	

2.2.96.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.16, "v1.BuildConfig"

2.2.96.3. Consumes

- /

2.2.96.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.96.5. Tags

- oapiv1

2.2.97. delete collection of BuildConfig

```
DELETE /oapi/v1/namespaces/{namespace}/buildconfigs
```

2.2.97.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParam eter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParam ter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParam ter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParam eter	resourceVersi on	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParam eter	timeoutSecon ds	Timeout for the list/watch call.	false	integer	
PathParamet er	namespace	object name and auth scope, such as for teams and projects	true	string	

2.2.97.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.264, "v1.Status"

2.2.97.3. Consumes

- /

2.2.97.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.97.5. Tags

- oapiv1

2.2.98. read the specified BuildConfig

GET /oapi/v1/namespaces/{namespace}/buildconfigs/{name}

2.2.98.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParam eter	export	Should this value be exported. Export strips fields that a user can not specify.	false	boolean	
QueryParam eter	exact	Should the export be exact. Exact export maintains cluster-specific fields like 'Namespace'.	false	boolean	

Type	Name	Description	Required	Schema	Default
PathParamet er	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParamet er	name	name of the BuildConfig	true	string	

2.2.98.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.16, "v1.BuildConfig"

2.2.98.3. Consumes

- /

2.2.98.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.98.5. Tags

- oapiv1

2.2.99. partially update the specified BuildConfig

```
PATCH /oapi/v1/namespaces/{namespace}/buildconfigs/{name}
```

2.2.99.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParame ter	pretty	If 'true', then the output is pretty printed.	false	string	

Type	Name	Description	Required	Schema	Default
BodyParameter	body		true	Section 2.3.180, "v1.Patch"	
PathParamter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParamter	name	name of the BuildConfig	true	string	

2.2.99.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.16, "v1.BuildConfig"

2.2.99.3. Consumes

- application/json-patch+json
- application/merge-patch+json
- application/strategic-merge-patch+json

2.2.99.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.99.5. Tags

- oapiv1

2.2.100. replace the specified BuildConfig

```
PUT /oapi/v1/namespaces/{namespace}/buildconfigs/{name}
```

2.2.100.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParameter	body		true	Section 2.3.16 , "v1.BuildConfig"	
PathParamter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParamter	name	name of the BuildConfig	true	string	

2.2.100.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.16 , "v1.BuildConfig"

2.2.100.3. Consumes

- /

2.2.100.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.100.5. Tags

- oapiv1

2.2.101. delete a BuildConfig

```
DELETE /oapi/v1/namespaces/{namespace}/buildconfigs/{name}
```

2.2.101.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParameter	body		true	Section 2.3.6 1, "v1.DeleteOptions"	
QueryParamter	gracePeriodSeconds	The duration in seconds before the object should be deleted. Value must be non-negative integer. The value zero indicates delete immediately. If this value is nil, the default grace period for the specified type will be used. Defaults to a per object value if not specified. zero means delete immediately.	false	integer	

Type	Name	Description	Required	Schema	Default
QueryParam eter	orphanDepen dents	Deprecated: please use the PropagationP olicy, this field will be deprecated in 1.7. Should the dependent objects be orphaned. If true/false, the "orphan" finalizer will be added to/removed from the object's finalizers list. Either this field or PropagationP olicy may be set, but not both.	false	boolean	
QueryParam eter	propagationP olicy	Whether and how garbage collection will be performed. Either this field or OrphanDepen dents may be set, but not both. The default policy is decided by the existing finalizer set in the metadata.fin alizers and the resource- specific default policy.	false	string	

Type	Name	Description	Required	Schema	Default
PathParamet er	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParamet er	name	name of the BuildConfig	true	string	

2.2.101.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.264, "v1.Status"

2.2.101.3. Consumes

- /

2.2.101.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.101.5. Tags

- oapiv1

2.2.102. create instantiate of a BuildRequest

POST /oapi/v1/namespaces/{namespace}/buildconfigs/{name}/instantiate

2.2.102.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	

Type	Name	Description	Required	Schema	Default
BodyParameter	body		true	Section 2.3.24 , "v1.BuildRequest"	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParameter	name	name of the BuildRequest	true	string	

2.2.102.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.24 , "v1.BuildRequest"

2.2.102.3. Consumes

- /

2.2.102.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.102.5. Tags

- oapiv1

2.2.103. connect POST requests to instantiatebinary of BinaryBuildRequestOptions

POST /oapi/v1/namespaces/{namespace}/buildconfigs/{name}/instantiatebinary

2.2.103.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamter	asFile	asFile determines if the binary should be created as a file within the source rather than extracted as an archive	false	string	
QueryParamter	revision.commit	revision.commit is the value identifying a specific commit	false	string	
QueryParamter	revision.message	revision.message is the description of a specific commit	false	string	
QueryParamter	revision.authorName	revision.authorName of the source control user	false	string	
QueryParamter	revision.authorEmail	revision.authorEmail of the source control user	false	string	
QueryParamter	revision.committerName	revision.committerName of the source control user	false	string	
QueryParamter	revision.committerEmail	revision.committerEmail of the source control user	false	string	
PathParamter	namespace	object name and auth scope, such as for teams and projects	true	string	

Type	Name	Description	Required	Schema	Default
PathParamet er	name	name of the BinaryBuildR equestOption s	true	string	

2.2.103.2. Responses

HTTP Code	Description	Schema
default	success	string

2.2.103.3. Consumes

- /

2.2.103.4. Produces

- /

2.2.103.5. Tags

- oapiv1

2.2.104. connect POST requests to webhooks of Build

POST /oapi/v1/namespaces/{namespace}/buildconfigs/{name}/webhooks

2.2.104.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	path	Path is the URL path to use for the current proxy request to pod.	false	string	
PathParamet er	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParamet er	name	name of the Build	true	string	

2.2.104.2. Responses

HTTP Code	Description	Schema
default	success	string

2.2.104.3. Consumes

- /

2.2.104.4. Produces

- /

2.2.104.5. Tags

- oapiv1

2.2.105. connect POST requests to webhooks of Build

POST /oapi/v1/namespaces/{namespace}/buildconfigs/{name}/webhooks/{path}

2.2.105.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	path	Path is the URL path to use for the current proxy request to pod.	false	string	
PathParam eter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParam eter	name	name of the Build	true	string	
PathParam eter	path	path to the resource	true	string	

2.2.105.2. Responses

HTTP Code	Description	Schema
default	success	string

2.2.105.3. Consumes

- /

2.2.105.4. Produces

- /

2.2.105.5. Tags

- oapiv1

2.2.106. list or watch objects of kind Build

GET /oapi/v1/namespaces/{namespace}/builds

2.2.106.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParam eter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParam eter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParam ter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParam eter	resourceVersi on	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParam eter	timeoutSecon ds	Timeout for the list/watch call.	false	integer	
PathParamet er	namespace	object name and auth scope, such as for teams and projects	true	string	

2.2.106.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.20, “v1.BuildList”

2.2.106.3. Consumes

- /

2.2.106.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf
- application/json;stream=watch
- application/vnd.kubernetes.protobuf;stream=watch

2.2.106.5. Tags

- oapiv1

2.2.107. create a Build

POST /oapi/v1/namespaces/{namespace}/builds

2.2.107.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamenter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParameter	body		true	Section 2.3.15, “v1.Build”	
PathParamenter	namespace	object name and auth scope, such as for teams and projects	true	string	

2.2.107.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.15, “v1.Build”

2.2.107.3. Consumes

- /

2.2.107.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.107.5. Tags

- oapiv1

2.2.108. delete collection of Build

DELETE /oapi/v1/namespaces/{namespace}/builds

2.2.108.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParam eter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParam eter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParam ter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParam ter	resourceVersi on	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParam ter	timeoutSecon ds	Timeout for the list/watch call.	false	integer	
PathParamet er	namespace	object name and auth scope, such as for teams and projects	true	string	

2.2.108.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.264, "v1.Status"

2.2.108.3. Consumes

- /

2.2.108.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.108.5. Tags

- oapiv1

2.2.109. read the specified Build

GET /oapi/v1/namespaces/{namespace}/builds/{name}

2.2.109.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParam eter	export	Should this value be exported. Export strips fields that a user can not specify.	false	boolean	
QueryParam eter	exact	Should the export be exact. Exact export maintains cluster-specific fields like 'Namespace'.	false	boolean	

Type	Name	Description	Required	Schema	Default
PathParamet er	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParamet er	name	name of the Build	true	string	

2.2.109.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.15, "v1.Build"

2.2.109.3. Consumes

- /

2.2.109.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.109.5. Tags

- oapiv1

2.2.110. partially update the specified Build

```
PATCH /oapi/v1/namespaces/{namespace}/builds/{name}
```

2.2.110.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParame ter	pretty	If 'true', then the output is pretty printed.	false	string	

Type	Name	Description	Required	Schema	Default
BodyParameter	body		true	Section 2.3.180, "v1.Patch"	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParameter	name	name of the Build	true	string	

2.2.110.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.15, "v1.Build"

2.2.110.3. Consumes

- application/json-patch+json
- application/merge-patch+json
- application/strategic-merge-patch+json

2.2.110.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.110.5. Tags

- oapiv1

2.2.111. replace the specified Build

```
PUT /oapi/v1/namespaces/{namespace}/builds/{name}
```

2.2.111.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParameter	body		true	Section 2.3.15, "v1.Build"	
PathParamter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParamter	name	name of the Build	true	string	

2.2.111.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.15, "v1.Build"

2.2.111.3. Consumes

- /

2.2.111.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.111.5. Tags

- oapiv1

2.2.112. delete a Build

```
DELETE /oapi/v1/namespaces/{namespace}/builds/{name}
```

2.2.112.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParameter	body		true	Section 2.3.6 1, "v1.DeleteOptions"	
QueryParamter	gracePeriodSeconds	The duration in seconds before the object should be deleted. Value must be non-negative integer. The value zero indicates delete immediately. If this value is nil, the default grace period for the specified type will be used. Defaults to a per object value if not specified. zero means delete immediately.	false	integer	

Type	Name	Description	Required	Schema	Default
QueryParam eter	orphanDepen dents	Deprecated: please use the PropagationP olicy, this field will be deprecated in 1.7. Should the dependent objects be orphaned. If true/false, the "orphan" finalizer will be added to/removed from the object's finalizers list. Either this field or PropagationP olicy may be set, but not both.	false	boolean	
QueryParam eter	propagationP olicy	Whether and how garbage collection will be performed. Either this field or OrphanDepen dents may be set, but not both. The default policy is decided by the existing finalizer set in the metadata.fin alizers and the resource- specific default policy.	false	string	

Type	Name	Description	Required	Schema	Default
PathParamet er	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParamet er	name	name of the Build	true	string	

2.2.112.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.264, "v1.Status"

2.2.112.3. Consumes

- /

2.2.112.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.112.5. Tags

- oapiv1

2.2.113. create clone of a BuildRequest

POST /oapi/v1/namespaces/{namespace}/builds/{name}/clone

2.2.113.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParame ter	pretty	If 'true', then the output is pretty printed.	false	string	

Type	Name	Description	Required	Schema	Default
BodyParameter	body		true	Section 2.3.24, "v1.BuildRequest"	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParameter	name	name of the BuildRequest	true	string	

2.2.113.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.24, "v1.BuildRequest"

2.2.113.3. Consumes

- /

2.2.113.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.113.5. Tags

- oapiv1

2.2.114. replace details of the specified Build

```
PUT /oapi/v1/namespaces/{namespace}/builds/{name}/details
```

2.2.114.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParameter	body		true	Section 2.3.15, "v1.Build"	
PathParamter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParamter	name	name of the Build	true	string	

2.2.114.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.15, "v1.Build"

2.2.114.3. Consumes

- /

2.2.114.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.114.5. Tags

- oapiv1

2.2.115. read log of the specified BuildLog

```
GET /oapi/v1/namespaces/{namespace}/builds/{name}/log
```

2.2.115.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamter	container	cointainer for which to stream logs. Defaults to only container if there is one container in the pod.	false	string	
QueryParamter	follow	follow if true indicates that the build log should be streamed until the build terminates.	false	boolean	
QueryParamter	previous	previous returns previous build logs. Defaults to false.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParam ter	sinceSeconds	sinceSeconds is a relative time in seconds before the current time from which to show logs. If this value precedes the time a pod was started, only logs since the pod start will be returned. If this value is in the future, no logs will be returned. Only one of sinceSeconds or sinceTime may be specified.	false	integer	
QueryParam ter	timestamps	timestamps, If true, add an RFC3339 or RFC3339Nano timestamp at the beginning of every line of log output. Defaults to false.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParam ter	tailLines	tailLines, If set, is the number of lines from the end of the logs to show. If not specified, logs are shown from the creation of the container or sinceSeconds or sinceTime	false	integer	
QueryParam ter	limitBytes	limitBytes, If set, is the number of bytes to read from the server before terminating the log output. This may not display a complete final line of logging, and may return slightly more or slightly less than the specified limit.	false	integer	
QueryParam ter	nowait	noWait if true causes the call to return immediately even if the build is not available yet. Otherwise the server will wait until the build has started.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParamter	version	version of the build for which to view logs.	false	integer	
PathParamter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParamter	name	name of the BuildLog	true	string	

2.2.115.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.21, "v1.BuildLog"

2.2.115.3. Consumes

- /

2.2.115.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.115.5. Tags

- oapiv1

2.2.116. create a DeploymentConfigRollback

POST /oapi/v1/namespaces/{namespace}/deploymentconfigrollbacks

2.2.116.1. Parameters

Type	Name	Description	Required	Schema	Default
------	------	-------------	----------	--------	---------

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamet er	body		true	Section 2.3.68 , "v1.Deploy mentConfigRoll back"	
PathParamet er	namespace	object name and auth scope, such as for teams and projects	true	string	

2.2.116.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.68 , "v1.DeploymentConfigRollbac k"

2.2.116.3. Consumes

- /

2.2.116.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.116.5. Tags

- oapiv1

2.2.117. list or watch objects of kind DeploymentConfig

GET /oapi/v1/namespaces/{namespace}/deploymentconfigs

2.2.117.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam ter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParam ter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParam ter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParam ter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParam eter	resourceVersi on	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParam eter	timeoutSecon ds	Timeout for the list/watch call.	false	integer	
PathParam eter	namespace	object name and auth scope, such as for teams and projects	true	string	

2.2.117.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.67, "v1.DeploymentConfigList"

2.2.117.3. Consumes

- /

2.2.117.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf
- application/json;stream=watch
- application/vnd.kubernetes.protobuf;stream=watch

2.2.117.5. Tags

- oapiv1

2.2.118. create a DeploymentConfig

POST /oapi/v1/namespaces/{namespace}/deploymentconfigs

2.2.118.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamenter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParameter	body		true	Section 2.3.66, "v1.DeploymentConfig"	
PathParamenter	namespace	object name and auth scope, such as for teams and projects	true	string	

2.2.118.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.66, "v1.DeploymentConfig"

2.2.118.3. Consumes

- /

2.2.118.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.118.5. Tags

- oapiv1

2.2.119. delete collection of DeploymentConfig

DELETE /oapi/v1/namespaces/{namespace}/deploymentconfigs

2.2.119.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParam eter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParam ter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParam ter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParam eter	resourceVersi on	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParam eter	timeoutSecon ds	Timeout for the list/watch call.	false	integer	
PathParamet er	namespace	object name and auth scope, such as for teams and projects	true	string	

2.2.119.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.264, "v1.Status"

2.2.119.3. Consumes

- /

2.2.119.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.119.5. Tags

- oapiv1

2.2.120. read the specified DeploymentConfig

```
GET /oapi/v1/namespaces/{namespace}/deploymentconfigs/{name}
```

2.2.120.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParam eter	export	Should this value be exported. Export strips fields that a user can not specify.	false	boolean	
QueryParam eter	exact	Should the export be exact. Exact export maintains cluster-specific fields like 'Namespace'.	false	boolean	

Type	Name	Description	Required	Schema	Default
PathParamet er	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParamet er	name	name of the DeploymentC onfig	true	string	

2.2.120.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.66, "v1.DeploymentConfig"

2.2.120.3. Consumes

- /

2.2.120.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.120.5. Tags

- oapiv1

2.2.121. partially update the specified DeploymentConfig

```
PATCH /oapi/v1/namespaces/{namespace}/deploymentconfigs/{name}
```

2.2.121.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParame ter	pretty	If 'true', then the output is pretty printed.	false	string	

Type	Name	Description	Required	Schema	Default
BodyParameter	body		true	Section 2.3.180 , "v1.Patch"	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParameter	name	name of the DeploymentConfig	true	string	

2.2.121.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.66 , "v1.DeploymentConfig"

2.2.121.3. Consumes

- application/json-patch+json
- application/merge-patch+json
- application/strategic-merge-patch+json

2.2.121.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.121.5. Tags

- oapiv1

2.2.122. replace the specified DeploymentConfig

```
PUT /oapi/v1/namespaces/{namespace}/deploymentconfigs/{name}
```

2.2.122.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParameter	body		true	Section 2.3.66 , "v1.DeploymentConfig"	
PathParamter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParamter	name	name of the DeploymentConfig	true	string	

2.2.122.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.66 , "v1.DeploymentConfig"

2.2.122.3. Consumes

- /

2.2.122.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.122.5. Tags

- oapiv1

2.2.123. delete a DeploymentConfig

```
DELETE /oapi/v1/namespaces/{namespace}/deploymentconfigs/{name}
```

2.2.123.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamet er	body		true	Section 2.3.6 1, "v1.DeleteOptions"	
QueryParam eter	gracePeriodS econds	The duration in seconds before the object should be deleted. Value must be non-negative integer. The value zero indicates delete immediately. If this value is nil, the default grace period for the specified type will be used. Defaults to a per object value if not specified. zero means delete immediately.	false	integer	

Type	Name	Description	Required	Schema	Default
QueryParam eter	orphanDepen dents	Deprecated: please use the PropagationP olicy, this field will be deprecated in 1.7. Should the dependent objects be orphaned. If true/false, the "orphan" finalizer will be added to/removed from the object's finalizers list. Either this field or PropagationP olicy may be set, but not both.	false	boolean	
QueryParam eter	propagationP olicy	Whether and how garbage collection will be performed. Either this field or OrphanDepen dents may be set, but not both. The default policy is decided by the existing finalizer set in the metadata.fin alizers and the resource- specific default policy.	false	string	

Type	Name	Description	Required	Schema	Default
PathParamet er	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParamet er	name	name of the DeploymentC onfig	true	string	

2.2.123.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.264, "v1.Status"

2.2.123.3. Consumes

- /

2.2.123.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.123.5. Tags

- oapiv1

2.2.124. create instantiate of a DeploymentRequest

POST /oapi/v1/namespaces/{namespace}/deploymentconfigs/{name}/instantiate

2.2.124.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParame ter	pretty	If 'true', then the output is pretty printed.	false	string	

Type	Name	Description	Required	Schema	Default
BodyParameter	body		true	Section 2.3.74 , “v1.DeploymentRequest”	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParameter	name	name of the DeploymentRequest	true	string	

2.2.124.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.74 , “v1.DeploymentRequest”

2.2.124.3. Consumes

- /

2.2.124.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.124.5. Tags

- oapiv1

2.2.125. read log of the specified DeploymentLog

```
GET /oapi/v1/namespaces/{namespace}/deploymentconfigs/{name}/log
```

2.2.125.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam ter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParam ter	container	The container for which to stream logs. Defaults to only container if there is one container in the pod.	false	string	
QueryParam ter	follow	Follow if true indicates that the build log should be streamed until the build terminates.	false	boolean	
QueryParam ter	previous	Return previous deployment logs. Defaults to false.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParameter	sinceSeconds	A relative time in seconds before the current time from which to show logs. If this value precedes the time a pod was started, only logs since the pod start will be returned. If this value is in the future, no logs will be returned. Only one of sinceSeconds or sinceTime may be specified.	false	integer	
QueryParameter	timestamps	If true, add an RFC3339 or RFC3339Nano timestamp at the beginning of every line of log output. Defaults to false.	false	boolean	
QueryParameter	tailLines	If set, the number of lines from the end of the logs to show. If not specified, logs are shown from the creation of the container or sinceSeconds or sinceTime	false	integer	

Type	Name	Description	Required	Schema	Default
QueryParam eter	limitBytes	If set, the number of bytes to read from the server before terminating the log output. This may not display a complete final line of logging, and may return slightly more or slightly less than the specified limit.	false	integer	
QueryParam eter	nowait	NoWait if true causes the call to return immediately even if the deployment is not available yet. Otherwise the server will wait until the deployment has started.	false	boolean	
QueryParam eter	version	Version of the deployment for which to view logs.	false	integer	
PathParamet er	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParamet er	name	name of the DeploymentL og	true	string	

Type	Name	Description	Required	Schema	Default
------	------	-------------	----------	--------	---------

2.2.125.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.73, "v1.DeploymentLog"

2.2.125.3. Consumes

- /

2.2.125.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.125.5. Tags

- oapiv1

2.2.126. create rollback of a DeploymentConfigRollback

POST /oapi/v1/namespaces/{namespace}/deploymentconfigs/{name}/rollback

2.2.126.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamenter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParameter	body		true	Section 2.3.68, "v1.DeploymentConfigRollback"	

Type	Name	Description	Required	Schema	Default
PathParamet er	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParamet er	name	name of the DeploymentC onfigRollback	true	string	

2.2.126.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.68, "v1.DeploymentConfigRollback"

2.2.126.3. Consumes

- /

2.2.126.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.126.5. Tags

- oapiv1

2.2.127. read scale of the specified Scale

GET /oapi/v1/namespaces/{namespace}/deploymentconfigs/{name}/scale

2.2.127.1. Parameters

Type	Name	Description	Required	Schema	Default
------	------	-------------	----------	--------	---------

Type	Name	Description	Required	Schema	Default
QueryParamter	pretty	If 'true', then the output is pretty printed.	false	string	
PathParamter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParamter	name	name of the Scale	true	string	

2.2.127.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.294, "v1beta1.Scale"

2.2.127.3. Consumes

- /

2.2.127.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.127.5. Tags

- oapiv1

2.2.128. partially update scale of the specified Scale

```
PATCH /oapi/v1/namespaces/{namespace}/deploymentconfigs/{name}/scale
```

2.2.128.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParameter	body		true	Section 2.3.180 , "v1.Patch"	
PathParamter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParamter	name	name of the Scale	true	string	

2.2.128.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.294 , "v1beta1.Scale"

2.2.128.3. Consumes

- application/json-patch+json
- application/merge-patch+json
- application/strategic-merge-patch+json

2.2.128.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.128.5. Tags

- oapiv1

2.2.129. replace scale of the specified Scale

```
PUT /oapi/v1/namespaces/{namespace}/deploymentconfigs/{name}/scale
```

2.2.129.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParameter	body		true	Section 2.3.294 , "v1beta1.Scale"	
PathParamter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParamter	name	name of the Scale	true	string	

2.2.129.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.294 , "v1beta1.Scale"

2.2.129.3. Consumes

- /

2.2.129.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.129.5. Tags

- oapiv1

2.2.130. read status of the specified DeploymentConfig

```
GET /oapi/v1/namespaces/{namespace}/deploymentconfigs/{name}/status
```

2.2.130.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamter	pretty	If 'true', then the output is pretty printed.	false	string	
PathParamter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParamter	name	name of the DeploymentConfig	true	string	

2.2.130.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.66, "v1.DeploymentConfig"

2.2.130.3. Consumes

- /

2.2.130.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.130.5. Tags

- oapiv1

2.2.131. partially update status of the specified DeploymentConfig

```
PATCH /oapi/v1/namespaces/{namespace}/deploymentconfigs/{name}/status
```

2.2.131.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParameter	body		true	Section 2.3.180 , "v1.Patch"	
PathParamter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParamter	name	name of the DeploymentConfig	true	string	

2.2.131.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.66 , "v1.DeploymentConfig"

2.2.131.3. Consumes

- application/json-patch+json
- application/merge-patch+json
- application/strategic-merge-patch+json

2.2.131.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.131.5. Tags

- oapiv1

2.2.132. replace status of the specified DeploymentConfig

PUT /oapi/v1/namespaces/{namespace}/deploymentconfigs/{name}/status

2.2.132.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParameter	body		true	Section 2.3.66 , "v1.DeploymentConfig"	
PathParamter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParamter	name	name of the DeploymentConfig	true	string	

2.2.132.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.66 , "v1.DeploymentConfig"

2.2.132.3. Consumes

- /

2.2.132.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.132.5. Tags

- oapiv1

2.2.133. list or watch objects of kind EgressNetworkPolicy

GET /oapi/v1/namespaces/{namespace}/egressnetworkpolicies

2.2.133.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParam eter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParam eter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParam eter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParam ter	resourceVersi on	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParam ter	timeoutSecon ds	Timeout for the list/watch call.	false	integer	
PathParamet er	namespace	object name and auth scope, such as for teams and projects	true	string	

2.2.133.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.87 , “v1.EgressNetworkPolicyList”

2.2.133.3. Consumes

- /

2.2.133.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf
- application/json;stream=watch
- application/vnd.kubernetes.protobuf;stream=watch

2.2.133.5. Tags

- oapiv1

2.2.134. create an EgressNetworkPolicy

POST /oapi/v1/namespaces/{namespace}/egressnetworkpolicies

2.2.134.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamenter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParameter	body		true	Section 2.3.86 , “v1.EgressNetworkPolicy”	
PathParamenter	namespace	object name and auth scope, such as for teams and projects	true	string	

2.2.134.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.86, "v1.EgressNetworkPolicy"

2.2.134.3. Consumes

- /

2.2.134.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.134.5. Tags

- oapiv1

2.2.135. delete collection of EgressNetworkPolicy

DELETE /oapi/v1/namespaces/{namespace}/egressnetworkpolicies

2.2.135.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParam eter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParam ter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParam ter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParamter	resourceVersion	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParamter	timeoutSeconds	Timeout for the list/watch call.	false	integer	
PathParamter	namespace	object name and auth scope, such as for teams and projects	true	string	

2.2.135.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.264, "v1.Status"

2.2.135.3. Consumes

- /

2.2.135.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.135.5. Tags

- oapiv1

2.2.136. read the specified EgressNetworkPolicy

```
GET /oapi/v1/namespaces/{namespace}/egressnetworkpolicies/{name}
```

2.2.136.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParam eter	export	Should this value be exported. Export strips fields that a user can not specify.	false	boolean	
QueryParam eter	exact	Should the export be exact. Exact export maintains cluster-specific fields like 'Namespace'.	false	boolean	

Type	Name	Description	Required	Schema	Default
PathParamet er	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParamet er	name	name of the EgressNetworkkPolicy	true	string	

2.2.136.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.86, "v1.EgressNetworkPolicy"

2.2.136.3. Consumes

- /

2.2.136.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.136.5. Tags

- oapiv1

2.2.137. partially update the specified EgressNetworkPolicy

```
PATCH /oapi/v1/namespaces/{namespace}/egressnetworkpolicies/{name}
```

2.2.137.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParame ter	pretty	If 'true', then the output is pretty printed.	false	string	

Type	Name	Description	Required	Schema	Default
BodyParameter	body		true	Section 2.3.180 , "v1.Patch"	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParameter	name	name of the EgressNetworkPolicy	true	string	

2.2.137.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.86 , "v1.EgressNetworkPolicy"

2.2.137.3. Consumes

- application/json-patch+json
- application/merge-patch+json
- application/strategic-merge-patch+json

2.2.137.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.137.5. Tags

- oapiv1

2.2.138. replace the specified EgressNetworkPolicy

```
PUT /oapi/v1/namespaces/{namespace}/egressnetworkpolicies/{name}
```

2.2.138.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParameter	body		true	Section 2.3.86 , "v1.EgressNetworkPolicy"	
PathParamter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParamter	name	name of the EgressNetworkPolicy	true	string	

2.2.138.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.86 , "v1.EgressNetworkPolicy"

2.2.138.3. Consumes

- /

2.2.138.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.138.5. Tags

- oapiv1

2.2.139. delete an EgressNetworkPolicy

```
DELETE /oapi/v1/namespaces/{namespace}/egressnetworkpolicies/{name}
```

2.2.139.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParameter	body		true	Section 2.3.6 1, "v1.DeleteOptions"	
QueryParamter	gracePeriodSeconds	The duration in seconds before the object should be deleted. Value must be non-negative integer. The value zero indicates delete immediately. If this value is nil, the default grace period for the specified type will be used. Defaults to a per object value if not specified. zero means delete immediately.	false	integer	

Type	Name	Description	Required	Schema	Default
QueryParam ter	orphanDepen dents	Deprecated: please use the PropagationP olicy, this field will be deprecated in 1.7. Should the dependent objects be orphaned. If true/false, the "orphan" finalizer will be added to/removed from the object's finalizers list. Either this field or PropagationP olicy may be set, but not both.	false	boolean	
QueryParam ter	propagationP olicy	Whether and how garbage collection will be performed. Either this field or OrphanDepen dents may be set, but not both. The default policy is decided by the existing finalizer set in the metadata.fin alizers and the resource- specific default policy.	false	string	

Type	Name	Description	Required	Schema	Default
PathParamet er	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParamet er	name	name of the EgressNetworkPolicy	true	string	

2.2.139.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.264, "v1.Status"

2.2.139.3. Consumes

- /

2.2.139.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.139.5. Tags

- oapiv1

2.2.140. read the specified ImageStreamImage

```
GET /oapi/v1/namespaces/{namespace}/imagestreamimages/{name}
```

2.2.140.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParame ter	pretty	If 'true', then the output is pretty printed.	false	string	

Type	Name	Description	Required	Schema	Default
PathParamet er	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParamet er	name	name of the ImageStream Image	true	string	

2.2.140.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.135, "v1.ImageStreamImage"

2.2.140.3. Consumes

- /

2.2.140.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.140.5. Tags

- oapiv1

2.2.141. create an ImageStreamImport

POST /oapi/v1/namespaces/{namespace}/imagestreamimports

2.2.141.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParame ter	pretty	If 'true', then the output is pretty printed.	false	string	

Type	Name	Description	Required	Schema	Default
BodyParameter	body		true	Section 2.3.136 , "v1.ImageStreamImport"	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	

2.2.141.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.136 , "v1.ImageStreamImport"

2.2.141.3. Consumes

- /

2.2.141.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.141.5. Tags

- oapiv1

2.2.142. create an ImageStreamMapping

```
POST /oapi/v1/namespaces/{namespace}/imagestreammappings
```

2.2.142.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParameter	pretty	If 'true', then the output is pretty printed.	false	string	

Type	Name	Description	Required	Schema	Default
BodyParameter	body		true	Section 2.3.140 , "v1.ImageStreamMapping"	
PathParamter	namespace	object name and auth scope, such as for teams and projects	true	string	

2.2.142.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.140 , "v1.ImageStreamMapping"

2.2.142.3. Consumes

- /

2.2.142.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.142.5. Tags

- oapiv1

2.2.143. list or watch objects of kind ImageStream

```
GET /oapi/v1/namespaces/{namespace}/imagestreams
```

2.2.143.1. Parameters

Type	Name	Description	Required	Schema	Default
------	------	-------------	----------	--------	---------

Type	Name	Description	Required	Schema	Default
QueryParamter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParamter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParamter	resourceVersion	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParamter	timeoutSeconds	Timeout for the list/watch call.	false	integer	
PathParamter	namespace	object name and auth scope, such as for teams and projects	true	string	

2.2.143.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.139, "v1.ImageStreamList"

2.2.143.3. Consumes

- /

2.2.143.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf
- application/json;stream=watch
- application/vnd.kubernetes.protobuf;stream=watch

2.2.143.5. Tags

- oapiv1

2.2.144. create an ImageStream

POST /oapi/v1/namespaces/{namespace}/imagestreams

2.2.144.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamenter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParameter	body		true	Section 2.3.134, "v1.ImageStream"	
PathParamenter	namespace	object name and auth scope, such as for teams and projects	true	string	

2.2.144.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.134, "v1.ImageStream"

2.2.144.3. Consumes

- /

2.2.144.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.144.5. Tags

- oapiv1

2.2.145. delete collection of ImageStream

DELETE /oapi/v1/namespaces/{namespace}/imagestreams

2.2.145.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParam eter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParamter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParamter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParam eter	resourceVersi on	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParam eter	timeoutSecon ds	Timeout for the list/watch call.	false	integer	
PathParamet er	namespace	object name and auth scope, such as for teams and projects	true	string	

2.2.145.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.264, "v1.Status"

2.2.145.3. Consumes

- /

2.2.145.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.145.5. Tags

- oapiv1

2.2.146. read the specified ImageStream

```
GET /oapi/v1/namespaces/{namespace}/imagestreams/{name}
```

2.2.146.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParam eter	export	Should this value be exported. Export strips fields that a user can not specify.	false	boolean	
QueryParam eter	exact	Should the export be exact. Exact export maintains cluster-specific fields like 'Namespace'.	false	boolean	

Type	Name	Description	Required	Schema	Default
PathParamet er	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParamet er	name	name of the ImageStream	true	string	

2.2.146.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.134, "v1.ImageStream"

2.2.146.3. Consumes

- /

2.2.146.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.146.5. Tags

- oapiv1

2.2.147. partially update the specified ImageStream

```
PATCH /oapi/v1/namespaces/{namespace}/imagestreams/{name}
```

2.2.147.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParame ter	pretty	If 'true', then the output is pretty printed.	false	string	

Type	Name	Description	Required	Schema	Default
BodyParameter	body		true	Section 2.3.180 , "v1.Patch"	
PathParamter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParamter	name	name of the ImageStream	true	string	

2.2.147.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.134 , "v1.ImageStream"

2.2.147.3. Consumes

- application/json-patch+json
- application/merge-patch+json
- application/strategic-merge-patch+json

2.2.147.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.147.5. Tags

- oapiv1

2.2.148. replace the specified ImageStream

```
PUT /oapi/v1/namespaces/{namespace}/imagestreams/{name}
```

2.2.148.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParameter	body		true	Section 2.3.134 , "v1.ImageStream"	
PathParamter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParamter	name	name of the ImageStream	true	string	

2.2.148.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.134 , "v1.ImageStream"

2.2.148.3. Consumes

- /

2.2.148.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.148.5. Tags

- oapiv1

2.2.149. delete an ImageStream

```
DELETE /oapi/v1/namespaces/{namespace}/imagestreams/{name}
```

2.2.149.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam ter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamet er	body		true	Section 2.3.6 1, "v1.DeleteOptions"	
QueryParam ter	gracePeriodS econds	The duration in seconds before the object should be deleted. Value must be non-negative integer. The value zero indicates delete immediately. If this value is nil, the default grace period for the specified type will be used. Defaults to a per object value if not specified. zero means delete immediately.	false	integer	

Type	Name	Description	Required	Schema	Default
QueryParam ter	orphanDepen dents	Deprecated: please use the PropagationP olicy, this field will be deprecated in 1.7. Should the dependent objects be orphaned. If true/false, the "orphan" finalizer will be added to/removed from the object's finalizers list. Either this field or PropagationP olicy may be set, but not both.	false	boolean	
QueryParam ter	propagationP olicy	Whether and how garbage collection will be performed. Either this field or OrphanDepen dents may be set, but not both. The default policy is decided by the existing finalizer set in the metadata.fin alizers and the resource- specific default policy.	false	string	

Type	Name	Description	Required	Schema	Default
PathParamet er	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParamet er	name	name of the ImageStream	true	string	

2.2.149.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.264, "v1.Status"

2.2.149.3. Consumes

- /

2.2.149.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.149.5. Tags

- oapiv1

2.2.150. read secrets of the specified SecretList

```
GET /oapi/v1/namespaces/{namespace}/imagestreams/{name}/secrets
```

2.2.150.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParam ter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParam ter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParam ter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParameter	resourceVersion	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParameter	timeoutSeconds	Timeout for the list/watch call.	false	integer	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	

Type	Name	Description	Required	Schema	Default
PathParamet er	name	name of the SecretList	true	string	

2.2.150.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.247, "v1.SecretList"

2.2.150.3. Consumes

- /

2.2.150.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.150.5. Tags

- oapiv1

2.2.151. read status of the specified ImageStream

GET /oapi/v1/namespaces/{namespace}/imagestreams/{name}/status

2.2.151.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
PathParamet er	namespace	object name and auth scope, such as for teams and projects	true	string	

Type	Name	Description	Required	Schema	Default
PathParam eter	name	name of the ImageStream	true	string	

2.2.151.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.134 , "v1.ImageStream"

2.2.151.3. Consumes

- /

2.2.151.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.151.5. Tags

- oapiv1

2.2.152. partially update status of the specified ImageStream

```
PATCH /oapi/v1/namespaces/{namespace}/imagestreams/{name}/status
```

2.2.152.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamet er	body		true	Section 2.3.180 , "v1.Patch"	

Type	Name	Description	Required	Schema	Default
PathParamet er	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParamet er	name	name of the ImageStream	true	string	

2.2.152.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.134, "v1.ImageStream"

2.2.152.3. Consumes

- application/json-patch+json
- application/merge-patch+json
- application/strategic-merge-patch+json

2.2.152.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.152.5. Tags

- oapiv1

2.2.153. replace status of the specified ImageStream

```
PUT /oapi/v1/namespaces/{namespace}/imagestreams/{name}/status
```

2.2.153.1. Parameters

Type	Name	Description	Required	Schema	Default
------	------	-------------	----------	--------	---------

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamet er	body		true	Section 2.3.134 , "v1.ImageStream"	
PathParamet er	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParamet er	name	name of the ImageStream	true	string	

2.2.153.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.134 , "v1.ImageStream"

2.2.153.3. Consumes

- /

2.2.153.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.153.5. Tags

- oapiv1

2.2.154. list objects of kind ImageStreamTag

```
GET /oapi/v1/namespaces/{namespace}/imagestreamtags
```

2.2.154.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParamter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParamter	resourceVersion	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParamter	timeoutSeconds	Timeout for the list/watch call.	false	integer	
PathParamter	namespace	object name and auth scope, such as for teams and projects	true	string	

2.2.154.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.144, "v1.ImageStreamTagList"

2.2.154.3. Consumes

- /

2.2.154.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf
- application/json;stream=watch
- application/vnd.kubernetes.protobuf;stream=watch

2.2.154.5. Tags

- oapiv1

2.2.155. create an ImageStreamTag

POST /oapi/v1/namespaces/{namespace}/imagestreamtags

2.2.155.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamenter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParameter	body		true	Section 2.3.143, "v1.ImageStreamTag"	
PathParamenter	namespace	object name and auth scope, such as for teams and projects	true	string	

2.2.155.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.143, "v1.ImageStreamTag"

2.2.155.3. Consumes

- /

2.2.155.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.155.5. Tags

- oapiv1

2.2.156. read the specified ImageStreamTag

```
GET /oapi/v1/namespaces/{namespace}/imagestreamtags/{name}
```

2.2.156.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParameter	pretty	If 'true', then the output is pretty printed.	false	string	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParameter	name	name of the ImageStream Tag	true	string	

2.2.156.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.143, "v1.ImageStreamTag"

2.2.156.3. Consumes

- /

2.2.156.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.156.5. Tags

- oapiv1

2.2.157. partially update the specified ImageStreamTag

PATCH /oapi/v1/namespaces/{namespace}/imagestreamtags/{name}

2.2.157.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParameter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParameter	body		true	Section 2.3.180, "v1.Patch"	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParameter	name	name of the ImageStream Tag	true	string	

2.2.157.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.143, "v1.ImageStreamTag"

2.2.157.3. Consumes

- application/json-patch+json
- application/merge-patch+json
- application/strategic-merge-patch+json

2.2.157.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.157.5. Tags

- oapiv1

2.2.158. replace the specified ImageStreamTag

```
PUT /oapi/v1/namespaces/{namespace}/imagestreamtags/{name}
```

2.2.158.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamet er	body		true	Section 2.3.143, "v1.ImageStreamTag"	
PathParamet er	namespace	object name and auth scope, such as for teams and projects	true	string	

Type	Name	Description	Required	Schema	Default
PathParamet er	name	name of the ImageStream Tag	true	string	

2.2.158.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.143, "v1.ImageStreamTag"

2.2.158.3. Consumes

- /

2.2.158.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.158.5. Tags

- oapiv1

2.2.159. delete an ImageStreamTag

```
DELETE /oapi/v1/namespaces/{namespace}/imagestreamtags/{name}
```

2.2.159.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
PathParamet er	namespace	object name and auth scope, such as for teams and projects	true	string	

Type	Name	Description	Required	Schema	Default
PathParam eter	name	name of the ImageStream Tag	true	string	

2.2.159.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.264, "v1.Status"

2.2.159.3. Consumes

- /

2.2.159.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.159.5. Tags

- oapiv1

2.2.160. create a LocalResourceAccessReview

POST /oapi/v1/namespaces/{namespace}/localresourceaccessreviews

2.2.160.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParam eter	body		true	Section 2.3.1 53, "v1.LocalRes ourceAccessR eview"	

Type	Name	Description	Required	Schema	Default
PathParam eter	namespace	object name and auth scope, such as for teams and projects	true	string	

2.2.160.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.153, "v1.LocalResourceAccessReview"

2.2.160.3. Consumes

- /

2.2.160.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.160.5. Tags

- oapiv1

2.2.161. create a LocalSubjectAccessReview

POST /oapi/v1/namespaces/{namespace}/localsubjectaccessreviews

2.2.161.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	

Type	Name	Description	Required	Schema	Default
BodyParameter	body		true	Section 2.3.154 , "v1.LocalSubjectAccessReview"	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	

2.2.161.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.154 , "v1.LocalSubjectAccessReview"

2.2.161.3. Consumes

- /

2.2.161.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.161.5. Tags

- oapiv1

2.2.162. create a PodSecurityPolicyReview

POST /oapi/v1/namespaces/{namespace}/podsecuritypolicyreviews

2.2.162.1. Parameters

Type	Name	Description	Required	Schema	Default
------	------	-------------	----------	--------	---------

Type	Name	Description	Required	Schema	Default
QueryParamter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParameter	body		true	Section 2.3.187 , "v1.PodSecurityPolicyReview"	
PathParamter	namespace	object name and auth scope, such as for teams and projects	true	string	

2.2.162.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.187 , "v1.PodSecurityPolicyReview"

2.2.162.3. Consumes

- /

2.2.162.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.162.5. Tags

- oapiv1

2.2.163. create a PodSecurityPolicySelfSubjectReview

POST /oapi/v1/namespaces/{namespace}/podsecuritypolicyselfsubjectreviews

2.2.163.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamet er	body		true	Section 2.3.190 , "v1.PodSecurityPolicySelfSubjectReview"	
PathParamet er	namespace	object name and auth scope, such as for teams and projects	true	string	

2.2.163.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.190 , "v1.PodSecurityPolicySelfSubjectReview"

2.2.163.3. Consumes

- /

2.2.163.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.163.5. Tags

- oapiv1

2.2.164. create a PodSecurityPolicySubjectReview

POST /oapi/v1/namespaces/{namespace}/podsecuritypolicysubjectreviews

2.2.164.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParameter	body		true	Section 2.3.192 , "v1.PodSecurityPolicySubjectReview"	
PathParamter	namespace	object name and auth scope, such as for teams and projects	true	string	

2.2.164.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.192 , "v1.PodSecurityPolicySubjectReview"

2.2.164.3. Consumes

- /

2.2.164.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.164.5. Tags

- oapiv1

2.2.165. list or watch objects of kind Policy

```
GET /oapi/v1/namespaces/{namespace}/policies
```

2.2.165.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParamter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParam eter	resourceVersi on	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParam eter	timeoutSecon ds	Timeout for the list/watch call.	false	integer	
PathParam eter	namespace	object name and auth scope, such as for teams and projects	true	string	

2.2.165.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.200, "v1.PolicyList"

2.2.165.3. Consumes

- /

2.2.165.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf
- application/json;stream=watch
- application/vnd.kubernetes.protobuf;stream=watch

2.2.165.5. Tags

- oapiv1

2.2.166. create a Policy

POST /oapi/v1/namespaces/{namespace}/policies

2.2.166.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParameter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParameter	body		true	Section 2.3.197, "v1.Policy"	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	

2.2.166.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.197, "v1.Policy"

2.2.166.3. Consumes

- /

2.2.166.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.166.5. Tags

- oapiv1

2.2.167. delete collection of Policy

DELETE /oapi/v1/namespaces/{namespace}/policies

2.2.167.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParam eter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParam eter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParam ter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParamter	resourceVersion	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParamter	timeoutSeconds	Timeout for the list/watch call.	false	integer	
PathParamter	namespace	object name and auth scope, such as for teams and projects	true	string	

2.2.167.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.264, "v1.Status"

2.2.167.3. Consumes

- /

2.2.167.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.167.5. Tags

- oapiv1

2.2.168. read the specified Policy

GET /oapi/v1/namespaces/{namespace}/policies/{name}

2.2.168.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParam eter	export	Should this value be exported. Export strips fields that a user can not specify.	false	boolean	
QueryParam eter	exact	Should the export be exact. Exact export maintains cluster-specific fields like 'Namespace'.	false	boolean	

Type	Name	Description	Required	Schema	Default
PathParamet er	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParamet er	name	name of the Policy	true	string	

2.2.168.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.197, "v1.Policy"

2.2.168.3. Consumes

- /

2.2.168.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.168.5. Tags

- oapiv1

2.2.169. partially update the specified Policy

```
PATCH /oapi/v1/namespaces/{namespace}/policies/{name}
```

2.2.169.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	

Type	Name	Description	Required	Schema	Default
BodyParameter	body		true	Section 2.3.180, "v1.Patch"	
PathParamter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParamter	name	name of the Policy	true	string	

2.2.169.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.197, "v1.Policy"

2.2.169.3. Consumes

- application/json-patch+json
- application/merge-patch+json
- application/strategic-merge-patch+json

2.2.169.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.169.5. Tags

- oapiv1

2.2.170. replace the specified Policy

```
PUT /oapi/v1/namespaces/{namespace}/policies/{name}
```

2.2.170.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParameter	body		true	Section 2.3.197, "v1.Policy"	
PathParamter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParamter	name	name of the Policy	true	string	

2.2.170.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.197, "v1.Policy"

2.2.170.3. Consumes

- /

2.2.170.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.170.5. Tags

- oapiv1

2.2.171. delete a Policy

```
DELETE /oapi/v1/namespaces/{namespace}/policies/{name}
```

2.2.171.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam ter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamet er	body		true	Section 2.3.6 1, "v1.DeleteOptions"	
QueryParam ter	gracePeriodS econds	The duration in seconds before the object should be deleted. Value must be non-negative integer. The value zero indicates delete immediately. If this value is nil, the default grace period for the specified type will be used. Defaults to a per object value if not specified. zero means delete immediately.	false	integer	

Type	Name	Description	Required	Schema	Default
QueryParam eter	orphanDepen dents	Deprecated: please use the PropagationP olicy, this field will be deprecated in 1.7. Should the dependent objects be orphaned. If true/false, the "orphan" finalizer will be added to/removed from the object's finalizers list. Either this field or PropagationP olicy may be set, but not both.	false	boolean	
QueryParam eter	propagationP olicy	Whether and how garbage collection will be performed. Either this field or OrphanDepen dents may be set, but not both. The default policy is decided by the existing finalizer set in the metadata.fin alizers and the resource- specific default policy.	false	string	

Type	Name	Description	Required	Schema	Default
PathParamet er	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParamet er	name	name of the Policy	true	string	

2.2.171.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.264, "v1.Status"

2.2.171.3. Consumes

- /

2.2.171.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.171.5. Tags

- oapiv1

2.2.172. list or watch objects of kind PolicyBinding

GET /oapi/v1/namespaces/{namespace}/policybindings

2.2.172.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParam ter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParam ter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParam ter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParamter	resourceVersion	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParamter	timeoutSeconds	Timeout for the list/watch call.	false	integer	
PathParamter	namespace	object name and auth scope, such as for teams and projects	true	string	

2.2.172.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.199, "v1.PolicyBindingList"

2.2.172.3. Consumes

- /

2.2.172.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf
- application/json;stream=watch
- application/vnd.kubernetes.protobuf;stream=watch

2.2.172.5. Tags

- oapiv1

2.2.173. create a PolicyBinding

POST /oapi/v1/namespaces/{namespace}/policybindings

2.2.173.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParameter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParameter	body		true	Section 2.3.198, "v1.PolicyBinding"	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	

2.2.173.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.198, "v1.PolicyBinding"

2.2.173.3. Consumes

- /

2.2.173.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.173.5. Tags

- oapiv1

2.2.174. delete collection of PolicyBinding

```
DELETE /oapi/v1/namespaces/{namespace}/policybindings
```

2.2.174.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParam eter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParam ter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParam ter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParam eter	resourceVersi on	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParam eter	timeoutSecon ds	Timeout for the list/watch call.	false	integer	
PathParamet er	namespace	object name and auth scope, such as for teams and projects	true	string	

2.2.174.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.264, "v1.Status"

2.2.174.3. Consumes

- /

2.2.174.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.174.5. Tags

- oapiv1

2.2.175. read the specified PolicyBinding

GET /oapi/v1/namespaces/{namespace}/policybindings/{name}

2.2.175.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParam eter	export	Should this value be exported. Export strips fields that a user can not specify.	false	boolean	
QueryParam eter	exact	Should the export be exact. Exact export maintains cluster-specific fields like 'Namespace'.	false	boolean	

Type	Name	Description	Required	Schema	Default
PathParamet er	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParamet er	name	name of the PolicyBinding	true	string	

2.2.175.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.198, "v1.PolicyBinding"

2.2.175.3. Consumes

- /

2.2.175.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.175.5. Tags

- oapiv1

2.2.176. partially update the specified PolicyBinding

```
PATCH /oapi/v1/namespaces/{namespace}/policybindings/{name}
```

2.2.176.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParame ter	pretty	If 'true', then the output is pretty printed.	false	string	

Type	Name	Description	Required	Schema	Default
BodyParameter	body		true	Section 2.3.180, "v1.Patch"	
PathParamter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParamter	name	name of the PolicyBinding	true	string	

2.2.176.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.198, "v1.PolicyBinding"

2.2.176.3. Consumes

- application/json-patch+json
- application/merge-patch+json
- application/strategic-merge-patch+json

2.2.176.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.176.5. Tags

- oapiv1

2.2.177. replace the specified PolicyBinding

```
PUT /oapi/v1/namespaces/{namespace}/policybindings/{name}
```

2.2.177.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParameter	body		true	Section 2.3.198 , "v1.PolicyBinding"	
PathParamter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParamter	name	name of the PolicyBinding	true	string	

2.2.177.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.198 , "v1.PolicyBinding"

2.2.177.3. Consumes

- /

2.2.177.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.177.5. Tags

- oapiv1

2.2.178. delete a PolicyBinding

```
DELETE /oapi/v1/namespaces/{namespace}/policybindings/{name}
```

2.2.178.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParameter	body		true	Section 2.3.6 1, "v1.DeleteOptions"	
QueryParamter	gracePeriodSeconds	The duration in seconds before the object should be deleted. Value must be non-negative integer. The value zero indicates delete immediately. If this value is nil, the default grace period for the specified type will be used. Defaults to a per object value if not specified. zero means delete immediately.	false	integer	

Type	Name	Description	Required	Schema	Default
QueryParam ter	orphanDepen dents	Deprecated: please use the PropagationP olicy, this field will be deprecated in 1.7. Should the dependent objects be orphaned. If true/false, the "orphan" finalizer will be added to/removed from the object's finalizers list. Either this field or PropagationP olicy may be set, but not both.	false	boolean	
QueryParam ter	propagationP olicy	Whether and how garbage collection will be performed. Either this field or OrphanDepen dents may be set, but not both. The default policy is decided by the existing finalizer set in the metadata.fin alizers and the resource- specific default policy.	false	string	

Type	Name	Description	Required	Schema	Default
PathParamet er	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParamet er	name	name of the PolicyBinding	true	string	

2.2.178.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.264, "v1.Status"

2.2.178.3. Consumes

- /

2.2.178.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.178.5. Tags

- oapiv1

2.2.179. create a Template

POST /oapi/v1/namespaces/{namespace}/processedtemplates

2.2.179.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParame ter	pretty	If 'true', then the output is pretty printed.	false	string	

Type	Name	Description	Required	Schema	Default
BodyParameter	body		true	Section 2.3.280 , "v1.Template"	
PathParam	namespace	object name and auth scope, such as for teams and projects	true	string	

2.2.179.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.280 , "v1.Template"

2.2.179.3. Consumes

- /

2.2.179.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.179.5. Tags

- oapiv1

2.2.180. create a ResourceAccessReview

POST /oapi/v1/namespaces/{namespace}/resourceaccessreviews

2.2.180.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam	pretty	If 'true', then the output is pretty printed.	false	string	

Type	Name	Description	Required	Schema	Default
BodyParameter	body		true	Section 2.3.217, "v1.ResourceAccessReview"	
PathParamter	namespace	object name and auth scope, such as for teams and projects	true	string	

2.2.180.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.217, "v1.ResourceAccessReview"

2.2.180.3. Consumes

- /

2.2.180.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.180.5. Tags

- oapiv1

2.2.181. list or watch objects of kind RoleBindingRestriction

```
GET /oapi/v1/namespaces/{namespace}/rolebindingrestrictions
```

2.2.181.1. Parameters

Type	Name	Description	Required	Schema	Default
------	------	-------------	----------	--------	---------

Type	Name	Description	Required	Schema	Default
QueryParam ter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParam ter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParam ter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParam ter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParamter	resourceVersion	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParamter	timeoutSeconds	Timeout for the list/watch call.	false	integer	
PathParamter	namespace	object name and auth scope, such as for teams and projects	true	string	

2.2.181.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.228 , "v1.RoleBindingRestrictionList"

2.2.181.3. Consumes

- /

2.2.181.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf
- application/json;stream=watch
- application/vnd.kubernetes.protobuf;stream=watch

2.2.181.5. Tags

- oapiv1

2.2.182. create a RoleBindingRestriction

POST /oapi/v1/namespaces/{namespace}/rolebindingrestrictions

2.2.182.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParameter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParameter	body		true	Section 2.3.227 , "v1.RoleBindingRestriction"	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	

2.2.182.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.227, "v1.RoleBindingRestriction"

2.2.182.3. Consumes

- /

2.2.182.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.182.5. Tags

- oapiv1

2.2.183. delete collection of RoleBindingRestriction

```
DELETE /oapi/v1/namespaces/{namespace}/rolebindingrestrictions
```

2.2.183.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParam eter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParam ter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParam ter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParamter	resourceVersion	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParamter	timeoutSeconds	Timeout for the list/watch call.	false	integer	
PathParamter	namespace	object name and auth scope, such as for teams and projects	true	string	

2.2.183.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.264, "v1.Status"

2.2.183.3. Consumes

- /

2.2.183.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.183.5. Tags

- oapiv1

2.2.184. read the specified RoleBindingRestriction

```
GET /oapi/v1/namespaces/{namespace}/rolebindingrestrictions/{name}
```

2.2.184.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParam eter	export	Should this value be exported. Export strips fields that a user can not specify.	false	boolean	
QueryParam eter	exact	Should the export be exact. Exact export maintains cluster-specific fields like 'Namespace'.	false	boolean	

Type	Name	Description	Required	Schema	Default
PathParamet er	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParamet er	name	name of the RoleBindingRestriction	true	string	

2.2.184.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.227, "v1.RoleBindingRestriction"

2.2.184.3. Consumes

- /

2.2.184.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.184.5. Tags

- oapiv1

2.2.185. partially update the specified RoleBindingRestriction

```
PATCH /oapi/v1/namespaces/{namespace}/rolebindingrestrictions/{name}
```

2.2.185.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParame ter	pretty	If 'true', then the output is pretty printed.	false	string	

Type	Name	Description	Required	Schema	Default
BodyParameter	body		true	Section 2.3.180 , "v1.Patch"	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParameter	name	name of the RoleBindingRestriction	true	string	

2.2.185.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.227 , "v1.RoleBindingRestriction"

2.2.185.3. Consumes

- application/json-patch+json
- application/merge-patch+json
- application/strategic-merge-patch+json

2.2.185.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.185.5. Tags

- oapiv1

2.2.186. replace the specified RoleBindingRestriction

```
PUT /oapi/v1/namespaces/{namespace}/rolebindingrestrictions/{name}
```

2.2.186.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamet er	body		true	Section 2.3.227 , "v1.RoleBindi ngRestriction "	
PathParamet er	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParamet er	name	name of the RoleBindingR estriction	true	string	

2.2.186.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.227 , "v1.RoleBindingRestriction"

2.2.186.3. Consumes

- /

2.2.186.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.186.5. Tags

- oapiv1

2.2.187. delete a RoleBindingRestriction


```
DELETE /oapi/v1/namespaces/{namespace}/rolebindingrestrictions/{name}
```

2.2.187.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamet er	body		true	Section 2.3.6 1, "v1.DeleteOptions"	
QueryParam eter	gracePeriodS econds	The duration in seconds before the object should be deleted. Value must be non-negative integer. The value zero indicates delete immediately. If this value is nil, the default grace period for the specified type will be used. Defaults to a per object value if not specified. zero means delete immediately.	false	integer	

Type	Name	Description	Required	Schema	Default
QueryParam eter	orphanDepen dents	Deprecated: please use the PropagationP olicy, this field will be deprecated in 1.7. Should the dependent objects be orphaned. If true/false, the "orphan" finalizer will be added to/removed from the object's finalizers list. Either this field or PropagationP olicy may be set, but not both.	false	boolean	
QueryParam eter	propagationP olicy	Whether and how garbage collection will be performed. Either this field or OrphanDepen dents may be set, but not both. The default policy is decided by the existing finalizer set in the metadata.fin alizers and the resource- specific default policy.	false	string	

Type	Name	Description	Required	Schema	Default
PathParamet er	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParamet er	name	name of the RoleBindingR estricition	true	string	

2.2.187.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.264, "v1.Status"

2.2.187.3. Consumes

- /

2.2.187.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.187.5. Tags

- oapiv1

2.2.188. list objects of kind RoleBinding

GET /oapi/v1/namespaces/{namespace}/rolebindings

2.2.188.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParame ter	pretty	If 'true', then the output is pretty printed.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParam ter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParam ter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParam ter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParameter	resourceVersion	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParameter	timeoutSeconds	Timeout for the list/watch call.	false	integer	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	

2.2.188.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.226, "v1.RoleBindingList"

2.2.188.3. Consumes

- /

2.2.188.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf
- application/json;stream=watch
- application/vnd.kubernetes.protobuf;stream=watch

2.2.188.5. Tags

- oapiv1

2.2.189. create a RoleBinding

POST /oapi/v1/namespaces/{namespace}/rolebindings

2.2.189.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParameter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParameter	body		true	Section 2.3.225, "v1.RoleBinding"	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	

2.2.189.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.225, "v1.RoleBinding"

2.2.189.3. Consumes

- /

2.2.189.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.189.5. Tags

- oapiv1

2.2.190. read the specified RoleBinding

```
GET /oapi/v1/namespaces/{namespace}/rolebindings/{name}
```

2.2.190.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
PathParam eter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParam eter	name	name of the RoleBinding	true	string	

2.2.190.2. Responses

HTTP Code	Description	Schema
-----------	-------------	--------

HTTP Code	Description	Schema
200	success	Section 2.3.225, "v1.RoleBinding"

2.2.190.3. Consumes

- /

2.2.190.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.190.5. Tags

- oapiv1

2.2.191. partially update the specified RoleBinding

```
PATCH /oapi/v1/namespaces/{namespace}/rolebindings/{name}
```

2.2.191.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamet er	body		true	Section 2.3.180, "v1.Patch"	
PathParamet er	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParamet er	name	name of the RoleBinding	true	string	

2.2.191.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.225, "v1.RoleBinding"

2.2.191.3. Consumes

- application/json-patch+json
- application/merge-patch+json
- application/strategic-merge-patch+json

2.2.191.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.191.5. Tags

- oapiv1

2.2.192. replace the specified RoleBinding

```
PUT /oapi/v1/namespaces/{namespace}/rolebindings/{name}
```

2.2.192.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParameter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParameter	body		true	Section 2.3.225, "v1.RoleBinding"	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	

Type	Name	Description	Required	Schema	Default
PathParamet er	name	name of the RoleBinding	true	string	

2.2.192.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.225, "v1.RoleBinding"

2.2.192.3. Consumes

- /

2.2.192.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.192.5. Tags

- oapiv1

2.2.193. delete a RoleBinding

```
DELETE /oapi/v1/namespaces/{namespace}/rolebindings/{name}
```

2.2.193.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamet er	body		true	Section 2.3.61, "v1.DeleteOptions"	

Type	Name	Description	Required	Schema	Default
QueryParam ter	gracePeriodS econds	The duration in seconds before the object should be deleted. Value must be non-negative integer. The value zero indicates delete immediately. If this value is nil, the default grace period for the specified type will be used. Defaults to a per object value if not specified. zero means delete immediately.	false	integer	

Type	Name	Description	Required	Schema	Default
QueryParam ter	orphanDepen dents	Deprecated: please use the PropagationP olicy, this field will be deprecated in 1.7. Should the dependent objects be orphaned. If true/false, the "orphan" finalizer will be added to/removed from the object's finalizers list. Either this field or PropagationP olicy may be set, but not both.	false	boolean	
QueryParam ter	propagationP olicy	Whether and how garbage collection will be performed. Either this field or OrphanDepen dents may be set, but not both. The default policy is decided by the existing finalizer set in the metadata.fin alizers and the resource- specific default policy.	false	string	

Type	Name	Description	Required	Schema	Default
PathParamet er	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParamet er	name	name of the RoleBinding	true	string	

2.2.193.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.264, "v1.Status"

2.2.193.3. Consumes

- /

2.2.193.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.193.5. Tags

- oapiv1

2.2.194. list objects of kind Role

GET /oapi/v1/namespaces/{namespace}/roles

2.2.194.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParame ter	pretty	If 'true', then the output is pretty printed.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParam ter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParam ter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParam ter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParam eter	resourceVersi on	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParam eter	timeoutSecon ds	Timeout for the list/watch call.	false	integer	
PathParamet er	namespace	object name and auth scope, such as for teams and projects	true	string	

2.2.194.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.230, "v1.RoleList"

2.2.194.3. Consumes

- /

2.2.194.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf
- application/json;stream=watch
- application/vnd.kubernetes.protobuf;stream=watch

2.2.194.5. Tags

- oapiv1

2.2.195. create a Role

POST /oapi/v1/namespaces/{namespace}/roles

2.2.195.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamet er	body		true	Section 2.3.24, "v1.Role"	
PathParamet er	namespace	object name and auth scope, such as for teams and projects	true	string	

2.2.195.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.224, "v1.Role"

2.2.195.3. Consumes

- /

2.2.195.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.195.5. Tags

- oapiv1

2.2.196. read the specified Role

GET /oapi/v1/namespaces/{namespace}/roles/{name}

2.2.196.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
PathParam eter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParam eter	name	name of the Role	true	string	

2.2.196.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.224, "v1.Role"

2.2.196.3. Consumes

- /

2.2.196.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.196.5. Tags

- oapiv1

2.2.197. partially update the specified Role

PATCH /oapi/v1/namespaces/{namespace}/roles/{name}

2.2.197.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParameter	body		true	Section 2.3.180, "v1.Patch"	
PathParamter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParamter	name	name of the Role	true	string	

2.2.197.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.224, "v1.Role"

2.2.197.3. Consumes

- application/json-patch+json
- application/merge-patch+json
- application/strategic-merge-patch+json

2.2.197.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.197.5. Tags

- oapiv1

2.2.198. replace the specified Role

```
PUT /oapi/v1/namespaces/{namespace}/roles/{name}
```

2.2.198.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamenter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParameter	body		true	Section 2.3.24, "v1.Role"	
PathParamenter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParamenter	name	name of the Role	true	string	

2.2.198.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.224, "v1.Role"

2.2.198.3. Consumes

- /

2.2.198.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.198.5. Tags

- oapiv1

2.2.199. delete a Role

DELETE /oapi/v1/namespaces/{namespace}/roles/{name}

2.2.199.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamet er	body		true	Section 2.3.6 1 , "v1.DeleteOptions"	

Type	Name	Description	Required	Schema	Default
QueryParam ter	gracePeriodS econds	The duration in seconds before the object should be deleted. Value must be non-negative integer. The value zero indicates delete immediately. If this value is nil, the default grace period for the specified type will be used. Defaults to a per object value if not specified. zero means delete immediately.	false	integer	

Type	Name	Description	Required	Schema	Default
QueryParam ter	orphanDepen dents	Deprecated: please use the PropagationP olicy, this field will be deprecated in 1.7. Should the dependent objects be orphaned. If true/false, the "orphan" finalizer will be added to/removed from the object's finalizers list. Either this field or PropagationP olicy may be set, but not both.	false	boolean	
QueryParam ter	propagationP olicy	Whether and how garbage collection will be performed. Either this field or OrphanDepen dents may be set, but not both. The default policy is decided by the existing finalizer set in the metadata.fin alizers and the resource- specific default policy.	false	string	

Type	Name	Description	Required	Schema	Default
PathParamet er	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParamet er	name	name of the Role	true	string	

2.2.199.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.264, "v1.Status"

2.2.199.3. Consumes

- /

2.2.199.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.199.5. Tags

- oapiv1

2.2.200. list or watch objects of kind Route

GET /oapi/v1/namespaces/{namespace}/routes

2.2.200.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParame ter	pretty	If 'true', then the output is pretty printed.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParam ter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParam ter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParam ter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParam eter	resourceVersi on	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParam eter	timeoutSecon ds	Timeout for the list/watch call.	false	integer	
PathParamet er	namespace	object name and auth scope, such as for teams and projects	true	string	

2.2.200.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.235, "v1.RouteList"

2.2.200.3. Consumes

- /

2.2.200.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf
- application/json;stream=watch
- application/vnd.kubernetes.protobuf;stream=watch

2.2.200.5. Tags

- oapiv1

2.2.201. create a Route

POST /oapi/v1/namespaces/{namespace}/routes

2.2.201.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParameter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParameter	body		true	Section 2.3.232, "v1.Route"	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	

2.2.201.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.232, "v1.Route"

2.2.201.3. Consumes

- /

2.2.201.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.201.5. Tags

- oapiv1

2.2.202. delete collection of Route

DELETE /oapi/v1/namespaces/{namespace}/routes

2.2.202.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParam eter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParam eter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParam ter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParam eter	resourceVersi on	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParam eter	timeoutSecon ds	Timeout for the list/watch call.	false	integer	
PathParamet er	namespace	object name and auth scope, such as for teams and projects	true	string	

2.2.202.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.264, "v1.Status"

2.2.202.3. Consumes

- /

2.2.202.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.202.5. Tags

- oapiv1

2.2.203. read the specified Route

GET /oapi/v1/namespaces/{namespace}/routes/{name}

2.2.203.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParam eter	export	Should this value be exported. Export strips fields that a user can not specify.	false	boolean	
QueryParam eter	exact	Should the export be exact. Exact export maintains cluster-specific fields like 'Namespace'.	false	boolean	

Type	Name	Description	Required	Schema	Default
PathParamet er	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParamet er	name	name of the Route	true	string	

2.2.203.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.232, "v1.Route"

2.2.203.3. Consumes

- /

2.2.203.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.203.5. Tags

- oapiv1

2.2.204. partially update the specified Route

PATCH /oapi/v1/namespaces/{namespace}/routes/{name}

2.2.204.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	

Type	Name	Description	Required	Schema	Default
BodyParameter	body		true	Section 2.3.180 , "v1.Patch"	
PathParamter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParamter	name	name of the Route	true	string	

2.2.204.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.232 , "v1.Route"

2.2.204.3. Consumes

- application/json-patch+json
- application/merge-patch+json
- application/strategic-merge-patch+json

2.2.204.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.204.5. Tags

- oapiv1

2.2.205. replace the specified Route

```
PUT /oapi/v1/namespaces/{namespace}/routes/{name}
```

2.2.205.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParameter	body		true	Section 2.3.232, "v1.Route"	
PathParamter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParamter	name	name of the Route	true	string	

2.2.205.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.232, "v1.Route"

2.2.205.3. Consumes

- /

2.2.205.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.205.5. Tags

- oapiv1

2.2.206. delete a Route

```
DELETE /oapi/v1/namespaces/{namespace}/routes/{name}
```

2.2.206.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam ter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamet er	body		true	Section 2.3.6 1, "v1.DeleteOptions"	
QueryParam ter	gracePeriodS econds	The duration in seconds before the object should be deleted. Value must be non-negative integer. The value zero indicates delete immediately. If this value is nil, the default grace period for the specified type will be used. Defaults to a per object value if not specified. zero means delete immediately.	false	integer	

Type	Name	Description	Required	Schema	Default
QueryParam ter	orphanDepen dents	Deprecated: please use the PropagationP olicy, this field will be deprecated in 1.7. Should the dependent objects be orphaned. If true/false, the "orphan" finalizer will be added to/removed from the object's finalizers list. Either this field or PropagationP olicy may be set, but not both.	false	boolean	
QueryParam ter	propagationP olicy	Whether and how garbage collection will be performed. Either this field or OrphanDepen dents may be set, but not both. The default policy is decided by the existing finalizer set in the metadata.fin alizers and the resource- specific default policy.	false	string	

Type	Name	Description	Required	Schema	Default
PathParamet er	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParamet er	name	name of the Route	true	string	

2.2.206.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.264, "v1.Status"

2.2.206.3. Consumes

- /

2.2.206.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.206.5. Tags

- oapiv1

2.2.207. read status of the specified Route

```
GET /oapi/v1/namespaces/{namespace}/routes/{name}/status
```

2.2.207.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParame ter	pretty	If 'true', then the output is pretty printed.	false	string	

Type	Name	Description	Required	Schema	Default
PathParamet er	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParamet er	name	name of the Route	true	string	

2.2.207.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.232, "v1.Route"

2.2.207.3. Consumes

- /

2.2.207.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.207.5. Tags

- oapiv1

2.2.208. partially update status of the specified Route

PATCH /oapi/v1/namespaces/{namespace}/routes/{name}/status

2.2.208.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParame ter	pretty	If 'true', then the output is pretty printed.	false	string	

Type	Name	Description	Required	Schema	Default
BodyParameter	body		true	Section 2.3.180, "v1.Patch"	
PathParamter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParamter	name	name of the Route	true	string	

2.2.208.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.232, "v1.Route"

2.2.208.3. Consumes

- application/json-patch+json
- application/merge-patch+json
- application/strategic-merge-patch+json

2.2.208.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.208.5. Tags

- oapiv1

2.2.209. replace status of the specified Route

```
PUT /oapi/v1/namespaces/{namespace}/routes/{name}/status
```

2.2.209.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParameter	body		true	Section 2.3.232, "v1.Route"	
PathParamter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParamter	name	name of the Route	true	string	

2.2.209.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.232, "v1.Route"

2.2.209.3. Consumes

- /

2.2.209.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.209.5. Tags

- oapiv1

2.2.210. create a SelfSubjectRulesReview

POST /oapi/v1/namespaces/{namespace}/selfsubjectrulesreviews

2.2.210.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParameter	body		true	Section 2.3.252 , "v1.SelfSubjectRulesReview"	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	

2.2.210.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.252 , "v1.SelfSubjectRulesReview"

2.2.210.3. Consumes

- /

2.2.210.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.210.5. Tags

- oapiv1

2.2.211. create a SubjectAccessReview

POST /oapi/v1/namespaces/{namespace}/subjectaccessreviews

2.2.211.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParameter	body		true	Section 2.3.268 , "v1.SubjectAccessReview"	
PathParamter	namespace	object name and auth scope, such as for teams and projects	true	string	

2.2.211.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.268 , "v1.SubjectAccessReview"

2.2.211.3. Consumes

- /

2.2.211.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.211.5. Tags

- oapiv1

2.2.212. create a SubjectRulesReview

POST /oapi/v1/namespaces/{namespace}/subjectrulesreviews

2.2.212.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParameter	body		true	Section 2.3.269, "v1.SubjectRulesReview"	
PathParamter	namespace	object name and auth scope, such as for teams and projects	true	string	

2.2.212.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.269, "v1.SubjectRulesReview"

2.2.212.3. Consumes

- /

2.2.212.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.212.5. Tags

- oapiv1

2.2.213. list or watch objects of kind Template

```
GET /oapi/v1/namespaces/{namespace}/templates
```

2.2.213.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParamter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParam eter	resourceVersi on	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParam eter	timeoutSecon ds	Timeout for the list/watch call.	false	integer	
PathParam eter	namespace	object name and auth scope, such as for teams and projects	true	string	

2.2.213.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.281, "v1.TemplateList"

2.2.213.3. Consumes

- /

2.2.213.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf
- application/json;stream=watch
- application/vnd.kubernetes.protobuf;stream=watch

2.2.213.5. Tags

- oapiv1

2.2.214. create a Template

POST /oapi/v1/namespaces/{namespace}/templates

2.2.214.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParameter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParameter	body		true	Section 2.3.280, "v1.Template"	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	

2.2.214.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.280, "v1.Template"

2.2.214.3. Consumes

- /

2.2.214.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.214.5. Tags

- oapiv1

2.2.215. delete collection of Template

DELETE /oapi/v1/namespaces/{namespace}/templates

2.2.215.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParam eter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParam ter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParam ter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParam eter	resourceVersi on	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParam eter	timeoutSecon ds	Timeout for the list/watch call.	false	integer	
PathParamet er	namespace	object name and auth scope, such as for teams and projects	true	string	

2.2.215.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.264, "v1.Status"

2.2.215.3. Consumes

- /

2.2.215.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.215.5. Tags

- oapiv1

2.2.216. read the specified Template

```
GET /oapi/v1/namespaces/{namespace}/templates/{name}
```

2.2.216.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParam eter	export	Should this value be exported. Export strips fields that a user can not specify.	false	boolean	
QueryParam eter	exact	Should the export be exact. Exact export maintains cluster-specific fields like 'Namespace'.	false	boolean	

Type	Name	Description	Required	Schema	Default
PathParamet er	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParamet er	name	name of the Template	true	string	

2.2.216.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.280, "v1.Template"

2.2.216.3. Consumes

- /

2.2.216.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.216.5. Tags

- oapiv1

2.2.217. partially update the specified Template

```
PATCH /oapi/v1/namespaces/{namespace}/templates/{name}
```

2.2.217.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParame ter	pretty	If 'true', then the output is pretty printed.	false	string	

Type	Name	Description	Required	Schema	Default
BodyParameter	body		true	Section 2.3.180 , "v1.Patch"	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParameter	name	name of the Template	true	string	

2.2.217.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.280 , "v1.Template"

2.2.217.3. Consumes

- application/json-patch+json
- application/merge-patch+json
- application/strategic-merge-patch+json

2.2.217.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.217.5. Tags

- oapiv1

2.2.218. replace the specified Template

```
PUT /oapi/v1/namespaces/{namespace}/templates/{name}
```

2.2.218.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParameter	body		true	Section 2.3.280 , "v1.Template"	
PathParamter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParamter	name	name of the Template	true	string	

2.2.218.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.280 , "v1.Template"

2.2.218.3. Consumes

- /

2.2.218.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.218.5. Tags

- oapiv1

2.2.219. delete a Template

```
DELETE /oapi/v1/namespaces/{namespace}/templates/{name}
```

2.2.219.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam ter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamet er	body		true	Section 2.3.6 1, "v1.DeleteOptions"	
QueryParam ter	gracePeriodS econds	The duration in seconds before the object should be deleted. Value must be non-negative integer. The value zero indicates delete immediately. If this value is nil, the default grace period for the specified type will be used. Defaults to a per object value if not specified. zero means delete immediately.	false	integer	

Type	Name	Description	Required	Schema	Default
QueryParam eter	orphanDepen dents	Deprecated: please use the PropagationP olicy, this field will be deprecated in 1.7. Should the dependent objects be orphaned. If true/false, the "orphan" finalizer will be added to/removed from the object's finalizers list. Either this field or PropagationP olicy may be set, but not both.	false	boolean	
QueryParam eter	propagationP olicy	Whether and how garbage collection will be performed. Either this field or OrphanDepen dents may be set, but not both. The default policy is decided by the existing finalizer set in the metadata.fin alizers and the resource- specific default policy.	false	string	

Type	Name	Description	Required	Schema	Default
PathParamet er	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParamet er	name	name of the Template	true	string	

2.2.219.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.264, "v1.Status"

2.2.219.3. Consumes

- /

2.2.219.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.219.5. Tags

- oapiv1

2.2.220. list or watch objects of kind NetNamespace

GET /oapi/v1/netnamespaces

2.2.220.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParam ter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParam ter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParam ter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParamter	resourceVersion	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParamter	timeoutSeconds	Timeout for the list/watch call.	false	integer	

2.2.220.2. Responses

HTTP Code	Description	Schema
-----------	-------------	--------

HTTP Code	Description	Schema
200	success	Section 2.3.162, "v1.NetNamespaceList"

2.2.220.3. Consumes

- /

2.2.220.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf
- application/json;stream=watch
- application/vnd.kubernetes.protobuf;stream=watch

2.2.220.5. Tags

- oapiv1

2.2.221. create a NetNamespace

POST /oapi/v1/netnamespaces

2.2.221.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParameter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParameter	body		true	Section 2.3.161, "v1.NetNamespace"	

2.2.221.2. Responses

HTTP Code	Description	Schema
-----------	-------------	--------

HTTP Code	Description	Schema
200	success	Section 2.3.161, "v1.NetNamespace"

2.2.221.3. Consumes

- /

2.2.221.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.221.5. Tags

- oapiv1

2.2.222. delete collection of NetNamespace

DELETE /oapi/v1/netnamespaces

2.2.222.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParam eter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParam ter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParam ter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParamter	resourceVersion	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParamter	timeoutSeconds	Timeout for the list/watch call.	false	integer	

2.2.222.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.264, "v1.Status"

2.2.222.3. Consumes

- /

2.2.222.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.222.5. Tags

- oapiv1

2.2.223. read the specified NetNamespace

GET /oapi/v1/netnamespaces/{name}

2.2.223.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParam eter	export	Should this value be exported. Export strips fields that a user can not specify.	false	boolean	
QueryParam eter	exact	Should the export be exact. Exact export maintains cluster-specific fields like 'Namespace'.	false	boolean	
PathParamet er	name	name of the NetNamespac e	true	string	

2.2.223.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.161 , "v1.NetNamespace"

2.2.223.3. Consumes

- /

2.2.223.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.223.5. Tags

- oapiv1

2.2.224. partially update the specified NetNamespace

PATCH /oapi/v1/netnamespaces/{name}

2.2.224.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParameter	body		true	Section 2.3.180 , "v1.Patch"	
PathParamet	name	name of the NetNamespac	true	string	

2.2.224.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.161, "v1.NetNamespace"

2.2.224.3. Consumes

- application/json-patch+json
- application/merge-patch+json
- application/strategic-merge-patch+json

2.2.224.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.224.5. Tags

- oapiv1

2.2.225. replace the specified NetNamespace

```
PUT /oapi/v1/netnamespaces/{name}
```

2.2.225.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamet er	body		true	Section 2.3.161, "v1.NetName space"	
PathParamet er	name	name of the NetNamespac e	true	string	

2.2.225.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.161 , "v1.NetNamespace"

2.2.225.3. Consumes

- /

2.2.225.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.225.5. Tags

- oapiv1

2.2.226. delete a NetNamespace

```
DELETE /oapi/v1/netnamespaces/{name}
```

2.2.226.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamet er	body		true	Section 2.3.61 , "v1.DeleteOptions"	

Type	Name	Description	Required	Schema	Default
QueryParam ter	gracePeriodS econds	The duration in seconds before the object should be deleted. Value must be non-negative integer. The value zero indicates delete immediately. If this value is nil, the default grace period for the specified type will be used. Defaults to a per object value if not specified. zero means delete immediately.	false	integer	

Type	Name	Description	Required	Schema	Default
QueryParam eter	orphanDepen dents	Deprecated: please use the PropagationP olicy, this field will be deprecated in 1.7. Should the dependent objects be orphaned. If true/false, the "orphan" finalizer will be added to/removed from the object's finalizers list. Either this field or PropagationP olicy may be set, but not both.	false	boolean	
QueryParam eter	propagationP olicy	Whether and how garbage collection will be performed. Either this field or OrphanDepen dents may be set, but not both. The default policy is decided by the existing finalizer set in the metadata.fin alizers and the resource- specific default policy.	false	string	

Type	Name	Description	Required	Schema	Default
PathParam eter	name	name of the NetNamespac e	true	string	

2.2.226.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.264, "v1.Status"

2.2.226.3. Consumes

- /

2.2.226.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.226.5. Tags

- oapiv1

2.2.227. list or watch objects of kind OAuthAccessToken

GET /oapi/v1/oauthaccesstokens

2.2.227.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParamter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParamter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParamter	resourceVersion	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParamter	timeoutSeconds	Timeout for the list/watch call.	false	integer	

2.2.227.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.168, "v1.OAuthAccessTokenList"

2.2.227.3. Consumes

- /

2.2.227.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf
- application/json;stream=watch
- application/vnd.kubernetes.protobuf;stream=watch

2.2.227.5. Tags

- oapiv1

2.2.228. create an OAuthAccessToken

POST /oapi/v1/oauthaccesstokens

2.2.228.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParameter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParameter	body		true	Section 2.3.167 , "v1.OAuthAccessToken"	

2.2.228.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.167 , "v1.OAuthAccessToken"

2.2.228.3. Consumes

- /

2.2.228.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.228.5. Tags

- oapiv1

2.2.229. delete collection of OAuthAccessToken

DELETE /oapi/v1/oauthaccessstokens

2.2.229.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParameter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParameter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParameter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParam ter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParamter	resourceVersion	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParamter	timeoutSeconds	Timeout for the list/watch call.	false	integer	

2.2.229.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.264, "v1.Status"

2.2.229.3. Consumes

- /

2.2.229.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.229.5. Tags

- oapiv1

2.2.230. read the specified OAuthAccessToken

```
GET /oapi/v1/oauthaccessstokens/{name}
```

2.2.230.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParam eter	export	Should this value be exported. Export strips fields that a user can not specify.	false	boolean	
QueryParam eter	exact	Should the export be exact. Exact export maintains cluster-specific fields like 'Namespace'.	false	boolean	
PathParam eter	name	name of the OAuthAccess Token	true	string	

2.2.230.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.167 , "v1.OAuthAccessToken"

2.2.230.3. Consumes

- /

2.2.230.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.230.5. Tags

- oapiv1

2.2.231. partially update the specified OAuthAccessToken

PATCH /oapi/v1/oauthaccesstokens/{name}

2.2.231.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParameter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParameter	body		true	Section 2.3.180 , "v1.Patch"	
PathParameter	name	name of the OAuthAccess Token	true	string	

2.2.231.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.167, "v1.OAuthAccessToken"

2.2.231.3. Consumes

- application/json-patch+json
- application/merge-patch+json
- application/strategic-merge-patch+json

2.2.231.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.231.5. Tags

- oapiv1

2.2.232. replace the specified OAuthAccessToken

```
PUT /oapi/v1/oauthaccessstokens/{name}
```

2.2.232.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParameter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParameter	body		true	Section 2.3.167, "v1.OAuthAccessToken"	
PathParameter	name	name of the OAuthAccess Token	true	string	

2.2.232.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.167 , "v1.OAuthAccessToken"

2.2.232.3. Consumes

- /

2.2.232.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.232.5. Tags

- oapiv1

2.2.233. delete an OAuthAccessToken

```
DELETE /oapi/v1/oauthaccessstokens/{name}
```

2.2.233.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamet er	body		true	Section 2.3.61 , "v1.DeleteOptions"	

Type	Name	Description	Required	Schema	Default
QueryParam ter	gracePeriodS econds	The duration in seconds before the object should be deleted. Value must be non-negative integer. The value zero indicates delete immediately. If this value is nil, the default grace period for the specified type will be used. Defaults to a per object value if not specified. zero means delete immediately.	false	integer	

Type	Name	Description	Required	Schema	Default
QueryParam ter	orphanDepen dents	Deprecated: please use the PropagationP olicy, this field will be deprecated in 1.7. Should the dependent objects be orphaned. If true/false, the "orphan" finalizer will be added to/removed from the object's finalizers list. Either this field or PropagationP olicy may be set, but not both.	false	boolean	
QueryParam ter	propagationP olicy	Whether and how garbage collection will be performed. Either this field or OrphanDepen dents may be set, but not both. The default policy is decided by the existing finalizer set in the metadata.fin alizers and the resource- specific default policy.	false	string	

Type	Name	Description	Required	Schema	Default
PathParam eter	name	name of the OAuthAccess Token	true	string	

2.2.233.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.264, "v1.Status"

2.2.233.3. Consumes

- /

2.2.233.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.233.5. Tags

- oapiv1

2.2.234. list or watch objects of kind OAuthAuthorizeToken

GET /oapi/v1/oauthauthorizetokens

2.2.234.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParamter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParamter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParam ter	resourceVersi on	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParam ter	timeoutSecon ds	Timeout for the list/watch call.	false	integer	

2.2.234.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.170, "v1.OAuthAuthorizeTokenList"

2.2.234.3. Consumes

- /

2.2.234.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf
- application/json;stream=watch
- application/vnd.kubernetes.protobuf;stream=watch

2.2.234.5. Tags

- oapiv1

2.2.235. create an OAuthAuthorizeToken

POST /oapi/v1/oauthauthorizetokens

2.2.235.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamet er	body		true	Section 2.3.169 , "v1.OAuthAu thorizeToken "	

2.2.235.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.169 , "v1.OAuthAuthorizeToken"

2.2.235.3. Consumes

- /

2.2.235.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.235.5. Tags

- oapiv1

2.2.236. delete collection of OAuthAuthorizeToken

```
DELETE /oapi/v1/oauthauthorizetokens
```

2.2.236.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParam eter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParam eter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParam ter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParamter	resourceVersion	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParamter	timeoutSeconds	Timeout for the list/watch call.	false	integer	

2.2.236.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.264, "v1.Status"

2.2.236.3. Consumes

- /

2.2.236.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.236.5. Tags

- oapiv1

2.2.237. read the specified OAuthAuthorizeToken

GET /oapi/v1/oauthauthorizetokens/{name}

2.2.237.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParam eter	export	Should this value be exported. Export strips fields that a user can not specify.	false	boolean	
QueryParam eter	exact	Should the export be exact. Exact export maintains cluster-specific fields like 'Namespace'.	false	boolean	
PathParam eter	name	name of the OAuthAuthorizeToken	true	string	

2.2.237.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.169, "v1.OAuthAuthorizeToken"

2.2.237.3. Consumes

- /

2.2.237.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.237.5. Tags

- oapiv1

2.2.238. partially update the specified OAuthAuthorizeToken

PATCH /oapi/v1/oauthauthorizetokens/{name}

2.2.238.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParameter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParameter	body		true	Section 2.3.180, "v1.Patch"	
PathParameter	name	name of the OAuthAuthorizeToken	true	string	

2.2.238.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.169, "v1.OAuthAuthorizeToken"

2.2.238.3. Consumes

- application/json-patch+json
- application/merge-patch+json
- application/strategic-merge-patch+json

2.2.238.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.238.5. Tags

- oapiv1

2.2.239. replace the specified OAuthAuthorizeToken

```
PUT /oapi/v1/oauthauthorizetokens/{name}
```

2.2.239.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParameter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParameter	body		true	Section 2.3.169, "v1.OAuthAuthorizeToken"	
PathParameter	name	name of the OAuthAuthorizeToken	true	string	

2.2.239.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.169, "v1.OAuthAuthorizeToken"

2.2.239.3. Consumes

- /

2.2.239.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.239.5. Tags

- oapiv1

2.2.240. delete an OAuthAuthorizeToken

DELETE /oapi/v1/oauthauthorizetokens/{name}

2.2.240.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamet er	body		true	Section 2.3.61, "v1.DeleteOptions"	

Type	Name	Description	Required	Schema	Default
QueryParam ter	gracePeriodS econds	The duration in seconds before the object should be deleted. Value must be non-negative integer. The value zero indicates delete immediately. If this value is nil, the default grace period for the specified type will be used. Defaults to a per object value if not specified. zero means delete immediately.	false	integer	

Type	Name	Description	Required	Schema	Default
QueryParam eter	orphanDepen dents	Deprecated: please use the PropagationP olicy, this field will be deprecated in 1.7. Should the dependent objects be orphaned. If true/false, the "orphan" finalizer will be added to/removed from the object's finalizers list. Either this field or PropagationP olicy may be set, but not both.	false	boolean	
QueryParam eter	propagationP olicy	Whether and how garbage collection will be performed. Either this field or OrphanDepen dents may be set, but not both. The default policy is decided by the existing finalizer set in the metadata.fin alizers and the resource- specific default policy.	false	string	

Type	Name	Description	Required	Schema	Default
PathParamet er	name	name of the OAuthAuthori zeToken	true	string	

2.2.240.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.264, "v1.Status"

2.2.240.3. Consumes

- /

2.2.240.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.240.5. Tags

- oapiv1

2.2.241. list or watch objects of kind OAuthClientAuthorization

GET /oapi/v1/oauthclientauthorizations

2.2.241.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParam ter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParam ter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParam ter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParamter	resourceVersion	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParamter	timeoutSeconds	Timeout for the list/watch call.	false	integer	

2.2.241.2. Responses

HTTP Code	Description	Schema
-----------	-------------	--------

HTTP Code	Description	Schema
200	success	Section 2.3.173, "v1.OAuthClientAuthorizationList"

2.2.241.3. Consumes

- /

2.2.241.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf
- application/json;stream=watch
- application/vnd.kubernetes.protobuf;stream=watch

2.2.241.5. Tags

- oapiv1

2.2.242. create an OAuthClientAuthorization

POST /oapi/v1/oauthclientauthorizations

2.2.242.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamenter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParameter	body		true	Section 2.3.172, "v1.OAuthClientAuthorization"	

2.2.242.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.172, "v1.OAuthClientAuthorization"

2.2.242.3. Consumes

- /

2.2.242.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.242.5. Tags

- oapiv1

2.2.243. delete collection of OAuthClientAuthorization

DELETE /oapi/v1/oauthclientauthorizations

2.2.243.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParam eter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParam ter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParam ter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParamter	resourceVersion	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParamter	timeoutSeconds	Timeout for the list/watch call.	false	integer	

2.2.243.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.264, "v1.Status"

2.2.243.3. Consumes

- /

2.2.243.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.243.5. Tags

- oapiv1

2.2.244. read the specified OAuthClientAuthorization

```
GET /oapi/v1/oauthclientauthorizations/{name}
```

2.2.244.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParam eter	export	Should this value be exported. Export strips fields that a user can not specify.	false	boolean	
QueryParam eter	exact	Should the export be exact. Exact export maintains cluster-specific fields like 'Namespace'.	false	boolean	
PathParam eter	name	name of the OAuthClientA uthorization	true	string	

2.2.244.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.172 , "v1.OAuthClientAuthorization"

2.2.244.3. Consumes

- /

2.2.244.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.244.5. Tags

- oapiv1

2.2.245. partially update the specified OAuthClientAuthorization

PATCH /oapi/v1/oauthclientauthorizations/{name}

2.2.245.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParameter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParameter	body		true	Section 2.3.180 , "v1.Patch"	
PathParameter	name	name of the OAuthClientA uthorization	true	string	

2.2.245.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.172, "v1.OAuthClientAuthorization"

2.2.245.3. Consumes

- application/json-patch+json
- application/merge-patch+json
- application/strategic-merge-patch+json

2.2.245.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.245.5. Tags

- oapiv1

2.2.246. replace the specified OAuthClientAuthorization

```
PUT /oapi/v1/oauthclientauthorizations/{name}
```

2.2.246.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParameter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParameter	body		true	Section 2.3.172, "v1.OAuthClientAuthorization"	
PathParameter	name	name of the OAuthClientA uthorization	true	string	

2.2.246.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.172, "v1.OAuthClientAuthorization"

2.2.246.3. Consumes

- /

2.2.246.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.246.5. Tags

- oapiv1

2.2.247. delete an OAuthClientAuthorization

DELETE /oapi/v1/oauthclientauthorizations/{name}

2.2.247.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamet er	body		true	Section 2.3.61, "v1.DeleteOptions"	

Type	Name	Description	Required	Schema	Default
QueryParam ter	gracePeriodS econds	The duration in seconds before the object should be deleted. Value must be non-negative integer. The value zero indicates delete immediately. If this value is nil, the default grace period for the specified type will be used. Defaults to a per object value if not specified. zero means delete immediately.	false	integer	

Type	Name	Description	Required	Schema	Default
QueryParam ter	orphanDepen dents	Deprecated: please use the PropagationP olicy, this field will be deprecated in 1.7. Should the dependent objects be orphaned. If true/false, the "orphan" finalizer will be added to/removed from the object's finalizers list. Either this field or PropagationP olicy may be set, but not both.	false	boolean	
QueryParam ter	propagationP olicy	Whether and how garbage collection will be performed. Either this field or OrphanDepen dents may be set, but not both. The default policy is decided by the existing finalizer set in the metadata.fin alizers and the resource- specific default policy.	false	string	

Type	Name	Description	Required	Schema	Default
PathParamet er	name	name of the OAuthClientA uthorization	true	string	

2.2.247.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.264, "v1.Status"

2.2.247.3. Consumes

- /

2.2.247.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.247.5. Tags

- oapiv1

2.2.248. list or watch objects of kind OAuthClient

GET /oapi/v1/oauthclients

2.2.248.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParam ter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParam ter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParam ter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParam ter	resourceVersi on	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParam ter	timeoutSecon ds	Timeout for the list/watch call.	false	integer	

2.2.248.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.174, "v1.OAuthClientList"

2.2.248.3. Consumes

- /

2.2.248.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf
- application/json;stream=watch
- application/vnd.kubernetes.protobuf;stream=watch

2.2.248.5. Tags

- oapiv1

2.2.249. create an OAuthClient

POST /oapi/v1/oauthclients

2.2.249.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParameter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParameter	body		true	Section 2.3.171 , "v1.OAuthClient"	

2.2.249.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.171 , "v1.OAuthClient"

2.2.249.3. Consumes

- /

2.2.249.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.249.5. Tags

- oapiv1

2.2.250. delete collection of OAuthClient

```
DELETE /oapi/v1/oauthclients
```

2.2.250.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParam eter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParam eter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParam ter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParamter	resourceVersion	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParamter	timeoutSeconds	Timeout for the list/watch call.	false	integer	

2.2.250.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.264, "v1.Status"

2.2.250.3. Consumes

- /

2.2.250.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.250.5. Tags

- oapiv1

2.2.251. read the specified OAuthClient

GET /oapi/v1/oauthclients/{name}

2.2.251.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParam eter	export	Should this value be exported. Export strips fields that a user can not specify.	false	boolean	
QueryParam eter	exact	Should the export be exact. Exact export maintains cluster-specific fields like 'Namespace'.	false	boolean	
PathParam eter	name	name of the OAuthClient	true	string	

2.2.251.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.171, "v1.OAuthClient"

2.2.251.3. Consumes

- /

2.2.251.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.251.5. Tags

- oapiv1

2.2.252. partially update the specified OAuthClient

```
PATCH /oapi/v1/oauthclients/{name}
```

2.2.252.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamet er	body		true	Section 2.3.180, "v1.Patch"	
PathParamet er	name	name of the OAuthClient	true	string	

2.2.252.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.171, "v1.OAuthClient"

2.2.252.3. Consumes

- application/json-patch+json
- application/merge-patch+json
- application/strategic-merge-patch+json

2.2.252.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.252.5. Tags

- oapiv1

2.2.253. replace the specified OAuthClient

```
PUT /oapi/v1/oauthclients/{name}
```

2.2.253.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParameter	body		true	Section 2.3.171 , "v1.OAuthClient"	
PathParamter	name	name of the OAuthClient	true	string	

2.2.253.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.171 , "v1.OAuthClient"

2.2.253.3. Consumes

- /

2.2.253.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.253.5. Tags

- oapiv1

2.2.254. delete an OAuthClient

```
DELETE /oapi/v1/oauthclients/{name}
```

2.2.254.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamet er	body		true	Section 2.3.6 1, "v1.DeleteOptions"	

Type	Name	Description	Required	Schema	Default
QueryParam ter	gracePeriodS econds	The duration in seconds before the object should be deleted. Value must be non-negative integer. The value zero indicates delete immediately. If this value is nil, the default grace period for the specified type will be used. Defaults to a per object value if not specified. zero means delete immediately.	false	integer	

Type	Name	Description	Required	Schema	Default
QueryParam eter	orphanDepen dents	Deprecated: please use the PropagationP olicy, this field will be deprecated in 1.7. Should the dependent objects be orphaned. If true/false, the "orphan" finalizer will be added to/removed from the object's finalizers list. Either this field or PropagationP olicy may be set, but not both.	false	boolean	
QueryParam eter	propagationP olicy	Whether and how garbage collection will be performed. Either this field or OrphanDepen dents may be set, but not both. The default policy is decided by the existing finalizer set in the metadata.fin alizers and the resource- specific default policy.	false	string	
PathParamet er	name	name of the OAuthClient	true	string	

2.2.254.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.264, "v1.Status"

2.2.254.3. Consumes

- /

2.2.254.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.254.5. Tags

- oapiv1

2.2.255. create a PodSecurityPolicyReview

POST /oapi/v1/podsecuritypolicyreviews

2.2.255.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamet er	body		true	Section 2.3.187, "v1.PodSecurityPolicyReview"	

2.2.255.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.187, "v1.PodSecurityPolicyReview"

2.2.255.3. Consumes

- /

2.2.255.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.255.5. Tags

- oapiv1

2.2.256. create a PodSecurityPolicySelfSubjectReview

POST /oapi/v1/podsecuritypolicyselfsubjectreviews

2.2.256.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamet er	body		true	Section 2.3.190 , "v1.PodSecurityPolicySelfSubjectReview"	

2.2.256.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.190 , "v1.PodSecurityPolicySelfSubjectReview"

2.2.256.3. Consumes

- /

2.2.256.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.256.5. Tags

- oapiv1

2.2.257. create a PodSecurityPolicySubjectReview

POST /oapi/v1/podsecuritypolicysubjectreviews

2.2.257.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParameter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParameter	body		true	Section 2.3.192 , "v1.PodSecurityPolicySubjectReview"	

2.2.257.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.192 , "v1.PodSecurityPolicySubjectReview"

2.2.257.3. Consumes

- /

2.2.257.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.257.5. Tags

- oapiv1

2.2.258. list or watch objects of kind Policy

GET /oapi/v1/policies

2.2.258.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParam eter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParam eter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParam eter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParamter	resourceVersion	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParamter	timeoutSeconds	Timeout for the list/watch call.	false	integer	

2.2.258.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.200, "v1.PolicyList"

2.2.258.3. Consumes

- /

2.2.258.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf
- application/json;stream=watch
- application/vnd.kubernetes.protobuf;stream=watch

2.2.258.5. Tags

- oapiv1

2.2.259. create a Policy

POST /oapi/v1/policies

2.2.259.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParameter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParameter	body		true	Section 2.3.197 , "v1.Policy"	

2.2.259.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.197 , "v1.Policy"

2.2.259.3. Consumes

- /

2.2.259.4. Produces

- application/json

- application/yaml
- application/vnd.kubernetes.protobuf

2.2.259.5. Tags

- oapiv1

2.2.260. list or watch objects of kind PolicyBinding

GET /oapi/v1/policybindings

2.2.260.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParam eter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParam eter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParam eter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParam ter	resourceVersi on	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParam ter	timeoutSecon ds	Timeout for the list/watch call.	false	integer	

2.2.260.2. Responses

HTTP Code	Description	Schema
-----------	-------------	--------

HTTP Code	Description	Schema
200	success	Section 2.3.199, "v1.PolicyBindingList"

2.2.260.3. Consumes

- /

2.2.260.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf
- application/json;stream=watch
- application/vnd.kubernetes.protobuf;stream=watch

2.2.260.5. Tags

- oapiv1

2.2.261. create a PolicyBinding

POST /oapi/v1/policybindings

2.2.261.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParameter	body		true	Section 2.3.198, "v1.PolicyBinding"	

2.2.261.2. Responses

HTTP Code	Description	Schema
-----------	-------------	--------

HTTP Code	Description	Schema
200	success	Section 2.3.198, "v1.PolicyBinding"

2.2.261.3. Consumes

- /

2.2.261.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.261.5. Tags

- oapiv1

2.2.262. create a Template

POST /oapi/v1/processedtemplates

2.2.262.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamet er	body		true	Section 2.3.280, "v1.Template"	

2.2.262.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.280, "v1.Template"

2.2.262.3. Consumes

- /

2.2.262.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.262.5. Tags

- oapiv1

2.2.263. list objects of kind ProjectRequest

GET /oapi/v1/projectrequests

2.2.263.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParam eter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParam eter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParam ter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParamter	resourceVersion	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParamter	timeoutSeconds	Timeout for the list/watch call.	false	integer	

2.2.263.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.264, "v1.Status"

2.2.263.3. Consumes

- /

2.2.263.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf
- application/json;stream=watch
- application/vnd.kubernetes.protobuf;stream=watch

2.2.263.5. Tags

- oapiv1

2.2.264. create a ProjectRequest

POST /oapi/v1/projectrequests

2.2.264.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamet er	body		true	Section 2.3.208 , "v1.ProjectRe quest"	

2.2.264.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.208 , "v1.ProjectRequest"

2.2.264.3. Consumes

- /

2.2.264.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.264.5. Tags

- oapiv1

2.2.265. list or watch objects of kind Project

GET /oapi/v1/projects

2.2.265.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParam eter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParam eter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParam ter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParamter	resourceVersion	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParamter	timeoutSeconds	Timeout for the list/watch call.	false	integer	

2.2.265.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.207, "v1.ProjectList"

2.2.265.3. Consumes

- /

2.2.265.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf
- application/json;stream=watch
- application/vnd.kubernetes.protobuf;stream=watch

2.2.265.5. Tags

- oapiv1

2.2.266. create a Project

POST /oapi/v1/projects

2.2.266.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamet er	body		true	Section 2.3.206 , "v1.Project"	

2.2.266.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.206 , "v1.Project"

2.2.266.3. Consumes

- /

2.2.266.4. Produces

- application/json

- application/yaml
- application/vnd.kubernetes.protobuf

2.2.266.5. Tags

- oapiv1

2.2.267. read the specified Project

GET /oapi/v1/projects/{name}

2.2.267.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
PathParam eter	name	name of the Project	true	string	

2.2.267.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.206, "v1.Project"

2.2.267.3. Consumes

- /

2.2.267.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.267.5. Tags

- oapiv1

2.2.268. partially update the specified Project

PATCH /oapi/v1/projects/{name}

2.2.268.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParameter	body		true	Section 2.3.180, "v1.Patch"	
PathParamter	name	name of the Project	true	string	

2.2.268.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.206, "v1.Project"

2.2.268.3. Consumes

- application/json-patch+json
- application/merge-patch+json
- application/strategic-merge-patch+json

2.2.268.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.268.5. Tags

- oapiv1

2.2.269. replace the specified Project

```
PUT /oapi/v1/projects/{name}
```

2.2.269.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamet er	body		true	Section 2.3.206, "v1.Project"	
PathParamet er	name	name of the Project	true	string	

2.2.269.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.206, "v1.Project"

2.2.269.3. Consumes

- /

2.2.269.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.269.5. Tags

- oapiv1

2.2.270. delete a Project

```
DELETE /oapi/v1/projects/{name}
```

2.2.270.1. Parameters

Type	Name	Description	Required	Schema	Default
------	------	-------------	----------	--------	---------

Type	Name	Description	Required	Schema	Default
QueryParamter	pretty	If 'true', then the output is pretty printed.	false	string	
PathParamter	name	name of the Project	true	string	

2.2.270.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.264, "v1.Status"

2.2.270.3. Consumes

- /

2.2.270.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.270.5. Tags

- oapiv1

2.2.271. create a ResourceAccessReview

POST /oapi/v1/resourceaccessreviews

2.2.271.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamter	pretty	If 'true', then the output is pretty printed.	false	string	

Type	Name	Description	Required	Schema	Default
BodyParameter	body		true	Section 2.3.217, "v1.ResourceAccessReview"	

2.2.271.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.217, "v1.ResourceAccessReview"

2.2.271.3. Consumes

- /

2.2.271.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.271.5. Tags

- oapiv1

2.2.272. list or watch objects of kind RoleBindingRestriction

```
GET /oapi/v1/rolebindingrestrictions
```

2.2.272.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParameter	pretty	If 'true', then the output is pretty printed.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParamter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParamter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParam ter	resourceVersion	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParam ter	timeoutSeconds	Timeout for the list/watch call.	false	integer	

2.2.272.2. Responses

HTTP Code	Description	Schema
-----------	-------------	--------

HTTP Code	Description	Schema
200	success	Section 2.3.228 , "v1.RoleBindingRestrictionList"

2.2.272.3. Consumes

- /

2.2.272.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf
- application/json;stream=watch
- application/vnd.kubernetes.protobuf;stream=watch

2.2.272.5. Tags

- oapiv1

2.2.273. create a RoleBindingRestriction

POST /oapi/v1/rolebindingrestrictions

2.2.273.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamenter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParameter	body		true	Section 2.3.27 , "v1.RoleBindingRestriction"	

2.2.273.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.227, "v1.RoleBindingRestriction"

2.2.273.3. Consumes

- /

2.2.273.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.273.5. Tags

- oapiv1

2.2.274. list objects of kind RoleBinding

GET /oapi/v1/rolebindings

2.2.274.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParam eter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParam ter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParam ter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParamter	resourceVersion	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParamter	timeoutSeconds	Timeout for the list/watch call.	false	integer	

2.2.274.2. Responses

HTTP Code	Description	Schema
-----------	-------------	--------

HTTP Code	Description	Schema
200	success	Section 2.3.226, "v1.RoleBindingList"

2.2.274.3. Consumes

- /

2.2.274.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf
- application/json;stream=watch
- application/vnd.kubernetes.protobuf;stream=watch

2.2.274.5. Tags

- oapiv1

2.2.275. create a RoleBinding

POST /oapi/v1/rolebindings

2.2.275.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParameter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParameter	body		true	Section 2.3.225, "v1.RoleBinding"	

2.2.275.2. Responses

HTTP Code	Description	Schema
-----------	-------------	--------

HTTP Code	Description	Schema
200	success	Section 2.3.225, "v1.RoleBinding"

2.2.275.3. Consumes

- /

2.2.275.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.275.5. Tags

- oapiv1

2.2.276. list objects of kind Role

GET /oapi/v1/roles

2.2.276.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParam eter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParam ter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParam ter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParamter	resourceVersion	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParamter	timeoutSeconds	Timeout for the list/watch call.	false	integer	

2.2.276.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.230, "v1.RoleList"

2.2.276.3. Consumes

- /

2.2.276.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf
- application/json;stream=watch
- application/vnd.kubernetes.protobuf;stream=watch

2.2.276.5. Tags

- oapiv1

2.2.277. create a Role

POST /oapi/v1/roles

2.2.277.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamet er	body		true	Section 2.3.224, "v1.Role"	

2.2.277.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.224, "v1.Role"

2.2.277.3. Consumes

- /

2.2.277.4. Produces

- application/json

- application/yaml
- application/vnd.kubernetes.protobuf

2.2.277.5. Tags

- oapiv1

2.2.278. list or watch objects of kind Route

GET /oapi/v1/routes

2.2.278.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParameter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParameter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParameter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParameter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParamter	resourceVersion	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParamter	timeoutSeconds	Timeout for the list/watch call.	false	integer	

2.2.278.2. Responses

HTTP Code	Description	Schema
-----------	-------------	--------

HTTP Code	Description	Schema
200	success	Section 2.3.235, "v1.RouteList"

2.2.278.3. Consumes

- /

2.2.278.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf
- application/json;stream=watch
- application/vnd.kubernetes.protobuf;stream=watch

2.2.278.5. Tags

- oapiv1

2.2.279. create a Route

POST /oapi/v1/routes

2.2.279.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParameter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParameter	body		true	Section 2.3.232, "v1.Route"	

2.2.279.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.232, "v1.Route"

2.2.279.3. Consumes

- /

2.2.279.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.279.5. Tags

- oapiv1

2.2.280. create a SelfSubjectRulesReview

POST /oapi/v1/selfsubjectrulesreviews

2.2.280.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParameter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParameter	body		true	Section 2.3.252 , "v1.SelfSubjectRulesReview"	

2.2.280.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.252 , "v1.SelfSubjectRulesReview"

2.2.280.3. Consumes

- /

2.2.280.4. Produces

- application/json

- application/yaml
- application/vnd.kubernetes.protobuf

2.2.280.5. Tags

- oapiv1

2.2.281. create a SubjectAccessReview

POST /oapi/v1/subjectaccessreviews

2.2.281.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamet er	body		true	Section 2.3.268 , "v1.SubjectA ccessReview"	

2.2.281.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.268 , "v1.SubjectAccessReview"

2.2.281.3. Consumes

- /

2.2.281.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.281.5. Tags

- oapiv1

2.2.282. create a SubjectRulesReview

POST /oapi/v1/subjectrulesreviews

2.2.282.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamet er	body		true	Section 2.3.269 , "v1.SubjectR ulesReview"	

2.2.282.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.269 , "v1.SubjectRulesReview"

2.2.282.3. Consumes

- /

2.2.282.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.282.5. Tags

- oapiv1

2.2.283. list or watch objects of kind Template

GET /oapi/v1/templates

2.2.283.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParamter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParamter	resourceVersion	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParamter	timeoutSeconds	Timeout for the list/watch call.	false	integer	

2.2.283.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.281, "v1.TemplateList"

2.2.283.3. Consumes

- /

2.2.283.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf
- application/json;stream=watch
- application/vnd.kubernetes.protobuf;stream=watch

2.2.283.5. Tags

- oapiv1

2.2.284. create a Template

POST /oapi/v1/templates

2.2.284.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParameter	body		true	Section 2.3.280 , "v1.Template"	

2.2.284.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.280 , "v1.Template"

2.2.284.3. Consumes

- /

2.2.284.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.284.5. Tags

- oapiv1

2.2.285. create an UserIdentityMapping

POST /oapi/v1/useridentitymappings

2.2.285.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamet er	body		true	Section 2.3.284 , "v1.UserIdentityMapping"	

2.2.285.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.284 , "v1.UserIdentityMapping"

2.2.285.3. Consumes

- /

2.2.285.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.285.5. Tags

- oapiv1

2.2.286. read the specified UserIdentityMapping

```
GET /oapi/v1/useridentitymappings/{name}
```

2.2.286.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
PathParam eter	name	name of the UserIdentity Mapping	true	string	

2.2.286.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.284, "v1.UserIdentityMapping"

2.2.286.3. Consumes

- /

2.2.286.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.286.5. Tags

- oapiv1

2.2.287. partially update the specified UserIdentityMapping

```
PATCH /oapi/v1/useridentitymappings/{name}
```

2.2.287.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamet er	body		true	Section 2.3.180, "v1.Patch"	
PathParamet er	name	name of the UserIdentity Mapping	true	string	

2.2.287.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.284, "v1.UserIdentityMapping"

2.2.287.3. Consumes

- application/json-patch+json
- application/merge-patch+json
- application/strategic-merge-patch+json

2.2.287.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.287.5. Tags

- oapiv1

2.2.288. replace the specified UserIdentityMapping

```
PUT /oapi/v1/useridentitymappings/{name}
```

2.2.288.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParameter	body		true	Section 2.3.284 , "v1.UserIdentityMapping"	
PathParamter	name	name of the UserIdentity Mapping	true	string	

2.2.288.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.284 , "v1.UserIdentityMapping"

2.2.288.3. Consumes

- /

2.2.288.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.288.5. Tags

- oapiv1

2.2.289. delete an UserIdentityMapping

```
DELETE /oapi/v1/useridentitymappings/{name}
```

2.2.289.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamter	pretty	If 'true', then the output is pretty printed.	false	string	
PathParamter	name	name of the UserIdentity Mapping	true	string	

2.2.289.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.264, "v1.Status"

2.2.289.3. Consumes

- /

2.2.289.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.289.5. Tags

- oapiv1

2.2.290. list or watch objects of kind User

GET /oapi/v1/users

2.2.290.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamter	pretty	If 'true', then the output is pretty printed.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParam ter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParam ter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParam ter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParam eter	resourceVersi on	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParam eter	timeoutSecon ds	Timeout for the list/watch call.	false	integer	

2.2.290.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.285, "v1.UserList"

2.2.290.3. Consumes

- /

2.2.290.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf
- application/json;stream=watch
- application/vnd.kubernetes.protobuf;stream=watch

2.2.290.5. Tags

- oapiv1

2.2.291. create an User

POST /oapi/v1/users

2.2.291.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamenter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParameter	body		true	Section 2.3.283 , "v1.User"	

2.2.291.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.283 , "v1.User"

2.2.291.3. Consumes

- /

2.2.291.4. Produces

- application/json

- application/yaml
- application/vnd.kubernetes.protobuf

2.2.291.5. Tags

- oapiv1

2.2.292. delete collection of User

DELETE /oapi/v1/users

2.2.292.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParam eter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParam eter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParam eter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParamter	resourceVersion	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParamter	timeoutSeconds	Timeout for the list/watch call.	false	integer	

2.2.292.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.264, "v1.Status"

2.2.292.3. Consumes

- /

2.2.292.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.292.5. Tags

- oapiv1

2.2.293. read the specified User

GET /oapi/v1/users/{name}

2.2.293.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParam eter	export	Should this value be exported. Export strips fields that a user can not specify.	false	boolean	
QueryParam eter	exact	Should the export be exact. Exact export maintains cluster-specific fields like 'Namespace'.	false	boolean	
PathParam eter	name	name of the User	true	string	

2.2.293.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.283, "v1.User"

2.2.293.3. Consumes

- /

2.2.293.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.293.5. Tags

- oapiv1

2.2.294. partially update the specified User

PATCH /oapi/v1/users/{name}

2.2.294.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamet er	body		true	Section 2.3.180, "v1.Patch"	
PathParamet er	name	name of the User	true	string	

2.2.294.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.283, "v1.User"

2.2.294.3. Consumes

- application/json-patch+json
- application/merge-patch+json
- application/strategic-merge-patch+json

2.2.294.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.294.5. Tags

- oapiv1

2.2.295. replace the specified User

```
PUT /oapi/v1/users/{name}
```

2.2.295.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParameter	body		true	Section 2.3.283 , "v1.User"	
PathParamter	name	name of the User	true	string	

2.2.295.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.283 , "v1.User"

2.2.295.3. Consumes

- /

2.2.295.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.295.5. Tags

- oapiv1

2.2.296. delete an User

```
DELETE /oapi/v1/users/{name}
```

2.2.296.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamet er	body		true	Section 2.3.6 1, "v1.DeleteOptions"	

Type	Name	Description	Required	Schema	Default
QueryParam ter	gracePeriodS econds	The duration in seconds before the object should be deleted. Value must be non-negative integer. The value zero indicates delete immediately. If this value is nil, the default grace period for the specified type will be used. Defaults to a per object value if not specified. zero means delete immediately.	false	integer	

Type	Name	Description	Required	Schema	Default
QueryParam ter	orphanDepen dents	Deprecated: please use the PropagationP olicy, this field will be deprecated in 1.7. Should the dependent objects be orphaned. If true/false, the "orphan" finalizer will be added to/removed from the object's finalizers list. Either this field or PropagationP olicy may be set, but not both.	false	boolean	
QueryParam ter	propagationP olicy	Whether and how garbage collection will be performed. Either this field or OrphanDepen dents may be set, but not both. The default policy is decided by the existing finalizer set in the metadata.fin alizers and the resource- specific default policy.	false	string	
PathParamet er	name	name of the User	true	string	

2.2.296.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.264, "v1.Status"

2.2.296.3. Consumes

- /

2.2.296.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

2.2.296.5. Tags

- oapiv1

2.2.297. watch individual changes to a list of BuildConfig

GET /oapi/v1/watch/buildconfigs

2.2.297.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParam eter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParam ter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParam ter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParamter	resourceVersion	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParamter	timeoutSeconds	Timeout for the list/watch call.	false	integer	

2.2.297.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.291, "v1.WatchEvent"

2.2.297.3. Consumes

- /

2.2.297.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf
- application/json;stream=watch
- application/vnd.kubernetes.protobuf;stream=watch

2.2.297.5. Tags

- oapiv1

2.2.298. watch individual changes to a list of Build

GET /oapi/v1/watch/builds

2.2.298.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParam eter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParam eter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParam ter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParamter	resourceVersion	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParamter	timeoutSeconds	Timeout for the list/watch call.	false	integer	

2.2.298.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.291, "v1.WatchEvent"

2.2.298.3. Consumes

- /

2.2.298.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf
- application/json;stream=watch
- application/vnd.kubernetes.protobuf;stream=watch

2.2.298.5. Tags

- oapiv1

2.2.299. watch individual changes to a list of ClusterNetwork

GET /oapi/v1/watch/clusternetworks

2.2.299.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParam eter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParam eter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParam ter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParamter	resourceVersion	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParamter	timeoutSeconds	Timeout for the list/watch call.	false	integer	

2.2.299.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.291, "v1.WatchEvent"

2.2.299.3. Consumes

- /

2.2.299.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf
- application/json;stream=watch
- application/vnd.kubernetes.protobuf;stream=watch

2.2.299.5. Tags

- oapiv1

2.2.300. watch changes to an object of kind ClusterNetwork

GET /oapi/v1/watch/clusternetworks/{name}

2.2.300.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParam ter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParam eter	resourceVersi on	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParam eter	timeoutSecon ds	Timeout for the list/watch call.	false	integer	
PathParamet er	name	name of the ClusterNetwo rk	true	string	

2.2.300.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.291, "v1.WatchEvent"

2.2.300.3. Consumes

- /

2.2.300.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf
- application/json;stream=watch
- application/vnd.kubernetes.protobuf;stream=watch

2.2.300.5. Tags

- oapiv1

2.2.301. watch individual changes to a list of ClusterPolicy

GET /oapi/v1/watch/clusterpolicies

2.2.301.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParam ter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParam ter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParamter	resourceVersion	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParamter	timeoutSeconds	Timeout for the list/watch call.	false	integer	

2.2.301.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.291, "v1.WatchEvent"

2.2.301.3. Consumes

- /

2.2.301.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf
- application/json;stream=watch
- application/vnd.kubernetes.protobuf;stream=watch

2.2.301.5. Tags

- oapiv1

2.2.302. watch changes to an object of kind ClusterPolicy

GET /oapi/v1/watch/clusterpolicies/{name}

2.2.302.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParameter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParameter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParameter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParameter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParam eter	resourceVersi on	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParam eter	timeoutSecon ds	Timeout for the list/watch call.	false	integer	
PathParamet er	name	name of the ClusterPolicy	true	string	

2.2.302.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.291, "v1.WatchEvent"

2.2.302.3. Consumes

- /

2.2.302.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf
- application/json;stream=watch
- application/vnd.kubernetes.protobuf;stream=watch

2.2.302.5. Tags

- oapiv1

2.2.303. watch individual changes to a list of ClusterPolicyBinding

GET /oapi/v1/watch/clusterpolicybindings

2.2.303.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParameter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParameter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParam ter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParam ter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParam ter	resourceVersi on	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParam ter	timeoutSecon ds	Timeout for the list/watch call.	false	integer	

2.2.303.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.291, "v1.WatchEvent"

2.2.303.3. Consumes

- /

2.2.303.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf
- application/json;stream=watch
- application/vnd.kubernetes.protobuf;stream=watch

2.2.303.5. Tags

- oapiv1

2.2.304. watch changes to an object of kind ClusterPolicyBinding

```
GET /oapi/v1/watch/clusterpolicybindings/{name}
```

2.2.304.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParam eter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParam ter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParam ter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParam eter	resourceVersi on	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParam eter	timeoutSecon ds	Timeout for the list/watch call.	false	integer	
PathParamet er	name	name of the ClusterPolicy Binding	true	string	

2.2.304.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.291, "v1.WatchEvent"

2.2.304.3. Consumes

- /

2.2.304.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf
- application/json;stream=watch
- application/vnd.kubernetes.protobuf;stream=watch

2.2.304.5. Tags

- oapiv1

2.2.305. watch individual changes to a list of ClusterResourceQuota

GET /oapi/v1/watch/clusterresourcequotas

2.2.305.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParam ter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParam ter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParam ter	resourceVersi on	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParam ter	timeoutSecon ds	Timeout for the list/watch call.	false	integer	

2.2.305.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.291, "v1.WatchEvent"

2.2.305.3. Consumes

- /

2.2.305.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf
- application/json;stream=watch
- application/vnd.kubernetes.protobuf;stream=watch

2.2.305.5. Tags

- oapiv1

2.2.306. watch changes to an object of kind ClusterResourceQuota

GET /oapi/v1/watch/clusterresourcequotas/{name}

2.2.306.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParam ter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParam ter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParam eter	resourceVersi on	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParam eter	timeoutSecon ds	Timeout for the list/watch call.	false	integer	
PathParamet er	name	name of the ClusterResourceQuota	true	string	

2.2.306.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.291, "v1.WatchEvent"

2.2.306.3. Consumes

- /

2.2.306.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf
- application/json;stream=watch
- application/vnd.kubernetes.protobuf;stream=watch

2.2.306.5. Tags

- oapiv1

2.2.307. watch individual changes to a list of DeploymentConfig

GET /oapi/v1/watch/deploymentconfigs

2.2.307.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParameter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParameter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParam ter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParam ter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParamter	resourceVersion	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParamter	timeoutSeconds	Timeout for the list/watch call.	false	integer	

2.2.307.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.291, "v1.WatchEvent"

2.2.307.3. Consumes

- /

2.2.307.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf
- application/json;stream=watch
- application/vnd.kubernetes.protobuf;stream=watch

2.2.307.5. Tags

- oapiv1

2.2.308. watch individual changes to a list of EgressNetworkPolicy

GET /oapi/v1/watch/egressnetworkpolicies

2.2.308.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParameter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParameter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParamter	resourceVersion	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParamter	timeoutSeconds	Timeout for the list/watch call.	false	integer	

2.2.308.2. Responses

HTTP Code	Description	Schema
-----------	-------------	--------

HTTP Code	Description	Schema
200	success	Section 2.3.291, "v1.WatchEvent"

2.2.308.3. Consumes

- /

2.2.308.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf
- application/json;stream=watch
- application/vnd.kubernetes.protobuf;stream=watch

2.2.308.5. Tags

- oapiv1

2.2.309. watch individual changes to a list of Group

GET /oapi/v1/watch/groups

2.2.309.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParam ter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParam ter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParamter	resourceVersion	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParamter	timeoutSeconds	Timeout for the list/watch call.	false	integer	

2.2.309.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.291, "v1.WatchEvent"

2.2.309.3. Consumes

- /

2.2.309.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf
- application/json;stream=watch
- application/vnd.kubernetes.protobuf;stream=watch

2.2.309.5. Tags

- oapiv1

2.2.310. watch changes to an object of kind Group

GET /oapi/v1/watch/groups/{name}

2.2.310.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParameter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParameter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParam ter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParam ter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParam eter	resourceVersi on	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParam eter	timeoutSecon ds	Timeout for the list/watch call.	false	integer	
PathParamet er	name	name of the Group	true	string	

2.2.310.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.291, "v1.WatchEvent"

2.2.310.3. Consumes

- /

2.2.310.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf
- application/json;stream=watch
- application/vnd.kubernetes.protobuf;stream=watch

2.2.310.5. Tags

- oapiv1

2.2.311. watch individual changes to a list of HostSubnet

GET /oapi/v1/watch/hostsubnets

2.2.311.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParam ter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParam ter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParam ter	resourceVersi on	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParam ter	timeoutSecon ds	Timeout for the list/watch call.	false	integer	

2.2.311.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.291, "v1.WatchEvent"

2.2.311.3. Consumes

- /

2.2.311.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf
- application/json;stream=watch
- application/vnd.kubernetes.protobuf;stream=watch

2.2.311.5. Tags

- oapiv1

2.2.312. watch changes to an object of kind HostSubnet

```
GET /oapi/v1/watch/hostsubnets/{name}
```

2.2.312.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParameter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParameter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParam eter	resourceVersi on	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParam eter	timeoutSecon ds	Timeout for the list/watch call.	false	integer	
PathParamet er	name	name of the HostSubnet	true	string	

2.2.312.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.291, "v1.WatchEvent"

2.2.312.3. Consumes

- /

2.2.312.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf
- application/json;stream=watch
- application/vnd.kubernetes.protobuf;stream=watch

2.2.312.5. Tags

- oapiv1

2.2.313. watch individual changes to a list of Identity

GET /oapi/v1/watch/identities

2.2.313.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParam ter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParam ter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParam ter	resourceVersi on	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParam ter	timeoutSecon ds	Timeout for the list/watch call.	false	integer	

2.2.313.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.291, "v1.WatchEvent"

2.2.313.3. Consumes

- /

2.2.313.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf
- application/json;stream=watch
- application/vnd.kubernetes.protobuf;stream=watch

2.2.313.5. Tags

- oapiv1

2.2.314. watch changes to an object of kind Identity

```
GET /oapi/v1/watch/identities/{name}
```

2.2.314.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParam ter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParam ter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParam eter	resourceVersi on	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParam eter	timeoutSecon ds	Timeout for the list/watch call.	false	integer	
PathParamet er	name	name of the Identity	true	string	

2.2.314.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.291, "v1.WatchEvent"

2.2.314.3. Consumes

- /

2.2.314.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf
- application/json;stream=watch
- application/vnd.kubernetes.protobuf;stream=watch

2.2.314.5. Tags

- oapiv1

2.2.315. watch individual changes to a list of Image

GET /oapi/v1/watch/images

2.2.315.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParam ter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParam ter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParam ter	resourceVersi on	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParam ter	timeoutSecon ds	Timeout for the list/watch call.	false	integer	

2.2.315.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.291, "v1.WatchEvent"

2.2.315.3. Consumes

- /

2.2.315.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf
- application/json;stream=watch
- application/vnd.kubernetes.protobuf;stream=watch

2.2.315.5. Tags

- oapiv1

2.2.316. watch changes to an object of kind Image

GET /oapi/v1/watch/images/{name}

2.2.316.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParameter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParameter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParamter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParamter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParam eter	resourceVersi on	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParam eter	timeoutSecon ds	Timeout for the list/watch call.	false	integer	
PathParamet er	name	name of the Image	true	string	

2.2.316.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.291, "v1.WatchEvent"

2.2.316.3. Consumes

- /

2.2.316.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf
- application/json;stream=watch
- application/vnd.kubernetes.protobuf;stream=watch

2.2.316.5. Tags

- oapiv1

2.2.317. watch individual changes to a list of ImageStream

GET /oapi/v1/watch/imagestreams

2.2.317.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParam ter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParam ter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParamter	resourceVersion	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParamter	timeoutSeconds	Timeout for the list/watch call.	false	integer	

2.2.317.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.291, "v1.WatchEvent"

2.2.317.3. Consumes

- /

2.2.317.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf
- application/json;stream=watch
- application/vnd.kubernetes.protobuf;stream=watch

2.2.317.5. Tags

- oapiv1

2.2.318. watch individual changes to a list of BuildConfig

GET /oapi/v1/watch/namespaces/{namespace}/buildconfigs

2.2.318.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParam ter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParam ter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParam eter	resourceVersi on	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParam eter	timeoutSecon ds	Timeout for the list/watch call.	false	integer	
PathParamet er	namespace	object name and auth scope, such as for teams and projects	true	string	

2.2.318.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.291, "v1.WatchEvent"

2.2.318.3. Consumes

- /

2.2.318.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf
- application/json;stream=watch
- application/vnd.kubernetes.protobuf;stream=watch

2.2.318.5. Tags

- oapiv1

2.2.319. watch changes to an object of kind BuildConfig

```
GET /oapi/v1/watch/namespaces/{namespace}/buildconfigs/{name}
```

2.2.319.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParam ter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParam ter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParam eter	resourceVersi on	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParam eter	timeoutSecon ds	Timeout for the list/watch call.	false	integer	
PathParamet er	namespace	object name and auth scope, such as for teams and projects	true	string	

Type	Name	Description	Required	Schema	Default
PathParam eter	name	name of the BuildConfig	true	string	

2.2.319.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.291, "v1.WatchEvent"

2.2.319.3. Consumes

- /

2.2.319.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf
- application/json;stream=watch
- application/vnd.kubernetes.protobuf;stream=watch

2.2.319.5. Tags

- oapiv1

2.2.320. watch individual changes to a list of Build

```
GET /oapi/v1/watch/namespaces/{namespace}/builds
```

2.2.320.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParamter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParamter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParam eter	resourceVersi on	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParam eter	timeoutSecon ds	Timeout for the list/watch call.	false	integer	
PathParamet er	namespace	object name and auth scope, such as for teams and projects	true	string	

2.2.320.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.291, "v1.WatchEvent"

2.2.320.3. Consumes

- /

2.2.320.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf
- application/json;stream=watch
- application/vnd.kubernetes.protobuf;stream=watch

2.2.320.5. Tags

- oapiv1

2.2.321. watch changes to an object of kind Build

```
GET /oapi/v1/watch/namespaces/{namespace}/builds/{name}
```

2.2.321.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParameter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParameter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParam ter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParam ter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParam eter	resourceVersi on	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParam eter	timeoutSecon ds	Timeout for the list/watch call.	false	integer	
PathParam eter	namespace	object name and auth scope, such as for teams and projects	true	string	

Type	Name	Description	Required	Schema	Default
PathParamet er	name	name of the Build	true	string	

2.2.321.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.291, "v1.WatchEvent"

2.2.321.3. Consumes

- /

2.2.321.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf
- application/json;stream=watch
- application/vnd.kubernetes.protobuf;stream=watch

2.2.321.5. Tags

- oapiv1

2.2.322. watch individual changes to a list of DeploymentConfig

```
GET /oapi/v1/watch/namespaces/{namespace}/deploymentconfigs
```

2.2.322.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParame ter	pretty	If 'true', then the output is pretty printed.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParamter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParamter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParam eter	resourceVersi on	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParam eter	timeoutSecon ds	Timeout for the list/watch call.	false	integer	
PathParamet er	namespace	object name and auth scope, such as for teams and projects	true	string	

2.2.322.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.291, "v1.WatchEvent"

2.2.322.3. Consumes

- /

2.2.322.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf
- application/json;stream=watch
- application/vnd.kubernetes.protobuf;stream=watch

2.2.322.5. Tags

- oapiv1

2.2.323. watch changes to an object of kind DeploymentConfig

```
GET /oapi/v1/watch/namespaces/{namespace}/deploymentconfigs/{name}
```

2.2.323.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParam ter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParam ter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParamter	resourceVersion	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParamter	timeoutSeconds	Timeout for the list/watch call.	false	integer	
PathParamter	namespace	object name and auth scope, such as for teams and projects	true	string	

Type	Name	Description	Required	Schema	Default
PathParamet er	name	name of the DeploymentC onfig	true	string	

2.2.323.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.291, "v1.WatchEvent"

2.2.323.3. Consumes

- /

2.2.323.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf
- application/json;stream=watch
- application/vnd.kubernetes.protobuf;stream=watch

2.2.323.5. Tags

- oapiv1

2.2.324. watch individual changes to a list of EgressNetworkPolicy

GET /oapi/v1/watch/namespaces/{namespace}/egressnetworkpolicies

2.2.324.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParamter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParamter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParam eter	resourceVersi on	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParam eter	timeoutSecon ds	Timeout for the list/watch call.	false	integer	
PathParamet er	namespace	object name and auth scope, such as for teams and projects	true	string	

2.2.324.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.291, "v1.WatchEvent"

2.2.324.3. Consumes

- /

2.2.324.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf
- application/json;stream=watch
- application/vnd.kubernetes.protobuf;stream=watch

2.2.324.5. Tags

- oapiv1

2.2.325. watch changes to an object of kind EgressNetworkPolicy

```
GET /oapi/v1/watch/namespaces/{namespace}/egressnetworkpolicies/{name}
```

2.2.325.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParam ter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParam ter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParam eter	resourceVersi on	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParam eter	timeoutSecon ds	Timeout for the list/watch call.	false	integer	
PathParam eter	namespace	object name and auth scope, such as for teams and projects	true	string	

Type	Name	Description	Required	Schema	Default
PathParam eter	name	name of the EgressNetworkPolicy	true	string	

2.2.325.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.291, "v1.WatchEvent"

2.2.325.3. Consumes

- /

2.2.325.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf
- application/json;stream=watch
- application/vnd.kubernetes.protobuf;stream=watch

2.2.325.5. Tags

- oapiv1

2.2.326. watch individual changes to a list of ImageStream

GET /oapi/v1/watch/namespaces/{namespace}/imagestreams

2.2.326.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParamter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParamter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParam eter	resourceVersi on	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParam eter	timeoutSecon ds	Timeout for the list/watch call.	false	integer	
PathParamet er	namespace	object name and auth scope, such as for teams and projects	true	string	

2.2.326.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.291, "v1.WatchEvent"

2.2.326.3. Consumes

- /

2.2.326.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf
- application/json;stream=watch
- application/vnd.kubernetes.protobuf;stream=watch

2.2.326.5. Tags

- oapiv1

2.2.327. watch changes to an object of kind ImageStream

```
GET /oapi/v1/watch/namespaces/{namespace}/imagestreams/{name}
```

2.2.327.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParam ter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParam ter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParam eter	resourceVersi on	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParam eter	timeoutSecon ds	Timeout for the list/watch call.	false	integer	
PathParam eter	namespace	object name and auth scope, such as for teams and projects	true	string	

Type	Name	Description	Required	Schema	Default
PathParam eter	name	name of the ImageStream	true	string	

2.2.327.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.291, "v1.WatchEvent"

2.2.327.3. Consumes

- /

2.2.327.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf
- application/json;stream=watch
- application/vnd.kubernetes.protobuf;stream=watch

2.2.327.5. Tags

- oapiv1

2.2.328. watch individual changes to a list of Policy

```
GET /oapi/v1/watch/namespaces/{namespace}/policies
```

2.2.328.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParamter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParamter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParamter	resourceVersion	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParamter	timeoutSeconds	Timeout for the list/watch call.	false	integer	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	

2.2.328.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.291, "v1.WatchEvent"

2.2.328.3. Consumes

- /

2.2.328.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf
- application/json;stream=watch
- application/vnd.kubernetes.protobuf;stream=watch

2.2.328.5. Tags

- oapiv1

2.2.329. watch changes to an object of kind Policy

```
GET /oapi/v1/watch/namespaces/{namespace}/policies/{name}
```

2.2.329.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParam eter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParam ter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParam ter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParamter	resourceVersion	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParamter	timeoutSeconds	Timeout for the list/watch call.	false	integer	
PathParamter	namespace	object name and auth scope, such as for teams and projects	true	string	

Type	Name	Description	Required	Schema	Default
PathParamet er	name	name of the Policy	true	string	

2.2.329.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.291, "v1.WatchEvent"

2.2.329.3. Consumes

- /

2.2.329.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf
- application/json;stream=watch
- application/vnd.kubernetes.protobuf;stream=watch

2.2.329.5. Tags

- oapiv1

2.2.330. watch individual changes to a list of PolicyBinding

```
GET /oapi/v1/watch/namespaces/{namespace}/policybindings
```

2.2.330.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParamter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParamter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParam eter	resourceVersi on	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParam eter	timeoutSecon ds	Timeout for the list/watch call.	false	integer	
PathParamet er	namespace	object name and auth scope, such as for teams and projects	true	string	

2.2.330.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.291, "v1.WatchEvent"

2.2.330.3. Consumes

- /

2.2.330.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf
- application/json;stream=watch
- application/vnd.kubernetes.protobuf;stream=watch

2.2.330.5. Tags

- oapiv1

2.2.331. watch changes to an object of kind PolicyBinding

```
GET /oapi/v1/watch/namespaces/{namespace}/policybindings/{name}
```

2.2.331.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParam eter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParam ter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParam ter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParamter	resourceVersion	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParamter	timeoutSeconds	Timeout for the list/watch call.	false	integer	
PathParamter	namespace	object name and auth scope, such as for teams and projects	true	string	

Type	Name	Description	Required	Schema	Default
PathParamet er	name	name of the PolicyBinding	true	string	

2.2.331.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.291, "v1.WatchEvent"

2.2.331.3. Consumes

- /

2.2.331.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf
- application/json;stream=watch
- application/vnd.kubernetes.protobuf;stream=watch

2.2.331.5. Tags

- oapiv1

2.2.332. watch individual changes to a list of RoleBindingRestriction

```
GET /oapi/v1/watch/namespaces/{namespace}/rolebindingrestrictions
```

2.2.332.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParame ter	pretty	If 'true', then the output is pretty printed.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParamter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParamter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParam eter	resourceVersi on	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParam eter	timeoutSecon ds	Timeout for the list/watch call.	false	integer	
PathParamet er	namespace	object name and auth scope, such as for teams and projects	true	string	

2.2.332.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.291, "v1.WatchEvent"

2.2.332.3. Consumes

- /

2.2.332.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf
- application/json;stream=watch
- application/vnd.kubernetes.protobuf;stream=watch

2.2.332.5. Tags

- oapiv1

2.2.333. watch changes to an object of kind RoleBindingRestriction

```
GET /oapi/v1/watch/namespaces/{namespace}/rolebindingrestrictions/{name}
```

2.2.333.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParam eter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParam ter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParam ter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParamter	resourceVersion	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParamter	timeoutSeconds	Timeout for the list/watch call.	false	integer	
PathParamter	namespace	object name and auth scope, such as for teams and projects	true	string	

Type	Name	Description	Required	Schema	Default
PathParamet er	name	name of the RoleBindingR estricition	true	string	

2.2.333.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.291, "v1.WatchEvent"

2.2.333.3. Consumes

- /

2.2.333.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf
- application/json;stream=watch
- application/vnd.kubernetes.protobuf;stream=watch

2.2.333.5. Tags

- oapiv1

2.2.334. watch individual changes to a list of Route

GET /oapi/v1/watch/namespaces/{namespace}/routes

2.2.334.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParamter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParamter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParam eter	resourceVersion	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParam eter	timeoutSeconds	Timeout for the list/watch call.	false	integer	
PathParam eter	namespace	object name and auth scope, such as for teams and projects	true	string	

2.2.334.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.291, "v1.WatchEvent"

2.2.334.3. Consumes

- /

2.2.334.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf
- application/json;stream=watch
- application/vnd.kubernetes.protobuf;stream=watch

2.2.334.5. Tags

- oapiv1

2.2.335. watch changes to an object of kind Route

```
GET /oapi/v1/watch/namespaces/{namespace}/routes/{name}
```

2.2.335.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParam eter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParam ter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParam ter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParam eter	resourceVersi on	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParam eter	timeoutSecon ds	Timeout for the list/watch call.	false	integer	
PathParam eter	namespace	object name and auth scope, such as for teams and projects	true	string	

Type	Name	Description	Required	Schema	Default
PathParamet er	name	name of the Route	true	string	

2.2.335.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.291, "v1.WatchEvent"

2.2.335.3. Consumes

- /

2.2.335.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf
- application/json;stream=watch
- application/vnd.kubernetes.protobuf;stream=watch

2.2.335.5. Tags

- oapiv1

2.2.336. watch individual changes to a list of Template

```
GET /oapi/v1/watch/namespaces/{namespace}/templates
```

2.2.336.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParame ter	pretty	If 'true', then the output is pretty printed.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParamter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParamter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParamter	resourceVersion	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParamter	timeoutSeconds	Timeout for the list/watch call.	false	integer	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	

2.2.336.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.291, "v1.WatchEvent"

2.2.336.3. Consumes

- /

2.2.336.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf
- application/json;stream=watch
- application/vnd.kubernetes.protobuf;stream=watch

2.2.336.5. Tags

- oapiv1

2.2.337. watch changes to an object of kind Template

```
GET /oapi/v1/watch/namespaces/{namespace}/templates/{name}
```

2.2.337.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParam ter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParam ter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParamter	resourceVersion	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParamter	timeoutSeconds	Timeout for the list/watch call.	false	integer	
PathParamter	namespace	object name and auth scope, such as for teams and projects	true	string	

Type	Name	Description	Required	Schema	Default
PathParamet er	name	name of the Template	true	string	

2.2.337.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.291, "v1.WatchEvent"

2.2.337.3. Consumes

- /

2.2.337.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf
- application/json;stream=watch
- application/vnd.kubernetes.protobuf;stream=watch

2.2.337.5. Tags

- oapiv1

2.2.338. watch individual changes to a list of NetNamespaces

GET /oapi/v1/watch/netnamespaces

2.2.338.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParam ter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParam ter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParam ter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParamter	resourceVersion	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParamter	timeoutSeconds	Timeout for the list/watch call.	false	integer	

2.2.338.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.291, "v1.WatchEvent"

2.2.338.3. Consumes

- /

2.2.338.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf
- application/json;stream=watch
- application/vnd.kubernetes.protobuf;stream=watch

2.2.338.5. Tags

- oapiv1

2.2.339. watch changes to an object of kind NetNamespace

GET /oapi/v1/watch/netnamespaces/{name}

2.2.339.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParam eter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParam eter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParam ter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParamter	resourceVersion	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParamter	timeoutSeconds	Timeout for the list/watch call.	false	integer	
PathParamter	name	name of the NetNamespace	true	string	

2.2.339.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.291, "v1.WatchEvent"

2.2.339.3. Consumes

- /

2.2.339.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf
- application/json;stream=watch
- application/vnd.kubernetes.protobuf;stream=watch

2.2.339.5. Tags

- oapiv1

2.2.340. watch individual changes to a list of OAuthAccessToken

GET /oapi/v1/watch/oauthaccessstokens

2.2.340.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParameter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParameter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParam ter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParam ter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParamter	resourceVersion	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParamter	timeoutSeconds	Timeout for the list/watch call.	false	integer	

2.2.340.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.291, "v1.WatchEvent"

2.2.340.3. Consumes

- /

2.2.340.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf
- application/json;stream=watch
- application/vnd.kubernetes.protobuf;stream=watch

2.2.340.5. Tags

- oapiv1

2.2.341. watch changes to an object of kind OAuthAccessToken

```
GET /oapi/v1/watch/oauthaccesstokens/{name}
```

2.2.341.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParam ter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParam ter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParam eter	resourceVersi on	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParam eter	timeoutSecon ds	Timeout for the list/watch call.	false	integer	
PathParamet er	name	name of the OAuthAccess Token	true	string	

2.2.341.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.291, "v1.WatchEvent"

2.2.341.3. Consumes

- /

2.2.341.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf
- application/json;stream=watch
- application/vnd.kubernetes.protobuf;stream=watch

2.2.341.5. Tags

- oapiv1

2.2.342. watch individual changes to a list of OAuthAuthorizeToken

GET /oapi/v1/watch/oauthauthorizetokens

2.2.342.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParameter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParameter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParam ter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParam ter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParamter	resourceVersion	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParamter	timeoutSeconds	Timeout for the list/watch call.	false	integer	

2.2.342.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.291, "v1.WatchEvent"

2.2.342.3. Consumes

- /

2.2.342.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf
- application/json;stream=watch
- application/vnd.kubernetes.protobuf;stream=watch

2.2.342.5. Tags

- oapiv1

2.2.343. watch changes to an object of kind OAuthAuthorizeToken

```
GET /oapi/v1/watch/oauthauthorizetokens/{name}
```

2.2.343.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParam eter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParam ter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParam ter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParam eter	resourceVersi on	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParam eter	timeoutSecon ds	Timeout for the list/watch call.	false	integer	
PathParamet er	name	name of the OAuthAuthorizeToken	true	string	

2.2.343.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.291, "v1.WatchEvent"

2.2.343.3. Consumes

- /

2.2.343.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf
- application/json;stream=watch
- application/vnd.kubernetes.protobuf;stream=watch

2.2.343.5. Tags

- oapiv1

2.2.344. watch individual changes to a list of OAuthClientAuthorizations

GET /oapi/v1/watch/oauthclientauthorizations

2.2.344.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParam eter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParam ter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParam ter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParam ter	resourceVersi on	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParam ter	timeoutSecon ds	Timeout for the list/watch call.	false	integer	

2.2.344.2. Responses

HTTP Code	Description	Schema
-----------	-------------	--------

HTTP Code	Description	Schema
200	success	Section 2.3.291, "v1.WatchEvent"

2.2.344.3. Consumes

- /

2.2.344.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf
- application/json;stream=watch
- application/vnd.kubernetes.protobuf;stream=watch

2.2.344.5. Tags

- oapiv1

2.2.345. watch changes to an object of kind OAuthClientAuthorization

```
GET /oapi/v1/watch/oauthclientauthorizations/{name}
```

2.2.345.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParam eter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParam ter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParam ter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParam eter	resourceVersi on	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParam eter	timeoutSecon ds	Timeout for the list/watch call.	false	integer	
PathParamet er	name	name of the OAuthClientA uthorization	true	string	

2.2.345.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.291, "v1.WatchEvent"

2.2.345.3. Consumes

- /

2.2.345.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf
- application/json;stream=watch
- application/vnd.kubernetes.protobuf;stream=watch

2.2.345.5. Tags

- oapiv1

2.2.346. watch individual changes to a list of OAuthClient

GET /oapi/v1/watch/oauthclients

2.2.346.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParam ter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParam ter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParamter	resourceVersion	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParamter	timeoutSeconds	Timeout for the list/watch call.	false	integer	

2.2.346.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.291, "v1.WatchEvent"

2.2.346.3. Consumes

- /

2.2.346.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf
- application/json;stream=watch
- application/vnd.kubernetes.protobuf;stream=watch

2.2.346.5. Tags

- oapiv1

2.2.347. watch changes to an object of kind OAuthClient

```
GET /oapi/v1/watch/oauthclients/{name}
```

2.2.347.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParam ter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParam ter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParam eter	resourceVersi on	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParam eter	timeoutSecon ds	Timeout for the list/watch call.	false	integer	
PathParam eter	name	name of the OAuthClient	true	string	

2.2.347.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.291, "v1.WatchEvent"

2.2.347.3. Consumes

- /

2.2.347.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf
- application/json;stream=watch
- application/vnd.kubernetes.protobuf;stream=watch

2.2.347.5. Tags

- oapiv1

2.2.348. watch individual changes to a list of Policy

GET /oapi/v1/watch/policies

2.2.348.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParam ter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParam ter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParamter	resourceVersion	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParamter	timeoutSeconds	Timeout for the list/watch call.	false	integer	

2.2.348.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.291, "v1.WatchEvent"

2.2.348.3. Consumes

- /

2.2.348.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf
- application/json;stream=watch
- application/vnd.kubernetes.protobuf;stream=watch

2.2.348.5. Tags

- oapiv1

2.2.349. watch individual changes to a list of PolicyBinding

GET /oapi/v1/watch/policybindings

2.2.349.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParam eter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParam ter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParam ter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParam eter	resourceVersi on	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParam eter	timeoutSecon ds	Timeout for the list/watch call.	false	integer	

2.2.349.2. Responses

HTTP Code	Description	Schema
-----------	-------------	--------

HTTP Code	Description	Schema
200	success	Section 2.3.291, "v1.WatchEvent"

2.2.349.3. Consumes

- /

2.2.349.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf
- application/json;stream=watch
- application/vnd.kubernetes.protobuf;stream=watch

2.2.349.5. Tags

- oapiv1

2.2.350. watch individual changes to a list of Project

GET /oapi/v1/watch/projects

2.2.350.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParam ter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParam ter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParamter	resourceVersion	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParamter	timeoutSeconds	Timeout for the list/watch call.	false	integer	

2.2.350.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.291, "v1.WatchEvent"

2.2.350.3. Consumes

- /

2.2.350.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf
- application/json;stream=watch
- application/vnd.kubernetes.protobuf;stream=watch

2.2.350.5. Tags

- oapiv1

2.2.351. watch changes to an object of kind Project

GET /oapi/v1/watch/projects/{name}

2.2.351.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParam eter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParam ter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParam ter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParam eter	resourceVersi on	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParam eter	timeoutSecon ds	Timeout for the list/watch call.	false	integer	
PathParamet er	name	name of the Project	true	string	

2.2.351.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.291, "v1.WatchEvent"

2.2.351.3. Consumes

- /

2.2.351.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf
- application/json;stream=watch
- application/vnd.kubernetes.protobuf;stream=watch

2.2.351.5. Tags

- oapiv1

2.2.352. watch individual changes to a list of RoleBindingRestriction

GET /oapi/v1/watch/rolebindingrestrictions

2.2.352.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParameter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParameter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParam ter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParam ter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParamter	resourceVersion	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParamter	timeoutSeconds	Timeout for the list/watch call.	false	integer	

2.2.352.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.291, "v1.WatchEvent"

2.2.352.3. Consumes

- /

2.2.352.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf
- application/json;stream=watch
- application/vnd.kubernetes.protobuf;stream=watch

2.2.352.5. Tags

- oapiv1

2.2.353. watch individual changes to a list of Route

GET /oapi/v1/watch/routes

2.2.353.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParam eter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParam ter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParam ter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParam eter	resourceVersi on	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParam eter	timeoutSecon ds	Timeout for the list/watch call.	false	integer	

2.2.353.2. Responses

HTTP Code	Description	Schema
-----------	-------------	--------

HTTP Code	Description	Schema
200	success	Section 2.3.291, "v1.WatchEvent"

2.2.353.3. Consumes

- /

2.2.353.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf
- application/json;stream=watch
- application/vnd.kubernetes.protobuf;stream=watch

2.2.353.5. Tags

- oapiv1

2.2.354. watch individual changes to a list of Template

GET /oapi/v1/watch/templates

2.2.354.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParam ter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParam ter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParamter	resourceVersion	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParamter	timeoutSeconds	Timeout for the list/watch call.	false	integer	

2.2.354.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.291, "v1.WatchEvent"

2.2.354.3. Consumes

- /

2.2.354.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf
- application/json;stream=watch
- application/vnd.kubernetes.protobuf;stream=watch

2.2.354.5. Tags

- oapiv1

2.2.355. watch individual changes to a list of User

GET /oapi/v1/watch/users

2.2.355.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParam eter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParam ter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParam ter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParam eter	resourceVersi on	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParam eter	timeoutSecon ds	Timeout for the list/watch call.	false	integer	

2.2.355.2. Responses

HTTP Code	Description	Schema
-----------	-------------	--------

HTTP Code	Description	Schema
200	success	Section 2.3.291, "v1.WatchEvent"

2.2.355.3. Consumes

- /

2.2.355.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf
- application/json;stream=watch
- application/vnd.kubernetes.protobuf;stream=watch

2.2.355.5. Tags

- oapiv1

2.2.356. watch changes to an object of kind User

```
GET /oapi/v1/watch/users/{name}
```

2.2.356.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParam ter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParam ter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParam ter	resourceVersion	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParam ter	timeoutSeconds	Timeout for the list/watch call.	false	integer	
PathParam eter	name	name of the User	true	string	

2.2.356.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.291, "v1.WatchEvent"

2.2.356.3. Consumes

- /

2.2.356.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf
- application/json;stream=watch
- application/vnd.kubernetes.protobuf;stream=watch

2.2.356.5. Tags

- oapiv1

2.3. DEFINITIONS

2.3.1. patch.Object

represents an object patch, which may be any of: JSON patch (RFC 6902), JSON merge patch (RFC 7396), or the Kubernetes strategic merge patch

2.3.2. runtime.RawExtension

this may be any JSON object with a 'kind' and 'apiVersion' field; and is preserved unmodified by processing

2.3.3. types.UID

2.3.4. v1.APIResource

APIResource specifies the name of a resource and whether it is namespaced.

Name	Description	Required	Schema	Default
name	name is the name of the resource.	true	string	

Name	Description	Required	Schema	Default
namespaced	namespaced indicates if a resource is namespaced or not.	true	boolean	
kind	kind is the kind for the resource (e.g. 'Foo' is the kind for a resource 'foo')	true	string	
verbs	verbs is a list of supported kube verbs (this includes get, list, watch, create, update, patch, delete, deletecollection, and proxy)	true	string array	
shortNames	shortNames is a list of suggested short names of the resource.	false	string array	

2.3.5. v1.APIResourceList

APIResourceList is a list of APIResource, it is used to expose the name of the resources supported in a specific group and version, and if the resource is namespaced.

Name	Description	Required	Schema	Default
------	-------------	----------	--------	---------

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#types-kinds	false	string	
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#resources	false	string	
groupVersion	groupVersion is the group and version this APIResourceList is for.	true	string	

Name	Description	Required	Schema	Default
resources	resources contains the name of the resources and if they are namespaced.	true	Section 2.3.4, "v1.APIResource" array	

2.3.6. v1.AWSElasticBlockStoreVolumeSource

Represents a Persistent Disk resource in AWS.

An AWS EBS disk must exist before mounting to a container. The disk must also be in the same AWS zone as the kubelet. An AWS EBS disk can only be mounted as read/write once. AWS EBS volumes support ownership management and SELinux relabeling.

Name	Description	Required	Schema	Default
volumeID	Unique ID of the persistent disk resource in AWS (Amazon EBS volume). More info: http://kubernetes.io/docs/user-guide/volumes#awselasticblockstore	true	string	

Name	Description	Required	Schema	Default
fsType	<p>Filesystem type of the volume that you want to mount. Tip: Ensure that the filesystem type is supported by the host operating system.</p> <p>Examples: "ext4", "xfs", "ntfs". Implicitly inferred to be "ext4" if unspecified.</p> <p>More info: http://kubernetes.io/docs/user-guide/volumes#awselasticblockstore</p>	false	string	
partition	<p>The partition in the volume that you want to mount. If omitted, the default is to mount by volume name.</p> <p>Examples: For volume /dev/sda1, you specify the partition as "1". Similarly, the volume partition for /dev/sda is "0" (or you can leave the property empty).</p>	false	integer (int32)	

Name	Description	Required	Schema	Default
readOnly	Specify "true" to force and set the ReadOnly property in VolumeMounts to "true". If omitted, the default is "false". More info: http://kubernetes.io/docs/user-guide/volumes#awselasticblocksstore	false	boolean	

2.3.7. v1.Affinity

Affinity is a group of affinity scheduling rules.

Name	Description	Required	Schema	Default
nodeAffinity	Describes node affinity scheduling rules for the pod.	false	Section 2.3.163, "v1.NodeAffinity"	
podAffinity	Describes pod affinity scheduling rules (e.g. co-locate this pod in the same node, zone, etc. as some other pod(s)).	false	Section 2.3.183, "v1.PodAffinity"	
podAntiAffinity	Describes pod anti-affinity scheduling rules (e.g. avoid putting this pod in the same node, zone, etc. as some other pod(s)).	false	Section 2.3.185, "v1.PodAntiAffinity"	

2.3.8. v1.AppliedClusterResourceQuota

AppliedClusterResourceQuota mirrors ClusterResourceQuota at a project scope, for projection into a project. It allows a project-admin to know which ClusterResourceQuotas are applied to his project and their associated usage.

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/HEAD/docs/dev/api-conventions.md#types-kinds	false	string	
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/HEAD/docs/dev/api-conventions.md#resources	false	string	
metadata	Standard object's metadata.	true	Section 2.3.176, "v1.ObjectMeta"	

Name	Description	Required	Schema	Default
spec	Spec defines the desired quota	true	Section 2.3.46, "v1.ClusterResourceQuotaSpec"	
status	Status defines the actual enforced quota and its current usage	false	Section 2.3.47, "v1.ClusterResourceQuotaStatus"	

2.3.9. v1.AppliedClusterResourceQuotaList

AppliedClusterResourceQuotaList is a collection of AppliedClusterResourceQuotas

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#types-kinds	false	string	

Name	Description	Required	Schema	Default
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#resources	false	string	
metadata	Standard object's metadata.	false	Section 2.3.151, "v1.ListMeta"	
items	Items is a list of AppliedClusterResourceQuota	true	Section 2.3.8, "v1.AppliedClusterResourceQuota" array	

2.3.10. v1.AzureDataDiskCachingMode

2.3.11. v1.AzureDiskVolumeSource

AzureDisk represents an Azure Data Disk mount on the host and bind mount to the pod.

Name	Description	Required	Schema	Default
diskName	The Name of the data disk in the blob storage	true	string	
diskURI	The URI the data disk in the blob storage	true	string	

Name	Description	Required	Schema	Default
cacheMode	Host Caching mode: None, Read Only, Read Write.	false	Section 2.3.10, "v1.AzureDataDiskCachingMode"	
fsType	Filesystem type to mount. Must be a filesystem type supported by the host operating system. Ex. "ext4", "xfs", "ntfs". Implicitly inferred to be "ext4" if unspecified.	false	string	
readOnly	Defaults to false (read/write). ReadOnly here will force the ReadOnly setting in VolumeMounts.	false	boolean	

2.3.12. v1.AzureFileVolumeSource

AzureFile represents an Azure File Service mount on the host and bind mount to the pod.

Name	Description	Required	Schema	Default
secretName	the name of secret that contains Azure Storage Account Name and Key	true	string	
shareName	Share Name	true	string	
readOnly	Defaults to false (read/write). ReadOnly here will force the ReadOnly setting in VolumeMounts.	false	boolean	

2.3.13. v1.BinaryBuildSource

BinaryBuildSource describes a binary file to be used for the Docker and Source build strategies, where the file will be extracted and used as the build source.

Name	Description	Required	Schema	Default
asFile	asFile indicates that the provided binary input should be considered a single file within the build input. For example, specifying "webapp.war" would place the provided binary as /webapp.war for the builder. If left empty, the Docker and Source build strategies assume this file is a zip, tar, or tar.gz file and extract it as the source. The custom strategy receives this binary as standard input. This filename may not contain slashes or be '..' or '..'.	false	string	

2.3.14. v1.BitbucketWebHookCause

BitbucketWebHookCause has information about a Bitbucket webhook that triggered a build.

Name	Description	Required	Schema	Default
revision	Revision is the git source revision information of the trigger.	false	Section 2.3.262, "v1.SourceRevision"	

Name	Description	Required	Schema	Default
secret	Secret is the obfuscated webhook secret that triggered a build.	false	string	

2.3.15. v1.Build

Build encapsulates the inputs needed to produce a new deployable image, as well as the status of the execution and a reference to the Pod which executed the build.

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#types-kinds	false	string	

Name	Description	Required	Schema	Default
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#resources	false	string	
metadata	Standard object's metadata.	false	Section 2.3.176, "v1.ObjectMeta"	
spec	spec is all the inputs used to execute the build.	false	Section 2.3.26, "v1.BuildSpec"	
status	status is the current status of the build.	false	Section 2.3.27, "v1.BuildStatus"	

2.3.16. v1.BuildConfig

Build configurations define a build process for new Docker images. There are three types of builds possible - a Docker build using a Dockerfile, a Source-to-Image build that uses a specially prepared base image that accepts source code that it can make runnable, and a custom build that can run // arbitrary Docker images as a base and accept the build parameters. Builds run on the cluster and on completion are pushed to the Docker registry specified in the "output" section. A build can be triggered via a webhook, when the base image changes, or when a user manually requests a new build be // created.

Each build created by a build configuration is numbered and refers back to its parent configuration. Multiple builds can be triggered at once. Builds that do not have "output" set can be used to test code or run a verification build.

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#types-kinds	false	string	
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#resources	false	string	
metadata	metadata for BuildConfig.	false	Section 2.3.176, "v1.ObjectMeta"	

Name	Description	Required	Schema	Default
spec	spec holds all the input necessary to produce a new build, and the conditions when to trigger them.	true	Section 2.3.18, "v1.BuildConfigSpec"	
status	status holds any relevant information about a build config	true	Section 2.3.19, "v1.BuildConfigStatus"	

2.3.17. v1.BuildConfigList

BuildConfigList is a collection of BuildConfigs.

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#types-kinds	false	string	

Name	Description	Required	Schema	Default
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/HEAD/docs/dev/api-conventions.md#resources	false	string	
metadata	metadata for BuildConfigList.	false	Section 2.3.151, "v1.ListMeta"	
items	items is a list of build configs	true	Section 2.3.16, "v1.BuildConfig" array	

2.3.18. v1.BuildConfigSpec

BuildConfigSpec describes when and how builds are created

Name	Description	Required	Schema	Default
triggers	triggers determine how new Builds can be launched from a BuildConfig. If no triggers are defined, a new build can only occur as a result of an explicit client build creation.	true	Section 2.3.32, "v1.BuildTriggerPolicy" array	

Name	Description	Required	Schema	Default
runPolicy	RunPolicy describes how the new build created from this build configuration will be scheduled for execution. This is optional, if not specified we default to "Serial".	false	string	
serviceAccount	serviceAccount is the name of the ServiceAccount to use to run the pod created by this build. The pod will be allowed to use secrets referenced by the ServiceAccount	false	string	
source	source describes the SCM in use.	false	Section 2.3.25, "v1.BuildSource"	
revision	revision is the information from the source for a specific repo snapshot. This is optional.	false	Section 2.3.262, "v1.SourceRevision"	
strategy	strategy defines how to perform a build.	true	Section 2.3.30, "v1.BuildStrategy"	
output	output describes the Docker image the Strategy should produce.	false	Section 2.3.22, "v1.BuildOutput"	

Name	Description	Required	Schema	Default
resources	resources computes resource requirements to execute the build.	false	Section 2.3.223, "v1.ResourceRequirements"	
postCommit	postCommit is a build hook executed after the build output image is committed, before it is pushed to a registry.	false	Section 2.3.23, "v1.BuildPostCommitSpec"	
completionDeadlineSeconds	completionDeadlineSeconds is an optional duration in seconds, counted from the time when a build pod gets scheduled in the system, that the build may be active on a node before the system actively tries to terminate the build; value must be positive integer	false	integer (int64)	

Name	Description	Required	Schema	Default
nodeSelector	nodeSelector is a selector which must be true for the build pod to fit on a node. If nil, it can be overridden by default build nodeSelector values for the cluster. If set to an empty map or a map with any values, default build nodeSelector values are ignored.	true	object	
successfulBuildsHistoryLimit	successfulBuildsHistoryLimit is the number of old successful builds to retain. If not specified, all successful builds are retained.	false	integer (int32)	
failedBuildsHistoryLimit	failedBuildsHistoryLimit is the number of old failed builds to retain. If not specified, all failed builds are retained.	false	integer (int32)	

2.3.19. v1.BuildConfigStatus

BuildConfigStatus contains current state of the build config object.

Name	Description	Required	Schema	Default
------	-------------	----------	--------	---------

Name	Description	Required	Schema	Default
lastVersion	lastVersion is used to inform about number of last triggered build.	true	integer (int64)	

2.3.20. v1.BuildList

BuildList is a collection of Builds.

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/HEAD/docs/dev/api-conventions.md#types-kinds	false	string	

Name	Description	Required	Schema	Default
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/HEAD/docs/dev/api-conventions.md#resources	false	string	
metadata	metadata for BuildList.	false	Section 2.3.151, "v1.ListMeta"	
items	items is a list of builds	true	Section 2.3.15, "v1.Build" array	

2.3.21. v1.BuildLog

BuildLog is the (unused) resource associated with the build log redirector

Name	Description	Required	Schema	Default
------	-------------	----------	--------	---------

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#types-kinds	false	string	
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#resources	false	string	

2.3.22. v1.BuildOutput

BuildOutput is input to a build strategy and describes the Docker image that the strategy should produce.

Name	Description	Required	Schema	Default
to	to defines an optional location to push the output of this build to. Kind must be one of 'ImageStreamTag' or 'DockerImage'. This value will be used to look up a Docker image repository to push to. In the case of an ImageStreamTag, the ImageStreamTag will be looked for in the namespace of the build unless Namespace is specified.	false	Section 2.3.177, "v1.ObjectReference"	
pushSecret	PushSecret is the name of a Secret that would be used for setting up the authentication for executing the Docker push to authentication enabled Docker Registry (or Docker Hub).	false	Section 2.3.152, "v1.LocalObjectReference"	

Name	Description	Required	Schema	Default
imageLabels	imageLabels define a list of labels that are applied to the resulting image. If there are multiple labels with the same name then the last one in the list is used.	false	Section 2.3.126 , "v1.ImageLabel" array	

2.3.23. v1.BuildPostCommitSpec

A BuildPostCommitSpec holds a build post commit hook specification. The hook executes a command in a temporary container running the build output image, immediately after the last layer of the image is committed and before the image is pushed to a registry. The command is executed with the current working directory (\$PWD) set to the image's WORKDIR.

The build will be marked as failed if the hook execution fails. It will fail if the script or command return a non-zero exit code, or if there is any other error related to starting the temporary container.

There are five different ways to configure the hook. As an example, all forms below are equivalent and will execute **rake test --verbose**.

1. Shell script:

```
"postCommit": {
  "script": "rake test --verbose",
}
```

The above is a convenient form which is equivalent to:

```
"postCommit": {
  "command": ["/bin/sh", "-ic"],
  "args": ["rake test --verbose"]
}
```

2. A command as the image entrypoint:

```
"postCommit": {
  "commit": ["rake", "test", "--verbose"]
}
```

Command overrides the image entrypoint in the exec form, as documented in Docker:
<https://docs.docker.com/engine/reference/builder/#entrypoint>.

3. Pass arguments to the default entrypoint:

```
"postCommit": {
  "args": ["rake", "test", "--verbose"]
}
```

This form is only useful if the image entrypoint can handle arguments.

4. Shell script with arguments:

```
"postCommit": {
  "script": "rake test $1",
  "args": ["--verbose"]
}
```

This form is useful if you need to pass arguments that would otherwise be hard to quote properly in the shell script. In the script, \$0 will be `/bin/sh` and \$1, \$2, etc, are the positional arguments from Args.

5. Command with arguments:

```
"postCommit": {
  "command": ["rake", "test"],
  "args": ["--verbose"]
}
```

This form is equivalent to appending the arguments to the Command slice.

It is invalid to provide both Script and Command simultaneously. If none of the fields are specified, the hook is not executed.

Name	Description	Required	Schema	Default
------	-------------	----------	--------	---------

Name	Description	Required	Schema	Default
command	command is the command to run. It may not be specified with Script. This might be needed if the image doesn't have /bin/sh , or if you do not want to use a shell. In all other cases, using Script might be more convenient.	false	string array	
args	args is a list of arguments that are provided to either Command, Script or the Docker image's default entrypoint. The arguments are placed immediately after the command to be run.	false	string array	

Name	Description	Required	Schema	Default
script	<p>script is a shell script to be run with /bin/sh -i. It may not be specified with Command. Use Script when a shell script is appropriate to execute the post build hook, for example for running unit tests with rake test. If you need control over the image entrypoint, or if the image does not have /bin/sh, use Command and/or Args. The -i flag is needed to support CentOS and RHEL images that use Software Collections (SCL), in order to have the appropriate collections enabled in the shell. E.g., in the Ruby image, this is necessary to make ruby, bundle and other binaries available in the PATH.</p>	false	string	

2.3.24. v1.BuildRequest

BuildRequest is the resource used to pass parameters to build generator

Name	Description	Required	Schema	Default
------	-------------	----------	--------	---------

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#types-kinds	false	string	
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#resources	false	string	
metadata	metadata for BuildRequest.	false	Section 2.3.176, "v1.ObjectMeta"	

Name	Description	Required	Schema	Default
revision	revision is the information from the source for a specific repo snapshot.	false	Section 2.3.262, "v1.SourceRevision"	
triggeredByImage	triggeredByImage is the Image that triggered this build.	false	Section 2.3.177, "v1.ObjectReference"	
from	from is the reference to the ImageStreamTag that triggered the build.	false	Section 2.3.177, "v1.ObjectReference"	
binary	binary indicates a request to build from a binary provided to the builder	false	Section 2.3.13, "v1.BinaryBuildSource"	
lastVersion	lastVersion (optional) is the LastVersion of the BuildConfig that was used to generate the build. If the BuildConfig in the generator doesn't match, a build will not be generated.	false	integer (int64)	
env	env contains additional environment variables you want to pass into a builder container.	false	Section 2.3.93, "v1.EnvVar" array	

Name	Description	Required	Schema	Default
triggeredBy	triggeredBy describes which triggers started the most recent update to the build configuration and contains information about those triggers.	true	Section 2.3.31, "v1.BuildTriggerCause" array	
dockerStrategyOptions	DockerStrategyOptions contains additional docker-strategy specific options for the build	false	Section 2.3.82, "v1.DockerStrategyOptions"	

2.3.25. v1.BuildSource

BuildSource is the SCM used for the build.

Name	Description	Required	Schema	Default
type	type of build input to accept	true	string	

Name	Description	Required	Schema	Default
binary	<p>binary builds accept a binary as their input. The binary is generally assumed to be a tar, gzipped tar, or zip file depending on the strategy. For Docker builds, this is the build context and an optional Dockerfile may be specified to override any Dockerfile in the build context. For Source builds, this is assumed to be an archive as described above. For Source and Docker builds, if <code>binary.asFile</code> is set the build will receive a directory with a single file. <code>contextDir</code> may be used when an archive is provided. Custom builds will receive this binary as input on STDIN.</p>	false	Section 2.3.13, "v1.BinaryBuildSource"	

Name	Description	Required	Schema	Default
dockerfile	dockerfile is the raw contents of a Dockerfile which should be built. When this option is specified, the FROM may be modified based on your strategy base image and additional ENV stanzas from your strategy environment will be added after the FROM, but before the rest of your Dockerfile stanzas. The Dockerfile source type may be used with other options like git - in those cases the Git repo will have any innate Dockerfile replaced in the context dir.	false	string	
git	git contains optional information about git build source	false	Section 2.3.103, "v1.GitBuildSource"	
images	images describes a set of images to be used to provide source for the build	false	Section 2.3.132, "v1.ImageSource" array	

Name	Description	Required	Schema	Default
contextDir	contextDir specifies the sub-directory where the source code for the application exists. This allows to have buildable sources in directory other than root of repository.	false	string	
sourceSecret	sourceSecret is the name of a Secret that would be used for setting up the authentication for cloning private repository. The secret contains valid credentials for remote repository, where the data's key represent the authentication method to be used and value is the base64 encoded credentials. Supported auth methods are: ssh-privatekey.	false	Section 2.3.152, "v1.LocalObject Reference"	
secrets	secrets represents a list of secrets and their destinations that will be used only for the build.	false	Section 2.3.244, "v1.SecretBuildSource" array	

2.3.26. v1.BuildSpec

BuildSpec has the information to represent a build and also additional information about a build

Name	Description	Required	Schema	Default
serviceAccount	serviceAccount is the name of the ServiceAccount to use to run the pod created by this build. The pod will be allowed to use secrets referenced by the ServiceAccount	false	string	
source	source describes the SCM in use.	false	Section 2.3.25, "v1.BuildSource"	
revision	revision is the information from the source for a specific repo snapshot. This is optional.	false	Section 2.3.262, "v1.SourceRevision"	
strategy	strategy defines how to perform a build.	true	Section 2.3.30, "v1.BuildStrategy"	
output	output describes the Docker image the Strategy should produce.	false	Section 2.3.22, "v1.BuildOutput"	
resources	resources computes resource requirements to execute the build.	false	Section 2.3.223, "v1.ResourceRequirements"	

Name	Description	Required	Schema	Default
postCommit	postCommit is a build hook executed after the build output image is committed, before it is pushed to a registry.	false	Section 2.3.23, "v1.BuildPostCommitSpec"	
completionDeadlineSeconds	completionDeadlineSeconds is an optional duration in seconds, counted from the time when a build pod gets scheduled in the system, that the build may be active on a node before the system actively tries to terminate the build; value must be positive integer	false	integer (int64)	
nodeSelector	nodeSelector is a selector which must be true for the build pod to fit on a node. If nil, it can be overridden by default build nodeSelector values for the cluster. If set to an empty map or a map with any values, default build nodeSelector values are ignored.	true	object	

Name	Description	Required	Schema	Default
triggeredBy	triggeredBy describes which triggers started the most recent update to the build configuration and contains information about those triggers.	true	Section 2.3.31, "v1.BuildTriggerCause" array	

2.3.27. v1.BuildStatus

BuildStatus contains the status of a build

Name	Description	Required	Schema	Default
phase	phase is the point in the build lifecycle. Possible values are "New", "Pending", "Running", "Complete", "Failed", "Error", and "Cancelled".	true	string	
cancelled	cancelled describes if a cancel event was triggered for the build.	false	boolean	
reason	reason is a brief CamelCase string that describes any failure and is meant for machine parsing and tidy display in the CLI.	false	string	

Name	Description	Required	Schema	Default
message	message is a human-readable message indicating details about why the build has this status.	false	string	
startTimestamp	startTimestamp is a timestamp representing the server time when this Build started running in a Pod. It is represented in RFC3339 form and is in UTC.	false	string	
completionTimestamp	completionTimestamp is a timestamp representing the server time when this Build was finished, whether that build failed or succeeded. It reflects the time at which the Pod running the Build terminated. It is represented in RFC3339 form and is in UTC.	false	string	
duration	duration contains time.Duration object describing build time.	false	time.Duration	

Name	Description	Required	Schema	Default
outputDockerImageReference	outputDockerImageReference contains a reference to the Docker image that will be built by this build. Its value is computed from Build.Spec.Output.To, and should include the registry address, so that it can be used to push and pull the image.	false	string	
config	config is an ObjectReference to the BuildConfig this Build is based on.	false	Section 2.3.177, "v1.ObjectReference"	
output	output describes the Docker image the build has produced.	false	Section 2.3.28, "v1.BuildStatusOutput"	
stages	stages contains details about each stage that occurs during the build including start time, duration (in milliseconds), and the steps that occurred within each stage.	false	Section 2.3.263, "v1.StageInfo" array	
logSnippet	logSnippet is the last few lines of the build log. This value is only set for builds that failed.	false	string	

2.3.28. v1.BuildStatusOutput

BuildStatusOutput contains the status of the built image.

Name	Description	Required	Schema	Default
to	to describes the status of the built image being pushed to a registry.	false	Section 2.3.29, "v1.BuildStatusOutputTo"	

2.3.29. v1.BuildStatusOutputTo

BuildStatusOutputTo describes the status of the built image with regards to image registry to which it was supposed to be pushed.

Name	Description	Required	Schema	Default
imageDigest	<p>imageDigest is the digest of the built Docker image. The digest uniquely identifies the image in the registry to which it was pushed.</p> <p>Please note that this field may not always be set even if the push completes successfully - e.g. when the registry returns no digest or returns it in a format that the builder doesn't understand.</p>	false	string	

2.3.30. v1.BuildStrategy

BuildStrategy contains the details of how to perform a build.

Name	Description	Required	Schema	Default
type	type is the kind of build strategy.	true	string	

Name	Description	Required	Schema	Default
dockerStrategy	dockerStrategy holds the parameters to the Docker build strategy.	false	Section 2.3.81, "v1.DockerBuild Strategy"	
sourceStrategy	sourceStrategy holds the parameters to the Source build strategy.	false	Section 2.3.260, "v1.SourceBuild Strategy"	
customStrategy	customStrategy holds the parameters to the Custom build strategy	false	Section 2.3.59, "v1.CustomBuild Strategy"	
jenkinsPipelineStrategy	JenkinsPipelineStrategy holds the parameters to the Jenkins Pipeline build strategy. This strategy is in tech preview.	false	Section 2.3.145, "v1.JenkinsPipelineBuildStrategy"	

2.3.31. v1.BuildTriggerCause

BuildTriggerCause holds information about a triggered build. It is used for displaying build trigger data for each build and build configuration in oc describe. It is also used to describe which triggers led to the most recent update in the build configuration.

Name	Description	Required	Schema	Default
message	message is used to store a human readable message for why the build was triggered. E.g.: "Manually triggered by user", "Configuration change", etc.	false	string	

Name	Description	Required	Schema	Default
genericWebHook	genericWebHook holds data about a builds generic webhook trigger.	false	Section 2.3.102, "v1.GenericWebHookCause"	
githubWebHook	gitHubWebHook represents data for a GitHub webhook that fired a specific build.	false	Section 2.3.104, "v1.GitHubWebHookCause"	
imageChangeBuild	imageChangeBuild stores information about an imagechange event that triggered a new build.	false	Section 2.3.122, "v1.ImageChangeCause"	
gitlabWebHook	GitLabWebHook represents data for a GitLab webhook that fired a specific build.	false	Section 2.3.105, "v1.GitLabWebHookCause"	
bitbucketWebHook	BitbucketWebHook represents data for a Bitbucket webhook that fired a specific build.	false	Section 2.3.14, "v1.BitbucketWebHookCause"	

2.3.32. v1.BuildTriggerPolicy

BuildTriggerPolicy describes a policy for a single trigger that results in a new Build.

Name	Description	Required	Schema	Default
type	type is the type of build trigger	true	string	

Name	Description	Required	Schema	Default
github	github contains the parameters for a GitHub webhook type of trigger	false	Section 2.3.292, "v1.WebHookTrigger"	
generic	generic contains the parameters for a Generic webhook type of trigger	false	Section 2.3.292, "v1.WebHookTrigger"	
imageChange	imageChange contains parameters for an ImageChange type of trigger	false	Section 2.3.123, "v1.ImageChangeTrigger"	
gitlab	GitLabWebHook contains the parameters for a GitLab webhook type of trigger	false	Section 2.3.292, "v1.WebHookTrigger"	
bitbucket	BitbucketWebHook contains the parameters for a Bitbucket webhook type of trigger	false	Section 2.3.292, "v1.WebHookTrigger"	

2.3.33. v1.Capabilities

Adds and removes POSIX capabilities from running containers.

Name	Description	Required	Schema	Default
add	Added capabilities	false	Section 2.3.34, "v1.Capability" array	
drop	Removed capabilities	false	Section 2.3.34, "v1.Capability" array	

2.3.34. v1.Capability

2.3.35. v1.CephFSVolumeSource

Represents a Ceph Filesystem mount that lasts the lifetime of a pod Cephfs volumes do not support ownership management or SELinux relabeling.

Name	Description	Required	Schema	Default
monitors	Required: Monitors is a collection of Ceph monitors More info: http://releases.k8s.io/HEAD/examples/volumes/cephfs/README.md#how-to-use-it	true	string array	
path	Optional: Used as the mounted root, rather than the full Ceph tree, default is /	false	string	
user	Optional: User is the rados user name, default is admin More info: http://releases.k8s.io/HEAD/examples/volumes/cephfs/README.md#how-to-use-it	false	string	
secretFile	Optional: SecretFile is the path to key ring for User, default is /etc/ceph/user.secret More info: http://releases.k8s.io/HEAD/examples/volumes/cephfs/README.md#how-to-use-it	false	string	

Name	Description	Required	Schema	Default
secretRef	Optional: SecretRef is reference to the authentication secret for User, default is empty. More info: http://releases.k8s.io/HEAD/examples/volumes/cephfs/README.md#how-to-use-it	false	Section 2.3.152, "v1.LocalObject Reference"	
readOnly	Optional: Defaults to false (read/write). ReadOnly here will force the ReadOnly setting in VolumeMounts. More info: http://releases.k8s.io/HEAD/examples/volumes/cephfs/README.md#how-to-use-it	false	boolean	

2.3.36. v1.CinderVolumeSource

Represents a cinder volume resource in Openstack. A Cinder volume must exist before mounting to a container. The volume must also be in the same region as the kubelet. Cinder volumes support ownership management and SELinux relabeling.

Name	Description	Required	Schema	Default
volumeID	volume id used to identify the volume in cinder More info: http://releases.k8s.io/HEAD/examples/mysql-cinder-pd/README.md	true	string	

Name	Description	Required	Schema	Default
fsType	Filesystem type to mount. Must be a filesystem type supported by the host operating system. Examples: "ext4", "xfs", "ntfs". Implicitly inferred to be "ext4" if unspecified. More info: http://releases.k8s.io/HEAD/examples/mysql-cinder-pd/README.md	false	string	
readOnly	Optional: Defaults to false (read/write). ReadOnly here will force the ReadOnly setting in VolumeMounts. More info: http://releases.k8s.io/HEAD/examples/mysql-cinder-pd/README.md	false	boolean	

2.3.37. v1.ClusterNetwork

ClusterNetwork describes the cluster network. There is normally only one object of this type, named "default", which is created by the SDN network plugin based on the master configuration when the cluster is brought up for the first time.

Name	Description	Required	Schema	Default
------	-------------	----------	--------	---------

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#types-kinds	false	string	
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#resources	false	string	
metadata	Standard object's metadata.	false	Section 2.3.176, "v1.ObjectMeta"	

Name	Description	Required	Schema	Default
network	Network is a CIDR string specifying the global overlay network's L3 space	true	string	
hostsubnetlength	HostSubnetLength is the number of bits of network to allocate to each node. eg, 8 would mean that each node would have a /24 slice of the overlay network for its pods	true	integer	
serviceNetwork	ServiceNetwork is the CIDR range that Service IP addresses are allocated from	true	string	
pluginName	PluginName is the name of the network plugin being used	false	string	

2.3.38. v1.ClusterNetworkList

ClusterNetworkList is a collection of ClusterNetworks

Name	Description	Required	Schema	Default
------	-------------	----------	--------	---------

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#types-kinds	false	string	
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#resources	false	string	
metadata	Standard object's metadata.	false	Section 2.3.151, "v1.ListMeta"	
items	Items is the list of cluster networks	true	Section 2.3.37, "v1.ClusterNetwork" array	

2.3.39. v1.ClusterPolicy

ClusterPolicy is a object that holds all the ClusterRoles for a particular namespace. There is at most one ClusterPolicy document per namespace.

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/HEAD/docs/dev/api-conventions.md#types-kinds	false	string	
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/HEAD/docs/dev/api-conventions.md#resources	false	string	
metadata	Standard object's metadata.	false	Section 2.3.176, "v1.ObjectMeta"	

Name	Description	Required	Schema	Default
lastModified	LastModified is the last time that any part of the ClusterPolicy was created, updated, or deleted	true	string	
roles	Roles holds all the ClusterRoles held by this ClusterPolicy, mapped by ClusterRole.Name	true	Section 2.3.156, "v1.NamedClusterRole" array	

2.3.40. v1.ClusterPolicyBinding

ClusterPolicyBinding is a object that holds all the ClusterRoleBindings for a particular namespace. There is one ClusterPolicyBinding document per referenced ClusterPolicy namespace

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/HEAD/docs/dev/api-conventions.md#types-kinds	false	string	

Name	Description	Required	Schema	Default
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#resources	false	string	
metadata	Standard object's metadata.	false	Section 2.3.176, "v1.ObjectMeta"	
lastModified	LastModified is the last time that any part of the ClusterPolicyBinding was created, updated, or deleted	true	string	
policyRef	PolicyRef is a reference to the ClusterPolicy that contains all the ClusterRoles that this ClusterPolicyBinding's RoleBindings may reference	true	Section 2.3.177, "v1.ObjectReference"	

Name	Description	Required	Schema	Default
roleBindings	RoleBindings holds all the ClusterRoleBindings held by this ClusterPolicyBinding, mapped by ClusterRoleBinding.Name	true	Section 2.3.157 , "v1.NamedClusterRoleBinding" array	

2.3.41. v1.ClusterPolicyBindingList

ClusterPolicyBindingList is a collection of ClusterPolicyBindings

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#types-kinds	false	string	

Name	Description	Required	Schema	Default
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#resources	false	string	
metadata	Standard object's metadata.	false	Section 2.3.151, "v1.ListMeta"	
items	Items is a list of ClusterPolicyBindings	true	Section 2.3.40, "v1.ClusterPolicyBinding" array	

2.3.42. v1.ClusterPolicyList

ClusterPolicyList is a collection of ClusterPolicies

Name	Description	Required	Schema	Default
------	-------------	----------	--------	---------

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#types-kinds	false	string	
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#resources	false	string	
metadata	Standard object's metadata.	false	Section 2.3.151, "v1.ListMeta"	
items	Items is a list of ClusterPolicies	true	Section 2.3.39, "v1.ClusterPolicy" array	

2.3.43. v1.ClusterResourceQuota

ClusterResourceQuota mirrors ResourceQuota at a cluster scope. This object is easily convertible to synthetic ResourceQuota object to allow quota evaluation re-use.

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/HEAD/docs/dev/api-conventions.md#types-kinds	false	string	
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/HEAD/docs/dev/api-conventions.md#resources	false	string	
metadata	Standard object's metadata.	true	Section 2.3.176, "v1.ObjectMeta"	

Name	Description	Required	Schema	Default
spec	Spec defines the desired quota	true	Section 2.3.46, "v1.ClusterResourceQuotaSpec"	
status	Status defines the actual enforced quota and its current usage	false	Section 2.3.47, "v1.ClusterResourceQuotaStatus"	

2.3.44. v1.ClusterResourceQuotaList

ClusterResourceQuotaList is a collection of ClusterResourceQuotas

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#types-kinds	false	string	

Name	Description	Required	Schema	Default
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#resources	false	string	
metadata	Standard object's metadata.	false	Section 2.3.151, "v1.ListMeta"	
items	Items is a list of ClusterResource Quotas	true	Section 2.3.43, "v1.ClusterResourceQuota" array	

2.3.45. v1.ClusterResourceQuotaSelector

ClusterResourceQuotaSelector is used to select projects. At least one of LabelSelector or AnnotationSelector must present. If only one is present, it is the only selection criteria. If both are specified, the project must match both restrictions.

Name	Description	Required	Schema	Default
labels	LabelSelector is used to select projects by label.	true	Section 2.3.147, "v1.LabelSelector"	
annotations	AnnotationSelector or is used to select projects by annotation.	true	object	

2.3.46. v1.ClusterResourceQuotaSpec

ClusterResourceQuotaSpec defines the desired quota restrictions

Name	Description	Required	Schema	Default
selector	Selector is the selector used to match projects. It should only select active projects on the scale of dozens (though it can select many more less active projects). These projects will contend on object creation through this resource.	true	Section 2.3.45, "v1.ClusterResourceQuotaSelector"	
quota	Quota defines the desired quota	true	Section 2.3.220, "v1.ResourceQuotaSpec"	

2.3.47. v1.ClusterResourceQuotaStatus

ClusterResourceQuotaStatus defines the actual enforced quota and its current usage

Name	Description	Required	Schema	Default
total	Total defines the actual enforced quota and its current usage across all projects	true	Section 2.3.221, "v1.ResourceQuotaStatus"	

Name	Description	Required	Schema	Default
namespaces	Namespaces slices the usage by project. This division allows for quick resolution of deletion reconciliation inside of a single project without requiring a recalculation across all projects. This can be used to pull the deltas for a given project.	true	Section 2.3.222, "v1.ResourceQuotaStatusByNamespace" array	

2.3.48. v1.ClusterRole

ClusterRole is a logical grouping of PolicyRules that can be referenced as a unit by ClusterRoleBindings.

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#types-kinds	false	string	

Name	Description	Required	Schema	Default
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#resources	false	string	
metadata	Standard object's metadata.	false	Section 2.3.176, "v1.ObjectMeta"	
rules	Rules holds all the PolicyRules for this ClusterRole	true	Section 2.3.201, "v1.PolicyRule" array	

2.3.49. v1.ClusterRoleBinding

ClusterRoleBinding references a ClusterRole, but not contain it. It can reference any ClusterRole in the same namespace or in the global namespace. It adds who information via (Users and Groups) OR Subjects and namespace information by which namespace it exists in. ClusterRoleBindings in a given namespace only have effect in that namespace (excepting the master namespace which has power in all namespaces).

Name	Description	Required	Schema	Default
------	-------------	----------	--------	---------

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#types-kinds	false	string	
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#resources	false	string	
metadata	Standard object's metadata.	false	Section 2.3.176, "v1.ObjectMeta"	

Name	Description	Required	Schema	Default
userNames	UserNames holds all the usernames directly bound to the role. This field should only be specified when supporting legacy clients and servers. See Subjects for further details.	true	string array	
groupNames	GroupNames holds all the groups directly bound to the role. This field should only be specified when supporting legacy clients and servers. See Subjects for further details.	true	string array	

Name	Description	Required	Schema	Default
subjects	Subjects hold object references to authorize with this rule. This field is ignored if UserNames or GroupNames are specified to support legacy clients and servers. Thus newer clients that do not need to support backwards compatibility should send only fully qualified Subjects and should omit the UserNames and GroupNames fields. Clients that need to support backwards compatibility can use this field to build the UserNames and GroupNames.	true	Section 2.3.177, "v1.ObjectReference" array	
roleRef	RoleRef can only reference the current namespace and the global namespace. If the ClusterRoleRef cannot be resolved, the Authorizer must return an error. Since Policy is a singleton, this is sufficient knowledge to locate a role.	true	Section 2.3.177, "v1.ObjectReference"	

2.3.50. v1.ClusterRoleBindingList

ClusterRoleBindingList is a collection of ClusterRoleBindings

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/HEAD/docs/dev/api-conventions.md#types-kinds	false	string	
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/HEAD/docs/dev/api-conventions.md#resources	false	string	
metadata	Standard object's metadata.	false	Section 2.3.151, "v1.ListMeta"	

Name	Description	Required	Schema	Default
items	Items is a list of ClusterRoleBindings	true	Section 2.3.49, "v1.ClusterRoleBinding" array	

2.3.51. v1.ClusterRoleList

ClusterRoleList is a collection of ClusterRoles

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#types-kinds	false	string	

Name	Description	Required	Schema	Default
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#resources	false	string	
metadata	Standard object's metadata.	false	Section 2.3.151 , "v1.ListMeta"	
items	Items is a list of ClusterRoles	true	Section 2.3.48 , "v1.ClusterRole" array	

2.3.52. v1.ClusterRoleScopeRestriction

ClusterRoleScopeRestriction describes restrictions on cluster role scopes

Name	Description	Required	Schema	Default
roleNames	RoleNames is the list of cluster roles that can be referenced. * means anything	true	string array	

Name	Description	Required	Schema	Default
namespaces	Namespaces is the list of namespaces that can be referenced. * means any of them (including *)	true	string array	
allowEscalation	AllowEscalation indicates whether you can request roles and their escalating resources	true	boolean	

2.3.53. v1.ConfigMapEnvSource

ConfigMapEnvSource selects a ConfigMap to populate the environment variables with.

The contents of the target ConfigMap's Data field will represent the key-value pairs as environment variables.

Name	Description	Required	Schema	Default
name	Name of the referent. More info: http://kubernetes.io/docs/user-guide/identifiers#names	false	string	
optional	Specify whether the ConfigMap must be defined	false	boolean	

2.3.54. v1.ConfigMapKeySelector

Selects a key from a ConfigMap.

Name	Description	Required	Schema	Default
------	-------------	----------	--------	---------

Name	Description	Required	Schema	Default
name	Name of the referent. More info: http://kubernetes.io/docs/user-guide/identifiers#names	false	string	
key	The key to select.	true	string	
optional	Specify whether the ConfigMap or it's key must be defined	false	boolean	

2.3.55. v1.ConfigMapProjection

Adapts a ConfigMap into a projected volume.

The contents of the target ConfigMap's Data field will be presented in a projected volume as files using the keys in the Data field as the file names, unless the items element is populated with specific mappings of keys to paths. Note that this is identical to a configmap volume source without the default mode.

Name	Description	Required	Schema	Default
name	Name of the referent. More info: http://kubernetes.io/docs/user-guide/identifiers#names	false	string	

Name	Description	Required	Schema	Default
items	If unspecified, each key-value pair in the Data field of the referenced ConfigMap will be projected into the volume as a file whose name is the key and content is the value. If specified, the listed keys will be projected into the specified paths, and unlisted keys will not be present. If a key is specified which is not present in the ConfigMap, the volume setup will error unless it is marked optional. Paths must be relative and may not contain the '..' path or start with '..'.	false	Section 2.3.146 , "v1.KeyToPath" array	
optional	Specify whether the ConfigMap or it's keys must be defined	false	boolean	

2.3.56. v1.ConfigMapVolumeSource

Adapts a ConfigMap into a volume.

The contents of the target ConfigMap's Data field will be presented in a volume as files using the keys in the Data field as the file names, unless the items element is populated with specific mappings of keys to paths. ConfigMap volumes support ownership management and SELinux relabeling.

Name	Description	Required	Schema	Default
name	Name of the referent. More info: http://kubernetes.io/docs/user-guide/identifiers#names	false	string	
items	If unspecified, each key-value pair in the Data field of the referenced ConfigMap will be projected into the volume as a file whose name is the key and content is the value. If specified, the listed keys will be projected into the specified paths, and unlisted keys will not be present. If a key is specified which is not present in the ConfigMap, the volume setup will error unless it is marked optional. Paths must be relative and may not contain the '..' path or start with '..'.	false	Section 2.3.146, "v1.KeyToPath" array	

Name	Description	Required	Schema	Default
defaultMode	Optional: mode bits to use on created files by default. Must be a value between 0 and 0777. Defaults to 0644. Directories within the path are not affected by this setting. This might be in conflict with other options that affect the file mode, like fsGroup, and the result can be other mode bits set.	false	integer (int32)	
optional	Specify whether the ConfigMap or it's keys must be defined	false	boolean	

2.3.57. v1.Container

A single application container that you want to run within a pod.

Name	Description	Required	Schema	Default
name	Name of the container specified as a DNS_LABEL. Each container in a pod must have a unique name (DNS_LABEL). Cannot be updated.	true	string	

Name	Description	Required	Schema	Default
image	Docker image name. More info: http://kubernetes.io/docs/user-guide/images	false	string	
command	Entrypoint array. Not executed within a shell. The docker image's ENTRYPOINT is used if this is not provided. Variable references <code>\$(VAR_NAME)</code> are expanded using the container's environment. If a variable cannot be resolved, the reference in the input string will be unchanged. The <code>\$(VAR_NAME)</code> syntax can be escaped with a double <code>,</code> ie: <code>(VAR_NAME)</code> . Escaped references will never be expanded, regardless of whether the variable exists or not. Cannot be updated. More info: http://kubernetes.io/docs/user-guide/containers#containers-and-commands	false	string array	

Name	Description	Required	Schema	Default
args	<p>Arguments to the entrypoint. The docker image's CMD is used if this is not provided. Variable references \$(VAR_NAME) are expanded using the container's environment. If a variable cannot be resolved, the reference in the input string will be unchanged. The \$(VAR_NAME) syntax can be escaped with a double , ie: \$(VAR_NAME). Escaped references will never be expanded, regardless of whether the variable exists or not. Cannot be updated. More info: http://kubernetes.io/docs/user-guide/containers#containers-and-commands</p>	false	string array	

Name	Description	Required	Schema	Default
workingDir	Container's working directory. If not specified, the container runtime's default will be used, which might be configured in the container image. Cannot be updated.	false	string	
ports	List of ports to expose from the container. Exposing a port here gives the system additional information about the network connections a container uses, but is primarily informational. Not specifying a port here DOES NOT prevent that port from being exposed. Any port which is listening on the default "0.0.0.0" address inside a container will be accessible from the network. Cannot be updated.	false	Section 2.3.58, "v1.ContainerPort" array	

Name	Description	Required	Schema	Default
envFrom	List of sources to populate environment variables in the container. The keys defined within a source must be a C_IDENTIFIER. All invalid keys will be reported as an event when the container is starting. When a key exists in multiple sources, the value associated with the last source will take precedence. Values defined by an Env with a duplicate key will take precedence. Cannot be updated.	false	Section 2.3.92, "v1.EnvFromSource" array	
env	List of environment variables to set in the container. Cannot be updated.	false	Section 2.3.93, "v1.EnvVar" array	
resources	Compute Resources required by this container. Cannot be updated. More info: http://kubernetes.io/docs/user-guide/persistent-volumes#resources	false	Section 2.3.223, "v1.ResourceRequirements"	

Name	Description	Required	Schema	Default
volumeMounts	Pod volumes to mount into the container's filesystem. Cannot be updated.	false	Section 2.3.288, "v1.VolumeMount" array	
livenessProbe	Periodic probe of container liveness. Container will be restarted if the probe fails. Cannot be updated. More info: http://kubernetes.io/docs/user-guide/pod-states#container-probes	false	Section 2.3.205, "v1.Probe"	
readinessProbe	Periodic probe of container service readiness. Container will be removed from service endpoints if the probe fails. Cannot be updated. More info: http://kubernetes.io/docs/user-guide/pod-states#container-probes	false	Section 2.3.205, "v1.Probe"	
lifecycle	Actions that the management system should take in response to container lifecycle events. Cannot be updated.	false	Section 2.3.149, "v1.Lifecycle"	

Name	Description	Required	Schema	Default
terminationMessagePath	Optional: Path at which the file to which the container's termination message will be written is mounted into the container's filesystem. Message written is intended to be brief final status, such as an assertion failure message. Will be truncated by the node if greater than 4096 bytes. The total message length across all containers will be limited to 12kb. Defaults to /dev/termination-log. Cannot be updated.	false	string	

Name	Description	Required	Schema	Default
terminationMessagePolicy	<p>Indicate how the termination message should be populated. File will use the contents of terminationMessagePath to populate the container status message on both success and failure. FallbackToLogsOnError will use the last chunk of container log output if the termination message file is empty and the container exited with an error. The log output is limited to 2048 bytes or 80 lines, whichever is smaller. Defaults to File. Cannot be updated.</p>	false	string	
imagePullPolicy	<p>Image pull policy. One of Always, Never, IfNotPresent. Defaults to Always if :latest tag is specified, or IfNotPresent otherwise. Cannot be updated. More info: http://kubernetes.io/docs/user-guide/images#updating-images</p>	false	string	

Name	Description	Required	Schema	Default
securityContext	Security options the pod should run with. More info: http://releases.k8s.io/HEAD/docs/design/security_context.md	false	Section 2.3.251, "v1.SecurityContext"	
stdin	Whether this container should allocate a buffer for stdin in the container runtime. If this is not set, reads from stdin in the container will always result in EOF. Default is false.	false	boolean	

Name	Description	Required	Schema	Default
stdinOnce	Whether the container runtime should close the stdin channel after it has been opened by a single attach. When stdin is true the stdin stream will remain open across multiple attach sessions. If stdinOnce is set to true, stdin is opened on container start, is empty until the first client attaches to stdin, and then remains open and accepts data until the client disconnects, at which time stdin is closed and remains closed until the container is restarted. If this flag is false, a container processes that reads from stdin will never receive an EOF. Default is false	false	boolean	
tty	Whether this container should allocate a TTY for itself, also requires 'stdin' to be true. Default is false.	false	boolean	

2.3.58. v1.ContainerPort

ContainerPort represents a network port in a single container.

Name	Description	Required	Schema	Default
name	If specified, this must be an IANA_SVC_NAME and unique within the pod. Each named port in a pod must have a unique name. Name for the port that can be referred to by services.	false	string	
hostPort	Number of port to expose on the host. If specified, this must be a valid port number, $0 < x < 65536$. If HostNetwork is specified, this must match ContainerPort. Most containers do not need this.	false	integer (int32)	
containerPort	Number of port to expose on the pod's IP address. This must be a valid port number, $0 < x < 65536$.	true	integer (int32)	
protocol	Protocol for port. Must be UDP or TCP. Defaults to "TCP".	false	string	
hostIP	What host IP to bind the external port to.	false	string	

2.3.59. v1.CustomBuildStrategy

CustomBuildStrategy defines input parameters specific to Custom build.

Name	Description	Required	Schema	Default
from	from is reference to an DockerImage, ImageStreamTag , or ImageStreamImage from which the docker image should be pulled	true	Section 2.3.177, "v1.ObjectReference"	
pullSecret	pullSecret is the name of a Secret that would be used for setting up the authentication for pulling the Docker images from the private Docker registries	false	Section 2.3.152, "v1.LocalObjectReference"	
env	env contains additional environment variables you want to pass into a builder container.	false	Section 2.3.93, "v1.EnvVar" array	
exposeDockerSocket	exposeDockerSocket will allow running Docker commands (and build Docker images) from inside the Docker container.	false	boolean	
forcePull	forcePull describes if the controller should configure the build pod to always pull the images for the builder or only pull if it is not present locally	false	boolean	

Name	Description	Required	Schema	Default
secrets	secrets is a list of additional secrets that will be included in the build pod	false	Section 2.3.249 , "v1.SecretSpec" array	
buildAPIVersion	buildAPIVersion is the requested API version for the Build object serialized and passed to the custom builder	false	string	

2.3.60. v1.CustomDeploymentStrategyParams

CustomDeploymentStrategyParams are the input to the Custom deployment strategy.

Name	Description	Required	Schema	Default
image	Image specifies a Docker image which can carry out a deployment.	false	string	
environment	Environment holds the environment which will be given to the container for Image.	false	Section 2.3.93 , "v1.EnvVar" array	
command	Command is optional and overrides CMD in the container Image.	false	string array	

2.3.61. v1.DeleteOptions

DeleteOptions may be provided when deleting an API object.

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/HEAD/docs/dev/api-conventions.md#types-kinds	false	string	
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/HEAD/docs/dev/api-conventions.md#resources	false	string	

Name	Description	Required	Schema	Default
gracePeriodSeconds	The duration in seconds before the object should be deleted. Value must be non-negative integer. The value zero indicates delete immediately. If this value is nil, the default grace period for the specified type will be used. Defaults to a per object value if not specified. zero means delete immediately.	false	integer (int64)	
preconditions	Must be fulfilled before a deletion is carried out. If not possible, a 409 Conflict status will be returned.	false	Section 2.3.203, "v1.Preconditions"	
orphanDependents	Deprecated: please use the PropagationPolicy, this field will be deprecated in 1.7. Should the dependent objects be orphaned. If true/false, the "orphan" finalizer will be added to/removed from the object's finalizers list. Either this field or PropagationPolicy may be set, but not both.	false	boolean	

Name	Description	Required	Schema	Default
propagationPolicy	Whether and how garbage collection will be performed. Either this field or OrphanDependents may be set, but not both. The default policy is decided by the existing finalizer set in the metadata.finalizers and the resource-specific default policy.	false	Section 2.3.62, "v1.DeletionPropagation"	

2.3.62. v1.DeletionPropagation

2.3.63. v1.DeploymentCause

DeploymentCause captures information about a particular cause of a deployment.

Name	Description	Required	Schema	Default
type	Type of the trigger that resulted in the creation of a new deployment	true	string	
imageTrigger	ImageTrigger contains the image trigger details, if this trigger was fired based on an image change	false	Section 2.3.64, "v1.DeploymentCauseImageTrigger"	

2.3.64. v1.DeploymentCauseImageTrigger

DeploymentCauseImageTrigger represents details about the cause of a deployment originating from an image change trigger

Name	Description	Required	Schema	Default
from	From is a reference to the changed object which triggered a deployment. The field may have the kinds DockerImage, ImageStreamTag, or ImageStreamImage.	true	Section 2.3.177, "v1.ObjectReference"	

2.3.65. v1.DeploymentCondition

DeploymentCondition describes the state of a deployment config at a certain point.

Name	Description	Required	Schema	Default
type	Type of deployment condition.	true	string	
status	Status of the condition, one of True, False, Unknown.	true	string	
lastUpdateTime	The last time this condition was updated.	false	string	
lastTransitionTime	The last time the condition transitioned from one status to another.	false	string	
reason	The reason for the condition's last transition.	false	string	
message	A human readable message indicating details about the transition.	false	string	

2.3.66. v1.DeploymentConfig

Deployment Configs define the template for a pod and manages deploying new images or configuration changes. A single deployment configuration is usually analogous to a single micro-service. Can support many different deployment patterns, including full restart, customizable rolling updates, and fully custom behaviors, as well as pre- and post-deployment hooks. Each individual deployment is represented as a replication controller.

A deployment is "triggered" when its configuration is changed or a tag in an Image Stream is changed. Triggers can be disabled to allow manual control over a deployment. The "strategy" determines how the deployment is carried out and may be changed at any time. The **latestVersion** field is updated when a new deployment is triggered by any means.

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#types-kinds	false	string	

Name	Description	Required	Schema	Default
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#resources	false	string	
metadata	Standard object's metadata.	false	Section 2.3.176, "v1.ObjectMeta"	
spec	Spec represents a desired deployment state and how to deploy to it.	true	Section 2.3.70, "v1.DeploymentConfigSpec"	
status	Status represents the current deployment state.	true	Section 2.3.71, "v1.DeploymentConfigStatus"	

2.3.67. v1.DeploymentConfigList

DeploymentConfigList is a collection of deployment configs.

Name	Description	Required	Schema	Default
------	-------------	----------	--------	---------

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#types-kinds	false	string	
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#resources	false	string	
metadata	Standard object's metadata.	false	Section 2.3.151, "v1.ListMeta"	
items	Items is a list of deployment configs	true	Section 2.3.66, "v1.DeploymentConfig" array	

2.3.68. v1.DeploymentConfigRollback

DeploymentConfigRollback provides the input to rollback generation.

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/HEAD/docs/dev/api-conventions.md#types-kinds	false	string	
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/HEAD/docs/dev/api-conventions.md#resources	false	string	
name	Name of the deployment config that will be rolled back.	true	string	

Name	Description	Required	Schema	Default
updatedAnnotations	UpdatedAnnotations is a set of new annotations that will be added in the deployment config.	false	object	
spec	Spec defines the options to rollback generation.	true	Section 2.3.69, "v1.DeploymentConfigRollbackSpec"	

2.3.69. v1.DeploymentConfigRollbackSpec

DeploymentConfigRollbackSpec represents the options for rollback generation.

Name	Description	Required	Schema	Default
from	From points to a ReplicationController which is a deployment.	true	Section 2.3.177, "v1.ObjectReference"	
revision	Revision to rollback to. If set to 0, rollback to the last revision.	false	integer (int64)	
includeTriggers	IncludeTriggers specifies whether to include config Triggers.	true	boolean	
includeTemplate	IncludeTemplate specifies whether to include the PodTemplateSpec.	true	boolean	
includeReplicationMeta	IncludeReplicationMeta specifies whether to include the replica count and selector.	true	boolean	

Name	Description	Required	Schema	Default
includeStrategy	IncludeStrategy specifies whether to include the deployment Strategy.	true	boolean	

2.3.70. v1.DeploymentConfigSpec

DeploymentConfigSpec represents the desired state of the deployment.

Name	Description	Required	Schema	Default
strategy	Strategy describes how a deployment is executed.	true	Section 2.3.75, "v1.Deployment Strategy"	
minReadySeconds	MinReadySeconds is the minimum number of seconds for which a newly created pod should be ready without any of its container crashing, for it to be considered available. Defaults to 0 (pod will be considered available as soon as it is ready)	false	integer (int32)	

Name	Description	Required	Schema	Default
triggers	Triggers determine how updates to a DeploymentConfig result in new deployments. If no triggers are defined, a new deployment can only occur as a result of an explicit client update to the DeploymentConfig with a new LatestVersion. If null, defaults to having a config change trigger.	true	Section 2.3.77, "v1.DeploymentTriggerPolicy" array	
replicas	Replicas is the number of desired replicas.	true	integer (int32)	
revisionHistoryLimit	RevisionHistoryLimit is the number of old ReplicationControllers to retain to allow for rollbacks. This field is a pointer to allow for differentiation between an explicit zero and not specified.	false	integer (int32)	

Name	Description	Required	Schema	Default
test	Test ensures that this deployment config will have zero replicas except while a deployment is running. This allows the deployment config to be used as a continuous deployment test - triggering on images, running the deployment, and then succeeding or failing. Post strategy hooks and After actions can be used to integrate successful deployment with an action.	true	boolean	
paused	Paused indicates that the deployment config is paused resulting in no new deployments on template changes or changes in the template caused by other triggers.	false	boolean	
selector	Selector is a label query over pods that should match the Replicas count.	false	object	

Name	Description	Required	Schema	Default
template	Template is the object that describes the pod that will be created if insufficient replicas are detected.	false	Section 2.3.196, "v1.PodTemplateSpec"	

2.3.71. v1.DeploymentConfigStatus

DeploymentConfigStatus represents the current deployment state.

Name	Description	Required	Schema	Default
latestVersion	LatestVersion is used to determine whether the current deployment associated with a deployment config is out of sync.	true	integer (int64)	
observedGeneration	ObservedGeneration is the most recent generation observed by the deployment config controller.	true	integer (int64)	
replicas	Replicas is the total number of pods targeted by this deployment config.	true	integer (int32)	
updatedReplicas	UpdatedReplicas is the total number of non-terminated pods targeted by this deployment config that have the desired template spec.	true	integer (int32)	

Name	Description	Required	Schema	Default
availableReplicas	AvailableReplicas is the total number of available pods targeted by this deployment config.	true	integer (int32)	
unavailableReplicas	UnavailableReplicas is the total number of unavailable pods targeted by this deployment config.	true	integer (int32)	
details	Details are the reasons for the update to this deployment config. This could be based on a change made by the user or caused by an automatic trigger	false	Section 2.3.72, "v1.DeploymentDetails"	
conditions	Conditions represents the latest available observations of a deployment config's current state.	false	Section 2.3.65, "v1.DeploymentCondition" array	
readyReplicas	Total number of ready pods targeted by this deployment.	false	integer (int32)	

2.3.72. v1.DeploymentDetails

DeploymentDetails captures information about the causes of a deployment.

Name	Description	Required	Schema	Default
------	-------------	----------	--------	---------

Name	Description	Required	Schema	Default
message	Message is the user specified change message, if this deployment was triggered manually by the user	false	string	
causes	Causes are extended data associated with all the causes for creating a new deployment	true	Section 2.3.63, "v1.Deployment Cause" array	

2.3.73. v1.DeploymentLog

DeploymentLog represents the logs for a deployment

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#types-kinds	false	string	

Name	Description	Required	Schema	Default
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#resources	false	string	

2.3.74. v1.DeploymentRequest

DeploymentRequest is a request to a deployment config for a new deployment.

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#types-kinds	false	string	

Name	Description	Required	Schema	Default
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#resources	false	string	
name	Name of the deployment config for requesting a new deployment.	true	string	
latest	Latest will update the deployment config with the latest state from all triggers.	true	boolean	
force	Force will try to force a new deployment to run. If the deployment config is paused, then setting this to true will return an Invalid error.	true	boolean	

Name	Description	Required	Schema	Default
excludeTriggers	ExcludeTriggers instructs the instantiator to avoid processing the specified triggers. This field overrides the triggers from latest and allows clients to control specific logic. This field is ignored if not specified.	false	Section 2.3.78, "v1.DeploymentTriggerType" array	

2.3.75. v1.DeploymentStrategy

DeploymentStrategy describes how to perform a deployment.

Name	Description	Required	Schema	Default
type	Type is the name of a deployment strategy.	false	string	
customParams	CustomParams are the input to the Custom deployment strategy, and may also be specified for the Recreate and Rolling strategies to customize the execution process that runs the deployment.	false	Section 2.3.60, "v1.CustomDeploymentStrategyParams"	
recreateParams	RecreateParams are the input to the Recreate deployment strategy.	false	Section 2.3.214, "v1.RecreateDeploymentStrategyParams"	

Name	Description	Required	Schema	Default
rollingParams	RollingParams are the input to the Rolling deployment strategy.	false	Section 2.3.231, "v1.RollingDeploymentStrategyParams"	
resources	Resources contains resource requirements to execute the deployment and any hooks.	false	Section 2.3.223, "v1.ResourceRequirements"	
labels	Labels is a set of key, value pairs added to custom deployer and lifecycle pre/post hook pods.	false	object	
annotations	Annotations is a set of key, value pairs added to custom deployer and lifecycle pre/post hook pods.	false	object	
activeDeadlineSeconds	ActiveDeadlineSeconds is the duration in seconds that the deployer pods for this deployment config may be active on a node before the system actively tries to terminate them.	false	integer (int64)	

2.3.76. v1.DeploymentTriggerImageChangeParams

DeploymentTriggerImageChangeParams represents the parameters to the ImageChange trigger.

Name	Description	Required	Schema	Default
automatic	Automatic means that the detection of a new tag value should result in an image update inside the pod template.	false	boolean	
containerNames	ContainerNames is used to restrict tag updates to the specified set of container names in a pod. If multiple triggers point to the same containers, the resulting behavior is undefined. Future API versions will make this a validation error. If ContainerNames does not point to a valid container, the trigger will be ignored. Future API versions will make this a validation error.	false	string array	

Name	Description	Required	Schema	Default
from	From is a reference to an image stream tag to watch for changes. From.Name is the only required subfield - if From.Namespace is blank, the namespace of the current deployment trigger will be used.	true	Section 2.3.177, "v1.ObjectReference"	
lastTriggeredImage	LastTriggeredImage is the last image to be triggered.	false	string	

2.3.77. v1.DeploymentTriggerPolicy

DeploymentTriggerPolicy describes a policy for a single trigger that results in a new deployment.

Name	Description	Required	Schema	Default
type	Type of the trigger	false	string	
imageChangeParams	ImageChangeParams represents the parameters for the ImageChange trigger.	false	Section 2.3.76, "v1.DeploymentTriggerImageChangeParams"	

2.3.78. v1.DeploymentTriggerType

2.3.79. v1.DeprecatedDownwardAPIVolumeFile

DeprecatedDownwardAPIVolumeFile represents information to create the file containing the pod field This type is deprecated and should be replaced by use of the downwardAPI volume source.

Name	Description	Required	Schema	Default
name	Required: Name is the relative path name of the file to be created. Must not be absolute or contain the '..' path. Must be utf-8 encoded. The first item of the relative path must not start with '..'	true	string	
fieldRef	Required: Selects a field of the pod: only annotations, labels, name and namespace are supported.	false	Section 2.3.175, "v1.ObjectFieldSelector"	
resourceFieldRef	Selects a resource of the container: only resources limits and requests (limits.cpu, limits.memory, requests.cpu and requests.memory) are currently supported.	false	Section 2.3.218, "v1.ResourceFieldSelector"	

Name	Description	Required	Schema	Default
mode	Optional: mode bits to use on this file, must be a value between 0 and 0777. If not specified, the volume defaultMode will be used. This might be in conflict with other options that affect the file mode, like fsGroup, and the result can be other mode bits set.	false	integer (int32)	

2.3.80. v1.DeprecatedDownwardAPIVolumeSource

DeprecatedDownwardAPIVolumeSource represents a volume containing downward API info. This type is deprecated and should be replaced by use of the downwardAPI volume source.

Name	Description	Required	Schema	Default
items	Items is a list of downward API volume file	false	Section 2.3.79, "v1.Deprecated DownwardAPIVolumeFile" array	

Name	Description	Required	Schema	Default
defaultMode	Optional: mode bits to use on created files by default. Must be a value between 0 and 0777. Defaults to 0644. Directories within the path are not affected by this setting. This might be in conflict with other options that affect the file mode, like fsGroup, and the result can be other mode bits set.	false	integer (int32)	

2.3.81. v1.DockerBuildStrategy

DockerBuildStrategy defines input parameters specific to Docker build.

Name	Description	Required	Schema	Default
from	from is reference to an DockerImage, ImageStreamTag, or ImageStreamImage from which the docker image should be pulled the resulting image will be used in the FROM line of the Dockerfile for this build.	false	Section 2.3.177, "v1.ObjectReference"	

Name	Description	Required	Schema	Default
pullSecret	pullSecret is the name of a Secret that would be used for setting up the authentication for pulling the Docker images from the private Docker registries	false	Section 2.3.152, "v1.LocalObjectReference"	
noCache	noCache if set to true indicates that the docker build must be executed with the --no-cache=true flag	false	boolean	
env	env contains additional environment variables you want to pass into a builder container.	false	Section 2.3.93, "v1.EnvVar" array	
forcePull	forcePull describes if the builder should pull the images from registry prior to building.	false	boolean	
dockerfilePath	dockerfilePath is the path of the Dockerfile that will be used to build the Docker image, relative to the root of the context (contextDir).	false	string	

Name	Description	Required	Schema	Default
buildArgs	buildArgs contains build arguments that will be resolved in the Dockerfile. See https://docs.docker.com/engine/reference/builder/#/arg for more details.	false	Section 2.3.93, "v1.EnvVar" array	

Name	Description	Required	Schema	Default
imageOptimizationPolicy	imageOptimizationPolicy describes what optimizations the system can use when building images to reduce the final size or time spent building the image. The default policy is 'None' which means the final build image will be equivalent to an image created by the Docker build API. The experimental policy 'SkipLayers' will avoid committing new layers in between each image step, and will fail if the Dockerfile cannot provide compatibility with the 'None' policy. An additional experimental policy 'SkipLayersAndWarn' is the same as 'SkipLayers' but simply warns if compatibility cannot be preserved.	false	Section 2.3.130, "v1.ImageOptimizationPolicy"	

2.3.82. v1.DockerStrategyOptions

DockerStrategyOptions contains extra strategy options for Docker builds

Name	Description	Required	Schema	Default
buildArgs	Args contains any build arguments that are to be passed to Docker. See https://docs.docker.com/engine/reference/builder/#/arg for more details	false	Section 2.3.93 , "v1.EnvVar" array	

2.3.83. v1.DownwardAPIProjection

Represents downward API info for projecting into a projected volume. Note that this is identical to a downwardAPI volume source without the default mode.

Name	Description	Required	Schema	Default
items	Items is a list of DownwardAPIVolume file	false	Section 2.3.84 , "v1.DownwardAPIVolumeFile" array	

2.3.84. v1.DownwardAPIVolumeFile

DownwardAPIVolumeFile represents information to create the file containing the pod field

Name	Description	Required	Schema	Default
path	Required: Path is the relative path name of the file to be created. Must not be absolute or contain the '..' path. Must be utf-8 encoded. The first item of the relative path must not start with '..'	true	string	

Name	Description	Required	Schema	Default
fieldRef	Required: Selects a field of the pod: only annotations, labels, name and namespace are supported.	false	Section 2.3.175, "v1.ObjectFieldSelector"	
resourceFieldRef	Selects a resource of the container: only resources limits and requests (limits.cpu, limits.memory, requests.cpu and requests.memory) are currently supported.	false	Section 2.3.218, "v1.ResourceFieldSelector"	
mode	Optional: mode bits to use on this file, must be a value between 0 and 0777. If not specified, the volume defaultMode will be used. This might be in conflict with other options that affect the file mode, like fsGroup, and the result can be other mode bits set.	false	integer (int32)	

2.3.85. v1.DownwardAPIVolumeSource

DownwardAPIVolumeSource represents a volume containing downward API info. Downward API volumes support ownership management and SELinux relabeling.

Name	Description	Required	Schema	Default
------	-------------	----------	--------	---------

Name	Description	Required	Schema	Default
items	Items is a list of downward API volume file	false	Section 2.3.84, "v1.DownwardAPIVolumeFile" array	
defaultMode	Optional: mode bits to use on created files by default. Must be a value between 0 and 0777. Defaults to 0644. Directories within the path are not affected by this setting. This might be in conflict with other options that affect the file mode, like fsGroup, and the result can be other mode bits set.	false	integer (int32)	

2.3.86. v1.EgressNetworkPolicy

EgressNetworkPolicy describes the current egress network policy for a Namespace. When using the 'redhat/openshift-ovs-multitenant' network plugin, traffic from a pod to an IP address outside the cluster will be checked against each EgressNetworkPolicyRule in the pod's namespace's EgressNetworkPolicy, in order. If no rule matches (or no EgressNetworkPolicy is present) then the traffic will be allowed by default.

Name	Description	Required	Schema	Default
------	-------------	----------	--------	---------

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/HEAD/docs/dev/api-conventions.md#types-kinds	false	string	
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/HEAD/docs/dev/api-conventions.md#resources	false	string	
metadata	metadata for EgressNetworkPolicy	false	Section 2.3.176, "v1.ObjectMeta"	

Name	Description	Required	Schema	Default
spec	spec is the specification of the current egress network policy	true	Section 2.3.90, "v1.EgressNetworkPolicySpec"	

2.3.87. v1.EgressNetworkPolicyList

EgressNetworkPolicyList is a collection of EgressNetworkPolicy

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#types-kinds	false	string	

Name	Description	Required	Schema	Default
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#resources	false	string	
metadata	metadata for EgressNetworkPolicyList	false	Section 2.3.151, "v1.ListMeta"	
items	items is the list of policies	true	Section 2.3.86, "v1.EgressNetworkPolicy" array	

2.3.88. v1.EgressNetworkPolicyPeer

EgressNetworkPolicyPeer specifies a target to apply egress network policy to

Name	Description	Required	Schema	Default
cidrSelector	cidrSelector is the CIDR range to allow/deny traffic to. If this is set, dnsName must be unset	false	string	

Name	Description	Required	Schema	Default
dnsName	dnsName is the domain name to allow/deny traffic to. If this is set, cidrSelector must be unset	false	string	

2.3.89. v1.EgressNetworkPolicyRule

EgressNetworkPolicyRule contains a single egress network policy rule

Name	Description	Required	Schema	Default
type	type marks this as an "Allow" or "Deny" rule	true	string	
to	to is the target that traffic is allowed/denied to	true	Section 2.3.88, "v1.EgressNetworkPolicyPeer"	

2.3.90. v1.EgressNetworkPolicySpec

EgressNetworkPolicySpec provides a list of policies on outgoing network traffic

Name	Description	Required	Schema	Default
egress	egress contains the list of egress policy rules	true	Section 2.3.89, "v1.EgressNetworkPolicyRule" array	

2.3.91. v1.EmptyDirVolumeSource

Represents an empty directory for a pod. Empty directory volumes support ownership management and SELinux relabeling.

Name	Description	Required	Schema	Default
------	-------------	----------	--------	---------

Name	Description	Required	Schema	Default
medium	What type of storage medium should back this directory. The default is "" which means to use the node's default medium. Must be an empty string (default) or Memory. More info: http://kubernetes.io/docs/user-guide/volumes#emptydir	false	string	

2.3.92. v1.EnvFromSource

EnvFromSource represents the source of a set of ConfigMaps

Name	Description	Required	Schema	Default
prefix	An optional identifier to prepend to each key in the ConfigMap. Must be a C_IDENTIFIER.	false	string	
configMapRef	The ConfigMap to select from	false	Section 2.3.53, "v1.ConfigMapEnvSource"	
secretRef	The Secret to select from	false	Section 2.3.245, "v1.SecretEnvSource"	

2.3.93. v1.EnvVar

EnvVar represents an environment variable present in a Container.

Name	Description	Required	Schema	Default
------	-------------	----------	--------	---------

Name	Description	Required	Schema	Default
name	Name of the environment variable. Must be a C_IDENTIFIER.	true	string	
value	Variable references \$(VAR_NAME) are expanded using the previous defined environment variables in the container and any service environment variables. If a variable cannot be resolved, the reference in the input string will be unchanged. The \$(VAR_NAME) syntax can be escaped with a double , ie: (VAR_NAME). Escaped references will never be expanded, regardless of whether the variable exists or not. Defaults to "".	false	string	
valueFrom	Source for the environment variable's value. Cannot be used if value is not empty.	false	Section 2.3.94, "v1.EnvVarSource"	

2.3.94. v1.EnvVarSource

EnvVarSource represents a source for the value of an EnvVar.

Name	Description	Required	Schema	Default
fieldRef	Selects a field of the pod: supports metadata.name, metadata.names pace, metadata.labels, metadata.annotations, spec.nodeName, spec.serviceAccountName, status.podIP.	false	Section 2.3.175, "v1.ObjectFieldSelector"	
resourceFieldRef	Selects a resource of the container: only resources limits and requests (limits.cpu, limits.memory, requests.cpu and requests.memory) are currently supported.	false	Section 2.3.218, "v1.ResourceFieldSelector"	
configMapKeyRef	Selects a key of a ConfigMap.	false	Section 2.3.54, "v1.ConfigMapKeySelector"	
secretKeyRef	Selects a key of a secret in the pod's namespace	false	Section 2.3.246, "v1.SecretKeySelector"	

2.3.95. v1.ExecAction

ExecAction describes a "run in container" action.

Name	Description	Required	Schema	Default
------	-------------	----------	--------	---------

Name	Description	Required	Schema	Default
command	Command is the command line to execute inside the container, the working directory for the command is root ('/') in the container's filesystem. The command is simply exec'd, it is not run inside a shell, so traditional shell instructions (' ', etc) won't work. To use a shell, you need to explicitly call out to that shell. Exit status of 0 is treated as live/healthy and non-zero is unhealthy.	false	string array	

2.3.96. v1.ExecNewPodHook

ExecNewPodHook is a hook implementation which runs a command in a new pod based on the specified container which is assumed to be part of the deployment template.

Name	Description	Required	Schema	Default
command	Command is the action command and its arguments.	true	string array	
env	Env is a set of environment variables to supply to the hook pod's container.	false	Section 2.3.93, "v1.EnvVar" array	

Name	Description	Required	Schema	Default
containerName	ContainerName is the name of a container in the deployment pod template whose Docker image will be used for the hook pod's container.	true	string	
volumes	Volumes is a list of named volumes from the pod template which should be copied to the hook pod. Volumes names not found in pod spec are ignored. An empty list means no volumes will be copied.	false	string array	

2.3.97. v1.FCVolumeSource

Represents a Fibre Channel volume. Fibre Channel volumes can only be mounted as read/write once. Fibre Channel volumes support ownership management and SELinux relabeling.

Name	Description	Required	Schema	Default
targetWWNs	Required: FC target worldwide names (WWNs)	true	string array	
lun	Required: FC target lun number	true	integer (int32)	

Name	Description	Required	Schema	Default
fsType	Filesystem type to mount. Must be a filesystem type supported by the host operating system. Ex. "ext4", "xfs", "ntfs". Implicitly inferred to be "ext4" if unspecified.	false	string	
readOnly	Optional: Defaults to false (read/write). ReadOnly here will force the ReadOnly setting in VolumeMounts.	false	boolean	

2.3.98. v1.FinalizerName

2.3.99. v1.FlexVolumeSource

FlexVolume represents a generic volume resource that is provisioned/attached using an exec based plugin. This is an alpha feature and may change in future.

Name	Description	Required	Schema	Default
driver	Driver is the name of the driver to use for this volume.	true	string	

Name	Description	Required	Schema	Default
fsType	Filesystem type to mount. Must be a filesystem type supported by the host operating system. Ex. "ext4", "xfs", "ntfs". The default filesystem depends on FlexVolume script.	false	string	
secretRef	Optional: SecretRef is reference to the secret object containing sensitive information to pass to the plugin scripts. This may be empty if no secret object is specified. If the secret object contains more than one secret, all secrets are passed to the plugin scripts.	false	Section 2.3.152, "v1.LocalObject Reference"	
readOnly	Optional: Defaults to false (read/write). ReadOnly here will force the ReadOnly setting in VolumeMounts.	false	boolean	
options	Optional: Extra command options if any.	false	object	

2.3.100. v1.FlockerVolumeSource

Represents a Flocker volume mounted by the Flocker agent. One and only one of `datasetName` and `datasetUUID` should be set. Flocker volumes do not support ownership management or SELinux relabeling.

Name	Description	Required	Schema	Default
<code>datasetName</code>	Name of the dataset stored as metadata → name on the dataset for Flocker should be considered as deprecated	false	string	
<code>datasetUUID</code>	UUID of the dataset. This is unique identifier of a Flocker dataset	false	string	

2.3.101. v1.GCEPersistentDiskVolumeSource

Represents a Persistent Disk resource in Google Compute Engine.

A GCE PD must exist before mounting to a container. The disk must also be in the same GCE project and zone as the kubelet. A GCE PD can only be mounted as read/write once or read-only many times. GCE PDs support ownership management and SELinux relabeling.

Name	Description	Required	Schema	Default
<code>pdName</code>	Unique name of the PD resource in GCE. Used to identify the disk in GCE. More info: http://kubernetes.io/docs/user-guide/volumes#gcepersistentdisk	true	string	

Name	Description	Required	Schema	Default
fsType	<p>Filesystem type of the volume that you want to mount. Tip: Ensure that the filesystem type is supported by the host operating system.</p> <p>Examples: "ext4", "xfs", "ntfs". Implicitly inferred to be "ext4" if unspecified.</p> <p>More info: http://kubernetes.io/docs/user-guide/volumes#gcepersistentdisk</p>	false	string	
partition	<p>The partition in the volume that you want to mount. If omitted, the default is to mount by volume name.</p> <p>Examples: For volume /dev/sda1, you specify the partition as "1". Similarly, the volume partition for /dev/sda is "0" (or you can leave the property empty).</p> <p>More info: http://kubernetes.io/docs/user-guide/volumes#gcepersistentdisk</p>	false	integer (int32)	

Name	Description	Required	Schema	Default
readOnly	ReadOnly here will force the ReadOnly setting in VolumeMounts. Defaults to false. More info: http://kubernetes.io/docs/user-guide/volumes#gcepersistentdisk	false	boolean	

2.3.102. v1.GenericWebHookCause

GenericWebHookCause holds information about a generic WebHook that triggered a build.

Name	Description	Required	Schema	Default
revision	revision is an optional field that stores the git source revision information of the generic webhook trigger when it is available.	false	Section 2.3.262, "v1.SourceRevision"	
secret	secret is the obfuscated webhook secret that triggered a build.	false	string	

2.3.103. v1.GitBuildSource

GitBuildSource defines the parameters of a Git SCM

Name	Description	Required	Schema	Default
------	-------------	----------	--------	---------

Name	Description	Required	Schema	Default
uri	uri points to the source that will be built. The structure of the source will depend on the type of build to run	true	string	
ref	ref is the branch/tag/ref to build.	false	string	
httpProxy	httpProxy is a proxy used to reach the git repository over http	false	string	
httpsProxy	httpsProxy is a proxy used to reach the git repository over https	false	string	
noProxy	noProxy is the list of domains for which the proxy should not be used	false	string	

2.3.104. v1.GitHubWebHookCause

GitHubWebHookCause has information about a GitHub webhook that triggered a build.

Name	Description	Required	Schema	Default
revision	revision is the git revision information of the trigger.	false	Section 2.3.262, "v1.SourceRevision"	

Name	Description	Required	Schema	Default
secret	secret is the obfuscated webhook secret that triggered a build.	false	string	

2.3.105. v1.GitLabWebHookCause

GitLabWebHookCause has information about a GitLab webhook that triggered a build.

Name	Description	Required	Schema	Default
revision	Revision is the git source revision information of the trigger.	false	Section 2.3.262, "v1.SourceRevision"	
secret	Secret is the obfuscated webhook secret that triggered a build.	false	string	

2.3.106. v1.GitRepoVolumeSource

Represents a volume that is populated with the contents of a git repository. Git repo volumes do not support ownership management. Git repo volumes support SELinux relabeling.

Name	Description	Required	Schema	Default
repository	Repository URL	true	string	
revision	Commit hash for the specified revision.	false	string	

Name	Description	Required	Schema	Default
directory	Target directory name. Must not contain or start with '..'. If '.' is supplied, the volume directory will be the git repository. Otherwise, if specified, the volume will contain the git repository in the subdirectory with the given name.	false	string	

2.3.107. v1.GitSourceRevision

GitSourceRevision is the commit information from a git source for a build

Name	Description	Required	Schema	Default
commit	commit is the commit hash identifying a specific commit	false	string	
author	author is the author of a specific commit	false	Section 2.3.261, "v1.SourceControlUser"	
committer	committer is the committer of a specific commit	false	Section 2.3.261, "v1.SourceControlUser"	
message	message is the description of a specific commit	false	string	

2.3.108. v1.GlusterfsVolumeSource

Represents a Glusterfs mount that lasts the lifetime of a pod. Glusterfs volumes do not support ownership management or SELinux relabeling.

Name	Description	Required	Schema	Default
endpoints	EndpointsName is the endpoint name that details Glusterfs topology. More info: http://releases.k8s.io/HEAD/examples/volumes/glusterfs/README.md#create-a-pod	true	string	
path	Path is the Glusterfs volume path. More info: http://releases.k8s.io/HEAD/examples/volumes/glusterfs/README.md#create-a-pod	true	string	
readOnly	ReadOnly here will force the Glusterfs volume to be mounted with read-only permissions. Defaults to false. More info: http://releases.k8s.io/HEAD/examples/volumes/glusterfs/README.md#create-a-pod	false	boolean	

2.3.109. v1.Group

Group represents a referenceable set of Users

Name	Description	Required	Schema	Default
------	-------------	----------	--------	---------

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#types-kinds	false	string	
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#resources	false	string	
metadata	Standard object's metadata.	false	Section 2.3.176, "v1.ObjectMeta"	
users	Users is the list of users in this group.	true	string array	

2.3.110. v1.GroupList

GroupList is a collection of Groups

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/HEAD/docs/dev/api-conventions.md#types-kinds	false	string	
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/HEAD/docs/dev/api-conventions.md#resources	false	string	
metadata	Standard object's metadata.	false	Section 2.3.151, "v1.ListMeta"	

Name	Description	Required	Schema	Default
items	Items is the list of groups	true	Section 2.3.109 , “v1.Group” array	

2.3.111. v1.GroupRestriction

GroupRestriction matches a group either by a string match on the group name or a label selector applied to group labels.

Name	Description	Required	Schema	Default
groups	Groups is a list of groups used to match against an individual user’s groups. If the user is a member of one of the whitelisted groups, the user is allowed to be bound to a role.	true	string array	
labels	Selectors specifies a list of label selectors over group labels.	true	Section 2.3.147 , “v1.LabelSelector” array	

2.3.112. v1.HTTPGetAction

HTTPGetAction describes an action based on HTTP Get requests.

Name	Description	Required	Schema	Default
path	Path to access on the HTTP server.	false	string	

Name	Description	Required	Schema	Default
port	Name or number of the port to access on the container. Number must be in the range 1 to 65535. Name must be an IANA_SVC_NAME .	true	string	
host	Host name to connect to, defaults to the pod IP. You probably want to set "Host" in httpHeaders instead.	false	string	
scheme	Scheme to use for connecting to the host. Defaults to HTTP.	false	string	
httpHeaders	Custom headers to set in the request. HTTP allows repeated headers.	false	Section 2.3.113 , "v1.HTTPHeader" array	

2.3.113. v1.HTTPHeader

HTTPHeader describes a custom header to be used in HTTP probes

Name	Description	Required	Schema	Default
name	The header field name	true	string	
value	The header field value	true	string	

2.3.114. v1.Handler

Handler defines a specific action that should be taken

Name	Description	Required	Schema	Default
exec	One and only one of the following should be specified. Exec specifies the action to take.	false	Section 2.3.95, "v1.ExecAction"	
httpGet	HTTPGet specifies the http request to perform.	false	Section 2.3.112, "v1.HTTPGetAction"	
tcpSocket	TCPsocket specifies an action involving a TCP port. TCP hooks not yet supported	false	Section 2.3.272, "v1.TCPsocketAction"	

2.3.115. v1.HostPathVolumeSource

Represents a host path mapped into a pod. Host path volumes do not support ownership management or SELinux relabeling.

Name	Description	Required	Schema	Default
path	Path of the directory on the host. More info: http://kubernetes.io/docs/user-guide/volumes#hostpath	true	string	

2.3.116. v1.HostSubnet

HostSubnet describes the container subnet network on a node. The HostSubnet object must have the same name as the Node object it corresponds to.

Name	Description	Required	Schema	Default
------	-------------	----------	--------	---------

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#types-kinds	false	string	
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#resources	false	string	
metadata	Standard object's metadata.	false	Section 2.3.176, "v1.ObjectMeta"	

Name	Description	Required	Schema	Default
host	Host is the name of the node. (This is the same as the object's name, but both fields must be set.)	true	string	
hostIP	HostIP is the IP address to be used as a VTEP by other nodes in the overlay network	true	string	
subnet	Subnet is the CIDR range of the overlay network assigned to the node for its pods	true	string	

2.3.117. v1.HostSubnetList

HostSubnetList is a collection of HostSubnets

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#types-kinds	false	string	

Name	Description	Required	Schema	Default
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#resources	false	string	
metadata	Standard object's metadata.	false	Section 2.3.151, "v1.ListMeta"	
items	Items is the list of host subnets	true	Section 2.3.116, "v1.HostSubnet" array	

2.3.118. v1.ISCSIVolumeSource

Represents an iSCSI disk. iSCSI volumes can only be mounted as read/write once. iSCSI volumes support ownership management and SELinux relabeling.

Name	Description	Required	Schema	Default
targetPortal	iSCSI target portal. The portal is either an IP or ip_addr:port if the port is other than default (typically TCP ports 860 and 3260).	true	string	

Name	Description	Required	Schema	Default
iqn	Target iSCSI Qualified Name.	true	string	
lun	iSCSI target lun number.	true	integer (int32)	
iscsiInterface	Optional: Defaults to 'default' (tcp). iSCSI interface name that uses an iSCSI transport.	false	string	
fsType	Filesystem type of the volume that you want to mount. Tip: Ensure that the filesystem type is supported by the host operating system. Examples: "ext4", "xfs", "ntfs". Implicitly inferred to be "ext4" if unspecified. More info: http://kubernetes.io/docs/user-guide/volumes#iscsi	false	string	
readOnly	ReadOnly here will force the ReadOnly setting in VolumeMounts. Defaults to false.	false	boolean	

Name	Description	Required	Schema	Default
portals	iSCSI target portal List. The portal is either an IP or ip_addr:port if the port is other than default (typically TCP ports 860 and 3260).	false	string array	
chapAuthDiscovery	whether support iSCSI Discovery CHAP authentication	false	boolean	
chapAuthSession	whether support iSCSI Session CHAP authentication	false	boolean	
secretRef	CHAP secret for iSCSI target and initiator authentication	false	Section 2.3.152, "v1.LocalObject Reference"	

2.3.119. v1.Identity

Identity records a successful authentication of a user with an identity provider. The information about the source of authentication is stored on the identity, and the identity is then associated with a single user object. Multiple identities can reference a single user. Information retrieved from the authentication provider is stored in the extra field using a schema determined by the provider.

Name	Description	Required	Schema	Default
------	-------------	----------	--------	---------

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#types-kinds	false	string	
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#resources	false	string	
metadata	Standard object's metadata.	false	Section 2.3.176, "v1.ObjectMeta"	
providerName	ProviderName is the source of identity information	true	string	

Name	Description	Required	Schema	Default
providerUserName	ProviderUserName uniquely represents this identity in the scope of the provider	true	string	
user	User is a reference to the user this identity is associated with Both Name and UID must be set	true	Section 2.3.177, "v1.ObjectReference"	
extra	Extra holds extra information about this identity	false	object	

2.3.120. v1.IdentityList

IdentityList is a collection of Identities

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#types-kinds	false	string	

Name	Description	Required	Schema	Default
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#resources	false	string	
metadata	Standard object's metadata.	false	Section 2.3.151, "v1.ListMeta"	
items	Items is the list of identities	true	Section 2.3.119, "v1.Identity" array	

2.3.121. v1.Image

Image is an immutable representation of a Docker image and metadata at a point in time.

Name	Description	Required	Schema	Default
------	-------------	----------	--------	---------

Name	Description	Required	Schema	Default
kind	<p>Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#types-kinds</p>	false	string	
apiVersion	<p>APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#resources</p>	false	string	
metadata	Standard object's metadata.	false	Section 2.3.176, "v1.ObjectMeta"	

Name	Description	Required	Schema	Default
dockerImageReference	DockerImageReference is the string that can be used to pull this image.	false	string	
dockerImageMetadata	DockerImageMetadata contains metadata about this image	false	string	
dockerImageMetadataVersion	DockerImageMetadataVersion conveys the version of the object, which if empty defaults to "1.0"	false	string	
dockerImageManifest	DockerImageManifest is the raw JSON of the manifest	false	string	
dockerImageLayers	DockerImageLayers represents the layers in the image. May not be set if the image does not define that data.	true	Section 2.3.127, "v1.ImageLayer" array	
signatures	Signatures holds all signatures of the image.	false	Section 2.3.131, "v1.ImageSignature" array	
dockerImageSignatures	DockerImageSignatures provides the signatures as opaque blobs. This is a part of manifest schema v1.	false	v1.Image.dockerImageSignatures array	

Name	Description	Required	Schema	Default
dockerImageManifestMediaType	DockerImageManifestMediaType specifies the mediaType of manifest. This is a part of manifest schema v2.	false	string	
dockerImageConfig	DockerImageConfig is a JSON blob that the runtime uses to set up the container. This is a part of manifest schema v2.	false	string	

2.3.122. v1.ImageChangeCause

ImageChangeCause contains information about the image that triggered a build

Name	Description	Required	Schema	Default
imageID	imageID is the ID of the image that triggered a new build.	false	string	
fromRef	fromRef contains detailed information about an image that triggered a build.	false	Section 2.3.177, "v1.ObjectReference"	

2.3.123. v1.ImageChangeTrigger

ImageChangeTrigger allows builds to be triggered when an ImageStream changes

Name	Description	Required	Schema	Default
------	-------------	----------	--------	---------

Name	Description	Required	Schema	Default
lastTriggeredImageID	lastTriggeredImageID is used internally by the ImageChangeController to save last used image ID for build	false	string	
from	from is a reference to an ImageStreamTag that will trigger a build when updated. It is optional. If no From is specified, the From image from the build strategy will be used. Only one ImageChangeTrigger with an empty From reference is allowed in a build configuration.	false	Section 2.3.177, "v1.ObjectReference"	

2.3.124. v1.ImageImportSpec

ImageImportSpec describes a request to import a specific image.

Name	Description	Required	Schema	Default
from	From is the source of an image to import; only kind DockerImage is allowed	true	Section 2.3.177, "v1.ObjectReference"	

Name	Description	Required	Schema	Default
to	To is a tag in the current image stream to assign the imported image to, if name is not specified the default tag from from.name will be used	false	Section 2.3.152, "v1.LocalObjectReference"	
importPolicy	ImportPolicy is the policy controlling how the image is imported	false	Section 2.3.277, "v1.TagImportPolicy"	
referencePolicy	ReferencePolicy defines how other components should consume the image	false	Section 2.3.279, "v1.TagReferencePolicy"	
includeManifest	IncludeManifest determines if the manifest for each image is returned in the response	false	boolean	

2.3.125. v1.ImageImportStatus

ImageImportStatus describes the result of an image import.

Name	Description	Required	Schema	Default
status	Status is the status of the image import, including errors encountered while retrieving the image	true	Section 2.3.264, "v1.Status"	

Name	Description	Required	Schema	Default
image	Image is the metadata of that image, if the image was located	false	Section 2.3.121, "v1.Image"	
tag	Tag is the tag this image was located under, if any	false	string	

2.3.126. v1.ImageLabel

ImageLabel represents a label applied to the resulting image.

Name	Description	Required	Schema	Default
name	name defines the name of the label. It must have non-zero length.	true	string	
value	value defines the literal value of the label.	false	string	

2.3.127. v1.ImageLayer

ImageLayer represents a single layer of the image. Some images may have multiple layers. Some may have none.

Name	Description	Required	Schema	Default
name	Name of the layer as defined by the underlying store.	true	string	
size	Size of the layer in bytes as defined by the underlying store.	true	integer (int64)	
mediaType	MediaType of the referenced object.	true	string	

2.3.128. v1.ImageList

ImageList is a list of Image objects.

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/HEAD/docs/dev/api-conventions.md#types-kinds	false	string	
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/HEAD/docs/dev/api-conventions.md#resources	false	string	
metadata	Standard object's metadata.	false	Section 2.3.151, "v1.ListMeta"	

Name	Description	Required	Schema	Default
items	Items is a list of images	true	Section 2.3.121 , "v1.Image" array	

2.3.129. v1.ImageLookupPolicy

ImageLookupPolicy describes how an image stream can be used to override the image references used by pods, builds, and other resources in a namespace.

Name	Description	Required	Schema	Default
local	local will change the docker short image references (like "mysql" or "php:latest") on objects in this namespace to the image ID whenever they match this image stream, instead of reaching out to a remote registry. The name will be fully qualified to an image ID if found. The tag's referencePolicy is taken into account on the replaced value. Only works within the current namespace.	true	boolean	

2.3.130. v1.ImageOptimizationPolicy

2.3.131. v1.ImageSignature

ImageSignature holds a signature of an image. It allows to verify image identity and possibly other claims as long as the signature is trusted. Based on this information it is possible to restrict runnable images to those matching cluster-wide policy. Mandatory fields

should be parsed by clients doing image verification. The others are parsed from signature's content by the server. They serve just an informative purpose.

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/HEAD/docs/dev/api-conventions.md#types-kinds	false	string	
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/HEAD/docs/dev/api-conventions.md#resources	false	string	
metadata	Standard object's metadata.	false	Section 2.3.176, "v1.ObjectMeta"	

Name	Description	Required	Schema	Default
type	Required: Describes a type of stored blob.	true	string	
content	Required: An opaque binary string which is an image's signature.	true	string	
conditions	Conditions represent the latest available observations of a signature's current state.	false	Section 2.3.257, "v1.SignatureCondition" array	
imageIdentity	A human readable string representing image's identity. It could be a product name and version, or an image pull spec (e.g. "registry.access.redhat.com/rhel7/rhel:7.2").	false	string	
signedClaims	Contains claims from the signature.	false	object	
created	If specified, it is the time of signature's creation.	false	string	

Name	Description	Required	Schema	Default
issuedBy	If specified, it holds information about an issuer of signing certificate or key (a person or entity who signed the signing certificate or key).	false	Section 2.3.258, "v1.SignatureIssuer"	
issuedTo	If specified, it holds information about a subject of signing certificate or key (a person or entity who signed the image).	false	Section 2.3.259, "v1.SignatureSubject"	

2.3.132. v1.ImageSource

ImageSource is used to describe build source that will be extracted from an image. A reference of type ImageStreamTag, ImageStreamImage or DockerImage may be used. A pull secret can be specified to pull the image from an external registry or override the default service account secret if pulling from the internal registry. A list of paths to copy from the image and their respective destination within the build directory must be specified in the paths array.

Name	Description	Required	Schema	Default
from	from is a reference to an ImageStreamTag, ImageStreamImage, or DockerImage to copy source from.	true	Section 2.3.177, "v1.ObjectReference"	
paths	paths is a list of source and destination paths to copy from the image.	true	Section 2.3.133, "v1.ImageSourcePath" array	

Name	Description	Required	Schema	Default
pullSecret	pullSecret is a reference to a secret to be used to pull the image from a registry. If the image is pulled from the OpenShift registry, this field does not need to be set.	false	Section 2.3.152, "v1.LocalObject Reference"	

2.3.133. v1.ImageSourcePath

ImageSourcePath describes a path to be copied from a source image and its destination within the build directory.

Name	Description	Required	Schema	Default
sourcePath	sourcePath is the absolute path of the file or directory inside the image to copy to the build directory. If the source path ends in /, then the content of the directory will be copied, but the directory itself will not be created at the destination.	true	string	
destinationDir	destinationDir is the relative directory within the build directory where files copied from the image are placed.	true	string	

2.3.134. v1.ImageStream

ImageStream stores a mapping of tags to images, metadata overrides that are applied when images are tagged in a stream, and an optional reference to a Docker image repository on a registry.

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/HEAD/docs/dev/api-conventions.md#types-kinds	false	string	
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/HEAD/docs/dev/api-conventions.md#resources	false	string	
metadata	Standard object's metadata.	false	Section 2.3.176, "v1.ObjectMeta"	

Name	Description	Required	Schema	Default
spec	Spec describes the desired state of this stream	true	Section 2.3.141, "v1.ImageStreamSpec"	
status	Status describes the current state of this stream	false	Section 2.3.142, "v1.ImageStreamStatus"	

2.3.135. v1.ImageStreamImage

ImageStreamImage represents an Image that is retrieved by image name from an ImageStream.

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#types-kinds	false	string	

Name	Description	Required	Schema	Default
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#resources	false	string	
metadata	Standard object's metadata.	false	Section 2.3.176, "v1.ObjectMeta"	
image	Image associated with the ImageStream and image name.	true	Section 2.3.121, "v1.Image"	

2.3.136. v1.ImageStreamImport

The image stream import resource provides an easy way for a user to find and import Docker images from other Docker registries into the server. Individual images or an entire image repository may be imported, and users may choose to see the results of the import prior to tagging the resulting images into the specified image stream.

This API is intended for end-user tools that need to see the metadata of the image prior to import (for instance, to generate an application from it). Clients that know the desired image can continue to create spec.tags directly into their image streams.

Name	Description	Required	Schema	Default
------	-------------	----------	--------	---------

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#types-kinds	false	string	
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#resources	false	string	
metadata	Standard object's metadata.	false	Section 2.3.176, "v1.ObjectMeta"	

Name	Description	Required	Schema	Default
spec	Spec is a description of the images that the user wishes to import	true	Section 2.3.137, "v1.ImageStreamImportSpec"	
status	Status is the the result of importing the image	true	Section 2.3.138, "v1.ImageStreamImportStatus"	

2.3.137. v1.ImageStreamImportSpec

ImageStreamImportSpec defines what images should be imported.

Name	Description	Required	Schema	Default
import	Import indicates whether to perform an import - if so, the specified tags are set on the spec and status of the image stream defined by the type meta.	true	boolean	
repository	Repository is an optional import of an entire Docker image repository. A maximum limit on the number of tags imported this way is imposed by the server.	false	Section 2.3.215, "v1.RepositoryImportSpec"	
images	Images are a list of individual images to import.	false	Section 2.3.124, "v1.ImageImportSpec" array	

2.3.138. v1.ImageStreamImportStatus

ImageStreamImportStatus contains information about the status of an image stream import.

Name	Description	Required	Schema	Default
import	Import is the image stream that was successfully updated or created when 'to' was set.	false	Section 2.3.134, "v1.ImageStream"	
repository	Repository is set if spec.repository was set to the outcome of the import	false	Section 2.3.216, "v1.RepositoryImportStatus"	
images	Images is set with the result of importing spec.images	false	Section 2.3.125, "v1.ImageImportStatus" array	

2.3.139. v1.ImageStreamList

ImageStreamList is a list of ImageStream objects.

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#types-kinds	false	string	

Name	Description	Required	Schema	Default
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#resources	false	string	
metadata	Standard object's metadata.	false	Section 2.3.151, "v1.ListMeta"	
items	Items is a list of imageStreams	true	Section 2.3.134, "v1.ImageStream" array	

2.3.140. v1.ImageStreamMapping

ImageStreamMapping represents a mapping from a single tag to a Docker image as well as the reference to the Docker image stream the image came from.

Name	Description	Required	Schema	Default
------	-------------	----------	--------	---------

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#types-kinds	false	string	
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#resources	false	string	
metadata	Standard object's metadata.	false	Section 2.3.176, "v1.ObjectMeta"	
image	Image is a Docker image.	true	Section 2.3.121, "v1.Image"	

Name	Description	Required	Schema	Default
tag	Tag is a string value this image can be located with inside the stream.	true	string	

2.3.141. v1.ImageStreamSpec

ImageStreamSpec represents options for ImageStreams.

Name	Description	Required	Schema	Default
lookupPolicy	lookupPolicy controls how other resources reference images within this namespace.	false	Section 2.3.129, "v1.ImageLookupPolicy"	
dockerImageRepository	dockerImageRepository is optional, if specified this stream is backed by a Docker repository on this server	false	string	
tags	tags map arbitrary string values to specific image locators	false	Section 2.3.278, "v1.TagReference" array	

2.3.142. v1.ImageStreamStatus

ImageStreamStatus contains information about the state of this image stream.

Name	Description	Required	Schema	Default
------	-------------	----------	--------	---------

Name	Description	Required	Schema	Default
dockerImageRepository	DockerImageRepository represents the effective location this stream may be accessed at. May be empty until the server determines where the repository is located	true	string	
tags	Tags are a historical record of images associated with each tag. The first entry in the TagEvent array is the currently tagged image.	false	Section 2.3.160, "v1.NamedTagEventList" array	

2.3.143. v1.ImageStreamTag

ImageStreamTag represents an Image that is retrieved by tag name from an ImageStream.

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#types-kinds	false	string	

Name	Description	Required	Schema	Default
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#resources	false	string	
metadata	Standard object's metadata.	false	Section 2.3.176, "v1.ObjectMeta"	
tag	tag is the spec tag associated with this image stream tag, and it may be null if only pushes have occurred to this image stream.	true	Section 2.3.278, "v1.TagReference"	

Name	Description	Required	Schema	Default
generation	generation is the current generation of the tagged image - if tag is provided and this value is not equal to the tag generation, a user has requested an import that has not completed, or conditions will be filled out indicating any error.	true	integer (int64)	
lookupPolicy	lookupPolicy indicates whether this tag will handle image references in this namespace.	true	Section 2.3.129, "v1.ImageLookupPolicy"	
conditions	conditions is an array of conditions that apply to the image stream tag.	false	Section 2.3.275, "v1.TagEventCondition" array	
image	image associated with the ImageStream and tag.	true	Section 2.3.121, "v1.Image"	

2.3.144. v1.ImageStreamTagList

ImageStreamTagList is a list of ImageStreamTag objects.

Name	Description	Required	Schema	Default
------	-------------	----------	--------	---------

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/HEAD/docs/dev/api-conventions.md#types-kinds	false	string	
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/HEAD/docs/dev/api-conventions.md#resources	false	string	
metadata	Standard object's metadata.	false	Section 2.3.151, "v1.ListMeta"	
items	Items is the list of image stream tags	true	Section 2.3.143, "v1.ImageStreamTag" array	

2.3.145. v1.JenkinsPipelineBuildStrategy

JenkinsPipelineBuildStrategy holds parameters specific to a Jenkins Pipeline build. This strategy is in tech preview.

Name	Description	Required	Schema	Default
jenkinsfilePath	JenkinsfilePath is the optional path of the Jenkinsfile that will be used to configure the pipeline relative to the root of the context (contextDir). If both JenkinsfilePath & Jenkinsfile are both not specified, this defaults to Jenkinsfile in the root of the specified contextDir.	false	string	
jenkinsfile	Jenkinsfile defines the optional raw contents of a Jenkinsfile which defines a Jenkins pipeline build.	false	string	
env	env contains additional environment variables you want to pass into a build pipeline.	false	Section 2.3.93, "v1.EnvVar" array	

2.3.146. v1.KeyToPath

Maps a string key to a path within a volume.

Name	Description	Required	Schema	Default
key	The key to project.	true	string	

Name	Description	Required	Schema	Default
path	The relative path of the file to map the key to. May not be an absolute path. May not contain the path element '..'. May not start with the string '..'.	true	string	
mode	Optional: mode bits to use on this file, must be a value between 0 and 0777. If not specified, the volume defaultMode will be used. This might be in conflict with other options that affect the file mode, like fsGroup, and the result can be other mode bits set.	false	integer (int32)	

2.3.147. v1.LabelSelector

A label selector is a label query over a set of resources. The result of matchLabels and matchExpressions are ANDed. An empty label selector matches all objects. A null label selector matches no objects.

Name	Description	Required	Schema	Default
------	-------------	----------	--------	---------

Name	Description	Required	Schema	Default
matchLabels	matchLabels is a map of {key,value} pairs. A single {key,value} in the matchLabels map is equivalent to an element of matchExpressions, whose key field is "key", the operator is "In", and the values array contains only "value". The requirements are ANDed.	false	object	
matchExpressions	matchExpressions is a list of label selector requirements. The requirements are ANDed.	false	Section 2.3.148, "v1.LabelSelectorRequirement" array	

2.3.148. v1.LabelSelectorRequirement

A label selector requirement is a selector that contains values, a key, and an operator that relates the key and values.

Name	Description	Required	Schema	Default
key	key is the label key that the selector applies to.	true	string	
operator	operator represents a key's relationship to a set of values. Valid operators are In, NotIn, Exists and DoesNotExist.	true	string	

Name	Description	Required	Schema	Default
values	values is an array of string values. If the operator is In or NotIn, the values array must be non-empty. If the operator is Exists or DoesNotExist, the values array must be empty. This array is replaced during a strategic merge patch.	false	string array	

2.3.149. v1.Lifecycle

Lifecycle describes actions that the management system should take in response to container lifecycle events. For the PostStart and PreStop lifecycle handlers, management of the container blocks until the action is complete, unless the container process fails, in which case the handler is aborted.

Name	Description	Required	Schema	Default
postStart	PostStart is called immediately after a container is created. If the handler fails, the container is terminated and restarted according to its restart policy. Other management of the container blocks until the hook completes. More info: http://kubernetes.io/docs/user-guide/container-environment#hook-details	false	Section 2.3.114, "v1.Handler"	

Name	Description	Required	Schema	Default
preStop	PreStop is called immediately before a container is terminated. The container is terminated after the handler completes. The reason for termination is passed to the handler. Regardless of the outcome of the handler, the container is eventually terminated. Other management of the container blocks until the hook completes. More info: http://kubernetes.io/docs/user-guide/container-environment#hook-details	false	Section 2.3.114, "v1.Handler"	

2.3.150. v1.LifecycleHook

LifecycleHook defines a specific deployment lifecycle action. Only one type of action may be specified at any time.

Name	Description	Required	Schema	Default
failurePolicy	FailurePolicy specifies what action to take if the hook fails.	true	string	
execNewPod	ExecNewPod specifies the options for a lifecycle hook backed by a pod.	false	Section 2.3.96, "v1.ExecNewPod Hook"	

Name	Description	Required	Schema	Default
tagImages	TagImages instructs the deployer to tag the current image referenced under a container onto an image stream tag.	false	Section 2.3.276 , “v1.TagImageHook” array	

2.3.151. v1.ListMeta

ListMeta describes metadata that synthetic resources must have, including lists and various status objects. A resource may have only one of {ObjectMeta, ListMeta}.

Name	Description	Required	Schema	Default
selfLink	SelfLink is a URL representing this object. Populated by the system. Read-only.	false	string	

Name	Description	Required	Schema	Default
resourceVersion	String that identifies the server's internal version of this object that can be used by clients to determine when objects have changed. Value must be treated as opaque by clients and passed unmodified back to the server. Populated by the system. Read-only. More info: http://releases.k8s.io/HEAD/docs/dev/api-conventions.md#concurrency-control-and-consistency	false	string	

2.3.152. v1.LocalObjectReference

LocalObjectReference contains enough information to let you locate the referenced object inside the same namespace.

Name	Description	Required	Schema	Default
name	Name of the referent. More info: http://kubernetes.io/docs/user-guide/identifiers#names	false	string	

2.3.153. v1.LocalResourceAccessReview

LocalResourceAccessReview is a means to request a list of which users and groups are authorized to perform the action specified by spec in a particular namespace

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#types-kinds	false	string	
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#resources	false	string	

Name	Description	Required	Schema	Default
namespace	Namespace is the namespace of the action being requested. Currently, there is no distinction between no namespace and all namespaces	true	string	
verb	Verb is one of: get, list, watch, create, update, delete	true	string	
resourceAPIGroup	Group is the API group of the resource Serialized as resourceAPIGroup to avoid confusion with the 'groups' field when inlined	true	string	
resourceAPIVersion	Version is the API version of the resource Serialized as resourceAPIVersion to avoid confusion with TypeMeta.apiVersion and ObjectMeta.resourceVersion when inlined	true	string	
resource	Resource is one of the existing resource types	true	string	
resourceName	ResourceName is the name of the resource being requested for a "get" or deleted for a "delete"	true	string	

Name	Description	Required	Schema	Default
path	Path is the path of a non resource URL	true	string	
isNonResourceURL	IsNonResourceURL is true if this is a request for a non-resource URL (outside of the resource hierarchy)	true	boolean	
content	Content is the actual content of the request for create and update	false	string	

2.3.154. v1.LocalSubjectAccessReview

LocalSubjectAccessReview is an object for requesting information about whether a user or group can perform an action in a particular namespace

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#types-kinds	false	string	

Name	Description	Required	Schema	Default
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#resources	false	string	
namespace	Namespace is the namespace of the action being requested. Currently, there is no distinction between no namespace and all namespaces	true	string	
verb	Verb is one of: get, list, watch, create, update, delete	true	string	
resourceAPIGroup	Group is the API group of the resource Serialized as resourceAPIGroup to avoid confusion with the 'groups' field when inlined	true	string	

Name	Description	Required	Schema	Default
resourceAPIVersion	Version is the API version of the resource Serialized as resourceAPIVersion to avoid confusion with TypeMeta.apiVersion and ObjectMeta.resourceVersion when inlined	true	string	
resource	Resource is one of the existing resource types	true	string	
resourceName	ResourceName is the name of the resource being requested for a "get" or deleted for a "delete"	true	string	
path	Path is the path of a non resource URL	true	string	
isNonResourceURL	IsNonResourceURL is true if this is a request for a non-resource URL (outside of the resource hierarchy)	true	boolean	
content	Content is the actual content of the request for create and update	false	string	
user	User is optional. If both User and Groups are empty, the current authenticated user is used.	true	string	

Name	Description	Required	Schema	Default
groups	Groups is optional. Groups is the list of groups to which the User belongs.	true	string array	
scopes	Scopes to use for the evaluation. Empty means "use the unscoped (full) permissions of the user/groups". Nil for a self-SAR, means "use the scopes on this request". Nil for a regular SAR, means the same as empty.	true	string array	

2.3.155. v1.NFSVolumeSource

Represents an NFS mount that lasts the lifetime of a pod. NFS volumes do not support ownership management or SELinux relabeling.

Name	Description	Required	Schema	Default
server	Server is the hostname or IP address of the NFS server. More info: http://kubernetes.io/docs/user-guide/volumes#nfs	true	string	
path	Path that is exported by the NFS server. More info: http://kubernetes.io/docs/user-guide/volumes#nfs	true	string	

Name	Description	Required	Schema	Default
readOnly	ReadOnly here will force the NFS export to be mounted with read-only permissions. Defaults to false. More info: http://kubernetes.io/docs/user-guide/volumes#nfs	false	boolean	

2.3.156. v1.NamedClusterRole

NamedClusterRole relates a name with a cluster role

Name	Description	Required	Schema	Default
name	Name is the name of the cluster role	true	string	
role	Role is the cluster role being named	true	Section 2.3.48, "v1.ClusterRole"	

2.3.157. v1.NamedClusterRoleBinding

NamedClusterRoleBinding relates a name with a cluster role binding

Name	Description	Required	Schema	Default
name	Name is the name of the cluster role binding	true	string	
roleBinding	RoleBinding is the cluster role binding being named	true	Section 2.3.49, "v1.ClusterRoleBinding"	

2.3.158. v1.NamedRole

NamedRole relates a Role with a name

Name	Description	Required	Schema	Default
name	Name is the name of the role	true	string	
role	Role is the role being named	true	Section 2.3.224, "v1.Role"	

2.3.159. v1.NamedRoleBinding

NamedRoleBinding relates a role binding with a name

Name	Description	Required	Schema	Default
name	Name is the name of the role binding	true	string	
roleBinding	RoleBinding is the role binding being named	true	Section 2.3.225, "v1.RoleBinding"	

2.3.160. v1.NamedTagEventList

NamedTagEventList relates a tag to its image history.

Name	Description	Required	Schema	Default
tag	Tag is the tag for which the history is recorded	true	string	
items	Standard object's metadata.	true	Section 2.3.274, "v1.TagEvent" array	
conditions	Conditions is an array of conditions that apply to the tag event list.	false	Section 2.3.275, "v1.TagEventCondition" array	

2.3.161. v1.NetNamespace

NetNamespace describes a single isolated network. When using the redhat/openshift-ovs-multitenant plugin, every Namespace will have a corresponding NetNamespace object with the same name. (When using redhat/openshift-ovs-subnet, NetNamespaces are not used.)

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#types-kinds	false	string	
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#resources	false	string	
metadata	Standard object's metadata.	false	Section 2.3.176, "v1.ObjectMeta"	

Name	Description	Required	Schema	Default
netname	NetName is the name of the network namespace. (This is the same as the object's name, but both fields must be set.)	true	string	
netid	NetID is the network identifier of the network namespace assigned to each overlay network packet. This can be manipulated with the "oc adm pod-network" commands.	true	integer	

2.3.162. v1.NetNamespaceList

NetNamespaceList is a collection of NetNamespaces

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#types-kinds	false	string	

Name	Description	Required	Schema	Default
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#resources	false	string	
metadata	Standard object's metadata.	false	Section 2.3.151, "v1.ListMeta"	
items	Items is the list of net namespaces	true	Section 2.3.161, "v1.NetNamespace" array	

2.3.163. v1.NodeAffinity

Node affinity is a group of node affinity scheduling rules.

Name	Description	Required	Schema	Default
------	-------------	----------	--------	---------

Name	Description	Required	Schema	Default
<code>requiredDuringSchedulingIgnoredDuringExecution</code>	If the affinity requirements specified by this field are not met at scheduling time, the pod will not be scheduled onto the node. If the affinity requirements specified by this field cease to be met at some point during pod execution (e.g. due to an update), the system may or may not try to eventually evict the pod from its node.	false	Section 2.3.164, "v1.NodeSelector"	

Name	Description	Required	Schema	Default
preferredDuringSchedulingIgnoredDuringExecution	The scheduler will prefer to schedule pods to nodes that satisfy the affinity expressions specified by this field, but it may choose a node that violates one or more of the expressions. The node that is most preferred is the one with the greatest sum of weights, i.e. for each node that meets all of the scheduling requirements (resource request, requiredDuringScheduling affinity expressions, etc.), compute a sum by iterating through the elements of this field and adding "weight" to the sum if the node matches the corresponding matchExpressions; the node(s) with the highest sum are the most preferred.	false	Section 2.3.204, "v1.PreferredSchedulingTerm" array	

2.3.164. v1.NodeSelector

A node selector represents the union of the results of one or more label queries over a set of nodes; that is, it represents the OR of the selectors represented by the node selector terms.

Name	Description	Required	Schema	Default
nodeSelectorTerms	Required. A list of node selector terms. The terms are ORed.	true	Section 2.3.166 , "v1.NodeSelectorTerm" array	

2.3.165. v1.NodeSelectorRequirement

A node selector requirement is a selector that contains values, a key, and an operator that relates the key and values.

Name	Description	Required	Schema	Default
key	The label key that the selector applies to.	true	string	
operator	Represents a key's relationship to a set of values. Valid operators are In, NotIn, Exists, DoesNotExist, Gt, and Lt.	true	string	

Name	Description	Required	Schema	Default
values	An array of string values. If the operator is In or NotIn, the values array must be non-empty. If the operator is Exists or DoesNotExist, the values array must be empty. If the operator is Gt or Lt, the values array must have a single element, which will be interpreted as an integer. This array is replaced during a strategic merge patch.	false	string array	

2.3.166. v1.NodeSelectorTerm

A null or empty node selector term matches no objects.

Name	Description	Required	Schema	Default
matchExpressions	Required. A list of node selector requirements. The requirements are ANDed.	true	Section 2.3.165, "v1.NodeSelectorRequirement" array	

2.3.167. v1.OAuthAccessToken

OAuthAccessToken describes an OAuth access token

Name	Description	Required	Schema	Default
------	-------------	----------	--------	---------

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/HEAD/docs/dev/api-conventions.md#types-kinds	false	string	
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/HEAD/docs/dev/api-conventions.md#resources	false	string	
metadata	Standard object's metadata.	false	Section 2.3.176, "v1.ObjectMeta"	

Name	Description	Required	Schema	Default
clientName	ClientName references the client that created this token.	false	string	
expiresIn	ExpiresIn is the seconds from CreationTime before this token expires.	false	integer (int64)	
scopes	Scopes is an array of the requested scopes.	false	string array	
redirectURI	RedirectURI is the redirection associated with the token.	false	string	
userName	UserName is the user name associated with this token	false	string	
userID	UserUID is the unique UID associated with this token	false	string	
authorizeToken	AuthorizeToken contains the token that authorized this token	false	string	
refreshToken	RefreshToken is the value by which this token can be renewed. Can be blank.	false	string	

2.3.168. v1.OAuthAccessTokenList

OAuthAccessTokenList is a collection of OAuth access tokens

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#types-kinds	false	string	
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#resources	false	string	
metadata	Standard object's metadata.	false	Section 2.3.151, "v1.ListMeta"	
items	Items is the list of OAuth access tokens	true	Section 2.3.167, "v1.OAuthAccessToken" array	

2.3.169. v1.OAuthAuthorizeToken

OAuthAuthorizeToken describes an OAuth authorization token

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/HEAD/docs/dev/api-conventions.md#types-kinds	false	string	
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/HEAD/docs/dev/api-conventions.md#resources	false	string	
metadata	Standard object's metadata.	false	Section 2.3.176, "v1.ObjectMeta"	

Name	Description	Required	Schema	Default
clientName	ClientName references the client that created this token.	false	string	
expiresIn	ExpiresIn is the seconds from CreationTime before this token expires.	false	integer (int64)	
scopes	Scopes is an array of the requested scopes.	false	string array	
redirectURI	RedirectURI is the redirection associated with the token.	false	string	
state	State data from request	false	string	
userName	UserName is the user name associated with this token	false	string	
userID	UserUID is the unique UID associated with this token. UserUID and UserName must both match for this token to be valid.	false	string	

Name	Description	Required	Schema	Default
codeChallenge	CodeChallenge is the optional code_challenge associated with this authorization code, as described in rfc7636	false	string	
codeChallengeMethod	CodeChallengeMethod is the optional code_challenge_method associated with this authorization code, as described in rfc7636	false	string	

2.3.170. v1.OAuthAuthorizeTokenList

OAuthAuthorizeTokenList is a collection of OAuth authorization tokens

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#types-kinds	false	string	

Name	Description	Required	Schema	Default
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#resources	false	string	
metadata	Standard object's metadata.	false	Section 2.3.151, "v1.ListMeta"	
items	Items is the list of OAuth authorization tokens	true	Section 2.3.169, "v1.OAuthAuthorizeToken" array	

2.3.171. v1.OAuthClient

OAuthClient describes an OAuth client

Name	Description	Required	Schema	Default
------	-------------	----------	--------	---------

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/HEAD/docs/dev/api-conventions.md#types-kinds	false	string	
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/HEAD/docs/dev/api-conventions.md#resources	false	string	
metadata	Standard object's metadata.	false	Section 2.3.176, "v1.ObjectMeta"	
secret	Secret is the unique secret associated with a client	false	string	

Name	Description	Required	Schema	Default
additionalSecrets	AdditionalSecrets holds other secrets that may be used to identify the client. This is useful for rotation and for service account token validation	false	string array	
respondWithChallenges	RespondWithChallenges indicates whether the client wants authentication needed responses made in the form of challenges instead of redirects	false	boolean	
redirectURIs	RedirectURIs is the valid redirection URIs associated with a client	false	string array	

Name	Description	Required	Schema	Default
grantMethod	GrantMethod determines how to handle grants for this client. If no method is provided, the cluster default grant handling method will be used. Valid grant handling methods are: <ul style="list-style-type: none"> - auto: always approves grant requests, useful for trusted clients - prompt: prompts the end user for approval of grant requests, useful for third-party clients - deny: always denies grant requests, useful for black-listed clients 	false	string	
scopeRestrictions	ScopeRestrictions describes which scopes this client can request. Each requested scope is checked against each restriction. If any restriction matches, then the scope is allowed. If no restriction matches, then the scope is denied.	false	Section 2.3.242, "v1.ScopeRestriction" array	

2.3.172. v1.OAuthClientAuthorization

OAuthClientAuthorization describes an authorization created by an OAuth client

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#types-kinds	false	string	
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#resources	false	string	
metadata	Standard object's metadata.	false	Section 2.3.176, "v1.ObjectMeta"	

Name	Description	Required	Schema	Default
clientName	ClientName references the client that created this authorization	false	string	
userName	UserName is the user name that authorized this client	false	string	
userID	UserUID is the unique UID associated with this authorization. UserUID and UserName must both match for this authorization to be valid.	false	string	
scopes	Scopes is an array of the granted scopes.	false	string array	

2.3.173. v1.OAuthClientAuthorizationList

OAuthClientAuthorizationList is a collection of OAuth client authorizations

Name	Description	Required	Schema	Default
------	-------------	----------	--------	---------

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#types-kinds	false	string	
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#resources	false	string	
metadata	Standard object's metadata.	false	Section 2.3.151, "v1.ListMeta"	
items	Items is the list of OAuth client authorizations	true	Section 2.3.172, "v1.OAuthClientAuthorization" array	

2.3.174. v1.OAuthClientList

OAuthClientList is a collection of OAuth clients

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/HEAD/docs/dev/api-conventions.md#types-kinds	false	string	
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/HEAD/docs/dev/api-conventions.md#resources	false	string	
metadata	Standard object's metadata.	false	Section 2.3.151, "v1.ListMeta"	

Name	Description	Required	Schema	Default
items	Items is the list of OAuth clients	true	Section 2.3.171 , "v1.OAuthClient" array	

2.3.175. v1.ObjectFieldSelector

ObjectFieldSelector selects an APIVersioned field of an object.

Name	Description	Required	Schema	Default
apiVersion	Version of the schema the FieldPath is written in terms of, defaults to "v1".	false	string	
fieldPath	Path of the field to select in the specified API version.	true	string	

2.3.176. v1.ObjectMeta

ObjectMeta is metadata that all persisted resources must have, which includes all objects users must create.

Name	Description	Required	Schema	Default
------	-------------	----------	--------	---------

Name	Description	Required	Schema	Default
name	<p>Name must be unique within a namespace. Is required when creating resources, although some resources may allow a client to request the generation of an appropriate name automatically. Name is primarily intended for creation idempotence and configuration definition. Cannot be updated. More info: http://kubernetes.io/docs/user-guide/identifiers#names</p>	false	string	
generateName	<p>GenerateName is an optional prefix, used by the server, to generate a unique name ONLY IF the Name field has not been provided. If this field is used, the name returned to the client will be different than the name passed. This value will also be combined with a unique suffix. The provided value has the same</p>	false	string	

Name	Description	Required	Schema	Default
	<p>validation rules as the name field, and may be truncated by the length of the suffix required to make the value unique on the server.</p> <p>If this field is specified and the generated name exists, the server will NOT return a 409 - instead, it will either return 201 Created or 500 with Reason ServerTimeout indicating a unique name could not be found in the time allotted, and the client should retry (optionally after the time indicated in the Retry-After header).</p> <p>Applied only if Name is not specified. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#idempotency</p>			

Name	Description	Required	Schema	Default
namespace	<p>Namespace defines the space within each name must be unique. An empty namespace is equivalent to the "default" namespace, but "default" is the canonical representation. Not all objects are required to be scoped to a namespace - the value of this field for those objects will be empty.</p> <p>Must be a DNS_LABEL. Cannot be updated. More info: http://kubernetes.io/docs/user-guide/namespaces</p>	false	string	
selfLink	<p>SelfLink is a URL representing this object. Populated by the system. Read-only.</p>	false	string	

Name	Description	Required	Schema	Default
uid	<p>UID is the unique in time and space value for this object. It is typically generated by the server on successful creation of a resource and is not allowed to change on PUT operations.</p> <p>Populated by the system. Read-only. More info: http://kubernetes.io/docs/user-guide/identifiers#uids</p>	false	string	

Name	Description	Required	Schema	Default
resourceVersion	<p>An opaque value that represents the internal version of this object that can be used by clients to determine when objects have changed. May be used for optimistic concurrency, change detection, and the watch operation on a resource or set of resources. Clients must treat these values as opaque and passed unmodified back to the server. They may only be valid for a particular resource or set of resources.</p> <p>Populated by the system. Read-only. Value must be treated as opaque by clients and . More info: http://releases.k8s.io/HEAD/docs/dev/api-conventions.md#concurrency-control-and-consistency</p>	false	string	

Name	Description	Required	Schema	Default
generation	A sequence number representing a specific generation of the desired state. Populated by the system. Read-only.	false	integer (int64)	
creationTimestamp	CreationTimestamp is a timestamp representing the server time when this object was created. It is not guaranteed to be set in happens-before order across separate operations. Clients may not set this value. It is represented in RFC3339 form and is in UTC. Populated by the system. Read-only. Null for lists. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#metadata	false	string	
deletionTimestamp	DeletionTimestamp is RFC 3339 date and time at which this resource will be deleted. This field is set by the server when a graceful deletion is requested by the user, and is not directly	false	string	

Name	Description	Required	Schema	Default
	<p>resource is expected to be deleted (no longer visible from resource lists, and not reachable by name) after the time in this field. Once set, this value may not be unset or be set further into the future, although it may be shortened or the resource may be deleted prior to this time. For example, a user may request that a pod is deleted in 30 seconds. The Kubelet will react by sending a graceful termination signal to the containers in the pod. After that 30 seconds, the Kubelet will send a hard termination signal (SIGKILL) to the container and after cleanup, remove the pod from the API. In the presence of network partitions, this object may still exist after this timestamp, until an administrator or automated process can determine the resource is fully terminated. If</p>			

Name	Description	Required	Schema	Default
	<p>not set, graceful deletion of the object has not been requested.</p> <p>Populated by the system when a graceful deletion is requested. Read-only. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#metadata</p>			
deletionGracePeriodSeconds	<p>Number of seconds allowed for this object to gracefully terminate before it will be removed from the system. Only set when deletionTimestamp is also set. May only be shortened. Read-only.</p>	false	integer (int64)	
labels	<p>Map of string keys and values that can be used to organize and categorize (scope and select) objects. May match selectors of replication controllers and services. More info: http://kubernetes.io/docs/user-guide/labels</p>	false	object	

Name	Description	Required	Schema	Default
annotations	<p>Annotations is an unstructured key value map stored with a resource that may be set by external tools to store and retrieve arbitrary metadata. They are not queryable and should be preserved when modifying objects. More info: http://kubernetes.io/docs/user-guide/annotations</p>	false	object	
ownerReferences	<p>List of objects depended by this object. If ALL objects in the list have been deleted, this object will be garbage collected. If this object is managed by a controller, then an entry in this list will point to this controller, with the controller field set to true. There cannot be more than one managing controller.</p>	false	Section 2.3.178, "v1.OwnerReference" array	

Name	Description	Required	Schema	Default
finalizers	Must be empty before the object is deleted from the registry. Each entry is an identifier for the responsible component that will remove the entry from the list. If the deletionTimestamp of the object is non-nil, entries in this list can only be removed.	false	string array	
clusterName	The name of the cluster which the object belongs to. This is used to distinguish resources with same name and namespace in different clusters. This field is not set anywhere right now and apiserver is going to ignore it if set in create or update request.	false	string	

2.3.177. v1.ObjectReference

ObjectReference contains enough information to let you inspect or modify the referred object.

Name	Description	Required	Schema	Default
------	-------------	----------	--------	---------

Name	Description	Required	Schema	Default
kind	Kind of the referent. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#types-kinds	false	string	
namespace	Namespace of the referent. More info: http://kubernetes.io/docs/user-guide/namespaces	false	string	
name	Name of the referent. More info: http://kubernetes.io/docs/user-guide/identifiers#names	false	string	
uid	UID of the referent. More info: http://kubernetes.io/docs/user-guide/identifiers#uids	false	string	
apiVersion	API version of the referent.	false	string	
resourceVersion	Specific resourceVersion to which this reference is made, if any. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#concurrency-control-and-consistency	false	string	

Name	Description	Required	Schema	Default
fieldPath	If referring to a piece of an object instead of an entire object, this string should contain a valid JSON/Go field access statement, such as <code>desiredState.manifest.containers[2]</code> . For example, if the object reference is to a container within a pod, this would take on a value like: <code>"spec.containers{name}"</code> (where "name" refers to the name of the container that triggered the event) or if no container name is specified <code>"spec.containers[2]"</code> (container with index 2 in this pod). This syntax is chosen only to have some well-defined way of referencing a part of an object.	false	string	

2.3.178. v1.OwnerReference

OwnerReference contains enough information to let you identify an owning object. Currently, an owning object must be in the same namespace, so there is no namespace field.

Name	Description	Required	Schema	Default
apiVersion	API version of the referent.	true	string	

Name	Description	Required	Schema	Default
kind	Kind of the referent. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#types-kinds	true	string	
name	Name of the referent. More info: http://kubernetes.io/docs/user-guide/identifiers#names	true	string	
uid	UID of the referent. More info: http://kubernetes.io/docs/user-guide/identifiers#uids	true	string	
controller	If true, this reference points to the managing controller.	false	boolean	

Name	Description	Required	Schema	Default
blockOwnerDeletion	If true, AND if the owner has the "foregroundDeletion" finalizer, then the owner cannot be deleted from the key-value store until this reference is removed. Defaults to false. To set this field, a user needs "delete" permission of the owner, otherwise 422 (Unprocessable Entity) will be returned.	false	boolean	

2.3.179. v1.Parameter

Parameter defines a name/value variable that is to be processed during the Template to Config transformation.

Name	Description	Required	Schema	Default
name	Name must be set and it can be referenced in Template Items using <code>\${PARAMETER_NAME}</code> . Required.	true	string	
displayName	Optional: The name that will show in UI instead of parameter 'Name'	false	string	
description	Description of a parameter. Optional.	false	string	

Name	Description	Required	Schema	Default
value	Value holds the Parameter data. If specified, the generator will be ignored. The value replaces all occurrences of the Parameter <code>\${Name}</code> expression during the Template to Config transformation. Optional.	false	string	

Name	Description	Required	Schema	Default
generate	<p>generate specifies the generator to be used to generate random string from an input value specified by From field. The result string is stored into Value field. If empty, no generator is being used, leaving the result Value untouched. Optional.</p> <p>The only supported generator is "expression", which accepts a "from" value in the form of a simple regular expression containing the range expression "[a-zA-Z0-9]", and the length expression "a{length}".</p> <p>Examples:</p> <p>from</p>	value	false	string
	from	From is an input value for the generator. Optional.	false	string
	required	Optional: Indicates the parameter must have a value. Defaults to false.	false	boolean

2.3.180. v1.Patch

Patch is provided to give a concrete name and type to the Kubernetes PATCH request body.

2.3.181. v1.PersistentVolumeClaimVolumeSource

PersistentVolumeClaimVolumeSource references the user's PVC in the same namespace. This volume finds the bound PV and mounts that volume for the pod. A PersistentVolumeClaimVolumeSource is, essentially, a wrapper around another type of volume that is owned by someone else (the system).

Name	Description	Required	Schema	Default
claimName	ClaimName is the name of a PersistentVolumeClaim in the same namespace as the pod using this volume. More info: http://kubernetes.io/docs/user-guide/persistent-volumes#persistentvolumeclaims	true	string	
readOnly	Will force the ReadOnly setting in VolumeMounts. Default false.	false	boolean	

2.3.182. v1.PhotonPersistentDiskVolumeSource

Represents a Photon Controller persistent disk resource.

Name	Description	Required	Schema	Default
pdID	ID that identifies Photon Controller persistent disk	true	string	

Name	Description	Required	Schema	Default
fsType	Filesystem type to mount. Must be a filesystem type supported by the host operating system. Ex. "ext4", "xfs", "ntfs". Implicitly inferred to be "ext4" if unspecified.	false	string	

2.3.183. v1.PodAffinity

Pod affinity is a group of inter pod affinity scheduling rules.

Name	Description	Required	Schema	Default
requiredDuringSchedulingIgnoredDuringExecution	NOT YET IMPLEMENTED. TODO: Uncomment field once it is implemented. If the affinity requirements specified by this field are not met at scheduling time, the pod will not be scheduled onto the node. If the affinity requirements specified by this field cease to be met at some point during pod execution (e.g. due to a pod label update), the system will try to eventually evict the pod from its node. When there are multiple elements, the lists of nodes	false	Section 2.3.184, "v1.PodAffinityTerm" array	

Name	Description	Required	Schema	Default
	<p>corresponding to each podAffinityTerm are intersected, i.e. all terms must be satisfied.</p> <p>RequiredDuringSchedulingRequiredDuringExecution</p> <p>[]PodAffinityTerm</p> <p>json:"requiredDuringSchedulingRequiredDuringExecution,omitEmpty" If the affinity requirements specified by this field are not met at scheduling time, the pod will not be scheduled onto the node. If the affinity requirements specified by this field cease to be met at some point during pod execution (e.g. due to a pod label update), the system may or may not try to eventually evict the pod from its node. When there are multiple elements, the lists of nodes corresponding to each podAffinityTerm are intersected, i.e. all terms must be satisfied.</p>			

Name	Description	Required	Schema	Default
preferredDuringSchedulingIgnoredDuringExecution	The scheduler will prefer to schedule pods to nodes that satisfy the affinity expressions specified by this field, but it may choose a node that violates one or more of the expressions. The node that is most preferred is the one with the greatest sum of weights, i.e. for each node that meets all of the scheduling requirements (resource request, requiredDuringScheduling affinity expressions, etc.), compute a sum by iterating through the elements of this field and adding "weight" to the sum if the node has pods which matches the corresponding podAffinityTerm; the node(s) with the highest sum are the most preferred.	false	Section 2.3.293, "v1.WeightedPodAffinityTerm" array	

2.3.184. v1.PodAffinityTerm

Defines a set of pods (namely those matching the labelSelector relative to the given namespace(s)) that this pod should be co-located (affinity) or not co-located (anti-affinity) with, where co-located is defined as running on a node whose value of the label with key <topologyKey> tches that of any node on which a pod of the set of pods is running

Name	Description	Required	Schema	Default
labelSelector	A label query over a set of resources, in this case pods.	false	Section 2.3.147, "v1.LabelSelector"	
namespaces	namespaces specifies which namespaces the labelSelector applies to (matches against); null or empty list means "this pod's namespace"	false	string array	

Name	Description	Required	Schema	Default
topologyKey	<p>This pod should be co-located (affinity) or not co-located (anti-affinity) with the pods matching the labelSelector in the specified namespaces, where co-located is defined as running on a node whose value of the label with key topologyKey matches that of any node on which any of the selected pods is running. For PreferredDuringScheduling pod anti-affinity, empty topologyKey is interpreted as "all topologies" ("all topologies" here means all the topologyKeys indicated by scheduler command-line argument --failure-domains); for affinity and for RequiredDuringScheduling pod anti-affinity, empty topologyKey is not allowed.</p>	false	string	

2.3.185. v1.PodAntiAffinity

Pod anti affinity is a group of inter pod anti affinity scheduling rules.

Name	Description	Required	Schema	Default
requiredDuringSchedulingIgnoredDuringExecution	<p>NOT YET IMPLEMENTED. TODO: Uncomment field once it is implemented. If the anti-affinity requirements specified by this field are not met at scheduling time, the pod will not be scheduled onto the node. If the anti-affinity requirements specified by this field cease to be met at some point during pod execution (e.g. due to a pod label update), the system will try to eventually evict the pod from its node. When there are multiple elements, the lists of nodes corresponding to each podAffinityTerm are intersected, i.e. all terms must be satisfied.</p> <p>RequiredDuringSchedulingRequiredDuringExecution</p> <p>[]PodAffinityTerm</p> <p>json:"requiredDuringSchedulingRequiredDuringExecution,omitEmpty" If the anti-affinity requirements</p>	false	Section 2.3.184, "v1.PodAffinityTerm" array	

Name	Description	Required	Schema	Default
	<p>specified by this field are not met at scheduling time, the pod will not be scheduled onto the node. If the anti-affinity requirements specified by this field cease to be met at some point during pod execution (e.g. due to a pod label update), the system may or may not try to eventually evict the pod from its node. When there are multiple elements, the lists of nodes corresponding to each podAffinityTerm are intersected, i.e. all terms must be satisfied.</p>			

Name	Description	Required	Schema	Default
preferredDuringSchedulingIgnoredDuringExecution	The scheduler will prefer to schedule pods to nodes that satisfy the anti-affinity expressions specified by this field, but it may choose a node that violates one or more of the expressions. The node that is most preferred is the one with the greatest sum of weights, i.e. for each node that meets all of the scheduling requirements (resource request, requiredDuringScheduling anti-affinity expressions, etc.), compute a sum by iterating through the elements of this field and adding "weight" to the sum if the node has pods which matches the corresponding podAffinityTerm; the node(s) with the highest sum are the most preferred.	false	Section 2.3.293 , "v1.WeightedPodAffinityTerm" array	

2.3.186. v1.PodSecurityContext

PodSecurityContext holds pod-level security attributes and common container settings. Some fields are also present in container.securityContext. Field values of container.securityContext take precedence over field values of PodSecurityContext.

Name	Description	Required	Schema	Default
seLinuxOptions	The SELinux context to be applied to all containers. If unspecified, the container runtime will allocate a random SELinux context for each container. May also be set in SecurityContext. If set in both SecurityContext and PodSecurityContext, the value specified in SecurityContext takes precedence for that container.	false	Section 2.3.240, "v1.SELinuxOptions"	
runAsUser	The UID to run the entrypoint of the container process. Defaults to user specified in image metadata if unspecified. May also be set in SecurityContext. If set in both SecurityContext and PodSecurityContext, the value specified in SecurityContext takes precedence for that container.	false	integer (int64)	

Name	Description	Required	Schema	Default
runAsNonRoot	Indicates that the container must run as a non-root user. If true, the Kubelet will validate the image at runtime to ensure that it does not run as UID 0 (root) and fail to start the container if it does. If unset or false, no such validation will be performed. May also be set in SecurityContext. If set in both SecurityContext and PodSecurityContext, the value specified in SecurityContext takes precedence.	false	boolean	
supplementalGroups	A list of groups applied to the first process run in each container, in addition to the container's primary GID. If unspecified, no groups will be added to any container.	false	integer array	

Name	Description	Required	Schema	Default
fsGroup	<p>A special supplemental group that applies to all containers in a pod. Some volume types allow the Kubelet to change the ownership of that volume to be owned by the pod:</p> <ol style="list-style-type: none"> 1. The owning GID will be the FSGroup 2. The setgid bit is set (new files created in the volume will be owned by FSGroup) 3. The permission bits are OR'd with rw-rw 	false	integer (int64)	

2.3.187. v1.PodSecurityPolicyReview

PodSecurityPolicyReview checks which service accounts (not users, since that would be cluster-wide) can create the **PodTemplateSpec** in question.

Name	Description	Required	Schema	Default
------	-------------	----------	--------	---------

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#types-kinds	false	string	
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#resources	false	string	
spec	spec is the PodSecurityPolicy to check.	true	Section 2.3.188, "v1.PodSecurityPolicyReviewSpec"	

Name	Description	Required	Schema	Default
status	status represents the current information/status for the PodSecurityPolicyReview.	false	Section 2.3.189, "v1.PodSecurityPolicyReviewStatus"	

2.3.188. v1.PodSecurityPolicyReviewSpec

PodSecurityPolicyReviewSpec defines specification for PodSecurityPolicyReview

Name	Description	Required	Schema	Default
template	template is the PodTemplateSpec to check. The template.spec.serviceAccountName field is used if serviceAccountNames is empty, unless the template.spec.serviceAccountName is empty, in which case "default" is used. If serviceAccountNames is specified, template.spec.serviceAccountName is ignored.	true	Section 2.3.196, "v1.PodTemplateSpec"	

Name	Description	Required	Schema	Default
serviceAccountNames	serviceAccountNames is an optional set of ServiceAccounts to run the check with. If serviceAccountNames is empty, the template.spec.serviceAccountName is used, unless it's empty, in which case "default" is used instead. If serviceAccountNames is specified, template.spec.serviceAccountName is ignored.	false	string array	

2.3.189. v1.PodSecurityPolicyReviewStatus

PodSecurityPolicyReviewStatus represents the status of PodSecurityPolicyReview.

Name	Description	Required	Schema	Default
allowedServiceAccounts	allowedServiceAccounts returns the list of service accounts in this namespace that have the power to create the PodTemplateSpec.	true	Section 2.3.254, "v1.ServiceAccountPodSecurityPolicyReviewStatus" array	

2.3.190. v1.PodSecurityPolicySelfSubjectReview

PodSecurityPolicySelfSubjectReview checks whether this user/SA tuple can create the PodTemplateSpec

Name	Description	Required	Schema	Default
------	-------------	----------	--------	---------

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#types-kinds	false	string	
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#resources	false	string	
spec	spec defines specification the PodSecurityPolicySelfSubjectReview.	true	Section 2.3.191, "v1.PodSecurityPolicySelfSubjectReviewSpec"	

Name	Description	Required	Schema	Default
status	status represents the current information/status for the PodSecurityPolicySelfSubjectReview.	false	Section 2.3.194, "v1.PodSecurityPolicySubjectReviewStatus"	

2.3.191. v1.PodSecurityPolicySelfSubjectReviewSpec

PodSecurityPolicySelfSubjectReviewSpec contains specification for PodSecurityPolicySelfSubjectReview.

Name	Description	Required	Schema	Default
template	template is the PodTemplateSpec to check.	true	Section 2.3.196, "v1.PodTemplateSpec"	

2.3.192. v1.PodSecurityPolicySubjectReview

PodSecurityPolicySubjectReview checks whether a particular user/SA tuple can create the PodTemplateSpec.

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#types-kinds	false	string	

Name	Description	Required	Schema	Default
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/HEAD/docs/dev/api-conventions.md#resources	false	string	
spec	spec defines specification for the PodSecurityPolicySubjectReview.	true	Section 2.3.193, "v1.PodSecurityPolicySubjectReviewSpec"	
status	status represents the current information/status for the PodSecurityPolicySubjectReview.	false	Section 2.3.194, "v1.PodSecurityPolicySubjectReviewStatus"	

2.3.193. v1.PodSecurityPolicySubjectReviewSpec

PodSecurityPolicySubjectReviewSpec defines specification for PodSecurityPolicySubjectReview

Name	Description	Required	Schema	Default
------	-------------	----------	--------	---------

Name	Description	Required	Schema	Default
template	template is the PodTemplateSpec to check. If template.spec.serviceAccountName is empty it will not be defaulted. If its non-empty, it will be checked.	true	Section 2.3.196, "v1.PodTemplateSpec"	
user	user is the user you're testing for. If you specify "user" but not "group", then is it interpreted as "What if user were not a member of any groups. If user and groups are empty, then the check is performed using only the serviceAccountName in the template.	false	string	
groups	groups is the groups you're testing for.	false	string array	

2.3.194. v1.PodSecurityPolicySubjectReviewStatus

PodSecurityPolicySubjectReviewStatus contains information/status for PodSecurityPolicySubjectReview.

Name	Description	Required	Schema	Default
------	-------------	----------	--------	---------

Name	Description	Required	Schema	Default
allowedBy	allowedBy is a reference to the rule that allows the PodTemplateSpec. A rule can be a SecurityContextConstraint or a PodSecurityPolicy. A nil , indicates that it was denied.	false	Section 2.3.177, "v1.ObjectReference"	
reason	A machine-readable description of why this operation is in the "Failure" status. If this value is empty there is no information available.	false	string	
template	template is the PodTemplateSpec after the defaulting is applied.	false	Section 2.3.196, "v1.PodTemplateSpec"	

2.3.195. v1.PodSpec

PodSpec is a description of a pod.

Name	Description	Required	Schema	Default
volumes	List of volumes that can be mounted by containers belonging to the pod. More info: http://kubernetes.io/docs/user-guide/volumes	false	Section 2.3.287, "v1.Volume" array	
initContainers	List of initialization	false		

Name	Description	Required	Schema	Default
	<p>containers belonging to the pod. Init containers are executed in order prior to containers being started. If any init container fails, the pod is considered to have failed and is handled according to its restartPolicy. The name for an init container or normal container must be unique among all containers. Init containers may not have Lifecycle actions, Readiness probes, or Liveness probes. The resourceRequirements of an init container are taken into account during scheduling by finding the highest request/limit for each resource type, and then using the max of that value or the sum of the normal containers. Limits are applied to init containers in a similar fashion. Init containers cannot currently be added or removed. Cannot be updated. More info:</p>		<p>Section 2.3.57, v1.Container array</p>	

Name	Description	Required	Schema	Default
	http://kubernetes.io/docs/user-guide/containers			

Name	Description	Required	Schema	Default
containers	List of containers belonging to the pod. Containers cannot currently be added or removed. There must be at least one container in a Pod. Cannot be updated. More info: http://kubernetes.io/docs/user-guide/containers	true	Section 2.3.57, "v1.Container" array	
restartPolicy	Restart policy for all containers within the pod. One of Always, OnFailure, Never. Default to Always. More info: http://kubernetes.io/docs/user-guide/pod-states#restartpolicy	false	string	

Name	Description	Required	Schema	Default
terminationGracePeriodSeconds	Optional duration in seconds the pod needs to terminate gracefully. May be decreased in delete request. Value must be non-negative integer. The value zero indicates delete immediately. If this value is nil, the default grace period will be used instead. The grace period is the duration in seconds after the processes running in the pod are sent a termination signal and the time when the processes are forcibly halted with a kill signal. Set this value longer than the expected cleanup time for your process. Defaults to 30 seconds.	false	integer (int64)	

Name	Description	Required	Schema	Default
activeDeadlineSeconds	Optional duration in seconds the pod may be active on the node relative to StartTime before the system will actively try to mark it failed and kill associated containers. Value must be a positive integer.	false	integer (int64)	
dnsPolicy	Set DNS policy for containers within the pod. One of 'ClusterFirstWithHostNet', 'ClusterFirst' or 'Default'. Defaults to "ClusterFirst". To have DNS options set along with hostNetwork, you have to specify DNS policy explicitly to 'ClusterFirstWithHostNet'.	false	string	

Name	Description	Required	Schema	Default
nodeSelector	NodeSelector is a selector which must be true for the pod to fit on a node. Selector which must match a node's labels for the pod to be scheduled on that node. More info: http://kubernetes.io/docs/user-guide/node-selection/README	false	object	
serviceAccountName	ServiceAccountName is the name of the ServiceAccount to use to run this pod. More info: http://releases.k8s.io/HEAD/docs/design/service_accounts.md	false	string	
serviceAccount	DeprecatedServiceAccount is a deprecated alias for ServiceAccountName. Deprecated: Use serviceAccountName instead.	false	string	
automountServiceAccountToken	AutomountServiceAccountToken indicates whether a service account token should be automatically mounted.	false	boolean	

Name	Description	Required	Schema	Default
nodeName	nodeName is a request to schedule this pod onto a specific node. If it is non-empty, the scheduler simply schedules this pod onto that node, assuming that it fits resource requirements.	false	string	
hostNetwork	Host networking requested for this pod. Use the host's network namespace. If this option is set, the ports that will be used must be specified. Default to false.	false	boolean	
hostPID	Use the host's pid namespace. Optional: Default to false.	false	boolean	
hostIPC	Use the host's ipc namespace. Optional: Default to false.	false	boolean	
securityContext	SecurityContext holds pod-level security attributes and common container settings. Optional: Defaults to empty. See type description for default values of each field.	false	Section 2.3.186, "v1.PodSecurityContext"	

Name	Description	Required	Schema	Default
imagePullSecrets	ImagePullSecrets is an optional list of references to secrets in the same namespace to use for pulling any of the images used by this PodSpec. If specified, these secrets will be passed to individual puller implementations for them to use. For example, in the case of docker, only DockerConfig type secrets are honored. More info: http://kubernetes.io/docs/user-guide/images#specifying-imagepullsecrets-on-a-pod	false	Section 2.3.152, "v1.LocalObjectReference" array	
hostname	Specifies the hostname of the Pod. If not specified, the pod's hostname will be set to a system-defined value.	false	string	

Name	Description	Required	Schema	Default
subdomain	If specified, the fully qualified Pod hostname will be " <hostname>. <subdomain>. <pod namespace>.svc .<cluster domain>". If not specified, the pod will not have a domainname at all.	false	string	
affinity	If specified, the pod's scheduling constraints	false	Section 2.3.7, "v1.Affinity"	
schedulerName	If specified, the pod will be dispatched by specified scheduler. If not specified, the pod will be dispatched by default scheduler.	false	string	
tolerations	If specified, the pod's tolerations.	false	Section 2.3.282, "v1.Toleration" array	

2.3.196. v1.PodTemplateSpec

PodTemplateSpec describes the data a pod should have when created from a template

Name	Description	Required	Schema	Default
------	-------------	----------	--------	---------

Name	Description	Required	Schema	Default
metadata	Standard object's metadata. More info: http://releases.k8s.io/HEAD/docs/dev/api-conventions.md#metadata	false	Section 2.3.176, "v1.ObjectMeta"	
spec	Specification of the desired behavior of the pod. More info: http://releases.k8s.io/HEAD/docs/dev/api-conventions.md#spec-and-status	false	Section 2.3.195, "v1.PodSpec"	

2.3.197. v1.Policy

Policy is a object that holds all the Roles for a particular namespace. There is at most one Policy document per namespace.

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/HEAD/docs/dev/api-conventions.md#types-kinds	false	string	

Name	Description	Required	Schema	Default
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#resources	false	string	
metadata	Standard object's metadata.	false	Section 2.3.176, "v1.ObjectMeta"	
lastModified	LastModified is the last time that any part of the Policy was created, updated, or deleted	true	string	
roles	Roles holds all the Roles held by this Policy, mapped by Role.Name	true	Section 2.3.158, "v1.NamedRole" array	

2.3.198. v1.PolicyBinding

PolicyBinding is a object that holds all the RoleBindings for a particular namespace. There is one PolicyBinding document per referenced Policy namespace

Name	Description	Required	Schema	Default
------	-------------	----------	--------	---------

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#types-kinds	false	string	
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#resources	false	string	
metadata	Standard object's metadata.	false	Section 2.3.176, "v1.ObjectMeta"	

Name	Description	Required	Schema	Default
lastModified	LastModified is the last time that any part of the PolicyBinding was created, updated, or deleted	true	string	
policyRef	PolicyRef is a reference to the Policy that contains all the Roles that this PolicyBinding's RoleBindings may reference	true	Section 2.3.177, "v1.ObjectReference"	
roleBindings	RoleBindings holds all the RoleBindings held by this PolicyBinding, mapped by RoleBinding.Name	true	Section 2.3.159, "v1.NamedRoleBinding" array	

2.3.199. v1.PolicyBindingList

PolicyBindingList is a collection of PolicyBindings

Name	Description	Required	Schema	Default
------	-------------	----------	--------	---------

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/HEAD/docs/dev/api-conventions.md#types-kinds	false	string	
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/HEAD/docs/dev/api-conventions.md#resources	false	string	
metadata	Standard object's metadata.	false	Section 2.3.151, "v1.ListMeta"	
items	Items is a list of PolicyBindings	true	Section 2.3.198, "v1.PolicyBinding" array	

2.3.200. v1.PolicyList

PolicyList is a collection of Policies

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/HEAD/docs/dev/api-conventions.md#types-kinds	false	string	
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/HEAD/docs/dev/api-conventions.md#resources	false	string	
metadata	Standard object's metadata.	false	Section 2.3.151, "v1.ListMeta"	

Name	Description	Required	Schema	Default
items	Items is a list of Policies	true	Section 2.3.197 , "v1.Policy" array	

2.3.201. v1.PolicyRule

PolicyRule holds information that describes a policy rule, but does not contain information about who the rule applies to or which namespace the rule applies to.

Name	Description	Required	Schema	Default
verbs	Verbs is a list of Verbs that apply to ALL the ResourceKinds and AttributeRestrictions contained in this rule. VerbAll represents all kinds.	true	string array	
attributeRestrictions	AttributeRestrictions will vary depending on what the Authorizer/AuthorizationAttribute Builder pair supports. If the Authorizer does not recognize how to handle the AttributeRestrictions, the Authorizer should report an error.	false	string	

Name	Description	Required	Schema	Default
apiGroups	APIGroups is the name of the APIGroup that contains the resources. If this field is empty, then both kubernetes and origin API groups are assumed. That means that if an action is requested against one of the enumerated resources in either the kubernetes or the origin API group, the request will be allowed	true	string array	
resources	Resources is a list of resources this rule applies to. ResourceAll represents all resources.	true	string array	
resourceNames	ResourceNames is an optional white list of names that the rule applies to. An empty set means that everything is allowed.	false	string array	

Name	Description	Required	Schema	Default
nonResourceURLs	NonResourceURLsSlice is a set of partial urls that a user should have access to. *s are allowed, but only as the full, final step in the path This name is intentionally different than the internal type so that the DefaultConvert works nicely and because the ordering may be different.	false	string array	

2.3.202. v1.PortworxVolumeSource

PortworxVolumeSource represents a Portworx volume resource.

Name	Description	Required	Schema	Default
volumeID	VolumeID uniquely identifies a Portworx volume	true	string	
fsType	FSType represents the filesystem type to mount Must be a filesystem type supported by the host operating system. Ex. "ext4", "xfs". Implicitly inferred to be "ext4" if unspecified.	false	string	

Name	Description	Required	Schema	Default
readOnly	Defaults to false (read/write). ReadOnly here will force the ReadOnly setting in VolumeMounts.	false	boolean	

2.3.203. v1.Preconditions

Preconditions must be fulfilled before an operation (update, delete, etc.) is carried out.

Name	Description	Required	Schema	Default
uid	Specifies the target UID.	false	Section 2.3.3, "types.UID"	

2.3.204. v1.PreferredSchedulingTerm

An empty preferred scheduling term matches all objects with implicit weight 0 (i.e. it's a no-op). A null preferred scheduling term matches no objects (i.e. is also a no-op).

Name	Description	Required	Schema	Default
weight	Weight associated with matching the corresponding nodeSelectorTerm, in the range 1-100.	true	integer (int32)	
preference	A node selector term, associated with the corresponding weight.	true	Section 2.3.166, "v1.NodeSelectorTerm"	

2.3.205. v1.Probe

Probe describes a health check to be performed against a container to determine whether it is alive or ready to receive traffic.

Name	Description	Required	Schema	Default
exec	One and only one of the following should be specified. Exec specifies the action to take.	false	Section 2.3.95, "v1.ExecAction"	
httpGet	HTTPGet specifies the http request to perform.	false	Section 2.3.112, "v1.HTTPGetAction"	
tcpSocket	TCPsocket specifies an action involving a TCP port. TCP hooks not yet supported	false	Section 2.3.272, "v1.TCPsocketAction"	
initialDelaySeconds	Number of seconds after the container has started before liveness probes are initiated. More info: http://kubernetes.io/docs/user-guide/pod-states#container-probes	false	integer (int32)	
timeoutSeconds	Number of seconds after which the probe times out. Defaults to 1 second. Minimum value is 1. More info: http://kubernetes.io/docs/user-guide/pod-states#container-probes	false	integer (int32)	

Name	Description	Required	Schema	Default
periodSeconds	How often (in seconds) to perform the probe. Default to 10 seconds. Minimum value is 1.	false	integer (int32)	
successThreshold	Minimum consecutive successes for the probe to be considered successful after having failed. Defaults to 1. Must be 1 for liveness. Minimum value is 1.	false	integer (int32)	
failureThreshold	Minimum consecutive failures for the probe to be considered failed after having succeeded. Defaults to 3. Minimum value is 1.	false	integer (int32)	

2.3.206. v1.Project

Projects are the unit of isolation and collaboration in OpenShift. A project has one or more members, a quota on the resources that the project may consume, and the security controls on the resources in the project. Within a project, members may have different roles - project administrators can set membership, editors can create and manage the resources, and viewers can see but not access running containers. In a normal cluster project administrators are not able to alter their quotas - that is restricted to cluster administrators.

Listing or watching projects will return only projects the user has the reader role on.

An OpenShift project is an alternative representation of a Kubernetes namespace. Projects are exposed as editable to end users while namespaces are not. Direct creation of a project is typically restricted to administrators, while end users should use the requestproject resource.

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#types-kinds	false	string	
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#resources	false	string	
metadata	Standard object's metadata.	false	Section 2.3.176, "v1.ObjectMeta"	
spec	Spec defines the behavior of the Namespace.	false	Section 2.3.209, "v1.ProjectSpec"	

Name	Description	Required	Schema	Default
status	Status describes the current status of a Namespace	false	Section 2.3.210, "v1.ProjectStatus"	

2.3.207. v1.ProjectList

ProjectList is a list of Project objects.

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#types-kinds	false	string	

Name	Description	Required	Schema	Default
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#resources	false	string	
metadata	Standard object's metadata.	false	Section 2.3.151, "v1.ListMeta"	
items	Items is the list of projects	true	Section 2.3.206, "v1.Project" array	

2.3.208. v1.ProjectRequest

ProjectRequest is the set of options necessary to fully qualify a project request

Name	Description	Required	Schema	Default
------	-------------	----------	--------	---------

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/HEAD/docs/dev/api-conventions.md#types-kinds	false	string	
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/HEAD/docs/dev/api-conventions.md#resources	true	string	
metadata	Standard object's metadata.	subfield name	Section 2.3.176, "v1.ObjectMeta"	
displayName	DisplayName is the display name to apply to a project	false	string	

Name	Description	Required	Schema	Default
description	Description is the description to apply to a project	false	string	

2.3.209. v1.ProjectSpec

ProjectSpec describes the attributes on a Project

Name	Description	Required	Schema	Default
finalizers	Finalizers is an opaque list of values that must be empty to permanently remove object from storage	false	Section 2.3.98, "v1.FinalizerName" array	

2.3.210. v1.ProjectStatus

ProjectStatus is information about the current status of a Project

Name	Description	Required	Schema	Default
phase	Phase is the current lifecycle phase of the project	false	string	

2.3.211. v1.ProjectedVolumeSource

Represents a projected volume source

Name	Description	Required	Schema	Default
sources	list of volume projections	true	Section 2.3.289, "v1.VolumeProjection" array	

Name	Description	Required	Schema	Default
defaultMode	Mode bits to use on created files by default. Must be a value between 0 and 0777. Directories within the path are not affected by this setting. This might be in conflict with other options that affect the file mode, like fsGroup, and the result can be other mode bits set.	false	integer (int32)	

2.3.212. v1.QuobyteVolumeSource

Represents a Quobyte mount that lasts the lifetime of a pod. Quobyte volumes do not support ownership management or SELinux relabeling.

Name	Description	Required	Schema	Default
registry	Registry represents a single or multiple Quobyte Registry services specified as a string as host:port pair (multiple entries are separated with commas) which acts as the central registry for volumes	true	string	
volume	Volume is a string that references an already created Quobyte volume by name.	true	string	

Name	Description	Required	Schema	Default
readOnly	ReadOnly here will force the Quobyte volume to be mounted with read-only permissions. Defaults to false.	false	boolean	
user	User to map volume access to Defaults to serviceaccount user	false	string	
group	Group to map volume access to Default is no group	false	string	

2.3.213. v1.RBDVolumeSource

Represents a Rados Block Device mount that lasts the lifetime of a pod. RBD volumes support ownership management and SELinux relabeling.

Name	Description	Required	Schema	Default
monitors	A collection of Ceph monitors. More info: http://releases.k8s.io/HEAD/examples/volumes/rbd/README.md#how-to-use-it	true	string array	
image	The rados image name. More info: http://releases.k8s.io/HEAD/examples/volumes/rbd/README.md#how-to-use-it	true	string	

Name	Description	Required	Schema	Default
fsType	Filesystem type of the volume that you want to mount. Tip: Ensure that the filesystem type is supported by the host operating system. Examples: "ext4", "xfs", "ntfs". Implicitly inferred to be "ext4" if unspecified. More info: http://kubernetes.io/docs/user-guide/volumes#rbd	false	string	
pool	The rados pool name. Default is rbd. More info: http://releases.k8s.io/HEAD/examples/volumes/rbd/README.md#how-to-use-it .	false	string	
user	The rados user name. Default is admin. More info: http://releases.k8s.io/HEAD/examples/volumes/rbd/README.md#how-to-use-it	false	string	

Name	Description	Required	Schema	Default
keyring	Keyring is the path to key ring for RBDUser. Default is /etc/ceph/keyring. More info: http://releases.k8s.io/HEAD/examples/volumes/rbd/README.md#how-to-use-it	false	string	
secretRef	SecretRef is name of the authentication secret for RBDUser. If provided overrides keyring. Default is nil. More info: http://releases.k8s.io/HEAD/examples/volumes/rbd/README.md#how-to-use-it	false	Section 2.3.152, "v1.LocalObject Reference"	
readOnly	ReadOnly here will force the ReadOnly setting in VolumeMounts. Defaults to false. More info: http://releases.k8s.io/HEAD/examples/volumes/rbd/README.md#how-to-use-it	false	boolean	

2.3.214. v1.RecreateDeploymentStrategyParams

RecreateDeploymentStrategyParams are the input to the Recreate deployment strategy.

Name	Description	Required	Schema	Default
------	-------------	----------	--------	---------

Name	Description	Required	Schema	Default
timeoutSeconds	TimeoutSeconds is the time to wait for updates before giving up. If the value is nil, a default will be used.	false	integer (int64)	
pre	Pre is a lifecycle hook which is executed before the strategy manipulates the deployment. All LifecycleHookFailurePolicy values are supported.	false	Section 2.3.150, "v1.LifecycleHook"	
mid	Mid is a lifecycle hook which is executed while the deployment is scaled down to zero before the first new pod is created. All LifecycleHookFailurePolicy values are supported.	false	Section 2.3.150, "v1.LifecycleHook"	
post	Post is a lifecycle hook which is executed after the strategy has finished all deployment logic. All LifecycleHookFailurePolicy values are supported.	false	Section 2.3.150, "v1.LifecycleHook"	

2.3.215. v1.RepositoryImportSpec

RepositoryImportSpec describes a request to import images from a Docker image repository.

Name	Description	Required	Schema	Default
------	-------------	----------	--------	---------

Name	Description	Required	Schema	Default
from	From is the source for the image repository to import; only kind DockerImage and a name of a Docker image repository is allowed	true	Section 2.3.177, "v1.ObjectReference"	
importPolicy	ImportPolicy is the policy controlling how the image is imported	false	Section 2.3.277, "v1.TagImportPolicy"	
referencePolicy	ReferencePolicy defines how other components should consume the image	false	Section 2.3.279, "v1.TagReferencePolicy"	
includeManifest	IncludeManifest determines if the manifest for each image is returned in the response	false	boolean	

2.3.216. v1.RepositoryImportStatus

RepositoryImportStatus describes the result of an image repository import

Name	Description	Required	Schema	Default
status	Status reflects whether any failure occurred during import	false	Section 2.3.264, "v1.Status"	

Name	Description	Required	Schema	Default
images	Images is a list of images successfully retrieved by the import of the repository.	false	Section 2.3.125, "v1.ImageImport Status" array	
additionalTags	AdditionalTags are tags that exist in the repository but were not imported because a maximum limit of automatic imports was applied.	false	string array	

2.3.217. v1.ResourceAccessReview

ResourceAccessReview is a means to request a list of which users and groups are authorized to perform the action specified by spec

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#types-kinds	false	string	

Name	Description	Required	Schema	Default
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#resources	false	string	
namespace	Namespace is the namespace of the action being requested. Currently, there is no distinction between no namespace and all namespaces	true	string	
verb	Verb is one of: get, list, watch, create, update, delete	true	string	
resourceAPIGroup	Group is the API group of the resource Serialized as resourceAPIGroup to avoid confusion with the 'groups' field when inlined	true	string	

Name	Description	Required	Schema	Default
resourceAPIVersion	Version is the API version of the resource Serialized as resourceAPIVersion to avoid confusion with TypeMeta.apiVersion and ObjectMeta.resourceVersion when inlined	true	string	
resource	Resource is one of the existing resource types	true	string	
resourceName	ResourceName is the name of the resource being requested for a "get" or deleted for a "delete"	true	string	
path	Path is the path of a non resource URL	true	string	
isNonResourceURL	IsNonResourceURL is true if this is a request for a non-resource URL (outside of the resource hierarchy)	true	boolean	
content	Content is the actual content of the request for create and update	false	string	

2.3.218. v1.ResourceFieldSelector

ResourceFieldSelector represents container resources (cpu, memory) and their output format

Name	Description	Required	Schema	Default
containerName	Container name: required for volumes, optional for env vars	false	string	
resource	Required: resource to select	true	string	
divisor	Specifies the output format of the exposed resources, defaults to "1"	false	string	

2.3.219. v1.ResourceQuotaScope

2.3.220. v1.ResourceQuotaSpec

ResourceQuotaSpec defines the desired hard limits to enforce for Quota.

Name	Description	Required	Schema	Default
hard	Hard is the set of desired hard limits for each named resource. More info: http://releases.k8s.io/HEAD/docs/design/admission_control_resource_quota.md#admissioncontrol-plugin-resourcequota	false	object	
scopes	A collection of filters that must match each object tracked by a quota. If not specified, the quota matches all objects.	false	Section 2.3.219, "v1.ResourceQuotaScope" array	

2.3.221. v1.ResourceQuotaStatus

ResourceQuotaStatus defines the enforced hard limits and observed use.

Name	Description	Required	Schema	Default
hard	Hard is the set of enforced hard limits for each named resource. More info: http://releases.k8s.io/HEAD/docs/design/admission_control_resource_quota.md#admissioncontrol-plugin-resourcequota	false	object	
used	Used is the current observed total usage of the resource in the namespace.	false	object	

2.3.222. v1.ResourceQuotaStatusByNamespace

ResourceQuotaStatusByNamespace gives status for a particular project

Name	Description	Required	Schema	Default
namespace	Namespace the project this status applies to	true	string	
status	Status indicates how many resources have been consumed by this project	true	Section 2.3.221, "v1.ResourceQuotaStatus"	

2.3.223. v1.ResourceRequirements

ResourceRequirements describes the compute resource requirements.

Name	Description	Required	Schema	Default
------	-------------	----------	--------	---------

Name	Description	Required	Schema	Default
limits	Limits describes the maximum amount of compute resources allowed. More info: http://kubernetes.io/docs/user-guide/compute-resources/	false	object	
requests	Requests describes the minimum amount of compute resources required. If Requests is omitted for a container, it defaults to Limits if that is explicitly specified, otherwise to an implementation-defined value. More info: http://kubernetes.io/docs/user-guide/compute-resources/	false	object	

2.3.224. v1.Role

Role is a logical grouping of PolicyRules that can be referenced as a unit by RoleBindings.

Name	Description	Required	Schema	Default
------	-------------	----------	--------	---------

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/HEAD/docs/dev/api-conventions.md#types-kinds	false	string	
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/HEAD/docs/dev/api-conventions.md#resources	false	string	
metadata	Standard object's metadata.	false	Section 2.3.176, "v1.ObjectMeta"	
rules	Rules holds all the PolicyRules for this Role	true	Section 2.3.201, "v1.PolicyRule" array	

2.3.225. v1.RoleBinding

RoleBinding references a Role, but not contain it. It can reference any Role in the same namespace or in the global namespace. It adds who information via (Users and Groups) OR Subjects and namespace information by which namespace it exists in. RoleBindings in a given namespace only have effect in that namespace (excepting the master namespace which has power in all namespaces).

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#types-kinds	false	string	
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#resources	false	string	

Name	Description	Required	Schema	Default
metadata	Standard object's metadata.	false	Section 2.3.176, "v1.ObjectMeta"	
userNames	UserNames holds all the usernames directly bound to the role. This field should only be specified when supporting legacy clients and servers. See Subjects for further details.	true	string array	
groupNames	GroupNames holds all the groups directly bound to the role. This field should only be specified when supporting legacy clients and servers. See Subjects for further details.	true	string array	

Name	Description	Required	Schema	Default
subjects	Subjects hold object references to authorize with this rule. This field is ignored if UserNames or GroupNames are specified to support legacy clients and servers. Thus newer clients that do not need to support backwards compatibility should send only fully qualified Subjects and should omit the UserNames and GroupNames fields. Clients that need to support backwards compatibility can use this field to build the UserNames and GroupNames.	true	Section 2.3.177, "v1.ObjectReference" array	
roleRef	RoleRef can only reference the current namespace and the global namespace. If the RoleRef cannot be resolved, the Authorizer must return an error. Since Policy is a singleton, this is sufficient knowledge to locate a role.	true	Section 2.3.177, "v1.ObjectReference"	

2.3.226. v1.RoleBindingList

RoleBindingList is a collection of RoleBindings

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#types-kinds	false	string	
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#resources	false	string	
metadata	Standard object's metadata.	false	Section 2.3.151, "v1.ListMeta"	
items	Items is a list of RoleBindings	true	Section 2.3.225, "v1.RoleBinding" array	

Name	Description	Required	Schema	Default
------	-------------	----------	--------	---------

2.3.227. v1.RoleBindingRestriction

RoleBindingRestriction is an object that can be matched against a subject (user, group, or service account) to determine whether rolebindings on that subject are allowed in the namespace to which the RoleBindingRestriction belongs. If any one of those RoleBindingRestriction objects matches a subject, rolebindings on that subject in the namespace are allowed.

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#types-kinds	false	string	

Name	Description	Required	Schema	Default
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#resources	false	string	
metadata	Standard object's metadata.	true	Section 2.3.176, "v1.ObjectMeta"	
spec	Spec defines the matcher.	true	Section 2.3.229, "v1.RoleBindingRestrictionSpec"	

2.3.228. v1.RoleBindingRestrictionList

RoleBindingRestrictionList is a collection of RoleBindingRestriction objects.

Name	Description	Required	Schema	Default
------	-------------	----------	--------	---------

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#types-kinds	false	string	
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#resources	false	string	
metadata	Standard object's metadata.	false	Section 2.3.151, "v1.ListMeta"	
items	Items is a list of RoleBindingRestriction objects.	true	Section 2.3.227, "v1.RoleBindingRestriction" array	

2.3.229. v1.RoleBindingRestrictionSpec

RoleBindingRestrictionSpec defines a rolebinding restriction. Exactly one field must be non-nil.

Name	Description	Required	Schema	Default
userrestriction	UserRestriction matches against user subjects.	true	Section 2.3.286, "v1.UserRestriction"	
grouprestriction	GroupRestriction matches against group subjects.	true	Section 2.3.111, "v1.GroupRestriction"	
serviceaccountrestriction	ServiceAccountRestriction matches against service-account subjects.	true	Section 2.3.256, "v1.ServiceAccountRestriction"	

2.3.230. v1.RoleList

RoleList is a collection of Roles

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#types-kinds	false	string	

Name	Description	Required	Schema	Default
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#resources	false	string	
metadata	Standard object's metadata.	false	Section 2.3.151, "v1.ListMeta"	
items	Items is a list of Roles	true	Section 2.3.224, "v1.Role" array	

2.3.231. v1.RollingDeploymentStrategyParams

RollingDeploymentStrategyParams are the input to the Rolling deployment strategy.

Name	Description	Required	Schema	Default
updatePeriodSeconds	UpdatePeriodSeconds is the time to wait between individual pod updates. If the value is nil, a default will be used.	false	integer (int64)	

Name	Description	Required	Schema	Default
intervalSeconds	IntervalSeconds is the time to wait between polling deployment status after update. If the value is nil, a default will be used.	false	integer (int64)	
timeoutSeconds	TimeoutSeconds is the time to wait for updates before giving up. If the value is nil, a default will be used.	false	integer (int64)	

Name	Description	Required	Schema	Default
maxUnavailable	<p>MaxUnavailable is the maximum number of pods that can be unavailable during the update. Value can be an absolute number (ex: 5) or a percentage of total pods at the start of update (ex: 10%). Absolute number is calculated from percentage by rounding down.</p> <p>This cannot be 0 if MaxSurge is 0. By default, 25% is used.</p> <p>Example: when this is set to 30%, the old RC can be scaled down by 30% immediately when the rolling update starts. Once new pods are ready, old RC can be scaled down further, followed by scaling up the new RC, ensuring that at least 70% of original number of pods are available at all times during the update.</p>	false	string	

Name	Description	Required	Schema	Default
maxSurge	<p>MaxSurge is the maximum number of pods that can be scheduled above the original number of pods. Value can be an absolute number (ex: 5) or a percentage of total pods at the start of the update (ex: 10%). Absolute number is calculated from percentage by rounding up.</p> <p>This cannot be 0 if MaxUnavailable is 0. By default, 25% is used.</p> <p>Example: when this is set to 30%, the new RC can be scaled up by 30% immediately when the rolling update starts. Once old pods have been killed, new RC can be scaled up further, ensuring that total number of pods running at any time during the update is atmost 130% of original pods.</p>	false	string	

Name	Description	Required	Schema	Default
pre	Pre is a lifecycle hook which is executed before the deployment process begins. All LifecycleHookFailurePolicy values are supported.	false	Section 2.3.150, "v1.LifecycleHook"	
post	Post is a lifecycle hook which is executed after the strategy has finished all deployment logic. All LifecycleHookFailurePolicy values are supported.	false	Section 2.3.150, "v1.LifecycleHook"	

2.3.232. v1.Route

A route allows developers to expose services through an HTTP(S) aware load balancing and proxy layer via a public DNS entry. The route may further specify TLS options and a certificate, or specify a public CNAME that the router should also accept for HTTP and HTTPS traffic. An administrator typically configures their router to be visible outside the cluster firewall, and may also add additional security, caching, or traffic controls on the service content. Routers usually talk directly to the service endpoints.

Once a route is created, the **host** field may not be changed. Generally, routers use the oldest route with a given host when resolving conflicts.

Routers are subject to additional customization and may support additional controls via the annotations field.

Because administrators may configure multiple routers, the route status field is used to return information to clients about the names and states of the route under each router. If a client chooses a duplicate name, for instance, the route status conditions are used to indicate the route cannot be chosen.

Name	Description	Required	Schema	Default
------	-------------	----------	--------	---------

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#types-kinds	false	string	
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#resources	false	string	
metadata	Standard object metadata.	false	Section 2.3.176, "v1.ObjectMeta"	
spec	spec is the desired state of the route	true	Section 2.3.237, "v1.RouteSpec"	

Name	Description	Required	Schema	Default
status	status is the current state of the route	true	Section 2.3.238, "v1.RouteStatus"	

2.3.233. v1.RouteIngress

RouteIngress holds information about the places where a route is exposed.

Name	Description	Required	Schema	Default
host	Host is the host string under which the route is exposed; this value is required	false	string	
routerName	Name is a name chosen by the router to identify itself; this value is required	false	string	
conditions	Conditions is the state of the route, may be empty.	false	Section 2.3.234, "v1.RouteIngressCondition" array	
wildcardPolicy	Wildcard policy is the wildcard policy that was allowed where this route is exposed.	false	string	
routerCanonicalHostname	CanonicalHostname is the external host name for the router that can be used as a CNAME for the host requested for this route. This value is optional and may not be set in all cases.	false	string	

2.3.234. v1.RouteIngressCondition

RouteIngressCondition contains details for the current condition of this route on a particular router.

Name	Description	Required	Schema	Default
type	Type is the type of the condition. Currently only Ready.	true	string	
status	Status is the status of the condition. Can be True, False, Unknown.	true	string	
reason	(brief) reason for the condition's last transition, and is usually a machine and human readable constant	false	string	
message	Human readable message indicating details about last transition.	false	string	
lastTransitionTime	RFC 3339 date and time when this condition last transitioned	false	string	

2.3.235. v1.RouteList

RouteList is a collection of Routes.

Name	Description	Required	Schema	Default
------	-------------	----------	--------	---------

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/HEAD/docs/dev/api-conventions.md#types-kinds	false	string	
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/HEAD/docs/dev/api-conventions.md#resources	false	string	
metadata	Standard object metadata.	false	Section 2.3.151 , "v1.ListMeta"	
items	items is a list of routes	true	Section 2.3.232 , "v1.Route" array	

2.3.236. v1.RoutePort

RoutePort defines a port mapping from a router to an endpoint in the service endpoints.

Name	Description	Required	Schema	Default
targetPort	The target port on pods selected by the service this route points to. If this is a string, it will be looked up as a named port in the target endpoints port list. Required	true	string	

2.3.237. v1.RouteSpec

RouteSpec describes the hostname or path the route exposes, any security information, and one or more backends the route points to. Weights on each backend can define the balance of traffic sent to each backend - if all weights are zero the route will be considered to have no backends and return a standard 503 response.

The `tls` field is optional and allows specific certificates or behavior for the route. Routers typically configure a default certificate on a wildcard domain to terminate routes without explicit certificates, but custom hostnames usually must choose passthrough (send traffic directly to the backend via the TLS Server-Name- Indication field) or provide a certificate.

Name	Description	Required	Schema	Default
host	host is an alias/DNS that points to the service. Optional. If not specified a route name will typically be automatically chosen. Must follow DNS952 subdomain conventions.	true	string	
path	Path that the router watches for, to route traffic for to the service. Optional	false	string	

Name	Description	Required	Schema	Default
to	to is an object the route should use as the primary backend. Only the Service kind is allowed, and it will be defaulted to Service. If the weight field is set to zero, no traffic will be sent to this service.	true	Section 2.3.239, "v1.RouteTargetReference"	
alternateBackends	alternateBackends is an extension of the 'to' field. If more than one service needs to be pointed to, then use this field. Use the weight field in RouteTargetReference object to specify relative preference. If the weight field is zero, the backend is ignored.	false	Section 2.3.239, "v1.RouteTargetReference" array	
port	If specified, the port to be used by the router. Most routers will use all endpoints exposed by the service by default - set this value to instruct routers which port to use.	false	Section 2.3.236, "v1.RoutePort"	

Name	Description	Required	Schema	Default
tls	The tls field provides the ability to configure certificates and termination for the route.	false	Section 2.3.273, "v1.TLSConfig"	
wildcardPolicy	Wildcard policy if any for the route. Currently only 'Subdomain' or 'None' is allowed.	false	string	

2.3.238. v1.RouteStatus

RouteStatus provides relevant info about the status of a route, including which routers acknowledge it.

Name	Description	Required	Schema	Default
ingress	ingress describes the places where the route may be exposed. The list of ingress points may contain duplicate Host or RouterName values. Routes are considered live once they are Ready	true	Section 2.3.233, "v1.RouteIngress" array	

2.3.239. v1.RouteTargetReference

RouteTargetReference specifies the target that resolve into endpoints. Only the 'Service' kind is allowed. Use 'weight' field to emphasize one over others.

Name	Description	Required	Schema	Default
------	-------------	----------	--------	---------

Name	Description	Required	Schema	Default
kind	The kind of target that the route is referring to. Currently, only 'Service' is allowed	true	string	
name	name of the service/target that is being referred to. e.g. name of the service	true	string	
weight	weight as an integer between 1 and 256 that specifies the target's relative weight against other target reference objects	true	integer (int32)	

2.3.240. v1.SELinuxOptions

SELinuxOptions are the labels to be applied to the container

Name	Description	Required	Schema	Default
user	User is a SELinux user label that applies to the container.	false	string	
role	Role is a SELinux role label that applies to the container.	false	string	
type	Type is a SELinux type label that applies to the container.	false	string	

Name	Description	Required	Schema	Default
level	Level is SELinux level label that applies to the container.	false	string	

2.3.241. v1.ScaleIOVolumeSource

ScaleIOVolumeSource represents a persistent ScaleIO volume

Name	Description	Required	Schema	Default
gateway	The host address of the ScaleIO API Gateway.	true	string	
system	The name of the storage system as configured in ScaleIO.	true	string	
secretRef	SecretRef references to the secret for ScaleIO user and other sensitive information. If this is not provided, Login operation will fail.	true	Section 2.3.152, "v1.LocalObject Reference"	
sslEnabled	Flag to enable/disable SSL communication with Gateway, default false	false	boolean	
protectionDomain	The name of the Protection Domain for the configured storage (defaults to "default").	false	string	

Name	Description	Required	Schema	Default
storagePool	The Storage Pool associated with the protection domain (defaults to "default").	false	string	
storageMode	Indicates whether the storage for a volume should be thick or thin (defaults to "thin").	false	string	
volumeName	The name of a volume already created in the ScaleIO system that is associated with this volume source.	false	string	
fsType	Filesystem type to mount. Must be a filesystem type supported by the host operating system. Ex. "ext4", "xfs", "ntfs". Implicitly inferred to be "ext4" if unspecified.	false	string	
readOnly	Defaults to false (read/write). ReadOnly here will force the ReadOnly setting in VolumeMounts.	false	boolean	

2.3.242. v1.ScopeRestriction

ScopeRestriction describe one restriction on scopes. Exactly one option must be non-nil.

Name	Description	Required	Schema	Default
literals	ExactValues means the scope has to match a particular set of strings exactly	false	string array	
clusterRole	ClusterRole describes a set of restrictions for cluster role scoping.	false	Section 2.3.52, "v1.ClusterRoleScopeRestriction"	

2.3.243. v1.Secret

Secret holds secret data of a certain type. The total bytes of the values in the Data field must be less than MaxSecretSize bytes.

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/HEAD/docs/dev/api-conventions.md#types-kinds	false	string	

Name	Description	Required	Schema	Default
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#resources	false	string	
metadata	Standard object's metadata. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#metadata	false	Section 2.3.176, "v1.ObjectMeta"	

Name	Description	Required	Schema	Default
data	Data contains the secret data. Each key must be a valid DNS_SUBDOMAIN or leading dot followed by valid DNS_SUBDOMAIN. The serialized form of the secret data is a base64 encoded string, representing the arbitrary (possibly non-string) data value here. Described in https://tools.ietf.org/html/rfc4648#section-4	false	object	
stringData	stringData allows specifying non-binary secret data in string form. It is provided as a write-only convenience method. All keys and values are merged into the data field on write, overwriting any existing values. It is never output when reading from the API.	false	object	
type	Used to facilitate programmatic handling of secret data.	false	string	

2.3.244. v1.SecretBuildSource

SecretBuildSource describes a secret and its destination directory that will be used only at the build time. The content of the secret referenced here will be copied into the destination directory instead of mounting.

Name	Description	Required	Schema	Default
secret	secret is a reference to an existing secret that you want to use in your build.	true	Section 2.3.152, "v1.LocalObject Reference"	
destinationDir	destinationDir is the directory where the files from the secret should be available for the build time. For the Source build strategy, these will be injected into a container where the assemble script runs. Later, when the script finishes, all files injected will be truncated to zero length. For the Docker build strategy, these will be copied into the build directory, where the Dockerfile is located, so users can ADD or COPY them during docker build.	false	string	

2.3.245. v1.SecretEnvSource

SecretEnvSource selects a Secret to populate the environment variables with.

The contents of the target Secret's Data field will represent the key-value pairs as environment variables.

Name	Description	Required	Schema	Default
name	Name of the referent. More info: http://kubernetes.io/docs/user-guide/identifiers#names	false	string	
optional	Specify whether the Secret must be defined	false	boolean	

2.3.246. v1.SecretKeySelector

SecretKeySelector selects a key of a Secret.

Name	Description	Required	Schema	Default
name	Name of the referent. More info: http://kubernetes.io/docs/user-guide/identifiers#names	false	string	
key	The key of the secret to select from. Must be a valid secret key.	true	string	
optional	Specify whether the Secret or it's key must be defined	false	boolean	

2.3.247. v1.SecretList

SecretList is a list of Secret.

Name	Description	Required	Schema	Default
------	-------------	----------	--------	---------

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#types-kinds	false	string	
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#resources	false	string	
metadata	Standard list metadata. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#types-kinds	false	Section 2.3.151, "v1.ListMeta"	

Name	Description	Required	Schema	Default
items	Items is a list of secret objects. More info: http://kubernetes.io/docs/user-guide/secrets	true	Section 2.3.243 , "v1.Secret" array	

2.3.248. v1.SecretProjection

Adapts a secret into a projected volume.

The contents of the target Secret's Data field will be presented in a projected volume as files using the keys in the Data field as the file names. Note that this is identical to a secret volume source without the default mode.

Name	Description	Required	Schema	Default
name	Name of the referent. More info: http://kubernetes.io/docs/user-guide/identifiers#names	false	string	

Name	Description	Required	Schema	Default
items	If unspecified, each key-value pair in the Data field of the referenced Secret will be projected into the volume as a file whose name is the key and content is the value. If specified, the listed keys will be projected into the specified paths, and unlisted keys will not be present. If a key is specified which is not present in the Secret, the volume setup will error unless it is marked optional. Paths must be relative and may not contain the '..' path or start with '..'.	false	Section 2.3.146 , "v1.KeyToPath" array	
optional	Specify whether the Secret or its key must be defined	false	boolean	

2.3.249. v1.SecretSpec

SecretSpec specifies a secret to be included in a build pod and its corresponding mount point

Name	Description	Required	Schema	Default
secretSource	secretSource is a reference to the secret	true	Section 2.3.152 , "v1.LocalObjectReference"	

Name	Description	Required	Schema	Default
mountPath	mountPath is the path at which to mount the secret	true	string	

2.3.250. v1.SecretVolumeSource

Adapts a Secret into a volume.

The contents of the target Secret's Data field will be presented in a volume as files using the keys in the Data field as the file names. Secret volumes support ownership management and SELinux relabeling.

Name	Description	Required	Schema	Default
secretName	Name of the secret in the pod's namespace to use. More info: http://kubernetes.io/docs/user-guide/volumes#secrets	false	string	

Name	Description	Required	Schema	Default
items	If unspecified, each key-value pair in the Data field of the referenced Secret will be projected into the volume as a file whose name is the key and content is the value. If specified, the listed keys will be projected into the specified paths, and unlisted keys will not be present. If a key is specified which is not present in the Secret, the volume setup will error unless it is marked optional. Paths must be relative and may not contain the '..' path or start with '..'.	false	Section 2.3.146 , "v1.KeyToPath" array	

Name	Description	Required	Schema	Default
defaultMode	Optional: mode bits to use on created files by default. Must be a value between 0 and 0777. Defaults to 0644. Directories within the path are not affected by this setting. This might be in conflict with other options that affect the file mode, like fsGroup, and the result can be other mode bits set.	false	integer (int32)	
optional	Specify whether the Secret or it's keys must be defined	false	boolean	

2.3.251. v1.SecurityContext

SecurityContext holds security configuration that will be applied to a container. Some fields are present in both SecurityContext and PodSecurityContext. When both are set, the values in SecurityContext take precedence.

Name	Description	Required	Schema	Default
capabilities	The capabilities to add/drop when running containers. Defaults to the default set of capabilities granted by the container runtime.	false	Section 2.3.33, "v1.Capabilities"	

Name	Description	Required	Schema	Default
privileged	Run container in privileged mode. Processes in privileged containers are essentially equivalent to root on the host. Defaults to false.	false	boolean	
seLinuxOptions	The SELinux context to be applied to the container. If unspecified, the container runtime will allocate a random SELinux context for each container. May also be set in PodSecurityContext ext. If set in both SecurityContext and PodSecurityContext ext, the value specified in SecurityContext takes precedence.	false	Section 2.3.240, "v1.SELinuxOptions"	

Name	Description	Required	Schema	Default
runAsUser	<p>The UID to run the entrypoint of the container process. Defaults to user specified in image metadata if unspecified. May also be set in PodSecurityContext ext. If set in both SecurityContext and PodSecurityContext ext, the value specified in SecurityContext takes precedence.</p>	false	integer (int64)	
runAsNonRoot	<p>Indicates that the container must run as a non-root user. If true, the Kubelet will validate the image at runtime to ensure that it does not run as UID 0 (root) and fail to start the container if it does. If unset or false, no such validation will be performed. May also be set in PodSecurityContext ext. If set in both SecurityContext and PodSecurityContext ext, the value specified in SecurityContext takes precedence.</p>	false	boolean	

Name	Description	Required	Schema	Default
readOnlyRootFilesystem	Whether this container has a read-only root filesystem. Default is false.	false	boolean	

2.3.252. v1.SelfSubjectRulesReview

SelfSubjectRulesReview is a resource you can create to determine which actions you can perform in a namespace

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#types-kinds	false	string	

Name	Description	Required	Schema	Default
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#resources	false	string	
spec	Spec adds information about how to conduct the check	true	Section 2.3.253, "v1.SelfSubjectRulesReviewSpec"	
status	Status is completed by the server to tell which permissions you have	false	Section 2.3.271, "v1.SubjectRulesReviewStatus"	

2.3.253. v1.SelfSubjectRulesReviewSpec

SelfSubjectRulesReviewSpec adds information about how to conduct the check

Name	Description	Required	Schema	Default
------	-------------	----------	--------	---------

Name	Description	Required	Schema	Default
scopes	Scopes to use for the evaluation. Empty means "use the unscoped (full) permissions of the user/groups". Nil means "use the scopes on this request".	true	string array	

2.3.254. v1.ServiceAccountPodSecurityPolicyReviewStatus

ServiceAccountPodSecurityPolicyReviewStatus represents ServiceAccount name and related review status

Name	Description	Required	Schema	Default
allowedBy	allowedBy is a reference to the rule that allows the PodTemplateSpec. A rule can be a SecurityContext Constraint or a PodSecurityPolicy. A nil , indicates that it was denied.	false	Section 2.3.177, "v1.ObjectReference"	
reason	A machine-readable description of why this operation is in the "Failure" status. If this value is empty there is no information available.	false	string	

Name	Description	Required	Schema	Default
template	template is the PodTemplateSpec after the defaulting is applied.	false	Section 2.3.196, "v1.PodTemplateSpec"	
name	name contains the allowed and the denied ServiceAccount name	true	string	

2.3.255. v1.ServiceAccountReference

ServiceAccountReference specifies a service account and namespace by their names.

Name	Description	Required	Schema	Default
name	Name is the name of the service account.	true	string	
namespace	Namespace is the namespace of the service account. Service accounts from inside the whitelisted namespaces are allowed to be bound to roles. If Namespace is empty, then the namespace of the RoleBindingRestriction in which the ServiceAccountReference is embedded is used.	true	string	

2.3.256. v1.ServiceAccountRestriction

ServiceAccountRestriction matches a service account by a string match on either the service-account name or the name of the service account's namespace.

Name	Description	Required	Schema	Default
serviceaccounts	ServiceAccounts specifies a list of literal service-account names.	true	Section 2.3.255, “v1.ServiceAccountReference” array	
namespaces	Namespaces specifies a list of literal namespace names.	true	string array	

2.3.257. v1.SignatureCondition

SignatureCondition describes an image signature condition of particular kind at particular probe time.

Name	Description	Required	Schema	Default
type	Type of signature condition, Complete or Failed.	true	string	
status	Status of the condition, one of True, False, Unknown.	true	string	
lastProbeTime	Last time the condition was checked.	false	string	
lastTransitionTime	Last time the condition transit from one status to another.	false	string	
reason	(brief) reason for the condition’s last transition.	false	string	
message	Human readable message indicating details about last transition.	false	string	

2.3.258. v1.SignatureIssuer

SignatureIssuer holds information about an issuer of signing certificate or key.

Name	Description	Required	Schema	Default
organization	Organization name.	false	string	
commonName	Common name (e.g. openshift-signing-service).	false	string	

2.3.259. v1.SignatureSubject

SignatureSubject holds information about a person or entity who created the signature.

Name	Description	Required	Schema	Default
organization	Organization name.	false	string	
commonName	Common name (e.g. openshift-signing-service).	false	string	
publicKeyID	If present, it is a human readable key id of public key belonging to the subject used to verify image signature. It should contain at least 64 lowest bits of public key's fingerprint (e.g. 0x685ebe62bf278440).	true	string	

2.3.260. v1.SourceBuildStrategy

SourceBuildStrategy defines input parameters specific to an Source build.

Name	Description	Required	Schema	Default
------	-------------	----------	--------	---------

Name	Description	Required	Schema	Default
from	from is reference to an DockerImage, ImageStreamTag , or ImageStreamImage from which the docker image should be pulled	true	Section 2.3.177, "v1.ObjectReference"	
pullSecret	pullSecret is the name of a Secret that would be used for setting up the authentication for pulling the Docker images from the private Docker registries	false	Section 2.3.152, "v1.LocalObjectReference"	
env	env contains additional environment variables you want to pass into a builder container.	false	Section 2.3.93, "v1.EnvVar" array	
scripts	scripts is the location of Source scripts	false	string	
incremental	incremental flag forces the Source build to do incremental builds if true.	false	boolean	
forcePull	forcePull describes if the builder should pull the images from registry prior to building.	false	boolean	

Name	Description	Required	Schema	Default
runtimeImage	<p>runtimeImage is an optional image that is used to run an application without unneeded dependencies installed. The building of the application is still done in the builder image but, post build, you can copy the needed artifacts in the runtime image for use.</p> <p>Deprecated: This feature will be removed in a future release. Use ImageSource to copy binary artifacts created from one build into a separate runtime image.</p>	false	Section 2.3.177, "v1.ObjectReference"	

Name	Description	Required	Schema	Default
runtimeArtifacts	runtimeArtifacts specifies a list of source/destination pairs that will be copied from the builder to the runtime image. sourcePath can be a file or directory. destinationDir must be a directory. destinationDir can also be empty or equal to ".", in this case it just refers to the root of WORKDIR. Deprecated: This feature will be removed in a future release. Use ImageSource to copy binary artifacts created from one build into a separate runtime image.	false	Section 2.3.133, "v1.ImageSource Path" array	

2.3.261. v1.SourceControlUser

SourceControlUser defines the identity of a user of source control

Name	Description	Required	Schema	Default
name	name of the source control user	false	string	
email	email of the source control user	false	string	

2.3.262. v1.SourceRevision

SourceRevision is the revision or commit information from the source for the build

Name	Description	Required	Schema	Default
type	type of the build source, may be one of 'Source', 'Dockerfile', 'Binary', or 'Images'	true	string	
git	Git contains information about git-based build source	false	Section 2.3.107, "v1.GitSourceRevision"	

2.3.263. v1.StageInfo

StageInfo contains details about a build stage.

Name	Description	Required	Schema	Default
name	name is a unique identifier for each build stage that occurs.	false	string	
startTime	startTime is a timestamp representing the server time when this Stage started. It is represented in RFC3339 form and is in UTC.	false	string	

Name	Description	Required	Schema	Default
durationMilliseconds	durationMilliseconds identifies how long the stage took to complete in milliseconds. Note: the duration of a stage can exceed the sum of the duration of the steps within the stage as not all actions are accounted for in explicit build steps.	false	integer (int64)	
steps	steps contains details about each step that occurs during a build stage including start time and duration in milliseconds.	false	Section 2.3.267 , "v1.StepInfo" array	

2.3.264. v1.Status

Status is a return value for calls that don't return other objects.

Name	Description	Required	Schema	Default
------	-------------	----------	--------	---------

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/HEAD/docs/dev/api-conventions.md#types-kinds	false	string	
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/HEAD/docs/dev/api-conventions.md#resources	false	string	
metadata	Standard list metadata. More info: http://releases.k8s.io/HEAD/docs/dev/api-conventions.md#types-kinds	false	Section 2.3.151, "v1.ListMeta"	

Name	Description	Required	Schema	Default
status	Status of the operation. One of: "Success" or "Failure". More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#spec-and-status	false	string	
message	A human-readable description of the status of this operation.	false	string	
reason	A machine-readable description of why this operation is in the "Failure" status. If this value is empty there is no information available. A Reason clarifies an HTTP status code but does not override it.	false	string	
details	Extended data associated with the reason. Each reason may define its own extended details. This field is optional and the data returned is not guaranteed to conform to any schema except that defined by the reason type.	false	Section 2.3.266, "v1.StatusDetails"	

Name	Description	Required	Schema	Default
code	Suggested HTTP return code for this status, 0 if not set.	false	integer (int32)	

2.3.265. v1.StatusCause

StatusCause provides more information about an api.Status failure, including cases when multiple errors are encountered.

Name	Description	Required	Schema	Default
reason	A machine-readable description of the cause of the error. If this value is empty there is no information available.	false	string	
message	A human-readable description of the cause of the error. This field may be presented as-is to a reader.	false	string	

Name	Description	Required	Schema	Default
field	<p>The field of the resource that has caused this error, as named by its JSON serialization. May include dot and postfix notation for nested attributes. Arrays are zero-indexed. Fields may appear more than once in an array of causes due to fields having multiple errors. Optional.</p> <p>Examples: "name" - the field "name" on the current resource "items[0].name" - the field "name" on the first array entry in "items"</p>	false	string	

2.3.266. v1.StatusDetails

StatusDetails is a set of additional properties that MAY be set by the server to provide additional information about a response. The Reason field of a Status object defines what attributes will be set. Clients must ignore fields that do not match the defined type of each attribute, and should assume that any attribute may be empty, invalid, or under defined.

Name	Description	Required	Schema	Default
------	-------------	----------	--------	---------

Name	Description	Required	Schema	Default
name	The name attribute of the resource associated with the status StatusReason (when there is a single name which can be described).	false	string	
group	The group attribute of the resource associated with the status StatusReason.	false	string	
kind	The kind attribute of the resource associated with the status StatusReason. On some operations may differ from the requested resource Kind. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#types-kinds	false	string	
causes	The Causes array includes more details associated with the StatusReason failure. Not all StatusReasons may provide detailed causes.	false	Section 2.3.265, "v1.StatusCause" array	

Name	Description	Required	Schema	Default
retryAfterSeconds	If specified, the time in seconds before the operation should be retried.	false	integer (int32)	

2.3.267. v1.StepInfo

StepInfo contains details about a build step.

Name	Description	Required	Schema	Default
name	name is a unique identifier for each build step.	false	string	
startTime	startTime is a timestamp representing the server time when this Step started. it is represented in RFC3339 form and is in UTC.	false	string	
durationMilliseconds	durationMilliseconds identifies how long the step took to complete in milliseconds.	false	integer (int64)	

2.3.268. v1.SubjectAccessReview

SubjectAccessReview is an object for requesting information about whether a user or group can perform an action

Name	Description	Required	Schema	Default
------	-------------	----------	--------	---------

Name	Description	Required	Schema	Default
kind	<p>Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#types-kinds</p>	false	string	
apiVersion	<p>APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#resources</p>	false	string	
namespace	<p>Namespace is the namespace of the action being requested. Currently, there is no distinction between no namespace and all namespaces</p>	true	string	

Name	Description	Required	Schema	Default
verb	Verb is one of: get, list, watch, create, update, delete	true	string	
resourceAPIGroup	Group is the API group of the resource Serialized as resourceAPIGroup to avoid confusion with the 'groups' field when inlined	true	string	
resourceAPIVersion	Version is the API version of the resource Serialized as resourceAPIVersion to avoid confusion with TypeMeta.apiVersion and ObjectMeta.resourceVersion when inlined	true	string	
resource	Resource is one of the existing resource types	true	string	
resourceName	ResourceName is the name of the resource being requested for a "get" or deleted for a "delete"	true	string	
path	Path is the path of a non resource URL	true	string	

Name	Description	Required	Schema	Default
isNonResourceURL	IsNonResourceURL is true if this is a request for a non-resource URL (outside of the resource hierarchy)	true	boolean	
content	Content is the actual content of the request for create and update	false	string	
user	User is optional. If both User and Groups are empty, the current authenticated user is used.	true	string	
groups	GroupsSlice is optional. Groups is the list of groups to which the User belongs.	true	string array	
scopes	Scopes to use for the evaluation. Empty means "use the unscoped (full) permissions of the user/groups". Nil for a self-SAR, means "use the scopes on this request". Nil for a regular SAR, means the same as empty.	true	string array	

2.3.269. v1.SubjectRulesReview

SubjectRulesReview is a resource you can create to determine which actions another user can perform in a namespace

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#types-kinds	false	string	
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#resources	false	string	
spec	Spec adds information about how to conduct the check	true	Section 2.3.270, "v1.SubjectRulesReviewSpec"	

Name	Description	Required	Schema	Default
status	Status is completed by the server to tell which permissions you have	false	Section 2.3.271, "v1.SubjectRulesReviewStatus"	

2.3.270. v1.SubjectRulesReviewSpec

SubjectRulesReviewSpec adds information about how to conduct the check

Name	Description	Required	Schema	Default
user	User is optional. At least one of User and Groups must be specified.	true	string	
groups	Groups is optional. Groups is the list of groups to which the User belongs. At least one of User and Groups must be specified.	true	string array	
scopes	Scopes to use for the evaluation. Empty means "use the unscoped (full) permissions of the user/groups".	true	string array	

2.3.271. v1.SubjectRulesReviewStatus

SubjectRulesReviewStatus is contains the result of a rules check

Name	Description	Required	Schema	Default
------	-------------	----------	--------	---------

Name	Description	Required	Schema	Default
rules	Rules is the list of rules (no particular sort) that are allowed for the subject	true	Section 2.3.201, "v1.PolicyRule" array	
evaluationError	EvaluationError can appear in combination with Rules. It means some error happened during evaluation that may have prevented additional rules from being populated.	false	string	

2.3.272. v1.TCPSocketAction

TCPSocketAction describes an action based on opening a socket

Name	Description	Required	Schema	Default
port	Number or name of the port to access on the container. Number must be in the range 1 to 65535. Name must be an IANA_SVC_NAME.	true	string	

2.3.273. v1.TLSConfig

TLSConfig defines config used to secure a route and provide termination

Name	Description	Required	Schema	Default
termination	termination indicates termination type.	true	string	

Name	Description	Required	Schema	Default
certificate	certificate provides certificate contents	false	string	
key	key provides key file contents	false	string	
caCertificate	caCertificate provides the cert authority certificate contents	false	string	
destinationCACertificate	destinationCACertificate provides the contents of the ca certificate of the final destination. When using reencrypt termination this file should be provided in order to have routers use it for health checks on the secure connection. If this field is not specified, the router may provide its own destination CA and perform hostname validation using the short service name (service.namespace.svc), which allows infrastructure generated certificates to automatically verify.	false	string	

Name	Description	Required	Schema	Default
insecureEdgeTerminationPolicy	<p>insecureEdgeTerminationPolicy indicates the desired behavior for insecure connections to a route. While each router may make its own decisions on which ports to expose, this is normally port 80.</p> <p>* Allow - traffic is sent to the server on the insecure port (default) * Disable - no traffic is allowed on the insecure port. * Redirect - clients are redirected to the secure port.</p>	false	string	

2.3.274. v1.TagEvent

TagEvent is used by ImageStreamStatus to keep a historical record of images associated with a tag.

Name	Description	Required	Schema	Default
created	Created holds the time the TagEvent was created	true	string	
dockerImageReference	DockerImageReference is the string that can be used to pull this image	true	string	
image	Image is the image	true	string	

Name	Description	Required	Schema	Default
generation	Generation is the spec tag generation that resulted in this tag being updated	true	integer (int64)	

2.3.275. v1.TagEventCondition

TagEventCondition contains condition information for a tag event.

Name	Description	Required	Schema	Default
type	Type of tag event condition, currently only ImportSuccess	true	string	
status	Status of the condition, one of True, False, Unknown.	true	string	
lastTransitionTime	LastTransitionTime is the time the condition transitioned from one status to another.	false	string	
reason	Reason is a brief machine readable explanation for the condition's last transition.	false	string	
message	Message is a human readable description of the details about last transition, complementing reason.	false	string	

Name	Description	Required	Schema	Default
generation	Generation is the spec tag generation that this status corresponds to	true	integer (int64)	

2.3.276. v1.TagImageHook

TagImageHook is a request to tag the image in a particular container onto an ImageStreamTag.

Name	Description	Required	Schema	Default
containerName	ContainerName is the name of a container in the deployment config whose image value will be used as the source of the tag. If there is only a single container this value will be defaulted to the name of that container.	true	string	
to	To is the target ImageStreamTag to set the container's image onto.	true	Section 2.3.177, "v1.ObjectReference"	

2.3.277. v1.TagImportPolicy

TagImportPolicy controls how images related to this tag will be imported.

Name	Description	Required	Schema	Default
------	-------------	----------	--------	---------

Name	Description	Required	Schema	Default
insecure	Insecure is true if the server may bypass certificate verification or connect directly over HTTP during image import.	false	boolean	
scheduled	Scheduled indicates to the server that this tag should be periodically checked to ensure it is up to date, and imported	false	boolean	

2.3.278. v1.TagReference

TagReference specifies optional annotations for images using this tag and an optional reference to an ImageStreamTag, ImageStreamImage, or DockerImage this tag should track.

Name	Description	Required	Schema	Default
name	Name of the tag	true	string	
annotations	Annotations associated with images using this tag	true	object	
from	From is a reference to an image stream tag or image stream this tag should track	false	Section 2.3.177, "v1.ObjectReference"	
reference	Reference states if the tag will be imported. Default value is false, which means the tag will be imported.	false	boolean	

Name	Description	Required	Schema	Default
generation	Generation is the image stream generation that updated this tag - setting it to 0 is an indication that the generation must be updated. Legacy clients will send this as nil, which means the client doesn't know or care.	true	integer (int64)	
importPolicy	Import is information that controls how images may be imported by the server.	false	Section 2.3.277, "v1.TagImportPolicy"	
referencePolicy	ReferencePolicy defines how other components should consume the image	false	Section 2.3.279, "v1.TagReferencePolicy"	

2.3.279. v1.TagReferencePolicy

TagReferencePolicy describes how pull-specs for images in this image stream tag are generated when image change triggers in deployment configs or builds are resolved. This allows the image stream author to control how images are accessed.

Name	Description	Required	Schema	Default
------	-------------	----------	--------	---------

Name	Description	Required	Schema	Default
type	Type determines how the image pull spec should be transformed when the image stream tag is used in deployment config triggers or new builds. The default value is Source , indicating the original location of the image should be used (if imported). The user may also specify Local , indicating that the pull spec should point to the integrated Docker registry and leverage the registry's ability to proxy the pull to an upstream registry. Local allows the credentials used to pull this image to be managed from the image stream's namespace, so others on the platform can access a remote image but have no access to the remote secret. It also allows the image layers to be mirrored into the local registry which the images can still be pulled even if	true	string	

Name	Description	Required	Schema	Default
	the upstream registry is unavailable.			

2.3.280. v1.Template

Template contains the inputs needed to produce a Config.

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#types-kinds	false	string	
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#resources	false	string	

Name	Description	Required	Schema	Default
metadata	Standard object's metadata.	false	Section 2.3.176, "v1.ObjectMeta"	
message	message is an optional instructional message that will be displayed when this template is instantiated. This field should inform the user how to utilize the newly created resources. Parameter substitution will be performed on the message before being displayed so that generated credentials and other parameters can be included in the output.	false	string	

Name	Description	Required	Schema	Default
objects	objects is an array of resources to include in this template. If a namespace value is hardcoded in the object, it will be removed during template instantiation, however if the namespace value is, or contains, a <code>\${PARAMETER_REFERENCE}</code> , the resolved value after parameter substitution will be respected and the object will be created in that namespace.	true	Section 2.3.2, "runtime.RawExtension" array	
parameters	parameters is an optional array of Parameters used during the Template to Config transformation.	false	Section 2.3.179, "v1.Parameter" array	
labels	labels is a optional set of labels that are applied to every object during the Template to Config transformation.	false	object	

2.3.281. v1.TemplateList

TemplateList is a list of Template objects.

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#types-kinds	false	string	
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#resources	false	string	
metadata	Standard object's metadata.	false	Section 2.3.151, "v1.ListMeta"	
items	Items is a list of templates	true	Section 2.3.280, "v1.Template" array	

2.3.282. v1.Toleration

The pod this Toleration is attached to tolerates any taint that matches the triple <key,value,effect> using the matching operator <operator>.

Name	Description	Required	Schema	Default
key	Key is the taint key that the toleration applies to. Empty means match all taint keys. If the key is empty, operator must be Exists; this combination means to match all values and all keys.	false	string	
operator	Operator represents a key's relationship to the value. Valid operators are Exists and Equal. Defaults to Equal. Exists is equivalent to wildcard for value, so that a pod can tolerate all taints of a particular category.	false	string	
value	Value is the taint value the toleration matches to. If the operator is Exists, the value should be empty, otherwise just a regular string.	false	string	

Name	Description	Required	Schema	Default
effect	Effect indicates the taint effect to match. Empty means match all taint effects. When specified, allowed values are NoSchedule, PreferNoSchedule and NoExecute.	false	string	
tolerationSeconds	TolerationSeconds represents the period of time the toleration (which must be of effect NoExecute, otherwise this field is ignored) tolerates the taint. By default, it is not set, which means tolerate the taint forever (do not evict). Zero and negative values will be treated as 0 (evict immediately) by the system.	false	integer (int64)	

2.3.283. v1.User

Upon log in, every user of the system receives a User and Identity resource. Administrators may directly manipulate the attributes of the users for their own tracking, or set groups via the API. The user name is unique and is chosen based on the value provided by the identity provider - if a user already exists with the incoming name, the user name may have a number appended to it depending on the configuration of the system.

Name	Description	Required	Schema	Default
------	-------------	----------	--------	---------

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/HEAD/docs/dev/api-conventions.md#types-kinds	false	string	
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/HEAD/docs/dev/api-conventions.md#resources	false	string	
metadata	Standard object's metadata.	false	Section 2.3.176, "v1.ObjectMeta"	
fullName	FullName is the full name of user	false	string	

Name	Description	Required	Schema	Default
identities	Identities are the identities associated with this user	true	string array	
groups	Groups specifies group names this user is a member of. This field is deprecated and will be removed in a future release. Instead, create a Group object containing the name of this User.	true	string array	

2.3.284. v1.UserIdentityMapping

UserIdentityMapping maps a user to an identity

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#types-kinds	false	string	

Name	Description	Required	Schema	Default
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#resources	false	string	
metadata	Standard object's metadata.	false	Section 2.3.176, "v1.ObjectMeta"	
identity	Identity is a reference to an identity	false	Section 2.3.177, "v1.ObjectReference"	
user	User is a reference to a user	false	Section 2.3.177, "v1.ObjectReference"	

2.3.285. v1.UserList

UserList is a collection of Users

Name	Description	Required	Schema	Default
------	-------------	----------	--------	---------

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#types-kinds	false	string	
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#resources	false	string	
metadata	Standard object's metadata.	false	Section 2.3.151, "v1.ListMeta"	
items	Items is the list of users	true	Section 2.3.283, "v1.User" array	

2.3.286. v1.UserRestriction

UserRestriction matches a user either by a string match on the user name, a string match on the name of a group to which the user belongs, or a label selector applied to the user labels.

Name	Description	Required	Schema	Default
users	Users specifies a list of literal user names.	true	string array	
groups	Groups specifies a list of literal group names.	true	string array	
labels	Selectors specifies a list of label selectors over user labels.	true	Section 2.3.147 , “v1.LabelSelector” array	

2.3.287. v1.Volume

Volume represents a named volume in a pod that may be accessed by any container in the pod.

Name	Description	Required	Schema	Default
name	Volume’s name. Must be a DNS_LABEL and unique within the pod. More info: http://kubernetes.io/docs/user-guide/identifiers#names	true	string	

Name	Description	Required	Schema	Default
hostPath	HostPath represents a pre-existing file or directory on the host machine that is directly exposed to the container. This is generally used for system agents or other privileged things that are allowed to see the host machine. Most containers will NOT need this. More info: http://kubernetes.io/docs/user-guide/volumes#hostpath	false	Section 2.3.115, "v1.HostPathVolumeSource"	
emptyDir	EmptyDir represents a temporary directory that shares a pod's lifetime. More info: http://kubernetes.io/docs/user-guide/volumes#emptydir	false	Section 2.3.91, "v1.EmptyDirVolumeSource"	
gcePersistentDisk	GCEPersistentDisk represents a GCE Disk resource that is attached to a kubelet's host machine and then exposed to the pod. More info: http://kubernetes.io/docs/user-guide/volumes#gcepersistentdisk	false	Section 2.3.101, "v1.GCEPersistentDiskVolumeSource"	

Name	Description	Required	Schema	Default
awsElasticBlockStore	AWSElasticBlockStore represents an AWS Disk resource that is attached to a kubelet's host machine and then exposed to the pod. More info: http://kubernetes.io/docs/user-guide/volumes#awselasticblockstore	false	Section 2.3.6, "v1.AWSElasticBlockStoreVolumeSource"	
gitRepo	GitRepo represents a git repository at a particular revision.	false	Section 2.3.106, "v1.GitRepoVolumeSource"	
secret	Secret represents a secret that should populate this volume. More info: http://kubernetes.io/docs/user-guide/volumes#secrets	false	Section 2.3.250, "v1.SecretVolumeSource"	
nfs	NFS represents an NFS mount on the host that shares a pod's lifetime More info: http://kubernetes.io/docs/user-guide/volumes#nfs	false	Section 2.3.155, "v1.NFSVolumeSource"	

Name	Description	Required	Schema	Default
iscsi	ISCSI represents an ISCSI Disk resource that is attached to a kubelet's host machine and then exposed to the pod. More info: http://releases.k8s.io/HEAD/examples/volumes/iscsi/README.md	false	Section 2.3.118, "v1.ISCSIVolumeSource"	
glusterfs	Glusterfs represents a Glusterfs mount on the host that shares a pod's lifetime. More info: http://releases.k8s.io/HEAD/examples/volumes/glusterfs/README.md	false	Section 2.3.108, "v1.GlusterfsVolumeSource"	
persistentVolumeClaim	PersistentVolumeClaimVolumeSource represents a reference to a PersistentVolumeClaim in the same namespace. More info: http://kubernetes.io/docs/user-guide/persistent-volumes#persistentvolumeclaims	false	Section 2.3.181, "v1.PersistentVolumeClaimVolumeSource"	

Name	Description	Required	Schema	Default
rbd	RBD represents a Rados Block Device mount on the host that shares a pod's lifetime. More info: http://releases.k8s.io/HEAD/examples/volumes/rbd/README.md	false	Section 2.3.213, "v1.RBDVolumeSource"	
flexVolume	FlexVolume represents a generic volume resource that is provisioned/attached using an exec based plugin. This is an alpha feature and may change in future.	false	Section 2.3.99, "v1.FlexVolumeSource"	
cinder	Cinder represents a cinder volume attached and mounted on kubelets host machine More info: http://releases.k8s.io/HEAD/examples/mysql-cinder-pd/README.md	false	Section 2.3.36, "v1.CinderVolumeSource"	
cephfs	CephFS represents a Ceph FS mount on the host that shares a pod's lifetime	false	Section 2.3.35, "v1.CephFSVolumeSource"	

Name	Description	Required	Schema	Default
flocker	Flocker represents a Flocker volume attached to a kubelet's host machine. This depends on the Flocker control service being running	false	Section 2.3.100, "v1.FlockerVolumeSource"	
downwardAPI	DownwardAPI represents downward API about the pod that should populate this volume	false	Section 2.3.85, "v1.DownwardAPIVolumeSource"	
fc	FC represents a Fibre Channel resource that is attached to a kubelet's host machine and then exposed to the pod.	false	Section 2.3.97, "v1.FCVolumeSource"	
azureFile	AzureFile represents an Azure File Service mount on the host and bind mount to the pod.	false	Section 2.3.12, "v1.AzureFileVolumeSource"	
configMap	ConfigMap represents a configMap that should populate this volume	false	Section 2.3.56, "v1.ConfigMapVolumeSource"	
vsphereVolume	VsphereVolume represents a vSphere volume attached and mounted on kubelets host machine	false	Section 2.3.290, "v1.VsphereVirtualDiskVolumeSource"	

Name	Description	Required	Schema	Default
quobyte	Quobyte represents a Quobyte mount on the host that shares a pod's lifetime	false	Section 2.3.212, "v1.QuobyteVolumeSource"	
azureDisk	AzureDisk represents an Azure Data Disk mount on the host and bind mount to the pod.	false	Section 2.3.11, "v1.AzureDiskVolumeSource"	
photonPersistentDisk	PhotonPersistentDisk represents a PhotonController persistent disk attached and mounted on kubelets host machine	false	Section 2.3.182, "v1.PhotonPersistentDiskVolumeSource"	
projected	Items for all in one resources secrets, configmaps, and downward API	false	Section 2.3.211, "v1.ProjectedVolumeSource"	
portworxVolume	PortworxVolume represents a portworx volume attached and mounted on kubelets host machine	false	Section 2.3.202, "v1.PortworxVolumeSource"	
scaleIO	ScaleIO represents a ScaleIO persistent volume attached and mounted on Kubernetes nodes.	false	Section 2.3.241, "v1.ScaleIOVolumeSource"	

Name	Description	Required	Schema	Default
metadata	Metadata represents metadata about the pod that should populate this volume Deprecated: Use downwardAPI instead.	false	Section 2.3.80, "v1.Deprecated DownwardAPIVolumeSource"	

2.3.288. v1.VolumeMount

VolumeMount describes a mounting of a Volume within a container.

Name	Description	Required	Schema	Default
name	This must match the Name of a Volume.	true	string	
readOnly	Mounted read-only if true, read-write otherwise (false or unspecified). Defaults to false.	false	boolean	
mountPath	Path within the container at which the volume should be mounted. Must not contain ':'. '.'	true	string	
subPath	Path within the volume from which the container's volume should be mounted. Defaults to "" (volume's root).	false	string	

2.3.289. v1.VolumeProjection

Projection that may be projected along with other supported volume types

Name	Description	Required	Schema	Default
secret	information about the secret data to project	false	Section 2.3.248, "v1.SecretProjection"	
downwardAPI	information about the downwardAPI data to project	false	Section 2.3.83, "v1.DownwardAPIProjection"	
configMap	information about the configMap data to project	false	Section 2.3.55, "v1.ConfigMapProjection"	

2.3.290. v1.VsphereVirtualDiskVolumeSource

Represents a vSphere volume resource.

Name	Description	Required	Schema	Default
volumePath	Path that identifies vSphere volume vmdk	true	string	
fsType	Filesystem type to mount. Must be a filesystem type supported by the host operating system. Ex. "ext4", "xfs", "ntfs". Implicitly inferred to be "ext4" if unspecified.	false	string	

2.3.291. v1.WatchEvent

Name	Description	Required	Schema	Default
type		true	string	
object		true	string	

2.3.292. v1.WebHookTrigger

WebHookTrigger is a trigger that gets invoked using a webhook type of post

Name	Description	Required	Schema	Default
secret	secret used to validate requests.	false	string	
allowEnv	allowEnv determines whether the webhook can set environment variables; can only be set to true for GenericWebHook.	false	boolean	

2.3.293. v1.WeightedPodAffinityTerm

The weights of all of the matched WeightedPodAffinityTerm fields are added per-node to find the most preferred node(s)

Name	Description	Required	Schema	Default
weight	weight associated with matching the corresponding podAffinityTerm, in the range 1-100.	true	integer (int32)	
podAffinityTerm	Required. A pod affinity term, associated with the corresponding weight.	true	Section 2.3.184, "v1.PodAffinityTerm"	

2.3.294. v1beta1.Scale

represents a scaling request for a resource.

Name	Description	Required	Schema	Default
------	-------------	----------	--------	---------

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/HEAD/docs/dev/api-conventions.md#types-kinds	false	string	
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/HEAD/docs/dev/api-conventions.md#resources	false	string	

Name	Description	Required	Schema	Default
metadata	Standard object metadata; More info: http://releases.k8s.io/HEAD/docs/dev/api-conventions.md#metadata .	false	Section 2.3.176, "v1.ObjectMeta"	
spec	defines the behavior of the scale. More info: http://releases.k8s.io/HEAD/docs/dev/api-conventions.md#spec-and-status .	false	Section 2.3.295, "v1beta1.ScaleSpec"	
status	current status of the scale. More info: http://releases.k8s.io/HEAD/docs/dev/api-conventions.md#spec-and-status . Read-only.	false	Section 2.3.296, "v1beta1.ScaleStatus"	

2.3.295. v1beta1.ScaleSpec

describes the attributes of a scale subresource

Name	Description	Required	Schema	Default
replicas	desired number of instances for the scaled object.	false	integer (int32)	

2.3.296. v1beta1.ScaleStatus

represents the current status of a scale subresource.

Name	Description	Required	Schema	Default
replicas	actual number of observed instances of the scaled object.	true	integer (int32)	
selector	label query over pods that should match the replicas count. More info: http://kubernetes.io/docs/user-guide/labels#label-selectors	false	object	
targetSelector	label selector for pods that should match the replicas count. This is a serialized version of both map-based and more expressive set-based selectors. This is done to avoid introspection in the clients. The string will be in the same format as the query-param syntax. If the target type only supports map-based selectors, both this field and map-based selector field are populated. More info: http://kubernetes.io/docs/user-guide/labels#label-selectors	false	string	

CHAPTER 3. KUBERNETES V1 REST API

3.1. OVERVIEW

The Kubernetes API allows you to run containerized applications, bind persistent storage, link those applications through service discovery, and manage the cluster infrastructure.

3.1.1. Version information

Version: v1

3.1.2. URI scheme

Host: 127.0.0.1:8443

BasePath: /

Schemes: HTTPS

3.2. PATHS

3.2.1. get available resources

GET /api/v1

3.2.1.1. Responses

HTTP Code	Description	Schema
default	success	Section 2.3.5, "v1.APIResourceList"

3.2.1.2. Consumes

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.1.3. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.1.4. Tags

- apiv1

3.2.2. create a Binding

POST /api/v1/bindings

3.2.2.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamenter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParameter	body		true	Section 3.3.10 , "v1.Binding"	

3.2.2.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.10 , "v1.Binding"

3.2.2.3. Consumes

- /

3.2.2.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.2.5. Tags

- apiv1

3.2.3. list objects of kind ComponentStatus

GET /api/v1/componentstatuses

3.2.3.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParameter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParameter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParameter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParameter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParamter	resourceVersion	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParamter	timeoutSeconds	Timeout for the list/watch call.	false	integer	

3.2.3.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.17, "v1.ComponentStatusList"

3.2.3.3. Consumes

- /

3.2.3.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf
- application/json;stream=watch
- application/vnd.kubernetes.protobuf;stream=watch

3.2.3.5. Tags

- apiv1

3.2.4. read the specified ComponentStatus

```
GET /api/v1/componentstatuses/{name}
```

3.2.4.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
PathParamet er	name	name of the ComponentSt atus	true	string	

3.2.4.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.16, "v1.ComponentStatus"

3.2.4.3. Consumes

- /

3.2.4.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.4.5. Tags

- apiv1

3.2.5. list or watch objects of kind ConfigMap

GET /api/v1/configmaps

3.2.5.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParameter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParameter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParameter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParam ter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParamter	resourceVersion	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParamter	timeoutSeconds	Timeout for the list/watch call.	false	integer	

3.2.5.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.21, "v1.ConfigMapList"

3.2.5.3. Consumes

- /

3.2.5.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf
- application/json;stream=watch
- application/vnd.kubernetes.protobuf;stream=watch

3.2.5.5. Tags

- apiv1

3.2.6. create a ConfigMap

POST /api/v1/configmaps

3.2.6.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParameter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParameter	body		true	Section 3.3.18 , "v1.ConfigMap"	

3.2.6.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.18 , "v1.ConfigMap"

3.2.6.3. Consumes

- /

3.2.6.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.6.5. Tags

- apiv1

3.2.7. list or watch objects of kind Endpoints

GET /api/v1/endpoints

3.2.7.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParameter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParameter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParameter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParam ter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParamter	resourceVersion	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParamter	timeoutSeconds	Timeout for the list/watch call.	false	integer	

3.2.7.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.45, "v1.EndpointsList"

3.2.7.3. Consumes

- /

3.2.7.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf
- application/json;stream=watch
- application/vnd.kubernetes.protobuf;stream=watch

3.2.7.5. Tags

- apiv1

3.2.8. create Endpoints

POST /api/v1/endpoints

3.2.8.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParameter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParameter	body		true	Section 3.3.44 , "v1.Endpoints"	

3.2.8.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.44 , "v1.Endpoints"

3.2.8.3. Consumes

- /

3.2.8.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.8.5. Tags

- apiv1

3.2.9. list or watch objects of kind Event

GET /api/v1/events

3.2.9.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParam eter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParam eter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParam ter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParamter	resourceVersion	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParamter	timeoutSeconds	Timeout for the list/watch call.	false	integer	

3.2.9.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.50, "v1.EventList"

3.2.9.3. Consumes

- /

3.2.9.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf
- application/json;stream=watch
- application/vnd.kubernetes.protobuf;stream=watch

3.2.9.5. Tags

- apiv1

3.2.10. create an Event

POST /api/v1/events

3.2.10.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParameter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParameter	body		true	Section 3.3.49 , "v1.Event"	

3.2.10.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.49 , "v1.Event"

3.2.10.3. Consumes

- /

3.2.10.4. Produces

- application/json

- application/yaml
- application/vnd.kubernetes.protobuf

3.2.10.5. Tags

- apiv1

3.2.11. list or watch objects of kind LimitRange

GET /api/v1/limitranges

3.2.11.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParam eter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParam eter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParam eter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParam ter	resourceVersi on	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParam ter	timeoutSecon ds	Timeout for the list/watch call.	false	integer	

3.2.11.2. Responses

HTTP Code	Description	Schema
-----------	-------------	--------

HTTP Code	Description	Schema
200	success	Section 3.3.74, "v1.LimitRangeList"

3.2.11.3. Consumes

- /

3.2.11.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf
- application/json;stream=watch
- application/vnd.kubernetes.protobuf;stream=watch

3.2.11.5. Tags

- apiv1

3.2.12. create a LimitRange

POST /api/v1/limitranges

3.2.12.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParameter	body		true	Section 3.3.72, "v1.LimitRange"	

3.2.12.2. Responses

HTTP Code	Description	Schema
-----------	-------------	--------

HTTP Code	Description	Schema
200	success	Section 3.3.72, "v1.LimitRange"

3.2.12.3. Consumes

- /

3.2.12.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.12.5. Tags

- apiv1

3.2.13. list or watch objects of kind Namespace

GET /api/v1/namespaces

3.2.13.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParam eter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParam ter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParam ter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParam ter	resourceVersi on	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParam ter	timeoutSecon ds	Timeout for the list/watch call.	false	integer	

3.2.13.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.82, "v1.NamespaceList"

3.2.13.3. Consumes

- /

3.2.13.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf
- application/json;stream=watch
- application/vnd.kubernetes.protobuf;stream=watch

3.2.13.5. Tags

- apiv1

3.2.14. create a Namespace

POST /api/v1/namespaces

3.2.14.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParameter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParameter	body		true	Section 3.3.81 , "v1.Namespace"	

3.2.14.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.81 , "v1.Namespace"

3.2.14.3. Consumes

- /

3.2.14.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.14.5. Tags

- apiv1

3.2.15. delete collection of Namespace

```
DELETE /api/v1/namespaces
```

3.2.15.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParam eter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParam eter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParam ter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParam ter	resourceVersi on	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParam ter	timeoutSecon ds	Timeout for the list/watch call.	false	integer	

3.2.15.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.264, "v1.Status"

3.2.15.3. Consumes

- /

3.2.15.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.15.5. Tags

- apiv1

3.2.16. create a Binding

POST /api/v1/namespaces/{namespace}/bindings

3.2.16.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamet er	body		true	Section 3.3.10 , "v1.Binding"	
PathParamet er	namespace	object name and auth scope, such as for teams and projects	true	string	

3.2.16.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.10 , "v1.Binding"

3.2.16.3. Consumes

- /

3.2.16.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.16.5. Tags

- apiv1

3.2.17. list or watch objects of kind ConfigMap

```
GET /api/v1/namespaces/{namespace}/configmaps
```

3.2.17.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParam ter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParam ter	resourceVersi on	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParam ter	timeoutSecon ds	Timeout for the list/watch call.	false	integer	
PathParam eter	namespace	object name and auth scope, such as for teams and projects	true	string	

3.2.17.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.21, "v1.ConfigMapList"

3.2.17.3. Consumes

- /

3.2.17.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf
- application/json;stream=watch
- application/vnd.kubernetes.protobuf;stream=watch

3.2.17.5. Tags

- apiv1

3.2.18. create a ConfigMap

POST /api/v1/namespaces/{namespace}/configmaps

3.2.18.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamenter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParameter	body		true	Section 3.3.18, "v1.ConfigMap"	
PathParamenter	namespace	object name and auth scope, such as for teams and projects	true	string	

3.2.18.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.18, "v1.ConfigMap"

3.2.18.3. Consumes

- /

3.2.18.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.18.5. Tags

- apiv1

3.2.19. delete collection of ConfigMap

DELETE /api/v1/namespaces/{namespace}/configmaps

3.2.19.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParameter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParameter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParam ter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParam ter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParam ter	resourceVersi on	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParam ter	timeoutSecon ds	Timeout for the list/watch call.	false	integer	
PathParamet er	namespace	object name and auth scope, such as for teams and projects	true	string	

3.2.19.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.264, "v1.Status"

3.2.19.3. Consumes

- /

3.2.19.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.19.5. Tags

- apiv1

3.2.20. read the specified ConfigMap

GET /api/v1/namespaces/{namespace}/configmaps/{name}

3.2.20.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParam eter	export	Should this value be exported. Export strips fields that a user can not specify.	false	boolean	
QueryParam eter	exact	Should the export be exact. Exact export maintains cluster-specific fields like 'Namespace'.	false	boolean	

Type	Name	Description	Required	Schema	Default
PathParamet er	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParamet er	name	name of the ConfigMap	true	string	

3.2.20.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.18, "v1.ConfigMap"

3.2.20.3. Consumes

- /

3.2.20.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.20.5. Tags

- apiv1

3.2.21. partially update the specified ConfigMap

```
PATCH /api/v1/namespaces/{namespace}/configmaps/{name}
```

3.2.21.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParame ter	pretty	If 'true', then the output is pretty printed.	false	string	

Type	Name	Description	Required	Schema	Default
BodyParameter	body		true	Section 2.3.180, "v1.Patch"	
PathParamter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParamter	name	name of the ConfigMap	true	string	

3.2.21.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.18, "v1.ConfigMap"

3.2.21.3. Consumes

- application/json-patch+json
- application/merge-patch+json
- application/strategic-merge-patch+json

3.2.21.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.21.5. Tags

- apiv1

3.2.22. replace the specified ConfigMap

```
PUT /api/v1/namespaces/{namespace}/configmaps/{name}
```

3.2.22.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParameter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParameter	body		true	Section 3.3.18 , "v1.ConfigMap"	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParameter	name	name of the ConfigMap	true	string	

3.2.22.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.18 , "v1.ConfigMap"

3.2.22.3. Consumes

- /

3.2.22.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.22.5. Tags

- apiv1

3.2.23. delete a ConfigMap

```
DELETE /api/v1/namespaces/{namespace}/configmaps/{name}
```

3.2.23.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParameter	body		true	Section 2.3.6 1, "v1.DeleteOptions"	
QueryParamter	gracePeriodSeconds	The duration in seconds before the object should be deleted. Value must be non-negative integer. The value zero indicates delete immediately. If this value is nil, the default grace period for the specified type will be used. Defaults to a per object value if not specified. zero means delete immediately.	false	integer	

Type	Name	Description	Required	Schema	Default
QueryParam eter	orphanDepen dents	Deprecated: please use the PropagationP olicy, this field will be deprecated in 1.7. Should the dependent objects be orphaned. If true/false, the "orphan" finalizer will be added to/removed from the object's finalizers list. Either this field or PropagationP olicy may be set, but not both.	false	boolean	
QueryParam eter	propagationP olicy	Whether and how garbage collection will be performed. Either this field or OrphanDepen dents may be set, but not both. The default policy is decided by the existing finalizer set in the metadata.fin alizers and the resource- specific default policy.	false	string	

Type	Name	Description	Required	Schema	Default
PathParamet er	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParamet er	name	name of the ConfigMap	true	string	

3.2.23.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.264, "v1.Status"

3.2.23.3. Consumes

- /

3.2.23.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.23.5. Tags

- apiv1

3.2.24. list or watch objects of kind Endpoints

GET /api/v1/namespaces/{namespace}/endpoints

3.2.24.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParame ter	pretty	If 'true', then the output is pretty printed.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParam ter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParam ter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParam ter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParamter	resourceVersion	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParamter	timeoutSeconds	Timeout for the list/watch call.	false	integer	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	

3.2.24.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.45, "v1.EndpointsList"

3.2.24.3. Consumes

- /

3.2.24.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf
- application/json;stream=watch
- application/vnd.kubernetes.protobuf;stream=watch

3.2.24.5. Tags

- apiv1

3.2.25. create Endpoints

POST /api/v1/namespaces/{namespace}/endpoints

3.2.25.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParameter	body		true	Section 3.3.44, "v1.Endpoints"	
PathParamter	namespace	object name and auth scope, such as for teams and projects	true	string	

3.2.25.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.44, "v1.Endpoints"

3.2.25.3. Consumes

- /

3.2.25.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.25.5. Tags

- apiv1

3.2.26. delete collection of Endpoints

DELETE /api/v1/namespaces/{namespace}/endpoints

3.2.26.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParam eter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParam ter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParam ter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParamter	resourceVersion	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParamter	timeoutSeconds	Timeout for the list/watch call.	false	integer	
PathParamter	namespace	object name and auth scope, such as for teams and projects	true	string	

3.2.26.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.264, "v1.Status"

3.2.26.3. Consumes

- /

3.2.26.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.26.5. Tags

- apiv1

3.2.27. read the specified Endpoints

GET /api/v1/namespaces/{namespace}/endpoints/{name}

3.2.27.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParameter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParameter	export	Should this value be exported. Export strips fields that a user can not specify.	false	boolean	
QueryParameter	exact	Should the export be exact. Exact export maintains cluster-specific fields like 'Namespace'.	false	boolean	

Type	Name	Description	Required	Schema	Default
PathParamet er	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParamet er	name	name of the Endpoints	true	string	

3.2.27.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.44, "v1.Endpoints"

3.2.27.3. Consumes

- /

3.2.27.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.27.5. Tags

- apiv1

3.2.28. partially update the specified Endpoints

```
PATCH /api/v1/namespaces/{namespace}/endpoints/{name}
```

3.2.28.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParame ter	pretty	If 'true', then the output is pretty printed.	false	string	

Type	Name	Description	Required	Schema	Default
BodyParameter	body		true	Section 2.3.180, "v1.Patch"	
PathParamter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParamter	name	name of the Endpoints	true	string	

3.2.28.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.44, "v1.Endpoints"

3.2.28.3. Consumes

- application/json-patch+json
- application/merge-patch+json
- application/strategic-merge-patch+json

3.2.28.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.28.5. Tags

- apiv1

3.2.29. replace the specified Endpoints

```
PUT /api/v1/namespaces/{namespace}/endpoints/{name}
```

3.2.29.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParameter	body		true	Section 3.3.44 , "v1.Endpoints"	
PathParamter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParamter	name	name of the Endpoints	true	string	

3.2.29.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.44 , "v1.Endpoints"

3.2.29.3. Consumes

- /

3.2.29.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.29.5. Tags

- apiv1

3.2.30. delete Endpoints

```
DELETE /api/v1/namespaces/{namespace}/endpoints/{name}
```

3.2.30.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam ter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamet er	body		true	Section 2.3.6 1, "v1.DeleteOptions"	
QueryParam ter	gracePeriodS econds	The duration in seconds before the object should be deleted. Value must be non-negative integer. The value zero indicates delete immediately. If this value is nil, the default grace period for the specified type will be used. Defaults to a per object value if not specified. zero means delete immediately.	false	integer	

Type	Name	Description	Required	Schema	Default
QueryParam eter	orphanDepen dents	Deprecated: please use the PropagationP olicy, this field will be deprecated in 1.7. Should the dependent objects be orphaned. If true/false, the "orphan" finalizer will be added to/removed from the object's finalizers list. Either this field or PropagationP olicy may be set, but not both.	false	boolean	
QueryParam eter	propagationP olicy	Whether and how garbage collection will be performed. Either this field or OrphanDepen dents may be set, but not both. The default policy is decided by the existing finalizer set in the metadata.fin alizers and the resource- specific default policy.	false	string	

Type	Name	Description	Required	Schema	Default
PathParamet er	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParamet er	name	name of the Endpoints	true	string	

3.2.30.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.264, "v1.Status"

3.2.30.3. Consumes

- /

3.2.30.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.30.5. Tags

- apiv1

3.2.31. list or watch objects of kind Event

GET /api/v1/namespaces/{namespace}/events

3.2.31.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParame ter	pretty	If 'true', then the output is pretty printed.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParam ter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParam ter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParam ter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParam eter	resourceVersi on	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParam eter	timeoutSecon ds	Timeout for the list/watch call.	false	integer	
PathParamet er	namespace	object name and auth scope, such as for teams and projects	true	string	

3.2.31.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.50, "v1.EventList"

3.2.31.3. Consumes

- /

3.2.31.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf
- application/json;stream=watch
- application/vnd.kubernetes.protobuf;stream=watch

3.2.31.5. Tags

- apiv1

3.2.32. create an Event

POST /api/v1/namespaces/{namespace}/events

3.2.32.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamet er	body		true	Section 3.3.49, "v1.Event"	
PathParamet er	namespace	object name and auth scope, such as for teams and projects	true	string	

3.2.32.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.49, “v1.Event”

3.2.32.3. Consumes

- /

3.2.32.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.32.5. Tags

- apiv1

3.2.33. delete collection of Event

DELETE /api/v1/namespaces/{namespace}/events

3.2.33.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParam eter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParam eter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParam ter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParam ter	resourceVersi on	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParam ter	timeoutSecon ds	Timeout for the list/watch call.	false	integer	
PathParam eter	namespace	object name and auth scope, such as for teams and projects	true	string	

3.2.33.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.264, "v1.Status"

3.2.33.3. Consumes

- /

3.2.33.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.33.5. Tags

- apiv1

3.2.34. read the specified Event

GET /api/v1/namespaces/{namespace}/events/{name}

3.2.34.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParam eter	export	Should this value be exported. Export strips fields that a user can not specify.	false	boolean	
QueryParam eter	exact	Should the export be exact. Exact export maintains cluster-specific fields like 'Namespace'.	false	boolean	

Type	Name	Description	Required	Schema	Default
PathParamet er	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParamet er	name	name of the Event	true	string	

3.2.34.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.49, "v1.Event"

3.2.34.3. Consumes

- /

3.2.34.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.34.5. Tags

- apiv1

3.2.35. partially update the specified Event

PATCH /api/v1/namespaces/{namespace}/events/{name}

3.2.35.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParame ter	pretty	If 'true', then the output is pretty printed.	false	string	

Type	Name	Description	Required	Schema	Default
BodyParameter	body		true	Section 2.3.180, "v1.Patch"	
PathParamter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParamter	name	name of the Event	true	string	

3.2.35.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.49, "v1.Event"

3.2.35.3. Consumes

- application/json-patch+json
- application/merge-patch+json
- application/strategic-merge-patch+json

3.2.35.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.35.5. Tags

- apiv1

3.2.36. replace the specified Event

```
PUT /api/v1/namespaces/{namespace}/events/{name}
```

3.2.36.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParameter	body		true	Section 3.3.49 , "v1.Event"	
PathParamter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParamter	name	name of the Event	true	string	

3.2.36.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.49 , "v1.Event"

3.2.36.3. Consumes

- /

3.2.36.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.36.5. Tags

- apiv1

3.2.37. delete an Event

```
DELETE /api/v1/namespaces/{namespace}/events/{name}
```

3.2.37.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam ter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamet er	body		true	Section 2.3.6 1, "v1.DeleteOptions"	
QueryParam ter	gracePeriodS econds	The duration in seconds before the object should be deleted. Value must be non-negative integer. The value zero indicates delete immediately. If this value is nil, the default grace period for the specified type will be used. Defaults to a per object value if not specified. zero means delete immediately.	false	integer	

Type	Name	Description	Required	Schema	Default
QueryParam ter	orphanDepen dents	Deprecated: please use the PropagationP olicy, this field will be deprecated in 1.7. Should the dependent objects be orphaned. If true/false, the "orphan" finalizer will be added to/removed from the object's finalizers list. Either this field or PropagationP olicy may be set, but not both.	false	boolean	
QueryParam ter	propagationP olicy	Whether and how garbage collection will be performed. Either this field or OrphanDepen dents may be set, but not both. The default policy is decided by the existing finalizer set in the metadata.fin alizers and the resource- specific default policy.	false	string	

Type	Name	Description	Required	Schema	Default
PathParamet er	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParamet er	name	name of the Event	true	string	

3.2.37.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.264, "v1.Status"

3.2.37.3. Consumes

- /

3.2.37.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.37.5. Tags

- apiv1

3.2.38. list or watch objects of kind LimitRange

GET /api/v1/namespaces/{namespace}/limitranges

3.2.38.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParame ter	pretty	If 'true', then the output is pretty printed.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParam ter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParam ter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParam ter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParam eter	resourceVersion	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParam eter	timeoutSeconds	Timeout for the list/watch call.	false	integer	
PathParam eter	namespace	object name and auth scope, such as for teams and projects	true	string	

3.2.38.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.74 , “v1.LimitRangeList”

3.2.38.3. Consumes

- /

3.2.38.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf
- application/json;stream=watch
- application/vnd.kubernetes.protobuf;stream=watch

3.2.38.5. Tags

- apiv1

3.2.39. create a LimitRange

POST /api/v1/namespaces/{namespace}/limitranges

3.2.39.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParameter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParameter	body		true	Section 3.3.72 , “v1.LimitRange”	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	

3.2.39.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.72, "v1.LimitRange"

3.2.39.3. Consumes

- /

3.2.39.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.39.5. Tags

- apiv1

3.2.40. delete collection of LimitRange

DELETE /api/v1/namespaces/{namespace}/limitranges

3.2.40.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParameter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParameter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParam ter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParam ter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParamter	resourceVersion	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParamter	timeoutSeconds	Timeout for the list/watch call.	false	integer	
PathParamter	namespace	object name and auth scope, such as for teams and projects	true	string	

3.2.40.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.264, "v1.Status"

3.2.40.3. Consumes

- /

3.2.40.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.40.5. Tags

- apiv1

3.2.41. read the specified LimitRange

GET /api/v1/namespaces/{namespace}/limitranges/{name}

3.2.41.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParam eter	export	Should this value be exported. Export strips fields that a user can not specify.	false	boolean	
QueryParam eter	exact	Should the export be exact. Exact export maintains cluster-specific fields like 'Namespace'.	false	boolean	

Type	Name	Description	Required	Schema	Default
PathParamet er	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParamet er	name	name of the LimitRange	true	string	

3.2.41.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.72, "v1.LimitRange"

3.2.41.3. Consumes

- /

3.2.41.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.41.5. Tags

- apiv1

3.2.42. partially update the specified LimitRange

```
PATCH /api/v1/namespaces/{namespace}/limitranges/{name}
```

3.2.42.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParame ter	pretty	If 'true', then the output is pretty printed.	false	string	

Type	Name	Description	Required	Schema	Default
BodyParameter	body		true	Section 2.3.180 , "v1.Patch"	
PathParamter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParamter	name	name of the LimitRange	true	string	

3.2.42.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.72 , "v1.LimitRange"

3.2.42.3. Consumes

- application/json-patch+json
- application/merge-patch+json
- application/strategic-merge-patch+json

3.2.42.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.42.5. Tags

- apiv1

3.2.43. replace the specified LimitRange

```
PUT /api/v1/namespaces/{namespace}/limitranges/{name}
```

3.2.43.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParameter	body		true	Section 3.3.72 , "v1.LimitRange"	
PathParamter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParamter	name	name of the LimitRange	true	string	

3.2.43.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.72 , "v1.LimitRange"

3.2.43.3. Consumes

- /

3.2.43.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.43.5. Tags

- apiv1

3.2.44. delete a LimitRange

```
DELETE /api/v1/namespaces/{namespace}/limitranges/{name}
```

3.2.44.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam ter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamet er	body		true	Section 2.3.6 1, "v1.DeleteOptions"	
QueryParam ter	gracePeriodS econds	The duration in seconds before the object should be deleted. Value must be non-negative integer. The value zero indicates delete immediately. If this value is nil, the default grace period for the specified type will be used. Defaults to a per object value if not specified. zero means delete immediately.	false	integer	

Type	Name	Description	Required	Schema	Default
QueryParam eter	orphanDepen dents	Deprecated: please use the PropagationP olicy, this field will be deprecated in 1.7. Should the dependent objects be orphaned. If true/false, the "orphan" finalizer will be added to/removed from the object's finalizers list. Either this field or PropagationP olicy may be set, but not both.	false	boolean	
QueryParam eter	propagationP olicy	Whether and how garbage collection will be performed. Either this field or OrphanDepen dents may be set, but not both. The default policy is decided by the existing finalizer set in the metadata.fin alizers and the resource- specific default policy.	false	string	

Type	Name	Description	Required	Schema	Default
PathParamet er	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParamet er	name	name of the LimitRange	true	string	

3.2.44.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.264, "v1.Status"

3.2.44.3. Consumes

- /

3.2.44.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.44.5. Tags

- apiv1

3.2.45. list or watch objects of kind PersistentVolumeClaim

```
GET /api/v1/namespaces/{namespace}/persistentvolumeclaims
```

3.2.45.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParam ter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParam ter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParam ter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParam eter	resourceVersi on	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParam eter	timeoutSecon ds	Timeout for the list/watch call.	false	integer	
PathParamet er	namespace	object name and auth scope, such as for teams and projects	true	string	

3.2.45.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.105 , "v1.PersistentVolumeClaimList"

3.2.45.3. Consumes

- /

3.2.45.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf
- application/json;stream=watch
- application/vnd.kubernetes.protobuf;stream=watch

3.2.45.5. Tags

- apiv1

3.2.46. create a PersistentVolumeClaim

POST /api/v1/namespaces/{namespace}/persistentvolumeclaims

3.2.46.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParameter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParameter	body		true	Section 3.3.104 , "v1.PersistentVolumeClaim"	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	

3.2.46.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.104, "v1.PersistentVolumeClaim"

3.2.46.3. Consumes

- /

3.2.46.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.46.5. Tags

- apiv1

3.2.47. delete collection of PersistentVolumeClaim

```
DELETE /api/v1/namespaces/{namespace}/persistentvolumeclaims
```

3.2.47.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParam eter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParam ter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParam ter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParam ter	resourceVersi on	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParam ter	timeoutSecon ds	Timeout for the list/watch call.	false	integer	
PathParamet er	namespace	object name and auth scope, such as for teams and projects	true	string	

3.2.47.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.264, "v1.Status"

3.2.47.3. Consumes

- /

3.2.47.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.47.5. Tags

- apiv1

3.2.48. read the specified PersistentVolumeClaim

GET /api/v1/namespaces/{namespace}/persistentvolumeclaims/{name}

3.2.48.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParam eter	export	Should this value be exported. Export strips fields that a user can not specify.	false	boolean	
QueryParam eter	exact	Should the export be exact. Exact export maintains cluster-specific fields like 'Namespace'.	false	boolean	

Type	Name	Description	Required	Schema	Default
PathParamet er	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParamet er	name	name of the PersistentVolumeClaim	true	string	

3.2.48.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.104, "v1.PersistentVolumeClaim"

3.2.48.3. Consumes

- /

3.2.48.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.48.5. Tags

- apiv1

3.2.49. partially update the specified PersistentVolumeClaim

```
PATCH /api/v1/namespaces/{namespace}/persistentvolumeclaims/{name}
```

3.2.49.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParame ter	pretty	If 'true', then the output is pretty printed.	false	string	

Type	Name	Description	Required	Schema	Default
BodyParameter	body		true	Section 2.3.1 80, "v1.Patch"	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParameter	name	name of the PersistentVolumeClaim	true	string	

3.2.49.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.104, "v1.PersistentVolumeClaim"

3.2.49.3. Consumes

- application/json-patch+json
- application/merge-patch+json
- application/strategic-merge-patch+json

3.2.49.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.49.5. Tags

- apiv1

3.2.50. replace the specified PersistentVolumeClaim

```
PUT /api/v1/namespaces/{namespace}/persistentvolumeclaims/{name}
```

3.2.50.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParameter	body		true	Section 3.3.104 , "v1.PersistentVolumeClaim"	
PathParamter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParamter	name	name of the PersistentVolumeClaim	true	string	

3.2.50.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.104 , "v1.PersistentVolumeClaim"

3.2.50.3. Consumes

- /

3.2.50.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.50.5. Tags

- apiv1

3.2.51. delete a PersistentVolumeClaim

DELETE /api/v1/namespaces/{namespace}/persistentvolumeclaims/{name}

3.2.51.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamet er	body		true	Section 2.3.6 1, "v1.DeleteOptions"	
QueryParam eter	gracePeriodS econds	The duration in seconds before the object should be deleted. Value must be non-negative integer. The value zero indicates delete immediately. If this value is nil, the default grace period for the specified type will be used. Defaults to a per object value if not specified. zero means delete immediately.	false	integer	

Type	Name	Description	Required	Schema	Default
QueryParam ter	orphanDepen dents	Deprecated: please use the PropagationP olicy, this field will be deprecated in 1.7. Should the dependent objects be orphaned. If true/false, the "orphan" finalizer will be added to/removed from the object's finalizers list. Either this field or PropagationP olicy may be set, but not both.	false	boolean	
QueryParam ter	propagationP olicy	Whether and how garbage collection will be performed. Either this field or OrphanDepen dents may be set, but not both. The default policy is decided by the existing finalizer set in the metadata.fin alizers and the resource- specific default policy.	false	string	

Type	Name	Description	Required	Schema	Default
PathParamet er	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParamet er	name	name of the PersistentVolumeClaim	true	string	

3.2.51.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.264, "v1.Status"

3.2.51.3. Consumes

- /

3.2.51.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.51.5. Tags

- apiv1

3.2.52. read status of the specified PersistentVolumeClaim

```
GET /api/v1/namespaces/{namespace}/persistentvolumeclaims/{name}/status
```

3.2.52.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	

Type	Name	Description	Required	Schema	Default
PathParamet er	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParamet er	name	name of the PersistentVolumeClaim	true	string	

3.2.52.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.104, "v1.PersistentVolumeClaim"

3.2.52.3. Consumes

- /

3.2.52.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.52.5. Tags

- apiv1

3.2.53. partially update status of the specified PersistentVolumeClaim

```
PATCH /api/v1/namespaces/{namespace}/persistentvolumeclaims/{name}/status
```

3.2.53.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParame ter	pretty	If 'true', then the output is pretty printed.	false	string	

Type	Name	Description	Required	Schema	Default
BodyParameter	body		true	Section 2.3.180, "v1.Patch"	
PathParamter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParamter	name	name of the PersistentVolumeClaim	true	string	

3.2.53.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.104, "v1.PersistentVolumeClaim"

3.2.53.3. Consumes

- application/json-patch+json
- application/merge-patch+json
- application/strategic-merge-patch+json

3.2.53.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.53.5. Tags

- apiv1

3.2.54. replace status of the specified PersistentVolumeClaim

```
PUT /api/v1/namespaces/{namespace}/persistentvolumeclaims/{name}/status
```

3.2.54.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamet er	body		true	Section 3.3.104, "v1.PersistentVolumeClaim"	
PathParamet er	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParamet er	name	name of the PersistentVolumeClaim	true	string	

3.2.54.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.104, "v1.PersistentVolumeClaim"

3.2.54.3. Consumes

- /

3.2.54.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.54.5. Tags

- apiv1

3.2.55. list or watch objects of kind Pod

```
GET /api/v1/namespaces/{namespace}/pods
```

3.2.55.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParam eter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParam eter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParam eter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParam eter	resourceVersi on	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParam eter	timeoutSecon ds	Timeout for the list/watch call.	false	integer	
PathParamet er	namespace	object name and auth scope, such as for teams and projects	true	string	

3.2.55.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.118, “v1.PodList”

3.2.55.3. Consumes

- /

3.2.55.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf
- application/json;stream=watch
- application/vnd.kubernetes.protobuf;stream=watch

3.2.55.5. Tags

- apiv1

3.2.56. create a Pod

POST /api/v1/namespaces/{namespace}/pods

3.2.56.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamet er	body		true	Section 3.3.13, “v1.Pod”	
PathParamet er	namespace	object name and auth scope, such as for teams and projects	true	string	

3.2.56.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.113, "v1.Pod"

3.2.56.3. Consumes

- /

3.2.56.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.56.5. Tags

- apiv1

3.2.57. delete collection of Pod

DELETE /api/v1/namespaces/{namespace}/pods

3.2.57.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParam eter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParam eter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParam ter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParam ter	resourceVersi on	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParam ter	timeoutSecon ds	Timeout for the list/watch call.	false	integer	
PathParam eter	namespace	object name and auth scope, such as for teams and projects	true	string	

3.2.57.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.264, "v1.Status"

3.2.57.3. Consumes

- /

3.2.57.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.57.5. Tags

- apiv1

3.2.58. read the specified Pod

GET /api/v1/namespaces/{namespace}/pods/{name}

3.2.58.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParam eter	export	Should this value be exported. Export strips fields that a user can not specify.	false	boolean	
QueryParam eter	exact	Should the export be exact. Exact export maintains cluster-specific fields like 'Namespace'.	false	boolean	

Type	Name	Description	Required	Schema	Default
PathParamet er	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParamet er	name	name of the Pod	true	string	

3.2.58.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.113, "v1.Pod"

3.2.58.3. Consumes

- /

3.2.58.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.58.5. Tags

- apiv1

3.2.59. partially update the specified Pod

PATCH /api/v1/namespaces/{namespace}/pods/{name}

3.2.59.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParame ter	pretty	If 'true', then the output is pretty printed.	false	string	

Type	Name	Description	Required	Schema	Default
BodyParameter	body		true	Section 2.3.180, "v1.Patch"	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParameter	name	name of the Pod	true	string	

3.2.59.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.113, "v1.Pod"

3.2.59.3. Consumes

- application/json-patch+json
- application/merge-patch+json
- application/strategic-merge-patch+json

3.2.59.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.59.5. Tags

- apiv1

3.2.60. replace the specified Pod

```
PUT /api/v1/namespaces/{namespace}/pods/{name}
```

3.2.60.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParameter	body		true	Section 3.3.13, “v1.Pod”	
PathParamter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParamter	name	name of the Pod	true	string	

3.2.60.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.113, “v1.Pod”

3.2.60.3. Consumes

- /

3.2.60.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.60.5. Tags

- apiv1

3.2.61. delete a Pod

```
DELETE /api/v1/namespaces/{namespace}/pods/{name}
```

3.2.61.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParameter	body		true	Section 2.3.6 1, "v1.DeleteOptions"	
QueryParamter	gracePeriodSeconds	The duration in seconds before the object should be deleted. Value must be non-negative integer. The value zero indicates delete immediately. If this value is nil, the default grace period for the specified type will be used. Defaults to a per object value if not specified. zero means delete immediately.	false	integer	

Type	Name	Description	Required	Schema	Default
QueryParam ter	orphanDepen dents	Deprecated: please use the PropagationP olicy, this field will be deprecated in 1.7. Should the dependent objects be orphaned. If true/false, the "orphan" finalizer will be added to/removed from the object's finalizers list. Either this field or PropagationP olicy may be set, but not both.	false	boolean	
QueryParam ter	propagationP olicy	Whether and how garbage collection will be performed. Either this field or OrphanDepen dents may be set, but not both. The default policy is decided by the existing finalizer set in the metadata.fin alizers and the resource- specific default policy.	false	string	

Type	Name	Description	Required	Schema	Default
PathParamet er	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParamet er	name	name of the Pod	true	string	

3.2.61.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.264, "v1.Status"

3.2.61.3. Consumes

- /

3.2.61.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.61.5. Tags

- apiv1

3.2.62. connect GET requests to attach of Pod

GET /api/v1/namespaces/{namespace}/pods/{name}/attach

3.2.62.1. Parameters

Type	Name	Description	Required	Schema	Default
------	------	-------------	----------	--------	---------

Type	Name	Description	Required	Schema	Default
QueryParam ter	stdin	Stdin if true, redirects the standard input stream of the pod for this call. Defaults to false.	false	boolean	
QueryParam ter	stdout	Stdout if true indicates that stdout is to be redirected for the attach call. Defaults to true.	false	boolean	
QueryParam ter	stderr	Stderr if true indicates that stderr is to be redirected for the attach call. Defaults to true.	false	boolean	
QueryParam ter	tty	TTY if true indicates that a tty will be allocated for the attach call. This is passed through the container runtime so the tty is allocated on the worker node by the container runtime. Defaults to false.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParam ter	container	The container in which to execute the command. Defaults to only container if there is only one container in the pod.	false	string	
PathParam er	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParam er	name	name of the Pod	true	string	

3.2.62.2. Responses

HTTP Code	Description	Schema
default	success	string

3.2.62.3. Consumes

- /

3.2.62.4. Produces

- /

3.2.62.5. Tags

- apiv1

3.2.63. connect POST requests to attach of Pod

POST /api/v1/namespaces/{namespace}/pods/{name}/attach

3.2.63.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParameter	stdin	Stdin if true, redirects the standard input stream of the pod for this call. Defaults to false.	false	boolean	
QueryParameter	stdout	Stdout if true indicates that stdout is to be redirected for the attach call. Defaults to true.	false	boolean	
QueryParameter	stderr	Stderr if true indicates that stderr is to be redirected for the attach call. Defaults to true.	false	boolean	
QueryParameter	tty	TTY if true indicates that a tty will be allocated for the attach call. This is passed through the container runtime so the tty is allocated on the worker node by the container runtime. Defaults to false.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParamter	container	The container in which to execute the command. Defaults to only container if there is only one container in the pod.	false	string	
PathParamter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParamter	name	name of the Pod	true	string	

3.2.63.2. Responses

HTTP Code	Description	Schema
default	success	string

3.2.63.3. Consumes

- /

3.2.63.4. Produces

- /

3.2.63.5. Tags

- apiv1

3.2.64. create binding of a Binding

POST /api/v1/namespaces/{namespace}/pods/{name}/binding

3.2.64.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParameter	body		true	Section 3.3.10 , "v1.Binding"	
PathParamter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParamter	name	name of the Binding	true	string	

3.2.64.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.10 , "v1.Binding"

3.2.64.3. Consumes

- /

3.2.64.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.64.5. Tags

- apiv1

3.2.65. create eviction of an Eviction

```
POST /api/v1/namespaces/{namespace}/pods/{name}/eviction
```

3.2.65.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParameter	body		true	Section 3.3.181 , "v1beta1.Eviction"	
PathParamter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParamter	name	name of the Eviction	true	string	

3.2.65.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.181 , "v1beta1.Eviction"

3.2.65.3. Consumes

- /

3.2.65.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.65.5. Tags

- apiv1

3.2.66. connect GET requests to exec of Pod

GET /api/v1/namespaces/{namespace}/pods/{name}/exec

3.2.66.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParameter	stdin	Redirect the standard input stream of the pod for this call. Defaults to false.	false	boolean	
QueryParameter	stdout	Redirect the standard output stream of the pod for this call. Defaults to true.	false	boolean	
QueryParameter	stderr	Redirect the standard error stream of the pod for this call. Defaults to true.	false	boolean	
QueryParameter	tty	TTY if true indicates that a tty will be allocated for the exec call. Defaults to false.	false	boolean	
QueryParameter	container	Container in which to execute the command. Defaults to only container if there is only one container in the pod.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParamter	command	Command is the remote command to execute. argv array. Not executed within a shell.	false	string	
PathParamter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParamter	name	name of the Pod	true	string	

3.2.66.2. Responses

HTTP Code	Description	Schema
default	success	string

3.2.66.3. Consumes

- /

3.2.66.4. Produces

- /

3.2.66.5. Tags

- apiv1

3.2.67. connect POST requests to exec of Pod

POST /api/v1/namespaces/{namespace}/pods/{name}/exec

3.2.67.1. Parameters

Type	Name	Description	Required	Schema	Default
------	------	-------------	----------	--------	---------

Type	Name	Description	Required	Schema	Default
QueryParameter	stdin	Redirect the standard input stream of the pod for this call. Defaults to false.	false	boolean	
QueryParameter	stdout	Redirect the standard output stream of the pod for this call. Defaults to true.	false	boolean	
QueryParameter	stderr	Redirect the standard error stream of the pod for this call. Defaults to true.	false	boolean	
QueryParameter	tty	TTY if true indicates that a tty will be allocated for the exec call. Defaults to false.	false	boolean	
QueryParameter	container	Container in which to execute the command. Defaults to only container if there is only one container in the pod.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParam eter	command	Command is the remote command to execute. argv array. Not executed within a shell.	false	string	
PathParam eter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParam eter	name	name of the Pod	true	string	

3.2.67.2. Responses

HTTP Code	Description	Schema
default	success	string

3.2.67.3. Consumes

- /

3.2.67.4. Produces

- /

3.2.67.5. Tags

- apiv1

3.2.68. read log of the specified Pod

```
GET /api/v1/namespaces/{namespace}/pods/{name}/log
```

3.2.68.1. Parameters

Type	Name	Description	Required	Schema	Default
------	------	-------------	----------	--------	---------

Type	Name	Description	Required	Schema	Default
QueryParamter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamter	container	The container for which to stream logs. Defaults to only container if there is one container in the pod.	false	string	
QueryParamter	follow	Follow the log stream of the pod. Defaults to false.	false	boolean	
QueryParamter	previous	Return previous terminated container logs. Defaults to false.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParam eter	sinceSeconds	A relative time in seconds before the current time from which to show logs. If this value precedes the time a pod was started, only logs since the pod start will be returned. If this value is in the future, no logs will be returned. Only one of sinceSeconds or sinceTime may be specified.	false	integer	
QueryParam eter	timestamps	If true, add an RFC3339 or RFC3339Nano timestamp at the beginning of every line of log output. Defaults to false.	false	boolean	
QueryParam eter	tailLines	If set, the number of lines from the end of the logs to show. If not specified, logs are shown from the creation of the container or sinceSeconds or sinceTime	false	integer	

Type	Name	Description	Required	Schema	Default
QueryParam eter	limitBytes	If set, the number of bytes to read from the server before terminating the log output. This may not display a complete final line of logging, and may return slightly more or slightly less than the specified limit.	false	integer	
PathParam eter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParam eter	name	name of the Pod	true	string	

3.2.68.2. Responses

HTTP Code	Description	Schema
200	success	string

3.2.68.3. Consumes

- /

3.2.68.4. Produces

- text/plain
- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.68.5. Tags

- apiv1

3.2.69. connect GET requests to portforward of Pod

GET /api/v1/namespaces/{namespace}/pods/{name}/portforward

3.2.69.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	ports	List of ports to forward Required when using WebSockets	false	integer	
PathParamet er	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParamet er	name	name of the Pod	true	string	

3.2.69.2. Responses

HTTP Code	Description	Schema
default	success	string

3.2.69.3. Consumes

- /

3.2.69.4. Produces

- /

3.2.69.5. Tags

- apiv1

3.2.70. connect POST requests to portforward of Pod

POST /api/v1/namespaces/{namespace}/pods/{name}/portforward

3.2.70.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamter	ports	List of ports to forward Required when using WebSockets	false	integer	
PathParamter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParamter	name	name of the Pod	true	string	

3.2.70.2. Responses

HTTP Code	Description	Schema
default	success	string

3.2.70.3. Consumes

- /

3.2.70.4. Produces

- /

3.2.70.5. Tags

- apiv1

3.2.71. connect GET requests to proxy of Pod

```
GET /api/v1/namespaces/{namespace}/pods/{name}/proxy
```

3.2.71.1. Parameters

Type	Name	Description	Required	Schema	Default
------	------	-------------	----------	--------	---------

Type	Name	Description	Required	Schema	Default
QueryParamter	path	Path is the URL path to use for the current proxy request to pod.	false	string	
PathParamter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParamter	name	name of the Pod	true	string	

3.2.71.2. Responses

HTTP Code	Description	Schema
default	success	string

3.2.71.3. Consumes

- /

3.2.71.4. Produces

- /

3.2.71.5. Tags

- apiv1

3.2.72. connect OPTIONS requests to proxy of Pod

```
OPTIONS /api/v1/namespaces/{namespace}/pods/{name}/proxy
```

3.2.72.1. Parameters

Type	Name	Description	Required	Schema	Default
------	------	-------------	----------	--------	---------

Type	Name	Description	Required	Schema	Default
QueryParam ter	path	Path is the URL path to use for the current proxy request to pod.	false	string	
PathParam er	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParam er	name	name of the Pod	true	string	

3.2.72.2. Responses

HTTP Code	Description	Schema
default	success	string

3.2.72.3. Consumes

- /

3.2.72.4. Produces

- /

3.2.72.5. Tags

- apiv1

3.2.73. connect POST requests to proxy of Pod

POST /api/v1/namespaces/{namespace}/pods/{name}/proxy

3.2.73.1. Parameters

Type	Name	Description	Required	Schema	Default
------	------	-------------	----------	--------	---------

Type	Name	Description	Required	Schema	Default
QueryParamter	path	Path is the URL path to use for the current proxy request to pod.	false	string	
PathParamter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParamter	name	name of the Pod	true	string	

3.2.73.2. Responses

HTTP Code	Description	Schema
default	success	string

3.2.73.3. Consumes

- /

3.2.73.4. Produces

- /

3.2.73.5. Tags

- apiv1

3.2.74. connect HEAD requests to proxy of Pod

HEAD /api/v1/namespaces/{namespace}/pods/{name}/proxy

3.2.74.1. Parameters

Type	Name	Description	Required	Schema	Default
------	------	-------------	----------	--------	---------

Type	Name	Description	Required	Schema	Default
QueryParam ter	path	Path is the URL path to use for the current proxy request to pod.	false	string	
PathParam er	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParam er	name	name of the Pod	true	string	

3.2.74.2. Responses

HTTP Code	Description	Schema
default	success	string

3.2.74.3. Consumes

- /

3.2.74.4. Produces

- /

3.2.74.5. Tags

- apiv1

3.2.75. connect PUT requests to proxy of Pod

```
PUT /api/v1/namespaces/{namespace}/pods/{name}/proxy
```

3.2.75.1. Parameters

Type	Name	Description	Required	Schema	Default
------	------	-------------	----------	--------	---------

Type	Name	Description	Required	Schema	Default
QueryParamter	path	Path is the URL path to use for the current proxy request to pod.	false	string	
PathParamter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParamter	name	name of the Pod	true	string	

3.2.75.2. Responses

HTTP Code	Description	Schema
default	success	string

3.2.75.3. Consumes

- /

3.2.75.4. Produces

- /

3.2.75.5. Tags

- apiv1

3.2.76. connect DELETE requests to proxy of Pod

```
DELETE /api/v1/namespaces/{namespace}/pods/{name}/proxy
```

3.2.76.1. Parameters

Type	Name	Description	Required	Schema	Default
------	------	-------------	----------	--------	---------

Type	Name	Description	Required	Schema	Default
QueryParam ter	path	Path is the URL path to use for the current proxy request to pod.	false	string	
PathParam er	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParam er	name	name of the Pod	true	string	

3.2.76.2. Responses

HTTP Code	Description	Schema
default	success	string

3.2.76.3. Consumes

- /

3.2.76.4. Produces

- /

3.2.76.5. Tags

- apiv1

3.2.77. connect GET requests to proxy of Pod

```
GET /api/v1/namespaces/{namespace}/pods/{name}/proxy/{path}
```

3.2.77.1. Parameters

Type	Name	Description	Required	Schema	Default
------	------	-------------	----------	--------	---------

Type	Name	Description	Required	Schema	Default
QueryParamter	path	Path is the URL path to use for the current proxy request to pod.	false	string	
PathParamter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParamter	name	name of the Pod	true	string	
PathParamter	path	path to the resource	true	string	

3.2.77.2. Responses

HTTP Code	Description	Schema
default	success	string

3.2.77.3. Consumes

- /

3.2.77.4. Produces

- /

3.2.77.5. Tags

- apiv1

3.2.78. connect OPTIONS requests to proxy of Pod

```
OPTIONS /api/v1/namespaces/{namespace}/pods/{name}/proxy/{path}
```

3.2.78.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamter	path	Path is the URL path to use for the current proxy request to pod.	false	string	
PathParamter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParamter	name	name of the Pod	true	string	
PathParamter	path	path to the resource	true	string	

3.2.78.2. Responses

HTTP Code	Description	Schema
default	success	string

3.2.78.3. Consumes

- /

3.2.78.4. Produces

- /

3.2.78.5. Tags

- apiv1

3.2.79. connect POST requests to proxy of Pod

```
POST /api/v1/namespaces/{namespace}/pods/{name}/proxy/{path}
```

3.2.79.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamter	path	Path is the URL path to use for the current proxy request to pod.	false	string	
PathParamter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParamter	name	name of the Pod	true	string	
PathParamter	path	path to the resource	true	string	

3.2.79.2. Responses

HTTP Code	Description	Schema
default	success	string

3.2.79.3. Consumes

- /

3.2.79.4. Produces

- /

3.2.79.5. Tags

- apiv1

3.2.80. connect HEAD requests to proxy of Pod

```
HEAD /api/v1/namespaces/{namespace}/pods/{name}/proxy/{path}
```

3.2.80.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamter	path	Path is the URL path to use for the current proxy request to pod.	false	string	
PathParamter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParamter	name	name of the Pod	true	string	
PathParamter	path	path to the resource	true	string	

3.2.80.2. Responses

HTTP Code	Description	Schema
default	success	string

3.2.80.3. Consumes

- /

3.2.80.4. Produces

- /

3.2.80.5. Tags

- apiv1

3.2.81. connect PUT requests to proxy of Pod

```
PUT /api/v1/namespaces/{namespace}/pods/{name}/proxy/{path}
```

3.2.81.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamter	path	Path is the URL path to use for the current proxy request to pod.	false	string	
PathParamter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParamter	name	name of the Pod	true	string	
PathParamter	path	path to the resource	true	string	

3.2.81.2. Responses

HTTP Code	Description	Schema
default	success	string

3.2.81.3. Consumes

- /

3.2.81.4. Produces

- /

3.2.81.5. Tags

- apiv1

3.2.82. connect DELETE requests to proxy of Pod

```
DELETE /api/v1/namespaces/{namespace}/pods/{name}/proxy/{path}
```

3.2.82.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamter	path	Path is the URL path to use for the current proxy request to pod.	false	string	
PathParamter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParamter	name	name of the Pod	true	string	
PathParamter	path	path to the resource	true	string	

3.2.82.2. Responses

HTTP Code	Description	Schema
default	success	string

3.2.82.3. Consumes

- /

3.2.82.4. Produces

- /

3.2.82.5. Tags

- apiv1

3.2.83. read status of the specified Pod

```
GET /api/v1/namespaces/{namespace}/pods/{name}/status
```

3.2.83.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamter	pretty	If 'true', then the output is pretty printed.	false	string	
PathParamter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParamter	name	name of the Pod	true	string	

3.2.83.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.113, "v1.Pod"

3.2.83.3. Consumes

- /

3.2.83.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.83.5. Tags

- apiv1

3.2.84. partially update status of the specified Pod

```
PATCH /api/v1/namespaces/{namespace}/pods/{name}/status
```

3.2.84.1. Parameters

Type	Name	Description	Required	Schema	Default
------	------	-------------	----------	--------	---------

Type	Name	Description	Required	Schema	Default
QueryParamter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParameter	body		true	Section 2.3.180 , "v1.Patch"	
PathParamter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParamter	name	name of the Pod	true	string	

3.2.84.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.113 , "v1.Pod"

3.2.84.3. Consumes

- application/json-patch+json
- application/merge-patch+json
- application/strategic-merge-patch+json

3.2.84.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.84.5. Tags

- apiv1

3.2.85. replace status of the specified Pod

```
PUT /api/v1/namespaces/{namespace}/pods/{name}/status
```

3.2.85.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamenter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParameter	body		true	Section 3.3.113, "v1.Pod"	
PathParamenter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParamenter	name	name of the Pod	true	string	

3.2.85.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.113, "v1.Pod"

3.2.85.3. Consumes

- /

3.2.85.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.85.5. Tags

- apiv1

3.2.86. list or watch objects of kind PodTemplate

```
GET /api/v1/namespaces/{namespace}/podtemplates
```

3.2.86.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam ter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParam ter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParam ter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParam ter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParam eter	resourceVersi on	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParam eter	timeoutSecon ds	Timeout for the list/watch call.	false	integer	
PathParamet er	namespace	object name and auth scope, such as for teams and projects	true	string	

3.2.86.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.123 , "v1.PodTemplateList"

3.2.86.3. Consumes

- /

3.2.86.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf
- application/json;stream=watch
- application/vnd.kubernetes.protobuf;stream=watch

3.2.86.5. Tags

- apiv1

3.2.87. create a PodTemplate

POST /api/v1/namespaces/{namespace}/podtemplates

3.2.87.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParameter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParameter	body		true	Section 3.3.122 , "v1.PodTemplate"	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	

3.2.87.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.122, "v1.PodTemplate"

3.2.87.3. Consumes

- /

3.2.87.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.87.5. Tags

- apiv1

3.2.88. delete collection of PodTemplate

DELETE /api/v1/namespaces/{namespace}/podtemplates

3.2.88.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParameter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParameter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParam ter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParam ter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParam eter	resourceVersi on	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParam eter	timeoutSecon ds	Timeout for the list/watch call.	false	integer	
PathParamet er	namespace	object name and auth scope, such as for teams and projects	true	string	

3.2.88.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.264, "v1.Status"

3.2.88.3. Consumes

- /

3.2.88.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.88.5. Tags

- apiv1

3.2.89. read the specified PodTemplate

GET /api/v1/namespaces/{namespace}/podtemplates/{name}

3.2.89.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParam eter	export	Should this value be exported. Export strips fields that a user can not specify.	false	boolean	
QueryParam eter	exact	Should the export be exact. Exact export maintains cluster-specific fields like 'Namespace'.	false	boolean	

Type	Name	Description	Required	Schema	Default
PathParamet er	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParamet er	name	name of the PodTemplate	true	string	

3.2.89.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.122, "v1.PodTemplate"

3.2.89.3. Consumes

- /

3.2.89.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.89.5. Tags

- apiv1

3.2.90. partially update the specified PodTemplate

```
PATCH /api/v1/namespaces/{namespace}/podtemplates/{name}
```

3.2.90.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParame ter	pretty	If 'true', then the output is pretty printed.	false	string	

Type	Name	Description	Required	Schema	Default
BodyParameter	body		true	Section 2.3.180 , "v1.Patch"	
PathParamter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParamter	name	name of the PodTemplate	true	string	

3.2.90.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.122 , "v1.PodTemplate"

3.2.90.3. Consumes

- application/json-patch+json
- application/merge-patch+json
- application/strategic-merge-patch+json

3.2.90.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.90.5. Tags

- apiv1

3.2.91. replace the specified PodTemplate

```
PUT /api/v1/namespaces/{namespace}/podtemplates/{name}
```

3.2.91.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParameter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParameter	body		true	Section 3.3.122 , "v1.PodTemplate"	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParameter	name	name of the PodTemplate	true	string	

3.2.91.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.122 , "v1.PodTemplate"

3.2.91.3. Consumes

- /

3.2.91.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.91.5. Tags

- apiv1

3.2.92. delete a PodTemplate

```
DELETE /api/v1/namespaces/{namespace}/podtemplates/{name}
```

3.2.92.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamet er	body		true	Section 2.3.6 1, "v1.DeleteOptions"	
QueryParam eter	gracePeriodS econds	The duration in seconds before the object should be deleted. Value must be non-negative integer. The value zero indicates delete immediately. If this value is nil, the default grace period for the specified type will be used. Defaults to a per object value if not specified. zero means delete immediately.	false	integer	

Type	Name	Description	Required	Schema	Default
QueryParam eter	orphanDepen dents	Deprecated: please use the PropagationP olicy, this field will be deprecated in 1.7. Should the dependent objects be orphaned. If true/false, the "orphan" finalizer will be added to/removed from the object's finalizers list. Either this field or PropagationP olicy may be set, but not both.	false	boolean	
QueryParam eter	propagationP olicy	Whether and how garbage collection will be performed. Either this field or OrphanDepen dents may be set, but not both. The default policy is decided by the existing finalizer set in the metadata.fin alizers and the resource- specific default policy.	false	string	

Type	Name	Description	Required	Schema	Default
PathParamet er	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParamet er	name	name of the PodTemplate	true	string	

3.2.92.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.264, "v1.Status"

3.2.92.3. Consumes

- /

3.2.92.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.92.5. Tags

- apiv1

3.2.93. list or watch objects of kind ReplicationController

GET /api/v1/namespaces/{namespace}/replicationcontrollers

3.2.93.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParam ter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParam ter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParam ter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParam ter	resourceVersi on	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParam ter	timeoutSecon ds	Timeout for the list/watch call.	false	integer	
PathParamet er	namespace	object name and auth scope, such as for teams and projects	true	string	

3.2.93.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.134, "v1.ReplicationControllerList"

3.2.93.3. Consumes

- /

3.2.93.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf
- application/json;stream=watch
- application/vnd.kubernetes.protobuf;stream=watch

3.2.93.5. Tags

- apiv1

3.2.94. create a ReplicationController

POST /api/v1/namespaces/{namespace}/replicationcontrollers

3.2.94.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParameter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParameter	body		true	Section 3.3.132, "v1.ReplicationController"	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	

3.2.94.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.132, "v1.ReplicationController"

3.2.94.3. Consumes

- /

3.2.94.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.94.5. Tags

- apiv1

3.2.95. delete collection of ReplicationController

```
DELETE /api/v1/namespaces/{namespace}/replicationcontrollers
```

3.2.95.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParam eter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParam ter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParam ter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParam eter	resourceVersi on	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParam eter	timeoutSecon ds	Timeout for the list/watch call.	false	integer	
PathParamet er	namespace	object name and auth scope, such as for teams and projects	true	string	

3.2.95.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.264, "v1.Status"

3.2.95.3. Consumes

- /

3.2.95.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.95.5. Tags

- apiv1

3.2.96. read the specified ReplicationController

GET /api/v1/namespaces/{namespace}/replicationcontrollers/{name}

3.2.96.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParam eter	export	Should this value be exported. Export strips fields that a user can not specify.	false	boolean	
QueryParam eter	exact	Should the export be exact. Exact export maintains cluster-specific fields like 'Namespace'.	false	boolean	

Type	Name	Description	Required	Schema	Default
PathParamet er	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParamet er	name	name of the ReplicationCo ntroller	true	string	

3.2.96.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.132, "v1.ReplicationController"

3.2.96.3. Consumes

- /

3.2.96.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.96.5. Tags

- apiv1

3.2.97. partially update the specified ReplicationController

```
PATCH /api/v1/namespaces/{namespace}/replicationcontrollers/{name}
```

3.2.97.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParame ter	pretty	If 'true', then the output is pretty printed.	false	string	

Type	Name	Description	Required	Schema	Default
BodyParameter	body		true	Section 2.3.180 , "v1.Patch"	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParameter	name	name of the ReplicationController	true	string	

3.2.97.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.132 , "v1.ReplicationController"

3.2.97.3. Consumes

- application/json-patch+json
- application/merge-patch+json
- application/strategic-merge-patch+json

3.2.97.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.97.5. Tags

- apiv1

3.2.98. replace the specified ReplicationController

```
PUT /api/v1/namespaces/{namespace}/replicationcontrollers/{name}
```

3.2.98.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParameter	body		true	Section 3.3.132 , "v1.ReplicationController"	
PathParamter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParamter	name	name of the ReplicationController	true	string	

3.2.98.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.132 , "v1.ReplicationController"

3.2.98.3. Consumes

- /

3.2.98.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.98.5. Tags

- apiv1

3.2.99. delete a ReplicationController

```
DELETE /api/v1/namespaces/{namespace}/replicationcontrollers/{name}
```

3.2.99.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamet er	body		true	Section 2.3.6 1, "v1.DeleteOptions"	
QueryParam eter	gracePeriodS econds	The duration in seconds before the object should be deleted. Value must be non-negative integer. The value zero indicates delete immediately. If this value is nil, the default grace period for the specified type will be used. Defaults to a per object value if not specified. zero means delete immediately.	false	integer	

Type	Name	Description	Required	Schema	Default
QueryParam eter	orphanDepen dents	Deprecated: please use the PropagationP olicy, this field will be deprecated in 1.7. Should the dependent objects be orphaned. If true/false, the "orphan" finalizer will be added to/removed from the object's finalizers list. Either this field or PropagationP olicy may be set, but not both.	false	boolean	
QueryParam eter	propagationP olicy	Whether and how garbage collection will be performed. Either this field or OrphanDepen dents may be set, but not both. The default policy is decided by the existing finalizer set in the metadata.fin alizers and the resource- specific default policy.	false	string	

Type	Name	Description	Required	Schema	Default
PathParamet er	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParamet er	name	name of the ReplicationController	true	string	

3.2.99.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.264, "v1.Status"

3.2.99.3. Consumes

- /

3.2.99.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.99.5. Tags

- apiv1

3.2.100. read scale of the specified Scale

GET /api/v1/namespaces/{namespace}/replicationcontrollers/{name}/scale

3.2.100.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	

Type	Name	Description	Required	Schema	Default
PathParamet er	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParamet er	name	name of the Scale	true	string	

3.2.100.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.147, "v1.Scale"

3.2.100.3. Consumes

- /

3.2.100.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.100.5. Tags

- apiv1

3.2.101. partially update scale of the specified Scale

PATCH /api/v1/namespaces/{namespace}/replicationcontrollers/{name}/scale

3.2.101.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	

Type	Name	Description	Required	Schema	Default
BodyParameter	body		true	Section 2.3.180, "v1.Patch"	
PathParamter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParamter	name	name of the Scale	true	string	

3.2.101.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.147, "v1.Scale"

3.2.101.3. Consumes

- application/json-patch+json
- application/merge-patch+json
- application/strategic-merge-patch+json

3.2.101.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.101.5. Tags

- apiv1

3.2.102. replace scale of the specified Scale

```
PUT /api/v1/namespaces/{namespace}/replicationcontrollers/{name}/scale
```

3.2.102.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParameter	body		true	Section 3.3.147, "v1.Scale"	
PathParamter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParamter	name	name of the Scale	true	string	

3.2.102.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.147, "v1.Scale"

3.2.102.3. Consumes

- /

3.2.102.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.102.5. Tags

- apiv1

3.2.103. read status of the specified ReplicationController

```
GET /api/v1/namespaces/{namespace}/replicationcontrollers/{name}/status
```

3.2.103.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
PathParam er	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParam er	name	name of the ReplicationCo ntroller	true	string	

3.2.103.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.132, "v1.ReplicationController"

3.2.103.3. Consumes

- /

3.2.103.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.103.5. Tags

- apiv1

3.2.104. partially update status of the specified ReplicationController

PATCH /api/v1/namespaces/{namespace}/replicationcontrollers/{name}/status

3.2.104.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParameter	body		true	Section 2.3.1 80, "v1.Patch"	
PathParamter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParamter	name	name of the ReplicationController	true	string	

3.2.104.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.132, "v1.ReplicationController"

3.2.104.3. Consumes

- application/json-patch+json
- application/merge-patch+json
- application/strategic-merge-patch+json

3.2.104.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.104.5. Tags

- apiv1

3.2.105. replace status of the specified ReplicationController

PUT /api/v1/namespaces/{namespace}/replicationcontrollers/{name}/status

3.2.105.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParameter	body		true	Section 3.3.132 , "v1.ReplicationController"	
PathParamter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParamter	name	name of the ReplicationController	true	string	

3.2.105.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.132 , "v1.ReplicationController"

3.2.105.3. Consumes

- /

3.2.105.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.105.5. Tags

- apiv1

3.2.106. list or watch objects of kind ResourceQuota

GET /api/v1/namespaces/{namespace}/resourcequotas

3.2.106.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParam eter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParam eter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParam eter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParamter	resourceVersion	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParamter	timeoutSeconds	Timeout for the list/watch call.	false	integer	
PathParamter	namespace	object name and auth scope, such as for teams and projects	true	string	

3.2.106.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.139, "v1.ResourceQuotaList"

3.2.106.3. Consumes

- /

3.2.106.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf
- application/json;stream=watch
- application/vnd.kubernetes.protobuf;stream=watch

3.2.106.5. Tags

- apiv1

3.2.107. create a ResourceQuota

POST /api/v1/namespaces/{namespace}/resourcequotas

3.2.107.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamenter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParameter	body		true	Section 3.3.138, "v1.ResourceQuota"	
PathParamenter	namespace	object name and auth scope, such as for teams and projects	true	string	

3.2.107.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.138, "v1.ResourceQuota"

3.2.107.3. Consumes

- /

3.2.107.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.107.5. Tags

- apiv1

3.2.108. delete collection of ResourceQuota

DELETE /api/v1/namespaces/{namespace}/resourcequotas

3.2.108.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParam eter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParam ter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParam ter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParamter	resourceVersion	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParamter	timeoutSeconds	Timeout for the list/watch call.	false	integer	
PathParamter	namespace	object name and auth scope, such as for teams and projects	true	string	

3.2.108.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.264, "v1.Status"

3.2.108.3. Consumes

- /

3.2.108.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.108.5. Tags

- apiv1

3.2.109. read the specified ResourceQuota

GET /api/v1/namespaces/{namespace}/resourcequotas/{name}

3.2.109.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParam eter	export	Should this value be exported. Export strips fields that a user can not specify.	false	boolean	
QueryParam eter	exact	Should the export be exact. Exact export maintains cluster-specific fields like 'Namespace'.	false	boolean	

Type	Name	Description	Required	Schema	Default
PathParamet er	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParamet er	name	name of the ResourceQuota	true	string	

3.2.109.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.138, "v1.ResourceQuota"

3.2.109.3. Consumes

- /

3.2.109.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.109.5. Tags

- apiv1

3.2.110. partially update the specified ResourceQuota

PATCH /api/v1/namespaces/{namespace}/resourcequotas/{name}

3.2.110.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParame ter	pretty	If 'true', then the output is pretty printed.	false	string	

Type	Name	Description	Required	Schema	Default
BodyParameter	body		true	Section 2.3.180 , "v1.Patch"	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParameter	name	name of the ResourceQuota	true	string	

3.2.110.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.138 , "v1.ResourceQuota"

3.2.110.3. Consumes

- application/json-patch+json
- application/merge-patch+json
- application/strategic-merge-patch+json

3.2.110.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.110.5. Tags

- apiv1

3.2.111. replace the specified ResourceQuota

```
PUT /api/v1/namespaces/{namespace}/resourcequotas/{name}
```

3.2.111.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParameter	body		true	Section 3.3.138 , "v1.ResourceQuota"	
PathParamter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParamter	name	name of the ResourceQuota	true	string	

3.2.111.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.138 , "v1.ResourceQuota"

3.2.111.3. Consumes

- /

3.2.111.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.111.5. Tags

- apiv1

3.2.112. delete a ResourceQuota

```
DELETE /api/v1/namespaces/{namespace}/resourcequotas/{name}
```

3.2.112.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam ter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamet er	body		true	Section 2.3.6 1 , "v1.DeleteOp tions"	
QueryParam ter	gracePeriodS econds	The duration in seconds before the object should be deleted. Value must be non-negative integer. The value zero indicates delete immediately. If this value is nil, the default grace period for the specified type will be used. Defaults to a per object value if not specified. zero means delete immediately.	false	integer	

Type	Name	Description	Required	Schema	Default
QueryParam ter	orphanDepen dents	Deprecated: please use the PropagationP olicy, this field will be deprecated in 1.7. Should the dependent objects be orphaned. If true/false, the "orphan" finalizer will be added to/removed from the object's finalizers list. Either this field or PropagationP olicy may be set, but not both.	false	boolean	
QueryParam ter	propagationP olicy	Whether and how garbage collection will be performed. Either this field or OrphanDepen dents may be set, but not both. The default policy is decided by the existing finalizer set in the metadata.fin alizers and the resource- specific default policy.	false	string	

Type	Name	Description	Required	Schema	Default
PathParamet er	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParamet er	name	name of the ResourceQuota	true	string	

3.2.112.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.264, "v1.Status"

3.2.112.3. Consumes

- /

3.2.112.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.112.5. Tags

- apiv1

3.2.113. read status of the specified ResourceQuota

```
GET /api/v1/namespaces/{namespace}/resourcequotas/{name}/status
```

3.2.113.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParame ter	pretty	If 'true', then the output is pretty printed.	false	string	

Type	Name	Description	Required	Schema	Default
PathParamet er	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParamet er	name	name of the ResourceQuota	true	string	

3.2.113.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.138, "v1.ResourceQuota"

3.2.113.3. Consumes

- /

3.2.113.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.113.5. Tags

- apiv1

3.2.114. partially update status of the specified ResourceQuota

```
PATCH /api/v1/namespaces/{namespace}/resourcequotas/{name}/status
```

3.2.114.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParame ter	pretty	If 'true', then the output is pretty printed.	false	string	

Type	Name	Description	Required	Schema	Default
BodyParameter	body		true	Section 2.3.180, "v1.Patch"	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParameter	name	name of the ResourceQuota	true	string	

3.2.114.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.138, "v1.ResourceQuota"

3.2.114.3. Consumes

- application/json-patch+json
- application/merge-patch+json
- application/strategic-merge-patch+json

3.2.114.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.114.5. Tags

- apiv1

3.2.115. replace status of the specified ResourceQuota

```
PUT /api/v1/namespaces/{namespace}/resourcequotas/{name}/status
```

3.2.115.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParameter	body		true	Section 3.3.138, "v1.ResourceQuota"	
PathParamter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParamter	name	name of the ResourceQuota	true	string	

3.2.115.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.138, "v1.ResourceQuota"

3.2.115.3. Consumes

- /

3.2.115.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.115.5. Tags

- apiv1

3.2.116. list or watch objects of kind Secret

```
GET /api/v1/namespaces/{namespace}/secrets
```

3.2.116.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParam eter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParam eter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParam eter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParamter	resourceVersion	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParamter	timeoutSeconds	Timeout for the list/watch call.	false	integer	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	

3.2.116.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.247 , "v1.SecretList"

3.2.116.3. Consumes

- /

3.2.116.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf
- application/json;stream=watch
- application/vnd.kubernetes.protobuf;stream=watch

3.2.116.5. Tags

- apiv1

3.2.117. create a Secret

POST /api/v1/namespaces/{namespace}/secrets

3.2.117.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParameter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParameter	body		true	Section 2.3.243 , "v1.Secret"	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	

3.2.117.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.243, "v1.Secret"

3.2.117.3. Consumes

- /

3.2.117.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.117.5. Tags

- apiv1

3.2.118. delete collection of Secret

DELETE /api/v1/namespaces/{namespace}/secrets

3.2.118.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParam eter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParam eter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParam ter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParam eter	resourceVersi on	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParam eter	timeoutSecon ds	Timeout for the list/watch call.	false	integer	
PathParamet er	namespace	object name and auth scope, such as for teams and projects	true	string	

3.2.118.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.264, "v1.Status"

3.2.118.3. Consumes

- /

3.2.118.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.118.5. Tags

- apiv1

3.2.119. read the specified Secret

GET /api/v1/namespaces/{namespace}/secrets/{name}

3.2.119.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParam eter	export	Should this value be exported. Export strips fields that a user can not specify.	false	boolean	
QueryParam eter	exact	Should the export be exact. Exact export maintains cluster-specific fields like 'Namespace'.	false	boolean	

Type	Name	Description	Required	Schema	Default
PathParamet er	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParamet er	name	name of the Secret	true	string	

3.2.119.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.243, "v1.Secret"

3.2.119.3. Consumes

- /

3.2.119.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.119.5. Tags

- apiv1

3.2.120. partially update the specified Secret

PATCH /api/v1/namespaces/{namespace}/secrets/{name}

3.2.120.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParame ter	pretty	If 'true', then the output is pretty printed.	false	string	

Type	Name	Description	Required	Schema	Default
BodyParameter	body		true	Section 2.3.180 , “v1.Patch”	
PathParamter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParamter	name	name of the Secret	true	string	

3.2.120.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.243 , “v1.Secret”

3.2.120.3. Consumes

- application/json-patch+json
- application/merge-patch+json
- application/strategic-merge-patch+json

3.2.120.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.120.5. Tags

- apiv1

3.2.121. replace the specified Secret

```
PUT /api/v1/namespaces/{namespace}/secrets/{name}
```

3.2.121.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParameter	body		true	Section 2.3.243, "v1.Secret"	
PathParamter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParamter	name	name of the Secret	true	string	

3.2.121.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.243, "v1.Secret"

3.2.121.3. Consumes

- /

3.2.121.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.121.5. Tags

- apiv1

3.2.122. delete a Secret

```
DELETE /api/v1/namespaces/{namespace}/secrets/{name}
```

3.2.122.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam ter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamet er	body		true	Section 2.3.6 1, "v1.DeleteOptions"	
QueryParam ter	gracePeriodS econds	The duration in seconds before the object should be deleted. Value must be non-negative integer. The value zero indicates delete immediately. If this value is nil, the default grace period for the specified type will be used. Defaults to a per object value if not specified. zero means delete immediately.	false	integer	

Type	Name	Description	Required	Schema	Default
QueryParam eter	orphanDepen dents	Deprecated: please use the PropagationP olicy, this field will be deprecated in 1.7. Should the dependent objects be orphaned. If true/false, the "orphan" finalizer will be added to/removed from the object's finalizers list. Either this field or PropagationP olicy may be set, but not both.	false	boolean	
QueryParam eter	propagationP olicy	Whether and how garbage collection will be performed. Either this field or OrphanDepen dents may be set, but not both. The default policy is decided by the existing finalizer set in the metadata.fin alizers and the resource- specific default policy.	false	string	

Type	Name	Description	Required	Schema	Default
PathParamet er	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParamet er	name	name of the Secret	true	string	

3.2.122.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.264, "v1.Status"

3.2.122.3. Consumes

- /

3.2.122.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.122.5. Tags

- apiv1

3.2.123. list or watch objects of kind ServiceAccount

GET /api/v1/namespaces/{namespace}/serviceaccounts

3.2.123.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParame ter	pretty	If 'true', then the output is pretty printed.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParam ter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParam ter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParam ter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParamter	resourceVersion	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParamter	timeoutSeconds	Timeout for the list/watch call.	false	integer	
PathParamter	namespace	object name and auth scope, such as for teams and projects	true	string	

3.2.123.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.162, "v1.ServiceAccountList"

3.2.123.3. Consumes

- /

3.2.123.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf
- application/json;stream=watch
- application/vnd.kubernetes.protobuf;stream=watch

3.2.123.5. Tags

- apiv1

3.2.124. create a ServiceAccount

POST /api/v1/namespaces/{namespace}/serviceaccounts

3.2.124.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamenter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParameter	body		true	Section 3.3.161, "v1.ServiceAccount"	
PathParamenter	namespace	object name and auth scope, such as for teams and projects	true	string	

3.2.124.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.161, "v1.ServiceAccount"

3.2.124.3. Consumes

- /

3.2.124.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.124.5. Tags

- apiv1

3.2.125. delete collection of ServiceAccount

DELETE /api/v1/namespaces/{namespace}/serviceaccounts

3.2.125.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParam eter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParam ter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParam ter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParam ter	resourceVersi on	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParam ter	timeoutSecon ds	Timeout for the list/watch call.	false	integer	
PathParamet er	namespace	object name and auth scope, such as for teams and projects	true	string	

3.2.125.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.264, "v1.Status"

3.2.125.3. Consumes

- /

3.2.125.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.125.5. Tags

- apiv1

3.2.126. read the specified ServiceAccount

GET /api/v1/namespaces/{namespace}/serviceaccounts/{name}

3.2.126.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParam eter	export	Should this value be exported. Export strips fields that a user can not specify.	false	boolean	
QueryParam eter	exact	Should the export be exact. Exact export maintains cluster-specific fields like 'Namespace'.	false	boolean	

Type	Name	Description	Required	Schema	Default
PathParamet er	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParamet er	name	name of the ServiceAccount	true	string	

3.2.126.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.161, "v1.ServiceAccount"

3.2.126.3. Consumes

- /

3.2.126.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.126.5. Tags

- apiv1

3.2.127. partially update the specified ServiceAccount

```
PATCH /api/v1/namespaces/{namespace}/serviceaccounts/{name}
```

3.2.127.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParame ter	pretty	If 'true', then the output is pretty printed.	false	string	

Type	Name	Description	Required	Schema	Default
BodyParameter	body		true	Section 2.3.180 , "v1.Patch"	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParameter	name	name of the ServiceAccount	true	string	

3.2.127.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.161 , "v1.ServiceAccount"

3.2.127.3. Consumes

- application/json-patch+json
- application/merge-patch+json
- application/strategic-merge-patch+json

3.2.127.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.127.5. Tags

- apiv1

3.2.128. replace the specified ServiceAccount

```
PUT /api/v1/namespaces/{namespace}/serviceaccounts/{name}
```

3.2.128.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParameter	body		true	Section 3.3.161 , "v1.ServiceAccount"	
PathParamter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParamter	name	name of the ServiceAccount	true	string	

3.2.128.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.161 , "v1.ServiceAccount"

3.2.128.3. Consumes

- /

3.2.128.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.128.5. Tags

- apiv1

3.2.129. delete a ServiceAccount

```
DELETE /api/v1/namespaces/{namespace}/serviceaccounts/{name}
```

3.2.129.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamet er	body		true	Section 2.3.6 1, "v1.DeleteOptions"	
QueryParam eter	gracePeriodS econds	The duration in seconds before the object should be deleted. Value must be non-negative integer. The value zero indicates delete immediately. If this value is nil, the default grace period for the specified type will be used. Defaults to a per object value if not specified. zero means delete immediately.	false	integer	

Type	Name	Description	Required	Schema	Default
QueryParam eter	orphanDepen dents	Deprecated: please use the PropagationP olicy, this field will be deprecated in 1.7. Should the dependent objects be orphaned. If true/false, the "orphan" finalizer will be added to/removed from the object's finalizers list. Either this field or PropagationP olicy may be set, but not both.	false	boolean	
QueryParam eter	propagationP olicy	Whether and how garbage collection will be performed. Either this field or OrphanDepen dents may be set, but not both. The default policy is decided by the existing finalizer set in the metadata.fin alizers and the resource- specific default policy.	false	string	

Type	Name	Description	Required	Schema	Default
PathParamet er	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParamet er	name	name of the ServiceAccount	true	string	

3.2.129.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.264, "v1.Status"

3.2.129.3. Consumes

- /

3.2.129.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.129.5. Tags

- apiv1

3.2.130. list or watch objects of kind Service

GET /api/v1/namespaces/{namespace}/services

3.2.130.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParame ter	pretty	If 'true', then the output is pretty printed.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParamter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParamter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParam eter	resourceVersion	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParam eter	timeoutSeconds	Timeout for the list/watch call.	false	integer	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	

3.2.130.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.163 , "v1.ServiceList"

3.2.130.3. Consumes

- /

3.2.130.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf
- application/json;stream=watch
- application/vnd.kubernetes.protobuf;stream=watch

3.2.130.5. Tags

- apiv1

3.2.131. create a Service

POST /api/v1/namespaces/{namespace}/services

3.2.131.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParameter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParameter	body		true	Section 3.3.160 , "v1.Service"	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	

3.2.131.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.160, "v1.Service"

3.2.131.3. Consumes

- /

3.2.131.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.131.5. Tags

- apiv1

3.2.132. read the specified Service

GET /api/v1/namespaces/{namespace}/services/{name}

3.2.132.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParameter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParameter	export	Should this value be exported. Export strips fields that a user can not specify.	false	boolean	
QueryParameter	exact	Should the export be exact. Exact export maintains cluster-specific fields like 'Namespace'.	false	boolean	

Type	Name	Description	Required	Schema	Default
PathParamet er	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParamet er	name	name of the Service	true	string	

3.2.132.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.160, "v1.Service"

3.2.132.3. Consumes

- /

3.2.132.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.132.5. Tags

- apiv1

3.2.133. partially update the specified Service

PATCH /api/v1/namespaces/{namespace}/services/{name}

3.2.133.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	

Type	Name	Description	Required	Schema	Default
BodyParameter	body		true	Section 2.3.180, "v1.Patch"	
PathParamter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParamter	name	name of the Service	true	string	

3.2.133.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.160, "v1.Service"

3.2.133.3. Consumes

- application/json-patch+json
- application/merge-patch+json
- application/strategic-merge-patch+json

3.2.133.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.133.5. Tags

- apiv1

3.2.134. replace the specified Service

```
PUT /api/v1/namespaces/{namespace}/services/{name}
```

3.2.134.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamet er	body		true	Section 3.3.160, "v1.Service"	
PathParamet er	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParamet er	name	name of the Service	true	string	

3.2.134.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.160, "v1.Service"

3.2.134.3. Consumes

- /

3.2.134.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.134.5. Tags

- apiv1

3.2.135. delete a Service

```
DELETE /api/v1/namespaces/{namespace}/services/{name}
```

3.2.135.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamter	pretty	If 'true', then the output is pretty printed.	false	string	
PathParamter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParamter	name	name of the Service	true	string	

3.2.135.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.264, "v1.Status"

3.2.135.3. Consumes

- /

3.2.135.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.135.5. Tags

- apiv1

3.2.136. connect GET requests to proxy of Service

GET /api/v1/namespaces/{namespace}/services/{name}/proxy

3.2.136.1. Parameters

Type	Name	Description	Required	Schema	Default
------	------	-------------	----------	--------	---------

Type	Name	Description	Required	Schema	Default
QueryParam eter	path	Path is the part of URLs that include service endpoints, suffixes, and parameters to use for the current proxy request to service. For example, the whole request URL is http://localhost/api/v1/namespaces/kube-system/services/elasticsearch-logging/_search?q=user:kimchy . Path is <code>_search?q=user:kimchy</code> .	false	string	
PathParam eter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParam eter	name	name of the Service	true	string	

3.2.136.2. Responses

HTTP Code	Description	Schema
default	success	string

3.2.136.3. Consumes

- /

3.2.136.4. Produces

- /

3.2.136.5. Tags

- apiv1

3.2.137. connect OPTIONS requests to proxy of Service

OPTIONS /api/v1/namespaces/{namespace}/services/{name}/proxy

3.2.137.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	path	Path is the part of URLs that include service endpoints, suffixes, and parameters to use for the current proxy request to service. For example, the whole request URL is http://localhost/api/v1/namespaces/kube-system/services/elasticsearch-logging/_search?q=user:kimchy . Path is <code>_search?q=user:kimchy</code> .	false	string	
PathParamet er	namespace	object name and auth scope, such as for teams and projects	true	string	

Type	Name	Description	Required	Schema	Default
PathParam er	name	name of the Service	true	string	

3.2.137.2. Responses

HTTP Code	Description	Schema
default	success	string

3.2.137.3. Consumes

- /

3.2.137.4. Produces

- /

3.2.137.5. Tags

- apiv1

3.2.138. connect POST requests to proxy of Service

POST /api/v1/namespaces/{namespace}/services/{name}/proxy

3.2.138.1. Parameters

Type	Name	Description	Required	Schema	Default
------	------	-------------	----------	--------	---------

Type	Name	Description	Required	Schema	Default
QueryParam eter	path	Path is the part of URLs that include service endpoints, suffixes, and parameters to use for the current proxy request to service. For example, the whole request URL is http://localhost/api/v1/namespaces/kube-system/services/elasticsearch-logging/_search?q=user:kimchy . Path is <code>_search?q=user:kimchy</code> .	false	string	
PathParam eter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParam eter	name	name of the Service	true	string	

3.2.138.2. Responses

HTTP Code	Description	Schema
default	success	string

3.2.138.3. Consumes

- /

3.2.138.4. Produces

- /

3.2.138.5. Tags

- apiv1

3.2.139. connect HEAD requests to proxy of Service

HEAD /api/v1/namespaces/{namespace}/services/{name}/proxy

3.2.139.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	path	Path is the part of URLs that include service endpoints, suffixes, and parameters to use for the current proxy request to service. For example, the whole request URL is http://localhost/api/v1/namespaces/kube-system/services/elasticsearch-logging/_search?q=user:kimchy . Path is <code>_search?q=user:kimchy</code> .	false	string	
PathParamet er	namespace	object name and auth scope, such as for teams and projects	true	string	

Type	Name	Description	Required	Schema	Default
PathParam er	name	name of the Service	true	string	

3.2.139.2. Responses

HTTP Code	Description	Schema
default	success	string

3.2.139.3. Consumes

- /

3.2.139.4. Produces

- /

3.2.139.5. Tags

- apiv1

3.2.140. connect PUT requests to proxy of Service

PUT /api/v1/namespaces/{namespace}/services/{name}/proxy

3.2.140.1. Parameters

Type	Name	Description	Required	Schema	Default
------	------	-------------	----------	--------	---------

Type	Name	Description	Required	Schema	Default
QueryParam eter	path	Path is the part of URLs that include service endpoints, suffixes, and parameters to use for the current proxy request to service. For example, the whole request URL is http://localhost/api/v1/namespaces/kube-system/services/elasticsearch-logging/_search?q=user:kimchy . Path is <code>_search?q=user:kimchy</code> .	false	string	
PathParam eter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParam eter	name	name of the Service	true	string	

3.2.140.2. Responses

HTTP Code	Description	Schema
default	success	string

3.2.140.3. Consumes

- /

3.2.140.4. Produces

- /

3.2.140.5. Tags

- apiv1

3.2.141. connect DELETE requests to proxy of Service

DELETE /api/v1/namespaces/{namespace}/services/{name}/proxy

3.2.141.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	path	Path is the part of URLs that include service endpoints, suffixes, and parameters to use for the current proxy request to service. For example, the whole request URL is http://localhost/api/v1/namespaces/kube-system/services/elasticsearch-logging/_search?q=user:kimchy . Path is <code>_search?q=user:kimchy</code> .	false	string	
PathParam eter	namespace	object name and auth scope, such as for teams and projects	true	string	

Type	Name	Description	Required	Schema	Default
PathParam eter	name	name of the Service	true	string	

3.2.141.2. Responses

HTTP Code	Description	Schema
default	success	string

3.2.141.3. Consumes

- /

3.2.141.4. Produces

- /

3.2.141.5. Tags

- apiv1

3.2.142. connect GET requests to proxy of Service

GET /api/v1/namespaces/{namespace}/services/{name}/proxy/{path}

3.2.142.1. Parameters

Type	Name	Description	Required	Schema	Default
------	------	-------------	----------	--------	---------

Type	Name	Description	Required	Schema	Default
QueryParam eter	path	Path is the part of URLs that include service endpoints, suffixes, and parameters to use for the current proxy request to service. For example, the whole request URL is http://localhost/api/v1/namespaces/kube-system/services/elasticsearch-logging/_search?q=user:kimchy . Path is <code>_search?q=user:kimchy</code> .	false	string	
PathParam eter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParam eter	name	name of the Service	true	string	
PathParam eter	path	path to the resource	true	string	

3.2.142.2. Responses

HTTP Code	Description	Schema
default	success	string

3.2.142.3. Consumes

- /

3.2.142.4. Produces

- /

3.2.142.5. Tags

- apiv1

3.2.143. connect OPTIONS requests to proxy of Service

`OPTIONS /api/v1/namespaces/{namespace}/services/{name}/proxy/{path}`

3.2.143.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	path	Path is the part of URLs that include service endpoints, suffixes, and parameters to use for the current proxy request to service. For example, the whole request URL is http://localhost/api/v1/namespaces/kube-system/services/elasticsearch-logging/_search?q=user:kimchy . Path is <code>_search?q=user:kimchy</code> .	false	string	

Type	Name	Description	Required	Schema	Default
PathParamet er	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParamet er	name	name of the Service	true	string	
PathParamet er	path	path to the resource	true	string	

3.2.143.2. Responses

HTTP Code	Description	Schema
default	success	string

3.2.143.3. Consumes

- /

3.2.143.4. Produces

- /

3.2.143.5. Tags

- apiv1

3.2.144. connect POST requests to proxy of Service

```
POST /api/v1/namespaces/{namespace}/services/{name}/proxy/{path}
```

3.2.144.1. Parameters

Type	Name	Description	Required	Schema	Default
------	------	-------------	----------	--------	---------

Type	Name	Description	Required	Schema	Default
QueryParam eter	path	Path is the part of URLs that include service endpoints, suffixes, and parameters to use for the current proxy request to service. For example, the whole request URL is http://localhost/api/v1/namespaces/kube-system/services/elasticsearch-logging/_search?q=user:kimchy . Path is <code>_search?q=user:kimchy</code> .	false	string	
PathParam eter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParam eter	name	name of the Service	true	string	
PathParam eter	path	path to the resource	true	string	

3.2.144.2. Responses

HTTP Code	Description	Schema
default	success	string

3.2.144.3. Consumes

- /

3.2.144.4. Produces

- /

3.2.144.5. Tags

- apiv1

3.2.145. connect HEAD requests to proxy of Service

HEAD /api/v1/namespaces/{namespace}/services/{name}/proxy/{path}

3.2.145.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	path	Path is the part of URLs that include service endpoints, suffixes, and parameters to use for the current proxy request to service. For example, the whole request URL is http://localhost/api/v1/namespaces/kube-system/services/elasticsearch-logging/_search?q=user:kimchy . Path is <code>_search?q=user:kimchy</code> .	false	string	

Type	Name	Description	Required	Schema	Default
PathParamet er	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParamet er	name	name of the Service	true	string	
PathParamet er	path	path to the resource	true	string	

3.2.145.2. Responses

HTTP Code	Description	Schema
default	success	string

3.2.145.3. Consumes

- /

3.2.145.4. Produces

- /

3.2.145.5. Tags

- apiv1

3.2.146. connect PUT requests to proxy of Service

```
PUT /api/v1/namespaces/{namespace}/services/{name}/proxy/{path}
```

3.2.146.1. Parameters

Type	Name	Description	Required	Schema	Default
------	------	-------------	----------	--------	---------

Type	Name	Description	Required	Schema	Default
QueryParam eter	path	Path is the part of URLs that include service endpoints, suffixes, and parameters to use for the current proxy request to service. For example, the whole request URL is http://localhost/api/v1/namespaces/kube-system/services/elasticsearch-logging/_search?q=user:kimchy . Path is <code>_search?q=user:kimchy</code> .	false	string	
PathParam eter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParam eter	name	name of the Service	true	string	
PathParam eter	path	path to the resource	true	string	

3.2.146.2. Responses

HTTP Code	Description	Schema
default	success	string

3.2.146.3. Consumes

- /

3.2.146.4. Produces

- /

3.2.146.5. Tags

- apiv1

3.2.147. connect DELETE requests to proxy of Service

```
DELETE /api/v1/namespaces/{namespace}/services/{name}/proxy/{path}
```

3.2.147.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	path	Path is the part of URLs that include service endpoints, suffixes, and parameters to use for the current proxy request to service. For example, the whole request URL is http://localhost/api/v1/namespaces/kube-system/services/elasticsearch-logging/_search?q=user:kimchy . Path is <code>_search?q=user:kimchy</code> .	false	string	

Type	Name	Description	Required	Schema	Default
PathParamet er	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParamet er	name	name of the Service	true	string	
PathParamet er	path	path to the resource	true	string	

3.2.147.2. Responses

HTTP Code	Description	Schema
default	success	string

3.2.147.3. Consumes

- /

3.2.147.4. Produces

- /

3.2.147.5. Tags

- apiv1

3.2.148. read status of the specified Service

```
GET /api/v1/namespaces/{namespace}/services/{name}/status
```

3.2.148.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParame ter	pretty	If 'true', then the output is pretty printed.	false	string	

Type	Name	Description	Required	Schema	Default
PathParamet er	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParamet er	name	name of the Service	true	string	

3.2.148.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.160, "v1.Service"

3.2.148.3. Consumes

- /

3.2.148.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.148.5. Tags

- apiv1

3.2.149. partially update status of the specified Service

PATCH /api/v1/namespaces/{namespace}/services/{name}/status

3.2.149.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	

Type	Name	Description	Required	Schema	Default
BodyParameter	body		true	Section 2.3.180, "v1.Patch"	
PathParamter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParamter	name	name of the Service	true	string	

3.2.149.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.160, "v1.Service"

3.2.149.3. Consumes

- application/json-patch+json
- application/merge-patch+json
- application/strategic-merge-patch+json

3.2.149.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.149.5. Tags

- apiv1

3.2.150. replace status of the specified Service

```
PUT /api/v1/namespaces/{namespace}/services/{name}/status
```

3.2.150.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamet er	body		true	Section 3.3.160, "v1.Service"	
PathParamet er	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParamet er	name	name of the Service	true	string	

3.2.150.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.160, "v1.Service"

3.2.150.3. Consumes

- /

3.2.150.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.150.5. Tags

- apiv1

3.2.151. read the specified Namespace

```
GET /api/v1/namespaces/{name}
```

3.2.151.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamter	export	Should this value be exported. Export strips fields that a user can not specify.	false	boolean	
QueryParamter	exact	Should the export be exact. Exact export maintains cluster-specific fields like 'Namespace'.	false	boolean	
PathParamter	name	name of the Namespace	true	string	

3.2.151.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.81, "v1.Namespace"

3.2.151.3. Consumes

- /

3.2.151.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.151.5. Tags

- apiv1

3.2.152. partially update the specified Namespace

PATCH /api/v1/namespaces/{name}

3.2.152.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamet er	body		true	Section 2.3.180 , "v1.Patch"	
PathParamet er	name	name of the Namespace	true	string	

3.2.152.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.81 , "v1.Namespace"

3.2.152.3. Consumes

- application/json-patch+json
- application/merge-patch+json
- application/strategic-merge-patch+json

3.2.152.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.152.5. Tags

- apiv1

3.2.153. replace the specified Namespace

PUT /api/v1/namespaces/{name}

■

3.2.153.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParameter	body		true	Section 3.3.81 , "v1.Namespace"	
PathParamter	name	name of the Namespace	true	string	

3.2.153.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.81 , "v1.Namespace"

3.2.153.3. Consumes

- /

3.2.153.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.153.5. Tags

- apiv1

3.2.154. delete a Namespace

```
DELETE /api/v1/namespaces/{name}
```

3.2.154.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParameter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParameter	body		true	Section 2.3.6 1, "v1.DeleteOptions"	
QueryParameter	gracePeriodSeconds	The duration in seconds before the object should be deleted. Value must be non-negative integer. The value zero indicates delete immediately. If this value is nil, the default grace period for the specified type will be used. Defaults to a per object value if not specified. zero means delete immediately.	false	integer	

Type	Name	Description	Required	Schema	Default
QueryParam eter	orphanDepen dents	Deprecated: please use the PropagationP olicy, this field will be deprecated in 1.7. Should the dependent objects be orphaned. If true/false, the "orphan" finalizer will be added to/removed from the object's finalizers list. Either this field or PropagationP olicy may be set, but not both.	false	boolean	
QueryParam eter	propagationP olicy	Whether and how garbage collection will be performed. Either this field or OrphanDepen dents may be set, but not both. The default policy is decided by the existing finalizer set in the metadata.fin alizers and the resource- specific default policy.	false	string	
PathParamet er	name	name of the Namespace	true	string	

3.2.154.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.264, "v1.Status"

3.2.154.3. Consumes

- /

3.2.154.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.154.5. Tags

- apiv1

3.2.155. replace finalize of the specified Namespace

```
PUT /api/v1/namespaces/{name}/finalize
```

3.2.155.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamet er	body		true	Section 3.3.81, "v1.Namespace"	
PathParamet er	name	name of the Namespace	true	string	

3.2.155.2. Responses

HTTP Code	Description	Schema
-----------	-------------	--------

HTTP Code	Description	Schema
200	success	Section 3.3.81, "v1.Namespace"

3.2.155.3. Consumes

- /

3.2.155.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.155.5. Tags

- apiv1

3.2.156. read status of the specified Namespace

GET /api/v1/namespaces/{name}/status

3.2.156.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
PathParam eter	name	name of the Namespace	true	string	

3.2.156.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.81, "v1.Namespace"

3.2.156.3. Consumes

- /

3.2.156.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.156.5. Tags

- apiv1

3.2.157. partially update status of the specified Namespace

PATCH /api/v1/namespaces/{name}/status

3.2.157.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParameter	body		true	Section 2.3.180 , "v1.Patch"	
PathParamter	name	name of the Namespace	true	string	

3.2.157.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.81 , "v1.Namespace"

3.2.157.3. Consumes

- application/json-patch+json
- application/merge-patch+json
- application/strategic-merge-patch+json

3.2.157.4. Produces

- application/json

- application/yaml
- application/vnd.kubernetes.protobuf

3.2.157.5. Tags

- apiv1

3.2.158. replace status of the specified Namespace

PUT /api/v1/namespaces/{name}/status

3.2.158.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParameter	body		true	Section 3.3.81 , "v1.Namespace"	
PathParamter	name	name of the Namespace	true	string	

3.2.158.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.81 , "v1.Namespace"

3.2.158.3. Consumes

- /

3.2.158.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.158.5. Tags

- apiv1

3.2.159. list or watch objects of kind Node

GET /api/v1/nodes

3.2.159.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParam eter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParam eter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParam eter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParam eter	resourceVersi on	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParam eter	timeoutSecon ds	Timeout for the list/watch call.	false	integer	

3.2.159.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.90, "v1.NodeList"

3.2.159.3. Consumes

- /

3.2.159.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf
- application/json;stream=watch
- application/vnd.kubernetes.protobuf;stream=watch

3.2.159.5. Tags

- apiv1

3.2.160. create a Node

POST /api/v1/nodes

3.2.160.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParameter	body		true	Section 3.3.85, "v1.Node"	

3.2.160.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.85, "v1.Node"

3.2.160.3. Consumes

- /

3.2.160.4. Produces

- application/json

- application/yaml
- application/vnd.kubernetes.protobuf

3.2.160.5. Tags

- apiv1

3.2.161. delete collection of Node

DELETE /api/v1/nodes

3.2.161.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParam eter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParam eter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParam eter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParam ter	resourceVersi on	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParam ter	timeoutSecon ds	Timeout for the list/watch call.	false	integer	

3.2.161.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.264, "v1.Status"

3.2.161.3. Consumes

- /

3.2.161.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.161.5. Tags

- apiv1

3.2.162. read the specified Node

GET /api/v1/nodes/{name}

3.2.162.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParam eter	export	Should this value be exported. Export strips fields that a user can not specify.	false	boolean	
QueryParam eter	exact	Should the export be exact. Exact export maintains cluster-specific fields like 'Namespace'.	false	boolean	
PathParam eter	name	name of the Node	true	string	

3.2.162.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.85, “v1.Node”

3.2.162.3. Consumes

- /

3.2.162.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.162.5. Tags

- apiv1

3.2.163. partially update the specified Node

PATCH /api/v1/nodes/{name}

3.2.163.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamet er	body		true	Section 2.3.180, “v1.Patch”	
PathParamet er	name	name of the Node	true	string	

3.2.163.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.85, “v1.Node”

3.2.163.3. Consumes

- application/json-patch+json
- application/merge-patch+json
- application/strategic-merge-patch+json

3.2.163.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.163.5. Tags

- apiv1

3.2.164. replace the specified Node

PUT /api/v1/nodes/{name}

3.2.164.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParameter	body		true	Section 3.3.85, "v1.Node"	
PathParamter	name	name of the Node	true	string	

3.2.164.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.85, "v1.Node"

3.2.164.3. Consumes

- /

3.2.164.4. Produces

- application/json

- application/yaml
- application/vnd.kubernetes.protobuf

3.2.164.5. Tags

- apiv1

3.2.165. delete a Node

```
DELETE /api/v1/nodes/{name}
```

3.2.165.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamet er	body		true	Section 2.3.6 1, "v1.DeleteOptions"	

Type	Name	Description	Required	Schema	Default
QueryParam ter	gracePeriodS econds	The duration in seconds before the object should be deleted. Value must be non-negative integer. The value zero indicates delete immediately. If this value is nil, the default grace period for the specified type will be used. Defaults to a per object value if not specified. zero means delete immediately.	false	integer	

Type	Name	Description	Required	Schema	Default
QueryParam eter	orphanDepen dents	Deprecated: please use the PropagationP olicy, this field will be deprecated in 1.7. Should the dependent objects be orphaned. If true/false, the "orphan" finalizer will be added to/removed from the object's finalizers list. Either this field or PropagationP olicy may be set, but not both.	false	boolean	
QueryParam eter	propagationP olicy	Whether and how garbage collection will be performed. Either this field or OrphanDepen dents may be set, but not both. The default policy is decided by the existing finalizer set in the metadata.fin alizers and the resource- specific default policy.	false	string	
PathParamet er	name	name of the Node	true	string	

3.2.165.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.264, "v1.Status"

3.2.165.3. Consumes

- /

3.2.165.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.165.5. Tags

- apiv1

3.2.166. connect GET requests to proxy of Node

GET /api/v1/nodes/{name}/proxy

3.2.166.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	path	Path is the URL path to use for the current proxy request to node.	false	string	
PathParam eter	name	name of the Node	true	string	

3.2.166.2. Responses

HTTP Code	Description	Schema
default	success	string

3.2.166.3. Consumes

- /

3.2.166.4. Produces

- /

3.2.166.5. Tags

- apiv1

3.2.167. connect OPTIONS requests to proxy of Node

OPTIONS /api/v1/nodes/{name}/proxy

3.2.167.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	path	Path is the URL path to use for the current proxy request to node.	false	string	
PathParam eter	name	name of the Node	true	string	

3.2.167.2. Responses

HTTP Code	Description	Schema
default	success	string

3.2.167.3. Consumes

- /

3.2.167.4. Produces

- /

3.2.167.5. Tags

- apiv1

3.2.168. connect POST requests to proxy of Node

POST /api/v1/nodes/{name}/proxy

■

3.2.168.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamter	path	Path is the URL path to use for the current proxy request to node.	false	string	
PathParamter	name	name of the Node	true	string	

3.2.168.2. Responses

HTTP Code	Description	Schema
default	success	string

3.2.168.3. Consumes

- /

3.2.168.4. Produces

- /

3.2.168.5. Tags

- apiv1

3.2.169. connect HEAD requests to proxy of Node

```
HEAD /api/v1/nodes/{name}/proxy
```

3.2.169.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamter	path	Path is the URL path to use for the current proxy request to node.	false	string	

Type	Name	Description	Required	Schema	Default
PathParamet er	name	name of the Node	true	string	

3.2.169.2. Responses

HTTP Code	Description	Schema
default	success	string

3.2.169.3. Consumes

- /

3.2.169.4. Produces

- /

3.2.169.5. Tags

- apiv1

3.2.170. connect PUT requests to proxy of Node

PUT /api/v1/nodes/{name}/proxy

3.2.170.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParame ter	path	Path is the URL path to use for the current proxy request to node.	false	string	
PathParamet er	name	name of the Node	true	string	

3.2.170.2. Responses

HTTP Code	Description	Schema
default	success	string

3.2.170.3. Consumes

- /

3.2.170.4. Produces

- /

3.2.170.5. Tags

- apiv1

3.2.171. connect DELETE requests to proxy of Node

DELETE /api/v1/nodes/{name}/proxy

3.2.171.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	path	Path is the URL path to use for the current proxy request to node.	false	string	
PathParam eter	name	name of the Node	true	string	

3.2.171.2. Responses

HTTP Code	Description	Schema
default	success	string

3.2.171.3. Consumes

- /

3.2.171.4. Produces

- /

3.2.171.5. Tags

- apiv1

3.2.172. connect GET requests to proxy of Node

```
GET /api/v1/nodes/{name}/proxy/{path}
```

3.2.172.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	path	Path is the URL path to use for the current proxy request to node.	false	string	
PathParam eter	name	name of the Node	true	string	
PathParam eter	path	path to the resource	true	string	

3.2.172.2. Responses

HTTP Code	Description	Schema
default	success	string

3.2.172.3. Consumes

- /

3.2.172.4. Produces

- /

3.2.172.5. Tags

- apiv1

3.2.173. connect OPTIONS requests to proxy of Node

```
OPTIONS /api/v1/nodes/{name}/proxy/{path}
```

3.2.173.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamter	path	Path is the URL path to use for the current proxy request to node.	false	string	
PathParamter	name	name of the Node	true	string	
PathParamter	path	path to the resource	true	string	

3.2.173.2. Responses

HTTP Code	Description	Schema
default	success	string

3.2.173.3. Consumes

- /

3.2.173.4. Produces

- /

3.2.173.5. Tags

- apiv1

3.2.174. connect POST requests to proxy of Node

POST /api/v1/nodes/{name}/proxy/{path}

3.2.174.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamter	path	Path is the URL path to use for the current proxy request to node.	false	string	

Type	Name	Description	Required	Schema	Default
PathParamet er	name	name of the Node	true	string	
PathParamet er	path	path to the resource	true	string	

3.2.174.2. Responses

HTTP Code	Description	Schema
default	success	string

3.2.174.3. Consumes

- /

3.2.174.4. Produces

- /

3.2.174.5. Tags

- apiv1

3.2.175. connect HEAD requests to proxy of Node

```
HEAD /api/v1/nodes/{name}/proxy/{path}
```

3.2.175.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParame ter	path	Path is the URL path to use for the current proxy request to node.	false	string	
PathParamet er	name	name of the Node	true	string	
PathParamet er	path	path to the resource	true	string	

3.2.175.2. Responses

HTTP Code	Description	Schema
default	success	string

3.2.175.3. Consumes

- /

3.2.175.4. Produces

- /

3.2.175.5. Tags

- apiv1

3.2.176. connect PUT requests to proxy of Node

PUT /api/v1/nodes/{name}/proxy/{path}

3.2.176.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	path	Path is the URL path to use for the current proxy request to node.	false	string	
PathParam eter	name	name of the Node	true	string	
PathParam eter	path	path to the resource	true	string	

3.2.176.2. Responses

HTTP Code	Description	Schema
default	success	string

3.2.176.3. Consumes

- /

3.2.176.4. Produces

- /

3.2.176.5. Tags

- apiv1

3.2.177. connect DELETE requests to proxy of Node

DELETE /api/v1/nodes/{name}/proxy/{path}

3.2.177.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	path	Path is the URL path to use for the current proxy request to node.	false	string	
PathParam eter	name	name of the Node	true	string	
PathParam eter	path	path to the resource	true	string	

3.2.177.2. Responses

HTTP Code	Description	Schema
default	success	string

3.2.177.3. Consumes

- /

3.2.177.4. Produces

- /

3.2.177.5. Tags

- apiv1

3.2.178. read status of the specified Node

GET /api/v1/nodes/{name}/status

3.2.178.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamter	pretty	If 'true', then the output is pretty printed.	false	string	
PathParamter	name	name of the Node	true	string	

3.2.178.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.85, "v1.Node"

3.2.178.3. Consumes

- /

3.2.178.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.178.5. Tags

- apiv1

3.2.179. partially update status of the specified Node

PATCH /api/v1/nodes/{name}/status

3.2.179.1. Parameters

Type	Name	Description	Required	Schema	Default
------	------	-------------	----------	--------	---------

Type	Name	Description	Required	Schema	Default
QueryParamter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParameter	body		true	Section 2.3.180, "v1.Patch"	
PathParamter	name	name of the Node	true	string	

3.2.179.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.85, "v1.Node"

3.2.179.3. Consumes

- application/json-patch+json
- application/merge-patch+json
- application/strategic-merge-patch+json

3.2.179.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.179.5. Tags

- apiv1

3.2.180. replace status of the specified Node

```
PUT /api/v1/nodes/{name}/status
```

3.2.180.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParameter	body		true	Section 3.3.85, "v1.Node"	
PathParamter	name	name of the Node	true	string	

3.2.180.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.85, "v1.Node"

3.2.180.3. Consumes

- /

3.2.180.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.180.5. Tags

- apiv1

3.2.181. list or watch objects of kind PersistentVolumeClaim

GET /api/v1/persistentvolumeclaims

3.2.181.1. Parameters

Type	Name	Description	Required	Schema	Default
------	------	-------------	----------	--------	---------

Type	Name	Description	Required	Schema	Default
QueryParam ter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParam ter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParam ter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParam ter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParam eter	resourceVersi on	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParam eter	timeoutSecon ds	Timeout for the list/watch call.	false	integer	

3.2.181.2. Responses

HTTP Code	Description	Schema
-----------	-------------	--------

HTTP Code	Description	Schema
200	success	Section 3.3.105 , “v1.PersistentVolumeClaimList”

3.2.181.3. Consumes

- /

3.2.181.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf
- application/json;stream=watch
- application/vnd.kubernetes.protobuf;stream=watch

3.2.181.5. Tags

- apiv1

3.2.182. create a PersistentVolumeClaim

POST /api/v1/persistentvolumeclaims

3.2.182.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamet er	body		true	Section 3.3.104 , “v1.PersistentVolumeClaim”	

3.2.182.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.104, "v1.PersistentVolumeClaim"

3.2.182.3. Consumes

- /

3.2.182.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.182.5. Tags

- apiv1

3.2.183. list or watch objects of kind PersistentVolume

GET /api/v1/persistentvolumes

3.2.183.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParam eter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParam ter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParam ter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParamter	resourceVersion	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParamter	timeoutSeconds	Timeout for the list/watch call.	false	integer	

3.2.183.2. Responses

HTTP Code	Description	Schema
-----------	-------------	--------

HTTP Code	Description	Schema
200	success	Section 3.3.109, "v1.PersistentVolumeList"

3.2.183.3. Consumes

- /

3.2.183.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf
- application/json;stream=watch
- application/vnd.kubernetes.protobuf;stream=watch

3.2.183.5. Tags

- apiv1

3.2.184. create a PersistentVolume

POST /api/v1/persistentvolumes

3.2.184.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParameter	body		true	Section 3.3.102, "v1.PersistentVolume"	

3.2.184.2. Responses

HTTP Code	Description	Schema
-----------	-------------	--------

HTTP Code	Description	Schema
200	success	Section 3.3.102, "v1.PersistentVolume"

3.2.184.3. Consumes

- /

3.2.184.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.184.5. Tags

- apiv1

3.2.185. delete collection of PersistentVolume

DELETE /api/v1/persistentvolumes

3.2.185.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParam eter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParam ter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParam ter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParam ter	resourceVersi on	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParam ter	timeoutSecon ds	Timeout for the list/watch call.	false	integer	

3.2.185.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.264, "v1.Status"

3.2.185.3. Consumes

- /

3.2.185.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.185.5. Tags

- apiv1

3.2.186. read the specified PersistentVolume

GET /api/v1/persistentvolumes/{name}

3.2.186.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParam eter	export	Should this value be exported. Export strips fields that a user can not specify.	false	boolean	
QueryParam eter	exact	Should the export be exact. Exact export maintains cluster-specific fields like 'Namespace'.	false	boolean	
PathParamet er	name	name of the PersistentVolume	true	string	

3.2.186.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.102, "v1.PersistentVolume"

3.2.186.3. Consumes

- /

3.2.186.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.186.5. Tags

- apiv1

3.2.187. partially update the specified PersistentVolume

PATCH /api/v1/persistentvolumes/{name}

3.2.187.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamet er	body		true	Section 2.3.180, "v1.Patch"	
PathParamet er	name	name of the PersistentVolume	true	string	

3.2.187.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.102, "v1.PersistentVolume"

3.2.187.3. Consumes

- application/json-patch+json
- application/merge-patch+json
- application/strategic-merge-patch+json

3.2.187.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.187.5. Tags

- apiv1

3.2.188. replace the specified PersistentVolume

```
PUT /api/v1/persistentvolumes/{name}
```

3.2.188.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamet er	body		true	Section 3.3.102, "v1.PersistentVolume"	
PathParamet er	name	name of the PersistentVolume	true	string	

3.2.188.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.102, "v1.PersistentVolume"

3.2.188.3. Consumes

- /

3.2.188.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.188.5. Tags

- apiv1

3.2.189. delete a PersistentVolume

```
DELETE /api/v1/persistentvolumes/{name}
```

3.2.189.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamet er	body		true	Section 2.3.6 1, "v1.DeleteOptions"	

Type	Name	Description	Required	Schema	Default
QueryParam ter	gracePeriodS econds	The duration in seconds before the object should be deleted. Value must be non-negative integer. The value zero indicates delete immediately. If this value is nil, the default grace period for the specified type will be used. Defaults to a per object value if not specified. zero means delete immediately.	false	integer	

Type	Name	Description	Required	Schema	Default
QueryParam eter	orphanDepen dents	Deprecated: please use the PropagationP olicy, this field will be deprecated in 1.7. Should the dependent objects be orphaned. If true/false, the "orphan" finalizer will be added to/removed from the object's finalizers list. Either this field or PropagationP olicy may be set, but not both.	false	boolean	
QueryParam eter	propagationP olicy	Whether and how garbage collection will be performed. Either this field or OrphanDepen dents may be set, but not both. The default policy is decided by the existing finalizer set in the metadata.fin alizers and the resource- specific default policy.	false	string	

Type	Name	Description	Required	Schema	Default
PathParamet er	name	name of the PersistentVolume	true	string	

3.2.189.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.264, "v1.Status"

3.2.189.3. Consumes

- /

3.2.189.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.189.5. Tags

- apiv1

3.2.190. read status of the specified PersistentVolume

GET /api/v1/persistentvolumes/{name}/status

3.2.190.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	
PathParamet er	name	name of the PersistentVolume	true	string	

3.2.190.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.102, "v1.PersistentVolume"

3.2.190.3. Consumes

- /

3.2.190.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.190.5. Tags

- apiv1

3.2.191. partially update status of the specified PersistentVolume

PATCH /api/v1/persistentvolumes/{name}/status

3.2.191.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParameter	body		true	Section 2.3.180, "v1.Patch"	
PathParamet	name	name of the PersistentVolume	true	string	

3.2.191.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.102, "v1.PersistentVolume"

3.2.191.3. Consumes

- application/json-patch+json
- application/merge-patch+json
- application/strategic-merge-patch+json

3.2.191.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.191.5. Tags

- apiv1

3.2.192. replace status of the specified PersistentVolume

```
PUT /api/v1/persistentvolumes/{name}/status
```

3.2.192.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParameter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParameter	body		true	Section 3.3.102, "v1.PersistentVolume"	
PathParameter	name	name of the PersistentVolume	true	string	

3.2.192.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.102, "v1.PersistentVolume"

3.2.192.3. Consumes

- /

3.2.192.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.192.5. Tags

- apiv1

3.2.193. list or watch objects of kind Pod

GET /api/v1/pods

3.2.193.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParam eter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParam eter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParam ter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParamter	resourceVersion	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParamter	timeoutSeconds	Timeout for the list/watch call.	false	integer	

3.2.193.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.118, "v1.PodList"

3.2.193.3. Consumes

- /

3.2.193.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf
- application/json;stream=watch
- application/vnd.kubernetes.protobuf;stream=watch

3.2.193.5. Tags

- apiv1

3.2.194. create a Pod

POST /api/v1/pods

3.2.194.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamet er	body		true	Section 3.3.113, "v1.Pod"	

3.2.194.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.113, "v1.Pod"

3.2.194.3. Consumes

- /

3.2.194.4. Produces

- application/json

- application/yaml
- application/vnd.kubernetes.protobuf

3.2.194.5. Tags

- apiv1

3.2.195. list or watch objects of kind PodTemplate

GET /api/v1/podtemplates

3.2.195.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParam eter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParam eter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParam eter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParam ter	resourceVersi on	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParam ter	timeoutSecon ds	Timeout for the list/watch call.	false	integer	

3.2.195.2. Responses

HTTP Code	Description	Schema
-----------	-------------	--------

HTTP Code	Description	Schema
200	success	Section 3.3.123, "v1.PodTemplateList"

3.2.195.3. Consumes

- /

3.2.195.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf
- application/json;stream=watch
- application/vnd.kubernetes.protobuf;stream=watch

3.2.195.5. Tags

- apiv1

3.2.196. create a PodTemplate

POST /api/v1/podtemplates

3.2.196.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParameter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParameter	body		true	Section 3.3.122, "v1.PodTemplate"	

3.2.196.2. Responses

HTTP Code	Description	Schema
-----------	-------------	--------

HTTP Code	Description	Schema
200	success	Section 3.3.122, "v1.PodTemplate"

3.2.196.3. Consumes

- /

3.2.196.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.196.5. Tags

- apiv1

3.2.197. proxy GET requests to Pod

GET /api/v1/proxy/namespaces/{namespace}/pods/{name}

3.2.197.1. Parameters

Type	Name	Description	Required	Schema	Default
PathParamet er	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParamet er	name	name of the Pod	true	string	

3.2.197.2. Responses

HTTP Code	Description	Schema
default	success	string

3.2.197.3. Consumes

- /

3.2.197.4. Produces

- /

3.2.197.5. Tags

- apiv1

3.2.198. proxy OPTIONS requests to Pod

`OPTIONS /api/v1/proxy/namespaces/{namespace}/pods/{name}`

3.2.198.1. Parameters

Type	Name	Description	Required	Schema	Default
PathParamet er	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParamet er	name	name of the Pod	true	string	

3.2.198.2. Responses

HTTP Code	Description	Schema
default	success	string

3.2.198.3. Consumes

- /

3.2.198.4. Produces

- /

3.2.198.5. Tags

- apiv1

3.2.199. proxy POST requests to Pod

`POST /api/v1/proxy/namespaces/{namespace}/pods/{name}`

3.2.199.1. Parameters

Type	Name	Description	Required	Schema	Default
PathParamet er	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParamet er	name	name of the Pod	true	string	

3.2.199.2. Responses

HTTP Code	Description	Schema
default	success	string

3.2.199.3. Consumes

- /

3.2.199.4. Produces

- /

3.2.199.5. Tags

- apiv1

3.2.200. proxy PATCH requests to Pod

PATCH /api/v1/proxy/namespaces/{namespace}/pods/{name}

3.2.200.1. Parameters

Type	Name	Description	Required	Schema	Default
PathParamet er	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParamet er	name	name of the Pod	true	string	

3.2.200.2. Responses

HTTP Code	Description	Schema
default	success	string

3.2.200.3. Consumes

- /

3.2.200.4. Produces

- /

3.2.200.5. Tags

- apiv1

3.2.201. proxy HEAD requests to Pod

HEAD /api/v1/proxy/namespaces/{namespace}/pods/{name}

3.2.201.1. Parameters

Type	Name	Description	Required	Schema	Default
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParameter	name	name of the Pod	true	string	

3.2.201.2. Responses

HTTP Code	Description	Schema
default	success	string

3.2.201.3. Consumes

- /

3.2.201.4. Produces

- /

3.2.201.5. Tags

- apiv1

3.2.202. proxy PUT requests to Pod

PUT /api/v1/proxy/namespaces/{namespace}/pods/{name}

3.2.202.1. Parameters

Type	Name	Description	Required	Schema	Default
PathParam eter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParam er	name	name of the Pod	true	string	

3.2.202.2. Responses

HTTP Code	Description	Schema
default	success	string

3.2.202.3. Consumes

- /

3.2.202.4. Produces

- /

3.2.202.5. Tags

- apiv1

3.2.203. proxy DELETE requests to Pod

DELETE /api/v1/proxy/namespaces/{namespace}/pods/{name}

3.2.203.1. Parameters

Type	Name	Description	Required	Schema	Default
PathParamet er	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParamet er	name	name of the Pod	true	string	

3.2.203.2. Responses

HTTP Code	Description	Schema
default	success	string

3.2.203.3. Consumes

- /

3.2.203.4. Produces

- /

3.2.203.5. Tags

- apiv1

3.2.204. proxy GET requests to Pod

GET /api/v1/proxy/namespaces/{namespace}/pods/{name}/{path}

3.2.204.1. Parameters

Type	Name	Description	Required	Schema	Default
PathParamet er	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParamet er	name	name of the Pod	true	string	

Type	Name	Description	Required	Schema	Default
PathParamet er	path	path to the resource	true	string	

3.2.204.2. Responses

HTTP Code	Description	Schema
default	success	string

3.2.204.3. Consumes

- /

3.2.204.4. Produces

- /

3.2.204.5. Tags

- apiv1

3.2.205. proxy OPTIONS requests to Pod

```
OPTIONS /api/v1/proxy/namespaces/{namespace}/pods/{name}/{path}
```

3.2.205.1. Parameters

Type	Name	Description	Required	Schema	Default
PathParamet er	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParamet er	name	name of the Pod	true	string	
PathParamet er	path	path to the resource	true	string	

3.2.205.2. Responses

HTTP Code	Description	Schema
default	success	string

3.2.205.3. Consumes

- /

3.2.205.4. Produces

- /

3.2.205.5. Tags

- apiv1

3.2.206. proxy POST requests to Pod

POST /api/v1/proxy/namespaces/{namespace}/pods/{name}/{path}

3.2.206.1. Parameters

Type	Name	Description	Required	Schema	Default
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParameter	name	name of the Pod	true	string	
PathParameter	path	path to the resource	true	string	

3.2.206.2. Responses

HTTP Code	Description	Schema
default	success	string

3.2.206.3. Consumes

- /

3.2.206.4. Produces

- /

3.2.206.5. Tags

- apiv1

3.2.207. proxy PATCH requests to Pod

PATCH /api/v1/proxy/namespaces/{namespace}/pods/{name}/{path}

3.2.207.1. Parameters

Type	Name	Description	Required	Schema	Default
PathParamet er	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParamet er	name	name of the Pod	true	string	
PathParamet er	path	path to the resource	true	string	

3.2.207.2. Responses

HTTP Code	Description	Schema
default	success	string

3.2.207.3. Consumes

- /

3.2.207.4. Produces

- /

3.2.207.5. Tags

- apiv1

3.2.208. proxy HEAD requests to Pod

HEAD /api/v1/proxy/namespaces/{namespace}/pods/{name}/{path}

3.2.208.1. Parameters

Type	Name	Description	Required	Schema	Default
PathParamet er	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParamet er	name	name of the Pod	true	string	
PathParamet er	path	path to the resource	true	string	

3.2.208.2. Responses

HTTP Code	Description	Schema
default	success	string

3.2.208.3. Consumes

- /

3.2.208.4. Produces

- /

3.2.208.5. Tags

- apiv1

3.2.209. proxy PUT requests to Pod

```
PUT /api/v1/proxy/namespaces/{namespace}/pods/{name}/{path}
```

3.2.209.1. Parameters

Type	Name	Description	Required	Schema	Default
PathParamet er	namespace	object name and auth scope, such as for teams and projects	true	string	

Type	Name	Description	Required	Schema	Default
PathParamet er	name	name of the Pod	true	string	
PathParamet er	path	path to the resource	true	string	

3.2.209.2. Responses

HTTP Code	Description	Schema
default	success	string

3.2.209.3. Consumes

- /

3.2.209.4. Produces

- /

3.2.209.5. Tags

- apiv1

3.2.210. proxy DELETE requests to Pod

```
DELETE /api/v1/proxy/namespaces/{namespace}/pods/{name}/{path}
```

3.2.210.1. Parameters

Type	Name	Description	Required	Schema	Default
PathParamet er	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParamet er	name	name of the Pod	true	string	
PathParamet er	path	path to the resource	true	string	

3.2.210.2. Responses

HTTP Code	Description	Schema
default	success	string

3.2.210.3. Consumes

- /

3.2.210.4. Produces

- /

3.2.210.5. Tags

- apiv1

3.2.211. proxy GET requests to Service

GET /api/v1/proxy/namespaces/{namespace}/services/{name}

3.2.211.1. Parameters

Type	Name	Description	Required	Schema	Default
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParameter	name	name of the Service	true	string	

3.2.211.2. Responses

HTTP Code	Description	Schema
default	success	string

3.2.211.3. Consumes

- /

3.2.211.4. Produces

- /

3.2.211.5. Tags

- apiv1

3.2.212. proxy OPTIONS requests to Service

`OPTIONS /api/v1/proxy/namespaces/{namespace}/services/{name}`

3.2.212.1. Parameters

Type	Name	Description	Required	Schema	Default
PathParam eter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParam eter	name	name of the Service	true	string	

3.2.212.2. Responses

HTTP Code	Description	Schema
default	success	string

3.2.212.3. Consumes

- /

3.2.212.4. Produces

- /

3.2.212.5. Tags

- apiv1

3.2.213. proxy POST requests to Service

`POST /api/v1/proxy/namespaces/{namespace}/services/{name}`

3.2.213.1. Parameters

Type	Name	Description	Required	Schema	Default
PathParamet er	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParamet er	name	name of the Service	true	string	

3.2.213.2. Responses

HTTP Code	Description	Schema
default	success	string

3.2.213.3. Consumes

- /

3.2.213.4. Produces

- /

3.2.213.5. Tags

- apiv1

3.2.214. proxy PATCH requests to Service

PATCH /api/v1/proxy/namespaces/{namespace}/services/{name}

3.2.214.1. Parameters

Type	Name	Description	Required	Schema	Default
PathParamet er	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParamet er	name	name of the Service	true	string	

3.2.214.2. Responses

HTTP Code	Description	Schema
default	success	string

3.2.214.3. Consumes

- /

3.2.214.4. Produces

- /

3.2.214.5. Tags

- apiv1

3.2.215. proxy HEAD requests to Service

HEAD /api/v1/proxy/namespaces/{namespace}/services/{name}

3.2.215.1. Parameters

Type	Name	Description	Required	Schema	Default
PathParamet er	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParamet er	name	name of the Service	true	string	

3.2.215.2. Responses

HTTP Code	Description	Schema
default	success	string

3.2.215.3. Consumes

- /

3.2.215.4. Produces

- /

3.2.215.5. Tags

- apiv1

3.2.216. proxy PUT requests to Service

```
PUT /api/v1/proxy/namespaces/{namespace}/services/{name}
```

3.2.216.1. Parameters

Type	Name	Description	Required	Schema	Default
PathParam eter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParam er	name	name of the Service	true	string	

3.2.216.2. Responses

HTTP Code	Description	Schema
default	success	string

3.2.216.3. Consumes

- /

3.2.216.4. Produces

- /

3.2.216.5. Tags

- apiv1

3.2.217. proxy DELETE requests to Service

```
DELETE /api/v1/proxy/namespaces/{namespace}/services/{name}
```

3.2.217.1. Parameters

Type	Name	Description	Required	Schema	Default
PathParamet er	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParamet er	name	name of the Service	true	string	

3.2.217.2. Responses

HTTP Code	Description	Schema
default	success	string

3.2.217.3. Consumes

- /

3.2.217.4. Produces

- /

3.2.217.5. Tags

- apiv1

3.2.218. proxy GET requests to Service

```
GET /api/v1/proxy/namespaces/{namespace}/services/{name}/{path}
```

3.2.218.1. Parameters

Type	Name	Description	Required	Schema	Default
PathParamet er	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParamet er	name	name of the Service	true	string	

Type	Name	Description	Required	Schema	Default
PathParamet er	path	path to the resource	true	string	

3.2.218.2. Responses

HTTP Code	Description	Schema
default	success	string

3.2.218.3. Consumes

- /

3.2.218.4. Produces

- /

3.2.218.5. Tags

- apiv1

3.2.219. proxy OPTIONS requests to Service

`OPTIONS /api/v1/proxy/namespaces/{namespace}/services/{name}/{path}`

3.2.219.1. Parameters

Type	Name	Description	Required	Schema	Default
PathParamet er	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParamet er	name	name of the Service	true	string	
PathParamet er	path	path to the resource	true	string	

3.2.219.2. Responses

HTTP Code	Description	Schema
default	success	string

3.2.219.3. Consumes

- /

3.2.219.4. Produces

- /

3.2.219.5. Tags

- apiv1

3.2.220. proxy POST requests to Service

POST /api/v1/proxy/namespaces/{namespace}/services/{name}/{path}

3.2.220.1. Parameters

Type	Name	Description	Required	Schema	Default
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParameter	name	name of the Service	true	string	
PathParameter	path	path to the resource	true	string	

3.2.220.2. Responses

HTTP Code	Description	Schema
default	success	string

3.2.220.3. Consumes

- /

3.2.220.4. Produces

- /

3.2.220.5. Tags

- apiv1

3.2.221. proxy PATCH requests to Service

PATCH /api/v1/proxy/namespaces/{namespace}/services/{name}/{path}

3.2.221.1. Parameters

Type	Name	Description	Required	Schema	Default
PathParamet er	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParamet er	name	name of the Service	true	string	
PathParamet er	path	path to the resource	true	string	

3.2.221.2. Responses

HTTP Code	Description	Schema
default	success	string

3.2.221.3. Consumes

- /

3.2.221.4. Produces

- /

3.2.221.5. Tags

- apiv1

3.2.222. proxy HEAD requests to Service

HEAD /api/v1/proxy/namespaces/{namespace}/services/{name}/{path}

3.2.222.1. Parameters

Type	Name	Description	Required	Schema	Default
PathParamet er	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParamet er	name	name of the Service	true	string	
PathParamet er	path	path to the resource	true	string	

3.2.222.2. Responses

HTTP Code	Description	Schema
default	success	string

3.2.222.3. Consumes

- /

3.2.222.4. Produces

- /

3.2.222.5. Tags

- apiv1

3.2.223. proxy PUT requests to Service

```
PUT /api/v1/proxy/namespaces/{namespace}/services/{name}/{path}
```

3.2.223.1. Parameters

Type	Name	Description	Required	Schema	Default
PathParamet er	namespace	object name and auth scope, such as for teams and projects	true	string	

Type	Name	Description	Required	Schema	Default
PathParamet er	name	name of the Service	true	string	
PathParamet er	path	path to the resource	true	string	

3.2.223.2. Responses

HTTP Code	Description	Schema
default	success	string

3.2.223.3. Consumes

- /

3.2.223.4. Produces

- /

3.2.223.5. Tags

- apiv1

3.2.224. proxy DELETE requests to Service

```
DELETE /api/v1/proxy/namespaces/{namespace}/services/{name}/{path}
```

3.2.224.1. Parameters

Type	Name	Description	Required	Schema	Default
PathParamet er	namespace	object name and auth scope, such as for teams and projects	true	string	
PathParamet er	name	name of the Service	true	string	
PathParamet er	path	path to the resource	true	string	

3.2.224.2. Responses

HTTP Code	Description	Schema
default	success	string

3.2.224.3. Consumes

- /

3.2.224.4. Produces

- /

3.2.224.5. Tags

- apiv1

3.2.225. proxy GET requests to Node

GET /api/v1/proxy/nodes/{name}

3.2.225.1. Parameters

Type	Name	Description	Required	Schema	Default
PathParamet er	name	name of the Node	true	string	

3.2.225.2. Responses

HTTP Code	Description	Schema
default	success	string

3.2.225.3. Consumes

- /

3.2.225.4. Produces

- /

3.2.225.5. Tags

- apiv1

3.2.226. proxy OPTIONS requests to Node

OPTIONS /api/v1/proxy/nodes/{name}

3.2.226.1. Parameters

Type	Name	Description	Required	Schema	Default
PathParamet er	name	name of the Node	true	string	

3.2.226.2. Responses

HTTP Code	Description	Schema
default	success	string

3.2.226.3. Consumes

- /

3.2.226.4. Produces

- /

3.2.226.5. Tags

- apiv1

3.2.227. proxy POST requests to Node

POST /api/v1/proxy/nodes/{name}

3.2.227.1. Parameters

Type	Name	Description	Required	Schema	Default
PathParamet er	name	name of the Node	true	string	

3.2.227.2. Responses

HTTP Code	Description	Schema
default	success	string

3.2.227.3. Consumes

- /

3.2.227.4. Produces

- /

3.2.227.5. Tags

- apiv1

3.2.228. proxy PATCH requests to Node

PATCH /api/v1/proxy/nodes/{name}

3.2.228.1. Parameters

Type	Name	Description	Required	Schema	Default
PathParam eter	name	name of the Node	true	string	

3.2.228.2. Responses

HTTP Code	Description	Schema
default	success	string

3.2.228.3. Consumes

- /

3.2.228.4. Produces

- /

3.2.228.5. Tags

- apiv1

3.2.229. proxy HEAD requests to Node

HEAD /api/v1/proxy/nodes/{name}

3.2.229.1. Parameters

Type	Name	Description	Required	Schema	Default
PathParamet er	name	name of the Node	true	string	

3.2.229.2. Responses

HTTP Code	Description	Schema
default	success	string

3.2.229.3. Consumes

- /

3.2.229.4. Produces

- /

3.2.229.5. Tags

- apiv1

3.2.230. proxy PUT requests to Node

PUT /api/v1/proxy/nodes/{name}

3.2.230.1. Parameters

Type	Name	Description	Required	Schema	Default
PathParamet er	name	name of the Node	true	string	

3.2.230.2. Responses

HTTP Code	Description	Schema
default	success	string

3.2.230.3. Consumes

- /

3.2.230.4. Produces

- /

3.2.230.5. Tags

- apiv1

3.2.231. proxy DELETE requests to Node

DELETE /api/v1/proxy/nodes/{name}

3.2.231.1. Parameters

Type	Name	Description	Required	Schema	Default
PathParamet er	name	name of the Node	true	string	

3.2.231.2. Responses

HTTP Code	Description	Schema
default	success	string

3.2.231.3. Consumes

- /

3.2.231.4. Produces

- /

3.2.231.5. Tags

- apiv1

3.2.232. proxy GET requests to Node

GET /api/v1/proxy/nodes/{name}/{path}

3.2.232.1. Parameters

Type	Name	Description	Required	Schema	Default
PathParamet er	name	name of the Node	true	string	

Type	Name	Description	Required	Schema	Default
PathParamet er	path	path to the resource	true	string	

3.2.232.2. Responses

HTTP Code	Description	Schema
default	success	string

3.2.232.3. Consumes

- /

3.2.232.4. Produces

- /

3.2.232.5. Tags

- apiv1

3.2.233. proxy OPTIONS requests to Node

```
OPTIONS /api/v1/proxy/nodes/{name}/{path}
```

3.2.233.1. Parameters

Type	Name	Description	Required	Schema	Default
PathParamet er	name	name of the Node	true	string	
PathParamet er	path	path to the resource	true	string	

3.2.233.2. Responses

HTTP Code	Description	Schema
default	success	string

3.2.233.3. Consumes

- /

3.2.233.4. Produces

- /

3.2.233.5. Tags

- apiv1

3.2.234. proxy POST requests to Node

POST /api/v1/proxy/nodes/{name}/{path}

3.2.234.1. Parameters

Type	Name	Description	Required	Schema	Default
PathParamet er	name	name of the Node	true	string	
PathParamet er	path	path to the resource	true	string	

3.2.234.2. Responses

HTTP Code	Description	Schema
default	success	string

3.2.234.3. Consumes

- /

3.2.234.4. Produces

- /

3.2.234.5. Tags

- apiv1

3.2.235. proxy PATCH requests to Node

PATCH /api/v1/proxy/nodes/{name}/{path}

3.2.235.1. Parameters

Type	Name	Description	Required	Schema	Default
PathParamet er	name	name of the Node	true	string	
PathParamet er	path	path to the resource	true	string	

3.2.235.2. Responses

HTTP Code	Description	Schema
default	success	string

3.2.235.3. Consumes

- /

3.2.235.4. Produces

- /

3.2.235.5. Tags

- apiv1

3.2.236. proxy HEAD requests to Node

```
HEAD /api/v1/proxy/nodes/{name}/{path}
```

3.2.236.1. Parameters

Type	Name	Description	Required	Schema	Default
PathParamet er	name	name of the Node	true	string	
PathParamet er	path	path to the resource	true	string	

3.2.236.2. Responses

HTTP Code	Description	Schema
default	success	string

3.2.236.3. Consumes

- /

3.2.236.4. Produces

- /

3.2.236.5. Tags

- apiv1

3.2.237. proxy PUT requests to Node

PUT /api/v1/proxy/nodes/{name}/{path}

3.2.237.1. Parameters

Type	Name	Description	Required	Schema	Default
PathParam eter	name	name of the Node	true	string	
PathParam eter	path	path to the resource	true	string	

3.2.237.2. Responses

HTTP Code	Description	Schema
default	success	string

3.2.237.3. Consumes

- /

3.2.237.4. Produces

- /

3.2.237.5. Tags

- apiv1

3.2.238. proxy DELETE requests to Node

DELETE /api/v1/proxy/nodes/{name}/{path}

3.2.238.1. Parameters

Type	Name	Description	Required	Schema	Default
PathParamet er	name	name of the Node	true	string	
PathParamet er	path	path to the resource	true	string	

3.2.238.2. Responses

HTTP Code	Description	Schema
default	success	string

3.2.238.3. Consumes

- /

3.2.238.4. Produces

- /

3.2.238.5. Tags

- apiv1

3.2.239. list or watch objects of kind ReplicationController

GET /api/v1/replicationcontrollers

3.2.239.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParame ter	pretty	If 'true', then the output is pretty printed.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParam ter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParam ter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParam ter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParam ter	resourceVersion	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParam ter	timeoutSeconds	Timeout for the list/watch call.	false	integer	

3.2.239.2. Responses

HTTP Code	Description	Schema
-----------	-------------	--------

HTTP Code	Description	Schema
200	success	Section 3.3.134, "v1.ReplicationControllerList"

3.2.239.3. Consumes

- /

3.2.239.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf
- application/json;stream=watch
- application/vnd.kubernetes.protobuf;stream=watch

3.2.239.5. Tags

- apiv1

3.2.240. create a ReplicationController

POST /api/v1/replicationcontrollers

3.2.240.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParameter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParameter	body		true	Section 3.3.132, "v1.ReplicationController"	

3.2.240.2. Responses

HTTP Code	Description	Schema
-----------	-------------	--------

HTTP Code	Description	Schema
200	success	Section 3.3.132, "v1.ReplicationController"

3.2.240.3. Consumes

- /

3.2.240.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.240.5. Tags

- apiv1

3.2.241. list or watch objects of kind ResourceQuota

GET /api/v1/resourcequotas

3.2.241.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParam eter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParam ter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParam ter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParamter	resourceVersion	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParamter	timeoutSeconds	Timeout for the list/watch call.	false	integer	

3.2.241.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.139, "v1.ResourceQuotaList"

3.2.241.3. Consumes

- /

3.2.241.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf
- application/json;stream=watch
- application/vnd.kubernetes.protobuf;stream=watch

3.2.241.5. Tags

- apiv1

3.2.242. create a ResourceQuota

POST /api/v1/resourcequotas

3.2.242.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamet er	body		true	Section 3.3.138, "v1.ResourceQuota"	

3.2.242.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.138, "v1.ResourceQuota"

3.2.242.3. Consumes

- /

3.2.242.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.242.5. Tags

- apiv1

3.2.243. list or watch objects of kind Secret

GET /api/v1/secrets

3.2.243.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParam eter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParam eter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParam ter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParamter	resourceVersion	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParamter	timeoutSeconds	Timeout for the list/watch call.	false	integer	

3.2.243.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.247, "v1.SecretList"

3.2.243.3. Consumes

- /

3.2.243.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf
- application/json;stream=watch
- application/vnd.kubernetes.protobuf;stream=watch

3.2.243.5. Tags

- apiv1

3.2.244. create a Secret

POST /api/v1/secrets

3.2.244.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamet er	body		true	Section 2.3.243 , "v1.Secret"	

3.2.244.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.243 , "v1.Secret"

3.2.244.3. Consumes

- /

3.2.244.4. Produces

- application/json

- application/yaml
- application/vnd.kubernetes.protobuf

3.2.244.5. Tags

- apiv1

3.2.245. list or watch objects of kind SecurityContextConstraints

GET /api/v1/securitycontextconstraints

3.2.245.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParameter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParameter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParameter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParameter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParam ter	resourceVersi on	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParam ter	timeoutSecon ds	Timeout for the list/watch call.	false	integer	

3.2.245.2. Responses

HTTP Code	Description	Schema
-----------	-------------	--------

HTTP Code	Description	Schema
200	success	Section 3.3.159, "v1.SecurityContextConstraintsList"

3.2.245.3. Consumes

- /

3.2.245.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf
- application/json;stream=watch
- application/vnd.kubernetes.protobuf;stream=watch

3.2.245.5. Tags

- apiv1

3.2.246. create SecurityContextConstraints

POST /api/v1/securitycontextconstraints

3.2.246.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamenter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParameter	body		true	Section 3.3.158, "v1.SecurityContextConstraints"	

3.2.246.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.158, "v1.SecurityContextConstraints"

3.2.246.3. Consumes

- /

3.2.246.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.246.5. Tags

- apiv1

3.2.247. delete collection of SecurityContextConstraints

DELETE /api/v1/securitycontextconstraints

3.2.247.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParam eter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParam ter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParam ter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParamter	resourceVersion	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParamter	timeoutSeconds	Timeout for the list/watch call.	false	integer	

3.2.247.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.264, "v1.Status"

3.2.247.3. Consumes

- /

3.2.247.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.247.5. Tags

- apiv1

3.2.248. read the specified SecurityContextConstraints

GET /api/v1/securitycontextconstraints/{name}

3.2.248.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParam eter	export	Should this value be exported. Export strips fields that a user can not specify.	false	boolean	
QueryParam eter	exact	Should the export be exact. Exact export maintains cluster-specific fields like 'Namespace'.	false	boolean	
PathParamet er	name	name of the SecurityContextConstraints	true	string	

3.2.248.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.158 , “v1.SecurityContextConstraints”

3.2.248.3. Consumes

- /

3.2.248.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.248.5. Tags

- apiv1

3.2.249. partially update the specified SecurityContextConstraints

```
PATCH /api/v1/securitycontextconstraints/{name}
```

3.2.249.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamet er	body		true	Section 2.3.180 , “v1.Patch”	
PathParamet er	name	name of the SecurityContextConstraints	true	string	

3.2.249.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.158, "v1.SecurityContextConstraints"

3.2.249.3. Consumes

- application/json-patch+json
- application/merge-patch+json
- application/strategic-merge-patch+json

3.2.249.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.249.5. Tags

- apiv1

3.2.250. replace the specified SecurityContextConstraints

```
PUT /api/v1/securitycontextconstraints/{name}
```

3.2.250.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParameter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParameter	body		true	Section 3.3.158, "v1.SecurityContextConstraints"	
PathParameter	name	name of the SecurityContextConstraints	true	string	

3.2.250.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.158, "v1.SecurityContextConstraints"

3.2.250.3. Consumes

- /

3.2.250.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.250.5. Tags

- apiv1

3.2.251. delete SecurityContextConstraints

DELETE /api/v1/securitycontextconstraints/{name}

3.2.251.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamet er	body		true	Section 2.3.6 1, "v1.DeleteOptions"	

Type	Name	Description	Required	Schema	Default
QueryParam ter	gracePeriodS econds	The duration in seconds before the object should be deleted. Value must be non-negative integer. The value zero indicates delete immediately. If this value is nil, the default grace period for the specified type will be used. Defaults to a per object value if not specified. zero means delete immediately.	false	integer	

Type	Name	Description	Required	Schema	Default
QueryParam ter	orphanDepen dents	Deprecated: please use the PropagationP olicy, this field will be deprecated in 1.7. Should the dependent objects be orphaned. If true/false, the "orphan" finalizer will be added to/removed from the object's finalizers list. Either this field or PropagationP olicy may be set, but not both.	false	boolean	
QueryParam ter	propagationP olicy	Whether and how garbage collection will be performed. Either this field or OrphanDepen dents may be set, but not both. The default policy is decided by the existing finalizer set in the metadata.fin alizers and the resource- specific default policy.	false	string	

Type	Name	Description	Required	Schema	Default
PathParamet er	name	name of the SecurityContextConstraints	true	string	

3.2.251.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.264, "v1.Status"

3.2.251.3. Consumes

- /

3.2.251.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.251.5. Tags

- apiv1

3.2.252. list or watch objects of kind ServiceAccount

GET /api/v1/serviceaccounts

3.2.252.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParamter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParamter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParam ter	resourceVersi on	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParam ter	timeoutSecon ds	Timeout for the list/watch call.	false	integer	

3.2.252.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.162, "v1.ServiceAccountList"

3.2.252.3. Consumes

- /

3.2.252.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf
- application/json;stream=watch
- application/vnd.kubernetes.protobuf;stream=watch

3.2.252.5. Tags

- apiv1

3.2.253. create a ServiceAccount

POST /api/v1/serviceaccounts

3.2.253.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParameter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParameter	body		true	Section 3.3.161 , "v1.ServiceAccount"	

3.2.253.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.161 , "v1.ServiceAccount"

3.2.253.3. Consumes

- /

3.2.253.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf

3.2.253.5. Tags

- apiv1

3.2.254. list or watch objects of kind Service

GET /api/v1/services

3.2.254.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParam eter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParam eter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParam ter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParamter	resourceVersion	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParamter	timeoutSeconds	Timeout for the list/watch call.	false	integer	

3.2.254.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.163, "v1.ServiceList"

3.2.254.3. Consumes

- /

3.2.254.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf
- application/json;stream=watch
- application/vnd.kubernetes.protobuf;stream=watch

3.2.254.5. Tags

- apiv1

3.2.255. create a Service

POST /api/v1/services

3.2.255.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
BodyParamet er	body		true	Section 3.3.160 , "v1.Service"	

3.2.255.2. Responses

HTTP Code	Description	Schema
200	success	Section 3.3.160 , "v1.Service"

3.2.255.3. Consumes

- /

3.2.255.4. Produces

- application/json

- application/yaml
- application/vnd.kubernetes.protobuf

3.2.255.5. Tags

- apiv1

3.2.256. watch individual changes to a list of ConfigMap

GET /api/v1/watch/configmaps

3.2.256.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParam eter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParam eter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParam eter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParam ter	resourceVersi on	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParam ter	timeoutSecon ds	Timeout for the list/watch call.	false	integer	

3.2.256.2. Responses

HTTP Code	Description	Schema
-----------	-------------	--------

HTTP Code	Description	Schema
200	success	Section 2.3.291, "v1.WatchEvent"

3.2.256.3. Consumes

- /

3.2.256.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf
- application/json;stream=watch
- application/vnd.kubernetes.protobuf;stream=watch

3.2.256.5. Tags

- apiv1

3.2.257. watch individual changes to a list of Endpoints

GET /api/v1/watch/endpoints

3.2.257.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParam ter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParam ter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParamter	resourceVersion	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParamter	timeoutSeconds	Timeout for the list/watch call.	false	integer	

3.2.257.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.291, "v1.WatchEvent"

3.2.257.3. Consumes

- /

3.2.257.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf
- application/json;stream=watch
- application/vnd.kubernetes.protobuf;stream=watch

3.2.257.5. Tags

- apiv1

3.2.258. watch individual changes to a list of Event

GET /api/v1/watch/events

3.2.258.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParam eter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParam ter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParam ter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParam ter	resourceVersi on	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParam ter	timeoutSecon ds	Timeout for the list/watch call.	false	integer	

3.2.258.2. Responses

HTTP Code	Description	Schema
-----------	-------------	--------

HTTP Code	Description	Schema
200	success	Section 2.3.291, "v1.WatchEvent"

3.2.258.3. Consumes

- /

3.2.258.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf
- application/json;stream=watch
- application/vnd.kubernetes.protobuf;stream=watch

3.2.258.5. Tags

- apiv1

3.2.259. watch individual changes to a list of LimitRange

GET /api/v1/watch/limitranges

3.2.259.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParam ter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParam ter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParamter	resourceVersion	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParamter	timeoutSeconds	Timeout for the list/watch call.	false	integer	

3.2.259.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.291, "v1.WatchEvent"

3.2.259.3. Consumes

- /

3.2.259.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf
- application/json;stream=watch
- application/vnd.kubernetes.protobuf;stream=watch

3.2.259.5. Tags

- apiv1

3.2.260. watch individual changes to a list of Namespace

GET /api/v1/watch/namespaces

3.2.260.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParam eter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParam ter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParam ter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParam ter	resourceVersi on	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParam ter	timeoutSecon ds	Timeout for the list/watch call.	false	integer	

3.2.260.2. Responses

HTTP Code	Description	Schema
-----------	-------------	--------

HTTP Code	Description	Schema
200	success	Section 2.3.291, "v1.WatchEvent"

3.2.260.3. Consumes

- /

3.2.260.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf
- application/json;stream=watch
- application/vnd.kubernetes.protobuf;stream=watch

3.2.260.5. Tags

- apiv1

3.2.261. watch individual changes to a list of ConfigMap

GET /api/v1/watch/namespaces/{namespace}/configmaps

3.2.261.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParam ter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParam ter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParam eter	resourceVersi on	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParam eter	timeoutSecon ds	Timeout for the list/watch call.	false	integer	
PathParamet er	namespace	object name and auth scope, such as for teams and projects	true	string	

3.2.261.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.291, "v1.WatchEvent"

3.2.261.3. Consumes

- /

3.2.261.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf
- application/json;stream=watch
- application/vnd.kubernetes.protobuf;stream=watch

3.2.261.5. Tags

- apiv1

3.2.262. watch changes to an object of kind ConfigMap

```
GET /api/v1/watch/namespaces/{namespace}/configmaps/{name}
```

3.2.262.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParam eter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParam ter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParam ter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParam eter	resourceVersi on	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParam eter	timeoutSecon ds	Timeout for the list/watch call.	false	integer	
PathParam eter	namespace	object name and auth scope, such as for teams and projects	true	string	

Type	Name	Description	Required	Schema	Default
PathParam eter	name	name of the ConfigMap	true	string	

3.2.262.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.291, "v1.WatchEvent"

3.2.262.3. Consumes

- /

3.2.262.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf
- application/json;stream=watch
- application/vnd.kubernetes.protobuf;stream=watch

3.2.262.5. Tags

- apiv1

3.2.263. watch individual changes to a list of Endpoints

```
GET /api/v1/watch/namespaces/{namespace}/endpoints
```

3.2.263.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParam ter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParam ter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParam ter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParam eter	resourceVersi on	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParam eter	timeoutSecon ds	Timeout for the list/watch call.	false	integer	
PathParamet er	namespace	object name and auth scope, such as for teams and projects	true	string	

3.2.263.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.291, "v1.WatchEvent"

3.2.263.3. Consumes

- /

3.2.263.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf
- application/json;stream=watch
- application/vnd.kubernetes.protobuf;stream=watch

3.2.263.5. Tags

- apiv1

3.2.264. watch changes to an object of kind Endpoints

```
GET /api/v1/watch/namespaces/{namespace}/endpoints/{name}
```

3.2.264.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParam eter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParam ter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParam ter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParam eter	resourceVersi on	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParam eter	timeoutSecon ds	Timeout for the list/watch call.	false	integer	
PathParam eter	namespace	object name and auth scope, such as for teams and projects	true	string	

Type	Name	Description	Required	Schema	Default
PathParam eter	name	name of the Endpoints	true	string	

3.2.264.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.291, "v1.WatchEvent"

3.2.264.3. Consumes

- /

3.2.264.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf
- application/json;stream=watch
- application/vnd.kubernetes.protobuf;stream=watch

3.2.264.5. Tags

- apiv1

3.2.265. watch individual changes to a list of Event

```
GET /api/v1/watch/namespaces/{namespace}/events
```

3.2.265.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParam ter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParam ter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParam ter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParam eter	resourceVersi on	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParam eter	timeoutSecon ds	Timeout for the list/watch call.	false	integer	
PathParamet er	namespace	object name and auth scope, such as for teams and projects	true	string	

3.2.265.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.291, "v1.WatchEvent"

3.2.265.3. Consumes

- /

3.2.265.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf
- application/json;stream=watch
- application/vnd.kubernetes.protobuf;stream=watch

3.2.265.5. Tags

- apiv1

3.2.266. watch changes to an object of kind Event

```
GET /api/v1/watch/namespaces/{namespace}/events/{name}
```

3.2.266.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParam ter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParam ter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParam eter	resourceVersi on	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParam eter	timeoutSecon ds	Timeout for the list/watch call.	false	integer	
PathParam eter	namespace	object name and auth scope, such as for teams and projects	true	string	

Type	Name	Description	Required	Schema	Default
PathParam eter	name	name of the Event	true	string	

3.2.266.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.291, "v1.WatchEvent"

3.2.266.3. Consumes

- /

3.2.266.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf
- application/json;stream=watch
- application/vnd.kubernetes.protobuf;stream=watch

3.2.266.5. Tags

- apiv1

3.2.267. watch individual changes to a list of LimitRange

GET /api/v1/watch/namespaces/{namespace}/limitranges

3.2.267.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParam ter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParam ter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParam ter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParam eter	resourceVersi on	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParam eter	timeoutSecon ds	Timeout for the list/watch call.	false	integer	
PathParamet er	namespace	object name and auth scope, such as for teams and projects	true	string	

3.2.267.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.291, "v1.WatchEvent"

3.2.267.3. Consumes

- /

3.2.267.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf
- application/json;stream=watch
- application/vnd.kubernetes.protobuf;stream=watch

3.2.267.5. Tags

- apiv1

3.2.268. watch changes to an object of kind LimitRange

```
GET /api/v1/watch/namespaces/{namespace}/limitranges/{name}
```

3.2.268.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParam eter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParam ter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParam ter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParam eter	resourceVersi on	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParam eter	timeoutSecon ds	Timeout for the list/watch call.	false	integer	
PathParam eter	namespace	object name and auth scope, such as for teams and projects	true	string	

Type	Name	Description	Required	Schema	Default
PathParamet er	name	name of the LimitRange	true	string	

3.2.268.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.291, "v1.WatchEvent"

3.2.268.3. Consumes

- /

3.2.268.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf
- application/json;stream=watch
- application/vnd.kubernetes.protobuf;stream=watch

3.2.268.5. Tags

- apiv1

3.2.269. watch individual changes to a list of PersistentVolumeClaim

```
GET /api/v1/watch/namespaces/{namespace}/persistentvolumeclaims
```

3.2.269.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParam ter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParam ter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParam ter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParam eter	resourceVersi on	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParam eter	timeoutSecon ds	Timeout for the list/watch call.	false	integer	
PathParamet er	namespace	object name and auth scope, such as for teams and projects	true	string	

3.2.269.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.291, "v1.WatchEvent"

3.2.269.3. Consumes

- /

3.2.269.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf
- application/json;stream=watch
- application/vnd.kubernetes.protobuf;stream=watch

3.2.269.5. Tags

- apiv1

3.2.270. watch changes to an object of kind PersistentVolumeClaim

```
GET /api/v1/watch/namespaces/{namespace}/persistentvolumeclaims/{name}
```

3.2.270.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParam eter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParam ter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParam ter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParam eter	resourceVersi on	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParam eter	timeoutSecon ds	Timeout for the list/watch call.	false	integer	
PathParam eter	namespace	object name and auth scope, such as for teams and projects	true	string	

Type	Name	Description	Required	Schema	Default
PathParam eter	name	name of the PersistentVolumeClaim	true	string	

3.2.270.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.291, "v1.WatchEvent"

3.2.270.3. Consumes

- /

3.2.270.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf
- application/json;stream=watch
- application/vnd.kubernetes.protobuf;stream=watch

3.2.270.5. Tags

- apiv1

3.2.271. watch individual changes to a list of Pod

```
GET /api/v1/watch/namespaces/{namespace}/pods
```

3.2.271.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParamter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParamter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParamter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParam eter	resourceVersion	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParam eter	timeoutSeconds	Timeout for the list/watch call.	false	integer	
PathParam eter	namespace	object name and auth scope, such as for teams and projects	true	string	

3.2.271.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.291, "v1.WatchEvent"

3.2.271.3. Consumes

- /

3.2.271.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf
- application/json;stream=watch
- application/vnd.kubernetes.protobuf;stream=watch

3.2.271.5. Tags

- apiv1

3.2.272. watch changes to an object of kind Pod

```
GET /api/v1/watch/namespaces/{namespace}/pods/{name}
```

3.2.272.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParam eter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParam ter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParam ter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParam eter	resourceVersi on	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParam eter	timeoutSecon ds	Timeout for the list/watch call.	false	integer	
PathParam eter	namespace	object name and auth scope, such as for teams and projects	true	string	

Type	Name	Description	Required	Schema	Default
PathParamet er	name	name of the Pod	true	string	

3.2.272.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.291, "v1.WatchEvent"

3.2.272.3. Consumes

- /

3.2.272.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf
- application/json;stream=watch
- application/vnd.kubernetes.protobuf;stream=watch

3.2.272.5. Tags

- apiv1

3.2.273. watch individual changes to a list of PodTemplate

GET /api/v1/watch/namespaces/{namespace}/podtemplates

3.2.273.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParame ter	pretty	If 'true', then the output is pretty printed.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParam ter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParam ter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParam ter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParamter	resourceVersion	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParamter	timeoutSeconds	Timeout for the list/watch call.	false	integer	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	

3.2.273.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.291, "v1.WatchEvent"

3.2.273.3. Consumes

- /

3.2.273.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf
- application/json;stream=watch
- application/vnd.kubernetes.protobuf;stream=watch

3.2.273.5. Tags

- apiv1

3.2.274. watch changes to an object of kind PodTemplate

```
GET /api/v1/watch/namespaces/{namespace}/podtemplates/{name}
```

3.2.274.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParam eter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParam ter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParam ter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParam eter	resourceVersi on	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParam eter	timeoutSecon ds	Timeout for the list/watch call.	false	integer	
PathParamet er	namespace	object name and auth scope, such as for teams and projects	true	string	

Type	Name	Description	Required	Schema	Default
PathParamet er	name	name of the PodTemplate	true	string	

3.2.274.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.291, "v1.WatchEvent"

3.2.274.3. Consumes

- /

3.2.274.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf
- application/json;stream=watch
- application/vnd.kubernetes.protobuf;stream=watch

3.2.274.5. Tags

- apiv1

3.2.275. watch individual changes to a list of ReplicationController

GET /api/v1/watch/namespaces/{namespace}/replicationcontrollers

3.2.275.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParam ter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParam ter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParam ter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParamter	resourceVersion	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParamter	timeoutSeconds	Timeout for the list/watch call.	false	integer	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	

3.2.275.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.291, "v1.WatchEvent"

3.2.275.3. Consumes

- /

3.2.275.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf
- application/json;stream=watch
- application/vnd.kubernetes.protobuf;stream=watch

3.2.275.5. Tags

- apiv1

3.2.276. watch changes to an object of kind ReplicationController

```
GET /api/v1/watch/namespaces/{namespace}/replicationcontrollers/{name}
```

3.2.276.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParam eter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParam ter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParam ter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParam eter	resourceVersi on	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParam eter	timeoutSecon ds	Timeout for the list/watch call.	false	integer	
PathParamet er	namespace	object name and auth scope, such as for teams and projects	true	string	

Type	Name	Description	Required	Schema	Default
PathParam eter	name	name of the ReplicationController	true	string	

3.2.276.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.291, "v1.WatchEvent"

3.2.276.3. Consumes

- /

3.2.276.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf
- application/json;stream=watch
- application/vnd.kubernetes.protobuf;stream=watch

3.2.276.5. Tags

- apiv1

3.2.277. watch individual changes to a list of ResourceQuota

GET /api/v1/watch/namespaces/{namespace}/resourcequotas

3.2.277.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParam ter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParam ter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParam ter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParam eter	resourceVersi on	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParam eter	timeoutSecon ds	Timeout for the list/watch call.	false	integer	
PathParamet er	namespace	object name and auth scope, such as for teams and projects	true	string	

3.2.277.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.291, "v1.WatchEvent"

3.2.277.3. Consumes

- /

3.2.277.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf
- application/json;stream=watch
- application/vnd.kubernetes.protobuf;stream=watch

3.2.277.5. Tags

- apiv1

3.2.278. watch changes to an object of kind ResourceQuota

```
GET /api/v1/watch/namespaces/{namespace}/resourcequotas/{name}
```

3.2.278.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParam eter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParam ter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParam ter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParam eter	resourceVersi on	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParam eter	timeoutSecon ds	Timeout for the list/watch call.	false	integer	
PathParam eter	namespace	object name and auth scope, such as for teams and projects	true	string	

Type	Name	Description	Required	Schema	Default
PathParam eter	name	name of the ResourceQuota	true	string	

3.2.278.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.291, "v1.WatchEvent"

3.2.278.3. Consumes

- /

3.2.278.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf
- application/json;stream=watch
- application/vnd.kubernetes.protobuf;stream=watch

3.2.278.5. Tags

- apiv1

3.2.279. watch individual changes to a list of Secret

```
GET /api/v1/watch/namespaces/{namespace}/secrets
```

3.2.279.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParam ter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParam ter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParam ter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParam eter	resourceVersi on	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParam eter	timeoutSecon ds	Timeout for the list/watch call.	false	integer	
PathParamet er	namespace	object name and auth scope, such as for teams and projects	true	string	

3.2.279.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.291, "v1.WatchEvent"

3.2.279.3. Consumes

- /

3.2.279.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf
- application/json;stream=watch
- application/vnd.kubernetes.protobuf;stream=watch

3.2.279.5. Tags

- apiv1

3.2.280. watch changes to an object of kind Secret

```
GET /api/v1/watch/namespaces/{namespace}/secrets/{name}
```

3.2.280.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParam eter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParam ter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParam ter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParam eter	resourceVersi on	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParam eter	timeoutSecon ds	Timeout for the list/watch call.	false	integer	
PathParamet er	namespace	object name and auth scope, such as for teams and projects	true	string	

Type	Name	Description	Required	Schema	Default
PathParamet er	name	name of the Secret	true	string	

3.2.280.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.291, "v1.WatchEvent"

3.2.280.3. Consumes

- /

3.2.280.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf
- application/json;stream=watch
- application/vnd.kubernetes.protobuf;stream=watch

3.2.280.5. Tags

- apiv1

3.2.281. watch individual changes to a list of ServiceAccount

GET /api/v1/watch/namespaces/{namespace}/serviceaccounts

3.2.281.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamet er	pretty	If 'true', then the output is pretty printed.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParam ter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParam ter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParam ter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParam eter	resourceVersi on	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParam eter	timeoutSecon ds	Timeout for the list/watch call.	false	integer	
PathParamet er	namespace	object name and auth scope, such as for teams and projects	true	string	

3.2.281.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.291, "v1.WatchEvent"

3.2.281.3. Consumes

- /

3.2.281.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf
- application/json;stream=watch
- application/vnd.kubernetes.protobuf;stream=watch

3.2.281.5. Tags

- apiv1

3.2.282. watch changes to an object of kind ServiceAccount

```
GET /api/v1/watch/namespaces/{namespace}/serviceaccounts/{name}
```

3.2.282.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParam eter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParam ter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParam ter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParam eter	resourceVersi on	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParam eter	timeoutSecon ds	Timeout for the list/watch call.	false	integer	
PathParam eter	namespace	object name and auth scope, such as for teams and projects	true	string	

Type	Name	Description	Required	Schema	Default
PathParam eter	name	name of the ServiceAccount	true	string	

3.2.282.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.291, "v1.WatchEvent"

3.2.282.3. Consumes

- /

3.2.282.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf
- application/json;stream=watch
- application/vnd.kubernetes.protobuf;stream=watch

3.2.282.5. Tags

- apiv1

3.2.283. watch individual changes to a list of Service

GET /api/v1/watch/namespaces/{namespace}/services

3.2.283.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParam ter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParam ter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParam ter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParamter	resourceVersion	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParamter	timeoutSeconds	Timeout for the list/watch call.	false	integer	
PathParameter	namespace	object name and auth scope, such as for teams and projects	true	string	

3.2.283.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.291, "v1.WatchEvent"

3.2.283.3. Consumes

- /

3.2.283.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf
- application/json;stream=watch
- application/vnd.kubernetes.protobuf;stream=watch

3.2.283.5. Tags

- apiv1

3.2.284. watch changes to an object of kind Service

```
GET /api/v1/watch/namespaces/{namespace}/services/{name}
```

3.2.284.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParam ter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParam ter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParam eter	resourceVersi on	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParam eter	timeoutSecon ds	Timeout for the list/watch call.	false	integer	
PathParam eter	namespace	object name and auth scope, such as for teams and projects	true	string	

Type	Name	Description	Required	Schema	Default
PathParam eter	name	name of the Service	true	string	

3.2.284.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.291, "v1.WatchEvent"

3.2.284.3. Consumes

- /

3.2.284.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf
- application/json;stream=watch
- application/vnd.kubernetes.protobuf;stream=watch

3.2.284.5. Tags

- apiv1

3.2.285. watch changes to an object of kind Namespace

```
GET /api/v1/watch/namespaces/{name}
```

3.2.285.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParam ter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParam ter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParam ter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParam eter	resourceVersi on	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParam eter	timeoutSecon ds	Timeout for the list/watch call.	false	integer	
PathParamet er	name	name of the Namespace	true	string	

3.2.285.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.291, "v1.WatchEvent"

3.2.285.3. Consumes

- /

3.2.285.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf
- application/json;stream=watch
- application/vnd.kubernetes.protobuf;stream=watch

3.2.285.5. Tags

- apiv1

3.2.286. watch individual changes to a list of Node

GET /api/v1/watch/nodes

3.2.286.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParam ter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParam ter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParam ter	resourceVersi on	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParam ter	timeoutSecon ds	Timeout for the list/watch call.	false	integer	

3.2.286.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.291, "v1.WatchEvent"

3.2.286.3. Consumes

- /

3.2.286.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf
- application/json;stream=watch
- application/vnd.kubernetes.protobuf;stream=watch

3.2.286.5. Tags

- apiv1

3.2.287. watch changes to an object of kind Node

```
GET /api/v1/watch/nodes/{name}
```

3.2.287.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParam ter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParam ter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParam eter	resourceVersi on	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParam eter	timeoutSecon ds	Timeout for the list/watch call.	false	integer	
PathParamet er	name	name of the Node	true	string	

3.2.287.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.291, "v1.WatchEvent"

3.2.287.3. Consumes

- /

3.2.287.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf
- application/json;stream=watch
- application/vnd.kubernetes.protobuf;stream=watch

3.2.287.5. Tags

- apiv1

3.2.288. watch individual changes to a list of PersistentVolumeClaim

GET /api/v1/watch/persistentvolumeclaims

3.2.288.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParameter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParameter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParam ter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParam ter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParam ter	resourceVersi on	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParam ter	timeoutSecon ds	Timeout for the list/watch call.	false	integer	

3.2.288.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.291, "v1.WatchEvent"

3.2.288.3. Consumes

- /

3.2.288.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf
- application/json;stream=watch
- application/vnd.kubernetes.protobuf;stream=watch

3.2.288.5. Tags

- apiv1

3.2.289. watch individual changes to a list of PersistentVolume

GET /api/v1/watch/persistentvolumes

3.2.289.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParam eter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParam ter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParam ter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParam ter	resourceVersi on	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParam ter	timeoutSecon ds	Timeout for the list/watch call.	false	integer	

3.2.289.2. Responses

HTTP Code	Description	Schema
-----------	-------------	--------

HTTP Code	Description	Schema
200	success	Section 2.3.291, "v1.WatchEvent"

3.2.289.3. Consumes

- /

3.2.289.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf
- application/json;stream=watch
- application/vnd.kubernetes.protobuf;stream=watch

3.2.289.5. Tags

- apiv1

3.2.290. watch changes to an object of kind PersistentVolume

```
GET /api/v1/watch/persistentvolumes/{name}
```

3.2.290.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParam eter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParam ter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParam ter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParam eter	resourceVersi on	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParam eter	timeoutSecon ds	Timeout for the list/watch call.	false	integer	
PathParam eter	name	name of the PersistentVolume	true	string	

3.2.290.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.291, "v1.WatchEvent"

3.2.290.3. Consumes

- /

3.2.290.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf
- application/json;stream=watch
- application/vnd.kubernetes.protobuf;stream=watch

3.2.290.5. Tags

- apiv1

3.2.291. watch individual changes to a list of Pod

GET /api/v1/watch/pods

3.2.291.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParam ter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParam ter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParamter	resourceVersion	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParamter	timeoutSeconds	Timeout for the list/watch call.	false	integer	

3.2.291.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.291, "v1.WatchEvent"

3.2.291.3. Consumes

- /

3.2.291.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf
- application/json;stream=watch
- application/vnd.kubernetes.protobuf;stream=watch

3.2.291.5. Tags

- apiv1

3.2.292. watch individual changes to a list of PodTemplate

GET /api/v1/watch/podtemplates

3.2.292.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParam eter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParam ter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParam ter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParam ter	resourceVersi on	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParam ter	timeoutSecon ds	Timeout for the list/watch call.	false	integer	

3.2.292.2. Responses

HTTP Code	Description	Schema
-----------	-------------	--------

HTTP Code	Description	Schema
200	success	Section 2.3.291, "v1.WatchEvent"

3.2.292.3. Consumes

- /

3.2.292.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf
- application/json;stream=watch
- application/vnd.kubernetes.protobuf;stream=watch

3.2.292.5. Tags

- apiv1

3.2.293. watch individual changes to a list of ReplicationController

GET /api/v1/watch/replicationcontrollers

3.2.293.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParam ter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParam ter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParamter	resourceVersion	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParamter	timeoutSeconds	Timeout for the list/watch call.	false	integer	

3.2.293.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.291, "v1.WatchEvent"

3.2.293.3. Consumes

- /

3.2.293.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf
- application/json;stream=watch
- application/vnd.kubernetes.protobuf;stream=watch

3.2.293.5. Tags

- apiv1

3.2.294. watch individual changes to a list of ResourceQuota

GET /api/v1/watch/resourcequotas

3.2.294.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParam eter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParam ter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParam ter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParam ter	resourceVersi on	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParam ter	timeoutSecon ds	Timeout for the list/watch call.	false	integer	

3.2.294.2. Responses

HTTP Code	Description	Schema
-----------	-------------	--------

HTTP Code	Description	Schema
200	success	Section 2.3.291, "v1.WatchEvent"

3.2.294.3. Consumes

- /

3.2.294.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf
- application/json;stream=watch
- application/vnd.kubernetes.protobuf;stream=watch

3.2.294.5. Tags

- apiv1

3.2.295. watch individual changes to a list of Secret

GET /api/v1/watch/secrets

3.2.295.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParam ter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParam ter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParamter	resourceVersion	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParamter	timeoutSeconds	Timeout for the list/watch call.	false	integer	

3.2.295.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.291, "v1.WatchEvent"

3.2.295.3. Consumes

- /

3.2.295.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf
- application/json;stream=watch
- application/vnd.kubernetes.protobuf;stream=watch

3.2.295.5. Tags

- apiv1

3.2.296. watch individual changes to a list of SecurityContextConstraints

GET /api/v1/watch/securitycontextconstraints

3.2.296.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParam eter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParam ter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParam ter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParamter	resourceVersion	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParamter	timeoutSeconds	Timeout for the list/watch call.	false	integer	

3.2.296.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.291, "v1.WatchEvent"

3.2.296.3. Consumes

- /

3.2.296.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf
- application/json;stream=watch
- application/vnd.kubernetes.protobuf;stream=watch

3.2.296.5. Tags

- apiv1

3.2.297. watch changes to an object of kind SecurityContextConstraints

GET /api/v1/watch/securitycontextconstraints/{name}

3.2.297.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParam eter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParam eter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	
QueryParam eter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParam ter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParam eter	resourceVersi on	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParam eter	timeoutSecon ds	Timeout for the list/watch call.	false	integer	
PathParamet er	name	name of the SecurityCont extConstraint s	true	string	

3.2.297.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.291, "v1.WatchEvent"

3.2.297.3. Consumes

- /

3.2.297.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf
- application/json;stream=watch
- application/vnd.kubernetes.protobuf;stream=watch

3.2.297.5. Tags

- apiv1

3.2.298. watch individual changes to a list of ServiceAccount

GET /api/v1/watch/serviceaccounts

3.2.298.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParameter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParameter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParam ter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParam ter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParam ter	resourceVersi on	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParam ter	timeoutSecon ds	Timeout for the list/watch call.	false	integer	

3.2.298.2. Responses

HTTP Code	Description	Schema
200	success	Section 2.3.291, "v1.WatchEvent"

3.2.298.3. Consumes

- /

3.2.298.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf
- application/json;stream=watch
- application/vnd.kubernetes.protobuf;stream=watch

3.2.298.5. Tags

- apiv1

3.2.299. watch individual changes to a list of Service

GET /api/v1/watch/services

3.2.299.1. Parameters

Type	Name	Description	Required	Schema	Default
QueryParamter	pretty	If 'true', then the output is pretty printed.	false	string	
QueryParamter	labelSelector	A selector to restrict the list of returned objects by their labels. Defaults to everything.	false	string	

Type	Name	Description	Required	Schema	Default
QueryParameter	fieldSelector	A selector to restrict the list of returned objects by their fields. Defaults to everything.	false	string	
QueryParameter	watch	Watch for changes to the described resources and return them as a stream of add, update, and remove notifications. Specify resourceVersion.	false	boolean	

Type	Name	Description	Required	Schema	Default
QueryParam ter	resourceVersi on	When specified with a watch call, shows changes that occur after that particular version of a resource. Defaults to changes from the beginning of history. When specified for list: - if unset, then the result is returned from remote storage based on quorum-read flag; - if it's 0, then we simply return what we currently have in cache, no guarantee; - if set to non zero, then the result is at least as fresh as given rv.	false	string	
QueryParam ter	timeoutSecon ds	Timeout for the list/watch call.	false	integer	

3.2.299.2. Responses

HTTP Code	Description	Schema
-----------	-------------	--------

HTTP Code	Description	Schema
200	success	Section 2.3.291, "v1.WatchEvent"

3.2.299.3. Consumes

- /

3.2.299.4. Produces

- application/json
- application/yaml
- application/vnd.kubernetes.protobuf
- application/json;stream=watch
- application/vnd.kubernetes.protobuf;stream=watch

3.2.299.5. Tags

- apiv1

3.3. DEFINITIONS

3.3.1. types.UID

3.3.2. v1.APIResource

APIResource specifies the name of a resource and whether it is namespaced.

Name	Description	Required	Schema	Default
name	name is the name of the resource.	true	string	
namespaced	namespaced indicates if a resource is namespaced or not.	true	boolean	
kind	kind is the kind for the resource (e.g. 'Foo' is the kind for a resource 'foo')	true	string	

Name	Description	Required	Schema	Default
verbs	verbs is a list of supported kube verbs (this includes get, list, watch, create, update, patch, delete, deletecollection, and proxy)	true	string array	
shortNames	shortNames is a list of suggested short names of the resource.	false	string array	

3.3.3. v1.APIResourceList

APIResourceList is a list of APIResource, it is used to expose the name of the resources supported in a specific group and version, and if the resource is namespaced.

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#types-kinds	false	string	

Name	Description	Required	Schema	Default
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#resources	false	string	
groupVersion	groupVersion is the group and version this APIResourceList is for.	true	string	
resources	resources contains the name of the resources and if they are namespaced.	true	Section 2.3.4, "v1.APIResource" array	

3.3.4. v1.AWSElasticBlockStoreVolumeSource

Represents a Persistent Disk resource in AWS.

An AWS EBS disk must exist before mounting to a container. The disk must also be in the same AWS zone as the kubelet. An AWS EBS disk can only be mounted as read/write once. AWS EBS volumes support ownership management and SELinux relabeling.

Name	Description	Required	Schema	Default
------	-------------	----------	--------	---------

Name	Description	Required	Schema	Default
volumeID	Unique ID of the persistent disk resource in AWS (Amazon EBS volume). More info: http://kubernetes.io/docs/user-guide/volumes#awselasticblockstore	true	string	
fsType	Filesystem type of the volume that you want to mount. Tip: Ensure that the filesystem type is supported by the host operating system. Examples: "ext4", "xfs", "ntfs". Implicitly inferred to be "ext4" if unspecified. More info: http://kubernetes.io/docs/user-guide/volumes#awselasticblockstore	false	string	

Name	Description	Required	Schema	Default
partition	The partition in the volume that you want to mount. If omitted, the default is to mount by volume name. Examples: For volume /dev/sda1, you specify the partition as "1". Similarly, the volume partition for /dev/sda is "0" (or you can leave the property empty).	false	integer (int32)	
readOnly	Specify "true" to force and set the ReadOnly property in VolumeMounts to "true". If omitted, the default is "false". More info: http://kubernetes.io/docs/user-guide/volumes#awselasticblocksstore	false	boolean	

3.3.5. v1.Affinity

Affinity is a group of affinity scheduling rules.

Name	Description	Required	Schema	Default
nodeAffinity	Describes node affinity scheduling rules for the pod.	false	Section 2.3.163, "v1.NodeAffinity"	

Name	Description	Required	Schema	Default
podAffinity	Describes pod affinity scheduling rules (e.g. co-locate this pod in the same node, zone, etc. as some other pod(s)).	false	Section 2.3.183, "v1.PodAffinity"	
podAntiAffinity	Describes pod anti-affinity scheduling rules (e.g. avoid putting this pod in the same node, zone, etc. as some other pod(s)).	false	Section 2.3.185, "v1.PodAntiAffinity"	

3.3.6. v1.AttachedVolume

AttachedVolume describes a volume attached to a node

Name	Description	Required	Schema	Default
name	Name of the attached volume	true	string	
devicePath	DevicePath represents the device path where the volume should be available	true	string	

3.3.7. v1.AzureDataDiskCachingMode

3.3.8. v1.AzureDiskVolumeSource

AzureDisk represents an Azure Data Disk mount on the host and bind mount to the pod.

Name	Description	Required	Schema	Default
diskName	The Name of the data disk in the blob storage	true	string	

Name	Description	Required	Schema	Default
diskURI	The URI the data disk in the blob storage	true	string	
cachingMode	Host Caching mode: None, Read Only, Read Write.	false	Section 2.3.10, "v1.AzureDataDiskCachingMode"	
fsType	Filesystem type to mount. Must be a filesystem type supported by the host operating system. Ex. "ext4", "xfs", "ntfs". Implicitly inferred to be "ext4" if unspecified.	false	string	
readOnly	Defaults to false (read/write). ReadOnly here will force the ReadOnly setting in VolumeMounts.	false	boolean	

3.3.9. v1.AzureFileVolumeSource

AzureFile represents an Azure File Service mount on the host and bind mount to the pod.

Name	Description	Required	Schema	Default
secretName	the name of secret that contains Azure Storage Account Name and Key	true	string	
shareName	Share Name	true	string	

Name	Description	Required	Schema	Default
readOnly	Defaults to false (read/write). ReadOnly here will force the ReadOnly setting in VolumeMounts.	false	boolean	

3.3.10. v1.Binding

Binding ties one object to another. For example, a pod is bound to a node by a scheduler.

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/HEAD/docs/dev/api-conventions.md#types-kinds	false	string	

Name	Description	Required	Schema	Default
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#resources	false	string	
metadata	Standard object's metadata. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#metadata	false	Section 2.3.176, "v1.ObjectMeta"	
target	The target object that you want to bind to the standard object.	true	Section 2.3.177, "v1.ObjectReference"	

3.3.11. v1.Capabilities

Adds and removes POSIX capabilities from running containers.

Name	Description	Required	Schema	Default
add	Added capabilities	false	Section 2.3.34, "v1.Capability" array	

Name	Description	Required	Schema	Default
drop	Removed capabilities	false	Section 2.3.34, "v1.Capability" array	

3.3.12. v1.Capability

3.3.13. v1.CephFSVolumeSource

Represents a Ceph Filesystem mount that lasts the lifetime of a pod Cephfs volumes do not support ownership management or SELinux relabeling.

Name	Description	Required	Schema	Default
monitors	Required: Monitors is a collection of Ceph monitors More info: http://releases.k8s.io/HEAD/examples/volumes/cephfs/README.md#how-to-use-it	true	string array	
path	Optional: Used as the mounted root, rather than the full Ceph tree, default is /	false	string	
user	Optional: User is the rados user name, default is admin More info: http://releases.k8s.io/HEAD/examples/volumes/cephfs/README.md#how-to-use-it	false	string	

Name	Description	Required	Schema	Default
secretFile	Optional: SecretFile is the path to key ring for User, default is /etc/ceph/user.secret More info: http://releases.k8s.io/HEAD/examples/volumes/cephfs/README.md#how-to-use-it	false	string	
secretRef	Optional: SecretRef is reference to the authentication secret for User, default is empty. More info: http://releases.k8s.io/HEAD/examples/volumes/cephfs/README.md#how-to-use-it	false	Section 2.3.152, "v1.LocalObjectReference"	
readOnly	Optional: Defaults to false (read/write). ReadOnly here will force the ReadOnly setting in VolumeMounts. More info: http://releases.k8s.io/HEAD/examples/volumes/cephfs/README.md#how-to-use-it	false	boolean	

3.3.14. v1.CinderVolumeSource

Represents a cinder volume resource in Openstack. A Cinder volume must exist before mounting to a container. The volume must also be in the same region as the kubelet. Cinder volumes support ownership management and SELinux relabeling.

Name	Description	Required	Schema	Default
volumeID	volume id used to identify the volume in cinder More info: http://releases.k8s.io/HEAD/examples/mysql-cinder-pd/README.md	true	string	
fsType	Filesystem type to mount. Must be a filesystem type supported by the host operating system. Examples: "ext4", "xfs", "ntfs". Implicitly inferred to be "ext4" if unspecified. More info: http://releases.k8s.io/HEAD/examples/mysql-cinder-pd/README.md	false	string	
readOnly	Optional: Defaults to false (read/write). ReadOnly here will force the ReadOnly setting in VolumeMounts. More info: http://releases.k8s.io/HEAD/examples/mysql-cinder-pd/README.md	false	boolean	

3.3.15. v1.ComponentCondition

Information about the condition of a component.

Name	Description	Required	Schema	Default
type	Type of condition for a component. Valid value: "Healthy"	true	string	
status	Status of the condition for a component. Valid values for "Healthy": "True", "False", or "Unknown".	true	string	
message	Message about the condition for a component. For example, information about a health check.	false	string	
error	Condition error code for a component. For example, a health check error code.	false	string	

3.3.16. v1.ComponentStatus

ComponentStatus (and ComponentStatusList) holds the cluster validation info.

Name	Description	Required	Schema	Default
------	-------------	----------	--------	---------

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#types-kinds	false	string	
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#resources	false	string	

Name	Description	Required	Schema	Default
metadata	Standard object's metadata. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#metadata	false	Section 2.3.176, "v1.ObjectMeta"	
conditions	List of component conditions observed	false	Section 3.3.15, "v1.ComponentCondition" array	

3.3.17. v1.ComponentStatusList

Status of all the conditions for the component as a list of ComponentStatus objects.

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#types-kinds	false	string	

Name	Description	Required	Schema	Default
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/HEAD/docs/dev/api-conventions.md#resources	false	string	
metadata	Standard list metadata. More info: http://releases.k8s.io/HEAD/docs/dev/api-conventions.md#types-kinds	false	Section 2.3.151, "v1.ListMeta"	
items	List of ComponentStatus objects.	true	Section 3.3.16, "v1.ComponentStatus" array	

3.3.18. v1.ConfigMap

ConfigMap holds configuration data for pods to consume.

Name	Description	Required	Schema	Default
------	-------------	----------	--------	---------

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#types-kinds	false	string	
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#resources	false	string	
metadata	Standard object's metadata. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#metadata	false	Section 2.3.176, "v1.ObjectMeta"	

Name	Description	Required	Schema	Default
data	Data contains the configuration data. Each key must be a valid DNS_SUBDOMAIN with an optional leading dot.	false	object	

3.3.19. v1.ConfigMapEnvSource

ConfigMapEnvSource selects a ConfigMap to populate the environment variables with.

The contents of the target ConfigMap's Data field will represent the key-value pairs as environment variables.

Name	Description	Required	Schema	Default
name	Name of the referent. More info: http://kubernetes.io/docs/user-guide/identifiers#names	false	string	
optional	Specify whether the ConfigMap must be defined	false	boolean	

3.3.20. v1.ConfigMapKeySelector

Selects a key from a ConfigMap.

Name	Description	Required	Schema	Default
name	Name of the referent. More info: http://kubernetes.io/docs/user-guide/identifiers#names	false	string	
key	The key to select.	true	string	

Name	Description	Required	Schema	Default
optional	Specify whether the ConfigMap or it's key must be defined	false	boolean	

3.3.21. v1.ConfigMapList

ConfigMapList is a resource containing a list of ConfigMap objects.

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/HEAD/docs/dev/api-conventions.md#types-kinds	false	string	

Name	Description	Required	Schema	Default
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#resources	false	string	
metadata	More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#metadata	false	Section 2.3.151, "v1.ListMeta"	
items	Items is the list of ConfigMaps.	true	Section 3.3.18, "v1.ConfigMap" array	

3.3.22. v1.ConfigMapProjection

Adapts a ConfigMap into a projected volume.

The contents of the target ConfigMap's Data field will be presented in a projected volume as files using the keys in the Data field as the file names, unless the items element is populated with specific mappings of keys to paths. Note that this is identical to a configmap volume source without the default mode.

Name	Description	Required	Schema	Default
------	-------------	----------	--------	---------

Name	Description	Required	Schema	Default
name	Name of the referent. More info: http://kubernetes.io/docs/user-guide/identifiers#names	false	string	
items	If unspecified, each key-value pair in the Data field of the referenced ConfigMap will be projected into the volume as a file whose name is the key and content is the value. If specified, the listed keys will be projected into the specified paths, and unlisted keys will not be present. If a key is specified which is not present in the ConfigMap, the volume setup will error unless it is marked optional. Paths must be relative and may not contain the '..' path or start with '..'.	false	Section 2.3.146 , "v1.KeyToPath" array	
optional	Specify whether the ConfigMap or it's keys must be defined	false	boolean	

3.3.23. v1.ConfigMapVolumeSource

Adapts a ConfigMap into a volume.

The contents of the target ConfigMap's Data field will be presented in a volume as files using the keys in the Data field as the file names, unless the items element is populated with specific mappings of keys to paths. ConfigMap volumes support ownership management and SELinux relabeling.

Name	Description	Required	Schema	Default
name	Name of the referent. More info: http://kubernetes.io/docs/user-guide/identifiers#names	false	string	
items	If unspecified, each key-value pair in the Data field of the referenced ConfigMap will be projected into the volume as a file whose name is the key and content is the value. If specified, the listed keys will be projected into the specified paths, and unlisted keys will not be present. If a key is specified which is not present in the ConfigMap, the volume setup will error unless it is marked optional. Paths must be relative and may not contain the '..' path or start with '..'.	false	Section 2.3.146, "v1.KeyToPath" array	

Name	Description	Required	Schema	Default
defaultMode	Optional: mode bits to use on created files by default. Must be a value between 0 and 0777. Defaults to 0644. Directories within the path are not affected by this setting. This might be in conflict with other options that affect the file mode, like fsGroup, and the result can be other mode bits set.	false	integer (int32)	
optional	Specify whether the ConfigMap or it's keys must be defined	false	boolean	

3.3.24. v1.Container

A single application container that you want to run within a pod.

Name	Description	Required	Schema	Default
name	Name of the container specified as a DNS_LABEL. Each container in a pod must have a unique name (DNS_LABEL). Cannot be updated.	true	string	
image	Docker image name. More info: http://kubernetes.io/docs/user-guide/images	false	string	

Name	Description	Required	Schema	Default
command	<p>Entrypoint array. Not executed within a shell. The docker image's ENTRYPOINT is used if this is not provided. Variable references \$(VAR_NAME) are expanded using the container's environment. If a variable cannot be resolved, the reference in the input string will be unchanged. The \$(VAR_NAME) syntax can be escaped with a double , ie: (VAR_NAME). Escaped references will never be expanded, regardless of whether the variable exists or not. Cannot be updated. More info: http://kubernetes.io/docs/user-guide/containers#containers-and-commands</p>	false	string array	

Name	Description	Required	Schema	Default
args	<p>Arguments to the entrypoint. The docker image's CMD is used if this is not provided. Variable references \$(VAR_NAME) are expanded using the container's environment. If a variable cannot be resolved, the reference in the input string will be unchanged. The \$(VAR_NAME) syntax can be escaped with a double , ie: \$(VAR_NAME). Escaped references will never be expanded, regardless of whether the variable exists or not. Cannot be updated. More info: http://kubernetes.io/docs/user-guide/containers#containers-and-commands</p>	false	string array	

Name	Description	Required	Schema	Default
workingDir	Container's working directory. If not specified, the container runtime's default will be used, which might be configured in the container image. Cannot be updated.	false	string	
ports	List of ports to expose from the container. Exposing a port here gives the system additional information about the network connections a container uses, but is primarily informational. Not specifying a port here DOES NOT prevent that port from being exposed. Any port which is listening on the default "0.0.0.0" address inside a container will be accessible from the network. Cannot be updated.	false	Section 2.3.58, "v1.ContainerPort" array	

Name	Description	Required	Schema	Default
envFrom	List of sources to populate environment variables in the container. The keys defined within a source must be a C_IDENTIFIER. All invalid keys will be reported as an event when the container is starting. When a key exists in multiple sources, the value associated with the last source will take precedence. Values defined by an Env with a duplicate key will take precedence. Cannot be updated.	false	Section 2.3.92, "v1.EnvFromSource" array	
env	List of environment variables to set in the container. Cannot be updated.	false	Section 2.3.93, "v1.EnvVar" array	
resources	Compute Resources required by this container. Cannot be updated. More info: http://kubernetes.io/docs/user-guide/persistent-volumes#resources	false	Section 2.3.223, "v1.ResourceRequirements"	

Name	Description	Required	Schema	Default
volumeMounts	Pod volumes to mount into the container's filesystem. Cannot be updated.	false	Section 2.3.288, "v1.VolumeMount" array	
livenessProbe	Periodic probe of container liveness. Container will be restarted if the probe fails. Cannot be updated. More info: http://kubernetes.io/docs/user-guide/pod-states#container-probes	false	Section 2.3.205, "v1.Probe"	
readinessProbe	Periodic probe of container service readiness. Container will be removed from service endpoints if the probe fails. Cannot be updated. More info: http://kubernetes.io/docs/user-guide/pod-states#container-probes	false	Section 2.3.205, "v1.Probe"	
lifecycle	Actions that the management system should take in response to container lifecycle events. Cannot be updated.	false	Section 2.3.149, "v1.Lifecycle"	

Name	Description	Required	Schema	Default
terminationMessagePath	Optional: Path at which the file to which the container's termination message will be written is mounted into the container's filesystem. Message written is intended to be brief final status, such as an assertion failure message. Will be truncated by the node if greater than 4096 bytes. The total message length across all containers will be limited to 12kb. Defaults to /dev/termination-log. Cannot be updated.	false	string	

Name	Description	Required	Schema	Default
terminationMessagePolicy	<p>Indicate how the termination message should be populated. File will use the contents of terminationMessagePath to populate the container status message on both success and failure. FallbackToLogsOnError will use the last chunk of container log output if the termination message file is empty and the container exited with an error. The log output is limited to 2048 bytes or 80 lines, whichever is smaller. Defaults to File. Cannot be updated.</p>	false	string	
imagePullPolicy	<p>Image pull policy. One of Always, Never, IfNotPresent. Defaults to Always if :latest tag is specified, or IfNotPresent otherwise. Cannot be updated. More info: http://kubernetes.io/docs/user-guide/images#updating-images</p>	false	string	

Name	Description	Required	Schema	Default
securityContext	Security options the pod should run with. More info: http://releases.k8s.io/HEAD/docs/design/security_context.md	false	Section 2.3.251, "v1.SecurityContext"	
stdin	Whether this container should allocate a buffer for stdin in the container runtime. If this is not set, reads from stdin in the container will always result in EOF. Default is false.	false	boolean	

Name	Description	Required	Schema	Default
stdinOnce	Whether the container runtime should close the stdin channel after it has been opened by a single attach. When stdin is true the stdin stream will remain open across multiple attach sessions. If stdinOnce is set to true, stdin is opened on container start, is empty until the first client attaches to stdin, and then remains open and accepts data until the client disconnects, at which time stdin is closed and remains closed until the container is restarted. If this flag is false, a container processes that reads from stdin will never receive an EOF. Default is false	false	boolean	
tty	Whether this container should allocate a TTY for itself, also requires 'stdin' to be true. Default is false.	false	boolean	

3.3.25. v1.ContainerImage

Describe a container image

Name	Description	Required	Schema	Default
names	Names by which this image is known. e.g. ["gcr.io/google_containers/hyperkube:v1.0.7", "dockerhub.io/google_containers/hyperkube:v1.0.7"]	true	string array	
sizeBytes	The size of the image in bytes.	false	integer (int64)	

3.3.26. v1.ContainerPort

ContainerPort represents a network port in a single container.

Name	Description	Required	Schema	Default
name	If specified, this must be an IANA_SVC_NAME and unique within the pod. Each named port in a pod must have a unique name. Name for the port that can be referred to by services.	false	string	
hostPort	Number of port to expose on the host. If specified, this must be a valid port number, $0 < x < 65536$. If HostNetwork is specified, this must match ContainerPort. Most containers do not need this.	false	integer (int32)	

Name	Description	Required	Schema	Default
containerPort	Number of port to expose on the pod's IP address. This must be a valid port number, $0 < x < 65536$.	true	integer (int32)	
protocol	Protocol for port. Must be UDP or TCP. Defaults to "TCP".	false	string	
hostIP	What host IP to bind the external port to.	false	string	

3.3.27. v1.ContainerState

ContainerState holds a possible state of container. Only one of its members may be specified. If none of them is specified, the default one is ContainerStateWaiting.

Name	Description	Required	Schema	Default
waiting	Details about a waiting container	false	Section 3.3.30, "v1.ContainerStateWaiting"	
running	Details about a running container	false	Section 3.3.28, "v1.ContainerStateRunning"	
terminated	Details about a terminated container	false	Section 3.3.29, "v1.ContainerStateTerminated"	

3.3.28. v1.ContainerStateRunning

ContainerStateRunning is a running state of a container.

Name	Description	Required	Schema	Default
------	-------------	----------	--------	---------

Name	Description	Required	Schema	Default
startedAt	Time at which the container was last (re-)started	false	string	

3.3.29. v1.ContainerStateTerminated

ContainerStateTerminated is a terminated state of a container.

Name	Description	Required	Schema	Default
exitCode	Exit status from the last termination of the container	true	integer (int32)	
signal	Signal from the last termination of the container	false	integer (int32)	
reason	(brief) reason from the last termination of the container	false	string	
message	Message regarding the last termination of the container	false	string	
startedAt	Time at which previous execution of the container started	false	string	
finishedAt	Time at which the container last terminated	false	string	
containerID	Container's ID in the format 'docker://<container_id>'	false	string	

3.3.30. v1.ContainerStateWaiting

ContainerStateWaiting is a waiting state of a container.

Name	Description	Required	Schema	Default
reason	(brief) reason the container is not yet running.	false	string	
message	Message regarding why the container is not yet running.	false	string	

3.3.31. v1.ContainerStatus

ContainerStatus contains details for the current status of this container.

Name	Description	Required	Schema	Default
name	This must be a DNS_LABEL. Each container in a pod must have a unique name. Cannot be updated.	true	string	
state	Details about the container's current condition.	false	Section 3.3.27, "v1.ContainerState"	
lastState	Details about the container's last termination condition.	false	Section 3.3.27, "v1.ContainerState"	
ready	Specifies whether the container has passed its readiness probe.	true	boolean	

Name	Description	Required	Schema	Default
restartCount	The number of times the container has been restarted, currently based on the number of dead containers that have not yet been removed. Note that this is calculated from dead containers. But those containers are subject to garbage collection. This value will get capped at 5 by GC.	true	integer (int32)	
image	The image the container is running. More info: http://kubernetes.io/docs/user-guide/images	true	string	
imageID	ImageID of the container's image.	true	string	
containerID	Container's ID in the format 'docker://<container_id>'. More info: http://kubernetes.io/docs/user-guide/container-environment#container-information	false	string	

3.3.32. v1.DaemonEndpoint

DaemonEndpoint contains information about a single Daemon endpoint.

Name	Description	Required	Schema	Default
Port	Port number of the given endpoint.	true	integer (int32)	

3.3.33. v1.DeleteOptions

DeleteOptions may be provided when deleting an API object.

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#types-kinds	false	string	

Name	Description	Required	Schema	Default
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#resources	false	string	
gracePeriodSeconds	The duration in seconds before the object should be deleted. Value must be non-negative integer. The value zero indicates delete immediately. If this value is nil, the default grace period for the specified type will be used. Defaults to a per object value if not specified. zero means delete immediately.	false	integer (int64)	

Name	Description	Required	Schema	Default
preconditions	Must be fulfilled before a deletion is carried out. If not possible, a 409 Conflict status will be returned.	false	Section 2.3.203, "v1.Preconditions"	
orphanDependencies	Deprecated: please use the PropagationPolicy, this field will be deprecated in 1.7. Should the dependent objects be orphaned. If true/false, the "orphan" finalizer will be added to/removed from the object's finalizers list. Either this field or PropagationPolicy may be set, but not both.	false	boolean	
propagationPolicy	Whether and how garbage collection will be performed. Either this field or OrphanDependencies may be set, but not both. The default policy is decided by the existing finalizer set in the metadata.finalizers and the resource-specific default policy.	false	Section 2.3.62, "v1.DeletionPropagation"	

3.3.34. v1.DeletionPropagation

3.3.35. v1.DeprecatedDownwardAPIVolumeFile

DeprecatedDownwardAPIVolumeFile represents information to create the file containing the pod field. This type is deprecated and should be replaced by use of the downwardAPI volume source.

Name	Description	Required	Schema	Default
name	Required: Name is the relative path name of the file to be created. Must not be absolute or contain the '..' path. Must be utf-8 encoded. The first item of the relative path must not start with '..'	true	string	
fieldRef	Required: Selects a field of the pod: only annotations, labels, name and namespace are supported.	false	Section 2.3.175, "v1.ObjectFieldSelector"	
resourceFieldRef	Selects a resource of the container: only resources limits and requests (limits.cpu, limits.memory, requests.cpu and requests.memory) are currently supported.	false	Section 2.3.218, "v1.ResourceFieldSelector"	

Name	Description	Required	Schema	Default
mode	Optional: mode bits to use on this file, must be a value between 0 and 0777. If not specified, the volume defaultMode will be used. This might be in conflict with other options that affect the file mode, like fsGroup, and the result can be other mode bits set.	false	integer (int32)	

3.3.36. v1.DeprecatedDownwardAPIVolumeSource

DeprecatedDownwardAPIVolumeSource represents a volume containing downward API info. This type is deprecated and should be replaced by use of the downwardAPI volume source.

Name	Description	Required	Schema	Default
items	Items is a list of downward API volume file	false	Section 2.3.79, "v1.Deprecated DownwardAPIVolumeFile" array	

Name	Description	Required	Schema	Default
defaultMode	Optional: mode bits to use on created files by default. Must be a value between 0 and 0777. Defaults to 0644. Directories within the path are not affected by this setting. This might be in conflict with other options that affect the file mode, like fsGroup, and the result can be other mode bits set.	false	integer (int32)	

3.3.37. v1.DownwardAPIProjection

Represents downward API info for projecting into a projected volume. Note that this is identical to a downwardAPI volume source without the default mode.

Name	Description	Required	Schema	Default
items	Items is a list of DownwardAPIVolumeFile	false	Section 2.3.84, "v1.DownwardAPIVolumeFile" array	

3.3.38. v1.DownwardAPIVolumeFile

DownwardAPIVolumeFile represents information to create the file containing the pod field

Name	Description	Required	Schema	Default
------	-------------	----------	--------	---------

Name	Description	Required	Schema	Default
path	Required: Path is the relative path name of the file to be created. Must not be absolute or contain the '..' path. Must be utf-8 encoded. The first item of the relative path must not start with '..'	true	string	
fieldRef	Required: Selects a field of the pod: only annotations, labels, name and namespace are supported.	false	Section 2.3.175, "v1.ObjectFieldSelector"	
resourceFieldRef	Selects a resource of the container: only resources limits and requests (limits.cpu, limits.memory, requests.cpu and requests.memory) are currently supported.	false	Section 2.3.218, "v1.ResourceFieldSelector"	

Name	Description	Required	Schema	Default
mode	Optional: mode bits to use on this file, must be a value between 0 and 0777. If not specified, the volume defaultMode will be used. This might be in conflict with other options that affect the file mode, like fsGroup, and the result can be other mode bits set.	false	integer (int32)	

3.3.39. v1.DownwardAPIVolumeSource

DownwardAPIVolumeSource represents a volume containing downward API info. Downward API volumes support ownership management and SELinux relabeling.

Name	Description	Required	Schema	Default
items	Items is a list of downward API volume file	false	Section 2.3.84, "v1.DownwardAPIVolumeFile" array	

Name	Description	Required	Schema	Default
defaultMode	Optional: mode bits to use on created files by default. Must be a value between 0 and 0777. Defaults to 0644. Directories within the path are not affected by this setting. This might be in conflict with other options that affect the file mode, like fsGroup, and the result can be other mode bits set.	false	integer (int32)	

3.3.40. v1.EmptyDirVolumeSource

Represents an empty directory for a pod. Empty directory volumes support ownership management and SELinux relabeling.

Name	Description	Required	Schema	Default
medium	What type of storage medium should back this directory. The default is "" which means to use the node's default medium. Must be an empty string (default) or Memory. More info: http://kubernetes.io/docs/user-guide/volumes#emptydir	false	string	

3.3.41. v1.EndpointAddress

EndpointAddress is a tuple that describes single IP address.

Name	Description	Required	Schema	Default
ip	The IP of this endpoint. May not be loopback (127.0.0.0/8), link-local (169.254.0.0/16), or link-local multicast ((224.0.0.0/24). IPv6 is also accepted but not fully supported on all platforms. Also, certain kubernetes components, like kube-proxy, are not IPv6 ready.	true	string	
hostname	The Hostname of this endpoint	false	string	
nodeName	Optional: Node hosting this endpoint. This can be used to determine endpoints local to a node.	false	string	
targetRef	Reference to object providing the endpoint.	false	Section 2.3.177, "v1.ObjectReference"	

3.3.42. v1.EndpointPort

EndpointPort is a tuple that describes a single port.

Name	Description	Required	Schema	Default
------	-------------	----------	--------	---------

Name	Description	Required	Schema	Default
name	The name of this port (corresponds to ServicePort.Name). Must be a DNS_LABEL. Optional only if one port is defined.	false	string	
port	The port number of the endpoint.	true	integer (int32)	
protocol	The IP protocol for this port. Must be UDP or TCP. Default is TCP.	false	string	

3.3.43. v1.EndpointSubset

EndpointSubset is a group of addresses with a common set of ports. The expanded set of endpoints is the Cartesian product of Addresses x Ports. For example, given:

```
{
  Addresses: [{"ip": "10.10.1.1"}, {"ip": "10.10.2.2"}],
  Ports: [{"name": "a", "port": 8675}, {"name": "b", "port": 309}]
}
```

The resulting set of endpoints can be viewed as:

```
a: [ 10.10.1.1:8675, 10.10.2.2:8675 ],
b: [ 10.10.1.1:309, 10.10.2.2:309 ]
```

Name	Description	Required	Schema	Default
addresses	IP addresses which offer the related ports that are marked as ready. These endpoints should be considered safe for load balancers and clients to utilize.	false	Section 3.3.41, "v1.EndpointAddress" array	

Name	Description	Required	Schema	Default
notReadyAddresses	IP addresses which offer the related ports but are not currently marked as ready because they have not yet finished starting, have recently failed a readiness check, or have recently failed a liveness check.	false	Section 3.3.41 , "v1.EndpointAddress" array	
ports	Port numbers available on the related IP addresses.	false	Section 3.3.42 , "v1.EndpointPort" array	

3.3.44. v1.Endpoints

Endpoints is a collection of endpoints that implement the actual service. Example:

Name: "mysvc",

Subsets: [

{

Addresses: [{"ip": "10.10.1.1"}, {"ip": "10.10.2.2"}],

Ports: [{"name": "a", "port": 8675}, {"name": "b", "port": 309}]

},

{

Addresses: [{"ip": "10.10.3.3"}],

Ports: [{"name": "a", "port": 93}, {"name": "b", "port": 76}]

},

]

Name	Description	Required	Schema	Default
------	-------------	----------	--------	---------

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#types-kinds	false	string	
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#resources	false	string	

Name	Description	Required	Schema	Default
metadata	Standard object's metadata. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#metadata	false	Section 2.3.176, "v1.ObjectMeta"	
subsets	The set of all endpoints is the union of all subsets. Addresses are placed into subsets according to the IPs they share. A single address with multiple ports, some of which are ready and some of which are not (because they come from different containers) will result in the address being displayed in different subsets for the different ports. No address will appear in both Addresses and NotReadyAddresses in the same subset. Sets of addresses and ports that comprise a service.	true	Section 3.3.43, "v1.EndpointSubset" array	

3.3.45. v1.EndpointsList

EndpointsList is a list of endpoints.

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#types-kinds	false	string	
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#resources	false	string	
metadata	Standard list metadata. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#types-kinds	false	Section 2.3.151, "v1.ListMeta"	

Name	Description	Required	Schema	Default
items	List of endpoints.	true	Section 3.3.44, “v1.Endpoints” array	

3.3.46. v1.EnvFromSource

EnvFromSource represents the source of a set of ConfigMaps

Name	Description	Required	Schema	Default
prefix	An optional identifier to prepend to each key in the ConfigMap. Must be a C_IDENTIFIER.	false	string	
configMapRef	The ConfigMap to select from	false	Section 2.3.53, “v1.ConfigMapEnvSource”	
secretRef	The Secret to select from	false	Section 2.3.245, “v1.SecretEnvSource”	

3.3.47. v1.EnvVar

EnvVar represents an environment variable present in a Container.

Name	Description	Required	Schema	Default
name	Name of the environment variable. Must be a C_IDENTIFIER.	true	string	

Name	Description	Required	Schema	Default
value	Variable references <code>\$(VAR_NAME)</code> are expanded using the previous defined environment variables in the container and any service environment variables. If a variable cannot be resolved, the reference in the input string will be unchanged. The <code>\$(VAR_NAME)</code> syntax can be escaped with a double <code>,</code> ie: <code>(VAR_NAME)</code> . Escaped references will never be expanded, regardless of whether the variable exists or not. Defaults to <code>""</code> .	false	string	
valueFrom	Source for the environment variable's value. Cannot be used if value is not empty.	false	Section 2.3.94, "v1.EnvVarSource"	

3.3.48. v1.EnvVarSource

EnvVarSource represents a source for the value of an EnvVar.

Name	Description	Required	Schema	Default
------	-------------	----------	--------	---------

Name	Description	Required	Schema	Default
fieldRef	Selects a field of the pod: supports metadata.name, metadata.names pace, metadata.labels, metadata.annotations, spec.nodeName, spec.serviceAccountName, status.podIP.	false	Section 2.3.175, "v1.ObjectFieldSelector"	
resourceFieldRef	Selects a resource of the container: only resources limits and requests (limits.cpu, limits.memory, requests.cpu and requests.memory) are currently supported.	false	Section 2.3.218, "v1.ResourceFieldSelector"	
configMapKeyRef	Selects a key of a ConfigMap.	false	Section 2.3.54, "v1.ConfigMapKeySelector"	
secretKeyRef	Selects a key of a secret in the pod's namespace	false	Section 2.3.246, "v1.SecretKeySelector"	

3.3.49. v1.Event

Event is a report of an event somewhere in the cluster.

Name	Description	Required	Schema	Default
------	-------------	----------	--------	---------

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#types-kinds	false	string	
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#resources	false	string	
metadata	Standard object's metadata. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#metadata	true	Section 2.3.176, "v1.ObjectMeta"	

Name	Description	Required	Schema	Default
involvedObject	The object that this event is about.	true	Section 2.3.177, "v1.ObjectReference"	
reason	This should be a short, machine understandable string that gives the reason for the transition into the object's current status.	false	string	
message	A human-readable description of the status of this operation.	false	string	
source	The component reporting this event. Should be a short machine understandable string.	false	Section 3.3.51, "v1.EventSource"	
firstTimestamp	The time at which the event was first recorded. (Time of server receipt is in TypeMeta.)	false	string	
lastTimestamp	The time at which the most recent occurrence of this event was recorded.	false	string	

Name	Description	Required	Schema	Default
count	The number of times this event has occurred.	false	integer (int32)	
type	Type of this event (Normal, Warning), new types could be added in the future	false	string	

3.3.50. v1.EventList

EventList is a list of events.

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#types-kinds	false	string	

Name	Description	Required	Schema	Default
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#resources	false	string	
metadata	Standard list metadata. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#types-kinds	false	Section 2.3.151, "v1.ListMeta"	
items	List of events	true	Section 3.3.49, "v1.Event" array	

3.3.51. v1.EventSource

EventSource contains information for an event.

Name	Description	Required	Schema	Default
component	Component from which the event is generated.	false	string	
host	Node name on which the event is generated.	false	string	

3.3.52. v1.ExecAction

ExecAction describes a "run in container" action.

Name	Description	Required	Schema	Default
command	Command is the command line to execute inside the container, the working directory for the command is root ('/') in the container's filesystem. The command is simply exec'd, it is not run inside a shell, so traditional shell instructions (' ', etc) won't work. To use a shell, you need to explicitly call out to that shell. Exit status of 0 is treated as live/healthy and non-zero is unhealthy.	false	string array	

3.3.53. v1.FCVolumeSource

Represents a Fibre Channel volume. Fibre Channel volumes can only be mounted as read/write once. Fibre Channel volumes support ownership management and SELinux relabeling.

Name	Description	Required	Schema	Default
targetWWNs	Required: FC target worldwide names (WWNs)	true	string array	
lun	Required: FC target lun number	true	integer (int32)	

Name	Description	Required	Schema	Default
fsType	Filesystem type to mount. Must be a filesystem type supported by the host operating system. Ex. "ext4", "xfs", "ntfs". Implicitly inferred to be "ext4" if unspecified.	false	string	
readOnly	Optional: Defaults to false (read/write). ReadOnly here will force the ReadOnly setting in VolumeMounts.	false	boolean	

3.3.54. v1.FSGroupStrategyOptions

FSGroupStrategyOptions defines the strategy type and options used to create the strategy.

Name	Description	Required	Schema	Default
type	Type is the strategy that will dictate what FSGroup is used in the SecurityContext.	false	string	
ranges	Ranges are the allowed ranges of fs groups. If you would like to force a single fs group then supply a single range with the same start and end.	false	Section 3.3.66, "v1.IDRange" array	

3.3.55. v1.FSType

3.3.56. v1.FinalizerName

3.3.57. v1.FlexVolumeSource

FlexVolume represents a generic volume resource that is provisioned/attached using an exec based plugin. This is an alpha feature and may change in future.

Name	Description	Required	Schema	Default
driver	Driver is the name of the driver to use for this volume.	true	string	
fsType	Filesystem type to mount. Must be a filesystem type supported by the host operating system. Ex. "ext4", "xfs", "ntfs". The default filesystem depends on FlexVolume script.	false	string	
secretRef	Optional: SecretRef is reference to the secret object containing sensitive information to pass to the plugin scripts. This may be empty if no secret object is specified. If the secret object contains more than one secret, all secrets are passed to the plugin scripts.	false	Section 2.3.152, "v1.LocalObject Reference"	

Name	Description	Required	Schema	Default
readOnly	Optional: Defaults to false (read/write). ReadOnly here will force the ReadOnly setting in VolumeMounts.	false	boolean	
options	Optional: Extra command options if any.	false	object	

3.3.58. v1.FlockerVolumeSource

Represents a Flocker volume mounted by the Flocker agent. One and only one of `datasetName` and `datasetUUID` should be set. Flocker volumes do not support ownership management or SELinux relabeling.

Name	Description	Required	Schema	Default
datasetName	Name of the dataset stored as metadata → name on the dataset for Flocker should be considered as deprecated	false	string	
datasetUUID	UUID of the dataset. This is unique identifier of a Flocker dataset	false	string	

3.3.59. v1.GCEPersistentDiskVolumeSource

Represents a Persistent Disk resource in Google Compute Engine.

A GCE PD must exist before mounting to a container. The disk must also be in the same GCE project and zone as the kubelet. A GCE PD can only be mounted as read/write once or read-only many times. GCE PDs support ownership management and SELinux relabeling.

Name	Description	Required	Schema	Default
------	-------------	----------	--------	---------

Name	Description	Required	Schema	Default
pdName	Unique name of the PD resource in GCE. Used to identify the disk in GCE. More info: http://kubernetes.io/docs/user-guide/volumes#gcepersistentdisk	true	string	
fsType	Filesystem type of the volume that you want to mount. Tip: Ensure that the filesystem type is supported by the host operating system. Examples: "ext4", "xfs", "ntfs". Implicitly inferred to be "ext4" if unspecified. More info: http://kubernetes.io/docs/user-guide/volumes#gcepersistentdisk	false	string	

Name	Description	Required	Schema	Default
partition	The partition in the volume that you want to mount. If omitted, the default is to mount by volume name. Examples: For volume /dev/sda1, you specify the partition as "1". Similarly, the volume partition for /dev/sda is "0" (or you can leave the property empty). More info: http://kubernetes.io/docs/user-guide/volumes#gcepersistentdisk	false	integer (int32)	
readOnly	ReadOnly here will force the ReadOnly setting in VolumeMounts. Defaults to false. More info: http://kubernetes.io/docs/user-guide/volumes#gcepersistentdisk	false	boolean	

3.3.60. v1.GitRepoVolumeSource

Represents a volume that is populated with the contents of a git repository. Git repo volumes do not support ownership management. Git repo volumes support SELinux relabeling.

Name	Description	Required	Schema	Default
repository	Repository URL	true	string	

Name	Description	Required	Schema	Default
revision	Commit hash for the specified revision.	false	string	
directory	Target directory name. Must not contain or start with '..'. If '.' is supplied, the volume directory will be the git repository. Otherwise, if specified, the volume will contain the git repository in the subdirectory with the given name.	false	string	

3.3.61. v1.GlusterfsVolumeSource

Represents a Glusterfs mount that lasts the lifetime of a pod. Glusterfs volumes do not support ownership management or SELinux relabeling.

Name	Description	Required	Schema	Default
endpoints	EndpointsName is the endpoint name that details Glusterfs topology. More info: http://releases.k8s.io/HEAD/examples/volumes/glusterfs/README.md#create-a-pod	true	string	
path	Path is the Glusterfs volume path. More info: http://releases.k8s.io/HEAD/examples/volumes/glusterfs/README.md#create-a-pod	true	string	

Name	Description	Required	Schema	Default
readOnly	ReadOnly here will force the Glusterfs volume to be mounted with read-only permissions. Defaults to false. More info: http://releases.k8s.io/HEAD/examples/volumes/glusterfs/README.md#create-a-pod	false	boolean	

3.3.62. v1.HTTPGetAction

HTTPGetAction describes an action based on HTTP Get requests.

Name	Description	Required	Schema	Default
path	Path to access on the HTTP server.	false	string	
port	Name or number of the port to access on the container. Number must be in the range 1 to 65535. Name must be an IANA_SVC_NAME	true	string	
host	Host name to connect to, defaults to the pod IP. You probably want to set "Host" in httpHeaders instead.	false	string	

Name	Description	Required	Schema	Default
scheme	Scheme to use for connecting to the host. Defaults to HTTP.	false	string	
httpHeaders	Custom headers to set in the request. HTTP allows repeated headers.	false	Section 2.3.113 , "v1.HTTPHeader" array	

3.3.63. v1.HTTPHeader

HTTPHeader describes a custom header to be used in HTTP probes

Name	Description	Required	Schema	Default
name	The header field name	true	string	
value	The header field value	true	string	

3.3.64. v1.Handler

Handler defines a specific action that should be taken

Name	Description	Required	Schema	Default
exec	One and only one of the following should be specified. Exec specifies the action to take.	false	Section 2.3.95 , "v1.ExecAction"	
httpGet	HTTPGet specifies the http request to perform.	false	Section 2.3.112 , "v1.HTTPGetAction"	

Name	Description	Required	Schema	Default
tcpSocket	TCP socket specifies an action involving a TCP port. TCP hooks not yet supported	false	Section 2.3.272, "v1.TCP socket Action"	

3.3.65. v1.HostPathVolumeSource

Represents a host path mapped into a pod. Host path volumes do not support ownership management or SELinux relabeling.

Name	Description	Required	Schema	Default
path	Path of the directory on the host. More info: http://kubernetes.io/docs/user-guide/volumes#hostpath	true	string	

3.3.66. v1.IDRange

IDRange provides a min/max of an allowed range of IDs.

Name	Description	Required	Schema	Default
min	Min is the start of the range, inclusive.	false	integer (int64)	
max	Max is the end of the range, inclusive.	false	integer (int64)	

3.3.67. v1.ISCSIVolumeSource

Represents an iSCSI disk. iSCSI volumes can only be mounted as read/write once. iSCSI volumes support ownership management and SELinux relabeling.

Name	Description	Required	Schema	Default
------	-------------	----------	--------	---------

Name	Description	Required	Schema	Default
targetPortal	iSCSI target portal. The portal is either an IP or ip_addr:port if the port is other than default (typically TCP ports 860 and 3260).	true	string	
iqn	Target iSCSI Qualified Name.	true	string	
lun	iSCSI target lun number.	true	integer (int32)	
iscsiInterface	Optional: Defaults to 'default' (tcp). iSCSI interface name that uses an iSCSI transport.	false	string	
fsType	Filesystem type of the volume that you want to mount. Tip: Ensure that the filesystem type is supported by the host operating system. Examples: "ext4", "xfs", "ntfs". Implicitly inferred to be "ext4" if unspecified. More info: http://kubernetes.io/docs/user-guide/volumes#iscsi	false	string	

Name	Description	Required	Schema	Default
readOnly	ReadOnly here will force the ReadOnly setting in VolumeMounts. Defaults to false.	false	boolean	
portals	iSCSI target portal List. The portal is either an IP or ip_addr:port if the port is other than default (typically TCP ports 860 and 3260).	false	string array	
chapAuthDiscovery	whether support iSCSI Discovery CHAP authentication	false	boolean	
chapAuthSession	whether support iSCSI Session CHAP authentication	false	boolean	
secretRef	CHAP secret for iSCSI target and initiator authentication	false	Section 2.3.152, "v1.LocalObject Reference"	

3.3.68. v1.KeyToPath

Maps a string key to a path within a volume.

Name	Description	Required	Schema	Default
key	The key to project.	true	string	

Name	Description	Required	Schema	Default
path	The relative path of the file to map the key to. May not be an absolute path. May not contain the path element '..'. May not start with the string '..'.	true	string	
mode	Optional: mode bits to use on this file, must be a value between 0 and 0777. If not specified, the volume defaultMode will be used. This might be in conflict with other options that affect the file mode, like fsGroup, and the result can be other mode bits set.	false	integer (int32)	

3.3.69. v1.LabelSelector

A label selector is a label query over a set of resources. The result of matchLabels and matchExpressions are ANDed. An empty label selector matches all objects. A null label selector matches no objects.

Name	Description	Required	Schema	Default
------	-------------	----------	--------	---------

Name	Description	Required	Schema	Default
matchLabels	matchLabels is a map of {key,value} pairs. A single {key,value} in the matchLabels map is equivalent to an element of matchExpressions, whose key field is "key", the operator is "In", and the values array contains only "value". The requirements are ANDed.	false	object	
matchExpressions	matchExpressions is a list of label selector requirements. The requirements are ANDed.	false	Section 2.3.148, "v1.LabelSelectorRequirement" array	

3.3.70. v1.LabelSelectorRequirement

A label selector requirement is a selector that contains values, a key, and an operator that relates the key and values.

Name	Description	Required	Schema	Default
key	key is the label key that the selector applies to.	true	string	
operator	operator represents a key's relationship to a set of values. Valid operators are In, NotIn, Exists and DoesNotExist.	true	string	

Name	Description	Required	Schema	Default
values	values is an array of string values. If the operator is In or NotIn, the values array must be non-empty. If the operator is Exists or DoesNotExist, the values array must be empty. This array is replaced during a strategic merge patch.	false	string array	

3.3.71. v1.Lifecycle

Lifecycle describes actions that the management system should take in response to container lifecycle events. For the PostStart and PreStop lifecycle handlers, management of the container blocks until the action is complete, unless the container process fails, in which case the handler is aborted.

Name	Description	Required	Schema	Default
postStart	PostStart is called immediately after a container is created. If the handler fails, the container is terminated and restarted according to its restart policy. Other management of the container blocks until the hook completes. More info: http://kubernetes.io/docs/user-guide/container-environment#hook-details	false	Section 2.3.114, "v1.Handler"	

Name	Description	Required	Schema	Default
preStop	<p>PreStop is called immediately before a container is terminated. The container is terminated after the handler completes. The reason for termination is passed to the handler. Regardless of the outcome of the handler, the container is eventually terminated. Other management of the container blocks until the hook completes. More info: http://kubernetes.io/docs/user-guide/container-environment#hook-details</p>	false	Section 2.3.114, "v1.Handler"	

3.3.72. v1.LimitRange

LimitRange sets resource usage limits for each kind of resource in a Namespace.

Name	Description	Required	Schema	Default
------	-------------	----------	--------	---------

Name	Description	Required	Schema	Default
kind	<p>Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#types-kinds</p>	false	string	
apiVersion	<p>APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#resources</p>	false	string	
metadata	<p>Standard object's metadata. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#metadata</p>	false	Section 2.3.176, "v1.ObjectMeta"	

Name	Description	Required	Schema	Default
spec	Spec defines the limits enforced. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#spec-and-status	false	Section 3.3.75, "v1.LimitRangeSpec"	

3.3.73. v1.LimitRangeItem

LimitRangeItem defines a min/max usage limit for any resource that matches on kind.

Name	Description	Required	Schema	Default
type	Type of resource that this limit applies to.	false	string	
max	Max usage constraints on this kind by resource name.	false	object	
min	Min usage constraints on this kind by resource name.	false	object	
default	Default resource requirement limit value by resource name if resource limit is omitted.	false	object	
defaultRequest	DefaultRequest is the default resource requirement request value by resource name if resource request is omitted.	false	object	

Name	Description	Required	Schema	Default
maxLimitReques tRatio	MaxLimitReques tRatio if specified, the named resource must have a request and limit that are both non-zero where limit divided by request is less than or equal to the enumerated value; this represents the max burst for the named resource.	false	object	

3.3.74. v1.LimitRangeList

LimitRangeList is a list of LimitRange items.

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#types-kinds	false	string	

Name	Description	Required	Schema	Default
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#resources	false	string	
metadata	Standard list metadata. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#types-kinds	false	Section 2.3.151, "v1.ListMeta"	
items	Items is a list of LimitRange objects. More info: http://releases.k8s.io/HEAD/docs/design/admission_control_limit_range.md	true	Section 3.3.72, "v1.LimitRange" array	

3.3.75. v1.LimitRangeSpec

LimitRangeSpec defines a min/max usage limit for resources that match on kind.

Name	Description	Required	Schema	Default
------	-------------	----------	--------	---------

Name	Description	Required	Schema	Default
limits	Limits is the list of LimitRangeItem objects that are enforced.	true	Section 3.3.73, “v1.LimitRangeItem” array	

3.3.76. v1.ListMeta

ListMeta describes metadata that synthetic resources must have, including lists and various status objects. A resource may have only one of {ObjectMeta, ListMeta}.

Name	Description	Required	Schema	Default
selfLink	SelfLink is a URL representing this object. Populated by the system. Read-only.	false	string	
resourceVersion	String that identifies the server’s internal version of this object that can be used by clients to determine when objects have changed. Value must be treated as opaque by clients and passed unmodified back to the server. Populated by the system. Read-only. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#concurrency-control-and-consistency	false	string	

3.3.77. v1.LoadBalancerIngress

LoadBalancerIngress represents the status of a load-balancer ingress point: traffic intended for the service should be sent to an ingress point.

Name	Description	Required	Schema	Default
ip	IP is set for load-balancer ingress points that are IP based (typically GCE or OpenStack load-balancers)	false	string	
hostname	Hostname is set for load-balancer ingress points that are DNS based (typically AWS load-balancers)	false	string	

3.3.78. v1.LoadBalancerStatus

LoadBalancerStatus represents the status of a load-balancer.

Name	Description	Required	Schema	Default
ingress	Ingress is a list containing ingress points for the load-balancer. Traffic intended for the service should be sent to these ingress points.	false	Section 3.3.77 , “v1.LoadBalancerIngress” array	

3.3.79. v1.LocalObjectReference

LocalObjectReference contains enough information to let you locate the referenced object inside the same namespace.

Name	Description	Required	Schema	Default
------	-------------	----------	--------	---------

Name	Description	Required	Schema	Default
name	Name of the referent. More info: http://kubernetes.io/docs/user-guide/identifiers#names	false	string	

3.3.80. v1.NFSVolumeSource

Represents an NFS mount that lasts the lifetime of a pod. NFS volumes do not support ownership management or SELinux relabeling.

Name	Description	Required	Schema	Default
server	Server is the hostname or IP address of the NFS server. More info: http://kubernetes.io/docs/user-guide/volumes#nfs	true	string	
path	Path that is exported by the NFS server. More info: http://kubernetes.io/docs/user-guide/volumes#nfs	true	string	
readOnly	ReadOnly here will force the NFS export to be mounted with read-only permissions. Defaults to false. More info: http://kubernetes.io/docs/user-guide/volumes#nfs	false	boolean	

3.3.81. v1.Namespace

Namespace provides a scope for Names. Use of multiple namespaces is optional.

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#types-kinds	false	string	
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#resources	false	string	

Name	Description	Required	Schema	Default
metadata	Standard object's metadata. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#metadata	false	Section 2.3.176, "v1.ObjectMeta"	
spec	Spec defines the behavior of the Namespace. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#spec-and-status	false	Section 3.3.83, "v1.NamespaceSpec"	
status	Status describes the current status of a Namespace. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#spec-and-status	false	Section 3.3.84, "v1.NamespaceStatus"	

3.3.82. v1.NamespaceList

NamespaceList is a list of Namespaces.

Name	Description	Required	Schema	Default
------	-------------	----------	--------	---------

Name	Description	Required	Schema	Default
kind	<p>Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/HEAD/docs/dev/api-conventions.md#types-kinds</p>	false	string	
apiVersion	<p>APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/HEAD/docs/dev/api-conventions.md#resources</p>	false	string	
metadata	<p>Standard list metadata. More info: http://releases.k8s.io/HEAD/docs/dev/api-conventions.md#types-kinds</p>	false	Section 2.3.151, "v1.ListMeta"	

Name	Description	Required	Schema	Default
items	Items is the list of Namespace objects in the list. More info: http://kubernetes.io/docs/user-guide/namespaces	true	Section 3.3.81, "v1.Namespace" array	

3.3.83. v1.NamespaceSpec

NamespaceSpec describes the attributes on a Namespace.

Name	Description	Required	Schema	Default
finalizers	Finalizers is an opaque list of values that must be empty to permanently remove object from storage. More info: http://releases.k8s.io/HEAD/docs/design/namespaces.md#finalizers	false	Section 2.3.98, "v1.FinalizerName" array	

3.3.84. v1.NamespaceStatus

NamespaceStatus is information about the current status of a Namespace.

Name	Description	Required	Schema	Default
phase	Phase is the current lifecycle phase of the namespace. More info: http://releases.k8s.io/HEAD/docs/design/namespaces.md#phases	false	string	

3.3.85. v1.Node

Node is a worker node in Kubernetes. Each node will have a unique identifier in the cache (i.e. in etcd).

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#types-kinds	false	string	
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#resources	false	string	
metadata	Standard object's metadata. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#metadata	false	Section 2.3.176, "v1.ObjectMeta"	

Name	Description	Required	Schema	Default
spec	Spec defines the behavior of a node. http://releases.k8s.io/HEAD/docs/dev/api-conventions.md#spec-and-status	false	Section 3.3.94, "v1.NodeSpec"	
status	Most recently observed status of the node. Populated by the system. Read-only. More info: http://releases.k8s.io/HEAD/docs/dev/api-conventions.md#spec-and-status	false	Section 3.3.95, "v1.NodeStatus"	

3.3.86. v1.NodeAddress

NodeAddress contains information for the node's address.

Name	Description	Required	Schema	Default
type	Node address type, one of Hostname, ExternalIP or InternalIP.	true	string	
address	The node address.	true	string	

3.3.87. v1.NodeAffinity

Node affinity is a group of node affinity scheduling rules.

Name	Description	Required	Schema	Default
------	-------------	----------	--------	---------

Name	Description	Required	Schema	Default
<code>requiredDuringSchedulingIgnoredDuringExecution</code>	If the affinity requirements specified by this field are not met at scheduling time, the pod will not be scheduled onto the node. If the affinity requirements specified by this field cease to be met at some point during pod execution (e.g. due to an update), the system may or may not try to eventually evict the pod from its node.	false	Section 2.3.164, "v1.NodeSelector"	

Name	Description	Required	Schema	Default
preferredDuringSchedulingIgnoredDuringExecution	The scheduler will prefer to schedule pods to nodes that satisfy the affinity expressions specified by this field, but it may choose a node that violates one or more of the expressions. The node that is most preferred is the one with the greatest sum of weights, i.e. for each node that meets all of the scheduling requirements (resource request, requiredDuringScheduling affinity expressions, etc.), compute a sum by iterating through the elements of this field and adding "weight" to the sum if the node matches the corresponding matchExpressions; the node(s) with the highest sum are the most preferred.	false	Section 2.3.204, "v1.PreferredSchedulingTerm" array	

3.3.88. v1.NodeCondition

NodeCondition contains condition information for a node.

Name	Description	Required	Schema	Default
type	Type of node condition.	true	string	

Name	Description	Required	Schema	Default
status	Status of the condition, one of True, False, Unknown.	true	string	
lastHeartbeatTime	Last time we got an update on a given condition.	false	string	
lastTransitionTime	Last time the condition transit from one status to another.	false	string	
reason	(brief) reason for the condition's last transition.	false	string	
message	Human readable message indicating details about last transition.	false	string	

3.3.89. v1.NodeDaemonEndpoints

NodeDaemonEndpoints lists ports opened by daemons running on the Node.

Name	Description	Required	Schema	Default
kubeletEndpoint	Endpoint on which Kubelet is listening.	false	Section 3.3.32, "v1.DaemonEndpoint"	

3.3.90. v1.NodeList

NodeList is the whole list of all Nodes which have been registered with master.

Name	Description	Required	Schema	Default
------	-------------	----------	--------	---------

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#types-kinds	false	string	
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#resources	false	string	
metadata	Standard list metadata. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#types-kinds	false	Section 2.3.151, "v1.ListMeta"	

Name	Description	Required	Schema	Default
items	List of nodes	true	Section 3.3.85 , "v1.Node" array	

3.3.91. v1.NodeSelector

A node selector represents the union of the results of one or more label queries over a set of nodes; that is, it represents the OR of the selectors represented by the node selector terms.

Name	Description	Required	Schema	Default
nodeSelectorTerms	Required. A list of node selector terms. The terms are ORed.	true	Section 2.3.166 , "v1.NodeSelectorTerm" array	

3.3.92. v1.NodeSelectorRequirement

A node selector requirement is a selector that contains values, a key, and an operator that relates the key and values.

Name	Description	Required	Schema	Default
key	The label key that the selector applies to.	true	string	
operator	Represents a key's relationship to a set of values. Valid operators are In, NotIn, Exists, DoesNotExist, Gt, and Lt.	true	string	

Name	Description	Required	Schema	Default
values	An array of string values. If the operator is In or NotIn, the values array must be non-empty. If the operator is Exists or DoesNotExist, the values array must be empty. If the operator is Gt or Lt, the values array must have a single element, which will be interpreted as an integer. This array is replaced during a strategic merge patch.	false	string array	

3.3.93. v1.NodeSelectorTerm

A null or empty node selector term matches no objects.

Name	Description	Required	Schema	Default
matchExpressions	Required. A list of node selector requirements. The requirements are ANDed.	true	Section 2.3.165, "v1.NodeSelectorRequirement" array	

3.3.94. v1.NodeSpec

NodeSpec describes the attributes that a node is created with.

Name	Description	Required	Schema	Default
------	-------------	----------	--------	---------

Name	Description	Required	Schema	Default
podCIDR	PodCIDR represents the pod IP range assigned to the node.	false	string	
externalID	External ID of the node assigned by some machine database (e.g. a cloud provider). Deprecated.	false	string	
providerID	ID of the node assigned by the cloud provider in the format: <code><ProviderName>://<ProviderSpecificNodeID></code>	false	string	
unschedulable	Unschedulable controls node schedulability of new pods. By default, node is schedulable. More info: http://releases.k8s.io/HEAD/docs/admin/node.md#manual-node-administration	false	boolean	
taints	If specified, the node's taints.	false	Section 3.3.172 , "v1.Taint" array	

3.3.95. v1.NodeStatus

NodeStatus is information about the current status of a node.

Name	Description	Required	Schema	Default
------	-------------	----------	--------	---------

Name	Description	Required	Schema	Default
capacity	Capacity represents the total resources of a node. More info: http://kubernetes.io/docs/user-guide/persistent-volumes#capacity for more details.	false	object	
allocatable	Allocatable represents the resources of a node that are available for scheduling. Defaults to Capacity.	false	object	
phase	NodePhase is the recently observed lifecycle phase of the node. More info: http://releases.k8s.io/HEAD/docs/admin/node.md#node-phase The field is never populated, and now is deprecated.	false	string	
conditions	Conditions is an array of current observed node conditions. More info: http://releases.k8s.io/HEAD/docs/admin/node.md#node-condition	false	Section 3.3.88, "v1.NodeCondition" array	

Name	Description	Required	Schema	Default
addresses	List of addresses reachable to the node. Queried from cloud provider, if available. More info: http://releases.k8s.io/HEAD/docs/admin/node.md#node-addresses	false	Section 3.3.86, "v1.NodeAddress" array	
daemonEndpoints	Endpoints of daemons running on the Node.	false	Section 3.3.89, "v1.NodeDaemonEndpoints"	
nodeInfo	Set of ids/uuids to uniquely identify the node. More info: http://releases.k8s.io/HEAD/docs/admin/node.md#node-info	false	Section 3.3.96, "v1.NodeSystemInfo"	
images	List of container images on this node	false	Section 3.3.25, "v1.ContainerImage" array	
volumesInUse	List of attachable volumes in use (mounted) by the node.	false	Section 3.3.174, "v1.UniqueVolumeName" array	
volumesAttached	List of volumes that are attached to the node.	false	Section 3.3.6, "v1.AttachedVolume" array	

3.3.96. v1.NodeSystemInfo

NodeSystemInfo is a set of ids/uuids to uniquely identify the node.

Name	Description	Required	Schema	Default
------	-------------	----------	--------	---------

Name	Description	Required	Schema	Default
machineID	MachineID reported by the node. For unique machine identification in the cluster this field is preferred. Learn more from <code>man(5) machine-id</code> : http://man7.org/linux/man-pages/man5/machine-id.5.html	true	string	
systemUUID	SystemUUID reported by the node. For unique machine identification MachineID is preferred. This field is specific to Red Hat hosts https://access.redhat.com/documentation/en-US/Red_Hat_Subscription_Management/1/html/RHSM/getting-system-uuid.html	true	string	
bootID	Boot ID reported by the node.	true	string	
kernelVersion	Kernel Version reported by the node from <code>'uname -r'</code> (e.g. 3.16.0-0.bpo.4-amd64).	true	string	

Name	Description	Required	Schema	Default
osImage	OS Image reported by the node from /etc/os-release (e.g. Debian GNU/Linux 7 (wheezy)).	true	string	
containerRuntimeVersion	ContainerRuntime Version reported by the node through runtime remote API (e.g. docker://1.5.0).	true	string	
kubeletVersion	Kubelet Version reported by the node.	true	string	
kubeProxyVersion	KubeProxy Version reported by the node.	true	string	
operatingSystem	The Operating System reported by the node	true	string	
architecture	The Architecture reported by the node	true	string	

3.3.97. v1.ObjectFieldSelector

ObjectFieldSelector selects an APIVersioned field of an object.

Name	Description	Required	Schema	Default
apiVersion	Version of the schema the FieldPath is written in terms of, defaults to "v1".	false	string	

Name	Description	Required	Schema	Default
fieldPath	Path of the field to select in the specified API version.	true	string	

3.3.98. v1.ObjectMeta

ObjectMeta is metadata that all persisted resources must have, which includes all objects users must create.

Name	Description	Required	Schema	Default
name	Name must be unique within a namespace. Is required when creating resources, although some resources may allow a client to request the generation of an appropriate name automatically. Name is primarily intended for creation idempotence and configuration definition. Cannot be updated. More info: http://kubernetes.io/docs/user-guide/identifiers#names	false	string	
generateName	GenerateName is an optional prefix, used by the server, to generate a unique name ONLY IF the Name field has not been	false	string	

Name	Description	Required	Schema	Default
	<p>provided. If this field is used, the name returned to the client will be different than the name passed. This value will also be combined with a unique suffix. The provided value has the same validation rules as the Name field, and may be truncated by the length of the suffix required to make the value unique on the server.</p> <p>If this field is specified and the generated name exists, the server will NOT return a 409 - instead, it will either return 201 Created or 500 with Reason ServerTimeout indicating a unique name could not be found in the time allotted, and the client should retry (optionally after the time indicated in the Retry-After header).</p> <p>Applied only if Name is not specified. More info: http://releases.k8s.io/HEAD/docs/dev/api-conventions.md#idempotency</p>			

Name	Description	Required	Schema	Default
	<p>defines the space within each name must be unique. An empty namespace is equivalent to the "default" namespace, but "default" is the canonical representation. Not all objects are required to be scoped to a namespace - the value of this field for those objects will be empty.</p> <p>Must be a DNS_LABEL. Cannot be updated. More info: http://kubernetes.io/docs/user-guide/namespaces</p>			
selfLink	SelfLink is a URL representing this object. Populated by the system. Read-only.	false	string	

Name	Description	Required	Schema	Default
uid	<p>UID is the unique in time and space value for this object. It is typically generated by the server on successful creation of a resource and is not allowed to change on PUT operations.</p> <p>Populated by the system. Read-only. More info: http://kubernetes.io/docs/user-guide/identifiers#uids</p>	false	string	

Name	Description	Required	Schema	Default
resourceVersion	<p>An opaque value that represents the internal version of this object that can be used by clients to determine when objects have changed. May be used for optimistic concurrency, change detection, and the watch operation on a resource or set of resources. Clients must treat these values as opaque and passed unmodified back to the server. They may only be valid for a particular resource or set of resources.</p> <p>Populated by the system. Read-only. Value must be treated as opaque by clients and . More info: http://releases.k8s.io/HEAD/docs/dev/api-conventions.md#concurrency-control-and-consistency</p>	false	string	

Name	Description	Required	Schema	Default
generation	A sequence number representing a specific generation of the desired state. Populated by the system. Read-only.	false	integer (int64)	
creationTimestamp	<p>CreationTimestamp is a timestamp representing the server time when this object was created. It is not guaranteed to be set in happens-before order across separate operations. Clients may not set this value. It is represented in RFC3339 form and is in UTC.</p> <p>Populated by the system. Read-only. Null for lists. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#metadata</p>	false	string	
deletionTimestamp	DeletionTimestamp is RFC 3339 date and time at which this resource will be deleted. This field is set by the server when a graceful deletion is requested by the user, and is	false	string	

Name	Description	Required	Schema	Default
	<p>not directly accessible by a client. The resource is expected to be deleted (no longer visible from resource lists, and not reachable by name) after the time in this field. Once set, this value may not be unset or be set further into the future, although it may be shortened or the resource may be deleted prior to this time. For example, a user may request that a pod is deleted in 30 seconds. The Kubelet will react by sending a graceful termination signal to the containers in the pod. After that 30 seconds, the Kubelet will send a hard termination signal (SIGKILL) to the container and after cleanup, remove the pod from the API. In the presence of network partitions, this object may still exist after this timestamp, until an administrator or automated process can determine the resource is fully</p>			

Name	Description	Required	Schema	Default
	<p>terminated. If not set, graceful deletion of the object has not been requested.</p> <p>Populated by the system when a graceful deletion is requested. Read-only. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#metadata</p>			
deletionGracePeriodSeconds	<p>Number of seconds allowed for this object to gracefully terminate before it will be removed from the system. Only set when deletionTimestamp is also set. May only be shortened. Read-only.</p>	false	integer (int64)	
labels	<p>Map of string keys and values that can be used to organize and categorize (scope and select) objects. May match selectors of replication controllers and services. More info: http://kubernetes.io/docs/user-guide/labels</p>	false	object	

Name	Description	Required	Schema	Default
annotations	Annotations is an unstructured key value map stored with a resource that may be set by external tools to store and retrieve arbitrary metadata. They are not queryable and should be preserved when modifying objects. More info: http://kubernetes.io/docs/user-guide/annotations	false	object	
ownerReferences	List of objects depended by this object. If ALL objects in the list have been deleted, this object will be garbage collected. If this object is managed by a controller, then an entry in this list will point to this controller, with the controller field set to true. There cannot be more than one managing controller.	false	Section 2.3.178, "v1.OwnerReference" array	

Name	Description	Required	Schema	Default
finalizers	Must be empty before the object is deleted from the registry. Each entry is an identifier for the responsible component that will remove the entry from the list. If the deletionTimestamp of the object is non-nil, entries in this list can only be removed.	false	string array	
clusterName	The name of the cluster which the object belongs to. This is used to distinguish resources with same name and namespace in different clusters. This field is not set anywhere right now and apiserver is going to ignore it if set in create or update request.	false	string	

3.3.99. v1.ObjectReference

ObjectReference contains enough information to let you inspect or modify the referred object.

Name	Description	Required	Schema	Default
------	-------------	----------	--------	---------

Name	Description	Required	Schema	Default
kind	Kind of the referent. More info: http://releases.k8s.io/HEAD/docs/dev/api-conventions.md#types-kinds	false	string	
namespace	Namespace of the referent. More info: http://kubernetes.io/docs/user-guide/namespaces	false	string	
name	Name of the referent. More info: http://kubernetes.io/docs/user-guide/identifiers#names	false	string	
uid	UID of the referent. More info: http://kubernetes.io/docs/user-guide/identifiers#uids	false	string	
apiVersion	API version of the referent.	false	string	
resourceVersion	Specific resourceVersion to which this reference is made, if any. More info: http://releases.k8s.io/HEAD/docs/dev/api-conventions.md#concurrency-control-and-consistency	false	string	

Name	Description	Required	Schema	Default
fieldPath	If referring to a piece of an object instead of an entire object, this string should contain a valid JSON/Go field access statement, such as <code>desiredState.manifest.containers[2]</code> . For example, if the object reference is to a container within a pod, this would take on a value like: <code>"spec.containers{name}"</code> (where "name" refers to the name of the container that triggered the event) or if no container name is specified <code>"spec.containers[2]"</code> (container with index 2 in this pod). This syntax is chosen only to have some well-defined way of referencing a part of an object.	false	string	

3.3.100. v1.OwnerReference

OwnerReference contains enough information to let you identify an owning object. Currently, an owning object must be in the same namespace, so there is no namespace field.

Name	Description	Required	Schema	Default
apiVersion	API version of the referent.	true	string	

Name	Description	Required	Schema	Default
kind	Kind of the referent. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#types-kinds	true	string	
name	Name of the referent. More info: http://kubernetes.io/docs/user-guide/identifiers#names	true	string	
uid	UID of the referent. More info: http://kubernetes.io/docs/user-guide/identifiers#uids	true	string	
controller	If true, this reference points to the managing controller.	false	boolean	

Name	Description	Required	Schema	Default
blockOwnerDeletion	If true, AND if the owner has the "foregroundDeletion" finalizer, then the owner cannot be deleted from the key-value store until this reference is removed. Defaults to false. To set this field, a user needs "delete" permission of the owner, otherwise 422 (Unprocessable Entity) will be returned.	false	boolean	

3.3.101. v1.Patch

Patch is provided to give a concrete name and type to the Kubernetes PATCH request body.

3.3.102. v1.PersistentVolume

PersistentVolume (PV) is a storage resource provisioned by an administrator. It is analogous to a node. More info: <http://kubernetes.io/docs/user-guide/persistent-volumes>

Name	Description	Required	Schema	Default
------	-------------	----------	--------	---------

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#types-kinds	false	string	
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#resources	false	string	

Name	Description	Required	Schema	Default
metadata	Standard object's metadata. More info: http://releases.k8s.io/HEAD/docs/dev/api-conventions.md#metadata	false	Section 2.3.176, "v1.ObjectMeta"	
spec	Spec defines a specification of a persistent volume owned by the cluster. Provisioned by an administrator. More info: http://kubernetes.io/docs/user-guide/persistent-volumes#persistent-volumes	false	Section 3.3.110, "v1.PersistentVolumeSpec"	
status	Status represents the current information/status for the persistent volume. Populated by the system. Read-only. More info: http://kubernetes.io/docs/user-guide/persistent-volumes#persistent-volumes	false	Section 3.3.111, "v1.PersistentVolumeStatus"	

3.3.103. v1.PersistentVolumeAccessMode

3.3.104. v1.PersistentVolumeClaim

PersistentVolumeClaim is a user's request for and claim to a persistent volume

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#types-kinds	false	string	
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#resources	false	string	
metadata	Standard object's metadata. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#metadata	false	Section 2.3.176, "v1.ObjectMeta"	

Name	Description	Required	Schema	Default
spec	Spec defines the desired characteristics of a volume requested by a pod author. More info: http://kubernetes.io/docs/user-guide/persistent-volumes#persistentvolumeclaims	false	Section 3.3.106, "v1.PersistentVolumeClaimSpec"	
status	Status represents the current information/status of a persistent volume claim. Read-only. More info: http://kubernetes.io/docs/user-guide/persistent-volumes#persistentvolumeclaims	false	Section 3.3.107, "v1.PersistentVolumeClaimStatus"	

3.3.105. v1.PersistentVolumeClaimList

PersistentVolumeClaimList is a list of PersistentVolumeClaim items.

Name	Description	Required	Schema	Default
------	-------------	----------	--------	---------

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#types-kinds	false	string	
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#resources	false	string	
metadata	Standard list metadata. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#types-kinds	false	Section 2.3.151, "v1.ListMeta"	

Name	Description	Required	Schema	Default
items	A list of persistent volume claims. More info: http://kubernetes.io/docs/user-guide/persistent-volumes#persistentvolumeclaims	true	Section 3.3.104, "v1.PersistentVolumeClaim" array	

3.3.106. v1.PersistentVolumeClaimSpec

PersistentVolumeClaimSpec describes the common attributes of storage devices and allows a Source for provider-specific attributes

Name	Description	Required	Schema	Default
accessModes	AccessModes contains the desired access modes the volume should have. More info: http://kubernetes.io/docs/user-guide/persistent-volumes#access-modes-1	false	Section 3.3.103, "v1.PersistentVolumeAccessMode" array	
selector	A label query over volumes to consider for binding.	false	Section 2.3.147, "v1.LabelSelector"	
resources	Resources represents the minimum resources the volume should have. More info: http://kubernetes.io/docs/user-guide/persistent-volumes#resources	false	Section 2.3.223, "v1.ResourceRequirements"	

Name	Description	Required	Schema	Default
volumeName	VolumeName is the binding reference to the PersistentVolume backing this claim.	false	string	
storageClassName	Name of the StorageClass required by the claim. More info: http://kubernetes.io/docs/user-guide/persistent-volumes#class-1	false	string	

3.3.107. v1.PersistentVolumeClaimStatus

PersistentVolumeClaimStatus is the current status of a persistent volume claim.

Name	Description	Required	Schema	Default
phase	Phase represents the current phase of PersistentVolumeClaim.	false	string	
accessModes	AccessModes contains the actual access modes the volume backing the PVC has. More info: http://kubernetes.io/docs/user-guide/persistent-volumes#access-modes-1	false	Section 3.3.103, "v1.PersistentVolumeAccessMode" array	
capacity	Represents the actual resources of the underlying volume.	false	object	

3.3.108. v1.PersistentVolumeClaimVolumeSource

PersistentVolumeClaimVolumeSource references the user's PVC in the same namespace. This volume finds the bound PV and mounts that volume for the pod. A PersistentVolumeClaimVolumeSource is, essentially, a wrapper around another type of volume that is owned by someone else (the system).

Name	Description	Required	Schema	Default
claimName	ClaimName is the name of a PersistentVolumeClaim in the same namespace as the pod using this volume. More info: http://kubernetes.io/docs/user-guide/persistent-volumes#persistentvolumeclaims	true	string	
readOnly	Will force the ReadOnly setting in VolumeMounts. Default false.	false	boolean	

3.3.109. v1.PersistentVolumeList

PersistentVolumeList is a list of PersistentVolume items.

Name	Description	Required	Schema	Default
------	-------------	----------	--------	---------

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#types-kinds	false	string	
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#resources	false	string	
metadata	Standard list metadata. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#types-kinds	false	Section 2.3.151, "v1.ListMeta"	

Name	Description	Required	Schema	Default
items	List of persistent volumes. More info: http://kubernetes.io/docs/user-guide/persistent-volumes	true	Section 3.3.102, “v1.PersistentVolume” array	

3.3.110. v1.PersistentVolumeSpec

PersistentVolumeSpec is the specification of a persistent volume.

Name	Description	Required	Schema	Default
capacity	A description of the persistent volume’s resources and capacity. More info: http://kubernetes.io/docs/user-guide/persistent-volumes#capacity	false	object	
gcePersistentDisk	GCEPersistentDisk represents a GCE Disk resource that is attached to a kubelet’s host machine and then exposed to the pod. Provisioned by an admin. More info: http://kubernetes.io/docs/user-guide/volumes#gcepersistentdisk	false	Section 2.3.101, “v1.GCEPersistentDiskVolumeSource”	

Name	Description	Required	Schema	Default
awsElasticBlockStore	<p>AWSElasticBlockStore represents an AWS Disk resource that is attached to a kubelet's host machine and then exposed to the pod. More info: http://kubernetes.io/docs/user-guide/volumes#awselasticblockstore</p>	false	Section 2.3.6, "v1.AWSElasticBlockStoreVolumeSource"	
hostPath	<p>HostPath represents a directory on the host. Provisioned by a developer or tester. This is useful for single-node development and testing only! On-host storage is not supported in any way and WILL NOT WORK in a multi-node cluster. More info: http://kubernetes.io/docs/user-guide/volumes#hostpath</p>	false	Section 2.3.115, "v1.HostPathVolumeSource"	

Name	Description	Required	Schema	Default
glusterfs	Glusterfs represents a Glusterfs volume that is attached to a host and exposed to the pod. Provisioned by an admin. More info: http://releases.k8s.io/HEAD/examples/volumes/glusterfs/README.md	false	Section 2.3.108, "v1.GlusterfsVolumeSource"	
nfs	NFS represents an NFS mount on the host. Provisioned by an admin. More info: http://kubernetes.io/docs/user-guide/volumes#nfs	false	Section 2.3.155, "v1.NFSVolumeSource"	
rbd	RBD represents a Rados Block Device mount on the host that shares a pod's lifetime. More info: http://releases.k8s.io/HEAD/examples/volumes/rbd/README.md	false	Section 2.3.213, "v1.RBDVolumeSource"	
iscsi	ISCSI represents an ISCSI Disk resource that is attached to a kubelet's host machine and then exposed to the pod. Provisioned by an admin.	false	Section 2.3.118, "v1.ISCSIVolumeSource"	

Name	Description	Required	Schema	Default
cinder	Cinder represents a cinder volume attached and mounted on kubelets host machine More info: http://releases.k8s.io/HEAD/examples/mysql-cinder-pd/README.md	false	Section 2.3.36, "v1.CinderVolumeSource"	
cephfs	CephFS represents a Ceph FS mount on the host that shares a pod's lifetime	false	Section 2.3.35, "v1.CephFSVolumeSource"	
fc	FC represents a Fibre Channel resource that is attached to a kubelet's host machine and then exposed to the pod.	false	Section 2.3.97, "v1.FCVolumeSource"	
flocker	Flocker represents a Flocker volume attached to a kubelet's host machine and exposed to the pod for its usage. This depends on the Flocker control service being running	false	Section 2.3.100, "v1.FlockerVolumeSource"	

Name	Description	Required	Schema	Default
flexVolume	FlexVolume represents a generic volume resource that is provisioned/attached using an exec based plugin. This is an alpha feature and may change in future.	false	Section 2.3.99, "v1.FlexVolume Source"	
azureFile	AzureFile represents an Azure File Service mount on the host and bind mount to the pod.	false	Section 2.3.12, "v1.AzureFileVolumeSource"	
vsphereVolume	VsphereVolume represents a vSphere volume attached and mounted on kubelets host machine	false	Section 2.3.290, "v1.VsphereVirtualDiskVolumeSource"	
quobyte	Quobyte represents a Quobyte mount on the host that shares a pod's lifetime	false	Section 2.3.212, "v1.QuobyteVolumeSource"	
azureDisk	AzureDisk represents an Azure Data Disk mount on the host and bind mount to the pod.	false	Section 2.3.11, "v1.AzureDiskVolumeSource"	

Name	Description	Required	Schema	Default
photonPersistentDisk	PhotonPersistentDisk represents a PhotonController persistent disk attached and mounted on kubelets host machine	false	Section 2.3.182, "v1.PhotonPersistentDiskVolumeSource"	
portworxVolume	PortworxVolume represents a portworx volume attached and mounted on kubelets host machine	false	Section 2.3.202, "v1.PortworxVolumeSource"	
scaleIO	ScaleIO represents a ScaleIO persistent volume attached and mounted on Kubernetes nodes.	false	Section 2.3.241, "v1.ScaleIOVolumeSource"	
accessModes	AccessModes contains all ways the volume can be mounted. More info: http://kubernetes.io/docs/user-guide/persistent-volumes#access-modes	false	Section 3.3.103, "v1.PersistentVolumeAccessMode" array	

Name	Description	Required	Schema	Default
claimRef	<p>ClaimRef is part of a bi-directional binding between PersistentVolume and PersistentVolumeClaim. Expected to be non-nil when bound. claim.VolumeName is the authoritative bind between PV and PVC. More info: http://kubernetes.io/docs/user-guide/persistent-volumes#binding</p>	false	Section 2.3.177, "v1.ObjectReference"	
persistentVolumeReclaimPolicy	<p>What happens to a persistent volume when released from its claim. Valid options are Retain (default) and Recycle. Recycling must be supported by the volume plugin underlying this persistent volume. More info: http://kubernetes.io/docs/user-guide/persistent-volumes#recycling-policy</p>	false	string	

Name	Description	Required	Schema	Default
storageClassName	Name of StorageClass to which this persistent volume belongs. Empty value means that this volume does not belong to any StorageClass.	false	string	

3.3.111. v1.PersistentVolumeStatus

PersistentVolumeStatus is the current status of a persistent volume.

Name	Description	Required	Schema	Default
phase	Phase indicates if a volume is available, bound to a claim, or released by a claim. More info: http://kubernetes.io/docs/user-guide/persistent-volumes#phase	false	string	
message	A human-readable message indicating details about why the volume is in this state.	false	string	
reason	Reason is a brief CamelCase string that describes any failure and is meant for machine parsing and tidy display in the CLI.	false	string	

3.3.112. v1.PhotonPersistentDiskVolumeSource

Represents a Photon Controller persistent disk resource.

Name	Description	Required	Schema	Default
pdID	ID that identifies Photon Controller persistent disk	true	string	
fsType	Filesystem type to mount. Must be a filesystem type supported by the host operating system. Ex. "ext4", "xfs", "ntfs". Implicitly inferred to be "ext4" if unspecified.	false	string	

3.3.113. v1.Pod

Pod is a collection of containers that can run on a host. This resource is created by clients and scheduled onto hosts.

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/HEAD/docs/dev/api-conventions.md#types-kinds	false	string	

Name	Description	Required	Schema	Default
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/HEAD/docs/dev/api-conventions.md#resources	false	string	
metadata	Standard object's metadata. More info: http://releases.k8s.io/HEAD/docs/dev/api-conventions.md#metadata	false	Section 2.3.176, "v1.ObjectMeta"	
spec	Specification of the desired behavior of the pod. More info: http://releases.k8s.io/HEAD/docs/dev/api-conventions.md#spec-and-status	false	Section 2.3.195, "v1.PodSpec"	

Name	Description	Required	Schema	Default
status	Most recently observed status of the pod. This data may not be up to date. Populated by the system. Read-only. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#spec-and-status	false	Section 3.3.121, "v1.PodStatus"	

3.3.114. v1.PodAffinity

Pod affinity is a group of inter pod affinity scheduling rules.

Name	Description	Required	Schema	Default
requiredDuringSchedulingIgnoredDuringExecution	NOT YET IMPLEMENTED. TODO: Uncomment field once it is implemented. If the affinity requirements specified by this field are not met at scheduling time, the pod will not be scheduled onto the node. If the affinity requirements specified by this field cease to be met at some point during pod execution (e.g. due to a pod label update), the system will try to eventually evict the pod from its node. When there are multiple	false	Section 2.3.184, "v1.PodAffinityTerm" array	

Name	Description	Required	Schema	Default
	<p>elements, the lists of nodes corresponding to each podAffinityTerm are intersected, i.e. all terms must be satisfied.</p> <p>RequiredDuringSchedulingRequiredDuringExecution</p> <p>[]PodAffinityTerm</p> <p>json:"requiredDuringSchedulingRequiredDuringExecution,omitEmpty" If the affinity requirements specified by this field are not met at scheduling time, the pod will not be scheduled onto the node. If the affinity requirements specified by this field cease to be met at some point during pod execution (e.g. due to a pod label update), the system may or may not try to eventually evict the pod from its node. When there are multiple elements, the lists of nodes corresponding to each podAffinityTerm are intersected, i.e. all terms must be satisfied.</p>			

Name	Description	Required	Schema	Default
preferredDuringSchedulingIgnoredDuringExecution	The scheduler will prefer to schedule pods to nodes that satisfy the affinity expressions specified by this field, but it may choose a node that violates one or more of the expressions. The node that is most preferred is the one with the greatest sum of weights, i.e. for each node that meets all of the scheduling requirements (resource request, requiredDuringScheduling affinity expressions, etc.), compute a sum by iterating through the elements of this field and adding "weight" to the sum if the node has pods which matches the corresponding podAffinityTerm; the node(s) with the highest sum are the most preferred.	false	Section 2.3.293, "v1.WeightedPodAffinityTerm" array	

3.3.115. v1.PodAffinityTerm

Defines a set of pods (namely those matching the labelSelector relative to the given namespace(s)) that this pod should be co-located (affinity) or not co-located (anti-affinity) with, where co-located is defined as running on a node whose value of the label with key <topologyKey> tches that of any node on which a pod of the set of pods is running

Name	Description	Required	Schema	Default
labelSelector	A label query over a set of resources, in this case pods.	false	Section 2.3.147, "v1.LabelSelector"	
namespaces	namespaces specifies which namespaces the labelSelector applies to (matches against); null or empty list means "this pod's namespace"	false	string array	

Name	Description	Required	Schema	Default
topologyKey	This pod should be co-located (affinity) or not co-located (anti-affinity) with the pods matching the labelSelector in the specified namespaces, where co-located is defined as running on a node whose value of the label with key topologyKey matches that of any node on which any of the selected pods is running. For PreferredDuringScheduling pod anti-affinity, empty topologyKey is interpreted as "all topologies" ("all topologies" here means all the topologyKeys indicated by scheduler command-line argument --failure-domains); for affinity and for RequiredDuringScheduling pod anti-affinity, empty topologyKey is not allowed.	false	string	

3.3.116. v1.PodAntiAffinity

Pod anti affinity is a group of inter pod anti affinity scheduling rules.

Name	Description	Required	Schema	Default
requiredDuringSchedulingIgnoredDuringExecution	<p>NOT YET IMPLEMENTED. TODO: Uncomment field once it is implemented. If the anti-affinity requirements specified by this field are not met at scheduling time, the pod will not be scheduled onto the node. If the anti-affinity requirements specified by this field cease to be met at some point during pod execution (e.g. due to a pod label update), the system will try to eventually evict the pod from its node. When there are multiple elements, the lists of nodes corresponding to each podAffinityTerm are intersected, i.e. all terms must be satisfied.</p> <p>RequiredDuringSchedulingRequiredDuringExecution</p> <p>[]PodAffinityTerm</p> <p>json:"requiredDuringSchedulingRequiredDuringExecution,omitEmpty" If the anti-affinity requirements</p>	false	Section 2.3.184, "v1.PodAffinityTerm" array	

Name	Description	Required	Schema	Default
	<p>specified by this field is not met at scheduling time, the pod will not be scheduled onto the node. If the anti-affinity requirements specified by this field cease to be met at some point during pod execution (e.g. due to a pod label update), the system may or may not try to eventually evict the pod from its node. When there are multiple elements, the lists of nodes corresponding to each podAffinityTerm are intersected, i.e. all terms must be satisfied.</p>			

Name	Description	Required	Schema	Default
preferredDuringSchedulingIgnoredDuringExecution	The scheduler will prefer to schedule pods to nodes that satisfy the anti-affinity expressions specified by this field, but it may choose a node that violates one or more of the expressions. The node that is most preferred is the one with the greatest sum of weights, i.e. for each node that meets all of the scheduling requirements (resource request, requiredDuringScheduling anti-affinity expressions, etc.), compute a sum by iterating through the elements of this field and adding "weight" to the sum if the node has pods which matches the corresponding podAffinityTerm; the node(s) with the highest sum are the most preferred.	false	Section 2.3.293, "v1.WeightedPodAffinityTerm" array	

3.3.117. v1.PodCondition

PodCondition contains details for the current condition of this pod.

Name	Description	Required	Schema	Default
type	Type is the type of the condition. Currently only Ready. More info: http://kubernetes.io/docs/user-guide/pod-states#pod-conditions	true	string	
status	Status is the status of the condition. Can be True, False, Unknown. More info: http://kubernetes.io/docs/user-guide/pod-states#pod-conditions	true	string	
lastProbeTime	Last time we probed the condition.	false	string	
lastTransitionTime	Last time the condition transitioned from one status to another.	false	string	
reason	Unique, one-word, CamelCase reason for the condition's last transition.	false	string	
message	Human-readable message indicating details about last transition.	false	string	

3.3.118. v1.PodList

PodList is a list of Pods.

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#types-kinds	false	string	
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#resources	false	string	
metadata	Standard list metadata. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#types-kinds	false	Section 2.3.151, "v1.ListMeta"	

Name	Description	Required	Schema	Default
items	List of pods. More info: http://kubernetes.io/docs/user-guide/pods	true	Section 3.3.113 , "v1.Pod" array	

3.3.119. v1.PodSecurityContext

PodSecurityContext holds pod-level security attributes and common container settings. Some fields are also present in container.securityContext. Field values of container.securityContext take precedence over field values of PodSecurityContext.

Name	Description	Required	Schema	Default
seLinuxOptions	The SELinux context to be applied to all containers. If unspecified, the container runtime will allocate a random SELinux context for each container. May also be set in SecurityContext. If set in both SecurityContext and PodSecurityContext, the value specified in SecurityContext takes precedence for that container.	false	Section 2.3.240 , "v1.SELinuxOptions"	

Name	Description	Required	Schema	Default
runAsUser	The UID to run the entrypoint of the container process. Defaults to user specified in image metadata if unspecified. May also be set in SecurityContext. If set in both SecurityContext and PodSecurityContext, the value specified in SecurityContext takes precedence for that container.	false	integer (int64)	
runAsNonRoot	Indicates that the container must run as a non-root user. If true, the Kubelet will validate the image at runtime to ensure that it does not run as UID 0 (root) and fail to start the container if it does. If unset or false, no such validation will be performed. May also be set in SecurityContext. If set in both SecurityContext and PodSecurityContext, the value specified in SecurityContext takes precedence.	false	boolean	

Name	Description	Required	Schema	Default
supplementalGroups	A list of groups applied to the first process run in each container, in addition to the container's primary GID. If unspecified, no groups will be added to any container.	false	integer array	
fsGroup	<p>A special supplemental group that applies to all containers in a pod. Some volume types allow the Kubelet to change the ownership of that volume to be owned by the pod:</p> <ol style="list-style-type: none"> 1. The owning GID will be the FSGroup 2. The setgid bit is set (new files created in the volume will be owned by FSGroup) 3. The permission bits are OR'd with rw-rw 	false	integer (int64)	

3.3.120. v1.PodSpec

PodSpec is a description of a pod.

Name	Description	Required	Schema	Default
------	-------------	----------	--------	---------

Name	Description	Required	Schema	Default
volumes	List of volumes that can be mounted by containers belonging to the pod. More info: http://kubernetes.io/docs/user-guide/volumes	false	Section 2.3.287 , "v1.Volume" array	
initContainers	List of initialization containers belonging to the pod. Init containers are executed in order prior to containers being started. If any init container fails, the pod is considered to have failed and is handled according to its restartPolicy. The name for an init container or normal container must be unique among all containers. Init containers may not have Lifecycle actions, Readiness probes, or Liveness probes. The resourceRequirements of an init container are taken into account during scheduling by finding the highest request/limit for each resource type, and then using the max of	false	Section 2.3.57 , "v1.Container" array	

Name	Description	Required	Schema	Default
	<p>of that value or the sum of the normal containers. Limits are applied to init containers in a similar fashion. Init containers cannot currently be added or removed. Cannot be updated. More info: http://kubernetes.io/docs/user-guide/containers</p>			
containers	<p>List of containers belonging to the pod. Containers cannot currently be added or removed. There must be at least one container in a Pod. Cannot be updated. More info: http://kubernetes.io/docs/user-guide/containers</p>	true	Section 2.3.57, "v1.Container" array	
restartPolicy	<p>Restart policy for all containers within the pod. One of Always, OnFailure, Never. Default to Always. More info: http://kubernetes.io/docs/user-guide/pod-states#restartpolicy</p>	false	string	

Name	Description	Required	Schema	Default
terminationGracePeriodSeconds	Optional duration in seconds the pod needs to terminate gracefully. May be decreased in delete request. Value must be non-negative integer. The value zero indicates delete immediately. If this value is nil, the default grace period will be used instead. The grace period is the duration in seconds after the processes running in the pod are sent a termination signal and the time when the processes are forcibly halted with a kill signal. Set this value longer than the expected cleanup time for your process. Defaults to 30 seconds.	false	integer (int64)	

Name	Description	Required	Schema	Default
activeDeadlineSeconds	Optional duration in seconds the pod may be active on the node relative to StartTime before the system will actively try to mark it failed and kill associated containers. Value must be a positive integer.	false	integer (int64)	
dnsPolicy	Set DNS policy for containers within the pod. One of 'ClusterFirstWithHostNet', 'ClusterFirst' or 'Default'. Defaults to "ClusterFirst". To have DNS options set along with hostNetwork, you have to specify DNS policy explicitly to 'ClusterFirstWithHostNet'.	false	string	

Name	Description	Required	Schema	Default
nodeSelector	NodeSelector is a selector which must be true for the pod to fit on a node. Selector which must match a node's labels for the pod to be scheduled on that node. More info: http://kubernetes.io/docs/user-guide/node-selection/README	false	object	
serviceAccountName	ServiceAccountName is the name of the ServiceAccount to use to run this pod. More info: http://releases.k8s.io/HEAD/docs/design/service_accounts.md	false	string	
serviceAccount	DeprecatedServiceAccount is a deprecated alias for ServiceAccountName. Deprecated: Use serviceAccountName instead.	false	string	
automountServiceAccountToken	AutomountServiceAccountToken indicates whether a service account token should be automatically mounted.	false	boolean	

Name	Description	Required	Schema	Default
nodeName	nodeName is a request to schedule this pod onto a specific node. If it is non-empty, the scheduler simply schedules this pod onto that node, assuming that it fits resource requirements.	false	string	
hostNetwork	Host networking requested for this pod. Use the host's network namespace. If this option is set, the ports that will be used must be specified. Default to false.	false	boolean	
hostPID	Use the host's pid namespace. Optional: Default to false.	false	boolean	
hostIPC	Use the host's ipc namespace. Optional: Default to false.	false	boolean	
securityContext	SecurityContext holds pod-level security attributes and common container settings. Optional: Defaults to empty. See type description for default values of each field.	false	Section 2.3.186, "v1.PodSecurity Context"	

Name	Description	Required	Schema	Default
imagePullSecrets	ImagePullSecrets is an optional list of references to secrets in the same namespace to use for pulling any of the images used by this PodSpec. If specified, these secrets will be passed to individual puller implementations for them to use. For example, in the case of docker, only DockerConfig type secrets are honored. More info: http://kubernetes.io/docs/user-guide/images#specifying-imagepullsecrets-on-a-pod	false	Section 2.3.152, "v1.LocalObjectReference" array	
hostname	Specifies the hostname of the Pod. If not specified, the pod's hostname will be set to a system-defined value.	false	string	

Name	Description	Required	Schema	Default
subdomain	If specified, the fully qualified Pod hostname will be " <hostname>. <subdomain>. <pod namespace>.svc .<cluster domain>". If not specified, the pod will not have a domainname at all.	false	string	
affinity	If specified, the pod's scheduling constraints	false	Section 2.3.7, "v1.Affinity"	
schedulerName	If specified, the pod will be dispatched by specified scheduler. If not specified, the pod will be dispatched by default scheduler.	false	string	
tolerations	If specified, the pod's tolerations.	false	Section 2.3.282, "v1.Toleration" array	

3.3.121. v1.PodStatus

PodStatus represents information about the status of a pod. Status may trail the actual state of a system.

Name	Description	Required	Schema	Default
------	-------------	----------	--------	---------

Name	Description	Required	Schema	Default
phase	Current condition of the pod. More info: http://kubernetes.io/docs/user-guide/pod-states#pod-phase	false	string	
conditions	Current service state of pod. More info: http://kubernetes.io/docs/user-guide/pod-states#pod-conditions	false	Section 3.3.117 , "v1.PodCondition" array	
message	A human readable message indicating details about why the pod is in this condition.	false	string	
reason	A brief CamelCase message indicating details about why the pod is in this state. e.g. 'OutOfDisk'	false	string	
hostIP	IP address of the host to which the pod is assigned. Empty if not yet scheduled.	false	string	
podIP	IP address allocated to the pod. Routable at least within the cluster. Empty if not yet allocated.	false	string	

Name	Description	Required	Schema	Default
startTime	RFC 3339 date and time at which the object was acknowledged by the Kubelet. This is before the Kubelet pulled the container image(s) for the pod.	false	string	
initContainerStatuses	The list has one entry per init container in the manifest. The most recent successful init container will have ready = true, the most recently started container will have startTime set. More info: http://kubernetes.io/docs/user-guide/pod-states#container-statuses	false	Section 3.3.31, "v1.ContainerStatus" array	
containerStatuses	The list has one entry per container in the manifest. Each entry is currently the output of docker inspect . More info: http://kubernetes.io/docs/user-guide/pod-states#container-statuses	false	Section 3.3.31, "v1.ContainerStatus" array	

Name	Description	Required	Schema	Default
qosClass	The Quality of Service (QOS) classification assigned to the pod based on resource requirements See PodQOSClass type for available QOS classes More info: https://github.com/kubernetes/kubernetes/blob/master/docs/design/resource-qos.md	false	string	

3.3.122. v1.PodTemplate

PodTemplate describes a template for creating copies of a predefined pod.

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#types-kinds	false	string	

Name	Description	Required	Schema	Default
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#resources	false	string	
metadata	Standard object's metadata. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#metadata	false	Section 2.3.176, "v1.ObjectMeta"	
template	Template defines the pods that will be created from this pod template. http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#spec-and-status	false	Section 2.3.196, "v1.PodTemplateSpec"	

3.3.123. v1.PodTemplateList

PodTemplateList is a list of PodTemplates.

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#types-kinds	false	string	
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#resources	false	string	
metadata	Standard list metadata. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#types-kinds	false	Section 2.3.151, "v1.ListMeta"	

Name	Description	Required	Schema	Default
items	List of pod templates	true	Section 3.3.122, “v1.PodTemplate” array	

3.3.124. v1.PodTemplateSpec

PodTemplateSpec describes the data a pod should have when created from a template

Name	Description	Required	Schema	Default
metadata	Standard object’s metadata. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#metadata	false	Section 2.3.176, “v1.ObjectMeta”	
spec	Specification of the desired behavior of the pod. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#spec-and-status	false	Section 2.3.195, “v1.PodSpec”	

3.3.125. v1.PortworxVolumeSource

PortworxVolumeSource represents a Portworx volume resource.

Name	Description	Required	Schema	Default
volumeID	VolumeID uniquely identifies a Portworx volume	true	string	

Name	Description	Required	Schema	Default
fsType	FSType represents the filesystem type to mount. Must be a filesystem type supported by the host operating system. Ex. "ext4", "xfs". Implicitly inferred to be "ext4" if unspecified.	false	string	
readOnly	Defaults to false (read/write). ReadOnly here will force the ReadOnly setting in VolumeMounts.	false	boolean	

3.3.126. v1.Preconditions

Preconditions must be fulfilled before an operation (update, delete, etc.) is carried out.

Name	Description	Required	Schema	Default
uid	Specifies the target UID.	false	Section 2.3.3, "types.UID"	

3.3.127. v1.PreferredSchedulingTerm

An empty preferred scheduling term matches all objects with implicit weight 0 (i.e. it's a no-op). A null preferred scheduling term matches no objects (i.e. is also a no-op).

Name	Description	Required	Schema	Default
weight	Weight associated with matching the corresponding nodeSelectorTerm, in the range 1-100.	true	integer (int32)	

Name	Description	Required	Schema	Default
preference	A node selector term, associated with the corresponding weight.	true	Section 2.3.166, "v1.NodeSelectorTerm"	

3.3.128. v1.Probe

Probe describes a health check to be performed against a container to determine whether it is alive or ready to receive traffic.

Name	Description	Required	Schema	Default
exec	One and only one of the following should be specified. Exec specifies the action to take.	false	Section 2.3.95, "v1.ExecAction"	
httpGet	HTTPGet specifies the http request to perform.	false	Section 2.3.112, "v1.HTTPGetAction"	
tcpSocket	TCPsocket specifies an action involving a TCP port. TCP hooks not yet supported	false	Section 2.3.272, "v1.TCPsocketAction"	
initialDelaySeconds	Number of seconds after the container has started before liveness probes are initiated. More info: http://kubernetes.io/docs/user-guide/pod-states#container-probes	false	integer (int32)	

Name	Description	Required	Schema	Default
timeoutSeconds	Number of seconds after which the probe times out. Defaults to 1 second. Minimum value is 1. More info: http://kubernetes.io/docs/user-guide/pod-states#container-probes	false	integer (int32)	
periodSeconds	How often (in seconds) to perform the probe. Default to 10 seconds. Minimum value is 1.	false	integer (int32)	
successThreshold	Minimum consecutive successes for the probe to be considered successful after having failed. Defaults to 1. Must be 1 for liveness. Minimum value is 1.	false	integer (int32)	
failureThreshold	Minimum consecutive failures for the probe to be considered failed after having succeeded. Defaults to 3. Minimum value is 1.	false	integer (int32)	

3.3.129. v1.ProjectedVolumeSource

Represents a projected volume source

Name	Description	Required	Schema	Default
sources	list of volume projections	true	Section 2.3.289, "v1.VolumeProjection" array	
defaultMode	Mode bits to use on created files by default. Must be a value between 0 and 0777. Directories within the path are not affected by this setting. This might be in conflict with other options that affect the file mode, like fsGroup, and the result can be other mode bits set.	false	integer (int32)	

3.3.130. v1.QuobyteVolumeSource

Represents a Quobyte mount that lasts the lifetime of a pod. Quobyte volumes do not support ownership management or SELinux relabeling.

Name	Description	Required	Schema	Default
registry	Registry represents a single or multiple Quobyte Registry services specified as a string as host:port pair (multiple entries are separated with commas) which acts as the central registry for volumes	true	string	

Name	Description	Required	Schema	Default
volume	Volume is a string that references an already created Quobyte volume by name.	true	string	
readOnly	ReadOnly here will force the Quobyte volume to be mounted with read-only permissions. Defaults to false.	false	boolean	
user	User to map volume access to Defaults to serviceaccount user	false	string	
group	Group to map volume access to Default is no group	false	string	

3.3.131. v1.RBDVolumeSource

Represents a Rados Block Device mount that lasts the lifetime of a pod. RBD volumes support ownership management and SELinux relabeling.

Name	Description	Required	Schema	Default
monitors	A collection of Ceph monitors. More info: http://releases.k8s.io/HEAD/examples/volumes/rbd/README.md#how-to-use-it	true	string array	
image	The rados image name. More info: http://releases.k8s.io/HEAD/examples/volumes/rbd/README.md#how-to-use-it	true	string	

Name	Description	Required	Schema	Default
fsType	Filesystem type of the volume that you want to mount. Tip: Ensure that the filesystem type is supported by the host operating system. Examples: "ext4", "xfs", "ntfs". Implicitly inferred to be "ext4" if unspecified. More info: http://kubernetes.io/docs/user-guide/volumes#rbd	false	string	
pool	The rados pool name. Default is rbd. More info: http://releases.k8s.io/HEAD/examples/volumes/rbd/README.md#how-to-use-it .	false	string	
user	The rados user name. Default is admin. More info: http://releases.k8s.io/HEAD/examples/volumes/rbd/README.md#how-to-use-it	false	string	

Name	Description	Required	Schema	Default
keyring	Keyring is the path to key ring for RBDUser. Default is /etc/ceph/keyring. More info: http://releases.k8s.io/HEAD/examples/volumes/rbd/README.md#how-to-use-it	false	string	
secretRef	SecretRef is name of the authentication secret for RBDUser. If provided overrides keyring. Default is nil. More info: http://releases.k8s.io/HEAD/examples/volumes/rbd/README.md#how-to-use-it	false	Section 2.3.152, "v1.LocalObject Reference"	
readOnly	ReadOnly here will force the ReadOnly setting in VolumeMounts. Defaults to false. More info: http://releases.k8s.io/HEAD/examples/volumes/rbd/README.md#how-to-use-it	false	boolean	

3.3.132. v1.ReplicationController

ReplicationController represents the configuration of a replication controller.

Name	Description	Required	Schema	Default
------	-------------	----------	--------	---------

Name	Description	Required	Schema	Default
kind	<p>Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/HEAD/docs/dev/api-conventions.md#types-kinds</p>	false	string	
apiVersion	<p>APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/HEAD/docs/dev/api-conventions.md#resources</p>	false	string	

Name	Description	Required	Schema	Default
metadata	If the Labels of a ReplicationController are empty, they are defaulted to be the same as the Pod(s) that the replication controller manages. Standard object's metadata. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#metadata	false	Section 2.3.176, "v1.ObjectMeta"	
spec	Spec defines the specification of the desired behavior of the replication controller. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#spec-and-status	false	Section 3.3.135, "v1.ReplicationControllerSpec"	

Name	Description	Required	Schema	Default
status	Status is the most recently observed status of the replication controller. This data may be out of date by some window of time. Populated by the system. Read-only. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#spec-and-status	false	Section 3.3.136, "v1.ReplicationControllerStatus"	

3.3.133. v1.ReplicationControllerCondition

ReplicationControllerCondition describes the state of a replication controller at a certain point.

Name	Description	Required	Schema	Default
type	Type of replication controller condition.	true	string	
status	Status of the condition, one of True, False, Unknown.	true	string	
lastTransitionTime	The last time the condition transitioned from one status to another.	false	string	
reason	The reason for the condition's last transition.	false	string	

Name	Description	Required	Schema	Default
message	A human readable message indicating details about the transition.	false	string	

3.3.134. v1.ReplicationControllerList

ReplicationControllerList is a collection of replication controllers.

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#types-kinds	false	string	

Name	Description	Required	Schema	Default
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/HEAD/docs/dev/api-conventions.md#resources	false	string	
metadata	Standard list metadata. More info: http://releases.k8s.io/HEAD/docs/dev/api-conventions.md#types-kinds	false	Section 2.3.151, "v1.ListMeta"	
items	List of replication controllers. More info: http://kubernetes.io/docs/user-guide/replication-controller	true	Section 3.3.132, "v1.ReplicationController" array	

3.3.135. v1.ReplicationControllerSpec

ReplicationControllerSpec is the specification of a replication controller.

Name	Description	Required	Schema	Default
------	-------------	----------	--------	---------

Name	Description	Required	Schema	Default
replicas	Replicas is the number of desired replicas. This is a pointer to distinguish between explicit zero and unspecified. Defaults to 1. More info: http://kubernetes.io/docs/user-guide/replication-controller#what-is-a-replication-controller	false	integer (int32)	
minReadySeconds	Minimum number of seconds for which a newly created pod should be ready without any of its container crashing, for it to be considered available. Defaults to 0 (pod will be considered available as soon as it is ready)	false	integer (int32)	

Name	Description	Required	Schema	Default
selector	Selector is a label query over pods that should match the Replicas count. If Selector is empty, it is defaulted to the labels present on the Pod template. Label keys and values that must match in order to be controlled by this replication controller, if empty defaulted to labels on Pod template. More info: http://kubernetes.io/docs/user-guide/labels#label-selectors	false	object	
template	Template is the object that describes the pod that will be created if insufficient replicas are detected. This takes precedence over a TemplateRef. More info: http://kubernetes.io/docs/user-guide/replication-controller#pod-template	false	Section 2.3.196, "v1.PodTemplateSpec"	

3.3.136. v1.ReplicationControllerStatus

ReplicationControllerStatus represents the current status of a replication controller.

Name	Description	Required	Schema	Default
replicas	Replicas is the most recently observed number of replicas. More info: http://kubernetes.io/docs/user-guide/replication-controller#what-is-a-replication-controller	true	integer (int32)	
fullyLabeledReplicas	The number of pods that have labels matching the labels of the pod template of the replication controller.	false	integer (int32)	
readyReplicas	The number of ready replicas for this replication controller.	false	integer (int32)	
availableReplicas	The number of available replicas (ready for at least minReadySeconds) for this replication controller.	false	integer (int32)	
observedGeneration	ObservedGeneration reflects the generation of the most recently observed replication controller.	false	integer (int64)	

Name	Description	Required	Schema	Default
conditions	Represents the latest available observations of a replication controller's current state.	false	Section 3.3.133 , "v1.ReplicationControllerCondition" array	

3.3.137. v1.ResourceFieldSelector

ResourceFieldSelector represents container resources (cpu, memory) and their output format

Name	Description	Required	Schema	Default
containerName	Container name: required for volumes, optional for env vars	false	string	
resource	Required: resource to select	true	string	
divisor	Specifies the output format of the exposed resources, defaults to "1"	false	string	

3.3.138. v1.ResourceQuota

ResourceQuota sets aggregate quota restrictions enforced per namespace

Name	Description	Required	Schema	Default
------	-------------	----------	--------	---------

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#types-kinds	false	string	
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#resources	false	string	
metadata	Standard object's metadata. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#metadata	false	Section 2.3.176, "v1.ObjectMeta"	

Name	Description	Required	Schema	Default
spec	Spec defines the desired quota. http://releases.k8s.io/HEAD/docs/dev/api-conventions.md#spec-and-status	false	Section 2.3.220, "v1.ResourceQuotaSpec"	
status	Status defines the actual enforced quota and its current usage. http://releases.k8s.io/HEAD/docs/dev/api-conventions.md#spec-and-status	false	Section 2.3.221, "v1.ResourceQuotaStatus"	

3.3.139. v1.ResourceQuotaList

ResourceQuotaList is a list of ResourceQuota items.

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/HEAD/docs/dev/api-conventions.md#types-kinds	false	string	

Name	Description	Required	Schema	Default
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/HEAD/docs/dev/api-conventions.md#resources	false	string	
metadata	Standard list metadata. More info: http://releases.k8s.io/HEAD/docs/dev/api-conventions.md#types-kinds	false	Section 2.3.151, "v1.ListMeta"	
items	Items is a list of ResourceQuota objects. More info: http://releases.k8s.io/HEAD/docs/design/admission_control_resource_quota.md#admissioncontrol-plugin-resourcequota	true	Section 3.3.138, "v1.ResourceQuota" array	

3.3.140. v1.ResourceQuotaScope

3.3.141. v1.ResourceQuotaSpec

ResourceQuotaSpec defines the desired hard limits to enforce for Quota.

Name	Description	Required	Schema	Default
hard	Hard is the set of desired hard limits for each named resource. More info: http://releases.k8s.io/HEAD/docs/design/admission_control_resource_quota.md#admissioncontrol-plugin-resourcequota	false	object	
scopes	A collection of filters that must match each object tracked by a quota. If not specified, the quota matches all objects.	false	Section 2.3.219, "v1.ResourceQuotaScope" array	

3.3.142. v1.ResourceQuotaStatus

ResourceQuotaStatus defines the enforced hard limits and observed use.

Name	Description	Required	Schema	Default
hard	Hard is the set of enforced hard limits for each named resource. More info: http://releases.k8s.io/HEAD/docs/design/admission_control_resource_quota.md#admissioncontrol-plugin-resourcequota	false	object	
used	Used is the current observed total usage of the resource in the namespace.	false	object	

3.3.143. v1.ResourceRequirements

ResourceRequirements describes the compute resource requirements.

Name	Description	Required	Schema	Default
limits	Limits describes the maximum amount of compute resources allowed. More info: http://kubernetes.io/docs/user-guide/compute-resources/	false	object	
requests	Requests describes the minimum amount of compute resources required. If Requests is omitted for a container, it defaults to Limits if that is explicitly specified, otherwise to an implementation-defined value. More info: http://kubernetes.io/docs/user-guide/compute-resources/	false	object	

3.3.144. v1.RunAsUserStrategyOptions

RunAsUserStrategyOptions defines the strategy type and any options used to create the strategy.

Name	Description	Required	Schema	Default
------	-------------	----------	--------	---------

Name	Description	Required	Schema	Default
type	Type is the strategy that will dictate what RunAsUser is used in the SecurityContext.	false	string	
uid	UID is the user id that containers must run as. Required for the MustRunAs strategy if not using namespace/service account allocated uids.	false	integer (int64)	
uidRangeMin	UIDRangeMin defines the min value for a strategy that allocates by range.	false	integer (int64)	
uidRangeMax	UIDRangeMax defines the max value for a strategy that allocates by range.	false	integer (int64)	

3.3.145. v1.SELinuxContextStrategyOptions

SELinuxContextStrategyOptions defines the strategy type and any options used to create the strategy.

Name	Description	Required	Schema	Default
type	Type is the strategy that will dictate what SELinux context is used in the SecurityContext.	false	string	

Name	Description	Required	Schema	Default
seLinuxOptions	seLinuxOptions required to run as; required for MustRunAs	false	Section 2.3.240, "v1.SELinuxOptions"	

3.3.146. v1.SELinuxOptions

SELinuxOptions are the labels to be applied to the container

Name	Description	Required	Schema	Default
user	User is a SELinux user label that applies to the container.	false	string	
role	Role is a SELinux role label that applies to the container.	false	string	
type	Type is a SELinux type label that applies to the container.	false	string	
level	Level is SELinux level label that applies to the container.	false	string	

3.3.147. v1.Scale

Scale represents a scaling request for a resource.

Name	Description	Required	Schema	Default
------	-------------	----------	--------	---------

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#types-kinds	false	string	
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#resources	false	string	
metadata	Standard object metadata; More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#metadata .	false	Section 2.3.176, "v1.ObjectMeta"	

Name	Description	Required	Schema	Default
spec	defines the behavior of the scale. More info: http://releases.k8s.io/HEAD/docs/dev/api-conventions.md#spec-and-status .	false	Section 3.3.149, "v1.ScaleSpec"	
status	current status of the scale. More info: http://releases.k8s.io/HEAD/docs/dev/api-conventions.md#spec-and-status . Read-only.	false	Section 3.3.150, "v1.ScaleStatus"	

3.3.148. v1.ScaleIOVolumeSource

ScaleIOVolumeSource represents a persistent ScaleIO volume

Name	Description	Required	Schema	Default
gateway	The host address of the ScaleIO API Gateway.	true	string	
system	The name of the storage system as configured in ScaleIO.	true	string	
secretRef	SecretRef references to the secret for ScaleIO user and other sensitive information. If this is not provided, Login operation will fail.	true	Section 2.3.152, "v1.LocalObject Reference"	

Name	Description	Required	Schema	Default
sslEnabled	Flag to enable/disable SSL communication with Gateway, default false	false	boolean	
protectionDomain	The name of the Protection Domain for the configured storage (defaults to "default").	false	string	
storagePool	The Storage Pool associated with the protection domain (defaults to "default").	false	string	
storageMode	Indicates whether the storage for a volume should be thick or thin (defaults to "thin").	false	string	
volumeName	The name of a volume already created in the ScaleIO system that is associated with this volume source.	false	string	

Name	Description	Required	Schema	Default
fsType	Filesystem type to mount. Must be a filesystem type supported by the host operating system. Ex. "ext4", "xfs", "ntfs". Implicitly inferred to be "ext4" if unspecified.	false	string	
readOnly	Defaults to false (read/write). ReadOnly here will force the ReadOnly setting in VolumeMounts.	false	boolean	

3.3.149. v1.ScaleSpec

ScaleSpec describes the attributes of a scale subresource.

Name	Description	Required	Schema	Default
replicas	desired number of instances for the scaled object.	false	integer (int32)	

3.3.150. v1.ScaleStatus

ScaleStatus represents the current status of a scale subresource.

Name	Description	Required	Schema	Default
replicas	actual number of observed instances of the scaled object.	true	integer (int32)	

Name	Description	Required	Schema	Default
selector	label query over pods that should match the replicas count. This is same as the label selector but in the string format to avoid introspection by clients. The string will be in the same format as the query-param syntax. More info about label selectors: http://kubernetes.io/docs/user-guide/labels#label-selectors	false	string	

3.3.151. v1.Secret

Secret holds secret data of a certain type. The total bytes of the values in the Data field must be less than MaxSecretSize bytes.

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#types-kinds	false	string	

Name	Description	Required	Schema	Default
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/HEAD/docs/dev/api-conventions.md#resources	false	string	
metadata	Standard object's metadata. More info: http://releases.k8s.io/HEAD/docs/dev/api-conventions.md#metadata	false	Section 2.3.176, "v1.ObjectMeta"	

Name	Description	Required	Schema	Default
data	Data contains the secret data. Each key must be a valid DNS_SUBDOMAIN or leading dot followed by valid DNS_SUBDOMAIN. The serialized form of the secret data is a base64 encoded string, representing the arbitrary (possibly non-string) data value here. Described in https://tools.ietf.org/html/rfc4648#section-4	false	object	
stringData	stringData allows specifying non-binary secret data in string form. It is provided as a write-only convenience method. All keys and values are merged into the data field on write, overwriting any existing values. It is never output when reading from the API.	false	object	
type	Used to facilitate programmatic handling of secret data.	false	string	

3.3.152. v1.SecretEnvSource

SecretEnvSource selects a Secret to populate the environment variables with.

The contents of the target Secret's Data field will represent the key-value pairs as environment variables.

Name	Description	Required	Schema	Default
name	Name of the referent. More info: http://kubernetes.io/docs/user-guide/identifiers#names	false	string	
optional	Specify whether the Secret must be defined	false	boolean	

3.3.153. v1.SecretKeySelector

SecretKeySelector selects a key of a Secret.

Name	Description	Required	Schema	Default
name	Name of the referent. More info: http://kubernetes.io/docs/user-guide/identifiers#names	false	string	
key	The key of the secret to select from. Must be a valid secret key.	true	string	
optional	Specify whether the Secret or it's key must be defined	false	boolean	

3.3.154. v1.SecretList

SecretList is a list of Secret.

Name	Description	Required	Schema	Default
------	-------------	----------	--------	---------

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/HEAD/docs/dev/api-conventions.md#types-kinds	false	string	
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/HEAD/docs/dev/api-conventions.md#resources	false	string	
metadata	Standard list metadata. More info: http://releases.k8s.io/HEAD/docs/dev/api-conventions.md#types-kinds	false	Section 2.3.151, "v1.ListMeta"	

Name	Description	Required	Schema	Default
items	Items is a list of secret objects. More info: http://kubernetes.io/docs/user-guide/secrets	true	Section 2.3.243 , "v1.Secret" array	

3.3.155. v1.SecretProjection

Adapts a secret into a projected volume.

The contents of the target Secret's Data field will be presented in a projected volume as files using the keys in the Data field as the file names. Note that this is identical to a secret volume source without the default mode.

Name	Description	Required	Schema	Default
name	Name of the referent. More info: http://kubernetes.io/docs/user-guide/identifiers#names	false	string	

Name	Description	Required	Schema	Default
items	If unspecified, each key-value pair in the Data field of the referenced Secret will be projected into the volume as a file whose name is the key and content is the value. If specified, the listed keys will be projected into the specified paths, and unlisted keys will not be present. If a key is specified which is not present in the Secret, the volume setup will error unless it is marked optional. Paths must be relative and may not contain the '..' path or start with '..'.	false	Section 2.3.146 , "v1.KeyToPath" array	
optional	Specify whether the Secret or its key must be defined	false	boolean	

3.3.156. v1.SecretVolumeSource

Adapts a Secret into a volume.

The contents of the target Secret's Data field will be presented in a volume as files using the keys in the Data field as the file names. Secret volumes support ownership management and SELinux relabeling.

Name	Description	Required	Schema	Default
------	-------------	----------	--------	---------

Name	Description	Required	Schema	Default
secretName	Name of the secret in the pod's namespace to use. More info: http://kubernetes.io/docs/user-guide/volumes#secrets	false	string	
items	If unspecified, each key-value pair in the Data field of the referenced Secret will be projected into the volume as a file whose name is the key and content is the value. If specified, the listed keys will be projected into the specified paths, and unlisted keys will not be present. If a key is specified which is not present in the Secret, the volume setup will error unless it is marked optional. Paths must be relative and may not contain the '..' path or start with '..'.	false	Section 2.3.146 , "v1.KeyToPath" array	

Name	Description	Required	Schema	Default
defaultMode	Optional: mode bits to use on created files by default. Must be a value between 0 and 0777. Defaults to 0644. Directories within the path are not affected by this setting. This might be in conflict with other options that affect the file mode, like fsGroup, and the result can be other mode bits set.	false	integer (int32)	
optional	Specify whether the Secret or it's keys must be defined	false	boolean	

3.3.157. v1.SecurityContext

SecurityContext holds security configuration that will be applied to a container. Some fields are present in both SecurityContext and PodSecurityContext. When both are set, the values in SecurityContext take precedence.

Name	Description	Required	Schema	Default
capabilities	The capabilities to add/drop when running containers. Defaults to the default set of capabilities granted by the container runtime.	false	Section 2.3.33, "v1.Capabilities"	

Name	Description	Required	Schema	Default
privileged	Run container in privileged mode. Processes in privileged containers are essentially equivalent to root on the host. Defaults to false.	false	boolean	
seLinuxOptions	The SELinux context to be applied to the container. If unspecified, the container runtime will allocate a random SELinux context for each container. May also be set in PodSecurityContext ext. If set in both SecurityContext and PodSecurityContext ext, the value specified in SecurityContext takes precedence.	false	Section 2.3.240, "v1.SELinuxOptions"	

Name	Description	Required	Schema	Default
runAsUser	The UID to run the entrypoint of the container process. Defaults to user specified in image metadata if unspecified. May also be set in PodSecurityContext ext. If set in both SecurityContext and PodSecurityContext ext, the value specified in SecurityContext takes precedence.	false	integer (int64)	
runAsNonRoot	Indicates that the container must run as a non-root user. If true, the Kubelet will validate the image at runtime to ensure that it does not run as UID 0 (root) and fail to start the container if it does. If unset or false, no such validation will be performed. May also be set in PodSecurityContext ext. If set in both SecurityContext and PodSecurityContext ext, the value specified in SecurityContext takes precedence.	false	boolean	

Name	Description	Required	Schema	Default
readOnlyRootFilesystem	Whether this container has a read-only root filesystem. Default is false.	false	boolean	

3.3.158. v1.SecurityContextConstraints

SecurityContextConstraints governs the ability to make requests that affect the SecurityContext that will be applied to a container.

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#types-kinds	false	string	

Name	Description	Required	Schema	Default
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/HEAD/docs/dev/api-conventions.md#resources	false	string	
metadata	Standard object's metadata. More info: http://releases.k8s.io/HEAD/docs/dev/api-conventions.md#metadata	false	Section 2.3.176, "v1.ObjectMeta"	
priority	Priority influences the sort order of SCCs when evaluating which SCCs to try first for a given pod request based on access in the Users and Groups fields. The higher the int, the higher priority. If scores for multiple SCCs are equal they will be sorted by name.	true	integer (int32)	

Name	Description	Required	Schema	Default
allowPrivilegedContainer	AllowPrivilegedContainer determines if a container can request to be run as privileged.	true	boolean	
defaultAddCapabilities	DefaultAddCapabilities is the default set of capabilities that will be added to the container unless the pod spec specifically drops the capability. You may not list a capability in both DefaultAddCapabilities and RequiredDropCapabilities.	true	Section 2.3.34, "v1.Capability" array	
requiredDropCapabilities	RequiredDropCapabilities are the capabilities that will be dropped from the container. These are required to be dropped and cannot be added.	true	Section 2.3.34, "v1.Capability" array	

Name	Description	Required	Schema	Default
allowedCapabilities	AllowedCapabilities is a list of capabilities that can be requested to add to the container. Capabilities in this field maybe added at the pod author's discretion. You must not list a capability in both AllowedCapabilities and RequiredDropCapabilities. To allow all capabilities you may use '*'.	true	Section 2.3.34, "v1.Capability" array	
allowHostDirVolumePlugin	AllowHostDirVolumePlugin determines if the policy allow containers to use the HostDir volume plugin	true	boolean	
volumes	Volumes is a white list of allowed volume plugins. FSType corresponds directly with the field names of a VolumeSource (azureFile, configMap, emptyDir). To allow all volumes you may use "*". To allow no volumes, set to ["none"].	true	Section 3.3.55, "v1.FSType" array	

Name	Description	Required	Schema	Default
allowHostNetwork	AllowHostNetwork determines if the policy allows the use of HostNetwork in the pod spec.	true	boolean	
allowHostPorts	AllowHostPorts determines if the policy allows host ports in the containers.	true	boolean	
allowHostPID	AllowHostPID determines if the policy allows host pid in the containers.	true	boolean	
allowHostIPC	AllowHostIPC determines if the policy allows host ipc in the containers.	true	boolean	
seLinuxContext	SELinuxContext is the strategy that will dictate what labels will be set in the SecurityContext.	false	Section 3.3.145, "v1.SELinuxContextStrategyOptions"	
runAsUser	RunAsUser is the strategy that will dictate what RunAsUser is used in the SecurityContext.	false	Section 3.3.144, "v1.RunAsUserStrategyOptions"	
supplementalGroups	SupplementalGroups is the strategy that will dictate what supplemental groups are used by the SecurityContext.	false	Section 3.3.170, "v1.SupplementalGroupsStrategyOptions"	

Name	Description	Required	Schema	Default
fsGroup	FSGroup is the strategy that will dictate what fs group is used by the SecurityContext.	false	Section 3.3.54, "v1.FSGroupStrategyOptions"	
readOnlyRootFilesystem	ReadOnlyRootFilesystem when set to true will force containers to run with a read only root file system. If the container specifically requests to run with a non-read only root file system the SCC should deny the pod. If set to false the container may run with a read only root file system if it wishes but it will not be forced to.	true	boolean	
users	The users who have permissions to use this security context constraints	false	string array	
groups	The groups that have permission to use this security context constraints	false	string array	

Name	Description	Required	Schema	Default
seccompProfiles	SeccompProfiles lists the allowed profiles that may be set for the pod or container's seccomp annotations. An unset (nil) or empty value means that no profiles may be specified by the pod or container. The wildcard '*' may be used to allow all profiles. When used to generate a value for a pod the first non-wildcard profile will be used as the default.	false	string array	

3.3.159. v1.SecurityContextConstraintsList

SecurityContextConstraintsList is a list of SecurityContextConstraints objects

Name	Description	Required	Schema	Default
------	-------------	----------	--------	---------

Name	Description	Required	Schema	Default
kind	<p>Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/HEAD/docs/dev/api-conventions.md#types-kinds</p>	false	string	
apiVersion	<p>APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/HEAD/docs/dev/api-conventions.md#resources</p>	false	string	
metadata	<p>More info: http://releases.k8s.io/HEAD/docs/dev/api-conventions.md#metadata</p>	false	Section 2.3.151, "v1.ListMeta"	

Name	Description	Required	Schema	Default
items	List of security context constraints.	true	Section 3.3.158, "v1.SecurityContextConstraints" array	

3.3.160. v1.Service

Service is a named abstraction of software service (for example, mysql) consisting of local port (for example 3306) that the proxy listens on, and the selector that determines which pods will answer requests sent through the proxy.

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#types-kinds	false	string	

Name	Description	Required	Schema	Default
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#resources	false	string	
metadata	Standard object's metadata. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#metadata	false	Section 2.3.176, "v1.ObjectMeta"	
spec	Spec defines the behavior of a service. http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#spec-and-status	false	Section 3.3.165, "v1.ServiceSpec"	

Name	Description	Required	Schema	Default
status	Most recently observed status of the service. Populated by the system. Read-only. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#spec-and-status	false	Section 3.3.166, "v1.ServiceStatus"	

3.3.161. v1.ServiceAccount

ServiceAccount binds together: * a name, understood by users, and perhaps by peripheral systems, for an identity * a principal that can be authenticated and authorized * a set of secrets

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#types-kinds	false	string	

Name	Description	Required	Schema	Default
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/HEAD/docs/dev/api-conventions.md#resources	false	string	
metadata	Standard object's metadata. More info: http://releases.k8s.io/HEAD/docs/dev/api-conventions.md#metadata	false	Section 2.3.176, "v1.ObjectMeta"	
secrets	Secrets is the list of secrets allowed to be used by pods running using this ServiceAccount. More info: http://kubernetes.io/docs/user-guide/secrets	false	Section 2.3.177, "v1.ObjectReference" array	

Name	Description	Required	Schema	Default
imagePullSecrets	ImagePullSecrets is a list of references to secrets in the same namespace to use for pulling any images in pods that reference this ServiceAccount. ImagePullSecrets are distinct from Secrets because Secrets can be mounted in the pod, but ImagePullSecrets are only accessed by the kubelet. More info: http://kubernetes.io/docs/user-guide/secrets#manually-specifying-an-imagepullsecret	false	Section 2.3.152, "v1.LocalObjectReference" array	
automountServiceAccountToken	AutomountServiceAccountToken indicates whether pods running as this service account should have an API token automatically mounted. Can be overridden at the pod level.	false	boolean	

3.3.162. v1.ServiceAccountList

ServiceAccountList is a list of ServiceAccount objects

Name	Description	Required	Schema	Default
------	-------------	----------	--------	---------

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/HEAD/docs/dev/api-conventions.md#types-kinds	false	string	
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/HEAD/docs/dev/api-conventions.md#resources	false	string	
metadata	Standard list metadata. More info: http://releases.k8s.io/HEAD/docs/dev/api-conventions.md#types-kinds	false	Section 2.3.151, "v1.ListMeta"	

Name	Description	Required	Schema	Default
items	List of ServiceAccounts. More info: http://releases.k8s.io/HEAD/docs/design/service_accounts.md#service-accounts	true	Section 3.3.161, "v1.ServiceAccount" array	

3.3.163. v1.ServiceList

ServiceList holds a list of services.

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/HEAD/docs/dev/api-conventions.md#types-kinds	false	string	

Name	Description	Required	Schema	Default
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#resources	false	string	
metadata	Standard list metadata. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#types-kinds	false	Section 2.3.151, "v1.ListMeta"	
items	List of services	true	Section 3.3.160, "v1.Service" array	

3.3.164. v1.ServicePort

ServicePort contains information on service's port.

Name	Description	Required	Schema	Default
------	-------------	----------	--------	---------

Name	Description	Required	Schema	Default
name	The name of this port within the service. This must be a DNS_LABEL. All ports within a ServiceSpec must have unique names. This maps to the 'Name' field in EndpointPort objects. Optional if only one ServicePort is defined on this service.	false	string	
protocol	The IP protocol for this port. Supports "TCP" and "UDP". Default is TCP.	false	string	
port	The port that will be exposed by this service.	true	integer (int32)	

Name	Description	Required	Schema	Default
targetPort	<p>Number or name of the port to access on the pods targeted by the service. Number must be in the range 1 to 65535. Name must be an IANA_SVC_NAME . If this is a string, it will be looked up as a named port in the target Pod's container ports. If this is not specified, the value of the 'port' field is used (an identity map). This field is ignored for services with clusterIP=None, and should be omitted or set equal to the 'port' field. More info: http://kubernetes.io/docs/user-guide/services#defining-a-service</p>	false	string	

Name	Description	Required	Schema	Default
nodePort	The port on each node on which this service is exposed when type=NodePort or LoadBalancer. Usually assigned by the system. If specified, it will be allocated to the service if unused or else creation of the service will fail. Default is to auto-allocate a port if the ServiceType of this Service requires one. More info: http://kubernetes.io/docs/user-guide/services#type—nodeport	false	integer (int32)	

3.3.165. v1.ServiceSpec

ServiceSpec describes the attributes that a user creates on a service.

Name	Description	Required	Schema	Default
ports	The list of ports that are exposed by this service. More info: http://kubernetes.io/docs/user-guide/services#virtual-ips-and-service-proxies	false	Section 3.3.164, "v1.ServicePort" array	

Name	Description	Required	Schema	Default
selector	Route service traffic to pods with label keys and values matching this selector. If empty or not present, the service is assumed to have an external process managing its endpoints, which Kubernetes will not modify. Only applies to types ClusterIP, NodePort, and LoadBalancer. Ignored if type is ExternalName. More info: http://kubernetes.io/docs/user-guide/services#overview	false	object	

Name	Description	Required	Schema	Default
clusterIP	<p>clusterIP is the IP address of the service and is usually assigned randomly by the master. If an address is specified manually and is not in use by others, it will be allocated to the service; otherwise, creation of the service will fail. This field can not be changed through updates. Valid values are "None", empty string (""), or a valid IP address. "None" can be specified for headless services when proxying is not required. Only applies to types ClusterIP, NodePort, and LoadBalancer. Ignored if type is ExternalName. More info: http://kubernetes.io/docs/user-guide/services#virtual-ips-and-service-proxies</p>	false	string	
type	<p>type determines how the Service is exposed. Defaults to ClusterIP. Valid options are ExternalName, ClusterIP, NodePort, and</p>	false	string	

Name	Description	Required	Schema	Default
	<p>maps to the specified externalName. "ClusterIP" allocates a cluster-internal IP address for load-balancing to endpoints. Endpoints are determined by the selector or if that is not specified, by manual construction of an Endpoints object. If clusterIP is "None", no virtual IP is allocated and the endpoints are published as a set of endpoints rather than a stable IP. "NodePort" builds on ClusterIP and allocates a port on every node which routes to the clusterIP. "LoadBalancer" builds on NodePort and creates an external load-balancer (if supported in the current cloud) which routes to the clusterIP. More info: http://kubernetes.io/docs/user-guide/services#overview</p>			

Name	Description	Required	Schema	Default
externalIPs	externalIPs is a list of IP addresses for which nodes in the cluster will also accept traffic for this service. These IPs are not managed by Kubernetes. The user is responsible for ensuring that traffic arrives at a node with this IP. A common example is external load-balancers that are not part of the Kubernetes system. A previous form of this functionality exists as the deprecatedPublicIPs field. When using this field, callers should also clear the deprecatedPublicIPs field.	false	string array	

Name	Description	Required	Schema	Default
deprecatedPublic IPs	<p>deprecatedPublic IPs is deprecated and replaced by the externalIPs field with almost the exact same semantics. This field is retained in the v1 API for compatibility until at least 8/20/2016. It will be removed from any new API revisions. If both deprecatedPublic IPs and externalIPs are set, deprecatedPublic IPs is used.</p>	false	string array	
sessionAffinity	<p>Supports "ClientIP" and "None". Used to maintain session affinity. Enable client IP based session affinity. Must be ClientIP or None. Defaults to None. More info: http://kubernetes.io/docs/user-guide/services#virtual-ips-and-service-proxies</p>	false	string	

Name	Description	Required	Schema	Default
loadBalancerIP	Only applies to Service Type: LoadBalancer. LoadBalancer will get created with the IP specified in this field. This feature depends on whether the underlying cloud-provider supports specifying the loadBalancerIP when a load balancer is created. This field will be ignored if the cloud-provider does not support the feature.	false	string	
loadBalancerSourceRanges	If specified and supported by the platform, this will restrict traffic through the cloud-provider load-balancer will be restricted to the specified client IPs. This field will be ignored if the cloud-provider does not support the feature." More info: http://kubernetes.io/docs/user-guide/services-firewalls	false	string array	

Name	Description	Required	Schema	Default
externalName	externalName is the external reference that kubedns or equivalent will return as a CNAME record for this service. No proxying will be involved. Must be a valid DNS name and requires Type to be ExternalName.	false	string	

3.3.166. v1.ServiceStatus

ServiceStatus represents the current status of a service.

Name	Description	Required	Schema	Default
loadBalancer	LoadBalancer contains the current status of the load-balancer, if one is present.	false	Section 3.3.78, "v1.LoadBalancerStatus"	

3.3.167. v1.Status

Status is a return value for calls that don't return other objects.

Name	Description	Required	Schema	Default
------	-------------	----------	--------	---------

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/HEAD/docs/dev/api-conventions.md#types-kinds	false	string	
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/HEAD/docs/dev/api-conventions.md#resources	false	string	
metadata	Standard list metadata. More info: http://releases.k8s.io/HEAD/docs/dev/api-conventions.md#types-kinds	false	Section 2.3.151, "v1.ListMeta"	

Name	Description	Required	Schema	Default
status	Status of the operation. One of: "Success" or "Failure". More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#spec-and-status	false	string	
message	A human-readable description of the status of this operation.	false	string	
reason	A machine-readable description of why this operation is in the "Failure" status. If this value is empty there is no information available. A Reason clarifies an HTTP status code but does not override it.	false	string	
details	Extended data associated with the reason. Each reason may define its own extended details. This field is optional and the data returned is not guaranteed to conform to any schema except that defined by the reason type.	false	Section 2.3.266, "v1.StatusDetails"	

Name	Description	Required	Schema	Default
code	Suggested HTTP return code for this status, 0 if not set.	false	integer (int32)	

3.3.168. v1.StatusCause

StatusCause provides more information about an api.Status failure, including cases when multiple errors are encountered.

Name	Description	Required	Schema	Default
reason	A machine-readable description of the cause of the error. If this value is empty there is no information available.	false	string	
message	A human-readable description of the cause of the error. This field may be presented as-is to a reader.	false	string	

Name	Description	Required	Schema	Default
field	<p>The field of the resource that has caused this error, as named by its JSON serialization. May include dot and postfix notation for nested attributes. Arrays are zero-indexed. Fields may appear more than once in an array of causes due to fields having multiple errors. Optional.</p> <p>Examples: "name" - the field "name" on the current resource "items[0].name" - the field "name" on the first array entry in "items"</p>	false	string	

3.3.169. v1.StatusDetails

StatusDetails is a set of additional properties that MAY be set by the server to provide additional information about a response. The Reason field of a Status object defines what attributes will be set. Clients must ignore fields that do not match the defined type of each attribute, and should assume that any attribute may be empty, invalid, or under defined.

Name	Description	Required	Schema	Default
------	-------------	----------	--------	---------

Name	Description	Required	Schema	Default
name	The name attribute of the resource associated with the status StatusReason (when there is a single name which can be described).	false	string	
group	The group attribute of the resource associated with the status StatusReason.	false	string	
kind	The kind attribute of the resource associated with the status StatusReason. On some operations may differ from the requested resource Kind. More info: http://releases.k8s.io/HEAD/docs/devel/api-conventions.md#types-kinds	false	string	
causes	The Causes array includes more details associated with the StatusReason failure. Not all StatusReasons may provide detailed causes.	false	Section 2.3.265, "v1.StatusCause" array	

Name	Description	Required	Schema	Default
retryAfterSeconds	If specified, the time in seconds before the operation should be retried.	false	integer (int32)	

3.3.170. v1.SupplementalGroupsStrategyOptions

SupplementalGroupsStrategyOptions defines the strategy type and options used to create the strategy.

Name	Description	Required	Schema	Default
type	Type is the strategy that will dictate what supplemental groups is used in the SecurityContext.	false	string	
ranges	Ranges are the allowed ranges of supplemental groups. If you would like to force a single supplemental group then supply a single range with the same start and end.	false	Section 3.3.66, "v1.IDRange" array	

3.3.171. v1.TCPSocketAction

TCPSocketAction describes an action based on opening a socket

Name	Description	Required	Schema	Default
------	-------------	----------	--------	---------

Name	Description	Required	Schema	Default
port	Number or name of the port to access on the container. Number must be in the range 1 to 65535. Name must be an IANA_SVC_NAME.	true	string	

3.3.172. v1.Taint

The node this Taint is attached to has the effect "effect" on any pod that that does not tolerate the Taint.

Name	Description	Required	Schema	Default
key	Required. The taint key to be applied to a node.	true	string	
value	Required. The taint value corresponding to the taint key.	false	string	
effect	Required. The effect of the taint on pods that do not tolerate the taint. Valid effects are NoSchedule, PreferNoSchedule and NoExecute.	true	string	

Name	Description	Required	Schema	Default
timeAdded	TimeAdded represents the time at which the taint was added. It is only written for NoExecute taints.	false	string	

3.3.173. v1.Toleration

The pod this Toleration is attached to tolerates any taint that matches the triple <key,value,effect> using the matching operator <operator>.

Name	Description	Required	Schema	Default
key	Key is the taint key that the toleration applies to. Empty means match all taint keys. If the key is empty, operator must be Exists; this combination means to match all values and all keys.	false	string	
operator	Operator represents a key's relationship to the value. Valid operators are Exists and Equal. Defaults to Equal. Exists is equivalent to wildcard for value, so that a pod can tolerate all taints of a particular category.	false	string	

Name	Description	Required	Schema	Default
value	Value is the taint value the toleration matches to. If the operator is Exists, the value should be empty, otherwise just a regular string.	false	string	
effect	Effect indicates the taint effect to match. Empty means match all taint effects. When specified, allowed values are NoSchedule, PreferNoSchedule and NoExecute.	false	string	
tolerationSeconds	TolerationSeconds represents the period of time the toleration (which must be of effect NoExecute, otherwise this field is ignored) tolerates the taint. By default, it is not set, which means tolerate the taint forever (do not evict). Zero and negative values will be treated as 0 (evict immediately) by the system.	false	integer (int64)	

3.3.174. v1.UniqueVolumeName

3.3.175. v1.Volume

Volume represents a named volume in a pod that may be accessed by any container in the pod.

Name	Description	Required	Schema	Default
name	Volume's name. Must be a DNS_LABEL and unique within the pod. More info: http://kubernetes.io/docs/user-guide/identifiers#names	true	string	
hostPath	HostPath represents a pre-existing file or directory on the host machine that is directly exposed to the container. This is generally used for system agents or other privileged things that are allowed to see the host machine. Most containers will NOT need this. More info: http://kubernetes.io/docs/user-guide/volumes#hostpath	false	Section 2.3.115, "v1.HostPathVolumeSource"	
emptyDir	EmptyDir represents a temporary directory that shares a pod's lifetime. More info: http://kubernetes.io/docs/user-guide/volumes#emptydir	false	Section 2.3.91, "v1.EmptyDirVolumeSource"	

Name	Description	Required	Schema	Default
gcePersistentDisk	GCEPersistentDisk represents a GCE Disk resource that is attached to a kubelet's host machine and then exposed to the pod. More info: http://kubernetes.io/docs/user-guide/volumes#gcepersistentdisk	false	Section 2.3.101, "v1.GCEPersistentDiskVolumeSource"	
awsElasticBlockStore	AWSElasticBlockStore represents an AWS Disk resource that is attached to a kubelet's host machine and then exposed to the pod. More info: http://kubernetes.io/docs/user-guide/volumes#awselasticblockstore	false	Section 2.3.6, "v1.AWSElasticBlockStoreVolumeSource"	
gitRepo	GitRepo represents a git repository at a particular revision.	false	Section 2.3.106, "v1.GitRepoVolumeSource"	
secret	Secret represents a secret that should populate this volume. More info: http://kubernetes.io/docs/user-guide/volumes#secrets	false	Section 2.3.250, "v1.SecretVolumeSource"	

Name	Description	Required	Schema	Default
nfs	NFS represents an NFS mount on the host that shares a pod's lifetime. More info: http://kubernetes.io/docs/user-guide/volumes#nfs	false	Section 2.3.155, "v1.NFSVolumeSource"	
iscsi	ISCSI represents an ISCSI Disk resource that is attached to a kubelet's host machine and then exposed to the pod. More info: http://releases.k8s.io/HEAD/examples/volumes/iscsi/README.md	false	Section 2.3.118, "v1.ISCSIVolumeSource"	
glusterfs	Glusterfs represents a Glusterfs mount on the host that shares a pod's lifetime. More info: http://releases.k8s.io/HEAD/examples/volumes/glusterfs/README.md	false	Section 2.3.108, "v1.GlusterfsVolumeSource"	

Name	Description	Required	Schema	Default
persistentVolumeClaim	PersistentVolumeClaimVolumeSource represents a reference to a PersistentVolumeClaim in the same namespace. More info: http://kubernetes.io/docs/user-guide/persistent-volumes#persistentvolumeclaims	false	Section 2.3.181, "v1.PersistentVolumeClaimVolumeSource"	
rbd	RBD represents a Rados Block Device mount on the host that shares a pod's lifetime. More info: http://releases.k8s.io/HEAD/examples/volumes/rbd/README.md	false	Section 2.3.213, "v1.RBDVolumeSource"	
flexVolume	FlexVolume represents a generic volume resource that is provisioned/attached using an exec based plugin. This is an alpha feature and may change in future.	false	Section 2.3.99, "v1.FlexVolumeSource"	

Name	Description	Required	Schema	Default
cinder	Cinder represents a cinder volume attached and mounted on kubelets host machine More info: http://releases.k8s.io/HEAD/examples/mysql-cinder-pd/README.md	false	Section 2.3.36, "v1.CinderVolumeSource"	
cephfs	CephFS represents a Ceph FS mount on the host that shares a pod's lifetime	false	Section 2.3.35, "v1.CephFSVolumeSource"	
flocker	Flocker represents a Flocker volume attached to a kubelet's host machine. This depends on the Flocker control service being running	false	Section 2.3.100, "v1.FlockerVolumeSource"	
downwardAPI	DownwardAPI represents downward API about the pod that should populate this volume	false	Section 2.3.85, "v1.DownwardAPIVolumeSource"	
fc	FC represents a Fibre Channel resource that is attached to a kubelet's host machine and then exposed to the pod.	false	Section 2.3.97, "v1.FCVolumeSource"	

Name	Description	Required	Schema	Default
azureFile	AzureFile represents an Azure File Service mount on the host and bind mount to the pod.	false	Section 2.3.12, "v1.AzureFileVolumeSource"	
configMap	ConfigMap represents a configMap that should populate this volume	false	Section 2.3.56, "v1.ConfigMapVolumeSource"	
vsphereVolume	VsphereVolume represents a vSphere volume attached and mounted on kubelets host machine	false	Section 2.3.290, "v1.VsphereVirtualDiskVolumeSource"	
quobyte	Quobyte represents a Quobyte mount on the host that shares a pod's lifetime	false	Section 2.3.212, "v1.QuobyteVolumeSource"	
azureDisk	AzureDisk represents an Azure Data Disk mount on the host and bind mount to the pod.	false	Section 2.3.11, "v1.AzureDiskVolumeSource"	
photonPersistentDisk	PhotonPersistentDisk represents a PhotonController persistent disk attached and mounted on kubelets host machine	false	Section 2.3.182, "v1.PhotonPersistentDiskVolumeSource"	

Name	Description	Required	Schema	Default
projected	Items for all in one resources secrets, configmaps, and downward API	false	Section 2.3.211, "v1.ProjectedVolumeSource"	
portworxVolume	PortworxVolume represents a portworx volume attached and mounted on kubelets host machine	false	Section 2.3.202, "v1.PortworxVolumeSource"	
scaleIO	ScaleIO represents a ScaleIO persistent volume attached and mounted on Kubernetes nodes.	false	Section 2.3.241, "v1.ScaleIOVolumeSource"	
metadata	Metadata represents metadata about the pod that should populate this volume Deprecated: Use downwardAPI instead.	false	Section 2.3.80, "v1.DeprecatedDownwardAPIVolumeSource"	

3.3.176. v1.VolumeMount

VolumeMount describes a mounting of a Volume within a container.

Name	Description	Required	Schema	Default
name	This must match the Name of a Volume.	true	string	
readOnly	Mounted read-only if true, read-write otherwise (false or unspecified). Defaults to false.	false	boolean	

Name	Description	Required	Schema	Default
mountPath	Path within the container at which the volume should be mounted. Must not contain '..'.	true	string	
subPath	Path within the volume from which the container's volume should be mounted. Defaults to "" (volume's root).	false	string	

3.3.177. v1.VolumeProjection

Projection that may be projected along with other supported volume types

Name	Description	Required	Schema	Default
secret	information about the secret data to project	false	Section 2.3.248, "v1.SecretProjection"	
downwardAPI	information about the downwardAPI data to project	false	Section 2.3.83, "v1.DownwardAPIProjection"	
configMap	information about the configMap data to project	false	Section 2.3.55, "v1.ConfigMapProjection"	

3.3.178. v1.VsphereVirtualDiskVolumeSource

Represents a vSphere volume resource.

Name	Description	Required	Schema	Default
volumePath	Path that identifies vSphere volume vmdk	true	string	

Name	Description	Required	Schema	Default
fsType	Filesystem type to mount. Must be a filesystem type supported by the host operating system. Ex. "ext4", "xfs", "ntfs". Implicitly inferred to be "ext4" if unspecified.	false	string	

3.3.179. v1.WatchEvent

Name	Description	Required	Schema	Default
type		true	string	
object		true	string	

3.3.180. v1.WeightedPodAffinityTerm

The weights of all of the matched WeightedPodAffinityTerm fields are added per-node to find the most preferred node(s)

Name	Description	Required	Schema	Default
weight	weight associated with matching the corresponding podAffinityTerm, in the range 1-100.	true	integer (int32)	
podAffinityTerm	Required. A pod affinity term, associated with the corresponding weight.	true	Section 2.3.184, "v1.PodAffinityTerm"	

3.3.181. v1beta1.Eviction

Eviction evicts a pod from its node subject to certain policies and safety constraints. This is a subresource of Pod. A request to cause such an eviction is created by POSTing to ... /pods/<pod name>/evictions.

Name	Description	Required	Schema	Default
kind	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: http://releases.k8s.io/HEAD/docs/dev/api-conventions.md#types-kinds	false	string	
apiVersion	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: http://releases.k8s.io/HEAD/docs/dev/api-conventions.md#resources	false	string	
metadata	ObjectMeta describes the pod that is being evicted.	false	Section 2.3.176, "v1.ObjectMeta"	

Name	Description	Required	Schema	Default
deleteOptions	DeleteOptions may be provided	false	Section 2.3.61, "v1.DeleteOptions"	