



# Red Hat CodeReady Workspaces 2.10

## Installation Guide

Installing Red Hat CodeReady Workspaces 2.10



# Red Hat CodeReady Workspaces 2.10 Installation Guide

---

## Installing Red Hat CodeReady Workspaces 2.10

Robert Kratky  
rkratky@redhat.com

Michal Maléř  
mmaler@redhat.com

Fabrice Flore-Thébault  
ffloreth@redhat.com

Yana Hontyk  
yhontyk@redhat.com

## Legal Notice

Copyright © 2021 Red Hat, Inc.

The text of and illustrations in this document are licensed by Red Hat under a Creative Commons Attribution–Share Alike 3.0 Unported license ("CC-BY-SA"). An explanation of CC-BY-SA is available at

<http://creativecommons.org/licenses/by-sa/3.0/>

. In accordance with CC-BY-SA, if you distribute this document or an adaptation of it, you must provide the URL for the original version.

Red Hat, as the licensor of this document, waives the right to enforce, and agrees not to assert, Section 4d of CC-BY-SA to the fullest extent permitted by applicable law.

Red Hat, Red Hat Enterprise Linux, the Shadowman logo, the Red Hat logo, JBoss, OpenShift, Fedora, the Infinity logo, and RHCE are trademarks of Red Hat, Inc., registered in the United States and other countries.

Linux<sup>®</sup> is the registered trademark of Linus Torvalds in the United States and other countries.

Java<sup>®</sup> is a registered trademark of Oracle and/or its affiliates.

XFS<sup>®</sup> is a trademark of Silicon Graphics International Corp. or its subsidiaries in the United States and/or other countries.

MySQL<sup>®</sup> is a registered trademark of MySQL AB in the United States, the European Union and other countries.

Node.js<sup>®</sup> is an official trademark of Joyent. Red Hat is not formally related to or endorsed by the official Joyent Node.js open source or commercial project.

The OpenStack<sup>®</sup> Word Mark and OpenStack logo are either registered trademarks/service marks or trademarks/service marks of the OpenStack Foundation, in the United States and other countries and are used with the OpenStack Foundation's permission. We are not affiliated with, endorsed or sponsored by the OpenStack Foundation, or the OpenStack community.

All other trademarks are the property of their respective owners.

## Abstract

Information for administrators installing Red Hat CodeReady Workspaces.

## Table of Contents

<b>MAKING OPEN SOURCE MORE INCLUSIVE</b> .....	<b>5</b>
<b>CHAPTER 1. SUPPORTED PLATFORMS</b> .....	<b>6</b>
<b>CHAPTER 2. CONFIGURING THE CODEREADY WORKSPACES INSTALLATION</b> .....	<b>7</b>
2.1. UNDERSTANDING THE CHECLUSTER CUSTOM RESOURCE	7
2.2. CHECLUSTER CUSTOM RESOURCE FIELDS REFERENCE	7
<b>CHAPTER 3. INSTALLING CODEREADY WORKSPACES</b> .....	<b>20</b>
3.1. INSTALLING CODEREADY WORKSPACES ON OPENSIFT 4 USING OPERATORHUB	20
3.1.1. Creating a project in OpenShift Web Console	20
3.1.2. Installing the Red Hat CodeReady Workspaces Operator	20
3.1.3. Creating an instance of the Red Hat CodeReady Workspaces Operator	21
3.2. INSTALLING CODEREADY WORKSPACES ON OPENSIFT 4 USING THE CLI	22
3.3. INSTALLING CODEREADY WORKSPACES ON OPENSIFT CONTAINER PLATFORM 3.11	23
3.3.1. Installing the crwctl CLI management tool	23
3.3.2. Installing CodeReady Workspaces on OpenShift 3 using the Operator	23
3.4. INSTALLING CODEREADY WORKSPACES IN A RESTRICTED ENVIRONMENT	25
3.4.1. Installing CodeReady Workspaces in a restricted environment using OperatorHub	25
3.4.2. Installing CodeReady Workspaces in a restricted environment using CLI management tool	26
3.4.2.1. Preparing an private registry	26
3.4.2.2. Preparing CodeReady Workspaces Custom Resource for restricted environment	32
3.4.2.2.1. Downloading the default CheCluster Custom Resource	32
3.4.2.2.2. Customizing the CheCluster Custom Resource for restricted environment	33
3.4.2.3. Starting CodeReady Workspaces installation in a restricted environment using CodeReady Workspaces CLI management tool	33
3.4.3. Preparing CodeReady Workspaces Custom Resource for installing behind a proxy	34
<b>CHAPTER 4. CONFIGURING CODEREADY WORKSPACES</b> .....	<b>35</b>
4.1. ADVANCED CONFIGURATION OPTIONS FOR THE CODEREADY WORKSPACES SERVER COMPONENT	35
4.1.1. Understanding CodeReady Workspaces server advanced configuration using the Operator	35
4.1.2. CodeReady Workspaces server component system properties reference	36
4.1.2.1. CodeReady Workspaces server	36
4.1.2.2. Authentication parameters	42
4.1.2.3. Internal	44
4.1.2.4. OpenShift Infra parameters	45
4.1.2.5. OpenShift Infra parameters	57
4.1.2.6. Experimental properties	58
4.1.2.7. Configuration of the major WebSocket endpoint	61
4.1.2.8. CORS settings	62
4.1.2.9. Factory defaults	62
4.1.2.10. Devfile defaults	63
4.1.2.11. Che system	66
4.1.2.12. Workspace limits	66
4.1.2.13. Users workspace limits	67
4.1.2.14. Organizations workspace limits	68
4.1.2.15. Multi-user-specific OpenShift infrastructure configuration	68
4.1.2.16. Keycloak configuration	69
4.2. CONFIGURING WORKSPACE TARGET PROJECT	72
4.2.1. One project per user strategy	74
4.2.2. Handling incompatible usernames or user IDs	74

4.2.3. Pre-creating a project for each user	74
4.2.4. Labeling the namespaces	75
4.3. CONFIGURING STORAGE STRATEGIES	76
4.3.1. Storage strategies for codeready-workspaces workspaces	76
4.3.1.1. The common PVC strategy	77
4.3.1.2. The per-workspace PVC strategy	78
4.3.1.3. The unique PVC strategy	78
4.3.1.4. How subpaths are used in PVCs	79
4.3.2. Configuring a CodeReady Workspaces workspace with a persistent volume strategy	79
4.3.2.1. Configuring a PVC strategy using the Operator	79
4.4. CONFIGURING STORAGE TYPES	80
4.4.1. Persistent storage	80
4.4.2. Ephemeral storage	81
4.4.3. Asynchronous storage	81
4.4.4. Configuring storage type defaults for CodeReady Workspaces dashboard	82
4.4.5. Idling asynchronous storage Pods	83
4.5. CONFIGURING THE NUMBER OF WORKSPACES THAT A USER CAN RUN	83
4.5.1. Using the Operator to configure the number of workspaces that a user can run	83
4.6. CONFIGURING THE NUMBER OF WORKSPACES THAT A USER CAN CREATE	84
4.6.1. Using the Operator to configure the number of workspaces that a user can create	84
4.7. CONFIGURING WORKSPACE EXPOSURE STRATEGIES	85
4.7.1. Configuring workspace exposure strategies using an Operator	85
4.7.2. Workspace exposure strategies	86
4.7.2.1. Multi-host strategy	86
4.7.2.2. Single-host strategy	86
4.7.2.2.1. devfile endpoints: single-host	87
4.7.2.2.2. devfile endpoints: multi-host	87
4.7.3. Security considerations	88
4.7.3.1. JSON web token (JWT) proxy	88
4.7.3.2. Secured plug-ins and editors	88
4.7.3.3. Secured container-image components	88
4.7.3.4. Cross-site request forgery attacks	89
4.7.3.5. Phishing attacks	89
4.8. CONFIGURING WORKSPACES NODESELECTOR	89
4.9. CONFIGURING RED HAT CODEREADY WORKSPACES SERVER HOSTNAME	89
4.10. CONFIGURING OPENSIFT ROUTE	90
4.11. CONFIGURING OPENSIFT ROUTE TO WORK WITH ROUTER SHARDING	92
4.12. DEPLOYING CODEREADY WORKSPACES WITH SUPPORT FOR GIT REPOSITORIES WITH SELF-SIGNED CERTIFICATES	96
4.13. INSTALLING CODEREADY WORKSPACES USING STORAGE CLASSES	97
4.14. IMPORTING UNTRUSTED TLS CERTIFICATES TO CODEREADY WORKSPACES	101
4.14.1. Adding new CA certificates into CodeReady Workspaces	101
4.14.2. Verification at the CodeReady Workspaces installation level	102
4.14.3. Verification at the workspace level	103
4.15. SWITCHING BETWEEN EXTERNAL AND INTERNAL DNS NAMES IN INTER-COMPONENT COMMUNICATION	104
4.16. SETTING UP THE RH-SSO CODEREADY-WORKSPACES-USERNAME-READONLY THEME FOR THE RED HAT CODEREADY WORKSPACES LOGIN PAGE	105
4.16.1. Logging in to RH-SSO	105
4.16.2. Setting up the RH-SSO codeready-workspaces-username-readonly theme	106
4.17. MOUNTING A SECRET AS A FILE OR AN ENVIRONMENT VARIABLE INTO A RED HAT CODEREADY WORKSPACES CONTAINER	107
4.17.1. Mounting a secret as a file into a Red Hat CodeReady Workspaces container	107

---

4.17.2. Mounting a secret as an environment variable into a Red Hat CodeReady Workspaces container	108
4.18. ENABLING DEV WORKSPACE ENGINE	110
<b>CHAPTER 5. UPGRADING CODEREADY WORKSPACES</b>	<b>111</b>
5.1. UPGRADING CODEREADY WORKSPACES USING OPERATORHUB	111
5.1.1. Specifying the approval strategy of CodeReady Workspaces in OperatorHub	111
5.1.2. Manually upgrading CodeReady Workspaces in OperatorHub	112
5.2. UPGRADING CODEREADY WORKSPACES USING THE CLI MANAGEMENT TOOL	113
5.3. UPGRADING CODEREADY WORKSPACES USING THE CLI MANAGEMENT TOOL IN RESTRICTED ENVIRONMENT	113
5.3.1. Understanding network connectivity in restricted environments	114
5.3.2. Building offline registry images	114
5.3.2.1. Building an offline devfile registry image	114
5.3.2.2. Building an offline plug-in registry image	115
5.3.3. Preparing an private registry	115
5.3.4. Upgrading CodeReady Workspaces using the CLI management tool in restricted environment	121
5.4. UPGRADING CODEREADY WORKSPACES THAT USES PROJECT STRATEGIES OTHER THAN 'PER USER'	122
5.4.1. Upgrading CodeReady Workspaces and backing up user data	123
5.4.2. Upgrading CodeReady Workspaces and losing user data	123
<b>CHAPTER 6. UNINSTALLING CODEREADY WORKSPACES</b>	<b>124</b>
6.1. UNINSTALLING CODEREADY WORKSPACES AFTER OPERATORHUB INSTALLATION USING THE OPENSIFT WEB CONSOLE	124
6.2. UNINSTALLING CODEREADY WORKSPACES AFTER OPERATORHUB INSTALLATION USING OPENSIFT CLI	125
6.3. UNINSTALLING CODEREADY WORKSPACES AFTER CRWCTL INSTALLATION	126





## MAKING OPEN SOURCE MORE INCLUSIVE

Red Hat is committed to replacing problematic language in our code, documentation, and web properties. We are beginning with these four terms: master, slave, blacklist, and whitelist. Because of the enormity of this endeavor, these changes will be implemented gradually over several upcoming releases. For more details, see [our CTO Chris Wright's message](#).

## CHAPTER 1. SUPPORTED PLATFORMS

This section describes the availability and the supported installation methods of CodeReady Workspaces 2.10 on OpenShift Container Platform 4.6, 3.11, and OpenShift Dedicated.

**Table 1.1. Supported deployment environments for CodeReady Workspaces 2.10 on OpenShift Container Platform and OpenShift Dedicated**

Platform	Architecture	Deployment method
OpenShift Container Platform 3.11	AMD64 and Intel 64 (x86_64)	<b>crwctl</b>
OpenShift Container Platform 4.6	AMD64 and Intel 64 (x86_64)	OperatorHub, <b>crwctl</b>
OpenShift Container Platform 4.6	IBM Z (s390x)	OperatorHub, <b>crwctl</b>
OpenShift Container Platform 4.6	IBM Power Systems (ppc64le)	OperatorHub, <b>crwctl</b>
OpenShift Container Platform 4.7	AMD64 and Intel 64 (x86_64)	OperatorHub, <b>crwctl</b>
OpenShift Container Platform 4.7	IBM Z (s390x)	OperatorHub, <b>crwctl</b>
OpenShift Container Platform 4.7	IBM Power Systems (ppc64le)	OperatorHub, <b>crwctl</b>
OpenShift Dedicated 4.7	AMD64 and Intel 64 (x86_64)	Add-On



### NOTE

Support for deploying CodeReady Workspaces on OpenShift Container Platform on IBM Z (s390x) is currently only available as a Technology Preview feature. Technology Preview features are not supported with Red Hat production service level agreements (SLAs) and might not be functionally complete. Red Hat does not recommend using them in production. These features provide early access to upcoming product features, enabling customers to test functionality and provide feedback during the development process. For details about the level of support for Technology Preview features, see Technology Preview Features Support Scope.

## CHAPTER 2. CONFIGURING THE CODEREADY WORKSPACES INSTALLATION

The following section describes configuration options to install Red Hat CodeReady Workspaces using the Operator.

### 2.1. UNDERSTANDING THE CHECLUSTER CUSTOM RESOURCE

A default deployment of CodeReady Workspaces consist in the application of a parametrized **CheCluster** Custom Resource by the Red Hat CodeReady Workspaces Operator.

#### CheCluster Custom Resource

- A YAML document describing the configuration of the overall CodeReady Workspaces installation.
- Contains sections to configure each component: **auth**, **database**, **server**, **storage**.

#### Role of the Red Hat CodeReady Workspaces Operator

- To translate the **CheCluster** Custom Resource into configuration (ConfigMap) usable by each component of the CodeReady Workspaces installation.

#### Role of the OpenShift platform

- To apply the configuration (ConfigMap) for each component.
- To create the necessary Pods.
- When OpenShift detects a change in the configuration of a component, it restarts the Pods accordingly.

#### Example 2.1. Configuring the main properties of the CodeReady Workspaces server component

1. The user applies a **CheCluster** Custom Resource containing some configuration related to the **server**.
2. The Operator generates a necessary ConfigMap, called **che**.
3. OpenShift detects change in the ConfigMap and triggers a restart of the CodeReady Workspaces Pod.

#### Additional resources

- [Understanding Operators](#).
- [Understanding Custom Resources](#).
- To learn how to modify the **CheCluster** Custom Resource, see the chosen installation procedure.

### 2.2. CHECLUSTER CUSTOM RESOURCE FIELDS REFERENCE

This section describes all fields available to customize the **CheCluster** Custom Resource.

- [Example 2.2, “A minimal \*\*CheCluster\*\* Custom Resource example.”](#)
- [Table 2.1, “\*\*CheCluster\*\* Custom Resource \*\*server\*\* settings, related to the CodeReady Workspaces server component.”](#)
- [Table 2.2, “\*\*CheCluster\*\* Custom Resource \*\*database\*\* configuration settings related to the database used by CodeReady Workspaces.”](#)
- [Table 2.3, “Custom Resource \*\*auth\*\* configuration settings related to authentication used by CodeReady Workspaces.”](#)
- [Table 2.4, “\*\*CheCluster\*\* Custom Resource \*\*storage\*\* configuration settings related to persistent storage used by CodeReady Workspaces.”](#)
- [Table 2.5, “\*\*CheCluster\*\* Custom Resource \*\*k8s\*\* configuration settings specific to CodeReady Workspaces installations on OpenShift.”](#)
- [Table 2.6, “\*\*CheCluster\*\* Custom Resource \*\*metrics\*\* settings, related to the CodeReady Workspaces metrics collection used by CodeReady Workspaces.”](#)
- [Table 2.7, “\*\*CheCluster\*\* Custom Resource \*\*status\*\* defines the observed state of CodeReady Workspaces installation”](#)

#### Example 2.2. A minimal **CheCluster** Custom Resource example.

```
apiVersion: org.eclipse.che/v1
kind: CheCluster
metadata:
  name: codeready-workspaces
spec:
  auth:
    externalIdentityProvider: false
  database:
    externalDb: false
  server:
    selfSignedCert: false
    gitSelfSignedCert: false
    tlsSupport: true
  storage:
    pvcStrategy: 'common'
    pvcClaimSize: '1Gi'
```

**Table 2.1. **CheCluster** Custom Resource **server** settings, related to the CodeReady Workspaces server component.**

Property	Description
airGapContainerRegistryHostname	Optional host name, or URL, to an alternate container registry to pull images from. This value overrides the container registry host name defined in all the default container images involved in a Che deployment. This is particularly useful to install Che in a restricted environment.

Property	Description
airGapContainerRegistryOrganization	Optional repository name of an alternate container registry to pull images from. This value overrides the container registry organization defined in all the default container images involved in a Che deployment. This is particularly useful to install CodeReady Workspaces in a restricted environment.
allowUserDefinedWorkspaceNamespaces	Deprecated. The value of this flag is ignored. Defines that a user is allowed to specify a OpenShift project, or an OpenShift project, which differs from the default. It's NOT RECOMMENDED to set to <b>true</b> without OpenShift OAuth configured. The OpenShift infrastructure also uses this property.
cheClusterRoles	A comma-separated list of ClusterRoles that will be assigned to Che ServiceAccount. Be aware that the Che Operator has to already have all permissions in these ClusterRoles to grant them.
cheDebug	Enables the debug mode for Che server. Defaults to <b>false</b> .
cheFlavor	Specifies a variation of the installation. The options are <b>che</b> for upstream Che installations, or <b>codeready</b> for <a href="#">CodeReady Workspaces</a> installation. Override the default value only on necessary occasions.
cheHost	Public host name of the installed Che server. When value is omitted, the value it will be automatically set by the Operator. See the <b>cheHostTLSSecret</b> field.
cheHostTLSSecret	Name of a secret containing certificates to secure ingress or route for the custom host name of the installed Che server. See the <b>cheHost</b> field.
cheImage	Overrides the container image used in Che deployment. This does NOT include the container image tag. Omit it or leave it empty to use the default container image provided by the Operator.
cheImagePullPolicy	Overrides the image pull policy used in Che deployment. Default value is <b>Always</b> for <b>nightly</b> or <b>latest</b> images, and <b>IfNotPresent</b> in other cases.
cheImageTag	Overrides the tag of the container image used in Che deployment. Omit it or leave it empty to use the default image tag provided by the Operator.
cheLogLevel	Log level for the Che server: <b>INFO</b> or <b>DEBUG</b> . Defaults to <b>INFO</b> .
cheServerIngress	The Che server ingress custom settings.
cheServerRoute	The Che server route custom settings.
cheWorkspaceClusterRole	Custom cluster role bound to the user for the Che workspaces. The default roles are used when omitted or left blank.

Property	Description
customCheProperties	Map of additional environment variables that will be applied in the generated <b>che</b> ConfigMap to be used by the Che server, in addition to the values already generated from other fields of the <b>CheCluster</b> custom resource (CR). When <b>customCheProperties</b> contains a property that would be normally generated in <b>che</b> ConfigMap from other CR fields, the value defined in the <b>customCheProperties</b> is used instead.
dashboardCpuLimit	Overrides the CPU limit used in the dashboard deployment. In cores. (500m = .5 cores). Default to 500m.
dashboardCpuRequest	Overrides the CPU request used in the dashboard deployment. In cores. (500m = .5 cores). Default to 100m.
dashboardImage	Overrides the container image used in the dashboard deployment. This includes the image tag. Omit it or leave it empty to use the default container image provided by the Operator.
dashboardImagePullPolicy	Overrides the image pull policy used in the dashboard deployment. Default value is <b>Always</b> for <b>nightly</b> or <b>latest</b> images, and <b>IfNotPresent</b> in other cases.
dashboardIngress	Dashboard ingress custom settings.
dashboardMemoryLimit	Overrides the memory limit used in the dashboard deployment. Defaults to 256Mi.
dashboardMemoryRequest	Overrides the memory request used in the dashboard deployment. Defaults to 16Mi.
dashboardRoute	Dashboard route custom settings.
devfileRegistryCpuLimit	Overrides the CPU limit used in the devfile registry deployment. In cores. (500m = .5 cores). Default to 500m.
devfileRegistryCpuRequest	Overrides the CPU request used in the devfile registry deployment. In cores. (500m = .5 cores). Default to 100m.
devfileRegistryImage	Overrides the container image used in the devfile registry deployment. This includes the image tag. Omit it or leave it empty to use the default container image provided by the Operator.
devfileRegistryIngress	The devfile registry ingress custom settings.
devfileRegistryMemoryLimit	Overrides the memory limit used in the devfile registry deployment. Defaults to 256Mi.

Property	Description
devfileRegistryMemoryRequest	Overrides the memory request used in the devfile registry deployment. Defaults to 16Mi.
devfileRegistryPullPolicy	Overrides the image pull policy used in the devfile registry deployment. Default value is <b>Always</b> for <b>nightly</b> or <b>latest</b> images, and <b>IfNotPresent</b> in other cases.
devfileRegistryRoute	The devfile registry route custom settings.
devfileRegistryUrl	Deprecated in favor of <b>externalDevfileRegistries</b> fields.
externalDevfileRegistries	External devfile registries, that serves sample, ready-to-use devfiles. Configure this in addition to a dedicated devfile registry (when <b>externalDevfileRegistry</b> is <b>false</b> ) or instead of it (when <b>externalDevfileRegistry</b> is <b>true</b> )
externalDevfileRegistry	Instructs the Operator on whether to deploy a dedicated devfile registry server. By default, a dedicated devfile registry server is started. When <b>externalDevfileRegistry</b> is <b>true</b> , no such dedicated server will be started by the Operator and configure at least one devfile registry with <b>externalDevfileRegistries</b> field.
externalPluginRegistry	Instructs the Operator on whether to deploy a dedicated plugin registry server. By default, a dedicated plugin registry server is started. When <b>externalPluginRegistry</b> is <b>true</b> , no such dedicated server will be started by the Operator and you will have to manually set the <b>pluginRegistryUrl</b> field.
gitSelfSignedCert	When enabled, the certificate from <b>che-git-self-signed-cert</b> ConfigMap will be propagated to the Che components and provide particular configuration for Git.
nonProxyHosts	List of hosts that will be reached directly, bypassing the proxy. Specify wild card domain use the following form <b>.&lt;DOMAIN&gt;</b> and <b> </b> as delimiter, for example: <b>localhost .my.host.com 123.42.12.32</b> Only use when configuring a proxy is required. Operator respects OpenShift cluster wide proxy configuration and no additional configuration is required, but defining <b>nonProxyHosts</b> in a custom resource leads to merging non proxy hosts lists from the cluster proxy configuration and ones defined in the custom resources. See the doc <a href="https://docs.openshift.com/container-platform/4.4/networking/enable-cluster-wide-proxy.html">https://docs.openshift.com/container-platform/4.4/networking/enable-cluster-wide-proxy.html</a> . See also the <b>proxyURL</b> fields.
pluginRegistryCpuLimit	Overrides the CPU limit used in the plugin registry deployment. In cores. (500m = .5 cores). Default to 500m.
pluginRegistryCpuRequest	Overrides the CPU request used in the plugin registry deployment. In cores. (500m = .5 cores). Default to 100m.

Property	Description
pluginRegistryImage	Overrides the container image used in the plugin registry deployment. This includes the image tag. Omit it or leave it empty to use the default container image provided by the Operator.
pluginRegistryIngress	Plugin registry ingress custom settings.
pluginRegistryMemoryLimit	Overrides the memory limit used in the plugin registry deployment. Defaults to 256Mi.
pluginRegistryMemoryRequest	Overrides the memory request used in the plugin registry deployment. Defaults to 16Mi.
pluginRegistryPullPolicy	Overrides the image pull policy used in the plugin registry deployment. Default value is <b>Always</b> for <b>nightly</b> or <b>latest</b> images, and <b>IfNotPresent</b> in other cases.
pluginRegistryRoute	Plugin registry route custom settings.
pluginRegistryUrl	Public URL of the plugin registry that serves sample ready-to-use devfiles. Set this <b>ONLY</b> when a use of an external devfile registry is needed. See the <b>externalPluginRegistry</b> field. By default, this will be automatically calculated by the Operator.
proxyPassword	Password of the proxy server. Only use when proxy configuration is required. See the <b>proxyURL</b> , <b>proxyUser</b> and <b>proxySecret</b> fields.
proxyPort	Port of the proxy server. Only use when configuring a proxy is required. See also the <b>proxyURL</b> and <b>nonProxyHosts</b> fields.
proxySecret	The secret that contains <b>user</b> and <b>password</b> for a proxy server. When the secret is defined, the <b>proxyUser</b> and <b>proxyPassword</b> are ignored.
proxyURL	URL (protocol+host name) of the proxy server. This drives the appropriate changes in the <b>JAVA_OPTS</b> and <b>https(s)_proxy</b> variables in the Che server and workspaces containers. Only use when configuring a proxy is required. Operator respects OpenShift cluster wide proxy configuration and no additional configuration is required, but defining <b>proxyUrl</b> in a custom resource leads to overrides the cluster proxy configuration with fields <b>proxyUrl</b> , <b>proxyPort</b> , <b>proxyUser</b> and <b>proxyPassword</b> from the custom resource. See the doc <a href="https://docs.openshift.com/container-platform/4.4/networking/enable-cluster-wide-proxy.html">https://docs.openshift.com/container-platform/4.4/networking/enable-cluster-wide-proxy.html</a> . See also the <b>proxyPort</b> and <b>nonProxyHosts</b> fields.
proxyUser	User name of the proxy server. Only use when configuring a proxy is required. See also the <b>proxyURL</b> , <b>proxyPassword</b> and <b>proxySecret</b> fields.



Property	Description
selfSignedCert	Deprecated. The value of this flag is ignored. The Che Operator will automatically detect whether the router certificate is self-signed and propagate it to other components, such as the Che server.
serverCpuLimit	Overrides the CPU limit used in the Che server deployment In cores. (500m = .5 cores). Default to 1.
serverCpuRequest	Overrides the CPU request used in the Che server deployment In cores. (500m = .5 cores). Default to 100m.
serverExposureStrategy	Sets the server and workspaces exposure type. Possible values are <b>multi-host</b> , <b>single-host</b> , <b>default-host</b> . Defaults to <b>multi-host</b> , which creates a separate ingress, or OpenShift routes, for every required endpoint. <b>single-host</b> makes Che exposed on a single host name with workspaces exposed on subpaths. Read the docs to learn about the limitations of this approach. Also consult the <b>singleHostExposureType</b> property to further configure how the Operator and the Che server make that happen on Kubernetes. <b>default-host</b> exposes the Che server on the host of the cluster. Read the docs to learn about the limitations of this approach.
serverMemoryLimit	Overrides the memory limit used in the Che server deployment. Defaults to 1Gi.
serverMemoryRequest	Overrides the memory request used in the Che server deployment. Defaults to 512Mi.
serverTrustStoreConfigMap Name	Name of the ConfigMap with public certificates to add to Java trust store of the Che server. This is often required when adding the OpenShift OAuth provider, which has HTTPS endpoint signed with self-signed cert. The Che server must be aware of its CA cert to be able to request it. This is disabled by default.
singleHostGatewayConfigMapLabels	The labels that need to be present in the ConfigMaps representing the gateway configuration.
singleHostGatewayConfigSidecarImage	The image used for the gateway sidecar that provides configuration to the gateway. Omit it or leave it empty to use the default container image provided by the Operator.
singleHostGatewayImage	The image used for the gateway in the single host mode. Omit it or leave it empty to use the default container image provided by the Operator.
tlsSupport	Deprecated. Instructs the Operator to deploy Che in TLS mode. This is enabled by default. Disabling TLS sometimes cause malfunction of some Che components.
useInternalClusterSvcNames	Use internal cluster SVC names to communicate between components to speed up the traffic and avoid proxy issues. The default value is <b>true</b> .

Property	Description
workspaceNamespaceDefault	Defines default OpenShift project in which user's workspaces are created for a case when a user does not override it. It's possible to use <b>&lt;username&gt;</b> , <b>&lt;userid&gt;</b> and <b>&lt;workspaceid&gt;</b> placeholders, such as <code>che-workspace-&lt;username&gt;</code> . In that case, a new namespace will be created for each user or workspace.

**Table 2.2. CheCluster Custom Resource database configuration settings related to the database used by CodeReady Workspaces.**

Property	Description
chePostgresContainerResources	PostgreSQL container custom settings
chePostgresDb	PostgreSQL database name that the Che server uses to connect to the DB. Defaults to <b>dbche</b> .
chePostgresHostName	PostgreSQL Database host name that the Che server uses to connect to. Defaults is <b>postgres</b> . Override this value ONLY when using an external database. See field <b>externalDb</b> . In the default case it will be automatically set by the Operator.
chePostgresPassword	PostgreSQL password that the Che server uses to connect to the DB. When omitted or left blank, it will be set to an automatically generated value.
chePostgresPort	PostgreSQL Database port that the Che server uses to connect to. Defaults to 5432. Override this value ONLY when using an external database. See field <b>externalDb</b> . In the default case it will be automatically set by the Operator.
chePostgresSecret	The secret that contains PostgreSQL `user` and <b>password</b> that the Che server uses to connect to the DB. When the secret is defined, the <b>chePostgresUser</b> and <b>chePostgresPassword</b> are ignored. When the value is omitted or left blank, the one of following scenarios applies: 1. <b>chePostgresUser</b> and <b>chePostgresPassword</b> are defined, then they will be used to connect to the DB. 2. <b>chePostgresUser</b> or <b>chePostgresPassword</b> are not defined, then a new secret with the name <b>che-postgres-secret</b> will be created with default value of <b>pgche</b> for <b>user</b> and with an auto-generated value for <b>password</b> .
chePostgresUser	PostgreSQL user that the Che server uses to connect to the DB. Defaults to <b>pgche</b> .
externalDb	Instructs the Operator on whether to deploy a dedicated database. By default, a dedicated PostgreSQL database is deployed as part of the Che installation. When <b>externalDb</b> is <b>true</b> , no dedicated database will be deployed by the Operator and you will need to provide connection details to the external DB you are about to use. See also all the fields starting with: <b>chePostgres</b> .

Property	Description
postgresImage	Overrides the container image used in the PostgreSQL database deployment. This includes the image tag. Omit it or leave it empty to use the default container image provided by the Operator.
postgresImagePullPolicy	Overrides the image pull policy used in the PostgreSQL database deployment. Default value is <b>Always</b> for <b>nightly</b> or <b>latest</b> images, and <b>IfNotPresent</b> in other cases.

**Table 2.3. Custom Resource `auth` configuration settings related to authentication used by CodeReady Workspaces.**

Property	Description
externalIdentityProvider	Instructs the Operator on whether or not to deploy a dedicated Identity Provider (Keycloak or RH SSO instance). Instructs the Operator on whether to deploy a dedicated Identity Provider (Keycloak or RH-SSO instance). By default, a dedicated Identity Provider server is deployed as part of the Che installation. When <b>externalIdentityProvider</b> is <b>true</b> , no dedicated identity provider will be deployed by the Operator and you will need to provide details about the external identity provider you are about to use. See also all the other fields starting with: <b>identityProvider</b> .
identityProviderAdminUserName	Overrides the name of the Identity Provider administrator user. Defaults to <b>admin</b> .
identityProviderClientId	Name of a Identity provider, Keycloak or RH-SSO, <b>client-id</b> that is used for Che. Override this when an external Identity Provider is in use. See the <b>externalIdentityProvider</b> field. When omitted or left blank, it is set to the value of the <b>flavour</b> field suffixed with <b>-public</b> .
identityProviderContainerResources	Identity provider container custom settings.
identityProviderImage	Overrides the container image used in the Identity Provider, Keycloak or RH-SSO, deployment. This includes the image tag. Omit it or leave it empty to use the default container image provided by the Operator.
identityProviderImagePullPolicy	Overrides the image pull policy used in the Identity Provider, Keycloak or RH-SSO, deployment. Default value is <b>Always</b> for <b>nightly</b> or <b>latest</b> images, and <b>IfNotPresent</b> in other cases.

Property	Description
identityProviderIngress	Ingress custom settings.
identityProviderPassword	Overrides the password of Keycloak administrator user. Override this when an external Identity Provider is in use. See the <b>externalIdentityProvider</b> field. When omitted or left blank, it is set to an auto-generated password.
identityProviderPostgresPassword	Password for a Identity Provider, Keycloak or RH-SSO, to connect to the database. Override this when an external Identity Provider is in use. See the <b>externalIdentityProvider</b> field. When omitted or left blank, it is set to an auto-generated password.
identityProviderPostgresSecret	The secret that contains <b>password</b> for the Identity Provider, Keycloak or RH-SSO, to connect to the database. When the secret is defined, the <b>identityProviderPostgresPassword</b> is ignored. When the value is omitted or left blank, the one of following scenarios applies: 1. <b>identityProviderPostgresPassword</b> is defined, then it will be used to connect to the database. 2. <b>identityProviderPostgresPassword</b> is not defined, then a new secret with the name <b>che-identity-postgres-secret</b> will be created with an auto-generated value for <b>password</b> .
identityProviderRealm	Name of a Identity provider, Keycloak or RH-SSO, realm that is used for Che. Override this when an external Identity Provider is in use. See the <b>externalIdentityProvider</b> field. When omitted or left blank, it is set to the value of the <b>flavour</b> field.
identityProviderRoute	Route custom settings.
identityProviderSecret	The secret that contains <b>user</b> and <b>password</b> for Identity Provider. When the secret is defined, the <b>identityProviderAdminUserName</b> and <b>identityProviderPassword</b> are ignored. When the value is omitted or left blank, the one of following scenarios applies: 1. <b>identityProviderAdminUserName</b> and <b>identityProviderPassword</b> are defined, then they will be used. 2. <b>identityProviderAdminUserName</b> or <b>identityProviderPassword</b> are not defined, then a new secret with the name <b>che-identity-secret</b> will be created with default value <b>admin</b> for <b>user</b> and with an auto-generated value for <b>password</b> .
identityProviderURL	Public URL of the Identity Provider server (Keycloak / RH-SSO server). Set this ONLY when a use of an external Identity Provider is needed. See the <b>externalIdentityProvider</b> field. By default, this will be automatically calculated and set by the Operator.
initialOpenShiftOAuthUser	For operating with the OpenShift OAuth authentication, create a new user account since the kubeadmin can not be used. If the value is true, then a new OpenShift OAuth user will be created for the HTTPasswd identity provider. If the value is false and the user has already been created, then it will be removed. If value is an empty, then do nothing. The user's credentials are stored in the <b>openshift-oauth-user-credentials</b> secret in 'openshift-config' namespace by Operator. Note that this solution is OpenShift 4 platform-specific.

Property	Description
oAuthClientName	Name of the OpenShift <b>OAuthClient</b> resource used to setup identity federation on the OpenShift side. Auto-generated when left blank. See also the <b>OpenShiftoAuth</b> field.
oAuthSecret	Name of the secret set in the OpenShift <b>OAuthClient</b> resource used to setup identity federation on the OpenShift side. Auto-generated when left blank. See also the <b>OAuthClientName</b> field.
openShiftoAuth	Enables the integration of the identity provider (Keycloak / RHSSO) with OpenShift OAuth. Empty value on OpenShift by default. This will allow users to directly login with their OpenShift user through the OpenShift login, and have their workspaces created under personal OpenShift namespaces. <b>WARNING:</b> the <b>kubeadmin</b> user is NOT supported, and logging through it will NOT allow accessing the Che Dashboard.
updateAdminPassword	Forces the default <b>admin</b> Che user to update password on first login. Defaults to <b>false</b> .

**Table 2.4. CheCluster Custom Resourcestorage configuration settings related to persistent storage used by CodeReady Workspaces.**

Property	Description
postgresPVCStorageClassName	Storage class for the Persistent Volume Claim dedicated to the PostgreSQL database. When omitted or left blank, a default storage class is used.
preCreateSubPaths	Instructs the Che server to start a special Pod to pre-create a sub-path in the Persistent Volumes. Defaults to <b>false</b> , however it will need to enable it according to the configuration of your OpenShift cluster.
pvcClaimSize	Size of the persistent volume claim for workspaces. Defaults to <b>1Gi</b> .
pvcJobsImage	Overrides the container image used to create sub-paths in the Persistent Volumes. This includes the image tag. Omit it or leave it empty to use the default container image provided by the Operator. See also the <b>preCreateSubPaths</b> field.
pvcStrategy	Persistent volume claim strategy for the Che server. This Can be: <code>common</code> (all workspaces PVCs in one volume), <b>per-workspace</b> (one PVC per workspace for all declared volumes) and <b>unique</b> (one PVC per declared volume). Defaults to <b>common</b> .
workspacePVCStorageClassName	Storage class for the Persistent Volume Claims dedicated to the Che workspaces. When omitted or left blank, a default storage class is used.

**Table 2.5. CheCluster Custom Resourcek8s configuration settings specific to CodeReady Workspaces installations on OpenShift.**

Property	Description
ingressClass	Ingress class that will define the which controller will manage ingresses. Defaults to <b>nginx</b> . NB: This drives the <b>kubernetes.io/ingress.class</b> annotation on Che-related ingresses.
ingressDomain	Global ingress domain for an OpenShift cluster. This MUST be explicitly specified: there are no defaults.
ingressStrategy	Strategy for ingress creation. Options are: <b>multi-host</b> (host is explicitly provided in ingress), <b>single-host</b> (host is provided, path-based rules) and <b>default-host</b> (no host is provided, path-based rules). Defaults to <b>multi-host</b> Deprecated in favor of <b>serverExposureStrategy</b> in the <b>server</b> section, which defines this regardless of the cluster type. When both are defined, the <b>serverExposureStrategy</b> option takes precedence.
securityContextFsGroup	The FSGroup in which the Che Pod and workspace Pods containers runs in. Default value is <b>1724</b> .
securityContextRunAsUser	ID of the user the Che Pod and workspace Pods containers run as. Default value is <b>1724</b> .
singleHostExposureType	When the serverExposureStrategy is set to <b>single-host</b> , the way the server, registries and workspaces are exposed is further configured by this property. The possible values are <b>native</b> , which means that the server and workspaces are exposed using ingresses on K8s or <b>gateway</b> where the server and workspaces are exposed using a custom gateway based on <a href="#">Traefik</a> . All the endpoints whether backed by the ingress or gateway <b>route</b> always point to the subpaths on the same domain. Defaults to <b>native</b> .
tlsSecretName	Name of a secret that will be used to setup ingress TLS termination when TLS is enabled. When the field is empty string, the default cluster certificate will be used. See also the <b>tlsSupport</b> field.

**Table 2.6. CheCluster Custom Resource metrics settings, related to the CodeReady Workspaces metrics collection used by CodeReady Workspaces.**

Property	Description
enable	Enables <b>metrics</b> the Che server endpoint. Default to <b>true</b> .

**Table 2.7. CheCluster Custom Resource status defines the observed state of CodeReady Workspaces installation**

Property	Description
cheClusterRunning	Status of a Che installation. Can be <b>Available</b> , <b>Unavailable</b> , or <b>Available, Rolling Update in Progress</b> .

Property	Description
cheURL	Public URL to the Che server.
cheVersion	Current installed Che version.
dbProvisioned	Indicates that a PostgreSQL instance has been correctly provisioned or not.
devfileRegistryURL	Public URL to the devfile registry.
devworkspaceStatus	The status of the Devworkspace subsystem
gitHubOAuthProvisioned	Indicates whether an Identity Provider instance, Keycloak or RH-SSO, has been configured to integrate with the GitHub OAuth.
helpLink	A URL that points to some URL where to find help related to the current Operator status.
keycloakProvisioned	Indicates whether an Identity Provider instance, Keycloak or RH-SSO, has been provisioned with realm, client and user.
keycloakURL	Public URL to the Identity Provider server, Keycloak or RH-SSO,.
message	A human readable message indicating details about why the Pod is in this condition.
openShiftOAuthUserCredentialsSecret	OpenShift OAuth secret in <b>openshift-config</b> namespace that contains user credentials for HTTPasswd identity provider.
openShifttoAuthProvisioned	Indicates whether an Identity Provider instance, Keycloak or RH-SSO, has been configured to integrate with the OpenShift OAuth.
pluginRegistryURL	Public URL to the plugin registry.
reason	A brief CamelCase message indicating details about why the Pod is in this state.

## CHAPTER 3. INSTALLING CODEREADY WORKSPACES

This section contains instructions to install Red Hat CodeReady Workspaces. The installation method depends on the target platform and the environment restrictions.

### 3.1. INSTALLING CODEREADY WORKSPACES ON OPENSIFT 4 USING OPERATORHUB

This section describes how to install CodeReady Workspaces using the CodeReady Workspaces Operator available in OpenShift 4 web console.

Operators are a method of packaging, deploying, and managing an OpenShift application which also provide the following:

- Repeatability of installation and upgrade.
- Constant health checks of every system component.
- Over-the-air (OTA) updates for OpenShift components and independent software vendor (ISV) content.
- A place to encapsulate knowledge from field engineers and spread it to all users.

#### Prerequisites

- An administrator account on a running instance of OpenShift 4.

#### 3.1.1. Creating a project in OpenShift Web Console

A project allows to organize and manage different resources on the cluster in an isolated unit. Create a project first to host the Red Hat CodeReady Workspaces Operator.

#### Procedure

1. Open the OpenShift web console, in the left panel navigate to the **Home → Projects** section.
2. Click **Create Project**.
3. Specify the project details:
  - **Name: openshift-workspaces**
  - **Display Name: Red Hat CodeReady Workspaces**
  - **Description: Red Hat CodeReady Workspaces**

#### 3.1.2. Installing the Red Hat CodeReady Workspaces Operator

Red Hat CodeReady Workspaces Operator provides all the resources for running CodeReady Workspaces, such as PostgreSQL, RH-SSO, image registries, and the CodeReady Workspaces server, and also configures all these services.

#### Prerequisites



- Access to the Web Console on the cluster.

### Procedure

1. To install the Red Hat CodeReady Workspaces Operator, in the left panel, navigate to the **Operators** → **OperatorHub** section.
2. In the **Filter by keyword** field, type **Red Hat CodeReady Workspaces** and click the **Red Hat CodeReady Workspaces** tile.
3. In the **Red Hat CodeReady Workspaces** pop-up window, click the **Install** button.
4. On the **Install Operator** screen, specify the following options:
  - **Installation mode: A specific project on the cluster**
  - **Installed Namespace:** \*Pick an existing project → **openshift-workspaces**

### Verification steps

1. To verify the Red Hat CodeReady Workspaces Operator has installed correctly, in the left panel navigate to the **Operators** → **Installed Operators** section.
2. In the **Installed Operators** screen, click the **Red Hat CodeReady Workspaces** name and navigate to the **Details** tab.
3. In the **ClusterServiceVersion Details** section at the bottom of the page, wait for these messages:
  - **Status: Succeeded**
  - **Status Reason: install strategy completed with no errors**
4. Navigate to the **Events** tab and wait for this message: **install strategy completed with no errors**.


### 3.1.3. Creating an instance of the Red Hat CodeReady Workspaces Operator

Follow this procedure to install Red Hat CodeReady Workspaces with the default configuration. To modify the configuration, see [Chapter 2, Configuring the CodeReady Workspaces installation](#).

### Procedure

1. To create an instance of the Red Hat CodeReady Workspaces Operator, in the left panel, navigate to the **Operators** → **Installed Operators** section.
2. In the **Installed Operators** screen, click the **Red Hat CodeReady Workspaces** name.
3. In the **Operator Details** screen, in the **Details** tab, inside of the **Provided APIs** section, click the **Create Instance** link.
4. The **Create CheCluster** page contains the configuration of the overall CodeReady Workspaces instance to create. It is the **CheCluster** Custom Resource. Keep the default values.
5. To create the **codeready-workspaces** cluster, click the **Create** button in the lower left corner of the window.

6. On the **Operator Details** screen, in the **Red Hat CodeReady Workspaces Cluster** tab, click on the **codeready-workspaces** link.
7. To navigate to the **codeready-workspaces** instance, click the link under **Red Hat CodeReady Workspaces URL**.



#### NOTE

The installation might take more than 5 minutes. The URL appears after the Red Hat CodeReady Workspaces installation finishes.

#### Verification steps

1. To verify that the Red Hat CodeReady Workspaces instance has installed correctly, navigate to the **CodeReady Workspaces Cluster** tab. The **CheClusters** screen displays the list of Red Hat CodeReady Workspaces instances and their status.
2. Click **codeready-workspaces CheCluster** in the table and navigate to the **Details** tab.
3. See the content of following fields:
  - **Message**: the field contains error messages, if any. The expected content is **None**.
  - **Red Hat CodeReady Workspaces URL**: displays the URL of the Red Hat CodeReady Workspaces instance, once the deployment is successful.
4. Navigate to the **Resources** tab. The screen displays the list of the resources assigned to the CodeReady Workspaces deployment.
5. To see more details about the state of a resource, click its name and inspect the content of the available tabs.

#### Additional resources

- [Navigating CodeReady Workspaces using the Dashboard](#).
- [Viewing the state of the CodeReady Workspaces cluster deployment using OpenShift 4 CLI tools](#).

## 3.2. INSTALLING CODEREADY WORKSPACES ON OPENSIFT 4 USING THE CLI

This section describes how to install CodeReady Workspaces on OpenShift 4 with the **crwctl** CLI management tool.

#### Prerequisites

- An OpenShift cluster with an administrator account.
- **oc** is available. See [Getting started with the OpenShift CLI](#). **oc** version must match the OpenShift cluster version.
- You have logged in to OpenShift. See [Logging in to the CLI](#).
- **crwctl** is available. See [Section 3.3.1, "Installing the crwctl CLI management tool"](#).

## Procedure

- Run the **server:deploy** command to create the CodeReady Workspaces instance:

```
$ crwctl server:deploy -n openshift-workspaces
```

## Verification steps

1. The output of the **server:deploy** command ends with:

```
Command server:deploy has completed successfully.
```

2. Navigate to the CodeReady Workspaces cluster instance: **https://codeready-  
<openshift\_deployment\_name>.<domain\_name>**.

## 3.3. INSTALLING CODEREADY WORKSPACES ON OPENSIFT CONTAINER PLATFORM 3.11

### 3.3.1. Installing the crwctl CLI management tool

This section describes how to install `crwctl`, the CodeReady Workspaces CLI management tool.

## Procedure

1. Navigate to <https://developers.redhat.com/products/codeready-workspaces/download>.
2. Download the CodeReady Workspaces CLI management tool archive for version 2.10.
3. Extract the archive to a folder, such as **\$HOME/crwctl** or **/opt/crwctl**.
4. Run the **crwctl** executable from the extracted folder. In this example, **\$HOME/crwctl/bin/crwctl version**.
5. Optionally, add the **bin** folder to your **\$PATH**, for example, **PATH=\$PATH:\$HOME/crwctl/bin** to enable running **crwctl** without the full path specification.

## Verification step

Running **crwctl version** displays the current version of the tool.

### 3.3.2. Installing CodeReady Workspaces on OpenShift 3 using the Operator

This section describes how to install CodeReady Workspaces on OpenShift 3 with the **crwctl** CLI management tool. The method of installation is using the Operator and enable TLS (HTTPS).



## NOTE

Methods for updating from a previous CodeReady Workspaces installation and enabling multiple instances in the same OpenShift Container Platform 3.11 cluster are provided below the installation procedure.

Operators are a method of packaging, deploying, and managing a OpenShift application which also provide the following:

- Repeatability of installation and upgrade.
- Constant health checks of every system component.
- Over-the-air (OTA) updates for OpenShift components and independent software vendor (ISV) content.
- A place to encapsulate knowledge from field engineers and spread it to all users.



## NOTE

This approach is only supported for use with OpenShift Container Platform and OpenShift Dedicated version 3.11, but also work for newer versions of OpenShift Container Platform and OpenShift Dedicated, and serves as a backup installation method for situations when the installation method using OperatorHub is not available.

## Prerequisites

- Administrator rights on a running instance of OpenShift 3.11.
- An installation of the **oc** OpenShift 3.11 CLI management tool. See [Installing the OpenShift 3.11 CLI](#).
- An installation of the **crwctl** management tool. See [Section 3.3.1, “Installing the crwctl CLI management tool”](#).
- To apply settings that the main crwctl command-line parameters cannot set, prepare a configuration file **operator-cr-patch.yaml** that will override the default values in the **CheCluster** Custom Resource used by the Operator. See [Chapter 2, Configuring the CodeReady Workspaces installation](#).
- Use the openshift-workspaces namespace as the default installation project.
- Configure OpenShift to pull images from **registry.redhat.com**. See [Red Hat Container Registry Authentication](#).

## Procedure

1. Log in to OpenShift. See [Basic Setup and Login](#).

```
$ oc login
```

2. Run the following command to verify that the version of the **oc** OpenShift CLI management tool is 3.11:

```
$ oc version  
oc v3.11.0+0cbc58b
```

3. Run the following command to create the CodeReady Workspaces instance in the default project called openshift-workspaces:

```
$ crwctl server:deploy -p openshift
```

## Verification steps

1. The output of the previous command ends with:

```
Command server:deploy has completed successfully.
```

2. Navigate to the CodeReady Workspaces cluster instance: `https://codeready-  
<openshift_deployment_name>.<domain_name>`.

## 3.4. INSTALLING CODEREADY WORKSPACES IN A RESTRICTED ENVIRONMENT

By default, Red Hat CodeReady Workspaces uses various external resources, mainly container images available in public registries.

To deploy CodeReady Workspaces in an environment where these external resources are not available (for example, on a cluster that is not exposed to the public Internet):

1. Identify the image registry used by the OpenShift cluster, and ensure you can push to it.
2. Push all the images needed for running CodeReady Workspaces to this registry.
3. Configure CodeReady Workspaces to use the images that have been pushed to the registry.
4. Proceed to the CodeReady Workspaces installation.

The procedure for installing CodeReady Workspaces in restricted environments is different based on the installation method you use:

- [Installation using OperatorHub on OpenShift 4.3](#) and above
- [Installation using the `crwctl` management tool on both OpenShift 3.11 or 4.x](#)

### Notes on network connectivity in restricted environments

Restricted network environments range from a private subnet in a cloud provider to a separate network owned by a company, disconnected from the public Internet. Regardless of the network configuration, CodeReady Workspaces works **provided that the Routes that are created for CodeReady Workspaces components (codeready-workspaces-server, identity provider, devfile and plugin registries) are accessible from inside the OpenShift cluster.**

Take into account the network topology of the environment to determine how best to accomplish this. For example, on a network owned by a company or an organization, the network administrators must ensure that traffic bound from the cluster can be routed to Route hostnames. In other cases, for example, on AWS, create a proxy configuration allowing the traffic to leave the node to reach an external-facing Load Balancer.

When the restricted network involves a proxy, follow the instructions provided in [Section 3.4.3, "Preparing CodeReady Workspaces Custom Resource for installing behind a proxy"](#).

### 3.4.1. Installing CodeReady Workspaces in a restricted environment using OperatorHub

#### Prerequisites

- A running OpenShift cluster. See the [OpenShift Container Platform 4.3 documentation](#) for instructions on how to install an OpenShift cluster on a restricted network.

- Access to the mirror registry used to installed the OpenShift disconnected cluster in restricted network. See the [Related OpenShift Container Platform 4.3 documentation about creating a mirror registry for installation in a restricted network](#).

On disconnected OpenShift 4 clusters running on restricted networks, an Operator can be successfully installed from OperatorHub only if it meets the additional requirements defined in [Enabling your Operator for restricted network environments](#).

The CodeReady Workspaces operator meets these requirements and is therefore compatible with the [official documentation about OLM on a restricted network](#) .

## Procedure

To install CodeReady Workspaces from OperatorHub:

1. Build a **redhat-operators** catalog image. See [Building an Operator catalog image](#) .
2. Configure OperatorHub to use this catalog image for operator installations. See [Configuring OperatorHub for restricted networks](#).
3. Proceed to the CodeReady Workspaces installation as usual as described in [Section 3.1, "Installing CodeReady Workspaces on OpenShift 4 using OperatorHub"](#).

### 3.4.2. Installing CodeReady Workspaces in a restricted environment using CLI management tool



#### NOTE

Use CodeReady Workspaces CLI management tool to install CodeReady Workspaces on restricted networks if installation through OperatorHub is not available. This method is supported for OpenShift Container Platform 3.11.

#### Prerequisites

- A running OpenShift cluster. See the [OpenShift Container Platform 3.11 documentation](#) for instructions on how to install an OpenShift cluster.

#### 3.4.2.1. Preparing an private registry

#### Prerequisites

- The **oc** tool is available.
- The **skopeo** tool, version 0.1.40 or later, is available.
- The **podman** tool is available.
- An image registry accessible from the OpenShift cluster and supporting the format of the V2 image manifest, schema version 2. Ensure you can push to it from a location having, at least temporarily, access to the internet.

#### Table 3.1. Placeholders used in examples

<b>&lt;source-image&gt;</b>	Full coordinates of the source image, including registry, organization, and digest.
<b>&lt;target-registry&gt;</b>	Host name and port of the target container-image registry.
<b>&lt;target-organization&gt;</b>	Organization in the target container-image registry
<b>&lt;target-image&gt;</b>	Image name and digest in the target container-image registry.
<b>&lt;target-user&gt;</b>	User name in the target container-image registry.
<b>&lt;target-password&gt;</b>	User password in the target container-image registry.

## Procedure

1. Log into the internal image registry:

```
$ podman login --username <user> --password <password> <target-registry>
```



### NOTE

If you encounter an error, like **x509: certificate signed by unknown authority**, when attempting to push to the internal registry, try one of these workarounds:

- add the OpenShift cluster's certificate to **/etc/containers/certs.d/<target-registry>**
- add the registry as an insecure registry by adding the following lines to the Podman configuration file located at **/etc/containers/registries.conf**:

```
[registries.insecure]
registries = ['<target-registry>']
```

2. Copy images without changing their digest. Repeat this step for every image in the following table:

```
$ skopeo copy --all docker://<source-image> docker://<target-registry>/<target-organization>/<target-image>
```

**NOTE**

Table 3.2. Understanding the usage of the container-images from the prefix or keyword they include in their name

Usage	Prefix or keyword
Essential	not <b>stacks-</b> , <b>plugin-</b> , or <b>-openj9-</b>
Workspaces	<b>stacks-</b> , <b>plugin-</b>
IBM Z and IBM Power Systems	<b>-openj9-</b>

**NOTE**

Images suffixed with **openj9** are the **Eclipse OpenJ9** image equivalents of the OpenJDK images used on x86\_64. IBM Power Systems and IBM Z use Eclipse OpenJ9 for better performance on those systems.

Table 3.3. Images to copy in the private registry

<source-image>	<target-image>
registry.redhat.io/codeready-workspaces/configbump-rhel8@sha256:df90e683ef3141ea5e5ba77e4346285685be527a35073855c936c6237e91a1a8	configbump-rhel8@sha256:df90e683ef3141ea5e5ba77e4346285685be527a35073855c936c6237e91a1a8
registry.redhat.io/codeready-workspaces/crw-2-rhel8-operator@sha256:eac1db6b4008ba849d4bcab9acc8542806b2aeda8a5a5f4b3c56fb87129d8e54	crw-2-rhel8-operator@sha256:eac1db6b4008ba849d4bcab9acc8542806b2aeda8a5a5f4b3c56fb87129d8e54
registry.redhat.io/codeready-workspaces/dashboard-rhel8@sha256:d6911d22200677aa0116f4523d325e5630b300788ee55fd2ba3b709714901d34	dashboard-rhel8@sha256:d6911d22200677aa0116f4523d325e5630b300788ee55fd2ba3b709714901d34
registry.redhat.io/codeready-workspaces/devfileregistry-rhel8@sha256:1bbe4ccc6ad751bedcf30f6db38180a02730de32e36195be804e610ae2c636d7	devfileregistry-rhel8@sha256:1bbe4ccc6ad751bedcf30f6db38180a02730de32e36195be804e610ae2c636d7



<source-image>	<target-image>
<p>registry.redhat.io/codeready-workspaces/devworkspace-controller-rhel8@sha256:ee3e6abf41fe504ef7c6c76a904542da0e22af242f2cd2007d3899e72fc17dab</p>	<p>devworkspace-controller-rhel8@sha256:ee3e6abf41fe504ef7c6c76a904542da0e22af242f2cd2007d3899e72fc17dab</p>
<p>registry.redhat.io/codeready-workspaces/devworkspace-rhel8@sha256:832ebf337003084ea649244b331bcc5442dae90f5ad5a0c83b2cc15e68b29fdf</p>	<p>devworkspace-rhel8@sha256:832ebf337003084ea649244b331bcc5442dae90f5ad5a0c83b2cc15e68b29fdf</p>
<p>registry.redhat.io/codeready-workspaces/jwtproxy-rhel8@sha256:c62c57ceb4b5f78eb62e43ee59e580e7df8cbe6e75a4e59ce344ea2c885c7129</p>	<p>jwtproxy-rhel8@sha256:c62c57ceb4b5f78eb62e43ee59e580e7df8cbe6e75a4e59ce344ea2c885c7129</p>
<p>registry.redhat.io/codeready-workspaces/machineexec-rhel8@sha256:56573ec2092ba1b4339e5ae9e9c128bb48c6ef08f95512fb7e12b6d732624899</p>	<p>machineexec-rhel8@sha256:56573ec2092ba1b4339e5ae9e9c128bb48c6ef08f95512fb7e12b6d732624899</p>
<p>registry.redhat.io/codeready-workspaces/plugin-java11-openj9-rhel8@sha256:adf7aedb113fda38db621f2660246ea011d5b25ce77734db406888545b194daf</p>	<p>plugin-java11-openj9-rhel8@sha256:adf7aedb113fda38db621f2660246ea011d5b25ce77734db406888545b194daf</p>
<p>registry.redhat.io/codeready-workspaces/plugin-java11-rhel8@sha256:f90e09397caa4dd5cd3476e495adfc0096272c0ba746a6e32215175c541ae058</p>	<p>plugin-java11-rhel8@sha256:f90e09397caa4dd5cd3476e495adfc0096272c0ba746a6e32215175c541ae058</p>
<p>registry.redhat.io/codeready-workspaces/plugin-java8-openj9-rhel8@sha256:f3dd1d9b76591a9aaeb34c609150db0775443d7db2db5593135cf5c8ee8729f8</p>	<p>plugin-java8-openj9-rhel8@sha256:f3dd1d9b76591a9aaeb34c609150db0775443d7db2db5593135cf5c8ee8729f8</p>
<p>registry.redhat.io/codeready-workspaces/plugin-java8-rhel8@sha256:1f5ac84a66454ab4b7b31cb259d30d1a5675dd5a342c9c7dfc536846c8d9a9b1</p>	<p>plugin-java8-rhel8@sha256:1f5ac84a66454ab4b7b31cb259d30d1a5675dd5a342c9c7dfc536846c8d9a9b1</p>

<source-image>	<target-image>
registry.redhat.io/codeready-workspaces/plugin-kubernetes-rhel8@sha256:82e5e4cc40a458b4ea3d7e070945532cbf6a2f3ae966a68b50fe4cd74348c283	plugin-kubernetes-rhel8@sha256:82e5e4cc40a458b4ea3d7e070945532cbf6a2f3ae966a68b50fe4cd74348c283
registry.redhat.io/codeready-workspaces/plugin-openshift-rhel8@sha256:00aeb2293b02a8875ca996b3b02cf7ece516fe5c254ce83ade8fa3648afb6a56	plugin-openshift-rhel8@sha256:00aeb2293b02a8875ca996b3b02cf7ece516fe5c254ce83ade8fa3648afb6a56
registry.redhat.io/codeready-workspaces/pluginbroker-artifacts-rhel8@sha256:0e6b054323fd8cfca3171fa5aaa25f48b1d4ebd098ca63e71d7f0a379e2a51a1	pluginbroker-artifacts-rhel8@sha256:0e6b054323fd8cfca3171fa5aaa25f48b1d4ebd098ca63e71d7f0a379e2a51a1
registry.redhat.io/codeready-workspaces/pluginbroker-metadata-rhel8@sha256:ca8ba32dd8c789cf4a384bf4bf1c63d845b370b7b1249dbbc0b7ebd1aab6437d	pluginbroker-metadata-rhel8@sha256:ca8ba32dd8c789cf4a384bf4bf1c63d845b370b7b1249dbbc0b7ebd1aab6437d
registry.redhat.io/codeready-workspaces/pluginregistry-rhel8@sha256:51f0aaf0f0967b7a986e8690b50a552a06a349cd2c24bfbfa1dbf6d7fb81f6e5	pluginregistry-rhel8@sha256:51f0aaf0f0967b7a986e8690b50a552a06a349cd2c24bfbfa1dbf6d7fb81f6e5
registry.redhat.io/codeready-workspaces/server-rhel8@sha256:591f23a2db6e6ced7bad91e33d2492bf796d8bad2f545dc17c79d23a39657b28	server-rhel8@sha256:591f23a2db6e6ced7bad91e33d2492bf796d8bad2f545dc17c79d23a39657b28
registry.redhat.io/codeready-workspaces/stacks-cpp-rhel8@sha256:4bd93c6fbd77acf07f2206fe76d9e8589f453aa219302c9b4ad0e80ca6180dce	stacks-cpp-rhel8@sha256:4bd93c6fbd77acf07f2206fe76d9e8589f453aa219302c9b4ad0e80ca6180dce
registry.redhat.io/codeready-workspaces/stacks-dotnet-rhel8@sha256:581d3da4bf1fe4467d688cd4390e958dc15f07b530845298c3fbc18bfdc033a	stacks-dotnet-rhel8@sha256:581d3da4bf1fe4467d688cd4390e958dc15f07b530845298c3fbc18bfdc033a

<source-image>	<target-image>
<p>registry.redhat.io/codeready-workspaces/stacks-golang-rhel8@sha256:a4c848642e5cbd2e503915932c27342c94904763caa9085a866cb39c7e443335</p>	<p>stacks-golang-rhel8@sha256:a4c848642e5cbd2e503915932c27342c94904763caa9085a866cb39c7e443335</p>
<p>registry.redhat.io/codeready-workspaces/stacks-php-rhel8@sha256:a3fc9a39225136f735660830787fdb84531db4481665a26e5be21e4534b6bac0</p>	<p>stacks-php-rhel8@sha256:a3fc9a39225136f735660830787fdb84531db4481665a26e5be21e4534b6bac0</p>
<p>registry.redhat.io/codeready-workspaces/theia-endpoint-rhel8@sha256:e19ab58d0bb1b4f39ff3f66edd2138fed76b8feae5db78acee0e364936a73827</p>	<p>theia-endpoint-rhel8@sha256:e19ab58d0bb1b4f39ff3f66edd2138fed76b8feae5db78acee0e364936a73827</p>
<p>registry.redhat.io/codeready-workspaces/theia-rhel8@sha256:1e77ab29f9a72ce94ae40670499c3823048cfdb4fe7de0707adeffd7274f78c9</p>	<p>theia-rhel8@sha256:1e77ab29f9a72ce94ae40670499c3823048cfdb4fe7de0707adeffd7274f78c9</p>
<p>registry.redhat.io/codeready-workspaces/traefik-rhel8@sha256:983abe532ec2d8741d326dd3cd2a4678ba82a3d4e71d77f02bf39d92a8ba3303</p>	<p>traefik-rhel8@sha256:983abe532ec2d8741d326dd3cd2a4678ba82a3d4e71d77f02bf39d92a8ba3303</p>
<p>registry.redhat.io/jboss-eap-7/eap-xp2-openj9-11-openshift-rhel8@sha256:3f2de8176fb0b0e996fb1051d4244b4720014e0767b60e4b815ef0f7ec33dec9</p>	<p>eap-xp2-openj9-11-openshift-rhel8@sha256:3f2de8176fb0b0e996fb1051d4244b4720014e0767b60e4b815ef0f7ec33dec9</p>
<p>registry.redhat.io/jboss-eap-7/eap-xp2-openjdk11-openshift-rhel8@sha256:647d092383a760edc083eafb2d7bc3208d6409097281bedbd5eaccde360e7e39</p>	<p>eap-xp2-openjdk11-openshift-rhel8@sha256:647d092383a760edc083eafb2d7bc3208d6409097281bedbd5eaccde360e7e39</p>
<p>registry.redhat.io/jboss-eap-7/eap73-openjdk8-openshift-rhel7@sha256:d16cfe30eaf20a157cd5d5980a6c34f3fcbcf2fd225e670a0138d81007dd919</p>	<p>eap73-openjdk8-openshift-rhel7@sha256:d16cfe30eaf20a157cd5d5980a6c34f3fcbcf2fd225e670a0138d81007dd919</p>

<code>&lt;source-image&gt;</code>	<code>&lt;target-image&gt;</code>
<code>registry.redhat.io/rh-ss0-7/ss074-0penj9-0penshift-rhel8@sha256:eb5110c22109412b5101f95d353603c7e3080844ee48f89186f139be5b5faa42</code>	<code>ss074-0penj9-0penshift-rhel8@sha256:eb5110c22109412b5101f95d353603c7e3080844ee48f89186f139be5b5faa42</code>
<code>registry.redhat.io/rh-ss0-7/ss074-0penshift-rhel8@sha256:05f97328bafa615ceca025a6a93051a1ecdc08ae6123a78bf6ce56096f2ad233</code>	<code>ss074-0penshift-rhel8@sha256:05f97328bafa615ceca025a6a93051a1ecdc08ae6123a78bf6ce56096f2ad233</code>
<code>registry.redhat.io/rhel8/postgresql-96@sha256:33643fb4cafffacb277982c6098b561aa80c06210e77d2badebef405ee953e43</code>	<code>postgresql-96@sha256:33643fb4cafffacb277982c6098b561aa80c06210e77d2badebef405ee953e43</code>
<code>registry.redhat.io/rhsc1/mongodb-36-rhel7@sha256:9f799d356d7d2e442bde9d401b720600fd9059a3d8eefea6f3b2ffa721c0dc73</code>	<code>mongodb-36-rhel7@sha256:9f799d356d7d2e442bde9d401b720600fd9059a3d8eefea6f3b2ffa721c0dc73</code>
<code>registry.redhat.io/ubi8/ubi-minimal@sha256:d9b92ea78e76300968f5c9a4a04c2cf220a0bbfac667f77e5e7287692163d898</code>	<code>ubi8ubi-minimal@sha256:d9b92ea78e76300968f5c9a4a04c2cf220a0bbfac667f77e5e7287692163d898</code>

### Verification steps

- Verify the images have the same digests:

```
$ skopeo inspect docker://<source-image>
$ skopeo inspect docker://<target-registry>/<target-organization>/<target-image>
```

### Additional resources

- To find the sources of the images list, see the values of the **relatedImages** attribute in the link:
  - [CodeReady Workspaces Operator ClusterServiceVersion sources](#).

### 3.4.2.2. Preparing CodeReady Workspaces Custom Resource for restricted environment

When installing CodeReady Workspaces in a restricted environment using **crwctl** or OperatorHub, provide a **CheCluster** custom resource with additional information.

#### 3.4.2.2.1. Downloading the defaultCheCluster Custom Resource

##### Procedure

1. Download [the default custom resource YAML file](#).

2. Name the downloaded custom resource **org\_v1\_che\_cr.yaml**. Keep it for further modification and usage.

#### 3.4.2.2.2. Customizing the **CheCluster** Custom Resource for restricted environment

##### Prerequisites

- All required images available in an image registry that is visible to the OpenShift cluster where CodeReady Workspaces is to be deployed. This is described in [Section 3.4.2.1, “Preparing an private registry”](#), where the placeholders used in the following examples are also defined.

##### Procedure

1. In the **CheCluster** Custom Resource, which is managed by the CodeReady Workspaces Operator, add the fields used to facilitate deploying an instance of CodeReady Workspaces in a restricted environment:

```
# [...]
spec:
  server:
    airGapContainerRegistryHostname: '<target-registry>'
    airGapContainerRegistryOrganization: '<target-organization>'
# [...]
```

#### 3.4.2.3. Starting CodeReady Workspaces installation in a restricted environment using CodeReady Workspaces CLI management tool

This sections describes how to start the CodeReady Workspaces installation in a restricted environment using the CodeReady Workspaces CLI management tool.

##### Prerequisites

- CodeReady Workspaces CLI management tool is installed. See [Section 3.3.1, “Installing the crwctl CLI management tool”](#).
- The **oc** tool is installed.
- Access to an OpenShift instance.


##### Procedure

1. Log in to OpenShift Container Platform:

```
$ oc login ${OPENSIFT_API_URL} --username ${OPENSIFT_USERNAME} \
           --password ${OPENSIFT_PASSWORD}
```

2. Install CodeReady Workspaces with a customized Custom Resource to add fields related to the restricted environment:

```
$ crwctl server:start \
  --che-operator-image=<target-registry>/<target-organization>/crw-2-rhel8-operator:2.10 \
  --che-operator-cr-yaml=org_v1_che_cr.yaml
```

**NOTE**

For slow systems or internet connections, add the `--k8spodwaittimeout=1800000` flag option to the `crwctl server:start` command to extend the Pod timeout period to 1800000 ms or longer.

### 3.4.3. Preparing CodeReady Workspaces Custom Resource for installing behind a proxy

This procedure describes how to provide necessary additional information to the **CheCluster** custom resource when installing CodeReady Workspaces behind a proxy.

#### Procedure

1. In the **CheCluster** Custom Resource, which is managed by the CodeReady Workspaces Operator, add the fields used to facilitate deploying an instance of CodeReady Workspaces in a restricted environment:

```
# [...]
spec:
  server:
    proxyURL: '<URL of the proxy, with the http protocol, and without the port>'
    proxyPort: '<Port of proxy, typically 3128>'
# [...]
```

2. In addition to those basic settings, the proxy configuration usually requires adding the host of the external OpenShift cluster API URL in the list of the hosts to be accessed from CodeReady Workspaces without using the proxy.

To retrieve this cluster API host, run the following command against the OpenShift cluster:

```
$ oc whoami --show-server | sed 's#https://##' | sed 's#:.*$##'
```

The corresponding field of the **CheCluster** Custom Resource is **nonProxyHosts**. If a host already exists in this field, use `|` as a delimiter to add the cluster API host:

```
# [...]
spec:
  server:
    nonProxyHosts: 'anotherExistingHost|<cluster api host>'
# [...]
```

## CHAPTER 4. CONFIGURING CODEREADY WORKSPACES

The following chapter describes configuration methods and options for Red Hat CodeReady Workspaces, with some user stories as example.

- [Section 4.1, “Advanced configuration options for the CodeReady Workspaces server component”](#) describes advanced configuration methods to use when the previous method is not applicable.

The next sections describe some specific user stories.

- [Section 4.2, “Configuring workspace target project”](#)
- [Section 4.6, “Configuring the number of workspaces that a user can create”](#)
- [Section 4.5, “Configuring the number of workspaces that a user can run”](#)
- [Section 4.8, “Configuring workspaces nodeSelector”](#)
- [Section 4.9, “Configuring Red Hat CodeReady Workspaces server hostname”](#)
- [Section 4.10, “Configuring OpenShift Route”](#)
- [Section 4.11, “Configuring OpenShift Route to work with Router Sharding”](#)
- [Section 4.12, “Deploying CodeReady Workspaces with support for Git repositories with self-signed certificates”](#)
- [Section 4.13, “Installing CodeReady Workspaces using storage classes”](#)
- [Section 4.4, “Configuring storage types”](#)
- [Section 4.14, “Importing untrusted TLS certificates to CodeReady Workspaces”](#)
- [Section 4.15, “Switching between external and internal DNS names in inter-component communication”](#)
- [Section 4.16, “Setting up the RH-SSO codeready-workspaces-username-readonly theme for the Red Hat CodeReady Workspaces login page”](#)
- [Section 4.17, “Mounting a secret as a file or an environment variable into a Red Hat CodeReady Workspaces container”](#)
- [Section 4.18, “Enabling Dev Workspace engine”](#)

### 4.1. ADVANCED CONFIGURATION OPTIONS FOR THE CODEREADY WORKSPACES SERVER COMPONENT

The following section describes advanced deployment and configuration methods for the CodeReady Workspaces server component.

#### 4.1.1. Understanding CodeReady Workspaces server advanced configuration using the Operator

The following section describes the CodeReady Workspaces server component advanced configuration method for a deployment using the Operator.

Advanced configuration is necessary to:

- Add environment variables not automatically generated by the Operator from the standard **CheCluster** Custom Resource fields.
- Override the properties automatically generated by the Operator from the standard **CheCluster** Custom Resource fields.

The **customCheProperties** field, part of the **CheCluster** Custom Resource **server** settings, contains a map of additional environment variables to apply to the CodeReady Workspaces server component.

#### Example 4.1. Override the default memory limit for workspaces

Add the **CHE\_WORKSPACE\_DEFAULT\_\_MEMORY\_\_LIMIT\_\_MB** property to **customCheProperties**:

```
apiVersion: org.eclipse.che/v1
kind: CheCluster
# [...]
spec:
  server:
    # [...]
    customCheProperties:
      CHE_WORKSPACE_DEFAULT__MEMORY__LIMIT__MB: "2048"
    # [...]
```



#### NOTE

Previous versions of the CodeReady Workspaces Operator had a ConfigMap named **custom** to fulfill this role. If the CodeReady Workspaces Operator finds a **configMap** with the name **custom**, it adds the data it contains into the **customCheProperties** field, redeploys CodeReady Workspaces, and deletes the **custom configMap**.

#### Additional resources

- For the list of all parameters available in the **CheCluster** Custom Resource, see [Chapter 2, Configuring the CodeReady Workspaces installation](#).
- For the list of all parameters available to configure **customCheProperties**, see [Section 4.1.2, "CodeReady Workspaces server component system properties reference"](#).

### 4.1.2. CodeReady Workspaces server component system properties reference

The following document describes all possible configuration properties of the CodeReady Workspaces server component.

#### 4.1.2.1. CodeReady Workspaces server

Table 4.1. CodeReady Workspaces server



Environment Variable Name	Default value	Description
<b>CHE_DATABASE</b>	<b><code>\${che.home}/storage</code></b>	Folder where CodeReady Workspaces stores internal data objects.
<b>CHE_API</b>	<b><code>http://\${CHE_HOST}:\${CHE_PORT}/api</code></b>	API service. Browsers initiate REST communications to CodeReady Workspaces server with this URL.
<b>CHE_API_INTERNAL</b>	<b><code>http://\${CHE_HOST}:\${CHE_PORT}/api</code></b>	API service internal network URL. Back-end services should initiate REST communications to CodeReady Workspaces server with this URL.
<b>CHE_WEBSOCKET_ENDPOINT</b>	<b><code>ws://\${CHE_HOST}:\${CHE_PORT}/api/websocket</code></b>	CodeReady Workspaces WebSocket major endpoint. Provides basic communication endpoint for major WebSocket interactions and messaging.
<b>CHE_WORKSPACE_PROJECTS_STORAGE</b>	<b><code>/projects</code></b>	Your projects are synchronized from the CodeReady Workspaces server into the machine running each workspace. This is the directory in the machine where your projects are placed.
<b>CHE_WORKSPACE_PROJECTS_STORAGE_DEFAULT_SIZE</b>	<b><code>1Gi</code></b>	Used when OpenShift-type components in a devfile request project PVC creation (Applied in case of <b>unique</b> and <b>per workspace</b> PVC strategy. In case of the <b>common</b> PVC strategy, it is rewritten with the value of the <b>che.infra.kubernetes.pvc.quantity</b> property.)
<b>CHE_WORKSPACE_LOGS_ROOT_DIR</b>	<b><code>/workspace_logs</code></b>	Defines the directory inside the machine where all the workspace logs are placed. Provide this value into the machine, for example, as an environment variable. This is to ensure that agent developers can use this directory to back up agent logs.

Environment Variable Name	Default value	Description
<b>CHE_WORKSPACE_HTTP__PROXY</b>		Configures environment variable HTTP_PROXY to a specified value in containers powering workspaces.
<b>CHE_WORKSPACE_HTTPS__PROXY</b>		Configures environment variable HTTPS_PROXY to a specified value in containers powering workspaces.
<b>CHE_WORKSPACE_NO__PROXY</b>		Configures environment variable NO_PROXY to a specified value in containers powering workspaces.
<b>CHE_WORKSPACE_AUTO__START</b>	<b>true</b>	By default, when users access a workspace with its URL, the workspace automatically starts (if currently stopped). Set this to <b>false</b> to disable this behavior.
<b>CHE_WORKSPACE_POOL_TTYPE</b>	<b>fixed</b>	Workspace threads pool configuration. This pool is used for workspace-related operations that require asynchronous execution, for example, starting and stopping. Possible values are <b>fixed</b> and <b>cached</b> .
<b>CHE_WORKSPACE_POOL_EXACT_SIZE</b>	<b>30</b>	This property is ignored when pool type is different from <b>fixed</b> . It configures the exact size of the pool. When set, the <b>multiplier</b> property is ignored. If this property is not set ( <b>0, &lt;0, NULL</b> ), then the pool size equals the number of cores. See also <b>che.workspace.pool.cores_multiplier</b> .
<b>CHE_WORKSPACE_POOL_CORES_MULTIPLIER</b>	<b>2</b>	This property is ignored when pool type is not set to <b>fixed</b> , <b>che.workspace.pool.exact_size</b> is set. When set, the pool size is <b>N_CORES * multiplier</b> .
<b>CHE_WORKSPACE_PROBE_POOL_SIZE</b>	<b>10</b>	This property specifies how many threads to use for workspace server liveness probes.

Environment Variable Name	Default value	Description
<b>CHE_WORKSPACE_HTTP_PROXY_JAVA_OPTIONS</b>	<b>NULL</b>	HTTP proxy setting for workspace JVM.
<b>CHE_WORKSPACE_JAVA_OPTIONS</b>	<b>-XX:MaxRAM=150m - XX:MaxRAMFraction=2 - XX:+UseParallelGC - XX:MinHeapFreeRatio=10 - XX:MaxHeapFreeRatio=20 - XX:GCTimeRatio=4 - XX:AdaptiveSizePolicyWeight=90 - Dsun.zip.disableMemoryMapping=true -Xms20m - Djava.security.egd=file:/dev/. /urandom</b>	Java command-line options added to JVMs running in workspaces.
<b>CHE_WORKSPACE_MAVEN_OPTIONS</b>	<b>-XX:MaxRAM=150m - XX:MaxRAMFraction=2 - XX:+UseParallelGC - XX:MinHeapFreeRatio=10 - XX:MaxHeapFreeRatio=20 - XX:GCTimeRatio=4 - XX:AdaptiveSizePolicyWeight=90 - Dsun.zip.disableMemoryMapping=true -Xms20m - Djava.security.egd=file:/dev/. /urandom</b>	Maven command-line options added to JVMs running agents in workspaces.
<b>CHE_WORKSPACE_DEFAULT_MEMORY_LIMIT_MB</b>	<b>1024</b>	RAM limit default for each machine that has no RAM settings in its environment. Value less or equal to 0 is interpreted as disabling the limit.
<b>CHE_WORKSPACE_DEFAULT_MEMORY_REQUEST_MB</b>	<b>200</b>	RAM request for each container that has no explicit RAM settings in its environment. This amount is allocated when the workspace container is created. This property may not be supported by all infrastructure implementations. Currently it is supported by OpenShift. A memory request exceeding the memory limit is ignored, and only the limit size is used. Value less or equal to 0 is interpreted as disabling the limit.

Environment Variable Name	Default value	Description
<b>CHE_WORKSPACE_DEFAULT_CPU_LIMIT_CORES</b>	<b>-1</b>	CPU limit for each container that has no CPU settings in its environment. Specify either in floating point cores number, for example, <b>0.125</b> , or using the OpenShift format, integer millicores, for example, <b>125m</b> . Value less or equal to 0 is interpreted as disabling the limit.
<b>CHE_WORKSPACE_DEFAULT_CPU_REQUEST_CORES</b>	<b>-1</b>	CPU request for each container that has no CPU settings in environment. A CPU request exceeding the CPU limit is ignored, and only limit number is used. Value less or equal to 0 is interpreted as disabling the limit.
<b>CHE_WORKSPACE_SIDECAR_DEFAULT_MEMORY_LIMIT_MB</b>	<b>128</b>	RAM limit for each sidecar that has no RAM settings in the CodeReady Workspaces plug-in configuration. Value less or equal to 0 is interpreted as disabling the limit.
<b>CHE_WORKSPACE_SIDECAR_DEFAULT_MEMORY_REQUEST_MB</b>	<b>64</b>	RAM request for each sidecar that has no RAM settings in the CodeReady Workspaces plug-in configuration.
<b>CHE_WORKSPACE_SIDECAR_DEFAULT_CPU_LIMIT_CORES</b>	<b>-1</b>	CPU limit default for each sidecar that has no CPU settings in the CodeReady Workspaces plug-in configuration. Specify either in floating point cores number, for example, <b>0.125</b> , or using the OpenShift format, integer millicores, for example, <b>125m</b> . Value less or equal to 0 is interpreted as disabling the limit.
<b>CHE_WORKSPACE_SIDECAR_DEFAULT_CPU_REQUEST_CORES</b>	<b>-1</b>	CPU request default for each sidecar that has no CPU settings in the CodeReady Workspaces plug-in configuration. Specify either in floating point cores number, for example, <b>0.125</b> , or using the OpenShift format, integer millicores, for example, <b>125m</b> .

Environment Variable Name	Default value	Description
<b>CHE_WORKSPACE_SIDECA R_IMAGE_PULL_POLICY</b>	<b>Always</b>	Defines image-pulling strategy for sidecars. Possible values are: <b>Always, Never, IfNotPresent</b> . For any other value, <b>Always</b> is assumed for images with the <b>:latest</b> tag, or <b>IfNotPresent</b> for all other cases.
<b>CHE_WORKSPACE_ACTIVIT Y_CHECK_SCHEDULER_ PERIOD__S</b>	<b>60</b>	Period of inactive workspaces suspend job execution.
<b>CHE_WORKSPACE_ACTIVIT Y_CLEANUP_SCHEDULER __PERIOD__S</b>	<b>3600</b>	The period of the cleanup of the activity table. The activity table can contain invalid or stale data if some unforeseen errors happen, as a server failure at a peculiar point in time. The default is to run the cleanup job every hour.
<b>CHE_WORKSPACE_ACTIVIT Y_CLEANUP_SCHEDULER __INITIAL_DELAY__S</b>	<b>60</b>	The delay after server startup to start the first activity clean up job.
<b>CHE_WORKSPACE_ACTIVIT Y_CHECK_SCHEDULER_ DELAY__S</b>	<b>180</b>	Delay before first workspace idleness check job started to avoid mass suspend if CodeReady Workspaces server was unavailable for period close to inactivity timeout.
<b>CHE_WORKSPACE_CLEANU P_TEMPORARY_INITIAL_ DELAY__MIN</b>	<b>5</b>	Time to delay the first execution of temporary workspaces cleanup job.
<b>CHE_WORKSPACE_CLEANU P_TEMPORARY_PERIOD_ __MIN</b>	<b>180</b>	Time to delay between the termination of one execution and the commencement of the next execution of temporary workspaces cleanup job
<b>CHE_WORKSPACE_SERVER _PING_SUCCESS_THRES HOLD</b>	<b>1</b>	Number of sequential successful pings to server after which it is treated as available. the CodeReady Workspaces Operator: the property is common for all servers, for example, workspace agent, terminal, exec.

Environment Variable Name	Default value	Description
<b>CHE_WORKSPACE_SERVER_PING_INTERVAL_MILLISECONDS</b>	<b>3000</b>	Interval, in milliseconds, between successive pings to workspace server.
<b>CHE_WORKSPACE_SERVER_LIVENESS_PROBES</b>	<b>wsagent/http,exec-agent/http,terminal,theia,jupyter,dirigible,cloud-shell,intellij</b>	List of servers names which require liveness probes
<b>CHE_WORKSPACE_STARTUP_DEBUG_LOG_LIMIT_BYTES</b>	<b>10485760</b>	Limit size of the logs collected from single container that can be observed by che-server when debugging workspace startup. default 10MB=10485760
<b>CHE_WORKSPACE_STOP_ROLE_ENABLED</b>	<b>true</b>	If true, 'stop-workspace' role with the edit privileges will be granted to the 'che' ServiceAccount if OpenShift OAuth is enabled. This configuration is mainly required for workspace idling when the OpenShift OAuth is enabled.
<b>CHE_DEVWORKSPACES_ENABLED</b>	<b>false</b>	Specifies whether CodeReady Workspaces is deployed with DevWorkspaces enabled. This property is set by the CodeReady Workspaces Operator if it also installed the support for DevWorkspaces. This property is used to advertise this fact to the CodeReady Workspaces dashboard. It does not make sense to change the value of this property manually.

#### 4.1.2.2. Authentication parameters

Table 4.2. Authentication parameters

Environment Variable Name	Default value	Description
<b>CHE_AUTH_USER_SELF_CREATION</b>	<b>false</b>	CodeReady Workspaces has a single identity implementation, so this does not change the user experience. If true, enables user creation at API level

Environment Variable Name	Default value	Description
<b>CHE_AUTH_ACCESS_DENIED_ERROR_PAGE</b>	<b>/error-oauth</b>	Authentication error page address
<b>CHE_AUTH_RESERVED_USER_NAMES</b>		Reserved user names
<b>CHE_OAUTH_GITHUB_CLIENTID</b>	<b>NULL</b>	Configuration of GitHub OAuth client. You can setup GitHub OAuth to automate authentication to remote repositories. You need to first register this application with GitHub OAuth. GitHub OAuth client ID.
<b>CHE_OAUTH_GITHUB_CLIENTSECRET</b>	<b>NULL</b>	GitHub OAuth client secret.
<b>CHE_OAUTH_GITHUB_AUTH_URI</b>	<b>https://github.com/login/oauth/authorize</b>	GitHub OAuth authorization URI.
<b>CHE_OAUTH_GITHUB_TOKEN_URI</b>	<b>https://github.com/login/oauth/access_token</b>	GitHub OAuth token URI.
<b>CHE_OAUTH_GITHUB_REDIRECTURIS</b>	<b>http://localhost:\${CHE_PORT}/api/oauth/callback</b>	GitHub OAuth redirect URIs. Separate multiple values with comma, for example: URI,URI,URI
<b>CHE_OAUTH_OPENSHIFT_CLIENTID</b>	<b>NULL</b>	Configuration of OpenShift OAuth client. Used to obtain OpenShift OAuth token. OpenShift OAuth client ID.
<b>CHE_OAUTH_OPENSHIFT_CLIENTSECRET</b>	<b>NULL</b>	Configuration of OpenShift OAuth client. Used to obtain OpenShift OAuth token. OpenShift OAuth client ID. OpenShift OAuth client secret.
<b>CHE_OAUTH_OPENSHIFT_OAUTH_ENDPOINT</b>	<b>NULL</b>	Configuration of OpenShift OAuth client. Used to obtain OpenShift OAuth token. OpenShift OAuth client ID. OpenShift OAuth client secret. OpenShift OAuth endpoint.

Environment Variable Name	Default value	Description
<b>CHE_OAUTH_OPENSIFT_VERIFY_TOKEN_URL</b>	<b>NULL</b>	Configuration of OpenShift OAuth client. Used to obtain OpenShift OAuth token. OpenShift OAuth client ID. OpenShift OAuth client secret. OpenShift OAuth endpoint. OpenShift OAuth verification token URL.
<b>CHE_OAUTH1_BITBUCKET_CONSUMERKEYPATH</b>	<b>NULL</b>	Configuration of Bitbucket Server OAuth1 client. Used to obtain Personal access tokens. Location of the file with Bitbucket Server application consumer key (equivalent to a username).
<b>CHE_OAUTH1_BITBUCKET_PRIVATEKEYPATH</b>	<b>NULL</b>	Configuration of Bitbucket Server OAuth1 client. Used to obtain Personal access tokens. Location of the file with Bitbucket Server application consumer key (equivalent to a username). Location of the file with Bitbucket Server application private key
<b>CHE_OAUTH1_BITBUCKET_ENDPOINT</b>	<b>NULL</b>	Configuration of Bitbucket Server OAuth1 client. Used to obtain Personal access tokens. Location of the file with Bitbucket Server application consumer key (equivalent to a username). Location of the file with Bitbucket Server application private key Bitbucket Server URL. To work correctly with factories the same URL has to be part of <b>che.integration.bitbucket.server_endpoints</b> too.

#### 4.1.2.3. Internal

Table 4.3. Internal

Environment Variable Name	Default value	Description
---------------------------	---------------	-------------



Environment Variable Name	Default value	Description
<b>SCHEDULE_CORE__POOL__SIZE</b>	<b>10</b>	CodeReady Workspaces extensions can be scheduled executions on a time basis. This configures the size of the thread pool allocated to extensions that are launched on a recurring schedule.
<b>DB_SCHEMA_FLYWAY_BASELINE_ENABLED</b>	<b>true</b>	DB initialization and migration configuration. If true, ignore scripts up to the version configured by <code>baseline.version</code> .
<b>DB_SCHEMA_FLYWAY_BASELINE_VERSION</b>	<b>5.0.0.8.1</b>	Scripts with version up to this are ignored. Note that scripts with version equal to baseline version are also ignored.
<b>DB_SCHEMA_FLYWAY_SCRIPTS_PREFIX</b>		Prefix of migration scripts.
<b>DB_SCHEMA_FLYWAY_SCRIPTS_SUFFIX</b>	<b>.sql</b>	Suffix of migration scripts.
<b>DB_SCHEMA_FLYWAY_SCRIPTS_VERSION_SEPARATOR</b>	<b>—</b>	Separator of version from the other part of script name.
<b>DB_SCHEMA_FLYWAY_SCRIPTS_LOCATIONS</b>	<b>classpath:che-schema</b>	Locations where to search migration scripts.

#### 4.1.2.4. OpenShift Infra parameters

Table 4.4. OpenShift Infra parameters

Environment Variable Name	Default value	Description
<b>CHE_INFRA_KUBERNETES_MASTER_URL</b>		Configuration of OpenShift client master URL that Infra will use.
<b>CHE_INFRA_KUBERNETES_TRUST_CERTS</b>	<b>false</b>	Boolean to configure OpenShift client to use trusted certificates.
<b>CHE_INFRA_KUBERNETES_CLUSTER_DOMAIN</b>	<b>NULL</b>	OpenShift cluster domain. If not set, svc names will not contain information about the cluster domain.

Environment Variable Name	Default value	Description
<b>CHE_INFRA_KUBERNETES_SERVER_STRATEGY</b>	<b>multi-host</b>	Defines the way how servers are exposed to the world in Kubernetes infra. List of strategies implemented in CodeReady Workspaces: <b>default-host, multi-host, single-host</b> .
<b>CHE_INFRA_KUBERNETES_SINGLEHOST_WORKSPACE_EXPOSURE</b>	<b>native</b>	Defines the way in which the workspace plugins and editors are exposed in the single-host mode. Supported exposures: <b>native</b> :: Exposes servers using OpenShift Routes. Works only on Kubernetes. <b>gateway</b> :: Exposes servers using reverse-proxy gateway.
<b>CHE_INFRA_KUBERNETES_SINGLEHOST_WORKSPACE_DEVFILE_ENDPOINT_EXPOSURE</b>	<b>multi-host</b>	Defines the way how to expose devfile endpoints, as end-user's applications, in single-host server strategy. They can either follow the single-host strategy and be exposed on subpaths, or they can be exposed on subdomains. <b>multi-host</b> :: expose on subdomains <b>single-host</b> :: expose on subpaths
<b>CHE_INFRA_KUBERNETES_SINGLEHOST_GATEWAY_CONFIGMAP_LABELS</b>	<b>app=che,component=che-gateway-config</b>	Defines labels which will be set to ConfigMaps configuring single-host gateway.
<b>CHE_INFRA_KUBERNETES_INGRESS_DOMAIN</b>		Used to generate domain for a server in a workspace in case property <b>che.infra.kubernetes.server_strategy</b> is set to <b>multi-host</b>
<b>CHE_INFRA_KUBERNETES_NAMESPACE_CREATION_ALLOWED</b>	<b>true</b>	Indicates whether CodeReady Workspaces server is allowed to create project for user workspaces, or they're intended to be created manually by cluster administrator. This property is also used by the OpenShift infra.

Environment Variable Name	Default value	Description
<b>CHE_INFRA_KUBERNETES_NAMESPACE_DEFAULT</b>	<b>&lt;username&gt;-che</b>	Defines default OpenShift project in which user's workspaces are created if user does not override it. It's possible to use <b>&lt;username&gt;</b> and <b>&lt;userid&gt;</b> placeholders (for example: <b>che-workspace-&lt;username&gt;</b> ). In that case, new namespace will be created for each user. Used by OpenShift infra as well to specify a Project. The <b>&lt;username&gt;</b> or <b>&lt;userid&gt;</b> placeholder is mandatory.
<b>CHE_INFRA_KUBERNETES_NAMESPACE_LABEL</b>	<b>true</b>	Defines whether che-server should try to label the workspace namespaces.
<b>CHE_INFRA_KUBERNETES_NAMESPACE_LABELS</b>	<b>app.kubernetes.io/part-of=che.eclipse.org,app.kubernetes.io/component=workspaces-namespace</b>	List of labels to find project that are used for CodeReady Workspaces Workspaces. They are used to: - find prepared project for users in combination with <b>che.infra.kubernetes.namespace.annotations</b> . - actively label project with any workspace.
<b>CHE_INFRA_KUBERNETES_NAMESPACE_ANNOTATIONS</b>	<b>che.eclipse.org/username=&lt;username&gt;</b>	List of annotations to find project prepared for CodeReady Workspaces users workspaces. Only project matching the <b>che.infra.kubernetes.namespace.labels</b> will be matched against these annotations. project that matches both <b>che.infra.kubernetes.namespace.labels</b> and <b>che.infra.kubernetes.namespace.annotations</b> will be preferentially used for User's workspaces. It's possible to use <b>&lt;username&gt;</b> placeholder to specify the project to concrete user.

Environment Variable Name	Default value	Description
<b>CHE_INFRA_KUBERNETES_SERVICE_ACCOUNT_NAME</b>	<b>NULL</b>	Defines Kubernetes Service Account name which should be specified to be bound to all workspaces Pods. the CodeReady Workspaces Operator that OpenShift Infrastructure will not create the service account and it should exist. OpenShift infrastructure will check if project is predefined(if <b>che.infra.openshift.project</b> is not empty): - if it is predefined then service account must exist there - if it is 'NULL' or empty string then infrastructure will create new OpenShift project per workspace and prepare workspace service account with needed roles there
<b>CHE_INFRA_KUBERNETES_WORKSPACE_SA_CLUSTER_ROLES</b>	<b>NULL</b>	Specifies optional, additional cluster roles to use with the workspace service account. the CodeReady Workspaces Operator that the cluster role names must already exist, and the CodeReady Workspaces service account needs to be able to create a Role Binding to associate these cluster roles with the workspace service account. The names are comma separated. This property deprecates <b>che.infra.kubernetes.cluster_role_name</b> .
<b>CHE_INFRA_KUBERNETES_WORKSPACE_START_TIMEOUT_MIN</b>	<b>8</b>	Defines wait time that limits the Kubernetes workspace start time.
<b>CHE_INFRA_KUBERNETES_INGRESS_START_TIMEOUT_MIN</b>	<b>5</b>	Defines the timeout in minutes that limits the period for which OpenShift Route become ready

Environment Variable Name	Default value	Description
<b>CHE_INFRA_KUBERNETES_WORKSPACE__UNRECOVERABLE__EVENTS</b>	<b>FailedMount,FailedScheduling,MountVolume.SetUpfailed,Failed to pull image,FailedCreate,ReplicaSetCreateError</b>	If during workspace startup an unrecoverable event defined in the property occurs, stop the workspace immediately rather than waiting until timeout. the CodeReady Workspaces Operator that this SHOULD NOT include a mere 'Failed' reason, because that might catch events that are not unrecoverable. A failed container startup is handled explicitly by CodeReady Workspaces server.
<b>CHE_INFRA_KUBERNETES_PVC_ENABLED</b>	<b>true</b>	Defines whether use the Persistent Volume Claim for CodeReady Workspaces workspace needs, for example: backup projects, logs, or disable it.
<b>CHE_INFRA_KUBERNETES_PVC_STRATEGY</b>	<b>common</b>	Defined which strategy will be used while choosing PVC for workspaces. Supported strategies: <b>common</b> :: All workspaces in the same project will reuse the same PVC. Name of PVC may be configured with <b>che.infra.kubernetes.pvc.name</b> . Existing PVC will be used or a new one will be created if it does not exist. <b>unique</b> :: Separate PVC for each workspace's volume will be used. Name of PVC is evaluated as <b>{che.infra.kubernetes.pvc.name} + '-' + {generated_8_chars}</b> '. Existing PVC will be used or a new one will be created if it does not exist. <b>per-workspace</b> :: Separate PVC for each workspace will be used. Name of PVC is evaluated as <b>{che.infra.kubernetes.pvc.name} + '-' + {WORKSPACE_ID}</b> '. Existing PVC will be used or a new one will be created if it doesn't exist.

Environment Variable Name	Default value	Description
<b>CHE_INFRA_KUBERNETES_PVC_PRECREATE__SUBPATHS</b>	<b>true</b>	Defines whether to run a job that creates workspace's subpath directories in persistent volume for the <b>common</b> strategy before launching a workspace. Necessary in some versions of OpenShift as workspace subpath volume mounts are created with root permissions, and therefore cannot be modified by workspaces running as a user (presents an error importing projects into a workspace in CodeReady Workspaces). The default is <b>true</b> , but should be set to <b>false</b> if the version of OpenShift creates subdirectories with user permissions. See: <a href="#">subPath in volumeMount is not writable for non-root users #41638</a> the CodeReady Workspaces Operator that this property has effect only if the <b>common</b> PVC strategy used.
<b>CHE_INFRA_KUBERNETES_PVC_NAME</b>	<b>claim-che-workspace</b>	Defines the settings of PVC name for CodeReady Workspaces workspaces. Each PVC strategy supplies this value differently. See documentation for <b>che.infra.kubernetes.pvc.strategy</b> property
<b>CHE_INFRA_KUBERNETES_PVC_STORAGE__CLASS__NAME</b>		Defines the storage class of Persistent Volume Claim for the workspaces. Empty strings means 'use default'.
<b>CHE_INFRA_KUBERNETES_PVC_QUANTITY</b>	<b>10Gi</b>	Defines the size of Persistent Volume Claim of CodeReady Workspaces workspace. See: <a href="#">Understanding persistent storage</a>
<b>CHE_INFRA_KUBERNETES_PVC_JOBS_IMAGE</b>	<b>registry.access.redhat.com/ubi8-minimal:8.3-230</b>	Pod that is launched when performing persistent volume claim maintenance jobs on OpenShift
<b>CHE_INFRA_KUBERNETES_PVC_JOBS_IMAGE_PULL__POLICY</b>	<b>IfNotPresent</b>	Image pull policy of container that used for the maintenance jobs on OpenShift cluster

Environment Variable Name	Default value	Description
<b>CHE_INFRA_KUBERNETES_PVC_JOBS_MEMORYLIMIT</b>	<b>250Mi</b>	Defines Pod memory limit for persistent volume claim maintenance jobs
<b>CHE_INFRA_KUBERNETES_PVC_ACCESS_MODE</b>	<b>ReadWriteOnce</b>	Defines Persistent Volume Claim access mode. the CodeReady Workspaces Operator that for common PVC strategy changing of access mode affects the number of simultaneously running workspaces. If the OpenShift instance running CodeReady Workspaces is using Persistent Volumes with RWX access mode, then a limit of running workspaces at the same time is bounded only by CodeReady Workspaces limits configuration: RAM, CPU, and so on. See: <a href="#">Understanding persistent storage</a>
<b>CHE_INFRA_KUBERNETES_PVC_WAIT_BOUND</b>	<b>true</b>	Defines if CodeReady Workspaces Server should wait workspaces Persistent Volume Claims to become bound after creating. Default value is <b>true</b> . The parameter is used by all Persistent Volume Claim strategies. It should be set to <b>false</b> when <b>volumeBindingMode</b> is configured to <b>WaitForFirstConsumer</b> otherwise workspace starts will hangs up on phase of waiting PVCs.
<b>CHE_INFRA_KUBERNETES_INGRESS_ANNOTATIONS_JSON</b>	<b>NULL</b>	Defines annotations for ingresses which are used for servers exposing. Value depends on the kind of ingress controller. OpenShift infrastructure ignores this property because it uses Routes rather than Ingresses. the CodeReady Workspaces Operator that for a single-host deployment strategy to work, a controller supporting URL rewriting has to be used (so that URLs can point to different servers while the servers do not need to support changing the app root). The

Environment Variable Name	Default value	<b>che.infra.kubernetes.ingress.path.rewrite_transform</b> Description
		<p>property defines how the path of the ingress should be transformed to support the URL rewriting and this property defines the set of annotations on the ingress itself that instruct the chosen ingress controller to actually do the URL rewriting, potentially building on the path transformation (if required by the chosen ingress controller). For example for Nginx ingress controller 0.22.0 and later the following value is recommended:</p> <pre><b>{'ingress.kubernetes.io/rewrite-target': '/\$1','ingress.kubernetes.io/ssl-redirect': 'false',\ 'ingress.kubernetes.io/proxy-connect-timeout': '3600','ingress.kubernetes.io/proxy-read-timeout': '3600'}</b></pre> <p>and the <b>che.infra.kubernetes.ingress.path.rewrite_transform</b> should be set to <b>'%s(*)'</b>. For nginx ingress controller older than 0.22.0, the rewrite-target should be set to merely / and the path transform to <b>%s</b> (see the <b>che.infra.kubernetes.ingress.path.rewrite_transform</b> property). See the Nginx ingress controller documentation for the explanation of how the ingress controller uses the regular expression available in the ingress path and how it achieves the URL rewriting.</p>



Environment Variable Name	Default value	Description
<b>CHE_INFRA_KUBERNETES_INGRESS_PATH_TRANSFORM</b>	<b>NULL</b>	Defines a recipe on how to declare the path of the ingress that should expose a server. The <b>%s</b> represents the base public URL of the server and is guaranteed to end with a forward slash. This property must be a valid input to the <b>String.format()</b> method and contain exactly one reference to <b>%s</b> . See the description of the <b>che.infra.kubernetes.ingress.annotations.json</b> property to see how these two properties interplay when specifying the ingress annotations and path. If not defined, this property defaults to <b>%s</b> (without the quotes) which means that the path is not transformed in any way for use with the ingress controller.
<b>CHE_INFRA_KUBERNETES_INGRESS_LABELS</b>	<b>NULL</b>	Additional labels to add into every Ingress created by CodeReady Workspaces server to allow clear identification.
<b>CHE_INFRA_KUBERNETES_POD_SECURITY_CONTEXT_RUN_AS_USER</b>	<b>NULL</b>	Defines security context for Pods that will be created by OpenShift Infra. This is ignored by OpenShift infra.
<b>CHE_INFRA_KUBERNETES_POD_SECURITY_CONTEXT_FS_GROUP</b>	<b>NULL</b>	Defines security context for Pods that will be created by OpenShift Infra. A special supplemental group that applies to all containers in a Pod. This is ignored by OpenShift infra.

Environment Variable Name	Default value	Description
<b>CHE_INFRA_KUBERNETES_POD_TERMINATION_GRACE_PERIOD_SEC</b>	<b>0</b>	Defines grace termination period for Pods that will be created by OpenShift infrastructures. Default value: <b>0</b> . It allows to stop Pods quickly and significantly decrease the time required for stopping a workspace. the CodeReady Workspaces Operator: if <b>terminationGracePeriodSeconds</b> have been explicitly set in OpenShift recipe it will not be overridden.
<b>CHE_INFRA_KUBERNETES_CLIENT_HTTP_ASYNC_REQUESTS_MAX</b>	<b>1000</b>	Number of maximum concurrent asynchronous web requests (HTTP requests or ongoing WebSocket calls) supported in the underlying shared HTTP client of the <b>KubernetesClient</b> instances. Default values: <b>max=64</b> , and <b>max_per_host:5</b> . Default values are not suitable for multi-user scenarios, as CodeReady Workspaces keeps open connections, for example for command or ws-agent logs.
<b>CHE_INFRA_KUBERNETES_CLIENT_HTTP_ASYNC_REQUESTS_MAX_PER_HOST</b>	<b>1000</b>	Number of maximum concurrent asynchronous web requests per host.
<b>CHE_INFRA_KUBERNETES_CLIENT_HTTP_CONNECTION_POOL_MAX_IDLE</b>	<b>5</b>	Max number of idle connections in the connection pool of the Kubernetes-client shared HTTP client.
<b>CHE_INFRA_KUBERNETES_CLIENT_HTTP_CONNECTION_POOL_KEEP_ALIVE_MIN</b>	<b>5</b>	Keep-alive timeout of the connection pool of the Kubernetes-client shared HTTP client in minutes.
<b>CHE_INFRA_KUBERNETES_TLS_ENABLED</b>	<b>false</b>	Creates Ingresses with Transport Layer Security (TLS) enabled. In OpenShift infrastructure, Routes will be TLS-enabled.

Environment Variable Name	Default value	Description
<b>CHE_INFRA_KUBERNETES_TLS__SECRET</b>		Name of a secret that should be used when creating workspace ingresses with TLS. This property is ignored by OpenShift infrastructure.
<b>CHE_INFRA_KUBERNETES_TLS__KEY</b>	<b>NULL</b>	Data for TLS Secret that should be used for workspaces Ingresses. <b>cert</b> and <b>key</b> should be encoded with Base64 algorithm. These properties are ignored by OpenShift infrastructure.
<b>CHE_INFRA_KUBERNETES_TLS__CERT</b>	<b>NULL</b>	Certificate data for TLS Secret that should be used for workspaces Ingresses. Certificate should be encoded with Base64 algorithm. This property is ignored by OpenShift infrastructure.
<b>CHE_INFRA_KUBERNETES_RUNTIMES__CONSISTENCY__CHECK__PERIOD__MIN</b>	<b>-1</b>	Defines the period with which runtimes consistency checks will be performed. If runtime has inconsistent state then runtime will be stopped automatically. Value must be more than 0 or <b>-1</b> , where <b>-1</b> means that checks won't be performed at all. It is disabled by default because there is possible CodeReady Workspaces Server configuration when CodeReady Workspaces Server doesn't have an ability to interact with Kubernetes API when operation is not invoked by user. It DOES work on the following configurations: - workspaces objects are created in the same namespace where CodeReady Workspaces Server is located; - <b>cluster-admin</b> service account token is mounted to CodeReady Workspaces Server Pod. It DOES NOT work on the following configurations: - CodeReady Workspaces Server communicates with Kubernetes API using token from OAuth provider.

Environment Variable Name	Default value	Description
<b>CHE_INFRA_KUBERNETES_TRUSTED__CA_SRC__CONFIGMAP</b>	<b>NULL</b>	Name of the ConfigMap in CodeReady Workspaces server namespace with additional CA TLS certificates to be propagated into all user's workspaces. If the property is set on OpenShift 4 infrastructure, and <b>che.infra.openshift.trusted_ca.dest_configmap_labels</b> includes the <b>config.openshift.io/inject-trusted-cabundle=true</b> label, then cluster CA bundle will be propagated too.
<b>CHE_INFRA_KUBERNETES_TRUSTED__CA_DEST__CONFIGMAP</b>	<b>ca-certs</b>	Name of the ConfigMap in a workspace namespace with additional CA TLS certificates. Holds the copy of <b>che.infra.kubernetes.trusted__ca.src_configmap</b> but in a workspace namespace. Content of this ConfigMap is mounted into all workspace containers including plugin brokers. Do not change the ConfigMap name unless it conflicts with the already existing ConfigMap. the CodeReady Workspaces Operator that the resulting ConfigMap name can be adjusted eventually to make it unique in project. The original name would be stored in <b>che.original_name</b> label.
<b>CHE_INFRA_KUBERNETES_TRUSTED__CA_MOUNT__PATH</b>	<b>/public-certs</b>	Configures path on workspace containers where the CA bundle should be mounted. Content of ConfigMap specified by <b>che.infra.kubernetes.trusted__ca.dest_configmap</b> is mounted.
<b>CHE_INFRA_KUBERNETES_TRUSTED__CA_DEST__CONFIGMAP__LABELS</b>		Comma separated list of labels to add to the CA certificates ConfigMap in user workspace. See the <b>che.infra.kubernetes.trusted__ca.dest_configmap</b> property.

Environment Variable Name	Default value	Description
<b>CHE_INFRA_KUBERNETES_ENABLE__UNSUPPORTED__K8S</b>	<b>false</b>	Enables the <b>/unsupported/OpenShift</b> endpoint to resolve calls on Kubernetes infrastructure. Provides direct access to the underlying infrastructure REST API. This results in huge privilege escalation. It impacts only Kubernetes infrastructure. Therefore it implies no security risk on OpenShift with OAuth. Do not enable this, unless you understand the risks.

#### 4.1.2.5. OpenShift Infra parameters

Table 4.5. OpenShift Infra parameters

Environment Variable Name	Default value	Description
<b>CHE_INFRA_OPENSIFT_TRUSTED__CA_DEST_CONFIGMAP__LABELS</b>	<b>config.openshift.io/inject-trusted-cabundle=true</b>	Comma separated list of labels to add to the CA certificates ConfigMap in user workspace. See <b>che.infra.kubernetes.trusted__ca.dest_configmap</b> property. This default value is used for automatic cluster CA bundle injection in OpenShift 4.
<b>CHE_INFRA_OPENSIFT_ROUTE_LABELS</b>	<b>NULL</b>	Additional labels to add into every Route created by CodeReady Workspaces server to allow clear identification.
<b>CHE_INFRA_OPENSIFT_ROUTE_HOST_DOMAIN_SUFFIX</b>	<b>NULL</b>	The hostname that should be used as a suffix for the workspace routes. For example: Using <b>domain_suffix=&lt;codeready-<i>&lt;openshift_deployment_name&gt;, the route resembles: <b>routed3qrtk.&lt;codeready-<i>&lt;openshift_deployment_name&gt;. It has to be a valid DNS name.</i></b></i></b>

Environment Variable Name	Default value	Description
<b>CHE_INFRA_OPENSHIFT_PROJECT_INIT_WITH_SERVER_SA</b>	<b>true</b>	Initialize OpenShift project with CodeReady Workspaces server's service account if OpenShift OAuth is enabled.

#### 4.1.2.6. Experimental properties

Table 4.6. Experimental properties

Environment Variable Name	Default value	Description
<b>CHE_WORKSPACE_PLUGIN_BROKER_METADATA_IMAGE</b>	<b>quay.io/eclipse/che-plugin-metadata-broker:v3.4.0</b>	Docker image of CodeReady Workspaces plugin broker app that resolves workspace tools configuration and copies plugins dependencies to a workspace. The CodeReady Workspaces Operator overrides these images by default. Changing the images here will not have an effect if CodeReady Workspaces is installed using the Operator.
<b>CHE_WORKSPACE_PLUGIN_BROKER_ARTIFACTS_IMAGE</b>	<b>quay.io/eclipse/che-plugin-artifacts-broker:v3.4.0</b>	Docker image of CodeReady Workspaces plugin artifacts broker. This broker runs as an init container on the workspace Pod. Its job is to take in a list of plugin identifiers (either references to a plugin in the registry or a link to a plugin meta.yaml) and ensure that the correct .vsix and .theia extensions are downloaded into the /plugins directory, for each plugin requested for the workspace.
<b>CHE_WORKSPACE_PLUGIN_BROKER_DEFAULT_MERGE_PLUGINS</b>	<b>false</b>	Configures the default behavior of the plugin brokers when provisioning plugins into a workspace. If set to true, the plugin brokers will attempt to merge plugins when possible: they run in the same sidecar image and do not have conflicting settings. This value is the default setting used when the devfile does not specify the <b>mergePlugins</b> attribute.

Environment Variable Name	Default value	Description
<b>CHE_WORKSPACE_PLUGIN__BROKER_PULL__POLICY</b>	<b>Always</b>	Docker image of CodeReady Workspaces plugin broker app that resolves workspace tools configuration and copies plugins dependencies to a workspace
<b>CHE_WORKSPACE_PLUGIN__BROKER_WAIT__TIMEOUT__MIN</b>	<b>3</b>	Defines the timeout in minutes that limits the max period of result waiting for plugin broker.
<b>CHE_WORKSPACE_PLUGIN__REGISTRY__URL</b>	<b>https://che-plugin-registry.prod-preview.openshift.io/v3</b>	Workspace plug-ins registry endpoint. Should be a valid HTTP URL. Example: http://che-plugin-registry-eclipse-che.192.168.65.2.nip.io In case CodeReady Workspaces plug-ins registry is not needed value 'NULL' should be used
<b>CHE_WORKSPACE_PLUGIN__REGISTRY__INTERNAL__URL</b>	<b>NULL</b>	Workspace plugins registry internal endpoint. Should be a valid HTTP URL. Example: http://devfile-registry.che.svc.cluster.local:8080 In case CodeReady Workspaces plug-ins registry is not needed value 'NULL' should be used
<b>CHE_WORKSPACE_DEVFILE__REGISTRY__URL</b>	<b>https://che-devfile-registry.prod-preview.openshift.io/</b>	Devfile Registry endpoint. Should be a valid HTTP URL. Example: http://che-devfile-registry-eclipse-che.192.168.65.2.nip.io In case CodeReady Workspaces plug-ins registry is not needed value 'NULL' should be used
<b>CHE_WORKSPACE_DEVFILE__REGISTRY__INTERNAL__URL</b>	<b>NULL</b>	Devfile Registry 'internal' endpoint. Should be a valid HTTP URL. Example: http://plugin-registry.che.svc.cluster.local:8080 In case CodeReady Workspaces plug-ins registry is not needed value 'NULL' should be used

Environment Variable Name	Default value	Description
<b>CHE_WORKSPACE_STORAGE_AVAILABLE_TYPES</b>	<b>persistent,ephemeral,async</b>	The configuration property that defines available values for storage types that clients such as the Dashboard should propose to users during workspace creation and update. Available values: - <b>persistent</b> : Persistent Storage slow I/O but persistent. - <b>ephemeral</b> : Ephemeral Storage allows for faster I/O but may have limited storage and is not persistent. - <b>async</b> : Experimental feature: Asynchronous storage is combination of Ephemeral and Persistent storage. Allows for faster I/O and keep your changes, will backup on stop and restore on start workspace. Will work only if: - <b>che.infra.kubernetes.pvc.strategy='common'</b> - <b>che.limits.user.workspaces.run.count=1</b> - <b>che.infra.kubernetes.namespace.default</b> contains <b>&lt;username&gt;</b> in other cases remove <b>async</b> from the list.
<b>CHE_WORKSPACE_STORAGE_PREFERRED_TYPE</b>	<b>persistent</b>	The configuration property that defines a default value for storage type that clients such as the Dashboard should propose to users during workspace creation and update. The <b>async</b> value is an experimental feature, not recommended as default type.
<b>CHE_SERVER_SECURE_EXPOSER</b>	<b>jwtproxy</b>	Configures in which way secure servers will be protected with authentication. Suitable values: - <b>default</b> : <b>jwtproxy</b> is configured in a pass-through mode. Servers should authenticate requests themselves. - <b>jwtproxy</b> : <b>jwtproxy</b> will authenticate requests. Servers will receive only authenticated requests.



Environment Variable Name	Default value	Description
<b>CHE_SERVER_SECURE_EX POSER_JWTPROXY_TOKEN _ISSUER</b>	<b>wsmaster</b>	<b>Jwtproxy</b> issuer string, token lifetime, and optional auth page path to route unsigned requests to.
<b>CHE_SERVER_SECURE_EX POSER_JWTPROXY_TOKEN _TTL</b>	<b>8800h</b>	JWTProxy issuer token lifetime.
<b>CHE_SERVER_SECURE_EX POSER_JWTPROXY_AUTH_ LOADER_PATH</b>	<b>/_app/loader.html</b>	Optional authentication page path to route unsigned requests to.
<b>CHE_SERVER_SECURE_EX POSER_JWTPROXY_IMAGE</b>	<b>quay.io/eclipse/che- jwtproxy:0.10.0</b>	JWTProxy image.
<b>CHE_SERVER_SECURE_EX POSER_JWTPROXY_MEMOR Y_REQUEST</b>	<b>15mb</b>	JWTProxy memory request.
<b>CHE_SERVER_SECURE_EX POSER_JWTPROXY_MEMOR Y_LIMIT</b>	<b>128mb</b>	JWTProxy memory limit.
<b>CHE_SERVER_SECURE_EX POSER_JWTPROXY_CPU_ REQUEST</b>	<b>0.03</b>	JWTProxy CPU request.
<b>CHE_SERVER_SECURE_EX POSER_JWTPROXY_CPU_ LIMIT</b>	<b>0.5</b>	JWTProxy CPU limit.

#### 4.1.2.7. Configuration of the major WebSocket endpoint

Table 4.7. Configuration of the major WebSocket endpoint

Environment Variable Name	Default value	Description
<b>CHE_CORE_JSONRPC_PRO CESSOR_MAX_POOL_SI ZE</b>	<b>50</b>	Maximum size of the JSON RPC processing pool in case if pool size would be exceeded message execution will be rejected

Environment Variable Name	Default value	Description
<b>CHE_CORE_JSONRPC_PROCESSOR_CORE_POOL_SIZE</b>	<b>5</b>	Initial JSON processing pool. Minimum number of threads that used to process major JSON RPC messages.
<b>CHE_CORE_JSONRPC_PROCESSOR_QUEUE_CAPACITY</b>	<b>100000</b>	Configuration of queue used to process JSON RPC messages.
<b>CHE_METRICS_PORT</b>	<b>8087</b>	Port the HTTP server endpoint that would be exposed with Prometheus metrics.

#### 4.1.2.8. CORS settings

Table 4.8. CORS settings

Environment Variable Name	Default value	Description
<b>CHE_CORS_ALLOWED_ORIGINS</b>	<b>*</b>	Indicates which request origins are allowed. CORS filter on WS Master is turned off by default. Use environment variable 'CHE_CORS_ENABLED=true' to turn it on.
<b>CHE_CORS_ALLOW_CREDENTIALS</b>	<b>false</b>	Indicates if it allows processing of requests with credentials (in cookies, headers, TLS client certificates).

#### 4.1.2.9. Factory defaults

Table 4.9. Factory defaults

Environment Variable Name	Default value	Description
---------------------------	---------------	-------------

Environment Variable Name	Default value	Description
<b>CHE_FACTORY_DEFAULT__PLUGINS</b>	<b>redhat/vscode-commons/latest</b>	Editor and plugin which will be used for factories that are created from a remote Git repository which does not contain any CodeReady Workspaces-specific workspace descriptor. Multiple plugins must be comma-separated, for example: <b>pluginFooPublisher/pluginFooName/pluginFooVersion,pluginBarPublisher/pluginBarName/pluginBarVersion</b>
<b>CHE_FACTORY_DEFAULT__DEVFILE__FILENAMES</b>	<b>devfile.yaml,.devfile.yaml</b>	Devfile filenames to look on repository-based factories (for example GitHub). Factory will try to locate those files in the order they enumerated in the property.

#### 4.1.2.10. Devfile defaults

Table 4.10. Devfile defaults

Environment Variable Name	Default value	Description
<b>CHE_FACTORY_DEFAULT__EDITOR</b>	<b>eclipse/che-theia/latest</b>	Editor that will be used for factories that are created from a remote Git repository which does not contain any CodeReady Workspaces-specific workspace descriptor.
<b>CHE_FACTORY_SCM__FILE__FETCHER__LIMIT__BYTES</b>	<b>102400</b>	File size limit for the URL fetcher which fetch files from the SCM repository.
<b>CHE_FACTORY_DEVFILE2__FILES__RESOLUTION__LIST</b>	<b>.che/che-editor.yaml,.che/che-theia-plugins.yaml,vscode/extensions.json</b>	Additional files which may be present in repository to complement devfile v2, and should be referenced as links to SCM resolver service in factory to retrieve them.

Environment Variable Name	Default value	Description
<b>CHE_WORKSPACE_DEVFILE_DEFAULT_EDITOR</b>	<b>eclipse/che-theia/latest</b>	Default Editor that should be provisioned into Devfile if there is no specified Editor Format is <b>editorPublisher/editorName/editorVersion</b> value. <b>NULL</b> or absence of value means that default editor should not be provisioned.
<b>CHE_WORKSPACE_DEVFILE_DEFAULT_EDITOR_PLUGINS</b>	<b>NULL</b>	Default Plug-ins which should be provisioned for Default Editor. All the plugins from this list that are not explicitly mentioned in the user-defined devfile will be provisioned but only when the default editor is used or if the user-defined editor is the same as the default one (even if in different version). Format is comma-separated <b>pluginPublisher/pluginName/pluginVersion</b> values, and URLs. For example: <b>eclipse/che-theia-exec-plugin/0.0.1,eclipse/che-theia-terminal-plugin/0.0.1,https://cdn.pluginregistry.com/vi-mode/meta.yaml</b> If the plugin is a URL, the plugin's <b>meta.yaml</b> is retrieved from that URL.
<b>CHE_WORKSPACE_PROVISION_SECRET_LABELS</b>	<b>app.kubernetes.io/part-of=che.eclipse.org,app.kubernetes.io/component=workspace-secret</b>	Defines comma-separated list of labels for selecting secrets from a user namespace, which will be mount into workspace containers as a files or environment variables. Only secrets that match ALL given labels will be selected.
<b>CHE_WORKSPACE_DEVFILE_ASYNC_STORAGE_PLUGIN</b>	<b>eclipse/che-async-pv-plugin/latest</b>	Plugin is added in case asynchronous storage feature will be enabled in workspace configuration and supported by environment

Environment Variable Name	Default value	Description
<b>CHE_INFRA_KUBERNETES_ASYNC_STORAGE_IMAGE</b>	<b>quay.io/eclipse/che-workspace-data-sync-storage:0.0.1</b>	Docker image for the CodeReady Workspaces asynchronous storage
<b>CHE_WORKSPACE_POD_NODE_SELECTOR</b>	<b>NULL</b>	Optionally configures node selector for workspace Pod. Format is comma-separated key=value pairs, for example: <b>disktype=ssd,cpu=xlarge,foo=bar</b>
<b>CHE_WORKSPACE_POD_TOLERATIONS_JSON</b>	<b>NULL</b>	Optionally configures tolerations for workspace Pod. Format is a string representing a JSON Array of taint tolerations, or <b>NULL</b> to disable it. The objects contained in the array have to follow the <a href="#">toleration v1 core specifications</a> Example: <b>[{'effect':'NoExecute','key':'aNodeTaint','operator':'Equal','value':'aValue'}]</b>
<b>CHE_INFRA_KUBERNETES_ASYNC_STORAGE_SHUTDOWN_TIMEOUT_MIN</b>	<b>120</b>	The timeout for the Asynchronous Storage Pod shutdown after stopping the last used workspace. Value less or equal to 0 interpreted as disabling shutdown ability.
<b>CHE_INFRA_KUBERNETES_ASYNC_STORAGE_SHUTDOWN_CHECK_PERIOD_MIN</b>	<b>30</b>	Defines the period with which the Asynchronous Storage Pod stopping ability will be performed (once in 30 minutes by default)
<b>CHE_INTEGRATION_BITBUCKET_SERVER_ENDPOINTS</b>	<b>NULL</b>	Bitbucket endpoints used for factory integrations. Comma separated list of Bitbucket server URLs or NULL if no integration expected.
<b>CHE_INTEGRATION_GITLAB_SERVER_ENDPOINTS</b>	<b>NULL#</b>	GitLab endpoints used for factory integrations. Comma separated list of GitLab server URLs or NULL if no integration expected. Address of the server with expected OAuth 2 integration <b>MUST</b> be the first in the list.

### 4.1.2.11. Che system

Table 4.11. Che system

Environment Variable Name	Default value	Description
<b>CHE_SYSTEM_SUPER_PRIVILEGED_MODE</b>	<b>false</b>	System Super Privileged Mode. Grants users with the manageSystem permission additional permissions for getByKey, getByNamespace, stopWorkspaces, and getResourcesInformation. These are not given to admins by default and these permissions allow admins gain visibility to any workspace along with naming themselves with administrator privileges to those workspaces.
<b>CHE_SYSTEM_ADMIN_NAME</b>	<b>admin</b>	Grant system permission for <b>che.admin.name</b> user. If the user already exists it'll happen on component startup, if not - during the first login when user is persisted in the database.

### 4.1.2.12. Workspace limits

Table 4.12. Workspace limits

Environment Variable Name	Default value	Description
<b>CHE_LIMITS_WORKSPACE_ENV_RAM</b>	<b>16gb</b>	Workspaces are the fundamental runtime for users when doing development. You can set parameters that limit how workspaces are created and the resources that are consumed. The maximum amount of RAM that a user can allocate to a workspace when they create a new workspace. The RAM slider is adjusted to this maximum value.

Environment Variable Name	Default value	Description
<b>CHE_LIMITS_WORKSPACE_IDLE_TIMEOUT</b>	<b>1800000</b>	The length of time in milliseconds that a user is idle with their workspace when the system will suspend the workspace and then stopping it. Idleness is the length of time that the user has not interacted with the workspace, meaning that one of the agents has not received interaction. Leaving a browser window open counts toward idleness.
<b>CHE_LIMITS_WORKSPACE_RUN_TIMEOUT</b>	<b>0</b>	The length of time in milliseconds that a workspace will run, regardless of activity, before the system will suspend it. Set this property if you want to automatically stop workspaces after a period of time. The default is zero, meaning that there is no run timeout.

#### 4.1.2.13. Users workspace limits

Table 4.13. Users workspace limits

Environment Variable Name	Default value	Description
<b>CHE_LIMITS_USER_WORKSPACES_RAM</b>	<b>-1</b>	The total amount of RAM that a single user is allowed to allocate to running workspaces. A user can allocate this RAM to a single workspace or spread it across multiple workspaces.
<b>CHE_LIMITS_USER_WORKSPACES_COUNT</b>	<b>-1</b>	The maximum number of workspaces that a user is allowed to create. The user will be presented with an error message if they try to create additional workspaces. This applies to the total number of both running and stopped workspaces.

Environment Variable Name	Default value	Description
<b>CHE_LIMITS_USER_WORKSPACES_RUN_COUNT</b>	1	The maximum number of running workspaces that a single user is allowed to have. If the user has reached this threshold and they try to start an additional workspace, they will be prompted with an error message. The user will need to stop a running workspace to activate another.

#### 4.1.2.14. Organizations workspace limits

Table 4.14. Organizations workspace limits

Environment Variable Name	Default value	Description
<b>CHE_LIMITS_ORGANIZATION_WORKSPACES_RAM</b>	-1	The total amount of RAM that a single organization (team) is allowed to allocate to running workspaces. An organization owner can allocate this RAM however they see fit across the team's workspaces.
<b>CHE_LIMITS_ORGANIZATION_WORKSPACES_COUNT</b>	-1	The maximum number of workspaces that a organization is allowed to own. The organization will be presented an error message if they try to create additional workspaces. This applies to the total number of both running and stopped workspaces.
<b>CHE_LIMITS_ORGANIZATION_WORKSPACES_RUN_COUNT</b>	-1	The maximum number of running workspaces that a single organization is allowed. If the organization has reached this threshold and they try to start an additional workspace, they will be prompted with an error message. The organization will need to stop a running workspace to activate another.

#### 4.1.2.15. Multi-user-specific OpenShift infrastructure configuration

Table 4.15. Multi-user-specific OpenShift infrastructure configuration



Environment Variable Name	Default value	Description
<b>CHE_INFRA_OPENSHIFT_OAUTH_IDENTITY_PROVIDER</b>	<b>NULL</b>	Alias of the OpenShift identity provider registered in Keycloak, that should be used to create workspace OpenShift resources in OpenShift namespaces owned by the current CodeReady Workspaces user. Should be set to NULL if <b>che.infra.openshift.project</b> is set to a non-empty value. See: <a href="#">OpenShift identity provider</a>

#### 4.1.2.16. Keycloak configuration

Table 4.16. Keycloak configuration

Environment Variable Name	Default value	Description
<b>CHE_KEYCLOAK_AUTH_SERVER_URL</b>	<b>http://\${CHE_HOST}:5050/auth</b>	Url to keycloak identity provider server Can be set to NULL only if <b>che.keycloak.oidcProvider</b> is used
<b>CHE_KEYCLOAK_AUTH_INTERNAL_SERVER_URL</b>	<b>NULL</b>	Internal network service Url to keycloak identity provider server
<b>CHE_KEYCLOAK_REALM</b>	<b>che</b>	Keycloak realm is used to authenticate users Can be set to NULL only if <b>che.keycloak.oidcProvider</b> is used
<b>CHE_KEYCLOAK_CLIENT_ID</b>	<b>che-public</b>	Keycloak client identifier in <b>che.keycloak.realm</b> to authenticate users in the dashboard, the IDE, and the CLI.
<b>CHE_KEYCLOAK_OSO_ENDPOINT</b>	<b>NULL</b>	URL to access OSO OAuth tokens
<b>CHE_KEYCLOAK_GITHUB_ENDPOINT</b>	<b>NULL</b>	URL to access Github OAuth tokens
<b>CHE_KEYCLOAK_ALLOWED_CLOCK_SKEW_SEC</b>	<b>3</b>	The number of seconds to tolerate for clock skew when verifying <b>exp</b> or <b>nbf</b> claims.

Environment Variable Name	Default value	Description
<b>CHE_KEYCLOAK_USE_NONCE</b>	<b>true</b>	Use the OIDC optional <b>nonce</b> feature to increase security.
<b>CHE_KEYCLOAK_JS_ADAPTER_URL</b>	<b>NULL</b>	URL to the Keycloak Javascript adapter to use. if set to NULL, then the default used value is <b>`\${che.keycloak.auth_server_url}/js/keycloak.js</b> , or <b>&lt;che-server&gt;/api/keycloak/OIDCKeycloak.js</b> if an alternate <b>oidc_provider</b> is used
<b>CHE_KEYCLOAK_OIDC_PROVIDER</b>	<b>NULL</b>	Base URL of an alternate OIDC provider that provides a discovery endpoint as detailed in the following specification <a href="#">Obtaining OpenID Provider Configuration Information</a>
<b>CHE_KEYCLOAK_USE_FIXED_REDIRECT_URLS</b>	<b>false</b>	Set to true when using an alternate OIDC provider that only supports fixed redirect Urls This property is ignored when <b>che.keycloak.oidc_provider</b> is NULL
<b>CHE_KEYCLOAK_USERNAME_CLAIM</b>	<b>NULL</b>	Username claim to be used as user display name when parsing JWT token if not defined the fallback value is 'preferred_username'
<b>CHE_OAUTH_SERVICE_MODE</b>	<b>delegated</b>	Configuration of OAuth Authentication Service that can be used in 'embedded' or 'delegated' mode. If set to 'embedded', then the service work as a wrapper to CodeReady Workspaces's OAuthAuthenticator ( as in Single User mode). If set to 'delegated', then the service will use Keycloak IdentityProvider mechanism. Runtime Exception <b>wii</b> be thrown, in case if this property is not set properly.

Environment Variable Name	Default value	Description
<b>CHE_KEYCLOAK_CASCADE_USER_REMOVAL_ENABLED</b>	<b>false</b>	Configuration for enabling removing user from Keycloak server on removing user from CodeReady Workspaces database. By default it's disabled. Can be enabled in some special cases when deleting a user in CodeReady Workspaces database should execute removing related-user from Keycloak. For correct work need to set administrator username <code>\${che.keycloak.admin_username}</code> and password <code>\${che.keycloak.admin_password}</code> .
<b>CHE_KEYCLOAK_ADMIN_USERNAME</b>	<b>NULL</b>	Keycloak administrator username. Will be used for deleting user from Keycloak on removing user from CodeReady Workspaces database. Make sense only in case <code>\${che.keycloak.cascade_user_removal_enabled}</code> set to 'true'
<b>CHE_KEYCLOAK_ADMIN_PASSWORD</b>	<b>NULL</b>	Keycloak administrator password. Will be used for deleting user from Keycloak on removing user from CodeReady Workspaces database. Make sense only in case <code>\${che.keycloak.cascade_user_removal_enabled}</code> set to 'true'

Environment Variable Name	Default value	Description
<b>CHE_KEYCLOAK_USERNAME_REPLACEMENT_PATTERNS</b>	<b>NULL</b>	User name adjustment configuration. CodeReady Workspaces needs to use the usernames as part of Kubernetes object names and labels and therefore has stricter requirements on their format than the identity providers usually allow (it needs them to be DNS-compliant). The adjustment is represented by comma-separated key-value pairs. These are sequentially used as arguments to the <code>String.replaceAll</code> function on the original username. The keys are regular expressions, values are replacement strings that replace the characters in the username that match the regular expression. The modified username will only be stored in the CodeReady Workspaces database and will not be advertised back to the identity provider. It is recommended to use DNS-compliant characters as replacement strings (values in the key-value pairs). Example: <code>\\=-, @=-at-</code> changes <code>\</code> to <code>-</code> and <code>@</code> to <code>-at-</code> so the username <code>org\user@com</code> becomes <code>org-user-at-com</code> .

#### Additional resources

- [Configuring Che to use an external Keycloak installation](#)

## 4.2. CONFIGURING WORKSPACE TARGET PROJECT

The OpenShift project where a new workspace is deployed depends on the CodeReady Workspaces server configuration. CodeReady Workspaces deploys each workspace into a user's dedicated project, which hosts all CodeReady Workspaces workspaces created by the user. The name of a OpenShift project must be provided as a CodeReady Workspaces server configuration property or pre-created by CodeReady Workspaces administrator.

With **Operator** installer, OpenShift project strategies are configured using **`server.workspaceNamespaceDefault`** property.

#### Operator CheCluster CR patch

```
apiVersion: org.eclipse.che/v1
```

```

kind: CheCluster
metadata:
  name: <che-cluster-name>
spec:
  server:
    workspaceNamespaceDefault: <workspace-namespace> 1

```

- 1 - CodeReady Workspaces workspace project configuration



## NOTE

The underlying environment variable that CodeReady Workspaces server uses is **CHE\_INFRA\_KUBERNETES\_NAMESPACE\_DEFAULT**.



## WARNING

By default, only one workspace in the same project can be running at one time. See [Section 4.5, "Configuring the number of workspaces that a user can run"](#).



## WARNING

Kubernetes limits the length of a project name to 63 characters (this includes the evaluated placeholders). Additionally, the names (after placeholder evaluation) must be valid DNS names.

On OpenShift with multi-host server exposure strategy, the length is further limited to 49 characters.

Be aware that the **<userid>** placeholder is evaluated into a 36 character long UUID string.

**WARNING**

Use [Section 4.2.3, “Pre-creating a project for each user”](#) when:

- **che** ServiceAccount does not have enough permissions when creating new project
- OpenShift OAuth with a **self-provisioner** cluster role is not linked to the **system:authenticated:oauth** group
- CodeReady Workspaces cannot create namespaces

### 4.2.1. One project per user strategy

The strategy isolates each user in their own project.

To use the strategy, set the *CodeReady Workspaces workspace project configuration* value to contain one or more user identifiers. Currently supported identifiers are **<username>** and **<userid>**.

#### Example 4.2. One project per user

To assign project names composed of a `codeready-ws`` prefix and individual usernames (**`codeready-ws-user1`**, **`codeready-ws-user2`**), set:

#### Operator installer (CheCluster CustomResource)

```
...
spec:
  server:
    workspaceNamespaceDefault: codeready-ws-<username>
...
```

### 4.2.2. Handling incompatible usernames or user IDs

CodeReady Workspaces server automatically checks usernames and IDs for compatibility with OpenShift objects naming convention before creating a project from a template. Incompatible usernames or IDs are reduced to the nearest valid name by replacing groups of unsuitable symbols with the `-` symbol. The addition of a random 6-symbol suffix prevents IDs from collisions. The result is stored in preferences for reuse.

### 4.2.3. Pre-creating a project for each user

To pre-create a project for each user, use OpenShift labels and annotations. Such project is used in preference to **CHE\_INFRA\_KUBERNETES\_NAMESPACE\_DEFAULT** variable.

```
metadata:
  labels:
    app.kubernetes.io/part-of: che.eclipse.org
```

```
app.kubernetes.io/component: workspaces-namespace
annotations:
  che.eclipse.org/username: <username> 1
```

**1** target user's username

To configure the labels, set the **CHE\_INFRA\_KUBERNETES\_NAMESPACE\_LABELS** to desired labels. To configure the annotations, set the **CHE\_INFRA\_KUBERNETES\_NAMESPACE\_ANNOTATIONS** to desired annotations. See the [CodeReady Workspaces server component system properties reference](#) for more details.



### WARNING

Do not create multiple namespaces for a single user. It may lead to undefined behavior.

### IMPORTANT

On OpenShift with OAuth, the target user must have **admin** role privileges in the target namespace:

```
apiVersion: rbac.authorization.k8s.io/v1
kind: RoleBinding
metadata:
  name: admin
  namespace: <namespace> 1
roleRef:
  apiGroup: rbac.authorization.k8s.io
  kind: ClusterRole
  name: admin
subjects:
- apiGroup: rbac.authorization.k8s.io
  kind: User
  name: <username> 2
```

**1** pre-created namespace  
**2** target user

On Kubernetes, **che** ServiceAccount must have a cluster-wide **list** and **get namespaces** permissions as well as an **admin** role in target namespace.

#### 4.2.4. Labeling the namespaces

CodeReady Workspaces updates the workspace's project on workspace startup by adding the labels defined in **CHE\_INFRA\_KUBERNETES\_NAMESPACE\_LABELS**. To do so, **che** ServiceAccount has to have the following cluster-wide permissions to **update** and **get namespaces**:

```
apiVersion: rbac.authorization.k8s.io/v1
kind: ClusterRole
```

```

metadata:
  name: <cluster-role-name> ❶
rules:
- apiGroups:
  - ""
  resources:
  - namespaces
  verbs:
  - update
  - get

```

- ❶ name of the cluster role

```

apiVersion: rbac.authorization.k8s.io/v1
kind: ClusterRoleBinding
metadata:
  name: <cluster-role-binding-name> ❶
subjects:
- kind: ServiceAccount
  name: <service-account-name> ❷
  namespace: <service-account-namespace> ❸
roleRef:
  kind: ClusterRole
  name: <cluster-role-name> ❹
  apiGroup: rbac.authorization.k8s.io

```

- ❶ name of the cluster role binding
- ❷ name of the **che** ServiceAccount
- ❸ CodeReady Workspaces installation namespace
- ❹ name of the cluster role created in previous step



#### NOTE

A lack of permissions does not prevent a CodeReady Workspaces workspace from starting, it only logs the warning. If you see the warnings in CodeReady Workspaces logs, consider disabling the feature by defining **CHE\_INFRA\_KUBERNETES\_NAMESPACE\_LABEL=false**.

## 4.3. CONFIGURING STORAGE STRATEGIES

This section describes how to configure storage strategies for CodeReady Workspaces workspaces.

### 4.3.1. Storage strategies for codeready-workspaces workspaces

Workspace Pods use Persistent Volume Claims (PVCs), which are bound to the physical Persistent Volumes (PVs) with [ReadWriteOnce access mode](#). It is possible to configure how the CodeReady Workspaces server uses PVCs for workspaces. The individual methods for this configuration are called PVC strategies:



strategy	details	pros	cons
<b>unique</b>	One PVC per workspace volume or user-defined PVC	Storage isolation	An undefined number of PVs is required
<b>per-workspace (default)</b>	One PVC for one workspace	Easier to manage and control storage compared to unique strategy	PV count still is not known and depends on workspaces number
<b>common</b>	One PVC for all workspaces in one OpenShift namespace	Easy to manage and control storage	<p>If PV does not support ReadWriteMany (RWX) access mode then workspaces must be in a separate OpenShift namespaces</p> <p>Or there must not be more than 1 running workspace per namespace at the same time</p>

CodeReady Workspaces uses the **common** PVC strategy in combination with the "one project per user" project strategy when all CodeReady Workspaces workspaces operate in the user's project, sharing one PVC.

#### 4.3.1.1. The common PVC strategy

All workspaces inside a OpenShift project use the same Persistent Volume Claim (PVC) as the default data storage when storing data such as the following in their declared volumes:


- projects
- workspace logs
- additional Volumes defined by a use

When the **common** PVC strategy is in use, user-defined PVCs are ignored, and volumes related to these user-defined PVCs are replaced with a volume that refers to the common PVC. In this strategy, all CodeReady Workspaces workspaces use the same PVC. When the user runs one workspace, it only binds to one node in the cluster at a time.

The corresponding containers volume mounts link to a common volume, and sub-paths are prefixed with **<workspace-ID>** or **<original-PVC-name>**. For more details, see [Section 4.3.1.4, "How subpaths are used in PVCs"](#).

The CodeReady Workspaces Volume name is identical to the name of the user-defined PVC. It means that if a machine is configured to use a CodeReady Workspaces volume with the same name as the user-defined PVC has, they will use the same shared folder in the common PVC.

When a workspace is deleted, a corresponding subdirectory (**/\${ws-id}**) is deleted in the PV directory.

**NOTE**

The common PVC will be removed when a user's workspaces are all deleted. The PVC will be re-created when a non-ephemeral workspace is started.

**Restrictions on using the common PVC strategy**

When the **common** strategy is used, and a workspace PVC access mode is ReadWriteOnce (RWO), only one node can simultaneously use the PVC.

If there are several nodes, you can use the **common** strategy, but:

- The workspace PVC access mode must be reconfigured to **ReadWriteMany** (RWM), so multiple nodes can use this PVC simultaneously.
- Only one workspace in the same project may be running. See [Section 4.5, "Configuring the number of workspaces that a user can run"](#).

The **common** PVC strategy is not suitable for large multi-node clusters. Therefore, it is best to use it in single-node clusters. However, in combination with the **per-workspace** project strategy, the **common** PVC strategy is usable for clusters with not more than 75 nodes. The PVC used with this strategy must be large enough to accommodate all projects to prevent a situation in which one project depletes the resources of others.

**4.3.1.2. The per-workspace PVC strategy**

The **per-workspace** strategy is similar to the **common** PVC strategy. The only difference is that all workspace Volumes, but not all the workspaces, use the same PVC as the default data storage for:

- projects
- workspace logs
- additional Volumes defined by a user

With this strategy, CodeReady Workspaces keeps its workspace data in assigned PVs that are allocated by a single PVC.

The **per-workspace** PVC strategy is the universal strategy out of the PVC strategies available and acts as a proper option for large multi-node clusters with a higher amount of users. Using the **per-workspace** PVC strategy, users can run multiple workspaces simultaneously, which results in more PVCs being created.

**4.3.1.3. The unique PVC strategy**

Using the `unique` PVC strategy, every CodeReady Workspaces Volume of a workspace has its own PVC. The workspace PVCs are then:

- Created when a workspace starts for the first time.
- Deleted when a corresponding workspace is deleted.

User-defined PVCs are created with the following specifics:

- They are provisioned with generated names to prevent naming conflicts with other PVCs in a project.

- Subpaths of the mounted Physical persistent volumes that reference user-defined PVCs are prefixed with **<workspace-ID>** or **<PVC-name>**. This ensures that the same PV data structure is configured with different PVC strategies. For details, see [Section 4.3.1.4, “How subpaths are used in PVCs”](#).

The **unique** PVC strategy is suitable for larger multi-node clusters with a lesser amount of users. Since this strategy operates with separate PVCs for each volume in a workspace, vastly more PVCs are created.

#### 4.3.1.4. How subpaths are used in PVCs

Subpaths illustrate the folder hierarchy in the Persistent Volumes (PV).

```

/pv0001
  /workspaceID1
  /workspaceID2
  /workspaceIDn
  /che-logs
  /projects
  /<volume1>
  /<volume2>
  /<User-defined PVC name 1 | volume 3>
  ...

```

When a user defines volumes for components in the devfile, all components that define the volume of the same name will be backed by the same directory in the PV as **<PV-name>**, **<workspace-ID>**, or **<original-PVC-name>**. Each component can have this location mounted on a different path in its containers.

#### Example

Using the **common** PVC strategy, user-defined PVCs are replaced with subpaths on the common PVC. When the user references a volume as **my-volume**, it is mounted in the common-pvc with the **/workspace-id/my-volume** subpath.

### 4.3.2. Configuring a CodeReady Workspaces workspace with a persistent volume strategy

A persistent volume (PV) acts as a virtual storage instance that adds a volume to a cluster.

A persistent volume claim (PVC) is a request to provision persistent storage of a specific type and configuration, available in the following CodeReady Workspaces storage configuration strategies:

- Common
- Per-workspace
- Unique

The mounted PVC is displayed as a folder in a container file system.

#### 4.3.2.1. Configuring a PVC strategy using the Operator

The following section describes how to configure workspace persistent volume claim (PVC) strategies of a CodeReady Workspaces server using the Operator.

**WARNING**

It is not recommended to reconfigure PVC strategies on an existing CodeReady Workspaces cluster with existing workspaces. Doing so causes data loss.

**Operators** are software extensions to OpenShift that use **Custom Resources** to manage applications and their components.

When deploying CodeReady Workspaces using the Operator, configure the intended strategy by modifying the **spec.storage.pvcStrategy** property of the CheCluster Custom Resource object YAML file.

**Prerequisites**

- The **oc** tool is available.

**Procedure**

The following procedure steps are available for OpenShift command-line tool, 'oc'.

To do changes to the CheCluster YAML file, choose one of the following:

- Create a new cluster by executing the **oc apply** command. For example:

```
$ oc apply -f <my-cluster.yaml>
```

- Update the YAML file properties of an already running cluster by executing the **oc patch** command. For example:

```
$ oc patch checluster/codeready-workspaces --type=json \
-p '[{"op": "replace", "path": "/spec/storage/pvcStrategy", "value": "per-workspace"}]'
```

Depending on the strategy used, replace the **per-workspace** option in the above example with **unique** or **common**.

## 4.4. CONFIGURING STORAGE TYPES

Red Hat CodeReady Workspaces supports three types of storage with different capabilities:

- Persistent
- Ephemeral
- Asynchronous

### 4.4.1. Persistent storage

Persistent storage allows storing user changes directly in the mounted Persistent Volume. User changes are kept safe by the OpenShift infrastructure (storage backend) at the cost of slow I/O, especially with many small files. For example, Node.js projects tend to have many dependencies and the

`node_modules/` directory is filled with thousands of small files.



#### NOTE

I/O speeds vary depending on the [Storage Classes](#) configured in the environment.

Persistent storage is the default mode for new workspaces. To make this setting visible in workspace configuration, add the following to the devfile:

```
attributes:
  persistVolumes: 'true'
```

### 4.4.2. Ephemeral storage

Ephemeral storage saves files to the `emptyDir` volume. This volume is initially empty. When a Pod is removed from a node, the data in the `emptyDir` volume is deleted forever. This means that all changes are lost on workspace stop or restart.



#### IMPORTANT

To save the changes, commit and push to the remote before stopping an ephemeral workspace.

Ephemeral mode provides faster I/O than persistent storage. To enable this storage type, add the following to workspace configuration:

```
attributes:
  persistVolumes: 'false'
```

Table 4.17. Comparison between I/O of ephemeral (`emptyDir`) and persistent modes on [AWS EBS](#)

Command	Ephemeral	Persistent
Clone Red Hat CodeReady Workspaces	0 m 19 s	1 m 26 s
Generate 1000 random files	1 m 12 s	44 m 53 s

### 4.4.3. Asynchronous storage



#### NOTE


Asynchronous storage is an experimental feature.

Asynchronous storage is a combination of persistent and ephemeral modes. The initial workspace container mounts the `emptyDir` volume. Then a backup is performed on workspace stop, and changes are restored on workspace start. Asynchronous storage provides fast I/O (similar to ephemeral mode), and workspace project changes are persisted.

Synchronization is performed by the `rsync` tool using the [SSH](#) protocol. When a workspace is configured

with asynchronous storage, the `workspace-data-sync` plug-in is automatically added to the workspace configuration. The plug-in runs the `rsync` command on workspace start to restore changes. When a workspace is stopped, it sends changes to the permanent storage.

For relatively small projects, the restore procedure is fast, and project source files are immediately available after Che-Theia is initialized. In case `rsync` takes longer, the synchronization process is shown in the Che-Theia status-bar area. ([Extension in Che-Theia repository](#)).



## NOTE

Asynchronous mode has the following limitations:

- Supports only the *common* PVC strategy
- Supports only the *per-user* project strategy
- Only one workspace can be running at a time

To configure asynchronous storage for a workspace, add the following to workspace configuration:

```
attributes:
  asyncPersist: 'true'
  persistVolumes: 'false'
```

### 4.4.4. Configuring storage type defaults for CodeReady Workspaces dashboard

Use the following two **che.properties** to configure the default client values in CodeReady Workspaces dashboard:

#### **che.workspace.storage.available\_types**

Defines available values for storage types that clients like the dashboard propose for users during workspace creation or update. Available values: **persistent**, **ephemeral**, and **async**. Separate multiple values by commas. For example:

```
che.workspace.storage.available_types=persistent,ephemeral,async
```

#### **che.workspace.storage.preferred\_type**

Defines the default value for storage type that clients like the dashboard propose for users during workspace creation. The **async** value is not recommended as the default type because it is experimental. For example:

```
che.workspace.storage.preferred_type=persistent
```

Then users are able to configure Storage Type on the **Create Custom Workspace** tab on CodeReady Workspaces dashboard during workspace creation. Storage type for existing workspace can be configured in on **Overview** tab of the workspace details.

#### 4.4.5. Idling asynchronous storage Pods

CodeReady Workspaces can shut down the Asynchronous Storage Pod when not used for a configured period of time.

Use these configuration properties to adjust the behavior:

##### **che.infra.kubernetes.async.storage.shutdown\_timeout\_min**

Defines the idle time after which the asynchronous storage Pod is stopped following the stopping of the last active workspace. The default value is 120 minutes.

##### **che.infra.kubernetes.async.storage.shutdown\_check\_period\_min**

Defines the frequency with which the asynchronous storage Pod is checked for idleness. The default value is 30 minutes.

To increase the timeout of a CodeReady Workspaces workspace, use the following example, which sets the workspace timeout for 1800000 milliseconds that correspond to the interval of 30 minutes.

+

```
$ oc patch checluster/codeready-workspaces --patch '{"spec":{"server":{"customCheProperties":{"CHE_LIMITS_WORKSPACE_IDLE_TIMEOUT": "1800000"}}}}' --type=merge -n openshift-workspaces
```

## 4.5. CONFIGURING THE NUMBER OF WORKSPACES THAT A USER CAN RUN

This article describes how to configure the number of workspaces that a user can run simultaneously.

### 4.5.1. Using the Operator to configure the number of workspaces that a user can run

This procedure describes how to configure **CodeReady Workspaces** to run more than one workspace simultaneously. By running multiple workspaces, users can use different work environments simultaneously.

#### Prerequisites

- You have installed an instance of **CodeReady Workspaces** by using the Operator.
- The combination of PVC strategy and access mode meets the following criteria:
  - **ReadWriteMany** access mode and an arbitrary PVC strategy
  - **ReadWriteOnce** access mode and **per-workspace** or **unique** PVC strategy

See [Section 4.3, "Configuring storage strategies"](#).

- You have determined the value of the **<number-of-workspaces>** placeholder.

**NOTE**

If the value is **-1**, an unlimited number of workspaces can run per user. If the value is a positive integer, users can run as many workspaces as the value of the integer. The default value is **1**.

**Procedure**

1. In the **CheCluster** Custom Resource **server** settings, configure the number of workspaces that a user can run by adding the **CHE\_LIMITS\_USER\_WORKSPACES\_RUN\_COUNT** property to **customCheProperties**:

```
apiVersion: org.eclipse.che/v1
kind: CheCluster
# [...]
spec:
  server:
    # [...]
    customCheProperties:
      CHE_LIMITS_USER_WORKSPACES_RUN_COUNT: "<number-of-workspaces>"
```

## 4.6. CONFIGURING THE NUMBER OF WORKSPACES THAT A USER CAN CREATE

This article describes how to configure the number of workspaces that a user can create.

### 4.6.1. Using the Operator to configure the number of workspaces that a user can create

This procedure describes how to configure the number of workspaces that a user can create. By creating multiple workspaces, users can have access to workspaces with different configurations simultaneously.

**Prerequisites**

- You have installed an instance of **CodeReady Workspaces** by using the Operator.
- You have determined the value of the **<number-of-workspaces>** placeholder.

**NOTE**

If the value is **-1**, users can create an unlimited number of workspaces. If the value is a positive integer, users can create as many workspaces as the value of the integer. The default value is **-1**.

**Procedure**

- In the **CheCluster** Custom Resource **server** settings, configure the number of workspaces that a user can create by adding the **CHE\_LIMITS\_USER\_WORKSPACES\_COUNT** property to **customCheProperties**:

```
apiVersion: org.eclipse.che/v1
kind: CheCluster
```



```
# [...]
spec:
  server:
    # [...]
    customCheProperties:
      CHE_LIMITS_USER_WORKSPACES_COUNT: "<number-of-workspaces>"
```

## 4.7. CONFIGURING WORKSPACE EXPOSURE STRATEGIES

The following section describes how to configure workspace exposure strategies of a CodeReady Workspaces server and ensure that applications running inside are not vulnerable to outside attacks.

### 4.7.1. Configuring workspace exposure strategies using an Operator

[Operators](#) are software extensions to OpenShift that use [Custom Resources](#) to manage applications and their components.

#### Prerequisites

- The **oc** tool is available.

#### Procedure

When deploying CodeReady Workspaces using the Operator, configure the intended strategy by modifying the **spec.server.serverExposureStrategy** property of the CheCluster Custom Resource object YAML file.

The supported values for **spec.server.serverExposureStrategy** are:

- **multi-host**
- **single-host**

See [Section 4.7.2, “Workspace exposure strategies”](#) for more detail about individual strategies.

To activate changes done to CheCluster YAML file, do one of the following:

- Create a new cluster by executing the **crwctl** command with applying a patch. For example:

```
$ crwctl server:deploy --installer=operator --platform=<platform> \
  --che-operator-cr-patch-yaml=patch.yaml
```



#### NOTE

For a list of available OpenShift deployment platforms, use **crwctl server:deploy --platform --help**.

- Use the following **patch.yaml** file:

```
apiVersion: org.eclipse.che/v1
kind: CheCluster
metadata:
  name: eclipse-che
```

```
spec:
  server:
    serverExposureStrategy: '<exposure-strategy>' 1
```

1 - used workspace exposure strategy

- Update the YAML file properties of an already running cluster by executing the **oc patch** command. For example:

```
$ oc patch checluster/codeready-workspaces --type=json \
-p '[{"op": "replace",
"path": "/spec/server/serverExposureStrategy",
"value": "<exposure-strategy>"}]' \ 1
-n openshift-workspaces
```

1 - used workspace exposure strategy

## 4.7.2. Workspace exposure strategies

Specific components of workspaces need to be made accessible outside of the OpenShift cluster. This is typically the user interface of the workspace's IDE, but it can also be the web UI of the application being developed. This enables developers to interact with the application during the development process.

The supported way of making workspace components available to the users is referred to as a *strategy*. This strategy defines whether new subdomains are created for the workspace components and what hosts these components are available on.

CodeReady Workspaces supports:

- **multi-host** strategy
- **single-host** strategy
  - with the **gateway** subtype

### 4.7.2.1. Multi-host strategy

With multi-host strategy, each workspace component is assigned a new subdomain of the main domain configured for the CodeReady Workspaces server. This is the default strategy.

This strategy is the easiest to understand from the perspective of component deployment because any paths present in the URL to the component are received as they are by the component.

On a CodeReady Workspaces server secured using the Transport Layer Security (TLS) protocol, creating new subdomains for each component of each workspace requires a wildcard certificate to be available for all such subdomains for the CodeReady Workspaces deployment to be practical.

### 4.7.2.2. Single-host strategy

With single-host strategy, all workspaces are deployed to sub-paths of the main CodeReady Workspaces server domain.

This is convenient for TLS-secured CodeReady Workspaces servers because it is sufficient to have a single certificate for the CodeReady Workspaces server, which will cover all the workspace component deployments as well.

Single-host strategy have two subtypes with different implementation methods. First subtype is named **native**. This strategy is available and default on Kubernetes, but not on OpenShift, since it uses Ingresses for servers exposing. The second subtype named **gateway**, works both on OpenShift, and uses a special Pod with reverse-proxy running inside to route requests.



#### WARNING

With **gateway** single-host strategy, cluster network policies has to be configured so that workspace's services are reachable from reverse-proxy Pod (typically in CodeReady Workspaces project). These typically lives in different project.

To define how to expose the endpoints specified in the devfile, define the **CHE\_INFRA\_KUBERNETES\_SINGLEHOST\_WORKSPACE\_DEVFILE\_ENDPOINT\_EXPOSURE** environment variable in the CodeReady Workspaces instance. This environment variable is only effective with the single-host server strategy and is applicable to all workspaces of all users.

#### 4.7.2.2.1. devfile endpoints: single-host

**CHE\_INFRA\_KUBERNETES\_SINGLEHOST\_WORKSPACE\_DEVFILE\_ENDPOINT\_EXPOSURE: 'single-host'**

This single-host configuration exposes the endpoints on subpaths, for example: **https://<che-host>/serverihzmuqqc/go-cli-server-8080**. This limits the exposed components and user applications. Any absolute URL generated on the server side that points back to the server does not work. This is because the server is hidden behind a path-rewriting reverse proxy that hides the unique URL path prefix from the component or user application.

For example, when the user accesses the hypothetical **https://codeready-<openshift\_deployment\_name>.<domain\_name>/component-prefix-djh3d/app/index.php** URL, the application sees the request coming to **https://internal-host/app/index.php**. If the application used the host in the URL that it generates in its UI, it would not work because the internal host is different from the externally visible host. However, if the application used an absolute path as the URL (for the example above, this would be **/app/index.php**), such URL would still not work. This is because on the outside, such URL does not point to the application, because it is missing the component-specific prefix.

Therefore, only applications that use relative URLs in their UI work with the single-host workspace exposure strategy.

#### 4.7.2.2.2. devfile endpoints: multi-host

**CHE\_INFRA\_KUBERNETES\_SINGLEHOST\_WORKSPACE\_DEVFILE\_ENDPOINT\_EXPOSURE: 'multi-host'**

This single-host configuration exposes the endpoints on subdomains, for example: **http://serverihzmuqqc-go-cli-server-8080.<che-host>**. These endpoints are exposed on an unsecured HTTP port. A dedicated Ingress or Route is used for such endpoints, even with **gateway** single-host setup.

This configuration limits the usability of previews shown directly in the editor page when CodeReady Workspaces is configured with TLS. Since **https** pages allow communication only with secured endpoints, users must open their application previews in another browser tab.

### 4.7.3. Security considerations

This section explains the security impact of using different CodeReady Workspaces workspace exposure strategies.

All the security-related considerations in this section are only applicable to CodeReady Workspaces in multiuser mode. The single user mode does not impose any security restrictions.

#### 4.7.3.1. JSON web token (JWT) proxy

All CodeReady Workspaces plug-ins, editors, and components can require authentication of the user accessing them. This authentication is performed using a JSON web token (JWT) proxy that functions as a reverse proxy of the corresponding component, based on its configuration, and performs the authentication on behalf of the component.

The authentication uses a redirect to a special page on the CodeReady Workspaces server that propagates the workspace and user-specific authentication token (workspace access token) back to the originally requested page.

The JWT proxy accepts the workspace access token from the following places in the incoming requests, in the following order:

1. The token query parameter
2. The Authorization header in the bearer-token format
3. The **access\_token** cookie

#### 4.7.3.2. Secured plug-ins and editors

CodeReady Workspaces users do not need to secure workspace plug-ins and workspace editors (such as Che-Theia). This is because the JWT proxy authentication is indiscernible to the user and is governed by the plug-in or editor definition in their **meta.yaml** descriptors.

#### 4.7.3.3. Secured container-image components

Container-image components can define custom endpoints for which the devfile author can require CodeReady Workspaces-provided authentication, if needed. This authentication is configured using two optional attributes of the endpoint:

- **secure** - A boolean attribute that instructs the CodeReady Workspaces server to put the JWT proxy in front of the endpoint. Such endpoints have to be provided with the workspace access token in one of the several ways explained in [Section 4.7.3.1, "JSON web token \(JWT\) proxy"](#). The default value of the attribute is **false**.
- **cookiesAuthEnabled** - A boolean attribute that instructs the CodeReady Workspaces server to automatically redirect the unauthenticated requests for current user authentication as described in [Section 4.7.3.1, "JSON web token \(JWT\) proxy"](#). Setting this attribute to **true** has security consequences because it makes Cross-site request forgery (CSRF) attacks possible. The default value of the attribute is **false**.

#### 4.7.3.4. Cross-site request forgery attacks

Cookie-based authentication can make an application secured by a JWT proxy prone to Cross-site request forgery (CSRF) attacks. See the [Cross-site request forgery](#) Wikipedia page and other resources to ensure your application is not vulnerable.

#### 4.7.3.5. Phishing attacks

An attacker who is able to create an Ingress or route inside the cluster with the workspace that shares the host with some services behind a JWT proxy, the attacker may be able to create a service and a specially forged Ingress object. When such a service or Ingress is accessed by a legitimate user that was previously authenticated with a workspace, it can lead to the attacker stealing the workspace access token from the cookies sent by the legitimate user's browser to the forged URL. To eliminate this attack vector, configure OpenShift to disallow setting the host of an Ingress.

## 4.8. CONFIGURING WORKSPACES NODESELECTOR

This section describes how to configure **nodeSelector** for Pods of CodeReady Workspaces workspaces.

### Procedure

CodeReady Workspaces uses the **CHE\_WORKSPACE\_POD\_NODE\_SELECTOR** environment variable to configure **nodeSelector**. This variable may contain a set of comma-separated **key=value** pairs to form the nodeSelector rule, or **NULL** to disable it.

```
CHE_WORKSPACE_POD_NODE_SELECTOR=disktype=ssd,cpu=xlarge,[key=value]
```

### IMPORTANT

**nodeSelector** must be configured during CodeReady Workspaces installation. This prevents existing workspaces from failing to run due to volumes affinity conflict caused by existing workspace PVC and Pod being scheduled in different zones.

To avoid Pods and PVCs to be scheduled in different zones on large, multi-zone clusters, create an additional **StorageClass** object (pay attention to the **allowedTopologies** field), which will coordinate the PVC creation process.

Pass the name of this newly created **StorageClass** to CodeReady Workspaces through the **CHE\_INFRA\_KUBERNETES\_PVC\_STORAGE\_CLASS\_NAME** environment variable. A default empty value of this variable instructs CodeReady Workspaces to use the cluster's default **StorageClass**.

## 4.9. CONFIGURING RED HAT CODEREADY WORKSPACES SERVER HOSTNAME


This procedure describes how to configure CodeReady Workspaces to use custom hostname.

### Prerequisites

- The **oc** tool is available.
- The certificate and the private key files are generated.

**IMPORTANT**

To generate the pair of a private key and certificate, the same certification authority (CA) must be used as for other CodeReady Workspaces hosts.

**IMPORTANT**

Ask a DNS provider to point the custom hostname to the cluster ingress.

**Procedure**

1. Pre-create a project for CodeReady Workspaces:

```
$ oc create project openshift-workspaces
```

2. Create a TLS secret:

```
$ oc create secret TLS ${secret} \ 1
--key ${key_file} \ 2
--cert ${cert_file} \ 3
-n openshift-workspaces
```

- 1 The TLS secret name
- 2 A file with the private key
- 3 A file with the certificate

3. Set the following values in the Custom Resource:

```
spec:
  server:
    cheHost: <hostname> 1
    cheHostTLSecret: <secret> 2
```

- 1 Custom Red Hat CodeReady Workspaces server hostname
- 2 The TLS secret name

4. If CodeReady Workspaces has been already deployed, wait until the rollout of all CodeReady Workspaces components finishes.

## 4.10. CONFIGURING OPENSIFT ROUTE

- This procedure describes how to configure labels and annotations for OpenShift Route to organize and categorize objects by scoping and selecting.

**Prerequisites**

- The **oc** tool is available.
- An instance of CodeReady Workspaces running in OpenShift.

## Procedure

1. To configure labels for OpenShift Route, update the Custom Resource:

**IMPORTANT**

Use comma to separate labels: **key1=value1,key2=value2**

```
$ oc patch checluster/codeready-workspaces -n openshift-workspaces --type=json -p \
'[{ "op": "replace", "path": "/spec/server/cheServerIngress/labels", \
"value": "<labels for a codeready-workspaces server ingress>" } ]'
```

```
$ oc patch checluster/codeready-workspaces -n openshift-workspaces --type=json -p \
'[{ "op": "replace", "path": "/spec/auth/identityProviderIngress/labels", \
"value": "<labels for a RH-SSO ingress>" } ]'
```


```
$ oc patch checluster/codeready-workspaces -n openshift-workspaces --type=json -p \
'[{ "op": "replace", "path": "/spec/server/pluginRegistryIngress/labels", \
"value": "<labels for a plug-ins registry ingress>" } ]'
```

```
$ oc patch checluster/codeready-workspaces -n openshift-workspaces --type=json -p \
'[{ "op": "replace", "path": "/spec/server/devfileRegistryIngress/labels", \
"value": "<labels for a devfile registry ingress>" } ]'
```

```
$ oc patch checluster/codeready-workspaces -n openshift-workspaces --type=json -p \
'[{ "op": "replace", "path": "/spec/server/dashboardIngress/labels", \
"value": "<labels for a dashboard ingress>" } ]'
```

```
$ oc patch checluster/codeready-workspaces -n openshift-workspaces --type=json -p \
'[{ "op": "replace", "path": \
"/spec/server/customCheProperties/CHE_INFRA_KUBERNETES_INGRESS_LABELS", \
"value": "<labels for a workspace ingress>" } ]'
```

2. To configure annotations for OpenShift Route, update the Custom Resource with the following commands:

**IMPORTANT**

Use object to specify annotations: **{"key1": "value1", "key2" : "value2"}**

```
$ oc patch checluster/codeready-workspaces -n openshift-workspaces --type=json -p \
'[{ "op": "replace", "path": "/spec/server/cheServerIngress/annotations", \
"value": <annotations for a codeready-workspaces server ingress> } ]'
```

```
$ oc patch checluster/codeready-workspaces -n openshift-workspaces --type=json -p \
'[{ "op": "replace", "path": "/spec/auth/identityProviderIngress/annotations", \
"value": <annotations for a RH-SSO ingress> } ]'
```

```
$ oc patch checluster/codeready-workspaces -n openshift-workspaces --type=json -p \
'[{ "op": "replace", "path": "/spec/server/pluginRegistryIngress/annotations", \
"value": <annotations for a plug-ins registry ingress> } ]'
```

```
$ oc patch checluster/codeready-workspaces -n openshift-workspaces --type=json -p \
'[{ "op": "replace", "path": "/spec/server/devfileRegistryIngress/annotations", \
```

```

"value": <annotations for a devfile registry ingress>}]'

$ oc patch checluster/codeready-workspaces -n openshift-workspaces --type=json -p \
'[{ "op": "replace", "path": "/spec/server/dashboardIngress/annotations", "\
"value": <annotations for a dashboard ingress>}]'

$ oc patch checluster/codeready-workspaces -n openshift-workspaces --type=json -p \
'[{ "op": "replace", "path": \
"/spec/server/customCheProperties/CHE_INFRA_KUBERNETES_INGRESS_ANNOTATIONS \
__JSON", "\
"value": "<annotations for a workspace ingress in json format>"}]'

```

## 4.11. CONFIGURING OPENSIFT ROUTE TO WORK WITH ROUTER SHARDING

This procedure describes how to configure labels, annotations, and domains for OpenShift Route to work with [Router Sharding](#). The chapter then mentions the configuration process for existing instances or those about to be installed.

### Prerequisites

- The **oc** and **crwctl** tool is available.

### Procedure

- For a new OperatorHub installation:
  1. Enter the CodeReady Workspaces Cluster using OpenShift Container Platform and create CheCluster Custom Resource (CR). See, [Creating an instance of the Red Hat CodeReady Workspaces Operator](#)
  2. Set the following values in codeready-workspaces Custom Resource (CR):

```

spec:
  server:
    devfileRegistryRoute:
      labels: <labels> 1
      domain: <domain> 2
      annotations: 3
        key1: value1
        key2: value2
    pluginRegistryRoute:
      labels: <labels> 4
      domain: <domain> 5
      annotations: 6
        key1: value1
        key2: value2
    dashboardRoute:
      labels: <labels> 7
      domain: <domain> 8
      annotations: 9
        key1: value1
        key2: value2

```



```

cheServerRoute:
  labels: <labels> 10
  domain: <domain> 11
  annotations: 12
    key1: value1
    key2: value2
  customCheProperties:
    CHE_INFRA_OPENSHIFT_ROUTE_LABELS: <labels> 13
    CHE_INFRA_OPENSHIFT_ROUTE_HOST_DOMAIN_SUFFIX: <domain> 14
  auth:
  identityProviderRoute:
    labels: <labels> 15
    domain: <domain> 16
    annotations: 17
      key1: value1
      key2: value2

```

1 4 7 10 13 15 comma separated list of labels that are used by the target ingress controller to filter the set of Routes to service

2 5 8 11 14 16 DNS name serviced by the target ingress controller

3 6 9 12 17 unstructured key value map stored with a resource

- For a new **crwctl** installation:

1. Configure the installation using:

```
$ crwctl server:deploy --che-operator-cr-patch-yaml=patch.yaml ...
```

The **patch.yaml** file must contain the following:

```

spec:
  server:
    devfileRegistryRoute:
      labels: <labels> 1
      domain: <domain> 2
      annotations: 3
        key1: value1
        key2: value2
    pluginRegistryRoute:
      labels: <labels> 4
      domain: <domain> 5
      annotations: 6
        key1: value1
        key2: value2
    dashboardRoute:
      labels: <labels> 7
      domain: <domain> 8
      annotations: 9
        key1: value1
        key2: value2
    cheServerRoute:

```

```

labels: <labels> 10
domain: <domain> 11
annotations: 12
  key1: value1
  key2: value2
customCheProperties:
  CHE_INFRA_OPENSHIFT_ROUTE_LABELS: <labels> 13
  CHE_INFRA_OPENSHIFT_ROUTE_HOST_DOMAIN_SUFFIX: <domain> 14
auth:
identityProviderRoute:
  labels: <labels> 15
  domain: <domain> 16
  annotations: 17
    key1: value1
    key2: value2

```

1 4 7 10 13 15 comma separated list of labels that are used by the target ingress controller to filter the set of Routes to service

2 5 8 11 14 16 DNS name serviced by the target ingress controller

3 6 9 12 17 unstructured key value map stored with a resource

- For already existing CodeReady Workspaces installation:
  1. Update **codeready-workspaces** CR using the **oc** tool:
    - a. To configure labels:



### IMPORTANT

Use comma to separate labels: **key1=value1,key2=value2**

```

$ oc patch checluster/codeready-workspaces -n openshift-workspaces --type=json -p \
\
'{"op": "replace", "path": "/spec/server/cheServerRoute/labels", \
"value": "<labels for a codeready-workspaces server route>"}'

```

```

$ oc patch checluster/codeready-workspaces -n openshift-workspaces --type=json -p \
\
'{"op": "replace", "path": "/spec/server/pluginRegistryRoute/labels", \
"value": "<labels for a plug-ins registry route>"}'

```

```

$ oc patch checluster/codeready-workspaces -n openshift-workspaces --type=json -p \
\
'{"op": "replace", "path": "/spec/server/devfileRegistryRoute/labels", \
"value": "<labels for a devfile registry route>"}'

```

```

$ oc patch checluster/codeready-workspaces -n openshift-workspaces --type=json -p \
\
'{"op": "replace", "path": "/spec/server/dashboardRoute/labels", \
"value": "<labels for a dashboard route>"}'

```

```
$ oc patch checluster/codeready-workspaces -n openshift-workspaces --type=json -p \
\
'{"op": "replace", "path": "/spec/auth/identityProviderRoute/labels", \
"value": "<labels for a RH-SSO route>"}'
```

```
$ oc patch checluster/codeready-workspaces -n openshift-workspaces --type=json -p \
\
'{"op": "replace", "path": \
"/spec/server/customCheProperties/CHE_INFRA_OPENS SHIFT_ROUTE_LABELS", \
\
"value": "<labels for a workspace routes>"}'
```

b. To configure domains:

```
$ oc patch checluster/codeready-workspaces -n openshift-workspaces --type=json -p \
\
'{"op": "replace", "path": "/spec/server/cheServerRoute/domain", \
"value": "<ingress domain>"}'
```

```
$ oc patch checluster/codeready-workspaces -n openshift-workspaces --type=json -p \
\
'{"op": "replace", "path": "/spec/server/pluginRegistryRoute/domain", \
"value": "<ingress domain>"}'
```

```
$ oc patch checluster/codeready-workspaces -n openshift-workspaces --type=json -p \
\
'{"op": "replace", "path": "/spec/server/devfileRegistryRoute/domain", \
"value": "<ingress domain>"}'
```

```
$ oc patch checluster/codeready-workspaces -n openshift-workspaces --type=json -p \
\
'{"op": "replace", "path": "/spec/server/dashboardRoute/domain", \
"value": "<ingress domain>"}'
```

```
$ oc patch checluster/codeready-workspaces -n openshift-workspaces --type=json -p \
\
'{"op": "replace", "path": "/spec/auth/identityProviderRoute/domain", \
"value": "<ingress domain>"}'
```

```
$ oc patch checluster/codeready-workspaces -n openshift-workspaces --type=json -p \
\
'{"op": "replace", "path": \
"/spec/server/customCheProperties/CHE_INFRA_OPENS SHIFT_ROUTE_HOST_DO \
MAIN_SUFFIX", \
"value": "<ingress domain>"}'
```

c. To configure annotations:



### IMPORTANT

Use object to specify annotations: {"key1": "value1", "key2" : "value2"}

```
$ oc patch checluster/codeready-workspaces -n openshift-workspaces --type=json -p \
\
[{"op": "replace", "path": "/spec/server/cheServerRoute/annotations", \
"value": <annotations for a codeready-workspaces ingress>}]
```

```
$ oc patch checluster/codeready-workspaces -n openshift-workspaces --type=json -p \
\
[{"op": "replace", "path": "/spec/server/pluginRegistryRoute/annotations", \
"value": <annotations for a plug-ins registry ingress>}]
```

```
$ oc patch checluster/codeready-workspaces -n openshift-workspaces --type=json -p \
\
[{"op": "replace", "path": "/spec/server/devfileRegistryRoute/annotations", \
"value": <annotations for a devfile registry ingress>}]
```

```
$ oc patch checluster/codeready-workspaces -n openshift-workspaces --type=json -p \
\
[{"op": "replace", "path": "/spec/server/dashboardRoute/annotations", \
"value": <annotations for a dashboard ingress>}]
```

```
$ oc patch checluster/codeready-workspaces -n openshift-workspaces --type=json -p \
\
[{"op": "replace", "path": "/spec/auth/identityProviderRoute/annotations", \
"value": <annotations for a RH-SSO ingress>}]
```

## 4.12. DEPLOYING CODEREADY WORKSPACES WITH SUPPORT FOR GIT REPOSITORIES WITH SELF-SIGNED CERTIFICATES

This procedure describes how to configure CodeReady Workspaces for deployment with support for Git operations on repositories that use self-signed certificates.

### Prerequisites

- Git version 2 or later

### Procedure

Configuring support for self-signed Git repositories.

1. Create a new **ConfigMap** with details about the Git server:

```
$ oc create configmap che-git-self-signed-cert --from-file=ca.crt \
--from-literal=githost=<host:port> -n {prod-namespace}
```

In the command, substitute **<host:port>** for the host and port of the HTTPS connection on the Git server (optional).

**NOTE**

- When **githost** is not specified, the given certificate is used for all HTTPS repositories.
- The certificate file must be named **ca.crt**.
- Certificate files are typically stored as Base64 ASCII files, such as **.pem**, **.crt**, **.ca-bundle**. Also, they can be encoded as binary data, for example, **.cer**. All **Secrets** that hold certificate files should use the Base64 ASCII certificate rather than the binary data certificate.

2. Configure the workspace exposure strategy:  
Update the **gitSelfSignedCert** property. To do that, execute:

```
$ oc patch checluster/codeready-workspaces -n openshift-workspaces --type=json \
-p '[{"op": "replace", "path": "/spec/server/gitSelfSignedCert", "value": true}]'
```

3. Create and start a new workspace. Every container used by the workspace mounts a special volume that contains a file with the self-signed certificate. The repository's **.git/config** file contains information about the Git server host (its URL) and the path to the certificate in the **http** section (see Git documentation about [git-config](#)). For example:

```
[http "https://10.33.177.118:3000"]
sslCAInfo = /etc/che/git/cert/ca.crt
```

## 4.13. INSTALLING CODEREADY WORKSPACES USING STORAGE CLASSES

To configure CodeReady Workspaces to use a configured infrastructure storage, install CodeReady Workspaces using storage classes. This is especially useful when a user wants to bind a persistent volume provided by a non-default provisioner. To do so, a user binds this storage for the CodeReady Workspaces data saving and sets the parameters for that storage. These parameters can determine the following:

- A special host path
- A storage capacity
- A volume mod
- Mount options
- A file system
- An access mode
- A storage type
- And many others

CodeReady Workspaces has two components that require persistent volumes to store data:

- A PostgreSQL database.

- A CodeReady Workspaces workspace. CodeReady Workspaces workspaces store source code using volumes, for example **/projects** volume.



## NOTE

CodeReady Workspaces workspace source code is stored in the persistent volume only if a workspace is not ephemeral.

### Persistent volume claims facts:

- CodeReady Workspaces does not create persistent volumes in the infrastructure.
- CodeReady Workspaces uses persistent volume claims (PVC) to mount persistent volumes.
- The CodeReady Workspaces server creates persistent volume claims.  
A user defines a storage class name in the CodeReady Workspaces configuration to use the storage classes feature in the CodeReady Workspaces PVC. With storage classes, a user configures infrastructure storage in a flexible way with additional storage parameters. It is also possible to bind a static provisioned persistent volumes to the CodeReady Workspaces PVC using the class name.

### Procedure

Use CheCluster Custom Resource definition to define storage classes:

1. Define storage class names

To do so, use one of the following methods:

- **Use arguments for the `server:deploy` command**
  - i. Provide the storage class name for the PostgreSQL PVC  
Use the **`crwctl server:deploy`** command with the **`--postgres-pvc-storage-class-name`** flag:

```
$ crwctl server:deploy -m -p minikube -a operator --postgres-pvc-storage-class-name=postgres-storage
```

- ii. Provide the storage class name for the CodeReady Workspaces workspace  
Use the **`server:deploy`** command with the **`--workspace-pvc-storage-class-name`** flag:

```
$ crwctl server:deploy -m -p minikube -a operator --workspace-pvc-storage-class-name=workspace-storage
```

For CodeReady Workspaces workspace, the storage class name has different behavior depending on the workspace PVC strategy.



## NOTE

**`postgres-pvc-storage-class-name=postgres-storage`** and **`workspace-pvc-storage-class-name`** work for the Operator installer and the Helm installer.

- Define storage class names using a Custom Resources YAML file:

- i. Create a YAML file with Custom Resources defined for the CodeReady Workspaces installation.
- ii. Define fields: **spec#storage#postgresPVCStorageClassName** and **spec#storage#workspacePVCStorageClassName**.

```

apiVersion: org.eclipse.che/v1
kind: CheCluster
metadata:
  name: codeready-workspaces
spec:
  # ...
  storage:
    # ...
    # keep blank unless you need to use a non default storage class for PostgreSQL
    PVC
    postgresPVCStorageClassName: 'postgres-storage'
    # ...
    # keep blank unless you need to use a non default storage class for workspace
    PVC(s)
    workspacePVCStorageClassName: 'workspace-storage'
    # ...

```

- iii. Start the codeready-workspaces server with your Custom Resources:

```

$ crwctl server:deploy -m -p minikube -a operator --che-operator-cr-
yaml=/path/to/custom/che/resource/org_v1_che_cr.yaml

```

2. Configure CodeReady Workspaces to store workspaces in one persistent volume and a PostgreSQL database in the second one:

- a. Modify your Custom Resources YAML file:

- Set **pvcStrategy** as **common**.
- Configure CodeReady Workspaces to start workspaces in a single project.
- Define storage class names for **postgresPVCStorageClassName** and **workspacePVCStorageClassName**.
- Example of the YAML file:

```

apiVersion: org.eclipse.che/v1
kind: CheCluster
metadata:
  name: codeready-workspaces
spec:
  server:
    # ...
    workspaceNamespaceDefault: codeready-ws-  
<username>
    # ...
  storage:
    # ...
    # Defaults to common
    pvcStrategy: 'common'
    # ...

```

```

# keep blank unless you need to use a non default storage class for PostgreSQL
PVC
  postgresPVCStorageClassName: 'postgres-storage'
# ...
# keep blank unless you need to use a non default storage class for workspace
PVC(s)
  workspacePVCStorageClassName: 'workspace-storage'
# ...

```

- b. Start the codeready-workspaces server with your Custom Resources:

```
$ crwctl server:deploy -m -p minikube -a operator --che-operator-cr-yaml=/path/to/custom/che/resource/org_v1_che_cr.yaml
```

3. Bind static provisioned volumes using class names:

- a. Define the persistent volume for a PostgreSQL database:

```

# che-postgres-pv.yaml
apiVersion: v1
kind: PersistentVolume
metadata:
  name: postgres-pv-volume
  labels:
    type: local
spec:
  storageClassName: postgres-storage
  capacity:
    storage: 1Gi
  accessModes:
    - ReadWriteOnce
  hostPath:
    path: "/data/che/postgres"

```

- b. Define the persistent volume for a CodeReady Workspaces workspace:

```


# che-workspace-pv.yaml
apiVersion: v1
kind: PersistentVolume
metadata:
  name: workspace-pv-volume
  labels:
    type: local
spec:
  storageClassName: workspace-storage
  capacity:
    storage: 10Gi
  accessModes:
    - ReadWriteOnce
  hostPath:
    path: "/data/che/workspace"

```

- c. Bind the two persistent volumes:

```
$ oc apply -f che-workspace-pv.yaml -f che-postgres-pv.yaml
```



**NOTE**

You must provide valid file permissions for volumes. You can do it using storage class configuration or manually. To manually define permissions, define **storageClass#mountOptions uid** and **gid**. PostgreSQL volume requires **uid=26** and **gid=26**.

## 4.14. IMPORTING UNTRUSTED TLS CERTIFICATES TO CODEREADY WORKSPACES

External communications between CodeReady Workspaces components are, by default, encrypted with TLS. Communications of CodeReady Workspaces components with external services such as proxies, source code repositories, identity providers may require using of TLS. Those communications require the use of TLS certificates signed by trusted Certificate Authorities.

When the certificates used by CodeReady Workspaces components or by an external service are signed by an untrusted CA it can be necessary to import the CA certificate in the CodeReady Workspaces installation, so that every CodeReady Workspaces component will consider them as signed by a trusted CA.

Typical cases that may require this addition are:


- when the underlying OpenShift cluster uses TLS certificates signed by a CA that is not trusted,
- when CodeReady Workspaces server or workspace components connect to external services such as RH-SSO or a Git server that use TLS certificates signed by an untrusted CA.

CodeReady Workspaces uses labeled ConfigMaps in project as sources for TLS certificates. The ConfigMaps can have arbitrary number of keys with arbitrary number of certificates each.

**NOTE**

When the cluster contains cluster-wide trusted CA certificates added through the [cluster-wide-proxy configuration](#), CodeReady Workspaces Operator detects them and automatically injects them into this ConfigMap:

- CodeReady Workspaces automatically labels the ConfigMap with the **config.openshift.io/inject-trusted-cabundle="true"** label.
- Based on this annotation, OpenShift automatically injects the cluster-wide trusted CA certificates inside the **ca-bundle.crt** key of ConfigMap

**IMPORTANT**

Some CodeReady Workspaces components require to have full certificate chain to trust the endpoint. If the cluster is configured with an intermediate certificate, then the whole chain (including self-signed root) should be added to CodeReady Workspaces.

### 4.14.1. Adding new CA certificates into CodeReady Workspaces

This guide can be used before the installations of CodeReady Workspaces or when CodeReady Workspaces is already installed and running.

**NOTE**

If you are using CodeReady Workspaces version lower than 2.5.1 see [this guide](#) on how to apply additional TLS certificates.

**Prerequisites**

- The **oc** tool is available.
- Namespace for CodeReady Workspaces exists.

**Procedure**

1. Save the certificates you need to import, to a local file system.

**CAUTION**

- Certificate files are typically stored as Base64 ASCII files, such as **.pem**, **.crt**, **.ca-bundle**. But, they can also be binary-encoded, for example, as **.cer** files. All Secrets that hold certificate files should use the Base64 ASCII certificate rather than the binary-encoded certificate.
  - CodeReady Workspaces already uses some reserved file names to automatically inject certificates into the ConfigMap, so you should avoid using the following reserved file names to save your certificates:
    - **ca-bundle.crt**
    - **ca.crt**
2. Create a new ConfigMap with the required TLS certificates:

```
$ oc create configmap custom-certs --from-file=<bundle-file-path> -n=openshift-workspaces
```

To apply more than one bundle, add another **--from-file=<bundle-file-path>** flag to the above command. Or you may create another ConfigMap.

3. Label created ConfigMaps with both **app.kubernetes.io/part-of=che.eclipse.org** and **app.kubernetes.io/component=ca-bundle** labels:

```
$ oc label configmap custom-certs app.kubernetes.io/part-of=che.eclipse.org
app.kubernetes.io/component=ca-bundle -n <crw-namespace-name>
```

4. Deploy CodeReady Workspaces if it has not been deployed before otherwise wait until rollout of CodeReady Workspaces components finishes. If there are running workspaces, they should be restarted in order the changes take effect.

**4.14.2. Verification at the CodeReady Workspaces installation level**

If after adding the certificates something does not work as expected, here is a list of things to verify:

- In case of a CodeReady Workspaces [Operator](#) deployment, namespace where **CheCluster** located contains labeled ConfigMaps with right content:

```
$ oc get cm --selector=app.kubernetes.io/component=ca-bundle,app.kubernetes.io/part-of=che.eclipse.org -n openshift-workspaces
```

And to check content of ConfigMap:

```
$ {orch-cli} get cm __<name>__ -n {prod-namespace} -o yaml
```

- CodeReady Workspaces Pod Volumes list contains a volume that uses **ca-certs-merged** ConfigMap as data-source. To get the list of Volumes of the CodeReady Workspaces Pod:

```
$ oc get pod -o json <codeready-workspaces-pod-name> -n openshift-workspaces | jq .spec.volumes
```

- CodeReady Workspaces mounts certificates in folder **/public-certs/** of the CodeReady Workspaces server container. This command returns the list of files in that folder:

```
$ oc exec -t <codeready-workspaces-pod-name> -n openshift-workspaces -- ls /public-certs/
```

- In the CodeReady Workspaces server logs there is a line for every certificate added to the Java truststore, including configured CodeReady Workspaces certificates.

```
$ oc logs <codeready-workspaces-pod-name> -n openshift-workspaces
```

- CodeReady Workspaces server Java truststore contains the certificates. The certificates SHA1 fingerprints are among the list of the SHA1 of the certificates included in the truststore returned by the following command:

```
$ oc exec -t <codeready-workspaces-pod-name> -n openshift-workspaces -- keytool -list -keystore /home/jboss/cacerts
Your keystore contains 141 entries
```

```
(...)
```

To get the SHA1 hash of a certificate on the local filesystem:

```
$ openssl x509 -in <certificate-file-path> -fingerprint -noout
SHA1 Fingerprint=3F:DA:BF:E7:A7:A7:90:62:CA:CF:C7:55:0E:1D:7D:05:16:7D:45:60
```

### 4.14.3. Verification at the workspace level

- Start a workspace, get the project in which it has been created, and wait for it to be started
- Get the name of the workspace Pod with the following command:

```
$ oc get pods -o=jsonpath='{.items[0].metadata.name}' -n <workspace namespace> | grep '^workspace.*'
```

- Get the name of the Theia IDE container in the workspace Pod with the following command:

```
$ oc get -o json pod <workspace pod name> -n <workspace namespace> | \
jq -r '.spec.containers[] | select(.name | startswith("theia-ide")).name'
```

- Look for a **ca-certs** ConfigMap that should have been created inside the workspace namespace:

```
$ oc get cm ca-certs <workspace namespace>
```

- Check that the entries in the **ca-certs** ConfigMap contain all the additional entries you added before. In addition it may contain **ca-bundle.crt** entry which is a reserved one:

```
$ oc get cm ca-certs -n <workspace namespace> -o json | jq -r '.data | keys[]'
ca-bundle.crt
source-config-map-name.data-key.crt
```

- Make sure that the **ca-certs** ConfigMap has been added as a volume in the workspace Pod:

```
$ oc get -o json pod <workspace pod name> -n <workspace namespace> | \
jq '.spec.volumes[] | select(.configMap.name == "ca-certs")'
{
  "configMap": {
    "defaultMode": 420,
    "name": "ca-certs"
  },
  "name": "che-self-signed-certs"
}
```

- Confirm that the volume has been mounted into containers, especially in the Theia IDE container:

```
$ oc get -o json pod <workspace pod name> -n <workspace namespace> | \
jq '.spec.containers[] | select(.name == "<theia ide container name>").volumeMounts[] |
select(.name == "che-self-signed-certs")'
{
  "mountPath": "/public-certs",
  "name": "che-self-signed-certs",
  "readOnly": true
}
```

- Inspect **/public-certs** folder in the Theia IDE container and check that its contents match the list of entries in the **ca-certs** ConfigMap:

```
$ oc exec <workspace pod name> -c <theia ide container name> -n <workspace
namespace> -- ls /public-certs
ca-bundle.crt
source-config-map-name.data-key.crt
```

## 4.15. SWITCHING BETWEEN EXTERNAL AND INTERNAL DNS NAMES IN INTER-COMPONENT COMMUNICATION

By default, new CodeReady Workspaces deployments use OpenShift services DNS names for communications between CodeReady Workspaces server, RH-SSO, registries, and helps with:

- Bypassing proxy, certificates, and firewalls issues
- Speeding up the traffic

This type of communication is an alternative to the external method of inter-component communication, which uses OpenShift Route cluster host names. In the situations described below, using OpenShift internal DNS names is not supported. By disabling the use of the internal cluster host name in inter-component communication, the communication using external OpenShift Route will come into effect.

### Internal inter-component communication restrictions in OpenShift

- The CodeReady Workspaces components are deployed across multi-cluster OpenShift environments.
- The OpenShift NetworkPolicies restricts communication between namespaces.

The following section describes how to enable and disable the external inter-component communication for OpenShift Route.

### Prerequisites

- The **oc** tool is available.
- An instance of CodeReady Workspaces running in OpenShift.

### Procedure

Switching between external and internal inter-component communication method is reached through the update against Custom Resource (CR).

1. To use external OpenShift Route in inter-component communication:

```
$ oc patch checluster/codeready-workspaces -n openshift-workspaces --type=json -p \
[{"op": "replace", "path": "/spec/server/useInternalClusterSVCNames", "value": false}]
```

2. To use internal OpenShift DNS names in the inter-component communication:

```
$ oc patch checluster/codeready-workspaces -n openshift-workspaces --type=json -p \
[{"op": "replace", "path": "/spec/server/useInternalClusterSVCNames", "value": true}]
```

## 4.16. SETTING UP THE RH-SSO CODEREADY-WORKSPACES-USERNAME-READONLY THEME FOR THE RED HAT CODEREADY WORKSPACES LOGIN PAGE

The following procedure is relevant for all CodeReady Workspaces instances with the OpenShift OAuth service enabled.

When a user with pre-created namespaces logs in to Red Hat CodeReady Workspaces Dashboard for the first time, a page allowing the user to update account information is displayed. It is possible to change the username, but choosing a username that doesn't match the OpenShift username, prevents the user's workspaces from running. This is caused by CodeReady Workspaces attempts to use a non-existing namespace, the name of which is derived from a user OpenShift username, to create a workspace. To prevent this, log in to RH-SSO and modify the theme settings.

### 4.16.1. Logging in to RH-SSO

The following procedure describes how to log in to RH-SSO, which acts as a route for OpenShift platforms. To log in to RH-SSO, a user has to obtain the RH-SSO URL and a user's credentials first.

### Prerequisites

- The **oc** tool installed.
- Logged in to OpenShift cluster using the **oc** tool.

### Procedure

1. Obtain a user RH-SSO login:

```
oc get secret che-identity-secret -n openshift-workspaces -o json | jq -r '.data.user' | base64 -d
```

2. Obtain a user RH-SSO password:

```
oc get secret che-identity-secret -n openshift-workspaces -o json | jq -r '.data.password' | base64 -d
```

3. Obtain the RH-SSO URL:

```
oc get ingress -n openshift-workspaces -l app=che,component=keycloak -o 'custom-columns=URL:.spec.rules[0].host' --no-headers
```

4. Open the URL in a browser and log in to RH-SSO using the obtained login and password.

## 4.16.2. Setting up the RH-SSO `codeready-workspaces-username-readonly` theme

### Prerequisites

- An instance of CodeReady Workspaces running in OpenShift.
- A user is logged in to the RH-SSO service.

### Procedure

After changing a username, set the **Login Theme** option to **readonly**.

1. In the main **Configure** menu on the left, select **Realm Settings**:

The screenshot shows the configuration interface for the 'Codeready' realm. On the left, a 'Configure' menu is visible with 'Realm Settings' selected. The main panel shows the 'Themes' tab with the following settings:

- Login Theme:** `codeready-username-readonly`
- Account Theme:** `rh-ssso`
- Admin Console Theme:** `rh-ssso`
- Email Theme:** `rh-ssso`
- Internationalization Enabled:**  OFF

Buttons for 'Save' and 'Cancel' are located at the bottom right of the configuration area.

2. Navigate to the **Themes** tab.
3. In the **Login Theme** field, select the **codeready-workspaces-username-readonly** option and click the **Save** button to apply the changes.

## 4.17. MOUNTING A SECRET AS A FILE OR AN ENVIRONMENT VARIABLE INTO A RED HAT CODEREADY WORKSPACES CONTAINER

Secrets are OpenShift objects that store sensitive data such as user names, passwords, authentication tokens, and configurations in an encrypted form.

Users can mount a OpenShift secret that contains sensitive data in a Red Hat CodeReady Workspaces container as:

- a file
- an environment variable

The mounting process uses the standard OpenShift mounting mechanism, but it requires additional annotations and labeling.

### 4.17.1. Mounting a secret as a file into a Red Hat CodeReady Workspaces container

#### Prerequisites

- A running instance of CodeReady Workspaces. To install an instance of CodeReady Workspaces, see [Installing CodeReady Workspaces](#).

#### Procedure

1. Create a new OpenShift secret in the OpenShift project where a CodeReady Workspaces is deployed. The labels of the secret that is about to be created must match the set of labels:
  - **app.kubernetes.io/part-of: che.eclipse.org**
  - **app.kubernetes.io/component: <DEPLOYMENT\_NAME>-secret**

Where **<DEPLOYMENT\_NAME>** is one of the following deployments: **postgres**, **keycloak**, **devfile-registry**, **plugin-registry** or **codeready**

#### Example 4.3. Example:

```
apiVersion: v1
kind: Secret
metadata:
  name: custom-certificate
labels:
  app.kubernetes.io/part-of: che.eclipse.org
  app.kubernetes.io/component: codeready-secret
...
```

Annotations must indicate that the given secret is mounted as a file. Configure the annotation values:

- **che.eclipse.org/mount-as: file** - to indicate that a secret is mounted as a file
- **che.eclipse.org/mount-path: <FOO\_ENV>** - to provide a required mount path

```

apiVersion: v1
kind: Secret
metadata:
  name: custom-certificate
annotations:
  che.eclipse.org/mount-path: /custom-certificates
  che.eclipse.org/mount-as: file
labels:
...

```

The OpenShift secret may contain several items whose names must match the desired file name mounted into the container.

```

apiVersion: v1
kind: Secret
metadata:
  name: custom-certificate
labels:
  app.kubernetes.io/part-of: che.eclipse.org
  app.kubernetes.io/component: codeready-secret
annotations:
  che.eclipse.org/mount-path: /custom-certificates
  che.eclipse.org/mount-as: file
data:
  ca.crt: <base64 encoded data content here>

```

This results in a file named **ca.crt** being mounted at the **/custom-certificates** path of CodeReady Workspaces container.

## 4.17.2. Mounting a secret as an environment variable into a Red Hat CodeReady Workspaces container

### Prerequisites

- A running instance of Red Hat CodeReady Workspaces. To install an instance of Red Hat CodeReady Workspaces, see [Installing CodeReady Workspaces](#).

### Procedure

1. Create a new OpenShift secret in the OpenShift project where a CodeReady Workspaces is deployed. The labels of the secret that is about to be created must match the set of labels:
  - **app.kubernetes.io/part-of: che.eclipse.org**
  - **app.kubernetes.io/component: <DEPLOYMENT\_NAME>-secret**

Where **<DEPLOYMENT\_NAME>** is one of the following deployments: **postgres**, **keycloak**, **devfile-registry**, **plugin-registry** or **codeready**



**Example 4.4. Example:**

```

apiVersion: v1
kind: Secret
metadata:
  name: custom-settings
  labels:
    app.kubernetes.io/part-of: che.eclipse.org
    app.kubernetes.io/component: codeready-secret
...

```

Annotations must indicate that the given secret is mounted as a environment variable. Configure the annotation values:

- **che.eclipse.org/mount-as: env** - to indicate that a secret is mounted as an environment variable
- **che.eclipse.org/env-name: <FOO\_ENV>** - to provide an environment variable name, which is required to mount a secret key value

```

apiVersion: v1
kind: Secret
metadata:
  name: custom-settings
  annotations:
    che.eclipse.org/env-name: FOO_ENV
    che.eclipse.org/mount-as: env
  labels:
    ...
data:
  mykey: myvalue

```

This results in the environment variable named **FOO\_ENV** and the value **myvalue** being provisioned into a CodeReady Workspaces container.


If the secret provides more than one data item, the environment variable name must be provided for each of the data keys as follows:

```

apiVersion: v1
kind: Secret
metadata:
  name: custom-settings
  annotations:
    che.eclipse.org/mount-as: env
    che.eclipse.org/mykey_env-name: FOO_ENV
    che.eclipse.org/otherkey_env-name: OTHER_ENV
  labels:
    ...
data:
  mykey: myvalue
  otherkey: othervalue

```

This results in two environment variables with names **FOO\_ENV**, **OTHER\_ENV**, and values **myvalue** and **othervalue**, being provisioned into a CodeReady Workspaces container.

**NOTE**

The maximum length of annotation names in a OpenShift secret is 63 characters, where 9 characters are reserved for a prefix that ends with /. This acts as a restriction for the maximum length of the key that can be used for the secret.

## 4.18. ENABLING DEV WORKSPACE ENGINE

This procedure describes how to enable the Dev Workspace engine to support the Devfile 2.0.0 file format and mentions how to do so on existing instances or those about to be installed.

### Prerequisites

- The **oc** and **crwctl** tools are available.

### Procedure

- For a new OperatorHub installation:
  1. Enter the Red Hat CodeReady Workspaces Cluster using OpenShift Container Platform and create CheCluster Custom Resource (CR). See, [Creating an instance of the Red Hat CodeReady Workspaces Operator](#)
  2. Set the following values in codeready-workspaces Custom Resource (CR):

```
spec:
  devWorkspace:
    enable: true
```

- For a new **crwctl** installation:
  1. Configure the the **crwctl** installation using:

```
$ crwctl server:deploy --che-operator-cr-patch-yaml=patch.yaml ...
```

**patch.yaml** must contain the following:

```
spec:
  devWorkspace:
    enable: true
```

- For already existing CodeReady Workspaces installation:
  1. Update **codeready-workspaces** CR using the **oc** tool:

```
$ oc patch checluster/codeready-workspaces -n openshift-workspaces --type=json -p \
' [{"op": "replace", "path": "/spec/devWorkspace/enable", "value": true}]'
```

### Additional resources

For information about installation methods mentioned in this chapter, see [Chapter 3, Installing CodeReady Workspaces](#).

## CHAPTER 5. UPGRADING CODEREADY WORKSPACES

This chapter describes how to upgrade a CodeReady Workspaces instance from version 2.9 to CodeReady Workspaces 2.10.

The method used to install the CodeReady Workspaces instance determines the method to proceed with for the upgrade:

- [Section 5.1, “Upgrading CodeReady Workspaces using OperatorHub”](#)
- [Section 5.2, “Upgrading CodeReady Workspaces using the CLI management tool”](#)
- [Section 5.3, “Upgrading CodeReady Workspaces using the CLI management tool in restricted environment”](#)

### 5.1. UPGRADING CODEREADY WORKSPACES USING OPERATORHUB

This section describes how to upgrade from an earlier minor version using the Operator from OperatorHub in the OpenShift web console.

OperatorHub supports **Automatic** and **Manual** upgrade strategies: **Automatic**:: The upgrade process starts when a new version of the Operator is published. **Manual**:: The update must be manually approved every time the new version of the Operator is published.

#### 5.1.1. Specifying the approval strategy of CodeReady Workspaces in OperatorHub

##### Prerequisites

- An administrator account on an OpenShift instance.
- An instance of an earlier minor version of CodeReady Workspaces, installed using the Operator from OperatorHub on the same instance of OpenShift.

##### Procedure

1. Open the OpenShift web console.
2. Navigate to the **Operators** → **Installed Operators** section.
3. Click **Red Hat CodeReady Workspaces** in the list of the installed Operators.
4. Navigate to the **Subscription** tab and specify the approval strategy:
  - **Approval: Automatic**  
or  
**Approval: Manual**

## Change Update Approval Strategy

What strategy is used for approving updates?

- Automatic (default)  
New updates will be installed as soon as they become available.
- Manual  
New updates need to be manually approved before installation begins.

Cancel

Save

### 5.1.2. Manually upgrading CodeReady Workspaces in OperatorHub

#### Prerequisites

- An administrator account on an OpenShift instance.
- An instance of an earlier minor version of CodeReady Workspaces, installed using the Operator from OperatorHub on the same instance of OpenShift.
- The approval strategy in the subscription is set to **Manual**.

#### Procedure

1. Open the OpenShift web console.
2. Navigate to the **Operators → Installed Operators** section.
3. Click **Red Hat CodeReady Workspaces** in the list of the installed Operators.
4. Navigate to the **Subscription** tab. Upgrades requiring approval are displayed next to **Upgrade Status**, for example **1 requires approval**.
5. Click **1 requires approval**, then click **Preview Install Plan**.
6. Review the resources that are listed as available for upgrade and click **Approve**.

#### Verification steps

1. Navigate to the **Operators → Installed Operators** page to monitor the progress of the upgrade. When complete, the status changes to **Succeeded** and **Up to date**.
2. The 2.10 version number is visible at the bottom of the page.

#### Additional resources

- [Upgrading installed Operators](#) section in the OpenShift documentation.

## 5.2. UPGRADING CODEREADY WORKSPACES USING THE CLI MANAGEMENT TOOL

This section describes how to upgrade from the previous minor version using the CLI management tool.

### Prerequisites

- An administrative account on OpenShift.
- A running instance of a previous minor version of Red Hat CodeReady Workspaces, installed using the CLI management tool on the same instance of OpenShift, in the **<openshift-workspaces>** project.
- **crwctl** is available and updated. See [Section 3.3.1, “Installing the crwctl CLI management tool”](#) .

### Procedure

1. Save and push changes back to the Git repositories for all running CodeReady Workspaces 2.9 workspaces.
2. Shut down all workspaces in the CodeReady Workspaces 2.9 instance.
3. Upgrade CodeReady Workspaces:

```
$ crwctl server:update -n openshift-workspaces
```



### NOTE

For slow systems or internet connections, add the **--k8spodwaittimeout=1800000** flag option to the **crwctl server:update** command to extend the Pod timeout period to 1800000 ms or longer.

### Verification steps

1. Navigate to the CodeReady Workspaces instance.
2. The 2.10 version number is visible at the bottom of the page.

## 5.3. UPGRADING CODEREADY WORKSPACES USING THE CLI MANAGEMENT TOOL IN RESTRICTED ENVIRONMENT

This section describes how to upgrade Red Hat CodeReady Workspaces using the CLI management tool in restricted environment. The upgrade path supports minor version update, from CodeReady Workspaces version 2.9 to version 2.10.

### Prerequisites

- An administrative account on an instance of OpenShift.
- A running instance version 2.9 of Red Hat CodeReady Workspaces, installed using the CLI management tool on the same instance of OpenShift, with the crwctl **--installer operator**

method, in the **<openshift-workspaces>** project. See [Section 3.4, “Installing CodeReady Workspaces in a restricted environment”](#).

- The **crwctl** 2.10 management tool is available. See [Section 3.3.1, “Installing the crwctl CLI management tool”](#).

### 5.3.1. Understanding network connectivity in restricted environments

CodeReady Workspaces requires that each OpenShift Route created for CodeReady Workspaces is accessible from inside the OpenShift cluster. These CodeReady Workspaces components have a OpenShift Route: **codeready-workspaces-server**, **keycloak**, **devfile-registry**, **plugin-registry**.

Consider the network topology of the environment to determine how best to accomplish this.

#### Example 5.1. Network owned by a company or an organization, disconnected from the public Internet

The network administrators must ensure that it is possible to route traffic bound from the cluster to OpenShift Route host names.

#### Example 5.2. Private subnetwork in a cloud provider

Create a proxy configuration allowing the traffic to leave the node to reach an external-facing Load Balancer.

### 5.3.2. Building offline registry images

#### 5.3.2.1. Building an offline devfile registry image

This section describes how to build an offline devfile registry image. Starting workspaces without relying on resources from the outside Internet requires building this image. The image contains all sample projects referenced in devfiles as **zip** files.

#### Prerequisites:

- A running installation of [podman](#) or [docker](#).

#### Procedure


1. Clone the devfile registry repository and check out the version to deploy:

```
$ git clone git@github.com:redhat-developer/codeready-workspaces.git
$ cd codeready-workspaces
$ git checkout crw-2.10-rhel-8
```

2. Build an offline devfile registry image:

```
$ cd dependencies/che-devfile-registry
$ ./build.sh --organization <my-org> \
  --registry <my-registry> \
```

```
--tag <my-tag> \  
--offline
```

**NOTE**

To display full options for the **build.sh** script, use the **--help** parameter.

**Additional resources**

- [Customizing the registries.](#)

**5.3.2.2. Building an offline plug-in registry image**

This section describes how to build an offline plug-in registry image. Starting workspaces without relying on resources from the outside Internet requires building this image. The image contains plug-in metadata and all plug-in or extension artifacts.

**Prerequisites**

- NodeJS 12.x
- A running version of yarn. See [Installing Yarn](#).
- **./node\_modules/.bin** is in the **PATH** environment variable.
- A running installation of [podman](#) or [docker](#).


**Procedure**

1. Clone the plug-in registry repository and check out the version to deploy:

```
$ git clone git@github.com:redhat-developer/codeready-workspaces.git  
$ cd codeready-workspaces  
$ git checkout crw-2.10-rhel-8
```

2. Build offline plug-in registry image:

```
$ cd dependencies/che-plugin-registry  
$ ./build.sh --organization <my-org> \  
  --registry <my-registry> \  
  --tag <my-tag> \  
  --offline \  
  --skip-digest-generation
```

**NOTE**

To display full options for the **build.sh** script, use the **--help** parameter.

**Additional resources**

- [Customizing the registries.](#)

**5.3.3. Preparing an private registry**

## Prerequisites

- The **oc** tool is available.
- The **skopeo** tool, version 0.1.40 or later, is available.
- The **podman** tool is available.
- An image registry accessible from the OpenShift cluster and supporting the format of the V2 image manifest, schema version 2. Ensure you can push to it from a location having, at least temporarily, access to the internet.

Table 5.1. Placeholders used in examples

<b>&lt;source-image&gt;</b>	Full coordinates of the source image, including registry, organization, and digest.
<b>&lt;target-registry&gt;</b>	Host name and port of the target container-image registry.
<b>&lt;target-organization&gt;</b>	Organization in the target container-image registry
<b>&lt;target-image&gt;</b>	Image name and digest in the target container-image registry.
<b>&lt;target-user&gt;</b>	User name in the target container-image registry.
<b>&lt;target-password&gt;</b>	User password in the target container-image registry.

## Procedure

1. Log into the internal image registry:

```
$ podman login --username <user> --password <password> <target-registry>
```



### NOTE

If you encounter an error, like **x509: certificate signed by unknown authority**, when attempting to push to the internal registry, try one of these workarounds:

- add the OpenShift cluster's certificate to **/etc/containers/certs.d/<target-registry>**
- add the registry as an insecure registry by adding the following lines to the Podman configuration file located at **/etc/containers/registries.conf**:

```
[registries.insecure]
registries = ['<target-registry>']
```

2. Copy images without changing their digest. Repeat this step for every image in the following table:

```
$ skopeo copy --all docker://<source-image> docker://<target-registry>/<target-organization>/<target-image>
```



**NOTE**

Table 5.2. Understanding the usage of the container-images from the prefix or keyword they include in their name

Usage	Prefix or keyword
Essential	not <b>stacks-</b> , <b>plugin-</b> , or <b>-openj9-</b>
Workspaces	<b>stacks-</b> , <b>plugin-</b>
IBM Z and IBM Power Systems	<b>-openj9-</b>

**NOTE**

Images suffixed with **openj9** are the **Eclipse OpenJ9** image equivalents of the OpenJDK images used on x86\_64. IBM Power Systems and IBM Z use Eclipse OpenJ9 for better performance on those systems.

Table 5.3. Images to copy in the private registry

<source-image>	<target-image>
registry.redhat.io/codeready-workspaces/configbump-rhel8@sha256:df90e683ef3141ea5e5ba77e4346285685be527a35073855c936c6237e91a1a8	configbump-rhel8@sha256:df90e683ef3141ea5e5ba77e4346285685be527a35073855c936c6237e91a1a8
registry.redhat.io/codeready-workspaces/crw-2-rhel8-operator@sha256:eac1db6b4008ba849d4bcab9acc8542806b2aeda8a5a5f4b3c56fb87129d8e54	crw-2-rhel8-operator@sha256:eac1db6b4008ba849d4bcab9acc8542806b2aeda8a5a5f4b3c56fb87129d8e54
registry.redhat.io/codeready-workspaces/dashboard-rhel8@sha256:d6911d22200677aa0116f4523d325e5630b300788ee55fd2ba3b709714901d34	dashboard-rhel8@sha256:d6911d22200677aa0116f4523d325e5630b300788ee55fd2ba3b709714901d34
registry.redhat.io/codeready-workspaces/devfileregistry-rhel8@sha256:1bbe4ccc6ad751bedcf30f6db38180a02730de32e36195be804e610ae2c636d7	devfileregistry-rhel8@sha256:1bbe4ccc6ad751bedcf30f6db38180a02730de32e36195be804e610ae2c636d7

<source-image>	<target-image>
registry.redhat.io/codeready-workspaces/devworkspace-controller-rhel8@sha256:ee3e6abf41fe504ef7c6c76a904542da0e22af242f2cd2007d3899e72fc17dab	devworkspace-controller-rhel8@sha256:ee3e6abf41fe504ef7c6c76a904542da0e22af242f2cd2007d3899e72fc17dab
registry.redhat.io/codeready-workspaces/devworkspace-rhel8@sha256:832ebf337003084ea649244b331bcc5442dae90f5ad5a0c83b2cc15e68b29fdf	devworkspace-rhel8@sha256:832ebf337003084ea649244b331bcc5442dae90f5ad5a0c83b2cc15e68b29fdf
registry.redhat.io/codeready-workspaces/jwtproxy-rhel8@sha256:c62c57ceb4b5f78eb62e43ee59e580e7df8cbe6e75a4e59ce344ea2c885c7129	jwtproxy-rhel8@sha256:c62c57ceb4b5f78eb62e43ee59e580e7df8cbe6e75a4e59ce344ea2c885c7129
registry.redhat.io/codeready-workspaces/machineexec-rhel8@sha256:56573ec2092ba1b4339e5ae9e9c128bb48c6ef08f95512fb7e12b6d732624899	machineexec-rhel8@sha256:56573ec2092ba1b4339e5ae9e9c128bb48c6ef08f95512fb7e12b6d732624899
registry.redhat.io/codeready-workspaces/plugin-java11-openj9-rhel8@sha256:adf7aedb113fda38db621f2660246ea011d5b25ce77734db406888545b194daf	plugin-java11-openj9-rhel8@sha256:adf7aedb113fda38db621f2660246ea011d5b25ce77734db406888545b194daf
registry.redhat.io/codeready-workspaces/plugin-java11-rhel8@sha256:f90e09397caa4dd5cd3476e495adfc0096272c0ba746a6e32215175c541ae058	plugin-java11-rhel8@sha256:f90e09397caa4dd5cd3476e495adfc0096272c0ba746a6e32215175c541ae058
registry.redhat.io/codeready-workspaces/plugin-java8-openj9-rhel8@sha256:f3dd1d9b76591a9aaeb34c609150db0775443d7db2db5593135cf5c8ee8729f8	plugin-java8-openj9-rhel8@sha256:f3dd1d9b76591a9aaeb34c609150db0775443d7db2db5593135cf5c8ee8729f8
registry.redhat.io/codeready-workspaces/plugin-java8-rhel8@sha256:1f5ac84a66454ab4b7b31cb259d30d1a5675dd5a342c9c7dfc536846c8d9a9b1	plugin-java8-rhel8@sha256:1f5ac84a66454ab4b7b31cb259d30d1a5675dd5a342c9c7dfc536846c8d9a9b1

<source-image>	<target-image>
<p>registry.redhat.io/codeready-workspaces/plugin-kubernetes-rhel8@sha256:82e5e4cc40a458b4ea3d7e070945532cbf6a2f3ae966a68b50fe4cd74348c283</p>	<p>plugin-kubernetes-rhel8@sha256:82e5e4cc40a458b4ea3d7e070945532cbf6a2f3ae966a68b50fe4cd74348c283</p>
<p>registry.redhat.io/codeready-workspaces/plugin-openshift-rhel8@sha256:00aeb2293b02a8875ca996b3b02cf7ece516fe5c254ce83ade8fa3648afb6a56</p>	<p>plugin-openshift-rhel8@sha256:00aeb2293b02a8875ca996b3b02cf7ece516fe5c254ce83ade8fa3648afb6a56</p>
<p>registry.redhat.io/codeready-workspaces/pluginbroker-artifacts-rhel8@sha256:0e6b054323fd8cfca3171fa5aaa25f48b1d4ebd098ca63e71d7f0a379e2a51a1</p>	<p>pluginbroker-artifacts-rhel8@sha256:0e6b054323fd8cfca3171fa5aaa25f48b1d4ebd098ca63e71d7f0a379e2a51a1</p>
<p>registry.redhat.io/codeready-workspaces/pluginbroker-metadata-rhel8@sha256:ca8ba32dd8c789cf4a384bf4bf1c63d845b370b7b1249dbbc0b7ebd1aab6437d</p>	<p>pluginbroker-metadata-rhel8@sha256:ca8ba32dd8c789cf4a384bf4bf1c63d845b370b7b1249dbbc0b7ebd1aab6437d</p>
<p>registry.redhat.io/codeready-workspaces/pluginregistry-rhel8@sha256:51f0aaf0f0967b7a986e8690b50a552a06a349cd2c24bfbfa1dbf6d7fb81f6e5</p>	<p>pluginregistry-rhel8@sha256:51f0aaf0f0967b7a986e8690b50a552a06a349cd2c24bfbfa1dbf6d7fb81f6e5</p>
<p>registry.redhat.io/codeready-workspaces/server-rhel8@sha256:591f23a2db6e6ced7bad91e33d2492bf796d8bad2f545dc17c79d23a39657b28</p>	<p>server-rhel8@sha256:591f23a2db6e6ced7bad91e33d2492bf796d8bad2f545dc17c79d23a39657b28</p>
<p>registry.redhat.io/codeready-workspaces/stacks-cpp-rhel8@sha256:4bd93c6fbd77acf07f2206fe76d9e8589f453aa219302c9b4ad0e80ca6180dce</p>	<p>stacks-cpp-rhel8@sha256:4bd93c6fbd77acf07f2206fe76d9e8589f453aa219302c9b4ad0e80ca6180dce</p>
<p>registry.redhat.io/codeready-workspaces/stacks-dotnet-rhel8@sha256:581d3da4bf1fe4467d688cd4390e958dc15f07b530845298c3fbc18bfdc033a</p>	<p>stacks-dotnet-rhel8@sha256:581d3da4bf1fe4467d688cd4390e958dc15f07b530845298c3fbc18bfdc033a</p>

<source-image>	<target-image>
<p>registry.redhat.io/codeready-workspaces/stacks-golang-rhel8@sha256:a4c848642e5cbd2e503915932c27342c94904763caa9085a866cb39c7e443335</p>	<p>stacks-golang-rhel8@sha256:a4c848642e5cbd2e503915932c27342c94904763caa9085a866cb39c7e443335</p>
<p>registry.redhat.io/codeready-workspaces/stacks-php-rhel8@sha256:a3fc9a39225136f735660830787fdb84531db4481665a26e5be21e4534b6bac0</p>	<p>stacks-php-rhel8@sha256:a3fc9a39225136f735660830787fdb84531db4481665a26e5be21e4534b6bac0</p>
<p>registry.redhat.io/codeready-workspaces/theia-endpoint-rhel8@sha256:e19ab58d0bb1b4f39ff3f66edd2138fed76b8feae5db78acee0e364936a73827</p>	<p>theia-endpoint-rhel8@sha256:e19ab58d0bb1b4f39ff3f66edd2138fed76b8feae5db78acee0e364936a73827</p>
<p>registry.redhat.io/codeready-workspaces/theia-rhel8@sha256:1e77ab29f9a72ce94ae40670499c3823048cfdb4fe7de0707adeffd7274f78c9</p>	<p>theia-rhel8@sha256:1e77ab29f9a72ce94ae40670499c3823048cfdb4fe7de0707adeffd7274f78c9</p>
<p>registry.redhat.io/codeready-workspaces/traefik-rhel8@sha256:983abe532ec2d8741d326dd3cd2a4678ba82a3d4e71d77f02bf39d92a8ba3303</p>	<p>traefik-rhel8@sha256:983abe532ec2d8741d326dd3cd2a4678ba82a3d4e71d77f02bf39d92a8ba3303</p>
<p>registry.redhat.io/jboss-eap-7/eap-xp2-openj9-11-openshift-rhel8@sha256:3f2de8176fb0b0e996fb1051d4244b4720014e0767b60e4b815ef0f7ec33dec9</p>	<p>eap-xp2-openj9-11-openshift-rhel8@sha256:3f2de8176fb0b0e996fb1051d4244b4720014e0767b60e4b815ef0f7ec33dec9</p>
<p>registry.redhat.io/jboss-eap-7/eap-xp2-openjdk11-openshift-rhel8@sha256:647d092383a760edc083eafb2d7bc3208d6409097281bedbd5eaccde360e7e39</p>	<p>eap-xp2-openjdk11-openshift-rhel8@sha256:647d092383a760edc083eafb2d7bc3208d6409097281bedbd5eaccde360e7e39</p>
<p>registry.redhat.io/jboss-eap-7/eap73-openjdk8-openshift-rhel7@sha256:d16cfe30eaf20a157cd5d5980a6c34f3fcbcf2fd225e670a0138d81007dd919</p>	<p>eap73-openjdk8-openshift-rhel7@sha256:d16cfe30eaf20a157cd5d5980a6c34f3fcbcf2fd225e670a0138d81007dd919</p>

<source-image>	<target-image>
registry.redhat.io/rh-ss0-7/sso74-openshift-rhel8@sha256:eb5110c22109412b5101f95d353603c7e3080844ee48f89186f139be5b5faa42	sso74-openshift-rhel8@sha256:eb5110c22109412b5101f95d353603c7e3080844ee48f89186f139be5b5faa42
registry.redhat.io/rh-ss0-7/sso74-openshift-rhel8@sha256:05f97328bafa615ceca025a6a93051a1ecdc08ae6123a78bf6ce56096f2ad233	sso74-openshift-rhel8@sha256:05f97328bafa615ceca025a6a93051a1ecdc08ae6123a78bf6ce56096f2ad233
registry.redhat.io/rhel8/postgresql-96@sha256:33643fb4caffacb277982c6098b561aa80c06210e77d2badebef405ee953e43	postgresql-96@sha256:33643fb4caffacb277982c6098b561aa80c06210e77d2badebef405ee953e43
registry.redhat.io/rhsc1/mongodb-36-rhel7@sha256:9f799d356d7d2e442bde9d401b720600fd9059a3d8eefea6f3b2ffa721c0dc73	mongodb-36-rhel7@sha256:9f799d356d7d2e442bde9d401b720600fd9059a3d8eefea6f3b2ffa721c0dc73
registry.redhat.io/ubi8/ubi-minimal@sha256:d9b92ea78e76300968f5c9a4a04c2cf220a0bbfac667f77e5e7287692163d898	ubi8ubi-minimal@sha256:d9b92ea78e76300968f5c9a4a04c2cf220a0bbfac667f77e5e7287692163d898

### Verification steps

- Verify the images have the same digests:

```
$ skopeo inspect docker://<source-image>
$ skopeo inspect docker://<target-registry>/<target-organization>/<target-image>
```

### Additional resources

- To find the sources of the images list, see the values of the **relatedImages** attribute in the link:
  - [CodeReady Workspaces Operator ClusterServiceVersion sources](#).

## 5.3.4. Upgrading CodeReady Workspaces using the CLI management tool in restricted environment

This section describes how to upgrade Red Hat CodeReady Workspaces using the CLI management tool in restricted environment.

### Prerequisites

- An administrative account on an OpenShift instance.

- A running instance version 2.9 of Red Hat CodeReady Workspaces, installed using the CLI management tool on the same instance of OpenShift, with the `crwctl --installer operator` method, in the `<openshift-workspaces>` project. See [Section 3.4, “Installing CodeReady Workspaces in a restricted environment”](#).
- Essential container images are available to the CodeReady Workspaces server running in the cluster. See [Section 5.3.3, “Preparing a private registry”](#).
- The `crwctl` 2.10 management tool is available. See [Section 3.3.1, “Installing the crwctl CLI management tool”](#).

## Procedure

1. In all running workspaces in the CodeReady Workspaces 2.9 instance, save and push changes back to the Git repositories.
2. Stop all workspaces in the CodeReady Workspaces 2.9 instance.
3. Run the following command:

```
$ crwctl server:update --che-operator-image=<image-registry>/<organization>/crw-2-rhel8-operator:2.10 -n openshift-workspaces
```

- `<image-registry>`: A host name and a port of the container-image registry accessible in the restricted environment.
- `<organization>`: An organization of the container-image registry. See: [Section 5.3.3, “Preparing a private registry”](#).

## Verification steps

1. Navigate to the CodeReady Workspaces instance.
2. The 2.10 version number is visible at the bottom of the page.



### NOTE

For slow systems or internet connections, add the `--k8spodwaittimeout=1800000` flag option to the `crwctl server:update` command to extend the Pod timeout period to 1800000 ms or longer.

## 5.4. UPGRADING CODEREADY WORKSPACES THAT USES PROJECT STRATEGIES OTHER THAN 'PER USER'

This section describes how to upgrade CodeReady Workspaces that uses project strategies other than 'per user'.

CodeReady Workspaces intends to use Kubernetes secrets as a storage for all sensitive user data. One project per user simplifies the design of the workspaces. This is the reason why project strategies other than **per user** become deprecated. The deprecation process happens in two steps. In the **First Step** project strategies other than **per user** are allowed but not recommended. In the **Second Step** support for project strategies other than **per user** is going to be removed.

**NOTE**


No automated upgrade support exists between **First Step** and **Second Step** for the installations where project strategies other than **per user** are used without losing data.

**Prerequisites**

- CodeReady Workspaces configured with the project strategies other than **per user**.
- Intention to use CodeReady Workspaces configured with the **per user** namespace strategies **per user**.

**5.4.1. Upgrading CodeReady Workspaces and backing up user data****Procedure**

1. Notify all CodeReady Workspaces users about the upcoming data wipe.

**NOTE**

To back up the data, you can commit workspace configuration to an SCM server and use factories to restore it later.

2. Re-install CodeReady Workspaces with **per user** namespace strategy.

**5.4.2. Upgrading CodeReady Workspaces and losing user data**

When CodeReady Workspaces is upgraded and user data is not backed up, workspace configuration and user preferences are going to be preserved but all runtime data will be wiped out.

**Procedure**

1. Notify all CodeReady Workspaces users about the upcoming data wipe.
2. Change project strategy to **per user**.

**NOTE**

Upgrading without backing up user data has disadvantage. Original PVs with runtime data are going to be preserved and will no longer be used. This may lead to the waste of resources.

**Additional resources**

- [Section 4.2, "Configuring workspace target project"](#)
- [Chapter 3, \*Installing CodeReady Workspaces\*](#)
- [Creating a workspace from code sample](#)
- [Creating a workspace by importing the source code of a project](#)

## CHAPTER 6. UNINSTALLING CODEREADY WORKSPACES

This section describes uninstallation procedures for Red Hat CodeReady Workspaces. The uninstallation process leads to a complete removal of CodeReady Workspaces-related user data. The method previously used to install the CodeReady Workspaces instance determines the uninstallation method.

- For CodeReady Workspaces installed using OperatorHub, for the OpenShift Web Console method see [Section 6.1, “Uninstalling CodeReady Workspaces after OperatorHub installation using the OpenShift web console”](#).
- For CodeReady Workspaces installed using OperatorHub, for the CLI method see [Section 6.2, “Uninstalling CodeReady Workspaces after OperatorHub installation using OpenShift CLI”](#).
- For CodeReady Workspaces installed using `crwctl`, see [Section 6.3, “Uninstalling CodeReady Workspaces after `crwctl` installation”](#)

### 6.1. UNINSTALLING CODEREADY WORKSPACES AFTER OPERATORHUB INSTALLATION USING THE OPENSIFT WEB CONSOLE


This section describes how to uninstall CodeReady Workspaces from a cluster using the OpenShift Administrator Perspective main menu.

#### Prerequisites

- CodeReady Workspaces was installed on an OpenShift cluster using OperatorHub.

#### Procedure

1. Navigate to the OpenShift web console and select the Administrator Perspective.
2. In the **Home** > **Projects** section, navigate to the project containing the CodeReady Workspaces instance.



#### NOTE

The default project name is `<openshift-workspaces>`.

3. In the **Operators** > **Installed Operators** section, click **Red Hat CodeReady Workspaces** in the list of installed operators.
4. In the **Red Hat CodeReady Workspaces Cluster** tab, click the displayed Red Hat CodeReady Workspaces Cluster, and select the **Delete cluster** option in the **Actions** drop-down menu on the top right.



#### NOTE

The default Red Hat CodeReady Workspaces Cluster name is `<red-hat-codeready-workspaces>`.

5. In the **Operators** > **Installed Operators** section, click **Red Hat CodeReady Workspaces** in the list of installed operators and select the **Uninstall Operator** option in the **Actions** drop-down menu on the top right.



- In the **Home > Projects** section, navigate to the project containing the CodeReady Workspaces instance, and select the **Delete Project** option in the **Actions** drop-down menu on the top right.

## 6.2. UNINSTALLING CODEREADY WORKSPACES AFTER OPERATORHUB INSTALLATION USING OPENSIFT CLI

This section provides instructions on how to uninstall a CodeReady Workspaces instance using **oc** commands.

### Prerequisites

- CodeReady Workspaces was installed on an OpenShift cluster using OperatorHub.
- The **oc** tool is available.

### Procedure

The following procedure provides command-line outputs as examples. Note that output in the user terminal may differ.

To uninstall a CodeReady Workspaces instance from a cluster:

- Sign in to the cluster:

```
$ oc login -u <username> -p <password> <cluster_URL>
```

- Switch to the project where the CodeReady Workspaces instance is deployed:

```
$ oc project <codeready-workspaces_project>
```

- Obtain the CodeReady Workspaces cluster name. The following shows a cluster named **red-hat-codeready-workspaces**:

```
$ oc get checluster
NAME          AGE
red-hat-codeready-workspaces 27m
```

- Delete the CodeReady Workspaces cluster:

```
$ oc delete checluster red-hat-codeready-workspaces
checluster.org.eclipse.che "red-hat-codeready-workspaces" deleted
```

- Obtain the name of the CodeReady Workspaces cluster service version (CSV) module. The following detects a CSV module named **red-hat-codeready-workspaces.v2.10**:

```
$ oc get csv
NAME                                DISPLAY          VERSION  REPLACES          PHASE
red-hat-codeready-workspaces.v2.10  Red Hat CodeReady Workspaces 2.10    red-hat-codeready-workspaces.v2.9  Succeeded
```

- Delete the CodeReady Workspaces CSV:

```
$ oc delete csv red-hat-codeready-workspaces.v2.10
clusterserviceversion.operators.coreos.com "red-hat-codeready-workspaces.v2.10" deleted
```

## 6.3. UNINSTALLING CODEREADY WORKSPACES AFTER CRWCTL INSTALLATION

This section describes how to uninstall an instance of Red Hat CodeReady Workspaces that was installed using the **crwctl** tool.

### Prerequisites

- The **crwctl** tool is available.
- The **oc** tool is available.
- The **crwctl** tool installed the CodeReady Workspaces instance on OpenShift.

### Procedure

1. Sign in to the OpenShift cluster:

```
$ oc login -u <username> -p <password> <cluster_URL>
```

2. Export the name of the CodeReady Workspaces namespace to remove:

```
$ export codereadyNamespace=<codeready-namespace-to-remove>
```

3. Export your user access token and Keycloak URLs:

```
$ export KEYCLOAK_BASE_URL="http://$KEYCLOAK_URL/auth"
```

```
$ export USER_ACCESS_TOKEN=$(curl -X POST
$KEYCLOAK_BASE_URL/realms/codeready/protocol/openid-connect/token \
-H "Content-Type: application/x-www-form-urlencoded" \
-d "username=admin" \
-d "password=admin" \
-d "grant_type=password" \
-d "client_id=codeready-public" | jq -r .access_token)
```

4. Stop the server using the UAT:

```
$ crwctl/bin/crwctl server:stop -n "$codereadyNamespace" --access-
token=$USER_ACCESS_TOKEN
```

5. Delete your project and your CodeReady Workspaces deployment:

```
$ oc project "$codereadyNamespace"
```

```
$ oc delete deployment codeready-operator
```

```
$ oc delete checluster codeready-workspaces
```

```
$ oc delete project "$codereadyNamespace"
```

6. Verify that the removal was successful by listing the information about the project:

```
$ oc describe project "$codereadyNamespace"
```

7. Remove a specified **ClusterRoleBinding**:

```
$ oc delete clusterrolebinding codeready-operator
```