



OpenJDK 8

Packaging OpenJDK 8 applications in containers

Legal Notice

Copyright © 2021 Red Hat, Inc.

The text of and illustrations in this document are licensed by Red Hat under a Creative Commons Attribution–Share Alike 3.0 Unported license ("CC-BY-SA"). An explanation of CC-BY-SA is available at

<http://creativecommons.org/licenses/by-sa/3.0/>

. In accordance with CC-BY-SA, if you distribute this document or an adaptation of it, you must provide the URL for the original version.

Red Hat, as the licensor of this document, waives the right to enforce, and agrees not to assert, Section 4d of CC-BY-SA to the fullest extent permitted by applicable law.

Red Hat, Red Hat Enterprise Linux, the Shadowman logo, the Red Hat logo, JBoss, OpenShift, Fedora, the Infinity logo, and RHCE are trademarks of Red Hat, Inc., registered in the United States and other countries.

Linux[®] is the registered trademark of Linus Torvalds in the United States and other countries.

Java[®] is a registered trademark of Oracle and/or its affiliates.

XFS[®] is a trademark of Silicon Graphics International Corp. or its subsidiaries in the United States and/or other countries.

MySQL[®] is a registered trademark of MySQL AB in the United States, the European Union and other countries.

Node.js[®] is an official trademark of Joyent. Red Hat is not formally related to or endorsed by the official Joyent Node.js open source or commercial project.

The OpenStack[®] Word Mark and OpenStack logo are either registered trademarks/service marks or trademarks/service marks of the OpenStack Foundation, in the United States and other countries and are used with the OpenStack Foundation's permission. We are not affiliated with, endorsed or sponsored by the OpenStack Foundation, or the OpenStack community.

All other trademarks are the property of their respective owners.

Abstract

OpenJDK is a Red Hat offering on the Red Hat Enterprise Linux platform. The Packaging OpenJDK 8 applications in containers guide provides an overview of this product and explains how to package the applications in a container.

Table of Contents

MAKING OPEN SOURCE MORE INCLUSIVE	3
PROVIDING FEEDBACK ON RED HAT DOCUMENTATION	4
CHAPTER 1. OPENJDK APPLICATIONS IN CONTAINERS	5
CHAPTER 2. DEPLOYING OPENJDK APPLICATIONS IN CONTAINERS	6
CHAPTER 3. UPDATING OPENJDK CONTAINER IMAGES	7

MAKING OPEN SOURCE MORE INCLUSIVE

Red Hat is committed to replacing problematic language in our code, documentation, and web properties. We are beginning with these four terms: master, slave, blacklist, and whitelist. Because of the enormity of this endeavor, these changes will be implemented gradually over several upcoming releases. For more details, see [our CTO Chris Wright's message](#).

PROVIDING FEEDBACK ON RED HAT DOCUMENTATION

We appreciate your feedback on our documentation. To provide feedback, you can highlight the text in a document and add comments.

This section explains how to submit feedback.


Prerequisites

- You are logged in to the Red Hat Customer Portal.
- In the Red Hat Customer Portal, view the document in **Multi-page HTML** format.

Procedure

To provide your feedback, perform the following steps:

1. Click the **Feedback** button in the top-right corner of the document to see existing feedback.



NOTE

The feedback feature is enabled only in the **Multi-page HTML** format.

2. Highlight the section of the document where you want to provide feedback.
3. Click the **Add Feedback** pop-up that appears near the highlighted text.
A text box appears in the feedback section on the right side of the page.
4. Enter your feedback in the text box and click **Submit**.
A documentation issue is created.
5. To view the issue, click the issue tracker link in the feedback view.

CHAPTER 1. OPENJDK APPLICATIONS IN CONTAINERS

OpenJDK images have default startup scripts that automatically detect application **JAR** files and launch Java. The script's behavior can be customized using environment variables. For more information, see **/help.md** in the container.

The OpenJDK applications in the **/deployments** directory of the OpenJDK image are run when the image loads.



NOTE

Containers that contain OpenJDK applications are not automatically updated with security updates. Ensure that you update these images at least once every three months.

Application **JAR** files can be fat JARs or thin JARs.

- Fat JARs contain all of the application's dependencies.
- Thin JARs reference other JARs that contain some, or all, of the application's dependencies. Thin JARs are only supported if:
 - They have a flat classpath.
 - All dependencies are JARs that are in the **/deployments** directory.

CHAPTER 2. DEPLOYING OPENJDK APPLICATIONS IN CONTAINERS

You can deploy OpenJDK applications in containers and have them run when the container is loaded.

Procedure

- Copy the application **JAR** to the **/deployments** directory in the image **JAR** file.
For example, the following shows a brief Dockerfile that adds an application called **testubi.jar** to the OpenJDK 8 UBI8 image:

```
FROM registry.access.redhat.com/ubi8/openjdk-8
```

```
COPY target/testubi.jar /deployments/testubi.jar
```

CHAPTER 3. UPDATING OPENJDK CONTAINER IMAGES

To ensure that an OpenJDK container with Java applications includes the latest security updates, rebuild the container.

Procedure

1. Pull the base OpenJDK image.
2. Deploy the OpenJDK application. For more information, see [Deploying OpenJDK applications in containers](#).
The OpenJDK container with the OpenJDK application is updated.

Additional resources

- For more information, see [Red Hat OpenJDK Container images](#) .