



# Red Hat Ceph Storage 3

## Monitoring Ceph with Datadog

Guide on Monitoring Ceph with Datadog



# Red Hat Ceph Storage 3 Monitoring Ceph with Datadog

---

Guide on Monitoring Ceph with Datadog

## Legal Notice

Copyright © 2021 Red Hat, Inc.

The text of and illustrations in this document are licensed by Red Hat under a Creative Commons Attribution–Share Alike 3.0 Unported license ("CC-BY-SA"). An explanation of CC-BY-SA is available at

<http://creativecommons.org/licenses/by-sa/3.0/>

. In accordance with CC-BY-SA, if you distribute this document or an adaptation of it, you must provide the URL for the original version.

Red Hat, as the licensor of this document, waives the right to enforce, and agrees not to assert, Section 4d of CC-BY-SA to the fullest extent permitted by applicable law.

Red Hat, Red Hat Enterprise Linux, the Shadowman logo, the Red Hat logo, JBoss, OpenShift, Fedora, the Infinity logo, and RHCE are trademarks of Red Hat, Inc., registered in the United States and other countries.

Linux<sup>®</sup> is the registered trademark of Linus Torvalds in the United States and other countries.

Java<sup>®</sup> is a registered trademark of Oracle and/or its affiliates.

XFS<sup>®</sup> is a trademark of Silicon Graphics International Corp. or its subsidiaries in the United States and/or other countries.

MySQL<sup>®</sup> is a registered trademark of MySQL AB in the United States, the European Union and other countries.

Node.js<sup>®</sup> is an official trademark of Joyent. Red Hat is not formally related to or endorsed by the official Joyent Node.js open source or commercial project.

The OpenStack<sup>®</sup> Word Mark and OpenStack logo are either registered trademarks/service marks or trademarks/service marks of the OpenStack Foundation, in the United States and other countries and are used with the OpenStack Foundation's permission. We are not affiliated with, endorsed or sponsored by the OpenStack Foundation, or the OpenStack community.

All other trademarks are the property of their respective owners.

## Abstract

This document provides information on monitoring the status of the Ceph Storage cluster with the Datadog monitoring tool.

---

## Table of Contents

|   |    |
|---|----|
| CHAPTER 1. INTRODUCTION .....                           | 3  |
| CHAPTER 2. INSTALLING THE CEPH INTEGRATION .....        | 4  |
| CHAPTER 3. CONFIGURING THE DATADOG AGENT FOR CEPH ..... | 6  |
| CHAPTER 4. MONITORING CEPH WITH DATADOG .....           | 8  |
| CHAPTER 5. CEPH METRICS .....                           | 9  |
| CHAPTER 6. CREATE AN ALERT .....                        | 11 |



# CHAPTER 1. INTRODUCTION

The [Datadog](#) integration with Ceph allows Datadog to execute and process the output from:

- **ceph status**
- **ceph health detail**
- **ceph df detail**
- **ceph osd perf**; and,
- **ceph osd pool stats**.

The integration enables Datadog to:

- Monitor the status and health of the Ceph Storage cluster
- Monitor I/O and performance metrics; and,
- Track disk usage across storage pools.

Using [Datadog](#) to monitor Ceph requires installing a Datadog agent on at least one Ceph monitor node. When monitoring Ceph, the Datadog agent will execute Ceph command line arguments. Consequently, each Ceph node must have an appropriate Ceph key providing access to the cluster, usually in `/etc/ceph`. Once the agent executes the Ceph command, it sends Ceph cluster status and statistics back to Datadog. Then, Datadog will present the status and statistics in the Datadog user interface.

Since Datadog uses an agent, the Ceph cluster must be able to reach the internet; however, the Ceph cluster does not have to be reachable from the internet.



## NOTE

Datadog supports retrieving **ceph status** with RHCS 2. Datadog will provide an update to support **ceph status** for RHCS 3 in a subsequent release of its **dd-agent**.




## IMPORTANT

Red Hat works with our technology partners to provide this documentation as a service to our customers. However, Red Hat does not provide support for this product. If you need technical assistance for this product, then contact Datadog for support.


## CHAPTER 2. INSTALLING THE CEPH INTEGRATION

To install the Ceph integration, log in to the [Datadog App](#). The user interface will present navigation on the left side of the screen. Click **Integrations**. Either enter **ceph** into the search field or scroll to find the Ceph integration. The user interface will present whether the Ceph integration is *available* or already *installed*. If it is *available*, click the button to install it.



### Installing the Datadog Agent for Ceph


To install the Datadog agent for Red Hat Ceph Storage, log in to the [Datadog App](#). The user interface will present navigation on the left side of the screen. Click **Integrations**. To install the agent from the command line, click on the **Agent** tab at the top of the screen.



For Red Hat Ceph Storage on RHEL 7 or Ubuntu 16.04, open a command line. Then, enter the one-step command line agent installation. For example:

```
# DD_API_KEY=<key-string> bash -c "$(curl -L https://raw.githubusercontent.com/DataDog/dd-agent/master/packaging/datadog-agent/source/install_agent.sh)"
```



**NOTE**

Copy the example from the Datadog user interface, as the key differs from the example above and with each user account.

## CHAPTER 3. CONFIGURING THE DATADOG AGENT FOR CEPH

After installing the Datadog agent, configure the Datadog agent to report Ceph metrics to Datadog.

1. Navigate to the Datadog Agent configuration directory.

```
# cd /etc/dd-agent/conf.d
```

2. Create a **ceph.yaml** file from the **ceph.yaml.sample** file.

```
# cp ceph.yaml.example ceph.yaml
```

3. Modify the **ceph.yaml** file.

```
# vim ceph.yaml
```

It will look like this:

```
init_config:

instances:
# - tags:
# - name:mars_cluster
#
# ceph_cmd: /usr/bin/ceph
# ceph_cluster: ceph
#
# If your environment requires sudo, please add a line like:
# dd-agent ALL=(ALL) NOPASSWD:/usr/bin/ceph
# to your sudoers file, and uncomment the below option.
#
# use_sudo: True
```

Uncomment the `-tags`, `-name`, `ceph_command` and `ceph_cluster` lines. The default values for `ceph_command` and `ceph_cluster` are `/usr/bin/ceph` and `ceph` respectively. For RHEL 7, uncomment `use_sudo: True`; however, this step is optional for Ubuntu, since Ubuntu disables the root user and gives the initial admin user root permissions.

When complete, it will look like this:

```
init_config:

instances:
- tags:
- name:ceph-RHEL
#
ceph_cmd: /usr/bin/ceph
ceph_cluster: ceph
#
# If your environment requires sudo, please add a line like:
# dd-agent ALL=(ALL) NOPASSWD:/usr/bin/ceph
```

```
# to your sudoers file, and uncomment the below option.  
#  
use_sudo: True
```

4. For RHEL 7, modify the sudoers file.

```
# visudo
```

Add the following line.

```
dd-agent ALL=(ALL) NOPASSWD:/usr/bin/ceph
```



#### NOTE

For Ubuntu, if **ceph.yml** enables **use\_sudo: True**, perform this step, too.

5. Enable the Datadog agent so that it will restart if the Ceph host reboots.

```
# systemctl enable datadog-agent
```

6. Finally, restart the Datadog agent.

```
# systemctl status datadog-agent
```



## CHAPTER 5. CEPH METRICS

The Datadog agent collects the following metrics from Ceph. These metrics may be included in custom dashboards and in alerts.


| Metric Name                      | Description   |
|----------------------------------|---|
| <b>ceph.commit_latency_ms</b>    | The time taken to commit an operation to the journal.   |
| <b>ceph.apply_latency_ms</b>     | Time taken to flush an update to disks.                 |
| <b>ceph.op_per_sec</b>           | The number of I/O operations per second for given pool. |
| <b>ceph.read_bytes_sec</b>       | The bytes per second being read.                        |
| <b>ceph.write_bytes_sec</b>      | The bytes per second being written.                     |
| <b>ceph.num_osds</b>             | The number of known storage daemons.                    |
| <b>ceph.num_in_osds</b>          | The number of participating storage daemons.            |
| <b>ceph.num_up_osds</b>          | The number of online storage daemons.                   |
| <b>ceph.num_pgs</b>              | The number of placement groups available.               |
| <b>ceph.num_mons</b>             | The number of monitor daemons.                          |
| <b>ceph.aggregate_pct_used</b>   | The overall capacity usage metric.                      |
| <b>ceph.total_objects</b>        | The object count from the underlying object store.      |
| <b>ceph.num_objects</b>          | The object count for a given pool.                      |
| <b>ceph.read_bytes</b>           | The per-pool read bytes.                                |
| <b>ceph.write_bytes</b>          | The per-pool write bytes.                               |
| <b>ceph.num_pools</b>            | The number of pools.                                    |
| <b>ceph.pgstate.active_clean</b> | The number of <b>active+clean</b> placement groups.     |
| <b>ceph.read_op_per_sec</b>      | The per-pool read operations per second.                |
| <b>ceph.write_op_per_sec</b>     | The per-pool write operations per second.               |
| <b>ceph.num_near_full_osds</b>   | The number of nearly full OSDs.                         |

| Metric Name               | Description                                    |
|---------------------------|--|
| <b>ceph.num_full_osds</b> | The number of full OSDs.                       |
| <b>ceph.osd.pct_used</b>  | The percentage used of full or near-full OSDs. |


## CHAPTER 6. CREATE AN ALERT

Administrators can create monitors that track the metrics of the Ceph cluster and generate alerts. For example, if an OSD is down, Datadog can alert an administrator that one or more OSDs are down.


Click **Monitors** to see an overview of the Datadog monitors.




To create a monitor, select **Monitors**→**New Monitor**. At step 1, select the detection method. For example, "Threshold Alert."



At step 2, define the metric. To create an advanced alert, click on the *Advanced...* link. Then, select a metric from the combo box. For example, select the **ceph.num\_in\_osds** Ceph metric. Then, click **Add Query+** to add another query.



Select another metric from the combo box. For example, select the **ceph.num\_up\_osds** Ceph metric.



In the **Express these queries as:** field, enter **a-b**, where **a** is the value of **ceph.num\_in\_osds** and **b** is the value of **ceph.num\_up\_osds**. When the difference is **1** or greater, there is at least one OSD down.

At step 3, set the alert conditions. For example, set the trigger to be **above or equal to**, the threshold to **in total** and the time elapsed to **1 minute**. Then, set the **Alert threshold** field to **1**. When at least one OSD is in the cluster and it is not up and running, the monitor will alert the user.

At step 4, give the monitor a title in the input field below **Preview** and **Edit**. This is required to save the monitor. Enter a description of the alert in the text field.



Note: We highly recommend you select "Do Not Require" for sparse metrics, otherwise some evaluations will be skipped.

Do not notify if data is missing.

Note: the missing data window must be at least 2x the evaluation period above to work

[Never] automatically resolve this event from a triggered state.

Delay evaluation by 0 seconds

### 4 Say what's happening

Use message template variables

Markdown supported

At least one OSD is down!

@jowilkin@redhat.com

At least one OSD is down. Restart it, or Ceph will begin backfilling shortly.

Service: Select or add related service

[Never] renotify if the monitor has not been resolved.

### 5 Notify your team

John Wilkins


Do not notify alert recipients when this alert is modified

Do not restrict editing this monitor to its creator or administrators

Export Monitor Save

Copyright Datadog, Inc. 2017 - 24. 101428 - Master Subscription Agreement - Privacy Policy - Cookie Policy - Status All Systems Operational

Chat with us!



## NOTE

The text field supports metric variables and Markdown syntax.

At step 5, add the recipients of the alert. This will add an email address to the text field of step 4. When the alert gets triggered, the recipients will receive the alert.