



Red Hat CodeReady Studio 12.19

Installation Guide

Installing Red Hat CodeReady Studio

Red Hat CodeReady Studio 12.19 Installation Guide

Installing Red Hat CodeReady Studio

Eva-Lotte Gebhardt
egebhard@redhat.com

Levi Valeeva
levi@redhat.com

Yana Hontyk
yhontyk@redhat.com

Legal Notice

Copyright © 2021 Red Hat, Inc.

The text of and illustrations in this document are licensed by Red Hat under a Creative Commons Attribution–Share Alike 3.0 Unported license ("CC-BY-SA"). An explanation of CC-BY-SA is available at

<http://creativecommons.org/licenses/by-sa/3.0/>

. In accordance with CC-BY-SA, if you distribute this document or an adaptation of it, you must provide the URL for the original version.

Red Hat, as the licensor of this document, waives the right to enforce, and agrees not to assert, Section 4d of CC-BY-SA to the fullest extent permitted by applicable law.

Red Hat, Red Hat Enterprise Linux, the Shadowman logo, the Red Hat logo, JBoss, OpenShift, Fedora, the Infinity logo, and RHCE are trademarks of Red Hat, Inc., registered in the United States and other countries.

Linux[®] is the registered trademark of Linus Torvalds in the United States and other countries.

Java[®] is a registered trademark of Oracle and/or its affiliates.

XFS[®] is a trademark of Silicon Graphics International Corp. or its subsidiaries in the United States and/or other countries.

MySQL[®] is a registered trademark of MySQL AB in the United States, the European Union and other countries.

Node.js[®] is an official trademark of Joyent. Red Hat is not formally related to or endorsed by the official Joyent Node.js open source or commercial project.

The OpenStack[®] Word Mark and OpenStack logo are either registered trademarks/service marks or trademarks/service marks of the OpenStack Foundation, in the United States and other countries and are used with the OpenStack Foundation's permission. We are not affiliated with, endorsed or sponsored by the OpenStack Foundation, or the OpenStack community.

All other trademarks are the property of their respective owners.

Abstract

This document describes the process of installing, upgrading, and uninstalling Red Hat CodeReady Studio.

Table of Contents

| | |
|--|-----------|
| MAKING OPEN SOURCE MORE INCLUSIVE | 3 |
| CHAPTER 1. MINIMAL REQUIREMENTS | 4 |
| CHAPTER 2. INSTALLING OPENJDK | 5 |
| 2.1. INSTALLING OPENJDK ON WINDOWS | 5 |
| 2.1.1. Additional resources | 5 |
| 2.2. INSTALLING OPENJDK ON RHEL | 5 |
| 2.2.1. Additional resources | 6 |
| CHAPTER 3. INSTALLING CODEREADY STUDIO | 7 |
| 3.1. INSTALLING CODEREADY STUDIO IN ECLIPSE | 7 |
| 3.1.1. Installing CodeReady Studio in Eclipse when online | 7 |
| 3.1.2. Installing CodeReady Studio in Eclipse when offline | 10 |
| 3.2. INSTALLING CODEREADY STUDIO STAND-ALONE USING THE INSTALLER | 12 |
| 3.3. PERFORMING ADVANCED INSTALLATION TASKS | 13 |
| 3.3.1. Installing CodeReady Studio using a script | 13 |
| 3.3.2. Building the CodeReady Studio stand-alone Installer from source | 13 |
| CHAPTER 4. UPGRADING CODEREADY STUDIO | 15 |
| 4.1. UPGRADING MAJOR VERSIONS OF CODEREADY STUDIO | 15 |
| 4.2. UPDATING MINOR VERSIONS OF RED HAT CODEREADY STUDIO | 15 |
| CHAPTER 5. UNINSTALLING CODEREADY STUDIO | 19 |
| 5.1. UNINSTALLING RED HAT CODEREADY STUDIO USING ECLIPSE | 19 |
| 5.2. UNINSTALLING CODEREADY STUDIO USING THE INSTALLER | 21 |
| CHAPTER 6. REPORTING ISSUES | 22 |

MAKING OPEN SOURCE MORE INCLUSIVE

Red Hat is committed to replacing problematic language in our code, documentation, and web properties. We are beginning with these four terms: master, slave, blacklist, and whitelist. Because of the enormity of this endeavor, these changes will be implemented gradually over several upcoming releases. For more details, see [our CTO Chris Wright's message](#).

CHAPTER 1. MINIMAL REQUIREMENTS

CodeReady Studio 12.19 is compatible with a range of operating systems, architectures, and Java Development Kit combinations. For a complete list, see [Supported Configurations and Components](#).

Hardware requirements

- 2 GB RAM
 - 4 GB RAM is **strongly** recommended.
- 2 GB hard disk space

Software requirements

- OpenJDK is installed.
 - Red Hat OpenJDK is **strongly** recommended.

Operating system requirements

- **For Linux (x86_64)**
 - Red Hat Enterprise Linux 7 or 8
 - Fedora 31 or 32
 - Ubuntu 20.04 LTS or 19.10
- **For Windows (x86_64)**
 - Microsoft Windows 8 or 10
- **For macOS (x86_64)**
 - Catalina (10.15) or Mojave (10.14)



NOTE

On Windows: If you want the CodeReady Studio instance to be available to all users, install it in a folder accessible to all users (**C:\codereadystudio**). If it is not possible for the given user to write this main installation folder, any newly installed features and updates will be saved inside the home directory of the user.

CHAPTER 2. INSTALLING OPENJDK

The following sections describe how to install OpenJDK on Microsoft Windows and Red Hat Enterprise Linux (RHEL).

2.1. INSTALLING OPENJDK ON WINDOWS

The following section describes how to install OpenJDK 11 on Windows using the MSI-based installer.

Procedure

1. Download the MSI-based Installer from the [Red Hat Developer Portal](#).
2. Run the installer and follow the on-screen installation instructions.
3. Configure CodeReady Studio to use OpenJDK by following the instructions for [Working with Java Runtime Environments](#).

2.1.1. Additional resources

- For more information on how to install OpenJDK 11, see the [Installing and Using OpenJDK 11 for Windows](#) Guide.

2.2. INSTALLING OPENJDK ON RHEL

The following section describes how to install OpenJDK 11 on RHEL.

Prerequisites

- **Root** access.
- A registered system with attached subscriptions.
For more information, see the [Registering the system and managing subscriptions](#) Guide.

Procedure

- To install OpenJDK RPMs, run:

```
# yum install java-11-openjdk-devel
```

Optionally, you can install the `java-11-openjdk-src` and the `java-11-openjdk-demo` packages. The `java-11-openjdk-src` package contains the complete OpenJDK 11 class library source code you can use with IDE indexers and debuggers. The `java-11-openjdk-demo` package contains Java runtimes for OpenJDK (demos and examples).

- To install `java-11-openjdk-demo` and `java-11-openjdk-src`, run:

```
# yum install java-11-openjdk-src java-11-openjdk-demo
```

Troubleshooting

If you encounter the following error message while attempting to log in to the OpenShift cluster, configure your Java to use TLSv1.2. This problem only occurs in Java JDK versions prior to Java 11.0.7 and OpenShift cluster 4.4.0 or higher.

Unable to execute request to request url https://<openshift-cluster-oauth-authorization-server>

- To configure Java to use TLSv1.2:
 1. Open the file **codereadystudio.ini** located in the **studio** directory inside of the CodeReady Studio installation directory.
 2. Add the following line under the **-vmargs** section:

```
    -Djdk.tls.client.protocols=TLSv1.2`
```

2.2.1. Additional resources

- For more information on how to install, run, and switch between two parallel installed major OpenJDK versions on RHEL8, see [How to install Java 8 and 11 on Red Hat Enterprise Linux 8](#) .

CHAPTER 3. INSTALLING CODEREADY STUDIO

The following section describes how to install CodeReady Studio:

- [Using Eclipse](#).
- [Using the Installer](#).
- [Using a script](#).
- [From source](#).

Note that you can have multiple versions of CodeReady Studio installed on your system with Installer or Eclipse, provided you have these versions located in different directories.

3.1. INSTALLING CODEREADY STUDIO IN ECLIPSE

CodeReady Studio for Eclipse packages the CodeReady Studio plug-ins for your existing Eclipse instance.

You can install CodeReady Studio from Eclipse Marketplace when you are online. This installation method is referred to as Bring Your Own Eclipse (BYOE).

Alternatively, you can use the **Update Site Zip** to install CodeReady Studio when you are offline.


The following sections describe how to install CodeReady Studio when online and offline.

3.1.1. Installing CodeReady Studio in Eclipse when online

The following section describes how to install CodeReady Studio BYOE from Eclipse Marketplace.


Procedure

1. Start the Eclipse IDE.
2. Click **Help** → **Eclipse Marketplace**.




The **Eclipse Marketplace** window appears.

3. Locate **Red Hat CodeReady Studio 12.19 GA**



Eclipse Marketplace x


Eclipse Marketplace 

Select solutions to install. Press Install Now to proceed with installation.
Press the "more info" link to learn more about a solution.

Search **Recent** Popular Favorites Installed Giving IoT an Edge

Find: All Markets v All Categories: v Go

Red Hat CodeReady Studio (formerly Developer Studio)



Single Development Tool, Tailored for Extreme Productivity. Red Hat CodeReady Studio provides superior support for your entire development lifecycle. It includes... [more info](#)

by [Red Hat, Inc.](#), EPL

[openshift](#) [jbosstools](#) [maven](#) [hibernate](#) [Mobile](#) ...


★ 136

➔ Installs: **124K** (936 last month)

Install


[2 matches. Browse for more solutions.](#)

4. Click **Install**.
5. Follow the on-screen instructions to complete the installation process.




IMPORTANT




When prompted to select additional features to install, select the **Fuse Tooling** feature for creating, testing, and debugging integration applications.



Eclipse Marketplace x

Confirm Selected Features 

Press Confirm to continue with the installation. Or go back to choose more solutions to install.

-  Red Hat CodeReady Studio (formerly Developer Studio)
 -  Red Hat CodeReady Studio (Core Features) (required)
 -  Red Hat Fuse Tooling

?

< Install More

Confirm >

Cancel

Finish

If you receive warnings about installing unsigned content, review the details of the content and, if satisfied, click **Install Anyway** to continue with the installation.

6. Restart Eclipse.

When prompted to restart the Eclipse IDE, click **Restart Now**. Note that the changes do not take effect until you restart Eclipse.

3.1.2. Installing CodeReady Studio in Eclipse when offline


The following section describes how to install CodeReady Studio with the **Update Site Zip**.

Prerequisites

- Download the **Red Hat CodeReady Studio 12.19 Update Site Zip** from the [Red Hat Developer Portal](#).

Procedure


1. Start the Eclipse IDE.
2. Click **Help** → **Install New Software**.




The **Available Software** window appears.

3. Click **Add**.

The **Add Repository** window appears.



4. Click **Archive** and locate the **Update Site Zip** file.
5. Click **Add**.
6. Select the **Red Hat CodeReady Studio - Bring Your Own Eclipse** and **Red Hat Fuse Tooling** check boxes.



7. Click **Next**.
8. Follow the on-screen instructions to complete the installation process.
If you receive warnings about installing unsigned content, review the details of the content and, if satisfied, click **Install Anyway** to continue with the installation.

9. Restart Eclipse.

When prompted to restart the Eclipse IDE, click **Restart Now**. Note that the changes do not take effect until you restart Eclipse.

3.2. INSTALLING CODEREADY STUDIO STAND-ALONE USING THE INSTALLER

The Installer contains CodeReady Studio stand-alone, which packages the CodeReady Studio plug-ins with Eclipse and dependent third-party plug-ins. The Installer is compatible with all operating systems and is available from a variety of sources, including the Red Hat Customer Portal.

The following section describes how to install CodeReady Studio using the Installer.

Procedure

1. Download the **Red Hat CodeReady Studio 12.19 Installer** from the [Red Hat Developer Portal](#).
2. Go to the directory that contains the **codereadystudio-12.19.0.GA-installer-standalone.jar** file you downloaded.
3. Start the Installer:


```
$ java -jar codereadystudio-12.19.0.GA-installer-standalone.jar
```

4. Follow the on-screen instructions to complete the installation process.



IMPORTANT

When prompted to select additional features to install, select the **Fuse Tooling** feature for creating, testing, and debugging integration applications.



3.3. PERFORMING ADVANCED INSTALLATION TASKS

The following sections describe how to install CodeReady Studio using a script and how to build the Red Hat CodeReady Studio Installer from source code.

3.3.1. Installing CodeReady Studio using a script

The following section describes how to install CodeReady Studio using a script.

Procedure

1. Download the **Red Hat CodeReady Studio 12.19 Installer** from the [Red Hat Developer Portal](#).
2. Go to the directory that contains the **codereadystudio-12.19.0.GA-installer-standalone.jar** file you downloaded.
3. Start the Installer:

```
$ java -jar codereadystudio-12.19.0.GA-installer-standalone.jar
```

4. Follow the on-screen instructions to complete the installation process.



IMPORTANT


When prompted to select additional features to install, select the **Fuse Tooling** feature for creating, testing and debugging integration applications.

After the installation is complete, an **InstallConfigRecord.xml** file is generated in the CodeReady Studio installation directory.

5. Run the following command:

```
$ java -jar codereadystudio-12.19.0.GA-installer-standalone.jar \  
/path-to/InstallConfigRecord.xml
```

6. Replace *path-to* with the path to the **InstallConfigRecord.xml** file.



NOTE

The generated **InstallConfigRecord.xml** file is machine-specific and uses Java Development Kit (JDK) and installation paths of your system. To use the **InstallConfigRecord.xml** file for other operating systems, JDKs, or paths, you must manually modify the file.

3.3.2. Building the CodeReady Studio stand-alone Installer from source

The following section describes how to build the CodeReady Studio stand-alone Installer from source.

Prerequisites

- Maven 3.3 or later with Java 11 is installed. To obtain and configure Maven, see the [Apache Maven Project](#).

Procedure

1. Clone the CodeReady Studio Git repository:

```
$ git clone https://github.com/jbdevstudio/jbdevstudio-product.git
```

2. Navigate to the **jbdevstudio-product** directory:

```
$ cd jbdevstudio-product
```

3. Checkout **master**:

```
$ git checkout master
```

4. Follow the instructions in the **README.adoc** file.

When the build is complete, the **.jar** file for the CodeReady Studio stand-alone Installer is located in the **/jbdevstudio-product/installer/target** directory.

CHAPTER 4. UPGRADING CODEREADY STUDIO

The following section describes the possibilities of upgrading your version of CodeReady Studio to the latest major and minor versions.

4.1. UPGRADING MAJOR VERSIONS OF CODEREADY STUDIO

Each major version of CodeReady Studio is based on a different version of Eclipse. As a result, it is not possible to upgrade an older major version of CodeReady Studio to a newer major version. For example, it is not possible to update a CodeReady Studio 10.x installation to 11.x. However, it is possible to use the workspaces created using CodeReady Studio 11.x with CodeReady Studio 12.x.

Note that you can have multiple versions of CodeReady Studio installed on your system with Installer or Eclipse, provided you have these versions located in different directories.

The following table details the Eclipse versions supported with each major version of Red Hat CodeReady Studio:


Table 4.1. Eclipse Version Support Matrix

| Red Hat CodeReady Studio Version | Base Eclipse Version |
|----------------------------------|---------------------------|
| CodeReady Studio 12.19 | Eclipse IDE 2021-03 |
| CodeReady Studio 12.18 | Eclipse IDE 2020-09 |
| CodeReady Studio 12.17 | Eclipse IDE 2020-09 |
| CodeReady Studio 12.16 | Eclipse IDE 2020-06 |
| CodeReady Studio 12.15 | Eclipse IDE 2020-03 |
| CodeReady Studio 12.14 | Eclipse IDE 2019-12 |
| CodeReady Studio 12.13 | Eclipse IDE 2019-09 |
| CodeReady Studio 12.11 | Eclipse SimRel 2019-03 GA |
| CodeReady Studio 12.9 | Eclipse SimRel 2018-09 GA |
| CodeReady Studio 12.0 | Eclipse 4.8 (Photon) |
| CodeReady Studio 11.x | Eclipse 4.7 (Oxygen) |
| Red Hat CodeReady Studio 10.x | Eclipse 4.6 (Neon) |
| Red Hat CodeReady Studio 9.x | Eclipse 4.5 (Mars) |

4.2. UPDATING MINOR VERSIONS OF RED HAT CODEREADY STUDIO

It is possible to update Red Hat CodeReady Studio to the latest minor versions within the major release. For example, you can update your Red Hat CodeReady Studio 12.0 installation to 12.9.

You may be automatically notified by the IDE when the latest Red Hat CodeReady Studio update is available, depending on your IDE settings for automatic updates.




IMPORTANT

Back up your workspace before updating. In addition to your project files, your workspace contains metadata about customized settings and preferences for the IDE. To back up your workspace, either copy the workspace directory to a backup location, or save it as a compressed file.


Procedure

1. Start the Eclipse IDE.
2. Click **Window** → **Preferences**.




The **Preferences** window appears.

3. Select **Install/Update** → **Available Software Sites**.



4. Ensure that the URL <https://devstudio.redhat.com/12/stable/updates/> is listed in enabled locations. If it is not listed, add it.
5. Click **Apply and Close**.
6. Click **Help** → **Check for Updates**.



Note that the search for updates might take some time.

7. Follow the on-screen instructions to apply available updates.
If you receive warnings about installing unsigned content, review the details of the content and, if satisfied, click **Install Anyway** to continue with the installation.
8. Restart Eclipse.
When prompted to restart the Eclipse IDE, click **Restart Now**. Note that the changes do not take effect until you restart Eclipse.

CHAPTER 5. UNINSTALLING CODEREADY STUDIO

The following section describes how to uninstall CodeReady Studio using Eclipse or the Installer.


Note that you can have multiple versions of CodeReady Studio installed on your system, provided you have these versions located in different directories.

5.1. UNINSTALLING RED HAT CODEREADY STUDIO USING ECLIPSE

The following section describes how to uninstall CodeReady Studio installed with Eclipse Marketplace or the **Update Site Zip**.


Procedure

1. Start the Eclipse IDE.
2. Click **Help** → **Eclipse Marketplace**.




The **Eclipse Marketplace** window appears.

3. Navigate to the **Installed** section.



4. Locate **Red Hat CodeReady Studio**.
5. Click the down arrow near the **Change** button.
6. Click **Uninstall**.
The **Confirm Selected Features** window appears.



7. Ensure that **Red Hat CodeReady Studio** is selected.

8. Click **Confirm**.
9. Click **Finish**.
The **Software Updates** dialog box appears prompting you to restart Eclipse.
10. Click **Restart Now**.
Note that the changes do not take effect until you restart Eclipse.

5.2. UNINSTALLING CODEREADY STUDIO USING THE INSTALLER

The following section describes how to uninstall CodeReady Studio installed with the Installer.


Procedure

1. Ensure that CodeReady Studio is not running.
2. Navigate to the **/Uninstaller** directory:

```
$ cd /path-to/codereadystudio/Uninstaller
```
3. Replace *path-to* with the path to the CodeReady Studio **/codereadystudio/Uninstaller** directory.
4. Start the Uninstaller:

```
$ java -jar uninstaller.jar
```

The **IzPack Uninstaller** dialog box appears.



5. Select the **Force the deletion** check box.
If the check box is not selected, some files will be left behind in the installation directory.
6. Click **Uninstall**.

CHAPTER 6. REPORTING ISSUES

You can report errors by raising a ticket in [JIRA](#). When creating a JIRA ticket, please create it against one of the following projects: [JBDS](#) or [JBIDE](#). Provide as much detail as possible in the JIRA ticket to help the team debug the error. You can also attach the error log to the JIRA tickets to provide context for the issue.