



Red Hat Process Automation Manager 7.0

Installing and configuring Red Hat Process
Automation Manager on Red Hat JBoss EAP 7.1

Red Hat Process Automation Manager 7.0 Installing and configuring Red Hat Process Automation Manager on Red Hat JBoss EAP 7.1

Red Hat Customer Content Services
brms-docs@redhat.com

Legal Notice

Copyright © 2020 Red Hat, Inc.

The text of and illustrations in this document are licensed by Red Hat under a Creative Commons Attribution–Share Alike 3.0 Unported license ("CC-BY-SA"). An explanation of CC-BY-SA is available at

<http://creativecommons.org/licenses/by-sa/3.0/>

. In accordance with CC-BY-SA, if you distribute this document or an adaptation of it, you must provide the URL for the original version.

Red Hat, as the licensor of this document, waives the right to enforce, and agrees not to assert, Section 4d of CC-BY-SA to the fullest extent permitted by applicable law.

Red Hat, Red Hat Enterprise Linux, the Shadowman logo, the Red Hat logo, JBoss, OpenShift, Fedora, the Infinity logo, and RHCE are trademarks of Red Hat, Inc., registered in the United States and other countries.

Linux[®] is the registered trademark of Linus Torvalds in the United States and other countries.

Java[®] is a registered trademark of Oracle and/or its affiliates.

XFS[®] is a trademark of Silicon Graphics International Corp. or its subsidiaries in the United States and/or other countries.

MySQL[®] is a registered trademark of MySQL AB in the United States, the European Union and other countries.

Node.js[®] is an official trademark of Joyent. Red Hat is not formally related to or endorsed by the official Joyent Node.js open source or commercial project.

The OpenStack[®] Word Mark and OpenStack logo are either registered trademarks/service marks or trademarks/service marks of the OpenStack Foundation, in the United States and other countries and are used with the OpenStack Foundation's permission. We are not affiliated with, endorsed or sponsored by the OpenStack Foundation, or the OpenStack community.

All other trademarks are the property of their respective owners.

Abstract

This document describes how to install Red Hat Process Automation Manager on a Red Hat JBoss EAP 7.1 installation.

Table of Contents

PREFACE	3
CHAPTER 1. ABOUT RED HAT PROCESS AUTOMATION MANAGER	4
CHAPTER 2. ROLES AND USERS	5
CHAPTER 3. DOWNLOADING THE RED HAT PROCESS AUTOMATION MANAGER INSTALLATION FILES	7
CHAPTER 4. USING THE RED HAT PROCESS AUTOMATION MANAGER INSTALLER	8
4.1. USING THE INSTALLER IN INTERACTIVE MODE	8
4.2. USING THE INSTALLER IN CLI MODE	11
4.3. USING THE INSTALLER TO CONFIGURE PROCESS SERVER WITH THE PROCESS AUTOMATION MANAGER CONTROLLER	12
CHAPTER 5. INSTALLING RED HAT PROCESS AUTOMATION MANAGER FROM ZIP FILES	14
5.1. INSTALLING BUSINESS CENTRAL FROM THE ZIP FILE	14
5.2. INSTALLING PROCESS SERVER FROM THE ZIP FILE	15
5.3. CONFIGURING JDBC DATA SOURCES FOR PROCESS SERVER	15
5.4. CREATING USERS	17
5.5. CONFIGURING PROCESS SERVER WITH THE INTEGRATED PROCESS AUTOMATION MANAGER CONTROLLER	18
CHAPTER 6. RUNNING RED HAT PROCESS AUTOMATION MANAGER	20
CHAPTER 7. INSTALLING AND RUNNING THE HEADLESS PROCESS AUTOMATION MANAGER CONTROLLER	21
7.1. INSTALLING THE HEADLESS PROCESS AUTOMATION MANAGER CONTROLLER	21
7.1.1. Creating a controller user	22
7.1.2. Configuring Process Server and the headless Process Automation Manager controller	22
7.2. RUNNING THE HEADLESS PROCESS AUTOMATION MANAGER CONTROLLER	24
CHAPTER 8. RUNNING STANDALONE BUSINESS CENTRAL	25
8.1. SUPPORTED PROPERTIES	26
CHAPTER 9. SETTING MAVEN DEPENDENCIES IN YOUR PROJECT	29
9.1. MODIFY THE MAVEN SETTINGS FILE	29
9.2. MODIFY THE MAVEN POM FILE	29
CHAPTER 10. IMPORTING PROJECTS FROM GIT REPOSITORIES	34
CHAPTER 11. VERIFYING THE RED HAT PROCESS AUTOMATION MANAGER INSTALLATION	35
CHAPTER 12. CUSTOMIZING BUSINESS CENTRAL	36
12.1. CUSTOMIZING THE BUSINESS CENTRAL LOGIN PAGE	36
12.2. CUSTOMIZING BUSINESS CENTRAL APPLICATION HEADER	36
CHAPTER 13. INTEGRATING LDAP AND SSL	37
CHAPTER 14. RELATED INFORMATION	38
CHAPTER 15. NEXT STEPS	39
APPENDIX A. VERSIONING INFORMATION	40

PREFACE

This document describes how to install Red Hat Process Automation Manager on a Red Hat JBoss Enterprise Application Platform 7.1 instance.

Prerequisite

Review the information in [Planning a Red Hat Process Automation Manager installation](#) .

CHAPTER 1. ABOUT RED HAT PROCESS AUTOMATION MANAGER

Red Hat Process Automation Manager is the Red Hat middleware platform for creating business automation applications and microservices. It enables enterprise business and IT users to document, simulate, manage, automate, and monitor business processes and policies. It is designed to empower business and IT users to collaborate more effectively, so business applications can be changed easily and quickly.

Red Hat JBoss Enterprise Application Platform (Red Hat JBoss EAP) 7.1 is a certified implementation of the Java Enterprise Edition 7 (Java EE 7) full and web profile specifications. Red Hat JBoss EAP provides preconfigured options for features such as high availability, clustering, messaging, and distributed caching. It also enables users to write, deploy, and run applications using the various APIs and services that Red Hat JBoss EAP provides.

The instructions in this document explain how to install Red Hat Process Automation Manager in a Red Hat JBoss EAP 7.1 server instance. For instruction on how to install Red Hat Process Automation Manager in other environments, see the following documents:

- [Installing and configuring Process Server on IBM WebSphere Application Server](#)
- [Installing and configuring Process Server on Oracle WebLogic Server](#)
- [Deploying a Red Hat Process Automation Manager authoring environment on Red Hat OpenShift Container Platform](#)
- [Deploying a Red Hat Process Automation Manager immutable server environment on Red Hat OpenShift Container Platform](#)
- [Deploying a Red Hat Process Automation Manager managed server environment on Red Hat OpenShift Container Platform](#)

For information on supported components, see the following documents: * [What is the mapping between RHPAM product and maven library version?](#) * [Red Hat Process Automation Manager 7 Supported Configurations](#)

CHAPTER 2. ROLES AND USERS

To access Business Central or Process Server, you must create users and assign them appropriate roles before the servers are started.

The Business Central and Process Server use Java Authentication and Authorization Service (JAAS) login module to authenticate the users. If both Business Central and Process Server are running on a single instance, then they share the same JAAS subject and security domain. Therefore, a user, who is authenticated for Business Central can also access Process Server.

However, if Business Central and Process Server are running on different instances, then the JAAS login module is triggered for both individually. Therefore, a user, who is authenticated for Business Central, needs to be authenticated separately to access the Process Server (for example, to view or manage process definitions in Business Central). In case, the user is not authenticated on the Process Server, then 401 error is logged in the log file, displaying **Invalid credentials to load data from remote server. Contact your system administrator.** message in Business Central.

This section describes available Red Hat Process Automation Manager user roles.



NOTE

The **admin**, **analyst**, **developer**, **manager**, **process-admin**, **user**, and **rest-all** roles are reserved for Business Central. The **kie-server** role is reserved for Process Server. For this reason, the available roles can differ depending on whether Business Central, Process Server, or both are installed.

- **admin:** Users with the **admin** role are the Business Central administrators. They can manage users and create, clone, and manage the repositories. They have full access to make required changes in the application. Users with the **admin** role have access to all areas within Red Hat Process Automation Manager.
- **analyst:** Users with the **analyst** role have access to all high-level features. They can model and execute their projects. However, these users cannot add contributors to spaces or delete spaces in the **Design → Projects** view. Access to the **Deploy → Execution Servers** view, which is intended for administrators, is not available to users with the **analyst** role. However, the **Deploy** button is available to these users when they access the Library perspective.
- **developer:** Users with the **developer** role have access to almost all features and can manage rules, models, process flows, forms, and dashboards. They can manage the asset repository, they can create, build, and deploy projects, and they can use Red Hat JBoss Developer Studio to view processes. Only certain administrative functions such as creating and cloning a new repository are hidden from users with the **developer** role.
- **manager:** Users with the **manager** role can view reports. These users are usually interested in statistics about the business processes and their performance, business indicators, and other business-related reporting. A user with this role has access only to process and task reports.
- **process-admin:** Users with the **process-admin** role are business process administrators. They have full access to business processes, business tasks, and execution errors. These users can also view business reports and have access to the Task Inbox list.
- **user:** Users with the **user** role can work on the Task Inbox list, which contains business tasks that are part of currently running processes. Users with this role can view process and task reports and manage processes.
- **rest-all:** Users with the **rest-all** role can access Business Central REST capabilities.

- **kie-server**: Users with the **kie-server** role can access Process Server (KIE Server) REST capabilities. This role is mandatory for users to have access to Manage and Track views in Business Central.

CHAPTER 3. DOWNLOADING THE RED HAT PROCESS AUTOMATION MANAGER INSTALLATION FILES

Depending on your environment and installation requirements, download a Red Hat Process Automation Manager distribution.

Procedure

1. Navigate to the [Software Downloads](#) page in the Red Hat Customer Portal (login required), and select the product and version from the drop-down options:
 - Product: Red Hat Process Automation Manager
 - Version: 7.0
2. Download one of the following product distributions:
 - To use the installer to install Red Hat Process Automation Manager on Red Hat JBoss EAP 7.1, download **Red Hat Process Automation Manager 7.0.0 Installer**(**rhpmam-installer-7.0.0.jar**). The installer graphical user interface guides you through the installation process.
 - To install Red Hat Process Automation Manager on Red Hat JBoss EAP 7.1 using the deployable zip files, download the following files:
 - **Red Hat Process Automation Manager 7.0.0 Process Server for All Supported EE7 Containers** (**rhpmam-7.0.0-kie-server-ee7.zip**)
 - **Red Hat Process Automation Manager 7.0.0 Business Central Deployable for EAP 7** (**rhpmam-7.0.0-business-central-eap7-deployable.zip**)

The ZIP files do not require a graphical user interface so you can install Red Hat Process Automation Manager using SSH.

- To run Business Central without needing to deploy it to an application server, download **Red Hat Process Automation Manager 7.0.0 Decision Central Standalone** (**rhpmam-7.0.0-business-central-standalone.jar**).

CHAPTER 4. USING THE RED HAT PROCESS AUTOMATION MANAGER INSTALLER

This section describes how to install Process Server and the headless Process Automation Manager controller using the installer JAR file. The JAR file is an executable file that installs Red Hat Process Automation Manager in an existing Red Hat JBoss EAP 7.1 server installation. You can run the installer in interactive or command line interface (CLI) mode.



NOTE

The Red Hat Process Automation Manager JAR file installer does *not* support the Red Hat JBoss EAP distribution installed by yum or RPM Package Manager. If you want to install Red Hat Process Automation Manager in this type of Red Hat JBoss EAP installation, download the **Red Hat Process Automation Manager 7.0 Deployable for Red Hat JBoss EAP 7.1** file and follow the steps in [Chapter 5, *Installing Red Hat Process Automation Manager from ZIP files*](#).



NOTE

Because IBM JDK cannot use keystores generated on other JDKs, you cannot install Red Hat Process Automation Manager into an existing Red Hat JBoss EAP installation running on IBM JDK with a keystore generated on another JDK.

Next steps:

Follow the instructions in one of the following sections:

- [Section 4.1, “Using the installer in interactive mode”](#)
- [Section 4.2, “Using the installer in CLI mode”](#)
- [Section 4.3, “Using the installer to configure Process Server with the Process Automation Manager controller”](#)

4.1. USING THE INSTALLER IN INTERACTIVE MODE

The installer for Red Hat Process Automation Manager is an executable JAR file. You can use it to install Red Hat Process Automation Manager in an existing Red Hat JBoss EAP 7.1 server installation.



NOTE

For security reasons, you should run the installer as a non-root user.

Prerequisites

- A backed-up Red Hat JBoss EAP 7.1 or higher server installation is available.
- Sufficient user permissions to complete the installation are granted.
- The JAR binary is included in **\$PATH** environment variable. On Red Hat Enterprise Linux, it is included in the **java-\$JAVA_VERSION-openjdk-devel** package.

**NOTE**

Red Hat Process Automation Manager is designed to work with UTF-8 encoding. If a different encoding system is used by the underlying JVM, unexpected errors might occur. To ensure UTF-8 is used by the JVM, use the "**-Dfile.encoding=UTF-8**" system property.

Procedure

1. In a terminal window, navigate to the directory where you downloaded the installer JAR file and enter the following command:

```
java -jar rhpam-installer-7.0.0.jar
```

**NOTE**

When running the installer on Windows, you may be prompted to provide administrator credentials during the installation. To prevent this requirement, add the **izpack.mode=privileged** option to the installation command:

```
java -Dizpack.mode=privileged -jar  
rhpam-installer-7.0.0.jar
```

Furthermore, when running the installer on a 32-bit Java virtual machine, you might encounter memory limitations. To prevent this issue, run this command:

```
java -XX:MaxHeapSize=4g -jar  
rhpam-installer-7.0.0.jar
```

The graphical installer displays a splash screen and a license agreement page.

2. Click **I accept the terms of this license agreement** and click **Next**.
3. Specify the Red Hat JBoss EAP 7.1 server home where you want to install Red Hat Process Automation Manager and click **Next**.
4. Select the components that you want to install and click **Next**.

**NOTE**

You can install Business Central and Process Server on the same server. However, you should install Business Central and Process Server on different servers in production environments. To do this, run the installer twice.

5. Create a user and click **Next**. By default, the new user is given the **admin**, **kie-server**, and **rest-all** roles. To select another role, deselect **admin**. For more information, see [Chapter 2, Roles and users](#).

**NOTE**

Make sure that the specified user name is not the same as an existing user, role, or group. For example, do not create a user with the user name **admin**.

The password must have at least eight characters and must contain at least one number and one non-alphanumeric character, but not & (ampersand).

Make a note of the user name and password. You will need them to access Business Central and Process Server.

6. On the **Installation Overview** page, click **Next** to start the installation. The Installation Overview page lists the components that you will install.
7. When the installation has completed, click **Next**.
8. On the **Configure Runtime Environment** page, choose whether to perform the default installation or perform an advanced configuration.
If you choose **Perform advanced configuration**, you can choose to configure database settings or customize certain Process Server options.
9. If you selected **Customize database settings**, on the **JDBC Drive Configuration** page specify a data source JDBC driver vendor, select one or more Driver JAR files, and click **Next**.
A data source is an object that enables a Java Database Connectivity (JDBC) client, such as an application server, to establish a connection with a database. Applications look up the data source on the Java Naming and Directory Interface (JNDI) tree or in the local application context and request a database connection to retrieve data. You must configure data sources for Process Server to ensure proper data exchange between the servers and the designated database.
10. If you selected **Customize Process Server settings**, change any of the following, if desired:
 - Change the name of the Process Server property.
 - Change the URL of the controller.
 - Deselect any Process Server server options.
11. Click **Next** to configure the runtime environment.
12. When **Processing finished** appears at the top of the screen, click **Next** to complete the installation.
13. If desired, click **Generate Installation Script and Properties File** to save the installation data in an XML file, then click **Done**. You can use this file to automatically install Red Hat Process Automation Manager on the same type of server. Note that you must change the **installpath** parameter in the XML file to specify the path of the new server that you want to install Red Hat Process Automation Manager on. Enter the following command to perform an installation with the XML file:

```
java -jar rhpam-installer-7.0.0.jar <path-to-file>
```

You have successfully installed Red Hat Process Automation Manager using the installer. If you installed only Business Central, repeat these steps to install Process Server on a separate server.

4.2. USING THE INSTALLER IN CLI MODE

You can run the Red Hat Process Automation Manager installer through the command-line interface (CLI).



NOTE

For security reasons, you should run the installer as a non-root user.

Prerequisites

- A backed-up Red Hat JBoss EAP 7.1 or higher server installation is available.
- Sufficient user permissions to complete the installation are granted.
- The JAR binary is included in the **\$PATH** environment variable. On Red Hat Enterprise Linux, it is included in the **java-\$JAVA_VERSION-openjdk-devel** package.



NOTE

Red Hat Process Automation Manager is designed to work with UTF-8 encoding. If a different encoding system is used by the underlying JVM, unexpected errors might occur. To ensure UTF-8 is used by the JVM, use the "**-Dfile.encoding=UTF-8**" system property.

Procedure

1. In a terminal window, navigate to the directory where you downloaded the installer file and enter the following command:

```
java -jar rhpam-installer-7.0.0.jar -console
```

The command-line interactive process will start and display the End-User License Agreement.

```
press 1 to continue, 2 to quit, 3 to redisplay.
```

2. Read the license agreement, enter **1**, and press Enter to continue:

```
Specify the home directory of one of the following servers: Red Hat JBoss EAP 7.1 or Red Hat JBoss Web Server 5.0
```

3. Enter the parent directory of an existing Red Hat JBoss EAP 7.1 installation. The installer will verify the location of the installation at the location provided. Enter **1** to confirm and continue.



NOTE

You can install Business Central and Process Server on the same server. However, you should install Business Central and Process Server on different servers in production environments.

4. Follow the instructions in the installer to complete the installation.



NOTE

When you create the user name and password, make sure that the specified user name does not conflict with any known title of a role or a group. For example, if there is a role called **admin**, you should not create a user with the user name **admin**.

The password must have at least eight characters and must contain at least one number and one non-alphanumeric character (*not* including the character **&**).

Make a note of the user name and password. You will need them to access Business Central and Process Server.

5. When the installation has completed, you will see this message:

Would you like to generate an automatic installation script and properties file?

6. Enter **y** to create an XML file that contains the installation data, or **n** to complete the installation. If you enter **y**, you are prompted to specify a path for the XML file.
7. Enter a path or press the Enter key to accept the suggested path.
8. If you installed only Business Central, repeat these steps to install Process Server on a separate server.

4.3. USING THE INSTALLER TO CONFIGURE PROCESS SERVER WITH THE PROCESS AUTOMATION MANAGER CONTROLLER

Process Server can be managed by the Process Automation Manager controller or it can be unmanaged. If Process Server is unmanaged, you must manually create and maintain containers. If Process Server is managed, the Process Automation Manager controller manages the Process Server configuration and you interact with the controller to create and maintain containers.

The Process Automation Manager controller is integrated with Business Central. If you install Business Central, you can use the **Execution Server** page in Business Central to interact with the controller.

You can use the installer in interactive or CLI mode to install Business Central and Process Server, and then configure Process Server with the Process Automation Manager controller.



NOTE

If you do not install Business Central, see [Chapter 7, Installing and running the headless Process Automation Manager controller](#) for information about using the headless Process Automation Manager controller.

Prerequisites

- Two computers with backed-up Red Hat JBoss EAP 7.1 or higher server installations are available.
- Sufficient user permissions to complete the installation are granted.

Procedure

1. On the first computer, run the installer in interactive mode or CLI mode. See one of the following sections for more information:
 - [Section 4.1, "Using the installer in interactive mode"](#)
 - [Section 4.2, "Using the installer in CLI mode"](#)
2. On the **Component Selection** page, clear the **Process Server** box.
3. Complete the Business Central installation.
4. On the second computer, run the installer in interactive mode or CLI mode.
5. On the **Component Selection** page, clear the **Business Central** box.
6. On the **Configure Runtime Environment** page, select **Perform Advanced Configuration**.
7. Select **Customize Process Server properties** and click **Next**.
8. On the **Process Server Properties Configuration** page, click **New Server Configuration** to add a Process Server and specify a unique name for that Process Server. This name will appear in Business Central and enable you to distinguish between different Process Servers.

CHAPTER 5. INSTALLING RED HAT PROCESS AUTOMATION MANAGER FROM ZIP FILES

The Red Hat Process Automation Manager ZIP files (one for Business Central and one for Process Server) do not require a graphical user interface so you can install Red Hat Process Automation Manager using SSH.



NOTE

You should install Business Central and the Process Server on different servers in production environments.

For information about installing the headless Process Automation Manager controller, see [Chapter 7, Installing and running the headless Process Automation Manager controller](#).

5.1. INSTALLING BUSINESS CENTRAL FROM THE ZIP FILE

Business Central is a web console that enables you to perform the following tasks over individual components in a unified web-based environment:

- Create, manage, and edit your rules, processes, and related assets.
- Manage connected Process Server instances and their containers.
- Execute runtime operations against processes and tasks in Process Server instances connected to Business Central.

Prerequisites

- A backed-up Red Hat JBoss EAP installation version 7.1 or higher is available. The base directory of the Red Hat JBoss EAP installation is referred to as **EAP_HOME**.
- Sufficient user permissions to complete the installation are granted.
- The following file is downloaded from the [Red Hat Customer Portal](#):
rhcam-7.0.0-business-central-eap7-deployable.zip

Procedure

1. Extract the **rhcam-7.0.0-business-central-eap7-deployable.zip** file to a temporary directory. In the following examples this directory is called **TEMP_DIR**.
2. Copy the contents of the **TEMP_DIR/rhcam-7.0.0-business-central-eap7-deployable/jboss-eap-7.1** directory to **EAP_HOME**. When prompted, merge or replace files.

**WARNING**

Ensure the names of the Red Hat Process Automation Manager deployments you are copying do not conflict with your existing deployments in the Red Hat JBoss EAP instance.

5.2. INSTALLING PROCESS SERVER FROM THE ZIP FILE

Process Server provides the runtime environment for business assets and accesses the data stored in the assets repository (knowledge store).

Prerequisites

- A backed-up Red Hat JBoss EAP installation version 7.1 or higher is available. The base directory of the Red Hat JBoss EAP installation is referred to as **EAP_HOME**.
- Sufficient user permissions to complete the installation are granted.
- The following file is downloaded from the [Red Hat Customer Portal](#):
rhpm-7.0.0-kie-server-ee7.zip

Procedure

1. Extract the **rhpm-7.0.0-kie-server-ee7.zip** archive to a temporary directory. In the following examples this directory is called **TEMP_DIR**.
2. Copy the **TEMP_DIR/rhpm-7.0.0-kie-server-ee7/rhpm-7.0.0-kie-server-ee7/kie-server.war** directory to **EAP_HOME/standalone/deployments/**.

**WARNING**

Ensure the names of the Red Hat Process Automation Manager deployments you are copying do not conflict with your existing deployments in the Red Hat JBoss EAP instance.

3. Copy the contents of the **TEMP_DIR/rhpm-7.0.0-kie-server-ee7/rhpm-7.0.0-kie-server-ee7/SecurityPolicy/** to **EAP_HOME/bin**. When asked to overwrite files, click **Replace**.
4. In the **EAP_HOME/standalone/deployments/** directory, create an empty file named **kie-server.war.dodeploy**. This file ensures that Process Server is automatically deployed when the server starts.

5.3. CONFIGURING JDBC DATA SOURCES FOR PROCESS SERVER

A data source is an object that enables a Java Database Connectivity (JDBC) client, such as an

application server, to establish a connection with a database. Applications look up the data source on the Java Naming and Directory Interface (JNDI) tree or in the local application context and request a database connection to retrieve data. You must configure data sources for Process Server to ensure proper data exchange between the servers and the designated database.

Prerequisite

The JDBC providers that you want to use to create database connections are configured on all servers on which you want to deploy Process Server.

Procedure

1. Open **`EAP_HOME/standalone/configuration/standalone-full.xml`** in a text editor and locate the **`<system-properties>`** tag.
2. Add the following properties to the **`<system-properties>`** tag where **`<DATASOURCE>`** is the name of your data source and **`<HIBERNATE_DIALECT>`** is the hibernate dialect for your database.



NOTE

The default value of the **`org.kie.server.persistence.ds`** property is **`java:jboss/datasources/ExampleDS`**. The default value of the **`org.kie.server.persistence.dialect`** property is **`org.hibernate.dialect.H2Dialect`**.

```
<property name="org.kie.server.persistence.ds" value="<DATASOURCE>"/>
<property name="org.kie.server.persistence.dialect" value="<HIBERNATE_DIALECT>"/>
```

For example:

```
<system-properties>
  <property name="org.kie.server.repo" value="{jboss.server.data.dir}"/>
  <property name="org.kie.example" value="true"/>
  <property name="org.jbpm.designer.perspective" value="full"/>
  <property name="designerdataobjects" value="false"/>
  <property name="org.kie.server.user" value="rhpamUser"/>
  <property name="org.kie.server.pwd" value="rhpam123!"/>
  <property name="org.kie.server.location" value="http://localhost:8080/kie-
server/services/rest/server"/>
  <property name="org.kie.server.controller" value="http://localhost:8080/business-
central/rest/controller"/>
  <property name="org.kie.server.controller.user" value="kieserver"/>
  <property name="org.kie.server.controller.pwd" value="kieserver1!"/>
  <property name="org.kie.server.id" value="local-server-123"/>

  <!-- Data source properties. -->
  <property name="org.kie.server.persistence.ds"
value="java:jboss/datasources/KieServerDS"/>
  <property name="org.kie.server.persistence.dialect"
value="org.hibernate.dialect.PostgreSQLDialect"/>
</system-properties>
```

The following dialects are supported:

- DB2: **`org.hibernate.dialect.DB2Dialect`**

- MSSQL: `org.hibernate.dialect.SQLServer2012Dialect`
- MySQL: `org.hibernate.dialect.MySQL5InnoDBDialect`
- MariaDB: `org.hibernate.dialect.MySQL5InnoDBDialect`
- Oracle: `org.hibernate.dialect.Oracle10gDialect`
- PostgreSQL: `org.hibernate.dialect.PostgreSQL82Dialect`
- PostgreSQL plus: `org.hibernate.dialect.PostgresPlusDialect`
- Sybase: `org.hibernate.dialect.SybaseASE157Dialect`

5.4. CREATING USERS

Before you can log in to Business Central or Process Server, you must create users. This section shows you how to create a Business Central user with the **admin**, **rest-all**, and **kie-server** roles and a Process Server user that has the **kie-server** role. For information about roles, see [Chapter 2, Roles and users](#).

Prerequisites

Red Hat Process Automation Manager is installed in the base directory of the Red Hat JBoss EAP installation (**EAP_HOME**) as described in [Chapter 5, Installing Red Hat Process Automation Manager from ZIP files](#).

Procedure

1. In a terminal application, navigate to the **EAP_HOME/bin** directory.
2. Create a user with the **admin** role that you will use to log in to Business Central. In the following command, replace **<username>** and **<password>** with the user name and password of your choice.

```
$ ./add-user.sh -a --user <USERNAME> --password <PASSWORD> --role admin,rest-all
```



NOTE

Make sure that the specified user name is not the same as an existing user, role, or group. For example, do not create a user with the user name **admin**.

The password must have at least eight characters and must contain at least one number and one non-alphanumeric character, but not & (ampersand).

3. Create a user with the **kie-server** role that you will use to log in to Process Server.

```
$ ./add-user.sh -a --user <USERNAME> --password <PASSWORD> --role kie-server
```

4. Make a note of your user names and passwords.

**NOTE**

If you installed Business Central and Process Server in the same server instance, you can create a single user that has both of these roles:

```
$. /add-user.sh -a --user <USERNAME> --password <PASSWORD> --role
admin,rest-all,kie-server
```

You should install Business Central and Process Server on different servers in production environments.

5.5. CONFIGURING PROCESS SERVER WITH THE INTEGRATED PROCESS AUTOMATION MANAGER CONTROLLER

**NOTE**

Only make the changes described in this section if Process Server will be managed by Business Central and you installed Red Hat Process Automation Manager from the ZIP files. If you did not install Business Central, you can use the headless Process Automation Manager controller to manage Process Server, as described in [Chapter 7, Installing and running the headless Process Automation Manager controller](#).

Process Server can be managed or it can be unmanaged. If Process Server is unmanaged, you must manually create and maintain containers. If Process Server is managed, the Process Automation Manager controller manages the Process Server configuration and you interact with the controller to create and maintain containers.

The Process Automation Manager controller is integrated with Business Central. If you install Business Central, you can use the **Execution Server** page in Business Central to interact with the controller.

If you installed Red Hat Process Automation Manager from the ZIP files, you must edit the **standalone-full.xml** file in both the Process Server and Business Central installations to configure Process Server with the integrated Process Automation Manager controller.

Prerequisites

- Business Central and Process Server are installed in the base directory of the Red Hat JBoss EAP installation (**EAP_HOME**) as described in the following sections:
 - [Section 5.1, "Installing Business Central from the ZIP file"](#)
 - [Section 5.2, "Installing Process Server from the ZIP file"](#)

**NOTE**

You should install Business Central and Process Server on different servers in production environments. However, if you install Process Server and Business Central on the same server, for example in a development environment, make the changes described in this section in the shared **standalone-full.xml** file.

- On Business Central server nodes, a user with the **rest-all** role exists. For more information, see [Section 5.4, "Creating users"](#).

Procedure

1. In the Business Central **EAP_HOME/standalone/configuration/standalone-full.xml** file, uncomment the following properties in the **<system-properties>** section and replace **<USERNAME>** and **<USER_PWD>** with the credentials of a user with the **kie-server** role:

```
<property name="org.kie.server.user" value="<USERNAME>"/>
<property name="org.kie.server.pwd" value="<USER_PWD>"/>
```

2. In the Process Server **EAP_HOME/standalone/configuration/standalone-full.xml** file, uncomment the following properties in the **<system-properties>** section.

```
<property name="org.kie.server.controller.user" value="<CONTROLLER_USER>"/>
<property name="org.kie.server.controller.pwd" value="<CONTROLLER_PWD>"/>
<property name="org.kie.server.id" value="<KIE_SERVER_ID>"/>
<property name="org.kie.server.location" value="http://<HOST>:<PORT>/kie-
server/services/rest/server"/>
<property name="org.kie.server.controller" value="<CONTROLLER_URL>"/>
```

3. Replace the following values:

- Replace **<CONTROLLER_USER>** and **<CONTROLLER_PWD>** with the credentials of a user with the **rest-all** role.
- Replace **<KIE_SERVER_ID>** with the ID or name of the Process Server installation, for example, **rhpam700-process-server-1**.
- Replace **<HOST>** with the ID or name of the Process Server host, for example, **localhost** or **192.7.8.9**.
- Replace **<PORT>** with the port of the Process Server host, for example, **8080**.



NOTE

The **org.kie.server.location** property specifies the location of Process Server.

- Replace **<CONTROLLER_URL>** with the URL of Business Central. Process Server connects to this URL during startup.
 - If you installed Business Central using the installer or Red Hat JBoss EAP zip installations, **<CONTROLLER_URL>** has this format:


```
http://<HOST>:<PORT>/business-central/rest/controller
```
 - If you are running Business Central using the **standalone.jar** file, **<CONTROLLER_URL>** has this format:


```
http://<HOST>:<PORT>/rest/controller
```

CHAPTER 6. RUNNING RED HAT PROCESS AUTOMATION MANAGER

Use this procedure to run the Red Hat Process Automation Manager on Red Hat JBoss EAP in standalone mode.

Prerequisite

Red Hat Process Automation Manager is installed and configured.

Procedure

1. In a terminal application, navigate to ***EAP_HOME/bin***.
2. Run the standalone configuration:

- On Linux or UNIX-based systems:

```
┆ $ ./standalone.sh -c standalone-full.xml
```

- On Windows:

```
┆ standalone.bat -c standalone-full.xml
```



NOTE

If you deployed Business Central without Process Server, you can start Business Central with the **standalone.sh** script without specifying the **standalone-full.xml** file. In this case, ensure that you make any configuration changes to the **standalone.xml** file before starting Business Central.

On Linux or UNIX-based systems:

```
┆ $ /standalone.sh
```

On Windows:

```
┆ standalone.bat
```

3. In a web browser, open the URL **localhost:8080/business-central**.
4. Log in using the credentials of the user that you created for Business Central in [Section 5.4, "Creating users"](#).

CHAPTER 7. INSTALLING AND RUNNING THE HEADLESS PROCESS AUTOMATION MANAGER CONTROLLER

You can configure Process Server to run in managed or unmanaged mode. If Process Server is unmanaged, you must manually create and maintain containers. If Process Server is managed, the Process Automation Manager controller manages the Process Server configuration and you interact with the controller to create and maintain containers.

The Process Automation Manager controller is integrated with Business Central. If you install Business Central, use the **Execution Server** page to create and maintain containers. However, if you do not install Business Central, you can install the headless Process Automation Manager controller and use the REST API or the Process Server Java Client API to interact with it.

7.1. INSTALLING THE HEADLESS PROCESS AUTOMATION MANAGER CONTROLLER

You can install the headless Process Automation Manager controller and use the REST API or the Process Server Java Client API to interact with it.

Prerequisites

- A backed-up Red Hat JBoss EAP installation version 7.1 or higher is available. The base directory of the Red Hat JBoss EAP installation is referred to as **EAP_HOME**.
- Sufficient user permissions to complete the installation are granted.

Procedure

1. Navigate to the [Software Downloads](#) page in the Red Hat Customer Portal (login required), and select the product and version from the drop-down options:
 - Product: Red Hat Process Automation Manager
 - Version: 7.0
2. Download **Red Hat Process Automation Manager 7.0.0 Add Ons**(the **rhpm-7.0.0-add-ons.zip** file).
3. Unzip the **rhpm-7.0.0-add-ons.zip** file. The **rhpm-7.0-controller-ee7.zip** file is in the unzipped directory.
4. Extract the **rhpm-7.0-controller-ee7** archive to a temporary directory. In the following examples this directory is called **TEMP_DIR**.
5. Copy the **TEMP_DIR/rhpm-7.0-controller-ee7/controller.war** directory to **EAP_HOME/standalone/deployments/**.

**WARNING**

Ensure that the names of the headless Process Automation Manager controller deployments you are copying do not conflict with your existing deployments in the Red Hat JBoss EAP instance.

6. Copy the contents of the ***TEMP_DIR*/rhpam-7.0-controller-ee7/SecurityPolicy/** directory to ***EAP_HOME*/bin**. When asked to overwrite files, select **Yes**.
7. In the ***EAP_HOME*/standalone/deployments/** directory, create an empty file named **controller.war.dodeploy**. This file ensures that the headless Process Automation Manager controller is automatically deployed when the server starts.

7.1.1. Creating a controller user

Before you can use the headless Process Automation Manager controller, you must create a user that has the **kie-server** role.

Prerequisite

The controller is installed in the base directory of the Red Hat JBoss EAP installation (***EAP_HOME***).

Procedure

1. In a terminal application, navigate to the ***EAP_HOME*/bin** directory.
2. Enter the following command and replace **<USER_NAME>** and **<PASSWORD>** with the user name and password of your choice.

```
$ ./add-user.sh -a --user <USER_NAME> --password <PASSWORD> --role kie-server
```

**NOTE**

Make sure that the specified user name is not the same as an existing user, role, or group. For example, do not create a user with the user name **admin**.

The password must have at least eight characters and must contain at least one number and one non-alphanumeric character, but not & (ampersand).

3. Make a note of your user name and password.

7.1.2. Configuring Process Server and the headless Process Automation Manager controller

If Process Server will be managed by the headless Process Automation Manager controller, you must edit the **standalone-full.xml** file in both the Process Server and headless Process Automation Manager controller installations, as described in this section.

Prerequisites

- Process Server is installed in the base directory of the Red Hat JBoss EAP installation (**EAP_HOME**) as described in [Chapter 5, *Installing Red Hat Process Automation Manager from ZIP files*](#) section.
- The Controller is installed in an **EAP_HOME**.



NOTE

You should install Process Server and the headless Process Automation Manager controller on different servers in production environments. However, if you install Process Server and the headless Process Automation Manager controller on the same server, for example in a development environment, make these changes in the shared **standalone-full.xml** file.

- On Process Server nodes, a user with the **kie-server** role exists.
- On the controller server nodes, a user with the **kie-server** role exists. For more information, see [Section 5.4, "Creating users"](#).

Procedure

1. In the controller **EAP_HOME/standalone/configuration/standalone-full.xml** file, add the following properties to the **<system-properties>** section and replace **<USERNAME>** and **<USER_PWD>** with the credentials of a user with the **kie-server** role:

```
<property name="org.kie.server.user" value="<USERNAME>"/>
<property name="org.kie.server.pwd" value="<USER_PWD>"/>
```

2. In the Process Server **EAP_HOME/standalone/configuration/standalone-full.xml** file, add the following properties to the **<system-properties>** section:

```
<property name="org.kie.server.controller.user" value="<CONTROLLER_USER>"/>
<property name="org.kie.server.controller.pwd" value="<CONTROLLER_PWD>"/>
<property name="org.kie.server.id" value="<KIE_SERVER_ID>"/>
<property name="org.kie.server.location" value="http://<HOST>:<PORT>/kie-
server/services/rest/server"/>
<property name="org.kie.server.controller" value="<CONTROLLER_URL>"/>
```

3. In this file, replace the following values:
 - Replace **<CONTROLLER_USER>** and **<CONTROLLER_PWD>** with the credentials of a user with the **kie-server** role.
 - Replace **<KIE_SERVER_ID>** with the ID or name of the Process Server installation, for example, **rhpam-7.0.0-process_server-1**.
 - Replace **<HOST>** with the ID or name of the Process Server host, for example, **localhost** or **192.7.8.9**.
 - Replace **<PORT>** with the port of the Process Server host, for example, **8080**.

**NOTE**

The **org.kie.server.location** property specifies the location of Process Server.

- Replace **<CONTROLLER_URL>** with the URL of the headless Process Automation Manager controller
4. Process Server connects to this URL during startup.

7.2. RUNNING THE HEADLESS PROCESS AUTOMATION MANAGER CONTROLLER

After you have installed the headless Process Automation Manager controller on Red Hat JBoss EAP, use this procedure to run the headless Process Automation Manager controller.

Prerequisite

The headless Process Automation Manager controller is installed and configured in the base directory of the Red Hat JBoss EAP installation (**EAP_HOME**).

Procedure

1. In a terminal application, navigate to **EAP_HOME/bin**.
2. Enter the following command:
 - On Linux or UNIX-based systems:


```
┆ $ ./standalone.sh
```
 - On Windows:


```
┆ standalone.bat
```
3. To verify that the Controller is working on Red Hat JBoss EAP, enter the following command where **<CONTROLLER>** and **<CONTROLLER_PWD>** is the user name and password combination that you created in [Section 7.1.1, "Creating a controller user"](#). The output of this command provides information about the Process Server instance.

```
┆ curl -X GET "http://<HOST>:<PORT>/controller/rest/controller/management/servers" -H "accept: application/xml" -u '<CONTROLLER>:<CONTROLLER_PWD>'
```

**NOTE**

Alternatively, you can use the Process Server Java API Client to access the headless Process Automation Manager controller.

CHAPTER 8. RUNNING STANDALONE BUSINESS CENTRAL

You can use the Business Central standalone JAR file to run Business Central without needing to deploy it to an application server such as Red Hat JBoss EAP.



NOTE

Red Hat supports this installation type only when it is installed on Red Hat Enterprise Linux.

Procedure

1. Navigate to the [Software Downloads](#) page in the Red Hat Customer Portal (login required), and select the product and version from the drop-down options:
 - Product: Red Hat Process Automation Manager
 - Version: 7.0
2. Download **Red Hat Process Automation Manager 7.0 Business Central Standalone(rhpam-7.0.0-business-central-standalone.jar)**.
3. Create a directory and move the **rhpam-7.0.0-business-central-standalone.jar** file to this directory.
4. In a terminal window, navigate to the directory that contains the standalone JAR file.
5. Create the **application-users.properties** file. Include an administrative user and if this Business Central instance will be a controller for Process Server, include a controller user, for example:

```
rhpamAdmin=password1
controllerUser=controllerUser1234
```

6. Create the **application-roles.properties** file to assign roles to the users that you included in the **application-users.properties** file, for example:

```
rhpamAdmin=admin
controllerUser=kie-server
```

7. Create the **application-config.yaml** configuration file with the following contents, where **<APPLICATION_USERS>** is the path to the **application-users.properties** file and **<APPLICATION_ROLES>** is the path to the **application-roles.properties** file:

```
swarm:
  security:
    security-domains:
      other:
        classic-authentication:
          login-modules:
            myloginmodule:
              code: org.kie.security.jaas.KieLoginModule
              flag: optional
              module: deployment.kie-wb-webapp.war
    management:
      security-realms:
```

```

ApplicationRealm:
  local-authentication:
    default-user: local
    allowed-users: local
    skip-group-loading: true
  properties-authentication:
    path: <APPLICATION_USERS>
    plain-text: true
  properties-authorization:
    path: <APPLICATION_ROLES>
datasource:
  management:
    wildfly:
      admin: admin

```

8. Enter the following command:

```
java -jar rhpam-7.0.0-business-central-standalone.jar -s application-config.yaml
```

In addition, you can set any properties supported by Business Central by including the **-D<property>=<value>** parameter in this command, for example:

```
java -jar rhpam-7.0.0-business-central-standalone.jar -s application-config.yaml -
-D<property>=<value> -D<property>=<value>
```

See [Section 8.1, "Supported properties"](#) for more information.

8.1. SUPPORTED PROPERTIES


When you install standalone Business Central, you can use the properties listed in this section in the following command:

```
java -jar rhpam-7.0.0-business-central-standalone.jar -s application-config.yaml -D<property>=
<value> -D<property>=<value>
```

In this command, **<property>** is a property from the following list and **<value>** is a value that you assign to that property:

- **org.uberfire.nio.git.dir**: Location of the Process Server Git directory.
- **org.uberfire.nio.git.dirname**: Name of the Process Server Git directory. Default value: **.niogit**.
- **org.uberfire.nio.git.daemon.enabled**: Enables or disables the Git daemon. Default value: **true**.
- **org.uberfire.nio.git.daemon.host**: If the Git daemon is enabled, it uses this property as the local host identifier. Default value: **localhost**.
- **org.uberfire.nio.git.daemon.port**: If the Git daemon is enabled, it uses this property as the port number. Default value: **9418**.
- **org.uberfire.nio.git.ssh.enabled**: Enables or disables the SSH daemon. Default value: **true**.
- **org.uberfire.nio.git.ssh.host**: If the SSH daemon enabled, it uses this property as the local host identifier. Default value: **localhost**.

- **org.uberfire.nio.git.SSH.port**: If the SSH daemon is enabled, it uses this property as the port number. Default value: **8001**.
- **org.uberfire.nio.git.ssh.cert.dir**: Location of the **.security** directory where local certificates are stored. Default: the working directory.
- **org.uberfire.nio.git.ssh.passphrase**: Pass phrase used to access the public key store of your operating system when cloning git repositories with SCP style URLs. Example: **git@github.com:user/repository.git**.
- **org.uberfire.nio.git.ssh.algorithm**: Algorithm used by SSH. Default value: **DSA**.



NOTE

If you plan to use RSA or any algorithm other than DSA, make sure you set up your application server to use the Bouncy Castle JCE library.

- **org.uberfire.metadata.index.dir**: Place where the Lucene **.index** directory is stored. Default: the working directory.
- **org.uberfire ldap.regex.role_mapper**: Regex pattern used to map LDAP principal names to the application role name. Note that the variable `role` must be part of the pattern because it is substituted by the application role name when matching a principal value to a role name. Default: Not used.
- **org.uberfire.sys.repo.monitor.disabled**: Disables the configuration monitor. Do not disable unless you are sure. Default value: **false**.
- **org.uberfire.secure.key**: Password used by password encryption. Default value: **org.uberfire.admin**.
- **org.uberfire.secure.alg**: Crypto algorithm used by password encryption. Default value: **PBEWithMD5AndDES**.
- **org.uberfire.domain**: Security-domain name used by uberfire. Default value: **ApplicationRealm**.
- **org.guvnor.m2repo.dir**: Place where the Maven repository folder is stored. Default value: **<working-directory>/repositories/kie**.
- **org.guvnor.project.gav.check.disabled**: Disables group ID, artifact ID, and version (GAV) checks. Default value: **false**.
- **org.kie.example**: Enables external cloning of a demo application from GitHub.
- **org.kie.build.disable-project-explorer**: Disables automatic build of a selected project in Project Explorer. Default value: **false**.
- **org.kie.verification.disable-dtable-realtime-verification**: Disables the real-time validation and verification of decision tables. Default value: **false**.
- **org.kie.server.controller**: URL for connecting with a Kie Server controller, for example: **ws://localhost:8080/business-central/websocket/controller**.

- **org.kie.server.user:** User name used to connect with the Process Server nodes from the controller. This property is only required when using this Business Central installation as a controller.
- **org.kie.server.pwd:** Password used to connect with the Process Server nodes from the controller. This property is only required when using this Business Central installation as a controller.

CHAPTER 9. SETTING MAVEN DEPENDENCIES IN YOUR PROJECT

You can use an external Maven repository to deploy a project. When you create a project, Business Central uses the Maven repositories that are configured for Business Central. You can use the Maven global or user settings to direct all Red Hat Process Automation Manager projects to retrieve dependencies from the public Red Hat Process Automation Manager repository by modifying the following files:

- The Maven **settings.xml** file.
- The Maven project object model (POM) file (**pom.xml**).

For more information, see [Packaging and deploying a Red Hat Process Automation Manager project](#) .

9.1. MODIFY THE MAVEN SETTINGS FILE

You can configure Business Central and Process Server to use an external Maven repository, such as Nexus, instead of the built-in repository. In this case, when you build projects in Business Central, all built project KJAR files are pushed into this external repository. You can progress these files through the repository as necessary to implement your integration process, and deploy the KJAR files using Business Central or the Process Server REST API.

Prerequisite

Business Central and Process Server are installed. For installation options, see [Planning a Red Hat Process Automation Manager installation](#).

Procedure

1. Create a Maven **settings.xml** file with connection and access details for your external repository. For details about the **settings.xml** file, see the Maven [Settings Reference](#).
2. Save the file in a known location, for example, **/opt/custom-config/settings.xml**.
3. In your Red Hat Process Automation Manager installation directory, navigate to the **standalone-full.xml** file. For example, if you use a Red Hat JBoss EAP installation for Red Hat Process Automation Manager, go to **\$EAP_HOME/standalone/configuration/standalone-full.xml**.
4. Open **standalone-full.xml** and under the **<system-properties>** tag, set the **kie.maven.settings.custom** property to the full path name of the **settings.xml** file. For example:

```
<property name="kie.maven.settings.custom" value="/opt/custom-config/settings.xml"/>
```

5. Start or restart Business Central and Process Server.

9.2. MODIFY THE MAVEN POM FILE

To use the correct Maven dependencies in your Red Hat Process Automation Manager project, you must add relevant bill of materials (BOM) files to the project's **pom.xml** file. When you add the BOM files, the correct versions of transitive dependencies from the provided Maven repositories are included in the project.

For more information, see [What is the mapping between RHPAM product and maven library version?](#) .

Procedure

1. Declare the BOM in the **pom.xml** file. For example:

```
<dependencyManagement>
  <dependencies>
    <dependency>
      <groupId>org.jboss.bom</groupId>
      <artifactId>rhpam-platform-bom</artifactId>
      <version>7.0.0-redhat-3</version>
      <type>pom</type>
      <scope>import</scope>
    </dependency>
  </dependencies>
</dependencyManagement>
<dependencies>
  <!-- Your dependencies -->
</dependencies>
```

2. Declare dependencies required for your project in the **<dependencies>** tag. After you import the product BOM into your project, the versions of the user-facing product dependencies are defined so you do not need to specify the **<version>** sub-element of these **<dependency>** elements. However, you must use the **<dependency>** element to declare dependencies which you want to use in your project.
3. For standalone projects that are not authored in Business Central, specify all dependencies required for your projects. In projects that you author in Business Central, the basic Drools and jBPM engine dependencies are provided automatically by Business Central.
 - For a basic Red Hat Process Automation Manager project, declare the following dependencies, depending on the features that you want to use:

Embedded jBPM engine dependencies

```
<!-- Public KIE API -->
<dependency>
  <groupId>org.kie</groupId>
  <artifactId>kie-api</artifactId>
</dependency>

<!-- jBPM engine core dependencies -->
<dependency>
  <groupId>org.jbpm</groupId>
  <artifactId>jbpm-flow</artifactId>
</dependency>

<dependency>
  <artifactId>jbpm-flow-builder</artifactId>
</dependency>

<dependency>
  <groupId>org.jbpm</groupId>
  <artifactId>jbpm-bpmn2</artifactId>
```

```

</dependency>

<dependency>
  <groupId>org.jbpm</groupId>
  <artifactId>jbpm-runtime-manager</artifactId>
</dependency>

<dependency>
  <groupId>org.jbpm</groupId>
  <artifactId>jbpm-persistence-jpa</artifactId>
</dependency>

<dependency>
  <groupId>org.jbpm</groupId>
  <artifactId>jbpm-query-jpa</artifactId>
</dependency>

<dependency>
  <groupId>org.jbpm</groupId>
  <artifactId>jbpm-audit</artifactId>
</dependency>

<dependency>
  <groupId>org.jbpm</groupId>
  <artifactId>jbpm-kie-services</artifactId>
</dependency>

<!-- Dependency needed for default WorkItemHandler implementations. -->
<dependency>
  <groupId>org.jbpm</groupId>
  <artifactId>jbpm-workitems-core</artifactId>
</dependency>

<!-- Logging dependency. You can use any logging framework compatible with slf4j. -->
<dependency>
  <groupId>ch.qos.logback</groupId>
  <artifactId>logback-classic</artifactId>
  <version>${logback.version}</version>
</dependency>

```

- For a Red Hat Process Automation Manager project that uses CDI, you typically declare the following dependencies:

CDI-enabled jBPM engine dependencies

```

<dependency>
  <groupId>org.kie</groupId>
  <artifactId>kie-api</artifactId>
</dependency>

<dependency>
  <groupId>org.jbpm</groupId>
  <artifactId>jbpm-kie-services</artifactId>
</dependency>

<dependency>

```

```
<groupId>org.jbpm</groupId>
<artifactId>jbpm-services-cdi</artifactId>
</dependency>
```

- For a basic Red Hat Process Automation Manager project, declare the following dependencies:

Embedded Drools engine dependencies

```
<dependency>
  <groupId>org.drools</groupId>
  <artifactId>drools-compiler</artifactId>
</dependency>

<!-- Dependency for persistence support. -->
<dependency>
  <groupId>org.drools</groupId>
  <artifactId>drools-persistence-jpa</artifactId>
</dependency>

<!-- Dependencies for decision tables, templates, and scorecards.
For other assets, declare org.drools:drools-workbench-models-* dependencies. -->
<dependency>
  <groupId>org.drools</groupId>
  <artifactId>drools-decisiontables</artifactId>
</dependency>
<dependency>
  <groupId>org.drools</groupId>
  <artifactId>drools-templates</artifactId>
</dependency>
<dependency>
  <groupId>org.drools</groupId>
  <artifactId>drools-scorecards</artifactId>
</dependency>

<!-- Dependency for loading KJARs from a Maven repository using KieScanner. -->
<dependency>
  <groupId>org.kie</groupId>
  <artifactId>kie-ci</artifactId>
</dependency>
```

- To use the Process Server, declare the following dependencies:

Client application Process Server dependencies

```
<dependency>
  <groupId>org.kie.server</groupId>
  <artifactId>kie-server-client</artifactId>
</dependency>
```

- To create a remote client for Red Hat Process Automation Manager, declare the following dependency:

Client dependency

-

```
<dependency>
  <groupId>org.uberfire</groupId>
  <artifactId>uberfire-rest-client</artifactId>
</dependency>
```

- When creating a JAR file that includes assets, such as rules and process definitions, specify the packaging type for your Maven project as **kjar** and use **org.kie:kie-maven-plugin** to process the **kjar** packaging type located under the **<project>** element. In the following example, **#{kie.version}** is the Maven library version listed in [What is the mapping between RHPAM product and maven library version?](#):

```
<packaging>kjar</packaging>
<build>
  <plugins>
    <plugin>
      <groupId>org.kie</groupId>
      <artifactId>kie-maven-plugin</artifactId>
      <version>#{kie.version}</version>
      <extensions>>true</extensions>
    </plugin>
  </plugins>
</build>
```

CHAPTER 10. IMPORTING PROJECTS FROM GIT REPOSITORIES

Git is a distributed version control system. It implements revisions as commit objects. When you save your changes to a repository, a new commit object in the Git repository is created.

Business Central uses Git to store project data, including assets such as rules and processes. When you create a project in Business Central, it is added to a Git repository that is connected to Business Central. If you have projects in Git repositories, you can import those projects into the Business Central Git repository through Business Central spaces.

Prerequisites

- Red Hat Process Automation Manager projects exist in an external Git repository.
- Credentials required for read access to that external Git repository are available.

Procedure

1. In Business Central, click **Menu** → **Design** → **Projects**.
2. Select or create the space into which you want to import the projects. The default space is **mySpace**.
3. Click the three vertical dots on the right side of the screen and select **Import Project**.
4. In the **Import Project** window, enter the URL and credentials for the Git repository that contains the projects that you want to import and click **Import**. The projects are added to the Business Central Git repository and are available from the current space.

CHAPTER 11. VERIFYING THE RED HAT PROCESS AUTOMATION MANAGER INSTALLATION

After you have installed Red Hat Process Automation Manager, create an asset to verify that the installation is working.

Procedure

1. In a terminal window, navigate to the **EAP_HOME/bin** directory and enter the following command to start Red Hat Process Automation Manager:

```
./standalone.sh -c standalone-full.xml
```



NOTE

If you deployed Business Central without Process Server, you can start Business Central with the **standalone.sh** script without specifying the **standalone-full.xml** file. In this case, ensure that you make any configuration changes to the **standalone.xml** file before starting Business Central.

2. In a web browser, enter **localhost:8080/business-central**.
 - If Red Hat Process Automation Manager has been configured to run from a domain name, replace **localhost** with the domain name, for example:
<http://www.example.com:8080/business-central>
 - If Red Hat Process Automation Manager has been configured to run in a cluster, replace **localhost** with the IP address of a particular node, for example:
http://<node_IP_address>:8080/business-central
3. Enter the **admin** user credentials that you created during installation. The Business Central home page appears.
4. Select **Menu** → **Design** → **Projects**.
5. Click **Try Samples** → **Mortgages** → **OK**. The Assets window appears.
6. Click **Create New Asset** → **Data Object**.
7. Enter **MyDataObject** in the **Data Object** field and click **OK**.
8. Click **Spaces** → **myteam** → **Mortgages** and confirm that **MyDataObject** is in the list of assets.
9. Delete **MyDataObject**.

CHAPTER 12. CUSTOMIZING BUSINESS CENTRAL

You can customize the Business Central login page and application header.

12.1. CUSTOMIZING THE BUSINESS CENTRAL LOGIN PAGE

You can customize the company logo and the project logo on the Business Central login page.

Procedure

1. Start Red Hat JBoss EAP and open Business Central in a web browser.
2. Copy a PNG format image to the ***EAP_HOME/standalone/deployments/business-central.war/img/*** directory in your Red Hat Process Automation Manager installation.
3. In the ***EAP_HOME/standalone/deployments/business-central.war/img/*** directory, either move or rename the existing **login-screen-logo.png** file.
4. Rename your PNG file **login-screen-logo.png**.
5. To change the project logo that appears above the **User name** and **Password** fields, replace the default image **RHPAM_Logo.svg** with a new SVG file.
6. Force a full reload of the login page, bypassing the cache, to view the changes. For example, in most Linux and Windows web browsers, press Ctrl+F5.

12.2. CUSTOMIZING BUSINESS CENTRAL APPLICATION HEADER

You can customize the Business Central application header.

Procedure

1. Start Red Hat JBoss EAP, open Business Central in a web browser, and log in with your user credentials.
2. Copy your new application header image in the SVG format to the ***EAP_HOME/standalone/deployments/business-central.war/banner/*** directory in your Red Hat Process Automation Manager installation.
3. Open the ***EAP_HOME/standalone/deployments/business-central.war/banner/banner.html*** file in a text editor.
4. Replace **logo.svg** in the **** tag with the file name of your new image:

```

```

5. Force a full reload of the login page, bypassing the cache, to view the changes. For example, in most Linux and Windows web browsers, press Ctrl+F5.

CHAPTER 13. INTEGRATING LDAP AND SSL

With Red Hat Process Automation Manager you can integrate LDAP and SSL through RH-SSO. For more information, see the [Red Hat Single Sign-On Server Administration Guide](#).

CHAPTER 14. RELATED INFORMATION

- [*Integrating Red Hat JBoss Developer Studio with Red Hat Process Automation Manager*](#)

CHAPTER 15. NEXT STEPS

- *Getting started with business processes*

APPENDIX A. VERSIONING INFORMATION

Documentation last updated on: Wednesday, July 15, 2020.