

Red Hat Enterprise Linux 4

Debugging with gdb



Red Hat Enterprise Linux 4: Debugging with gdb

Permission is granted to copy, distribute and/or modify this document under the terms of the GNU Free Documentation License, Version 1.2 or any later version published by the Free Software Foundation; with the Invariant Sections being "GNU General Public License" and "Funding Free Software", the Front-Cover texts being (a) (see below), and with the Back-Cover Texts being (b) (see below). A copy of the license is included in the section entitled "GNU Free Documentation License".

(a) The FSF's Front-Cover Text is: A GNU Manual

(b) The FSF's Back-Cover Text is: You have freedom to copy and modify this GNU Manual, like GNU software. Copies published by the Free Software Foundation raise funds for GNU development.

For a copy of the GNU General Public License, see <http://www.gnu.org/copyleft/gpl.html>.

This version is by Red Hat, Inc.



Red Hat, Inc.

1801 Varsity Drive
Raleigh NC 27606-2072 USA
Phone: +1 919 754 3700
Phone: 888 733 4281
Fax: +1 919 754 3701
PO Box 13588
Research Triangle Park NC 27709 USA

`gdb(EN)-4-HTML-RHI (2005-02-01)`

Red Hat and the Red Hat "Shadow Man" logo are registered trademarks of Red Hat, Inc. in the United States and other countries.

All other trademarks referenced herein are the property of their respective owners.

The GPG fingerprint of the `security@redhat.com` key is:

CA 20 86 86 2B D6 9D FC 65 F6 EC C4 21 91 80 CD DB 42 A6 0E

Table of Contents

1. Debugging with gdb	1
2. Summary of gdb	3
2.1. Free software	3
2.2. Free Software Needs Free Documentation	3
2.3. Contributors to gdb	4
3. A Sample gdb Session	7
4. Getting In and Out of gdb	11
4.1. Invoking gdb	11
4.1.1. Choosing files	12
4.1.2. Choosing modes	13
4.2. Quitting gdb	16
4.3. Shell commands	16
4.4. Logging output	16
5. gdb Commands	19
5.1. Command syntax	19
5.2. Command completion	19
5.3. Getting help	21
6. Running Programs Under gdb	25
6.1. Compiling for debugging	25
6.2. Starting your program	25
6.3. Your program's arguments	26
6.4. Your program's environment	27
6.5. Your program's working directory	28
6.6. Your program's input and output	28
6.7. Debugging an already-running process	29
6.8. Killing the child process	29
6.9. Debugging programs with multiple threads	30
6.10. Debugging programs with multiple processes	32
7. Stopping and Continuing	35
7.1. Breakpoints, watchpoints, and catchpoints	35
7.1.1. Setting breakpoints	35
7.1.2. Setting watchpoints	38
7.1.3. Setting catchpoints	40
7.1.4. Deleting breakpoints	41
7.1.5. Disabling breakpoints	42
7.1.6. Break conditions	43
7.1.7. Breakpoint command lists	44
7.1.8. Breakpoint menus	45
7.1.9. "Cannot insert breakpoints"	46
7.2. Continuing and stepping	46
7.3. Signals	49
7.4. Stopping and starting multi-thread programs	51
8. Examining the Stack	53
8.1. Stack frames	53
8.2. Backtraces	54
8.3. Selecting a frame	55
8.4. Information about a frame	56

9. Examining Source Files	59
9.1. Printing source lines	59
9.2. Editing source files	60
9.2.1. Choosing your editor	61
9.3. Searching source files	61
9.4. Specifying source directories	62
9.5. Source and machine code	63
10. Examining Data	65
10.1. Expressions	65
10.2. Program variables	66
10.3. Artificial arrays	67
10.4. Output formats	68
10.5. Examining memory	69
10.6. Automatic display	71
10.7. Print settings	72
10.8. Value history	77
10.9. Convenience variables	78
10.10. Registers	79
10.11. Floating point hardware	80
10.12. Vector Unit	81
10.13. Memory region attributes	81
10.13.1. Attributes	82
10.14. Copy between memory and a file	83
10.15. Character Sets	84
11. C Preprocessor Macros	89
12. Tracepoints	93
12.1. Commands to Set Tracepoints	93
12.1.1. Create and Delete Tracepoints	93
12.1.2. Enable and Disable Tracepoints	94
12.1.3. Tracepoint Passcounts	94
12.1.4. Tracepoint Action Lists	95
12.1.5. Listing Tracepoints	96
12.1.6. Starting and Stopping Trace Experiment	96
12.2. Using the collected data	97
12.2.1. <code>tfind n</code>	97
12.2.2. <code>tdump</code>	99
12.2.3. <code>save-tracepoints filename</code>	100
12.3. Convenience Variables for Tracepoints	100
13. Debugging Programs That Use Overlays	103
13.1. How Overlays Work	103
13.2. Overlay Commands	104
13.3. Automatic Overlay Debugging	106
13.4. Overlay Sample Program	107
14. Using gdb with Different Languages	109
14.1. Switching between source languages	109
14.1.1. List of filename extensions and languages	109
14.1.2. Setting the working language	110
14.1.3. Having gdb infer the source language	110
14.2. Displaying the language	110
14.3. Type and range checking	111
14.3.1. An overview of type checking	111
14.3.2. An overview of range checking	112
14.4. Supported languages	113

14.4.1. C and C++	113
14.4.2. Objective-C	119
14.4.3. Modula-2	121
14.5. Unsupported languages	126
15. Examining the Symbol Table	129
16. Altering Execution	135
16.1. Assignment to variables	135
16.2. Continuing at a different address	136
16.3. Giving your program a signal	137
16.4. Returning from a function	137
16.5. Calling program functions	137
16.6. Patching programs	138
17. gdb Files	139
17.1. Commands to specify files	139
17.2. Debugging Information in Separate Files	145
17.3. Errors reading symbol files	147
18. Specifying a Debugging Target	149
18.1. Active targets	149
18.2. Commands for managing targets	149
18.3. Choosing target byte order	151
18.4. Remote debugging	151
18.5. Kernel Object Display	151
19. Debugging remote programs	153
19.1. Connecting to a remote target	153
19.2. Using the <code>gdbserver</code> program	154
19.3. Using the <code>gdbserve.nlm</code> program	155
19.4. Remote configuration	155
19.5. Implementing a remote stub	156
19.5.1. What the stub can do for you	157
19.5.2. What you must do for the stub	157
19.5.3. Putting it all together	158
20. Configuration-Specific Information	161
20.1. Native	161
20.1.1. HP-UX	161
20.1.2. SVR4 process information	161
20.1.3. Features for Debugging djgpp Programs	161
20.1.4. Features for Debugging MS Windows PE executables	163
20.2. Embedded Operating Systems	166
20.2.1. Using <code>gdb</code> with <code>VxWorks</code>	166
20.3. Embedded Processors	168
20.3.1. ARM	168
20.3.2. Hitachi H8/300	168
20.3.3. H8/500	171
20.3.4. Mitsubishi M32R/D	171
20.3.5. M68k	171
20.3.6. MIPS Embedded	172
20.3.7. OpenRISC 1000	173
20.3.8. PowerPC	175
20.3.9. HP PA Embedded	176
20.3.10. Hitachi SH	176
20.3.11. Tsquare Sparclet	176
20.3.12. Fujitsu Sparclite	178
20.3.13. Tandem ST2000	178

20.3.14. Zilog Z8000	179
20.4. Architectures	180
20.4.1. A29K	180
20.4.2. Alpha	180
20.4.3. MIPS	180
21. Controlling gdb	181
21.1. Prompt	181
21.2. Command editing	181
21.3. Command history	181
21.4. Screen size	183
21.5. Numbers	183
21.6. Configuring the current ABI	184
21.7. Optional warnings and messages	185
21.8. Optional messages about internal happenings	186
22. Canned Sequences of Commands	189
22.1. User-defined commands	189
22.2. User-defined command hooks	190
22.3. Command files	191
22.4. Commands for controlled output	192
23. Command Interpreters	195
24. gdb Text User Interface	197
24.1. TUI overview	197
24.2. TUI Key Bindings	198
24.3. TUI Single Key Mode	200
24.4. TUI specific commands	200
24.5. TUI configuration variables	201
25. Using gdb under gnu Emacs	203
26. The gdb/mi Interface	207
26.1. Function and Purpose	207
26.2. Notation and Terminology	207
26.3. Acknowledgments	207
26.4. gdb/mi Command Syntax	207
26.4.1. gdb/mi Input Syntax	207
26.4.2. gdb/mi Output Syntax	208
26.4.3. Simple Examples of gdb/mi Interaction	210
26.5. gdb/mi Compatibility with CLI	211
26.6. gdb/mi Output Records	211
26.6.1. gdb/mi Result Records	211
26.6.2. gdb/mi Stream Records	212
26.6.3. gdb/mi Out-of-band Records	212
26.7. gdb/mi Command Description Format	212
26.7.1. Motivation	212
26.7.2. Introduction	213
26.7.3. Commands	213
26.8. gdb/mi Breakpoint table commands	213
26.8.1. The <code>-break-afterCommand</code>	213
26.8.2. The <code>-break-conditionCommand</code>	214
26.8.3. The <code>-break-deleteCommand</code>	215
26.8.4. The <code>-break-disableCommand</code>	216
26.8.5. The <code>-break-enableCommand</code>	216
26.8.6. The <code>-break-infoCommand</code>	217
26.8.7. The <code>-break-insertCommand</code>	217
26.8.8. The <code>-break-listCommand</code>	219

26.8.9. The <code>-break-watch</code> Command.....	220
26.9. gdb/mi Data Manipulation	223
26.9.1. The <code>-data-disassemble</code> Command	223
26.9.2. The <code>-data-evaluate-expression</code> Command.....	225
26.9.3. The <code>-data-list-changed-registers</code> Command	226
26.9.4. The <code>-data-list-register-names</code> Command.....	227
26.9.5. The <code>-data-list-register-values</code> Command	227
26.9.6. The <code>-data-read-memory</code> Command	229
26.9.7. The <code>-display-delete</code> Command	231
26.9.8. The <code>-display-disable</code> Command	231
26.9.9. The <code>-display-enable</code> Command	231
26.9.10. The <code>-display-insert</code> Command.....	232
26.9.11. The <code>-display-list</code> Command.....	232
26.9.12. The <code>-environment-cd</code> Command	233
26.9.13. The <code>-environment-directory</code> Command	233
26.9.14. The <code>-environment-path</code> Command.....	234
26.9.15. The <code>-environment-pwd</code> Command	235
26.10. gdb/mi Program control.....	235
26.10.1. Program termination	235
26.10.2. Examples.....	235
26.11. Command Descriptions.....	236
26.11.1. The <code>-exec-abort</code> Command.....	236
26.11.2. The <code>-exec-arguments</code> Command.....	236
26.11.3. The <code>-exec-continue</code> Command	237
26.11.4. The <code>-exec-finish</code> Command.....	237
26.11.5. The <code>-exec-interrupt</code> Command	238
26.11.6. The <code>-exec-next</code> Command	239
26.11.7. The <code>-exec-next-instruction</code> Command	239
26.11.8. The <code>-exec-return</code> Command.....	240
26.11.9. The <code>-exec-run</code> Command	241
26.11.10. The <code>-exec-show-arguments</code> Command	242
26.11.11. The <code>-exec-step</code> Command.....	242
26.11.12. The <code>-exec-step-instruction</code> Command	243
26.11.13. The <code>-exec-until</code> Command.....	243
26.11.14. The <code>-file-exec-and-symbols</code> Command	244
26.11.15. The <code>-file-exec-file</code> Command	245
26.11.16. The <code>-file-list-exec-sections</code> Command.....	245
26.11.17. The <code>-file-list-exec-source-file</code> Command	246
26.11.18. The <code>-file-list-exec-source-files</code> Command	246
26.11.19. The <code>-file-list-shared-libraries</code> Command	247
26.11.20. The <code>-file-list-symbol-files</code> Command.....	247
26.11.21. The <code>-file-symbol-file</code> Command.....	247
26.12. Miscellaneous gdb commands in gdb/mi.....	248
26.12.1. The <code>-gdb-exit</code> Command	248
26.12.2. The <code>-gdb-set</code> Command	249
26.12.3. The <code>-gdb-show</code> Command	249
26.12.4. The <code>-gdb-version</code> Command.....	250
26.12.5. The <code>-interpreter-exec</code> Command.....	250
26.12.6. Synopsis	250
26.12.7. gdb Command.....	251
26.12.8. Example	251
26.13. gdb/mi Stack Manipulation Commands	251
26.13.1. The <code>-stack-info-frame</code> Command.....	251
26.13.2. The <code>-stack-info-depth</code> Command.....	251
26.13.3. The <code>-stack-list-arguments</code> Command	252
26.13.4. The <code>-stack-list-frames</code> Command.....	253

26.13.5. The <code>-stack-list-localsCommand</code>	255
26.13.6. The <code>-stack-select-frameCommand</code>	256
26.14. gdb/mi Symbol Query Commands	256
26.14.1. The <code>-symbol-info-addressCommand</code>	256
26.14.2. The <code>-symbol-info-fileCommand</code>	257
26.14.3. The <code>-symbol-info-functionCommand</code>	257
26.14.4. The <code>-symbol-info-lineCommand</code>	258
26.14.5. The <code>-symbol-info-symbolCommand</code>	258
26.14.6. The <code>-symbol-list-functionsCommand</code>	258
26.14.7. The <code>-symbol-list-linesCommand</code>	259
26.14.8. The <code>-symbol-list-typesCommand</code>	259
26.14.9. The <code>-symbol-list-variablesCommand</code>	260
26.14.10. The <code>-symbol-locateCommand</code>	260
26.14.11. The <code>-symbol-typeCommand</code>	261
26.15. gdb/mi Target Manipulation Commands	261
26.15.1. The <code>-target-attachCommand</code>	261
26.15.2. The <code>-target-compare-sectionsCommand</code>	262
26.15.3. The <code>-target-detachCommand</code>	262
26.15.4. The <code>-target-disconnectCommand</code>	262
26.15.5. The <code>-target-downloadCommand</code>	263
26.15.6. The <code>-target-exec-statusCommand</code>	265
26.15.7. The <code>-target-list-available-targetsCommand</code>	265
26.15.8. The <code>-target-list-current-targetsCommand</code>	266
26.15.9. The <code>-target-list-parametersCommand</code>	266
26.15.10. The <code>-target-selectCommand</code>	266
26.16. gdb/mi Thread Commands.....	267
26.16.1. The <code>-thread-infoCommand</code>	267
26.16.2. The <code>-thread-list-all-threadsCommand</code>	268
26.16.3. The <code>-thread-list-idsCommand</code>	268
26.16.4. The <code>-thread-selectCommand</code>	269
26.17. gdb/mi Tracepoint Commands.....	270
26.18. gdb/mi Variable Objects.....	270
26.18.1. Motivation for Variable Objects in gdb/mi	270
26.18.2. Introduction to Variable Objects in gdb/mi.....	270
26.18.3. Description And Use of Operations on Variable Objects	271
26.18.4. The <code>-var-createCommand</code>	271
26.18.5. The <code>-var-deleteCommand</code>	272
26.18.6. The <code>-var-set-formatCommand</code>	272
26.18.7. The <code>-var-show-formatCommand</code>	272
26.18.8. The <code>-var-info-num-childrenCommand</code>	273
26.18.9. The <code>-var-list-childrenCommand</code>	273
26.18.10. The <code>-var-info-typeCommand</code>	273
26.18.11. The <code>-var-info-expressionCommand</code>	274
26.18.12. The <code>-var-show-attributes Command</code>	274
26.18.13. The <code>-var-evaluate-expression Command</code>	274
26.18.14. The <code>-var-assignCommand</code>	275
26.18.15. The <code>-var-updateCommand</code>	275
27. gdb Annotations	277
27.1. What is an Annotation?.....	277
27.2. The Server Prefix	277
27.3. Values.....	277
27.4. Frames.....	279
27.5. Displays.....	281
27.6. Annotation for gdb Input	281
27.7. Errors.....	282

27.8. Information on Breakpoints	282
27.9. Invalidation Notices	283
27.10. Running the Program	283
27.11. Displaying Source	284
27.12. Annotations We Might Want in the Future	285
28. Reporting Bugs in gdb	287
28.1. Have you found a bug?	287
28.2. How to report bugs	287
29. Command Line Editing	291
29.1. Introduction to Line Editing	291
29.2. Readline Interaction	291
29.2.1. Readline Bare Essentials	291
29.2.2. Readline Movement Commands	292
29.2.3. Readline Killing Commands	292
29.2.4. Readline Arguments	293
29.2.5. Searching for Commands in the History	293
29.3. Readline Init File	294
29.3.1. Readline Init File Syntax	294
29.3.2. Conditional Init Constructs	298
29.3.3. Sample Init File	299
29.4. Bindable Readline Commands	301
29.4.1. Commands For Moving	301
29.4.2. Commands For Manipulating The History	302
29.4.3. Commands For Changing Text	303
29.4.4. Killing And Yanking	304
29.4.5. Specifying Numeric Arguments	305
29.4.6. Letting Readline Type For You	305
29.4.7. Keyboard Macros	306
29.4.8. Some Miscellaneous Commands	306
29.5. Readline vi Mode	308
30. Using History Interactively	309
30.1. History Expansion	309
30.1.1. Event Designators	309
30.1.2. Word Designators	310
30.1.3. Modifiers	311
A. Formatting Documentation	313
B. Installing gdb	315
B.1. Compiling gdb in another directory	316
B.2. Specifying names for hosts and targets	317
B.3. <code>configure</code> options	318
C. Maintenance Commands	319
D. gdb Remote Serial Protocol	321
D.1. Overview	321
D.2. Packets	322
D.3. Stop Reply Packets	330
D.4. General Query Packets	331
D.5. Register Packet Format	334
D.6. Examples	334
D.7. File-I/O remote protocol extension	335
D.7.1. File-I/O Overview	335
D.7.2. Protocol basics	335
D.7.3. The <code>Frequest</code> packet	336
D.7.4. The <code>Freply</code> packet	336

D.7.5. Memory transfer.....	337
D.7.6. The Ctrl-C message.....	337
D.7.7. Console I/O	337
D.7.8. The isatty(3) call	338
D.7.9. The system(3) call.....	338
D.7.10. List of supported calls	338
D.7.11. Protocol specific representation of datatypes.....	347
D.7.12. Constants.....	349
D.7.13. File-I/O Examples.....	350
E. The GDB Agent Expression Mechanism.....	353
E.1. General Bytecode Design	353
E.2. Bytecode Descriptions.....	355
E.3. Using Agent Expressions	359
E.4. Varying Target Capabilities	359
E.5. Tracing on Symmetrix	360
E.6. Rationale.....	361
F. GNU GENERAL PUBLIC LICENSE.....	365
F.1. Preamble	365
F.2. How to Apply These Terms to Your New Programs.....	368
G. GNU Free Documentation License.....	371
G.1. ADDENDUM: How to use this License for your documents.....	375
Index.....	377



Chapter 1.

Debugging with gdb

This file describes gdb, the gnu symbolic debugger.

This is the Ninth Edition, for gdb Version 2003-07-22-cvs.

Copyright (C) 1988-2003 Free Software Foundation, Inc.

Summary of gdb

The purpose of a debugger such as `gdb` is to allow you to see what is going on "inside" another program while it executes--or what another program was doing at the moment it crashed.

`gdb` can do four main kinds of things (plus other things in support of these) to help you catch bugs in the act:

- Start your program, specifying anything that might affect its behavior.
- Make your program stop on specified conditions.
- Examine what has happened, when your program has stopped.
- Change things in your program, so you can experiment with correcting the effects of one bug and go on to learn about another.

You can use `gdb` to debug programs written in C and C++. For more information, (refer to Section 14.4 *Supported languages*. For more information, (refer to Section 14.4.1 *C and C++*.

Support for Modula-2 is partial. For information on Modula-2, refer to (refer to Section 14.4.3 *Modula-2*.

Debugging Pascal programs which use sets, subranges, file variables, or nested functions does not currently work. `gdb` does not support entering expressions, printing values, or similar features using Pascal syntax.

`gdb` can be used to debug programs written in Fortran, although it may be necessary to refer to some variables with a trailing underscore.

`gdb` can be used to debug programs written in Objective-C, using either the Apple/NeXT or the GNU Objective-C runtime.

2.1. Free software

`gdb` is *free software*, protected by the `gnu` General Public License (GPL). The GPL gives you the freedom to copy or adapt a licensed program--but every person getting a copy also gets with it the freedom to modify that copy (which means that they must get access to the source code), and the freedom to distribute further copies. Typical software companies use copyrights to limit your freedoms; the Free Software Foundation uses the GPL to preserve these freedoms.

Fundamentally, the General Public License is a license which says that you have these freedoms and that you cannot take these freedoms away from anyone else.

2.2. Free Software Needs Free Documentation

The biggest deficiency in the free software community today is not in the software--it is the lack of good free documentation that we can include with the free software. Many of our most important programs do not come with free reference manuals and free introductory texts. Documentation is an essential part of any software package; when an important free software package does not come with a free manual and a free tutorial, that is a major gap. We have many such gaps today.

Consider Perl, for instance. The tutorial manuals that people normally use are non-free. How did this come about? Because the authors of those manuals published them with restrictive terms--no copying, no modification, source files not available--which exclude them from the free software world.

That wasn't the first time this sort of thing happened, and it was far from the last. Many times we have heard a GNU user eagerly describe a manual that he is writing, his intended contribution to the community, only to learn that he had ruined everything by signing a publication contract to make it non-free.

Free documentation, like free software, is a matter of freedom, not price. The problem with the non-free manual is not that publishers charge a price for printed copies--that in itself is fine. (The Free Software Foundation sells printed copies of manuals, too.) The problem is the restrictions on the use of the manual. Free manuals are available in source code form, and give you permission to copy and modify. Non-free manuals do not allow this.

The criteria of freedom for a free manual are roughly the same as for free software. Redistribution (including the normal kinds of commercial redistribution) must be permitted, so that the manual can accompany every copy of the program, both on-line and on paper.

Permission for modification of the technical content is crucial too. When people modify the software, adding or changing features, if they are conscientious they will change the manual too--so they can provide accurate and clear documentation for the modified program. A manual that leaves you no choice but to write a new manual to document a changed version of the program is not really available to our community.

Some kinds of limits on the way modification is handled are acceptable. For example, requirements to preserve the original author's copyright notice, the distribution terms, or the list of authors, are ok. It is also no problem to require modified versions to include notice that they were modified. Even entire sections that may not be deleted or changed are acceptable, as long as they deal with nontechnical topics (like this one). These kinds of restrictions are acceptable because they don't obstruct the community's normal use of the manual.

However, it must be possible to modify all the *technical* content of the manual, and then distribute the result in all the usual media, through all the usual channels. Otherwise, the restrictions obstruct the use of the manual, it is not free, and we need another manual to replace it.

Please spread the word about this issue. Our community continues to lose manuals to proprietary publishing. If we spread the word that free software needs free reference manuals and free tutorials, perhaps the next person who wants to contribute by writing documentation will realize, before it is too late, that only free manuals contribute to the free software community.

If you are writing documentation, please insist on publishing it under the GNU Free Documentation License or another free documentation license. Remember that this decision requires your approval--you don't have to let the publisher decide. Some commercial publishers will use a free license if you insist, but they will not propose the option; it is up to you to raise the issue and say firmly that this is what you want. If the publisher you are dealing with refuses, please try other publishers. If you're not sure whether a proposed license is free, write to <mailto:licensing@@gnu.org>.

You can encourage commercial publishers to sell more free, copylefted manuals and tutorials by buying them, and particularly by buying copies from the publishers that paid for their writing or for major improvements. Meanwhile, try to avoid buying non-free documentation at all. Check the distribution terms of a manual before you buy it, and insist that whoever seeks your business must respect your freedom. Check the history of the book, and try to reward the publishers that have paid or pay the authors to work on it.

The Free Software Foundation maintains a list of free documentation published by other publishers, at <http://www.fsf.org/doc/other-free-books.html>.

2.3. Contributors to gdb

Richard Stallman was the original author of gdb, and of many other gnu programs. Many others have contributed to its development. This section attempts to credit major contributors. One of the virtues of free software is that everyone is free to contribute to it; with regret, we cannot actually acknowledge everyone here. The file `ChangeLog` in the gdb distribution approximates a blow-by-blow account.

Changes much prior to version 2.0 are lost in the mists of time.

Plea: Additions to this section are particularly welcome. If you or your friends (or enemies, to be even-handed) have been unfairly omitted from this list, we would like to add your names!

So that they may not regard their many labors as thankless, we particularly thank those who shepherded gdb through major releases: Andrew Cagney (releases 6.0, 5.3, 5.2, 5.1 and 5.0); Jim Blandy (release 4.18); Jason Molenda (release 4.17); Stan Shebs (release 4.14); Fred Fish (releases 4.16, 4.15, 4.13, 4.12, 4.11, 4.10, and 4.9); Stu Grossman and John Gilmore (releases 4.8, 4.7, 4.6, 4.5, and 4.4); John Gilmore (releases 4.3, 4.2, 4.1, 4.0, and 3.9); Jim Kingdon (releases 3.5, 3.4, and 3.3); and Randy Smith (releases 3.2, 3.1, and 3.0).

Richard Stallman, assisted at various times by Peter TerMaat, Chris Hanson, and Richard Mlynarik, handled releases through 2.8.

Michael Tiemann is the author of most of the gnu C++ support in gdb, with significant additional contributions from Per Bothner and Daniel Berlin. James Clark wrote the gnu C++ demangler. Early work on C++ was by Peter TerMaat (who also did much general update work leading to release 3.0).

gdb uses the BFD subroutine library to examine multiple object-file formats; BFD was a joint project of David V. Henkel-Wallace, Rich Pixley, Steve Chamberlain, and John Gilmore.

David Johnson wrote the original COFF support; Pace Willison did the original support for encapsulated COFF.

Brent Benson of Harris Computer Systems contributed DWARF 2 support.

Adam de Boor and Bradley Davis contributed the ISI Optimum V support. Per Bothner, Noboyuki Hikichi, and Alessandro Forin contributed MIPS support. Jean-Daniel Fekete contributed Sun 386i support. Chris Hanson improved the HP9000 support. Noboyuki Hikichi and Tomoyuki Hasei contributed Sony/News OS 3 support. David Johnson contributed Encore Umax support. Jyrki Kuoppala contributed Altos 3068 support. Jeff Law contributed HP PA and SOM support. Keith Packard contributed NS32K support. Doug Rabson contributed Acorn Risc Machine support. Bob Rusk contributed Harris Nighthawk CX-UX support. Chris Smith contributed Convex support (and Fortran debugging). Jonathan Stone contributed Pyramid support. Michael Tiemann contributed SPARC support. Tim Tucker contributed support for the Gould NP1 and Gould Powernode. Pace Willison contributed Intel 386 support. Jay Vosburgh contributed Symmetry support. Marko Mlinar contributed OpenRISC 1000 support.

Andreas Schwab contributed M68K gnu/Linux support.

Rich Schaefer and Peter Schauer helped with support of SunOS shared libraries.

Jay Fenlason and Roland McGrath ensured that gdb and GAS agree about several machine instruction sets.

Patrick Duval, Ted Goldstein, Vikram Koka and Glenn Engel helped develop remote debugging. Intel Corporation, Wind River Systems, AMD, and ARM contributed remote debugging modules for the i960, VxWorks, A29K UDI, and RDI targets, respectively.

Brian Fox is the author of the readline libraries providing command-line editing and command history.

Andrew Beers of SUNY Buffalo wrote the language-switching code, the Modula-2 support, and contributed the Languages chapter of this manual.

Fred Fish wrote most of the support for Unix System Vr4. He also enhanced the command-completion support to cover C++ overloaded symbols.

Hitachi America, Ltd. sponsored the support for H8/300, H8/500, and Super-H processors.

NEC sponsored the support for the v850, Vr4xxx, and Vr5xxx processors.

Mitsubishi sponsored the support for D10V, D30V, and M32R/D processors.

Toshiba sponsored the support for the TX39 Mips processor.

Matsushita sponsored the support for the MN10200 and MN10300 processors.

Fujitsu sponsored the support for SPARClike and FR30 processors.

Kung Hsu, Jeff Law, and Rick Sladkey added support for hardware watchpoints.

Michael Snyder added support for tracepoints.

Stu Grossman wrote gdbserver.

Jim Kingdon, Peter Schauer, Ian Taylor, and Stu Grossman made nearly innumerable bug fixes and cleanups throughout gdb.

The following people at the Hewlett-Packard Company contributed support for the PA-RISC 2.0 architecture, HP-UX 10.20, 10.30, and 11.0 (narrow mode), HP's implementation of kernel threads, HP's aC++ compiler, and the terminal user interface: Ben Krepp, Richard Title, John Bishop, Susan Macchia, Kathy Mann, Satish Pai, India Paul, Steve Rehrauer, and Elena Zannoni. Kim Haase provided HP-specific information in this manual.

DJ Delorie ported gdb to MS-DOS, for the DJGPP project. Robert Hoehne made significant contributions to the DJGPP port.

Cygnus Solutions has sponsored gdb maintenance and much of its development since 1991. Cygnus engineers who have worked on gdb fulltime include Mark Alexander, Jim Blandy, Per Bothner, Kevin Buettner, Edith Epstein, Chris Faylor, Fred Fish, Martin Hunt, Jim Ingham, John Gilmore, Stu Grossman, Kung Hsu, Jim Kingdon, John Metzler, Fernando Nasser, Geoffrey Noer, Dawn Perchik, Rich Pixley, Zdenek Radouch, Keith Seitz, Stan Shebs, David Taylor, and Elena Zannoni. In addition, Dave Brolley, Ian Carmichael, Steve Chamberlain, Nick Clifton, JT Conklin, Stan Cox, DJ Delorie, Ulrich Drepper, Frank Eigler, Doug Evans, Sean Fagan, David Henkel-Wallace, Richard Henderson, Jeff Holcomb, Jeff Law, Jim Lemke, Tom Lord, Bob Manson, Michael Meissner, Jason Merrill, Catherine Moore, Drew Moseley, Ken Raeburn, Gavin Romig-Koch, Rob Savoye, Jamie Smith, Mike Stump, Ian Taylor, Angela Thomas, Michael Tiemann, Tom Tromey, Ron Unrau, Jim Wilson, and David Zuhn have made contributions both large and small.

Jim Blandy added support for preprocessor macros, while working for Red Hat.

A Sample gdb Session

You can use this manual at your leisure to read all about gdb. However, a handful of commands are enough to get started using the debugger. This chapter illustrates those commands.

One of the preliminary versions of `gnu m4` (a generic macro processor) exhibits the following bug: sometimes, when we change its quote strings from the default, the commands used to capture one macro definition within another stop working. In the following short `m4` session, we define a macro `foo` which expands to `0000`; we then use the `m4` built-in `defn` to define `bar` as the same thing. However, when we change the open quote string to `<QUOTE>` and the close quote string to `<UNQUOTE>`, the same procedure fails to define a new synonym `baz`:

```
$ cd gnu/m4
$ ./m4
define(foo,0000)

foo
0000
define(bar,defn('foo'))

bar
0000
changequote(<QUOTE>,<UNQUOTE>)

define(baz,defn(<QUOTE>foo<UNQUOTE>))
baz
C-d
m4: End of input: 0: fatal error: EOF in string
```

Let us use `gdb` to try to see what is going on.

```
$ gdb m4
gdb is free software and you are welcome to distribute copies
of it under certain conditions; type "show copying" to see
the conditions.
There is absolutely no warranty for gdb; type "show warranty"
for details.

gdb 2003-07-22-cvs, Copyright 1999 Free Software Foundation, Inc...
(gdb)
```

`gdb` reads only enough symbol data to know where to find the rest when needed; as a result, the first prompt comes up very quickly. We now tell `gdb` to use a narrower display width than usual, so that examples fit in this manual.

```
(gdb) set width 70
```

We need to see how the `m4` built-in `changequote` works. Having looked at the source, we know the relevant subroutine is `m4_changequote`, so we set a breakpoint there with the `gdb break` command.

```
(gdb) break m4_changequote
Breakpoint 1 at 0x62f4: file builtin.c, line 879.
```

Using the `run` command, we start `m4` running under `gdb` control; as long as control does not reach the `m4_changequote` subroutine, the program runs as usual:

```
(gdb) run
Starting program: /work/Editorial/gdb/gnu/m4/m4
define (foo,0000)

foo
0000
```

To trigger the breakpoint, we call `changequote`. `gdb` suspends execution of `m4`, displaying information about the context where it stops.

```
changequote (<QUOTE>, <UNQUOTE>)

Breakpoint 1, m4_changequote (argc=3, argv=0x33c70)
  at builtin.c:879
879     if (bad_argc (TOKEN_DATA_TEXT (argv[0]), argc, 1, 3))
```

Now we use the command `n` (`next`) to advance execution to the next line of the current function.

```
(gdb) n
882     set_quotes ((argc >= 2) ? TOKEN_DATA_TEXT (argv[1]) \
: nil,
```

`set_quotes` looks like a promising subroutine. We can go into it by using the command `s` (`step`) instead of `next`. `step` goes to the next line to be executed in *any* subroutine, so it steps into `set_quotes`.

```
(gdb) s
set_quotes (lq=0x34c78 "<QUOTE>", rq=0x34c88 "<UNQUOTE>")
  at input.c:530
530     if (lquote != def_lquote)
```

The display that shows the subroutine where `m4` is now suspended (and its arguments) is called a stack frame display. It shows a summary of the stack. We can use the `backtrace` command (which can also be spelled `bt`), to see where we are in the stack as a whole: the `backtrace` command displays a stack frame for each active subroutine.

```
(gdb) bt
#0  set_quotes (lq=0x34c78 "<QUOTE>", rq=0x34c88 "<UNQUOTE>")
  at input.c:530
#1  0x6344 in m4_changequote (argc=3, argv=0x33c70)
  at builtin.c:882
#2  0x8174 in expand_macro (sym=0x33320) at macro.c:242
#3  0x7a88 in expand_token (obs=0x0, t=209696, td=0xf7ffa30)
  at macro.c:71
```

```
#4 0x79dc in expand_input () at macro.c:40
#5 0x2930 in main (argc=0, argv=0xf7fffb20) at m4.c:195
```

We step through a few more lines to see what happens. The first two times, we can use `s`; the next two times we use `n` to avoid falling into the `xstrdup` subroutine.

```
(gdb) s
0x3b5c 532         if (rquote != def_rquote)
(gdb) s
0x3b80 535         lquote = (lq == nil || *lq == '\0') ? \
def_lquote : xstrdup(lq);
(gdb) n
536         rquote = (rq == nil || *rq == '\0') ? def_rquote\
: xstrdup(rq);
(gdb) n
538         len_lquote = strlen(rquote);
```

The last line displayed looks a little odd; we can examine the variables `lquote` and `rquote` to see if they are in fact the new left and right quotes we specified. We use the command `p` (print) to see their values.

```
(gdb) p lquote
$1 = 0x35d40 "<QUOTE>"
(gdb) p rquote
$2 = 0x35d50 "<UNQUOTE>"
```

`lquote` and `rquote` are indeed the new left and right quotes. To look at some context, we can display ten lines of source surrounding the current line with the `l` (list) command.

```
(gdb) l
533         xfree(rquote);
534
535         lquote = (lq == nil || *lq == '\0') ? def_lquote\
: xstrdup (lq);
536         rquote = (rq == nil || *rq == '\0') ? def_rquote\
: xstrdup (rq);
537
538         len_lquote = strlen(rquote);
539         len_rquote = strlen(lquote);
540     }
541
542     void
```

Let us step past the two lines that set `len_lquote` and `len_rquote`, and then examine the values of those variables.

```
(gdb) n
539         len_rquote = strlen(lquote);
(gdb) n
540     }
(gdb) p len_lquote
$3 = 9
```

```
(gdb) p len_rquote
$4 = 7
```

That certainly looks wrong, assuming `len_lquote` and `len_rquote` are meant to be the lengths of `lquote` and `rquote` respectively. We can set them to better values using the `p` command, since it can print the value of any expression--and that expression can include subroutine calls and assignments.

```
(gdb) p len_lquote=strlen(lquote)
$5 = 7
(gdb) p len_rquote=strlen(rquote)
$6 = 9
```

Is that enough to fix the problem of using the new quotes with the `m4` built-in `defn`? We can allow `m4` to continue executing with the `c` (`continue`) command, and then try the example that caused trouble initially:

```
(gdb) c
Continuing.

define (baz, defn (<QUOTE> foo<UNQUOTE>))
baz
0000
```

Success! The new quotes now work just as well as the default ones. The problem seems to have been just the two typos defining the wrong lengths. We allow `m4` exit by giving it an EOF as input:

```
C-d
Program exited normally.
```

The message `Program exited normally.` is from `gdb`; it indicates `m4` has finished executing. We can end our `gdb` session with the `gdb quit` command.

```
(gdb) quit
```

Getting In and Out of gdb

This chapter discusses how to start gdb, and how to get out of it. The essentials are:

- type `gdb` to start gdb.
- type `quit` or `C-d` to exit.

4.1. Invoking gdb

Invoke gdb by running the program `gdb`. Once started, gdb reads commands from the terminal until you tell it to exit.

You can also run `gdb` with a variety of arguments and options, to specify more of your debugging environment at the outset.

The command-line options described here are designed to cover a variety of situations; in some environments, some of these options may effectively be unavailable.

The most usual way to start gdb is with one argument, specifying an executable program:

```
gdb program
```

You can also start with both an executable program and a core file specified:

```
gdb program core
```

You can, instead, specify a process ID as a second argument, if you want to debug a running process:

```
gdb program 1234
```

would attach gdb to process 1234 (unless you also have a file named 1234; gdb does check for a core file first).

Taking advantage of the second command-line argument requires a fairly complete operating system; when you use gdb as a remote debugger attached to a bare board, there may not be any notion of "process", and there is often no way to get a core dump. gdb will warn you if it is unable to attach or to read core dumps.

You can optionally have `gdb` pass any arguments after the executable file to the inferior using `-args`. This option stops option processing.

```
gdb --args gcc -O2 -c foo.c
```

This will cause `gdb` to debug `gcc`, and to set `gcc`'s command-line arguments (Refer to Section 6.3 *Your program's arguments*) to `-O2 -c foo.c`.

You can run `gdb` without printing the front material, which describes gdb's non-warranty, by specifying `-silent`:

```
gdb -silent
```

You can further control how gdb starts up by using command-line options. gdb itself can remind you of the options available.

Type

```
gdb -help
```

to display all available options and briefly describe their use (gdb -h is a shorter equivalent).

All options and command line arguments you give are processed in sequential order. The order makes a difference when the -x option is used.

4.1.1. Choosing files

When gdb starts, it reads any arguments other than options as specifying an executable file and core file (or process ID). This is the same as if the arguments were specified by the -se and -c (or -p options respectively. (gdb reads the first argument that does not have an associated option flag as equivalent to the -se option followed by that argument; and the second argument that does not have an associated option flag, if any, as equivalent to the -c/-p option followed by that argument.) If the second argument begins with a decimal digit, gdb will first attempt to attach to it as a process, and if that fails, attempt to open it as a corefile. If you have a corefile whose name begins with a digit, you can prevent gdb from treating it as a pid by prefixing it with ./, eg. ./12345.

If gdb has not been configured to included core file support, such as for most embedded targets, then it will complain about a second argument and ignore it.

Many options have both long and short forms; both are shown in the following list. gdb also recognizes the long forms if you truncate them, so long as enough of the option is present to be unambiguous. (If you prefer, you can flag option arguments with - rather than -, though we illustrate the more usual convention.)

```
-symbols file
```

```
-s file
```

Read symbol table from file *file*.

```
-exec file
```

```
-e file
```

Use file *file* as the executable file to execute when appropriate, and for examining pure data in conjunction with a core dump.

```
-se file
```

Read symbol table from file *file* and use it as the executable file.

```
-core file
```

```
-c file
```

Use file *file* as a core dump to examine.

```
-c number
-pid number
-p number
```

Connect to process ID `number`, as with the `attach` command. If there is no such process, `gdb` will attempt to open a core file named `number`.

```
-command file
-x file
```

Execute `gdb` commands from file `file`. Refer to Section 22.3 *Command files*.

```
-directory directory
-d directory
```

Add `directory` to the path to search for source files.

```
-m
-mapped
```

Warning: this option depends on operating system facilities that are not supported on all systems. If memory-mapped files are available on your system through the `mmap` system call, you can use this option to have `gdb` write the symbols from your program into a reusable file in the current directory. If the program you are debugging is called `/tmp/fred`, the mapped symbol file is `/tmp/fred.syms`. Future `gdb` debugging sessions notice the presence of this file, and can quickly map in symbol information from it, rather than reading the symbol table from the executable program.

The `.syms` file is specific to the host machine where `gdb` is run. It holds an exact image of the internal `gdb` symbol table. It cannot be shared across multiple host platforms.

```
-r
-readnow
```

Read each symbol file's entire symbol table immediately, rather than the default, which is to read it incrementally as it is needed. This makes startup slower, but makes future operations faster.

You typically combine the `-mapped` and `-readnow` options in order to build a `.syms` file that contains complete symbol information. (Refer to Section 17.1 *Commands to specify files* for information on `.syms` files.) A simple `gdb` invocation to do nothing but build a `.syms` file for future use is:

```
gdb -batch -nx -mapped -readnow programname
```

4.1.2. Choosing modes

You can run `gdb` in various alternative modes--for example, in batch mode or quiet mode.

```
-nx
-n
```

Do not execute commands found in any initialization files. Normally, `gdb` executes the commands in these files after all the command options and arguments have been processed. Refer to Section 22.3 *Command files*.

-quiet
-silent
-q

"Quiet". Do not print the introductory and copyright messages. These messages are also suppressed in batch mode.

-batch

Run in batch mode. Exit with status 0 after processing all the command files specified with `-x` (and all commands from initialization files, if not inhibited with `-n`). Exit with nonzero status if an error occurs in executing the gdb commands in the command files.

Batch mode may be useful for running gdb as a filter, for example to download and run a program on another computer; in order to make this more useful, the message

```
Program exited normally.
```

(which is ordinarily issued whenever a program running under gdb control terminates) is not issued when running in batch mode.

-nowindows
-nw

"No windows". If gdb comes with a graphical user interface (GUI) built in, then this option tells gdb to only use the command-line interface. If no GUI is available, this option has no effect.

-windows
-w

If gdb includes a GUI, then this option requires it to be used if possible.

-cd *directory*

Run gdb using *directory* as its working directory, instead of the current directory.

-fullname
-f

gnu Emacs sets this option when it runs gdb as a subprocess. It tells gdb to output the full file name and line number in a standard, recognizable fashion each time a stack frame is displayed (which includes each time your program stops). This recognizable format looks like two `\032` characters, followed by the file name, line number and character position separated by colons, and a newline. The Emacs-to-gdb interface program uses the two `\032` characters as a signal to display the source code for the frame.

-epoch

The Epoch Emacs-gdb interface sets this option when it runs gdb as a subprocess. It tells gdb to modify its print routines so as to allow Epoch to display values of expressions in a separate window.

-annotate *level*

This option sets the *annotation level* inside gdb. Its effect is identical to using `set annotate level` (refer to Chapter 27 *gdb Annotations*). Annotation level controls how much information does gdb print together with its prompt, values of expressions, source lines, and other types of output. Level 0 is the normal, level 1 is for use when gdb is run as a subprocess of gnu Emacs, level 2 is the maximum annotation suitable for programs that control gdb.

`-async`

Use the asynchronous event loop for the command-line interface. gdb processes all events, such as user keyboard input, via a special event loop. This allows gdb to accept and process user commands in parallel with the debugged process being run¹, so you don't need to wait for control to return to gdb before you type the next command. (*Note:* as of version 5.1, the target side of the asynchronous operation is not yet in place, so `-async` does not work fully yet.)

When the standard input is connected to a terminal device, gdb uses the asynchronous event loop by default, unless disabled by the `-noasync` option.

`-noasync`

Disable the asynchronous event loop for the command-line interface.

`-args`

Change interpretation of command line so that arguments following the executable file are passed as command line arguments to the inferior. This option stops option processing.

`-baud bps`

`-b bps`

Set the line speed (baud rate or bits per second) of any serial interface used by gdb for remote debugging.

`-tty device`

`-t device`

Run using `device` for your program's standard input and output.

`-tui`

Activate the Terminal User Interface when starting. The Terminal User Interface manages several text windows on the terminal, showing source, assembly, registers and gdb command outputs (refer to Chapter 24 *`gdb Text User Interface`*). Do not use this option if you run gdb from Emacs (refer to Chapter 25 *`Using gdb under gnu Emacs`*).

`-interpreter interp`

Use the interpreter `interp` for interface with the controlling program or device. This option is meant to be set by programs which communicate with gdb using it as a back end (refer to Chapter 23 *`Command Interpreters`*).

`-interpreter=mi` (or `-interpreter=mi2`) causes gdb to use the current *`gdb/mi interface`* (refer to Chapter 26 *`The gdb/mi Interface`*). The previous *`gdb/mi interface`*, included in gdb version 5.3, can be selected with `-interpreter=mi1`. Earlier *`gdb/mi interfaces`* are not supported.

`-write`

Open the executable and core files for both reading and writing. This is equivalent to the `set write on` command inside gdb (refer to Section 16.6 *`Patching programs`*).

`-statistics`

This option causes gdb to print statistics about time and memory usage after it completes each command and returns to the prompt.

1. gdb built with djgpp tools for MS-DOS/MS-Windows supports this mode of operation, but the event loop is suspended when the debuggee runs.

```
-version
```

This option causes `gdb` to print its version number and no-warranty blurb, and exit.

4.2. Quitting gdb

```
quit [expression]
q
```

To exit `gdb`, use the `quit` command (abbreviated `q`), or type an end-of-file character (usually `C-d`). If you do not supply `expression`, `gdb` will terminate normally; otherwise it will terminate using the result of `expression` as the error code.

An interrupt (often `C-c`) does not exit from `gdb`, but rather terminates the action of any `gdb` command that is in progress and returns to `gdb` command level. It is safe to type the interrupt character at any time because `gdb` does not allow it to take effect until a time when it is safe.

If you have been using `gdb` to control an attached process or device, you can release it with the `detach` command (refer to Section 6.7 *Debugging an already-running process*).

4.3. Shell commands

If you need to execute occasional shell commands during your debugging session, there is no need to leave or suspend `gdb`; you can just use the `shell` command.

```
shell command string
```

Invoke a standard shell to execute `command string`. If it exists, the environment variable `SHELL` determines which shell to run. Otherwise `gdb` uses the default shell (`/bin/sh` on Unix systems, `COMMAND.COM` on MS-DOS, etc.).

The utility `make` is often needed in development environments. You do not have to use the `shell` command for this purpose in `gdb`:

```
make make-args
```

Execute the `make` program with the specified arguments. This is equivalent to `shell make make-args`.

4.4. Logging output

You may want to save the output of `gdb` commands to a file. There are several commands to control `gdb`'s logging.

```
set logging on
```

Enable logging.

```
set logging off
```

Disable logging.

```
set logging file file
```

Change the name of the current logfile. The default logfile is `gdb.txt`.

```
set logging overwrite [on|off]
```

By default, `gdb` will append to the logfile. Set `overwrite` if you want `set logging on` to overwrite the logfile instead.

```
set logging redirect [on|off]
```

By default, `gdb` output will go to both the terminal and the logfile. Set `redirect` if you want output to go only to the log file.

```
show logging
```

Show the current values of the logging settings.

gdb Commands

You can abbreviate a `gdb` command to the first few letters of the command name, if that abbreviation is unambiguous; and you can repeat certain `gdb` commands by typing just [RET]. You can also use the [TAB] key to get `gdb` to fill out the rest of a word in a command (or to show you the alternatives available, if there is more than one possibility).

5.1. Command syntax

A `gdb` command is a single line of input. There is no limit on how long it can be. It starts with a command name, which is followed by arguments whose meaning depends on the command name. For example, the command `step` accepts an argument which is the number of times to step, as in `step 5`. You can also use the `step` command with no arguments. Some commands do not allow any arguments.

`gdb` command names may always be truncated if that abbreviation is unambiguous. Other possible command abbreviations are listed in the documentation for individual commands. In some cases, even ambiguous abbreviations are allowed; for example, `s` is specially defined as equivalent to `step` even though there are other commands whose names start with `s`. You can test abbreviations by using them as arguments to the `help` command.

A blank line as input to `gdb` (typing just [RET]) means to repeat the previous command. Certain commands (for example, `run`) will not repeat this way; these are commands whose unintentional repetition might cause trouble and which you are unlikely to want to repeat.

The `list` and `x` commands, when you repeat them with [RET], construct new arguments rather than repeating exactly as typed. This permits easy scanning of source or memory.

`gdb` can also use [RET] in another way: to partition lengthy output, in a way similar to the common utility `more` (refer to Section 21.4 *Screen size*). Since it is easy to press one [RET] too many in this situation, `gdb` disables command repetition after any command that generates this sort of display.

Any text from a `#` to the end of the line is a comment; it does nothing. This is useful mainly in command files (refer to Section 22.3 *Command files*).

The `C-o` binding is useful for repeating a complex sequence of commands. This command accepts the current line, like `RET`, and then fetches the next line relative to the current line from the history for editing.

5.2. Command completion

`gdb` can fill in the rest of a word in a command for you, if there is only one possibility; it can also show you what the valid possibilities are for the next word in a command, at any time. This works for `gdb` commands, `gdb` subcommands, and the names of symbols in your program.

Press the [TAB] key whenever you want `gdb` to fill out the rest of a word. If there is only one possibility, `gdb` fills in the word, and waits for you to finish the command (or press [RET] to enter it). For example, if you type

```
(gdb) info bre [TAB]
```

`gdb` fills in the rest of the word `breakpoints`, since that is the only `info` subcommand beginning with `bre`:

```
(gdb) info breakpoints
```

You can either press [RET] at this point, to run the `info breakpoints` command, or backspace and enter something else, if `breakpoints` does not look like the command you expected. (If you were sure you wanted `info breakpoints` in the first place, you might as well just type [RET] immediately after `info bre`, to exploit command abbreviations rather than command completion).

If there is more than one possibility for the next word when you press [TAB], gdb sounds a bell. You can either supply more characters and try again, or just press [TAB] a second time; gdb displays all the possible completions for that word. For example, you might want to set a breakpoint on a subroutine whose name begins with `make_`, but when you type `b make_[TAB]` gdb just sounds the bell. Typing [TAB] again displays all the function names in your program that begin with those characters, for example:

```
(gdb) b make_ [TAB]
gdb sounds bell; press [TAB] again, to see:                make_a_section_from_file
make_abs_section                make_function_type
make_blockvector               make_pointer_type
make_cleanup                    make_reference_type
make_command                   make_symbol_completion_list
(gdb) b make_
```

After displaying the available possibilities, gdb copies your partial input (`b make_` in the example) so you can finish the command.

If you just want to see the list of alternatives in the first place, you can press **M-?** rather than pressing [TAB] twice. **M-?** means **[META] ?**. You can type this either by holding down a key designated as the [META] shift on your keyboard (if there is one) while typing `?`, or as [ESC] followed by `?`.

Sometimes the string you need, while logically a "word", may contain parentheses or other characters that gdb normally excludes from its notion of a word. To permit word completion to work in this situation, you may enclose words in ' (single quote marks) in gdb commands.

The most likely situation where you might need this is in typing the name of a C++ function. This is because C++ allows function overloading (multiple definitions of the same function, distinguished by argument type). For example, when you want to set a breakpoint you may need to distinguish whether you mean the version of `name` that takes an `int` parameter, `name(int)`, or the version that takes a `float` parameter, `name(float)`. To use the word-completion facilities in this situation, type a single quote ' at the beginning of the function name. This alerts gdb that it may need to consider more information than usual when you press [TAB] or **M-?** to request word completion:

```
(gdb) b 'bubble( M-?
bubble(double,double)    bubble(int,int)
(gdb) b 'bubble(
```

In some cases, gdb can tell that completing a name requires using quotes. When this happens, gdb inserts the quote for you (while completing as much as it can) if you do not type the quote in the first place:

```
(gdb) b bub [TAB]
gdb alters your input line to the following, and rings a bell:
```

```
(gdb) b '
```

In general, gdb can tell that a quote is needed (and inserts it) if you have not yet started typing the argument list when you ask for completion on an overloaded symbol.

For more information about overloaded functions, refer to Section 14.4.1.3 *C++ expressions*. You can use the command `set overload-resolution off` to disable overload resolution; refer to Section 14.4.1.7 *gdb features for C++*.

5.3. Getting help

You can always ask gdb itself for information on its commands, using the command `help`.

```
help
h
```

You can use `help` (abbreviated `h`) with no arguments to display a short list of named classes of commands:

```
(gdb) help
List of classes of commands:

aliases -- Aliases of other commands
breakpoints -- Making program stop at certain points
data -- Examining data
files -- Specifying and examining files
internals -- Maintenance commands
obscure -- Obscure features
running -- Running the program
stack -- Examining the stack
status -- Status inquiries
support -- Support facilities
tracepoints -- Tracing of program execution without
                stopping the program
user-defined -- User-defined commands
```

```
Type "help" followed by a class name for a list of
commands in that class.
Type "help" followed by command name for full
documentation.
Command name abbreviations are allowed if unambiguous.
(gdb)
```

```
help class
```

Using one of the general help classes as an argument, you can get a list of the individual commands in that class. For example, here is the help display for the class `status`:

```
(gdb) help status
Status inquiries.

List of commands:

info -- Generic command for showing things
        about the program being debugged
show -- Generic command for showing things
        about the debugger

Type "help" followed by command name for full
documentation.
Command name abbreviations are allowed if unambiguous.
(gdb)
```

help command

With a command name as `help` argument, `gdb` displays a short paragraph on how to use that command.

apropos args

The `apropos args` command searches through all of the `gdb` commands, and their documentation, for the regular expression specified in `args`. It prints out all matches found. For example:

```
apropos reload
```

results in:

```
set symbol-reloading -- Set dynamic symbol table reloading
                        multiple times in one run
show symbol-reloading -- Show dynamic symbol table reloading
                        multiple times in one run
```

complete args

The `complete args` command lists all the possible completions for the beginning of a command. Use `args` to specify the beginning of the command you want completed. For example:

```
complete i
```

results in:

```
if
ignore
info
inspect
```

This is intended for use by `gnu Emacs`.

In addition to `help`, you can use the `gdb` commands `info` and `show` to inquire about the state of your program, or the state of `gdb` itself. Each command supports many topics of inquiry; this manual introduces each of them in the appropriate context. The listings under `info` and under `show` in the Index point to all the sub-commands. Refer to *Red Hat Enterprise Linux 4*.

info

This command (abbreviated `i`) is for describing the state of your program. For example, you can list the arguments given to your program with `info args`, list the registers currently in use with `info registers`, or list the breakpoints you have set with `info breakpoints`. You can get a complete list of the `info` sub-commands with `help info`.

set

You can assign the result of an expression to an environment variable with `set`. For example, you can set the `gdb` prompt to a `$`-sign with `set prompt $`.

show

In contrast to `info`, `show` is for describing the state of `gdb` itself. You can change most of the things you can `show`, by using the related command `set`; for example, you can control what number system is used for displays with `set radix`, or simply inquire which is currently in use with `show radix`.

To display all the settable parameters and their current values, you can use `show` with no arguments; you may also use `info set`. Both commands produce the same display.

Here are three miscellaneous `show` subcommands, all of which are exceptional in lacking corresponding `set` commands:

`show version`

Show what version of gdb is running. You should include this information in gdb bug-reports. If multiple versions of gdb are in use at your site, you may need to determine which version of gdb you are running; as gdb evolves, new commands are introduced, and old ones may wither away. Also, many system vendors ship variant versions of gdb, and there are variant versions of gdb in gnu/Linux distributions as well. The version number is the same as the one announced when you start gdb.

`show copying`

Display information about permission for copying gdb.

`show warranty`

Display the gnu "NO WARRANTY" statement, or a warranty, if your version of gdb comes with one.

Running Programs Under gdb

When you run a program under gdb, you must first generate debugging information when you compile it.

You may start gdb with its arguments, if any, in an environment of your choice. If you are doing native debugging, you may redirect your program's input and output, debug an already running process, or kill a child process.

6.1. Compiling for debugging

In order to debug a program effectively, you need to generate debugging information when you compile it. This debugging information is stored in the object file; it describes the data type of each variable or function and the correspondence between source line numbers and addresses in the executable code.

To request debugging information, specify the `-g` option when you run the compiler.

Most compilers do not include information about preprocessor macros in the debugging information if you specify the `-g` flag alone, because this information is rather large. Version 3.1 of gcc, the gnu C compiler, provides macro information if you specify the options `-gdwarf-2` and `-g3`; the former option requests debugging information in the Dwarf 2 format, and the latter requests "extra information". In the future, we hope to find more compact ways to represent macro information, so that it can be included with `-g` alone.

Many C compilers are unable to handle the `-g` and `-O` options together. Using those compilers, you cannot generate optimized executables containing debugging information.

gcc, the gnu C compiler, supports `-g` with or without `-O`, making it possible to debug optimized code. We recommend that you *always* use `-g` whenever you compile a program. You may think your program is correct, but there is no sense in pushing your luck.

When you debug a program compiled with `-g -O`, remember that the optimizer is rearranging your code; the debugger shows you what is really there. Do not be too surprised when the execution path does not exactly match your source file! An extreme example: if you define a variable, but never use it, gdb never sees that variable--because the compiler optimizes it out of existence.

Some things do not work as well with `-g -O` as with just `-g`, particularly on machines with instruction scheduling. If in doubt, recompile with `-g` alone, and if this fixes the problem, please report it to us as a bug (including a test case!).

Older versions of the gnu C compiler permitted a variant option `-gg` for debugging information. gdb no longer supports this format; if your gnu C compiler has this option, do not use it.

6.2. Starting your program

```
run  
r
```

Use the `run` command to start your program under gdb. You must first specify the program name (except on VxWorks) with an argument to gdb (refer to Chapter 4 *Getting In and Out of gdb*), or by using the `file` or `exec-file` command (refer to Section 17.1 *Commands to specify files*).

If you are running your program in an execution environment that supports processes, `run` creates an inferior process and makes that process run your program. (In environments without processes, `run` jumps to the start of your program.)

The execution of a program is affected by certain information it receives from its superior. `gdb` provides ways to specify this information, which you must do *before* starting your program. (You can change it after starting your program, but such changes only affect your program the next time you start it.) This information may be divided into four categories:

The *arguments*.

Specify the arguments to give your program as the arguments of the `run` command. If a shell is available on your target, the shell is used to pass the arguments, so that you may use normal conventions (such as wildcard expansion or variable substitution) in describing the arguments. In Unix systems, you can control which shell is used with the `SHELL` environment variable. Refer to Section 6.3 *Your program's arguments*.

The *environment*.

Your program normally inherits its environment from `gdb`, but you can use the `gdb` commands `set environment` and `unset environment` to change parts of the environment that affect your program. Refer to Section 6.4 *Your program's environment*.

The *working directory*.

Your program inherits its working directory from `gdb`. You can set the `gdb` working directory with the `cd` in command in `gdb`. Refer to Section 6.5 *Your program's working directory*.

The *standard input and output*.

Your program normally uses the same device for standard input and standard output as `gdb` is using. You can redirect input and output in the `run` command line, or you can use the `tty` command to set a different device for your program. Refer to Section 6.6 *Your program's input and output*.

Warning: While input and output redirection work, you cannot use pipes to pass the output of the program you are debugging to another program; if you attempt this, `gdb` is likely to wind up debugging the wrong program.

When you issue the `run` command, your program begins to execute immediately. Refer to Chapter 7 *Stopping and Continuing* for discussion of how to arrange for your program to stop. Once your program has stopped, you may call functions in your program, using the `print` or `call` commands. Refer to Chapter 10 *Examining Data*.

If the modification time of your symbol file has changed since the last time `gdb` read its symbols, `gdb` discards its symbol table, and reads it again. When it does this, `gdb` tries to retain your current breakpoints.

6.3. Your program's arguments

The arguments to your program can be specified by the arguments of the `run` command. They are passed to a shell, which expands wildcard characters and performs redirection of I/O, and thence to your program. Your `SHELL` environment variable (if it exists) specifies what shell `gdb` uses. If you do not define `SHELL`, `gdb` uses the default shell (`/bin/sh` on Unix).

On non-Unix systems, the program is usually invoked directly by `gdb`, which emulates I/O redirection via the appropriate system calls, and the wildcard characters are expanded by the startup code of the program, not by the shell.

`run` with no arguments uses the same arguments used by the previous `run`, or those set by the `set args` command.

```
set args
```

Specify the arguments to be used the next time your program is run. If `set args` has no arguments, `run` executes your program with no arguments. Once you have run your program with arguments, using `set args` before the next `run` is the only way to run it again without arguments.

```
show args
```

Show the arguments to give your program when it is started.

6.4. Your program's environment

The *environment* consists of a set of environment variables and their values. Environment variables conventionally record such things as your user name, your home directory, your terminal type, and your search path for programs to run. Usually you set up environment variables with the shell and they are inherited by all the other programs you run. When debugging, it can be useful to try running your program with a modified environment without having to start gdb over again.

```
path directory
```

Add `directory` to the front of the `PATH` environment variable (the search path for executables) that will be passed to your program. The value of `PATH` used by gdb does not change. You may specify several directory names, separated by whitespace or by a system-dependent separator character (`:` on Unix, `;` on MS-DOS and MS-Windows). If `directory` is already in the path, it is moved to the front, so it is searched sooner.

You can use the string `$cwd` to refer to whatever is the current working directory at the time gdb searches the path. If you use `.` instead, it refers to the directory where you executed the `path` command. gdb replaces `.` in the `directory` argument (with the current path) before adding `directory` to the search path.

```
show paths
```

Display the list of search paths for executables (the `PATH` environment variable).

```
show environment [varname]
```

Print the value of environment variable `varname` to be given to your program when it starts. If you do not supply `varname`, print the names and values of all environment variables to be given to your program. You can abbreviate `environment` as `env`.

```
set environment varname [=value]
```

Set environment variable `varname` to `value`. The value changes for your program only, not for gdb itself. `value` may be any string; the values of environment variables are just strings, and any interpretation is supplied by your program itself. The `value` parameter is optional; if it is eliminated, the variable is set to a null value.

For example, this command:

```
set env USER = foo
```

tells the debugged program, when subsequently run, that its user is named `foo`. (The spaces around `=` are used for clarity here; they are not actually required.)

```
unset environment varname
```

Remove variable `varname` from the environment to be passed to your program. This is different from `set env varname =;unset environment` removes the variable from the environment, rather than assigning it an empty value.

Warning: On Unix systems, `gdb` runs your program using the shell indicated by your `SHELL` environment variable if it exists (or `/bin/sh` if not). If your `SHELL` variable names a shell that runs an initialization file--such as `.cshrc` for C-shell, or `.bashrc` for BASH--any variables you set in that file affect your program. You may wish to move setting of environment variables to files that are only run when you sign on, such as `.login` or `.profile`.

6.5. Your program's working directory

Each time you start your program with `run`, it inherits its working directory from the current working directory of `gdb`. The `gdb` working directory is initially whatever it inherited from its parent process (typically the shell), but you can specify a new working directory in `gdb` with the `cd` command.

The `gdb` working directory also serves as a default for the commands that specify files for `gdb` to operate on. Refer to Section 17.1 *Commands to specify files*.

```
cd directory
```

Set the `gdb` working directory to `directory`.

```
pwd
```

Print the `gdb` working directory.

6.6. Your program's input and output

By default, the program you run under `gdb` does input and output to the same terminal that `gdb` uses. `gdb` switches the terminal to its own terminal modes to interact with you, but it records the terminal modes your program was using and switches back to them when you continue running your program.

```
info terminal
```

Displays information recorded by `gdb` about the terminal modes your program is using.

You can redirect your program's input and/or output using shell redirection with the `run` command. For example,

```
run > outfile
```

starts your program, diverting its output to the file `outfile`.

Another way to specify where your program should do input and output is with the `tty` command. This command accepts a file name as argument, and causes this file to be the default for future `run` commands. It also resets the controlling terminal for the child process, for future `run` commands. For example,

```
tty /dev/ttyb
```

directs that processes started with subsequent `run` commands default to do input and output on the terminal `/dev/ttyb` and have that as their controlling terminal.

An explicit redirection in `run` overrides the `tty` command's effect on the input/output device, but not its effect on the controlling terminal.

When you use the `tty` command or redirect input in the `run` command, only the input *for your program* is affected. The input for `gdb` still comes from your terminal.

6.7. Debugging an already-running process

```
attach process-id
```

This command attaches to a running process—one that was started outside `gdb`. (`info files` shows your active targets.) The command takes as argument a process ID. The usual way to find out the process-id of a Unix process is with the `ps` utility, or with the `jobs -l` shell command.

`attach` does not repeat if you press [RET] a second time after executing the command.

To use `attach`, your program must be running in an environment which supports processes; for example, `attach` does not work for programs on bare-board targets that lack an operating system. You must also have permission to send the process a signal.

When you use `attach`, the debugger finds the program running in the process first by looking in the current working directory, then (if the program is not found) by using the source file search path (refer to Section 9.4 *Specifying source directories*). You can also use the `file` command to load the program. Refer to Section 17.1 *Commands to specify files*.

The first thing `gdb` does after arranging to debug the specified process is to stop it. You can examine and modify an attached process with all the `gdb` commands that are ordinarily available when you start processes with `run`. You can insert breakpoints; you can step and continue; you can modify storage. If you would rather the process continue running, you may use the `continue` command after attaching `gdb` to the process.

```
detach
```

When you have finished debugging the attached process, you can use the `detach` command to release it from `gdb` control. Detaching the process continues its execution. After the `detach` command, that process and `gdb` become completely independent once more, and you are ready to `attach` another process or start one with `run`. `detach` does not repeat if you press [RET] again after executing the command.

If you exit `gdb` or use the `run` command while you have an attached process, you kill that process. By default, `gdb` asks for confirmation if you try to do either of these things; you can control whether or not you need to confirm by using the `set confirm` command (refer to Section 21.7 *Optional warnings and messages*).

6.8. Killing the child process

```
kill
```

Kill the child process in which your program is running under `gdb`.

This command is useful if you wish to debug a core dump instead of a running process. gdb ignores any core dump file while your program is running.

On some operating systems, a program cannot be executed outside gdb while you have breakpoints set on it inside gdb. You can use the `kill` command in this situation to permit running your program outside the debugger.

The `kill` command is also useful if you wish to recompile and relink your program, since on many systems it is impossible to modify an executable file while it is running in a process. In this case, when you next type `run`, gdb notices that the file has changed, and reads the symbol table again (while trying to preserve your current breakpoint settings).

6.9. Debugging programs with multiple threads

In some operating systems, such as HP-UX and Solaris, a single program may have more than one *thread* of execution. The precise semantics of threads differ from one operating system to another, but in general the threads of a single program are akin to multiple processes--except that they share one address space (that is, they can all examine and modify the same variables). On the other hand, each thread has its own registers and execution stack, and perhaps private memory.

gdb provides these facilities for debugging multi-thread programs:

- automatic notification of new threads
- `thread threadno`, a command to switch among threads
- `info threads`, a command to inquire about existing threads
- `thread apply [threadno] [all] args`, a command to apply a command to a list of threads
- thread-specific breakpoints

Warning: These facilities are not yet available on every gdb configuration where the operating system supports threads. If your gdb does not support threads, these commands have no effect. For example, a system without thread support shows no output from `info threads`, and always rejects the `thread` command, like this:

```
(gdb) info threads
(gdb) thread 1
Thread ID 1 not known. Use the "info threads" command to
see the IDs of currently known threads.
```

The gdb thread debugging facility allows you to observe all threads while your program runs--but whenever gdb takes control, one thread in particular is always the focus of debugging. This thread is called the *current thread*. Debugging commands show program information from the perspective of the current thread.

Whenever gdb detects a new thread in your program, it displays the target system's identification for the thread with a message in the form `[New systag]. systag` is a thread identifier whose form varies depending on the particular system. For example, on LynxOS, you might see

```
[New process 35 thread 27]
```

when gdb notices a new thread. In contrast, on an SGI system, the `systag` is simply something like `process 368`, with no further qualifier.

For debugging purposes, gdb associates its own thread number--always a single integer--with each thread in your program.

info threads

Display a summary of all threads currently in your program. gdb displays for each thread (in this order):

1. the thread number assigned by gdb
2. the target system's thread identifier (*systag*)
3. the current stack frame summary for that thread

An asterisk * to the left of the gdb thread number indicates the current thread.

For example,

```
(gdb) info threads
 3 process 35 thread 27 0x34e5 in sigpause ()
 2 process 35 thread 23 0x34e5 in sigpause ()
* 1 process 35 thread 13  main (argc=1, argv=0x7ffffff8)
   at threadtest.c:68
```

On HP-UX systems:

For debugging purposes, gdb associates its own thread number--a small integer assigned in thread-creation order--with each thread in your program.

Whenever gdb detects a new thread in your program, it displays both gdb's thread number and the target system's identification for the thread with a message in the form [New *systag*]. *systag* is a thread identifier whose form varies depending on the particular system. For example, on HP-UX, you see

```
[New thread 2 (system thread 26594)]
```

when gdb notices a new thread.

info threads

Display a summary of all threads currently in your program. gdb displays for each thread (in this order):

1. the thread number assigned by gdb
2. the target system's thread identifier (*systag*)
3. the current stack frame summary for that thread

An asterisk * to the left of the gdb thread number indicates the current thread.

For example,

```
(gdb) info threads
* 3 system thread 26607  worker (wptr=0x7b09c318 "@" ) \
   at quicksort.c:137
 2 system thread 26606  0x7b0030d8 in __ksleep () \
   from /usr/lib/libc.2
```

```
1 system thread 27905 0x7b003498 in _brk () \
    from /usr/lib/libc.2
```

```
thread threadno
```

Make thread number `threadno` the current thread. The command argument `threadno` is the internal gdb thread number, as shown in the first field of the `info threads` display. gdb responds by displaying the system identifier of the thread you selected, and its current stack frame summary:

```
(gdb) thread 2
[Switching to process 35 thread 23]
0x34e5 in sigpause ()
```

As with the `[New ...]` message, the form of the text after `Switching to` depends on your system's conventions for identifying threads.

```
thread apply [threadno] [all] args
```

The `thread apply` command allows you to apply a command to one or more threads. Specify the numbers of the threads that you want affected with the command argument `threadno`. `threadno` is the internal gdb thread number, as shown in the first field of the `info threads` display. To apply a command to all threads, use `thread apply all args`.

Whenever gdb stops your program, due to a breakpoint or a signal, it automatically selects the thread where that breakpoint or signal happened. gdb alerts you to the context switch with a message of the form `[Switching to systag]` to identify the thread.

Refer to Section 7.4 *Stopping and starting multi-thread programs* for more information about how gdb behaves when you stop and start programs with multiple threads.

Refer to Section 7.1.2 *Setting watchpoints*, for information about watchpoints in programs with multiple threads.

6.10. Debugging programs with multiple processes

On most systems, gdb has no special support for debugging programs which create additional processes using the `fork` function. When a program forks, gdb will continue to debug the parent process and the child process will run unimpeded. If you have set a breakpoint in any code which the child then executes, the child will get a `SIGTRAP` signal which (unless it catches the signal) will cause it to terminate.

However, if you want to debug the child process there is a workaround which isn't too painful. Put a call to `sleep` in the code which the child process executes after the fork. It may be useful to sleep only if a certain environment variable is set, or a certain file exists, so that the delay need not occur when you don't want to run gdb on the child. While the child is sleeping, use the `ps` program to get its process ID. Then tell gdb (a new invocation of gdb if you are also debugging the parent process) to attach to the child process (refer to Section 6.7 *Debugging an already-running process*). From that point on you can debug the child process just like any other process which you attached to.

On HP-UX (11.x and later only?), gdb provides support for debugging programs that create additional processes using the `fork` or `vfork` function.

By default, when a program forks, gdb will continue to debug the parent process and the child process will run unimpeded.

If you want to follow the child process instead of the parent process, use the command `set follow-fork-mode`.

```
set follow-fork-mode mode
```

Set the debugger response to a program call of `fork` or `vfork`. A call to `fork` or `vfork` creates a new process. The `mode` can be:

`parent`

The original process is debugged after a fork. The child process runs unimpeded. This is the default.

`child`

The new process is debugged after a fork. The parent process runs unimpeded.

`ask`

The debugger will ask for one of the above choices.

```
show follow-fork-mode
```

Display the current debugger response to a `fork` or `vfork` call.

If you ask to debug a child process and a `vfork` is followed by an `exec`, gdb executes the new target up to the first breakpoint in the new target. If you have a breakpoint set on `main` in your original program, the breakpoint will also be set on the child process's `main`.

When a child process is spawned by `vfork`, you cannot debug the child or parent until an `exec` call completes.

If you issue a `run` command to gdb after an `exec` call executes, the new target restarts. To restart the parent process, use the `file` command with the parent executable name as its argument.

You can use the `catch` command to make gdb stop whenever a `fork`, `vfork`, or `exec` call is made. Refer to Section 7.1.3 *Setting catchpoints*.

Stopping and Continuing

The principal purposes of using a debugger are so that you can stop your program before it terminates; or so that, if your program runs into trouble, you can investigate and find out why.

Inside `gdb`, your program may stop for any of several reasons, such as a signal, a breakpoint, or reaching a new line after a `gdb` command such as `step`. You may then examine and change variables, set new breakpoints or remove old ones, and then continue execution. Usually, the messages shown by `gdb` provide ample explanation of the status of your program--but you can also explicitly request this information at any time.

```
info program
```

Display information about the status of your program: whether it is running or not, what process it is, and why it stopped.

7.1. Breakpoints, watchpoints, and catchpoints

A *breakpoint* makes your program stop whenever a certain point in the program is reached. For each breakpoint, you can add conditions to control in finer detail whether your program stops. You can set breakpoints with the `break` command and its variants (refer to Section 7.1.1 *Setting breakpoints*), to specify the place where your program should stop by line number, function name or exact address in the program.

In HP-UX, SunOS 4.x, SVR4, and Alpha OSF/1 configurations, you can set breakpoints in shared libraries before the executable is run. There is a minor limitation on HP-UX systems: you must wait until the executable is run in order to set breakpoints in shared library routines that are not called directly by the program (for example, routines that are arguments in a `pthread_create` call).

A *watchpoint* is a special breakpoint that stops your program when the value of an expression changes. You must use a different command to set watchpoints (refer to Section 7.1.2 *Setting watchpoints*), but aside from that, you can manage a watchpoint like any other breakpoint: you enable, disable, and delete both breakpoints and watchpoints using the same commands.

You can arrange to have values from your program displayed automatically whenever `gdb` stops at a breakpoint. Refer to Section 10.6 *Automatic display*.

A *catchpoint* is another special breakpoint that stops your program when a certain kind of event occurs, such as the throwing of a C++ exception or the loading of a library. As with watchpoints, you use a different command to set a catchpoint (refer to Section 7.1.3 *Setting catchpoints*), but aside from that, you can manage a catchpoint like any other breakpoint. (To stop when your program receives a signal, use the `handle` command. Refer to Section 7.3 *Signals*.)

`gdb` assigns a number to each breakpoint, watchpoint, or catchpoint when you create it; these numbers are successive integers starting with one. In many of the commands for controlling various features of breakpoints you use the breakpoint number to say which breakpoint you want to change. Each breakpoint may be *enabled* or *disabled*; if disabled, it has no effect on your program until you enable it again.

Some `gdb` commands accept a range of breakpoints on which to operate. A breakpoint range is either a single breakpoint number, like 5, or two such numbers, in increasing order, separated by a hyphen, like 5-7. When a breakpoint range is given to a command, all breakpoint in that range are operated on.

7.1.1. Setting breakpoints

Breakpoints are set with the `break` command (abbreviated `b`). The debugger convenience variable `$bpnum` records the number of the breakpoint you've set most recently; refer to Section 10.9 *Convenience variables*, for a discussion of what you can do with convenience variables.

You have several ways to say where the breakpoint should go.

```
break function
```

Set a breakpoint at entry to function `function`. When using source languages that permit overloading of symbols, such as C++, `function` may refer to more than one possible place to break. Refer to Section 7.1.8 *Breakpoint menus*, for a discussion of that situation.

```
break +offset
break -offset
```

Set a breakpoint some number of lines forward or back from the position at which execution stopped in the currently selected *stack frame*. Refer to Section 8.1 *Stack frames* for a description of stack frames.)

```
break linenum
```

Set a breakpoint at line `linenum` in the current source file. The current source file is the last file whose source text was printed. The breakpoint will stop your program just before it executes any of the code on that line.

```
break filename:linenum
```

Set a breakpoint at line `linenum` in source file `filename`.

```
break filename:function
```

Set a breakpoint at entry to function `function` found in file `filename`. Specifying a file name as well as a function name is superfluous except when multiple files contain similarly named functions.

```
break *address
```

Set a breakpoint at address `address`. You can use this to set breakpoints in parts of your program which do not have debugging information or source files.

```
break
```

When called without any arguments, `break` sets a breakpoint at the next instruction to be executed in the selected stack frame (refer to Chapter 8 *Examining the Stack*). In any selected frame but the innermost, this makes your program stop as soon as control returns to that frame. This is similar to the effect of a `finish` command in the frame inside the selected frame--except that `finish` does not leave an active breakpoint. If you use `break` without an argument in the innermost frame, `gdb` stops the next time it reaches the current location; this may be useful inside loops.

`gdb` normally ignores breakpoints when it resumes execution, until at least one instruction has been executed. If it did not do this, you would be unable to proceed past a breakpoint without first disabling the breakpoint. This rule applies whether or not the breakpoint already existed when your program stopped.

```
break ... if cond
```

Set a breakpoint with condition `cond`; evaluate the expression `cond` each time the breakpoint is reached, and stop only if the value is nonzero--that is, if `cond` evaluates as true. `...` stands

for one of the possible arguments described above (or no argument) specifying where to break. Refer to Section 7.1.6 *Break conditions* for more information on breakpoint conditions.

`tbreak args`

Set a breakpoint enabled only for one stop. `args` are the same as for the `break` command, and the breakpoint is set in the same way, but the breakpoint is automatically deleted after the first time your program stops there. Refer to Section 7.1.5 *Disabling breakpoints*.

`hbreak args`

Set a hardware-assisted breakpoint. `args` are the same as for the `break` command and the breakpoint is set in the same way, but the breakpoint requires hardware support and some target hardware may not have this support. The main purpose of this is EPROM/ROM code debugging, so you can set a breakpoint at an instruction without changing the instruction. This can be used with the new trap-generation provided by SPARClike DSU and some x86-based targets. These targets will generate traps when a program accesses some data or instruction address that is assigned to the debug registers. However the hardware breakpoint registers can take a limited number of breakpoints. For example, on the DSU, only two data breakpoints can be set at a time, and `gdb` will reject this command if more than two are used. Delete or disable unused hardware breakpoints before setting new ones (refer to Section 7.1.5 *Disabling breakpoints* and Section 7.1.6 *Break conditions*).

`thbreak args`

Set a hardware-assisted breakpoint enabled only for one stop. `args` are the same as for the `hbreak` command and the breakpoint is set in the same way. However, like the `tbreak` command, the breakpoint is automatically deleted after the first time your program stops there. Also, like the `hbreak` command, the breakpoint requires hardware support and some target hardware may not have this support. Refer to Section 7.1.5 *Disabling breakpoints* and Section 7.1.6 *Break conditions*.

`rbreak regex`

Set breakpoints on all functions matching the regular expression `regex`. This command sets an unconditional breakpoint on all matches, printing a list of all breakpoints it set. Once these breakpoints are set, they are treated just like the breakpoints set with the `break` command. You can delete them, disable them, or make them conditional the same way as any other breakpoint.

The syntax of the regular expression is the standard one used with tools like `grep`. Note that this is different from the syntax used by shells, so for instance `f00*` matches all functions that include an `f0` followed by zero or more `0`s. There is an implicit `.` leading and trailing the regular expression you supply, so to match only functions that begin with `f00`, use `^f00`.

When debugging C++ programs, `rbreak` is useful for setting breakpoints on overloaded functions that are not members of any special classes.

```
info breakpoints [n]
info break [n]
info watchpoints [n]
```

Print a table of all breakpoints, watchpoints, and catchpoints set and not deleted, with the following columns for each breakpoint:

Breakpoint Numbers
Type

Breakpoint, watchpoint, or catchpoint.

Disposition

Whether the breakpoint is marked to be disabled or deleted when hit.

Enabled or Disabled

Enabled breakpoints are marked with `y. n` marks breakpoints that are not enabled.

Address

Where the breakpoint is in your program, as a memory address.

What

Where the breakpoint is in the source for your program, as a file and line number.

If a breakpoint is conditional, `info break` shows the condition on the line following the affected breakpoint; breakpoint commands, if any, are listed after that.

`info break` with a breakpoint number `n` as argument lists only that breakpoint. The convenience variable `$_` and the default examining-address for the `x` command are set to the address of the last breakpoint listed (refer to Section 10.5 *Examining memory*).

`info break` displays a count of the number of times the breakpoint has been hit. This is especially useful in conjunction with the `ignore` command. You can ignore a large number of breakpoint hits, look at the breakpoint `info` to see how many times the breakpoint was hit, and then run again, ignoring one less than that number. This will get you quickly to the last hit of that breakpoint.

`gdb` allows you to set any number of breakpoints at the same place in your program. There is nothing silly or meaningless about this. When the breakpoints are conditional, this is even useful (refer to Section 7.1.6 *Break conditions*).

`gdb` itself sometimes sets breakpoints in your program for special purposes, such as proper handling of `longjmp` (in C programs). These internal breakpoints are assigned negative numbers, starting with `-1`; `info breakpoints` does not display them. You can see these breakpoints with the `gdb` maintenance command `maint info breakpoints` (refer to Appendix C *Maintenance Commands*).

7.1.2. Setting watchpoints

You can use a watchpoint to stop execution whenever the value of an expression changes, without having to predict a particular place where this may happen.

Depending on your system, watchpoints may be implemented in software or hardware. `gdb` does software watchpointing by single-stepping your program and testing the variable's value each time, which is hundreds of times slower than normal execution. (But this may still be worth it, to catch errors where you have no clue what part of your program is the culprit.)

On some systems, such as HP-UX, `gnu/Linux` and some other x86-based targets, `gdb` includes support for hardware watchpoints, which do not slow down the running of your program.

```
watch expr
```

Set a watchpoint for an expression. `gdb` will break when `expr` is written into by the program and its value changes.

```
rwatch expr
```

Set a watchpoint that will break when `watch expr` is read by the program.

```
awatch expr
```

Set a watchpoint that will break when `expr` is either read or written into by the program.

```
info watchpoints
```

This command prints a list of watchpoints, breakpoints, and catchpoints; it is the same as `info break`.

`gdb` sets a *hardware watchpoint* if possible. Hardware watchpoints execute very quickly, and the debugger reports a change in value at the exact instruction where the change occurs. If `gdb` cannot set a hardware watchpoint, it sets a software watchpoint, which executes more slowly and reports the change in value at the next statement, not the instruction, after the change occurs.

When you issue the `watch` command, `gdb` reports

```
Hardware watchpoint num: expr
```

if it was able to set a hardware watchpoint.

Currently, the `awatch` and `rwatch` commands can only set hardware watchpoints, because accesses to data that don't change the value of the watched expression cannot be detected without examining every instruction as it is being executed, and `gdb` does not do that currently. If `gdb` finds that it is unable to set a hardware breakpoint with the `awatch` or `rwatch` command, it will print a message like this:

```
Expression cannot be implemented with read/access watchpoint.
```

Sometimes, `gdb` cannot set a hardware watchpoint because the data type of the watched expression is wider than what a hardware watchpoint on the target machine can handle. For example, some systems can only watch regions that are up to 4 bytes wide; on such systems you cannot set hardware watchpoints for an expression that yields a double-precision floating-point number (which is typically 8 bytes wide). As a work-around, it might be possible to break the large region into a series of smaller ones and watch them with separate watchpoints.

If you set too many hardware watchpoints, `gdb` might be unable to insert all of them when you resume the execution of your program. Since the precise number of active watchpoints is unknown until such time as the program is about to be resumed, `gdb` might not be able to warn you about this when you set the watchpoints, and the warning will be printed only when the program is resumed:

```
Hardware watchpoint num: Could not insert watchpoint
```

If this happens, delete or disable some of the watchpoints.

The SPARClite DSU will generate traps when a program accesses some data or instruction address that is assigned to the debug registers. For the data addresses, DSU facilitates the `watch` command. However the hardware breakpoint registers can only take two data watchpoints, and both watchpoints must be the same kind. For example, you can set two watchpoints with `watch` commands, two with `rwatch` commands, or two with `awatch` commands, but you cannot set one watchpoint with one command and the other with a different command. `gdb` will reject the command if you try to mix watchpoints. Delete or disable unused watchpoint commands before setting new ones.

If you call a function interactively using `print` or `call`, any watchpoints you have set will be inactive until `gdb` reaches another kind of breakpoint or the call completes.

gdb automatically deletes watchpoints that watch local (automatic) variables, or expressions that involve such variables, when they go out of scope, that is, when the execution leaves the block in which these variables were defined. In particular, when the program being debugged terminates, *all* local variables go out of scope, and so only watchpoints that watch global variables remain set. If you rerun the program, you will need to set all such watchpoints again. One way of doing that would be to set a code breakpoint at the entry to the `main` function and when it breaks, set all the watchpoints.

Warning: In multi-thread programs, watchpoints have only limited usefulness. With the current watchpoint implementation, gdb can only watch the value of an expression *in a single thread*. If you are confident that the expression can only change due to the current thread's activity (and if you are also confident that no other thread can become current), then you can use watchpoints as usual. However, gdb may not notice when a non-current thread's activity changes the expression.

HP-UX Warning: In multi-thread programs, software watchpoints have only limited usefulness. If gdb creates a software watchpoint, it can only watch the value of an expression *in a single thread*. If you are confident that the expression can only change due to the current thread's activity (and if you are also confident that no other thread can become current), then you can use software watchpoints as usual. However, gdb may not notice when a non-current thread's activity changes the expression. (Hardware watchpoints, in contrast, watch an expression in all threads.)

7.1.3. Setting catchpoints

You can use *catchpoints* to cause the debugger to stop for certain kinds of program events, such as C++ exceptions or the loading of a shared library. Use the `catch` command to set a catchpoint.

```
catch event
```

Stop when `event` occurs. `event` can be any of the following:

```
throw
```

The throwing of a C++ exception.

```
catch
```

The catching of a C++ exception.

```
exec
```

A call to `exec`. This is currently only available for HP-UX.

```
fork
```

A call to `fork`. This is currently only available for HP-UX.

```
vfork
```

A call to `vfork`. This is currently only available for HP-UX.

```
load
```

```
load libname
```

The dynamic loading of any shared library, or the loading of the library `libname`. This is currently only available for HP-UX.

```
unload
unload libname
```

The unloading of any dynamically loaded shared library, or the unloading of the library `libname`. This is currently only available for HP-UX.

```
tcatch event
```

Set a catchpoint that is enabled only for one stop. The catchpoint is automatically deleted after the first time the event is caught.

Use the `info break` command to list the current catchpoints.

There are currently some limitations to C++ exception handling (`catch throw` and `catch catch`) in `gdb`:

- If you call a function interactively, `gdb` normally returns control to you when the function has finished executing. If the call raises an exception, however, the call may bypass the mechanism that returns control to you and cause your program either to abort or to simply continue running until it hits a breakpoint, catches a signal that `gdb` is listening for, or exits. This is the case even if you set a catchpoint for the exception; catchpoints on exceptions are disabled within interactive calls.
- You cannot raise an exception interactively.
- You cannot install an exception handler interactively.

Sometimes `catch` is not the best way to debug exception handling: if you need to know exactly where an exception is raised, it is better to stop *before* the exception handler is called, since that way you can see the stack before any unwinding takes place. If you set a breakpoint in an exception handler instead, it may not be easy to find out where the exception was raised.

To stop just before an exception handler is called, you need some knowledge of the implementation. In the case of `gnu C++`, exceptions are raised by calling a library function named `__raise_exception` which has the following ANSI C interface:

```
/* addr is where the exception identifier is stored.
   id is the exception identifier. */
void __raise_exception (void **addr, void *id);
```

To make the debugger catch all exceptions before any stack unwinding takes place, set a breakpoint on `__raise_exception` (refer to Section 7.1 *Breakpoints, watchpoints, and catchpoints*).

With a conditional breakpoint (refer to Section 7.1.6 *Break conditions*) that depends on the value of `id`, you can stop your program when a specific exception is raised. You can use multiple conditional breakpoints to stop your program when any of a number of exceptions are raised.

7.1.4. Deleting breakpoints

It is often necessary to eliminate a breakpoint, watchpoint, or catchpoint once it has done its job and you no longer want your program to stop there. This is called *deleting* the breakpoint. A breakpoint that has been deleted no longer exists; it is forgotten.

With the `clear` command you can delete breakpoints according to where they are in your program. With the `delete` command you can delete individual breakpoints, watchpoints, or catchpoints by specifying their breakpoint numbers.

It is not necessary to delete a breakpoint to proceed past it. `gdb` automatically ignores breakpoints on the first instruction to be executed when you continue execution without changing the execution address.

```
clear
```

Delete any breakpoints at the next instruction to be executed in the selected stack frame (refer to Section 8.3 *Selecting a frame*). When the innermost frame is selected, this is a good way to delete a breakpoint where your program just stopped.

```
clear function
clear filename:function
```

Delete any breakpoints set at entry to the function `function`.

```
clear linenum
clear filename:linenum
```

Delete any breakpoints set at or within the code of the specified line.

```
delete [breakpoints] [range...]
```

Delete the breakpoints, watchpoints, or catchpoints of the breakpoint ranges specified as arguments. If no argument is specified, delete all breakpoints (`gdb` asks confirmation, unless you have set `confirm off`). You can abbreviate this command as `d`.

7.1.5. Disabling breakpoints

Rather than deleting a breakpoint, watchpoint, or catchpoint, you might prefer to *disable* it. This makes the breakpoint inoperative as if it had been deleted, but remembers the information on the breakpoint so that you can *enable* it again later.

You disable and enable breakpoints, watchpoints, and catchpoints with the `enable` and `disable` commands, optionally specifying one or more breakpoint numbers as arguments. Use `info break` or `info watch` to print a list of breakpoints, watchpoints, and catchpoints if you do not know which numbers to use.

A breakpoint, watchpoint, or catchpoint can have any of four different states of enablement:

- Enabled. The breakpoint stops your program. A breakpoint set with the `break` command starts out in this state.
- Disabled. The breakpoint has no effect on your program.
- Enabled once. The breakpoint stops your program, but then becomes disabled.
- Enabled for deletion. The breakpoint stops your program, but immediately after it does so it is deleted permanently. A breakpoint set with the `tbreak` command starts out in this state.

You can use the following commands to enable or disable breakpoints, watchpoints, and catchpoints:

```
disable [breakpoints] [range...]
```

Disable the specified breakpoints--or all breakpoints, if none are listed. A disabled breakpoint has no effect but is not forgotten. All options such as `ignore-counts`, `conditions` and `commands` are remembered in case the breakpoint is enabled again later. You may abbreviate `disable` as `dis`.

```
enable [breakpoints] [range...]
```

Enable the specified breakpoints (or all defined breakpoints). They become effective once again in stopping your program.

```
enable [breakpoints] once range...
```

Enable the specified breakpoints temporarily. `gdb` disables any of these breakpoints immediately after stopping your program.

```
enable [breakpoints] delete range...
```

Enable the specified breakpoints to work once, then die. `gdb` deletes any of these breakpoints as soon as your program stops there.

Except for a breakpoint set with `tbreak` (refer to Section 7.1.1 *Setting breakpoints*), breakpoints that you set are initially enabled; subsequently, they become disabled or enabled only when you use one of the commands above. (The command `until` can set and delete a breakpoint of its own, but it does not change the state of your other breakpoints; (refer to Section 7.2 *Continuing and stepping*.)

7.1.6. Break conditions

The simplest sort of breakpoint breaks every time your program reaches a specified place. You can also specify a *condition* for a breakpoint. A condition is just a Boolean expression in your programming language (refer to Section 10.1 *Expressions*). A breakpoint with a condition evaluates the expression each time your program reaches it, and your program stops only if the condition is *true*.

This is the converse of using assertions for program validation; in that situation, you want to stop when the assertion is violated--that is, when the condition is false. In C, if you want to test an assertion expressed by the condition `assert`, you should set the condition `! assert` on the appropriate breakpoint.

Conditions are also accepted for watchpoints; you may not need them, since a watchpoint is inspecting the value of an expression anyhow--but it might be simpler, say, to just set a watchpoint on a variable name, and specify a condition that tests whether the new value is an interesting one.

Break conditions can have side effects, and may even call functions in your program. This can be useful, for example, to activate functions that log program progress, or to use your own print functions to format special data structures. The effects are completely predictable unless there is another enabled breakpoint at the same address. (In that case, `gdb` might see the other breakpoint first and stop your program without checking the condition of this one.) Note that breakpoint commands are usually more convenient and flexible than break conditions for the purpose of performing side effects when a breakpoint is reached (refer to Section 7.1.7 *Breakpoint command lists*).

Break conditions can be specified when a breakpoint is set, by using `if` in the arguments to the `break` command. Refer to Section 7.1.1 *Setting breakpoints*. They can also be changed at any time with the `condition` command.

You can also use the `if` keyword with the `watch` command. The `catch` command does not recognize the `if` keyword; `condition` is the only way to impose a further condition on a catchpoint.

```
condition bnum expression
```

Specify `expression` as the break condition for breakpoint, watchpoint, or catchpoint number `bnum`. After you set a condition, breakpoint `bnum` stops your program only if the value of `expression` is true (nonzero, in C). When you use `condition`, `gdb` checks `expression` immediately for syntactic correctness, and to determine whether symbols in it have referents in the context of your breakpoint. If `expression` uses symbols not referenced in the context of the breakpoint, `gdb` prints an error message:

No symbol "foo" in current context.

`gdb` does not actually evaluate `expression` at the time the `condition` command (or a command that sets a breakpoint with a condition, like `break if ...`) is given, however. Refer to Section 10.1 *Expressions*.

```
condition bnum
```

Remove the condition from breakpoint number `bnum`. It becomes an ordinary unconditional breakpoint.

A special case of a breakpoint condition is to stop only when the breakpoint has been reached a certain number of times. This is so useful that there is a special way to do it, using the *ignore count* of the breakpoint. Every breakpoint has an ignore count, which is an integer. Most of the time, the ignore count is zero, and therefore has no effect. But if your program reaches a breakpoint whose ignore count is positive, then instead of stopping, it just decrements the ignore count by one and continues. As a result, if the ignore count value is `n`, the breakpoint does not stop the next `n` times your program reaches it.

```
ignore bnum count
```

Set the ignore count of breakpoint number `bnum` to `count`. The next `count` times the breakpoint is reached, your program's execution does not stop; other than to decrement the ignore count, `gdb` takes no action.

To make the breakpoint stop the next time it is reached, specify a count of zero.

When you use `continue` to resume execution of your program from a breakpoint, you can specify an ignore count directly as an argument to `continue`, rather than using `ignore`. Refer to Section 7.2 *Continuing and stepping*.

If a breakpoint has a positive ignore count and a condition, the condition is not checked. Once the ignore count reaches zero, `gdb` resumes checking the condition.

You could achieve the effect of the ignore count with a condition such as `$foo- <= 0` using a debugger convenience variable that is decremented each time. Refer to Section 10.9 *Convenience variables*.

Ignore counts apply to breakpoints, watchpoints, and catchpoints.

7.1.7. Breakpoint command lists

You can give any breakpoint (or watchpoint or catchpoint) a series of commands to execute when your program stops due to that breakpoint. For example, you might want to print the values of certain expressions, or enable other breakpoints.

```
commands [bnum]
... command-list ...
end
```

Specify a list of commands for breakpoint number `bnum`. The commands themselves appear on the following lines. Type a line containing just `end` to terminate the commands.

To remove all commands from a breakpoint, type `commands` and follow it immediately with `end`; that is, give no commands.

With no `bnum` argument, `commands` refers to the last breakpoint, watchpoint, or catchpoint set (not to the breakpoint most recently encountered).

Pressing [RET] as a means of repeating the last `gdb` command is disabled within a `command-list`.

You can use breakpoint commands to start your program up again. Simply use the `continue` command, or `step`, or any other command that resumes execution.

Any other commands in the command list, after a command that resumes execution, are ignored. This is because any time you resume execution (even with a simple `next` or `step`), you may encounter another breakpoint--which could have its own command list, leading to ambiguities about which list to execute.

If the first command you specify in a command list is `silent`, the usual message about stopping at a breakpoint is not printed. This may be desirable for breakpoints that are to print a specific message and then continue. If none of the remaining commands print anything, you see no sign that the breakpoint was reached. `silent` is meaningful only at the beginning of a breakpoint command list.

The commands `echo`, `output`, and `printf` allow you to print precisely controlled output, and are often useful in silent breakpoints. Refer to Section 22.4 *Commands for controlled output*.

For example, here is how you could use breakpoint commands to print the value of `x` at entry to `foo` whenever `x` is positive.

```
break foo if x>0
commands
silent
printf "x is %d\n",x
cont
end
```

One application for breakpoint commands is to compensate for one bug so you can test for another. Put a breakpoint just after the erroneous line of code, give it a condition to detect the case in which something erroneous has been done, and give it commands to assign correct values to any variables that need them. End with the `continue` command so that your program does not stop, and start with the `silent` command so that no output is produced. Here is an example:

```
break 403
commands
silent
set x = y + 4
cont
end
```

7.1.8. Breakpoint menus

Some programming languages (notably C++ and Objective-C) permit a single function name to be defined several times, for application in different contexts. This is called *overloading*. When a function name is overloaded, `break function` is not enough to tell `gdb` where you want a breakpoint. If you realize this is a problem, you can use something like `break function(types)` to specify which particular version of the function you want. Otherwise, `gdb` offers you a menu of numbered choices for different possible breakpoints, and waits for your selection with the prompt `>`. The first two options are always `[0] cancel` and `[1] all`. Typing `1` sets a breakpoint at each definition of `function`, and typing `0` aborts the `break` command without setting any new breakpoints.

For example, the following session excerpt shows an attempt to set a breakpoint at the overloaded symbol `String::after`. We choose three particular definitions of that function name:

```
(gdb) b String::after
[0] cancel
```

```
[1] all
[2] file:String.cc; line number:867
[3] file:String.cc; line number:860
[4] file:String.cc; line number:875
[5] file:String.cc; line number:853
[6] file:String.cc; line number:846
[7] file:String.cc; line number:735
> 2 4 6
Breakpoint 1 at 0xb26c: file String.cc, line 867.
Breakpoint 2 at 0xb344: file String.cc, line 875.
Breakpoint 3 at 0xafcc: file String.cc, line 846.
Multiple breakpoints were set.
Use the "delete" command to delete unwanted
breakpoints.
(gdb)
```

7.1.9. "Cannot insert breakpoints"

Under some operating systems, breakpoints cannot be used in a program if any other process is running that program. In this situation, attempting to run or continue a program with a breakpoint causes gdb to print an error message:

```
Cannot insert breakpoints.
The same program may be running in another process.
```

When this happens, you have three ways to proceed:

1. Remove or disable the breakpoints, then continue.
2. Suspend gdb, and copy the file containing your program to a new name. Resume gdb and use the `exec-file` command to specify that gdb should run your program under that name. Then start your program again.
3. Relink your program so that the text segment is nonsharable, using the linker option `-N`. The operating system limitation may not apply to nonsharable executables.

A similar message can be printed if you request too many active hardware-assisted breakpoints and watchpoints:

```
Stopped; cannot insert breakpoints.
You may have requested too many hardware breakpoints and watchpoints.
```

This message is printed when you attempt to resume the program, since only then gdb knows exactly how many hardware breakpoints and watchpoints it needs to insert.

When this message is printed, you need to disable or remove some of the hardware-assisted breakpoints and watchpoints, and then continue.

7.2. Continuing and stepping

Continuing means resuming program execution until your program completes normally. In contrast, *stepping* means executing just one more "step" of your program, where "step" may mean either one line of source code, or one machine instruction (depending on what particular command you use). Either when continuing or when stepping, your program may stop even sooner, due to a breakpoint or a signal. (If it stops due to a signal, you may want to use `handle`, or use `signal 0` to resume execution. Refer to Section 7.3 *Signals*.)

```
continue [ignore-count]
c [ignore-count]
fg [ignore-count]
```

Resume program execution, at the address where your program last stopped; any breakpoints set at that address are bypassed. The optional argument `ignore-count` allows you to specify a further number of times to ignore a breakpoint at this location; its effect is like that of `ignore` (refer to Section 7.1.6 *Break conditions*).

The argument `ignore-count` is meaningful only when your program stopped due to a breakpoint. At other times, the argument to `continue` is ignored.

The synonyms `c` and `fg` (for *foreground*, as the debugged program is deemed to be the foreground program) are provided purely for convenience, and have exactly the same behavior as `continue`.

To resume execution at a different place, you can use `return` (refer to Section 16.4 *Returning from a function*) to go back to the calling function; or `jump` (refer to Section 16.2 *Continuing at a different address*) to go to an arbitrary location in your program.

A typical technique for using stepping is to set a breakpoint (refer to Section 7.1 *Breakpoints, watchpoints, and catchpoints*) at the beginning of the function or the section of your program where a problem is believed to lie, run your program until it stops at that breakpoint, and then step through the suspect area, examining the variables that are interesting, until you see the problem happen.

```
step
```

Continue running your program until control reaches a different source line, then stop it and return control to `gdb`. This command is abbreviated `s`.

Warning: If you use the `step` command while control is within a function that was compiled without debugging information, execution proceeds until control reaches a function that does have debugging information. Likewise, it will not step into a function which is compiled without debugging information. To step through functions without debugging information, use the `stepi` command, described below.

The `step` command only stops at the first instruction of a source line. This prevents the multiple stops that could otherwise occur in `switch` statements, `for` loops, etc. `step` continues to stop if a function that has debugging information is called within the line. In other words, `step` *steps inside* any functions called within the line.

Also, the `step` command only enters a function if there is line number information for the function. Otherwise it acts like the `next` command. This avoids problems when using `cc -g1` on MIPS machines. Previously, `step` entered subroutines if there was any debugging information about the routine.

```
step count
```

Continue running as in `step`, but do so `count` times. If a breakpoint is reached, or a signal not related to stepping occurs before `count` steps, stepping stops right away.

```
next [count]
```

Continue to the next source line in the current (innermost) stack frame. This is similar to `step`, but function calls that appear within the line of code are executed without stopping. Execution stops when control reaches a different line of code at the original stack level that was executing when you gave the `next` command. This command is abbreviated `n`.

An argument `count` is a repeat count, as for `step`.

The `next` command only stops at the first instruction of a source line. This prevents multiple stops that could otherwise occur in `switch` statements, `for` loops, etc.

```
set step-mode
```

```
set step-mode on
```

The `set step-mode on` command causes the `step` command to stop at the first instruction of a function which contains no debug line information rather than stepping over it.

This is useful in cases where you may be interested in inspecting the machine instructions of a function which has no symbolic info and do not want `gdb` to automatically skip over this function.

```
set step-mode off
```

Causes the `step` command to step over any functions which contains no debug information. This is the default.

```
finish
```

Continue running until just after function in the selected stack frame returns. Print the returned value (if any).

Contrast this with the `return` command (refer to Section 16.4 *Returning from a function*).

```
until
```

```
u
```

Continue running until a source line past the current line, in the current stack frame, is reached. This command is used to avoid single stepping through a loop more than once. It is like the `next` command, except that when `until` encounters a jump, it automatically continues execution until the program counter is greater than the address of the jump.

This means that when you reach the end of a loop after single stepping though it, `until` makes your program continue execution until it exits the loop. In contrast, a `next` command at the end of a loop simply steps back to the beginning of the loop, which forces you to step through the next iteration.

`until` always stops your program if it attempts to exit the current stack frame.

`until` may produce somewhat counterintuitive results if the order of machine code does not match the order of the source lines. For example, in the following excerpt from a debugging session, the `f` (`frame`) command shows that execution is stopped at line 206; yet when we use `until`, we get to line 195:

```
(gdb) f
#0 main (argc=4, argv=0xf7fffae8) at m4.c:206
206         expand_input();
(gdb) until
195         for ( ; argc > 0; NEXTARG) {
```

This happened because, for execution efficiency, the compiler had generated code for the loop closure test at the end, rather than the start, of the loop--even though the test in a C `for`-loop is

written before the body of the loop. The `until` command appeared to step back to the beginning of the loop when it advanced to this expression; however, it has not really gone to an earlier statement--not in terms of the actual machine code.

`until` with no argument works by means of single instruction stepping, and hence is slower than `until` with an argument.

```
until location
u location
```

Continue running your program until either the specified location is reached, or the current stack frame returns. `location` is any of the forms of argument acceptable to `break` (refer to Section 7.1.1 *Setting breakpoints*). This form of the command uses breakpoints, and hence is quicker than `until` without an argument. The specified location is actually reached only if it is in the current frame. This implies that `until` can be used to skip over recursive function invocations. For instance in the code below, if the current location is line 96, issuing `until 99` will execute the program up to line 99 in the same invocation of `factorial`, that is, after the inner invocations have returned.

```
94 int factorial (int value)
95 {
96     if (value > 1) {
97         value *= factorial (value - 1);
98     }
99     return (value);
100 }
```

```
advance location
```

Continue running the program up to the given location. An argument is required, anything of the same form as arguments for the `break` command. Execution will also stop upon exit from the current stack frame. This command is similar to `until`, but `advance` will not skip over recursive function calls, and the target location doesn't have to be in the same frame as the current one.

```
stepi
stepi arg
si
```

Execute one machine instruction, then stop and return to the debugger.

It is often useful to do `display/i $pc` when stepping by machine instructions. This makes `gdb` automatically display the next instruction to be executed, each time your program stops. Refer to Section 10.6 *Automatic display*.

An argument is a repeat count, as in `step`.

```
nexti
nexti arg
ni
```

Execute one machine instruction, but if it is a function call, proceed until the function returns.

An argument is a repeat count, as in `next`.

7.3. Signals

A signal is an asynchronous event that can happen in a program. The operating system defines the possible kinds of signals, and gives each kind a name and a number. For example, in Unix `SIGINT` is the signal a program gets when you type an interrupt character (often **C-c**); `SIGSEGV` is the signal a

program gets from referencing a place in memory far away from all the areas in use; `SIGALRM` occurs when the alarm clock timer goes off (which happens only if your program has requested an alarm).

Some signals, including `SIGALRM`, are a normal part of the functioning of your program. Others, such as `SIGSEGV`, indicate errors; these signals are *fatal* (they kill your program immediately) if the program has not specified in advance some other way to handle the signal. `SIGINT` does not indicate an error in your program, but it is normally fatal so it can carry out the purpose of the interrupt: to kill the program.

`gdb` has the ability to detect any occurrence of a signal in your program. You can tell `gdb` in advance what to do for each kind of signal.

Normally, `gdb` is set up to let the non-erroneous signals like `SIGALRM` be silently passed to your program (so as not to interfere with their role in the program's functioning) but to stop your program immediately whenever an error signal happens. You can change these settings with the `handle` command.

```
info signals
info handle
```

Print a table of all the kinds of signals and how `gdb` has been told to handle each one. You can use this to see the signal numbers of all the defined types of signals.

`info handle` is an alias for `info signals`.

```
handle signal keywords...
```

Change the way `gdb` handles signal `signal`. `signal` can be the number of a signal or its name (with or without the `SIG` at the beginning); a list of signal numbers of the form `low-high`; or the word `all`, meaning all the known signals. The `keywords` say what change to make.

The keywords allowed by the `handle` command can be abbreviated. Their full names are:

```
nostop
```

{No value for '`<listitem>GDBN`'} should not stop your program when this signal happens. It may still print a message telling you that the signal has come in.

```
stop
```

{No value for '`<listitem>GDBN`'} should stop your program when this signal happens. This implies the `print` keyword as well.

```
print
```

{No value for '`<listitem>GDBN`'} should print a message when this signal happens.

```
noprint
```

{No value for '`<listitem>GDBN`'} should not mention the occurrence of the signal at all. This implies the `nostop` keyword as well.

```
pass
```

```
noignore
```

{No value for '`<listitem>GDBN`'} should allow your program to see this signal; your program can handle the signal, or else it may terminate if the signal is fatal and not handled. `pass` and `noignore` are synonyms.

```
nopass
ignore
```

{No value for ‘<listitem>GDBN’} should not allow your program to see this signal. `nopass` and `ignore` are synonyms.

When a signal stops your program, the signal is not visible to the program until you continue. Your program sees the signal then, if `pass` is in effect for the signal in question *at that time*. In other words, after `gdb` reports a signal, you can use the `handle` command with `pass` or `nopass` to control whether your program sees that signal when you continue.

The default is set to `nostop`, `noprint`, `pass` for non-erroneous signals such as `SIGALRM`, `SIGWINCH` and `SIGCHLD`, and to `stop`, `print`, `pass` for the erroneous signals.

You can also use the `signal` command to prevent your program from seeing a signal, or cause it to see a signal it normally would not see, or to give it any signal at any time. For example, if your program stopped due to some sort of memory reference error, you might store correct values into the erroneous variables and continue, hoping to see more execution; but your program would probably terminate immediately as a result of the fatal signal once it saw the signal. To prevent this, you can continue with `signal 0`. Refer to Section 16.3 *Giving your program a signal*.

7.4. Stopping and starting multi-thread programs

When your program has multiple threads (refer to Section 6.9 *Debugging programs with multiple threads*), you can choose whether to set breakpoints on all threads, or on a particular thread.

```
break linespec thread threadno
break linespec thread threadno if ...
```

`linespec` specifies source lines; there are several ways of writing them, but the effect is always to specify some source line.

Use the qualifier `thread threadno` with a breakpoint command to specify that you only want `gdb` to stop the program when a particular thread reaches this breakpoint. `threadno` is one of the numeric thread identifiers assigned by `gdb`, shown in the first column of the `info threads` display.

If you do not specify `thread threadno` when you set a breakpoint, the breakpoint applies to *all* threads of your program.

You can use the `thread` qualifier on conditional breakpoints as well; in this case, place `thread threadno` before the breakpoint condition, like this:

```
(gdb) break frik.c:13 thread 28 if bartab > lim
```

Whenever your program stops under `gdb` for any reason, *all* threads of execution stop, not just the current thread. This allows you to examine the overall state of the program, including switching between threads, without worrying that things may change underfoot.

Conversely, whenever you restart the program, *all* threads start executing. *This is true even when single-stepping* with commands like `step` or `next`.

In particular, `gdb` cannot single-step all threads in lockstep. Since thread scheduling is up to your debugging target’s operating system (not controlled by `gdb`), other threads may execute more than one statement while the current thread completes a single step. Moreover, in general other threads stop in the middle of a statement, rather than at a clean statement boundary, when the program stops.

You might even find your program stopped in another thread after continuing or even single-stepping. This happens whenever some other thread runs into a breakpoint, a signal, or an exception before the first thread completes whatever you requested.

On some OSes, you can lock the OS scheduler and thus allow only a single thread to run.

```
set scheduler-locking mode
```

Set the scheduler locking mode. If it is `off`, then there is no locking and any thread may run at any time. If `on`, then only the current thread may run when the inferior is resumed. The `step` mode optimizes for single-stepping. It stops other threads from "seizing the prompt" by preempting the current thread while you are stepping. Other threads will only rarely (or never) get a chance to run when you step. They are more likely to run when you `next` over a function call, and they are completely free to run when you use commands like `continue`, `until`, or `finish`. However, unless another thread hits a breakpoint during its timeslice, they will never steal the gdb prompt away from the thread that you are debugging.

```
show scheduler-locking
```

Display the current scheduler locking mode.

Examining the Stack

When your program has stopped, the first thing you need to know is where it stopped and how it got there.

Each time your program performs a function call, information about the call is generated. That information includes the location of the call in your program, the arguments of the call, and the local variables of the function being called. The information is saved in a block of data called a *stack frame*. The stack frames are allocated in a region of memory called the *call stack*.

When your program stops, the gdb commands for examining the stack allow you to see all of this information.

One of the stack frames is *selected* by gdb and many gdb commands refer implicitly to the selected frame. In particular, whenever you ask gdb for the value of a variable in your program, the value is found in the selected frame. There are special gdb commands to select whichever frame you are interested in. Refer to Section 8.3 *Selecting a frame*.

When your program stops, gdb automatically selects the currently executing frame and describes it briefly, similar to the `frame` command (refer to Section 8.4 *Information about a frame*).

8.1. Stack frames

The call stack is divided up into contiguous pieces called *stack frames*, or *frames* for short; each frame is the data associated with one call to one function. The frame contains the arguments given to the function, the function's local variables, and the address at which the function is executing.

When your program is started, the stack has only one frame, that of the function `main`. This is called the *initial* frame or the *outermost* frame. Each time a function is called, a new frame is made. Each time a function returns, the frame for that function invocation is eliminated. If a function is recursive, there can be many frames for the same function. The frame for the function in which execution is actually occurring is called the *innermost* frame. This is the most recently created of all the stack frames that still exist.

Inside your program, stack frames are identified by their addresses. A stack frame consists of many bytes, each of which has its own address; each kind of computer has a convention for choosing one byte whose address serves as the address of the frame. Usually this address is kept in a register called the *frame pointer register* while execution is going on in that frame.

gdb assigns numbers to all existing stack frames, starting with zero for the innermost frame, one for the frame that called it, and so on upward. These numbers do not really exist in your program; they are assigned by gdb to give you a way of designating stack frames in gdb commands.

Some compilers provide a way to compile functions so that they operate without stack frames. (For example, the gcc option

```
-fomit-frame-pointer
```

generates functions without a frame.) This is occasionally done with heavily used library functions to save the frame setup time. gdb has limited facilities for dealing with these function invocations. If the innermost function invocation has no stack frame, gdb nevertheless regards it as though it had a separate frame, which is numbered zero as usual, allowing correct tracing of the function call chain. However, gdb has no provision for frameless functions elsewhere in the stack.

```
frame args
```

The `frame` command allows you to move from one stack frame to another, and to print the stack frame you select. `args` may be either the address of the frame or the stack frame number. Without an argument, `frame` prints the current stack frame.

```
select-frame
```

The `select-frame` command allows you to move from one stack frame to another without printing the frame. This is the silent version of `frame`.

8.2. Backtraces

A backtrace is a summary of how your program got where it is. It shows one line per frame, for many frames, starting with the currently executing frame (frame zero), followed by its caller (frame one), and on up the stack.

```
backtrace
bt
```

Print a backtrace of the entire stack: one line per frame for all frames in the stack.

You can stop the backtrace at any time by typing the system interrupt character, normally **C-c**.

```
backtrace n
bt n
```

Similar, but print only the innermost `n` frames.

```
backtrace -n
bt -n
```

Similar, but print only the outermost `n` frames.

The names `where` and `info stack` (abbreviated `info s`) are additional aliases for `backtrace`.

Each line in the backtrace shows the frame number and the function name. The program counter value is also shown--unless you use `set print address off`. The backtrace also shows the source file name and line number, as well as the arguments to the function. The program counter value is omitted if it is at the beginning of the code for that line number.

Here is an example of a backtrace. It was made with the command `bt 3`, so it shows the innermost three frames.

```
#0  m4_traceon (obs=0x24eb0, argc=1, argv=0x2b8c8)
    at builtin.c:993
#1  0x6e38 in expand_macro (sym=0x2b600) at macro.c:242
#2  0x6840 in expand_token (obs=0x0, t=177664, td=0xf7fffb08)
    at macro.c:71
(More stack frames follow...)
```

The display for frame zero does not begin with a program counter value, indicating that your program has stopped at the beginning of the code for line 993 of `builtin.c`.

Most programs have a standard entry point--a place where system libraries and startup code transition into user code. For C this is `main`. When `gdb` finds the entry function in a backtrace it will terminate

the backtrace, to avoid tracing into highly system-specific (and generally uninteresting) code. If you need to examine the startup code, then you can change this behavior.

```
set backtrace-below-main off
```

Backtraces will stop when they encounter the user entry point. This is the default.

```
set backtrace-below-main
set backtrace-below-main on
```

Backtraces will continue past the user entry point to the top of the stack.

```
show backtrace-below-main
```

Display the current backtrace policy.

8.3. Selecting a frame

Most commands for examining the stack and other data in your program work on whichever stack frame is selected at the moment. Here are the commands for selecting a stack frame; all of them finish by printing a brief description of the stack frame just selected.

```
frame n
f n
```

Select frame number `n`. Recall that frame zero is the innermost (currently executing) frame, frame one is the frame that called the innermost one, and so on. The highest-numbered frame is the one for `main`.

```
frame addr
f addr
```

Select the frame at address `addr`. This is useful mainly if the chaining of stack frames has been damaged by a bug, making it impossible for `gdb` to assign numbers properly to all frames. In addition, this can be useful when your program has multiple stacks and switches between them.

On the SPARC architecture, `frame` needs two addresses to select an arbitrary frame: a frame pointer and a stack pointer.

On the MIPS and Alpha architecture, it needs two addresses: a stack pointer and a program counter.

On the 29k architecture, it needs three addresses: a register stack pointer, a program counter, and a memory stack pointer.

```
up n
```

Move `n` frames up the stack. For positive numbers `n`, this advances toward the outermost frame, to higher frame numbers, to frames that have existed longer. `n` defaults to one.

```
down n
```

Move `n` frames down the stack. For positive numbers `n`, this advances toward the innermost frame, to lower frame numbers, to frames that were created more recently. `n` defaults to one. You may abbreviate `down` as `do`.

All of these commands end by printing two lines of output describing the frame. The first line shows the frame number, the function name, the arguments, and the source file and line number of execution in that frame. The second line shows the text of that source line.

For example:

```
(gdb) up
#1 0x22f0 in main (argc=1, argv=0xf7fffbf4, env=0xf7ffbfbc)
    at env.c:10
10      read_input_file (argv[i]);
```

After such a printout, the `list` command with no arguments prints ten lines centered on the point of execution in the frame. You can also edit the program at the point of execution with your favorite editing program by typing `edit`. Refer to Section 9.1 *Printing source lines* for details.

```
up-silently n
down-silently n
```

These two commands are variants of `up` and `down`, respectively; they differ in that they do their work silently, without causing display of the new frame. They are intended primarily for use in gdb command scripts, where the output might be unnecessary and distracting.

8.4. Information about a frame

There are several other commands to print information about the selected stack frame.

```
frame
f
```

When used without any argument, this command does not change which frame is selected, but prints a brief description of the currently selected stack frame. It can be abbreviated `f`. With an argument, this command is used to select a stack frame. Refer to Section 8.3 *Selecting a frame*.

```
info frame
info f
```

This command prints a verbose description of the selected stack frame, including:

- the address of the frame
- the address of the next frame down (called by this frame)
- the address of the next frame up (caller of this frame)
- the language in which the source code corresponding to this frame is written
- the address of the frame's arguments
- the address of the frame's local variables
- the program counter saved in it (the address of execution in the caller frame)
- which registers were saved in the frame

The verbose description is useful when something has gone wrong that has made the stack format fail to fit the usual conventions.

```
info frame addr  
info f addr
```

Print a verbose description of the frame at address `addr`, without selecting that frame. The selected frame remains unchanged by this command. This requires the same kind of address (more than one for some architectures) that you specify in the `frame` command. Refer to Section 8.3 *Selecting a frame*.

```
info args
```

Print the arguments of the selected frame, each on a separate line.

```
info locals
```

Print the local variables of the selected frame, each on a separate line. These are all variables (declared either static or automatic) accessible at the point of execution of the selected frame.

```
info catch
```

Print a list of all the exception handlers that are active in the current stack frame at the current point of execution. To see other exception handlers, visit the associated frame (using the `up`, `down`, or `frame` commands); then type `info catch`. Refer to Section 7.1.3 *Setting catchpoints*.

Examining Source Files

`gdb` can print parts of your program's source, since the debugging information recorded in the program tells `gdb` what source files were used to build it. When your program stops, `gdb` spontaneously prints the line where it stopped. Likewise, when you select a stack frame (refer to Section 8.3 *Selecting a frame*), `gdb` prints the line where execution in that frame has stopped. You can print other portions of source files by explicit command.

If you use `gdb` through its `gnu Emacs` interface, you may prefer to use Emacs facilities to view source; refer to Chapter 25 *Using gdb under gnu Emacs*.

9.1. Printing source lines

To print lines from a source file, use the `list` command (abbreviated `l`). By default, ten lines are printed. There are several ways to specify what part of the file you want to print.

Here are the forms of the `list` command most commonly used:

```
list linenum
```

Print lines centered around line number `linenum` in the current source file.

```
list function
```

Print lines centered around the beginning of function `function`.

```
list
```

Print more lines. If the last lines printed were printed with a `list` command, this prints lines following the last lines printed; however, if the last line printed was a solitary line printed as part of displaying a stack frame (refer to Chapter 8 *Examining the Stack*), this prints lines centered around that line.

```
list -
```

Print lines just before the lines last printed.

By default, `gdb` prints ten source lines with any of these forms of the `list` command. You can change this using `set listsize`:

```
set listsize count
```

Make the `list` command display `count` source lines (unless the `list` argument explicitly specifies some other number).

```
show listsize
```

Display the number of lines that `list` prints.

Repeating a `list` command with [RET] discards the argument, so it is equivalent to typing just `list`. This is more useful than listing the same lines again. An exception is made for an argument of `-`; that argument is preserved in repetition so that each repetition moves up in the source file.

In general, the `list` command expects you to supply zero, one or two *linespecs*. Linespecs specify source lines; there are several ways of writing them, but the effect is always to specify some source line. Here is a complete description of the possible arguments for `list`:

`list linespec`

Print lines centered around the line specified by `linespec`.

`list first, last`

Print lines from `first` to `last`. Both arguments are `linespecs`.

`list , last`

Print lines ending with `last`.

`list first,`

Print lines starting with `first`.

`list +`

Print lines just after the lines last printed.

`list -`

Print lines just before the lines last printed.

`list`

As described in the preceding table.

Here are the ways of specifying a single source line--all the kinds of `linespec`.

`number`

Specifies line `number` of the current source file. When a `list` command has two `linespecs`, this refers to the same source file as the first `linespec`.

`+offset`

Specifies the line `offset` lines after the last line printed. When used as the second `linespec` in a `list` command that has two, this specifies the line `offset` lines down from the first `linespec`.

`-offset`

Specifies the line `offset` lines before the last line printed.

`filename: number`

Specifies line `number` in the source file `filename`.

`function`

Specifies the line that begins the body of the function `function`. For example: in C, this is the line with the open brace.

`filename: function`

Specifies the line of the open-brace that begins the body of the function `function` in the file `filename`. You only need the file name with a function name to avoid ambiguity when there are identically named functions in different source files.

`*address`

Specifies the line containing the program address `address`. `address` may be any expression.

9.2. Editing source files

To edit the lines in a source file, use the `edit` command. The editing program of your choice is invoked with the current line set to the active line in the program. Alternatively, there are several ways to specify what part of the file you want to print if you want to see other parts of the program.

Here are the forms of the `edit` command most commonly used:

```
edit
```

Edit the current source file at the active line number in the program.

```
edit number
```

Edit the current source file with `number` as the active line number.

```
edit function
```

Edit the file containing `function` at the beginning of its definition.

```
edit filename:number
```

Specifies line `number` in the source file `filename`.

```
edit filename:function
```

Specifies the line that begins the body of the function `function` in the file `filename`. You only need the file name with a function name to avoid ambiguity when there are identically named functions in different source files.

```
edit *address
```

Specifies the line containing the program address `address`. `address` may be any expression.

9.2.1. Choosing your editor

You can customize `gdb` to use any editor you want ¹. By default, it is `/bin/ex`, but you can change this by setting the environment variable `EDITOR` before using `gdb`. For example, to configure `gdb` to use the `vi` editor, you could use these commands with the `sh` shell:

```
EDITOR=/usr/bin/vi
export EDITOR
gdb ...
```

or in the `csh` shell,

```
setenv EDITOR /usr/bin/vi
gdb ...
```

9.3. Searching source files

There are two commands for searching through the current source file for a regular expression.

1. The only restriction is that your editor (say `ex`), recognizes the following command-line syntax:
`ex +number file` The optional numeric value `+number` designates the active line in the file.

```
forward-search regexp
search regexp
```

The command `forward-search regexp` checks each line, starting with the one following the last line listed, for a match for `regexp`. It lists the line that is found. You can use the synonym `search regexp` or abbreviate the command name as `fo`.

```
reverse-search regexp
```

The command `reverse-search regexp` checks each line, starting with the one before the last line listed and going backward, for a match for `regexp`. It lists the line that is found. You can abbreviate this command as `rev`.

9.4. Specifying source directories

Executable programs sometimes do not record the directories of the source files from which they were compiled, just the names. Even when they do, the directories could be moved between the compilation and your debugging session. `gdb` has a list of directories to search for source files; this is called the *source path*. Each time `gdb` wants a source file, it tries all the directories in the list, in the order they are present in the list, until it finds a file with the desired name. Note that the executable search path is *not* used for this purpose. Neither is the current working directory, unless it happens to be in the source path.

If `gdb` cannot find a source file in the source path, and the object program records a directory, `gdb` tries that directory too. If the source path is empty, and there is no record of the compilation directory, `gdb` looks in the current directory as a last resort.

Whenever you reset or rearrange the source path, `gdb` clears out any information it has cached about where source files are found and where each line is in the file.

When you start `gdb`, its source path includes only `cdir` and `cwd`, in that order. To add other directories, use the `directory` command.

```
directory dirname ...
dir dirname ...
```

Add `directory dirname` to the front of the source path. Several directory names may be given to this command, separated by `:` (on MS-DOS and MS-Windows, where `:` usually appears as part of absolute file names) or whitespace. You may specify a directory that is already in the source path; this moves it forward, so `gdb` searches it sooner.

You can use the string `$cdir` to refer to the compilation directory (if one is recorded), and `$cwd` to refer to the current working directory. `$cwd` is not the same as `.-`—the former tracks the current working directory as it changes during your `gdb` session, while the latter is immediately expanded to the current directory at the time you add an entry to the source path.

```
directory
```

Reset the source path to empty again. This requires confirmation.

```
show directories
```

Print the source path: show which directories it contains.

If your source path is cluttered with directories that are no longer of interest, `gdb` may sometimes cause confusion by finding the wrong versions of source. You can correct the situation as follows:

1. Use `directory` with no argument to reset the source path to empty.
2. Use `directory` with suitable arguments to reinstall the directories you want in the source path. You can add all the directories in one command.

9.5. Source and machine code

You can use the command `info line` to map source lines to program addresses (and vice versa), and the command `disassemble` to display a range of addresses as machine instructions. When run under `gnu Emacs` mode, the `info line` command causes the arrow to point to the line specified. Also, `info line` prints addresses in symbolic form as well as hex.

```
info line linespec
```

Print the starting and ending addresses of the compiled code for source line `linespec`. You can specify source lines in any of the ways understood by the `list` command (refer to Section 9.1 *Printing source lines*).

For example, we can use `info line` to discover the location of the object code for the first line of function `m4_changequote`:

```
(gdb) info line m4_changequote
Line 895 of "builtin.c" starts at pc 0x634c and ends at 0x6350.
```

We can also inquire (using `*addr` as the form for `linespec`) what source line covers a particular address:

```
(gdb) info line *0x63ff
Line 926 of "builtin.c" starts at pc 0x63e4 and ends at 0x6404.
```

After `info line`, the default address for the `x` command is changed to the starting address of the line, so that `x/i` is sufficient to begin examining the machine code (refer to Section 10.5 *Examining memory*). Also, this address is saved as the value of the convenience variable `$_` (refer to Section 10.9 *Convenience variables*).

```
disassemble
```

This specialized command dumps a range of memory as machine instructions. The default memory range is the function surrounding the program counter of the selected frame. A single argument to this command is a program counter value; `gdb` dumps the function surrounding this value. Two arguments specify a range of addresses (first inclusive, second exclusive) to dump.

The following example shows the disassembly of a range of addresses of HP PA-RISC 2.0 code:

```
(gdb) disas 0x32c4 0x32e4
Dump of assembler code from 0x32c4 to 0x32e4:
0x32c4 <main+204>:      addil 0,dp
0x32c8 <main+208>:      ldw 0x22c(sr0,r1),r26
0x32cc <main+212>:      ldil 0x3000,r31
0x32d0 <main+216>:      ble 0x3f8(sr4,r31)
0x32d4 <main+220>:      ldo 0(r31),rp
0x32d8 <main+224>:      addil -0x800,dp
0x32dc <main+228>:      ldo 0x588(r1),r26
0x32e0 <main+232>:      ldil 0x3000,r31
End of assembler dump.
```

Some architectures have more than one commonly-used set of instruction mnemonics or other syntax.

```
set disassembly-flavor instruction-set
```

Select the instruction set to use when disassembling the program via the `disassemble` or `x/i` commands.

Currently this command is only defined for the Intel x86 family. You can set `instruction-set` to either `intel` or `att`. The default is `att`, the AT&T flavor used by default by Unix assemblers for x86-based targets.

Chapter 10.

Examining Data

The usual way to examine data in your program is with the `print` command (abbreviated `p`), or its synonym `inspect`. It evaluates and prints the value of an expression of the language your program is written in (refer to Chapter 14 *Using gdb with Different Languages*).

```
print expr
print /f expr
```

`expr` is an expression (in the source language). By default the value of `expr` is printed in a format appropriate to its data type; you can choose a different format by specifying `/f`, where `f` is a letter specifying the format; refer to Section 10.4 *Output formats*.

```
print
print /f
```

If you omit `expr`, `gdb` displays the last value again (from the *value history*; refer to Section 10.8 *Value history*). This allows you to conveniently inspect the same value in an alternative format.

A more low-level way of examining data is with the `x` command. It examines data in memory at a specified address and prints it in a specified format. Refer to Section 10.5 *Examining memory*.

If you are interested in information about types, or about how the fields of a struct or a class are declared, use the `ptype exp` command rather than `print`. Refer to Chapter 15 *Examining the Symbol Table*.

10.1. Expressions

`print` and many other `gdb` commands accept an expression and compute its value. Any kind of constant, variable or operator defined by the programming language you are using is valid in an expression in `gdb`. This includes conditional expressions, function calls, casts, and string constants. It also includes preprocessor macros, if you compiled your program to include this information; refer to Section 6.1 *Compiling for debugging*.

`gdb` supports array constants in expressions input by the user. The syntax is `{element, element...}`. For example, you can use the command `print {1, 2, 3}` to build up an array in memory that is `malloced` in the target program.

Because C is so widespread, most of the expressions shown in examples in this manual are in C. Refer to Chapter 14 *Using gdb with Different Languages*, for information on how to use expressions in other languages.

In this section, we discuss operators that you can use in `gdb` expressions regardless of your programming language.

Casts are supported in all languages, not just in C, because it is so useful to cast a number into a pointer in order to examine a structure at that address in memory.

`gdb` supports these operators, in addition to those common to programming languages:

@

@ is a binary operator for treating parts of memory as arrays. Refer to Section 10.3 *Artificial arrays*, for more information.

```
::
```

:: allows you to specify a variable in terms of the file or function where it is defined. Refer to Section 10.2 *Program variables*.

```
{type} addr
```

Refers to an object of type `type` stored at address `addr` in memory. `addr` may be any expression whose value is an integer or pointer (but parentheses are required around binary operators, just as in a cast). This construct is allowed regardless of what kind of data is normally supposed to reside at `addr`.

10.2. Program variables

The most common kind of expression to use is the name of a variable in your program.

Variables in expressions are understood in the selected stack frame (refer to Section 8.3 *Selecting a frame*); they must be either:

- global (or file-static)

or

- visible according to the scope rules of the programming language from the point of execution in that frame

This means that in the function

```
foo (a)
    int a;
{
    bar (a);
    {
        int b = test ();
        bar (b);
    }
}
```

you can examine and use the variable `a` whenever your program is executing within the function `foo`, but you can only use or examine the variable `b` while your program is executing inside the block where `b` is declared.

There is an exception: you can refer to a variable or function whose scope is a single source file even if the current execution point is not in this file. But it is possible to have more than one such variable or function with the same name (in different source files). If that happens, referring to that name has unpredictable effects. If you wish, you can specify a static variable in a particular function or file, using the colon-colon notation:

```
file::variable
function::variable
```

Here `file` or `function` is the name of the context for the static `variable`. In the case of file names, you can use quotes to make sure `gdb` parses the file name as a single word—for example, to print a global value of `x` defined in `f2.c`:

```
(gdb) p 'f2.c'::x
```

This use of `::` is very rarely in conflict with the very similar use of the same notation in C++. `gdb` also supports use of the C++ scope resolution operator in `gdb` expressions.

Warning: Occasionally, a local variable may appear to have the wrong value at certain points in a function—just after entry to a new scope, and just before exit.

You may see this problem when you are stepping by machine instructions. This is because, on most machines, it takes more than one instruction to set up a stack frame (including local variable definitions); if you are stepping by machine instructions, variables may appear to have the wrong values until the stack frame is completely built. On exit, it usually also takes more than one machine instruction to destroy a stack frame; after you begin stepping through that group of instructions, local variable definitions may be gone.

This may also happen when the compiler does significant optimizations. To be sure of always seeing accurate values, turn off all optimization when compiling.

Another possible effect of compiler optimizations is to optimize unused variables out of existence, or assign variables to registers (as opposed to memory addresses). Depending on the support for such cases offered by the debug info format used by the compiler, `gdb` might not be able to display values for such local variables. If that happens, `gdb` will print a message like this:

```
No symbol "foo" in current context.
```

To solve such problems, either recompile without optimizations, or use a different debug info format, if the compiler supports several such formats. For example, `gcc`, the `gnu C/C++` compiler usually supports the `-gstabs+` option. `-gstabs+` produces debug info in a format that is superior to formats such as `COFF`. You may be able to use `DWARF 2` (`-gdwarf-2`), which is also an effective form for debug info. .

10.3. Artificial arrays

It is often useful to print out several successive objects of the same type in memory; a section of an array, or an array of dynamically determined size for which only a pointer exists in the program.

You can do this by referring to a contiguous span of memory as an *artificial array*, using the binary operator `@`. The left operand of `@` should be the first element of the desired array and be an individual object. The right operand should be the desired length of the array. The result is an array value whose elements are all of the type of the left argument. The first element is actually the left argument; the second element comes from bytes of memory immediately following those that hold the first element, and so on. Here is an example. If a program says

```
int *array = (int *) malloc (len * sizeof (int));
```

you can print the contents of `array` with

```
p *array@len
```

The left operand of @ must reside in memory. Array values made with @ in this way behave just like other arrays in terms of subscripting, and are coerced to pointers when used in expressions. Artificial arrays most often appear in expressions via the value history (refer to Section 10.8 *Value history*), after printing one out.

Another way to create an artificial array is to use a cast. This re-interprets a value as if it were an array. The value need not be in memory:

```
(gdb) p/x (short[2])0x12345678
$1 = {0x1234, 0x5678}
```

As a convenience, if you leave the array length out (as in `(type[])value`) gdb calculates the size to fill the value (as `sizeof(value)/sizeof(type)`):

```
(gdb) p/x (short[])0x12345678
$2 = {0x1234, 0x5678}
```

Sometimes the artificial array mechanism is not quite enough; in moderately complex data structures, the elements of interest may not actually be adjacent--for example, if you are interested in the values of pointers in an array. One useful work-around in this situation is to use a convenience variable (refer to Section 10.9 *Convenience variables*) as a counter in an expression that prints the first interesting value, and then repeat that expression via [RET]. For instance, suppose you have an array `dtab` of pointers to structures, and you are interested in the values of a field `fv` in each structure. Here is an example of what you might type:

```
set $i = 0
p dtab[$i++]->fv
[RET]
[RET]
...
```

10.4. Output formats

By default, gdb prints a value according to its data type. Sometimes this is not what you want. For example, you might want to print a number in hex, or a pointer in decimal. Or you might want to view data in memory at a certain address as a character string or as an instruction. To do these things, specify an *output format* when you print a value.

The simplest use of output formats is to say how to print a value already computed. This is done by starting the arguments of the `print` command with a slash and a format letter. The format letters supported are:

x

Regard the bits of the value as an integer, and print the integer in hexadecimal.

d

Print as integer in signed decimal.

u

Print as integer in unsigned decimal.

o

Print as integer in octal.

t

Print as integer in binary. The letter `t` stands for "two".¹

a

Print as an address, both absolute in hexadecimal and as an offset from the nearest preceding symbol. You can use this format used to discover where (in what function) an unknown address is located:

```
(gdb) p/a 0x54320
$3 = 0x54320 <_initialize_vx+396>
```

The command `info symbol 0x54320` yields similar results. `info symbol`.

c

Regard as an integer and print it as a character constant.

f

Regard the bits of the value as a floating point number and print using typical floating point syntax.

For example, to print the program counter in hex (refer to Section 10.10 *Registers*), type

```
p/x $pc
```

Note that no space is required before the slash; this is because command names in `gdb` cannot contain a slash.

To reprint the last value in the value history with a different format, you can use the `print` command with just a format and no expression. For example, `p/x` reprints the last value in hex.

10.5. Examining memory

You can use the command `x` (for "examine") to examine memory in any of several formats, independently of your program's data types.

```
x/nfu addr
x addr
x
```

Use the `x` command to examine memory.

`n`, `f`, and `u` are all optional parameters that specify how much memory to display and how to format it; `addr` is an expression giving the address where you want to start displaying memory. If you use defaults for `nfu`, you need not type the slash `/`. Several commands set convenient defaults for `addr`.

1. `b` cannot be used because these format letters are also used with the `x` command, where `b` stands for "byte"; refer to Section 10.5 *Examining memory*.

`n`, the repeat count

The repeat count is a decimal integer; the default is 1. It specifies how much memory (counting by units `u`) to display.

`f`, the display format

The display format is one of the formats used by `print`, `s` (null-terminated string), or `i` (machine instruction). The default is `x` (hexadecimal) initially. The default changes each time you use either `x` or `print`.

`u`, the unit size

The unit size is any of

`b`

Bytes.

`h`

Halfwords (two bytes).

`w`

Words (four bytes). This is the initial default.

`g`

Giant words (eight bytes).

Each time you specify a unit size with `x`, that size becomes the default unit the next time you use `x`. (For the `s` and `i` formats, the unit size is ignored and is normally not written.)

`addr`, starting display address

`addr` is the address where you want `gdb` to begin displaying memory. The expression need not have a pointer value (though it may); it is always interpreted as an integer address of a byte of memory. Refer to Section 10.1 *Expressions*, for more information on expressions. The default for `addr` is usually just after the last address examined—but several other commands also set the default address: `info breakpoints` (to the address of the last breakpoint listed), `info line` (to the starting address of a line), and `print` (if you use it to display a value from memory).

For example, `x/3uh 0x54320` is a request to display three halfwords (`h`) of memory, formatted as unsigned decimal integers (`u`), starting at address `0x54320`. `x/4xw $sp` prints the four words (`w`) of memory above the stack pointer (here, `$sp`; refer to Section 10.10 *Registers*) in hexadecimal (`x`).

Since the letters indicating unit sizes are all distinct from the letters specifying output formats, you do not have to remember whether unit size or format comes first; either order works. The output specifications `4xw` and `4wx` mean exactly the same thing. (However, the count `n` must come first; `wx4` does not work.)

Even though the unit size `u` is ignored for the formats `s` and `i`, you might still want to use a count `n`; for example, `3i` specifies that you want to see three machine instructions, including any operands. The command `disassemble` gives an alternative way of inspecting machine instructions; refer to Section 9.5 *Source and machine code*.

All the defaults for the arguments to `x` are designed to make it easy to continue scanning memory with minimal specifications each time you use `x`. For example, after you have inspected three machine instructions with `x/3i addr`, you can inspect the next seven with just `x/7`. If you use `[RET]` to repeat the `x` command, the repeat count `n` is used again; the other arguments default as for successive uses of `x`.

The addresses and contents printed by the `x` command are not saved in the value history because there is often too much of them and they would get in the way. Instead, `gdb` makes these values available for subsequent use in expressions as values of the convenience variables `$_` and `$__`. After an `x` command, the last address examined is available for use in expressions in the convenience variable `$_`. The contents of that address, as examined, are available in the convenience variable `$__`.

If the `x` command has a repeat count, the address and contents saved are from the last memory unit printed; this is not the same as the last address printed if several units were printed on the last line of output.

10.6. Automatic display

If you find that you want to print the value of an expression frequently (to see how it changes), you might want to add it to the *automatic display list* so that `gdb` prints its value each time your program stops. Each expression added to the list is given a number to identify it; to remove an expression from the list, you specify that number. The automatic display looks like this:

```
2: foo = 38
3: bar[5] = (struct hack *) 0x3804
```

This display shows item numbers, expressions and their current values. As with displays you request manually using `x` or `print`, you can specify the output format you prefer; in fact, `display` decides whether to use `print` or `x` depending on how elaborate your format specification is—it uses `x` if you specify a unit size, or one of the two formats (`i` and `s`) that are only supported by `x`; otherwise it uses `print`.

```
display expr
```

Add the expression `expr` to the list of expressions to display each time your program stops. Refer to Section 10.1 *Expressions*.

`display` does not repeat if you press [RET] again after using it.

```
display/fmt expr
```

For `fmt` specifying only a display format and not a size or count, add the expression `expr` to the auto-display list but arrange to display it each time in the specified format `fmt`. Refer to Section 10.4 *Output formats*.

```
display/fmt addr
```

For `fmt` `i` or `s`, or including a unit-size or a number of units, add the expression `addr` as a memory address to be examined each time your program stops. Examining means in effect doing `x/fmt addr`. Refer to Section 10.5 *Examining memory*.

For example, `display/i $pc` can be helpful, to see the machine instruction about to be executed each time execution stops (`$pc` is a common name for the program counter; refer to Section 10.10 *Registers*).

```
undisplay dnums...
```

```
delete display dnums...
```

Remove item numbers `dnums` from the list of expressions to display.

`undisplay` does not repeat if you press [RET] after using it. (Otherwise you would just get the error `No display number ...`)

```
disable display dnums...
```

Disable the display of item numbers `dnums`. A disabled display item is not printed automatically, but is not forgotten. It may be enabled again later.

```
enable display dnums...
```

Enable display of item numbers `dnums`. It becomes effective once again in auto display of its expression, until you specify otherwise.

```
display
```

Display the current values of the expressions on the list, just as is done when your program stops.

```
info display
```

Print the list of expressions previously set up to display automatically, each one with its item number, but without showing the values. This includes disabled expressions, which are marked as such. It also includes expressions which would not be displayed right now because they refer to automatic variables not currently available.

If a display expression refers to local variables, then it does not make sense outside the lexical context for which it was set up. Such an expression is disabled when execution enters a context where one of its variables is not defined. For example, if you give the command `display last_char` while inside a function with an argument `last_char`, `gdb` displays this argument while your program continues to stop inside that function. When it stops elsewhere--where there is no variable `last_char`--the display is disabled automatically. The next time your program stops where `last_char` is meaningful, you can enable the display expression once again.

10.7. Print settings

`gdb` provides the following ways to control how arrays, structures, and symbols are printed.

These settings are useful for debugging programs in any language:

```
set print address
set print address on
```

{No value for '`<listitem>GDBN`'} prints memory addresses showing the location of stack traces, structure values, pointer values, breakpoints, and so forth, even when it also displays the contents of those addresses. The default is `on`. For example, this is what a stack frame display looks like with `set print address on`:

```
(gdb) f
#0 set_quotes (lq=0x34c78 "<<", rq=0x34c88 ">>")
   at input.c:530
530     if (lquote != def_lquote)
```

```
set print address off
```

Do not print addresses when displaying their contents. For example, this is the same stack frame displayed with `set print address off`:

```
(gdb) set print addr off
(gdb) f
#0 set_quotes (lq="<<", rq=">>") at input.c:530
530     if (lquote != def_lquote)
```

You can use `set print address off` to eliminate all machine dependent displays from the gdb interface. For example, with `print address off`, you should get the same text for backtraces on all machines--whether or not they involve pointer arguments.

```
show print address
```

Show whether or not addresses are to be printed.

When gdb prints a symbolic address, it normally prints the closest earlier symbol plus an offset. If that symbol does not uniquely identify the address (for example, it is a name whose scope is a single source file), you may need to clarify. One way to do this is with `info line`, for example `info line *0x4537`. Alternately, you can set gdb to print the source file and line number when it prints a symbolic address:

```
set print symbol-filename on
```

Tell gdb to print the source file name and line number of a symbol in the symbolic form of an address.

```
set print symbol-filename off
```

Do not print source file name and line number of a symbol. This is the default.

```
show print symbol-filename
```

Show whether or not gdb will print the source file name and line number of a symbol in the symbolic form of an address.

Another situation where it is helpful to show symbol filenames and line numbers is when disassembling code; gdb shows you the line number and source file that corresponds to each instruction.

Also, you may wish to see the symbolic form only if the address being printed is reasonably close to the closest earlier symbol:

```
set print max-symbolic-offset max-offset
```

Tell gdb to only display the symbolic form of an address if the offset between the closest earlier symbol and the address is less than `max-offset`. The default is 0, which tells gdb to always print the symbolic form of an address if any symbol precedes it.

```
show print max-symbolic-offset
```

Ask how large the maximum offset is that gdb prints in a symbolic address.

If you have a pointer and you are not sure where it points, try `set print symbol-filename on`. Then you can determine the name and source file location of the variable where it points, using `p/a pointer`. This interprets the address in symbolic form. For example, here gdb shows that a variable `ptt` points at another variable `t`, defined in `hi2.c`:

```
(gdb) set print symbol-filename on
(gdb) p/a ptt
$4 = 0xe008 <t in hi2.c>
```

Warning: For pointers that point to a local variable, `p/a` does not show the symbol name and filename of the referent, even with the appropriate `set print` options turned on.

Other settings control how different kinds of objects are printed:

```
set print array
set print array on
```

Pretty print arrays. This format is more convenient to read, but uses more space. The default is off.

```
set print array off
```

Return to compressed format for arrays.

```
show print array
```

Show whether compressed or pretty format is selected for displaying arrays.

```
set print elements number-of-elements
```

Set a limit on how many elements of an array gdb will print. If gdb is printing a large array, it stops printing after it has printed the number of elements set by the `set print elements` command. This limit also applies to the display of strings. When gdb starts, this limit is set to 200. Setting `number-of-elements` to zero means that the printing is unlimited.

```
show print elements
```

Display the number of elements of a large array that gdb will print. If the number is 0, then the printing is unlimited.

```
set print null-stop
```

Cause gdb to stop printing the characters of an array when the first null is encountered. This is useful when large arrays actually contain only short strings. The default is off.

```
set print pretty on
```

Cause gdb to print structures in an indented format with one member per line, like this:

```
$1 = {
  next = 0x0,
  flags = {
    sweet = 1,
    sour = 1
  },
  meat = 0x54 "Pork"
}
```

```
set print pretty off
```

Cause gdb to print structures in a compact format, like this:

```
$1 = {next = 0x0, flags = {sweet = 1, sour = 1}, \
meat = 0x54 "Pork"}
```

This is the default format.

```
show print pretty
```

Show which format gdb is using to print structures.

```
set print sevenbit-strings on
```

Print using only seven-bit characters; if this option is set, gdb displays any eight-bit characters (in strings or character values) using the notation `\nnn`. This setting is best if you are working in English (ascii) and you use the high-order bit of characters as a marker or "meta" bit.

```
set print sevenbit-strings off
```

Print full eight-bit characters. This allows the use of more international character sets, and is the default.

```
show print sevenbit-strings
```

Show whether or not gdb is printing only seven-bit characters.

```
set print union on
```

Tell gdb to print unions which are contained in structures. This is the default setting.

```
set print union off
```

Tell gdb not to print unions which are contained in structures.

```
show print union
```

Ask gdb whether or not it will print unions which are contained in structures.

For example, given the declarations

```
typedef enum {Tree, Bug} Species;
typedef enum {Big_tree, Acorn, Seedling} Tree_forms;
typedef enum {Caterpillar, Cocoon, Butterfly}
    Bug_forms;
```

```
struct thing {
    Species it;
    union {
        Tree_forms tree;
        Bug_forms bug;
    } form;
};
```

```
struct thing foo = {Tree, {Acorn}};
```

with `set print union on` in effect `p foo` would print

```
$1 = {it = Tree, form = {tree = Acorn, bug = Cocoon}}
```

and with `set print union off` in effect it would print

```
$1 = {it = Tree, form = {...}}
```

These settings are of interest when debugging C++ programs:

```
set print demangle
```

```
set print demangle on
```

Print C++ names in their source form rather than in the encoded ("mangled") form passed to the assembler and linker for type-safe linkage. The default is on.

```
show print demangle
```

Show whether C++ names are printed in mangled or demangled form.

```
set print asm-demangle
set print asm-demangle on
```

Print C++ names in their source form rather than their mangled form, even in assembler code printouts such as instruction disassemblies. The default is off.

```
show print asm-demangle
```

Show whether C++ names in assembly listings are printed in mangled or demangled form.

```
set demangle-style style
```

Choose among several encoding schemes used by different compilers to represent C++ names. The choices for `style` are currently:

```
auto
```

Allow gdb to choose a decoding style by inspecting your program.

```
gnu
```

Decode based on the gnu C++ compiler (`g++`) encoding algorithm. This is the default.

```
hp
```

Decode based on the HP ANSI C++ (`acc`) encoding algorithm.

```
lucid
```

Decode based on the Lucid C++ compiler (`lcc`) encoding algorithm.

```
arm
```

Decode using the algorithm in the [C++ Annotated Reference Manual]. *Warning:* this setting alone is not sufficient to allow debugging `cfront`-generated executables. gdb would require further enhancement to permit that.

If you omit `style`, you will see a list of possible formats.

```
show demangle-style
```

Display the encoding style currently in use for decoding C++ symbols.

```
set print object
set print object on
```

When displaying a pointer to an object, identify the *actual* (derived) type of the object rather than the *declared* type, using the virtual function table.

```
set print object off
```

Display only the declared type of objects, without reference to the virtual function table. This is the default setting.

```
show print object
```

Show whether actual, or declared, object types are displayed.

```
set print static-members
set print static-members on
```

Print static members when displaying a C++ object. The default is on.

```
set print static-members off
```

Do not print static members when displaying a C++ object.

```
show print static-members
```

Show whether C++ static members are printed, or not.

```
set print vtbl
set print vtbl on
```

Pretty print C++ virtual function tables. The default is off. (The `vtbl` commands do not work on programs compiled with the HP ANSI C++ compiler (`aCC`.)

```
set print vtbl off
```

Do not pretty print C++ virtual function tables.

```
show print vtbl
```

Show whether C++ virtual function tables are pretty printed, or not.

10.8. Value history

Values printed by the `print` command are saved in the gdb *value history*. This allows you to refer to them in other expressions. Values are kept until the symbol table is re-read or discarded (for example with the `file` or `symbol-file` commands). When the symbol table changes, the value history is discarded, since the values may contain pointers back to the types defined in the symbol table.

The values printed are given *history numbers* by which you can refer to them. These are successive integers starting with one. `print` shows you the history number assigned to a value by printing `$num =` before the value; here `num` is the history number.

To refer to any previous value, use `$` followed by the value's history number. The way `print` labels its output is designed to remind you of this. Just `$` refers to the most recent value in the history, and `$$` refers to the value before that. `$$n` refers to the `n`th value from the end; `$$2` is the value just prior to `$$`, `$$1` is equivalent to `$$`, and `$$0` is equivalent to `$`.

For example, suppose you have just printed a pointer to a structure and want to see the contents of the structure. It suffices to type

```
p *$
```

If you have a chain of structures where the component `next` points to the next one, you can print the contents of the next one with this:

```
p *$.next
```

You can print successive links in the chain by repeating this command--which you can do by just typing [RET].

Note that the history records values, not expressions. If the value of `x` is 4 and you type these commands:

```
print x
set x=5
```

then the value recorded in the value history by the `print` command remains 4 even though the value of `x` has changed.

```
show values
```

Print the last ten values in the value history, with their item numbers. This is like `p $9` repeated ten times, except that `show values` does not change the history.

```
show values n
```

Print ten history values centered on history item number `n`.

```
show values +
```

Print ten history values just after the values last printed. If no more values are available, `show values +` produces no display.

Pressing [RET] to repeat `show values n` has exactly the same effect as `show values +`.

10.9. Convenience variables

`gdb` provides *convenience variables* that you can use within `gdb` to hold on to a value and refer to it later. These variables exist entirely within `gdb`; they are not part of your program, and setting a convenience variable has no direct effect on further execution of your program. That is why you can use them freely.

Convenience variables are prefixed with `$`. Any name preceded by `$` can be used for a convenience variable, unless it is one of the predefined machine-specific register names (refer to Section 10.10 *Registers*). (Value history references, in contrast, are *numbers* preceded by `$`. Refer to Section 10.8 *Value history*.)

You can save a value in a convenience variable with an assignment expression, just as you would set a variable in your program. For example:

```
set $foo = *object_ptr
```

would save in `$foo` the value contained in the object pointed to by `object_ptr`.

Using a convenience variable for the first time creates it, but its value is `void` until you assign a new value. You can alter the value with another assignment at any time.

Convenience variables have no fixed types. You can assign a convenience variable any type of value, including structures and arrays, even if that variable already has a value of a different type. The convenience variable, when used as an expression, has the type of its current value.

```
show convenience
```

Print a list of convenience variables used so far, and their values. Abbreviated `show conv`.

One of the ways to use a convenience variable is as a counter to be incremented or a pointer to be advanced. For example, to print a field from successive elements of an array of structures:

```
set $i = 0
print bar[$i++]>contents
```

Repeat that command by typing [RET].

Some convenience variables are created automatically by `gdb` and given values likely to be useful.

`$_`

The variable `$_` is automatically set by the `x` command to the last address examined (refer to Section 10.5 *Examining memory*). Other commands which provide a default address for `x` to examine also set `$_` to that address; these commands include `info line` and `info breakpoint`. The type of `$_` is `void *` except when set by the `x` command, in which case it is a pointer to the type of `$_`.

`$_`

The variable `$_` is automatically set by the `x` command to the value found in the last address examined. Its type is chosen to match the format in which the data was printed.

`$_exitcode`

The variable `$_exitcode` is automatically set to the exit code when the program being debugged terminates.

On HP-UX systems, if you refer to a function or variable name that begins with a dollar sign, `gdb` searches for a user or system name first, before it searches for a convenience variable.

10.10. Registers

You can refer to machine register contents, in expressions, as variables with names starting with `$`. The names of registers are different for each machine; use `info registers` to see the names used on your machine.

```
info registers
```

Print the names and values of all registers except floating-point and vector registers (in the selected stack frame).

```
info all-registers
```

Print the names and values of all registers, including floating-point and vector registers (in the selected stack frame).

```
info registers regname ...
```

Print the *relativized* value of each specified register `regname`. As discussed in detail below, register values are normally relative to the selected stack frame. `regname` may be any register name valid on the machine you are using, with or without the initial `$`.

`gdb` has four "standard" register names that are available (in expressions) on most machines--whenever they do not conflict with an architecture's canonical mnemonics for registers. The register names `$pc` and `$sp` are used for the program counter register and the stack pointer. `$fp` is used for a register that contains a pointer to the current stack frame, and `$ps` is used for a register that contains the processor status. For example, you could print the program counter in hex with

```
p/x $pc
```

or print the instruction to be executed next with

```
x/i $pc
```

or add four to the stack pointer² with

```
set $sp += 4
```

Whenever possible, these four standard register names are available on your machine even though the machine has different canonical mnemonics, so long as there is no conflict. The `info registers` command shows the canonical names. For example, on the SPARC, `info registers` displays the processor status register as `$psr` but you can also refer to it as `$ps`; and on x86-based machines `$ps` is an alias for the eflags register.

`gdb` always considers the contents of an ordinary register as an integer when the register is examined in this way. Some machines have special registers which can hold nothing but floating point; these registers are considered to have floating point values. There is no way to refer to the contents of an ordinary register as floating point value (although you can *print* it as a floating point value with `print/f $regname`).

Some registers have distinct "raw" and "virtual" data formats. This means that the data format in which the register contents are saved by the operating system is not the same one that your program normally sees. For example, the registers of the 68881 floating point coprocessor are always saved in "extended" (raw) format, but all C programs expect to work with "double" (virtual) format. In such cases, `gdb` normally works with the virtual format only (the format that makes sense for your program), but the `info registers` command prints the data in both formats.

Normally, register values are relative to the selected stack frame (refer to Section 8.3 *Selecting a frame*). This means that you get the value that the register would contain if all stack frames farther in were exited and their saved registers restored. In order to see the true contents of hardware registers, you must select the innermost frame (with `frame 0`).

However, `gdb` must deduce where registers are saved, from the machine code generated by your compiler. If some registers are not saved, or if `gdb` is unable to locate the saved registers, the selected stack frame makes no difference.

2. This is a way of removing one word from the stack, on machines where stacks grow downward in memory (most machines, nowadays). This assumes that the innermost stack frame is selected; setting `$sp` is not allowed when other stack frames are selected. To pop entire frames off the stack, regardless of machine architecture, use `return`; (refer to Section 16.4 *Returning from a function*).

10.11. Floating point hardware

Depending on the configuration, `gdb` may be able to give you more information about the status of the floating point hardware.

```
info float
```

Display hardware-dependent information about the floating point unit. The exact contents and layout vary depending on the floating point chip. Currently, `info float` is supported on the ARM and x86 machines.

10.12. Vector Unit

Depending on the configuration, `gdb` may be able to give you more information about the status of the vector unit.

```
info vector
```

Display information about the vector unit. The exact contents and layout vary depending on the hardware.

10.13. Memory region attributes

Memory region attributes allow you to describe special handling required by regions of your target's memory. `gdb` uses attributes to determine whether to allow certain types of memory accesses; whether to use specific width accesses; and whether to cache target memory.

Defined memory regions can be individually enabled and disabled. When a memory region is disabled, `gdb` uses the default attributes when accessing memory in that region. Similarly, if no memory regions have been defined, `gdb` uses the default attributes when accessing all memory.

When a memory region is defined, it is given a number to identify it; to enable, disable, or remove a memory region, you specify that number.

```
mem lower upper attributes...
```

Define memory region bounded by `lower` and `upper` with attributes `attributes...`. Note that `upper == 0` is a special case: it is treated as the the target's maximum memory address. (0xffff on 16 bit targets, 0xffffffff on 32 bit targets, etc.)

```
delete mem nums...
```

Remove memory regions `nums...`

```
disable mem nums...
```

Disable memory regions `nums...`. A disabled memory region is not forgotten. It may be enabled again later.

```
enable mem nums...
```

Enable memory regions `nums...`

`info mem`

Print a table of all defined memory regions, with the following columns for each region.

Memory Region Number
Enabled or Disabled.

Enabled memory regions are marked with `y`. Disabled memory regions are marked with `n`.

Lo Address

The address defining the inclusive lower bound of the memory region.

Hi Address

The address defining the exclusive upper bound of the memory region.

Attributes

The list of attributes set for this memory region.

10.13.1. Attributes

10.13.1.1. Memory Access Mode

The access mode attributes set whether `gdb` may make read or write accesses to a memory region.

While these attributes prevent `gdb` from performing invalid memory accesses, they do nothing to prevent the target system, I/O DMA, etc. from accessing memory.

`ro`

Memory is read only.

`wo`

Memory is write only.

`rw`

Memory is read/write. This is the default.

10.13.1.2. Memory Access Size

The access size attributes tells `gdb` to use specific sized accesses in the memory region. Often memory mapped device registers require specific sized accesses. If no access size attribute is specified, `gdb` may use accesses of any size.

`8`

Use 8 bit memory accesses.

`16`

Use 16 bit memory accesses.

`32`

Use 32 bit memory accesses.

64

Use 64 bit memory accesses.

10.13.1.3. Data Cache

The data cache attributes set whether gdb will cache target memory. While this generally improves performance by reducing debug protocol overhead, it can lead to incorrect results because gdb does not know about volatile variables or memory mapped device registers.

cache

Enable gdb to cache target memory.

nocache

Disable gdb from caching target memory. This is the default.

10.14. Copy between memory and a file

You can use the commands `dump`, `append`, and `restore` to copy data between target memory and a file. The `dump` and `append` commands write data to a file, and the `restore` command reads data from a file back into the inferior's memory. Files may be in binary, Motorola S-record, Intel hex, or Tektronix Hex format; however, gdb can only append to binary files.

```
dump [format] memory filename start_addr end_addr
```

```
dump [format] value filename expr
```

Dump the contents of memory from `start_addr` to `end_addr`, or the value of `expr`, to `filename` in the given format.

The `format` parameter may be any one of:

binary

Raw binary form.

ihex

Intel hex format.

srec

Motorola S-record format.

tekhex

Tektronix Hex format.

`gdb` uses the same definitions of these formats as the `gnu` binary utilities, like `objdump` and `objcopy`. If `format` is omitted, `gdb` dumps the data in raw binary form.

```
append [binary] memory filename start_addr end_addr
append [binary] value filename expr
```

Append the contents of memory from `start_addr` to `end_addr`, or the value of `expr`, to `filename`, in raw binary form. (gdb can only append data to files in raw binary form.)

```
restore filename [binary] bias start end
```

Restore the contents of file `filename` into memory. The `restore` command can automatically recognize any known bfd file format, except for raw binary. To restore a raw binary file you must specify the optional keyword `binary` after the filename.

If `bias` is non-zero, its value will be added to the addresses contained in the file. Binary files always start at address zero, so they will be restored at address `bias`. Other bfd files have a built-in location; they will be restored at offset `bias` from that location.

If `start` and/or `end` are non-zero, then only data between file offset `start` and file offset `end` will be restored. These offsets are relative to the addresses in the file, before the `bias` argument is applied.

10.15. Character Sets

If the program you are debugging uses a different character set to represent characters and strings than the one gdb uses itself, gdb can automatically translate between the character sets for you. The character set gdb uses we call the *host character set*; the one the inferior program uses we call the *target character set*.

For example, if you are running gdb on a gnu/Linux system, which uses the ISO Latin 1 character set, but you are using gdb's remote protocol (Remote Debugging) to debug a program running on an IBM mainframe, which uses the ebcdic character set, then the host character set is Latin-1, and the target character set is ebcdic. If you give gdb the command `set target-charset EBCDIC-US`, then gdb translates between ebcdic and Latin 1 as you print character or string values, or use character and string literals in expressions.

gdb has no way to automatically recognize which character set the inferior program uses; you must tell it, using the `set target-charset` command, described below.

Here are the commands for controlling gdb's character set support:

```
set target-charset charset
```

Set the current target character set to `charset`. We list the character set names gdb recognizes below, but if you type `set target-charset` followed by [TAB][TAB], gdb will list the target character sets it supports.

```
set host-charset charset
```

Set the current host character set to `charset`.

By default, gdb uses a host character set appropriate to the system it is running on; you can override that default using the `set host-charset` command.

gdb can only use certain character sets as its host character set. We list the character set names gdb recognizes below, and indicate which can be host character sets, but if you type `set target-charset` followed by [TAB][TAB], gdb will list the host character sets it supports.

```
set charset charset
```

Set the current host and target character sets to `charset`. As above, if you type `set charset` followed by [TAB][TAB], gdb will list the name of the character sets that can be used for both host and target.

```
show charset
```

Show the names of the current host and target charsets.

```
show host-charset
```

Show the name of the current host charset.

```
show target-charset
```

Show the name of the current target charset.

`gdb` currently includes support for the following character sets:

ASCII

Seven-bit U.S. `ascii`. `gdb` can use this as its host character set.

ISO-8859-1

The ISO Latin 1 character set. This extends `ascii` with accented characters needed for French, German, and Spanish. `gdb` can use this as its host character set.

EBCDIC-US

IBM1047

Variants of the `ebcdic` character set, used on some of IBM's mainframe operating systems. (`gnu/Linux` on the S/390 uses U.S. `ascii`.) `gdb` cannot use these as its host character set.

Note that these are all single-byte character sets. More work inside GDB is needed to support multi-byte or variable-width character encodings, like the UTF-8 and UCS-2 encodings of Unicode.

Here is an example of `gdb`'s character set support in action. Assume that the following source code has been placed in the file `charset-test.c`:

```
#include <stdio.h>

char ascii_hello[]
  = {72, 101, 108, 108, 111, 44, 32, 119,
     111, 114, 108, 100, 33, 10, 0};
char ibm1047_hello[]
  = {200, 133, 147, 147, 150, 107, 64, 166,
     150, 153, 147, 132, 90, 37, 0};

main ()
{
  printf ("Hello, world!\n");
}
```

In this program, `ascii_hello` and `ibm1047_hello` are arrays containing the string `Hello, world!` followed by a newline, encoded in the `ascii` and `ibm1047` character sets.

We compile the program, and invoke the debugger on it:

```
$ gcc -g charset-test.c -o charset-test
$ gdb -nw charset-test
GNU gdb 2001-12-19-cvs
Copyright 2001 Free Software Foundation, Inc.
...
(gdb)
```

We can use the `show charset` command to see what character sets `gdb` is currently using to interpret and display characters and strings:

```
(gdb) show charset
The current host and target character set is 'ISO-8859-1'.
(gdb)
```

For the sake of printing this manual, let's use `ascii` as our initial character set:

```
(gdb) set charset ASCII
(gdb) show charset
The current host and target character set is 'ASCII'.
(gdb)
```

Let's assume that `ascii` is indeed the correct character set for our host system -- in other words, let's assume that if `gdb` prints characters using the `ascii` character set, our terminal will display them properly. Since our current target character set is also `ascii`, the contents of `ascii_hello` print legibly:

```
(gdb) print ascii_hello
$1 = 0x401698 "Hello, world!\n"
(gdb) print ascii_hello[0]
$2 = 72 'H'
(gdb)
```

`gdb` uses the target character set for character and string literals you use in expressions:

```
(gdb) print '+'
$3 = 43 '+'
(gdb)
```

The `ascii` character set uses the number 43 to encode the `+` character.

`gdb` relies on the user to tell it which character set the target program uses. If we print `ibm1047_hello` while our target character set is still `ascii`, we get jibberish:

```
(gdb) print ibm1047_hello
$4 = 0x4016a8 "\310\205\223\223\226k@\246\226\231\223\204z%"
(gdb) print ibm1047_hello[0]
$5 = 200 '\310'
(gdb)
```

If we invoke the `set target-charset` followed by `[TAB][TAB]`, `gdb` tells us the character sets it supports:

```
(gdb) set target-charset
ASCII      EBCDIC-US  IBM1047    ISO-8859-1
(gdb) set target-charset
```

We can select `ibm1047` as our target character set, and examine the program's strings again. Now the `ascii` string is wrong, but `gdb` translates the contents of `ibm1047_hello` from the target character set, `ibm1047`, to the host character set, `ascii`, and they display correctly:

```
(gdb) set target-charset IBM1047
(gdb) show charset
The current host character set is 'ASCII'.
The current target character set is 'IBM1047'.
(gdb) print ascii_hello
$6 = 0x401698 "\110\145%%?\054\040\167?\162%\144\041\012"
(gdb) print ascii_hello[0]
$7 = 72 '\110'
(gdb) print ibm1047_hello
$8 = 0x4016a8 "Hello, world!\n"
(gdb) print ibm1047_hello[0]
$9 = 200 'H'
(gdb)
```

As above, `gdb` uses the target character set for character and string literals you use in expressions:

```
(gdb) print '+'
$10 = 78 '+'
(gdb)
```

The `ibm1047` character set uses the number 78 to encode the `+` character.

C Preprocessor Macros

Some languages, such as C and C++, provide a way to define and invoke "preprocessor macros" which expand into strings of tokens. `gdb` can evaluate expressions containing macro invocations, show the result of macro expansion, and show a macro's definition, including where it was defined.

You may need to compile your program specially to provide `gdb` with information about preprocessor macros. Most compilers do not include macros in their debugging information, even when you compile with the `-g` flag. Refer to Section 6.1 *Compiling for debugging*.

A program may define a macro at one point, remove that definition later, and then provide a different definition after that. Thus, at different points in the program, a macro may have different definitions, or have no definition at all. If there is a current stack frame, `gdb` uses the macros in scope at that frame's source code line. Otherwise, `gdb` uses the macros in scope at the current listing location; (refer to Section 9.1 *Printing source lines*).

At the moment, `gdb` does not support the `##` token-splicing operator, the `#` stringification operator, or variable-arity macros.

Whenever `gdb` evaluates an expression, it always expands any macro invocations present in the expression. `gdb` also provides the following commands for working with macros explicitly.

```
macro expand expression
macro exp expression
```

Show the results of expanding all preprocessor macro invocations in `expression`. Since `gdb` simply expands macros, but does not parse the result, `expression` need not be a valid expression; it can be any string of tokens.

```
macro expand-once expression
macro expl expression
```

(This command is not yet implemented.) Show the results of expanding those preprocessor macro invocations that appear explicitly in `expression`. Macro invocations appearing in that expansion are left unchanged. This command allows you to see the effect of a particular macro more clearly, without being confused by further expansions. Since `gdb` simply expands macros, but does not parse the result, `expression` need not be a valid expression; it can be any string of tokens.

```
info macro macro
```

Show the definition of the macro named `macro`, and describe the source location where that definition was established.

```
macro define macro replacement-list
macro define macro(arglist) replacement-list
```

(This command is not yet implemented.) Introduce a definition for a preprocessor macro named `macro`, invocations of which are replaced by the tokens given in `replacement-list`. The first form of this command defines an "object-like" macro, which takes no arguments; the second form defines a "function-like" macro, which takes the arguments given in `arglist`.

A definition introduced by this command is in scope in every expression evaluated in `gdb`, until it is removed with the `macro undef` command, described below. The definition overrides all

definitions for `macro` present in the program being debugged, as well as any previous user-supplied definition.

```
macro undef macro
```

(*This command is not yet implemented.*) Remove any user-supplied definition for the macro named `macro`. This command only affects definitions provided with the `macro define` command, described above; it cannot remove definitions present in the program being debugged.

Here is a transcript showing the above commands in action. First, we show our source files:

```
$ cat sample.c
#include <stdio.h>
#include "sample.h"

#define M 42
#define ADD(x) (M + x)

main ()
{
#define N 28
    printf ("Hello, world!\n");
#undef N
    printf ("We're so creative.\n");
#define N 1729
    printf ("Goodbye, world!\n");
}
$ cat sample.h
#define Q <
$
```

Now, we compile the program using the gnu C compiler, `gcc`. We pass the `-gdwarf-2` and `-g3` flags to ensure the compiler includes information about preprocessor macros in the debugging information.

```
$ gcc -gdwarf-2 -g3 sample.c -o sample
$
```

Now, we start `gdb` on our sample program:

```
$ gdb -nw sample
GNU gdb 2002-05-06-cvs
Copyright 2002 Free Software Foundation, Inc.
GDB is free software, ...
(gdb)
```

We can expand macros and examine their definitions, even when the program is not running. `gdb` uses the current listing position to decide which macro definitions are in scope:

```
(gdb) list main
3
4     #define M 42
5     #define ADD(x) (M + x)
6
7     main ()
```

```

8      {
9      #define N 28
10     printf ("Hello, world!\n");
11     #undef N
12     printf ("We're so creative.\n");
(gdb) info macro ADD
Defined at /home/jimb/gdb/macros/play/sample.c:5
#define ADD(x) (M + x)
(gdb) info macro Q
Defined at /home/jimb/gdb/macros/play/sample.h:1
  included at /home/jimb/gdb/macros/play/sample.c:2
#define Q <
(gdb) macro expand ADD(1)
expands to: (42 + 1)
(gdb) macro expand-once ADD(1)
expands to: once (M + 1)
(gdb)

```

In the example above, note that `macro expand-once` expands only the macro invocation explicit in the original text -- the invocation of `ADD` -- but does not expand the invocation of the macro `M`, which was introduced by `ADD`.

Once the program is running, GDB uses the macro definitions in force at the source line of the current stack frame:

```

(gdb) break main
Breakpoint 1 at 0x8048370: file sample.c, line 10.
(gdb) run
Starting program: /home/jimb/gdb/macros/play/sample

Breakpoint 1, main () at sample.c:10
10     printf ("Hello, world!\n");
(gdb)

```

At line 10, the definition of the macro `N` at line 9 is in force:

```

(gdb) info macro N
Defined at /home/jimb/gdb/macros/play/sample.c:9
#define N 28
(gdb) macro expand N Q M
expands to: 28 < 42
(gdb) print N Q M
$1 = 1
(gdb)

```

As we step over directives that remove `N`'s definition, and then give it a new definition, `gdb` finds the definition (or lack thereof) in force at each point:

```

(gdb) next
Hello, world!
12     printf ("We're so creative.\n");
(gdb) info macro N
The symbol 'N' has no definition as a C/C++ preprocessor macro
at /home/jimb/gdb/macros/play/sample.c:12
(gdb) next

```

```
We're so creative.  
14     printf ("Goodbye, world!\n");  
(gdb) info macro N  
Defined at /home/jimb/gdb/macros/play/sample.c:13  
#define N 1729  
(gdb) macro expand N Q M  
expands to: 1729 < 42  
(gdb) print N Q M  
$2 = 0  
(gdb)
```

In some applications, it is not feasible for the debugger to interrupt the program's execution long enough for the developer to learn anything helpful about its behavior. If the program's correctness depends on its real-time behavior, delays introduced by a debugger might cause the program to change its behavior drastically, or perhaps fail, even when the code itself is correct. It is useful to be able to observe the program's behavior without interrupting it.

Using `gdb`'s `trace` and `collect` commands, you can specify locations in the program, called *tracepoints*, and arbitrary expressions to evaluate when those tracepoints are reached. Later, using the `tfind` command, you can examine the values those expressions had when the program hit the tracepoints. The expressions may also denote objects in memory--structures or arrays, for example--whose values `gdb` should record; while visiting a particular tracepoint, you may inspect those objects as if they were in memory at that moment. However, because `gdb` records these values without interacting with you, it can do so quickly and unobtrusively, hopefully not disturbing the program's behavior.

The tracepoint facility is currently available only for remote targets. Refer to Chapter 18 *Specifying a Debugging Target*. In addition, your remote target must know how to collect trace data. This functionality is implemented in the remote stub; however, none of the stubs distributed with `gdb` support tracepoints as of this writing.

This chapter describes the tracepoint commands and features.

12.1. Commands to Set Tracepoints

Before running such a *trace experiment*, an arbitrary number of tracepoints can be set. Like a breakpoint (refer to Section 7.1.1 *Setting breakpoints*), a tracepoint has a number assigned to it by `gdb`. Like with breakpoints, tracepoint numbers are successive integers starting from one. Many of the commands associated with tracepoints take the tracepoint number as their argument, to identify which tracepoint to work on.

For each tracepoint, you can specify, in advance, some arbitrary set of data that you want the target to collect in the trace buffer when it hits that tracepoint. The collected data can include registers, local variables, or global data. Later, you can use `gdb` commands to examine the values these data had at the time the tracepoint was hit.

This section describes commands to set tracepoints and associated conditions and actions.

12.1.1. Create and Delete Tracepoints

`trace`

The `trace` command is very similar to the `break` command. Its argument can be a source line, a function name, or an address in the target program. Refer to Section 7.1.1 *Setting breakpoints*. The `trace` command defines a tracepoint, which is a point in the target program where the debugger will briefly stop, collect some data, and then allow the program to continue. Setting a tracepoint or changing its commands doesn't take effect until the next `tstart` command; thus, you cannot change the tracepoint attributes once a trace experiment is running.

Here are some examples of using the `trace` command:

```
(gdb) trace foo.c:121 // a source file and line number
(gdb) trace +2 // 2 lines forward
```

```
(gdb) trace my_function // first source line of function
(gdb) trace *my_function // EXACT start address of function
(gdb) trace *0x2117c4 // an address
```

You can abbreviate `trace` as `tr`.

The convenience variable `$tpnum` records the tracepoint number of the most recently set tracepoint.

```
delete tracepoint [num]
```

Permanently delete one or more tracepoints. With no argument, the default is to delete all tracepoints.

Examples:

```
(gdb) delete trace 1 2 3 // remove three tracepoints
(gdb) delete trace // remove all tracepoints
```

You can abbreviate this command as `del tr`.

12.1.2. Enable and Disable Tracepoints

```
disable tracepoint [num]
```

Disable tracepoint `num`, or all tracepoints if no argument `num` is given. A disabled tracepoint will have no effect during the next trace experiment, but it is not forgotten. You can re-enable a disabled tracepoint using the `enable tracepoint` command.

```
enable tracepoint [num]
```

Enable tracepoint `num`, or all tracepoints. The enabled tracepoints will become effective the next time a trace experiment is run.

12.1.3. Tracepoint Passcounts

```
passcount [n [num]]
```

Set the *passcount* of a tracepoint. The passcount is a way to automatically stop a trace experiment. If a tracepoint's passcount is `n`, then the trace experiment will be automatically stopped on the `n`'th time that tracepoint is hit. If the tracepoint number `num` is not specified, the `passcount` command sets the passcount of the most recently defined tracepoint. If no passcount is given, the trace experiment will run until stopped explicitly by the user.

Examples:

```
(gdb) passcount 5 2 // Stop on the 5th execution of
                    // tracepoint 2
(gdb) passcount 12 // Stop on the 12th execution of the
                    // most recently defined tracepoint.
(gdb) trace foo
(gdb) pass 3
(gdb) trace bar
(gdb) pass 2
(gdb) trace baz
```

```
(gdb) pass 1          // Stop tracing when foo has been
                    // executed 3 times OR when bar has
                    // been executed 2 times
                    // OR when baz has been executed 1 time.
```

12.1.4. Tracepoint Action Lists

actions [num]

This command will prompt for a list of actions to be taken when the tracepoint is hit. If the tracepoint number `num` is not specified, this command sets the actions for the one that was most recently defined (so that you can define a tracepoint and then say `actions` without bothering about its number). You specify the actions themselves on the following lines, one action at a time, and terminate the actions list with a line containing just `end`. So far, the only defined actions are `collect` and `while-stepping`.

To remove all actions from a tracepoint, type `actions num` and follow it immediately with `end`.

```
(gdb) collect data // collect some data

(gdb) while-stepping 5 // single-step 5 times, collect data

(gdb) end          // signals the end of actions.
```

In the following example, the action list begins with `collect` commands indicating the things to be collected when the tracepoint is hit. Then, in order to single-step and collect additional data following the tracepoint, a `while-stepping` command is used, followed by the list of things to be collected while stepping. The `while-stepping` command is terminated by its own separate `end` command. Lastly, the action list is terminated by an `end` command.

```
(gdb) trace foo
(gdb) actions
Enter actions for tracepoint 1, one per line:
> collect bar,baz
> collect $regs
> while-stepping 12
  > collect $fp, $sp
  > end
end
```

collect *expr1*, *expr2*, ...

Collect values of the given expressions when the tracepoint is hit. This command accepts a comma-separated list of any valid expressions. In addition to global, static, or local variables, the following special arguments are supported:

```
$regs
    collect all registers

$args
    collect all function arguments
```

```
$locals
```

collect all local variables.

You can give several consecutive `collect` commands, each one with a single argument, or one `collect` command with several arguments separated by commas: the effect is the same.

The command `info scope` (`info scope`) is particularly useful for figuring out what data to collect.

```
while-stepping n
```

Perform `n` single-step traces after the tracepoint, collecting new data at each step. The `while-stepping` command is followed by the list of what to collect while stepping (followed by its own `end` command):

```
> while-stepping 12
> collect $regs, myglobal
> end
>
```

You may abbreviate `while-stepping` as `ws` or `stepping`.

12.1.5. Listing Tracepoints

```
info tracepoints [num]
```

Display information about the tracepoint `num`. If you don't specify a tracepoint number, displays information about all the tracepoints defined so far. For each tracepoint, the following information is shown:

- its number
- whether it is enabled or disabled
- its address
- its passcount as given by the `passcount n` command
- its step count as given by the `while-stepping n` command
- where in the source files is the tracepoint set
- its action list as given by the `actions` command

```
(gdb) info trace
Num Enb Address PassC StepC What
1 y 0x002117c4 0 0 <gdb_asm>
2 y 0x0020dc64 0 0 in g_test at g_test.c:1375
3 y 0x0020b1f4 0 0 in get_data at ../foo.c:41
(gdb)
```

This command can be abbreviated `info tp`.

12.1.6. Starting and Stopping Trace Experiment

`tstart`

This command takes no arguments. It starts the trace experiment, and begins collecting data. This has the side effect of discarding all the data collected in the trace buffer during the previous trace experiment.

`tstop`

This command takes no arguments. It ends the trace experiment, and stops collecting data.

Note: a trace experiment and data collection may stop automatically if any tracepoint's passcount is reached (refer to Section 12.1.3 *Tracepoint Passcounts*), or if the trace buffer becomes full.

`tstatus`

This command displays the status of the current trace data collection.

Here is an example of the commands we described so far:

```
(gdb) trace gdb_c_test
(gdb) actions
Enter actions for tracepoint #1, one per line.
> collect $regs,$locals,$args
> while-stepping 11
  > collect $regs
  > end
> end
(gdb) tstart
[time passes ...]
(gdb) tstop
```

12.2. Using the collected data

After the tracepoint experiment ends, you use `gdb` commands for examining the trace data. The basic idea is that each tracepoint collects a trace *snapshot* every time it is hit and another snapshot every time it single-steps. All these snapshots are consecutively numbered from zero and go into a buffer, and you can examine them later. The way you examine them is to *focus* on a specific trace snapshot. When the remote stub is focused on a trace snapshot, it will respond to all `gdb` requests for memory and registers by reading from the buffer which belongs to that snapshot, rather than from *real* memory or registers of the program being debugged. This means that *all* `gdb` commands (`print`, `info registers`, `backtrace`, etc.) will behave as if we were currently debugging the program state as it was when the tracepoint occurred. Any requests for data that are not in the buffer will fail.

12.2.1. `tfind n`

The basic command for selecting a trace snapshot from the buffer is `tfind n`, which finds trace snapshot number `n`, counting from zero. If no argument `n` is given, the next snapshot is selected.

Here are the various forms of using the `tfind` command.

`tfind start`

Find the first snapshot in the buffer. This is a synonym for `tfind 0` (since 0 is the number of the first snapshot).

`tfind none`

Stop debugging trace snapshots, resume *live* debugging.

`tfind end`

Same as `tfind none`.

`tfind`

No argument means find the next trace snapshot.

`tfind -`

Find the previous trace snapshot before the current one. This permits retracing earlier steps.

`tfind tracepoint num`

Find the next snapshot associated with tracepoint `num`. Search proceeds forward from the last examined trace snapshot. If no argument `num` is given, it means find the next snapshot collected for the same tracepoint as the current snapshot.

`tfind pc addr`

Find the next snapshot associated with the value `addr` of the program counter. Search proceeds forward from the last examined trace snapshot. If no argument `addr` is given, it means find the next snapshot with the same value of PC as the current snapshot.

`tfind outside addr1, addr2`

Find the next snapshot whose PC is outside the given range of addresses.

`tfind range addr1, addr2`

Find the next snapshot whose PC is between `addr1` and `addr2`.

`tfind line [file:]n`

Find the next snapshot associated with the source line `n`. If the optional argument `file` is given, refer to line `n` in that source file. Search proceeds forward from the last examined trace snapshot. If no argument `n` is given, it means find the next line other than the one currently being examined; thus saying `tfind line` repeatedly can appear to have the same effect as stepping from line to line in a *live* debugging session.

The default arguments for the `tfind` commands are specifically designed to make it easy to scan through the trace buffer. For instance, `tfind` with no argument selects the next trace snapshot, and `tfind -` with no argument selects the previous trace snapshot. So, by giving one `tfind` command, and then simply hitting [RET] repeatedly you can examine all the trace snapshots in order. Or, by saying `tfind -` and then hitting [RET] repeatedly you can examine the snapshots in reverse order. The `tfind line` command with no argument selects the snapshot for the next source line executed. The `tfind pc` command with no argument selects the next snapshot with the same program counter (PC) as the current frame. The `tfind tracepoint` command with no argument selects the next trace snapshot collected by the same tracepoint as the current one.

In addition to letting you scan through the trace buffer manually, these commands make it easy to construct `gdb` scripts that scan through the trace buffer and print out whatever collected data you are interested in. Thus, if we want to examine the PC, FP, and SP registers from each trace frame in the buffer, we can say this:

```
(gdb) tfind start
(gdb) while ($trace_frame != -1)
> printf "Frame %d, PC = %08X, SP = %08X, FP = %08X\n", \
    $trace_frame, $pc, $sp, $fp
> tfind
> end

Frame 0, PC = 0020DC64, SP = 0030BF3C, FP = 0030BF44
Frame 1, PC = 0020DC6C, SP = 0030BF38, FP = 0030BF44
Frame 2, PC = 0020DC70, SP = 0030BF34, FP = 0030BF44
Frame 3, PC = 0020DC74, SP = 0030BF30, FP = 0030BF44
Frame 4, PC = 0020DC78, SP = 0030BF2C, FP = 0030BF44
Frame 5, PC = 0020DC7C, SP = 0030BF28, FP = 0030BF44
Frame 6, PC = 0020DC80, SP = 0030BF24, FP = 0030BF44
Frame 7, PC = 0020DC84, SP = 0030BF20, FP = 0030BF44
Frame 8, PC = 0020DC88, SP = 0030BF1C, FP = 0030BF44
Frame 9, PC = 0020DC8E, SP = 0030BF18, FP = 0030BF44
Frame 10, PC = 00203F6C, SP = 0030BE3C, FP = 0030BF14
```

Or, if we want to examine the variable `X` at each source line in the buffer:

```
(gdb) tfind start
(gdb) while ($trace_frame != -1)
> printf "Frame %d, X == %d\n", $trace_frame, X
> tfind line
> end

Frame 0, X = 1
Frame 7, X = 2
Frame 13, X = 255
```

12.2.2. `tdump`

This command takes no arguments. It prints all the data collected at the current trace snapshot.

```
(gdb) trace 444
(gdb) actions
Enter actions for tracepoint #2, one per line:
> collect $regs, $locals, $args, gdb_long_test
> end

(gdb) tstart

(gdb) tfind line 444
#0 gdb_test (p1=0x11, p2=0x22, p3=0x33, p4=0x44, p5=0x55, p6=0x66)
at gdb_test.c:444
444     printf( "%s: arguments = 0x%X 0x%X 0x%X 0x%X 0x%X\n", )

(gdb) tdump
Data collected at tracepoint 2, trace frame 1:
d0      0xc4aa0085      -995491707
d1      0x18             24
d2      0x80             128
d3      0x33             51
d4      0x71aea3d         119204413
d5      0x22             34
```

```

d6          0xe0      224
d7          0x380035 3670069
a0          0x19e24a 1696330
a1          0x3000668          50333288
a2          0x100      256
a3          0x322000 3284992
a4          0x3000698          50333336
a5          0x1ad3cc 1758156
fp          0x30bf3c 0x30bf3c
sp          0x30bf34 0x30bf34
ps          0x0        0
pc          0x20b2c8 0x20b2c8
fpcontrol  0x0        0
fpstatus   0x0        0
fpiaddr    0x0        0
p = 0x20e5b4 "gdb-test"
p1 = (void *) 0x11
p2 = (void *) 0x22
p3 = (void *) 0x33
p4 = (void *) 0x44
p5 = (void *) 0x55
p6 = (void *) 0x66
gdb_long_test = 17 '\021'

(gdb)

```

12.2.3. save-tracepoints filename

This command saves all current tracepoint definitions together with their actions and passcounts, into a file `filename` suitable for use in a later debugging session. To read the saved tracepoint definitions, use the `source` command (refer to Section 22.3 *Command files*).

12.3. Convenience Variables for Tracepoints

```
(int) $trace_frame
```

The current trace snapshot (a.k.a. *frame*) number, or -1 if no snapshot is selected.

```
(int) $tracepoint
```

The tracepoint for the current trace snapshot.

```
(int) $trace_line
```

The line number for the current trace snapshot.

```
(char []) $trace_file
```

The source file for the current trace snapshot.

```
(char []) $trace_func
```

The name of the function containing `$tracepoint`.

Note: `$trace_file` is not suitable for use in `printf`, use `output` instead.

Here's a simple example of using these convenience variables for stepping through all the trace snapshots and printing some of their data.

```
(gdb) tfind start
```

```
(gdb) while $trace_frame != -1
```

```
> output $trace_file
```

```
> printf ", line %d (tracepoint #%d)\n", $trace_line, $tracepoint
```

```
> tfind
```

```
> end
```


except that the program variables and heap would share an address space with the main program and the overlay area.

An overlay loaded into instruction memory and ready for use is called a *mapped* overlay; its *mapped address* is its address in the instruction memory. An overlay not present (or only partially present) in instruction memory is called *unmapped*; its *load address* is its address in the larger memory. The mapped address is also called the *virtual memory address*, or *VMA*; the load address is also called the *load memory address*, or *LMA*.

Unfortunately, overlays are not a completely transparent way to adapt a program to limited instruction memory. They introduce a new set of global constraints you must keep in mind as you design your program:

- Before calling or returning to a function in an overlay, your program must make sure that overlay is actually mapped. Otherwise, the call or return will transfer control to the right address, but in the wrong overlay, and your program will probably crash.
- If the process of mapping an overlay is expensive on your system, you will need to choose your overlays carefully to minimize their effect on your program's performance.
- The executable file you load onto your system must contain each overlay's instructions, appearing at the overlay's load address, not its mapped address. However, each overlay's instructions must be relocated and its symbols defined as if the overlay were at its mapped address. You can use GNU linker scripts to specify different load and relocation addresses for pieces of your program; see .
- The procedure for loading executable files onto your system must be able to load their contents into the larger address space as well as the instruction and data spaces.

The overlay system described above is rather simple, and could be improved in many ways:

- If your system has suitable bank switch registers or memory management hardware, you could use those facilities to make an overlay's load area contents simply appear at their mapped address in instruction space. This would probably be faster than copying the overlay to its mapped area in the usual way.
- If your overlays are small enough, you could set aside more than one overlay area, and have more than one overlay mapped at a time.
- You can use overlays to manage data, as well as instructions. In general, data overlays are even less transparent to your design than code overlays: whereas code overlays only require care when you call or return to functions, data overlays require care every time you access the data. Also, if you change the contents of a data overlay, you must copy its contents back out to its load address before you can copy a different data overlay into the same mapped area.

13.2. Overlay Commands

To use `gdb`'s overlay support, each overlay in your program must correspond to a separate section of the executable file. The section's virtual memory address and load memory address must be the overlay's mapped and load addresses. Identifying overlays with sections allows `gdb` to determine the appropriate address of a function or variable, depending on whether the overlay is mapped or not.

`gdb`'s overlay commands all start with the word `overlay`; you can abbreviate this as `ov` or `ovly`. The commands are:

```
overlay off
```

Disable `gdb`'s overlay support. When overlay support is disabled, `gdb` assumes that all functions and variables are always present at their mapped addresses. By default, `gdb`'s overlay support is disabled.

overlay manual

Enable *manual* overlay debugging. In this mode, gdb relies on you to tell it which overlays are mapped, and which are not, using the `overlay map-overlay` and `overlay unmap-overlay` commands described below.

```
overlay map-overlay overlay
overlay map overlay
```

Tell gdb that `overlay` is now mapped; `overlay` must be the name of the object file section containing the overlay. When an overlay is mapped, gdb assumes it can find the overlay's functions and variables at their mapped addresses. gdb assumes that any other overlays whose mapped ranges overlap that of `overlay` are now unmapped.

```
overlay unmap-overlay overlay
overlay unmap overlay
```

Tell gdb that `overlay` is no longer mapped; `overlay` must be the name of the object file section containing the overlay. When an overlay is unmapped, gdb assumes it can find the overlay's functions and variables at their load addresses.

overlay auto

Enable *automatic* overlay debugging. In this mode, gdb consults a data structure the overlay manager maintains in the inferior to see which overlays are mapped. For details, (refer to Section 13.3 *Automatic Overlay Debugging*).

```
overlay load-target
overlay load
```

Re-read the overlay table from the inferior. Normally, gdb re-reads the table gdb automatically each time the inferior stops, so this command should only be necessary if you have changed the overlay mapping yourself using gdb. This command is only useful when using automatic overlay debugging.

```
overlay list-overlays
overlay list
```

Display a list of the overlays currently mapped, along with their mapped addresses, load addresses, and sizes.

Normally, when gdb prints a code address, it includes the name of the function the address falls in:

```
(gdb) print main
$3 = {int ()} 0x11a0 <main>
```

When overlay debugging is enabled, gdb recognizes code in unmapped overlays, and prints the names of unmapped functions with asterisks around them. For example, if `foo` is a function in an unmapped overlay, gdb prints it this way:

```
(gdb) overlay list
No sections are mapped.
(gdb) print foo
$5 = {int (int)} 0x100000 <*foo*>
```

When `foo`'s overlay is mapped, gdb prints the function's name normally:

```
(gdb) overlay list
Section .ov.foo.text, loaded at 0x100000 - 0x100034,
        mapped at 0x1016 - 0x104a
(gdb) print foo
$6 = {int (int)} 0x1016 <foo>
```

When overlay debugging is enabled, `gdb` can find the correct address for functions and variables in an overlay, whether or not the overlay is mapped. This allows most `gdb` commands, like `break` and `disassemble`, to work normally, even on unmapped code. However, `gdb`'s breakpoint support has some limitations:

- You can set breakpoints in functions in unmapped overlays, as long as `gdb` can write to the overlay at its load address.
- `gdb` can not set hardware or simulator-based breakpoints in unmapped overlays. However, if you set a breakpoint at the end of your overlay manager (and tell `gdb` which overlays are now mapped, if you are using manual overlay management), `gdb` will re-set its breakpoints properly.

13.3. Automatic Overlay Debugging

`gdb` can automatically track which overlays are mapped and which are not, given some simple co-operation from the overlay manager in the inferior. If you enable automatic overlay debugging with the `overlay auto` command (refer to Section 13.2 *Overlay Commands*), `gdb` looks in the inferior's memory for certain variables describing the current state of the overlays.

Here are the variables your overlay manager must define to support `gdb`'s automatic overlay debugging:

`_ovly_table`:

This variable must be an array of the following structures:

```
struct
{
    /* The overlay's mapped address. */
    unsigned long vma;

    /* The size of the overlay, in bytes. */
    unsigned long size;

    /* The overlay's load address. */
    unsigned long lma;

    /* Non-zero if the overlay is currently mapped;
       zero otherwise. */
    unsigned long mapped;
}
```

`_novlys`:

This variable must be a four-byte signed integer, holding the total number of elements in `_ovly_table`.

To decide whether a particular overlay is mapped or not, `gdb` looks for an entry in `_ovly_table` whose `vma` and `lma` members equal the VMA and LMA of the overlay's section in the executable file. When `gdb` finds a matching entry, it consults the entry's `mapped` member to determine whether the overlay is currently mapped.

In addition, your overlay manager may define a function called `_ovly_debug_event`. If this function is defined, `gdb` will silently set a breakpoint there. If the overlay manager then calls this function whenever it has changed the overlay table, this will enable `gdb` to accurately keep track of which overlays are in program memory, and update any breakpoints that may be set in overlays. This will allow breakpoints to work even if the overlays are kept in ROM or other non-writable memory while they are not being executed.

13.4. Overlay Sample Program

When linking a program which uses overlays, you must place the overlays at their load addresses, while relocating them to run at their mapped addresses. To do this, you must write a linker script (`.`). Unfortunately, since linker scripts are specific to a particular host system, target architecture, and target memory layout, this manual cannot provide portable sample code demonstrating `gdb`'s overlay support.

However, the `gdb` source distribution does contain an overlaid program, with linker scripts for a few systems, as part of its test suite. The program consists of the following files from `gdb/testsuite/gdb.base`:

`overlays.c`

The main program file.

`ovlymgr.c`

A simple overlay manager, used by `overlays.c`.

`foo.c`

`bar.c`

`baz.c`

`grbx.c`

Overlay modules, loaded and used by `overlays.c`.

`d10v.ld`

`m32r.ld`

Linker scripts for linking the test program on the `d10v-elf` and `m32r-elf` targets.

You can build the test program using the `d10v-elf` GCC cross-compiler like this:

```
$ d10v-elf-gcc -g -c overlays.c
$ d10v-elf-gcc -g -c ovlymgr.c
$ d10v-elf-gcc -g -c foo.c
$ d10v-elf-gcc -g -c bar.c
$ d10v-elf-gcc -g -c baz.c
$ d10v-elf-gcc -g -c grbx.c
$ d10v-elf-gcc -g overlays.o ovlymgr.o foo.o bar.o \
    baz.o grbx.o -Wl,-Td10v.ld -o overlays
```

The build process is identical for any other architecture, except that you must substitute the appropriate compiler and linker script for the target system for `d10v-elf-gcc` and `d10v.ld`.

Using gdb with Different Languages

Although programming languages generally have common aspects, they are rarely expressed in the same manner. For instance, in ANSI C, dereferencing a pointer `p` is accomplished by `*p`, but in Modula-2, it is accomplished by `p^`. Values can also be represented (and displayed) differently. Hex numbers in C appear as `0x1ae`, while in Modula-2 they appear as `1AEH`.

Language-specific information is built into `gdb` for some languages, allowing you to express operations like the above in your program's native language, and allowing `gdb` to output values in a manner consistent with the syntax of your program's native language. The language you use to build expressions is called the *working language*.

14.1. Switching between source languages

There are two ways to control the working language--either have `gdb` set it automatically, or select it manually yourself. You can use the `set language` command for either purpose. On startup, `gdb` defaults to setting the language automatically. The working language is used to determine how expressions you type are interpreted, how values are printed, etc.

In addition to the working language, every source file that `gdb` knows about has its own working language. For some object file formats, the compiler might indicate which language a particular source file is in. However, most of the time `gdb` infers the language from the name of the file. The language of a source file controls whether C++ names are demangled--this way `backtrace` can show each frame appropriately for its own language. There is no way to set the language of a source file from within `gdb`, but you can set the language associated with a filename extension. Refer to Section 14.2 *Displaying the language*.

This is most commonly a problem when you use a program, such as `cfront` or `f2c`, that generates C but is written in another language. In that case, make the program use `#line` directives in its C output; that way `gdb` will know the correct language of the source code of the original program, and will display that source code, not the generated C code.

14.1.1. List of filename extensions and languages

If a source file name ends in one of the following extensions, then `gdb` infers that its language is the one indicated.

```
.c
    C source file

.C
.cc
.cp
.cpp
.cxx
.c++
    C++ source file

.m
    Objective-C source file
```

`.f`

`.F`

Fortran source file

`.mod`

Modula-2 source file

`.s`

`.S`

Assembler source file. This actually behaves almost like C, but gdb does not skip over function prologues when stepping.

In addition, you may set the language associated with a filename extension. Refer to Section 14.2 *Displaying the language*.

14.1.2. Setting the working language

If you allow gdb to set the language automatically, expressions are interpreted the same way in your debugging session and your program.

If you wish, you may set the language manually. To do this, issue the command `set language lang`, where `lang` is the name of a language, such as `c` or `modula-2`. For a list of the supported languages, type `set language`.

Setting the language manually prevents gdb from updating the working language automatically. This can lead to confusion if you try to debug a program when the working language is not the same as the source language, when an expression is acceptable to both languages--but means different things. For instance, if the current source file were written in C, and gdb was parsing Modula-2, a command such as:

```
print a = b + c
```

might not have the effect you intended. In C, this means to add `b` and `c` and place the result in `a`. The result printed would be the value of `a`. In Modula-2, this means to compare `a` to the result of `b+c`, yielding a `BOOLEAN` value.

14.1.3. Having gdb infer the source language

To have gdb set the working language automatically, use `set language local` or `set language auto`. gdb then infers the working language. That is, when your program stops in a frame (usually by encountering a breakpoint), gdb sets the working language to the language recorded for the function in that frame. If the language for a frame is unknown (that is, if the function or block corresponding to the frame was defined in a source file that does not have a recognized extension), the current working language is not changed, and gdb issues a warning.

This may not seem necessary for most programs, which are written entirely in one source language. However, program modules and libraries written in one source language can be used by a main program written in a different source language. Using `set language auto` in this case frees you from having to set the working language manually.

14.2. Displaying the language

The following commands help you find out which language is the working language, and also what language source files were written in.

```
show language
```

Display the current working language. This is the language you can use with commands such as `print` to build and compute expressions that may involve variables in your program.

```
info frame
```

Display the source language for this frame. This language becomes the working language if you use an identifier from this frame. Refer to Section 8.4 *Information about a frame*, to identify the other information listed here.

```
info source
```

Display the source language of this source file. Refer to Chapter 15 *Examining the Symbol Table*, to identify the other information listed here.

In unusual circumstances, you may have source files with extensions not in the standard list. You can then set the extension associated with a language explicitly:

```
set extension-language .ext language
```

Set source files with extension `.ext` to be assumed to be in the source language `language`.

```
info extensions
```

List all the filename extensions and the associated languages.

14.3. Type and range checking

Warning: In this release, the gdb commands for type and range checking are included, but they do not yet have any effect. This section documents the intended facilities.

Some languages are designed to guard you against making seemingly common errors through a series of compile- and run-time checks. These include checking the type of arguments to functions and operators, and making sure mathematical overflows are caught at run time. Checks such as these help to ensure a program's correctness once it has been compiled by eliminating type mismatches, and providing active checks for range errors when your program is running.

gdb can check for conditions like the above if you wish. Although gdb does not check the statements in your program, it can check expressions entered directly into gdb for evaluation via the `print` command, for example. As with the working language, gdb can also decide whether or not to check automatically based on your program's source language. Refer to Section 14.4 *Supported languages*, for the default settings of supported languages.

14.3.1. An overview of type checking

Some languages, such as Modula-2, are strongly typed, meaning that the arguments to operators and functions have to be of the correct type, otherwise an error occurs. These checks prevent type mismatch errors from ever causing any run-time problems. For example,

```
1 + 2 => 3
```

```
but      error--> 1 + 2.3
```

The second example fails because the `CARDINAL 1` is not type-compatible with the `REAL 2.3`.

For the expressions you use in gdb commands, you can tell the gdb type checker to skip checking; to treat any mismatches as errors and abandon the expression; or to only issue warnings when type mismatches occur, but evaluate the expression anyway. When you choose the last of these, gdb evaluates expressions like the second example above, but also issues a warning.

Even if you turn type checking off, there may be other reasons related to type that prevent gdb from evaluating an expression. For instance, gdb does not know how to add an `int` and a `struct foo`. These particular type errors have nothing to do with the language in use, and usually arise from expressions, such as the one described above, which make little sense to evaluate anyway.

Each language defines to what degree it is strict about type. For instance, both Modula-2 and C require the arguments to arithmetical operators to be numbers. In C, enumerated types and pointers can be represented as numbers, so that they are valid arguments to mathematical operators. Refer to Section 14.4 *Supported languages*, for further details on specific languages.

`gdb` provides some additional commands for controlling the type checker:

```
set check type auto
```

Set type checking on or off based on the current working language. Refer to Section 14.4 *Supported languages*, for the default settings for each language.

```
set check type on
set check type off
```

Set type checking on or off, overriding the default setting for the current working language. Issue a warning if the setting does not match the language default. If any type mismatches occur in evaluating an expression while type checking is on, gdb prints a message and aborts evaluation of the expression.

```
set check type warn
```

Cause the type checker to issue warnings, but to always attempt to evaluate the expression. Evaluating the expression may still be impossible for other reasons. For example, gdb cannot add numbers and structures.

```
show type
```

Show the current setting of the type checker, and whether or not gdb is setting it automatically.

14.3.2. An overview of range checking

In some languages (such as Modula-2), it is an error to exceed the bounds of a type; this is enforced with run-time checks. Such range checking is meant to ensure program correctness by making sure computations do not overflow, or indices on an array element access do not exceed the bounds of the array.

For expressions you use in gdb commands, you can tell gdb to treat range errors in one of three ways: ignore them, always treat them as errors and abandon the expression, or issue warnings but evaluate the expression anyway.

A range error can result from numerical overflow, from exceeding an array index bound, or when you type a constant that is not a member of any type. Some languages, however, do not treat overflows as

an error. In many implementations of C, mathematical overflow causes the result to "wrap around" to lower values--for example, if `m` is the largest integer value, and `s` is the smallest, then

```
m + 1 => s
```

This, too, is specific to individual languages, and in some cases specific to individual compilers or machines. Refer to Section 14.4 *Supported languages*, for further details on specific languages.

`gdb` provides some additional commands for controlling the range checker:

```
set check range auto
```

Set range checking on or off based on the current working language. Refer to Section 14.4 *Supported languages*, for the default settings for each language.

```
set check range on
set check range off
```

Set range checking on or off, overriding the default setting for the current working language. A warning is issued if the setting does not match the language default. If a range error occurs and range checking is on, then a message is printed and evaluation of the expression is aborted.

```
set check range warn
```

Output messages when the `gdb` range checker detects a range error, but attempt to evaluate the expression anyway. Evaluating the expression may still be impossible for other reasons, such as accessing memory that the process does not own (a typical example from many Unix systems).

```
show range
```

Show the current setting of the range checker, and whether or not it is being set automatically by `gdb`.

14.4. Supported languages

`gdb` supports C, C++, Objective-C, Fortran, Java, assembly, and Modula-2. Some `gdb` features may be used in expressions regardless of the language you use: the `gdb @` and `::` operators, and the `{type}addr` construct (refer to Section 10.1 *Expressions*) can be used with the constructs of any supported language.

The following sections detail to what degree each source language is supported by `gdb`. These sections are not meant to be language tutorials or references, but serve only as a reference guide to what the `gdb` expression parser accepts, and what input and output formats should look like for different languages. There are many good books written on each of these languages; please look to these for a language reference or tutorial.

14.4.1. C and C++

Since C and C++ are so closely related, many features of `gdb` apply to both languages. Whenever this is the case, we discuss those languages together.

The C++ debugging facilities are jointly implemented by the C++ compiler and `gdb`. Therefore, to debug your C++ code effectively, you must compile your C++ programs with a supported C++ compiler, such as `gnu g++`, or the HP ANSI C++ compiler (`aCC`).

For best results when using gnu C++, use the DWARF 2 debugging format; if it doesn't work on your system, try the stabs+ debugging format. You can select those formats explicitly with the g++ command-line options `-gdwarf-2` and `-gstabs+`.

14.4.1.1. C and C++ operators

Operators must be defined on values of specific types. For instance, `+` is defined on numbers, but not on structures. Operators are often defined on groups of types.

For the purposes of C and C++, the following definitions hold:

- *Integral types* include `int` with any of its storage-class specifiers; `char`; `enum`; and, for C++, `bool`.
- *Floating-point types* include `float`, `double`, and `long double` (if supported by the target platform).
- *Pointer types* include all types defined as `(type *)`.
- *Scalar types* include all of the above.

The following operators are supported. They are listed here in order of increasing precedence:

,	The comma or sequencing operator. Expressions in a comma-separated list are evaluated from left to right, with the result of the entire expression being the last expression evaluated.
=	Assignment. The value of an assignment expression is the value assigned. Defined on scalar types.
op=	Used in an expression of the form <code>a op= b</code> , and translated to <code>a = a op b</code> . <code>op=</code> and <code>=</code> have the same precedence. <code>op</code> is any one of the operators <code> </code> , <code>^</code> , <code>&</code> , <code><<</code> , <code>>></code> , <code>+</code> , <code>-</code> , <code>*</code> , <code>/</code> , <code>%</code> .
?:	The ternary operator. <code>a ? b : c</code> can be thought of as: if <code>a</code> then <code>b</code> else <code>c</code> . <code>a</code> should be of an integral type.
	Logical or. Defined on integral types.
&&	Logical and. Defined on integral types.
	Bitwise or. Defined on integral types.
^	Bitwise exclusive-or. Defined on integral types.
&	Bitwise and. Defined on integral types.

==, !=

Equality and inequality. Defined on scalar types. The value of these expressions is 0 for false and non-zero for true.

<, >, <=, >=

Less than, greater than, less than or equal, greater than or equal. Defined on scalar types. The value of these expressions is 0 for false and non-zero for true.

<<, >>

left shift, and right shift. Defined on integral types.

@

The gdb "artificial array" operator (refer to Section 10.1 *Expressions*).

+, -

Addition and subtraction. Defined on integral types, floating-point types and pointer types.

*, /, %

Multiplication, division, and modulus. Multiplication and division are defined on integral and floating-point types. Modulus is defined on integral types.

++, -

Increment and decrement. When appearing before a variable, the operation is performed before the variable is used in an expression; when appearing after it, the variable's value is used before the operation takes place.

*

Pointer dereferencing. Defined on pointer types. Same precedence as ++.

&

Address operator. Defined on variables. Same precedence as ++.

For debugging C++, gdb implements a use of & beyond what is allowed in the C++ language itself: you can use `&(&ref)` (or, if you prefer, simply `&&ref`) to examine the address where a C++ reference variable (declared with `&ref`) is stored.

-

Negative. Defined on integral and floating-point types. Same precedence as ++.

!

Logical negation. Defined on integral types. Same precedence as ++.

~

Bitwise complement operator. Defined on integral types. Same precedence as ++.

., ->

Structure member, and pointer-to-structure member. For convenience, gdb regards the two as equivalent, choosing whether to dereference a pointer based on the stored type information. Defined on `struct` and `union` data.

.*, ->*

Dereferences of pointers to members.

[]

Array indexing. `a[i]` is defined as `*(a+i)`. Same precedence as `->`.

()

Function parameter list. Same precedence as `->`.

::

C++ scope resolution operator. Defined on `struct`, `union`, and `class` types.

:::

Doubled colons also represent the gdb scope operator (refer to Section 10.1 *Expressions*). Same precedence as `::`, above.

If an operator is redefined in the user code, gdb usually attempts to invoke the redefined version instead of using the operator's predefined meaning.

14.4.1.2. C and C++ constants

gdb allows you to express the constants of C and C++ in the following ways:

- Integer constants are a sequence of digits. Octal constants are specified by a leading 0 (that is, zero), and hexadecimal constants by a leading 0x or 0X. Constants may also end with a letter l, specifying that the constant should be treated as a long value.
- Floating point constants are a sequence of digits, followed by a decimal point, followed by a sequence of digits, and optionally followed by an exponent. An exponent is of the form: `e[+|-]nnn`, where `nnn` is another sequence of digits. The + is optional for positive exponents. A floating-point constant may also end with a letter f or F, specifying that the constant should be treated as being of the float (as opposed to the default double) type; or with a letter l or L, which specifies a long double constant.
- Enumerated constants consist of enumerated identifiers, or their integral equivalents.
- Character constants are a single character surrounded by single quotes ('), or a number--the ordinal value of the corresponding character (usually its ascii value). Within quotes, the single character may be represented by a letter or by *escape sequences*, which are of the form `\nnn`, where `nnn` is the octal representation of the character's ordinal value; or of the form `\x`, where `x` is a predefined special character--for example, `\n` for newline.
- String constants are a sequence of character constants surrounded by double quotes ("). Any valid character constant (as described above) may appear. Double quotes within the string must be preceded by a backslash, so for instance `"a\"b'c"` is a string of five characters.
- Pointer constants are an integral value. You can also write pointers to constants using the C operator `&`.
- Array constants are comma-separated lists surrounded by braces { and }; for example, `{1, 2, 3}` is a three-element array of integers, `{{1, 2}, {3, 4}, {5, 6}}` is a three-by-two array, and `{&"hi", &"there", &"fred"}` is a three-element array of pointers.

14.4.1.3. C++expressions

gdb expression handling can interpret most C++ expressions.

Warning: gdb can only debug C++ code if you use the proper compiler and the proper debug format. Currently, gdb works best when debugging C++ code that is compiled with gcc 2.95.3 or with gcc 3.1 or newer, using the options `-gdwarf-2` or `-gstabs+`. DWARF 2 is preferred over `stabs+`. Most configurations of gcc emit either DWARF 2 or `stabs+` as their default debug format, so you usually don't need to specify a debug format explicitly. Other compilers and/or debug formats are likely to work badly or not at all when using gdb to debug C++ code.

1. Member function calls are allowed; you can use expressions like

```
count = aml->GetOriginal(x, y)
```

2. While a member function is active (in the selected stack frame), your expressions have the same namespace available as the member function; that is, gdb allows implicit references to the class instance pointer `this` following the same rules as C++.
3. You can call overloaded functions; gdb resolves the function call to the right definition, with some restrictions. gdb does not perform overload resolution involving user-defined type conversions, calls to constructors, or instantiations of templates that do not exist in the program. It also cannot handle ellipsis argument lists or default arguments.

It does perform integral conversions and promotions, floating-point promotions, arithmetic conversions, pointer conversions, conversions of class objects to base classes, and standard conversions such as those of functions or arrays to pointers; it requires an exact match on the number of function arguments.

Overload resolution is always performed, unless you have specified `set overload-resolution off`. Refer to Section 14.4.1.7 *gdb features for C++*.

You must specify `set overload-resolution off` in order to use an explicit function signature to call an overloaded function, as in

```
p 'foo(char,int)'('x', 13)
```

The gdb command-completion facility can simplify this; (refer to Section 5.2 *Command completion*).

4. gdb understands variables declared as C++ references; you can use them in expressions just as you do in C++ source--they are automatically dereferenced.

In the parameter list shown when gdb displays a frame, the values of reference variables are not displayed (unlike other variables); this avoids clutter, since references are often used for large structures. The *address* of a reference variable is always shown, unless you have specified `set print address off`.

5. gdb supports the C++ name resolution operator `::`--your expressions can use it just as expressions in your program do. Since one scope may be defined in another, you can use `::` repeatedly if necessary, for example in an expression like `scope1::scope2::name`. gdb also allows resolving name scope by reference to source files, in both C and C++ debugging (refer to Section 10.2 *Program variables*).

In addition, when used with HP's C++ compiler, gdb supports calling virtual functions correctly, printing out virtual bases of objects, calling functions in a base subobject, casting objects, and invoking user-defined operators.

14.4.1.4. C and C++ defaults

If you allow `gdb` to set type and range checking automatically, they both default to `off` whenever the working language changes to C or C++. This happens regardless of whether you or `gdb` selects the working language.

If you allow `gdb` to set the language automatically, it recognizes source files whose names end with `.c`, `.C`, or `.cc`, etc, and when `gdb` enters code compiled from one of these files, it sets the working language to C or C++. Refer to Section 14.1.3 *Having gdb infer the source language*, for further details.

14.4.1.5. C and C++ type and range checks

By default, when `gdb` parses C or C++ expressions, type checking is not used. However, if you turn type checking on, `gdb` considers two variables type equivalent if:

- The two variables are structured and have the same structure, union, or enumerated tag.
- The two variables have the same type name, or types that have been declared equivalent through `typedef`.

Range checking, if turned on, is done on mathematical operations. Array indices are not checked, since they are often used to index a pointer that is not itself an array.

14.4.1.6. gdb and C

The `set print union` and `show print union` commands apply to the `union` type. When set to `on`, any `union` that is inside a `struct` or `class` is also printed. Otherwise, it appears as `{...}`.

The `@` operator aids in the debugging of dynamic arrays, formed with pointers and a memory allocation function. Refer to Section 10.1 *Expressions*.

14.4.1.7. gdb features for C++

Some `gdb` commands are particularly useful with C++, and some are designed specifically for use with C++. Here is a summary:

`breakpoint menus`

When you want a breakpoint in a function whose name is overloaded, `gdb breakpoint menus` help you specify which function definition you want. Refer to Section 7.1.8 *Breakpoint menus*.

`rbreak regex`

Setting breakpoints using regular expressions is helpful for setting breakpoints on overloaded functions that are not members of any special classes. Refer to Section 7.1.1 *Setting breakpoints*.

`catch throw`

`catch catch`

Debug C++ exception handling using these commands. Refer to Section 7.1.3 *Setting catchpoints*.

```
ptype typename
```

Print inheritance relationships as well as other information for type `typename`. Refer to Chapter 15 *Examining the Symbol Table*.

```
set print demangle
show print demangle
set print asm-demangle
show print asm-demangle
```

Control whether C++ symbols display in their source form, both when displaying code as C++ source and when displaying disassemblies. Refer to Section 10.7 *Print settings*.

```
set print object
show print object
```

Choose whether to print derived (actual) or declared types of objects. Refer to Section 10.7 *Print settings*.

```
set print vtbl
show print vtbl
```

Control the format for printing virtual function tables. Refer to Section 10.7 *Print settings*. (The `vtbl` commands do not work on programs compiled with the HP ANSI C++ compiler (`acc`).

```
set overload-resolution on
```

Enable overload resolution for C++ expression evaluation. The default is `on`. For overloaded functions, gdb evaluates the arguments and searches for a function whose signature matches the argument types, using the standard C++ conversion rules (refer to Section 14.4.1.3 *C++ expressions*, for details). If it cannot find a match, it emits a message.

```
set overload-resolution off
```

Disable overload resolution for C++ expression evaluation. For overloaded functions that are not class member functions, gdb chooses the first function of the specified name that it finds in the symbol table, whether or not its arguments are of the correct type. For overloaded functions that are class member functions, gdb searches for a function whose signature *exactly* matches the argument types.

```
Overloaded symbol names
```

You can specify a particular definition of an overloaded symbol, using the same notation that is used to declare such symbols in C++: `type symbol(types)` rather than just `symbol`. You can also use the gdb command-line word completion facilities to list the available choices, or to finish the type list for you. Refer to Section 5.2 *Command completion*, for details on how to do this.

14.4.2. Objective-C

This section provides information about some commands and command options that are useful for debugging Objective-C code.

14.4.2.1. Method Names in Commands

The following commands have been extended to accept Objective-C method names as line specifications:

- `clear`
- `break`
- `info line`
- `jump`
- `list`

A fully qualified Objective-C method name is specified as

```
-[Class methodName]
```

where the minus sign is used to indicate an instance method and a plus sign (not shown) is used to indicate a class method. The class name `Class` and method name `methoName` are enclosed in brackets, similar to the way messages are specified in Objective-C source code. For example, to set a breakpoint at the `create` instance method of class `Fruit` in the program currently being debugged, enter:

```
break -[Fruit create]
```

To list ten program lines around the `initialize` class method, enter:

```
list +[NSText initialize]
```

In the current version of GDB, the plus or minus sign is required. In future versions of GDB, the plus or minus sign will be optional, but you can use it to narrow the search. It is also possible to specify just a method name:

```
break create
```

You must specify the complete method name, including any colons. If your program's source files contain more than one `create` method, you'll be presented with a numbered list of classes that implement that method. Indicate your choice by number, or type 0 to exit if none apply.

As another example, to clear a breakpoint established at the `makeKeyAndOrderFront:` method of the `NSWindow` class, enter:

```
clear -[NSWindow makeKeyAndOrderFront:]
```

14.4.2.2. The Print Command With Objective-C

The print command has also been extended to accept methods. For example:

```
print -[object hash]
```

will tell gdb to send the `-hash` message to object and print the result. Also an additional command has been added, `print-object` or `po` for short, which is meant to print the description of an object. However, this command may only work with certain Objective-C libraries that have a particular hook function, called `_NSPrintForDebugger` defined.

14.4.3. Modula-2

The extensions made to gdb to support Modula-2 only support output from the gnu Modula-2 compiler (which is currently being developed). Other Modula-2 compilers are not currently supported, and attempting to debug executables produced by them is most likely to give an error as gdb reads in the executable's symbol table.

14.4.3.1. Operators

Operators must be defined on values of specific types. For instance, `+` is defined on numbers, but not on structures. Operators are often defined on groups of types. For the purposes of Modula-2, the following definitions hold:

- *Integral types* consist of `INTEGER`, `CARDINAL`, and their subranges.
- *Character types* consist of `CHAR` and its subranges.
- *Floating-point types* consist of `REAL`.
- *Pointer types* consist of anything declared as `POINTER TO type`.
- *Scalar types* consist of all of the above.
- *Set types* consist of `SET` and `BITSET` types.
- *Boolean types* consist of `BOOLEAN`.

The following operators are supported, and appear in order of increasing precedence:

<code>,</code>	Function argument or array index separator.
<code>:=</code>	Assignment. The value of <code>var := value</code> is <code>value</code> .
<code><</code> , <code>></code>	Less than, greater than on integral, floating-point, or enumerated types.
<code><=</code> , <code>>=</code>	Less than or equal to, greater than or equal to on integral, floating-point and enumerated types, or set inclusion on set types. Same precedence as <code><</code> .
<code>=</code> , <code><></code> , <code>#</code>	Equality and two ways of expressing inequality, valid on scalar types. Same precedence as <code><</code> . In gdb scripts, only <code><></code> is available for inequality, since <code>#</code> conflicts with the script comment character.
<code>IN</code>	Set membership. Defined on set types and the types of their members. Same precedence as <code><</code> .

OR

Boolean disjunction. Defined on boolean types.

AND, &

Boolean conjunction. Defined on boolean types.

@

The gdb "artificial array" operator (refer to Section 10.1 *Expressions*).

+, -

Addition and subtraction on integral and floating-point types, or union and difference on set types.

*

Multiplication on integral and floating-point types, or set intersection on set types.

/

Division on floating-point types, or symmetric set difference on set types. Same precedence as *.

DIV, MOD

Integer division and remainder. Defined on integral types. Same precedence as *.

-

Negative. Defined on INTEGER and REAL data.

^

Pointer dereferencing. Defined on pointer types.

NOT

Boolean negation. Defined on boolean types. Same precedence as ^.

.

RECORD field selector. Defined on RECORD data. Same precedence as ^.

[]

Array indexing. Defined on ARRAY data. Same precedence as ^.

()

Procedure argument list. Defined on PROCEDURE objects. Same precedence as ^.

::, .

{No value for ‘<listitem>GDBN’} and Modula-2 scope operators.

Warning: Sets and their operations are not yet supported, so gdb treats the use of the operator IN, or the use of operators +, -, *, /, =, <>, #, <=, and >= on sets as an error.

14.4.3.2. Built-in functions and procedures

Modula-2 also makes available several built-in procedures and functions. In describing these, the following metavariables are used:

a

represents an `ARRAY` variable.

c

represents a `CHAR` constant or variable.

i

represents a variable or constant of integral type.

m

represents an identifier that belongs to a set. Generally used in the same function with the metavariable `s`. The type of `s` should be `SET OF mtype` (where `mtype` is the type of `m`).

n

represents a variable or constant of integral or floating-point type.

r

represents a variable or constant of floating-point type.

t

represents a type.

v

represents a variable.

x

represents a variable or constant of one of many types. See the explanation of the function for details.

All Modula-2 built-in procedures also return a result, described below.

`ABS (n)`

Returns the absolute value of `n`.

`CAP (c)`

If `c` is a lower case letter, it returns its upper case equivalent, otherwise it returns its argument.

`CHR (i)`

Returns the character whose ordinal value is `i`.

`DEC (v)`

Decrements the value in the variable `v` by one. Returns the new value.

`DEC (v, i)`

Decrements the value in the variable `v` by `i`. Returns the new value.

EXCL (*m*, *s*)

Removes the element *m* from the set *s*. Returns the new set.

FLOAT (*i*)

Returns the floating point equivalent of the integer *i*.

HIGH (*a*)

Returns the index of the last member of *a*.

INC (*v*)

Increments the value in the variable *v* by one. Returns the new value.

INC (*v*, *i*)

Increments the value in the variable *v* by *i*. Returns the new value.

INCL (*m*, *s*)

Adds the element *m* to the set *s* if it is not already there. Returns the new set.

MAX (*t*)

Returns the maximum value of the type *t*.

MIN (*t*)

Returns the minimum value of the type *t*.

ODD (*i*)

Returns boolean TRUE if *i* is an odd number.

ORD (*x*)

Returns the ordinal value of its argument. For example, the ordinal value of a character is its ascii value (on machines supporting the ascii character set). *x* must be of an ordered type, which include integral, character and enumerated types.

SIZE (*x*)

Returns the size of its argument. *x* can be a variable or a type.

TRUNC (*r*)

Returns the integral part of *r*.

VAL (*t*, *i*)

Returns the member of the type *t* whose ordinal value is *i*.

Warning: Sets and their operations are not yet supported, so gdb treats the use of procedures INCL and EXCL as an error.

14.4.3.3. Constants

`gdb` allows you to express the constants of Modula-2 in the following ways:

- Integer constants are simply a sequence of digits. When used in an expression, a constant is interpreted to be type-compatible with the rest of the expression. Hexadecimal integers are specified by a trailing `H`, and octal integers by a trailing `O`.
- Floating point constants appear as a sequence of digits, followed by a decimal point and another sequence of digits. An optional exponent can then be specified, in the form `E [+|-] nnn`, where `[+|-] nnn` is the desired exponent. All of the digits of the floating point constant must be valid decimal (base 10) digits.
- Character constants consist of a single character enclosed by a pair of like quotes, either single (`'`) or double (`"`). They may also be expressed by their ordinal value (their `ascii` value, usually) followed by a `C`.
- String constants consist of a sequence of characters enclosed by a pair of like quotes, either single (`'`) or double (`"`). Escape sequences in the style of `C` are also allowed. Refer to Section 14.4.1.2 *C and C++ constants*, for a brief explanation of escape sequences.
- Enumerated constants consist of an enumerated identifier.
- Boolean constants consist of the identifiers `TRUE` and `FALSE`.
- Pointer constants consist of integral values only.
- Set constants are not yet supported.

14.4.3.4. Modula-2 defaults

If type and range checking are set automatically by `gdb`, they both default to `on` whenever the working language changes to Modula-2. This happens regardless of whether you or `gdb` selected the working language.

If you allow `gdb` to set the language automatically, then entering code compiled from a file whose name ends with `.mod` sets the working language to Modula-2. Refer to Section 14.1.3 *Having gdb infer the source language*, for further details.

14.4.3.5. Deviations from standard Modula-2

A few changes have been made to make Modula-2 programs easier to debug. This is done primarily via loosening its type strictness:

- Unlike in standard Modula-2, pointer constants can be formed by integers. This allows you to modify pointer variables during debugging. (In standard Modula-2, the actual address contained in a pointer variable is hidden from you; it can only be modified through direct assignment to another pointer variable or expression that returned a pointer.)
- `C` escape sequences can be used in strings and characters to represent non-printable characters. `gdb` prints out strings with these escape sequences embedded. Single non-printable characters are printed using the `CHR (nnn)` format.
- The assignment operator (`:=`) returns the value of its right-hand argument.
- All built-in procedures both modify *and* return their argument.

14.4.3.6. Modula-2 type and range checks

Warning: in this release, gdb does not yet perform type or range checking.

gdb considers two Modula-2 variables type equivalent if:

- They are of types that have been declared equivalent via a `TYPE t1 = t2` statement
- They have been declared on the same line. (Note: This is true of the gnu Modula-2 compiler, but it may not be true of other compilers.)

As long as type checking is enabled, any attempt to combine variables whose types are not equivalent is an error.

Range checking is done on all mathematical operations, assignment, array index bounds, and all built-in functions and procedures.

14.4.3.7. The scope operators `::` and `.`

There are a few subtle differences between the Modula-2 scope operator (`.`) and the gdb scope operator (`::`). The two have similar syntax:

```
module . id
scope :: id
```

where `scope` is the name of a module or a procedure, `module` the name of a module, and `id` is any declared identifier within your program, except another module.

Using the `::` operator makes gdb search the scope specified by `scope` for the identifier `id`. If it is not found in the specified scope, then gdb searches all scopes enclosing the one specified by `scope`.

Using the `.` operator makes gdb search the current scope for the identifier specified by `id` that was imported from the definition module specified by `module`. With this operator, it is an error if the identifier `id` was not imported from definition module `module`, or if `id` is not an identifier in `module`.

14.4.3.8. gdb and Modula-2

Some gdb commands have little use when debugging Modula-2 programs. Five subcommands of `set print` and `show print` apply specifically to C and C++: `vtbl`, `demangle`, `asm-demangle`, `object`, and `union`. The first four apply to C++, and the last to the C `union` type, which has no direct analogue in Modula-2.

The `@` operator (refer to Section 10.1 *Expressions*), while available with any language, is not useful with Modula-2. Its intent is to aid the debugging of *dynamic arrays*, which cannot be created in Modula-2 as they can in C or C++. However, because an address can be specified by an integral constant, the construct `{type}adrexpr` is still useful.

In gdb scripts, the Modula-2 inequality operator `#` is interpreted as the beginning of a comment. Use `<>` instead.

14.5. Unsupported languages

In addition to the other fully-supported programming languages, gdb also provides a pseudo-language, called `minimal`. It does not represent a real programming language, but provides a set of capabilities close to what the C or assembly languages provide. This should allow most simple operations to be performed while debugging an application that uses a language currently not supported by gdb.

If the language is set to `auto`, gdb will automatically select this language if the current frame corresponds to an unsupported language.

Examining the Symbol Table

The commands described in this chapter allow you to inquire about the symbols (names of variables, functions and types) defined in your program. This information is inherent in the text of your program and does not change as your program executes. `gdb` finds it in your program's symbol table, in the file indicated when you started `gdb` (refer to Section 4.1.1 *Choosing files*), or by one of the file-management commands (refer to Section 17.1 *Commands to specify files*).

Occasionally, you may need to refer to symbols that contain unusual characters, which `gdb` ordinarily treats as word delimiters. The most frequent case is in referring to static variables in other source files (refer to Section 10.2 *Program variables*). File names are recorded in object files as debugging symbols, but `gdb` would ordinarily parse a typical file name, like `foo.c`, as the three words `foo . c`. To allow `gdb` to recognize `foo.c` as a single symbol, enclose it in single quotes; for example,

```
p 'foo.c'::x
```

looks up the value of `x` in the scope of the file `foo.c`.

```
info address symbol
```

Describe where the data for `symbol` is stored. For a register variable, this says which register it is kept in. For a non-register local variable, this prints the stack-frame offset at which the variable is always stored.

Note the contrast with `print &symbol`, which does not work at all for a register variable, and for a stack local variable prints the exact address of the current instantiation of the variable.

```
info symbol addr
```

Print the name of a symbol which is stored at the address `addr`. If no symbol is stored exactly at `addr`, `gdb` prints the nearest symbol and an offset from it:

```
(gdb) info symbol 0x54320
_initialize_vx + 396 in section .text
```

This is the opposite of the `info address` command. You can use it to find out the name of a variable or a function given its address.

```
whatis expr
```

Print the data type of expression `expr`. `expr` is not actually evaluated, and any side-effecting operations (such as assignments or function calls) inside it do not take place. Refer to Section 10.1 *Expressions*.

```
whatis
```

Print the data type of `$_`, the last value in the value history.

```
ptype typename
```

Print a description of data type `typename`. `typename` may be the name of a type, or for C code it may have the form `class class-name`, `struct struct-tag`, `union union-tag` or `enum enum-tag`.

```
ptype expr
ptype
```

Print a description of the type of expression `expr`. `ptype` differs from `whatis` by printing a detailed description, instead of just the name of the type.

For example, for this variable declaration:

```
struct complex {double real; double imag;} v;
```

the two commands give this output:

```
(gdb) whatis v
type = struct complex
(gdb) ptype v
type = struct complex {
    double real;
    double imag;
}
```

As with `whatis`, using `ptype` without an argument refers to the type of `$`, the last value in the value history.

```
info types regexp
info types
```

Print a brief description of all types whose names match `regexp` (or all types in your program, if you supply no argument). Each complete typename is matched as though it were a complete line; thus, `i type value` gives information on all types in your program whose names include the string `value`, but `i type ^value$` gives information only on types whose complete name is `value`.

This command differs from `ptype` in two ways: first, like `whatis`, it does not print a detailed description; second, it lists all source files where a type is defined.

```
info scope addr
```

List all the variables local to a particular scope. This command accepts a location--a function name, a source line, or an address preceded by a `*`, and prints all the variables local to the scope defined by that location. For example:

```
(gdb) info scope command_line_handler
Scope for command_line_handler:
Symbol rl is an argument at stack/frame offset 8, length 4.
Symbol linebuffer is in static storage at address 0x150a18, length 4.
Symbol linelength is in static storage at address 0x150a1c, length 4.
Symbol p is a local variable in register $esi, length 4.
Symbol pl is a local variable in register $ebx, length 4.
Symbol nline is a local variable in register $edx, length 4.
Symbol repeat is a local variable at frame offset -8, length 4.
```

This command is especially useful for determining what data to collect during a *trace experiment*, see `collect`.

```
info source
```

Show information about the current source file--that is, the source file for the function containing the current point of execution:

- the name of the source file, and the directory containing it,
- the directory it was compiled in,
- its length, in lines,

- which programming language it is written in,
- whether the executable includes debugging information for that file, and if so, what format the information is in (e.g., STABS, Dwarf 2, etc.), and
- whether the debugging information includes information about preprocessor macros.

`info sources`

Print the names of all source files in your program for which there is debugging information, organized into two lists: files whose symbols have already been read, and files whose symbols will be read when needed.

`info functions`

Print the names and data types of all defined functions.

`info functions regexp`

Print the names and data types of all defined functions whose names contain a match for regular expression `regexp`. Thus, `info fun step` finds all functions whose names include `step`; `info fun ^step` finds those whose names start with `step`. If a function name contains characters that conflict with the regular expression language (eg. `operator*()`), they may be quoted with a backslash.

`info variables`

Print the names and data types of all variables that are declared outside of functions (that is, excluding local variables).

`info variables regexp`

Print the names and data types of all variables (except for local variables) whose names contain a match for regular expression `regexp`.

`info classes`

`info classes regexp`

Display all Objective-C classes in your program, or (with the `regexp` argument) all those matching a particular regular expression.

`info selectors`

`info selectors regexp`

Display all Objective-C selectors in your program, or (with the `regexp` argument) all those matching a particular regular expression.

Some systems allow individual object files that make up your program to be replaced without stopping and restarting your program. For example, in VxWorks you can simply recompile a defective object file and keep on running. If you are running on one of these systems, you can allow `gdb` to reload the symbols for automatically relinked modules:

`set symbol-reloading on`

Replace symbol definitions for the corresponding source file when an object file with a particular name is seen again.

```
set symbol-reloading off
```

Do not replace symbol definitions when encountering object files of the same name more than once. This is the default state; if you are not running on a system that permits automatic relinking of modules, you should leave `symbol-reloading` off, since otherwise `gdb` may discard symbols when linking large programs, that may contain several modules (from different directories or libraries) with the same name.

```
show symbol-reloading
```

Show the current on or off setting.

```
set opaque-type-resolution on
```

Tell `gdb` to resolve opaque types. An opaque type is a type declared as a pointer to a `struct`, `class`, or `union`--for example, `struct MyType *`--that is used in one source file although the full declaration of `struct MyType` is in another source file. The default is on.

A change in the setting of this subcommand will not take effect until the next time symbols for a file are loaded.

```
set opaque-type-resolution off
```

Tell `gdb` not to resolve opaque types. In this case, the type is printed as follows:

```
{<no data fields>}
```

```
show opaque-type-resolution
```

Show whether opaque types are resolved or not.

```
maint print symbols filename
maint print psymbols filename
maint print msymbols filename
```

Write a dump of debugging symbol data into the file `filename`. These commands are used to debug the `gdb` symbol-reading code. Only symbols with debugging data are included. If you use `maint print symbols`, `gdb` includes all the symbols for which it has already collected full details: that is, `filename` reflects symbols for only those files whose symbols `gdb` has read. You can use the command `info sources` to find out which files these are. If you use `maint print psymbols` instead, the dump shows information about symbols that `gdb` only knows partially--that is, symbols defined in files that `gdb` has skimmed, but not yet read completely. Finally, `maint print msymbols` dumps just the minimal symbol information required for each object file from which `gdb` has read some symbols. Refer to Section 17.1 *Commands to specify files*, for a discussion of how `gdb` reads symbols (in the description of `symbol-file`).

```
maint info symtabs [ regexp ]
maint info psymtabs [ regexp ]
```

List the `struct symtab` or `struct partial_symtab` structures whose names match `regexp`. If `regexp` is not given, list them all. The output includes expressions which you can copy into a `gdb` debugging this one to examine a particular structure in more detail. For example:

```
(gdb) maint info psymtabs dwarf2read
{ objfile /home/gnu/build/gdb/gdb
  ((struct objfile *) 0x82e69d0)
  { psymtab /home/gnu/src/gdb/dwarf2read.c
    ((struct partial_symtab *) 0x8474b10)
    readin no
    fullname (null)
```

```

text addresses 0x814d3c8 -- 0x8158074
globals (* (struct partial_symbol **) 0x8507a08 @ 9)
statics (* (struct partial_symbol **) 0x40e95b78 @ 2882)
dependencies (none)
}
}
(gdb) maint info symtabs
(gdb)

```

We see that there is one partial symbol table whose filename contains the string `dwarf2read`, belonging to the `gdb` executable; and we see that `gdb` has not read in any `symtabs` yet at all. If we set a breakpoint on a function, that will cause `gdb` to read the `symtab` for the compilation unit containing that function:

```

(gdb) break dwarf2_psymtab_to_symtab
Breakpoint 1 at 0x814e5da: file /home/gnu/src/gdb/dwarf2read.c,
line 1574.
(gdb) maint info symtabs
{ objfile /home/gnu/build/gdb/gdb
  ((struct objfile *) 0x82e69d0)
  { symtab /home/gnu/src/gdb/dwarf2read.c
    ((struct symtab *) 0x86c1f38)
    dirname (null)
    fullname (null)
    blockvector ((struct blockvector *) 0x86c1bd0) (primary)
    debugformat DWARF 2
  }
}
(gdb)

```


Altering Execution

Once you think you have found an error in your program, you might want to find out for certain whether correcting the apparent error would lead to correct results in the rest of the run. You can find the answer by experiment, using the `gdb` features for altering execution of the program.

For example, you can store new values into variables or memory locations, give your program a signal, restart it at a different address, or even return prematurely from a function.

16.1. Assignment to variables

To alter the value of a variable, evaluate an assignment expression. Refer to Section 10.1 *Expressions*. For example,

```
print x=4
```

stores the value 4 into the variable `x`, and then prints the value of the assignment expression (which is 4). Refer to Chapter 14 *Using gdb with Different Languages*, for more information on operators in supported languages.

If you are not interested in seeing the value of the assignment, use the `set` command instead of the `print` command. `set` is really the same as `print` except that the expression's value is not printed and is not put in the value history (refer to Section 10.8 *Value history*). The expression is evaluated only for its effects.

If the beginning of the argument string of the `set` command appears identical to a `set` subcommand, use the `set variable` command instead of just `set`. This command is identical to `set` except for its lack of subcommands. For example, if your program has a variable `width`, you get an error if you try to set a new value with just `set width=13`, because `gdb` has the command `set width`:

```
(gdb) whatis width
type = double
(gdb) p width
$4 = 13
(gdb) set width=47
Invalid syntax in expression.
```

The invalid expression, of course, is `=47`. In order to actually set the program's variable `width`, use

```
(gdb) set var width=47
```

Because the `set` command has many subcommands that can conflict with the names of program variables, it is a good idea to use the `set variable` command instead of just `set`. For example, if your program has a variable `g`, you run into problems if you try to set a new value with just `set g=4`, because `gdb` has the command `set gnutarget`, abbreviated `set g`:

```
(gdb) whatis g
type = double
(gdb) p g
```

```

$1 = 1
(gdb) set g=4
(gdb) p g
$2 = 1
(gdb) r
The program being debugged has been started already.
Start it from the beginning? (y or n) y
Starting program: /home/smith/cc_progs/a.out
"/home/smith/cc_progs/a.out": can't open to read symbols:
                                Invalid bfd target.
(gdb) show g
The current BFD target is "=4".

```

The program variable `g` did not change, and you silently set the `gntarget` to an invalid value. In order to set the variable `g`, use

```
(gdb) set var g=4
```

`gdb` allows more implicit conversions in assignments than `C`; you can freely store an integer value into a pointer variable or vice versa, and you can convert any structure to any other structure that is the same length or shorter.

To store values into arbitrary places in memory, use the `{...}` construct to generate a value of specified type at a specified address (refer to Section 10.1 *Expressions*). For example, `{int}0x83040` refers to memory location `0x83040` as an integer (which implies a certain size and representation in memory), and

```
set {int}0x83040 = 4
```

stores the value 4 into that memory location.

16.2. Continuing at a different address

Ordinarily, when you continue your program, you do so at the place where it stopped, with the `continue` command. You can instead continue at an address of your own choosing, with the following commands:

```
jump linespec
```

Resume execution at line `linespec`. Execution stops again immediately if there is a breakpoint there. Refer to Section 9.1 *Printing source lines*, for a description of the different forms of `linespec`. It is common practice to use the `tbreak` command in conjunction with `jump`. Refer to Section 7.1.1 *Setting breakpoints*.

The `jump` command does not change the current stack frame, or the stack pointer, or the contents of any memory location or any register other than the program counter. If line `linespec` is in a different function from the one currently executing, the results may be bizarre if the two functions expect different patterns of arguments or of local variables. For this reason, the `jump` command requests confirmation if the specified line is not in the function currently executing. However, even bizarre results are predictable if you are well acquainted with the machine-language code of your program.

```
jump *address
```

Resume execution at the instruction at address `address`.

On many systems, you can get much the same effect as the `jump` command by storing a new value into the register `$pc`. The difference is that this does not start your program running; it only changes the address of where it *will* run when you continue. For example,

```
set $pc = 0x485
```

makes the next `continue` command or stepping command execute at address `0x485`, rather than at the address where your program stopped. Refer to Section 7.2 *Continuing and stepping*.

The most common occasion to use the `jump` command is to back up--perhaps with more breakpoints set--over a portion of a program that has already executed, in order to examine its execution in more detail.

16.3. Giving your program a signal

```
signal signal
```

Resume execution where your program stopped, but immediately give it the signal `signal`. `signal` can be the name or the number of a signal. For example, on many systems `signal 2` and `signal SIGINT` are both ways of sending an interrupt signal.

Alternatively, if `signal` is zero, continue execution without giving a signal. This is useful when your program stopped on account of a signal and would ordinarily see the signal when resumed with the `continue` command; `signal 0` causes it to resume without a signal.

`signal` does not repeat when you press [RET] a second time after executing the command.

Invoking the `signal` command is not the same as invoking the `kill` utility from the shell. Sending a signal with `kill` causes `gdb` to decide what to do with the signal depending on the signal handling tables (refer to Section 7.3 *Signals*). The `signal` command passes the signal directly to your program.

16.4. Returning from a function

```
return
return expression
```

You can cancel execution of a function call with the `return` command. If you give an `expression` argument, its value is used as the function's return value.

When you use `return`, `gdb` discards the selected stack frame (and all frames within it). You can think of this as making the discarded frame return prematurely. If you wish to specify a value to be returned, give that value as the argument to `return`.

This pops the selected stack frame (refer to Section 8.3 *Selecting a frame*), and any other frames inside of it, leaving its caller as the innermost remaining frame. That frame becomes selected. The specified value is stored in the registers used for returning values of functions.

The `return` command does not resume execution; it leaves the program stopped in the state that would exist if the function had just returned. In contrast, the `finish` command (refer to Section 7.2 *Continuing and stepping*) resumes execution until the selected stack frame returns naturally.

16.5. Calling program functions

```
call expr
```

Evaluate the expression `expr` without displaying `void` returned values.

You can use this variant of the `print` command if you want to execute a function from your program, but without cluttering the output with `void` returned values. If the result is not `void`, it is printed and saved in the value history.

16.6. Patching programs

By default, `gdb` opens the file containing your program's executable code (or the corefile) read-only. This prevents accidental alterations to machine code; but it also prevents you from intentionally patching your program's binary.

If you'd like to be able to patch the binary, you can specify that explicitly with the `set write` command. For example, you might want to turn on internal debugging flags, or even to make emergency repairs.

```
set write on
set write off
```

If you specify `set write on`, `gdb` opens executable and core files for both reading and writing; if you specify `set write off` (the default), `gdb` opens them read-only.

If you have already loaded a file, you must load it again (using the `exec-file` or `core-file` command) after changing `set write`, for your new setting to take effect.

```
show write
```

Display whether executable files and core files are opened for writing as well as reading.

gdb needs to know the file name of the program to be debugged, both in order to read its symbol table and in order to start your program. To debug a core dump of a previous run, you must also tell gdb the name of the core dump file.

17.1. Commands to specify files

You may want to specify executable and core dump file names. The usual way to do this is at start-up time, using the arguments to gdb's start-up commands (refer to Chapter 4 *Getting In and Out of gdb*).

Occasionally it is necessary to change to a different file during a gdb session. Or you may run gdb and forget to specify a file you want to use. In these situations the gdb commands to specify new files are useful.

`file filename`

Use `filename` as the program to be debugged. It is read for its symbols and for the contents of pure memory. It is also the program executed when you use the `run` command. If you do not specify a directory and the file is not found in the gdb working directory, gdb uses the environment variable `PATH` as a list of directories to search, just as the shell does when looking for a program to run. You can change the value of this variable, for both gdb and your program, using the `path` command.

On systems with memory-mapped files, an auxiliary file named `filename.syms` may hold symbol table information for `filename`. If so, gdb maps in the symbol table from `filename.syms`, starting up more quickly. See the descriptions of the file options `-mapped` and `-readnow` (available on the command line, and with the commands `file`, `symbol-file`, or `add-symbol-file`, described below), for more information.

`file`

`file` with no argument makes gdb discard any information it has on both executable file and the symbol table.

`exec-file [filename]`

Specify that the program to be run (but not the symbol table) is found in `filename`. gdb searches the environment variable `PATH` if necessary to locate your program. Omitting `filename` means to discard information on the executable file.

`symbol-file [filename]`

Read symbol table information from file `filename`. `PATH` is searched when necessary. Use the `file` command to get both symbol table and program to run from the same file.

`symbol-file` with no argument clears out gdb information on your program's symbol table.

The `symbol-file` command causes gdb to forget the contents of its convenience variables, the value history, and all breakpoints and auto-display expressions. This is because they may contain pointers to the internal data recording symbols and data types, which are part of the old symbol table data being discarded inside gdb.

`symbol-file` does not repeat if you press [RET] again after executing it once.

When gdb is configured for a particular environment, it understands debugging information in whatever format is the standard generated for that environment; you may use either a gnu compiler, or other compilers that adhere to the local conventions. Best results are usually obtained from gnu compilers; for example, using gcc you can generate debugging information for optimized code.

For most kinds of object files, with the exception of old SVR3 systems using COFF, the `symbol-file` command does not normally read the symbol table in full right away. Instead, it scans the symbol table quickly to find which source files and which symbols are present. The details are read later, one source file at a time, as they are needed.

The purpose of this two-stage reading strategy is to make gdb start up faster. For the most part, it is invisible except for occasional pauses while the symbol table details for a particular source file are being read. (The `set verbose` command can turn these pauses into messages if desired. Refer to Section 21.7 *Optional warnings and messages*.)

We have not implemented the two-stage strategy for COFF yet. When the symbol table is stored in COFF format, `symbol-file` reads the symbol table data in full right away. Note that "stabs-in-COFF" still does the two-stage strategy, since the debug info is actually in stabs format.

```
symbol-file filename [ -readnow ] [ -mapped ]
file filename [ -readnow ] [ -mapped ]
```

You can override the gdb two-stage strategy for reading symbol tables by using the `-readnow` option with any of the commands that load symbol table information, if you want to be sure gdb has the entire symbol table available.

If memory-mapped files are available on your system through the `mmap` system call, you can use another option, `-mapped`, to cause gdb to write the symbols for your program into a reusable file. Future gdb debugging sessions map in symbol information from this auxiliary symbol file (if the program has not changed), rather than spending time reading the symbol table from the executable program. Using the `-mapped` option has the same effect as starting gdb with the `-mapped` command-line option.

You can use both options together, to make sure the auxiliary symbol file has all the symbol information for your program.

The auxiliary symbol file for a program called `myprog` is called `myprog.syms`. Once this file exists (so long as it is newer than the corresponding executable), gdb always attempts to use it when you debug `myprog`; no special options or commands are needed.

The `.syms` file is specific to the host machine where you run gdb. It holds an exact image of the internal gdb symbol table. It cannot be shared across multiple host platforms.

```
core-file [ filename ]
```

Specify the whereabouts of a core dump file to be used as the "contents of memory". Traditionally, core files contain only some parts of the address space of the process that generated them; gdb can access the executable file itself for other parts.

`core-file` with no argument specifies that no core file is to be used.

Note that the core file is ignored when your program is actually running under gdb. So, if you have been running your program and you wish to debug a core file instead, you must kill the subprocess in which the program is running. To do this, use the `kill` command (refer to Section 6.8 *Killing the child process*).

```
add-symbol-file filename address
add-symbol-file filename address [ -readnow ] [ -mapped ]
add-symbol-file filename -ssection address ...
```

The `add-symbol-file` command reads additional symbol table information from the file `filename`. You would use this command when `filename` has been dynamically loaded (by some other means) into the program that is running. `address` should be the memory address at which the file has been loaded; `gdb` cannot figure this out for itself. You can additionally specify an arbitrary number of `-ssection address` pairs, to give an explicit section name and base address for that section. You can specify any `address` as an expression.

The symbol table of the file `filename` is added to the symbol table originally read with the `symbol-file` command. You can use the `add-symbol-file` command any number of times; the new symbol data thus read keeps adding to the old. To discard all old symbol data instead, use the `symbol-file` command without any arguments.

Although `filename` is typically a shared library file, an executable file, or some other object file which has been fully relocated for loading into a process, you can also load symbolic information from relocatable `.o` files, as long as:

- the file's symbolic information refers only to linker symbols defined in that file, not to symbols defined by other object files,
- every section the file's symbolic information refers to has actually been loaded into the inferior, as it appears in the file, and
- you can determine the address at which every section was loaded, and provide these to the `add-symbol-file` command.

Some embedded operating systems, like Sun Chorus and VxWorks, can load relocatable files into an already running program; such systems typically make the requirements above easy to meet. However, it's important to recognize that many native systems use complex link procedures (`.linkonce` section factoring and C++ constructor table assembly, for example) that make the requirements difficult to meet. In general, one cannot assume that using `add-symbol-file` to read a relocatable object file's symbolic information will have the same effect as linking the relocatable object file into the program in the normal way.

`add-symbol-file` does not repeat if you press [RET] after using it.

You can use the `-mapped` and `-readnow` options just as with the `symbol-file` command, to change how `gdb` manages the symbol table information for `filename`.

```
add-shared-symbol-file
```

The `add-shared-symbol-file` command can be used only under Harris' CXUX operating system for the Motorola 88k. `gdb` automatically looks for shared libraries, however if `gdb` does not find yours, you can run `add-shared-symbol-file`. It takes no arguments.

```
section
```

The `section` command changes the base address of section `SECTION` of the `exec` file to `ADDR`. This can be used if the `exec` file does not contain section addresses, (such as in the `a.out` format), or when the addresses specified in the file itself are wrong. Each section must be changed separately. The `info files` command, described below, lists all the sections and their addresses.

```
info files
info target
```

`info files` and `info target` are synonymous; both print the current target (refer to Chapter 18 *Specifying a Debugging Target*), including the names of the executable and core dump files

currently in use by gdb, and the files from which symbols were loaded. The command `help target` lists all possible targets rather than current ones.

`maint info sections`

Another command that can give you extra information about program sections is `maint info sections`. In addition to the section information displayed by `info files`, this command displays the flags and file offset of each section in the executable and core dump files. In addition, `maint info sections` provides the following command options (which may be arbitrarily combined):

`ALLOBJ`

Display sections for all loaded object files, including shared libraries.

`sections`

Display info only for named `sections`.

`section-flags`

Display info only for sections for which `section-flags` are true. The section flags that gdb currently knows about are:

`ALLOC`

Section will have space allocated in the process when loaded. Set for all sections except those containing debug information.

`LOAD`

Section will be loaded from the file into the child process memory. Set for pre-initialized code and data, clear for `.bss` sections.

`RELOC`

Section needs to be relocated before loading.

`READONLY`

Section cannot be modified by the child process.

`CODE`

Section contains executable code only.

`DATA`

Section contains data only (no executable code).

`ROM`

Section will reside in ROM.

`CONSTRUCTOR`

Section contains data for constructor/destructor lists.

`HAS_CONTENTS`

Section is not empty.

NEVER_LOAD

An instruction to the linker to not output the section.

COFF_SHARED_LIBRARY

A notification to the linker that the section contains COFF shared library information.

IS_COMMON

Section contains common symbols.

```
set trust-readonly-sections on
```

Tell gdb that readonly sections in your object file really are read-only (that is, that their contents will not change). In that case, gdb can fetch values from these sections out of the object file, rather than from the target program. For some targets (notably embedded ones), this can be a significant enhancement to debugging performance.

The default is off.

```
set trust-readonly-sections off
```

Tell gdb not to trust readonly sections. This means that the contents of the section might change while the program is running, and must therefore be fetched from the target when needed.

All file-specifying commands allow both absolute and relative file names as arguments. gdb always converts the file name to an absolute file name and remembers it that way.

gdb supports HP-UX, SunOS, SVr4, Irix 5, and IBM RS/6000 shared libraries.

gdb automatically loads symbol definitions from shared libraries when you use the `run` command, or when you examine a core file. (Before you issue the `run` command, gdb does not understand references to a function in a shared library, however--unless you are debugging a core file).

On HP-UX, if the program loads a library explicitly, gdb automatically loads the symbols at the time of the `shl_load` call.

There are times, however, when you may wish to not automatically load symbol definitions from shared libraries, such as when they are particularly large or there are many of them.

To control the automatic loading of shared library symbols, use the commands:

```
set auto-solib-add mode
```

If `mode` is `on`, symbols from all shared object libraries will be loaded automatically when the inferior begins execution, you attach to an independently started inferior, or when the dynamic linker informs gdb that a new library has been loaded. If `mode` is `off`, symbols must be loaded manually, using the `sharedlibrary` command. The default value is `on`.

```
show auto-solib-add
```

Display the current autoloading mode.

To explicitly load shared library symbols, use the `sharedlibrary` command:

```
info share
info sharedlibrary
```

Print the names of the shared libraries which are currently loaded.

```
sharedlibrary regex
share regex
```

Load shared object library symbols for files matching a Unix regular expression. As with files loaded automatically, it only loads shared libraries required by your program for a core file or after typing `run`. If `regex` is omitted all shared libraries required by your program are loaded.

On some systems, such as HP-UX systems, `gdb` supports autoloading shared library symbols until a limiting threshold size is reached. This provides the benefit of allowing autoloading to remain on by default, but avoids autoloading excessively large shared libraries, up to a threshold that is initially set, but which you can modify if you wish.

Beyond that threshold, symbols from shared libraries must be explicitly loaded. To load these symbols, use the command `sharedlibrary filename`. The base address of the shared library is determined automatically by `gdb` and need not be specified.

To display or set the threshold, use the commands:

```
set auto-solib-limit threshold
```

Set the autoloading size threshold, in an integral number of megabytes. If `threshold` is nonzero and shared library autoloading is enabled, symbols from all shared object libraries will be loaded until the total size of the loaded shared library symbols exceeds this threshold. Otherwise, symbols must be loaded manually, using the `sharedlibrary` command. The default threshold is 100 (that is, 100 Mb).

```
show auto-solib-limit
```

Display the current autoloading size threshold, in megabytes.

Shared libraries are also supported in many cross or remote debugging configurations. A copy of the target's libraries need to be present on the host system; they need to be the same as the target libraries, although the copies on the target can be stripped as long as the copies on the host are not.

You need to tell `gdb` where the target libraries are, so that it can load the correct copies--otherwise, it may try to load the host's libraries. `gdb` has two variables to specify the search directories for target libraries.

```
set solib-absolute-prefix path
```

If this variable is set, `path` will be used as a prefix for any absolute shared library paths; many runtime loaders store the absolute paths to the shared library in the target program's memory. If you use `solib-absolute-prefix` to find shared libraries, they need to be laid out in the same way that they are on the target, with e.g. a `/usr/lib` hierarchy under `path`.

You can set the default value of `solib-absolute-prefix` by using the `configure-time --with-sysroot` option.

```
show solib-absolute-prefix
```

Display the current shared library prefix.

```
set solib-search-path path
```

If this variable is set, `path` is a colon-separated list of directories to search for shared libraries. `solib-search-path` is used after `solib-absolute-prefix` fails to locate the library, or if the path to the library is relative instead of absolute. If you want to use `solib-search-path` instead of `solib-absolute-prefix`, be sure to set `solib-absolute-prefix` to a nonexistent directory to prevent `gdb` from finding your host's libraries.

```
show solib-search-path
```

Display the current shared library search path.

17.2. Debugging Information in Separate Files

`gdb` allows you to put a program's debugging information in a file separate from the executable itself, in a way that allows `gdb` to find and load the debugging information automatically. Since debugging information can be very large -- sometimes larger than the executable code itself -- some systems distribute debugging information for their executables in separate files, which users can install only when they need to debug a problem.

If an executable's debugging information has been extracted to a separate file, the executable should contain a *debug link* giving the name of the debugging information file (with no directory components), and a checksum of its contents. (The exact form of a debug link is described below.) If the full name of the directory containing the executable is `execdir`, and the executable has a debug link that specifies the name `debugfile`, then `gdb` will automatically search for the debugging information file in three places:

- the directory containing the executable file (that is, it will look for a file named `execdir/debugfile`,
- a subdirectory of that directory named `.debug` (that is, the file `execdir/.debug/debugfile`, and
- a subdirectory of the global debug file directory that includes the executable's full path, and the name from the link (that is, the file `globaldebugdir/execdir/debugfile`, where `globaldebugdir` is the global debug file directory, and `execdir` has been turned into a relative path).

`gdb` checks under each of these names for a debugging information file whose checksum matches that given in the link, and reads the debugging information from the first one it finds.

So, for example, if you ask `gdb` to debug `/usr/bin/ls`, which has a link containing the name `ls.debug`, and the global debug directory is `/usr/lib/debug`, then `gdb` will look for debug information in `/usr/bin/ls.debug`, `/usr/bin/.debug/ls.debug`, and `/usr/lib/debug/usr/bin/ls.debug`.

You can set the global debugging info directory's name, and view the name `gdb` is currently using.

```
set debug-file-directory directory
```

Set the directory which `gdb` searches for separate debugging information files to `directory`.

```
show debug-file-directory
```

Show the directory `gdb` searches for separate debugging information files.

A debug link is a special section of the executable file named `.gnu_debuglink`. The section must contain:

- A filename, with any leading directory components removed, followed by a zero byte,
- zero to three bytes of padding, as needed to reach the next four-byte boundary within the section, and
- a four-byte CRC checksum, stored in the same endianness used for the executable file itself. The checksum is computed on the debugging information file's full contents by the function given below, passing zero as the `crc` argument.

Any executable file format can carry a debug link, as long as it can contain a section named `.gnu_debuglink` with the contents described above.

The debugging information file itself should be an ordinary executable, containing a full set of linker symbols, sections, and debugging information. The sections of the debugging information file should have the same names, addresses and sizes as the original file, but they need not contain any data -- much like a `.bss` section in an ordinary executable.

As of December 2002, there is no standard GNU utility to produce separated executable / debugging information file pairs. Ulrich Drepper's `elfutils` package, starting with version 0.53, contains a version of the `strip` command such that the command `strip foo -f foo.debug` removes the debugging information from the executable file `foo`, places it in the file `foo.debug`, and leaves behind a debug link in `foo`.

Since there are many different ways to compute CRC's (different polynomials, reversals, byte ordering, etc.), the simplest way to describe the CRC used in `.gnu_debuglink` sections is to give the complete code for a function that computes it:

```
unsigned long
gnu_debuglink_crc32 (unsigned long crc,
                    unsigned char *buf, size_t len)
{
    static const unsigned long crc32_table[256] =
    {
        0x00000000, 0x77073096, 0xee0e612c, 0x990951ba, 0x076dc419,
        0x706af48f, 0xe963a535, 0x9e6495a3, 0x0edb8832, 0x79dcb8a4,
        0xe0d5e91e, 0x97d2d988, 0x09b64c2b, 0x7eb17cbd, 0xe1b82d07,
        0x90bf1d91, 0x1db71064, 0x6ab020f2, 0xf3b97148, 0x84be41de,
        0x1dad47d, 0x6ddde4eb, 0xf4d4b551, 0x83d385c7, 0x136c9856,
        0x646ba8c0, 0xfd62f97a, 0x8a65c9ec, 0x14015c4f, 0x63066cd9,
        0xfa0f3d63, 0x8d080df5, 0x3b6e20c8, 0x4c69105e, 0xd56041e4,
        0xa2677172, 0x3c03e4d1, 0x4b04d447, 0xd20d85fd, 0xa50ab56b,
        0x325b5a8fa, 0x42b2986c, 0xdbb9c9d6, 0xacbcf940, 0x32d86ce3,
        0x45df5c75, 0xdcd60dcf, 0xabd13d59, 0x26d930ac, 0x51de003a,
        0xc8d75180, 0xbfd06116, 0x21b4f4b5, 0x56b3c423, 0xcfbfa9599,
        0xb8bda50f, 0x2802b89e, 0x5f058808, 0xc60cd9b2, 0xb10be924,
        0x22f26f7c87, 0x58684c11, 0xc1611dab, 0xb6662d3d, 0x76dc4190,
        0x01db7106, 0x98d220bc, 0xefd5102a, 0x71b18589, 0x06b6b51f,
        0x9fbfe4a5, 0xe8b8d433, 0x7807c9a2, 0x0f00f934, 0x9609a88e,
        0xe10e9818, 0x7f6a0dbb, 0x086d3d2d, 0x91646c97, 0xe6635c01,
        0x1b66b51f4, 0x1c6c6162, 0x856530d8, 0xf262004e, 0x6c6095ed,
        0x1b01a57b, 0x2808f4c1, 0xf50fc457, 0x65b0d9c6, 0x12b7e950,
        0x8bbbeb8ea, 0xfcb9887c, 0x62dd1ddf, 0x15da2d49, 0x8cd37cf3,
        0xfbd44c65, 0x4db26158, 0x3ab551ce, 0xa3bc0074, 0xd4bb30e2,
        0x4adfa541, 0x3dd895d7, 0xa4d1c46d, 0xd3d6f4fb, 0x4369e96a,
        0x346ed9fc, 0xad678846, 0xda60b8d0, 0x44042d73, 0x33031de5,
        0xaa0a4c5f, 0xdd0d7cc9, 0x5005713c, 0x270241aa, 0xe0b1010,
        0xc90c2086, 0x5768b525, 0x206f85b3, 0xb966d409, 0xce61e49f,
        0x5edef90e, 0x29d9c998, 0xb0d09822, 0xc7d7a8b4, 0x59b33d17,
        0x2eb40d81, 0xb7bd5c3b, 0xc0ba6cad, 0xedb88320, 0x9abfb3b6,
        0x03b6e20c, 0x74b1d29a, 0xeadd5473, 0x9dd277af, 0x04db2615,
        0x73dc1683, 0xe3630b12, 0x94643b84, 0x0d6d6a3e, 0x7a6a5aa8,
        0xe40ecf0b, 0x9309ff9d, 0x0a00ae27, 0x7d079eb1, 0xf00f9344,
        0x8708a3d2, 0x1e01f268, 0x6906c2fe, 0xf762575d, 0x806567cb,
        0x196c3671, 0x6e6b06e7, 0xfed41b76, 0x89d32be0, 0x10da7a5a,
        0x67dd4acc, 0xf9b9df6f, 0x8ebeeff9, 0x17b7be43, 0x60b08ed5,
        0xd6d6a3e8, 0x1a1d1937e, 0x33d88c2c4, 0x46fdff252, 0xd1bb67f1,
        0xa6bc5767, 0x3fb506dd, 0x48b2364b, 0xd80d2bda, 0xaf0a1b4c,
        0x36034af6, 0x41047a60, 0xdf60efc3, 0xa867df55, 0x316e8e3f,
        0x4669be79, 0xc6b1b38c, 0xbcb66831a, 0x256fd2a0, 0x52682e36,
        0xcc0c7795, 0xbb0b4703, 0x220216b9, 0x5505262f, 0xc5ba3bbe,
        0xb2bd0b28, 0x2bb45a92, 0x5cb36a04, 0xc2d7ffa7, 0xb5d0cf31,
        0x2cd99e8b, 0x5bdeae1d, 0x9b64c2b0, 0xec63f226, 0x756aa39c,
        0x026d930a, 0x9c0906a9, 0xeb0e363f, 0x72076785, 0x05005713,
```

```

0x95bf4a82, 0xe2b87a14, 0x7bb12bae, 0x0cb61b38, 0x92d28e9b,
0xe5d5be0d, 0x7cdcefb7, 0x0bdbdf21, 0x86d3d2d4, 0xf1d4e242,
0x68ddb3f8, 0x1fda836e, 0x81be16cd, 0xf6b9265b, 0x6fb077e1,
0x18b74777, 0x88085ae6, 0xff0f6a70, 0x66063bca, 0x11010b5c,
0x8f659eff, 0xf862ae69, 0x616bfffd3, 0x166ccf45, 0xa00ae278,
0xd70dd2ee, 0x4e048354, 0x3903b3c2, 0xa7672661, 0xd06016f7,
0x4969474d, 0x3e6e77db, 0xaed16a4a, 0xd9d65adc, 0x40df0b66,
0x37d83bf0, 0xa9bcae53, 0xd9bb9ec5, 0x47b2cf7f, 0x30b5ffe9,
0xbdbdf21c, 0xcabac28a, 0x53b39330, 0x24b4a3a6, 0xbad03605,
0xcd70693, 0x54de5729, 0x23d967bf, 0xb3667a2e, 0xc4614ab8,
0x5d681b02, 0x2a6f2b94, 0xb40bbe37, 0xc30c8ea1, 0x5a05df1b,
0x2d02ef8d
};
unsigned char *end;

crc = ~crc & 0xffffffff;
for (end = buf + len; buf < end; ++buf)
    crc = crc32_table[(crc ^ *buf) & 0xff] ^ (crc >> 8);
return ~crc & 0xffffffff;
}

```

17.3. Errors reading symbol files

While reading a symbol file, gdb occasionally encounters problems, such as symbol types it does not recognize, or known bugs in compiler output. By default, gdb does not notify you of such problems, since they are relatively common and primarily of interest to people debugging compilers. If you are interested in seeing information about ill-constructed symbol tables, you can either ask gdb to print only one message about each such type of problem, no matter how many times the problem occurs; or you can ask gdb to print more messages, to see how many times the problems occur, with the `set complaints` command (refer to Section 21.7 *Optional warnings and messages*).

The messages currently printed, and their meanings, include:

```
inner block not inside outer block in symbol
```

The symbol information shows where symbol scopes begin and end (such as at the start of a function or a block of statements). This error indicates that an inner scope block is not fully contained in its outer scope blocks.

gdb circumvents the problem by treating the inner block as if it had the same scope as the outer block. In the error message, `symbol` may be shown as "(don't know)" if the outer block is not a function.

```
block at address out of order
```

The symbol information for symbol scope blocks should occur in order of increasing addresses. This error indicates that it does not do so.

gdb does not circumvent this problem, and has trouble locating symbols in the source file whose symbols it is reading. (You can often determine what source file is affected by specifying `set verbose on`. Refer to Section 21.7 *Optional warnings and messages*.)

```
bad block start address patched
```

The symbol information for a symbol scope block has a start address smaller than the address of the preceding source line. This is known to occur in the SunOS 4.1.1 (and earlier) C compiler.

gdb circumvents the problem by treating the symbol scope block as starting on the previous source line.

bad string table offset in symbol `n`

Symbol number `n` contains a pointer into the string table which is larger than the size of the string table.

`gdb` circumvents the problem by considering the symbol to have the name `f00`, which may cause other problems if many symbols end up with this name.

unknown symbol type `0xnn`

The symbol information contains new data types that `gdb` does not yet know how to read. `0xnn` is the symbol type of the uncomprehended information, in hexadecimal.

`gdb` circumvents the error by ignoring this symbol information. This usually allows you to debug your program, though certain symbols are not accessible. If you encounter such a problem and feel like debugging it, you can debug `gdb` with itself, breakpoint on `complain`, then go up to the function `read_dbx_symtab` and examine `*bufp` to see the symbol.

stub type has NULL name

`gdb` could not find the full definition for a struct or class.

const/volatile indicator missing (ok if using `g++ v1.x`), got...

The symbol information for a C++ member function is missing some information that recent versions of the compiler should have output for it.

info mismatch between compiler and debugger

`gdb` could not parse a type specification output by the compiler.

Specifying a Debugging Target

A *target* is the execution environment occupied by your program.

Often, `gdb` runs in the same host environment as your program; in that case, the debugging target is specified as a side effect when you use the `file` or `core` commands. When you need more flexibility--for example, running `gdb` on a physically separate host, or controlling a standalone system over a serial port or a realtime system over a TCP/IP connection--you can use the `target` command to specify one of the target types configured for `gdb` (refer to Section 18.2 *Commands for managing targets*).

18.1. Active targets

There are three classes of targets: processes, core files, and executable files. `gdb` can work concurrently on up to three active targets, one in each class. This allows you to (for example) start a process and inspect its activity without abandoning your work on a core file.

For example, if you execute `gdb a.out`, then the executable file `a.out` is the only active target. If you designate a core file as well--presumably from a prior run that crashed and coredumped--then `gdb` has two active targets and uses them in tandem, looking first in the corefile target, then in the executable file, to satisfy requests for memory addresses. (Typically, these two classes of target are complementary, since core files contain only a program's read-write memory--variables and so on--plus machine status, while executable files contain only the program text and initialized data.)

When you type `run`, your executable file becomes an active process target as well. When a process target is active, all `gdb` commands requesting memory addresses refer to that target; addresses in an active core file or executable file target are obscured while the process target is active.

Use the `core-file` and `exec-file` commands to select a new core file or executable target (refer to Section 17.1 *Commands to specify files*). To specify as a target a process that is already running, use the `attach` command (refer to Section 6.7 *Debugging an already-running process*).

18.2. Commands for managing targets

`target type parameters`

Connects the `gdb` host environment to a target machine or process. A target is typically a protocol for talking to debugging facilities. You use the argument `type` to specify the type or protocol of the target machine.

Further `parameters` are interpreted by the target protocol, but typically include things like device names or host names to connect with, process numbers, and baud rates.

The `target` command does not repeat if you press [RET] again after executing the command.

`help target`

Displays the names of all targets available. To display targets currently selected, use either `info target` or `info files` (refer to Section 17.1 *Commands to specify files*).

`help target name`

Describe a particular target, including any parameters necessary to select it.

```
set gnutarget args
```

{No value for '`<listitem>GDBN`'} uses its own library BFD to read your files. `gdb` knows whether it is reading an *executable*, a *core*, or a *.o* file; however, you can specify the file format with the `set gnutarget` command. Unlike most `target` commands, with `gnutarget` the `target` refers to a program, not a machine.

Warning: To specify a file format with `set gnutarget`, you must know the actual BFD name.

Refer to Section 17.1 *Commands to specify files*.

```
show gnutarget
```

Use the `show gnutarget` command to display what file format `gnutarget` is set to read. If you have not set `gnutarget`, `gdb` will determine the file format for each file automatically, and `show gnutarget` displays The current BFD target is "auto".

Here are some common targets (available, or not, depending on the GDB configuration):

```
target exec program
```

An executable file. `target exec program` is the same as `exec-file program`.

```
target core filename
```

A core dump file. `target core filename` is the same as `core-file filename`.

```
target remote dev
```

Remote serial target in GDB-specific protocol. The argument `dev` specifies what serial device to use for the connection (e.g. `/dev/ttya`). Refer to Section 18.4 *Remote debugging*. `target remote` supports the `load` command. This is only useful if you have some other way of getting the stub to the target system, and you can put it somewhere in memory where it won't get clobbered by the download.

```
target sim
```

Builtin CPU simulator. `gdb` includes simulators for most architectures. In general,

```
target sim
load
run
```

works; however, you cannot assume that a specific memory map, device drivers, or even basic I/O is available, although some simulators do provide these. For info about any processor-specific simulator details, see the appropriate section in (refer to Section 20.3 *Embedded Processors*).

Some configurations may include these targets as well:

```
target nrom dev
```

NetROM ROM emulator. This target only supports downloading.

Different targets are available on different configurations of `gdb`; your configuration may have more or fewer targets.

Many remote targets require you to download the executable's code once you've successfully established a connection.

```
load filename
```

Depending on what remote debugging facilities are configured into `gdb`, the `load` command may be available. Where it exists, it is meant to make `filename` (an executable) available for debugging on the remote system--by downloading, or dynamic linking, for example. `load` also records the `filename` symbol table in `gdb`, like the `add-symbol-file` command.

If your `gdb` does not have a `load` command, attempting to execute it gets the error message "You can't do that when your target is ..."

The file is loaded at whatever address is specified in the executable. For some object file formats, you can specify the load address when you link the program; for other formats, like `a.out`, the object file format specifies a fixed address.

`load` does not repeat if you press [RET] again after using it.

18.3. Choosing target byte order

Some types of processors, such as the MIPS, PowerPC, and Hitachi SH, offer the ability to run either big-endian or little-endian byte orders. Usually the executable or symbol will include a bit to designate the endian-ness, and you will not need to worry about which to use. However, you may still find it useful to adjust `gdb`'s idea of processor endian-ness manually.

```
set endian big
```

Instruct `gdb` to assume the target is big-endian.

```
set endian little
```

Instruct `gdb` to assume the target is little-endian.

```
set endian auto
```

Instruct `gdb` to use the byte order associated with the executable.

```
show endian
```

Display `gdb`'s current idea of the target byte order.

Note that these commands merely adjust interpretation of symbolic data on the host, and that they have absolutely no effect on the target system.

18.4. Remote debugging

If you are trying to debug a program running on a machine that cannot run `gdb` in the usual way, it is often useful to use remote debugging. For example, you might use remote debugging on an operating system kernel, or on a small system which does not have a general purpose operating system powerful enough to run a full-featured debugger.

Some configurations of `gdb` have special serial or TCP/IP interfaces to make this work with particular debugging targets. In addition, `gdb` comes with a generic serial protocol (specific to `gdb`, but not specific to any particular target system) which you can use if you write the remote stubs--the code that runs on the remote system to communicate with `gdb`.

Other remote targets may be available in your configuration of `gdb`; use `help target` to list them.

18.5. Kernel Object Display

Some targets support kernel object display. Using this facility, `gdb` communicates specially with the underlying operating system and can display information about operating system-level objects such as mutexes and other synchronization objects. Exactly which objects can be displayed is determined on a per-OS basis.

Use the `set os` command to set the operating system. This tells `gdb` which kernel object display module to initialize:

```
(gdb) set os cisco
```

If `set os` succeeds, `gdb` will display some information about the operating system, and will create a new `info` command which can be used to query the target. The `info` command is named after the operating system:

```
(gdb) info cisco
List of Cisco Kernel Objects
Object      Description
any         Any and all objects
```

Further subcommands can be used to query about particular objects known by the kernel.

There is currently no way to determine whether a given operating system is supported other than to try it.

Debugging remote programs

19.1. Connecting to a remote target

On the `gdb` host machine, you will need an unstripped copy of your program, since `gdb` needs symbol and debugging information. Start up `gdb` as usual, using the name of the local copy of your program as the first argument.

If you're using a serial line, you may want to give `gdb` the `-baud` option, or use the `set remotebaund` command before the `target` command.

After that, use `target remote` to establish communications with the target machine. Its argument specifies how to communicate--either via a devicename attached to a direct serial line, or a TCP or UDP port (possibly to a terminal server which in turn has a serial line to the target). For example, to use a serial line connected to the device named `/dev/ttyb`:

```
target remote /dev/ttyb
```

To use a TCP connection, use an argument of the form `host:port` or `tcp:host:port`. For example, to connect to port 2828 on a terminal server named `manyfarms`:

```
target remote manyfarms:2828
```

If your remote target is actually running on the same machine as your debugger session (e.g. a simulator of your target running on the same host), you can omit the hostname. For example, to connect to port 1234 on your local machine:

```
target remote :1234
```

Note that the colon is still required here.

To use a UDP connection, use an argument of the form `udp:host:port`. For example, to connect to UDP port 2828 on a terminal server named `manyfarms`:

```
target remote udp:manyfarms:2828
```

When using a UDP connection for remote debugging, you should keep in mind that the 'U' stands for "Unreliable". UDP can silently drop packets on busy or unreliable networks, which will cause havoc with your debugging session.

Now you can use all the usual commands to examine and change data and to step and continue the remote program.

Whenever `gdb` is waiting for the remote program, if you type the interrupt character (often [C-C]), `gdb` attempts to stop the program. This may or may not succeed, depending in part on the hardware and

the serial drivers the remote system uses. If you type the interrupt character once again, `gdb` displays this prompt:

```
Interrupted while waiting for the program.
Give up (and stop debugging it)? (y or n)
```

If you type `y`, `gdb` abandons the remote debugging session. (If you decide you want to try again later, you can use `target remote` again to connect once more.) If you type `n`, `gdb` goes back to waiting.

`detach`

When you have finished debugging the remote program, you can use the `detach` command to release it from `gdb` control. Detaching from the target normally resumes its execution, but the results will depend on your particular remote stub. After the `detach` command, `gdb` is free to connect to another target.

`disconnect`

The `disconnect` command behaves like `detach`, except that the target is generally not resumed. It will wait for `gdb` (this instance or another one) to connect and continue debugging. After the `disconnect` command, `gdb` is again free to connect to another target.

19.2. Using the `gdbserver` program

`gdbserver` is a control program for Unix-like systems, which allows you to connect your program with a remote `gdb` via `target remote`--but without linking in the usual debugging stub.

`gdbserver` is not a complete replacement for the debugging stubs, because it requires essentially the same operating-system facilities that `gdb` itself does. In fact, a system that can run `gdbserver` to connect to a remote `gdb` could also run `gdb` locally! `gdbserver` is sometimes useful nevertheless, because it is a much smaller program than `gdb` itself. It is also easier to port than all of `gdb`, so you may be able to get started more quickly on a new system by using `gdbserver`. Finally, if you develop code for real-time systems, you may find that the tradeoffs involved in real-time operation make it more convenient to do as much development work as possible on another system, for example by cross-compiling. You can use `gdbserver` to make a similar choice for debugging.

`gdb` and `gdbserver` communicate via either a serial line or a TCP connection, using the standard `gdb` remote serial protocol.

On the target machine,

you need to have a copy of the program you want to debug. `gdbserver` does not need your program's symbol table, so you can strip the program if necessary to save space. `gdb` on the host system does all the symbol handling.

To use the server, you must tell it how to communicate with `gdb`; the name of your program; and the arguments for your program. The usual syntax is:

```
target> gdbserver comm program [ args ... ]
```

`comm` is either a device name (to use a serial line) or a TCP hostname and portnumber. For example, to debug Emacs with the argument `foo.txt` and communicate with `gdb` over the serial port `/dev/com1`:

```
target> gdbserver /dev/com1 emacs foo.txt
```

`gdbserver` waits passively for the host `gdb` to communicate with it.

To use a TCP connection instead of a serial line:

```
target> gdbserver host:2345 emacs foo.txt
```

The only difference from the previous example is the first argument, specifying that you are communicating with the host `gdb` via TCP. The `host:2345` argument means that `gdbserver` is to expect a TCP connection from machine `host` to local TCP port 2345. (Currently, the `host` part is ignored.) You can choose any number you want for the port number as long as it does not conflict with any TCP ports already in use on the target system (for example, 23 is reserved for `telnet`).¹ You must use the same port number with the host `gdb target remote` command.

On some targets, `gdbserver` can also attach to running programs. This is accomplished via the `--attach` argument. The syntax is:

```
target> gdbserver comm --attach pid
```

`pid` is the process ID of a currently running process. It isn't necessary to point `gdbserver` at a binary for the running process.

On the host machine,

connect to your target (refer to Section 19.1 *Connecting to a remote target*). For TCP connections, you must start up `gdbserver` prior to using the `target remote` command. Otherwise you may get an error whose text depends on the host system, but which usually looks something like `Connection refused`. You don't need to use the `load` command in `gdb` when using `gdbserver`, since the program is already on the target.

19.3. Using the `gdbserve.nlm` program

`gdbserve.nlm` is a control program for NetWare systems, which allows you to connect your program with a remote `gdb` via `target remote`.

`gdb` and `gdbserve.nlm` communicate via a serial line, using the standard `gdb` remote serial protocol.

On the target machine,

you need to have a copy of the program you want to debug. `gdbserve.nlm` does not need your program's symbol table, so you can strip the program if necessary to save space. `gdb` on the host system does all the symbol handling.

To use the server, you must tell it how to communicate with `gdb`; the name of your program; and the arguments for your program. The syntax is:

```
load gdbserve [ BOARD=board ] [ PORT=port ]
               [ BAUD=baud ] program [ args ... ]
```

`board` and `port` specify the serial line; `baud` specifies the baud rate used by the connection. `port` and `node` default to 0, `baud` defaults to 9600bps.

For example, to debug Emacs with the argument `foo.txt` and communicate with `gdb` over serial port number 2 or board 1 using a 19200bps connection:

```
load gdbserve BOARD=1 PORT=2 BAUD=19200 emacs foo.txt
```

On the `gdb` host machine, connect to your target (refer to Section 19.1 *Connecting to a remote target*).

1. If you choose a port number that conflicts with another service, `gdbserver` prints an error message and exits.

19.4. Remote configuration

The following configuration options are available when debugging remote programs:

```
set remote hardware-watchpoint-limit limit
set remote hardware-breakpoint-limit limit
```

Restrict gdb to using `limit` remote hardware breakpoint or watchpoints. A limit of -1, the default, is treated as unlimited.

19.5. Implementing a remote stub

The stub files provided with gdb implement the target side of the communication protocol, and the gdb side is implemented in the gdb source file `remote.c`. Normally, you can simply allow these subroutines to communicate, and ignore the details. (If you're implementing your own stub file, you can still ignore the details: start with one of the existing stub files. `sparc-stub.c` is the best organized, and therefore the easiest to read.)

To debug a program running on another machine (the debugging *target* machine), you must first arrange for all the usual prerequisites for the program to run by itself. For example, for a C program, you need:

1. A startup routine to set up the C runtime environment; these usually have a name like `crto`. The startup routine may be supplied by your hardware supplier, or you may have to write your own.
2. A C subroutine library to support your program's subroutine calls, notably managing input and output.
3. A way of getting your program to the other machine--for example, a download program. These are often supplied by the hardware manufacturer, but you may have to write your own from hardware documentation.

The next step is to arrange for your program to use a serial port to communicate with the machine where gdb is running (the *host* machine). In general terms, the scheme looks like this:

On the host,

{No value for '`<listitem>GDBN`'} already understands how to use this protocol; when everything else is set up, you can simply use the `target remote` command (refer to Chapter 18 *Specifying a Debugging Target*).

On the target,

you must link with your program a few special-purpose subroutines that implement the gdb remote serial protocol. The file containing these subroutines is called a *debugging stub*.

On certain remote targets, you can use an auxiliary program `gdbserver` instead of linking a stub into your program. Refer to Section 19.2 *Using the gdbserver program*, for details.

The debugging stub is specific to the architecture of the remote machine; for example, use `sparc-stub.c` to debug programs on sparc boards.

These working remote stubs are distributed with gdb:

```
i386-stub.c
```

For Intel 386 and compatible architectures.

`m68k-stub.c`

For Motorola 680x0 architectures.

`sh-stub.c`

For Hitachi SH architectures.

`sparc-stub.c`

For sparc architectures.

`sparcl-stub.c`

For Fujitsu sparclite architectures.

The `README` file in the `gdb` distribution may list other recently added stubs.

19.5.1. What the stub can do for you

The debugging stub for your architecture supplies these three subroutines:

`set_debug_traps`

This routine arranges for `handle_exception` to run when your program stops. You must call this subroutine explicitly near the beginning of your program.

`handle_exception`

This is the central workhorse, but your program never calls it explicitly--the setup code arranges for `handle_exception` to run when a trap is triggered.

`handle_exception` takes control when your program stops during execution (for example, on a breakpoint), and mediates communications with `gdb` on the host machine. This is where the communications protocol is implemented; `handle_exception` acts as the `gdb` representative on the target machine. It begins by sending summary information on the state of your program, then continues to execute, retrieving and transmitting any information `gdb` needs, until you execute a `gdb` command that makes your program resume; at that point, `handle_exception` returns control to your own code on the target machine.

`breakpoint`

Use this auxiliary subroutine to make your program contain a breakpoint. Depending on the particular situation, this may be the only way for `gdb` to get control. For instance, if your target machine has some sort of interrupt button, you won't need to call this; pressing the interrupt button transfers control to `handle_exception`--in effect, to `gdb`. On some machines, simply receiving characters on the serial port may also trigger a trap; again, in that situation, you don't need to call `breakpoint` from your own program--simply running `target remote` from the host `gdb` session gets control.

Call `breakpoint` if none of these is true, or if you simply want to make certain your program stops at a predetermined point for the start of your debugging session.

19.5.2. What you must do for the stub

The debugging stubs that come with `gdb` are set up for a particular chip architecture, but they have no information about the rest of your debugging target machine.

First of all you need to tell the stub how to communicate with the serial port.

```
int getDebugChar()
```

Write this subroutine to read a single character from the serial port. It may be identical to `getchar` for your target system; a different name is used to allow you to distinguish the two if you wish.

```
void putDebugChar(int)
```

Write this subroutine to write a single character to the serial port. It may be identical to `putchar` for your target system; a different name is used to allow you to distinguish the two if you wish.

If you want `gdb` to be able to stop your program while it is running, you need to use an interrupt-driven serial driver, and arrange for it to stop when it receives a `^C` (`\003`, the control-C character). That is the character which `gdb` uses to tell the remote system to stop.

Getting the debugging target to return the proper status to `gdb` probably requires changes to the standard stub; one quick and dirty way is to just execute a breakpoint instruction (the "dirty" part is that `gdb` reports a `SIGTRAP` instead of a `SIGINT`).

Other routines you need to supply are:

```
void exceptionHandler (int exception_number, void *exception_address)
```

Write this function to install `exception_address` in the exception handling tables. You need to do this because the stub does not have any way of knowing what the exception handling tables on your target system are like (for example, the processor's table might be in rom, containing entries which point to a table in ram). `exception_number` is the exception number which should be changed; its meaning is architecture-dependent (for example, different numbers might represent divide by zero, misaligned access, etc). When this exception occurs, control should be transferred directly to `exception_address`, and the processor state (stack, registers, and so on) should be just as it is when a processor exception occurs. So if you want to use a jump instruction to reach `exception_address`, it should be a simple jump, not a jump to subroutine.

For the 386, `exception_address` should be installed as an interrupt gate so that interrupts are masked while the handler runs. The gate should be at privilege level 0 (the most privileged level). The sparc and 68k stubs are able to mask interrupts themselves without help from `exceptionHandler`.

```
void flush_i_cache()
```

On sparc and sparclite only, write this subroutine to flush the instruction cache, if any, on your target machine. If there is no instruction cache, this subroutine may be a no-op.

On target machines that have instruction caches, `gdb` requires this function to make certain that the state of your program is stable.

You must also make sure this library routine is available:

```
void *memset(void *, int, int)
```

This is the standard library function `memset` that sets an area of memory to a known value. If you have one of the free versions of `libc.a`, `memset` can be found there; otherwise, you must either obtain it from your hardware manufacturer, or write your own.

If you do not use the GNU C compiler, you may need other standard library subroutines as well; this varies from one stub to another, but in general the stubs are likely to use any of the common library subroutines which `gcc` generates as inline code.

19.5.3. Putting it all together

In summary, when your program is ready to debug, you must follow these steps.

1. Make sure you have defined the supporting low-level routines (refer to Section 19.5.2 *What you must do for the stub*):

```
getDebugChar, putDebugChar,  
flush_i_cache, memset, exceptionHandler.
```

2. Insert these lines near the top of your program:

```
set_debug_traps();  
breakpoint();
```

3. For the 680x0 stub only, you need to provide a variable called `exceptionHook`. Normally you just use:

```
void (*exceptionHook)() = 0;
```

but if before calling `set_debug_traps`, you set it to point to a function in your program, that function is called when `gdb` continues after stopping on a trap (for example, bus error). The function indicated by `exceptionHook` is called with one parameter: an `int` which is the exception number.

4. Compile and link together: your program, the `gdb` debugging stub for your target architecture, and the supporting subroutines.
5. Make sure you have a serial connection between your target machine and the `gdb` host, and identify the serial port on the host.
6. Download your program to your target machine (or get it there by whatever means the manufacturer provides), and start it.
7. Start `gdb` on the host, and connect to the target (refer to Section 19.1 *Connecting to a remote target*).

Configuration-Specific Information

While nearly all `gdb` commands are available for all native and cross versions of the debugger, there are some exceptions. This chapter describes things that are only available in certain configurations.

There are three major categories of configurations: native configurations, where the host and target are the same, embedded operating system configurations, which are usually the same for several different processor architectures, and bare embedded processors, which are quite different from each other.

20.1. Native

This section describes details specific to particular native configurations.

20.1.1. HP-UX

On HP-UX systems, if you refer to a function or variable name that begins with a dollar sign, `gdb` searches for a user or system name first, before it searches for a convenience variable.

20.1.2. SVR4 process information

Many versions of SVR4 provide a facility called `/proc` that can be used to examine the image of a running process using file-system subroutines. If `gdb` is configured for an operating system with this facility, the command `info proc` is available to report on several kinds of information about the process running your program. `info proc` works only on SVR4 systems that include the `procfcs` code. This includes OSF/1 (Digital Unix), Solaris, Irix, and Unixware, but not HP-UX or `gnu/Linux`, for example.

```
info proc
```

Summarize available information about the process.

```
info proc mappings
```

Report on the address ranges accessible in the program, with information on whether your program may read, write, or execute each range.

20.1.3. Features for Debugging `djgpp` Programs

`djgpp` is the port of `gnu` development tools to MS-DOS and MS-Windows. `djgpp` programs are 32-bit protected-mode programs that use the *DPMI* (DOS Protected-Mode Interface) API to run on top of real-mode DOS systems and their emulations.

`gdb` supports native debugging of `djgpp` programs, and defines a few commands specific to the `djgpp` port. This subsection describes those commands.

```
info dos
```

This is a prefix of `djgpp`-specific commands which print information about the target system and important OS structures.

```
info dos sysinfo
```

This command displays assorted information about the underlying platform: the CPU type and features, the OS version and flavor, the DPMI version, and the available conventional and DPMI memory.

```
info dos gdt
info dos ldt
info dos idt
```

These 3 commands display entries from, respectively, Global, Local, and Interrupt Descriptor Tables (GDT, LDT, and IDT). The descriptor tables are data structures which store a descriptor for each segment that is currently in use. The segment's selector is an index into a descriptor table; the table entry for that index holds the descriptor's base address and limit, and its attributes and access rights.

A typical djgpp program uses 3 segments: a code segment, a data segment (used for both data and the stack), and a DOS segment (which allows access to DOS/BIOS data structures and absolute addresses in conventional memory). However, the DPMI host will usually define additional segments in order to support the DPMI environment.

These commands allow to display entries from the descriptor tables. Without an argument, all entries from the specified table are displayed. An argument, which should be an integer expression, means display a single entry whose index is given by the argument. For example, here's a convenient way to display information about the debugged program's data segment:

```
(gdb) info dos ldt $ds                0x13f: base=0x11970000 limit=0x0009ffff 32-Bit Data
```

This comes in handy when you want to see whether a pointer is outside the data segment's limit (that is, *garbled*).

```
info dos pde
info dos pte
```

These two commands display entries from, respectively, the Page Directory and the Page Tables. Page Directories and Page Tables are data structures which control how virtual memory addresses are mapped into physical addresses. A Page Table includes an entry for every page of memory that is mapped into the program's address space; there may be several Page Tables, each one holding up to 4096 entries. A Page Directory has up to 4096 entries, one each for every Page Table that is currently in use.

Without an argument, **info dos pde** displays the entire Page Directory, and **info dos pte** displays all the entries in all of the Page Tables. An argument, an integer expression, given to the **info dos pde** command means display only that entry from the Page Directory table. An argument given to the **info dos pte** command means display entries from a single Page Table, the one pointed to by the specified entry in the Page Directory.

These commands are useful when your program uses *DMA* (Direct Memory Access), which needs physical addresses to program the DMA controller.

These commands are supported only with some DPMI servers.

```
info dos address-pte addr
```

This command displays the Page Table entry for a specified linear address. The argument linear address *addr* should already have the appropriate segment's base address added to it, because this command accepts addresses which may belong to *any* segment. For example, here's how to display the Page Table entry for the page where the variable *i* is stored:

```
(gdb) info dos address-pte __djgpp_base_address + (char *)&i          Page Table entry fo
Base=0x02698000 Dirty Acc. Not-Cached Write-Back Usr Read-Write +0xd30
```

This says that `i` is stored at offset `0xd30` from the page whose physical base address is `0x02698000`, and prints all the attributes of that page.

Note that you must cast the addresses of variables to a `char *`, since otherwise the value of `__djgpp_base_address`, the base address of all variables and functions in a djgpp program, will be added using the rules of C pointer arithmetics: if `i` is declared an `int`, gdb will add 4 times the value of `__djgpp_base_address` to the address of `i`.

Here's another example, it displays the Page Table entry for the transfer buffer:

```
(gdb) info dos address-pte *((unsigned *)&_go32_info_block + 3)      Page Table entry
      Base=0x00029000 Dirty Acc. Not-Cached Write-Back Usr Read-Write +0x110
```

(The `+ 3` offset is because the transfer buffer's address is the 3rd member of the `_go32_info_block` structure.) The output of this command clearly shows that addresses in conventional memory are mapped 1:1, that is, the physical and linear addresses are identical.

This command is supported only with some DPMI servers.

20.1.4. Features for Debugging MS Windows PE executables

`gdb` supports native debugging of MS Windows programs, including DLLs with and without symbolic debugging information. There are various additional Cygwin-specific commands, described in this subsection. The subsection (refer to Section 20.1.4.1 *Support for DLLs without debugging symbols*) describes working with DLLs that have no debugging symbols.

```
info w32
```

This is a prefix of MS Windows specific commands which print information about the target system and important OS structures.

```
info w32 selector
```

This command displays information returned by the Win32 API `GetThreadSelectorEntry` function. It takes an optional argument that is evaluated to a long value to give the information about this given selector. Without argument, this command displays information about the the six segment registers.

```
info dll
```

This is a Cygwin specific alias of `info shared`.

```
dll-symbols
```

This command loads symbols from a dll similarly to `add-sym` command but without the need to specify a base address.

```
set new-console mode
```

If `mode` is `on` the debuggee will be started in a new console on next start. If `mode` is `off`, the debuggee will be started in the same console as the debugger.

```
show new-console
```

Displays whether a new console is used when the debugger is started.

```
set new-group mode
```

This boolean value controls whether the debuggee should start a new group or stay in the same group as the debugger. This affects the way the Windows OS handles Ctrl-C.

```
show new-group
```

Displays current value of new-group boolean.

```
set debugevents
```

This boolean value adds debug output concerning events seen by the debugger.

```
set debugexec
```

This boolean value adds debug output concerning execute events seen by the debugger.

```
set debugexceptions
```

This boolean value adds debug output concerning exception events seen by the debugger.

```
set debugmemory
```

This boolean value adds debug output concerning memory events seen by the debugger.

```
set shell
```

This boolean value specifies whether the debuggee is called via a shell or directly (default value is on).

```
show shell
```

Displays if the debuggee will be started with a shell.

20.1.4.1. Support for DLLs without debugging symbols

Very often on windows, some of the DLLs that your program relies on do not include symbolic debugging information (for example, `kernel32.dll`). When `gdb` doesn't recognize any debugging symbols in a DLL, it relies on the minimal amount of symbolic information contained in the DLL's export table. This subsection describes working with such symbols, known internally to `gdb` as "minimal symbols".

Note that before the debugged program has started execution, no DLLs will have been loaded. The easiest way around this problem is simply to start the program -- either by setting a breakpoint or letting the program run once to completion. It is also possible to force `gdb` to load a particular DLL before starting the executable -- see the shared library information in (refer to Section 17.1 *Commands to specify files* or the `dll-symbols` command in (refer to Section 20.1.4 *Features for Debugging MS Windows PE executables*). Currently, explicitly loading symbols from a DLL with no debugging information will cause the symbol names to be duplicated in `gdb`'s lookup table, which may adversely affect symbol lookup performance.

20.1.4.2. DLL name prefixes

In keeping with the naming conventions used by the Microsoft debugging tools, DLL export symbols are made available with a prefix based on the DLL name, for instance `KERNEL32!CreateFileA`. The plain name is also entered into the symbol table, so `CreateFileA` is often sufficient. In some cases there will be name clashes within a program (particularly if the executable itself includes full debugging symbols) necessitating the use of the fully qualified name when referring to the contents

of the DLL. Use single-quotes around the name to avoid the exclamation mark ("!") being interpreted as a language operator.

Note that the internal name of the DLL may be all upper-case, even though the file name of the DLL is lower-case, or vice-versa. Since symbols within `gdb` are *case-sensitive* this may cause some confusion. If in doubt, try the `info functions` and `info variables` commands or even `maint print msymbols` (refer to Chapter 15 *Examining the Symbol Table*). Here's an example:

```
(gdb) info function CreateFileA
All functions matching regular expression "CreateFileA":
```

```
Non-debugging symbols:
0x77e885f4  CreateFileA
0x77e885f4  KERNEL32!CreateFileA
```

```
(gdb) info function !
All functions matching regular expression "!":
```

```
Non-debugging symbols:
0x6100114c  cygwin!__assert
0x61004034  cygwin!_dll_crt0@0
0x61004240  cygwin!dll_crt0(per_process *)
[etc...]
```

20.1.4.3. Working with minimal symbols

Symbols extracted from a DLL's export table do not contain very much type information. All that `gdb` can do is guess whether a symbol refers to a function or variable depending on the linker section that contains the symbol. Also note that the actual contents of the memory contained in a DLL are not available unless the program is running. This means that you cannot examine the contents of a variable or disassemble a function within a DLL without a running program.

Variables are generally treated as pointers and dereferenced automatically. For this reason, it is often necessary to prefix a variable name with the address-of operator ("&") and provide explicit type information in the command. Here's an example of the type of problem:

```
(gdb) print 'cygwin!__argv'
$1 = 268572168
```

```
(gdb) x 'cygwin!__argv'
0x10021610:      "\230y\ ""
```

And two possible solutions:

```
(gdb) print ((char **) 'cygwin!__argv')[0]
$2 = 0x22fd98 "/cygdrive/c/mydirectory/myprogram"
```

```
(gdb) x/2x &'cygwin1!__argv'
0x610c0aa8 <cygwin1!__argv>:    0x10021608    0x00000000
(gdb) x/x 0x10021608
0x10021608:    0x0022fd98
(gdb) x/s 0x0022fd98
0x22fd98:    "/cygdrive/c/mydirectory/myprogram"
```

Setting a break point within a DLL is possible even before the program starts execution. However, under these circumstances, `gdb` can't examine the initial instructions of the function in order to skip the function's frame set-up code. You can work around this by using `"*&"` to set the breakpoint at a raw memory address:

```
(gdb) break *&'python22!PyOS_Readline'
Breakpoint 1 at 0x1e04eff0
```

The author of these extensions is not entirely convinced that setting a break point within a shared DLL like `kernel132.dll` is completely safe.

20.2. Embedded Operating Systems

This section describes configurations involving the debugging of embedded operating systems that are available for several different architectures.

`gdb` includes the ability to debug programs running on various real-time operating systems.

20.2.1. Using `gdb` with VxWorks

```
target vxworks machinename
```

A VxWorks system, attached via TCP/IP. The argument `machinename` is the target system's machine name or IP address.

On VxWorks, `load` links `filename` dynamically on the current target system as well as adding its symbols in `gdb`.

`gdb` enables developers to spawn and debug tasks running on networked VxWorks targets from a Unix host. Already-running tasks spawned from the VxWorks shell can also be debugged. `gdb` uses code that runs on both the Unix host and on the VxWorks target. The program `gdb` is installed and executed on the Unix host. (It may be installed with the name `vxgdb`, to distinguish it from a `gdb` for debugging programs on the host itself.)

```
VxWorks-timeout args
```

All VxWorks-based targets now support the option `vxworks-timeout`. This option is set by the user, and `args` represents the number of seconds `gdb` waits for responses to `rpc`'s. You might use this if your VxWorks target is a slow software simulator or is on the far side of a thin network line.

The following information on connecting to VxWorks was current when this manual was produced; newer releases of VxWorks may use revised procedures.

To use `gdb` with VxWorks, you must rebuild your VxWorks kernel to include the remote debugging interface routines in the VxWorks library `rdb.a`. To do this, define `INCLUDE_RDB` in the VxWorks configuration file `configAll.h` and rebuild your VxWorks kernel. The resulting kernel contains `rdb.a`, and spawns the source debugging task `tRdbTask` when VxWorks is booted. For more information on configuring and remaking VxWorks, see the manufacturer's manual.

Once you have included `rdb.a` in your VxWorks system image and set your Unix execution search path to find `gdb`, you are ready to run `gdb`. From your Unix host, run `gdb` (or `vxgdb`, depending on your installation).

`gdb` comes up showing the prompt:

```
(vxgdb)
```

20.2.1.1. Connecting to VxWorks

The `gdb` command `target` lets you connect to a VxWorks target on the network. To connect to a target whose host name is "tt", type:

```
(vxgdb) target vxworks tt
```

`gdb` displays messages like these:

```
Attaching remote machine across net...
Connected to tt.
```

`gdb` then attempts to read the symbol tables of any object modules loaded into the VxWorks target since it was last booted. `gdb` locates these files by searching the directories listed in the command search path (refer to Section 6.4 *Your program's environment*); if it fails to find an object file, it displays a message such as:

```
prog.o: No such file or directory.
```

When this happens, add the appropriate directory to the search path with the `gdb` command `path`, and execute the `target` command again.

20.2.1.2. VxWorks download

If you have connected to the VxWorks target and you want to debug an object that has not yet been loaded, you can use the `gdb` `load` command to download a file from Unix to VxWorks incrementally. The object file given as an argument to the `load` command is actually opened twice: first by the VxWorks target in order to download the code, then by `gdb` in order to read the symbol table. This can lead to problems if the current working directories on the two systems differ. If both systems have NFS mounted the same filesystems, you can avoid these problems by using absolute paths. Otherwise, it is simplest to set the working directory on both systems to the directory in which the object file resides, and then to reference the file by its name, without any path. For instance, a program `prog.o` may reside in `vxpath/vw/demo/rdb` in VxWorks and in `hostpath/vw/demo/rdb` on the host. To load this program, type this on VxWorks:

```
-> cd "vxpath/vw/demo/rdb"
```

Then, in gdb, type:

```
(vxgdb) cd hostpath/vw/demo/rdb
(vxgdb) load prog.o
```

gdb displays a response similar to this:

```
Reading symbol data from wherever/vw/demo/rdb/prog.o... done.
```

You can also use the `load` command to reload an object module after editing and recompiling the corresponding source file. Note that this makes gdb delete all currently-defined breakpoints, auto-displays, and convenience variables, and to clear the value history. (This is necessary in order to preserve the integrity of debugger's data structures that reference the target system's symbol table.)

20.2.1.3. Running tasks

You can also attach to an existing task using the `attach` command as follows:

```
(vxgdb) attach task
```

where `task` is the VxWorks hexadecimal task ID. The task can be running or suspended when you attach to it. Running tasks are suspended at the time of attachment.

20.3. Embedded Processors

This section goes into details specific to particular embedded configurations.

20.3.1. ARM

```
target rdi dev
```

ARM Angel monitor, via RDI library interface to ADP protocol. You may use this target to communicate with both boards running the Angel monitor, or with the EmbeddedICE JTAG debug device.

```
target rdp dev
```

ARM Demon monitor.

20.3.2. Hitachi H8/300

```
target hms dev
```

A Hitachi SH, H8/300, or H8/500 board, attached via serial line to your host. Use special commands `device` and `speed` to control the serial line and the communications speed used.

```
target e7000 dev
```

E7000 emulator for Hitachi H8 and SH.

```
target sh3 dev
```

```
target sh3e dev
```

Hitachi SH-3 and SH-3E target systems.

When you select remote debugging to a Hitachi SH, H8/300, or H8/500 board, the `load` command downloads your program to the Hitachi board and also opens it as the current executable target for `gdb` on your host (like the `file` command).

`gdb` needs to know these things to talk to your Hitachi SH, H8/300, or H8/500:

1. that you want to use `target hms`, the remote debugging interface for Hitachi microprocessors, or `target e7000`, the in-circuit emulator for the Hitachi SH and the Hitachi 300H. (`target hms` is the default when `gdb` is configured specifically for the Hitachi SH, H8/300, or H8/500.)
2. what serial device connects your host to your Hitachi board (the first serial device available on your host is the default).
3. what speed to use over the serial device.

20.3.2.1. Connecting to Hitachi boards

Use the special `gdb` command `device port` if you need to explicitly set the serial device. The default `port` is the first available port on your host. This is only necessary on Unix hosts, where it is typically something like `/dev/ttya`.

`gdb` has another special command to set the communications speed: `speed bps`. This command also is only used from Unix hosts; on DOS hosts, set the line speed as usual from outside `gdb` with the DOS `mode` command (for instance, `mode com2:9600,n,8,1,p` for a 9600bps connection).

The `device` and `speed` commands are available only when you use a Unix host to debug your Hitachi microprocessor programs. If you use a DOS host, `gdb` depends on an auxiliary terminate-and-stay-resident program called `asynctr` to communicate with the development board through a PC serial port. You must also use the DOS `mode` command to set up the serial port on the DOS side.

The following sample session illustrates the steps needed to start a program under `gdb` control on an H8/300. The example uses a sample H8/300 program called `t.x`. The procedure is the same for the Hitachi SH and the H8/500.

First hook up your development board. In this example, we use a board attached to serial port `COM2`; if you use a different serial port, substitute its name in the argument of the `mode` command. When you call `asynctr`, the auxiliary comms program used by the debugger, you give it just the numeric part of the serial port's name; for example, `asynctr 2` below runs `asynctr` on `COM2`.

```
C:\H8300\TEST> asynctr 2
C:\H8300\TEST> mode com2:9600,n,8,1,p
```

```
Resident portion of MODE loaded
```

```
COM2: 9600, n, 8, 1, p
```

Warning: We have noticed a bug in PC-NFS that conflicts with `asynctsr`. If you also run PC-NFS on your DOS host, you may need to disable it, or even boot without it, to use `asynctsr` to control your development board.

Now that serial communications are set up, and the development board is connected, you can start up `gdb`. Call `gdb` with the name of your program as the argument. `gdb` prompts you, as usual, with the prompt `(gdb)`. Use two special commands to begin your debugging session: `target hms` to specify cross-debugging to the Hitachi board, and the `load` command to download your program to the board. `load` displays the names of the program's sections, and a * for each 2K of data downloaded. (If you want to refresh `gdb` data on symbols or on the executable file without downloading, use the `gdb` commands `file` or `symbol-file`. These commands, and `load` itself, are described in (refer to Section 17.1 *Commands to specify files*.)

```
(eg-C:\H8300\TEST) gdb t.x
gdb is free software and you are welcome to distribute copies
of it under certain conditions; type "show copying" to see
the conditions.
There is absolutely no warranty for gdb; type "show warranty"
for details.
gdb 2003-07-22-cvs, Copyright 1992 Free Software Foundation, Inc...
(gdb) target hms
Connected to remote H8/300 HMS system.
(gdb) load t.x
.text   : 0x8000 .. 0xabde *****
.data   : 0xabde .. 0xad30 *
.stack  : 0xf000 .. 0xf014 *
```

At this point, you're ready to run or debug your program. From here on, you can use all the usual `gdb` commands. The `break` command sets breakpoints; the `run` command starts your program; `print` or `x` display data; the `continue` command resumes execution after stopping at a breakpoint. You can use the `help` command at any time to find out more about `gdb` commands.

Remember, however, that *operating system* facilities aren't available on your development board; for example, if your program hangs, you can't send an interrupt--but you can press the reset switch!

Use the reset button on the development board

- to interrupt your program (don't use `ctrl-C` on the DOS host--it has no way to pass an interrupt signal to the development board); and
- to return to the `gdb` command prompt after your program finishes normally. The communications protocol provides no other way for `gdb` to detect program completion.

In either case, `gdb` sees the effect of a reset on the development board as a "normal exit" of your program.

20.3.2.2. Using the E7000 in-circuit emulator

You can use the E7000 in-circuit emulator to develop code for either the Hitachi SH or the H8/300H. Use one of these forms of the `target e7000` command to connect `gdb` to your E7000:

```
target e7000 port speed
```

Use this form if your E7000 is connected to a serial port. The `port` argument identifies what serial port to use (for example, `com2`). The third argument is the line speed in bits per second (for example, `9600`).

```
target e7000 hostname
```

If your E7000 is installed as a host on a TCP/IP network, you can just specify its hostname; `gdb` uses `telnet` to connect.

20.3.2.3. Special gdb commands for Hitachi micros

Some `gdb` commands are available only for the H8/300:

```
set machine h8300
set machine h8300h
```

Condition `gdb` for one of the two variants of the H8/300 architecture with `set machine`. You can use `show machine` to check which variant is currently in effect.

20.3.3. H8/500

```
set memory mod
show memory
```

Specify which H8/500 memory model (`mod`) you are using with `set memory`; check which memory model is in effect with `show memory`. The accepted values for `mod` are `small`, `big`, `medium`, and `compact`.

20.3.4. Mitsubishi M32R/D

```
target m32r dev
```

Mitsubishi M32R/D ROM monitor.

20.3.5. M68k

The Motorola m68k configuration includes ColdFire support, and `target` command for the following ROM monitors.

```
target abug dev
```

ABug ROM monitor for M68K.

```
target cpu32bug dev
```

CPU32BUG monitor, running on a CPU32 (M68K) board.

```
target dbug dev
```

dBUG ROM monitor for Motorola ColdFire.

```
target est dev
```

EST-300 ICE monitor, running on a CPU32 (M68K) board.

```
target rom68k dev
```

ROM 68K monitor, running on an M68K IDP board.

```
target rombug dev
```

ROMBUG ROM monitor for OS/9000.

20.3.6. MIPS Embedded

`gdb` can use the MIPS remote debugging protocol to talk to a MIPS board attached to a serial line. This is available when you configure `gdb` with `-target=mips-idt-ecoff`.

Use these `gdb` commands to specify the connection to your target board:

```
target mips port
```

To run a program on the board, start up `gdb` with the name of your program as the argument. To connect to the board, use the command `target mips port`, where `port` is the name of the serial port connected to the board. If the program has not already been downloaded to the board, you may use the `load` command to download it. You can then use all the usual `gdb` commands.

For example, this sequence connects to the target board through a serial port, and loads and runs a program called `prog` through the debugger:

```
host$ gdb prog
gdb is free software and ...
(gdb) target mips /dev/ttyb
(gdb) load prog
(gdb) run
```

```
target mips hostname:portnumber
```

On some `gdb` host configurations, you can specify a TCP connection (for instance, to a serial line managed by a terminal concentrator) instead of a serial port, using the syntax `hostname:portnumber`.

```
target pmon port
```

PMON ROM monitor.

```
target ddb port
```

NEC's DDB variant of PMON for Vr4300.

```
target lsi port
```

LSI variant of PMON.

```
target r3900 dev
```

Densan DVE-R3900 ROM monitor for Toshiba R3900 Mips.

```
target array dev
```

Array Tech LSI33K RAID controller board.

`gdb` also supports these special commands for MIPS targets:

```
set processor args
```

```
show processor
```

Use the `set processor` command to set the type of MIPS processor when you want to access processor-type-specific registers. For example, `set processor r3041` tells `gdb` to use the CPU registers appropriate for the 3041 chip. Use the `show processor` command to see what MIPS processor `gdb` is using. Use the `info reg` command to see what registers `gdb` is using.

```
set mipsfpu double
```

```
set mipsfpu single
```

```
set mipsfpu none
```

```
show mipsfpu
```

If your target board does not support the MIPS floating point coprocessor, you should use the command `set mipsfpu none` (if you need this, you may wish to put the command in your `gdb` init file). This tells `gdb` how to find the return value of functions which return floating point values. It also allows `gdb` to avoid saving the floating point registers when calling functions on the board. If you are using a floating point coprocessor with only single precision floating point support, as on the `r4650` processor, use the command `set mipsfpu single`. The default double precision floating point coprocessor may be selected using `set mipsfpu double`.

In previous versions the only choices were double precision or no floating point, so `set mipsfpu on` will select double precision and `set mipsfpu off` will select no floating point.

As usual, you can inquire about the `mipsfpu` variable with `show mipsfpu`.

```
set remotedebug n
```

```
show remotedebug
```

You can see some debugging information about communications with the board by setting the `remotedebug` variable. If you set it to 1 using `set remotedebug 1`, every packet is displayed. If you set it to 2, every character is displayed. You can check the current value at any time with the command `show remotedebug`.

```
set timeout seconds
```

```
set retransmit-timeout seconds
```

```
show timeout
```

```
show retransmit-timeout
```

You can control the timeout used while waiting for a packet, in the MIPS remote protocol, with the `set timeout seconds` command. The default is 5 seconds. Similarly, you can control the timeout used while waiting for an acknowledgement of a packet with the `set retransmit-timeout seconds` command. The default is 3 seconds. You can inspect both values with `show timeout` and `show retransmit-timeout`. (These commands are *only* available when `gdb` is configured for `-target=mips-idt-ecoff`.)

The timeout set by `set timeout` does not apply when `gdb` is waiting for your program to stop. In that case, `gdb` waits forever because it has no way of knowing how long the program is going to run before stopping.

20.3.7. OpenRISC 1000

See OR1k Architecture document (www.opencores.org) for more information about platform and commands.

```
target jtag jtag://host:port
```

Connects to remote JTAG server. JTAG remote server can be either an orlksim or JTAG server, connected via parallel port to the board.

Example: `target jtag jtag://localhost:9999`

```
orlksim command
```

If connected to orlksim OpenRISC 1000 Architectural Simulator, proprietary commands can be executed.

```
info orlk spr
```

Displays spr groups.

```
info orlk spr group
```

```
info orlk spr groupno
```

Displays register names in selected group.

```
info orlk spr group register
```

```
info orlk spr register
```

```
info orlk spr groupno registerno
```

```
info orlk spr registerno
```

Shows information about specified spr register.

```
spr group register value
```

```
spr register value
```

```
spr groupno registerno value
```

```
spr registerno value
```

Writes value to specified spr register.

Some implementations of OpenRISC 1000 Architecture also have hardware trace. It is very similar to gdb trace, except it does not interfere with normal program execution and is thus much faster. Hardware breakpoints/watchpoint triggers can be set using:

```
$LEA/$LDATA
```

Load effective address/data

```
$SEA/$SDATA
```

Store effective address/data

```
$AEA/$ADATA
```

Access effective address (\$SEA or \$LEA) or data (\$SDATA/\$LDATA)

```
$FETCH
```

Fetch data

When triggered, it can capture low level data, like: PC, LSEA, LDATA, SDATA, READSPR, WRITESPR, INSTR.

httrace commands:

hwatch conditional

Set hardware watchpoint on combination of Load/Store Effective Address(es) or Data. For example:

```
hwatch ($LEA == my_var) && ($LDATA < 50) || ($SEA == my_var) &&
($SDATA >= 50)
```

```
hwatch ($LEA == my_var) && ($LDATA < 50) || ($SEA == my_var) &&
($SDATA >= 50)
```

htrace info

Display information about current HW trace configuration.

htrace trigger conditional

Set starting criteria for HW trace.

htrace qualifier conditional

Set acquisition qualifier for HW trace.

htrace stop conditional

Set HW trace stopping criteria.

htrace record [data]*

Selects the data to be recorded, when qualifier is met and HW trace was triggered.

htrace enable

htrace disable

Enables/disables the HW trace.

htrace rewind [filename]

Clears currently recorded trace data.

If filename is specified, new trace file is made and any newly collected data will be written there.

htrace print [start [len]]

Prints trace buffer, using current record configuration.

htrace mode continuous

Set continuous trace mode.

htrace mode suspend

Set suspend trace mode.

20.3.8. PowerPC

```
target dink32 dev
```

DINK32 ROM monitor.

```
target ppcbug dev
```

```
target ppcbug1 dev
```

PPCBUG ROM monitor for PowerPC.

```
target sds dev
```

SDS monitor, running on a PowerPC board (such as Motorola's ADS).

20.3.9. HP PA Embedded

```
target op50n dev
```

OP50N monitor, running on an OKI HPPA board.

```
target w89k dev
```

W89K monitor, running on a Winbond HPPA board.

20.3.10. Hitachi SH

```
target hms dev
```

A Hitachi SH board attached via serial line to your host. Use special commands `device` and `speed` to control the serial line and the communications speed used.

```
target e7000 dev
```

E7000 emulator for Hitachi SH.

```
target sh3 dev
```

```
target sh3e dev
```

Hitachi SH-3 and SH-3E target systems.

20.3.11. Tsquare Sparclet

`gdb` enables developers to debug tasks running on Sparclet targets from a Unix host. `gdb` uses code that runs on both the Unix host and on the Sparclet target. The program `gdb` is installed and executed on the Unix host.

`gdb` displays messages like these:

```
Connected to ttya.
```

20.3.11.3. Sparclet download

Once connected to the Sparclet target, you can use the `gdb load` command to download the file from the host to the target. The file name and load offset should be given as arguments to the `load` command. Since the file format is `aout`, the program must be loaded to the starting address. You can use `objdump` to find out what this value is. The load offset is an offset which is added to the VMA (virtual memory address) of each of the file's sections. For instance, if the program `prog` was linked to text address `0x1201000`, with data at `0x12010160` and bss at `0x12010170`, in `gdb`, type:

```
(gdb) load prog 0x12010000
Loading section .text, size 0xdb0 vma 0x12010000
```

If the code is loaded at a different address than what the program was linked to, you may need to use the `section` and `add-symbol-file` commands to tell `gdb` where to map the symbol table.

20.3.11.4. Running and debugging

You can now begin debugging the task using `gdb`'s execution control commands, `b`, `step`, `run`, etc. See the `gdb` manual for the list of commands.

```
(gdb) b main
Breakpoint 1 at 0x12010000: file prog.c, line 3.
(gdb) run
Starting program: prog
Breakpoint 1, main (argc=1, argv=0xeffff21c) at prog.c:3
3     char *symarg = 0;
(gdb) step
4     char *execarg = "hello!";
(gdb)
```

20.3.12. Fujitsu Sparclite

```
target sparclite dev
```

Fujitsu sparclite boards, used only for the purpose of loading. You must use an additional command to debug the program. For example: `target remote dev` using `gdb` standard remote protocol.

20.3.13. Tandem ST2000

`gdb` may be used with a Tandem ST2000 phone switch, running Tandem's STDEBUG protocol.

To connect your ST2000 to the host system, see the manufacturer's manual. Once the ST2000 is physically attached, you can run:

```
target st2000 dev speed
```

to establish it as your debugging environment. `dev` is normally the name of a serial device, such as `/dev/ttya`, connected to the ST2000 via a serial line. You can instead specify `dev` as a TCP connection (for example, to a serial line attached via a terminal concentrator) using the syntax `hostname:portnumber`.

The `load` and `attach` commands are *not* defined for this target; you must load your program into the ST2000 as you normally would for standalone operation. `gdb` reads debugging information (such as symbols) from a separate, debugging version of the program available on your host computer.

These auxiliary `gdb` commands are available to help you with the ST2000 environment:

```
st2000 command
```

Send a command to the STDEBUG monitor. See the manufacturer's manual for available commands.

```
connect
```

Connect the controlling terminal to the STDEBUG command monitor. When you are done interacting with STDEBUG, typing either of two character sequences gets you back to the `gdb` command prompt: `[RET]~.` (Return, followed by tilde and period) or `[RET]~[C-d]` (Return, followed by tilde and control-D).

20.3.14. Zilog Z8000

When configured for debugging Zilog Z8000 targets, `gdb` includes a Z8000 simulator.

For the Z8000 family, `target sim` simulates either the Z8002 (the unsegmented variant of the Z8000 architecture) or the Z8001 (the segmented variant). The simulator recognizes which architecture is appropriate by inspecting the object code.

```
target sim args
```

Debug programs on a simulated CPU. If the simulator supports setup options, specify them via `args`.

After specifying this target, you can debug programs for the simulated CPU in the same style as programs for your host computer; use the `file` command to load a new program image, the `run` command to run your program, and so on.

As well as making available all the usual machine registers (refer to Section 10.10 *Registers*), the Z8000 simulator provides three additional items of information as specially named registers:

```
cycles
```

Counts clock-ticks in the simulator.

```
insts
```

Counts instructions run in the simulator.

time

Execution time in 60ths of a second.

You can refer to these values in `gdb` expressions with the usual conventions; for example, `b fputc if $cycles>5000` sets a conditional breakpoint that suspends only after at least 5000 simulated clock ticks.

20.4. Architectures

This section describes characteristics of architectures that affect all uses of `gdb` with the architecture, both native and cross.

20.4.1. A29K

```
set rstack_high_address address
```

On AMD 29000 family processors, registers are saved in a separate *register stack*. There is no way for `gdb` to determine the extent of this stack. Normally, `gdb` just assumes that the stack is "large enough". This may result in `gdb` referencing memory locations that do not exist. If necessary, you can get around this problem by specifying the ending address of the register stack with the `set rstack_high_address` command. The argument should be an address, which you probably want to precede with `0x` to specify in hexadecimal.

```
show rstack_high_address
```

Display the current limit of the register stack, on AMD 29000 family processors.

20.4.2. Alpha

See the following section.

20.4.3. MIPS

Alpha- and MIPS-based computers use an unusual stack frame, which sometimes requires `gdb` to search backward in the object code to find the beginning of a function.

To improve response time (especially for embedded applications, where `gdb` may be restricted to a slow serial line for this search) you may want to limit the size of this search, using one of these commands:

```
set heuristic-fence-post limit
```

Restrict `gdb` to examining at most `limit` bytes in its search for the beginning of a function. A value of 0 (the default) means there is no limit. However, except for 0, the larger the limit the more bytes `heuristic-fence-post` must search and therefore the longer it takes to run.

```
show heuristic-fence-post
```

Display the current limit.

These commands are available *only* when `gdb` is configured for debugging programs on Alpha or MIPS processors.

You can alter the way `gdb` interacts with you by using the `set` command. For commands controlling how `gdb` displays data, (refer to Section 10.7 *Print settings*). Other settings are described here.

21.1. Prompt

`gdb` indicates its readiness to read a command by printing a string called the *prompt*. This string is normally `(gdb)`. You can change the prompt string with the `set prompt` command. For instance, when debugging `gdb` with `gdb`, it is useful to change the prompt in one of the `gdb` sessions so that you can always tell which one you are talking to.

Note: `set prompt` does not add a space for you after the prompt you set. This allows you to set a prompt which ends in a space or a prompt that does not.

```
set prompt newprompt
```

Directs `gdb` to use `newprompt` as its prompt string henceforth.

```
show prompt
```

Prints a line of the form: `Gdb's prompt is: your-prompt`

21.2. Command editing

`gdb` reads its input commands via the *readline* interface. This `gnu` library provides consistent behavior for programs which provide a command line interface to the user. Advantages are `gnu Emacs`-style or *vi*-style inline editing of commands, `csh`-like history substitution, and a storage and recall of command history across debugging sessions.

You may control the behavior of command line editing in `gdb` with the command `set`.

```
set editing
```

```
set editing on
```

Enable command line editing (enabled by default).

```
set editing off
```

Disable command line editing.

```
show editing
```

Show whether command line editing is enabled.

21.3. Command history

`gdb` can keep track of the commands you type during your debugging sessions, so that you can be certain of precisely what happened. Use these commands to manage the `gdb` command history facility.

```
set history filename fname
```

Set the name of the gdb command history file to `fname`. This is the file where gdb reads an initial command history list, and where it writes the command history from this session when it exits. You can access this list through history expansion or through the history command editing characters listed below. This file defaults to the value of the environment variable `GDBHISTFILE`, or to `./gdb_history` (`./_gdb_history` on MS-DOS) if this variable is not set.

```
set history save
set history save on
```

Record command history in a file, whose name may be specified with the `set history filename` command. By default, this option is disabled.

```
set history save off
```

Stop recording command history in a file.

```
set history size size
```

Set the number of commands which gdb keeps in its history list. This defaults to the value of the environment variable `HISTSIZE`, or to 256 if this variable is not set.

History expansion assigns special meaning to the character `!`.

Since `!` is also the logical not operator in C, history expansion is off by default. If you decide to enable history expansion with the `set history expansion on` command, you may sometimes need to follow `!` (when it is used as logical not, in an expression) with a space or a tab to prevent it from being expanded. The readline history facilities do not attempt substitution on the strings `!=` and `! (`, even when history expansion is enabled.

The commands to control history expansion are:

```
set history expansion on
set history expansion
```

Enable history expansion. History expansion is off by default.

```
set history expansion off
```

Disable history expansion.

The readline code comes with more complete documentation of editing and history expansion features. Users unfamiliar with gnu Emacs or vi may wish to read it.

```
show history
show history filename
show history save
show history size
show history expansion
```

These commands display the state of the gdb history parameters. `show history` by itself displays all four states.

```
show commands
```

Display the last ten commands in the command history.

```
show commands n
```

Print ten commands centered on command number `n`.

```
show commands +
```

Print ten commands just after the commands last printed.

21.4. Screen size

Certain commands to `gdb` may produce large amounts of information output to the screen. To help you read all of it, `gdb` pauses and asks you for input at the end of each page of output. Type `[RET]` when you want to continue the output, or `q` to discard the remaining output. Also, the screen width setting determines when to wrap lines of output. Depending on what is being printed, `gdb` tries to break the line at a readable place, rather than simply letting it overflow onto the following line.

Normally `gdb` knows the size of the screen from the terminal driver software. For example, on Unix `gdb` uses the `termcap` data base together with the value of the `TERM` environment variable and the `stty rows` and `stty cols` settings. If this is not correct, you can override it with the `set height` and `set width` commands:

```
set height lpp
show height
set width cpl
show width
```

These `set` commands specify a screen height of `lpp` lines and a screen width of `cpl` characters. The associated `show` commands display the current settings.

If you specify a height of zero lines, `gdb` does not pause during output no matter how long the output is. This is useful if output is to a file or to an editor buffer.

Likewise, you can specify `set width 0` to prevent `gdb` from wrapping its output.

21.5. Numbers

You can always enter numbers in octal, decimal, or hexadecimal in `gdb` by the usual conventions: octal numbers begin with `0`, decimal numbers end with `.`, and hexadecimal numbers begin with `0x`. Numbers that begin with none of these are, by default, entered in base 10; likewise, the default display for numbers--when no particular format is specified--is base 10. You can change the default base for both input and output with the `set radix` command.

```
set input-radix base
```

Set the default base for numeric input. Supported choices for `base` are decimal 8, 10, or 16. `base` must itself be specified either unambiguously or using the current default radix; for example, any of

```
set radix 012
set radix 10.
set radix 0xa
```

sets the base to decimal. On the other hand, `set radix 10` leaves the radix unchanged no matter what it was.

```
set output-radix base
```

Set the default base for numeric display. Supported choices for `base` are decimal 8, 10, or 16. `base` must itself be specified either unambiguously or using the current default radix.

```
show input-radix
```

Display the current default base for numeric input.

```
show output-radix
```

Display the current default base for numeric display.

21.6. Configuring the current ABI

gdb can determine the *ABI* (Application Binary Interface) of your application automatically. However, sometimes you need to override its conclusions. Use these commands to manage gdb's view of the current ABI.

One gdb configuration can debug binaries for multiple operating system targets, either via remote debugging or native emulation. gdb will autodetect the *OS ABI* (Operating System ABI) in use, but you can override its conclusion using the `set osabi` command. One example where this is useful is in debugging of binaries which use an alternate C library (e.g. uClibc for gnu/Linux) which does not have the same identifying marks that the standard C library for your platform provides.

```
show osabi
```

Show the OS ABI currently in use.

```
set osabi
```

With no argument, show the list of registered available OS ABI's.

```
set osabi abi
```

Set the current OS ABI to `abi`.

Generally, the way that an argument of type `float` is passed to a function depends on whether the function is prototyped. For a prototyped (that is, ANSI/ISO style) function, `float` arguments are passed unchanged, according to the architecture's convention for `float`. For unprototyped (that is, K&R style) functions, `float` arguments are first promoted to type `double` and then passed.

Unfortunately, some forms of debug information do not reliably indicate whether a function is prototyped. If gdb calls a function that is not marked as prototyped, it consults **set coerce-float-to-double**.

```
set coerce-float-to-double
```

```
set coerce-float-to-double on
```

Arguments of type `float` will be promoted to `double` when passed to an unprototyped function. This is the default setting.

```
set coerce-float-to-double off
```

Arguments of type `float` will be passed directly to unprototyped functions.

gdb needs to know the ABI used for your program's C++ objects. The correct C++ ABI depends on which C++ compiler was used to build your application. gdb only fully supports programs with a single C++ ABI; if your program contains code using multiple C++ ABI's or if gdb can not identify your program's ABI correctly, you can tell gdb which ABI to use. Currently supported ABI's include

"gnu-v2", for g++ versions before 3.0, "gnu-v3", for g++ versions 3.0 and later, and "hpaCC" for the HP ANSI C++ compiler. Other C++ compilers may use the "gnu-v2" or "gnu-v3" ABI's as well. The default setting is "auto".

```
show cp-abi
```

Show the C++ ABI currently in use.

```
set cp-abi
```

With no argument, show the list of supported C++ ABI's.

```
set cp-abi abi
set cp-abi auto
```

Set the current C++ ABI to *abi*, or return to automatic detection.

21.7. Optional warnings and messages

By default, gdb is silent about its inner workings. If you are running on a slow machine, you may want to use the `set verbose` command. This makes gdb tell you when it does a lengthy internal operation, so you will not think it has crashed.

Currently, the messages controlled by `set verbose` are those which announce that the symbol table for a source file is being read; see `symbol-file` in (refer to Section 17.1 *Commands to specify files*).

```
set verbose on
```

Enables gdb output of certain informational messages.

```
set verbose off
```

Disables gdb output of certain informational messages.

```
show verbose
```

Displays whether `set verbose` is on or off.

By default, if gdb encounters bugs in the symbol table of an object file, it is silent; but if you are debugging a compiler, you may find this information useful (refer to Section 17.3 *Errors reading symbol files*).

```
set complaints limit
```

Permits gdb to output `limit` complaints about each type of unusual symbols before becoming silent about the problem. Set `limit` to zero to suppress all complaints; set it to a large number to prevent complaints from being suppressed.

```
show complaints
```

Displays how many symbol complaints gdb is permitted to produce.

By default, gdb is cautious, and asks what sometimes seems to be a lot of stupid questions to confirm certain commands. For example, if you try to run a program which is already running:

```
(gdb) run
The program being debugged has been started already.
Start it from the beginning? (y or n)
```

If you are willing to unflinchingly face the consequences of your own commands, you can disable this "feature":

```
set confirm off
```

Disables confirmation requests.

```
set confirm on
```

Enables confirmation requests (the default).

```
show confirm
```

Displays state of confirmation requests.

21.8. Optional messages about internal happenings

```
set debug arch
```

Turns on or off display of gdbarch debugging info. The default is off.

```
show debug arch
```

Displays the current state of displaying gdbarch debugging info.

```
set debug event
```

Turns on or off display of gdb event debugging info. The default is off.

```
show debug event
```

Displays the current state of displaying gdb event debugging info.

```
set debug expression
```

Turns on or off display of gdb expression debugging info. The default is off.

```
show debug expression
```

Displays the current state of displaying gdb expression debugging info.

```
set debug frame
```

Turns on or off display of gdb frame debugging info. The default is off.

```
show debug frame
```

Displays the current state of displaying gdb frame debugging info.

```
set debug overload
```

Turns on or off display of gdb C++ overload debugging info. This includes info such as ranking of functions, etc. The default is off.

```
show debug overload
```

Displays the current state of displaying gdb C++ overload debugging info.

`set debug remote`

Turns on or off display of reports on all packets sent back and forth across the serial line to the remote machine. The info is printed on the gdb standard output stream. The default is off.

`show debug remote`

Displays the state of display of remote packets.

`set debug serial`

Turns on or off display of gdb serial debugging info. The default is off.

`show debug serial`

Displays the current state of displaying gdb serial debugging info.

`set debug target`

Turns on or off display of gdb target debugging info. This info includes what is going on at the target level of GDB, as it happens. The default is off.

`show debug target`

Displays the current state of displaying gdb target debugging info.

`set debug varobj`

Turns on or off display of gdb variable object debugging info. The default is off.

`show debug varobj`

Displays the current state of displaying gdb variable object debugging info.

Canned Sequences of Commands

Aside from breakpoint commands (refer to Section 7.1.7 *Breakpoint command lists*), `gdb` provides two ways to store sequences of commands for execution as a unit: user-defined commands and command files.

22.1. User-defined commands

A *user-defined command* is a sequence of `gdb` commands to which you assign a new name as a command. This is done with the `define` command. User commands may accept up to 10 arguments separated by whitespace. Arguments are accessed within the user command via `$arg0...$arg9`. A trivial example:

```
define adder
  print $arg0 + $arg1 + $arg2
```

To execute the command use:

```
adder 1 2 3
```

This defines the command `adder`, which prints the sum of its three arguments. Note the arguments are text substitutions, so they may reference variables, use complex expressions, or even perform inferior functions calls.

```
define commandname
```

Define a command named `commandname`. If there is already a command by that name, you are asked to confirm that you want to redefine it.

The definition of the command is made up of other `gdb` command lines, which are given following the `define` command. The end of these commands is marked by a line containing `end`.

```
if
```

Takes a single argument, which is an expression to evaluate. It is followed by a series of commands that are executed only if the expression is true (nonzero). There can then optionally be a line `else`, followed by a series of commands that are only executed if the expression was false. The end of the list is marked by a line containing `end`.

```
while
```

The syntax is similar to `if`: the command takes a single argument, which is an expression to evaluate, and must be followed by the commands to execute, one per line, terminated by an `end`. The commands are executed repeatedly as long as the expression evaluates to true.

```
document commandname
```

Document the user-defined command `commandname`, so that it can be accessed by `help`. The command `commandname` must already be defined. This command reads lines of documentation just as `define` reads the lines of the command definition, ending with `end`. After the `document` command is finished, `help on command commandname` displays the documentation you have written.

You may use the `document` command again to change the documentation of a command. Re-defining the command with `define` does not change the documentation.

```
help user-defined
```

List all user-defined commands, with the first line of the documentation (if any) for each.

```
show user
show user commandname
```

Display the `gdb` commands used to define `commandname` (but not its documentation). If no `commandname` is given, display the definitions for all user-defined commands.

```
show max-user-call-depth
set max-user-call-depth
```

The value of `max-user-call-depth` controls how many recursion levels are allowed in user-defined commands before GDB suspects an infinite recursion and aborts the command.

When user-defined commands are executed, the commands of the definition are not printed. An error in any command stops execution of the user-defined command.

If used interactively, commands that would ask for confirmation proceed without asking when used inside a user-defined command. Many `gdb` commands that normally print messages to say what they are doing omit the messages when used in a user-defined command.

22.2. User-defined command hooks

You may define *hooks*, which are a special kind of user-defined command. Whenever you run the command `foo`, if the user-defined command `hook-foo` exists, it is executed (with no arguments) before that command.

A hook may also be defined which is run after the command you executed. Whenever you run the command `foo`, if the user-defined command `hookpost-foo` exists, it is executed (with no arguments) after that command. Post-execution hooks may exist simultaneously with pre-execution hooks, for the same command.

It is valid for a hook to call the command which it hooks. If this occurs, the hook is not re-executed, thereby avoiding infinite recursion.

In addition, a pseudo-command, `stop` exists. Defining (`hook-stop`) makes the associated commands execute every time execution stops in your program: before breakpoint commands are run, displays are printed, or the stack frame is printed.

For example, to ignore `SIGALRM` signals while single-stepping, but treat them normally during normal execution, you could define:

```
define hook-stop
handle SIGALRM nopass
end

define hook-run
```

```

handle SIGALRM pass
end

define hook-continue
handle SIGLARM pass
end

```

As a further example, to hook at the beginning and end of the `echo` command, and to add extra text to the beginning and end of the message, you could define:

```

define hook-echo
echo <<<---
end

define hookpost-echo
echo --->>>\n
end

(gdb) echo Hello World
<<<---Hello World--->>>
(gdb)

```

You can define a hook for any single-word command in `gdb`, but not for command aliases; you should define a hook for the basic command name, e.g. `backtrace` rather than `bt`. If an error occurs during the execution of your hook, execution of `gdb` commands stops and `gdb` issues a prompt (before the command that you actually typed had a chance to run).

If you try to define a hook which does not match any known command, you get a warning from the `define` command.

22.3. Command files

A command file for `gdb` is a file of lines that are `gdb` commands. Comments (lines starting with `#`) may also be included. An empty line in a command file does nothing; it does not mean to repeat the last command, as it would from the terminal.

When you start `gdb`, it automatically executes commands from its *init files*, normally called `.gdbinit`¹. During startup, `gdb` does the following:

1. Reads the init file (if any) in your home directory².
2. Processes command line options and operands.
3. Reads the init file (if any) in the current working directory.
4. Reads command files specified by the `-x` option.

The init file in your home directory can set options (such as `set complaints`) that affect subsequent processing of command line options and operands. Init files are not executed if you use the `-nx` option (refer to Section 4.1.2 *Choosing modes*).

-
1. The DJGPP port of `gdb` uses the name `gdb.ini` instead, due to the limitations of file names imposed by DOS filesystems.
 2. On DOS/Windows systems, the home directory is the one pointed to by the `HOME` environment variable.

On some configurations of gdb, the init file is known by a different name (these are typically environments where a specialized form of gdb may need to coexist with other forms, hence a different name for the specialized version's init file). These are the environments with special init file names:

- VxWorks (Wind River Systems real-time OS): `.vxgdbinit`
- OS68K (Enea Data Systems real-time OS): `.os68gdbinit`
- ES-1800 (Ericsson Telecom AB M68000 emulator): `.esgdbinit`

You can also request the execution of a command file with the `source` command:

```
source filename
```

Execute the command file `filename`.

The lines in a command file are executed sequentially. They are not printed as they are executed. An error in any command terminates execution of the command file and control is returned to the console.

Commands that would ask for confirmation if used interactively proceed without asking when used in a command file. Many gdb commands that normally print messages to say what they are doing omit the messages when called from command files.

gdb also accepts command input from standard input. In this mode, normal output goes to standard output and error output goes to standard error. Errors in a command file supplied on standard input do not terminate execution of the command file -- execution continues with the next command.

```
gdb < cmds > log 2>&1
```

(The syntax above will vary depending on the shell used.) This example will execute commands from the file `cmds`. All output and errors would be directed to `log`.

22.4. Commands for controlled output

During the execution of a command file or a user-defined command, normal gdb output is suppressed; the only output that appears is what is explicitly printed by the commands in the definition. This section describes three commands useful for generating exactly the output you want.

```
echo text
```

Print `text`. Nonprinting characters can be included in `text` using C escape sequences, such as `\n` to print a newline. *No newline is printed unless you specify one.* In addition to the standard C escape sequences, a backslash followed by a space stands for a space. This is useful for displaying a string with spaces at the beginning or the end, since leading and trailing spaces are otherwise trimmed from all arguments. To print `and foo =`, use the command `echo \ and foo = \`.

A backslash at the end of `text` can be used, as in C, to continue the command onto subsequent lines. For example,

```
echo This is some text\n\
which is continued\n\
onto several lines.\n
```

produces the same output as

```
echo This is some text\n
echo which is continued\n
echo onto several lines.\n
```

`output expression`

Print the value of `expression` and nothing but that value: no newlines, no `$nn =` . The value is not entered in the value history either. Refer to Section 10.1 *Expressions*, for more information on expressions.

`output/fmt expression`

Print the value of `expression` in format `fmt`. You can use the same formats as for `print`. Refer to Section 10.4 *Output formats*, for more information.

`printf string, expressions...`

Print the values of the `expressions` under the control of `string`. The `expressions` are separated by commas and may be either numbers or pointers. Their values are printed as specified by `string`, exactly as if your program were to execute the C subroutine

```
printf (string, expressions...);
```

For example, you can print two values in hex like this:

```
printf "foo, bar-foo = 0x%x, 0x%x\n", foo, bar-foo
```

The only backslash-escape sequences that you can use in the format string are the simple ones that consist of backslash followed by a letter.

Command Interpreters

`gdb` supports multiple command interpreters, and some command infrastructure to allow users or user interface writers to switch between interpreters or run commands in other interpreters.

`gdb` currently supports two command interpreters, the console interpreter (sometimes called the command-line interpreter or `cli`) and the machine interface interpreter (or `gdb/mi`). This manual describes both of these interfaces in great detail.

By default, `gdb` will start with the console interpreter. However, the user may choose to start `gdb` with another interpreter by specifying the `-i` or `-interpreter` startup options. Defined interpreters include:

`console`

The traditional console or command-line interpreter. This is the most often used interpreter with `gdb`. With no interpreter specified at runtime, `gdb` will use this interpreter.

`mi`

The newest `gdb/mi` interface (currently `mi2`). Used primarily by programs wishing to use `gdb` as a backend for a debugger GUI or an IDE. For more information, (refer to Chapter 26 *The `gdb/mi` Interface*).

`mi2`

The current `gdb/mi` interface.

`mi1`

The `gdb/mi` interface included in `gdb` 5.1, 5.2, and 5.3.

The interpreter being used by `gdb` may not be dynamically switched at runtime. Although possible, this could lead to a very precarious situation. Consider an IDE using `gdb/mi`. If a user enters the command "interpreter-set console" in a console view, `gdb` would switch to using the console interpreter, rendering the IDE inoperable!

Although you may only choose a single interpreter at startup, you may execute commands in any interpreter from the current interpreter using the appropriate command. If you are running the console interpreter, simply use the `interpreter-exec` command:

```
interpreter-exec mi "-data-list-register-names"
```

`gdb/mi` has a similar command, although it is only available in versions of `gdb` which support `gdb/mi` version 2 (or greater).

gdb Text User Interface

The gdb Text User Interface, TUI in short, is a terminal interface which uses the `curses` library to show the source file, the assembly output, the program registers and gdb commands in separate text windows. The TUI is available only when gdb is configured with the `-enable-tui` configure option (refer to Section B.3 *configure options*).

24.1. TUI overview

The TUI has two display modes that can be switched while gdb runs:

- A curses (or TUI) mode in which it displays several text windows on the terminal.
- A standard mode which corresponds to the gdb configured without the TUI.

In the TUI mode, gdb can display several text window on the terminal:

command

This window is the gdb command window with the gdb prompt and the gdb outputs. The gdb input is still managed using readline but through the TUI. The *command* window is always visible.

source

The source window shows the source file of the program. The current line as well as active breakpoints are displayed in this window.

assembly

The assembly window shows the disassembly output of the program.

register

This window shows the processor registers. It detects when a register is changed and when this is the case, registers that have changed are highlighted.

The source and assembly windows show the current program position by highlighting the current line and marking them with the `>` marker. Breakpoints are also indicated with two markers. A first one indicates the breakpoint type:

B

Breakpoint which was hit at least once.

b

Breakpoint which was never hit.

H

Hardware breakpoint which was hit at least once.

h

Hardware breakpoint which was never hit.

The second marker indicates whether the breakpoint is enabled or not:

+

Breakpoint is enabled.

-

Breakpoint is disabled.

The source, assembly and register windows are attached to the thread and the frame position. They are updated when the current thread changes, when the frame changes or when the program counter changes. These three windows are arranged by the TUI according to several layouts. The layout defines which of these three windows are visible. The following layouts are available:

- source
- assembly
- source and assembly
- source and registers
- assembly and registers

On top of the command window a status line gives various information concerning the current process being debugged. The status line is updated when the information it shows changes. The following fields are displayed:

target

Indicates the current gdb target (refer to Chapter 18 *Specifying a Debugging Target*).

process

Gives information about the current process or thread number. When no process is being debugged, this field is set to `No process`.

function

Gives the current function name for the selected frame. The name is demangled if demangling is turned on (refer to Section 10.7 *Print settings*). When there is no symbol corresponding to the current program counter the string `??` is displayed.

line

Indicates the current line number for the selected frame. When the current line number is not known the string `??` is displayed.

pc

Indicates the current program counter address.

24.2. TUI Key Bindings

The TUI installs several key bindings in the readline keymaps (refer to Chapter 29 *Command Line Editing*). They allow to leave or enter in the TUI mode or they operate directly on the TUI layout and windows. The TUI also provides a *SingleKey* keymap which binds several keys directly to gdb commands. The following key bindings are installed for both TUI mode and the gdb standard mode.

C-x C-a

C-x a

C-x A

Enter or leave the TUI mode. When the TUI mode is left, the curses window management is left and gdb operates using its standard mode writing on the terminal directly. When the TUI mode is entered, the control is given back to the curses windows. The screen is then refreshed.

C-x 1

Use a TUI layout with only one window. The layout will either be `source` or `assembly`. When the TUI mode is not active, it will switch to the TUI mode.

Think of this key binding as the Emacs **C-x 1** binding.

C-x 2

Use a TUI layout with at least two windows. When the current layout shows already two windows, a next layout with two windows is used. When a new layout is chosen, one window will always be common to the previous layout and the new one.

Think of it as the Emacs **C-x 2** binding.

C-x s

Use the TUI *SingleKey* keymap that binds single key to gdb commands (refer to Section 24.3 *TUI Single Key Mode*).

The following key bindings are handled only by the TUI mode:

[PgUp]

Scroll the active window one page up.

[PgDn]

Scroll the active window one page down.

[Up]

Scroll the active window one line up.

[Down]

Scroll the active window one line down.

[Left]

Scroll the active window one column left.

[Right]

Scroll the active window one column right.

[C-L]

Refresh the screen.

In the TUI mode, the arrow keys are used by the active window for scrolling. This means they are not available for readline. It is necessary to use other readline key bindings such as [C-p], [C-n], [C-b] and [C-f].

24.3. TUI Single Key Mode

The TUI provides a *SingleKey* mode in which it installs a particular key binding in the readline keymaps to connect single keys to some gdb commands.

c

continue

d

down

f

finish

n

next

q

exit the *SingleKey* mode.

r

run

s

step

u

up

v

info locals

w

where

Other keys temporarily switch to the gdb command prompt. The key that was pressed is inserted in the editing buffer so that it is possible to type most gdb commands without interaction with the TUI *SingleKey* mode. Once the command is entered the TUI *SingleKey* mode is restored. The only way to permanently leave this mode is by hitting [q] or [C-x] [s].

24.4. TUI specific commands

The TUI has specific commands to control the text windows. These commands are always available, that is they do not depend on the current terminal mode in which gdb runs. When gdb is in the standard mode, using these commands will automatically switch in the TUI mode.

`info win`

List and give the size of all displayed windows.

`layout next`

Display the next layout.

`layout prev`

Display the previous layout.

`layout src`

Display the source window only.

`layout asm`

Display the assembly window only.

`layout split`

Display the source and assembly window.

`layout regs`

Display the register window together with the source or assembly window.

`focus next | prev | src | asm | regs | split`

Set the focus to the named window. This command allows to change the active window so that scrolling keys can be affected to another window.

`refresh`

Refresh the screen. This is similar to using [C-L] key.

`update`

Update the source window and the current execution point.

`winheight name +count`

`winheight name -count`

Change the height of the window `name` by `count` lines. Positive counts increase the height, while negative counts decrease it.

24.5. TUI configuration variables

The TUI has several configuration variables that control the appearance of windows on the terminal.

`set tui border-kind kind`

Select the border appearance for the source, assembly and register windows. The possible values are the following:

space

Use a space character to draw the border.

ascii

Use ascii characters + - and | to draw the border.

acs

Use the Alternate Character Set to draw the border. The border is drawn using character line graphics if the terminal supports them.

```
set tui active-border-mode mode
```

Select the attributes to display the border of the active window. The possible values are `normal`, `standout`, `reverse`, `half`, `half-standout`, `bold` and `bold-standout`.

```
set tui border-mode mode
```

Select the attributes to display the border of other windows. The `mode` can be one of the following:

`normal`

Use normal attributes to display the border.

`standout`

Use standout mode.

`reverse`

Use reverse video mode.

`half`

Use half bright mode.

`half-standout`

Use half bright and standout mode.

`bold`

Use extra bright or bold mode.

`bold-standout`

Use extra bright or bold and standout mode.

Using gdb under gnu Emacs

A special interface allows you to use gnu Emacs to view (and edit) the source files for the program you are debugging with gdb.

To use this interface, use the command **M-x gdb** in Emacs. Give the executable file you want to debug as an argument. This command starts gdb as a subprocess of Emacs, with input and output through a newly created Emacs buffer.

Using gdb under Emacs is just like using gdb normally except for two things:

- All "terminal" input and output goes through the Emacs buffer.

This applies both to gdb commands and their output, and to the input and output done by the program you are debugging.

This is useful because it means that you can copy the text of previous commands and input them again; you can even use parts of the output in this way.

All the facilities of Emacs' Shell mode are available for interacting with your program. In particular, you can send signals the usual way--for example, **C-c C-c** for an interrupt, **C-c C-z** for a stop.

- gdb displays source code through Emacs.

Each time gdb displays a stack frame, Emacs automatically finds the source file for that frame and puts an arrow (**=>**) at the left margin of the current line. Emacs uses a separate buffer for source display, and splits the screen to show both your gdb session and the source.

Explicit gdb `list` or search commands still produce output as usual, but you probably have no reason to use them from Emacs.

Warning: If the directory where your program resides is not your current directory, it can be easy to confuse Emacs about the location of the source files, in which case the auxiliary display buffer does not appear to show your source. gdb can find programs by searching your environment's `PATH` variable, so the gdb input and output session proceeds normally; but Emacs does not get enough information back from gdb to locate the source files in this situation. To avoid this problem, either start gdb mode from the directory where your program resides, or specify an absolute file name when prompted for the **M-x gdb** argument.

A similar confusion can result if you use the gdb `file` command to switch to debugging a program in some other location, from an existing gdb buffer in Emacs.

By default, **M-x gdb** calls the program called `gdb`. If you need to call `gdb` by a different name (for example, if you keep several configurations around, with different names) you can set the Emacs variable `gdb-command-name`; for example,

```
(setq gdb-command-name "mygdb")
```

(preceded by **M-:** or **ESC :**, or typed in the `*scratch*` buffer, or in your `.emacs` file) makes Emacs call the program named "mygdb" instead.

In the gdb I/O buffer, you can use these special Emacs commands in addition to the standard Shell mode commands:

C-h m

Describe the features of Emacs' gdb Mode.

M-s

Execute to another source line, like the gdb `step` command; also update the display window to show the current file and location.

M-n

Execute to next source line in this function, skipping all function calls, like the gdb `next` command. Then update the display window to show the current file and location.

M-i

Execute one instruction, like the gdb `stepi` command; update display window accordingly.

M-x gdb-nexti

Execute to next instruction, using the gdb `nexti` command; update display window accordingly.

C-c C-f

Execute until exit from the selected stack frame, like the gdb `finish` command.

M-c

Continue execution of your program, like the gdb `continue` command.

Warning: In Emacs v19, this command is **C-c C-p**.

M-u

Go up the number of frames indicated by the numeric argument (), like the gdb `up` command.

Warning: In Emacs v19, this command is **C-c C-u**.

M-d

Go down the number of frames indicated by the numeric argument, like the gdb `down` command.

Warning: In Emacs v19, this command is **C-c C-d**.

C-x &

Read the number where the cursor is positioned, and insert it at the end of the gdb I/O buffer. For example, if you wish to disassemble code around an address that was displayed earlier, type **disassemble**; then move the cursor to the address display, and pick up the argument for `disassemble` by typing **C-x &**.

You can customize this further by defining elements of the list `gdb-print-command`; once it is defined, you can format or otherwise process numbers picked up by **C-x &** before they are inserted. A numeric argument to **C-x &** indicates that you wish special formatting, and also acts as an index to pick an element of the list. If the list element is a string, the number to be inserted is formatted using the Emacs function `format`; otherwise the number is passed as an argument to the corresponding list element.

In any source file, the Emacs command **C-x SPC** (`gdb-break`) tells gdb to set a breakpoint on the source line point is on.

If you accidentally delete the source-display buffer, an easy way to get it back is to type the command **f** in the gdb buffer, to request a frame display; when you run under Emacs, this recreates the source buffer if necessary to show you the context of the current frame.

The source files displayed in Emacs are in ordinary Emacs buffers which are visiting the source files in the usual way. You can edit the files with these buffers if you wish; but keep in mind that gdb communicates with Emacs in terms of line numbers. If you add or delete lines from the text, the line numbers that gdb knows cease to correspond properly with the code.

The gdb/mi Interface

26.1. Function and Purpose

`gdb/mi` is a line based machine oriented text interface to `gdb`. It is specifically intended to support the development of systems which use the debugger as just one small component of a larger system.

This chapter is a specification of the `gdb/mi` interface. It is written in the form of a reference manual.

Note that `gdb/mi` is still under construction, so some of the features described below are incomplete and subject to change.

26.2. Notation and Terminology

This chapter uses the following notation:

- `|` separates two alternatives.
- `[something]` indicates that `something` is optional: it may or may not be given.
- `(group) *` means that `group` inside the parentheses may repeat zero or more times.
- `(group) +` means that `group` inside the parentheses may repeat one or more times.
- `"string"` means a literal `string`.

26.3. Acknowledgments

In alphabetic order: Andrew Cagney, Fernando Nasser, Stan Shebs and Elena Zannoni.

26.4. `gdb/mi` Command Syntax

26.4.1. `gdb/mi` Input Syntax

```
command ==>
    cli-command | mi-command

cli-command ==>
    [ token ] cli-command nl, where cli-command is any existing gdb CLI command.

mi-command ==>
    [ token ] "-" operation ( " " option ) * [ " -" ] ( " " parameter ) * nl

token ==>
    "any sequence of digits"
```

```

option ==>
    "-" parameter [ " " parameter ]

parameter ==>
    non-blank-sequence | c-string

operation ==>
    any of the operations described in this chapter

non-blank-sequence ==>
    anything, provided it doesn't contain special characters such as "-", nl, "" and of course ""

c-string ==>
    "" seven-bit-iso-c-string-content ""

nl ==>
    CR | CR-LF

```

Notes:

- The CLI commands are still handled by the mi interpreter; their output is described below.
- The `token`, when present, is passed back when the command finishes.
- Some mi commands accept optional arguments as part of the parameter list. Each option is identified by a leading `-` (dash) and may be followed by an optional argument `parameter`. Options occur first in the parameter list and can be delimited from normal parameters using `-` (this is useful when some parameters begin with a dash).

Pragmatics:

- We want easy access to the existing CLI syntax (for debugging).
- We want it to be easy to spot a mi operation.

26.4.2. gdb/mi Output Syntax

The output from `gdb/mi` consists of zero or more out-of-band records followed, optionally, by a single result record. This result record is for the most recent command. The sequence of output records is terminated by `(gdb)`.

If an input command was prefixed with a `token` then the corresponding output for that command will also be prefixed by that same `token`.

```

output ==>
    ( out-of-band-record ) * [ result-record ] "(gdb)" nl

result-record ==>
    [ token ] "^" result-class ( "," result ) * nl

out-of-band-record ==>
    async-record | stream-record

```

```

async-record ==>
    exec-async-output | status-async-output | notify-async-output
exec-async-output ==>
    [ token ] "*" async-output
status-async-output ==>
    [ token ] "+" async-output
notify-async-output ==>
    [ token ] "=" async-output
async-output ==>
    async-class ( ", " result ) * nl
result-class ==>
    "done" | "running" | "connected" | "error" | "exit"
async-class ==>
    "stopped" | others (where others will be added depending on the needs--this is still in
    development).
result ==>
    variable "=" value
variable ==>
    string
value ==>
    const | tuple | list
const ==>
    c-string
tuple ==>
    "{}" | "{" result ( ", " result ) * "}"
list ==>
    "[]" | "[" value ( ", " value ) * "]" | "[" result ( ", " result ) * "]"
stream-record ==>
    console-stream-output | target-stream-output | log-stream-output
console-stream-output ==>
    "~" c-string
target-stream-output ==>
    "@" c-string

```

```
log-stream-output ==>
    "&" c-string
nl ==>
    CR | CR-LF
token ==>
    any sequence of digits.
```

Notes:

- All output sequences end in a single line containing a period.
- The `token` is from the corresponding request. If an execution command is interrupted by the `-exec-interrupt` command, the `token` associated with the `*stopped` message is the one of the original execution command, not the one of the interrupt command.
- `status-async-output` contains on-going status information about the progress of a slow operation. It can be discarded. All status output is prefixed by `+`.
- `exec-async-output` contains asynchronous state change on the target (stopped, started, disappeared). All async output is prefixed by `*`.
- `notify-async-output` contains supplementary information that the client should handle (e.g., a new breakpoint information). All notify output is prefixed by `=`.
- `console-stream-output` is output that should be displayed as is in the console. It is the textual response to a CLI command. All the console output is prefixed by `~`.
- `target-stream-output` is the output produced by the target program. All the target output is prefixed by `@`.
- `log-stream-output` is output text coming from gdb's internals, for instance messages that should be displayed as part of an error log. All the log output is prefixed by `⋄`.
- New gdb/mi commands should only output `lists` containing values.

Refer to Section 26.6.2 *gdb/mi Stream Records*, for more details about the various output records.

26.4.3. Simple Examples of gdb/mi Interaction

This subsection presents several simple examples of interaction using the gdb/mi interface. In these examples, `->` means that the following line is passed to gdb/mi as input, while `<-` means the output received from gdb/mi.

26.4.3.1. Target Stop

Here's an example of stopping the inferior process:

```
-> -stop
<- (gdb)
```

and later:

```
<- *stop,reason="stop",address="0x123",source="a.c:123"
<- (gdb)
```

26.4.3.2. Simple CLI Command

Here's an example of a simple CLI command being passed through gdb/mi and on to the CLI.

```
-> print 1+2
<- &"print 1+2\n"
<- ~"$1 = 3\n"
<- ^done
<- (gdb)
```

26.4.3.3. Command With Side Effects

```
-> -symbol-file xyz.exe
<- *breakpoint,nr="3",address="0x123",source="a.c:123"
<- (gdb)
```

26.4.3.4. A Bad Command

Here's what happens if you pass a non-existent command:

```
-> -rubbish
<- ^error,msg="Undefined MI command: rubbish"
<- (gdb)
```

26.5. gdb/mi Compatibility with CLI

To help users familiar with gdb's existing CLI interface, gdb/mi accepts existing CLI commands. As specified by the syntax, such commands can be directly entered into the gdb/mi interface and gdb will respond.

This mechanism is provided as an aid to developers of gdb/mi clients and not as a reliable interface into the CLI. Since the command is being interpreted in an environment that assumes gdb/mi behaviour, the exact output of such commands is likely to end up being an un-supported hybrid of gdb/mi and CLI output.

26.6. gdb/mi Output Records

26.6.1. gdb/mi Result Records

In addition to a number of out-of-band notifications, the response to a gdb/mi command includes one of the following result indications:

```
"^done" [ ",", " results ]
```

The synchronous operation was successful, `results` are the return values.

```
"^running"
```

The asynchronous operation was successfully started. The target is running.

```
"^error" ", " c-string
```

The operation failed. The `c-string` contains the corresponding error message.

26.6.2. gdb/mi Stream Records

`gdb` internally maintains a number of output streams: the console, the target, and the log. The output intended for each of these streams is funneled through the `gdb/mi` interface using *stream records*.

Each stream record begins with a unique *prefix character* which identifies its stream (refer to Section 26.4.2 *gdb/mi Output Syntax*). In addition to the prefix, each stream record contains a `string-output`. This is either raw text (with an implicit new line) or a quoted C string (which does not contain an implicit newline).

```
"~" string-output
```

The console output stream contains text that should be displayed in the CLI console window. It contains the textual responses to CLI commands.

```
"@" string-output
```

The target output stream contains any textual output from the running target.

```
"&" string-output
```

The log stream contains debugging messages being produced by `gdb`'s internals.

26.6.3. gdb/mi Out-of-band Records

Out-of-band records are used to notify the `gdb/mi` client of additional changes that have occurred. Those changes can either be a consequence of `gdb/mi` (e.g., a breakpoint modified) or a result of target activity (e.g., target stopped).

The following is a preliminary list of possible out-of-band records.

```
"*" "stop"
```

```
stop
```

26.7. gdb/mi Command Description Format

The remaining sections describe blocks of commands. Each block of commands is laid out in a fashion similar to this section.

Note the the line breaks shown in the examples are here only for readability. They don't appear in the real output. Also note that the commands with a non-available example (N.A.) are not yet implemented.

26.7.1. Motivation

The motivation for this collection of commands.

26.7.2. Introduction

A brief introduction to this collection of commands as a whole.

26.7.3. Commands

For each command in the block, the following is described:

26.7.3.1. Synopsis

```
-command args...
```

26.7.3.2. gdb Command

The corresponding gdb CLI command.

26.7.3.3. Result

The result.

26.7.3.4. Out-of-band

The out-of-band result.

26.7.3.5. Notes

The notes.

26.7.3.6. Example

An example.

26.8. gdb/mi Breakpoint table commands

This section documents gdb/mi commands for manipulating breakpoints.

26.8.1. The `-break-afterCommand`

26.8.1.1. Synopsis

```
-break-after number count
```

The breakpoint number `number` is not in effect until it has been hit `count` times. To see how this is reflected in the output of the `-break-list` command, see the description of the `-break-list` command below.

26.8.1.2. gdb Command

The corresponding gdb command is `ignore`.

26.8.1.3. Example

```
(gdb)
-break-insert main
^done,bkpt={number="1",addr="0x000100d0",file="hello.c",line="5"}
(gdb)
-break-after 1 3
~
^done
(gdb)
-break-list
^done,BreakpointTable={nr_rows="1",nr_cols="6",
hdr=[{width="3",alignment="-1",col_name="number",colhdr="Num"},
{width="14",alignment="-1",col_name="type",colhdr="Type"},
{width="4",alignment="-1",col_name="disp",colhdr="Disp"},
{width="3",alignment="-1",col_name="enabled",colhdr="Enb"},
{width="10",alignment="-1",col_name="addr",colhdr="Address"},
{width="40",alignment="2",col_name="what",colhdr="What"}],
body=[bkpt={number="1",type="breakpoint",disp="keep",enabled="y",
addr="0x000100d0",func="main",file="hello.c",line="5",times="0",
ignore="3"}]}
```

26.8.2. The `-break-condition` Command

26.8.2.1. Synopsis

```
-break-condition number expr
```

Breakpoint `number` will stop the program only if the condition in `expr` is true. The condition becomes part of the `-break-list` output (see the description of the `-break-list` command below).

26.8.2.2. gdb Command

The corresponding gdb command is `condition`.

26.8.2.3. Example

```
(gdb)
-break-condition 1 1
^done
(gdb)
-break-list
^done,BreakpointTable={nr_rows="1",nr_cols="6",
hdr={width="3",alignment="-1",col_name="number",colhdr="Num"},
{width="14",alignment="-1",col_name="type",colhdr="Type"},
{width="4",alignment="-1",col_name="disp",colhdr="Disp"},
{width="3",alignment="-1",col_name="enabled",colhdr="Enb"},
{width="10",alignment="-1",col_name="addr",colhdr="Address"},
{width="40",alignment="2",col_name="what",colhdr="What"}},
body={bkpt={number="1",type="breakpoint",disp="keep",enabled="y",
addr="0x000100d0",func="main",file="hello.c",line="5",cond="1",
times="0",ignore="3"}}}
```

26.8.3. The `-break-delete` Command

26.8.3.1. Synopsis

```
-break-delete ( breakpoint ) +
```

Delete the breakpoint(s) whose number(s) are specified in the argument list. This is obviously reflected in the breakpoint list.

26.8.3.2. gdb command

The corresponding gdb command is `delete`.

26.8.3.3. Example

```
(gdb)
-break-delete 1
^done
(gdb)
-break-list
^done,BreakpointTable={nr_rows="0",nr_cols="6",
hdr={width="3",alignment="-1",col_name="number",colhdr="Num"},
{width="14",alignment="-1",col_name="type",colhdr="Type"},
{width="4",alignment="-1",col_name="disp",colhdr="Disp"},
{width="3",alignment="-1",col_name="enabled",colhdr="Enb"}},
```

```
{width="10", alignment="-1", col_name="addr", colhdr="Address"},
{width="40", alignment="2", col_name="what", colhdr="What"}},
body=[]}
(gdb)
```

26.8.4. The `-break-disable` Command

26.8.4.1. Synopsis

```
-break-disable ( breakpoint )+
```

Disable the named `breakpoint(s)`. The field `enabled` in the break list is now set to `n` for the named `breakpoint(s)`.

26.8.4.2. `gdb` Command

The corresponding `gdb` command is `disable`.

26.8.4.3. Example

```
(gdb)
-break-disable 2
^done
(gdb)
-break-list
^done,BreakpointTable={nr_rows="1",nr_cols="6",
hdr={width="3",alignment="-1",col_name="number",colhdr="Num"},
{width="14",alignment="-1",col_name="type",colhdr="Type"},
{width="4",alignment="-1",col_name="disp",colhdr="Disp"},
{width="3",alignment="-1",col_name="enabled",colhdr="Enb"},
{width="10",alignment="-1",col_name="addr",colhdr="Address"},
{width="40",alignment="2",col_name="what",colhdr="What"}},
body=[bkpt={number="2",type="breakpoint",disp="keep",enabled="n",
addr="0x000100d0",func="main",file="hello.c",line="5",times="0"}]}
(gdb)
```

26.8.5. The `-break-enable` Command

26.8.5.1. Synopsis

```
-break-enable ( breakpoint )+
```

Enable (previously disabled) breakpoint(s).

26.8.5.2. gdb Command

The corresponding gdb command is `enable`.

26.8.5.3. Example

```
(gdb)
-break-enable 2
^done
(gdb)
-break-list
^done,BreakpointTable={nr_rows="1",nr_cols="6",
hdr=[{width="3",alignment="-1",col_name="number",colhdr="Num"},
{width="14",alignment="-1",col_name="type",colhdr="Type"},
{width="4",alignment="-1",col_name="disp",colhdr="Disp"},
{width="3",alignment="-1",col_name="enabled",colhdr="Enb"},
{width="10",alignment="-1",col_name="addr",colhdr="Address"},
{width="40",alignment="2",col_name="what",colhdr="What"}],
body=[bkpt={number="2",type="breakpoint",disp="keep",enabled="y",
addr="0x000100d0",func="main",file="hello.c",line="5",times="0"}]}
```

26.8.6. The `-break-info` Command

26.8.6.1. Synopsis

```
-break-info breakpoint
```

Get information about a single breakpoint.

26.8.6.2. gdb command

The corresponding gdb command is `info break breakpoint`.

26.8.6.3. Example

N.A.

26.8.7. The `-break-insert` Command

26.8.7.1. Synopsis

```
-break-insert [ -t ] [ -h ] [ -r ]
             [ -c condition ] [ -i ignore-count ]
             [ -p thread ] [ line | addr ]
```

If specified, `line`, can be one of:

- function
- filename:linenum
- filename:function
- *address

The possible optional parameters of this command are:

`-t`

Insert a temporary breakpoint.

`-h`

Insert a hardware breakpoint.

`-c condition`

Make the breakpoint conditional on `condition`.

`-i ignore-count`

Initialize the `ignore-count`.

`-r`

Insert a regular breakpoint in all the functions whose names match the given regular expression. Other flags are not applicable to regular expression.

26.8.7.2. Result

The result is in the form:

```
^done,bkptno="number",func="funcname",
file="filename",line="lineno"
```

where `number` is the gdb number for this breakpoint, `funcname` is the name of the function where the breakpoint was inserted, `filename` is the name of the source file which contains this function, and `lineno` is the source line number within that file.

Note: this format is open to change.

26.8.7.3. gdb Command

The corresponding gdb commands are `break`, `tbreak`, `hbreak`, `thbreak`, and `rbreak`.

26.8.7.4. Example

```
(gdb)
~break-insert main
^done,bkpt={number="1",addr="0x0001072c",file="recursive2.c",line="4"}
(gdb)
~break-insert -t foo
^done,bkpt={number="2",addr="0x00010774",file="recursive2.c",line="11"}
(gdb)
~break-list
^done,BreakpointTable={nr_rows="2",nr_cols="6",
hdr={width="3",alignment="-1",col_name="number",colhdr="Num"},
{width="14",alignment="-1",col_name="type",colhdr="Type"},
{width="4",alignment="-1",col_name="disp",colhdr="Disp"},
{width="3",alignment="-1",col_name="enabled",colhdr="Enb"},
{width="10",alignment="-1",col_name="addr",colhdr="Address"},
{width="40",alignment="2",col_name="what",colhdr="What"}},
body=[bkpt={number="1",type="breakpoint",disp="keep",enabled="y",
addr="0x0001072c",func="main",file="recursive2.c",line="4",times="0"},
bkpt={number="2",type="breakpoint",disp="del",enabled="y",
addr="0x00010774",func="foo",file="recursive2.c",line="11",times="0"}]}
(gdb)
~break-insert -r foo.*
~int foo(int, int);
^done,bkpt={number="3",addr="0x00010774",file="recursive2.c",line="11"}
(gdb)
```

26.8.8. The `~break-list` Command

26.8.8.1. Synopsis

```
~break-list
```

Displays the list of inserted breakpoints, showing the following fields:

Number

number of the breakpoint

Type

type of the breakpoint: `breakpoint` or `watchpoint`

Disposition

should the breakpoint be deleted or disabled when it is hit: `keep` or `nokeep`

Enabled

is the breakpoint enabled or no: y or n

Address

memory location at which the breakpoint is set

What

logical location of the breakpoint, expressed by function name, file name, line number

Times

number of times the breakpoint has been hit

If there are no breakpoints or watchpoints, the `BreakpointTable` body field is an empty list.

26.8.8.2. gdb Command

The corresponding gdb command is `info break`.

26.8.8.3. Example

```
(gdb)
-break-list
^done,BreakpointTable={nr_rows="2",nr_cols="6",
hdr={width="3",alignment="-1",col_name="number",colhdr="Num"},
{width="14",alignment="-1",col_name="type",colhdr="Type"},
{width="4",alignment="-1",col_name="disp",colhdr="Disp"},
{width="3",alignment="-1",col_name="enabled",colhdr="Enb"},
{width="10",alignment="-1",col_name="addr",colhdr="Address"},
{width="40",alignment="2",col_name="what",colhdr="What"}},
body=[bkpt={number="1",type="breakpoint",disp="keep",enabled="y",
addr="0x000100d0",func="main",file="hello.c",line="5",times="0"},
bkpt={number="2",type="breakpoint",disp="keep",enabled="y",
addr="0x00010114",func="foo",file="hello.c",line="13",times="0"}]}
(gdb)
```

Here's an example of the result when there are no breakpoints:

```
(gdb)
-break-list
^done,BreakpointTable={nr_rows="0",nr_cols="6",
hdr={width="3",alignment="-1",col_name="number",colhdr="Num"},
{width="14",alignment="-1",col_name="type",colhdr="Type"},
{width="4",alignment="-1",col_name="disp",colhdr="Disp"},
{width="3",alignment="-1",col_name="enabled",colhdr="Enb"},
{width="10",alignment="-1",col_name="addr",colhdr="Address"},
{width="40",alignment="2",col_name="what",colhdr="What"}},
body=[]}
(gdb)
```

26.8.9. The `-break-watch` Command

26.8.9.1. Synopsis

```
-break-watch [ -a | -r ]
```

Create a watchpoint. With the `-a` option it will create an *access* watchpoint, that is, a watchpoint that triggers either on a read from or on a write to the memory location. With the `-r` option, the watchpoint created is a *read* watchpoint, that is, it will trigger only when the memory location is accessed for reading. Without either of the options, the watchpoint created is a regular watchpoint, that is, it will trigger when the memory location is accessed for writing. Refer to Section 7.1.2 *Setting watchpoints*.

Note that `-break-list` will report a single list of watchpoints and breakpoints inserted.

26.8.9.2. gdb Command

The corresponding gdb commands are `watch`, `awatch`, and `rwatch`.

26.8.9.3. Example

Setting a watchpoint on a variable in the `main` function:

```
(gdb)
-break-watch x
^done,wpt={number="2",exp="x"}
(gdb)
-exec-continue
^running
^done,reason="watchpoint-trigger",wpt={number="2",exp="x"},
value={old="-268439212",new="55"},
frame={func="main",args=[],file="recursive2.c",line="5"}
(gdb)
```

Setting a watchpoint on a variable local to a function. gdb will stop the program execution twice: first for the variable changing value, then for the watchpoint going out of scope.

```
(gdb)
-break-watch C
^done,wpt={number="5",exp="C"}
(gdb)
-exec-continue
^running
^done,reason="watchpoint-trigger",
wpt={number="5",exp="C"},value={old="-276895068",new="3"},
frame={func="callee4",args=[],
file="../../../devo/gdb/testsuite/gdb.mi/basics.c",line="13"}
(gdb)
-exec-continue
^running
^done,reason="watchpoint-scope",wpnum="5",
frame={func="callee3",args=[{name="strarg",
value="0x11940 \"A string argument.\""}]},
```

```
file="../../../../devo/gdb/testsuite/gdb.mi/basics.c",line="18"}
(gdb)
```

Listing breakpoints and watchpoints, at different points in the program execution. Note that once the watchpoint goes out of scope, it is deleted.

```
(gdb)
-break-watch C
^done,wpt={number="2",exp="C"}
(gdb)
-break-list
^done,BreakpointTable={nr_rows="2",nr_cols="6",
hdr={ {width="3",alignment="-1",col_name="number",colhdr="Num"},
      {width="14",alignment="-1",col_name="type",colhdr="Type"},
      {width="4",alignment="-1",col_name="disp",colhdr="Disp"},
      {width="3",alignment="-1",col_name="enabled",colhdr="Enb"},
      {width="10",alignment="-1",col_name="addr",colhdr="Address"},
      {width="40",alignment="2",col_name="what",colhdr="What"} },
body={bkpt={number="1",type="breakpoint",disp="keep",enabled="y",
addr="0x00010734",func="callee4",
file="../../../../devo/gdb/testsuite/gdb.mi/basics.c",line="8",times="1"},
bkpt={number="2",type="watchpoint",disp="keep",
enabled="y",addr="",what="C",times="0"} }}
(gdb)
-exec-continue
^running
^done,reason="watchpoint-trigger",wpt={number="2",exp="C"},
value={old="-276895068",new="3"},
frame={func="callee4",args=[],
file="../../../../devo/gdb/testsuite/gdb.mi/basics.c",line="13"}
(gdb)
-break-list
^done,BreakpointTable={nr_rows="2",nr_cols="6",
hdr={ {width="3",alignment="-1",col_name="number",colhdr="Num"},
      {width="14",alignment="-1",col_name="type",colhdr="Type"},
      {width="4",alignment="-1",col_name="disp",colhdr="Disp"},
      {width="3",alignment="-1",col_name="enabled",colhdr="Enb"},
      {width="10",alignment="-1",col_name="addr",colhdr="Address"},
      {width="40",alignment="2",col_name="what",colhdr="What"} },
body={bkpt={number="1",type="breakpoint",disp="keep",enabled="y",
addr="0x00010734",func="callee4",
file="../../../../devo/gdb/testsuite/gdb.mi/basics.c",line="8",times="1"},
bkpt={number="2",type="watchpoint",disp="keep",
enabled="y",addr="",what="C",times="-5"} }}
(gdb)
-exec-continue
^running
^done,reason="watchpoint-scope",wpnum="2",
frame={func="callee3",args=[ {name="strarg",
value="0x11940 \"A string argument.\""} ],
file="../../../../devo/gdb/testsuite/gdb.mi/basics.c",line="18"}
(gdb)
-break-list
^done,BreakpointTable={nr_rows="1",nr_cols="6",
hdr={ {width="3",alignment="-1",col_name="number",colhdr="Num"},
      {width="14",alignment="-1",col_name="type",colhdr="Type"},
      {width="4",alignment="-1",col_name="disp",colhdr="Disp"},
      {width="3",alignment="-1",col_name="enabled",colhdr="Enb"},
      {width="10",alignment="-1",col_name="addr",colhdr="Address"},
      {width="40",alignment="2",col_name="what",colhdr="What"} },
```

```
body={bkpt={number="1",type="breakpoint",disp="keep",enabled="y",
addr="0x00010734",func="callee4",
file="../../devo/gdb/testsuite/gdb.mi/basics.c",line="8",times="1"}}}
(gdb)
```

26.9. gdb/mi Data Manipulation

This section describes the gdb/mi commands that manipulate data: examine memory and registers, evaluate expressions, etc.

26.9.1. The `-data-disassemble` Command

26.9.1.1. Synopsis

```
-data-disassemble
  [ -s start-addr -e end-addr ]
  | [ -f filename -l linenum [ -n lines ] ]
  -- mode
```

Where:

`start-addr`

is the beginning address (or `$pc`)

`end-addr`

is the end address

`filename`

is the name of the file to disassemble

`linenum`

is the line number to disassemble around

`lines`

is the the number of disassembly lines to be produced. If it is `-1`, the whole function will be disassembled, in case no `end-addr` is specified. If `end-addr` is specified as a non-zero value, and `lines` is lower than the number of disassembly lines between `start-addr` and `end-addr`, only `lines` lines are displayed; if `lines` is higher than the number of lines between `start-addr` and `end-addr`, only the lines up to `end-addr` are displayed.

`mode`

is either 0 (meaning only disassembly) or 1 (meaning mixed source and disassembly).

26.9.1.2. Result

The output for each instruction is composed of four fields:

- Address
- Func-name
- Offset
- Instruction

Note that whatever included in the instruction field, is not manipulated directly by gdb/mi, that is, it is not possible to adjust its format.

26.9.1.3. gdb Command

There's no direct mapping from this command to the CLI.

26.9.1.4. Example

Disassemble from the current value of `$pc` to `$pc + 20`:

```
(gdb)
-data-disassemble -s $pc -e "$pc + 20" -- 0
^done,
asm_insns=[
  {address="0x000107c0",func-name="main",offset="4",
  inst="mov 2, %o"},
  {address="0x000107c4",func-name="main",offset="8",
  inst="sethi %hi(0x11800), %o2"},
  {address="0x000107c8",func-name="main",offset="12",
  inst="or %o2, 0x140, %o1\t! 0x11940 <_lib_version+8>"},
  {address="0x000107cc",func-name="main",offset="16",
  inst="sethi %hi(0x11800), %o2"},
  {address="0x000107d0",func-name="main",offset="20",
  inst="or %o2, 0x168, %o4\t! 0x11968 <_lib_version+48>"}]
(gdb)
```

Disassemble the whole `main` function. Line 32 is part of `main`.

```
-data-disassemble -f basics.c -l 32 -- 0
^done,asm_insns=[
  {address="0x000107bc",func-name="main",offset="0",
  inst="save %sp, -112, %sp"},
  {address="0x000107c0",func-name="main",offset="4",
  inst="mov 2, %o"},
  {address="0x000107c4",func-name="main",offset="8",
  inst="sethi %hi(0x11800), %o2"},
  [...]
  {address="0x0001081c",func-name="main",offset="96",inst="ret "},
  {address="0x00010820",func-name="main",offset="100",inst="restore "}]]
(gdb)
```

Disassemble 3 instructions from the start of `main`:

```
(gdb)
-data-disassemble -f basics.c -l 32 -n 3 -- 0
^done,asm_insns=[
  {address="0x000107bc",func-name="main",offset="0",
  inst="save %sp, -112, %sp"},
  {address="0x000107c0",func-name="main",offset="4",
  inst="mov 2, %o0"},
  {address="0x000107c4",func-name="main",offset="8",
  inst="sethi %hi(0x11800), %o2"}]
(gdb)
```

Disassemble 3 instructions from the start of `main` in mixed mode:

```
(gdb)
-data-disassemble -f basics.c -l 32 -n 3 -- 1
^done,asm_insns=[
  src_and_asm_line={line="31",
  file="/kwikemart/marge/ezannoni/flathead-dev/devo/gdb/ \
  testsuite/gdb.mi/basics.c",line_asm_insn=[
  {address="0x000107bc",func-name="main",offset="0",
  inst="save %sp, -112, %sp"}]},
  src_and_asm_line={line="32",
  file="/kwikemart/marge/ezannoni/flathead-dev/devo/gdb/ \
  testsuite/gdb.mi/basics.c",line_asm_insn=[
  {address="0x000107c0",func-name="main",offset="4",
  inst="mov 2, %o0"},
  {address="0x000107c4",func-name="main",offset="8",
  inst="sethi %hi(0x11800), %o2"}]}}]
(gdb)
```

26.9.2. The `-data-evaluate-expression` Command

26.9.2.1. Synopsis

```
-data-evaluate-expression expr
```

Evaluate `expr` as an expression. The expression could contain an inferior function call. The function call will execute synchronously. If the expression contains spaces, it must be enclosed in double quotes.

26.9.2.2. `gdb` Command

The corresponding `gdb` commands are `print`, `output`, and `call`. In `gdbtk` only, there's a corresponding `gdb_eval` command.

26.9.2.3. Example

In the following example, the numbers that precede the commands are the *tokens* described in (refer to Section 26.4 *gdb/mi Command Syntax*). Notice how gdb/mi returns the same tokens in its output.

```
211-data-evaluate-expression A
211^done,value="1"
(gdb)
311-data-evaluate-expression &A
311^done,value="0xefffeb7c"
(gdb)
411-data-evaluate-expression A+3
411^done,value="4"
(gdb)
511-data-evaluate-expression "A + 3"
511^done,value="4"
(gdb)
```

26.9.3. The `-data-list-changed-registers` Command

26.9.3.1. Synopsis

```
-data-list-changed-registers
```

Display a list of the registers that have changed.

26.9.3.2. gdb Command

gdb doesn't have a direct analog for this command; gdbtk has the corresponding command `gdb_changed_register_list`.

26.9.3.3. Example

On a PPC MBX board:

```
(gdb)
-exec-continue
^running

(gdb)
*stopped,reason="breakpoint-hit",bkptno="1",frame={func="main",
args=[],file="try.c",line="5"}
(gdb)
-data-list-changed-registers
^done,changed-registers=["0","1","2","4","5","6","7","8","9",
"10","11","13","14","15","16","17","18","19","20","21","22","23",
"24","25","26","27","28","30","31","64","65","66","67","69"]
(gdb)
```

26.9.4. The `-data-list-register-names` Command

26.9.4.1. Synopsis

```
-data-list-register-names [ ( regno )+ ]
```

Show a list of register names for the current target. If no arguments are given, it shows a list of the names of all the registers. If integer numbers are given as arguments, it will print a list of the names of the registers corresponding to the arguments. To ensure consistency between a register name and its number, the output list may include empty register names.

26.9.4.2. gdb Command

`gdb` does not have a command which corresponds to `-data-list-register-names`. In `gdbtk` there is a corresponding command `gdb_regnames`.

26.9.4.3. Example

For the PPC MBX board:

```
(gdb)
-data-list-register-names
^done,register-names=["r0","r1","r2","r3","r4","r5","r6","r7",
"r8","r9","r10","r11","r12","r13","r14","r15","r16","r17","r18",
"r19","r20","r21","r22","r23","r24","r25","r26","r27","r28","r29",
"r30","r31","f0","f1","f2","f3","f4","f5","f6","f7","f8","f9",
"f10","f11","f12","f13","f14","f15","f16","f17","f18","f19","f20",
"f21","f22","f23","f24","f25","f26","f27","f28","f29","f30","f31",
"","pc","ps","cr","lr","ctr","xer"]
(gdb)
-data-list-register-names 1 2 3
^done,register-names=["r1","r2","r3"]
(gdb)
```

26.9.5. The `-data-list-register-values` Command

26.9.5.1. Synopsis

```
-data-list-register-values fmt [ ( regno )*]
```

Display the registers' contents. `fmt` is the format according to which the registers' contents are to be returned, followed by an optional list of numbers specifying the registers to display. A missing list of numbers indicates that the contents of all the registers must be returned.

Allowed formats for `fmt` are:

```

x
    Hexadecimal

o
    Octal

t
    Binary

d
    Decimal

r
    Raw

N
    Natural

```

26.9.5.2. gdb Command

The corresponding gdb commands are `info reg`, `info all-reg`, and `(in gdbtk) gdb_fetch_registers`.

26.9.5.3. Example

For a PPC MBX board (note: line breaks are for readability only, they don't appear in the actual output):

```

(gdb)
-data-list-register-values r 64 65
^done,register-values=[{number="64",value="0xfe00a300"},
{number="65",value="0x00029002"}]
(gdb)
-data-list-register-values x
^done,register-values=[{number="0",value="0xfe0043c8"},
{number="1",value="0x3fff88"},{number="2",value="0xffffffff"},
{number="3",value="0x0"},{number="4",value="0xa"},
{number="5",value="0x3fff68"},{number="6",value="0x3fff58"},
{number="7",value="0xfe011e98"},{number="8",value="0x2"},
{number="9",value="0xfa202820"},{number="10",value="0xfa202808"},
{number="11",value="0x1"},{number="12",value="0x0"},
{number="13",value="0x4544"},{number="14",value="0xffdffff"},
{number="15",value="0xffffffff"},{number="16",value="0xffffeff"},
{number="17",value="0xefffffff"},{number="18",value="0xfffffff"},
{number="19",value="0xffffffff"},{number="20",value="0xffffffff"},
{number="21",value="0xffffffff"},{number="22",value="0xffffffff7"},
{number="23",value="0xffffffff"},{number="24",value="0xffffffff"},
{number="25",value="0xffffffff"},{number="26",value="0xfffffff"},
{number="27",value="0xffffffff"},{number="28",value="0xf7bffff"},
{number="29",value="0x0"},{number="30",value="0xfe010000"},
{number="31",value="0x0"},{number="32",value="0x0"},
{number="33",value="0x0"},{number="34",value="0x0"},
{number="35",value="0x0"},{number="36",value="0x0"},
{number="37",value="0x0"},{number="38",value="0x0"},
{number="39",value="0x0"},{number="40",value="0x0"},

```

```
{number="41", value="0x0"}, {number="42", value="0x0"},
{number="43", value="0x0"}, {number="44", value="0x0"},
{number="45", value="0x0"}, {number="46", value="0x0"},
{number="47", value="0x0"}, {number="48", value="0x0"},
{number="49", value="0x0"}, {number="50", value="0x0"},
{number="51", value="0x0"}, {number="52", value="0x0"},
{number="53", value="0x0"}, {number="54", value="0x0"},
{number="55", value="0x0"}, {number="56", value="0x0"},
{number="57", value="0x0"}, {number="58", value="0x0"},
{number="59", value="0x0"}, {number="60", value="0x0"},
{number="61", value="0x0"}, {number="62", value="0x0"},
{number="63", value="0x0"}, {number="64", value="0xfe00a300"},
{number="65", value="0x29002"}, {number="66", value="0x202f04b5"},
{number="67", value="0xfe0043b0"}, {number="68", value="0xfe00b3e4"},
{number="69", value="0x20002b03"}]
(gdb)
```

26.9.6. The `-data-read-memory` Command

26.9.6.1. Synopsis

```
-data-read-memory [ -o byte-offset ]
  address word-format word-size
  nr-rows nr-cols [ aschar ]
```

where:

`address`

An expression specifying the address of the first memory word to be read. Complex expressions containing embedded white space should be quoted using the C convention.

`word-format`

The format to be used to print the memory words. The notation is the same as for gdb's print command (refer to Section 10.4 *Output formats*).

`word-size`

The size of each memory word in bytes.

`nr-rows`

The number of rows in the output table.

`nr-cols`

The number of columns in the output table.

`aschar`

If present, indicates that each row should include an ascii dump. The value of `aschar` is used as a padding character when a byte is not a member of the printable ascii character set (printable ascii characters are those whose code is between 32 and 126, inclusively).

byte-offset

An offset to add to the `address` before fetching memory.

This command displays memory contents as a table of `nr-rows` by `nr-cols` words, each word being `word-size` bytes. In total, `nr-rows * nr-cols * word-size` bytes are read (returned as `total-bytes`). Should less than the requested number of bytes be returned by the target, the missing words are identified using N/A. The number of bytes read from the target is returned in `nr-bytes` and the starting address used to read memory in `addr`.

The address of the next/previous row or page is available in `next-row` and `prev-row`, `next-page` and `prev-page`.

26.9.6.2. gdb Command

The corresponding gdb command is `x.gdbtk` has `gdb_get_mem` memory read command.

26.9.6.3. Example

Read six bytes of memory starting at `bytes+6` but then offset by `-6` bytes. Format as three rows of two columns. One byte per word. Display each word in hex.

```
(gdb)
9-data-read-memory -o -6 -- bytes+6 x 1 3 2
9^done, addr="0x00001390", nr-bytes="6", total-bytes="6",
next-row="0x00001396", prev-row="0x0000138e", next-page="0x00001396",
prev-page="0x0000138a", memory=[
{addr="0x00001390", data=["0x00", "0x01"]},
{addr="0x00001392", data=["0x02", "0x03"]},
{addr="0x00001394", data=["0x04", "0x05"]}]
(gdb)
```

Read two bytes of memory starting at address `shorts + 64` and display as a single word formatted in decimal.

```
(gdb)
5-data-read-memory shorts+64 d 2 1 1
5^done, addr="0x00001510", nr-bytes="2", total-bytes="2",
next-row="0x00001512", prev-row="0x0000150e",
next-page="0x00001512", prev-page="0x0000150e", memory=[
{addr="0x00001510", data=["128"]}]
(gdb)
```

Read thirty two bytes of memory starting at `bytes+16` and format as eight rows of four columns. Include a string encoding with `x` used as the non-printable character.

```
(gdb)
4-data-read-memory bytes+16 x 1 8 4 x
4^done, addr="0x000013a0", nr-bytes="32", total-bytes="32",
next-row="0x000013c0", prev-row="0x0000139c",
next-page="0x000013c0", prev-page="0x00001380", memory=[
{addr="0x000013a0", data=["0x10", "0x11", "0x12", "0x13"], ascii="xxxx"},
{addr="0x000013a4", data=["0x14", "0x15", "0x16", "0x17"], ascii="xxxx"},
{addr="0x000013a8", data=["0x18", "0x19", "0x1a", "0x1b"], ascii="xxxx"},
{addr="0x000013ac", data=["0x1c", "0x1d", "0x1e", "0x1f"], ascii="xxxx"}]
```

```
{addr="0x000013b0",data=["0x20","0x21","0x22","0x23"],ascii="!\\"#"},
{addr="0x000013b4",data=["0x24","0x25","0x26","0x27"],ascii="$%&'"},
{addr="0x000013b8",data=["0x28","0x29","0x2a","0x2b"],ascii="()*+"},
{addr="0x000013bc",data=["0x2c","0x2d","0x2e","0x2f"],ascii="-. /"}
(gdb)
```

26.9.7. The `-display-delete` Command

26.9.7.1. Synopsis

```
-display-delete number
```

Delete the display `number`.

26.9.7.2. gdb Command

The corresponding gdb command is `delete display`.

26.9.7.3. Example

N.A.

26.9.8. The `-display-disable` Command

26.9.8.1. Synopsis

```
-display-disable number
```

Disable display `number`.

26.9.8.2. gdb Command

The corresponding gdb command is `disable display`.

26.9.8.3. Example

N.A.

26.9.9. The `-display-enable` Command

26.9.9.1. Synopsis

```
-display-enable number
```

Enable display *number*.

26.9.9.2. gdb Command

The corresponding gdb command is `enable display`.

26.9.9.3. Example

N.A.

26.9.10. The `-display-insert` Command

26.9.10.1. Synopsis

```
-display-insert expression
```

Display *expression* every time the program stops.

26.9.10.2. gdb Command

The corresponding gdb command is `display`.

26.9.10.3. Example

N.A.

26.9.11. The `-display-list` Command

26.9.11.1. Synopsis

```
-display-list
```

List the displays. Do not show the current values.

26.9.11.2. gdb Command

The corresponding gdb command is `info display`.

26.9.11.3. Example

N.A.

26.9.12. The `-environment-cd` Command**26.9.12.1. Synopsis**

```
-environment-cd pathdir
```

Set gdb's working directory.

26.9.12.2. gdb Command

The corresponding gdb command is `cd`.

26.9.12.3. Example

```
(gdb)
-environment-cd /kwikemart/marge/ezannoni/flathead-dev/devo/gdb
^done
(gdb)
```

26.9.13. The `-environment-directory` Command**26.9.13.1. Synopsis**

```
-environment-directory [ -r ] [ pathdir ]+
```

Add directories `pathdir` to beginning of search path for source files. If the `-r` option is used, the search path is reset to the default search path. If directories `pathdir` are supplied in addition to the `-r` option, the search path is first reset and then addition occurs as normal. Multiple directories may be specified, separated by blanks. Specifying multiple directories in a single command results in the directories added to the beginning of the search path in the same order they were presented in the command. If blanks are needed as part of a directory name, double-quotes should be used around the name. In the command output, the path will show up separated by the system directory-separator character. The directory-separator character must not be used in any directory name. If no directories are specified, the current search path is displayed.

26.9.13.2. gdb Command

The corresponding gdb command is `dir`.

26.9.13.3. Example

```
(gdb)
-environment-directory /kwikemart/marge/ezannoni/flathead-dev/devo/gdb
^done,source-path="/kwikemart/marge/ezannoni/flathead-dev/devo/gdb:$cdir:$cwd"
(gdb)
-environment-directory ""
^done,source-path="/kwikemart/marge/ezannoni/flathead-dev/devo/gdb:$cdir:$cwd"
(gdb)
-environment-directory -r /home/jjohnstn/src/gdb /usr/src
^done,source-path="/home/jjohnstn/src/gdb:/usr/src:$cdir:$cwd"
(gdb)
-environment-directory -r
^done,source-path="$cdir:$cwd"
(gdb)
```

26.9.14. The `-environment-path` Command

26.9.14.1. Synopsis

```
-environment-path [ -r ] [ pathdir ]+
```

Add directories `pathdir` to beginning of search path for object files. If the `-r` option is used, the search path is reset to the original search path that existed at gdb start-up. If directories `pathdir` are supplied in addition to the `-r` option, the search path is first reset and then addition occurs as normal. Multiple directories may be specified, separated by blanks. Specifying multiple directories in a single command results in the directories added to the beginning of the search path in the same order they were presented in the command. If blanks are needed as part of a directory name, double-quotes should be used around the name. In the command output, the path will show up separated by the system directory-separator character. The directory-separator character must not be used in any directory name. If no directories are specified, the current path is displayed.

26.9.14.2. gdb Command

The corresponding gdb command is `path`.

26.9.14.3. Example

```
(gdb)
-environment-path
^done,path="/usr/bin"
(gdb)
-environment-path /kwikemart/marge/ezannoni/flathead-dev/ppc-eabi/gdb /bin
```

```
^done,path="/kwikemart/marge/ezannoni/flathead-dev/ppc-eabi/gdb:/bin:/usr/bin"
(gdb)
-environment-path -r /usr/local/bin
^done,path="/usr/local/bin:/usr/bin"
(gdb)
```

26.9.15. The `-environment-pwd` Command

26.9.15.1. Synopsis

```
-environment-pwd
```

Show the current working directory.

26.9.15.2. gdb command

The corresponding gdb command is `pwd`.

26.9.15.3. Example

```
(gdb)
-environment-pwd
^done,cwd="/kwikemart/marge/ezannoni/flathead-dev/devo/gdb"
(gdb)
```

26.10. gdb/mi Program control

26.10.1. Program termination

As a result of execution, the inferior program can run to completion, if it doesn't encounter any breakpoints. In this case the output will include an exit code, if the program has exited exceptionally.

26.10.2. Examples

Program exited normally:

```
(gdb)
-exec-run
^running
(gdb)
x = 55
```

```
*stopped, reason="exited-normally"  
(gdb)
```

Program exited exceptionally:

```
(gdb)  
-exec-run  
^running  
(gdb)  
x = 55  
*stopped, reason="exited", exit-code="01"  
(gdb)
```

Another way the program can terminate is if it receives a signal such as `SIGINT`. In this case, `gdb/mi` displays this:

```
(gdb)  
*stopped, reason="exited-signalled", signal-name="SIGINT",  
signal-meaning="Interrupt"
```

26.11. Command Descriptions

The following sections describe various commands.

26.11.1. The `-exec-abort` Command

26.11.1.1. Synopsis

```
-exec-abort
```

Kill the inferior running program.

26.11.1.2. `gdb` Command

The corresponding `gdb` command is `kill`.

26.11.1.3. Example

N.A.

26.11.2. The `-exec-arguments` Command

26.11.2.1. Synopsis

```
-exec-arguments args
```

Set the inferior program arguments, to be used in the next `-exec-run`.

26.11.2.2. gdb Command

The corresponding gdb command is `set args`.

26.11.2.3. Example

Don't have one around.

26.11.3. The `-exec-continue` Command

26.11.3.1. Synopsis

```
-exec-continue
```

Asynchronous command. Resumes the execution of the inferior program until a breakpoint is encountered, or until the inferior exits.

26.11.3.2. gdb Command

The corresponding gdb command is `continue`.

26.11.3.3. Example

```
-exec-continue
^running
(gdb)
@Hello world
*stopped,reason="breakpoint-hit",bkptno="2",frame={func="foo",args=[],
file="hello.c",line="13"}
(gdb)
```

26.11.4. The `-exec-finish` Command

26.11.4.1. Synopsis

```
-exec-finish
```

Asynchronous command. Resumes the execution of the inferior program until the current function is exited. Displays the results returned by the function.

26.11.4.2. gdb Command

The corresponding gdb command is `finish`.

26.11.4.3. Example

Function returning `void`.

```
-exec-finish
^running
(gdb)
@hello from foo
*stopped,reason="function-finished",frame={func="main",args=[]},
file="hello.c",line="7"}
(gdb)
```

Function returning other than `void`. The name of the internal gdb variable storing the result is printed, together with the value itself.

```
-exec-finish
^running
(gdb)
*stopped,reason="function-finished",frame={addr="0x000107b0",func="foo",
args=[{name="a",value="1"},{name="b",value="9"}]},
file="recursive2.c",line="14"},
gdb-result-var="$1",return-value="0"
(gdb)
```

26.11.5. The `-exec-interrupt` Command

26.11.5.1. Synopsis

```
-exec-interrupt
```

Asynchronous command. Interrupts the background execution of the target. Note how the token associated with the stop message is the one for the execution command that has been interrupted. The token for the interrupt itself only appears in the `^done` output. If the user is trying to interrupt a non-running program, an error message will be printed.

26.11.5.2. gdb Command

The corresponding gdb command is `interrupt`.

26.11.5.3. Example

```
(gdb)
111-exec-continue
111^running

(gdb)
222-exec-interrupt
222^done
(gdb)
111*stopped, signal-name="SIGINT", signal-meaning="Interrupt",
frame={addr="0x00010140", func="foo", args=[], file="try.c", line="13"}
(gdb)

(gdb)
-exec-interrupt
^error,msg="mi_cmd_exec_interrupt: Inferior not executing."
(gdb)
```

26.11.6. The `-exec-next` Command

26.11.6.1. Synopsis

```
-exec-next
```

Asynchronous command. Resumes execution of the inferior program, stopping when the beginning of the next source line is reached.

26.11.6.2. gdb Command

The corresponding gdb command is `next`.

26.11.6.3. Example

```
-exec-next
^running
(gdb)
*stopped, reason="end-stepping-range", line="8", file="hello.c"
(gdb)
```

26.11.7. The `-exec-next-instruction` Command

26.11.7.1. Synopsis

```
-exec-next-instruction
```

Asynchronous command. Executes one machine instruction. If the instruction is a function call continues until the function returns. If the program stops at an instruction in the middle of a source line, the address will be printed as well.

26.11.7.2. gdb Command

The corresponding gdb command is `nexti`.

26.11.7.3. Example

```
(gdb)
-exec-next-instruction
^running

(gdb)
*stopped, reason="end-stepping-range",
addr="0x000100d4", line="5", file="hello.c"
(gdb)
```

26.11.8. The `-exec-return` Command

26.11.8.1. Synopsis

```
-exec-return
```

Makes current function return immediately. Doesn't execute the inferior. Displays the new current frame.

26.11.8.2. gdb Command

The corresponding gdb command is `return`.

26.11.8.3. Example

```
(gdb)
200-break-insert callee4
200^done,bkpt={number="1",addr="0x00010734",
file="../../../../devo/gdb/testsuite/gdb.mi/basics.c",line="8"}
(gdb)
000-exec-run
000^running
(gdb)
000*stopped,reason="breakpoint-hit",bkptno="1",
frame={func="callee4",args=[],
file="../../../../devo/gdb/testsuite/gdb.mi/basics.c",line="8"}
(gdb)
205-break-delete
205^done
(gdb)
111-exec-return
111^done,frame={level="0",func="callee3",
args={name="strarg",
value="0x11940 \"A string argument.\""},
file="../../../../devo/gdb/testsuite/gdb.mi/basics.c",line="18"}
(gdb)
```

26.11.9. The `-exec-run` Command

26.11.9.1. Synopsis

```
-exec-run
```

Asynchronous command. Starts execution of the inferior from the beginning. The inferior executes until either a breakpoint is encountered or the program exits.

26.11.9.2. gdb Command

The corresponding gdb command is `run`.

26.11.9.3. Example

```
(gdb)
-break-insert main
^done,bkpt={number="1",addr="0x0001072c",file="recursive2.c",line="4"}
(gdb)
-exec-run
^running
(gdb)
*stopped,reason="breakpoint-hit",bkptno="1",
frame={func="main",args=[],file="recursive2.c",line="4"}
(gdb)
```

26.11.10. The `-exec-show-arguments` Command

26.11.10.1. Synopsis

```
-exec-show-arguments
```

Print the arguments of the program.

26.11.10.2. gdb Command

The corresponding gdb command is `show args`.

26.11.10.3. Example

N.A.

26.11.11. The `-exec-step` Command

26.11.11.1. Synopsis

```
-exec-step
```

Asynchronous command. Resumes execution of the inferior program, stopping when the beginning of the next source line is reached, if the next source line is not a function call. If it is, stop at the first instruction of the called function.

26.11.11.2. gdb Command

The corresponding gdb command is `step`.

26.11.11.3. Example

Stepping into a function:

```
-exec-step
^running
(gdb)
*stopped, reason="end-stepping-range",
frame={func="foo", args=[{name="a", value="10"},
{name="b", value="0"}], file="recursive2.c", line="11"}
(gdb)
```

Regular stepping:

```
-exec-step
^running
(gdb)
*stopped, reason="end-stepping-range", line="14", file="recursive2.c"
(gdb)
```

26.11.12. The `-exec-step-instruction` Command

26.11.12.1. Synopsis

```
-exec-step-instruction
```

Asynchronous command. Resumes the inferior which executes one machine instruction. The output, once gdb has stopped, will vary depending on whether we have stopped in the middle of a source line or not. In the former case, the address at which the program stopped will be printed as well.

26.11.12.2. gdb Command

The corresponding gdb command is `stepi`.

26.11.12.3. Example

```
(gdb)
-exec-step-instruction
^running

(gdb)
*stopped, reason="end-stepping-range",
frame={func="foo", args=[], file="try.c", line="10"}
(gdb)
-exec-step-instruction
^running

(gdb)
*stopped, reason="end-stepping-range",
frame={addr="0x000100f4", func="foo", args=[], file="try.c", line="10"}
(gdb)
```

26.11.13. The `-exec-until` Command

26.11.13.1. Synopsis

```
-exec-until [ location ]
```

Asynchronous command. Executes the inferior until the `location` specified in the argument is reached. If there is no argument, the inferior executes until a source line greater than the current one is reached. The reason for stopping in this case will be `location-reached`.

26.11.13.2. gdb Command

The corresponding gdb command is `until`.

26.11.13.3. Example

```
(gdb)
-exec-until recursive2.c:6
^running
(gdb)
x = 55
*stopped, reason="location-reached", frame={func="main", args=[],
file="recursive2.c", line="6"}
(gdb)
```

26.11.14. The `-file-exec-and-symbols` Command

26.11.14.1. Synopsis

```
-file-exec-and-symbols file
```

Specify the executable file to be debugged. This file is the one from which the symbol table is also read. If no file is specified, the command clears the executable and symbol information. If breakpoints are set when using this command with no arguments, gdb will produce error messages. Otherwise, no output is produced, except a completion notification.

26.11.14.2. gdb Command

The corresponding gdb command is `file`.

26.11.14.3. Example

```
(gdb)
-file-exec-and-symbols /kwikemart/marge/ezannoni/TRUNK/mbx/hello.mbx
^done
(gdb)
```

26.11.15. The `-file-exec-file` Command

26.11.15.1. Synopsis

```
-file-exec-file file
```

Specify the executable file to be debugged. Unlike `-file-exec-and-symbols`, the symbol table is *not* read from this file. If used without argument, gdb clears the information about the executable file. No output is produced, except a completion notification.

26.11.15.2. gdb Command

The corresponding gdb command is `exec-file`.

26.11.15.3. Example

```
(gdb)
-file-exec-file /kwikemart/marge/ezannoni/TRUNK/mbx/hello.mbx
^done
(gdb)
```

26.11.16. The `-file-list-exec-sections` Command

26.11.16.1. Synopsis

```
-file-list-exec-sections
```

List the sections of the current executable file.

26.11.16.2. gdb Command

The gdb command `info file` shows, among the rest, the same information as this command. `gdbtk` has a corresponding command `gdb_load_info`.

26.11.16.3. Example

N.A.

26.11.17. The `-file-list-exec-source-file` Command

26.11.17.1. Synopsis

```
-file-list-exec-source-file
```

List the line number, the current source file, and the absolute path to the current source file for the current executable.

26.11.17.2. gdb Command

There's no gdb command which directly corresponds to this one.

26.11.17.3. Example

```
(gdb)
123-file-list-exec-source-file
123^done,line="1",file="foo.c",fullname="/home/bar/foo.c"
(gdb)
```

26.11.18. The `-file-list-exec-source-files` Command

26.11.18.1. Synopsis

```
-file-list-exec-source-files
```

List the source files for the current executable.

26.11.18.2. gdb Command

There's no gdb command which directly corresponds to this one. `gdbtk` has an analogous command `gdb_listfiles`.

26.11.18.3. Example

N.A.

26.11.19. The `-file-list-shared-libraries` Command

26.11.19.1. Synopsis

```
-file-list-shared-libraries
```

List the shared libraries in the program.

26.11.19.2. gdb Command

The corresponding gdb command is `info shared`.

26.11.19.3. Example

N.A.

26.11.20. The `-file-list-symbol-files` Command

26.11.20.1. Synopsis

```
-file-list-symbol-files
```

List symbol files.

26.11.20.2. gdb Command

The corresponding gdb command is `info file` (part of it).

26.11.20.3. Example

N.A.

26.11.21. The `-file-symbol-file` Command

26.11.21.1. Synopsis

```
-file-symbol-file file
```

Read symbol table info from the specified `file` argument. When used without arguments, clears gdb's symbol table info. No output is produced, except for a completion notification.

26.11.21.2. gdb Command

The corresponding gdb command is `symbol-file`.

26.11.21.3. Example

```
(gdb)
-file-symbol-file /kwikemart/marge/ezannoni/TRUNK/mbx/hello.mbx
^done
(gdb)
```

26.12. Miscellaneous gdb commands in gdb/mi

26.12.1. The `-gdb-exit` Command

26.12.1.1. Synopsis

```
-gdb-exit
```

Exit gdb immediately.

26.12.1.2. gdb Command

Approximately corresponds to `quit`.

26.12.1.3. Example

```
(gdb)
-gdb-exit
```

26.12.2. The `-gdb-set` Command

26.12.2.1. Synopsis

```
-gdb-set
```

Set an internal gdb variable.

26.12.2.2. gdb Command

The corresponding gdb command is `set`.

26.12.2.3. Example

```
(gdb)
-gdb-set $foo=3
^done
(gdb)
```

26.12.3. The `-gdb-show` Command

26.12.3.1. Synopsis

```
-gdb-show
```

Show the current value of a gdb variable.

26.12.3.2. gdb command

The corresponding gdb command is `show`.

26.12.3.3. Example

```
(gdb)
-gdb-show annotate
^done,value="0"
(gdb)
```

26.12.4. The `-gdb-version` Command

26.12.4.1. Synopsis

```
-gdb-version
```

Show version information for gdb. Used mostly in testing.

26.12.4.2. `gdb` Command

There's no equivalent `gdb` command. `gdb` by default shows this information when you start an interactive session.

26.12.4.3. Example

```
(gdb)
-gdb-version
~GNU gdb 5.2.1
~Copyright 2000 Free Software Foundation, Inc.
~GDB is free software, covered by the GNU General Public License, and
~you are welcome to change it and/or distribute copies of it under
~ certain conditions.
~Type "show copying" to see the conditions.
~There is absolutely no warranty for GDB. Type "show warranty" for
~ details.
~This GDB was configured as
  "--host=sparc-sun-solaris2.5.1 --target=ppc-eabi".
^done
(gdb)
```

26.12.5. The `-interpreter-exec` Command

26.12.6. Synopsis

```
-interpreter-exec interpreter command
```

Execute the specified `command` in the given `interpreter`.

26.12.7. gdb Command

The corresponding `gdb` command is `interpreter-exec`.

26.12.8. Example

```
(gdb)
-interpreter-exec console "break main"
&"During symbol reading, couldn't parse type; debugger out of date?.\n"
&"During symbol reading, bad structure-type format.\n"
~"Breakpoint 1 at 0x8074fc6: file ../../src/gdb/main.c, line 743.\n"
^done
(gdb)
```

26.13. gdb/mi Stack Manipulation Commands

26.13.1. The `-stack-info-frame` Command

26.13.1.1. Synopsis

```
-stack-info-frame
```

Get info on the current frame.

26.13.1.2. gdb Command

The corresponding `gdb` command is `info frame` or `frame` (without arguments).

26.13.1.3. Example

N.A.

26.13.2. The `-stack-info-depth` Command

26.13.2.1. Synopsis

```
-stack-info-depth [ max-depth ]
```

Return the depth of the stack. If the integer argument `max-depth` is specified, do not count beyond `max-depth` frames.

26.13.2.2. gdb Command

There's no equivalent gdb command.

26.13.2.3. Example

For a stack with frame levels 0 through 11:

```
(gdb)
-stack-info-depth
^done,depth="12"
(gdb)
-stack-info-depth 4
^done,depth="4"
(gdb)
-stack-info-depth 12
^done,depth="12"
(gdb)
-stack-info-depth 11
^done,depth="11"
(gdb)
-stack-info-depth 13
^done,depth="12"
(gdb)
```

26.13.3. The `-stack-list-arguments` Command

26.13.3.1. Synopsis

```
-stack-list-arguments show-values
  [ low-frame high-frame ]
```

Display a list of the arguments for the frames between `low-frame` and `high-frame` (inclusive). If `low-frame` and `high-frame` are not provided, list the arguments for the whole call stack.

The `show-values` argument must have a value of 0 or 1. A value of 0 means that only the names of the arguments are listed, a value of 1 means that both names and values of the arguments are printed.

26.13.3.2. gdb Command

`gdb` does not have an equivalent command. `gdbtk` has a `gdb_get_args` command which partially overlaps with the functionality of `-stack-list-arguments`.

26.13.3.3. Example

```
(gdb)
-stack-list-frames
^done,
stack=[
frame={level="0",addr="0x00010734",func="callee4",
file="../../../../devo/gdb/testsuite/gdb.mi/basics.c",line="8"},
frame={level="1",addr="0x0001076c",func="callee3",
file="../../../../devo/gdb/testsuite/gdb.mi/basics.c",line="17"},
frame={level="2",addr="0x0001078c",func="callee2",
file="../../../../devo/gdb/testsuite/gdb.mi/basics.c",line="22"},
frame={level="3",addr="0x000107b4",func="calleel1",
file="../../../../devo/gdb/testsuite/gdb.mi/basics.c",line="27"},
frame={level="4",addr="0x000107e0",func="main",
file="../../../../devo/gdb/testsuite/gdb.mi/basics.c",line="32"}}]
(gdb)
-stack-list-arguments 0
^done,
stack-args=[
frame={level="0",args=[]},
frame={level="1",args=[name="strarg"]},
frame={level="2",args=[name="intarg",name="strarg"]},
frame={level="3",args=[name="intarg",name="strarg",name="fltarg"]},
frame={level="4",args=[]}]
(gdb)
-stack-list-arguments 1
^done,
stack-args=[
frame={level="0",args=[]},
frame={level="1",
args=[{name="strarg",value="0x11940 \A string argument.\""}]},
frame={level="2",args=[
{name="intarg",value="2"},
{name="strarg",value="0x11940 \A string argument.\""}]},
frame={level="3",args=[
{name="intarg",value="2"},
{name="strarg",value="0x11940 \A string argument.\""},
{name="fltarg",value="3.5"}]},
frame={level="4",args=[]}]
(gdb)
-stack-list-arguments 0 2 2
^done,stack-args=[frame={level="2",args=[name="intarg",name="strarg"]}]
(gdb)
-stack-list-arguments 1 2 2
^done,stack-args=[frame={level="2",
args=[{name="intarg",value="2"},
{name="strarg",value="0x11940 \A string argument.\""}]}]
```

26.13.4. The `-stack-list-frames` Command

26.13.4.1. Synopsis

```
-stack-list-frames [ low-frame high-frame ]
```

List the frames currently on the stack. For each frame it displays the following info:

level

The frame number, 0 being the topmost frame, that is, the innermost function.

addr

The `$pc` value for that frame.

func

Function name.

file

File name of the source file where the function lives.

line

Line number corresponding to the `$pc`.

If invoked without arguments, this command prints a backtrace for the whole stack. If given two integer arguments, it shows the frames whose levels are between the two arguments (inclusive). If the two arguments are equal, it shows the single frame at the corresponding level.

26.13.4.2. `gdb` Command

The corresponding `gdb` commands are `backtrace` and `where`.

26.13.4.3. Example

Full stack backtrace:

```
(gdb)
-stack-list-frames
^done, stack=
[frame={level="0", addr="0x0001076c", func="foo",
  file="recursive2.c", line="11"},
frame={level="1", addr="0x000107a4", func="foo",
  file="recursive2.c", line="14"},
frame={level="2", addr="0x000107a4", func="foo",
  file="recursive2.c", line="14"},
frame={level="3", addr="0x000107a4", func="foo",
  file="recursive2.c", line="14"},
frame={level="4", addr="0x000107a4", func="foo",
  file="recursive2.c", line="14"},
frame={level="5", addr="0x000107a4", func="foo",
  file="recursive2.c", line="14"},
frame={level="6", addr="0x000107a4", func="foo",
```

```

file="recursive2.c",line="14"},
frame={level="7",addr="0x000107a4",func="foo",
file="recursive2.c",line="14"},
frame={level="8",addr="0x000107a4",func="foo",
file="recursive2.c",line="14"},
frame={level="9",addr="0x000107a4",func="foo",
file="recursive2.c",line="14"},
frame={level="10",addr="0x000107a4",func="foo",
file="recursive2.c",line="14"},
frame={level="11",addr="0x00010738",func="main",
file="recursive2.c",line="4"}]
(gdb)

```

Show frames between `low_frame` and `high_frame`:

```

(gdb)
-stack-list-frames 3 5
^done,stack=
[frame={level="3",addr="0x000107a4",func="foo",
file="recursive2.c",line="14"},
frame={level="4",addr="0x000107a4",func="foo",
file="recursive2.c",line="14"},
frame={level="5",addr="0x000107a4",func="foo",
file="recursive2.c",line="14"}]
(gdb)

```

Show a single frame:

```

(gdb)
-stack-list-frames 3 3
^done,stack=
[frame={level="3",addr="0x000107a4",func="foo",
file="recursive2.c",line="14"}]
(gdb)

```

26.13.5. The `-stack-list-locals` Command

26.13.5.1. Synopsis

```
-stack-list-locals print-values
```

Display the local variable names for the current frame. With an argument of 0 prints only the names of the variables, with argument of 1 prints also their values.

26.13.5.2. gdb Command

`info locals` in `gdb`, `gdb_get_locals` in `gdbtk`.

26.13.5.3. Example

```
(gdb)
-stack-list-locals 0
^done,locals=[name="A",name="B",name="C"]
(gdb)
-stack-list-locals 1
^done,locals=[{name="A",value="1"},{name="B",value="2"},
  {name="C",value="3"}]
(gdb)
```

26.13.6. The `-stack-select-frame` Command

26.13.6.1. Synopsis

```
-stack-select-frame framenum
```

Change the current frame. Select a different frame `framenum` on the stack.

26.13.6.2. gdb Command

The corresponding `gdb` commands are `frame`, `up`, `down`, `select-frame`, `up-silent`, and `down-silent`.

26.13.6.3. Example

```
(gdb)
-stack-select-frame 2
^done
(gdb)
```

26.14. gdb/mi Symbol Query Commands

26.14.1. The `-symbol-info-address` Command

26.14.1.1. Synopsis

```
-symbol-info-address symbol
```

Describe where `symbol` is stored.

26.14.1.2. gdb Command

The corresponding gdb command is `info address`.

26.14.1.3. Example

N.A.

26.14.2. The `-symbol-info-file` Command

26.14.2.1. Synopsis

```
-symbol-info-file
```

Show the file for the symbol.

26.14.2.2. gdb Command

There's no equivalent gdb command. `gdbtk` has `gdb_find_file`.

26.14.2.3. Example

N.A.

26.14.3. The `-symbol-info-function` Command

26.14.3.1. Synopsis

```
-symbol-info-function
```

Show which function the symbol lives in.

26.14.3.2. gdb Command

`gdb_get_function` in `gdbtk`.

26.14.3.3. Example

N.A.

26.14.4. The `-symbol-info-line` Command

26.14.4.1. Synopsis

```
-symbol-info-line
```

Show the core addresses of the code for a source line.

26.14.4.2. gdb Command

The corresponding gdb command is `info line`. `gdbtk` has the `gdb_get_line` and `gdb_get_file` commands.

26.14.4.3. Example

N.A.

26.14.5. The `-symbol-info-symbol` Command

26.14.5.1. Synopsis

```
-symbol-info-symbol addr
```

Describe what symbol is at location `addr`.

26.14.5.2. gdb Command

The corresponding gdb command is `info symbol`.

26.14.5.3. Example

N.A.

26.14.6. The `-symbol-list-functions` Command

26.14.6.1. Synopsis

```
-symbol-list-functions
```

List the functions in the executable.

26.14.6.2. gdb Command

`info functions` in `gdb`, `gdb_listfunc` and `gdb_search` in `gdbtk`.

26.14.6.3. Example

N.A.

26.14.7. The `-symbol-list-lines` Command

26.14.7.1. Synopsis

```
-symbol-list-lines filename
```

Print the list of lines that contain code and their associated program addresses for the given source filename. The entries are sorted in ascending PC order.

26.14.7.2. gdb Command

There is no corresponding `gdb` command.

26.14.7.3. Example

```
(gdb)
-symbol-list-lines basics.c
^done,lines=[{pc="0x08048554",line="7"},{pc="0x0804855a",line="8"}]
(gdb)
```

26.14.8. The `-symbol-list-types` Command

26.14.8.1. Synopsis

```
-symbol-list-types
```

List all the type names.

26.14.8.2. gdb Command

The corresponding commands are `info types` in `gdb`, `gdb_search` in `gdbtk`.

26.14.8.3. Example

N.A.

26.14.9. The `-symbol-list-variables` Command

26.14.9.1. Synopsis

```
-symbol-list-variables
```

List all the global and static variable names.

26.14.9.2. gdb Command

`info variables` in `gdb`, `gdb_search` in `gdbtk`.

26.14.9.3. Example

N.A.

26.14.10. The `-symbol-locate` Command

26.14.10.1. Synopsis

```
-symbol-locate
```

26.14.10.2. gdb Command

`gdb_loc` in `gdbtk`.

26.14.10.3. Example

N.A.

26.14.11. The `-symbol-type` Command

26.14.11.1. Synopsis

```
-symbol-type variable
```

Show type of `variable`.

26.14.11.2. gdb Command

The corresponding gdb command is `p`type, `gdbtk` has `gdb_obj_variable`.

26.14.11.3. Example

N.A.

26.15. gdb/mi Target Manipulation Commands

26.15.1. The `-target-attach` Command

26.15.1.1. Synopsis

```
-target-attach pid | file
```

Attach to a process `pid` or a file `file` outside of `gdb`.

26.15.1.2. gdb command

The corresponding gdb command is `attach`.

26.15.1.3. Example

N.A.

26.15.2. The `-target-compare-sections` Command**26.15.2.1. Synopsis**

```
-target-compare-sections [ section ]
```

Compare data of section `section` on target to the exec file. Without the argument, all sections are compared.

26.15.2.2. gdb Command

The gdb equivalent is `compare-sections`.

26.15.2.3. Example

N.A.

26.15.3. The `-target-detach` Command**26.15.3.1. Synopsis**

```
-target-detach
```

Disconnect from the remote target. There's no output.

26.15.3.2. gdb command

The corresponding gdb command is `detach`.

26.15.3.3. Example

```
(gdb)
-target-detach
^done
(gdb)
```

26.15.4. The `-target-disconnect` Command

26.15.4.1. Synopsis

```
-target-disconnect
```

Disconnect from the remote target. There's no output.

26.15.4.2. gdb command

The corresponding gdb command is `disconnect`.

26.15.4.3. Example

```
(gdb)
-target-disconnect
^done
(gdb)
```

26.15.5. The `-target-download` Command

26.15.5.1. Synopsis

```
-target-download
```

Loads the executable onto the remote target. It prints out an update message every half second, which includes the fields:

```
section
```

The name of the section.

```
section-sent
```

The size of what has been sent so far for that section.

```
section-size
```

The size of the section.

```
total-sent
```

The total size of what was sent so far (the current and the previous sections).

total-size

The size of the overall executable to download.

Each message is sent as status record (refer to Section 26.4.2 *gdb/mi Output Syntax*).

In addition, it prints the name and size of the sections, as they are downloaded. These messages include the following fields:

section

The name of the section.

section-size

The size of the section.

total-size

The size of the overall executable to download.

At the end, a summary is printed.

26.15.5.2. gdb Command

The corresponding gdb command is `load`.

26.15.5.3. Example

Note: each status message appears on a single line. Here the messages have been broken down so that they can fit onto a page.

```
(gdb)
-target-download
+download,{section=".text",section-size="6668",total-size="9880"}
+download,{section=".text",section-sent="512",section-size="6668",
total-sent="512",total-size="9880"}
+download,{section=".text",section-sent="1024",section-size="6668",
total-sent="1024",total-size="9880"}
+download,{section=".text",section-sent="1536",section-size="6668",
total-sent="1536",total-size="9880"}
+download,{section=".text",section-sent="2048",section-size="6668",
total-sent="2048",total-size="9880"}
+download,{section=".text",section-sent="2560",section-size="6668",
total-sent="2560",total-size="9880"}
+download,{section=".text",section-sent="3072",section-size="6668",
total-sent="3072",total-size="9880"}
+download,{section=".text",section-sent="3584",section-size="6668",
total-sent="3584",total-size="9880"}
+download,{section=".text",section-sent="4096",section-size="6668",
total-sent="4096",total-size="9880"}
+download,{section=".text",section-sent="4608",section-size="6668",
total-sent="4608",total-size="9880"}
+download,{section=".text",section-sent="5120",section-size="6668",
total-sent="5120",total-size="9880"}
+download,{section=".text",section-sent="5632",section-size="6668",
total-sent="5632",total-size="9880"}
+download,{section=".text",section-sent="6144",section-size="6668",
total-sent="6144",total-size="9880"}
+download,{section=".text",section-sent="6656",section-size="6668",
total-sent="6656",total-size="9880"}
```

```
+download,{section=".init",section-size="28",total-size="9880"}
+download,{section=".fini",section-size="28",total-size="9880"}
+download,{section=".data",section-size="3156",total-size="9880"}
+download,{section=".data",section-sent="512",section-size="3156",
total-sent="7236",total-size="9880"}
+download,{section=".data",section-sent="1024",section-size="3156",
total-sent="7748",total-size="9880"}
+download,{section=".data",section-sent="1536",section-size="3156",
total-sent="8260",total-size="9880"}
+download,{section=".data",section-sent="2048",section-size="3156",
total-sent="8772",total-size="9880"}
+download,{section=".data",section-sent="2560",section-size="3156",
total-sent="9284",total-size="9880"}
+download,{section=".data",section-sent="3072",section-size="3156",
total-sent="9796",total-size="9880"}
^done,address="0x10004",load-size="9880",transfer-rate="6586",
write-rate="429"
(gdb)
```

26.15.6. The `-target-exec-status` Command

26.15.6.1. Synopsis

```
-target-exec-status
```

Provide information on the state of the target (whether it is running or not, for instance).

26.15.6.2. gdb Command

There's no equivalent gdb command.

26.15.6.3. Example

N.A.

26.15.7. The `-target-list-available-targets` Command

26.15.7.1. Synopsis

```
-target-list-available-targets
```

List the possible targets to connect to.

26.15.7.2. gdb Command

The corresponding gdb command is `help target`.

26.15.7.3. Example

N.A.

26.15.8. The `-target-list-current-targets` Command

26.15.8.1. Synopsis

```
-target-list-current-targets
```

Describe the current target.

26.15.8.2. gdb Command

The corresponding information is printed by `info file` (among other things).

26.15.8.3. Example

N.A.

26.15.9. The `-target-list-parameters` Command

26.15.9.1. Synopsis

```
-target-list-parameters
```

26.15.9.2. gdb Command

No equivalent.

26.15.9.3. Example

N.A.

26.15.10. The `-target-select` Command

26.15.10.1. Synopsis

```
-target-select type parameters ...
```

Connect gdb to the remote target. This command takes two args:

type

The type of target, for instance `async`, `remote`, etc.

parameters

Device names, host names and the like. Refer to Section 18.2 *Commands for managing targets*, for more details.

The output is a connection notification, followed by the address at which the target program is, in the following form:

```
^connected,addr="address",func="function name",
  args=[arg list]
```

26.15.10.2. `gdb` Command

The corresponding `gdb` command is `target`.

26.15.10.3. Example

```
(gdb)
-target-select async /dev/ttya
^connected,addr="0xfe00a300",func="??",args=[]
(gdb)
```

26.16. gdb/mi Thread Commands

26.16.1. The `-thread-info` Command

26.16.1.1. Synopsis

`-thread-info`

26.16.1.2. gdb command

No equivalent.

26.16.1.3. Example

N.A.

26.16.2. The `-thread-list-all-threads` Command

26.16.2.1. Synopsis

`-thread-list-all-threads`

26.16.2.2. gdb Command

The equivalent gdb command is `info threads`.

26.16.2.3. Example

N.A.

26.16.3. The `-thread-list-ids` Command

26.16.3.1. Synopsis

`-thread-list-ids`

Produces a list of the currently known gdb thread ids. At the end of the list it also prints the total number of such threads.

26.16.3.2. gdb Command

Part of `info threads` supplies the same information.

26.16.3.3. Example

No threads present, besides the main process:

```
(gdb)
~thread-list-ids
^done,thread-ids={},number-of-threads="0"
(gdb)
```

Several threads:

```
(gdb)
~thread-list-ids
^done,thread-ids={thread-id="3",thread-id="2",thread-id="1"},
number-of-threads="3"
(gdb)
```

26.16.4. The `-thread-select` Command**26.16.4.1. Synopsis**

```
-thread-select threadnum
```

Make `threadnum` the current thread. It prints the number of the new current thread, and the topmost frame for that thread.

26.16.4.2. gdb Command

The corresponding gdb command is `thread`.

26.16.4.3. Example

```
(gdb)
~exec-next
^running
(gdb)
*stopped,reason="end-stepping-range",thread-id="2",line="187",
file="../../../../devo/gdb/testsuite/gdb.threads/linux-dp.c"
(gdb)
~thread-list-ids
^done,
thread-ids={thread-id="3",thread-id="2",thread-id="1"},
number-of-threads="3"
(gdb)
~thread-select 3
^done,new-thread-id="3",
frame={level="0",func="vprintf",
```

```
args={name="format",value="0x8048e9c \"%*s%c %d %c\\n\\n\""},
{name="arg",value="0x2"}},file="vprintf.c",line="31"}
(gdb)
```

26.17. gdb/mi Tracepoint Commands

The tracepoint commands are not yet implemented.

26.18. gdb/mi Variable Objects

26.18.1. Motivation for Variable Objects in gdb/mi

For the implementation of a variable debugger window (locals, watched expressions, etc.), we are proposing the adaptation of the existing code used by *Insight*.

The two main reasons for that are:

1. It has been proven in practice (it is already on its second generation).
2. It will shorten development time (needless to say how important it is now).

The original interface was designed to be used by Tcl code, so it was slightly changed so it could be used through gdb/mi. This section describes the gdb/mi operations that will be available and gives some hints about their use.

Note: In addition to the set of operations described here, we expect the gui implementation of a variable window to require, at least, the following operations:

- `-gdb-show output-radix`
- `-stack-list-arguments`
- `-stack-list-locals`
- `-stack-select-frame`

26.18.2. Introduction to Variable Objects in gdb/mi

The basic idea behind variable objects is the creation of a named object to represent a variable, an expression, a memory location or even a CPU register. For each object created, a set of operations is available for examining or changing its properties.

Furthermore, complex data types, such as C structures, are represented in a tree format. For instance, the `struct` type variable is the root and the children will represent the struct members. If a child is itself of a complex type, it will also have children of its own. Appropriate language differences are handled for C, C++ and Java.

When returning the actual values of the objects, this facility allows for the individual selection of the display format used in the result creation. It can be chosen among: binary, decimal, hexadecimal, octal and natural. Natural refers to a default format automatically chosen based on the variable type (like decimal for an `int`, hex for pointers, etc.).

The following is the complete set of gdb/mi operations defined to access this functionality:

<i>Operation</i>	<i>Description</i>
<code>-var-create</code>	create a variable object
<code>-var-delete</code>	delete the variable object and its children
<code>-var-set-format</code>	set the display format of this variable
<code>-var-show-format</code>	show the display format of this variable
<code>-var-info-num-children</code>	tells how many children this object has
<code>-var-list-children</code>	return a list of the object's children
<code>-var-info-type</code>	show the type of this variable object
<code>-var-info-expression</code>	print what this variable object represents
<code>-var-show-attributes</code>	is this variable editable? does it exist here?
<code>-var-evaluate-expression</code>	get the value of this variable
<code>-var-assign</code>	set the value of this variable
<code>-var-update</code>	update the variable and its children

In the next subsection we describe each operation in detail and suggest how it can be used.

26.18.3. Description And Use of Operations on Variable Objects

This section describes the use of operations on variable objects.

26.18.4. The `-var-create` Command

26.18.4.1. Synopsis

```
-var-create {name | "-"}
           {frame-addr | "*"} expression
```

This operation creates a variable object, which allows the monitoring of a variable, the result of an expression, a memory cell or a CPU register.

The `name` parameter is the string by which the object can be referenced. It must be unique. If `-` is specified, the `varobj` system will generate a string "varNNNNNN" automatically. It will be unique provided that one does not specify `name` on that format. The command fails if a duplicate name is found.

The frame under which the expression should be evaluated can be specified by `frame-addr`. A `*` indicates that the current frame should be used.

`expression` is any expression valid on the current language set (must not begin with a `*`), or one of the following:

- `*addr`, where `addr` is the address of a memory cell
- `*addr-addr --` a memory address range (TBD)

- `$regname` -- a CPU register name

26.18.4.2. Result

This operation returns the name, number of children and the type of the object created. Type is returned as a string as the ones generated by the gdb CLI:

```
name="name", numchild="N", type="type"
```

26.18.5. The `-var-delete` Command

26.18.5.1. Synopsis

```
-var-delete name
```

Deletes a previously created variable object and all of its children.

Returns an error if the object `name` is not found.

26.18.6. The `-var-set-format` Command

26.18.6.1. Synopsis

```
-var-set-format name format-spec
```

Sets the output format for the value of the object `name` to be `format-spec`.

The syntax for the `format-spec` is as follows:

```
format-spec ==>
{binary | decimal | hexadecimal | octal | natural}
```

26.18.7. The `-var-show-format` Command

26.18.7.1. Synopsis

```
-var-show-format name
```

Returns the format used to display the value of the object name.

```
format ==>
format-spec
```

26.18.8. The `-var-info-num-children` Command**26.18.8.1. Synopsis**

```
-var-info-num-children name
```

Returns the number of children of a variable object name:

```
numchild=n
```

26.18.9. The `-var-list-children` Command**26.18.9.1. Synopsis**

```
-var-list-children name
```

Returns a list of the children of the specified variable object:

```
numchild=n, children=[{name=name,
numchild=n,type=type}, (repeats N times)]
```

26.18.10. The `-var-info-type` Command

26.18.10.1. Synopsis

```
-var-info-type name
```

Returns the type of the specified variable `name`. The type is returned as a string in the same format as it is output by the gdb CLI:

```
type=typename
```

26.18.11. The `-var-info-expression` Command**26.18.11.1. Synopsis**

```
-var-info-expression name
```

Returns what is represented by the variable object `name`:

```
lang=lang-spec,exp=expression
```

where `lang-spec` is { "C" | "C++" | "Java" }.

26.18.12. The `-var-show-attributes` Command**26.18.12.1. Synopsis**

```
-var-show-attributes name
```

List attributes of the specified variable object `name`:

```
status=attr [ ( ,attr ) * ]
```

where `attr` is { { editable | noneditable } | TBD }.

26.18.13. The `-var-evaluate-expression` Command

26.18.13.1. Synopsis

```
-var-evaluate-expression name
```

Evaluates the expression that is represented by the specified variable object and returns its value as a string in the current format specified for the object:

```
value=value
```

Note that one must invoke `-var-list-children` for a variable before the value of a child variable can be evaluated.

26.18.14. The `-var-assign` Command**26.18.14.1. Synopsis**

```
-var-assign name expression
```

Assigns the value of `expression` to the variable object specified by `name`. The object must be `editable`. If the variable's value is altered by the assign, the variable will show up in any subsequent `-var-update list`.

26.18.14.2. Example

```
(gdb)
-var-assign var1 3
^done,value="3"
(gdb)
-var-update *
^done,changelist=[{name="var1",in_scope="true",type_changed="false"}]
(gdb)
```

26.18.15. The `-var-update` Command**26.18.15.1. Synopsis**

```
-var-update {name | "*"}
```

Update the value of the variable object `name` by evaluating its expression after fetching all the new values from memory or registers. A `*` causes all existing variable objects to be updated.

This chapter describes annotations in `gdb`. Annotations are designed to interface `gdb` to graphical user interfaces or other similar programs which want to interact with `gdb` at a relatively high level.

27.1. What is an Annotation?

To produce annotations, start `gdb` with the `--annotate=2` option.

Annotations start with a newline character, two `control-z` characters, and the name of the annotation. If there is no additional information associated with this annotation, the name of the annotation is followed immediately by a newline. If there is additional information, the name of the annotation is followed by a space, the additional information, and a newline. The additional information cannot contain newline characters.

Any output not beginning with a newline and two `control-z` characters denotes literal output from `gdb`. Currently there is no need for `gdb` to output a newline followed by two `control-z` characters, but if there was such a need, the annotations could be extended with an `escape` annotation which means those three characters as output.

A simple example of starting up `gdb` with annotations is:

```
$ gdb --annotate=2
GNU GDB 5.0
Copyright 2000 Free Software Foundation, Inc.
GDB is free software, covered by the GNU General Public License,
and you are welcome to change it and/or distribute copies of it
under certain conditions.
Type "show copying" to see the conditions.
There is absolutely no warranty for GDB. Type "show warranty"
for details.
This GDB was configured as "sparc-sun-sunos4.1.3"

^Z^Zpre-prompt
(gdb)
^Z^Zprompt
quit

^Z^Zpost-prompt
$
```

Here `quit` is input to `gdb`; the rest is output from `gdb`. The three lines beginning `^Z^Z` (where `^Z` denotes a `control-z` character) are annotations; the rest is output from `gdb`.

27.2. The Server Prefix

To issue a command to `gdb` without affecting certain aspects of the state which is seen by users, prefix it with `server`. This means that this command will not affect the command history, nor will it affect `gdb`'s notion of which command to repeat if [RET] is pressed on a line by itself.

The server prefix does not affect the recording of values into the value history; to print a value without recording it into the value history, use the `output` command instead of the `print` command.

27.3. Values

When a value is printed in various contexts, gdb uses annotations to delimit the value from the surrounding text.

If a value is printed using `print` and added to the value history, the annotation looks like

```
^Z^Zvalue-history-begin history-number value-flags
history-string
^Z^Zvalue-history-value
the-value
^Z^Zvalue-history-end
```

where `history-number` is the number it is getting in the value history, `history-string` is a string, such as `$5 =`, which introduces the value to the user, `the-value` is the output corresponding to the value itself, and `value-flags` is `*` for a value which can be dereferenced and `-` for a value which cannot.

If the value is not added to the value history (it is an invalid float or it is printed with the `output` command), the annotation is similar:

```
^Z^Zvalue-begin value-flags
the-value
^Z^Zvalue-end
```

When gdb prints an argument to a function (for example, in the output from the `backtrace` command), it annotates it as follows:

```
^Z^Zarg-begin
argument-name
^Z^Zarg-name-end
separator-string
^Z^Zarg-value value-flags
the-value
^Z^Zarg-end
```

where `argument-name` is the name of the argument, `separator-string` is text which separates the name from the value for the user's benefit (such as `=`), and `value-flags` and `the-value` have the same meanings as in a `value-history-begin` annotation.

When printing a structure, gdb annotates it as follows:

```
^Z^Zfield-begin value-flags
field-name
^Z^Zfield-name-end
separator-string
^Z^Zfield-value
the-value
^Z^Zfield-end
```

where `field-name` is the name of the field, `separator-string` is text which separates the name from the value for the user's benefit (such as `=`), and `value-flags` and `the-value` have the same meanings as in a `value-history-begin` annotation.

When printing an array, gdb annotates it as follows:

```
^Z^Zarray-section-begin array-index value-flags
```

where `array-index` is the index of the first element being annotated and `value-flags` has the same meaning as in a `value-history-begin` annotation. This is followed by any number of elements, where is element can be either a single element:

```
, whitespace          ; omitted for the first element
the-value
^Z^Zelt
```

or a repeated element

```
, whitespace          ; omitted for the first element
the-value
^Z^Zelt-rep number-of-repetitions
repetition-string
^Z^Zelt-rep-end
```

In both cases, `the-value` is the output for the value of the element and `whitespace` can contain spaces, tabs, and newlines. In the repeated case, `number-of-repetitions` is the number of consecutive array elements which contain that value, and `repetition-string` is a string which is designed to convey to the user that repetition is being depicted.

Once all the array elements have been output, the array annotation is ended with

```
^Z^Zarray-section-end
```

27.4. Frames

Whenever gdb prints a frame, it annotates it. For example, this applies to frames printed when gdb stops, output from commands such as `backtrace` or `up`, etc.

The frame annotation begins with

```
^Z^Zframe-begin level address
level-string
```

where `level` is the number of the frame (0 is the innermost frame, and other frames have positive numbers), `address` is the address of the code executing in that frame, and `level-string` is a string designed to convey the level to the user. `address` is in the form `0x` followed by one or more lowercase hex digits (note that this does not depend on the language). The frame ends with

```
^Z^Zframe-end
```

Between these annotations is the main body of the frame, which can consist of

- ```

^Z^Zfunction-call
function-call-string

```

where `function-call-string` is text designed to convey to the user that this frame is associated with a function call made by gdb to a function in the program being debugged.

- ```

^Z^Zsignal-handler-caller
signal-handler-caller-string
      
```

where `signal-handler-caller-string` is text designed to convey to the user that this frame is associated with whatever mechanism is used by this operating system to call a signal handler (it is the frame which calls the signal handler, not the frame for the signal handler itself).

- A normal frame.

This can optionally (depending on whether this is thought of as interesting information for the user to see) begin with

```

^Z^Zframe-address
address
^Z^Zframe-address-end
separator-string
      
```

where `address` is the address executing in the frame (the same address as in the `frame-begin` annotation, but printed in a form which is intended for user consumption--in particular, the syntax varies depending on the language), and `separator-string` is a string intended to separate this address from what follows for the user's benefit.

Then comes

```

^Z^Zframe-function-name
function-name
^Z^Zframe-args
arguments
      
```

where `function-name` is the name of the function executing in the frame, or `??` if not known, and `arguments` are the arguments to the frame, with parentheses around them (each argument is annotated individually as well, (refer to Section 27.3 *Values*)).

If source information is available, a reference to it is then printed:

```

^Z^Zframe-source-begin
source-intro-string
^Z^Zframe-source-file
filename
^Z^Zframe-source-file-end
:
^Z^Zframe-source-line
line-number
^Z^Zframe-source-end
      
```

where `source-intro-string` separates for the user's benefit the reference from the text which precedes it, `filename` is the name of the source file, and `line-number` is the line number within that file (the first line is line 1).

If gdb prints some information about where the frame is from (which library, which load segment, etc.; currently only done on the RS/6000), it is annotated with

```

^Z^Zframe-where
information
      
```

Then, if source is to actually be displayed for this frame (for example, this is not true for output from the `backtrace` command), then a `source` annotation (refer to Section 27.11 *Displaying Source*) is displayed. Unlike most annotations, this is output instead of the normal text which would be output, not in addition.

27.5. Displays

When gdb is told to display something using the `display` command, the results of the display are annotated:

```
^Z^Zdisplay-begin
number
^Z^Zdisplay-number-end
number-separator
^Z^Zdisplay-format
format
^Z^Zdisplay-expression
expression
^Z^Zdisplay-expression-end
expression-separator
^Z^Zdisplay-value
value
^Z^Zdisplay-end
```

where `number` is the number of the display, `number-separator` is intended to separate the number from what follows for the user, `format` includes information such as the size, format, or other information about how the value is being displayed, `expression` is the expression being displayed, `expression-separator` is intended to separate the expression from the text that follows for the user, and `value` is the actual value being displayed.

27.6. Annotation for gdb Input

When gdb prompts for input, it annotates this fact so it is possible to know when to send output, when the output from a given command is over, etc.

Different kinds of input each have a different *input type*. Each input type has three annotations: a `pre-` annotation, which denotes the beginning of any prompt which is being output, a plain annotation, which denotes the end of the prompt, and then a `post-` annotation which denotes the end of any echo which may (or may not) be associated with the input. For example, the `prompt` input type features the following annotations:

```
^Z^Zpre-prompt
^Z^Zprompt
^Z^Zpost-prompt
```

The input types are

```
prompt
```

When gdb is prompting for a command (the main gdb prompt).

commands

When gdb prompts for a set of commands, like in the `commands` command. The annotations are repeated for each command which is input.

overload-choice

When gdb wants the user to select between various overloaded functions.

query

When gdb wants the user to confirm a potentially dangerous operation.

prompt-for-continue

When gdb is asking the user to press return to continue. Note: Don't expect this to work well; instead use `set height 0` to disable prompting. This is because the counting of lines is buggy in the presence of annotations.

27.7. Errors

`^Z^Zquit`

This annotation occurs right before gdb responds to an interrupt.

`^Z^Zerror`

This annotation occurs right before gdb responds to an error.

Quit and error annotations indicate that any annotations which gdb was in the middle of may end abruptly. For example, if a `value-history-begin` annotation is followed by a `error`, one cannot expect to receive the matching `value-history-end`. One cannot expect not to receive it either, however; an error annotation does not necessarily mean that gdb is immediately returning all the way to the top level.

A quit or error annotation may be preceded by

`^Z^Zerror-begin`

Any output between that and the quit or error annotation is the error message.

Warning messages are not yet annotated.

27.8. Information on Breakpoints

The output from the `info breakpoints` command is annotated as follows:

```
^Z^Zbreakpoints-headers
header-entry
^Z^Zbreakpoints-table
```

where `header-entry` has the same syntax as an entry (see below) but instead of containing data, it contains strings which are intended to convey the meaning of each field to the user. This is followed by any number of entries. If a field does not apply for this entry, it is omitted. Fields may contain trailing whitespace. Each entry consists of:

```

^Z^Zrecord
^Z^Zfield 0
number
^Z^Zfield 1
type
^Z^Zfield 2
disposition
^Z^Zfield 3
enable
^Z^Zfield 4
address
^Z^Zfield 5
what
^Z^Zfield 6
frame
^Z^Zfield 7
condition
^Z^Zfield 8
ignore-count
^Z^Zfield 9
commands

```

Note that `address` is intended for user consumption--the syntax varies depending on the language.

The output ends with

```
^Z^Zbreakpoints-table-end
```

27.9. Invalidation Notices

The following annotations say that certain pieces of state may have changed.

```
^Z^Zframes-invalid
```

The frames (for example, output from the `backtrace` command) may have changed.

```
^Z^Zbreakpoints-invalid
```

The breakpoints may have changed. For example, the user just added or deleted a breakpoint.

27.10. Running the Program

When the program starts executing due to a `gdb` command such as `step` or `continue`,

```
^Z^Zstarting
```

is output. When the program stops,

```
^Z^Zstopped
```

is output. Before the `stopped` annotation, a variety of annotations describe how the program stopped.

```
^Z^Zexited exit-status
```

The program exited, and `exit-status` is the exit status (zero for successful exit, otherwise nonzero).

```
^Z^Zsignalled
```

The program exited with a signal. After the `^Z^Zsignalled`, the annotation continues:

```
intro-text
^Z^Zsignal-name
name
^Z^Zsignal-name-end
middle-text
^Z^Zsignal-string
string
^Z^Zsignal-string-end
end-text
```

where `name` is the name of the signal, such as `SIGILL` or `SIGSEGV`, and `string` is the explanation of the signal, such as `Illegal Instruction` or `Segmentation fault`. `intro-text`, `middle-text`, and `end-text` are for the user's benefit and have no particular format.

```
^Z^Zsignal
```

The syntax of this annotation is just like `signalled`, but `gdb` is just saying that the program received the signal, not that it was terminated with it.

```
^Z^Zbreakpoint number
```

The program hit breakpoint `number`.

```
^Z^Zwatchpoint number
```

The program hit watchpoint `number`.

27.11. Displaying Source

The following annotation is used instead of displaying source code:

```
^Z^Zsource filename:line:character:middle:addr
```

where `filename` is an absolute file name indicating which source file, `line` is the line number within that file (where 1 is the first line in the file), `character` is the character position within the file (where 0 is the first character in the file) (for most debug formats this will necessarily point to the beginning of a line), `middle` is middle if `addr` is in the middle of the line, or `beg` if `addr` is at the beginning of the line, and `addr` is the address in the target program associated with the source which is being displayed. `addr` is in the form `0x` followed by one or more lowercase hex digits (note that this does not depend on the language).

27.12. Annotations We Might Want in the Future

- `target-invalid`
the target might have changed (registers, heap contents, or execution status). For performance, we might eventually want to hit `'registers-invalid'` and `'all-registers-invalid'` with greater precision
- systematic annotation for `set/show` parameters (including invalidation notices).
- similarly, `'info'` returns a list of candidates for invalidation notices.

Reporting Bugs in gdb

Your bug reports play an essential role in making gdb reliable.

Reporting a bug may help you by bringing a solution to your problem, or it may not. But in any case the principal function of a bug report is to help the entire community by making the next version of gdb work better. Bug reports are your contribution to the maintenance of gdb.

In order for a bug report to serve its purpose, you must include the information that enables us to fix the bug.

28.1. Have you found a bug?

If you are not sure whether you have found a bug, here are some guidelines:

- If the debugger gets a fatal signal, for any input whatever, that is a gdb bug. Reliable debuggers never crash.
- If gdb produces an error message for valid input, that is a bug. (Note that if you're cross debugging, the problem may also be somewhere in the connection to the target.)
- If gdb does not produce an error message for invalid input, that is a bug. However, you should note that your idea of "invalid input" might be our idea of "an extension" or "support for traditional practice".
- If you are an experienced user of debugging tools, your suggestions for improvement of gdb are welcome in any case.

28.2. How to report bugs

A number of companies and individuals offer support for gnu products. If you obtained gdb from a support organization, we recommend you contact that organization first.

You can find contact information for many support companies and individuals in the file `etc/SERVICE` in the gnu Emacs distribution.

In any event, we also recommend that you submit bug reports for gdb. The preferred method is to submit them directly using <http://www.gnu.org/software/gdb/bugs/gdb's> Bugs web page. Alternatively, the e-mail gateway can be used.

Do not send bug reports to `info-gdb`, or to `help-gdb`, or to any newsgroups. Most users of gdb do not want to receive bug reports. Those that do have arranged to receive `bug-gdb`.

The mailing list `bug-gdb` has a newsgroup `gnu.gdb.bug` which serves as a repeater. The mailing list and the newsgroup carry exactly the same messages. Often people think of posting bug reports to the newsgroup instead of mailing them. This appears to work, but it has one problem which can be crucial: a newsgroup posting often lacks a mail path back to the sender. Thus, if we need to ask for more information, we may be unable to reach you. For this reason, it is better to send bug reports to the mailing list.

The fundamental principle of reporting bugs usefully is this: *report all the facts*. If you are not sure whether to state a fact or leave it out, state it!

Often people omit facts because they think they know what causes the problem and assume that some details do not matter. Thus, you might assume that the name of the variable you use in an example

does not matter. Well, probably it does not, but one cannot be sure. Perhaps the bug is a stray memory reference which happens to fetch from the location where that name is stored in memory; perhaps, if the name were different, the contents of that location would fool the debugger into doing the right thing despite the bug. Play it safe and give a specific, complete example. That is the easiest thing for you to do, and the most helpful.

Keep in mind that the purpose of a bug report is to enable us to fix the bug. It may be that the bug has been reported previously, but neither you nor we can know that unless your bug report is complete and self-contained.

Sometimes people give a few sketchy facts and ask, "Does this ring a bell?" Those bug reports are useless, and we urge everyone to *refuse to respond to them* except to chide the sender to report bugs properly.

To enable us to fix the bug, you should include all these things:

- The version of gdb. gdb announces it if you start with no arguments; you can also print it at any time using `show version`.

Without this, we will not know whether there is any point in looking for the bug in the current version of gdb.

- The type of machine you are using, and the operating system name and version number.
- What compiler (and its version) was used to compile gdb--e.g. "gcc-2.8.1".
- What compiler (and its version) was used to compile the program you are debugging--e.g. "gcc-2.8.1", or "HP92453-01 A.10.32.03 HP C Compiler". For GCC, you can say `gcc -version` to get this information; for other compilers, see the documentation for those compilers.
- The command arguments you gave the compiler to compile your example and observe the bug. For example, did you use `-o`? To guarantee you will not omit something important, list them all. A copy of the Makefile (or the output from make) is sufficient.

If we were to try to guess the arguments, we would probably guess wrong and then we might not encounter the bug.

- A complete input script, and all necessary source files, that will reproduce the bug.
- A description of what behavior you observe that you believe is incorrect. For example, "It gets a fatal signal."

Of course, if the bug is that gdb gets a fatal signal, then we will certainly notice it. But if the bug is incorrect output, we might not notice unless it is glaringly wrong. You might as well not give us a chance to make a mistake.

Even if the problem you experience is a fatal signal, you should still say so explicitly. Suppose something strange is going on, such as, your copy of gdb is out of synch, or you have encountered a bug in the C library on your system. (This has happened!) Your copy might crash and ours would not. If you told us to expect a crash, then when ours fails to crash, we would know that the bug was not happening for us. If you had not told us to expect a crash, then we would not be able to draw any conclusion from our observations.

- If you wish to suggest changes to the gdb source, send us context diffs. If you even discuss something in the gdb source, refer to it by context, not by line number.

The line numbers in our development sources will not match those in your sources. Your line numbers would convey no useful information to us.

Here are some things that are not necessary:

- A description of the envelope of the bug.

Often people who encounter a bug spend a lot of time investigating which changes to the input file will make the bug go away and which changes will not affect it.

This is often time consuming and not very useful, because the way we will find the bug is by running a single example under the debugger with breakpoints, not by pure deduction from a series of examples. We recommend that you save your time for something else.

Of course, if you can find a simpler example to report *instead* of the original one, that is a convenience for us. Errors in the output will be easier to spot, running under the debugger will take less time, and so on.

However, simplification is not vital; if you do not want to do this, report the bug anyway and send us the entire test case you used.

- A patch for the bug.

A patch for the bug does help us if it is a good one. But do not omit the necessary information, such as the test case, on the assumption that a patch is all we need. We might see problems with your patch and decide to fix the problem another way, or we might not understand it at all.

Sometimes with a program as complicated as gdb it is very hard to construct an example that will make the program follow a certain path through the code. If you do not send us the example, we will not be able to construct one, so we will not be able to verify that the bug is fixed.

And if we cannot understand what bug you are trying to fix, or why your patch should be an improvement, we will not install it. A test case will help us to understand.

- A guess about what the bug is or what it depends on.

Such guesses are usually wrong. Even we cannot guess right about such things without first using the debugger to find the facts.

<setfilename>rluser.info</setfilename>

Command Line Editing

This chapter describes the basic features of the gnu command line editing interface.

29.1. Introduction to Line Editing

The following paragraphs describe the notation used to represent keystrokes.

The text **C-k** is read as ‘Control-K’ and describes the character produced when the [k] key is pressed while the Control key is depressed.

The text **M-k** is read as ‘Meta-K’ and describes the character produced when the Meta key (if you have one) is depressed, and the [k] key is pressed. The Meta key is labeled [ALT] on many keyboards. On keyboards with two keys labeled [ALT] (usually to either side of the space bar), the [ALT] on the left side is generally set to work as a Meta key. The [ALT] key on the right may also be configured to work as a Meta key or may be configured as some other modifier, such as a Compose key for typing accented characters.

If you do not have a Meta or [ALT] key, or another key working as a Meta key, the identical keystroke can be generated by typing [ESC] *first*, and then typing [k]. Either process is known as *metafying* the [k] key.

The text **M-C-k** is read as ‘Meta-Control-k’ and describes the character produced by *metafying* **C-k**.

In addition, several keys have their own names. Specifically, [DEL], [ESC], [LFD], [SPC], [RET], and [TAB] all stand for themselves when seen in this text, or in an init file (refer to Section 29.3 *Readline Init File*). If your keyboard lacks a [LFD] key, typing [C-j] will produce the desired character. The [RET] key may be labeled [Return] or [Enter] on some keyboards.

29.2. Readline Interaction

Often during an interactive session you type in a long line of text, only to notice that the first word on the line is misspelled. The Readline library gives you a set of commands for manipulating the text as you type it in, allowing you to just fix your typo, and not forcing you to retype the majority of the line. Using these editing commands, you move the cursor to the place that needs correction, and delete or insert the text of the corrections. Then, when you are satisfied with the line, you simply press [RET]. You do not have to be at the end of the line to press [RET]; the entire line is accepted regardless of the location of the cursor within the line.

29.2.1. Readline Bare Essentials

In order to enter characters into the line, simply type them. The typed character appears where the cursor was, and then the cursor moves one space to the right. If you mistype a character, you can use your erase character to back up and delete the mistyped character.

Sometimes you may mistype a character, and not notice the error until you have typed several other characters. In that case, you can type **C-b** to move the cursor to the left, and then correct your mistake. Afterwards, you can move the cursor to the right with **C-f**.

When you add text in the middle of a line, you will notice that characters to the right of the cursor are ‘pushed over’ to make room for the text that you have inserted. Likewise, when you delete text behind the cursor, characters to the right of the cursor are ‘pulled back’ to fill in the blank space created by the removal of the text. A list of the bare essentials for editing the text of an input line follows.

C-b

Move back one character.

C-f

Move forward one character.

[DEL] or [Backspace]

Delete the character to the left of the cursor.

C-d

Delete the character underneath the cursor.

Printing characters

Insert the character into the line at the cursor.

C-_ or C-x C-u

Undo the last editing command. You can undo all the way back to an empty line.

(Depending on your configuration, the [Backspace] key be set to delete the character to the left of the cursor and the [DEL] key set to delete the character underneath the cursor, like **C-d**, rather than the character to the left of the cursor.)

29.2.2. Readline Movement Commands

The above table describes the most basic keystrokes that you need in order to do editing of the input line. For your convenience, many other commands have been added in addition to **C-b**, **C-f**, **C-d**, and [DEL]. Here are some commands for moving more rapidly about the line.

C-a

Move to the start of the line.

C-e

Move to the end of the line.

M-f

Move forward a word, where a word is composed of letters and digits.

M-b

Move backward a word.

C-l

Clear the screen, reprinting the current line at the top.

Notice how **C-f** moves forward a character, while **M-f** moves forward a word. It is a loose convention that control keystrokes operate on characters while meta keystrokes operate on words.

29.2.3. Readline Killing Commands

Killing text means to delete the text from the line, but to save it away for later use, usually by *yanking* (re-inserting) it back into the line. ('Cut' and 'paste' are more recent jargon for 'kill' and 'yank'.)

If the description for a command says that it 'kills' text, then you can be sure that you can get the text back in a different (or the same) place later.

When you use a kill command, the text is saved in a *kill-ring*. Any number of consecutive kills save all of the killed text together, so that when you yank it back, you get it all. The kill ring is not line specific; the text that you killed on a previously typed line is available to be yanked back later, when you are typing another line. Here is the list of commands for killing text.

C-k

Kill the text from the current cursor position to the end of the line.

M-d

Kill from the cursor to the end of the current word, or, if between words, to the end of the next word. Word boundaries are the same as those used by **M-f**.

M- [DEL]

Kill from the cursor the start of the current word, or, if between words, to the start of the previous word. Word boundaries are the same as those used by **M-b**.

C-w

Kill from the cursor to the previous whitespace. This is different than **M- [DEL]** because the word boundaries differ.

Here is how to *yank* the text back into the line. Yanking means to copy the most-recently-killed text from the kill buffer.

C-y

Yank the most recently killed text back into the buffer at the cursor.

M-y

Rotate the kill-ring, and yank the new top. You can only do this if the prior command is **C-y** or **M-y**.

29.2.4. Readline Arguments

You can pass numeric arguments to Readline commands. Sometimes the argument acts as a repeat count, other times it is the *sign* of the argument that is significant. If you pass a negative argument to a command which normally acts in a forward direction, that command will act in a backward direction. For example, to kill text back to the start of the line, you might type **M- C-k**.

The general way to pass numeric arguments to a command is to type meta digits before the command. If the first 'digit' typed is a minus sign (-), then the sign of the argument will be negative. Once you have typed one meta digit to get the argument started, you can type the remainder of the digits, and then the command. For example, to give the **C-d** command an argument of 10, you could type **M-1 0 C-d**, which will delete the next ten characters on the input line.

29.2.5. Searching for Commands in the History

Readline provides commands for searching through the command history for lines containing a specified string. There are two search modes: *incremental* and *non-incremental*.

Incremental searches begin before the user has finished typing the search string. As each character of the search string is typed, Readline displays the next entry from the history matching the string typed so far. An incremental search requires only as many characters as needed to find the desired history entry. To search backward in the history for a particular string, type **C-r**. Typing **C-s** searches forward through the history. The characters present in the value of the `isearch-terminators` variable are used to terminate an incremental search. If that variable has not been assigned a value, the [ESC] and **C-J** characters will terminate an incremental search. **C-g** will abort an incremental search and restore the original line. When the search is terminated, the history entry containing the search string becomes the current line.

To find other matching entries in the history list, type **C-r** or **C-s** as appropriate. This will search backward or forward in the history for the next entry matching the search string typed so far. Any other key sequence bound to a Readline command will terminate the search and execute that command. For instance, a [RET] will terminate the search and accept the line, thereby executing the command from the history list. A movement command will terminate the search, make the last line found the current line, and begin editing.

Readline remembers the last incremental search string. If two **C-rs** are typed without any intervening characters defining a new search string, any remembered search string is used.

Non-incremental searches read the entire search string before starting to search for matching history lines. The search string may be typed by the user or be part of the contents of the current line.

29.3. Readline Init File

Although the Readline library comes with a set of Emacs-like keybindings installed by default, it is possible to use a different set of keybindings. Any user can customize programs that use Readline by putting commands in an *inputrc* file, conventionally in his home directory. The name of this file is taken from the value of the environment variable `INPUTRC`. If that variable is unset, the default is `~/.inputrc`.

When a program which uses the Readline library starts up, the init file is read, and the key bindings are set.

In addition, the **C-x C-r** command re-reads this init file, thus incorporating any changes that you might have made to it.

29.3.1. Readline Init File Syntax

There are only a few basic constructs allowed in the Readline init file. Blank lines are ignored. Lines beginning with a # are comments. Lines beginning with a \$ indicate conditional constructs (refer to Section 29.3.2 *Conditional Init Constructs*). Other lines denote variable settings and key bindings.

Variable Settings

You can modify the run-time behavior of Readline by altering the values of variables in Readline using the `set` command within the init file. The syntax is simple:

```
set variable value
```

Here, for example, is how to change from the default Emacs-like key binding to use `vi` line editing commands:

```
set editing-mode vi
```

Variable names and values, where appropriate, are recognized without regard to case.

A great deal of run-time behavior is changeable with the following variables.

`bell-style`

Controls what happens when Readline wants to ring the terminal bell. If set to `none`, Readline never rings the bell. If set to `visible`, Readline uses a visible bell if one is available. If set to `audible` (the default), Readline attempts to ring the terminal's bell.

`comment-begin`

The string to insert at the beginning of the line when the `insert-comment` command is executed. The default value is `"#"`.

`completion-ignore-case`

If set to `on`, Readline performs filename matching and completion in a case-insensitive fashion. The default value is `off`.

`completion-query-items`

The number of possible completions that determines when the user is asked whether he wants to see the list of possibilities. If the number of possible completions is greater than this value, Readline will ask the user whether or not he wishes to view them; otherwise, they are simply listed. This variable must be set to an integer value greater than or equal to 0. The default limit is 100.

`convert-meta`

If set to `on`, Readline will convert characters with the eighth bit set to an ascii key sequence by stripping the eighth bit and prefixing an [ESC] character, converting them to a meta-prefixed key sequence. The default value is `on`.

`disable-completion`

If set to `on`, Readline will inhibit word completion. Completion characters will be inserted into the line as if they had been mapped to `self-insert`. The default is `off`.

`editing-mode`

The `editing-mode` variable controls which default set of key bindings is used. By default, Readline starts up in Emacs editing mode, where the keystrokes are most similar to Emacs. This variable can be set to either `emacs` or `vi`.

`enable-keypad`

When set to `on`, Readline will try to enable the application keypad when it is called. Some systems need this to enable the arrow keys. The default is `off`.

`expand-tilde`

If set to `on`, tilde expansion is performed when Readline attempts word completion. The default is `off`.

If set to `on`, the history code attempts to place point at the same location on each history line retrieved with `previous-history` or `next-history`.

`horizontal-scroll-mode`

This variable can be set to either `on` or `off`. Setting it to `on` means that the text of the lines being edited will scroll horizontally on a single screen line when they are longer than the

width of the screen, instead of wrapping onto a new screen line. By default, this variable is set to `off`.

`input-meta`

If set to `on`, Readline will enable eight-bit input (it will not clear the eighth bit in the characters it reads), regardless of what the terminal claims it can support. The default value is `off`. The name `meta-flag` is a synonym for this variable.

`isearch-terminators`

The string of characters that should terminate an incremental search without subsequently executing the character as a command (refer to Section 29.2.5 *Searching for Commands in the History*). If this variable has not been given a value, the characters `[ESC]` and `C-J` will terminate an incremental search.

`keymap`

Sets Readline's idea of the current keymap for key binding commands. Acceptable keymap names are `emacs`, `emacs-standard`, `emacs-meta`, `emacs-ctlx`, `vi`, `vi-move`, `vi-command`, and `vi-insert`. `vi` is equivalent to `vi-command`; `emacs` is equivalent to `emacs-standard`. The default value is `emacs`. The value of the `editing-mode` variable also affects the default keymap.

`mark-directories`

If set to `on`, completed directory names have a slash appended. The default is `on`.

`mark-modified-lines`

This variable, when set to `on`, causes Readline to display an asterisk (*) at the start of history lines which have been modified. This variable is `off` by default.

`mark-symlinked-directories`

If set to `on`, completed names which are symbolic links to directories have a slash appended (subject to the value of `mark-directories`). The default is `off`.

`match-hidden-files`

This variable, when set to `on`, causes Readline to match files whose names begin with a `.` (hidden files) when performing filename completion, unless the leading `.` is supplied by the user in the filename to be completed. This variable is `on` by default.

`output-meta`

If set to `on`, Readline will display characters with the eighth bit set directly rather than as a meta-prefixed escape sequence. The default is `off`.

`page-completions`

If set to `on`, Readline uses an internal `more`-like pager to display a screenful of possible completions at a time. This variable is `on` by default.

`print-completions-horizontally`

If set to `on`, Readline will display completions with matches sorted horizontally in alphabetical order, rather than down the screen. The default is `off`.

```
show-all-if-ambiguous
```

This alters the default behavior of the completion functions. If set to `on`, words which have more than one possible completion cause the matches to be listed immediately instead of ringing the bell. The default value is `off`.

```
visible-stats
```

If set to `on`, a character denoting a file's type is appended to the filename when listing possible completions. The default is `off`.

Key Bindings

The syntax for controlling key bindings in the init file is simple. First you need to find the name of the command that you want to change. The following sections contain tables of the command name, the default keybinding, if any, and a short description of what the command does.

Once you know the name of the command, simply place on a line in the init file the name of the key you wish to bind the command to, a colon, and then the name of the command. The name of the key can be expressed in different ways, depending on what you find most comfortable.

In addition to command names, readline allows keys to be bound to a string that is inserted when the key is pressed (a macro).

```
keyname: function-name OR macro
```

`keyname` is the name of a key spelled out in English. For example:

```
Control-u: universal-argument
Meta-Rubout: backward-kill-word
Control-o: "> output"
```

In the above example, **C-u** is bound to the function `universal-argument`, **M-DEL** is bound to the function `backward-kill-word`, and **C-o** is bound to run the macro expressed on the right hand side (that is, to insert the text `> output` into the line).

A number of symbolic character names are recognized while processing this key binding syntax: DEL, ESC, ESCAPE, LFD, NEWLINE, RET, RETURN, RUBOUT, SPACE, SPC, and TAB.

```
"keyseq": function-name OR macro
```

`keyseq` differs from `keyname` above in that strings denoting an entire key sequence can be specified, by placing the key sequence in double quotes. Some gnu Emacs style key escapes can be used, as in the following example, but the special character names are not recognized.

```
"\C-u": universal-argument
"\C-x\C-r": re-read-init-file
"\e[11~": "Function Key 1"
```

In the above example, **C-u** is again bound to the function `universal-argument` (just as it was in the first example), **C-x C-r** is bound to the function `re-read-init-file`, and `[ESC] [[[1] [1] [~]` is bound to insert the text `Function Key 1`.

The following gnu Emacs style escape sequences are available when specifying key sequences:

```
\C-
```

control prefix

```
\M-
```

meta prefix

`\e`
an escape character

`\\`
backslash

`\"`
["], a double quotation mark

`\'`
['], a single quote or apostrophe

In addition to the GNU Emacs style escape sequences, a second set of backslash escapes is available:

`\a`
alert (bell)

`\b`
backspace

`\d`
delete

`\f`
form feed

`\n`
newline

`\r`
carriage return

`\t`
horizontal tab

`\v`
vertical tab

`\nnn`
the eight-bit character whose value is the octal value `nnn` (one to three digits)

`\xHH`
the eight-bit character whose value is the hexadecimal value `HH` (one or two hex digits)

When entering the text of a macro, single or double quotes must be used to indicate a macro definition. Unquoted text is assumed to be a function name. In the macro body, the backslash escapes described above are expanded. Backslash will quote any other character in the macro text, including " and '. For example, the following binding will make `C-x \` insert a single `\` into the line:

```
"\C-x\\": "\\\""
```

29.3.2. Conditional Init Constructs

Readline implements a facility similar in spirit to the conditional compilation features of the C pre-processor which allows key bindings and variable settings to be performed as the result of tests. There are four parser directives used.

`$if`

The `$if` construct allows bindings to be made based on the editing mode, the terminal being used, or the application using Readline. The text of the test extends to the end of the line; no characters are required to isolate it.

`mode`

The `mode=` form of the `$if` directive is used to test whether Readline is in `emacs` or `vi` mode. This may be used in conjunction with the `set keymap` command, for instance, to set bindings in the `emacs-standard` and `emacs-ctlx` keymaps only if Readline is starting out in `emacs` mode.

`term`

The `term=` form may be used to include terminal-specific key bindings, perhaps to bind the key sequences output by the terminal's function keys. The word on the right side of the `=` is tested against both the full name of the terminal and the portion of the terminal name before the first `-`. This allows `sun` to match both `sun` and `sun-cmd`, for instance.

`application`

The `application` construct is used to include application-specific settings. Each program using the Readline library sets the `application` name, and you can test for a particular value. This could be used to bind key sequences to functions useful for a specific program. For instance, the following command adds a key sequence that quotes the current or previous word in Bash:

```
$if Bash
# Quote the current or previous word
"\C-xq": "\eb"\ef\"
$endif
```

`$endif`

This command, as seen in the previous example, terminates an `$if` command.

`$else`

Commands in this branch of the `$if` directive are executed if the test fails.

`$include`

This directive takes a single filename as an argument and reads commands and bindings from that file. For example, the following directive reads from `/etc/inputrc`:

```
$include /etc/inputrc
```

29.3.3. Sample Init File

Here is an example of an `inputrc` file. This illustrates key binding, variable assignment, and conditional syntax.

```
# This file controls the behaviour of line input editing for
```

```

# programs that use the GNU Readline library. Existing
# programs include FTP, Bash, and GDB.
#
# You can re-read the inputrc file with C-x C-r.
# Lines beginning with '#' are comments.
#
# First, include any systemwide bindings and variable
# assignments from /etc/Inputrc
$include /etc/Inputrc

#
# Set various bindings for emacs mode.

set editing-mode emacs

$if mode=emacs

Meta-Control-h: backward-kill-word Text after the function name is ignored

#
# Arrow keys in keypad mode
#
#\M-OD":      backward-char
#\M-OC":      forward-char
#\M-OA":      previous-history
#\M-OB":      next-history
#
# Arrow keys in ANSI mode
#
\M-[D":      backward-char
\M-[C":      forward-char
\M-[A":      previous-history
\M-[B":      next-history
#
# Arrow keys in 8 bit keypad mode
#
#\M-\C-OD":   backward-char
#\M-\C-OC":   forward-char
#\M-\C-OA":   previous-history
#\M-\C-OB":   next-history
#
# Arrow keys in 8 bit ANSI mode
#
#\M-\C-[D":   backward-char
#\M-\C-[C":   forward-char
#\M-\C-[A":   previous-history
#\M-\C-[B":   next-history

C-q: quoted-insert

$endif

# An old-style binding. This happens to be the default.
TAB: complete

# Macros that are convenient for shell interaction
$if Bash
# edit the path
\C-xp": "PATH=${PATH}\e\C-e\C-a\ef\C-f"
# prepare to type a quoted word --
# insert open and close double quotes
# and move to just after the open quote

```

```

\C-x\": "\C-b"
# insert a backslash (testing backslash escapes
# in sequences and macros)
\C-x\": "\"
# Quote the current or previous word
\C-xq": "\eb"\ef\"
# Add a binding to refresh the line, which is unbound
\C-xr": redraw-current-line
# Edit variable on current line.
\M\C-v": "\C-a\C-k\C-y\M\C-e\C-a\C-y="
$endif

# use a visible bell if one is available
set bell-style visible

# don't strip characters to 7 bits when reading
set input-meta on

# allow iso-latin1 characters to be inserted rather
# than converted to prefix-meta sequences
set convert-meta off

# display characters with the eighth bit set directly
# rather than as meta-prefixed characters
set output-meta on

# if there are more than 150 possible completions for
# a word, ask the user if he wants to see all of them
set completion-query-items 150

# For FTP
$if Ftp
\C-xg": "get \M-?"
\C-xt": "put \M-?"
\M-.": yank-last-arg
$endif

```

29.4. Bindable Readline Commands

This section describes Readline commands that may be bound to key sequences. Command names without an accompanying key sequence are unbound by default.

In the following descriptions, *point* refers to the current cursor position, and *mark* refers to a cursor position saved by the `set-mark` command. The text between the point and mark is referred to as the *region*.

29.4.1. Commands For Moving

beginning-of-line (C-a)

Move to the start of the current line.

end-of-line (C-e)

Move to the end of the line.

`forward-char` (C-f)

Move forward a character.

`backward-char` (C-b)

Move back a character.

`forward-word` (M-f)

Move forward to the end of the next word. Words are composed of letters and digits.

`backward-word` (M-b)

Move back to the start of the current or previous word. Words are composed of letters and digits.

`clear-screen` (C-l)

Clear the screen and redraw the current line, leaving the current line at the top of the screen.

`redraw-current-line` ()

Refresh the current line. By default, this is unbound.

29.4.2. Commands For Manipulating The History

`accept-line` (Newline or Return)

Accept the line regardless of where the cursor is. If this line is non-empty, it may be added to the history list for future recall with `add_history()`. If this line is a modified history line, the history line is restored to its original state.

`previous-history` (C-p)

Move 'back' through the history list, fetching the previous command.

`next-history` (C-n)

Move 'forward' through the history list, fetching the next command.

`beginning-of-history` (M-<)

Move to the first line in the history.

`end-of-history` (M->)

Move to the end of the input history, i.e., the line currently being entered.

`reverse-search-history` (C-r)

Search backward starting at the current line and moving 'up' through the history as necessary. This is an incremental search.

`forward-search-history` (C-s)

Search forward starting at the current line and moving 'down' through the the history as necessary. This is an incremental search.

`non-incremental-reverse-search-history` (M-p)

Search backward starting at the current line and moving 'up' through the history as necessary using a non-incremental search for a string supplied by the user.

`non-incremental-forward-search-history` (M-n)

Search forward starting at the current line and moving 'down' through the the history as necessary using a non-incremental search for a string supplied by the user.

`history-search-forward` ()

Search forward through the history for the string of characters between the start of the current line and the point. This is a non-incremental search. By default, this command is unbound.

`history-search-backward` ()

Search backward through the history for the string of characters between the start of the current line and the point. This is a non-incremental search. By default, this command is unbound.

`yank-nth-arg` (M-C-y)

Insert the first argument to the previous command (usually the second word on the previous line) at point. With an argument *n*, insert the *n*th word from the previous command (the words in the previous command begin with word 0). A negative argument inserts the *n*th word from the end of the previous command.

`yank-last-arg` (M-. or M-_)

Insert last argument to the previous command (the last word of the previous history entry). With an argument, behave exactly like `yank-nth-arg`. Successive calls to `yank-last-arg` move back through the history list, inserting the last argument of each line in turn.

29.4.3. Commands For Changing Text

`delete-char` (C-d)

Delete the character at point. If point is at the beginning of the line, there are no characters in the line, and the last character typed was not bound to `delete-char`, then return eof.

`backward-delete-char` (Rubout)

Delete the character behind the cursor. A numeric argument means to kill the characters instead of deleting them.

`forward-backward-delete-char` ()

Delete the character under the cursor, unless the cursor is at the end of the line, in which case the character behind the cursor is deleted. By default, this is not bound to a key.

`quoted-insert` (C-q or C-v)

Add the next character typed to the line verbatim. This is how to insert key sequences like **C-q**, for example.

`tab-insert` (M-[TAB])

Insert a tab character.

`self-insert` (a, b, A, l, !, ...)

Insert yourself.

`transpose-chars` (C-t)

Drag the character before the cursor forward over the character at the cursor, moving the cursor forward as well. If the insertion point is at the end of the line, then this transposes the last two characters of the line. Negative arguments have no effect.

`transpose-words` (M-t)

Drag the word before point past the word after point, moving point past that word as well. If the insertion point is at the end of the line, this transposes the last two words on the line.

`upcase-word` (M-u)

Uppercase the current (or following) word. With a negative argument, uppercase the previous word, but do not move the cursor.

`downcase-word` (M-l)

Lowercase the current (or following) word. With a negative argument, lowercase the previous word, but do not move the cursor.

`capitalize-word` (M-c)

Capitalize the current (or following) word. With a negative argument, capitalize the previous word, but do not move the cursor.

`overwrite-mode` ()

Toggle overwrite mode. With an explicit positive numeric argument, switches to overwrite mode. With an explicit non-positive numeric argument, switches to insert mode. This command affects only `emacs` mode; `vi` mode does overwrite differently. Each call to `readline()` starts in insert mode.

In overwrite mode, characters bound to `self-insert` replace the text at point rather than pushing the text to the right. Characters bound to `backward-delete-char` replace the character before point with a space.

By default, this command is unbound.

29.4.4. Killing And Yanking

`kill-line` (C-k)

Kill the text from point to the end of the line.

`backward-kill-line` (C-x Rubout)

Kill backward to the beginning of the line.

`unix-line-discard` (C-u)

Kill backward from the cursor to the beginning of the current line.

`kill-whole-line` ()

Kill all characters on the current line, no matter where point is. By default, this is unbound.

`kill-word` (M-d)

Kill from point to the end of the current word, or if between words, to the end of the next word. Word boundaries are the same as `forward-word`.

`backward-kill-word` (M-[DEL])

Kill the word behind point. Word boundaries are the same as `backward-word`.

`unix-word-rubout` (C-w)

Kill the word behind point, using white space as a word boundary. The killed text is saved on the kill-ring.

`delete-horizontal-space` ()

Delete all spaces and tabs around point. By default, this is unbound.

`kill-region` ()

Kill the text in the current region. By default, this command is unbound.

`copy-region-as-kill` ()

Copy the text in the region to the kill buffer, so it can be yanked right away. By default, this command is unbound.

`copy-backward-word` ()

Copy the word before point to the kill buffer. The word boundaries are the same as `backward-word`. By default, this command is unbound.

`copy-forward-word` ()

Copy the word following point to the kill buffer. The word boundaries are the same as `forward-word`. By default, this command is unbound.

`yank` (C-y)

Yank the top of the kill ring into the buffer at point.

`yank-pop` (M-y)

Rotate the kill-ring, and yank the new top. You can only do this if the prior command is `yank` or `yank-pop`.

29.4.5. Specifying Numeric Arguments

`digit-argument` (M-0, M-1, ... M-)

Add this digit to the argument already accumulating, or start a new argument. M- starts a negative argument.

`universal-argument` ()

This is another way to specify an argument. If this command is followed by one or more digits, optionally with a leading minus sign, those digits define the argument. If the command is followed by digits, executing `universal-argument` again ends the numeric argument, but is otherwise ignored. As a special case, if this command is immediately followed by a character that is neither a digit or minus sign, the argument count for the next command is multiplied by four. The argument count is initially one, so executing this function the first time makes the argument count four, a second time makes the argument count sixteen, and so on. By default, this is not bound to a key.

29.4.6. Letting Readline Type For You

`complete` ([TAB])

Attempt to perform completion on the text before point. The actual completion performed is application-specific. The default is filename completion.

`possible-completions` (M-?)

List the possible completions of the text before point.

`insert-completions` (M-*)

Insert all completions of the text before point that would have been generated by `possible-completions`.

`menu-complete` ()

Similar to `complete`, but replaces the word to be completed with a single match from the list of possible completions. Repeated execution of `menu-complete` steps through the list of possible completions, inserting each match in turn. At the end of the list of completions, the bell is rung (subject to the setting of `bell-style`) and the original text is restored. An argument of `n` moves `n` positions forward in the list of matches; a negative argument may be used to move backward through the list. This command is intended to be bound to [TAB], but is unbound by default.

`delete-char-or-list` ()

Deletes the character under the cursor if not at the beginning or end of the line (like `delete-char`). If at the end of the line, behaves identically to `possible-completions`. This command is unbound by default.

29.4.7. Keyboard Macros

`start-kbd-macro` (C-x ())

Begin saving the characters typed into the current keyboard macro.

`end-kbd-macro` (C-x)

Stop saving the characters typed into the current keyboard macro and save the definition.

`call-last-kbd-macro` (C-x e)

Re-execute the last keyboard macro defined, by making the characters in the macro appear as if typed at the keyboard.

29.4.8. Some Miscellaneous Commands

`re-read-init-file` (C-x C-r)

Read in the contents of the `inputrc` file, and incorporate any bindings or variable assignments found there.

`abort` (C-g)

Abort the current editing command and ring the terminal's bell (subject to the setting of `bell-style`).

`do-uppercase-version` (M-a, M-b, M-x, ...)

If the metaified character `x` is lowercase, run the command that is bound to the corresponding uppercase character.

`prefix-meta` ([ESC])

Metafy the next character typed. This is for keyboards without a meta key. Typing [ESC] `f` is equivalent to typing **M-f**.

`undo` (C-_ or C-x C-u)

Incremental undo, separately remembered for each line.

`revert-line` (M-r)

Undo all changes made to this line. This is like executing the `undo` command enough times to get back to the beginning.

`tilde-expand` (M-~)

Perform tilde expansion on the current word.

`set-mark` (C-@)

Set the mark to the point. If a numeric argument is supplied, the mark is set to that position.

`exchange-point-and-mark` (C-x C-x)

Swap the point with the mark. The current cursor position is set to the saved position, and the old cursor position is saved as the mark.

`character-search` (C-])

A character is read and point is moved to the next occurrence of that character. A negative count searches for previous occurrences.

`character-search-backward` (M-C-])

A character is read and point is moved to the previous occurrence of that character. A negative count searches for subsequent occurrences.

`insert-comment` (M-#)

Without a numeric argument, the value of the `comment-begin` variable is inserted at the beginning of the current line. If a numeric argument is supplied, this command acts as a toggle: if the characters at the beginning of the line do not match the value of `comment-begin`, the value is inserted, otherwise the characters in `comment-begin` are deleted from the beginning of the line. In either case, the line is accepted as if a newline had been typed.

`dump-functions` ()

Print all of the functions and their key bindings to the Readline output stream. If a numeric argument is supplied, the output is formatted in such a way that it can be made part of an `inputrc` file. This command is unbound by default.

`dump-variables` ()

Print all of the settable variables and their values to the Readline output stream. If a numeric argument is supplied, the output is formatted in such a way that it can be made part of an `inputrc` file. This command is unbound by default.

`dump-macros ()`

Print all of the Readline key sequences bound to macros and the strings they output. If a numeric argument is supplied, the output is formatted in such a way that it can be made part of an `inputrc` file. This command is unbound by default.

`emacs-editing-mode (C-e)`

When in `vi` command mode, this causes a switch to `emacs` editing mode.

`vi-editing-mode (M-C-j)`

When in `emacs` editing mode, this causes a switch to `vi` editing mode.

29.5. Readline vi Mode

While the Readline library does not have a full set of `vi` editing functions, it does contain enough to allow simple editing of the line. The Readline `vi` mode behaves as specified in the `posix 1003.2` standard.

In order to switch interactively between `emacs` and `vi` editing modes, use the command **M-C-j** (bound to `emacs-editing-mode` when in `vi` mode and to `vi-editing-mode` in `emacs` mode). The Readline default is `emacs` mode.

When you enter a line in `vi` mode, you are already placed in ‘insertion’ mode, as if you had typed an `i`. Pressing [ESC] switches you into ‘command’ mode, where you can edit the text of the line with the standard `vi` movement keys, move to previous history lines with `k` and subsequent lines with `j`, and so forth.

Using History Interactively

This chapter describes how to use the GNU History Library interactively, from a user's standpoint. It should be considered a user's guide.

30.1. History Expansion

The History library provides a history expansion feature that is similar to the history expansion provided by `cs`. This section describes the syntax used to manipulate the history information.

History expansions introduce words from the history list into the input stream, making it easy to repeat commands, insert the arguments to a previous command into the current input line, or fix errors in previous commands quickly.

History expansion takes place in two parts. The first is to determine which line from the history list should be used during substitution. The second is to select portions of that line for inclusion into the current one. The line selected from the history is called the *event*, and the portions of that line that are acted upon are called *words*. Various *modifiers* are available to manipulate the selected words. The line is broken into words in the same fashion that Bash does, so that several words surrounded by quotes are considered one word. History expansions are introduced by the appearance of the history expansion character, which is `!` by default.

30.1.1. Event Designators

An event designator is a reference to a command line entry in the history list.

- `!`
Start a history substitution, except when followed by a space, tab, the end of the line, = or (.
- `!n`
Refer to command line `n`.
- `!-n`
Refer to the command `n` lines back.
- `!!`
Refer to the previous command. This is a synonym for `!-1`.
- `!string`
Refer to the most recent command starting with `string`.
- `!?string[?]`
Refer to the most recent command containing `string`. The trailing `?` may be omitted if the `string` is followed immediately by a newline.
- `^string1^string2^`
Quick Substitution. Repeat the last command, replacing `string1` with `string2`. Equivalent to `!!:s/string1/string2/.`

!#

The entire command line typed so far.

30.1.2. Word Designators

Word designators are used to select desired words from the event. A `:` separates the event specification from the word designator. It may be omitted if the word designator begins with a `^`, `$`, `*`, `-`, or `%`. Words are numbered from the beginning of the line, with the first word being denoted by 0 (zero). Words are inserted into the current line separated by single spaces.

For example,

!!

designates the preceding command. When you type this, the preceding command is repeated in toto.

!!: \$

designates the last argument of the preceding command. This may be shortened to `!$`.

!fi:2

designates the second argument of the most recent command starting with the letters `fi`.

Here are the word designators:

0 (zero)

The 0th word. For many applications, this is the command word.

n

The nth word.

^

The first argument; that is, word 1.

\$

The last argument.

%

The word matched by the most recent `?string?` search.

x-y

A range of words; `-y` abbreviates `0-y`.

*

All of the words, except the 0th. This is a synonym for `1-$`. It is not an error to use `*` if there is just one word in the event; the empty string is returned in that case.

x*

Abbreviates `x-$`

x-

Abbreviates x- $\$$ like x*, but omits the last word.

If a word designator is supplied without an event specification, the previous command is used as the event.

30.1.3. Modifiers

After the optional word designator, you can add a sequence of one or more of the following modifiers, each preceded by a `:`.

h

Remove a trailing pathname component, leaving only the head.

t

Remove all leading pathname components, leaving the tail.

r

Remove a trailing suffix of the form `.suffix`, leaving the basename.

e

Remove all but the trailing suffix.

p

Print the new command but do not execute it.

s/old/new/

Substitute `new` for the first occurrence of `old` in the event line. Any delimiter may be used in place of `/`. The delimiter may be quoted in `old` and `new` with a single backslash. If `&` appears in `new`, it is replaced by `old`. A single backslash will quote the `&`. The final delimiter is optional if it is the last character on the input line.

&

Repeat the previous substitution.

g

Cause changes to be applied over the entire event line. Used in conjunction with `s`, as in `gs/old/new/`, or with `&`.

Formatting Documentation

The gdb 4 release includes an already-formatted reference card, ready for printing with PostScript or Ghostscript, in the `gdb` subdirectory of the main source directory¹. If you can use PostScript or Ghostscript with your printer, you can print the reference card immediately with `refcard.ps`.

The release also includes the source for the reference card. You can format it, using TeX, by typing:

```
make refcard.dvi
```

The gdb reference card is designed to print in *landscape* mode on US "letter" size paper; that is, on a sheet 11 inches wide by 8.5 inches high. You will need to specify this form of printing as an option to your dvi output program.

All the documentation for gdb comes as part of the machine-readable distribution. The documentation is written in Texinfo format, which is a documentation system that uses a single source file to produce both on-line information and a printed manual. You can use one of the Info formatting commands to create the on-line version of the documentation and TeX (or `texi2roff`) to typeset the printed version.

gdb includes an already formatted copy of the on-line Info version of this manual in the `gdb` subdirectory. The main Info file is `gdb-2003-07-22-cvs/gdb/gdb.info`, and it refers to subordinate files matching `gdb.info*` in the same directory. If necessary, you can print out these files, or read them with any editor; but they are easier to read using the `info` subsystem in gnu Emacs or the standalone `info` program, available as part of the gnu Texinfo distribution.

If you want to format these Info files yourself, you need one of the Info formatting programs, such as `texinfo-format-buffer` or `makeinfo`.

If you have `makeinfo` installed, and are in the top level `gdb` source directory (`gdb-2003-07-22-cvs`, in the case of version 2003-07-22-cvs), you can make the Info file by typing:

```
cd gdb
make gdb.info
```

If you want to typeset and print copies of this manual, you need TeX, a program to print its dvi output files, and `texinfo.tex`, the Texinfo definitions file.

TeX is a typesetting program; it does not print files directly, but produces output files called dvi files. To print a typeset document, you need a program to print dvi files. If your system has TeX installed, chances are it has such a program. The precise command to use depends on your system; `lpr -d` is common; another (for PostScript devices) is `dvips`. The dvi print command may require a file name without any extension or a `.dvi` extension.

TeX also requires a macro definitions file called `texinfo.tex`. This file tells TeX how to typeset a document written in Texinfo format. On its own, TeX cannot either read or typeset a Texinfo file. `texinfo.tex` is distributed with GDB and is located in the `gdb-version-number/texinfo` directory.

1. In `gdb-2003-07-22-cvs/gdb/refcard.ps` of the version 2003-07-22-cvs release.

If you have TeX and a dvi printer program installed, you can typeset and print this manual. First switch to the the `gdb` subdirectory of the main source directory (for example, to `gdb-2003-07-22-cvs/gdb`) and type:

```
make gdb.dvi
```

Then give `gdb.dvi` to your dvi printing program.



Appendix B.

Installing gdb

`gdb` comes with a `configure` script that automates the process of preparing `gdb` for installation; you can then use `make` to build the `gdb` program.

The `gdb` distribution includes all the source code you need for `gdb` in a single directory, whose name is usually composed by appending the version number to `gdb`.

For example, the `gdb` version 2003-07-22-cvs distribution is in the `gdb-2003-07-22-cvs` directory. That directory contains:

```
gdb-2003-07-22-cvs/configure (and supporting files)
```

script for configuring `gdb` and all its supporting libraries

```
gdb-2003-07-22-cvs/gdb
```

the source specific to `gdb` itself

```
gdb-2003-07-22-cvs/bfd
```

source for the Binary File Descriptor library

```
gdb-2003-07-22-cvs/include
```

gnu include files

```
gdb-2003-07-22-cvs/libiberty
```

source for the `-liberty` free software library

```
gdb-2003-07-22-cvs/opcodes
```

source for the library of opcode tables and disassemblers

```
gdb-2003-07-22-cvs/readline
```

source for the `gnu` command-line interface

```
gdb-2003-07-22-cvs/glob
```

source for the `gnu` filename pattern-matching subroutine

```
gdb-2003-07-22-cvs/mmalloc
```

source for the `gnu` memory-mapped `malloc` package

The simplest way to configure and build `gdb` is to run `configure` from the `gdb-version-number` source directory, which in this example is the `gdb-2003-07-22-cvs` directory.

First switch to the `gdb-version-number` source directory if you are not already in it; then run `configure`. Pass the identifier for the platform on which `gdb` will run as an argument.

For example:

```
cd gdb-2003-07-22-cvs
./configure host
make
```

where `host` is an identifier such as `sun4` or `decstation`, that identifies the platform where `gdb` will run. (You can often leave off `host`; `configure` tries to guess the correct value by examining your system.)

Running `configure host` and then running `make` builds the `bfd`, `readline`, `mmalloc`, and `libiberty` libraries, then `gdb` itself. The configured source files, and the binaries, are left in the corresponding source directories.

`configure` is a Bourne-shell (`/bin/sh`) script; if your system does not recognize this automatically when you run a different shell, you may need to run `sh` on it explicitly:

```
sh configure host
```

If you run `configure` from a directory that contains source directories for multiple libraries or programs, such as the `gdb-2003-07-22-cvs` source directory for version `2003-07-22-cvs`, `configure` creates configuration files for every directory level underneath (unless you tell it not to, with the `-norecursion` option).

You should run the `configure` script from the top directory in the source tree, the `gdb-version-number` directory. If you run `configure` from one of the subdirectories, you will configure only that subdirectory. That is usually not what you want. In particular, if you run the first `configure` from the `gdb` subdirectory of the `gdb-version-number` directory, you will omit the configuration of `bfd`, `readline`, and other sibling directories of the `gdb` subdirectory. This leads to build errors about missing include files such as `bfd/bfd.h`.

You can install `gdb` anywhere; it has no hardwired paths. However, you should make sure that the shell on your path (named by the `SHELL` environment variable) is publicly readable. Remember that `gdb` uses the shell to start your program--some systems refuse to let `gdb` debug child processes whose programs are not readable.

B.1. Compiling gdb in another directory

If you want to run `gdb` versions for several host or target machines, you need a different `gdb` compiled for each combination of host and target. `configure` is designed to make this easy by allowing you to generate each configuration in a separate subdirectory, rather than in the source directory. If your `make` program handles the `VPATH` feature (gnu `make` does), running `make` in each of these directories builds the `gdb` program specified there.

To build `gdb` in a separate directory, run `configure` with the `-srcdir` option to specify where to find the source. (You also need to specify a path to find `configure` itself from your working directory. If the path to `configure` would be the same as the argument to `-srcdir`, you can leave out the `-srcdir` option; it is assumed.)

For example, with version `2003-07-22-cvs`, you can build `gdb` in a separate directory for a Sun 4 like this:

```
cd gdb-2003-07-22-cvs
mkdir ../gdb-sun4
cd ../gdb-sun4
../gdb-2003-07-22-cvs/configure sun4
make
```

When `configure` builds a configuration using a remote source directory, it creates a tree for the binaries with the same structure (and using the same names) as the tree under the source directory.

In the example, you'd find the Sun 4 library `libiberty.a` in the directory `gdb-sun4/libiberty`, and `gdb` itself in `gdb-sun4/gdb`.

Make sure that your path to the `configure` script has just one instance of `gdb` in it. If your path to `configure` looks like `../gdb-2003-07-22-cvs/gdb/configure`, you are configuring only one subdirectory of `gdb`, not the whole package. This leads to build errors about missing include files such as `bfd/bfd.h`.

One popular reason to build several `gdb` configurations in separate directories is to configure `gdb` for cross-compiling (where `gdb` runs on one machine--the *host*--while debugging programs that run on another machine--the *target*). You specify a cross-debugging target by giving the `-target=target` option to `configure`.

When you run `make` to build a program or library, you must run it in a configured directory--whatever directory you were in when you called `configure` (or one of its subdirectories).

The `Makefile` that `configure` generates in each source directory also runs recursively. If you type `make` in a source directory such as `gdb-2003-07-22-cvs` (or in a separate configured directory configured with `-srcdir=dirname/gdb-2003-07-22-cvs`), you will build all the required libraries, and then build GDB.

When you have multiple hosts or targets configured in separate directories, you can run `make` on them in parallel (for example, if they are NFS-mounted on each of the hosts); they will not interfere with each other.

B.2. Specifying names for hosts and targets

The specifications used for hosts and targets in the `configure` script are based on a three-part naming scheme, but some short predefined aliases are also supported. The full naming scheme encodes three pieces of information in the following pattern:

```
architecture-vendor-os
```

For example, you can use the alias `sun4` as a `host` argument, or as the value for `target` in a `-target=target` option. The equivalent full name is `sparc-sun-sunos4`.

The `configure` script accompanying `gdb` does not provide any query facility to list all supported host and target names or aliases. `configure` calls the Bourne shell script `config.sub` to map abbreviations to full names; you can read the script, if you wish, or you can use it to test your guesses on abbreviations--for example:

```
% sh config.sub i386-linux
i386-pc-linux-gnu
% sh config.sub alpha-linux
alpha-unknown-linux-gnu
% sh config.sub hp9k700
hppa1.1-hp-hpux
% sh config.sub sun4
sparc-sun-sunos4.1.1
% sh config.sub sun3
m68k-sun-sunos4.1.1
% sh config.sub i986v
Invalid configuration 'i986v': machine 'i986v' not recognized
```

`config.sub` is also distributed in the `gdb` source directory (`gdb-2003-07-22-cvs`, for version `2003-07-22-cvs`).

B.3. configure options

Here is a summary of the `configure` options and arguments that are most often useful for building `gdb`. `configure` also has several other options not listed here. *note (configure.info)What Configure Does::, for a full explanation of `configure`.

```
configure [--help]
          [--prefix=dir]
          [--exec-prefix=dir]
          [--srcdir=dirname]
          [--norecursion] [--rm]
          [--target=target]
          host
```

You may introduce options with a single `-` rather than `--` if you prefer; but you may abbreviate option names if you use `-`.

`-help`

Display a quick summary of how to invoke `configure`.

`-prefix=dir`

Configure the source to install programs and files under directory `dir`.

`-exec-prefix=dir`

Configure the source to install programs under directory `dir`.

`-srcdir=dirname`

Warning: using this option requires `gnu make`, or another `make` that implements the `VPATH` feature. Use this option to make configurations in directories separate from the `gdb` source directories. Among other things, you can use this to build (or maintain) several configurations simultaneously, in separate directories. `configure` writes configuration specific files in the current directory, but arranges for them to use the source in the directory `dirname`. `configure` creates directories under the working directory in parallel to the source directories below `dirname`.

`-norecursion`

Configure only the directory level where `configure` is executed; do not propagate configuration to subdirectories.

`-target=target`

Configure `gdb` for cross-debugging programs running on the specified `target`. Without this option, `gdb` is configured to debug programs that run on the same machine (`host`) as `gdb` itself.

There is no convenient way to generate a list of all available targets.

`host ...`

Configure `gdb` to run on the specified `host`.

There is no convenient way to generate a list of all available hosts.

There are many other options available as well, but they are generally needed for special purposes only.

Maintenance Commands

In addition to commands intended for `gdb` users, `gdb` includes a number of commands intended for `gdb` developers. These commands are provided here for reference.

```
maint info breakpoints
```

Using the same format as `info breakpoints`, display both the breakpoints you've set explicitly, and those `gdb` is using for internal purposes. Internal breakpoints are shown with negative breakpoint numbers. The type column identifies what kind of breakpoint is shown:

```
breakpoint
```

Normal, explicitly set breakpoint.

```
watchpoint
```

Normal, explicitly set watchpoint.

```
longjmp
```

Internal breakpoint, used to handle correctly stepping through `longjmp` calls.

```
longjmp resume
```

Internal breakpoint at the target of a `longjmp`.

```
until
```

Temporary internal breakpoint used by the `gdb until` command.

```
finish
```

Temporary internal breakpoint used by the `gdb finish` command.

```
shlib events
```

Shared library events.

```
maint internal-error
```

```
maint internal-warning
```

Cause `gdb` to call the internal function `internal_error` or `internal_warning` and hence behave as though an internal error or internal warning has been detected. In addition to reporting the internal problem, these functions give the user the opportunity to either quit `gdb` or create a core file of the current `gdb` session.

```
(gdb) maint internal-error testing, 1, 2
../maint.c:121: internal-error: testing, 1, 2
A problem internal to GDB has been detected. Further
debugging may prove unreliable.
Quit this debugging session? (y or n) n
Create a core file? (y or n) n
(gdb)
```

Takes an optional parameter that is used as the text of the error or warning message.

```
maint print dummy-frames
```

Prints the contents of gdb's internal dummy-frame stack.

```
(gdb) b add
...
(gdb) print add(2,3)
Breakpoint 2, add (a=2, b=3) at ...
58 return (a + b);
The program being debugged stopped while in a function called from GDB.
...
(gdb) maint print dummy-frames
0x1a57c80: pc=0x01014068 fp=0x0200bddc sp=0x0200bdd6
top=0x0200bdd4 id={stack=0x200bddc,code=0x101405c}
call_lo=0x01014000 call_hi=0x01014001
(gdb)
```

Takes an optional file parameter.

```
maint print registers
maint print raw-registers
maint print cooked-registers
maint print register-groups
```

Print gdb's internal register data structures.

The command `maint print raw-registers` includes the contents of the raw register cache; the command `maint print cooked-registers` includes the (cooked) value of all registers; and the command `maint print register-groups` includes the groups that each register is a member of. .

Takes an optional file parameter.

```
maint print reggroups
```

Print gdb's internal register group data structures.

Takes an optional file parameter.

```
(gdb) maint print reggroups
Group      Type
general    user
float      user
all        user
vector     user
system     user
save       internal
restore    internal
```

```
maint set profile
maint show profile
```

Control profiling of gdb.

Profiling will be disabled until you use the `maint set profile` command to enable it. When you enable profiling, the system will begin collecting timing and execution count data; when you disable profiling or exit gdb, the results will be written to a log file. Remember that if you use profiling, gdb will overwrite the profiling log file (often called `gmon.out`). If you have a record of important profiling data in a `gmon.out` file, be sure to move it to a safe location.

Configuring with `-enable-profiling` arranges for gdb to be compiled with the `-pg` compiler option.

gdb Remote Serial Protocol

D.1. Overview

There may be occasions when you need to know something about the protocol—for example, if there is only one serial port to your target machine, you might want your program to do something special if it recognizes a packet meant for gdb.

In the examples below, `->` and `<-` are used to indicate transmitted and received data respectfully.

All gdb commands and responses (other than acknowledgments) are sent as a `packet`. A `packet` is introduced with the character `$`, the actual `packet-data`, and the terminating character `#` followed by a two-digit `checksum`:

```
$packet-data#checksum
```

The two-digit `checksum` is computed as the modulo 256 sum of all characters between the leading `$` and the trailing `#` (an eight bit unsigned checksum).

Implementors should note that prior to gdb 5.0 the protocol specification also included an optional two-digit `sequence-id`:

```
$sequence-id:packet-data#checksum
```

That `sequence-id` was appended to the acknowledgment. gdb has never output `sequence-ids`. Stubs that handle packets added since gdb 5.0 must not accept `sequence-id`.

When either the host or the target machine receives a packet, the first response expected is an acknowledgment: either `+` (to indicate the package was received correctly) or `-` (to request retransmission):

```
-> $packet-data#checksum
<- +
```

The host (gdb) sends `commands`, and the target (the debugging stub incorporated in your program) sends a `response`. In the case of `step` and `continue` `commands`, the response is only sent when the operation has completed (the target has again stopped).

`packet-data` consists of a sequence of characters with the exception of `#` and `$` (see `x packet` for additional exceptions).

Fields within the packet should be separated using `,` `;` or `:`. Except where otherwise noted all numbers are represented in hex with leading zeros suppressed.

Implementors should note that prior to gdb 5.0, the character `:` could not appear as the third character in a packet (as it would potentially conflict with the `sequence-id`).

Response `data` can be run-length encoded to save space. A `*` means that the next character is an ascii encoding giving a repeat count which stands for that many repetitions of the character preceding the `*`. The encoding is `n+29`, yielding a printable character where `n >=3` (which is where `rlc` starts to

win). The printable characters \$, #, + and - or with a numeric value greater than 126 should not be used.

Some remote systems have used a different run-length encoding mechanism loosely referred to as the cisco encoding. Following the * character are two hex digits that indicate the size of the packet.

So:

```
"0* "
```

means the same as "0000".

The error response returned for some packets includes a two character error number. That number is not well defined.

For any `command` not supported by the stub, an empty response (`$#00`) should be returned. That way it is possible to extend the protocol. A newer gdb can tell if a packet is supported based on that response.

A stub is required to support the `g`, `G`, `m`, `M`, `c`, and `s` `commands`. All other `commands` are optional.

D.2. Packets

The following table provides a complete list of all currently defined `commands` and their corresponding response `data`.

! -- extended mode

Enable extended mode. In extended mode, the remote server is made persistent. The `R` packet is used to restart the program being debugged.

Reply:

```
OK
```

The remote target both supports and has enabled extended mode.

? -- last signal

Indicate the reason the target halted. The reply is the same as for `step` and `continue`.

Reply: (refer to Section D.3 *Stop Reply Packets*, for the reply specifications).

a -- reserved

Reserved for future use.

`Aarglen, argnum, arg, ... -- set program arguments (reserved)`

Initialized `argv[]` array passed into program. `arglen` specifies the number of bytes in the hex encoded byte stream `arg`. See `gdbserver` for more details.

Reply:

```
OK
```

```
ENN
```

No other details.

`bbaud -- set baud` (*deprecated*)

Change the serial line speed to `baud`.

JTC: When does the transport layer state change? When it's received, or after the ACK is transmitted. In either case, there are problems if the command or the acknowledgment packet is dropped.

Stan: If people really wanted to add something like this, and get it working for the first time, they ought to modify `ser-unix.c` to send some kind of out-of-band message to a specially-setup stub and have the switch happen "in between" packets, so that from remote protocol's point of view, nothing actually happened.

`Baddr,mode -- set breakpoint` (*deprecated*)

Set (`mode` is `S`) or clear (`mode` is `C`) a breakpoint at `addr`.

This packet has been replaced by the `Z` and `z` packets.

`caddr -- continue`

`addr` is address to resume. If `addr` is omitted, resume at current address.

Reply: (refer to Section D.3 *Stop Reply Packets*, for the reply specifications).

`Csig;addr -- continue with signal`

Continue with signal `sig` (hex signal number). If `addr` is omitted, resume at same address.

Reply: (refer to Section D.3 *Stop Reply Packets*, for the reply specifications).

`d -- toggle debug` (*deprecated*)

Toggle debug flag.

`D -- detach`

Detach gdb from the remote system. Sent to the remote target before gdb disconnects via the `detach` command.

Reply:

no response

{No value for '`<listitem>GDBN`'} does not check for any response after sending this packet.

`e -- reserved`

Reserved for future use.

`E -- reserved`

Reserved for future use.

`f -- reserved`

Reserved for future use.

`FRC,EE,CF;XX -- Reply to target's F packet.`

This packet is send by gdb as reply to a `F` request packet sent by the target. This is part of the File-I/O protocol extension. Refer to Section D.7 *File-I/O remote protocol extension*, for the specification.

`g` -- read registers

Read general registers.

Reply:

XX...

Each byte of register data is described by two hex digits. The bytes with the register are transmitted in target byte order. The size of each register and their position within the `g` packet are determined by the gdb internal macros `REGISTER_RAW_SIZE` and `REGISTER_NAME` macros. The specification of several standard `g` packets is specified below.

ENN

for an error.

`GXX...` -- write regs

Reply:

OK

for success

ENN

for an error

`h` -- reserved

Reserved for future use.

`Hct...` -- set thread

Set thread for subsequent operations (`m`, `M`, `g`, `G`, et.al.). `c` depends on the operation to be performed: it should be `c` for step and continue operations, `g` for other operations. The thread designator `t...` may be `-1`, meaning all the threads, a thread number, or zero which means pick any thread.

Reply:

OK

for success

ENN

for an error

`iaddr, nnn` -- cycle step (*draft*)

Step the remote target by a single clock cycle. If `i`, `nnn` is present, cycle step `nnn` cycles. If `addr` is present, cycle step starting at that address.

I -- signal then cycle step (*reserved*)

j -- reserved

Reserved for future use.

J -- reserved

Reserved for future use.

k -- kill request

FIXME: There is no description of how to operate when a specific thread context has been selected (that is, does 'k' kill only that thread?).

K -- reserved

Reserved for future use.

l -- reserved

Reserved for future use.

L -- reserved

Reserved for future use.

maddr,length -- read memory

Read `length` bytes of memory starting at address `addr`. Neither gdb nor the stub assume that sized memory transfers are assumed using word aligned accesses. *FIXME: A word aligned memory transfer mechanism is needed.*

Reply:

XX...

XX... is mem contents. Can be fewer bytes than requested if able to read only part of the data. Neither gdb nor the stub assume that sized memory transfers are assumed using word aligned accesses. *FIXME: A word aligned memory transfer mechanism is needed.*

ENN

NN is errno

Maddr,length:XX... -- write mem

Write `length` bytes of memory starting at address `addr`. XX... is the data.

Reply:

OK

for success

ENN

for an error (this includes the case where only part of the data was written).

n -- reserved

Reserved for future use.

N -- reserved

Reserved for future use.

o -- reserved

Reserved for future use.

O -- reserved

Reserved for future use.

pn... -- read reg (*reserved*)

Reply:

r...

The hex encoded value of the register in target byte order.

Pn...=r... -- write register

Write register n... with value r..., which contains two hex digits for each byte in the register (target byte order).

Reply:

OK

for success

ENN

for an error

qquery -- general query

Request info about `query`. In general gdb queries have a leading upper case letter. Custom vendor queries should use a company prefix (in lower case) ex: `qfsf.var.query` may optionally be followed by a , or ; separated list. Stubs must ensure that they match the full `query` name.

Reply:

xx...

Hex encoded data from query. The reply can not be empty.

ENN

error reply

Indicating an unrecognized `query`.

`Qvar=val` -- general set

Set value of `var` to `val`.

Refer to Section D.4 *General Query Packets*, for a discussion of naming conventions.

`r` -- reset (*deprecated*)

Reset the entire system.

`RXX` -- remote restart

Restart the program being debugged. `XX`, while needed, is ignored. This packet is only available in extended mode.

Reply:

no reply

The `R` packet has no reply.

`saddr` -- step

`addr` is address to resume. If `addr` is omitted, resume at same address.

Reply: (refer to Section D.3 *Stop Reply Packets*, for the reply specifications).

`Ssig;addr` -- step with signal

Like `C` but step not continue.

Reply: (refer to Section D.3 *Stop Reply Packets*, for the reply specifications).

`taddr:PP,MM` -- search

Search backwards starting at address `addr` for a match with pattern `PP` and mask `MM`. `PP` and `MM` are 4 bytes. `addr` must be at least 3 digits.

`TXX` -- thread alive

Find out if the thread `XX` is alive.

Reply:

OK

thread is still alive

ENN

thread is dead

`u` -- reserved

Reserved for future use.

`U` -- reserved

Reserved for future use.

`v` -- reserved

Reserved for future use.

V -- reserved

Reserved for future use.

w -- reserved

Reserved for future use.

W -- reserved

Reserved for future use.

x -- reserved

Reserved for future use.

Xaddr, length:XX... -- write mem (binary)

addr is address, length is number of bytes, XX... is binary data. The characters \$, #, and 0x7d are escaped using 0x7d.

Reply:

OK

for success

ENN

for an error

y -- reserved

Reserved for future use.

Y reserved

Reserved for future use.

ztype, addr, length -- remove breakpoint or watchpoint (*draft*)

Ztype, addr, length -- insert breakpoint or watchpoint (*draft*)

Insert (Z) or remove (z) a type breakpoint or watchpoint starting at address address and covering the next length bytes.

Each breakpoint and watchpoint packet type is documented separately.

Implementation notes: A remote target shall return an empty string for an unrecognized breakpoint or watchpoint packet type. A remote target shall support either both or neither of a given Ztype... and ztype... packet pair. To avoid potential problems with duplicate packets, the operations should be implemented in an idempotent way.

z0, addr, length -- remove memory breakpoint (*draft*)

Z0, addr, length -- insert memory breakpoint (*draft*)

Insert (Z0) or remove (z0) a memory breakpoint at address addr of size length.

A memory breakpoint is implemented by replacing the instruction at addr with a software breakpoint or trap instruction. The length is used by targets that indicates the size of the breakpoint (in bytes) that should be inserted (e.g., the arm and mips can insert either a 2 or 4 byte breakpoint).

Implementation note: It is possible for a target to copy or move code that contains memory breakpoints (e.g., when implementing overlays). The behavior of this packet, in the presence of such a target, is not defined.

Reply:

OK

success

not supported

ENN

for an error

`z1,addr,length` -- remove hardware breakpoint (*draft*)

`Z1,addr,length` -- insert hardware breakpoint (*draft*)

Insert (`Z1`) or remove (`z1`) a hardware breakpoint at address `addr` of size `length`.

A hardware breakpoint is implemented using a mechanism that is not dependant on being able to modify the target's memory.

Implementation note: A hardware breakpoint is not affected by code movement.

Reply:

OK

success

not supported

ENN

for an error

`z2,addr,length` -- remove write watchpoint (*draft*)

`Z2,addr,length` -- insert write watchpoint (*draft*)

Insert (`Z2`) or remove (`z2`) a write watchpoint.

Reply:

OK

success

not supported

ENN

for an error

`z3,addr,length` -- remove read watchpoint (*draft*)

`Z3,addr,length` -- insert read watchpoint (*draft*)

Insert (`Z3`) or remove (`z3`) a read watchpoint.

Reply:

OK

success

not supported

ENN

for an error

`z4,addr,length` -- remove access watchpoint (*draft*)

`Z4,addr,length` -- insert access watchpoint (*draft*)

Insert (`Z4`) or remove (`z4`) an access watchpoint.

Reply:

OK

success

not supported

ENN

for an error

D.3. Stop Reply Packets

The `C`, `c`, `S`, `s` and `?` packets can receive any of the below as a reply. In the case of the `C`, `c`, `S` and `s` packets, that reply is only returned when the target halts. In the below the exact meaning of `signal number` is poorly defined. In general one of the UNIX signal numbering conventions is used.

SAA

AA is the signal number

TAA`n...:r...;n...:r...;n...:r...;`

AA = two hex digit signal number; `n...` = register number (hex), `r...` = target byte ordered register contents, size defined by `REGISTER_RAW_SIZE`; `n...` = `thread`, `r...` = thread process ID, this is a hex integer; `n...` = (`watch` | `rwatch` | `awatch`), `r...` = data address, this is a hex integer; `n...` = other string not starting with valid hex digit. gdb should ignore this `n...`, `r...` pair and go on to the next. This way we can extend the protocol.

WAA

The process exited, and AA is the exit status. This is only applicable to certain targets.

XAA

The process terminated with signal AA.

NAA;t...;d...;b...

(*obsolete*)

AA = signal number; t... = address of symbol `_start`; d... = base of data section; b... = base of bss section. *Note: only used by Cisco Systems targets. The difference between this reply and the `qOffsets` query is that the N packet may arrive spontaneously whereas the `qOffsets` is a query initiated by the host debugger.*

OXX...

XX... is hex encoding of ascii data. This can happen at any time while the program is running and the debugger should continue to wait for W, T, etc.

Fcall-id,parameter...

call-id is the identifier which says which host system call should be called. This is just the name of the function. Translation into the correct system call is only applicable as it's defined in gdb. Refer to Section D.7 *File-I/O remote protocol extension*, for a list of implemented system calls.

parameter... is a list of parameters as defined for this very system call.

The target replies with this packet when it expects gdb to call a host system call on behalf of the target. gdb replies with an appropriate F packet and keeps up waiting for the next reply packet from the target. The latest C, c, S or s action is expected to be continued. Refer to Section D.7 *File-I/O remote protocol extension*, for more details.

D.4. General Query Packets

The following set and query packets have already been defined.

qC -- current thread

Return the current thread id.

Reply:

QCpid

Where pid is a HEX encoded 16 bit process id.

*

Any other reply implies the old pid.

qfThreadInfo - all thread ids

qsThreadInfo

Obtain a list of active thread ids from the target (OS). Since there may be too many active threads to fit into one reply packet, this query works iteratively: it may require more than one query/reply sequence to obtain the entire list of threads. The first query of the sequence will be the `qfThreadInfo` query; subsequent queries in the sequence will be the `qsThreadInfo` query.

NOTE: replaces the `qL` query (see below).

Reply:

mid

A single thread id

mid, id...

a comma-separated list of thread ids

l

(lower case 'el') denotes end of list.

In response to each query, the target will reply with a list of one or more thread ids, in big-endian hex, separated by commas. gdb will respond to each reply with a request for more thread ids (using the `qs` form of the query), until the target responds with `l` (lower-case el, for 'last').

`qThreadExtraInfo, id` -- extra thread info

Where `id` is a thread-id in big-endian hex. Obtain a printable string description of a thread's attributes from the target OS. This string may contain anything that the target OS thinks is interesting for gdb to tell the user about the thread. The string is displayed in gdb's `info threads` display. Some examples of possible thread extra info strings are "Runnable", or "Blocked on Mutex".

Reply:

xx...

Where `xx...` is a hex encoding of ascii data, comprising the printable string containing the extra information about the thread's attributes.

`qLstartflagthreadcountnextthread` -- query LIST or threadLIST (*deprecated*)

Obtain thread information from RTOS. Where: `startflag` (one hex digit) is one to indicate the first query and zero to indicate a subsequent query; `threadcount` (two hex digits) is the maximum number of threads the response packet can contain; and `nextthread` (eight hex digits), for subsequent queries (`startflag` is zero), is returned in the response as `argthread`.

NOTE: this query is replaced by the `qfThreadInfo` query (see above).

Reply:

`qMcountdoneargthreadthread...`

Where: `count` (two hex digits) is the number of threads being returned; `done` (one hex digit) is zero to indicate more threads and one indicates no further threads; `argthreadid` (eight hex digits) is `nextthread` from the request packet; `thread...` is a sequence of thread IDs from the target. `threadid` (eight hex digits). See `remote.c:parse_threadlist_response()`.

`qCRC: addr, length` -- compute CRC of memory block

Reply:

ENN

An error (such as memory fault)

CCRC32

A 32 bit cyclic redundancy check of the specified memory region.

`qOffsets` -- query sect offs

Get section offsets that the target used when re-locating the downloaded image. *Note: while a Bss offset is included in the response, gdb ignores this and instead applies the Data offset to the Bss section.*

Reply:

Text=xxx;Data=yyy;Bss=zzz

Text command.

`qPmodethreadid` -- thread info request

Returns information on `threadid`. Where: `mode` is a hex encoded 32 bit mode; `threadid` is a hex encoded 64 bit thread ID.

Reply:

*

* command

See `remote.c:remote_unpack_thread_info_response()`.

`qRcmd, command` -- remote command

`command` (hex encoded) is passed to the local interpreter for execution. Invalid commands should be reported using the output string. Before the final result packet, the target may also respond with a number of intermediate `Output` console output packets. *Implementors should note that providing access to a stubs's interpreter may have security implications.*

Reply:

OK

A command response with no output.

OUTPUT

A command response with the hex encoded output string `OUTPUT`.

ENN

Indicate a badly formed request.

When `qRcmd` is not recognized.

`qSymbol:` -- symbol lookup

Notify the target that `gdb` is prepared to serve symbol lookup requests. Accept requests from the target for the values of symbols.

Reply:

OK

The target does not need to look up any (more) symbols.

qSymbol:sym_name

The target requests the value of symbol `sym_name` (hex encoded). gdb may provide the value by using the `qSymbol:sym_value:sym_name` message, described below.

qSymbol:sym_value:sym_name -- symbol value

Set the value of `sym_name` to `sym_value`.

`sym_name` (hex encoded) is the name of a symbol whose value the target has previously requested.

`sym_value` (hex) is the value for symbol `sym_name`. If gdb cannot supply a value for `sym_name`, then this field will be empty.

Reply:

OK

The target does not need to look up any (more) symbols.

qSymbol:sym_name

The target requests the value of a new symbol `sym_name` (hex encoded). gdb will continue to supply the values of symbols (if available), until the target ceases to request them.

D.5. Register Packet Format

The following *g/g* packets have previously been defined. In the below, some thirty-two bit registers are transferred as sixty-four bits. Those registers should be zero/sign extended (which?) to fill the space allocated. Register bytes are transferred in target byte order. The two nibbles within a register byte are transferred most-significant - least-significant.

MIPS32

All registers are transferred as thirty-two bit quantities in the order: 32 general-purpose; `sr`; `lo`; `hi`; `bad`; `cause`; `pc`; 32 floating-point registers; `fsr`; `fir`; `fp`.

MIPS64

All registers are transferred as sixty-four bit quantities (including thirty-two bit registers such as `sr`). The ordering is the same as `MIPS32`.

D.6. Examples

Example sequence of a target being re-started. Notice how the restart does not get any direct output:

```
-> R00
<- +
target restarts
-> ?
<- +
```

```
<- T001:1234123412341234
-> +
```

Example sequence of a target being stepped by a single instruction:

```
-> G1445...
<- +
-> s
<- +
time passes
<- T001:1234123412341234
-> +
-> g
<- +
<- 1455...
-> +
```

D.7. File-I/O remote protocol extension

D.7.1. File-I/O Overview

The File I/O remote protocol extension (short: File-I/O) allows the target to use the hosts file system and console I/O when calling various system calls. System calls on the target system are translated into a remote protocol packet to the host system which then performs the needed actions and returns with an adequate response packet to the target system. This simulates file system operations even on targets that lack file systems.

The protocol is defined host- and target-system independent. It uses it's own independent representation of datatypes and values. Both, gdb and the target's gdb stub are responsible for translating the system dependent values into the unified protocol values when data is transmitted.

The communication is synchronous. A system call is possible only when GDB is waiting for the `C`, `c`, `S` or `s` packets. While gdb handles the request for a system call, the target is stopped to allow deterministic access to the target's memory. Therefore File-I/O is not interruptible by target signals. It is possible to interrupt File-I/O by a user interrupt (Ctrl-C), though.

The target's request to perform a host system call does not finish the latest `C`, `c`, `S` or `s` action. That means, after finishing the system call, the target returns to continuing the previous activity (continue, step). No additional continue or step request from gdb is required.

```
(gdb) continue
<- target requests 'system call X'
target is stopped, gdb executes system call
-> GDB returns result
... target continues, GDB returns to wait for the target
<- target hits breakpoint and sends a Txx packet
```

The protocol is only used for files on the host file system and for I/O on the console. Character or block special devices, pipes, named pipes or sockets or any other communication method on the host system are not supported by this protocol.

D.7.2. Protocol basics

The File-I/O protocol uses the `F` packet, as request as well as as reply packet. Since a File-I/O system call can only occur when gdb is waiting for the continuing or stepping target, the File-I/O request is a reply that gdb has to expect as a result of a former `C`, `c`, `S` or `s` packet. This `F` packet contains all information needed to allow gdb to call the appropriate host system call:

- A unique identifier for the requested system call.
- All parameters to the system call. Pointers are given as addresses in the target memory address space. Pointers to strings are given as pointer/length pair. Numerical values are given as they are. Numerical control values are given in a protocol specific representation.

At that point gdb has to perform the following actions.

- If parameter pointer values are given, which point to data needed as input to a system call, gdb requests this data from the target with a standard `m` packet request. This additional communication has to be expected by the target implementation and is handled as any other `m` packet.
- gdb translates all value from protocol representation to host representation as needed. Datatypes are coerced into the host types.
- gdb calls the system call
- It then coerces datatypes back to protocol representation.
- If pointer parameters in the request packet point to buffer space in which a system call is expected to copy data to, the data is transmitted to the target using a `M` or `X` packet. This packet has to be expected by the target implementation and is handled as any other `M` or `X` packet.

Eventually gdb replies with another `F` packet which contains all necessary information for the target to continue. This at least contains

- Return value.
- `errno`, if has been changed by the system call.
- "Ctrl-C" flag.

After having done the needed type and value coercion, the target continues the latest continue or step action.

D.7.3. The `Frequest` packet

The `F` request packet has the following format:

```
Fcall-id,parameter...
```

`call-id` is the identifier to indicate the host system call to be called. This is just the name of the function. `parameter...` are the parameters to the system call.

Parameters are hexadecimal integer values, either the real values in case of scalar datatypes, as pointers to target buffer space in case of compound datatypes and unspecified memory areas or as pointer/length pairs in case of string parameters. These are appended to the call-id, each separated from its predecessor by a comma. All values are transmitted in ASCII string representation, pointer/length pairs separated by a slash.

D.7.4. The F reply packet

The F reply packet has the following format:

```
Fretcode,errno,Ctrl-C flag;call specific attachment
```

`retcode` is the return code of the system call as hexadecimal value. `errno` is the `errno` set by the call, in protocol specific representation. This parameter can be omitted if the call was successful. `Ctrl-C flag` is only send if the user requested a break. In this case, `errno` must be send as well, even if the call was successful. The `Ctrl-C flag` itself consists of the character 'C':

```
F0,0,C
```

or, if the call was interrupted before the host call has been performed:

```
F-1,4,C
```

assuming 4 is the protocol specific representation of `EINTR`.

D.7.5. Memory transfer

Structured data which is transferred using a memory read or write as e.g. a `struct stat` is expected to be in a protocol specific format with all scalar multibyte datatypes being big endian. This should be done by the target before the F packet is sent resp. by gdb before it transfers memory to the target. Transferred pointers to structured data should point to the already coerced data at any time.

D.7.6. The Ctrl-C message

A special case is, if the `Ctrl-C flag` is set in the gdb reply packet. In this case the target should behave, as if it had gotten a break message. The meaning for the target is "system call interrupted by SIGINT". Consequentially, the target should actually stop (as with a break message) and return to gdb with a T02 packet. In this case, it's important for the target to know, in which state the system call was interrupted. Since this action is by design not an atomic operation, we have to differ between two cases:

- The system call hasn't been performed on the host yet.
- The system call on the host has been finished.

These two states can be distinguished by the target by the value of the returned `errno`. If it's the protocol representation of `EINTR`, the system call hasn't been performed. This is equivalent to the `EINTR` handling on POSIX systems. In any other case, the target may presume that the system call has been finished -- successful or not -- and should behave as if the break message arrived right after the system call.

gdb must behave reliable. If the system call has not been called yet, gdb may send the F reply immediately, setting `EINTR` as `errno` in the packet. If the system call on the host has been finished before the user requests a break, the full action must be finished by gdb. This requires sending M or X packets as they fit. The F packet may only be send when either nothing has happened or the full action has been completed.

D.7.7. Console I/O

By default and if not explicitly closed by the target system, the file descriptors 0, 1 and 2 are connected to the gdb console. Output on the gdb console is handled as any other file output operation (`write(1, ...)` or `write(2, ...)`). Console input is handled by gdb so that after the target read request from file descriptor 0 all following typing is buffered until either one of the following conditions is met:

- The user presses **Ctrl-C**. The behaviour is as explained above, the `read` system call is treated as finished.
- The user presses **Enter**. This is treated as end of input with a trailing line feed.
- The user presses **Ctrl-D**. This is treated as end of input. No trailing character, especially no **Ctrl-D** is appended to the input.

If the user has typed more characters as fit in the buffer given to the `read` call, the trailing characters are buffered in `gdb` until either another `read(0, ...)` is requested by the target or debugging is stopped on users request.

D.7.8. The `isatty(3)` call

A special case in this protocol is the library call `isatty` which is implemented as it's own call inside of this protocol. It returns 1 to the target if the file descriptor given as parameter is attached to the `gdb` console, 0 otherwise. Implementing through system calls would require implementing `ioctl` and would be more complex than needed.

D.7.9. The `system(3)` call

The other special case in this protocol is the `system` call which is implemented as it's own call, too. `gdb` is taking over the full task of calling the necessary host calls to perform the `system` call. The return value of `system` is simplified before it's returned to the target. Basically, the only signal transmitted back is `EINTR` in case the user pressed **Ctrl-C**. Otherwise the return value consists entirely of the exit status of the called command.

Due to security concerns, the `system` call is refused to be called by `gdb` by default. The user has to allow this call explicitly by entering

```
set remote system-call-allowed 1
```

Set the call.

Disabling the `system` call is done by

```
set remote system-call-allowed 0
```

Set the call.

The current setting is shown by typing

```
show remote system-call-allowed
```

Set the call.

D.7.10. List of supported calls

D.7.10.1. open

Synopsis: int open(const char *pathname, int flags);
 int open(const char *pathname, int flags, mode_t mode);

Request:

 Fopen, pathptr/len, flags, mode

flags is the bitwise or of the following values:

O_CREAT

 If the file does not exist it will be created. The host rules apply as far as file ownership and time stamps are concerned.

O_EXCL

 When used with O_CREAT, if the file already exists it is an error and open() fails.

O_TRUNC

 If the file already exists and the open mode allows writing (O_RDWR or O_WRONLY is given) it will be truncated to length 0.

O_APPEND

 The file is opened in append mode.

O_RDONLY

 The file is opened for reading only.

O_WRONLY

 The file is opened for writing only.

O_RDWR

 The file is opened for reading and writing.

 Each other bit is silently ignored.

mode is the bitwise or of the following values:

S_IRUSR

 User has read permission.

S_IWUSR

 User has write permission.

S_IRGRP

 Group has read permission.

S_IWGRP

 Group has write permission.

S_IROTH

 Others have read permission.

S_IWOTH

Others have write permission.

Each other bit is silently ignored.

Return value: `open` returns the new file descriptor or `-1` if an error occurred.

Errors:

EEXIST

`pathname` already exists and `O_CREAT` and `O_EXCL` were used.

EISDIR

`pathname` refers to a directory.

EACCES

The requested access is not allowed.

ENAMETOOLONG

`pathname` was too long.

ENOENT

A directory component in `pathname` does not exist.

ENODEV

`pathname` refers to a device, pipe, named pipe or socket.

EROFS

`pathname` refers to a file on a read-only filesystem and write access was requested.

EFAULT

`pathname` is an invalid pointer value.

ENOSPC

No space on device to create the file.

EMFILE

The process already has the maximum number of files open.

ENFILE

The limit on the total number of files open on the system has been reached.

EINTR

The call was interrupted by the user.

D.7.10.2. close

Synopsis: int close(int fd);

Request:
 Fclose, fd

Return value:
 close returns zero on success, or -1 if an error occurred.

Errors:

EBADF

 fd isn't a valid open file descriptor.

EINTR

 The call was interrupted by the user.

D.7.10.3. read

Synopsis: int read(int fd, void *buf, unsigned int count);

Request:
 Fread, fd, bufptr, count

Return value:
 On success, the number of bytes read is returned.
 Zero indicates end of file. If count is zero, read
 returns zero as well. On error, -1 is returned.

Errors:

EBADF

 fd is not a valid file descriptor or is not open for reading.

EFAULT

 buf is an invalid pointer value.

EINTR

 The call was interrupted by the user.

D.7.10.4. write

Synopsis: `int write(int fd, const void *buf, unsigned int count);`

Request:
`Fwrite, fd, bufptr, count`

Return value:
 On success, the number of bytes written are returned.
 Zero indicates nothing was written. On error, -1
 is returned.

Errors:

EBADF

`fd` is not a valid file descriptor or is not open for writing.

EFAULT

`buf` is an invalid pointer value.

EFBIG

An attempt was made to write a file that exceeds the host specific maximum file size allowed.

ENOSPC

No space on device to write the data.

EINTR

The call was interrupted by the user.

D.7.10.5. lseek

Synopsis: `long lseek (int fd, long offset, int flag);`

Request:
`Fseek, fd, offset, flag`

`flag` is one of:

SEEK_SET

The offset is set to offset bytes.

SEEK_CUR

The offset is set to its current location plus offset bytes.

SEEK_END

The offset is set to the size of the file plus offset bytes.

Return value: On success, the resulting unsigned offset in bytes from the beginning of the file is returned. Otherwise, a value of -1 is returned.

Errors:

EBADF

fd is not a valid open file descriptor.

ESPIPE

fd is associated with the gdb console.

EINVAL

flag is not a proper value.

EINTR

The call was interrupted by the user.

D.7.10.6. rename

Synopsis: `int rename(const char *oldpath, const char *newpath);`

Request:

`Frename, oldpathptr/len, newpathptr/len`

Return value:

On success, zero is returned. On error, -1 is returned.

Errors:

EISDIR

newpath is an existing directory, but oldpath is not a directory.

EEXIST

newpath is a non-empty directory.

EBUSY

oldpath or newpath is a directory that is in use by some process.

EINVAL

An attempt was made to make a directory a subdirectory of itself.

ENOTDIR

A component used as a directory in `oldpath` or `newpath` is not a directory. Or `oldpath` is a directory and `newpath` exists but is not a directory.

EFAULT

`oldpathptr` or `newpathptr` are invalid pointer values.

EACCES

No access to the file or the path of the file.

ENAMETOOLONG

`oldpath` or `newpath` was too long.

ENOENT

A directory component in `oldpath` or `newpath` does not exist.

EROFS

The file is on a read-only filesystem.

ENOSPC

The device containing the file has no room for the new directory entry.

EINTR

The call was interrupted by the user.

D.7.10.7. unlink

Synopsis: `int unlink(const char *pathname);`

Request:

`Funlink, pathnameptr/len`

Return value:

On success, zero is returned. On error, `-1` is returned.

Errors:

EACCES

No access to the file or the path of the file.

EPERM

The system does not allow unlinking of directories.

EBUSY

The file `pathname` cannot be unlinked because it's being used by another process.

EFAULT

pathnameptr is an invalid pointer value.

ENAMETOOLONG

pathname was too long.

ENOENT

A directory component in pathname does not exist.

ENOTDIR

A component of the path is not a directory.

EROFS

The file is on a read-only filesystem.

EINTR

The call was interrupted by the user.

D.7.10.8. stat/fstat

```
Synopsis:      int stat(const char *pathname, struct stat *buf);
int fstat(int fd, struct stat *buf);
```

Request:

```
    Fstat,pathnameptr/len,bufptr
Ffstat,fd,bufptr
```

Return value:

On success, zero is returned. On error, -1 is returned.

Errors:

EBADF

fd is not a valid open file.

ENOENT

A directory component in pathname does not exist or the path is an empty string.

ENOTDIR

A component of the path is not a directory.

EFAULT

pathnameptr is an invalid pointer value.

EACCES

No access to the file or the path of the file.

ENAMETOOLONG

pathname was too long.

EINTR

The call was interrupted by the user.

D.7.10.9. gettimeofday

Synopsis: `int gettimeofday(struct timeval *tv, void *tz);`

Request:
`Fgettimeofday, tvptr, tzptr`

Return value:
On success, 0 is returned, -1 otherwise.

Errors:

EINVAL

tz is a non-NULL pointer.

EFAULT

tvptr and/or tzptr is an invalid pointer value.

D.7.10.10. isatty

Synopsis: `int isatty(int fd);`

Request:
`Fisatty, fd`

Return value:
Returns 1 if fd refers to the gdb console, 0 otherwise.

Errors:

EINTR

The call was interrupted by the user.

D.7.10.11. system

Synopsis: int system(const char *command);

Request:
 Fsystem,commandptr/len

Return value:
 The value returned is -1 on error and the return status of the command otherwise. Only the exit status of the command is returned, which is extracted from the hosts system return value by calling WEXITSTATUS(retval). In case /bin/sh could not be executed, 127 is returned.

Errors:

EINTR

 The call was interrupted by the user.

D.7.11. Protocol specific representation of datatypes**D.7.11.1. Integral datatypes**

The integral datatypes used in the system calls are

int, unsigned int, long, unsigned long, mode_t and time_t

Int, unsigned int, mode_t and time_t are implemented as 32 bit values in this protocol.

Long and unsigned long are implemented as 64 bit types.

Refer to Section D.7.12.5 *Limits*, for corresponding MIN and MAX values (similar to those in limits.h) to allow range checking on host and target.

time_t datatypes are defined as seconds since the Epoch.

All integral datatypes transferred as part of a memory read or write of a structured datatype e.g. a struct stat have to be given in big endian byte order.

D.7.11.2. Pointer values

Pointers to target data are transmitted as they are. An exception is made for pointers to buffers for which the length isn't transmitted as part of the function call, namely strings. Strings are transmitted as a pointer/length pair, both as hex values, e.g.

laaf/12

which is a pointer to data of length 18 bytes at position 0x1aaf. The length is defined as the full string length in bytes, including the trailing null byte. Example:

```
"hello, world" at address 0x123456
```

is transmitted as

```
123456/d
```

D.7.11.3. struct stat

The buffer of type struct stat used by the target and gdb is defined as follows:

```
struct stat {
    unsigned int  st_dev;          /* device */
    unsigned int  st_ino;         /* inode */
    mode_t       st_mode;        /* protection */
    unsigned int  st_nlink;       /* number of hard links */
    unsigned int  st_uid;         /* user ID of owner */
    unsigned int  st_gid;        /* group ID of owner */
    unsigned int  st_rdev;        /* device type (if inode device) */
    unsigned long st_size;        /* total size, in bytes */
    unsigned long st_blksize;     /* blocksize for filesystem I/O */
    unsigned long st_blocks;      /* number of blocks allocated */
    time_t       st_atime;        /* time of last access */
    time_t       st_mtime;        /* time of last modification */
    time_t       st_ctime;        /* time of last change */
};
```

The integral datatypes are conforming to the definitions given in the appropriate section ((refer to Section D.7.11.1 *Integral datatypes*, for details) so this structure is of size 64 bytes.

The values of several fields have a restricted meaning and/or range of values.

```
st_dev:      0      file
             1      console

st_ino:      No valid meaning for the target.  Transmitted unchanged.

st_mode:     Valid mode bits are described in Appendix C.  Any other
             bits have currently no meaning for the target.

st_uid:      No valid meaning for the target.  Transmitted unchanged.

st_gid:      No valid meaning for the target.  Transmitted unchanged.

st_rdev:     No valid meaning for the target.  Transmitted unchanged.

st_atime, st_mtime, st_ctime:
             These values have a host and file system dependent
             accuracy.  Especially on Windows hosts the file systems
             don't support exact timing values.
```

The target gets a struct stat of the above representation and is responsible to coerce it to the target representation before continuing.

Note that due to size differences between the host and target representation of stat members, these members could eventually get truncated on the target.

D.7.11.4. struct timeval

The buffer of type struct timeval used by the target and gdb is defined as follows:

```
struct timeval {
    time_t tv_sec; /* second */
    long tv_usec; /* microsecond */
};
```

The integral datatypes are conforming to the definitions given in the appropriate section ((refer to Section D.7.11.1 *Integral datatypes*, for details) so this structure is of size 8 bytes.

D.7.12. Constants

The following values are used for the constants inside of the protocol. gdb and target are responsible to translate these values before and after the call as needed.

D.7.12.1. Open flags

All values are given in hexadecimal representation.

O_RDONLY	0x0
O_WRONLY	0x1
O_RDWR	0x2
O_APPEND	0x8
O_CREAT	0x200
O_TRUNC	0x400
O_EXCL	0x800

D.7.12.2. mode_t values

All values are given in octal representation.

S_IFREG	0100000
S_IFDIR	040000
S_IRUSR	0400
S_IWUSR	0200
S_IXUSR	0100
S_IRGRP	040
S_IWGRP	020
S_IXGRP	010
S_IROTH	04
S_IWOTH	02

S_IXOTH 01

D.7.12.3. Errno values

All values are given in decimal representation.

EPERM	1
ENOENT	2
EINTR	4
EBADF	9
EACCESS	13
EFAULT	14
EBUSY	16
EEXIST	17
ENODEV	19
ENOTDIR	20
EISDIR	21
EINVAL	22
ENFILE	23
EMFILE	24
EFBIG	27
ENOSPC	28
ESPIPE	29
EROFS	30
ENAMETOOLONG	91
EUNKNOWN	9999

EUNKNOWN is used as a fallback error value if a host system returns any error value not in the list of supported error numbers.

D.7.12.4. Lseek flags

SEEK_SET	0
SEEK_CUR	1
SEEK_END	2

D.7.12.5. Limits

All values are given in decimal representation.

INT_MIN	-2147483648
INT_MAX	2147483647
UINT_MAX	4294967295
LONG_MIN	-9223372036854775808
LONG_MAX	9223372036854775807
ULONG_MAX	18446744073709551615

D.7.13. File-I/O Examples

Example sequence of a write call, file descriptor 3, buffer is at target address 0x1234, 6 bytes should be written:

```
<- Fwrite,3,1234,6
request memory read from target
-> m1234,6
<- XXXXXX
return "6 bytes written"
-> F6
```

Example sequence of a read call, file descriptor 3, buffer is at target address 0x1234, 6 bytes should be read:

```
<- Fread,3,1234,6
request memory write to target
-> X1234,6:XXXXXX
return "6 bytes read"
-> F6
```

Example sequence of a read call, call fails on the host due to invalid file descriptor (EBADF):

```
<- Fread,3,1234,6
-> F-1,9
```

Example sequence of a read call, user presses Ctrl-C before syscall on host is called:

```
<- Fread,3,1234,6
-> F-1,4,C
<- T02
```

Example sequence of a read call, user presses Ctrl-C after syscall on host is called:

```
<- Fread,3,1234,6
-> X1234,6:XXXXXX
<- T02
```


The GDB Agent Expression Mechanism

In some applications, it is not feasible for the debugger to interrupt the program's execution long enough for the developer to learn anything helpful about its behavior. If the program's correctness depends on its real-time behavior, delays introduced by a debugger might cause the program to fail, even when the code itself is correct. It is useful to be able to observe the program's behavior without interrupting it.

Using GDB's `trace` and `collect` commands, the user can specify locations in the program, and arbitrary expressions to evaluate when those locations are reached. Later, using the `tfind` command, she can examine the values those expressions had when the program hit the trace points. The expressions may also denote objects in memory -- structures or arrays, for example -- whose values GDB should record; while visiting a particular tracepoint, the user may inspect those objects as if they were in memory at that moment. However, because GDB records these values without interacting with the user, it can do so quickly and unobtrusively, hopefully not disturbing the program's behavior.

When GDB is debugging a remote target, the GDB *agent* code running on the target computes the values of the expressions itself. To avoid having a full symbolic expression evaluator on the agent, GDB translates expressions in the source language into a simpler bytecode language, and then sends the bytecode to the agent; the agent then executes the bytecode, and records the values for GDB to retrieve later.

The bytecode language is simple; there are forty-odd opcodes, the bulk of which are the usual vocabulary of C operands (addition, subtraction, shifts, and so on) and various sizes of literals and memory reference operations. The bytecode interpreter operates strictly on machine-level values -- various sizes of integers and floating point numbers -- and requires no information about types or symbols; thus, the interpreter's internal data structures are simple, and each bytecode requires only a few native machine instructions to implement it. The interpreter is small, and strict limits on the memory and time required to evaluate an expression are easy to determine, making it suitable for use by the debugging agent in real-time applications.

E.1. General Bytecode Design

The agent represents bytecode expressions as an array of bytes. Each instruction is one byte long (thus the term *bytecode*). Some instructions are followed by operand bytes; for example, the `goto` instruction is followed by a destination for the jump.

The bytecode interpreter is a stack-based machine; most instructions pop their operands off the stack, perform some operation, and push the result back on the stack for the next instruction to consume. Each element of the stack may contain either a integer or a floating point value; these values are as many bits wide as the largest integer that can be directly manipulated in the source language. Stack elements carry no record of their type; bytecode could push a value as an integer, then pop it as a floating point value. However, GDB will not generate code which does this. In C, one might define the type of a stack element as follows:

```
union agent_val {
    LONGEST l;
    DOUBLEST d;
};
```

where `LONGEST` and `DOUBLEST` are `typedef` names for the largest integer and floating point types on the machine.

By the time the bytecode interpreter reaches the end of the expression, the value of the expression should be the only value left on the stack. For tracing applications, `trace` bytecodes in the expression will have recorded the necessary data, and the value on the stack may be discarded. For other applications, like conditional breakpoints, the value may be useful.

Separate from the stack, the interpreter has two registers:

`pc`

The address of the next bytecode to execute.

`start`

The address of the start of the bytecode expression, necessary for interpreting the `goto` and `if_goto` instructions.

Neither of these registers is directly visible to the bytecode language itself, but they are useful for defining the meanings of the bytecode operations.

There are no instructions to perform side effects on the running program, or call the program's functions; we assume that these expressions are only used for unobtrusive debugging, not for patching the running code.

Most bytecode instructions do not distinguish between the various sizes of values, and operate on full-width values; the upper bits of the values are simply ignored, since they do not usually make a difference to the value computed. The exceptions to this rule are:

memory reference instructions (`refn`)

There are distinct instructions to fetch different word sizes from memory. Once on the stack, however, the values are treated as full-size integers. They may need to be sign-extended; the `ext` instruction exists for this purpose.

the sign-extension instruction (`ext n`)

These clearly need to know which portion of their operand is to be extended to occupy the full length of the word.

If the interpreter is unable to evaluate an expression completely for some reason (a memory location is inaccessible, or a divisor is zero, for example), we say that interpretation "terminates with an error". This means that the problem is reported back to the interpreter's caller in some helpful way. In general, code using agent expressions should assume that they may attempt to divide by zero, fetch arbitrary memory locations, and misbehave in other ways.

Even complicated C expressions compile to a few bytecode instructions; for example, the expression `x + y * z` would typically produce code like the following, assuming that `x` and `y` live in registers, and `z` is a global variable holding a 32-bit `int`:

```
reg 1
reg 2
const32 address of z
ref32
ext 32
mul
add
end
```

In detail, these mean:

`reg 1`

Push the value of register 1 (presumably holding x) onto the stack.

`reg 2`

Push the value of register 2 (holding y).

`const32 address of z`

Push the address of z onto the stack.

`ref32`

Fetch a 32-bit word from the address at the top of the stack; replace the address on the stack with the value. Thus, we replace the address of z with z 's value.

`ext 32`

Sign-extend the value on the top of the stack from 32 bits to full length. This is necessary because z is a signed integer.

`mul`

Pop the top two numbers on the stack, multiply them, and push their product. Now the top of the stack contains the value of the expression $y * z$.

`add`

Pop the top two numbers, add them, and push the sum. Now the top of the stack contains the value of $x + y * z$.

`end`

Stop executing; the value left on the stack top is the value to be recorded.

E.2. Bytecode Descriptions

Each bytecode description has the following form:

`add (0x02): a b => a+b`

Pop the top two stack items, a and b , as integers; push their sum, as an integer.

In this example, `add` is the name of the bytecode, and `(0x02)` is the one-byte value used to encode the bytecode, in hexadecimal. The phrase "`a b => a+b`" shows the stack before and after the bytecode executes. Beforehand, the stack must contain at least two values, a and b ; since the top of the stack is to the right, b is on the top of the stack, and a is underneath it. After execution, the bytecode will have popped a and b from the stack, and replaced them with a single value, $a+b$. There may be other values on the stack below those shown, but the bytecode affects only those shown.

Here is another example:

`const8 (0x22) n: => n`

Push the 8-bit integer constant n on the stack, without sign extension.

In this example, the bytecode `const8` takes an operand n directly from the bytecode stream; the operand follows the `const8` bytecode itself. We write any such operands immediately after the name of the bytecode, before the colon, and describe the exact encoding of the operand in the bytecode stream in the body of the bytecode description.

For the `const8` bytecode, there are no stack items given before the `=>`; this simply means that the bytecode consumes no values from the stack. If a bytecode consumes no values, or produces no values, the list on either side of the `=>` may be empty.

If a value is written as `a`, `b`, or `n`, then the bytecode treats it as an integer. If a value is written as `addr`, then the bytecode treats it as an address.

We do not fully describe the floating point operations here; although this design can be extended in a clean way to handle floating point values, they are not of immediate interest to the customer, so we avoid describing them, to save time.

`float (0x01): =>`

Prefix for floating-point bytecodes. Not implemented yet.

`add (0x02): a b => a+b`

Pop two integers from the stack, and push their sum, as an integer.

`sub (0x03): a b => a-b`

Pop two integers from the stack, subtract the top value from the next-to-top value, and push the difference.

`mul (0x04): a b => a*b`

Pop two integers from the stack, multiply them, and push the product on the stack. Note that, when one multiplies two `n`-bit numbers yielding another `n`-bit number, it is irrelevant whether the numbers are signed or not; the results are the same.

`div_signed (0x05): a b => a/b`

Pop two signed integers from the stack; divide the next-to-top value by the top value, and push the quotient. If the divisor is zero, terminate with an error.

`div_unsigned (0x06): a b => a/b`

Pop two unsigned integers from the stack; divide the next-to-top value by the top value, and push the quotient. If the divisor is zero, terminate with an error.

`rem_signed (0x07): a b => a modulo b`

Pop two signed integers from the stack; divide the next-to-top value by the top value, and push the remainder. If the divisor is zero, terminate with an error.

`rem_unsigned (0x08): a b => a modulo b`

Pop two unsigned integers from the stack; divide the next-to-top value by the top value, and push the remainder. If the divisor is zero, terminate with an error.

`lsh (0x09): a b => a<<b`

Pop two integers from the stack; let `a` be the next-to-top value, and `b` be the top value. Shift `a` left by `b` bits, and push the result.

`rsh_signed (0x0a): a b => (signed) a>>b`

Pop two integers from the stack; let `a` be the next-to-top value, and `b` be the top value. Shift `a` right by `b` bits, inserting copies of the top bit at the high end, and push the result.

`rsh_unsigned (0x0b): a b => a>>b`

Pop two integers from the stack; let `a` be the next-to-top value, and `b` be the top value. Shift `a` right by `b` bits, inserting zero bits at the high end, and push the result.

`log_not (0x0e): a => !a`

Pop an integer from the stack; if it is zero, push the value one; otherwise, push the value zero.

`bit_and (0x0f): a b => a&b`

Pop two integers from the stack, and push their bitwise `and`.

`bit_or (0x10): a b => a|b`

Pop two integers from the stack, and push their bitwise `or`.

`bit_xor (0x11): a b => a^b`

Pop two integers from the stack, and push their bitwise exclusive-`or`.

`bit_not (0x12): a => ~a`

Pop an integer from the stack, and push its bitwise complement.

`equal (0x13): a b => a=b`

Pop two integers from the stack; if they are equal, push the value one; otherwise, push the value zero.

`less_signed (0x14): a b => a<b`

Pop two signed integers from the stack; if the next-to-top value is less than the top value, push the value one; otherwise, push the value zero.

`less_unsigned (0x15): a b => a<b`

Pop two unsigned integers from the stack; if the next-to-top value is less than the top value, push the value one; otherwise, push the value zero.

`ext (0x16) n: a => a, sign-extended from n bits`

Pop an unsigned value from the stack; treating it as an n -bit twos-complement value, extend it to full length. This means that all bits to the left of bit $n-1$ (where the least significant bit is bit 0) are set to the value of bit $n-1$. Note that n may be larger than or equal to the width of the stack elements of the bytecode engine; in this case, the bytecode should have no effect.

The number of source bits to preserve, n , is encoded as a single byte unsigned integer following the `ext` bytecode.

`zero_ext (0x2a) n: a => a, zero-extended from n bits`

Pop an unsigned value from the stack; zero all but the bottom n bits. This means that all bits to the left of bit $n-1$ (where the least significant bit is bit 0) are set to the value of bit $n-1$.

The number of source bits to preserve, n , is encoded as a single byte unsigned integer following the `zero_ext` bytecode.

`ref8 (0x17): addr => a`

`ref16 (0x18): addr => a`

`ref32 (0x19): addr => a`

`ref64 (0x1a): addr => a`

Pop an address `addr` from the stack. For bytecode `ref n` , fetch an n -bit value from `addr`, using the natural target endianness. Push the fetched value as an unsigned integer.

Note that `addr` may not be aligned in any particular way; the `ref n` bytecodes should operate correctly for any address.

If attempting to access memory at `addr` would cause a processor exception of some sort, terminate with an error.

```
ref_float (0x1b): addr => d
ref_double (0x1c): addr => d
ref_long_double (0x1d): addr => d
l_to_d (0x1e): a => d
d_to_l (0x1f): d => a
```

Not implemented yet.

```
dup (0x28): a => a a
```

Push another copy of the stack's top element.

```
swap (0x2b): a b => b a
```

Exchange the top two items on the stack.

```
pop (0x29): a =>
```

Discard the top value on the stack.

```
if_goto (0x20) offset: a =>
```

Pop an integer off the stack; if it is non-zero, branch to the given offset in the bytecode string. Otherwise, continue to the next instruction in the bytecode stream. In other words, if `a` is non-zero, set the `pc` register to `start + offset`. Thus, an offset of zero denotes the beginning of the expression.

The `offset` is stored as a sixteen-bit unsigned value, stored immediately following the `if_goto` bytecode. It is always stored most significant byte first, regardless of the target's normal endianness. The offset is not guaranteed to fall at any particular alignment within the bytecode stream; thus, on machines where fetching a 16-bit on an unaligned address raises an exception, you should fetch the offset one byte at a time.

```
goto (0x21) offset: =>
```

Branch unconditionally to `offset`; in other words, set the `pc` register to `start + offset`.

The offset is stored in the same way as for the `if_goto` bytecode.

```
const8 (0x22) n: => n
const16 (0x23) n: => n
const32 (0x24) n: => n
const64 (0x25) n: => n
```

Push the integer constant `n` on the stack, without sign extension. To produce a small negative value, push a small twos-complement value, and then sign-extend it using the `ext` bytecode.

The constant `n` is stored in the appropriate number of bytes following the `constb` bytecode. The constant `n` is always stored most significant byte first, regardless of the target's normal endianness. The constant is not guaranteed to fall at any particular alignment within the bytecode stream; thus, on machines where fetching a 16-bit on an unaligned address raises an exception, you should fetch `n` one byte at a time.

```
reg (0x26) n: => a
```

Push the value of register number `n`, without sign extension. The registers are numbered following GDB's conventions.

The register number `n` is encoded as a 16-bit unsigned integer immediately following the `reg` bytecode. It is always stored most significant byte first, regardless of the target's normal endianness.

ness. The register number is not guaranteed to fall at any particular alignment within the bytecode stream; thus, on machines where fetching a 16-bit on an unaligned address raises an exception, you should fetch the register number one byte at a time.

```
trace (0x0c): addr size =>
```

Record the contents of the `size` bytes at `addr` in a trace buffer, for later retrieval by GDB.

```
trace_quick (0x0d) size: addr => addr
```

Record the contents of the `size` bytes at `addr` in a trace buffer, for later retrieval by GDB. `size` is a single byte unsigned integer following the `trace` opcode.

This bytecode is equivalent to the sequence `dup const8 size trace`, but we provide it anyway to save space in bytecode strings.

```
trace16 (0x30) size: addr => addr
```

Identical to `trace_quick`, except that `size` is a 16-bit big-endian unsigned integer, not a single byte. This should probably have been named `trace_quick16`, for consistency.

```
end (0x27): =>
```

Stop executing bytecode; the result should be the top element of the stack. If the purpose of the expression was to compute an lvalue or a range of memory, then the next-to-top of the stack is the lvalue's address, and the top of the stack is the lvalue's size, in bytes.

E.3. Using Agent Expressions

Here is a sketch of a full non-stop debugging cycle, showing how agent expressions fit into the process.

- The user selects trace points in the program's code at which GDB should collect data.
- The user specifies expressions to evaluate at each trace point. These expressions may denote objects in memory, in which case those objects' contents are recorded as the program runs, or computed values, in which case the values themselves are recorded.
- GDB transmits the tracepoints and their associated expressions to the GDB agent, running on the debugging target.
- The agent arranges to be notified when a trace point is hit. Note that, on some systems, the target operating system is completely responsible for collecting the data; refer to Section E.5 *Tracing on Symmetric*.
- When execution on the target reaches a trace point, the agent evaluates the expressions associated with that trace point, and records the resulting values and memory ranges.
- Later, when the user selects a given trace event and inspects the objects and expression values recorded, GDB talks to the agent to retrieve recorded data as necessary to meet the user's requests. If the user asks to see an object whose contents have not been recorded, GDB reports an error.

E.4. Varying Target Capabilities

Some targets don't support floating-point, and some would rather not have to deal with `long long` operations. Also, different targets will have different stack sizes, and different bytecode buffer lengths.

Thus, GDB needs a way to ask the target about itself. We haven't worked out the details yet, but in general, GDB should be able to send the target a packet asking it to describe itself. The reply should be a packet whose length is explicit, so we can add new information to the packet in future revisions

of the agent, without confusing old versions of GDB, and it should contain a version number. It should contain at least the following information:

- whether floating point is supported
- whether `long long` is supported
- maximum acceptable size of bytecode stack
- maximum acceptable length of bytecode expressions
- which registers are actually available for collection
- whether the target supports disabled tracepoints

E.5. Tracing on Symmetrix

This section documents the API used by the GDB agent to collect data on Symmetrix systems.

Cygnus originally implemented these tracing features to help EMC Corporation debug their Symmetrix high-availability disk drives. The Symmetrix application code already includes substantial tracing facilities; the GDB agent for the Symmetrix system uses those facilities for its own data collection, via the API described here.

`DTC_RESPONSEadbg_find_memory_in_frame` (`FRAME_DEF *frame`, `char *address`, `char **buffer`, `unsigned int *size`) Search the trace frame `frame` for memory saved from `address`. If the memory is available, provide the address of the buffer holding it; otherwise, provide the address of the next saved area.

- If the memory at `address` was saved in `frame`, set `*buffer` to point to the buffer in which that memory was saved, set `*size` to the number of bytes from `address` that are saved at `*buffer`, and return `OK_TARGET_RESPONSE`. (Clearly, in this case, the function will always set `*size` to a value greater than zero.)
- If `frame` does not record any memory at `address`, set `*size` to the distance from `address` to the start of the saved region with the lowest address higher than `address`. If there is no memory saved from any higher address, set `*size` to zero. Return `NOT_FOUND_TARGET_RESPONSE`.

These two possibilities allow the caller to either retrieve the data, or walk the address space to the next saved area.

This function allows the GDB agent to map the regions of memory saved in a particular frame, and retrieve their contents efficiently.

This function also provides a clean interface between the GDB agent and the Symmetrix tracing structures, making it easier to adapt the GDB agent to future versions of the Symmetrix system, and vice versa. This function searches all data saved in `frame`, whether the data is there at the request of a bytecode expression, or because it falls in one of the format's memory ranges, or because it was saved from the top of the stack. EMC can arbitrarily change and enhance the tracing mechanism, but as long as this function works properly, all collected memory is visible to GDB.

The function itself is straightforward to implement. A single pass over the trace frame's stack area, memory ranges, and expression blocks can yield the address of the buffer (if the requested address was saved), and also note the address of the next higher range of memory, to be returned when the search fails.

As an example, suppose the trace frame `f` has saved sixteen bytes from address `0x8000` in a buffer at `0x1000`, and thirty-two bytes from address `0xc000` in a buffer at `0x1010`. Here are some sample calls, and the effect each would have:

```
adbg_find_memory_in_frame (f, (char*) 0x8000, &buffer, &size)
```

This would set `buffer` to `0x1000`, set `size` to sixteen, and return `OK_TARGET_RESPONSE`, since `f` saves sixteen bytes from `0x8000` at `0x1000`.

```
adbg_find_memory_in_frame (f, (char *) 0x8004, &buffer, &size)
```

This would set `buffer` to `0x1004`, set `size` to twelve, and return `OK_TARGET_RESPONSE`, since `f` saves the twelve bytes from `0x8004` starting four bytes into the buffer at `0x1000`. This shows that request addresses may fall in the middle of saved areas; the function should return the address and size of the remainder of the buffer.

```
adbg_find_memory_in_frame (f, (char *) 0x8100, &buffer, &size)
```

This would set `size` to `0x3f00` and return `NOT_FOUND_TARGET_RESPONSE`, since there is no memory saved in `f` from the address `0x8100`, and the next memory available is at `0x8100 + 0x3f00`, or `0xc000`. This shows that request addresses may fall outside of all saved memory ranges; the function should indicate the next saved area, if any.

```
adbg_find_memory_in_frame (f, (char *) 0x7000, &buffer, &size)
```

This would set `size` to `0x1000` and return `NOT_FOUND_TARGET_RESPONSE`, since the next saved memory is at `0x7000 + 0x1000`, or `0x8000`.

```
adbg_find_memory_in_frame (f, (char *) 0xf000, &buffer, &size)
```

This would set `size` to zero, and return `NOT_FOUND_TARGET_RESPONSE`. This shows how the function tells the caller that no further memory ranges have been saved.

As another example, here is a function which will print out the addresses of all memory saved in the trace frame `frame` on the Symmetrix INLINES console:

```
void
print_frame_addresses (FRAME_DEF *frame)
{
    char *addr;
    char *buffer;
    unsigned long size;

    addr = 0;
    for (;;)
    {
        /* Either find out how much memory we have here, or discover
           where the next saved region is. */
        if (adbg_find_memory_in_frame (frame, addr, &buffer, &size)
            == OK_TARGET_RESPONSE)
            printp ("saved %x to %x\n", addr, addr + size);
        if (size == 0)
            break;
        addr += size;
    }
}
```

Note that there is not necessarily any connection between the order in which the data is saved in the trace frame, and the order in which `adbg_find_memory_in_frame` will return those memory ranges. The code above will always print the saved memory regions in order of increasing address, while the underlying frame structure might store the data in a random order.

[[This section should cover the rest of the Symmetrix functions the stub relies upon, too.]]

E.6. Rationale

Some of the design decisions apparent above are arguable.

What about stack overflow/underflow?

GDB should be able to query the target to discover its stack size. Given that information, GDB can determine at translation time whether a given expression will overflow the stack. But this spec isn't about what kinds of error-checking GDB ought to do.

Why are you doing everything in LONGEST?

Speed isn't important, but agent code size is; using LONGEST brings in a bunch of support code to do things like division, etc. So this is a serious concern.

First, note that you don't need different bytecodes for different operand sizes. You can generate code without *knowing* how big the stack elements actually are on the target. If the target only supports 32-bit ints, and you don't send any 64-bit bytecodes, everything just works. The observation here is that the MIPS and the Alpha have only fixed-size registers, and you can still get C's semantics even though most instructions only operate on full-sized words. You just need to make sure everything is properly sign-extended at the right times. So there is no need for 32- and 64-bit variants of the bytecodes. Just implement everything using the largest size you support.

GDB should certainly check to see what sizes the target supports, so the user can get an error earlier, rather than later. But this information is not necessary for correctness.

Why don't you have > or <= operators?

I want to keep the interpreter small, and we don't need them. We can combine the `less_` opcodes with `log_not`, and swap the order of the operands, yielding all four asymmetrical comparison operators. For example, $(x \leq y)$ is $!(x > y)$, which is $!(y < x)$.

Why do you have log_not?

Why do you have ext?

Why do you have zero_ext?

These are all easily synthesized from other instructions, but I expect them to be used frequently, and they're simple, so I include them to keep bytecode strings short.

`log_not` is equivalent to `const8 0 equal`; it's used in half the relational operators.

`ext n` is equivalent to `const8 s-n lsh const8 s-n rsh_signed`, where `s` is the size of the stack elements; it follows `refm` and `reg` bytecodes when the value should be signed. See the next bulleted item.

`zero_ext n` is equivalent to `constm mask log_and`; it's used whenever we push the value of a register, because we can't assume the upper bits of the register aren't garbage.

Why not have sign-extending variants of the ref operators?

Because that would double the number of `ref` operators, and we need the `ext` bytecode anyway for accessing bitfields.

Why not have constant-address variants of the ref operators?

Because that would double the number of `ref` operators again, and `const32 address ref32` is only one byte longer.

Why do the refn operators have to support unaligned fetches?

GDB will generate bytecode that fetches multi-byte values at unaligned addresses whenever the executable's debugging information tells it to. Furthermore, GDB does not know the value the

pointer will have when GDB generates the bytecode, so it cannot determine whether a particular fetch will be aligned or not.

In particular, structure bitfields may be several bytes long, but follow no alignment rules; members of packed structures are not necessarily aligned either.

In general, there are many cases where unaligned references occur in correct C code, either at the programmer's explicit request, or at the compiler's discretion. Thus, it is simpler to make the GDB agent bytecodes work correctly in all circumstances than to make GDB guess in each case whether the compiler did the usual thing.

Why are there no side-effecting operators?

Because our current client doesn't want them? That's a cheap answer. I think the real answer is that I'm afraid of implementing function calls. We should re-visit this issue after the present contract is delivered.

Why aren't the `goto` ops PC-relative?

The interpreter has the base address around anyway for PC bounds checking, and it seemed simpler.

Why is there only one offset size for the `goto` ops?

Offsets are currently sixteen bits. I'm not happy with this situation either:

Suppose we have multiple branch ops with different offset sizes. As I generate code left-to-right, all my jumps are forward jumps (there are no loops in expressions), so I never know the target when I emit the jump opcode. Thus, I have to either always assume the largest offset size, or do jump relaxation on the code after I generate it, which seems like a big waste of time.

I can imagine a reasonable expression being longer than 256 bytes. I can't imagine one being longer than 64k. Thus, we need 16-bit offsets. This kind of reasoning is so bogus, but relaxation is pathetic.

The other approach would be to generate code right-to-left. Then I'd always know my offset size. That might be fun.

Where is the function call bytecode?

When we add side-effects, we should add this.

Why does the `reg` bytecode take a 16-bit register number?

Intel's IA-64 architecture has 128 general-purpose registers, and 128 floating-point registers, and I'm sure it has some random control registers.

Why do we need `trace` and `trace_quick`?

Because GDB needs to record all the memory contents and registers an expression touches. If the user wants to evaluate an expression $x \rightarrow y \rightarrow z$, the agent must record the values of x and $x \rightarrow y$ as well as the value of $x \rightarrow y \rightarrow z$.

Don't the `trace` bytecodes make the interpreter less general?

They do mean that the interpreter contains special-purpose code, but that doesn't mean the interpreter can only be used for that purpose. If an expression doesn't use the `trace` bytecodes, they don't get in its way.

Why doesn't `trace_quick` consume its arguments the way everything else does?

In general, you do want your operators to consume their arguments; it's consistent, and generally reduces the amount of stack rearrangement necessary. However, `trace_quick` is a kludge to save space; it only exists so we needn't write `dup const8 SIZE trace` before every memory

reference. Therefore, it's okay for it not to consume its arguments; it's meant for a specific context in which we know exactly what it should do with the stack. If we're going to have a kludge, it should be an effective kludge.

Why does `trace16` exist?

That opcode was added by the customer that contracted Cygnus for the data tracing work. I personally think it is unnecessary; objects that large will be quite rare, so it is okay to use `dup const16 size trace` in those cases.

Whatever we decide to do with `trace16`, we should at least leave opcode 0x30 reserved, to remain compatible with the customer who added it.



GNU GENERAL PUBLIC LICENSE

Version 2, June 1991

Copyright © 1989, 1991 Free Software Foundation, Inc.
59 Temple Place - Suite 330, Boston, MA 02111-1307, USA

Everyone is permitted to copy and distribute verbatim copies of this license document, but changing it is not allowed.

F.1. Preamble

The licenses for most software are designed to take away your freedom to share and change it. By contrast, the GNU General Public License is intended to guarantee your freedom to share and change free software--to make sure the software is free for all its users. This General Public License applies to most of the Free Software Foundation's software and to any other program whose authors commit to using it. (Some other Free Software Foundation software is covered by the GNU Library General Public License instead.) You can apply it to your programs, too.

When we speak of free software, we are referring to freedom, not price. Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for this service if you wish), that you receive source code or can get it if you want it, that you can change the software or use pieces of it in new free programs; and that you know you can do these things.

To protect your rights, we need to make restrictions that forbid anyone to deny you these rights or to ask you to surrender the rights. These restrictions translate to certain responsibilities for you if you distribute copies of the software, or if you modify it.

For example, if you distribute copies of such a program, whether gratis or for a fee, you must give the recipients all the rights that you have. You must make sure that they, too, receive or can get the source code. And you must show them these terms so they know their rights.

We protect your rights with two steps: (1) copyright the software, and (2) offer you this license which gives you legal permission to copy, distribute and/or modify the software.

Also, for each author's protection and ours, we want to make certain that everyone understands that there is no warranty for this free software. If the software is modified by someone else and passed on, we want its recipients to know that what they have is not the original, so that any problems introduced by others will not reflect on the original authors' reputations.

Finally, any free program is threatened constantly by software patents. We wish to avoid the danger that redistributors of a free program will individually obtain patent licenses, in effect making the program proprietary. To prevent this, we have made it clear that any patent must be licensed for everyone's free use or not licensed at all.

The precise terms and conditions for copying, distribution and modification follow.

TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

1. This License applies to any program or other work which contains a notice placed by the copyright holder saying it may be distributed under the terms of this General Public License. The "Program", below, refers to any such program or work, and a "work based on the Program"

means either the Program or any derivative work under copyright law: that is to say, a work containing the Program or a portion of it, either verbatim or with modifications and/or translated into another language. (Hereinafter, translation is included without limitation in the term "modification".) Each licensee is addressed as "you".

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running the Program is not restricted, and the output from the Program is covered only if its contents constitute a work based on the Program (independent of having been made by running the Program). Whether that is true depends on what the Program does.

2. You may copy and distribute verbatim copies of the Program's source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and give any other recipients of the Program a copy of this License along with the Program.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

3. You may modify your copy or copies of the Program or any portion of it, thus forming a work based on the Program, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:
 - a. You must cause the modified files to carry prominent notices stating that you changed the files and the date of any change.
 - b. You must cause any work that you distribute or publish, that in whole or in part contains or is derived from the Program or any part thereof, to be licensed as a whole at no charge to all third parties under the terms of this License.
 - c. If the modified program normally reads commands interactively when run, you must cause it, when started running for such interactive use in the most ordinary way, to print or display an announcement including an appropriate copyright notice and a notice that there is no warranty (or else, saying that you provide a warranty) and that users may redistribute the program under these conditions, and telling the user how to view a copy of this License. (Exception: if the Program itself is interactive but does not normally print such an announcement, your work based on the Program is not required to print an announcement.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Program, and can be reasonably considered independent and separate works in themselves, then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based on the Program, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or collective works based on the Program.

In addition, mere aggregation of another work not based on the Program with the Program (or with a work based on the Program) on a volume of a storage or distribution medium does not bring the other work under the scope of this License.

4. You may copy and distribute the Program (or a work based on it, under Section 2) in object code or executable form under the terms of Sections 1 and 2 above provided that you also do one of the following:
 - a. Accompany it with the complete corresponding machine-readable source code, which must be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,

- b. Accompany it with a written offer, valid for at least three years, to give any third party, for a charge no more than your cost of physically performing source distribution, a complete machine-readable copy of the corresponding source code, to be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,
- c. Accompany it with the information you received as to the offer to distribute corresponding source code. (This alternative is allowed only for noncommercial distribution and only if you received the program in object code or executable form with such an offer, in accord with Subsection b above.)

The source code for a work means the preferred form of the work for making modifications to it. For an executable work, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the executable. However, as a special exception, the source code distributed need not include anything that is normally distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

If distribution of executable or object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place counts as distribution of the source code, even though third parties are not compelled to copy the source along with the object code.

5. You may not copy, modify, sublicense, or distribute the Program except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense or distribute the Program is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.
6. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Program or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Program (or any work based on the Program), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Program or works based on it.
7. Each time you redistribute the Program (or any work based on the Program), the recipient automatically receives a license from the original licensor to copy, distribute or modify the Program subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties to this License.
8. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Program at all. For example, if a patent license would not permit royalty-free redistribution of the Program by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Program.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system, which is implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the

author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

9. If the distribution and/or use of the Program is restricted in certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Program under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.
10. The Free Software Foundation may publish revised and/or new versions of the General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Program specifies a version number of this License which applies to it and "any later version", you have the option of following the terms and conditions either of that version or of any later version published by the Free Software Foundation. If the Program does not specify a version number of this License, you may choose any version ever published by the Free Software Foundation.

11. If you wish to incorporate parts of the Program into other free programs whose distribution conditions are different, write to the author to ask for permission. For software which is copyrighted by the Free Software Foundation, write to the Free Software Foundation; we sometimes make exceptions for this. Our decision will be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting the sharing and reuse of software generally.

NO WARRANTY

12. BECAUSE THE PROGRAM IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.
13. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

F.2. How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest possible use to the public, the best way to achieve this is to make it free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest to attach them to the start of each source file to most effectively convey the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

```
one line to give the program's name and a brief idea of what it does.
Copyright (C) year name of author
```

```
This program is free software; you can redistribute it and/or modify
it under the terms of the GNU General Public License as published by
the Free Software Foundation; either version 2 of the License, or
(at your option) any later version.
```

```
This program is distributed in the hope that it will be useful,
but WITHOUT ANY WARRANTY; without even the implied warranty of
MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
GNU General Public License for more details.
```

```
You should have received a copy of the GNU General Public License
along with this program; if not, write to the Free Software
Foundation, Inc., 59 Temple Place - Suite 330,
Boston, MA 02111-1307, USA.
```

Also add information on how to contact you by electronic and paper mail.

If the program is interactive, make it output a short notice like this when it starts in an interactive mode:

```
Gnomovision version 69, Copyright (C) year name of author
Gnomovision comes with ABSOLUTELY NO WARRANTY; for details
type `show w`.
This is free software, and you are welcome to redistribute it
under certain conditions; type `show c` for details.
```

The hypothetical commands `show w` and `show c` should show the appropriate parts of the General Public License. Of course, the commands you use may be called something other than `show w` and `show c`; they could even be mouse-clicks or menu items--whatever suits your program.

You should also get your employer (if you work as a programmer) or your school, if any, to sign a "copyright disclaimer" for the program, if necessary. Here is a sample; alter the names:

```
Yoyodyne, Inc., hereby disclaims all copyright interest in the program
`Gnomovision' (which makes passes at compilers) written by James Hacker.
```

```
signature of Ty Coon, 1 April 1989
Ty Coon, President of Vice
```

This General Public License does not permit incorporating your program into proprietary programs. If your program is a subroutine library, you may consider it more useful to permit linking proprietary applications with the library. If this is what you want to do, use the GNU Library General Public License instead of this License.



Appendix G.

GNU Free Documentation License

Version 1.1, March 2000

Copyright (C) 2000 Free Software Foundation, Inc.
59 Temple Place, Suite 330, Boston, MA 02111-1307 USA

Everyone is permitted to copy and distribute verbatim copies of this license document, but changing it is not allowed.

1. PREAMBLE

The purpose of this License is to make a manual, textbook, or other written document "free" in the sense of freedom: to assure everyone the effective freedom to copy and redistribute it, with or without modifying it, either commercially or noncommercially. Secondly, this License preserves for the author and publisher a way to get credit for their work, while not being considered responsible for modifications made by others.

This License is a kind of "copyleft", which means that derivative works of the document must themselves be free in the same sense. It complements the GNU General Public License, which is a copyleft license designed for free software.

We have designed this License in order to use it for manuals for free software, because free software needs free documentation: a free program should come with manuals providing the same freedoms that the software does. But this License is not limited to software manuals; it can be used for any textual work, regardless of subject matter or whether it is published as a printed book. We recommend this License principally for works whose purpose is instruction or reference.

2. APPLICABILITY AND DEFINITIONS

This License applies to any manual or other work that contains a notice placed by the copyright holder saying it can be distributed under the terms of this License. The "Document", below, refers to any such manual or work. Any member of the public is a licensee, and is addressed as "you."

A "Modified Version" of the Document means any work containing the Document or a portion of it, either copied verbatim, or with modifications and/or translated into another language.

A "Secondary Section" is a named appendix or a front-matter section of the Document that deals exclusively with the relationship of the publishers or authors of the Document to the Document's overall subject (or to related matters) and contains nothing that could fall directly within that overall subject. (For example, if the Document is in part a textbook of mathematics, a Secondary Section may not explain any mathematics.) The relationship could be a matter of historical connection with the subject or with related matters, or of legal, commercial, philosophical, ethical or political position regarding them.

The "Invariant Sections" are certain Secondary Sections whose titles are designated, as being those of Invariant Sections, in the notice that says that the Document is released under this License.

The "Cover Texts" are certain short passages of text that are listed, as Front-Cover Texts or Back-Cover Texts, in the notice that says that the Document is released under this License.

A "Transparent" copy of the Document means a machine-readable copy, represented in a format whose specification is available to the general public, whose contents can be viewed and edited directly and straightforwardly with generic text editors or (for images composed of pixels) generic paint programs or (for drawings) some widely available drawing editor, and that is suitable for input to text formatters or for automatic translation to a variety of formats suitable for input to text formatters. A copy made in an otherwise Transparent file format whose markup has been designed to thwart or discourage subsequent modification by readers is not Transparent. A copy that is not "Transparent" is called "Opaque."

Examples of suitable formats for Transparent copies include plain ASCII without markup, Texinfo input format, LaTeX input format, SGML or XML using a publicly available DTD, and standard-conforming simple HTML designed for human modification. Opaque formats include PostScript, PDF, proprietary formats that can be read and edited only by proprietary word processors, SGML or XML for which the DTD and/or processing tools are not generally available, and the machine-generated HTML produced by some word processors for output purposes only.

The "Title Page" means, for a printed book, the title page itself, plus such following pages as are needed to hold, legibly, the material this License requires to appear in the title page. For works in formats which do not have any title page as such, "Title Page" means the text near the most prominent appearance of the work's title, preceding the beginning of the body of the text.

3. VERBATIM COPYING

You may copy and distribute the Document in any medium, either commercially or noncommercially, provided that this License, the copyright notices, and the license notice saying this License applies to the Document are reproduced in all copies, and that you add no other conditions whatsoever to those of this License. You may not use technical measures to obstruct or control the reading or further copying of the copies you make or distribute. However, you may accept compensation in exchange for copies. If you distribute a large enough number of copies you must also follow the conditions in section 3.

You may also lend copies, under the same conditions stated above, and you may publicly display copies.

4. COPYING IN QUANTITY

If you publish printed copies of the Document numbering more than 100, and the Document's license notice requires Cover Texts, you must enclose the copies in covers that carry, clearly and legibly, all these Cover Texts: Front-Cover Texts on the front cover, and Back-Cover Texts on the back cover. Both covers must also clearly and legibly identify you as the publisher of these copies. The front cover must present the full title with all words of the title equally prominent and visible. You may add other material on the covers in addition. Copying with changes limited to the covers, as long as they preserve the title of the Document and satisfy these conditions, can be treated as verbatim copying in other respects.

If the required texts for either cover are too voluminous to fit legibly, you should put the first ones listed (as many as fit reasonably) on the actual cover, and continue the rest onto adjacent pages.

If you publish or distribute Opaque copies of the Document numbering more than 100, you must either include a machine-readable Transparent copy along with each Opaque copy, or state in or with each Opaque copy a publicly-accessible computer-network location containing a complete Transparent copy of the Document, free of added material, which the general network-using public has access to download anonymously at no charge using public-standard network protocols. If you use the latter option, you must take reasonably prudent steps, when you begin distribution of Opaque copies in quantity, to ensure that this Transparent copy will remain thus accessible at the stated location until at least one year after the last time you distribute an Opaque copy (directly or through your agents or retailers) of that edition to the public.

It is requested, but not required, that you contact the authors of the Document well before redistributing any large number of copies, to give them a chance to provide you with an updated

version of the Document.

5. MODIFICATIONS

You may copy and distribute a Modified Version of the Document under the conditions of sections 2 and 3 above, provided that you release the Modified Version under precisely this License, with the Modified Version filling the role of the Document, thus licensing distribution and modification of the Modified Version to whoever possesses a copy of it. In addition, you must do these things in the Modified Version:

A. Use in the Title Page (and on the covers, if any) a title distinct from that of the Document, and from those of previous versions (which should, if there were any, be listed in the History section of the Document). You may use the same title as a previous version if the original publisher of that version gives permission. B. List on the Title Page, as authors, one or more persons or entities responsible for authorship of the modifications in the Modified Version, together with at least five of the principal authors of the Document (all of its principal authors, if it has less than five). C. State on the Title page the name of the publisher of the Modified Version, as the publisher. D. Preserve all the copyright notices of the Document. E. Add an appropriate copyright notice for your modifications adjacent to the other copyright notices. F. Include, immediately after the copyright notices, a license notice giving the public permission to use the Modified Version under the terms of this License, in the form shown in the Addendum below. G. Preserve in that license notice the full lists of Invariant Sections and required Cover Texts given in the Document's license notice. H. Include an unaltered copy of this License. I. Preserve the section entitled "History", and its title, and add to it an item stating at least the title, year, new authors, and publisher of the Modified Version as given on the Title Page. If there is no section entitled "History" in the Document, create one stating the title, year, authors, and publisher of the Document as given on its Title Page, then add an item describing the Modified Version as stated in the previous sentence. J. Preserve the network location, if any, given in the Document for public access to a Transparent copy of the Document, and likewise the network locations given in the Document for previous versions it was based on. These may be placed in the "History" section. You may omit a network location for a work that was published at least four years before the Document itself, or if the original publisher of the version it refers to gives permission. K. In any section entitled "Acknowledgements" or "Dedications", preserve the section's title, and preserve in the section all the substance and tone of each of the contributor acknowledgements and/or dedications given therein. L. Preserve all the Invariant Sections of the Document, unaltered in their text and in their titles. Section numbers or the equivalent are not considered part of the section titles. M. Delete any section entitled "Endorsements." Such a section may not be included in the Modified Version. N. Do not retitle any existing section as "Endorsements" or to conflict in title with any Invariant Section. If the Modified Version includes new front-matter sections or appendices that qualify as Secondary Sections and contain no material copied from the Document, you may at your option designate some or all of these sections as invariant. To do this, add their titles to the list of Invariant Sections in the Modified Version's license notice. These titles must be distinct from any other section titles.

You may add a section entitled "Endorsements", provided it contains nothing but endorsements of your Modified Version by various parties—for example, statements of peer review or that the text has been approved by an organization as the authoritative definition of a standard.

You may add a passage of up to five words as a Front-Cover Text, and a passage of up to 25 words as a Back-Cover Text, to the end of the list of Cover Texts in the Modified Version. Only one passage of Front-Cover Text and one of Back-Cover Text may be added by (or through arrangements made by) any one entity. If the Document already includes a cover text for the same cover, previously added by you or by arrangement made by the same entity you are acting on behalf of, you may not add another; but you may replace the old one, on explicit permission from the previous publisher that added the old one.

The author(s) and publisher(s) of the Document do not by this License give permission to use their names for publicity for or to assert or imply endorsement of any Modified Version.

6. COMBINING DOCUMENTS

You may combine the Document with other documents released under this License, under the terms defined in section 4 above for modified versions, provided that you include in the combination all of the Invariant Sections of all of the original documents, unmodified, and list them all as Invariant Sections of your combined work in its license notice.

The combined work need only contain one copy of this License, and multiple identical Invariant Sections may be replaced with a single copy. If there are multiple Invariant Sections with the same name but different contents, make the title of each such section unique by adding at the end of it, in parentheses, the name of the original author or publisher of that section if known, or else a unique number. Make the same adjustment to the section titles in the list of Invariant Sections in the license notice of the combined work.

In the combination, you must combine any sections entitled "History" in the various original documents, forming one section entitled "History"; likewise combine any sections entitled "Acknowledgements", and any sections entitled "Dedications." You must delete all sections entitled "Endorsements."

7. COLLECTIONS OF DOCUMENTS

You may make a collection consisting of the Document and other documents released under this License, and replace the individual copies of this License in the various documents with a single copy that is included in the collection, provided that you follow the rules of this License for verbatim copying of each of the documents in all other respects.

You may extract a single document from such a collection, and distribute it individually under this License, provided you insert a copy of this License into the extracted document, and follow this License in all other respects regarding verbatim copying of that document.

8. AGGREGATION WITH INDEPENDENT WORKS

A compilation of the Document or its derivatives with other separate and independent documents or works, in or on a volume of a storage or distribution medium, does not as a whole count as a Modified Version of the Document, provided no compilation copyright is claimed for the compilation. Such a compilation is called an "aggregate", and this License does not apply to the other self-contained works thus compiled with the Document, on account of their being thus compiled, if they are not themselves derivative works of the Document.

If the Cover Text requirement of section 3 is applicable to these copies of the Document, then if the Document is less than one quarter of the entire aggregate, the Document's Cover Texts may be placed on covers that surround only the Document within the aggregate. Otherwise they must appear on covers around the whole aggregate.

9. TRANSLATION

Translation is considered a kind of modification, so you may distribute translations of the Document under the terms of section 4. Replacing Invariant Sections with translations requires special permission from their copyright holders, but you may include translations of some or all Invariant Sections in addition to the original versions of these Invariant Sections. You may include a translation of this License provided that you also include the original English version of this License. In case of a disagreement between the translation and the original English version of this License, the original English version will prevail.

10. TERMINATION

You may not copy, modify, sublicense, or distribute the Document except as expressly provided for under this License. Any other attempt to copy, modify, sublicense or distribute the Document is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

11. FUTURE REVISIONS OF THIS LICENSE

The Free Software Foundation may publish new, revised versions of the GNU Free Documentation License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns. See <http://www.gnu.org/copyleft/>.

Each version of the License is given a distinguishing version number. If the Document specifies that a particular numbered version of this License "or any later version" applies to it, you have the option of following the terms and conditions either of that specified version or of any later version that has been published (not as a draft) by the Free Software Foundation. If the Document does not specify a version number of this License, you may choose any version ever published (not as a draft) by the Free Software Foundation.

G.1. ADDENDUM: How to use this License for your documents

To use this License in a document you have written, include a copy of the License in the document and put the following copyright and license notices just after the title page:

```
Copyright (C)  year  your name.
Permission is granted to copy, distribute and/or modify this document
under the terms of the GNU Free Documentation License, Version 1.1
or any later version published by the Free Software Foundation;
with the Invariant Sections being list their titles, with the
Front-Cover Texts being list, and with the Back-Cover Texts being list.
A copy of the license is included in the section entitled "GNU
Free Documentation License."
```

If you have no Invariant Sections, write "with no Invariant Sections" instead of saying which ones are invariant. If you have no Front-Cover Texts, write "no Front-Cover Texts" instead of "Front-Cover Texts being list"; likewise for Back-Cover Texts.

If your document contains nontrivial examples of program code, we recommend releasing these examples in parallel under your choice of free software license, such as the GNU General Public License, to permit their use in free software.

Index

! packet, (refer to Section D.2 *Packets*)
"No symbol "foo" in current context", (refer to Section 10.2 *Program variables*)
(a comment), (refer to Section 5.1 *Command syntax*)
in Modula-2, (refer to Section 14.4.3.8 *gdb and Modula-2*)
\$, (refer to Section 10.8 *Value history*)
\$\$, (refer to Section 10.8 *Value history*)
\$_ and info breakpoints, (refer to Section 7.1.1 *Setting breakpoints*)
\$_ and info line, (refer to Section 9.5 *Source and machine code*)
\$_, \$__, and value history, (refer to Section 10.5 *Examining memory*)
\$_, convenience variable, (refer to Section 10.9 *Convenience variables*)
\$__ , convenience variable, (refer to Section 10.9 *Convenience variables*)
\$_exitcode, convenience variable, (refer to Section 10.9 *Convenience variables*)
\$bpnum, convenience variable, (refer to Section 7.1.1 *Setting breakpoints*)
\$cdir, convenience variable, (refer to Section 9.4 *Specifying source directories*)
\$cwd, convenience variable, (refer to Section 9.4 *Specifying source directories*)
\$stnum, (refer to Section 12.1.1 *Create and Delete Tracepoints*)
\$trace_file, (refer to Section 12.3 *Convenience Variables for Tracepoints*)
\$trace_frame, (refer to Section 12.3 *Convenience Variables for Tracepoints*)
\$trace_func, (refer to Section 12.3 *Convenience Variables for Tracepoints*)
\$trace_line, (refer to Section 12.3 *Convenience Variables for Tracepoints*)
\$tracepoint, (refer to Section 12.3 *Convenience Variables for Tracepoints*)
-annotate, (refer to Section 4.1.2 *Choosing modes*)
-args, (refer to Section 4.1.2 *Choosing modes*)
-async, (refer to Section 4.1.2 *Choosing modes*)
-b, (refer to Section 4.1.2 *Choosing modes*)
-batch, (refer to Section 4.1.2 *Choosing modes*)
-baud, (refer to Section 4.1.2 *Choosing modes*)
-break-after, (refer to Section 26.8 *gdb/mi Breakpoint table commands*)
-break-condition, (refer to Section 26.8 *gdb/mi Breakpoint table commands*)
-break-delete, (refer to Section 26.8 *gdb/mi Breakpoint table commands*)
-break-disable, (refer to Section 26.8 *gdb/mi Breakpoint table commands*)

-break-enable, (refer to Section 26.8 *gdb/mi Breakpoint table commands*)
-break-info, (refer to Section 26.8 *gdb/mi Breakpoint table commands*)
-break-insert, (refer to Section 26.8 *gdb/mi Breakpoint table commands*)
-break-list, (refer to Section 26.8 *gdb/mi Breakpoint table commands*)
-break-watch, (refer to Section 26.8 *gdb/mi Breakpoint table commands*)
-c, (refer to Section 4.1.1 *Choosing files*)
-cd, (refer to Section 4.1.2 *Choosing modes*)
-command, (refer to Section 4.1.1 *Choosing files*)
-core, (refer to Section 4.1.1 *Choosing files*)
-d, (refer to Section 4.1.1 *Choosing files*)
-data-disassemble, (refer to Section 26.9 *gdb/mi Data Manipulation*)
-data-evaluate-expression, (refer to Section 26.9 *gdb/mi Data Manipulation*)
-data-list-changed-registers, (refer to Section 26.9 *gdb/mi Data Manipulation*)
-data-list-register-names, (refer to Section 26.9 *gdb/mi Data Manipulation*)
-data-list-register-values, (refer to Section 26.9 *gdb/mi Data Manipulation*)
-data-read-memory, (refer to Section 26.9 *gdb/mi Data Manipulation*)
-directory, (refer to Section 4.1.1 *Choosing files*)
-display-delete, (refer to Section 26.9 *gdb/mi Data Manipulation*)
-display-disable, (refer to Section 26.9 *gdb/mi Data Manipulation*)
-display-enable, (refer to Section 26.9 *gdb/mi Data Manipulation*)
-display-insert, (refer to Section 26.9 *gdb/mi Data Manipulation*)
-display-list, (refer to Section 26.9 *gdb/mi Data Manipulation*)
-e, (refer to Section 4.1.1 *Choosing files*)
-environment-cd, (refer to Section 26.9 *gdb/mi Data Manipulation*)
-environment-directory, (refer to Section 26.9 *gdb/mi Data Manipulation*)
-environment-path, (refer to Section 26.9 *gdb/mi Data Manipulation*)
-environment-pwd, (refer to Section 26.9 *gdb/mi Data Manipulation*)
-epoch, (refer to Section 4.1.2 *Choosing modes*)
-exec, (refer to Section 4.1.1 *Choosing files*)
-exec-abort, (refer to Section 26.10 *gdb/mi Program control*)
-exec-arguments, (refer to Section 26.10 *gdb/mi Program control*)
-exec-continue, (refer to Section 26.10 *gdb/mi Program control*)

- exec-finish, (refer to Section 26.10 *gdb/mi Program control*)
- exec-interrupt, (refer to Section 26.10 *gdb/mi Program control*)
- exec-next, (refer to Section 26.10 *gdb/mi Program control*)
- exec-next-instruction, (refer to Section 26.10 *gdb/mi Program control*)
- exec-return, (refer to Section 26.10 *gdb/mi Program control*)
- exec-run, (refer to Section 26.10 *gdb/mi Program control*)
- exec-show-arguments, (refer to Section 26.10 *gdb/mi Program control*)
- exec-step, (refer to Section 26.10 *gdb/mi Program control*)
- exec-step-instruction, (refer to Section 26.10 *gdb/mi Program control*)
- exec-until, (refer to Section 26.10 *gdb/mi Program control*)
- f, (refer to Section 4.1.2 *Choosing modes*)
- file-exec-and-symbols, (refer to Section 26.10 *gdb/mi Program control*)
- file-exec-file, (refer to Section 26.10 *gdb/mi Program control*)
- file-list-exec-sections, (refer to Section 26.10 *gdb/mi Program control*)
- file-list-exec-source-file, (refer to Section 26.10 *gdb/mi Program control*)
- file-list-exec-source-files, (refer to Section 26.10 *gdb/mi Program control*)
- file-list-shared-libraries, (refer to Section 26.10 *gdb/mi Program control*)
- file-list-symbol-files, (refer to Section 26.10 *gdb/mi Program control*)
- file-symbol-file, (refer to Section 26.10 *gdb/mi Program control*)
- fullname, (refer to Section 4.1.2 *Choosing modes*)
- gdb-exit, (refer to Section 26.12 *Miscellaneous gdb commands in gdb/mi*)
- gdb-set, (refer to Section 26.12 *Miscellaneous gdb commands in gdb/mi*)
- gdb-show, (refer to Section 26.12 *Miscellaneous gdb commands in gdb/mi*)
- gdb-version, (refer to Section 26.12 *Miscellaneous gdb commands in gdb/mi*)
- interpreter, (refer to Section 4.1.2 *Choosing modes*)
- interpreter-exec, (refer to Section 26.12 *Miscellaneous gdb commands in gdb/mi*)
- m, (refer to Section 4.1.1 *Choosing files*)
- mapped, (refer to Section 4.1.1 *Choosing files*)
- n, (refer to Section 4.1.2 *Choosing modes*)
- noasync, (refer to Section 4.1.2 *Choosing modes*)
- nowindows, (refer to Section 4.1.2 *Choosing modes*)
- nw, (refer to Section 4.1.2 *Choosing modes*)
- nx, (refer to Section 4.1.2 *Choosing modes*)
- p, (refer to Section 4.1.1 *Choosing files*)
- pid, (refer to Section 4.1.1 *Choosing files*)
- q, (refer to Section 4.1.2 *Choosing modes*)
- quiet, (refer to Section 4.1.2 *Choosing modes*)
- r, (refer to Section 4.1.1 *Choosing files*)
- readnow, (refer to Section 4.1.1 *Choosing files*)
- s, (refer to Section 4.1.1 *Choosing files*)
- se, (refer to Section 4.1.1 *Choosing files*)
- silent, (refer to Section 4.1.2 *Choosing modes*)
- stack-info-depth, (refer to Section 26.13 *gdb/mi Stack Manipulation Commands*)
- stack-info-frame, (refer to Section 26.13 *gdb/mi Stack Manipulation Commands*)
- stack-list-arguments, (refer to Section 26.13 *gdb/mi Stack Manipulation Commands*)
- stack-list-frames, (refer to Section 26.13 *gdb/mi Stack Manipulation Commands*)
- stack-list-locals, (refer to Section 26.13 *gdb/mi Stack Manipulation Commands*)
- stack-select-frame, (refer to Section 26.13 *gdb/mi Stack Manipulation Commands*)
- statistics, (refer to Section 4.1.2 *Choosing modes*)
- symbol-info-address, (refer to Section 26.14 *gdb/mi Symbol Query Commands*)
- symbol-info-file, (refer to Section 26.14 *gdb/mi Symbol Query Commands*)
- symbol-info-function, (refer to Section 26.14 *gdb/mi Symbol Query Commands*)
- symbol-info-line, (refer to Section 26.14 *gdb/mi Symbol Query Commands*)
- symbol-info-symbol, (refer to Section 26.14 *gdb/mi Symbol Query Commands*)
- symbol-list-functions, (refer to Section 26.14 *gdb/mi Symbol Query Commands*)
- symbol-list-lines, (refer to Section 26.14 *gdb/mi Symbol Query Commands*)
- symbol-list-types, (refer to Section 26.14 *gdb/mi Symbol Query Commands*)
- symbol-list-variables, (refer to Section 26.14 *gdb/mi Symbol Query Commands*)
- symbol-locate, (refer to Section 26.14 *gdb/mi Symbol Query Commands*)
- symbol-type, (refer to Section 26.14 *gdb/mi Symbol Query Commands*)
- symbols, (refer to Section 4.1.1 *Choosing files*)
- t, (refer to Section 4.1.2 *Choosing modes*)
- target-attach, (refer to Section 26.15 *gdb/mi Target Manipulation Commands*)
- target-compare-sections, (refer to Section 26.15 *gdb/mi Target Manipulation Commands*)
- target-detach, (refer to Section 26.15 *gdb/mi Target Manipulation Commands*)
- target-disconnect, (refer to Section 26.15 *gdb/mi Target Manipulation Commands*)

- target-download, (refer to Section 26.15 *gdb/mi Target Manipulation Commands*)
- target-exec-status, (refer to Section 26.15 *gdb/mi Target Manipulation Commands*)
- target-list-available-targets, (refer to Section 26.15 *gdb/mi Target Manipulation Commands*)
- target-list-current-targets, (refer to Section 26.15 *gdb/mi Target Manipulation Commands*)
- target-list-parameters, (refer to Section 26.15 *gdb/mi Target Manipulation Commands*)
- target-select, (refer to Section 26.15 *gdb/mi Target Manipulation Commands*)
- thread-info, (refer to Section 26.16 *gdb/mi Thread Commands*)
- thread-list-all-threads, (refer to Section 26.16 *gdb/mi Thread Commands*)
- thread-list-ids, (refer to Section 26.16 *gdb/mi Thread Commands*)
- thread-select, (refer to Section 26.16 *gdb/mi Thread Commands*)
- tty, (refer to Section 4.1.2 *Choosing modes*)
- tui, (refer to Section 4.1.2 *Choosing modes*)
- var-assign, (refer to Section 26.18 *gdb/mi Variable Objects*)
- var-create, (refer to Section 26.18 *gdb/mi Variable Objects*)
- var-delete, (refer to Section 26.18 *gdb/mi Variable Objects*)
- var-evaluate-expression, (refer to Section 26.18 *gdb/mi Variable Objects*)
- var-info-expression, (refer to Section 26.18 *gdb/mi Variable Objects*)
- var-info-num-children, (refer to Section 26.18 *gdb/mi Variable Objects*)
- var-info-type, (refer to Section 26.18 *gdb/mi Variable Objects*)
- var-list-children, (refer to Section 26.18 *gdb/mi Variable Objects*)
- var-set-format, (refer to Section 26.18 *gdb/mi Variable Objects*)
- var-show-attributes, (refer to Section 26.18 *gdb/mi Variable Objects*)
- var-show-format, (refer to Section 26.18 *gdb/mi Variable Objects*)
- var-update, (refer to Section 26.18 *gdb/mi Variable Objects*)
- version, (refer to Section 4.1.2 *Choosing modes*)
- w, (refer to Section 4.1.2 *Choosing modes*)
- windows, (refer to Section 4.1.2 *Choosing modes*)
- write, (refer to Section 4.1.2 *Choosing modes*)
- x, (refer to Section 4.1.1 *Choosing files*)
- ., Modula-2 scope operator, (refer to Section 14.4.3.7 *The scope operators : : and .*)
- .debug subdirectories, (refer to Section 17.2 *Debugging Information in Separate Files*)
- .esgdbinit, (refer to Section 22.3 *Command files*)

- .gdbinit, (refer to Section 22.3 *Command files*)
- .gnu_debuglink sections, (refer to Section 17.2 *Debugging Information in Separate Files*)
- .o files, reading symbols from, (refer to Section 17.1 *Commands to specify files*)
- .os68gdbinit, (refer to Section 22.3 *Command files*)
- .vxgdbinit, (refer to Section 22.3 *Command files*)
- /proc, (refer to Section 20.1.2 *SVR4 process information*)
- ? packet, (refer to Section D.2 *Packets*)
- @, referencing memory as an array, (refer to Section 10.3 *Artificial arrays*)
- ^done, (refer to Section 26.6.1 *gdb/mi Result Records*)
- ^error, (refer to Section 26.6.1 *gdb/mi Result Records*)
- ^running, (refer to Section 26.6.1 *gdb/mi Result Records*)
- A packet, (refer to Section D.2 *Packets*)

A

- abbreviation, (refer to Section 5.1 *Command syntax*)
- acknowledgment, for gdb remote, (refer to Section D.1 *Overview*)
- actions, (refer to Section 12.1.4 *Tracepoint Action Lists*)
- active targets, (refer to Section 18.1 *Active targets*)
- adb_find_memory_in_frame, (refer to Section E.5 *Tracing on Symmetrix*)
- add-shared-symbol-file, (refer to Section 17.1 *Commands to specify files*)
- add-symbol-file, (refer to Section 17.1 *Commands to specify files*)
- address of a symbol, (refer to Chapter 15 *Examining the Symbol Table*)
- advance location, (refer to Section 7.2 *Continuing and stepping*)
- Alpha stack, (refer to Section 20.4.3 *MIPS*)
- AMD 29K register stack, (refer to Section 20.4.1 *A29K*)
- annotations, (refer to Section 27.1 *What is an Annotation?*)
- annotations for breakpoints, (refer to Section 27.8 *Information on Breakpoints*)
- annotations for display, (refer to Section 27.5 *Displays*)
- annotations for errors, warnings and interrupts, (refer to Section 27.7 *Errors*)
- annotations for frames, (refer to Section 27.4 *Frames*)
- annotations for invalidation messages, (refer to Section 27.9 *Invalidation Notices*)
- annotations for prompts, (refer to Section 27.6 *Annotation for gdb Input*)
- annotations for running programs, (refer to Section 27.10 *Running the Program*)
- annotations for source display, (refer to Section 27.11 *Displaying Source*)

annotations for values, (refer to Section 27.3 *Values*
 append, (refer to Section 10.14 *Copy between memory
 and a file*
 append data to a file, (refer to Section 10.14 *Copy be-
 tween memory and a file*
 apropos, (refer to Section 5.3 *Getting help*
 arg-begin, (refer to Section 27.3 *Values*
 arg-end, (refer to Section 27.3 *Values*
 arg-name-end, (refer to Section 27.3 *Values*
 arg-value, (refer to Section 27.3 *Values*
 arguments (to your program), (refer to Section 6.3
Your program's arguments
 array-section-end, (refer to Section 27.3 *Values*
 artificial array, (refer to Section 10.3 *Artificial arrays*
 ASCII character set, (refer to Section 10.15 *Character
 Sets*
 assembly instructions, (refer to Section 9.5 *Source
 and machine code*
 assignment, (refer to Section 16.1 *Assignment to vari-
 ables*
 async output in gdb/mi, (refer to Section 26.4.2
gdb/mi Output Syntax
 AT&T disassembly flavor, (refer to Section 9.5 *Source
 and machine code*
 attach, (refer to Section 6.7 *Debugging an already-
 running process*
 automatic display, (refer to Section 10.6 *Automatic
 display*
 automatic overlay debugging, (refer to Section 13.3
Automatic Overlay Debugging
 automatic thread selection, (refer to Section 6.9 *De-
 bugging programs with multiple threads*
 atwatch, (refer to Section 7.1.2 *Setting watchpoints*

B

b (break), (refer to Section 7.1.1 *Setting breakpoints*
 B packet, (refer to Section D.2 *Packets*
 b packet, (refer to Section D.2 *Packets*
 backtrace, (refer to Section 8.2 *Backtraces*
 backtraces, (refer to Section 8.2 *Backtraces*
 bell-style, (refer to Section 29.3.1 *Readline Init File
 Syntax*
 break, (refer to Section 7.1.1 *Setting breakpoints*
 break... thread `threadno`, (refer to Section 7.4 *Stop-
 ping and starting multi-thread programs*
 break in overloaded functions, (refer to Section
 14.4.1.7 *gdb features for C++*
 break, and Objective-C, (refer to Section 14.4.2.1
Method Names in Commands
 breakpoint, (refer to Section 27.10 *Running the Pro-
 gram*
 breakpoint commands, (refer to Section 7.1.7 *Break-
 point command lists*

breakpoint commands for gdb/mi, (refer to Section
 26.8 *gdb/mi Breakpoint table commands*
 breakpoint conditions, (refer to Section 7.1.6 *Break
 conditions*
 breakpoint numbers, (refer to Section 7.1 *Breakpoints,
 watchpoints, and catchpoints*
 breakpoint on events, (refer to Section 7.1 *Break-
 points, watchpoints, and catchpoints*
 breakpoint on memory address, (refer to Section 7.1
Breakpoints, watchpoints, and catchpoints
 breakpoint on variable modification, (refer to Section
 7.1 *Breakpoints, watchpoints, and catchpoints*
 breakpoint ranges, (refer to Section 7.1 *Breakpoints,
 watchpoints, and catchpoints*
 breakpoint subroutine, remote, (refer to Section
 19.5.1 *What the stub can do for you*
 breakpoints, (refer to Section 7.1 *Breakpoints, watch-
 points, and catchpoints*
 breakpoints and threads, (refer to Section 7.4 *Stopping
 and starting multi-thread programs*
 breakpoints in overlays, (refer to Section 13.2 *Overlay
 Commands*
 breakpoints-headers, (refer to Section 27.8 *Informa-
 tion on Breakpoints*
 breakpoints-invalid, (refer to Section 27.9 *Invalida-
 tion Notices*
 breakpoints-table, (refer to Section 27.8 *Information
 on Breakpoints*
 breakpoints-table-end, (refer to Section 27.8 *Informa-
 tion on Breakpoints*
 bt (backtrace), (refer to Section 8.2 *Backtraces*
 bug criteria, (refer to Section 28.1 *Have you found a
 bug?*
 bug reports, (refer to Section 28.2 *How to report bugs*
 bugs in gdb, (refer to Chapter 28 *Reporting Bugs in
 gdb*

C

c (continue), (refer to Section 7.2 *Continuing and
 stepping*
 c (SingleKey TUI key), (refer to Section 24.3 *TUI Sin-
 gle Key Mode*
 C and C++, (refer to Section 14.4.1 *C and C++*
 C and C++ checks, (refer to Section 14.4.1.5 *C and
 C++ type and range checks*
 C and C++ constants, (refer to Section 14.4.1.2 *C and
 C++ constants*
 C and C++ defaults, (refer to Section 14.4.1.4 *C and
 C++ defaults*
 C and C++ operators, (refer to Section 14.4.1.1 *C and
 C++ operators*
 c packet, (refer to Section D.2 *Packets*
 c packet, (refer to Section D.2 *Packets*
 C++, (refer to Section 14.4.1 *C and C++*

- C++ compilers, (refer to Section 14.4.1.3 *C++ expressions*)
- C++ exception handling, (refer to Section 14.4.1.7 *gdb features for C++*)
- C++ scope resolution, (refer to Section 10.2 *Program variables*)
- C++ symbol decoding style, (refer to Section 10.7 *Print settings*)
- C+ symbol display, (refer to Section 14.4.1.7 *gdb features for C++*)
- C-L, (refer to Section 24.2 *TUI Key Bindings*)
- C-o (operate-and-get-next), (refer to Section 5.1 *Command syntax*)
- C-x 1, (refer to Section 24.2 *TUI Key Bindings*)
- C-x 2, (refer to Section 24.2 *TUI Key Bindings*)
- C-x a, (refer to Section 24.2 *TUI Key Bindings*)
- C-x A, (refer to Section 24.2 *TUI Key Bindings*)
- C-x C-a, (refer to Section 24.2 *TUI Key Bindings*)
- C-x s, (refer to Section 24.2 *TUI Key Bindings*)
- call, (refer to Section 16.5 *Calling program functions*)
- call overloaded functions, (refer to Section 14.4.1.3 *C++ expressions*)
- call stack, (refer to Chapter 8 *Examining the Stack*)
- calling functions, (refer to Section 16.5 *Calling program functions*)
- calling make, (refer to Section 4.3 *Shell commands*)
- casts, to view memory, (refer to Section 10.1 *Expressions*)
- catch, (refer to Section 7.1.3 *Setting catchpoints*)
- catch catch, (refer to Section 7.1.3 *Setting catchpoints*)
- catch exceptions, list active handlers, (refer to Section 8.4 *Information about a frame*)
- catch exec, (refer to Section 7.1.3 *Setting catchpoints*)
- catch fork, (refer to Section 7.1.3 *Setting catchpoints*)
- catch load, (refer to Section 7.1.3 *Setting catchpoints*)
- catch throw, (refer to Section 7.1.3 *Setting catchpoints*)
- catch unload, (refer to Section 7.1.3 *Setting catchpoints*)
- catch vfork, (refer to Section 7.1.3 *Setting catchpoints*)
- catchpoints, (refer to Section 7.1 *Breakpoints, watchpoints, and catchpoints*)
- catchpoints, setting, (refer to Section 7.1.3 *Setting catchpoints*)
- cd, (refer to Section 6.5 *Your program's working directory*)
- cdir, (refer to Section 9.4 *Specifying source directories*)
- character sets, (refer to Section 10.15 *Character Sets*)
- charset, (refer to Section 10.15 *Character Sets*)
- checks, range, (refer to Section 14.3.1 *An overview of type checking*)
- checks, type, (refer to Section 14.3 *Type and range checking*)
- checksum, for `gdb` remote, (refer to Section D.1 *Overview*)
- choosing target byte order, (refer to Section 18.3 *Choosing target byte order*)
- clear, (refer to Section 7.1.4 *Deleting breakpoints*)
- clear, and Objective-C, (refer to Section 14.4.2.1 *Method Names in Commands*)
- clearing breakpoints, watchpoints, catchpoints, (refer to Section 7.1.4 *Deleting breakpoints*)
- close, file-i/o system call, (refer to Section D.7.10.2 *close*)
- collect (tracepoints), (refer to Section 12.1.4 *Tracepoint Action Lists*)
- collected data discarded, (refer to Section 12.1.6 *Starting and Stopping Trace Experiment*)
- colon, doubled as scope operator, (refer to Section 14.4.3.7 *The scope operators :: and .*)
- colon-colon, context for variables/functions, (refer to Section 10.2 *Program variables*)
- command editing, (refer to Section 29.2.1 *Readline Bare Essentials*)
- command files, (refer to Section 22.3 *Command files*)
- command hooks, (refer to Section 22.2 *User-defined command hooks*)
- command interpreters, (refer to Chapter 23 *Command Interpreters*)
- command line editing, (refer to Section 21.2 *Command editing*)
- commands, (refer to Section 7.1.7 *Breakpoint command lists*)
- commands, (refer to Section 27.6 *Annotation for gdb Input*)
- commands for C++, (refer to Section 14.4.1.7 *gdb features for C++*)
- commands to STDBUG (ST2000), (refer to Section 20.3.13 *Tandem ST2000*)
- comment, (refer to Section 5.1 *Command syntax*)
- comment-begin, (refer to Section 29.3.1 *Readline Init File Syntax*)
- compatibility, `gdb/mi` and CLI, (refer to Section 26.5 *gdb/mi Compatibility with CLI*)
- compilation directory, (refer to Section 9.4 *Specifying source directories*)
- compiling, on Sparclet, (refer to Section 20.3.11 *Tsquare Sparclet*)
- complete, (refer to Section 5.3 *Getting help*)
- completion, (refer to Section 5.2 *Command completion*)
- completion of quoted strings, (refer to Section 5.2 *Command completion*)
- completion-query-items, (refer to Section 29.3.1 *Readline Init File Syntax*)
- condition, (refer to Section 7.1.6 *Break conditions*)
- conditional breakpoints, (refer to Section 7.1.6 *Break conditions*)
- configuring `gdb`, (refer to Appendix B *Installing gdb*)
- configuring `gdb`, and source tree subdirectories, (refer to Appendix B *Installing gdb*)
- confirmation, (refer to Section 21.7 *Optional warnings and messages*)

connect (to STDBG), (refer to Section 20.3.13 *Tandem ST2000*)
 console i/o as part of file-i/o, (refer to Section D.7.7 *Console I/O*)
 console interpreter, (refer to Chapter 23 *Command Interpreters*)
 console output in gdb/mi, (refer to Section 26.4.2 *gdb/mi Output Syntax*)
 constants, in file-i/o protocol, (refer to Section D.7.12 *Constants*)
 continue, (refer to Section 7.2 *Continuing and stepping*)
 continuing, (refer to Section 7.2 *Continuing and stepping*)
 continuing threads, (refer to Section 7.4 *Stopping and starting multi-thread programs*)
 control C, and remote debugging, (refer to Section 19.5.2 *What you must do for the stub*)
 controlling terminal, (refer to Section 6.6 *Your program's input and output*)
 convenience variables, (refer to Section 10.9 *Convenience variables*)
 convenience variables for tracepoints, (refer to Section 12.3 *Convenience Variables for Tracepoints*)
 convert-meta, (refer to Section 29.3.1 *Readline Init File Syntax*)
 core, (refer to Section 17.1 *Commands to specify files*)
 core dump file, (refer to Section 17.1 *Commands to specify files*)
 core-file, (refer to Section 17.1 *Commands to specify files*)
 crash of debugger, (refer to Section 28.1 *Have you found a bug?*)
 ctrl-c message, in file-i/o protocol, (refer to Section D.7.6 *The Ctrl-C message*)
 current directory, (refer to Section 9.4 *Specifying source directories*)
 current stack frame, (refer to Section 8.1 *Stack frames*)
 current thread, (refer to Section 6.9 *Debugging programs with multiple threads*)
 cwd, (refer to Section 9.4 *Specifying source directories*)
 Cygwin-specific commands, (refer to Section 20.1.4 *Features for Debugging MS Windows PE executables*)

D

d (delete), (refer to Section 7.1.4 *Deleting breakpoints*)
 d (SingleKey TUI key), (refer to Section 24.3 *TUI Single Key Mode*)
 D packet, (refer to Section D.2 *Packets*)
 d packet, (refer to Section D.2 *Packets*)
 data manipulation, in gdb/mi, (refer to Section 26.9 *gdb/mi Data Manipulation*)
 debug formats and C++, (refer to Section 14.4.1.3 *C++expressions*)
 debug links, (refer to Section 17.2 *Debugging Information in Separate Files*)
 debugger crash, (refer to Section 28.1 *Have you found a bug?*)
 debugging C++ programs, (refer to Section 14.4.1.3 *C++expressions*)
 debugging information directory, global, (refer to Section 17.2 *Debugging Information in Separate Files*)
 debugging information in separate files, (refer to Section 17.2 *Debugging Information in Separate Files*)
 debugging optimized code, (refer to Section 6.1 *Compiling for debugging*)
 debugging stub, example, (refer to Section 19.5 *Implementing a remote stub*)
 debugging target, (refer to Chapter 18 *Specifying a Debugging Target*)
 define, (refer to Section 22.1 *User-defined commands*)
 defining macros interactively, (refer to Chapter 11 *C Preprocessor Macros*)
 definition, showing a macro's, (refer to Chapter 11 *C Preprocessor Macros*)
 delete, (refer to Section 7.1.4 *Deleting breakpoints*)
 delete breakpoints, (refer to Section 7.1.4 *Deleting breakpoints*)
 delete display, (refer to Section 10.6 *Automatic display*)
 delete mem, (refer to Section 10.13 *Memory region attributes*)
 delete tracepoint, (refer to Section 12.1.1 *Create and Delete Tracepoints*)
 deleting breakpoints, watchpoints, catchpoints, (refer to Section 7.1.4 *Deleting breakpoints*)
 demangling, (refer to Section 10.7 *Print settings*)
 descriptor tables display, (refer to Section 20.1.3 *Features for Debugging djgpp Programs*)
 detach, (refer to Section 6.7 *Debugging an already-running process*)
 detach (remote), (refer to Section 19.1 *Connecting to a remote target*)
 device, (refer to Section 20.3.2.1 *Connecting to Hitachi boards*)
 dir, (refer to Section 9.4 *Specifying source directories*)
 direct memory access (DMA) on MS-DOS, (refer to Section 20.1.3 *Features for Debugging djgpp Programs*)
 directories for source files, (refer to Section 9.4 *Specifying source directories*)
 directory, (refer to Section 9.4 *Specifying source directories*)
 directory, compilation, (refer to Section 9.4 *Specifying source directories*)
 directory, current, (refer to Section 9.4 *Specifying source directories*)

dis (disable), (refer to Section 7.1.5 *Disabling breakpoints*)
 disable, (refer to Section 7.1.5 *Disabling breakpoints*)
 disable breakpoints, (refer to Section 7.1.5 *Disabling breakpoints*)
 disable display, (refer to Section 10.6 *Automatic display*)
 disable mem, (refer to Section 10.13 *Memory region attributes*)
 disable tracepoint, (refer to Section 12.1.2 *Enable and Disable Tracepoints*)
 disable-completion, (refer to Section 29.3.1 *Readline Init File Syntax*)
 disassemble, (refer to Section 9.5 *Source and machine code*)
 disconnect, (refer to Section 19.1 *Connecting to a remote target*)
 display, (refer to Section 10.6 *Automatic display*)
 display of expressions, (refer to Section 10.6 *Automatic display*)
 display-begin, (refer to Section 27.5 *Displays*)
 display-end, (refer to Section 27.5 *Displays*)
 display-expression, (refer to Section 27.5 *Displays*)
 display-expression-end, (refer to Section 27.5 *Displays*)
 display-format, (refer to Section 27.5 *Displays*)
 display-number-end, (refer to Section 27.5 *Displays*)
 display-value, (refer to Section 27.5 *Displays*)
 djgpp debugging, (refer to Section 20.1.3 *Features for Debugging djgpp Programs*)
 dll-symbols, (refer to Section 20.1.4 *Features for Debugging MS Windows PE executables*)
 DLLs with no debugging symbols, (refer to Section 20.1.4.1 *Support for DLLs without debugging symbols*)
 do (down), (refer to Section 8.3 *Selecting a frame*)
 document, (refer to Section 22.1 *User-defined commands*)
 documentation, (refer to Appendix A *Formatting Documentation*)
 Down, (refer to Section 24.2 *TUI Key Bindings*)
 down, (refer to Section 8.3 *Selecting a frame*)
 down-silently, (refer to Section 8.3 *Selecting a frame*)
 download to H8/300 or H8/500, (refer to Section 20.3.2 *Hitachi H8/300*)
 download to Hitachi SH, (refer to Section 20.3.2 *Hitachi H8/300*)
 download to Sparclet, (refer to Section 20.3.11.3 *Sparclet download*)
 download to VxWorks, (refer to Section 20.2.1.2 *VxWorks download*)
 dump, (refer to Section 10.14 *Copy between memory and a file*)
 dump all data collected at tracepoint, (refer to Section 12.2.2 *tcdump*)
 dump data to a file, (refer to Section 10.14 *Copy between memory and a file*)

dump/restore files, (refer to Section 10.14 *Copy between memory and a file*)
 dynamic linking, (refer to Section 17.1 *Commands to specify files*)

E

e (edit), (refer to Section 9.2 *Editing source files*)
 EBCDIC character set, (refer to Section 10.15 *Character Sets*)
 echo, (refer to Section 22.4 *Commands for controlled output*)
 edit, (refer to Section 9.2 *Editing source files*)
 editing, (refer to Section 21.2 *Command editing*)
 editing command lines, (refer to Section 29.2.1 *Readline Bare Essentials*)
 editing source files, (refer to Section 9.2 *Editing source files*)
 editing-mode, (refer to Section 29.3.1 *Readline Init File Syntax*)
 else, (refer to Section 22.1 *User-defined commands*)
 elt, (refer to Section 27.3 *Values*)
 elt-rep, (refer to Section 27.3 *Values*)
 elt-rep-end, (refer to Section 27.3 *Values*)
 Emacs, (refer to Chapter 25 *Using gdb under gnu Emacs*)
 enable, (refer to Section 7.1.5 *Disabling breakpoints*)
 enable breakpoints, (refer to Section 7.1.5 *Disabling breakpoints*)
 enable display, (refer to Section 10.6 *Automatic display*)
 enable mem, (refer to Section 10.13 *Memory region attributes*)
 enable tracepoint, (refer to Section 12.1.2 *Enable and Disable Tracepoints*)
 enable-keypad, (refer to Section 29.3.1 *Readline Init File Syntax*)
 end, (refer to Section 7.1.7 *Breakpoint command lists*)
 entering numbers, (refer to Section 21.5 *Numbers*)
 environment (of your program), (refer to Section 6.4 *Your program's environment*)
 erno values, in file-i/o protocol, (refer to Section D.7.12.3 *Erno values*)
 error, (refer to Section 27.7 *Errors*)
 error on valid input, (refer to Section 28.1 *Have you found a bug?*)
 error-begin, (refer to Section 27.7 *Errors*)
 event designators, (refer to Section 30.1.1 *Event Designators*)
 event handling, (refer to Section 7.1.3 *Setting catchpoints*)
 examining data, (refer to Chapter 10 *Examining Data*)
 examining memory, (refer to Section 10.5 *Examining memory*)

exception handlers, (refer to Section 7.1.3 *Setting catchpoints*)
 exception handlers, how to list, (refer to Section 8.4 *Information about a frame*)
 exceptionHandler, (refer to Section 19.5.2 *What you must do for the stub*)
 exec-file, (refer to Section 17.1 *Commands to specify files*)
 executable file, (refer to Section 17.1 *Commands to specify files*)
 exited, (refer to Section 27.10 *Running the Program*)
 exiting gdb, (refer to Section 4.2 *Quitting gdb*)
 expand-tilde, (refer to Section 29.3.1 *Readline Init File Syntax*)
 expanding preprocessor macros, (refer to Chapter 11 *C Preprocessor Macros*)
 expressions, (refer to Section 10.1 *Expressions*)
 expressions in C or C++, (refer to Section 14.4.1 *C and C++*)
 expressions in C++, (refer to Section 14.4.1.3 *C++ expressions*)
 expressions in Modula-2, (refer to Section 14.4.3 *Modula-2*)

F

f (frame), (refer to Section 8.3 *Selecting a frame*)
 f (SingleKey TUI key), (refer to Section 24.3 *TUI Single Key Mode*)
 F packet, (refer to Section D.2 *Packets*)
 F reply packet, (refer to Section D.7.4 *The Freply packet*)
 F request packet, (refer to Section D.7.3 *The Frequest packet*)
 fatal signal, (refer to Section 28.1 *Have you found a bug?*)
 fatal signals, (refer to Section 7.3 *Signals*)
 fg (resume foreground execution), (refer to Section 7.2 *Continuing and stepping*)
 field, (refer to Section 27.8 *Information on Breakpoints*)
 field-begin, (refer to Section 27.3 *Values*)
 field-end, (refer to Section 27.3 *Values*)
 field-name-end, (refer to Section 27.3 *Values*)
 field-value, (refer to Section 27.3 *Values*)
 file, (refer to Section 17.1 *Commands to specify files*)
 file-i/o examples, (refer to Section D.7.13 *File-I/O Examples*)
 file-i/o overview, (refer to Section D.7.1 *File-I/O Overview*)
 File-I/O remote protocol extension, (refer to Section D.7 *File-I/O remote protocol extension*)
 file-i/o reply packet, (refer to Section D.7.4 *The Freply packet*)
 file-i/o request packet, (refer to Section D.7.3 *The Frequest packet*)
 find trace snapshot, (refer to Section 12.2.1 *tfind n*)
 finish, (refer to Section 7.2 *Continuing and stepping*)
 flinching, (refer to Section 21.7 *Optional warnings and messages*)
 float promotion, (refer to Section 21.6 *Configuring the current ABI*)
 floating point, (refer to Section 10.11 *Floating point hardware*)
 floating point registers, (refer to Section 10.10 *Registers*)
 floating point, MIPS remote, (refer to Section 20.3.6 *MIPS Embedded*)
 flush_i_cache, (refer to Section 19.5.2 *What you must do for the stub*)
 focus, (refer to Section 24.4 *TUI specific commands*)
 focus of debugging, (refer to Section 6.9 *Debugging programs with multiple threads*)
 foo, (refer to Section 17.3 *Errors reading symbol files*)
 fork, debugging programs which call, (refer to Section 6.10 *Debugging programs with multiple processes*)
 format options, (refer to Section 10.7 *Print settings*)
 formatted output, (refer to Section 10.4 *Output formats*)
 Fortran, (refer to Chapter 2 *Summary of gdb*)
 forward-search, (refer to Section 9.3 *Searching source files*)
 frame number, (refer to Section 8.1 *Stack frames*)
 frame pointer, (refer to Section 8.1 *Stack frames*)
 frame, command, (refer to Section 8.1 *Stack frames*)
 frame, definition, (refer to Section 8.1 *Stack frames*)
 frame, selecting, (refer to Section 8.3 *Selecting a frame*)
 frame-address, (refer to Section 27.4 *Frames*)
 frame-address-end, (refer to Section 27.4 *Frames*)
 frame-args, (refer to Section 27.4 *Frames*)
 frame-begin, (refer to Section 27.4 *Frames*)
 frame-end, (refer to Section 27.4 *Frames*)
 frame-function-name, (refer to Section 27.4 *Frames*)
 frame-source-begin, (refer to Section 27.4 *Frames*)
 frame-source-end, (refer to Section 27.4 *Frames*)
 frame-source-file, (refer to Section 27.4 *Frames*)
 frame-source-file-end, (refer to Section 27.4 *Frames*)
 frame-source-line, (refer to Section 27.4 *Frames*)
 frame-where, (refer to Section 27.4 *Frames*)
 frameless execution, (refer to Section 8.1 *Stack frames*)
 frames-invalid, (refer to Section 27.9 *Invalidation Notices*)
 free memory information (MS-DOS), (refer to Section 20.1.3 *Features for Debugging djgpp Programs*)
 fstat, file-i/o system call, (refer to Section D.7.10.8 *stat/fstat*)
 Fujitsu, (refer to Section 19.5 *Implementing a remote stub*)

full symbol tables, listing gdb's internal, (refer to Chapter 15 *Examining the Symbol Table*)
 function-call, (refer to Section 27.4 *Frames*)
 functions without line info, and stepping, (refer to Section 7.2 *Continuing and stepping*)
 G packet, (refer to Section D.2 *Packets*)
 g packet, (refer to Section D.2 *Packets*)
 g++, gnu C++ compiler, (refer to Section 14.4.1 *C and C++*)

G

garbled pointers, (refer to Section 20.1.3 *Features for Debugging djgpp Programs*)
 gcc and C++, (refer to Section 14.4.1.3 *C++ expressions*)
 gdb bugs, reporting, (refer to Section 28.2 *How to report bugs*)
 gdb reference card, (refer to Appendix A *Formatting Documentation*)
 gdb.ini, (refer to Section 22.3 *Command files*)
 gdb/mi, breakpoint commands, (refer to Section 26.8 *gdb/mi Breakpoint table commands*)
 gdb/mi, compatibility with CLI, (refer to Section 26.5 *gdb/mi Compatibility with CLI*)
 gdb/mi, data manipulation, (refer to Section 26.9 *gdb/mi Data Manipulation*)
 gdb/mi, input syntax, (refer to Section 26.4.1 *gdb/mi Input Syntax*)
 gdb/mi, its purpose, (refer to Chapter 26 *The gdb/mi Interface*)
 gdb/mi, out-of-band records, (refer to Section 26.6.3 *gdb/mi Out-of-band Records*)
 gdb/mi, output syntax, (refer to Section 26.4.2 *gdb/mi Output Syntax*)
 gdb/mi, result records, (refer to Section 26.6.1 *gdb/mi Result Records*)
 gdb/mi, simple examples, (refer to Section 26.4.3 *Simple Examples of gdb/mi Interaction*)
 gdb/mi, stream records, (refer to Section 26.6.2 *gdb/mi Stream Records*)
 GDBHISTFILE, (refer to Section 21.3 *Command history*)
 gdbserve.nlm, (refer to Section 19.3 *Using the gdbserve.nlm program*)
 gdbserver, (refer to Section 19.2 *Using the gdbserver program*)
 GDT, (refer to Section 20.1.3 *Features for Debugging djgpp Programs*)
 getDebugChar, (refer to Section 19.5.2 *What you must do for the stub*)
 gettimeofday, file-i/o system call, (refer to Section D.7.10.9 *gettimeofday*)
 global debugging information directory, (refer to Section 17.2 *Debugging Information in Separate Files*)

gnu C++, (refer to Section 14.4.1 *C and C++*)
 gnu Emacs, (refer to Chapter 25 *Using gdb under gnu Emacs*)
 gnu_debuglink_crc32, (refer to Section 17.2 *Debugging Information in Separate Files*)

H

h (help), (refer to Section 5.3 *Getting help*)
 H packet, (refer to Section D.2 *Packets*)
 H8/300 or H8/500 download, (refer to Section 20.3.2 *Hitachi H8/300*)
 handle, (refer to Section 7.3 *Signals*)
 handle_exception, (refer to Section 19.5.1 *What the stub can do for you*)
 handling signals, (refer to Section 7.3 *Signals*)
 hardware watchpoints, (refer to Section 7.1.2 *Setting watchpoints*)
 hbreak, (refer to Section 7.1.1 *Setting breakpoints*)
 help, (refer to Section 5.3 *Getting help*)
 help target, (refer to Section 18.2 *Commands for managing targets*)
 help user-defined, (refer to Section 22.1 *User-defined commands*)
 heuristic-fence-post (Alpha, MIPS), (refer to Section 20.4.3 *MIPS*)
 history events, (refer to Section 30.1.1 *Event Designators*)
 history expansion, (refer to Section 30.1 *History Expansion*)
 history expansion, (refer to Section 21.3 *Command history*)
 history file, (refer to Section 21.3 *Command history*)
 history number, (refer to Section 10.8 *Value history*)
 history save, (refer to Section 21.3 *Command history*)
 history size, (refer to Section 21.3 *Command history*)
 history substitution, (refer to Section 21.3 *Command history*)
 history-preserve-point, (refer to Section 29.3.1 *Readline Init File Syntax*)
 Hitachi, (refer to Section 19.5 *Implementing a remote stub*)
 Hitachi SH download, (refer to Section 20.3.2 *Hitachi H8/300*)
 hook, (refer to Section 22.2 *User-defined command hooks*)
 hook-, (refer to Section 22.2 *User-defined command hooks*)
 hookpost, (refer to Section 22.2 *User-defined command hooks*)
 hookpost-, (refer to Section 22.2 *User-defined command hooks*)
 hooks, for commands, (refer to Section 22.2 *User-defined command hooks*)

hooks, post-command, (refer to Section 22.2 *User-defined command hooks*)
 hooks, pre-command, (refer to Section 22.2 *User-defined command hooks*)
 horizontal-scroll-mode, (refer to Section 29.3.1 *Readline Init File Syntax*)
 host character set, (refer to Section 10.15 *Character Sets*)
 htrace disable, (refer to Section 20.3.7 *OpenRISC 1000*)
 htrace enable, (refer to Section 20.3.7 *OpenRISC 1000*)
 htrace info, (refer to Section 20.3.7 *OpenRISC 1000*)
 htrace mode continuous, (refer to Section 20.3.7 *OpenRISC 1000*)
 htrace mode suspend, (refer to Section 20.3.7 *OpenRISC 1000*)
 htrace print, (refer to Section 20.3.7 *OpenRISC 1000*)
 htrace qualifier, (refer to Section 20.3.7 *OpenRISC 1000*)
 htrace record, (refer to Section 20.3.7 *OpenRISC 1000*)
 htrace rewind, (refer to Section 20.3.7 *OpenRISC 1000*)
 htrace stop, (refer to Section 20.3.7 *OpenRISC 1000*)
 htrace trigger, (refer to Section 20.3.7 *OpenRISC 1000*)
 hwatch, (refer to Section 20.3.7 *OpenRISC 1000*)

I

i (info), (refer to Section 5.3 *Getting help*)
 I packet, (refer to Section D.2 *Packets*)
 i packet, (refer to Section D.2 *Packets*)
 i/o, (refer to Section 6.6 *Your program's input and output*)
 i386, (refer to Section 19.5 *Implementing a remote stub*)
 i386-stub.c, (refer to Section 19.5 *Implementing a remote stub*)
 IBM1047 character set, (refer to Section 10.15 *Character Sets*)
 IDT, (refer to Section 20.1.3 *Features for Debugging djgpp Programs*)
 if, (refer to Section 22.1 *User-defined commands*)
 ignore, (refer to Section 7.1.6 *Break conditions*)
 ignore count (of breakpoint), (refer to Section 7.1.6 *Break conditions*)
 INCLUDE_RDB, (refer to Section 20.2.1 *Using gdb with VxWorks*)
 info, (refer to Section 5.3 *Getting help*)
 info address, (refer to Chapter 15 *Examining the Symbol Table*)
 info all-registers, (refer to Section 10.10 *Registers*)
 info args, (refer to Section 8.4 *Information about a frame*)
 info breakpoints, (refer to Section 7.1.1 *Setting breakpoints*)
 info catch, (refer to Section 8.4 *Information about a frame*)
 info classes, (refer to Chapter 15 *Examining the Symbol Table*)
 info display, (refer to Section 10.6 *Automatic display*)
 info dll, (refer to Section 20.1.4 *Features for Debugging MS Windows PE executables*)
 info dos, (refer to Section 20.1.3 *Features for Debugging djgpp Programs*)
 info extensions, (refer to Section 14.2 *Displaying the language*)
 info f (info frame), (refer to Section 8.4 *Information about a frame*)
 info files, (refer to Section 17.1 *Commands to specify files*)
 info float, (refer to Section 10.11 *Floating point hardware*)
 info frame, (refer to Section 8.4 *Information about a frame*)
 info frame, show the source language, (refer to Section 14.2 *Displaying the language*)
 info functions, (refer to Chapter 15 *Examining the Symbol Table*)
 info line, (refer to Section 9.5 *Source and machine code*)
 info line, and Objective-C, (refer to Section 14.4.2.1 *Method Names in Commands*)
 info locals, (refer to Section 8.4 *Information about a frame*)
 info macro, (refer to Chapter 11 *C Preprocessor Macros*)
 info mem, (refer to Section 10.13 *Memory region attributes*)
 info or1k spr, (refer to Section 20.3.7 *OpenRISC 1000*)
 info proc, (refer to Section 20.1.2 *SVR4 process information*)
 info proc mappings, (refer to Section 20.1.2 *SVR4 process information*)
 info program, (refer to Chapter 7 *Stopping and Continuing*)
 info registers, (refer to Section 10.10 *Registers*)
 info s (info stack), (refer to Section 8.2 *Backtraces*)
 info scope, (refer to Chapter 15 *Examining the Symbol Table*)
 info selectors, (refer to Chapter 15 *Examining the Symbol Table*)
 info set, (refer to Section 5.3 *Getting help*)
 info share, (refer to Section 17.1 *Commands to specify files*)
 info sharedlibrary, (refer to Section 17.1 *Commands to specify files*)
 info signals, (refer to Section 7.3 *Signals*)
 info source, (refer to Chapter 15 *Examining the Symbol Table*)
 info source, show the source language, (refer to Section 14.2 *Displaying the language*)

info sources, (refer to Chapter 15 *Examining the Symbol Table*)

info stack, (refer to Section 8.2 *Backtraces*)

info symbol, (refer to Chapter 15 *Examining the Symbol Table*)

info target, (refer to Section 17.1 *Commands to specify files*)

info terminal, (refer to Section 6.6 *Your program's input and output*)

info threads, (refer to Section 6.9 *Debugging programs with multiple threads*)

info tracepoints, (refer to Section 12.1.5 *Listing Tracepoints*)

info types, (refer to Chapter 15 *Examining the Symbol Table*)

info variables, (refer to Chapter 15 *Examining the Symbol Table*)

info vector, (refer to Section 10.12 *Vector Unit*)

info w32, (refer to Section 20.1.4 *Features for Debugging MS Windows PE executables*)

info watchpoints, (refer to Section 7.1.2 *Setting watchpoints*)

info win, (refer to Section 24.4 *TUI specific commands*)

information about tracepoints, (refer to Section 12.1.5 *Listing Tracepoints*)

inheritance, (refer to Section 14.4.1.7 *gdb features for C++*)

init file, (refer to Section 22.3 *Command files*)

init file name, (refer to Section 22.3 *Command files*)

initial frame, (refer to Section 8.1 *Stack frames*)

initialization file, readline, (refer to Section 29.3 *Readline Init File*)

innermost frame, (refer to Section 8.1 *Stack frames*)

input syntax for gdb/mi, (refer to Section 26.4.1 *gdb/mi Input Syntax*)

input-meta, (refer to Section 29.3.1 *Readline Init File Syntax*)

inspect, (refer to Chapter 10 *Examining Data*)

installation, (refer to Appendix B *Installing gdb*)

instructions, assembly, (refer to Section 9.5 *Source and machine code*)

integral datatypes, in file-i/o protocol, (refer to Section D.7.11.1 *Integral datatypes*)

Intel, (refer to Section 19.5 *Implementing a remote stub*)

Intel disassembly flavor, (refer to Section 9.5 *Source and machine code*)

interaction, readline, (refer to Section 29.2 *Readline Interaction*)

internal commands, (refer to Appendix C *Maintenance Commands*)

internal gdb breakpoints, (refer to Section 7.1.1 *Setting breakpoints*)

interpreter-exec, (refer to Chapter 23 *Command Interpreters*)

interrupt, (refer to Section 4.2 *Quitting gdb*)

interrupting remote programs, (refer to Section 19.1 *Connecting to a remote target*)

interrupting remote targets, (refer to Section 19.5.2 *What you must do for the stub*)

invalid input, (refer to Section 28.1 *Have you found a bug?*)

invoke another interpreter, (refer to Chapter 23 *Command Interpreters*)

isatty call, file-i/o protocol, (refer to Section D.7.8 *The isatty(3) call*)

isatty, file-i/o system call, (refer to Section D.7.10.10 *isatty*)

isearch-terminators, (refer to Section 29.3.1 *Readline Init File Syntax*)

ISO 8859-1 character set, (refer to Section 10.15 *Character Sets*)

ISO Latin 1 character set, (refer to Section 10.15 *Character Sets*)

J

jump, (refer to Section 16.2 *Continuing at a different address*)

jump, and Objective-C, (refer to Section 14.4.2.1 *Method Names in Commands*)

k packet, (refer to Section D.2 *Packets*)

K

kernel object, (refer to Section 18.5 *Kernel Object Display*)

kernel object display, (refer to Section 18.5 *Kernel Object Display*)

keymap, (refer to Section 29.3.1 *Readline Init File Syntax*)

kill, (refer to Section 6.8 *Killing the child process*)

kill ring, (refer to Section 29.2.3 *Readline Killing Commands*)

killing text, (refer to Section 29.2.3 *Readline Killing Commands*)

KOD, (refer to Section 18.5 *Kernel Object Display*)

L

l(list), (refer to Section 9.1 *Printing source lines*)

languages, (refer to Chapter 14 *Using gdb with Different Languages*)

last tracepoint number, (refer to Section 12.1.1 *Create and Delete Tracepoints*)

latest breakpoint, (refer to Section 7.1.1 *Setting breakpoints*)

layout asm, (refer to Section 24.4 *TUI specific commands*)

layout next, (refer to Section 24.4 *TUI specific commands*)

layout prev, (refer to Section 24.4 *TUI specific commands*)

layout regs, (refer to Section 24.4 *TUI specific commands*)

layout split, (refer to Section 24.4 *TUI specific commands*)

layout src, (refer to Section 24.4 *TUI specific commands*)

LDT, (refer to Section 20.1.3 *Features for Debugging djgpp Programs*)

leaving gdb, (refer to Section 4.2 *Quitting gdb*)

Left, (refer to Section 24.2 *TUI Key Bindings*)

limits, in file-i/o protocol, (refer to Section D.7.12.5 *Limits*)

linespec, (refer to Section 9.1 *Printing source lines*)

list, (refer to Section 9.1 *Printing source lines*)

list of supported file-i/o calls, (refer to Section D.7.10 *List of supported calls*)

list output in gdb/mi, (refer to Section 26.4.2 *gdb/mi Output Syntax*)

list, and Objective-C, (refer to Section 14.4.2.1 *Method Names in Commands*)

listing gdb's internal symbol tables, (refer to Chapter 15 *Examining the Symbol Table*)

listing machine instructions, (refer to Section 9.5 *Source and machine code*)

listing mapped overlays, (refer to Section 13.2 *Overlay Commands*)

load address, overlay's, (refer to Section 13.1 *How Overlays Work*)

load filename, (refer to Section 18.2 *Commands for managing targets*)

local variables, (refer to Chapter 15 *Examining the Symbol Table*)

locate address, (refer to Section 10.4 *Output formats*)

log output in gdb/mi, (refer to Section 26.4.2 *gdb/mi Output Syntax*)

logging gdb output, (refer to Section 4.4 *Logging output*)

lseek flags, in file-i/o protocol, (refer to Section D.7.12.4 *Lseek flags*)

lseek, file-i/o system call, (refer to Section D.7.10.5 *Lseek*)

M packet, (refer to Section D.2 *Packets*)

m packet, (refer to Section D.2 *Packets*)

M

m680x0, (refer to Section 19.5 *Implementing a remote stub*)

m68k-stub.c, (refer to Section 19.5 *Implementing a remote stub*)

machine instructions, (refer to Section 9.5 *Source and machine code*)

macro define, (refer to Chapter 11 *C Preprocessor Macros*)

macro definition, showing, (refer to Chapter 11 *C Preprocessor Macros*)

macro expand, (refer to Chapter 11 *C Preprocessor Macros*)

macro expand-once, (refer to Chapter 11 *C Preprocessor Macros*)

macro expansion, showing the results of preprocessor, (refer to Chapter 11 *C Preprocessor Macros*)

macro undef, (refer to Chapter 11 *C Preprocessor Macros*)

macros, example of debugging with, (refer to Chapter 11 *C Preprocessor Macros*)

macros, user-defined, (refer to Chapter 11 *C Preprocessor Macros*)

maint info breakpoints, (refer to Appendix C *Maintenance Commands*)

maint info psymtabs, (refer to Chapter 15 *Examining the Symbol Table*)

maint info sections, (refer to Section 17.1 *Commands to specify files*)

maint info symtabs, (refer to Chapter 15 *Examining the Symbol Table*)

maint internal-error, (refer to Appendix C *Maintenance Commands*)

maint internal-warning, (refer to Appendix C *Maintenance Commands*)

maint print cooked-registers, (refer to Appendix C *Maintenance Commands*)

maint print dummy-frames, (refer to Appendix C *Maintenance Commands*)

maint print psymbols, (refer to Chapter 15 *Examining the Symbol Table*)

maint print raw-registers, (refer to Appendix C *Maintenance Commands*)

maint print reggroups, (refer to Appendix C *Maintenance Commands*)

maint print register-groups, (refer to Appendix C *Maintenance Commands*)

maint print registers, (refer to Appendix C *Maintenance Commands*)

maint print symbols, (refer to Chapter 15 *Examining the Symbol Table*)

maint set profile, (refer to Appendix C *Maintenance Commands*)

maint show profile, (refer to Appendix C *Maintenance Commands*)

maintenance commands, (refer to Appendix C *Maintenance Commands*)

make, (refer to Section 4.3 *Shell commands*)

manual overlay debugging, (refer to Section 13.2 *Overlay Commands*)

map an overlay, (refer to Section 13.2 *Overlay Commands*)

mapped, (refer to Section 17.1 *Commands to specify files*)

mapped address, (refer to Section 13.1 *How Overlays Work*)

mapped overlays, (refer to Section 13.1 *How Overlays Work*)

mark-modified-lines, (refer to Section 29.3.1 *Readline Init File Syntax*)

mark-symlinked-directories, (refer to Section 29.3.1 *Readline Init File Syntax*)

match-hidden-files, (refer to Section 29.3.1 *Readline Init File Syntax*)

mem, (refer to Section 10.13 *Memory region attributes*)

member functions, (refer to Section 14.4.1.3 *C++expressions*)

memory models, H8/500, (refer to Section 20.3.3 *H8/500*)

memory region attributes, (refer to Section 10.13 *Memory region attributes*)

memory tracing, (refer to Section 7.1 *Breakpoints, watchpoints, and catchpoints*)

memory transfer, in file-i/o protocol, (refer to Section D.7.5 *Memory transfer*)

memory, viewing as typed object, (refer to Section 10.1 *Expressions*)

memory-mapped symbol file, (refer to Section 17.1 *Commands to specify files*)

memset, (refer to Section 19.5.2 *What you must do for the stub*)

meta-flag, (refer to Section 29.3.1 *Readline Init File Syntax*)

mi interpreter, (refer to Chapter 23 *Command Interpreters*)

mi1 interpreter, (refer to Chapter 23 *Command Interpreters*)

mi2 interpreter, (refer to Chapter 23 *Command Interpreters*)

minimal language, (refer to Section 14.5 *Unsupported languages*)

Minimal symbols and DLLs, (refer to Section 20.1.4.1 *Support for DLLs without debugging symbols*)

MIPS boards, (refer to Section 20.3.6 *MIPS Embedded*)

MIPS remote floating point, (refer to Section 20.3.6 *MIPS Embedded*)

MIPS remotodebug protocol, (refer to Section 20.3.6 *MIPS Embedded*)

MIPS stack, (refer to Section 20.4.3 *MIPS*)

mode_t values, in file-i/o protocol, (refer to Section D.7.12.2 *mode_t values*)

Modula-2, (refer to Chapter 2 *Summary of gdb*)

Modula-2 built-ins, (refer to Section 14.4.3.2 *Built-in functions and procedures*)

Modula-2 checks, (refer to Section 14.4.3.6 *Modula-2 type and range checks*)

Modula-2 constants, (refer to Section 14.4.3.2 *Built-in functions and procedures*)

Modula-2 defaults, (refer to Section 14.4.3.4 *Modula-2 defaults*)

Modula-2 operators, (refer to Section 14.4.3.1 *Operators*)

Modula-2, deviations from, (refer to Section 14.4.3.5 *Deviations from standard Modula-2*)

Modula-2, gdb support, (refer to Section 14.4.3 *Modula-2*)

Motorola 680x0, (refer to Section 19.5 *Implementing a remote stub*)

MS Windows debugging, (refer to Section 20.1.4 *Features for Debugging MS Windows PE executables*)

MS-DOS system info, (refer to Section 20.1.3 *Features for Debugging djgpp Programs*)

MS-DOS-specific commands, (refer to Section 20.1.3 *Features for Debugging djgpp Programs*)

multiple processes, (refer to Section 6.10 *Debugging programs with multiple processes*)

multiple targets, (refer to Section 18.1 *Active targets*)

multiple threads, (refer to Section 6.9 *Debugging programs with multiple threads*)

N

n (next), (refer to Section 7.2 *Continuing and stepping*)

n (SingleKey TUI key), (refer to Section 24.3 *TUI Single Key Mode*)

names of symbols, (refer to Chapter 15 *Examining the Symbol Table*)

namespace in C++, (refer to Section 14.4.1.3 *C++expressions*)

native Cygwin debugging, (refer to Section 20.1.4 *Features for Debugging MS Windows PE executables*)

native djgpp debugging, (refer to Section 20.1.3 *Features for Debugging djgpp Programs*)

negative breakpoint numbers, (refer to Section 7.1.1 *Setting breakpoints*)

New systag message, (refer to Section 6.9 *Debugging programs with multiple threads*)

New systag message, on HP-UX, (refer to Section 6.9 *Debugging programs with multiple threads*)

next, (refer to Section 7.2 *Continuing and stepping*)

nexti, (refer to Section 7.2 *Continuing and stepping*)

ni (nexti), (refer to Section 7.2 *Continuing and stepping*)

notation, readline, (refer to Section 29.2.1 *Readline Bare Essentials*)

notational conventions, for gdb/mi, (refer to Chapter 26 *The gdb/mi Interface*)

notify output in gdb/mi, (refer to Section 26.4.2 *gdb/mi Output Syntax*)
 number representation, (refer to Section 21.5 *Numbers*)
 numbers for breakpoints, (refer to Section 7.1 *Breakpoints, watchpoints, and catchpoints*)

O

object files, relocatable, reading symbols from, (refer to Section 17.1 *Commands to specify files*)
 Objective-C, (refer to Section 14.4.2 *Objective-C*)
 online documentation, (refer to Section 5.3 *Getting help*)
 open flags, in file-i/o protocol, (refer to Section D.7.12.1 *Open flags*)
 open, file-i/o system call, (refer to Section D.7.10.1 *open*)
 OpenRISC 1000, (refer to Section 20.3.7 *OpenRISC 1000*)
 OpenRISC 1000 htrace, (refer to Section 20.3.7 *OpenRISC 1000*)
 optimized code, debugging, (refer to Section 6.1 *Compiling for debugging*)
 or1k boards, (refer to Section 20.3.7 *OpenRISC 1000*)
 or1ksim, (refer to Section 20.3.7 *OpenRISC 1000*)
 OS ABI, (refer to Section 21.6 *Configuring the current ABI*)
 out-of-band records in gdb/mi, (refer to Section 26.6.3 *gdb/mi Out-of-band Records*)
 outermost frame, (refer to Section 8.1 *Stack frames*)
 output, (refer to Section 22.4 *Commands for controlled output*)
 output formats, (refer to Section 10.4 *Output formats*)
 output syntax of gdb/mi, (refer to Section 26.4.2 *gdb/mi Output Syntax*)
 output-meta, (refer to Section 29.3.1 *Readline Init File Syntax*)
 overlay area, (refer to Section 13.1 *How Overlays Work*)
 overlay auto, (refer to Section 13.2 *Overlay Commands*)
 overlay example program, (refer to Section 13.4 *Overlay Sample Program*)
 overlay load-target, (refer to Section 13.2 *Overlay Commands*)
 overlay manual, (refer to Section 13.2 *Overlay Commands*)
 overlay map-overlay, (refer to Section 13.2 *Overlay Commands*)
 overlay off, (refer to Section 13.2 *Overlay Commands*)
 overlay unmap-overlay, (refer to Section 13.2 *Overlay Commands*)
 overlays, (refer to Chapter 13 *Debugging Programs That Use Overlays*)

overlays, setting breakpoints in, (refer to Section 13.2 *Overlay Commands*)
 overload-choice, (refer to Section 27.6 *Annotation for gdb Input*)
 overloaded functions, calling, (refer to Section 14.4.1.3 *C++ expressions*)
 overloaded functions, overload resolution, (refer to Section 14.4.1.7 *gdb features for C++*)
 overloading, (refer to Section 7.1.8 *Breakpoint menus*)
 overloading in C++, (refer to Section 14.4.1.7 *gdb features for C++*)
 P packet, (refer to Section D.2 *Packets*)
 p packet, (refer to Section D.2 *Packets*)

P

packets, reporting on stdout, (refer to Section 21.8 *Optional messages about internal happenings*)
 page tables display (MS-DOS), (refer to Section 20.1.3 *Features for Debugging djgpp Programs*)
 page-completions, (refer to Section 29.3.1 *Readline Init File Syntax*)
 partial symbol dump, (refer to Chapter 15 *Examining the Symbol Table*)
 partial symbol tables, listing gdb's internal, (refer to Chapter 15 *Examining the Symbol Table*)
 Pascal, (refer to Chapter 2 *Summary of gdb*)
 passcount, (refer to Section 12.1.3 *Tracepoint Passcounts*)
 patching binaries, (refer to Section 16.6 *Patching programs*)
 path, (refer to Section 6.4 *Your program's environment*)
 pauses in output, (refer to Section 21.4 *Screen size*)
 PgDn, (refer to Section 24.2 *TUI Key Bindings*)
 PgUp, (refer to Section 24.2 *TUI Key Bindings*)
 physical address from linear address, (refer to Section 20.1.3 *Features for Debugging djgpp Programs*)
 pipes, (refer to Section 6.2 *Starting your program*)
 pointer values, in file-i/o protocol, (refer to Section D.7.11.2 *Pointer values*)
 pointer, finding referent, (refer to Section 10.7 *Print settings*)
 post-commands, (refer to Section 27.6 *Annotation for gdb Input*)
 post-overload-choice, (refer to Section 27.6 *Annotation for gdb Input*)
 post-prompt, (refer to Section 27.6 *Annotation for gdb Input*)
 post-prompt-for-continue, (refer to Section 27.6 *Annotation for gdb Input*)
 post-query, (refer to Section 27.6 *Annotation for gdb Input*)
 pre-commands, (refer to Section 27.6 *Annotation for gdb Input*)

pre-overload-choice, (refer to Section 27.6 *Annotation for gdb Input*)

pre-prompt, (refer to Section 27.6 *Annotation for gdb Input*)

pre-prompt-for-continue, (refer to Section 27.6 *Annotation for gdb Input*)

pre-query, (refer to Section 27.6 *Annotation for gdb Input*)

preprocessor macro expansion, showing the results of, (refer to Chapter 11 *C Preprocessor Macros*)

print, (refer to Chapter 10 *Examining Data*)

print an Objective-C object description, (refer to Section 14.4.2.2 *The Print Command With Objective-C*)

print settings, (refer to Section 10.7 *Print settings*)

printf, (refer to Section 22.4 *Commands for controlled output*)

printing data, (refer to Chapter 10 *Examining Data*)

process image, (refer to Section 20.1.2 *SVR4 process information*)

processes, multiple, (refer to Section 6.10 *Debugging programs with multiple processes*)

profiling GDB, (refer to Appendix C *Maintenance Commands*)

prompt, (refer to Section 27.6 *Annotation for gdb Input*)

prompt, (refer to Section 21.1 *Prompt*)

prompt-for-continue, (refer to Section 27.6 *Annotation for gdb Input*)

protocol basics, file-i/o, (refer to Section D.7.2 *Protocol basics*)

protocol specific representation of datatypes, in file-i/o protocol, (refer to Section D.7.11 *Protocol specific representation of datatypes*)

protocol, gdb remote serial, (refer to Section D.1 *Overview*)

ptype, (refer to Chapter 15 *Examining the Symbol Table*)

putDebugChar, (refer to Section 19.5.2 *What you must do for the stub*)

pwd, (refer to Section 6.5 *Your program's working directory*)

Q

q (quit), (refer to Section 4.2 *Quitting gdb*)

q (SingleKey TUI key), (refer to Section 24.3 *TUI Single Key Mode*)

Q packet, (refer to Section D.2 *Packets*)

q packet, (refer to Section D.2 *Packets*)

query, (refer to Section 27.6 *Annotation for gdb Input*)

quit, (refer to Section 27.7 *Errors*)

quit [expression], (refer to Section 4.2 *Quitting gdb*)

quotes in commands, (refer to Section 5.2 *Command completion*)

quoting names, (refer to Chapter 15 *Examining the Symbol Table*)

R

r (run), (refer to Section 6.2 *Starting your program*)

r (SingleKey TUI key), (refer to Section 24.3 *TUI Single Key Mode*)

R packet, (refer to Section D.2 *Packets*)

r packet, (refer to Section D.2 *Packets*)

raise exceptions, (refer to Section 7.1.3 *Setting catch-points*)

range checking, (refer to Section 14.3.1 *An overview of type checking*)

ranges of breakpoints, (refer to Section 7.1 *Breakpoints, watchpoints, and catchpoints*)

rbreak, (refer to Section 7.1.1 *Setting breakpoints*)

read, file-i/o system call, (refer to Section D.7.10.3 *read*)

reading symbols from relocatable object files, (refer to Section 17.1 *Commands to specify files*)

reading symbols immediately, (refer to Section 17.1 *Commands to specify files*)

readline, (refer to Section 21.2 *Command editing*)

readnow, (refer to Section 17.1 *Commands to specify files*)

recent tracepoint number, (refer to Section 12.1.1 *Create and Delete Tracepoints*)

record, (refer to Section 27.8 *Information on Breakpoints*)

redirection, (refer to Section 6.6 *Your program's input and output*)

reference card, (refer to Appendix A *Formatting Documentation*)

reference declarations, (refer to Section 14.4.1.3 *C++expressions*)

refresh, (refer to Section 24.4 *TUI specific commands*)

register stack, AMD29K, (refer to Section 20.4.1 *A29K*)

registers, (refer to Section 10.10 *Registers*)

regular expression, (refer to Section 7.1.1 *Setting breakpoints*)

reloading symbols, (refer to Chapter 15 *Examining the Symbol Table*)

reloading the overlay table, (refer to Section 13.2 *Overlay Commands*)

relocatable object files, reading symbols from, (refer to Section 17.1 *Commands to specify files*)

remote connection without stubs, (refer to Section 19.2 *Using the gdbserver program*)

remote debugging, (refer to Section 18.4 *Remote debugging*)

remote programs, interrupting, (refer to Section 19.1 *Connecting to a remote target*)

remote protocol, field separator, (refer to Section D.1 *Overview*)

remote serial debugging summary, (refer to Section 19.5.3 *Putting it all together*)

remote serial debugging, overview, (refer to Section 19.5 *Implementing a remote stub*)

remote serial protocol, (refer to Section D.1 *Overview*)

remote serial stub, (refer to Section 19.5.1 *What the stub can do for you*)

remote serial stub list, (refer to Section 19.5 *Implementing a remote stub*)

remote serial stub, initialization, (refer to Section 19.5.1 *What the stub can do for you*)

remote serial stub, main routine, (refer to Section 19.5.1 *What the stub can do for you*)

remote stub, example, (refer to Section 19.5 *Implementing a remote stub*)

remote stub, support routines, (refer to Section 19.5.2 *What you must do for the stub*)

remotedebug, MIPS protocol, (refer to Section 20.3.6 *MIPS Embedded*)

remotetimeout, (refer to Section 20.3.11 *Tsquare Sparclet*)

remove actions from a tracepoint, (refer to Section 12.1.4 *Tracepoint Action Lists*)

rename, file-i/o system call, (refer to Section D.7.10.6 *rename*)

repeating command sequences, (refer to Section 5.1 *Command syntax*)

repeating commands, (refer to Section 5.1 *Command syntax*)

reporting bugs in gdb, (refer to Chapter 28 *Reporting Bugs in gdb*)

response time, MIPS debugging, (refer to Section 20.4.3 *MIPS*)

restore, (refer to Section 10.14 *Copy between memory and a file*)

restore data from a file, (refer to Section 10.14 *Copy between memory and a file*)

result records in gdb/mi, (refer to Section 26.6.1 *gdb/mi Result Records*)

resuming execution, (refer to Section 7.2 *Continuing and stepping*)

RET (repeat last command), (refer to Section 5.1 *Command syntax*)

retransmit-timeout, MIPS protocol, (refer to Section 20.3.6 *MIPS Embedded*)

return, (refer to Section 16.4 *Returning from a function*)

returning from a function, (refer to Section 16.4 *Returning from a function*)

reverse-search, (refer to Section 9.3 *Searching source files*)

Right, (refer to Section 24.2 *TUI Key Bindings*)

run, (refer to Section 6.2 *Starting your program*)

running, (refer to Section 6.2 *Starting your program*)

running and debugging Sparclet programs, (refer to Section 20.3.11.4 *Running and debugging*)

running VxWorks tasks, (refer to Section 20.2.1.3 *Running tasks*)

running, on Sparclet, (refer to Section 20.3.11 *Tsquare Sparclet*)

rwatck, (refer to Section 7.1.2 *Setting watchpoints*)

S

s (SingleKey TUI key), (refer to Section 24.3 *TUI Single Key Mode*)

s (step), (refer to Section 7.2 *Continuing and stepping*)

S packet, (refer to Section D.2 *Packets*)

s packet, (refer to Section D.2 *Packets*)

save tracepoints for future sessions, (refer to Section 12.2.3 *save-tracepoints filename*)

save-tracepoints, (refer to Section 12.2.3 *save-tracepoints filename*)

saving symbol table, (refer to Section 17.1 *Commands to specify files*)

scope, (refer to Section 14.4.3.7 *The scope operators : :and .*)

search, (refer to Section 9.3 *Searching source files*)

searching, (refer to Section 9.3 *Searching source files*)

section, (refer to Section 17.1 *Commands to specify files*)

segment descriptor tables, (refer to Section 20.1.3 *Features for Debugging djgpp Programs*)

select trace snapshot, (refer to Section 12.2.1 *tfind n*)

select-frame, (refer to Section 8.1 *Stack frames*)

selected frame, (refer to Chapter 8 *Examining the Stack*)

selecting frame silently, (refer to Section 8.1 *Stack frames*)

separate debugging information files, (refer to Section 17.2 *Debugging Information in Separate Files*)

sequence-id, for gdb remote, (refer to Section D.1 *Overview*)

serial connections, debugging, (refer to Section 21.8 *Optional messages about internal happenings*)

serial device, Hitachi micros, (refer to Section 20.3.2.1 *Connecting to Hitachi boards*)

serial line speed, Hitachi micros, (refer to Section 20.3.2.1 *Connecting to Hitachi boards*)

serial line, target remote, (refer to Section 19.1 *Connecting to a remote target*)

serial protocol, gdb remote, (refer to Section D.1 *Overview*)

server prefix for annotations, (refer to Section 27.2 *The Server Prefix*)

set, (refer to Section 5.3 *Getting help*)

- set args, (refer to Section 6.3 *Your program's arguments*)
- set auto-solib-add, (refer to Section 17.1 *Commands to specify files*)
- set auto-solib-limit, (refer to Section 17.1 *Commands to specify files*)
- set backtrace-below-main, (refer to Section 8.2 *Backtraces*)
- set charset, (refer to Section 10.15 *Character Sets*)
- set check range, (refer to Section 14.3.2 *An overview of range checking*)
- set check type, (refer to Section 14.3.1 *An overview of type checking*)
- set check, range, (refer to Section 14.3.2 *An overview of range checking*)
- set check, type, (refer to Section 14.3.1 *An overview of type checking*)
- set coerce-float-to-double, (refer to Section 21.6 *Configuring the current ABI*)
- set complaints, (refer to Section 21.7 *Optional warnings and messages*)
- set confirm, (refer to Section 21.7 *Optional warnings and messages*)
- set cp-abi, (refer to Section 21.6 *Configuring the current ABI*)
- set debug arch, (refer to Section 21.8 *Optional messages about internal happenings*)
- set debug event, (refer to Section 21.8 *Optional messages about internal happenings*)
- set debug expression, (refer to Section 21.8 *Optional messages about internal happenings*)
- set debug frame, (refer to Section 21.8 *Optional messages about internal happenings*)
- set debug overload, (refer to Section 21.8 *Optional messages about internal happenings*)
- set debug remote, (refer to Section 21.8 *Optional messages about internal happenings*)
- set debug serial, (refer to Section 21.8 *Optional messages about internal happenings*)
- set debug target, (refer to Section 21.8 *Optional messages about internal happenings*)
- set debug varobj, (refer to Section 21.8 *Optional messages about internal happenings*)
- set debug-file-directory, (refer to Section 17.2 *Debugging Information in Separate Files*)
- set debugevents, (refer to Section 20.1.4 *Features for Debugging MS Windows PE executables*)
- set debugexceptions, (refer to Section 20.1.4 *Features for Debugging MS Windows PE executables*)
- set debugexec, (refer to Section 20.1.4 *Features for Debugging MS Windows PE executables*)
- set debugmemory, (refer to Section 20.1.4 *Features for Debugging MS Windows PE executables*)
- set demangle-style, (refer to Section 10.7 *Print settings*)
- set disassembly-flavor, (refer to Section 9.5 *Source and machine code*)
- set editing, (refer to Section 21.2 *Command editing*)
- set endian auto, (refer to Section 18.3 *Choosing target byte order*)
- set endian big, (refer to Section 18.3 *Choosing target byte order*)
- set endian little, (refer to Section 18.3 *Choosing target byte order*)
- set environment, (refer to Section 6.4 *Your program's environment*)
- set extension-language, (refer to Section 14.2 *Displaying the language*)
- set follow-fork-mode, (refer to Section 6.10 *Debugging programs with multiple processes*)
- set gnutarget, (refer to Section 18.2 *Commands for managing targets*)
- set height, (refer to Section 21.4 *Screen size*)
- set history expansion, (refer to Section 21.3 *Command history*)
- set history filename, (refer to Section 21.3 *Command history*)
- set history save, (refer to Section 21.3 *Command history*)
- set history size, (refer to Section 21.3 *Command history*)
- set host-charset, (refer to Section 10.15 *Character Sets*)
- set input-radix, (refer to Section 21.5 *Numbers*)
- set language, (refer to Section 14.1.2 *Setting the working language*)
- set listsize, (refer to Section 9.1 *Printing source lines*)
- set logging, (refer to Section 4.4 *Logging output*)
- set machine, (refer to Section 20.3.2.3 *Special gdb commands for Hitachi micros*)
- set max-user-call-depth, (refer to Section 22.1 *User-defined commands*)
- set memory mod, (refer to Section 20.3.3 *H8/500*)
- set mipsfpu, (refer to Section 20.3.6 *MIPS Embedded*)
- set new-console, (refer to Section 20.1.4 *Features for Debugging MS Windows PE executables*)
- set new-group, (refer to Section 20.1.4 *Features for Debugging MS Windows PE executables*)
- set opaque-type-resolution, (refer to Chapter 15 *Examining the Symbol Table*)
- set osabi, (refer to Section 21.6 *Configuring the current ABI*)
- set output-radix, (refer to Section 21.5 *Numbers*)
- set overload-resolution, (refer to Section 14.4.1.7 *gdb features for C++*)
- set print address, (refer to Section 10.7 *Print settings*)
- set print array, (refer to Section 10.7 *Print settings*)
- set print asm-demangle, (refer to Section 10.7 *Print settings*)
- set print demangle, (refer to Section 10.7 *Print settings*)

- set print elements, (refer to Section 10.7 *Print settings*)
- set print max-symbolic-offset, (refer to Section 10.7 *Print settings*)
- set print null-stop, (refer to Section 10.7 *Print settings*)
- set print object, (refer to Section 10.7 *Print settings*)
- set print pretty, (refer to Section 10.7 *Print settings*)
- set print sevenbit-strings, (refer to Section 10.7 *Print settings*)
- set print static-members, (refer to Section 10.7 *Print settings*)
- set print symbol-filename, (refer to Section 10.7 *Print settings*)
- set print union, (refer to Section 10.7 *Print settings*)
- set print vtbl, (refer to Section 10.7 *Print settings*)
- set processor `args`, (refer to Section 20.3.6 *MIPS Embedded*)
- set prompt, (refer to Section 21.1 *Prompt*)
- set remote hardware-breakpoint-limit, (refer to Section 19.4 *Remote configuration*)
- set remote hardware-watchpoint-limit, (refer to Section 19.4 *Remote configuration*)
- set remote system-call-allowed 0, (refer to Section D.7.9 *The system(3) call*)
- set remote system-call-allowed 1, (refer to Section D.7.9 *The system(3) call*)
- set remotedebug, MIPS protocol, (refer to Section 20.3.6 *MIPS Embedded*)
- set retransmit-timeout, (refer to Section 20.3.6 *MIPS Embedded*)
- set `rstack_high_address`, (refer to Section 20.4.1 *A29K*)
- set shell, (refer to Section 20.1.4 *Features for Debugging MS Windows PE executables*)
- set solib-absolute-prefix, (refer to Section 17.1 *Commands to specify files*)
- set solib-search-path, (refer to Section 17.1 *Commands to specify files*)
- set step-mode, (refer to Section 7.2 *Continuing and stepping*)
- set symbol-reloading, (refer to Chapter 15 *Examining the Symbol Table*)
- set target-charset, (refer to Section 10.15 *Character Sets*)
- set timeout, (refer to Section 20.3.6 *MIPS Embedded*)
- set tracepoint, (refer to Section 12.1.1 *Create and Delete Tracepoints*)
- set trust-readonly-sections, (refer to Section 17.1 *Commands to specify files*)
- set tui active-border-mode, (refer to Section 24.5 *TUI configuration variables*)
- set tui border-kind, (refer to Section 24.5 *TUI configuration variables*)
- set tui border-mode, (refer to Section 24.5 *TUI configuration variables*)
- set variable, (refer to Section 16.1 *Assignment to variables*)
- set verbose, (refer to Section 21.7 *Optional warnings and messages*)
- set width, (refer to Section 21.4 *Screen size*)
- set write, (refer to Section 16.6 *Patching programs*)
- set_debug_traps, (refer to Section 19.5.1 *What the stub can do for you*)
- setting variables, (refer to Section 16.1 *Assignment to variables*)
- setting watchpoints, (refer to Section 7.1.2 *Setting watchpoints*)
- SH, (refer to Section 19.5 *Implementing a remote stub*)
- `sh-stub.c`, (refer to Section 19.5 *Implementing a remote stub*)
- share, (refer to Section 17.1 *Commands to specify files*)
- shared libraries, (refer to Section 17.1 *Commands to specify files*)
- sharedlibrary, (refer to Section 17.1 *Commands to specify files*)
- shell, (refer to Section 4.3 *Shell commands*)
- shell escape, (refer to Section 4.3 *Shell commands*)
- show, (refer to Section 5.3 *Getting help*)
- show args, (refer to Section 6.3 *Your program's arguments*)
- show auto-solib-add, (refer to Section 17.1 *Commands to specify files*)
- show auto-solib-limit, (refer to Section 17.1 *Commands to specify files*)
- show backtrace-below-main, (refer to Section 8.2 *Backtraces*)
- show charset, (refer to Section 10.15 *Character Sets*)
- show check range, (refer to Section 14.3.2 *An overview of range checking*)
- show check type, (refer to Section 14.3.1 *An overview of type checking*)
- show complaints, (refer to Section 21.7 *Optional warnings and messages*)
- show confirm, (refer to Section 21.7 *Optional warnings and messages*)
- show convenience, (refer to Section 10.9 *Convenience variables*)
- show copying, (refer to Section 5.3 *Getting help*)
- show cp-abi, (refer to Section 21.6 *Configuring the current ABI*)
- show debug arch, (refer to Section 21.8 *Optional messages about internal happenings*)
- show debug event, (refer to Section 21.8 *Optional messages about internal happenings*)
- show debug expression, (refer to Section 21.8 *Optional messages about internal happenings*)
- show debug frame, (refer to Section 21.8 *Optional messages about internal happenings*)
- show debug overload, (refer to Section 21.8 *Optional messages about internal happenings*)
- show debug remote, (refer to Section 21.8 *Optional messages about internal happenings*)

- show debug serial, (refer to Section 21.8 *Optional messages about internal happenings*)
- show debug target, (refer to Section 21.8 *Optional messages about internal happenings*)
- show debug varobj, (refer to Section 21.8 *Optional messages about internal happenings*)
- show debug-file-directory, (refer to Section 17.2 *Debugging Information in Separate Files*)
- show demangle-style, (refer to Section 10.7 *Print settings*)
- show directories, (refer to Section 9.4 *Specifying source directories*)
- show editing, (refer to Section 21.2 *Command editing*)
- show environment, (refer to Section 6.4 *Your program's environment*)
- show gnutarget, (refer to Section 18.2 *Commands for managing targets*)
- show height, (refer to Section 21.4 *Screen size*)
- show history, (refer to Section 21.3 *Command history*)
- show host-charset, (refer to Section 10.15 *Character Sets*)
- show input-radix, (refer to Section 21.5 *Numbers*)
- show language, (refer to Section 14.2 *Displaying the language*)
- show listsize, (refer to Section 9.1 *Printing source lines*)
- show logging, (refer to Section 4.4 *Logging output*)
- show machine, (refer to Section 20.3.2.3 *Special gdb commands for Hitachi micros*)
- show max-user-call-depth, (refer to Section 22.1 *User-defined commands*)
- show mipsfpu, (refer to Section 20.3.6 *MIPS Embedded*)
- show new-console, (refer to Section 20.1.4 *Features for Debugging MS Windows PE executables*)
- show new-group, (refer to Section 20.1.4 *Features for Debugging MS Windows PE executables*)
- show opaque-type-resolution, (refer to Chapter 15 *Examining the Symbol Table*)
- show osabi, (refer to Section 21.6 *Configuring the current ABI*)
- show output-radix, (refer to Section 21.5 *Numbers*)
- show paths, (refer to Section 6.4 *Your program's environment*)
- show print address, (refer to Section 10.7 *Print settings*)
- show print array, (refer to Section 10.7 *Print settings*)
- show print asm-demangle, (refer to Section 10.7 *Print settings*)
- show print demangle, (refer to Section 10.7 *Print settings*)
- show print elements, (refer to Section 10.7 *Print settings*)
- show print max-symbolic-offset, (refer to Section 10.7 *Print settings*)
- show print object, (refer to Section 10.7 *Print settings*)
- show print pretty, (refer to Section 10.7 *Print settings*)
- show print sevenbit-strings, (refer to Section 10.7 *Print settings*)
- show print static-members, (refer to Section 10.7 *Print settings*)
- show print symbol-filename, (refer to Section 10.7 *Print settings*)
- show print union, (refer to Section 10.7 *Print settings*)
- show print vtbl, (refer to Section 10.7 *Print settings*)
- show processor, (refer to Section 20.3.6 *MIPS Embedded*)
- show prompt, (refer to Section 21.1 *Prompt*)
- show remote system-call-allowed, (refer to Section D.7.9 *The system(3) call*)
- show remotedebug, MIPS protocol, (refer to Section 20.3.6 *MIPS Embedded*)
- show retransmit-timeout, (refer to Section 20.3.6 *MIPS Embedded*)
- show rstack_high_address, (refer to Section 20.4.1 *A29K*)
- show shell, (refer to Section 20.1.4 *Features for Debugging MS Windows PE executables*)
- show solib-absolute-prefix, (refer to Section 17.1 *Commands to specify files*)
- show solib-search-path, (refer to Section 17.1 *Commands to specify files*)
- show symbol-reloading, (refer to Chapter 15 *Examining the Symbol Table*)
- show target-charset, (refer to Section 10.15 *Character Sets*)
- show timeout, (refer to Section 20.3.6 *MIPS Embedded*)
- show user, (refer to Section 22.1 *User-defined commands*)
- show values, (refer to Section 10.8 *Value history*)
- show verbose, (refer to Section 21.7 *Optional warnings and messages*)
- show version, (refer to Section 5.3 *Getting help*)
- show warranty, (refer to Section 5.3 *Getting help*)
- show width, (refer to Section 21.4 *Screen size*)
- show write, (refer to Section 16.6 *Patching programs*)
- show-all-if-ambiguous, (refer to Section 29.3.1 *Readline Init File Syntax*)
- shows, (refer to Section 21.3 *Command history*)
- si (stepi), (refer to Section 7.2 *Continuing and stepping*)
- signal, (refer to Section 16.3 *Giving your program a signal*)
- signal, (refer to Section 27.10 *Running the Program*)
- signal-handler-caller, (refer to Section 27.4 *Frames*)
- signal-name, (refer to Section 27.10 *Running the Program*)
- signal-name-end, (refer to Section 27.10 *Running the Program*)
- signal-string, (refer to Section 27.10 *Running the Program*)

- signal-string-end, (refer to Section 27.10 *Running the Program*)
- signalled, (refer to Section 27.10 *Running the Program*)
- signals, (refer to Section 7.3 *Signals*)
- silent, (refer to Section 7.1.7 *Breakpoint command lists*)
- sim, (refer to Section 20.3.14 *Zilog Z8000*)
- simulator, Z8000, (refer to Section 20.3.14 *Zilog Z8000*)
- size of screen, (refer to Section 21.4 *Screen size*)
- software watchpoints, (refer to Section 7.1.2 *Setting watchpoints*)
- source, (refer to Section 27.11 *Displaying Source*)
- source, (refer to Section 22.3 *Command files*)
- source path, (refer to Section 9.4 *Specifying source directories*)
- Sparc, (refer to Section 19.5 *Implementing a remote stub*)
- sparc-stub.c, (refer to Section 19.5 *Implementing a remote stub*)
- sparcl-stub.c, (refer to Section 19.5 *Implementing a remote stub*)
- Sparclet, (refer to Section 20.3.11 *Tsquare Sparclet*)
- SparcLite, (refer to Section 19.5 *Implementing a remote stub*)
- speed, (refer to Section 20.3.2.1 *Connecting to Hitachi boards*)
- spr, (refer to Section 20.3.7 *OpenRISC 1000*)
- ST2000 auxiliary commands, (refer to Section 20.3.13 *Tandem ST2000*)
- st2000 cmd, (refer to Section 20.3.13 *Tandem ST2000*)
- stack frame, (refer to Section 8.1 *Stack frames*)
- stack on Alpha, (refer to Section 20.4.3 *MIPS*)
- stack on MIPS, (refer to Section 20.4.3 *MIPS*)
- stack traces, (refer to Section 8.2 *Backtraces*)
- stacking targets, (refer to Section 18.1 *Active targets*)
- start a new trace experiment, (refer to Section 12.1.6 *Starting and Stopping Trace Experiment*)
- starting, (refer to Section 6.2 *Starting your program*)
- starting, (refer to Section 27.10 *Running the Program*)
- stat, file-i/o system call, (refer to Section D.7.10.8 *stat/fstat*)
- status of trace data collection, (refer to Section 12.1.6 *Starting and Stopping Trace Experiment*)
- status output in gdb/mi, (refer to Section 26.4.2 *gdb/mi Output Syntax*)
- STDEBUG commands (ST2000), (refer to Section 20.3.13 *Tandem ST2000*)
- step, (refer to Section 7.2 *Continuing and stepping*)
- stepi, (refer to Section 7.2 *Continuing and stepping*)
- stepping, (refer to Section 7.2 *Continuing and stepping*)
- stepping into functions with no line info, (refer to Section 7.2 *Continuing and stepping*)
- stop a running trace experiment, (refer to Section 12.1.6 *Starting and Stopping Trace Experiment*)
- stop reply packets, (refer to Section D.3 *Stop Reply Packets*)
- stop, a pseudo-command, (refer to Section 22.2 *User-defined command hooks*)
- stopped threads, (refer to Section 7.4 *Stopping and starting multi-thread programs*)
- stopping, (refer to Section 27.10 *Running the Program*)
- stream records in gdb/mi, (refer to Section 26.6.2 *gdb/mi Stream Records*)
- struct stat, in file-i/o protocol, (refer to Section D.7.11.3 *struct stat*)
- struct timeval, in file-i/o protocol, (refer to Section D.7.11.4 *struct timeval*)
- stub example, remote debugging, (refer to Section 19.5 *Implementing a remote stub*)
- stupid questions, (refer to Section 21.7 *Optional warnings and messages*)
- switching threads, (refer to Section 6.9 *Debugging programs with multiple threads*)
- switching threads automatically, (refer to Section 6.9 *Debugging programs with multiple threads*)
- symbol decoding style, C++, (refer to Section 10.7 *Print settings*)
- symbol dump, (refer to Chapter 15 *Examining the Symbol Table*)
- symbol from address, (refer to Chapter 15 *Examining the Symbol Table*)
- symbol names, (refer to Chapter 15 *Examining the Symbol Table*)
- symbol overloading, (refer to Section 7.1.8 *Breakpoint menus*)
- symbol table, (refer to Section 17.1 *Commands to specify files*)
- symbol tables, listing gdb's internal, (refer to Chapter 15 *Examining the Symbol Table*)
- symbol-file, (refer to Section 17.1 *Commands to specify files*)
- symbols, reading from relocatable object files, (refer to Section 17.1 *Commands to specify files*)
- symbols, reading immediately, (refer to Section 17.1 *Commands to specify files*)
- sysinfo, (refer to Section 20.1.3 *Features for Debugging djgpp Programs*)
- system call, file-i/o protocol, (refer to Section D.7.9 *The system(3) call*)
- system, file-i/o system call, (refer to Section D.7.10.11 *system*)
- t packet, (refer to Section D.2 *Packets*)
- T packet, (refer to Section D.2 *Packets*)
- T packet reply, (refer to Section D.3 *Stop Reply Packets*)

T

target, (refer to Chapter 18 *Specifying a Debugging Target*)

target abug, (refer to Section 20.3.5 *M68k*)

target array, (refer to Section 20.3.6 *MIPS Embedded*)

target byte order, (refer to Section 18.3 *Choosing target byte order*)

target character set, (refer to Section 10.15 *Character Sets*)

target core, (refer to Section 18.2 *Commands for managing targets*)

target cpu32bug, (refer to Section 20.3.5 *M68k*)

target dbug, (refer to Section 20.3.5 *M68k*)

target `ddb port`, (refer to Section 20.3.6 *MIPS Embedded*)

target dink32, (refer to Section 20.3.8 *PowerPC*)

target e7000, with H8/300, (refer to Section 20.3.2 *Hitachi H8/300*)

target e7000, with Hitachi ICE, (refer to Section 20.3.2.2 *Using the E7000 in-circuit emulator*)

target e7000, with Hitachi SH, (refer to Section 20.3.10 *Hitachi SH*)

target est, (refer to Section 20.3.5 *M68k*)

target exec, (refer to Section 18.2 *Commands for managing targets*)

target hms, and serial protocol, (refer to Section 20.3.2.1 *Connecting to Hitachi boards*)

target hms, with H8/300, (refer to Section 20.3.2 *Hitachi H8/300*)

target hms, with Hitachi SH, (refer to Section 20.3.10 *Hitachi SH*)

target jtag, (refer to Section 20.3.7 *OpenRISC 1000*)

target lsi `port`, (refer to Section 20.3.6 *MIPS Embedded*)

target m32r, (refer to Section 20.3.4 *Mitsubishi M32R/D*)

target mips `port`, (refer to Section 20.3.6 *MIPS Embedded*)

target nrom, (refer to Section 18.2 *Commands for managing targets*)

target op50n, (refer to Section 20.3.9 *HP PA Embedded*)

target output in `gdb/mi`, (refer to Section 26.4.2 *gdb/mi Output Syntax*)

target pmon `port`, (refer to Section 20.3.6 *MIPS Embedded*)

target ppcbug, (refer to Section 20.3.8 *PowerPC*)

target ppcbug1, (refer to Section 20.3.8 *PowerPC*)

target r3900, (refer to Section 20.3.6 *MIPS Embedded*)

target rdi, (refer to Section 20.3.1 *ARM*)

target rdp, (refer to Section 20.3.1 *ARM*)

target remote, (refer to Section 18.2 *Commands for managing targets*)

target rom68k, (refer to Section 20.3.5 *M68k*)

target rombug, (refer to Section 20.3.5 *M68k*)

target sds, (refer to Section 20.3.8 *PowerPC*)

target sh3, with H8/300, (refer to Section 20.3.2 *Hitachi H8/300*)

target sh3, with SH, (refer to Section 20.3.10 *Hitachi SH*)

target sh3e, with H8/300, (refer to Section 20.3.2 *Hitachi H8/300*)

target sh3e, with SH, (refer to Section 20.3.10 *Hitachi SH*)

target sim, (refer to Section 18.2 *Commands for managing targets*)

target sim, with Z8000, (refer to Section 20.3.14 *Zilog Z8000*)

target sparclite, (refer to Section 20.3.12 *Fujitsu Sparclite*)

target vxworks, (refer to Section 20.2.1 *Using gdb with VxWorks*)

target w89k, (refer to Section 20.3.9 *HP PA Embedded*)

tbreak, (refer to Section 7.1.1 *Setting breakpoints*)

TCP port, target `remote`, (refer to Section 19.1 *Connecting to a remote target*)

tdump, (refer to Section 12.2.2 *tdump*)

terminal, (refer to Section 6.6 *Your program's input and output*)

tfind, (refer to Section 12.2.1 *tfind n*)

thbreak, (refer to Section 7.1.1 *Setting breakpoints*)

this, inside C++ member functions, (refer to Section 14.4.1.3 *C++ expressions*)

thread apply, (refer to Section 6.9 *Debugging programs with multiple threads*)

thread breakpoints, (refer to Section 7.4 *Stopping and starting multi-thread programs*)

thread identifier (GDB), (refer to Section 6.9 *Debugging programs with multiple threads*)

thread identifier (system), (refer to Section 6.9 *Debugging programs with multiple threads*)

thread identifier (system), on HP-UX, (refer to Section 6.9 *Debugging programs with multiple threads*)

thread number, (refer to Section 6.9 *Debugging programs with multiple threads*)

thread `threadno`, (refer to Section 6.9 *Debugging programs with multiple threads*)

threads and watchpoints, (refer to Section 7.1.2 *Setting watchpoints*)

threads of execution, (refer to Section 6.9 *Debugging programs with multiple threads*)

threads, automatic switching, (refer to Section 6.9 *Debugging programs with multiple threads*)

threads, continuing, (refer to Section 7.4 *Stopping and starting multi-thread programs*)

threads, stopped, (refer to Section 7.4 *Stopping and starting multi-thread programs*)

`timeout`, MIPS protocol, (refer to Section 20.3.6 *MIPS Embedded*)

trace, (refer to Section 12.1.1 *Create and Delete Tracepoints*)
 trace experiment, status of, (refer to Section 12.1.6 *Starting and Stopping Trace Experiment*)
 tracebacks, (refer to Section 8.2 *Backtraces*)
 tracepoint actions, (refer to Section 12.1.4 *Tracepoint Action Lists*)
 tracepoint data, display, (refer to Section 12.2.2 *tdump*)
 tracepoint deletion, (refer to Section 12.1.1 *Create and Delete Tracepoints*)
 tracepoint number, (refer to Section 12.1.1 *Create and Delete Tracepoints*)
 tracepoint pass count, (refer to Section 12.1.3 *Tracepoint Passcounts*)
 tracepoint variables, (refer to Section 12.3 *Convenience Variables for Tracepoints*)
 tracepoints, (refer to Chapter 12 *Tracepoints*)
 translating between character sets, (refer to Section 10.15 *Character Sets*)
 tstart, (refer to Section 12.1.6 *Starting and Stopping Trace Experiment*)
 tstatus, (refer to Section 12.1.6 *Starting and Stopping Trace Experiment*)
 tstop, (refer to Section 12.1.6 *Starting and Stopping Trace Experiment*)
 tty, (refer to Section 6.6 *Your program's input and output*)
 TUI, (refer to Chapter 24 *gdb Text User Interface*)
 TUI commands, (refer to Section 24.4 *TUI specific commands*)
 TUI configuration variables, (refer to Section 24.5 *TUI configuration variables*)
 TUI key bindings, (refer to Section 24.2 *TUI Key Bindings*)
 TUI single key mode, (refer to Section 24.3 *TUI Single Key Mode*)
 type casting memory, (refer to Section 10.1 *Expressions*)
 type checking, (refer to Section 14.3 *Type and range checking*)
 type conversions in C++, (refer to Section 14.4.1.3 *C++expressions*)

U

u (SingleKey TUI key), (refer to Section 24.3 *TUI Single Key Mode*)
 u (until), (refer to Section 7.2 *Continuing and stepping*)
 UDP port, target remote, (refer to Section 19.1 *Connecting to a remote target*)
 undisplay, (refer to Section 10.6 *Automatic display*)
 unknown address, locating, (refer to Section 10.4 *Output formats*)

unlink, file-i/o system call, (refer to Section D.7.10.7 *unlink*)
 unmap an overlay, (refer to Section 13.2 *Overlay Commands*)
 unmapped overlays, (refer to Section 13.1 *How Overlays Work*)
 unset environment, (refer to Section 6.4 *Your program's environment*)
 unsupported languages, (refer to Section 14.5 *Unsupported languages*)
 until, (refer to Section 7.2 *Continuing and stepping*)
 Up, (refer to Section 24.2 *TUI Key Bindings*)
 up, (refer to Section 8.3 *Selecting a frame*)
 up-silently, (refer to Section 8.3 *Selecting a frame*)
 update, (refer to Section 24.4 *TUI specific commands*)
 user-defined command, (refer to Section 22.1 *User-defined commands*)
 user-defined macros, (refer to Chapter 11 *C Preprocessor Macros*)

V

v (SingleKey TUI key), (refer to Section 24.3 *TUI Single Key Mode*)
 value history, (refer to Section 10.8 *Value history*)
 value-begin, (refer to Section 27.3 *Values*)
 value-end, (refer to Section 27.3 *Values*)
 value-history-begin, (refer to Section 27.3 *Values*)
 value-history-end, (refer to Section 27.3 *Values*)
 value-history-value, (refer to Section 27.3 *Values*)
 variable name conflict, (refer to Section 10.2 *Program variables*)
 variable objects in gdb/mi, (refer to Section 26.18 *gdb/mi Variable Objects*)
 variable values, wrong, (refer to Section 10.2 *Program variables*)
 variables, readline, (refer to Section 29.3.1 *Readline Init File Syntax*)
 variables, setting, (refer to Section 16.1 *Assignment to variables*)
 vector unit, (refer to Section 10.12 *Vector Unit*)
 version number, (refer to Section 5.3 *Getting help*)
 visible-stats, (refer to Section 29.3.1 *Readline Init File Syntax*)
 VxWorks, (refer to Section 20.2.1 *Using gdb with VxWorks*)
 vxworks-timeout, (refer to Section 20.2.1 *Using gdb with VxWorks*)

W

w (SingleKey TUI key), (refer to Section 24.3 *TUI Single Key Mode*)
 watch, (refer to Section 7.1.2 *Setting watchpoints*)
 watchpoint, (refer to Section 27.10 *Running the Program*)
 watchpoints, (refer to Section 7.1 *Breakpoints, watchpoints, and catchpoints*)
 watchpoints and threads, (refer to Section 7.1.2 *Setting watchpoints*)
 whatis, (refer to Chapter 15 *Examining the Symbol Table*)
 where, (refer to Section 8.2 *Backtraces*)
 while, (refer to Section 22.1 *User-defined commands*)
 while-stepping (tracepoints), (refer to Section 12.1.4 *Tracepoint Action Lists*)
 wild pointer, interpreting, (refer to Section 10.7 *Print settings*)
 winheight, (refer to Section 24.4 *TUI specific commands*)
 word completion, (refer to Section 5.2 *Command completion*)
 working directory, (refer to Section 9.4 *Specifying source directories*)
 working directory (of your program), (refer to Section 6.5 *Your program's working directory*)
 working language, (refer to Chapter 14 *Using gdb with Different Languages*)
 write, file-i/o system call, (refer to Section D.7.10.4 *write*)
 writing into corefiles, (refer to Section 16.6 *Patching programs*)
 writing into executables, (refer to Section 16.6 *Patching programs*)
 wrong values, (refer to Section 10.2 *Program variables*)

X

x (examine memory), (refer to Section 10.5 *Examining memory*)
 x packet, (refer to Section D.2 *Packets*)
 x(examine), and info line, (refer to Section 9.5 *Source and machine code*)

Y

yanking text, (refer to Section 29.2.3 *Readline Killing Commands*)
 z packet, (refer to Section D.2 *Packets*)
 Z packets, (refer to Section D.2 *Packets*)
 Z0 packet, (refer to Section D.2 *Packets*)
 z0 packet, (refer to Section D.2 *Packets*)
 Z1 packet, (refer to Section D.2 *Packets*)

z1 packet, (refer to Section D.2 *Packets*)
 Z2 packet, (refer to Section D.2 *Packets*)
 z2 packet, (refer to Section D.2 *Packets*)
 Z3 packet, (refer to Section D.2 *Packets*)
 z3 packet, (refer to Section D.2 *Packets*)
 Z4 packet, (refer to Section D.2 *Packets*)
 z4 packet, (refer to Section D.2 *Packets*)

Z

Z8000, (refer to Section 20.3.14 *Zilog Z8000*)
 Zilog Z8000 simulator, (refer to Section 20.3.14 *Zilog Z8000*)
 {type}, (refer to Section 10.1 *Expressions*)

