



Red Hat OpenStack Platform 10 DNS-as-a-Service Guide

Integrate DNS Management with Red Hat OpenStack Platform

OpenStack Team

Red Hat OpenStack Platform 10 DNS-as-a-Service Guide

Integrate DNS Management with Red Hat OpenStack Platform

OpenStack Team
rhos-docs@redhat.com

Legal Notice

Copyright © 2017 Red Hat, Inc.

The text of and illustrations in this document are licensed by Red Hat under a Creative Commons Attribution–Share Alike 3.0 Unported license ("CC-BY-SA"). An explanation of CC-BY-SA is available at

<http://creativecommons.org/licenses/by-sa/3.0/>

. In accordance with CC-BY-SA, if you distribute this document or an adaptation of it, you must provide the URL for the original version.

Red Hat, as the licensor of this document, waives the right to enforce, and agrees not to assert, Section 4d of CC-BY-SA to the fullest extent permitted by applicable law.

Red Hat, Red Hat Enterprise Linux, the Shadowman logo, JBoss, OpenShift, Fedora, the Infinity logo, and RHCE are trademarks of Red Hat, Inc., registered in the United States and other countries.

Linux ® is the registered trademark of Linus Torvalds in the United States and other countries.

Java ® is a registered trademark of Oracle and/or its affiliates.

XFS ® is a trademark of Silicon Graphics International Corp. or its subsidiaries in the United States and/or other countries.

MySQL ® is a registered trademark of MySQL AB in the United States, the European Union and other countries.

Node.js ® is an official trademark of Joyent. Red Hat Software Collections is not formally related to or endorsed by the official Joyent Node.js open source or commercial project.

The OpenStack ® Word Mark and OpenStack logo are either registered trademarks/service marks or trademarks/service marks of the OpenStack Foundation, in the United States and other countries and are used with the OpenStack Foundation's permission. We are not affiliated with, endorsed or sponsored by the OpenStack Foundation, or the OpenStack community.

All other trademarks are the property of their respective owners.

Abstract

A guide for integrating DNS with Red Hat OpenStack Platform.

Table of Contents

CHAPTER 1. OVERVIEW OF DNSAAS	3
1.1. TOPICS COVERED IN THIS GUIDE	3
1.2. DNSAAS PREREQUISITES	3
1.3. DNSAAS SERVICES	3
1.4. DNSAAS INTEGRATION WITH COMPUTE AND OPENSTACK NETWORKING	4
CHAPTER 2. MANUAL DNSAAS INSTALLATION	5
CHAPTER 3. INSTALL AND CONFIGURE BIND9	10
3.1. BASIC BIND INSTALLATION	10
3.2. CONFIGURE BIND	10
3.3. CONFIGURE THE DNSAAS POOL TARGET FOR BIND	11
3.4. TEST BIND	11
3.5. TEST DNSAAS INTEGRATION WITH BIND9	12
3.6. CONFIGURE AUTO-GENERATION OF DNS RECORDS (NOVA FIXED AND NEUTRON FLOATING)	12
3.7. TEST OPENSTACK NETWORKING FLOATING IP RECORD CREATION	13
3.8. CLEANUP OPENSTACK NETWORKING AND COMPUTE DNS ENTRIES	13

CHAPTER 1. OVERVIEW OF DNSAAS

Red Hat OpenStack Platform 10 includes a Technology Preview of DNS-as-a-Service (DNSaaS), also known as Designate. DNSaaS includes a REST API for domain and record management, is multi-tenanted, and integrates with OpenStack Identity Service (*keystone*) for authentication. DNSaaS includes a framework for integration with Compute (*nova*) and OpenStack Networking (*neutron*) notifications, allowing auto-generated DNS records. In addition, DNSaaS includes integration support for Bind9.

1.1. TOPICS COVERED IN THIS GUIDE

- ✦ Manual DNSaaS installation steps, as DNSaaS is not currently included in Director deployment.
- ✦ Managing and configuring DNSaaS from the command line interface.
- ✦ Integration with Bind9, including auto-creation of instance records.

1.2. DNSAAS PREREQUISITES

- ✦ A fully functioning OpenStack Networking-based, non-HA OpenStack environment.
- ✦ An OpenStack Image Service (*glance*) image loaded, for testing auto-creation.

1.3. DNSAAS SERVICES

A deployment of DNSaaS includes the following components:

designate-api	Provides an OpenStack-native REST API.
designate-central	Handles requests and coordinates storage in the mysql database.
designate-mdns	A small MiniDNS server used only to communicate with other DNS servers over standard DNS protocol.
designate-pool-manager	Manages the states of the DNS servers that DNSaaS manages. Ensures the backend DNS servers are in sync with DNSaaS.
designate-sink	An optional service that is used to listen to nova and neutron notification events to trigger automatic record creation/deletion.

designate-agentUsed for DNS servers that cannot accept zone transfers (*AXFR*). Not needed for BIND backends.**Note**

The **zone-manager** service is expected to be added in the next major release. It will run periodic tasks on zones to provide a mechanism for identifying lost events.

1.4. DNSaaS INTEGRATION WITH COMPUTE AND OPENSTACK NETWORKING

DNSaaS record management begins when the **designate-sink** service sends a message to **designate-central**, which then triggers the workflow described below:

- 1. designate-sink** receives an *instance boot/delete* event from Compute, or a *floating IP add/remove* event from OpenStack Networking. These events are sent using the OpenStack message bus.
- 2. designate-sink** constructs the FQDN of the host from the VM name and the configured domain ID (see below).
- 3. designate-sink** tells **designate-central** to add/delete the record with the given name and IP address.
- 4. designate-central** adds/deletes the record in the DNSaaS database (shared between **designate-central** and **designate-mdns**).
- 5. designate-central** tells **designate-pool-manager** to send a **DNS NOTIFY** to the backend DNS server (BIND9) for this domain.
- The backend DNS servers receive the **DNS NOTIFY** and send an **AXFR** (zone transfer) request to **designate-mdns**.
- 7. designate-mdns** reads the changes from the database and sends them to the backend DNS servers in the **AXFR** response.

CHAPTER 2. MANUAL DNSaaS INSTALLATION

1. Install the DNSaaS packages on the *controller* node:

```
# yum install openstack-designate-api openstack-designate-central
openstack-designate-sink openstack-designate-pool-manager openstack-
designate-mdns openstack-designate-common python-designate python-
designateclient openstack-designate-agent
```

2. Create the DNSaaS and Pool Manager databases. Update the **IDENTIFIED BY** '**ComplexAlphanumericPassword**' value to suit your environment.

```
# mysql -u root << EOF
CREATE DATABASE designate;
GRANT ALL ON designate.* TO 'designate'@'%' IDENTIFIED BY
'ComplexAlphanumericPassword';
GRANT ALL ON designate.* TO 'designate'@'localhost' IDENTIFIED BY
'ComplexAlphanumericPassword';
CREATE DATABASE designate_pool_manager;
GRANT ALL ON designate_pool_manager.* TO 'designate'@'%' IDENTIFIED BY
'ComplexAlphanumericPassword';
GRANT ALL ON designate_pool_manager.* TO 'designate'@'localhost'
IDENTIFIED BY 'ComplexAlphanumericPassword';
FLUSH PRIVILEGES;
quit
EOF
```

3. Create the DNSaaS service accounts and endpoint in OpenStack Identity (keystone): This example uses the DNSaaS host IP address **192.168.100.20**. You will likely need to update these steps to suit your environment.

```
# openstack user create designate --password
ComplexAlphanumericPassword --email designate@localhost
# openstack role add --project services --user designate admin
# openstack service create dns --name designate --description
"Designate DNS Service"
# openstack endpoint create --region RegionOne designate public
http://192.168.100.20:9001
# openstack endpoint create --region RegionOne designate admin
http://192.168.100.20:9001
# openstack endpoint create --region RegionOne designate internal
http://192.168.100.20:9001
```

4. Add firewall rules for DNSaaS:

```
# iptables -I INPUT -p tcp -m multiport --dports 9001 -m comment --
comment "designate incoming" -j ACCEPT
# iptables -I INPUT -p tcp -m multiport --dports 5354 -m comment --
comment "Designate mdns incoming" -j ACCEPT
```

If hosting DNS locally, check that the required ports are open:

```
# iptables -I INPUT -p tcp -m multiport --dports 953 -m comment --
comment "rndc incoming - bind only" -j ACCEPT
# service iptables save; service iptables restart
```

5. Configure the DNSaaS database connection: Be sure to enter your DNSaaS host IP address correctly in the steps below; replace **ComplexAlphanumericPassword** with the value that aligns with your environment.

```
# openstack-config --set /etc/designate/designate.conf
storage:sqlalchemy connection
mysql://designate:ComplexAlphanumericPassword@192.168.100.20/designate
# openstack-config --set /etc/designate/designate.conf
storage:sqlalchemy max_retries -1
# openstack-config --set /etc/designate/designate.conf
pool_manager_cache:sqlalchemy connection
mysql://designate:ComplexAlphanumericPassword@192.168.100.20/designate_
pool_manager
# openstack-config --set /etc/designate/designate.conf
pool_manager_cache:sqlalchemy max_retries -1
```

6. Configure authentication to the Identity Service (*keystone*): Make certain that the **admin_password** option aligns with your environment.

```
# openstack-config --set /etc/designate/designate.conf
keystone_authtoken auth_uri http://192.168.100.20:5000/v2.0
# openstack-config --set /etc/designate/designate.conf
keystone_authtoken identity_uri http://192.168.100.20:35357/
# openstack-config --set /etc/designate/designate.conf
keystone_authtoken admin_tenant_name services
# openstack-config --set /etc/designate/designate.conf
keystone_authtoken admin_user designate
# openstack-config --set /etc/designate/designate.conf
keystone_authtoken admin_password ComplexAlphanumericPassword
```

7. Configure the DNSaaS connection to RabbitMQ:

Make certain the **rabbit_userid** and **rabbit_password** options align with your environment.

```
# openstack-config --set /etc/designate/designate.conf
oslo_messaging_rabbit rabbit_hosts 192.168.100.20:5672
# openstack-config --set /etc/designate/designate.conf
oslo_messaging_rabbit rabbit_ha_queues False
# openstack-config --set /etc/designate/designate.conf
oslo_messaging_rabbit rabbit_host 192.168.100.20
# openstack-config --set /etc/designate/designate.conf
oslo_messaging_rabbit rabbit_port 5672
# openstack-config --set /etc/designate/designate.conf
oslo_messaging_rabbit rabbit_userid amqp_user
# openstack-config --set /etc/designate/designate.conf
oslo_messaging_rabbit rabbit_password ComplexAlphanumericPassword
# openstack-config --set /etc/designate/designate.conf
oslo_messaging_rabbit rabbit_virtual_host /
```

8. Add the initial DNSaaS configuration:

```
# openstack-config --set /etc/designate/designate.conf DEFAULT
notification_driver nova.openstack.common.notifier.rpc_notifier
# openstack-config --set /etc/designate/designate.conf DEFAULT
notification_driver messaging
# openstack-config --set /etc/designate/designate.conf DEFAULT
notification_topics notifications_designate
# openstack-config --set /etc/designate/designate.conf service:api
api_host 0.0.0.0
# openstack-config --set /etc/designate/designate.conf service:api
api_port 9001
# openstack-config --set /etc/designate/designate.conf service:api
auth_strategy keystone
# openstack-config --set /etc/designate/designate.conf service:api
enable_api_v1 True
# openstack-config --set /etc/designate/designate.conf service:api
enabled_extensions_v1 "diagnostics, quotas, reports, sync, touch"
# openstack-config --set /etc/designate/designate.conf service:api
enable_api_v2 True
# openstack-config --set /etc/designate/designate.conf service:api
enabled_extensions_v2 "quotas, reports"
```

9. Configure the pool manager:



Note

At present, you will not yet configure a pool target as you have not selected a backend. That occurs later in this procedure.

The **pool_id** is hardcoded, so use the **UUID** shown below:

```
# pool_id=794ccc2c-d751-44fe-b57f-8894c9f5c842
# nameserver_id=$(uuidgen)
# target_id=$(uuidgen)
# openstack-config --set /etc/designate/designate.conf
service:pool_manager pool_id $pool_id
# openstack-config --set /etc/designate/designate.conf pool:$pool_id
nameservers $nameserver_id
# openstack-config --set /etc/designate/designate.conf pool:$pool_id
targets $target_id
# openstack-config --set /etc/designate/designate.conf
pool_nameserver:$nameserver_id port 53
# openstack-config --set /etc/designate/designate.conf
pool_nameserver:$nameserver_id host 192.168.100.20
```

10. Configure the DNSaaS Sink:



Note

For now, you will not configure the domain used by sink (as it does not exist yet).

```
# openstack-config --set /etc/designate/designate.conf service:sink
enabled_notification_handlers "nova_fixed, neutron_floatingip"
```

```
# openstack-config --set /etc/designate/designate.conf
handler:nova_fixed notification_topics notifications_designate
# openstack-config --set /etc/designate/designate.conf
handler:nova_fixed control_exchange nova
# openstack-config --set /etc/designate/designate.conf
handler:nova_fixed format "%(display_name)s.%(domain)s"
# openstack-config --set /etc/designate/designate.conf
handler:neutron_floatingip notification_topics notifications_designate
# openstack-config --set /etc/designate/designate.conf
handler:neutron_floatingip control_exchange neutron
# openstack-config --set /etc/designate/designate.conf
handler:neutron_floatingip format "%(octet0)s-%(octet1)s-%(octet2)s-%
(octet3)s.%(domain)s"
```

11. Configure Compute and OpenStack Networking to send notifications



Note

Ceilometer's agent also listens and consumes notifications. Create a specific **Designate** notifications queue (as shown below) so they don't conflict.

OpenStack Compute in the *Kilo* release uses **messaging** as its notification driver; previously it was **nova.openstack.common.notifier.rpc_notifier**

```
# openstack-config --set /etc/nova/nova.conf DEFAULT
notification_topics notifications,notifications_designate
# openstack-config --set /etc/nova/nova.conf DEFAULT
notify_on_state_change vm_and_task_state
# openstack-config --set /etc/nova/nova.conf DEFAULT
instance_usage_audit_period hour
# openstack-config --set /etc/nova/nova.conf DEFAULT
instance_usage_audit true
# openstack-config --set /etc/neutron/neutron.conf DEFAULT
notification_driver neutron.openstack.common.notifier.rpc_notifier
# openstack-config --set /etc/neutron/neutron.conf DEFAULT
notification_topics notifications,notifications_designate
# openstack-service restart nova
# openstack-service restart neutron
```

12. Manually verify the **notification_driver** in *nova.conf*:



Note

Due to the possibility of multiple **notification_drivers** in *nova.conf*, the *openstack-config* command might cause problems. Check in the **DEFAULT** section to ensure you have these two entries:

```
notification_driver=ceilometer.compute.nova_notifier
notification_driver=messaging
```

**Note**

If using a separate Compute node, it will need the following settings in *nova.conf*:

```
notification_driver
=nova.openstack.common.notifier.rabbit_notifier,ceilometer.compu
te.nova_notifier
notification_driver =messaging
notification_topics=notifications,notifications_designate
```

13. Sync the DNSaaS and Pool Manager cache:

```
# designate-manage database sync
# designate-manage pool-manager-cache sync
```

14. Enable and start the DNSaaS services:

```
# systemctl enable designate-central
# systemctl enable designate-api
# systemctl enable designate-mdns
# systemctl enable designate-pool-manager
# systemctl start designate-central
# systemctl start designate-api
# systemctl start designate-mdns
# systemctl start designate-pool-manager
```

**Note**

At this point you have not created a DNS target for your pool, so don't expect a functioning DNSaaS deployment yet.

CHAPTER 3. INSTALL AND CONFIGURE BIND9

These steps install Bind9, and then configure integration with DNSaaS.

3.1. BASIC BIND INSTALLATION

1. Install the *BIND* packages:

```
# yum install bind bind-utils
```

2. Configure *named* to listen for incoming connections:

```
# cp /etc/named.conf /etc/named.conf.orig
# sed -i -e "s/listen-on port.*/listen-on port 53 { 127.0.0.1;
192.168.100.20; };" /etc/named.conf
```

3.2. CONFIGURE BIND

1. Write to */etc/rndc.key*:

```
# rndc-confgen -a
```

2. Add the following before **options**

```
# sed -i '/^options.*/i \
include "/etc/rndc.key"; \
controls { \
    inet 127.0.0.1 allow { localhost; } keys { "rndc-key"; }; \
};' /etc/named.conf
```

3. Remove a few existing options you will rewrite later:

```
# sed -i '/allow-query.*/d' /etc/named.conf
# sed -i '/recursion.*/d' /etc/named.conf
```

4. Add the following after **options**:

```
# sed -i '/^options.*/a \
    allow-new-zones yes; \
    allow-query { any; }; \
    recursion no;' /etc/named.conf
```

5. Create the *rndc* configuration. For the Compute node, the *rndc* configuration must point to the DNS server. For example:

```
# cat << EOF > /etc/rndc.conf
include "/etc/rndc.key";
options {
    default-key "rndc-key";
```

```

        default-server 192.168.100.20;
        default-port 953;
    };
EOF

```

6. Review the *named* configuration:

```
# named-checkconf /etc/named.conf
```

7. Correct the file permissions:

```

# setsebool -P named_write_master_zones on
# chmod g+w /var/named
# chown named:named /etc/rndc.conf
# chown named:named /etc/rndc.key
# chmod 600 /etc/rndc.key

```

8. Enable and start the *named* service:

```

# systemctl enable named
# systemctl start named

```

9. Validate *named* and *rndc*:

```

# dig @localhost localhost
# rndc status

```

3.3. CONFIGURE THE DNSaaS POOL TARGET FOR BIND

1. Set the pool target configuration:

```

# openstack-config --set /etc/designate/designate.conf
pool_target:$target_id type bind9
# openstack-config --set /etc/designate/designate.conf
pool_target:$target_id options "rndc_host: 192.168.100.20, rndc_port:
953, rndc_config_file: /etc/rndc.conf, rndc_key_file: /etc/rndc.key"
# openstack-config --set /etc/designate/designate.conf
pool_target:$target_id masters 192.168.100.20:5354

```

2. Restart DNSaaS to apply your pool changes:

```

# systemctl restart designate-api
# systemctl restart designate-central
# systemctl restart designate-mdns
# systemctl restart designate-pool-manager
# systemctl restart designate-sink

```

3.4. TEST BIND

1. Perform the diagnostic commands below:

```
# netstat -tap | grep named
# netstat -tulpn | grep 53
# dig @192.168.100.20
```

2. Check the DNSaaS Logs for errors. Ignore errors in Sink for now, as you have not modified its configuration.

```
# cd /var/log/designate
# tail api.log
# tail central.log
# tail mdns.log
# tail pool-manager.log
# tail sink.log
```

3.5. TEST DNSAAS INTEGRATION WITH BIND9

1. Create an entry for your server:

```
# designate server-create --name $(hostname).
```

2. Verify your DNS server record was previously created:

```
# designate server-list
```

3. Create a domain (don't forget the . at the end of the --name option)

```
# designate domain-list
# designate domain-create --name example.com. --email root@example.com
# DOMAINID=$(designate domain-list | grep example.com | awk '{print
$2}')
```



Note

When creating a domain from designate against BIND, it is basically running a command similar to this:

```
# rndc -s 192.168.122.41 -p 953 -c /etc/rndc.conf -k /etc/rndc.key
addzone example.com '{ type slave; masters { 192.168.122.41 port 5354;
}; file "slave.example.com.ff532e15-55a9-4966-8f1e-b3eddb2891ba"; }';'
```

4. Create a record and test lookup (don't forget the . at the end of the --name option)

```
# designate record-create --name server1.example.com. --type A --data
1.2.3.4 $DOMAINID
# dig +short -p 53 @192.168.100.20 server1.example.com A
```

3.6. CONFIGURE AUTO-GENERATION OF DNS RECORDS (NOVA FIXED AND NEUTRON FLOATING)

1. Modify the DNSaaS configuration for the example domain:

```
# openstack-config --set /etc/designate/designate.conf
handler:nova_fixed domain_id $DOMAINID
# openstack-config --set /etc/designate/designate.conf
handler:neutron_floatingip domain_id $DOMAINID
# systemctl restart designate-api
# systemctl restart designate-central
# systemctl restart designate-mdns
# systemctl restart designate-pool-manager
# systemctl restart designate-sink
```

2. Test OpenStack Compute (nova) record creation:

```
# glance image-list
# neutron net-list
# nova boot testserver --flavor m1.tiny --image cirros-0.3.4-x86_64 --
key-name yourkey --security-groups default --nic net-id=<Private Net
ID>
```

3. Check the Sink log:

Once the instance is up, you should see a **create_record** entry, if it has picked up the notification correctly:

```
# tail /var/log/designate/sink.log
```

Check in BIND

```
# dig +short @192.168.100.20 testserver.example.com
```

If this doesn't work, you can also check the files in **/var/named**.

3.7. TEST OPENSTACK NETWORKING FLOATING IP RECORD CREATION

1. Perform the diagnostic commands below (replace **pubnet1** with a name appropriate for your environment):

```
# FLOATINGIP=$(neutron floatingip-create pubnet1 | grep
floating_ip_address | awk '{print $4}')
# nova add-floating-ip testserver $FLOATINGIP
# DNSRESULT=$(echo $FLOATINGIP |sed 's/\./-/g').example.com
# dig +short @192.168.100.20 $DNSRESULT
```

2. You should see a **create_record** event in the log file:

```
# tail /var/log/designate/sink.log
```

3.8. CLEANUP OPENSTACK NETWORKING AND COMPUTE DNS ENTRIES

1. Remove the test floating IP created previously:

```
# nova remove-floating-ip testserver $FLOATINGIP
```

2. You should see a **delete_record** event in the log file:

```
# tail /var/log/designate/sink.log
```

And the record should now be removed.

3. Remove the *testserver* created previously:

```
# designate record-list $DOMAINID  
# nova delete testserver
```

You should see another **delete_record** entry in the log file:

```
# tail /var/log/designate/sink.log
```